

# CSCI235 Database Systems

# Transaction Processing in Oracle DBMS

Dr Janusz R. Getta

School of Computing and Information Technology -  
University of Wollongong

# Transaction Processing in Oracle DBMS

## Outline

Transaction scope

Isolation levels and read consistency levels

Rollback/Undo segments

READ COMMITTED versus SERIALIZABLE levels

Locking

READ COMMITTED isolation level

SERIALIZABLE isolation level

[TOP](#)

Created by Janusz R. Getta, CSCI235 Database Systems, Spring 2020

2/26

# Transaction scope

Transaction starts from the first executable SQL statement after connection, **COMMIT**, or **ROLLBACK** statement

Transaction ends with either **COMMIT**, **ROLLBACK**, or DDL statement **CREATE**, **DROP**, **ALTER**

Transaction also ends with disconnection (**auto-commit** or **auto-rollback** depending on default or set up parameters) or process failure followed by automatic **ROLLBACK** statement

# Transaction Processing in Oracle DBMS

## Outline

Transaction scope

Isolation levels and read consistency levels

Rollback/Undo segments

READ COMMITTED versus SERIALIZABLE levels

Locking

READ COMMITTED isolation level

SERIALIZABLE isolation level

[TOP](#)

Created by Janusz R. Getta, CSCI235 Database Systems, Spring 2020

4/26

# Isolation levels and read consistency levels

Oracle DBMS implements three **isolation levels**

**READ COMMITTED** - a transaction may exhibit:

- non-repeatable read phenomenon,
- phantom phenomenon

**SERIALIZABLE** - a transaction may exhibit:

- none of the phenomena

**READ ONLY** - a transaction consists only of **read** operations

At **READ COMMITTED** isolation level all data read by a query (**SELECT** statement) come from a single point in time (**statement-level read consistency**)

At **SERIALIZABLE** isolation level all queries (**SELECT** statements) in a transaction read data that come from a single point in time (**transaction-level read consistency**)

# Transaction Processing in Oracle DBMS

## Outline

Transaction scope

Isolation levels and read consistency levels

Rollback/Undo segments

READ COMMITTED versus SERIALIZABLE levels

Locking

READ COMMITTED isolation level

SERIALIZABLE isolation level

[TOP](#)

Created by Janusz R. Getta, CSCI235 Database Systems, Spring 2020

6/26

## Rollback/undo segments


**Rollback/undo segments** consist of data blocks that contain the old values of data that have been changed by the uncommitted or recently committed transactions

Each time a row in a data block is changed a new version of the block together with a **timestamp** is added to **rollback/undo segment**

A new version of a data block obtains a **timestamp** higher than the previous version

A data block may have many versions updated in the different moments in time

See below the data blocks read by a transaction **T** with a timestamp **t<sub>i</sub>** such that  $t_2, t_3 > t_i > t_0, t_1$



[TOP](#)

Created by Janusz R. Gęta, CSCI235 Database Systems, Spring 2020

7/26

# Transaction Processing in Oracle DBMS

## Outline

Transaction scope

Isolation levels and read consistency levels

Rollback/Undo segments

READ COMMITTED versus SERIALIZABLE levels

Locking

READ COMMITTED isolation level

SERIALIZABLE isolation level

[TOP](#)

Created by Janusz R. Getta, CSCI235 Database Systems, Spring 2020

8/26



## READ COMMITTED versus SERIALIZABLE levels

At **READ COMMITTED** isolation level each query executes with respect to its own materialized view time, thereby permitting nonrepeatable reads and phantoms for multiple executions of a query

**READ COMMITTED** isolation level is recommended when few transactions are likely to conflict

If a transaction **T** running at **SERIALIZABLE** isolation level tries to update or delete data modified by a transaction that commits after the serializable transaction **T** began then the system aborts transaction **T**

If a serializable transaction fails then it is possible to:

- commit the work executed to that point,
- execute additional (but different) statements,
- rollback the entire transaction

# Transaction Processing in Oracle DBMS

## Outline

Transaction scope

Isolation levels and read consistency levels

Rollback/Undo segments

READ COMMITTED versus SERIALIZABLE levels

Locking

READ COMMITTED isolation level

SERIALIZABLE isolation level

[TOP](#)

Created by Janusz R. Getta, CSCI235 Database Systems, Spring 2020

10/26

# Locking

**Locking** is performed automatically by the system

It is also possible to lock data items manually

There are two types of locks:

- **shared** (read locks),
- **exclusive** (write locks)

A transaction holds **exclusive row locks** for all rows **inserted**, **updated**, or **deleted** within the transaction

The system releases all locks acquired by a transaction when the transaction either **commits** or **rollbacks**

The system automatically converts a lock of **lower restrictiveness** to one of **higher restrictiveness** when it is appropriate

For example, **SELECT** statement with **FOR UPDATE** clause initially locks the rows in **shared mode**, then when **UPDATE** is performed the locks are upgraded to **exclusive locks**

[TOP](#)

Created by Janusz R. Getta, CSCI235 Database Systems, Spring 2020

11/26

# Locking

Both **READ COMMITTED** and **SERIALIZABLE** transactions use row-level locking to ensure database consistency

A transaction must wait if it tries to change a row updated by an uncommitted transaction

If a transaction rolls back then the waiting transactions regardless of its isolation mode can proceed to change the previously locked row

If a transaction commits than any other transaction at **READ COMMITTED** level waiting for a locked row can proceed to change the previously locked row

If a transaction commits than any other transaction at **SERIALIZABLE** level waiting for a locked row fails with the error "Cannot serialize access", because the other transaction has committed a change that was made since the serializable transaction began

# Locking

A **deadlock** occurs when two or more users are waiting for data locked by each other

The system automatically detects a **deadlock** and rolls back one of the statements involved in the deadlock

It is possible to perform **manual locking** of entire relational table with **LOCK TABLE** statement

# Transaction Processing in Oracle DBMS

## Outline

Transaction scope

Isolation levels and read consistency levels

Rollback/Undo segments

READ COMMITTED versus SERIALIZABLE levels

Locking

READ COMMITTED isolation level

SERIALIZABLE isolation level

[TOP](#)

Created by Janusz R. Getta, CSCI235 Database Systems, Spring 2020

14/26

# READ COMMITTED isolation level

Setting **READ COMMITTED isolation level** is performed at the beginning of transaction with the following statement

```
SET TRANSACTION ISOLATION LEVEL READ COMMITTED;
```

At **READ COMMITTED** isolation level each query executes with the respect to its own materialized view time, thereby permitting **nonrepeatable reads** and **phantoms** for multiple processing of the same query

**READ COMMITTED** isolation level is recommended when few transactions are likely to conflict

**READ COMMITTED** is a default isolation level

# READ COMMITTED isolation level

Sample concurrent processing of database transactions at **READ COMMITTED** isolation level that **does not corrupt** a database

Concurrent processing of database transactions at READ COMMITTED isolation level	
Transaction 1	Transaction 2
	<code>SELECT budget</code> <code>FROM DEPARTMENT</code> <code>WHERE name = 'SALES';</code>
	2000
<code>UPDATE DEPARTMENT</code> <code>SET budget = budget + 1000</code> <code>WHERE NAME = 'Sales';</code>	
	<code>SELECT budget</code> <code>FROM DEPARTMENT</code> <code>WHERE name = 'SALES';</code>
	2000

**Transaction 2** cannot read uncommitted modifications



# READ COMMITTED isolation level

Sample concurrent processing of database transactions at **READ COMMITTED** isolation level that **does not corrupt** a database

Concurrent processing of database transactions at READ COMMITTED isolation level	
Transaction 1	Transaction 2
	<code>SELECT budget</code> <code>FROM Department</code> <code>WHERE name = 'SALES';</code>
	2000
<code>UPDATE DEPARTMENT</code> <code>SET budget = budget + 1000</code> <code>WHERE name = 'Sales';</code>	
<code>COMMIT;</code>	
	<code>SELECT budget</code> <code>FROM Department</code> <code>WHERE name = 'SALES';</code>
	3000

**Transaction 2** can only read committed modifications

[TOP](#)

Created by Janusz R. Getta, CSCI235 Database Systems, Spring 2020

17/26

# READ COMMITTED isolation level

Sample concurrent processing of database transactions at **READ COMMITTED** isolation level that **does not corrupt** a database

Concurrent processing of database transactions at READ COMMITTED isolation level	
Transaction 1	Transaction 2
<pre>SELECT budget FROM DEPARTMENT WHERE name = 'SALES';</pre>	
3000	
	<pre>UPDATE DEPARTMENT SET budget = budget + 10 WHERE name = 'Sales';</pre>
<pre>UPDATE DEPARTMENT SET budget = budget + 1000 WHERE name = 'SALES';</pre>	
Wait	
	<pre>COMMIT;</pre>
<pre>SELECT budget FROM DEPARTMENT WHERE name = 'SALES';</pre>	
4010	

[TOP](#)

# READ COMMITTED isolation level

Transaction 1	Transaction 2	Processing at READ COMMITTED isolation level
<pre>SELECT budget FROM DEPARTMENT WHERE name = 'SALES';</pre>		
3000		
	<pre>UPDATE DEPARTMENT SET budget = budget + 10 WHERE name = 'Sales';</pre>	
<pre>UPDATE DEPARTMENT SET budget = budget + 1000 WHERE name = 'SALES';</pre>		
Wait		
	COMMIT;	
<pre>SELECT budget FROM DEPARTMENT WHERE name = 'SALES';</pre>		
4010		

Transaction 1 must wait until Transaction 2 either commits or rolls back its update

[TOP](#)

# READ COMMITTED isolation level

Sample concurrent processing of database transactions at **READ COMMITTED** isolation level that **does not corrupt** a database

Transaction 1	Transaction 2	Processing at READ COMMITTED isolation level
<pre> SELECT budget FROM DEPARTMENT WHERE name = 'SALES' </pre>		
3000		
	<pre> UPDATE DEPARTMENT SET budget = budget + 10 WHERE name = 'SALES' </pre>	
<pre> UPDATE DEPARTMENT SET budget = budget + 1000 WHERE name = 'Sales'; </pre>		
Wait		
	ROLLBACK;	
<pre> SELECT budget FROM DEPARTMENT WHERE name = 'SALES' </pre>		
4000		

[TOP](#)

Created by Janusz R. Getta, CSCI235 Database Systems, Spring 2020

20/26

# READ COMMITTED isolation level

Transaction 1	Transaction 2	Processing at READ COMMITTED isolation level
<pre> SSELECT budget FROM DEPARTMENT WHERE name = 'SALES' </pre>		
3000		
	<pre> UPDATE DEPARTMENT SET budget = budget + 10 WHERE name = 'SALES' </pre>	
<pre> UPDATE DEPARTMENT SET budget = budget + 1000 WHERE name = 'Sales'; </pre>		
Wait		
	ROLLBACK;	
<pre> SELECT budget FROM DEPARTMENT WHERE name = 'SALES' </pre>		
4000		

Transaction 1 must wait until Transaction 2 either commits or rolls back its update

[TOP](#)

# READ COMMITTED isolation level

A sample processing of database transactions at **READ COMMITTED** isolation level that **corrupts** a database

Processing at READ COMMITTED isolation level	
Transaction 1	Transaction 2
<pre>UPDATE DEPARTMENT SET budget = (SELECT budget               FROM DEPARTMENT               WHERE name = 'Sales') WHERE name = 'Finance';</pre>	
	<pre>UPDATE DEPARTMENT SET budget = 500 WHERE name = 'Sales'; COMMIT;</pre>
<pre>UPDATE DEPARTMENT SET budget = budget + (SELECT budget                       FROM DEPARTMENT                       WHERE name = 'Sales') WHERE name = 'Finance'; COMMIT;</pre>	

Transaction 1 corrupts a database, because a budget of department **Finance** is not equal to  $2 * \text{budget of department Sales}$

[TOP](#)

Created by Janusz R. Getta, CSC1235 Database Systems, Spring 2020

22/26

# Transaction Processing in Oracle DBMS

## Outline

Transaction scope

Isolation levels and read consistency levels

Rollback/Undo segments

READ COMMITTED versus SERIALIZABLE levels

Locking

READ COMMITTED isolation level

SERIALIZABLE isolation level

[TOP](#)

Created by Janusz R. Getta, CSCI235 Database Systems, Spring 2020

23/26

# SERIALIZABLE isolation level

If a transaction **T** running at **SERIALIZABLE** isolation level tries to update or delete data modified by a transaction that commits after the serializable transaction **T** began then the system aborts transaction **T**

A sample processing of database transactions at **SERIALIZABLE** isolation level that **fails** one of the transactions

Processing database transactions at SERIALIZABLE isolation level	
Transaction 1	Transaction 2
	<code>UPDATE DEPARTMENT</code> <code>SET budget = budget + 10</code> <code>WHERE name = 'SALES'</code>
<code>UPDATE DEPARTMENT</code> <code>SET budget = budget + 1000</code> <code>WHERE name = 'Sales';</code>	
<code>Wait</code>	
	<code>COMMIT;</code>
<code>ERROR at line 2:</code> <code>ORA-08177: can't serialize</code> <code>access for this transaction</code>	

[TOP](#)

Created by Janusz R. Getta, CSCI235 Database Systems, Spring 2020

24/26



# SERIALIZABLE isolation level

A sample processing of database transactions at **SERIALIZABLE** isolation level that ends **successfully** for both transactions

Processing database transactions at SERIALIZABLE isolation level	
Transaction 1	Transaction 2
	<code>SELECT budget</code> <code>FROM Department</code> <code>WHERE name = 'SALES'</code>
	2000
<code>UPDATE DEPARTMENT</code> <code>SET budget = budget + 1000</code> <code>WHERE name = 'Sales';</code>	
<code>COMMIT</code>	
	<code>SELECT budget</code> <code>FROM Department</code> <code>WHERE name = 'SALES'</code>
	2000

**Transaction 1** creates a new version of a row for **Sales** department

[TOP](#)

Created by Janusz R. Getta, CSCI235 Database Systems, Spring 2020

25/26

# References

T. Connolly, C. Begg, Database Systems, A Practical Approach to Design, Implementation, and Management, Chapter 22.5 Concurrency Control and Recovery in Oracle, Pearson Education Ltd, 2015