CSCI235 Database Systems Introduction to Transaction Processing (3)

Dr Janusz R. Getta

School of Computing and Information Technology - University of Wollongong

1 of 19 28/8/20, 8:45 am

Outline

Serialization graph

Serialization graph testing protocol

Two phase locking protocol (2PL)

Timestamp ordering protocol

TOP

Serialization graph

Serialization graph is constructed in the following way

- If a transaction ${\bf T}$ participates in a concurrent execution then we add a node labeled with ${\bf T}$ to a serialization graph
- If the transactions T_i and T_j process conflicting operations such that T_i processes its operation first then we add an edge directed from T_i to T_j

Sample construction of a serialization graph

```
Concurrent execution of database transactions
T1 T2 T3

write(x, 10)

Create a node T1

write(x, 20)
```

Create a node T2 and add an edge from T1 to T2

TOP Created by Janusz R. Getta, CSCI235 Database Systems, Autumn 2020 3/19

3 of 19 28/8/20, 8:45 am


Serialization graph

write(x,30)

Create a node T3 and add the edges from T1 to T3 and from T2 to T3

```
write(y,10)
read(y)
```

Add an edge from T2 to T1



TOP Created by Janusz R. Getta, CSCI235 Database Systems, Autumn 2020

TOP

Serialization graph

A serialization graph for nonconflict serializable execution of database transactions

```
Nonconflict serializable execution of database transactions

T1

T2

read(x)

Create a node T1

read(x)

Create a node T2

write(x,x-10)

Add an edge from T2 to T1

write(x,x+20)

Add an edge from T1 to T2
```


Created by Janusz R. Getta, CSCI235 Database Systems, Autumn 2020 5/19

5 of 19 28/8/20, 8:45 am

Serialization graph

A serialization graph for nonconflict serializable execution of database transactions

```
Nonconflict serializable execution of database transactions T1 \qquad \qquad T2 \\ read(x) \qquad \qquad \\ read(x) \\ write(x,x-10) \qquad \qquad \\ write(x,x+20)
```



Created by Janusz R. Getta, CSCI235 Database Systems, Autumn 2020

6/19

TOP

Outline

Serialization graph

Serialization graph testing protocol

Two phase locking protocol (2PL)

Timestamp ordering protocol

TOP Created by Janusz R. Getta, CSCI235 Database Systems, Autumn 2020

Serialization graph testing protocol (SGT)

Principles

- Scheduler maintains and tests serialization graph
- If an operation issued by a transaction violates conflict serializability, i.e. if it creates a cycle in serialization graph then such transaction is aborted

Problems

- Cascading aborts: if a transaction **T** that created a data item **x** is aborted then all transactions that read a new value of **x** must be aborted
- Performance: testing acyclicity of serialization graph has O(n2) complexity

TOP Created by Janu

Created by Janusz R. Getta, CSCI235 Database Systems, Autumn 2020

Outline

Serialization graph

Serialization graph testing protocol

Two phase locking protocol (2PL)

Timestamp ordering protocol

TOP

Created by Janusz R. Getta, CSCI235 Database Systems, Autumn 2020

Principles

- Access to data items is controlled by shared (read) and exclusive (write) locks
- A transaction can read a data item only if a data item is read or write locked by the same transaction or a data item is read locked by another transaction
- A transaction can write a data item only if a data item is write locked by the same same transaction
- Each transaction must acquire all locks before releasing any lock

Two-phase locking protocol belongs to a class of pessimistic protocols Problems

- Deadlocks
- Unnecessary locks and delays when an execution is conflict serializable

TOP Created by Janusz R. Getta, CSCI235 Database Systems, Autumn 2020

A sample execution controlled by two-phase locking protocol


	Concurrent execution of database transactions controlled by 2PL protocol		
т1	T2		
lock(u) read(u)			
lock(v) write(v,10)			
write(u,u+2)			
lock(v) wait			
	lock(x) read(x)		
	unlock(v)		
	write(x,x+2)		
lock(v)			
	unlock(x)		
write(v,v+1)			
unlock(v)			
unlock(u)			

TOP Created by Janusz R. Getta, CSCI235 Database Systems, Autumn 2020

11/19

11 of 19

A sample execution that ends in a deadlock



Both transactions are in a wait state

In a database system deadlock is eliminated through either wait for graph or throught timeout

TOP Created by Janusz R. Getta, CSCI235 Database Systems, Autumn 2020

A sample execution that unnecessarily delays a transaction

```
T1 Concurrent execution of database transactions that unnecessarily delays a transaction lock(u) read(u)

lock(u) wait

lock(v) write(v,v+1)

unlock(v,u)

lock(u) write(u,u+1)
```

The transactions T1 and T2 never get into non conflict serializable execution

Therefore, there is no need to delay a transaction T2

TOP Created by Janusz R. Getta, CSCI235 Database Systems, Autumn 2020

Outline

Serialization graph

Serialization graph testing protocol

Two phase locking protocol (2PL)

Timestamp ordering protocol

TOP Created by Janusz R. Getta, CSCI235 Database Systems, Autumn 2020

Principles

- Each transaction obtains a timestamp at its start point
- Data items are stamped each time any transaction accesses data items in a read or write mode
- Access to data items is permitted in an increasing order of timestamps

Timestamp ordering protocol belongs to a class of optimistic protocols

Problems

- Cascading aborts
- Unnecessary aborts when execution is conflict serializable

TOP Created by Janusz R. Getta, CSCI235 Database Systems, Autumn 2020

A sample execution controlled by the timestamp ordering protocol

т1	Concurrent execution of databate T2	ase transactions controlled by TO protocol	
timestamp(t1)			
read(x)		x:t1	
write(x,x-10)			
timestamp(t2)			
	write(x)	x:t1:t2	
	read(y)	y:t2	
read(y)		y:t2:t1	
write(y,y+1)		y:t2:t1	
abort			

Created by Janusz R. Getta, CSCI235 Database Systems, Autumn 2020

16/19

TOP

A sample excution controlled by the timestamp ordering protocol with cascading abort

```
Concurrent execution of database transactions controlled by TO protocol with cascading abort T1 T2 x

timestamp(t1)

read(x) x:t1

write(x,x-10)

timestamp(t2)

read(x) x:t1:t2

fail

forced abort
```

A transaction T2 is forced to abort because it reads a dirty data item written by a failed transaction T1

TOP Created by Janusz R. Getta, CSCI235 Database Systems, Autumn 2020

A sample excution controlled by the timestamp ordering protocol where a transaction is unnecessarily aborted

```
Concurrent execution of database transactions controlled by TO protocol with unnecessary abort
T1 T2 x

timestamp(t2)

timestamp(t1)

read(x) x:t1

write(x,x-10)

read(x) forced abort x:t1:t2
```

A transaction T2 is aborted even the execution is conflict serializable

TOP Created by Janusz R. Getta, CSCI235 Database Systems, Autumn 2020

References

T. Connoly, C. Begg, Database Systems, A Practical Approach to Design, Implementation, and Management, Chapter 22.2 Concurrency Control, Pearson Education Ltd, 2015

Created by Janusz R. Getta, CSCI235 Database Systems, Autumn 2020

19/19

TOP