

Introduction to Web Technology

XML and DTD

Joseph Tonien
School of Computing and Information Technology
University of Wollongong

XML and DTD

Objectives:

- use XML to store and transport data over the Internet
- learn DTD language to define the structure of an XML document

XML

EXtensible Markup Language

- XML is a markup language much like HTML
- XML is a software- and hardware-independent tool for storing and transporting data.
- XML separates data from presentation.
- File extension is .xml

```
<?xml version="1.0" ?>
<student>
  <firstName>John</firstName>
  <lastName>Smith</lastName>
  <email>jsmith@gmail.com</email>
  <mobile>0211223344</mobile>
</student>
```

XML

- HTML tags are predefined.
- XML tags are defined by user.
- Using XML **D**ocument **T**ype **D**efinition (DTD), or **X**ML **S**chema **D**efinition (XSD), different parties can agree on a standard XML format for interchanging data.
- Another popular format for interchanging data is **J**ava**S**cript **O**bject **N**otation (JSON)

```
{  
  "firstName": "John",  
  "lastName": "Smith",  
  "email": "jsmith@gmail.com",  
  "mobile": "0211223344"  
}
```

- In most web applications, XML and JSON are used to store or transport data, while HTML and XSLT are used to transform and display the data.

XML:

The first example of XML:

```
<?xml version="1.0" ?>
<student>
  <firstName>John</firstName>
  <lastName>Smith</lastName>
  <email>jsmith@gmail.com</email>
  <mobile>0211223344</mobile>
</student>
```

XML: XML declaration

```
<?xml version="1.0" ?> ← XML declaration
<student>
  <firstName>John</firstName>
  <lastName>Smith</lastName>
  <email>jsmith@gmail.com</email>
  <mobile>0211223344</mobile>
</student>
```

- The **XML declaration** is optional and it **must come first in the document**.
- The XML declaration identifies the document as being XML. Even though it is optional, all XML documents should begin with an XML declaration.
- The XML declaration must be situated at the first position of the first line in the XML document.
 - **Do not start an XML file with a blank line!!!**
- Syntax for the XML declaration:

```
<?xml version="version_number"
encoding="encoding_declaration"
standalone="standalone_status" ?>
```

XML: root element

```
<?xml version="1.0" encoding="UTF-8" ?>
<student> ←———— root element
  <firstName>John</firstName>
  <lastName>Smith</lastName>
  <email>jsmith@gmail.com</email>
  <mobile>0211223344</mobile>
</student>
```

- An XML document **must contain one root element** that is the parent of all other elements

```
<rootElement>
  <child>
    <subchild>.....</subchild>
  </child>
</rootElement>
```

XML: root element

This is NOT a well-formed XML document because it has no root element

```
<?xml version="1.0" encoding="UTF-8"?>
<student>
  <firstName>John</firstName>
  <lastName>Smith</lastName>
  <email>jsmith@gmail.com</email>
</student>
<student>
  <firstName>Mary</firstName>
  <lastName>Jane</lastName>
  <email>mjane@gmail.com</email>
</student>
```


XML: root element

This is a well-formed XML document because it has a root element

```
<?xml version="1.0" encoding="UTF-8"?>
```

```
<studentList>
```

```
  <student>
```

```
    <firstName>John</firstName>
```

```
    <lastName>Smith</lastName>
```

```
    <email>jsmith@gmail.com</email>
```

```
  </student>
```

```
  <student>
```

```
    <firstName>Mary</firstName>
```

```
    <lastName>Jane</lastName>
```

```
    <email>mjane@gmail.com</email>
```

```
  </student>
```

```
</studentList>
```

XML: element

```
<tag attribute1="..." attribute2="...">
```

```
</tag>
```

- An **XML element** is everything from (including) the element's start tag to (including) the element's end tag.

```
<?xml version="1.0" encoding="UTF-8"?>
<dailyTransaction date="24/02/2015">
  <person staffDbId="103" operation="update">
    <firstName>John</firstName>
    <lastName>Smith</lastName>
    <mobile>0211223344</mobile>
  </person>
  <person staffDbId="-1" operation="add">
    <firstName>Mary</firstName>
    <lastName>Jane</lastName>
    <mobile>0244556677</mobile>
  </person>
</dailyTransaction>
```

Where is the `dailyTransaction` element?

Where is a `person` element?

Where is a `mobile` element?

XML: element

XML tags are **case sensitive**.

The tag `<student>` is different from the tag `<STUDENT>`

Common **naming convention** for XML tags

```
<student_list>  
...  
</student_list>
```

or

```
<studentList>  
...  
</studentList>
```

XML: attribute

```
<tag attribute1="..." attribute2="...">
```

```
</tag>
```

- **XML attributes** are used to describe XML elements, or to provide additional information about elements.

```
<?xml version="1.0" encoding="UTF-8"?>
<dailyTransaction date="24/02/2015">
  <person staffDbId="103" operation="update">
    <firstName>John</firstName>
    <lastName>Smith</lastName>
    <mobile>0211223344</mobile>
  </person>
  <person staffDbId="-1" operation="add">
    <firstName>Mary</firstName>
    <lastName>Jane</lastName>
    <mobile>0244556677</mobile>
  </person>
</dailyTransaction>
```

Does the `dailyTransaction` element has attributes?

Does a `person` element has attributes?

Does a `mobile` element has attributes?

XML: attribute

In XML, the attribute values must always be quoted (either by single quote or double quote):

```
<dailyTransaction date='24/02/2015'>  
  <person staffDbId="103" operation="update">  
    <firstName>John</firstName>  
    <lastName>Smith</lastName>  
    <mobile>0211223344</mobile>  
  </person>  
</dailyTransaction>
```

XML: relationship between elements

```
<parent>
  <child>
    <subchild>.....</subchild>
  </child>
</parent>
```

- An XML tree starts at a root element and branches from the root to child elements.
- The terms parent, child, and sibling are used to describe the relationships between elements.
 - Parent have children. Children have parents.
 - Siblings are children on the same level

XML: attribute vs child element

Any attribute can be defined as a child element.

For example, instead of using `gender` as an attribute

```
<person gender="M">  
  <firstName>John</firstName>  
  <lastName>Smith</lastName>  
  <email>jsmith@gmail.com</email>  
</person>
```

we can define `gender` as a child element of `person`

```
<person>  
  <firstName>John</firstName>  
  <lastName>Smith</lastName>  
  <email>jsmith@gmail.com</email>  
  <gender>M</gender>  
</person>
```

This contains the same information.

XML: attribute vs child element

Any attribute can be defined as a child element.

For example, attributes `staffDbId` and `operation`

```
<person staffDbId="103" operation="update">  
  <firstName>John</firstName>  
  <lastName>Smith</lastName>  
  <mobile>0211223344</mobile>  
</person>
```

can become child elements

```
<person>  
  <firstName>John</firstName>  
  <lastName>Smith</lastName>  
  <mobile>0211223344</mobile>  
  <staffDbId>103</staffDbId>  
  <operation>update</operation>  
</person>
```

This contains the same information.

XML: attribute vs child element

Any attribute can be defined as a child element, **so when should we use attribute and when should we use element?**

Metadata (data about data) should be stored as attributes, and the data itself should be stored as elements.

```
<person gender="M">  
  <firstName>John</firstName>  
  <lastName>Smith</lastName>  
  <email>jsmith@gmail.com</email>  
</person>
```

```
<person>  
  <firstName>John</firstName>  
  <lastName>Smith</lastName>  
  <email>jsmith@gmail.com</email>  
  <gender>M</gender>  
</person>
```

————— this is better

XML: attribute vs child element

Any attribute can be defined as a child element, **so when should we use attribute and when should we use element?**

Metadata (data about data) should be stored as attributes, and the data itself should be stored as elements.

```
<person staffDbId="103" operation="update">  
  <firstName>John</firstName>  
  <lastName>Smith</lastName>  
  <mobile>0211223344</mobile>  
</person>
```

```
<person>  
  <firstName>John</firstName>  
  <lastName>Smith</lastName>  
  <mobile>0211223344</mobile>  
  <staffDbId>103</staffDbId>  
  <operation>update</operation>  
</person>
```



this is better

XML: empty element and self-closing tag

In HTML, some elements might work well, even with a missing closing tag:

```
<br>
<hr>
<p>
<input ...>
```

In XML, all elements **must** have a closing tag:

```
<student>
...
</student>
```

An element with no content is called an **empty element**:

```
<emptyElement></emptyElement>
```

We can use **self-closing tag** for an empty element:

```
<emptyElement />
```

XML: nested rule

In HTML, some elements might not be nested properly:

```
<b><i>This text is bold and italic</b></i>
```

In XML, all elements **must** be properly nested:

```
<student>  
  <firstName>John</firstName>  
  <lastName>Smith</lastName>  
  <email>jsmith@gmail.com</email>  
</student>
```

XML: entity reference

If we place a character like `<` inside an XML element, it will generate an error. In this case, we need to use the entity reference `<`;

Entity references

<code>&lt;</code>	<code><</code>	less than
<code>&gt;</code>	<code>></code>	greater than
<code>&amp;</code>	<code>&</code>	ampersand
<code>&apos;</code>	<code>'</code>	apostrophe
<code>&quot;</code>	<code>"</code>	quotation mark

XML: comments

Comments in XML:

```
<!-- this is a comment -->
```

DTD

- XML **D**ocument **T**ype **D**efinition commonly known as DTD is a way to define the legal building blocks of an XML document. It defines the document structure with a list of legal elements and attributes.
- Using a DTD, different parties can agree on a standard XML format for interchanging data.
- We can check whether an XML document conforms to a DTD or not.
- File extension is .dtd

DTD

The DTD can be declared inside the XML file, or it can be defined in a separate file:

- Internal DTD
- External DTD

DTD: internal DTD

The following DTD is declared inside the XML file:

```
<?xml version="1.0" standalone="yes" ?>
<!DOCTYPE student [
    <!ELEMENT student (firstName,lastName,email,mobile)>
    <!ELEMENT firstName (#PCDATA)>
    <!ELEMENT lastName (#PCDATA)>
    <!ELEMENT email (#PCDATA)>
    <!ELEMENT mobile (#PCDATA)>
]>
<student>
    <firstName>John</firstName>
    <lastName>Smith</lastName>
    <email>jsmith@gmail.com</email>
    <mobile>0211223344</mobile>
</student>
```

DTD: external DTD

DTD is declared outside the XML file:

```
<?xml version="1.0" standalone="no" ?>
<!DOCTYPE student SYSTEM "student.dtd">
<student>
  <firstName>John</firstName>
  <lastName>Smith</lastName>
  <email>jsmith@gmail.com</email>
  <mobile>0211223344</mobile>
</student>
```

The content of `student.dtd`

```
<!ELEMENT student (firstName,lastName,email,mobile)>
<!ELEMENT firstName (#PCDATA)>
<!ELEMENT lastName (#PCDATA)>
<!ELEMENT email (#PCDATA)>
<!ELEMENT mobile (#PCDATA)>
```

DTD: internal DTD

The following DTD is declared inside the XML file:

```
<?xml version="1.0" encoding="UTF-8" standalone="yes" ?>
<!DOCTYPE studentList [
    <!ELEMENT studentList (student*)>
    <!ELEMENT student (firstName,lastName,email)>
    <!ELEMENT firstName (#PCDATA)>
    <!ELEMENT lastName (#PCDATA)>
    <!ELEMENT email (#PCDATA)>
]>
<studentList>
  <student>
    <firstName>John</firstName>
    <lastName>Smith</lastName>
    <email>jsmith@gmail.com</email>
  </student>
  <student>
    <firstName>Mary</firstName>
    <lastName>Jane</lastName>
    <email>mjane@gmail.com</email>
  </student>
</studentList>
```

DTD: external DTD

DTD is declared outside the XML file:


```
<?xml version="1.0" encoding="UTF-8" standalone="no" ?>
<!DOCTYPE studentList SYSTEM "studentList.dtd">
<studentList>
  <student>
    <firstName>John</firstName>
    <lastName>Smith</lastName>
    <email>jsmith@gmail.com</email>
  </student>
  <student>
    <firstName>Mary</firstName>
    <lastName>Jane</lastName>
    <email>mjane@gmail.com</email>
  </student>
</studentList>
```

The content of **studentList.dtd**

```
<!ELEMENT studentList (student*)>
<!ELEMENT student (firstName,lastName,email)>
<!ELEMENT firstName (#PCDATA)>
<!ELEMENT lastName (#PCDATA)>
<!ELEMENT email (#PCDATA)>
```

DTD: external DTD

DTD is declared outside the XML file:

```
<?xml version="1.0" encoding="UTF-8" standalone="no" ?>
<!DOCTYPE studentList SYSTEM "studentList.dtd
```

To reference it as external DTD, **standalone** attribute in the XML declaration must be set as **no**. This means, declaration includes information from the external source.

DTD: Element declaration

XML elements are building blocks of an XML document.

An element is everything from the element's start tag to the element's end tag:

```
<firstName>John</firstName>  
<lastName>Smith</lastName>
```

In DTD, we declare element as follows:

```
<!ELEMENT firstName (#PCDATA)>  
<!ELEMENT lastName (#PCDATA)>
```

Here PCDATA stands for parsed character data.

DTD: Element declaration

An element can contain other elements

```
<student>  
  <firstName>John</firstName>  
  <lastName>Smith</lastName>  
  <email>jsmith@gmail.com</email>  
</student>
```

In DTD, we declare as follows:

```
<!ELEMENT student (firstName,lastName,email)>
```

It means, the element **student** contains elements **firstName**, **lastName** and **email**.

DTD: Element declaration

An element can contain other elements

```
<studentList>
  <student>
    <firstName>John</firstName>
    <lastName>Smith</lastName>
    <email>jsmith@gmail.com</email>
  </student>
  <student>
    <firstName>Mary</firstName>
    <lastName>Jane</lastName>
    <email>mjane@gmail.com</email>
  </student>
</studentList>
```

In DTD, we declare as follows:

```
<!ELEMENT studentList (student*)>
```

It means, the element **studentList** contains zero or more elements **student**.

DTD: Element declaration

This is the general form of element declaration:

```
<!ELEMENT elementName (content)>
```

- **elementName** is the element name that you are defining.
- **content** defines what content (if any) can go within the element

DTD: Element declaration

Element content:

```
<!ELEMENT elementName (child1, child2,...)>
```

Example:

```
<!ELEMENT studentList (student*)>
```

```
<!ELEMENT student (firstName,lastName,email)>
```

<pre><!ELEMENT elementName (child+)></pre>	child element can occur one or more times inside parent element
<pre><!ELEMENT elementName (child*)></pre>	child element can occur zero or more times inside parent element
<pre><!ELEMENT elementName (child?)></pre>	child element can occur zero or one time inside parent element
<pre><!ELEMENT elementName (child1 child2)></pre>	either of <code>child1</code> or <code>child2</code> must occur in inside parent element
<pre><!ELEMENT elementName (child1,child2,child3,...)></pre>	Parent element must have <code>child1,child2,child3,...</code> appear in this order

DTD: Attribute declaration

This is the general form of attribute declaration:

```
<!ATTLIST elementName attributeName attributeType attributeValue>
```

- `elementName` specifies the name of the element to which the attribute applies,
- `attributeName` specifies the name of the attribute,
- `attributeType` defines the type of attributes
- `attributeValue` defines the attribute value

DTD: Attribute declaration

```
<!ATTLIST elementName attributeName attributeType attributeValue>  
attributeValue
```

- can have a default value

```
<!ATTLIST elementName attributeName attributeType "default-value">
```

- can have a fixed value

```
<!ATTLIST elementName attributeName attributeType #FIXED "value">
```

- is required

```
<!ATTLIST elementName attributeName attributeType #REQUIRED>
```

- is implied: if the attribute has no default value, has no fixed value, and is not required, then it must be declared as implied

```
<!ATTLIST elementName attributeName attributeType #IMPLIED>
```

DTD: Attribute declaration

```
<?xml version="1.0" ?>
<dailyTransaction date="24/02/2015">
  <person staffDbId="103" operation="update">
    <firstName>John</firstName>
    <lastName>Smith</lastName>
    <mobile>0211223344</mobile>
  </person>
  <person staffDbId="-1" operation="add">
    <firstName>Mary</firstName>
    <lastName>Jane</lastName>
    <mobile>0244556677</mobile>
  </person>
</dailyTransaction>
```

```
<!ELEMENT dailyTransaction (person*)>
<!ATTLIST dailyTransaction date CDATA #REQUIRED>
<!ELEMENT person (firstName,lastName,mobile)>
<!ATTLIST person staffDbId CDATA #REQUIRED>
<!ATTLIST person operation CDATA #REQUIRED>
<!ELEMENT firstName (#PCDATA)>
<!ELEMENT lastName (#PCDATA)>
<!ELEMENT mobile (#PCDATA)>
```

References

- XML:

<https://developer.mozilla.org/en-US/docs/Web/XML>

- DTD:

[https://msdn.microsoft.com/en-us/library/ms256469\(v=vs.110\).aspx](https://msdn.microsoft.com/en-us/library/ms256469(v=vs.110).aspx)