

ASSIGNMENT NO.1**TITLE: Chinese Remainder Theorem**

PROBLEM STATEMENT: Implement a number theory such as Chinese remainder Theorem

OBJECTIVE:

To study & implement Chinese Remainder Theorem

THEORY:

Chinese Remainder Theorem is used to solve set of congruent equations with one variable but different modulus, which are relatively prime

$$x \equiv a_1 \pmod{m_1}$$

$$x \equiv a_2 \pmod{m_2}$$

$$x \equiv a_3 \pmod{m_3}$$

.....

$$x \equiv a_k \pmod{m_k}$$

The Chinese Remainder Theorem states that the above equations have a unique solution if the moduli are relatively prime. Below are the steps needed to follow to solve set of congruent equations using Chinese Remainder Theorem

Step I: Find $M = m_1 \times m_2 \times m_3 \dots m_k$ where M is common modulus Step II: Find $M_1 = M/m_1$, $M_2 = M/m_2$ and so on

Step III: Find multiplicative inverses for M_1 , M_2 and so on

Step IV: Put the values in the below equation to solve for X

$$X = (a_1 \times M_1 \times M_1^{-1} + a_2 \times M_2 \times M_2^{-1} + a_3 \times M_3 \times M_3^{-1}) \pmod{M}$$

Example

$$X = 4 \pmod{5}$$

$$X = 6 \pmod{8}$$

$$X = 8 \pmod{9}$$

$$\text{Step I: } M = 5 \times 8 \times 9 = 360$$

$$\text{Step II: } M_1 = M/m_1 = 360 / 5 = 72$$

$$M_2 = M/m_2 = 360 / 8 = 45$$

$$M_3 = M/m_3 = 360 / 9 = 40$$

Step III:

To find M_1 inverse, Solve for GCD (m_1 , M_1) using Extended Euclidean Algorithm. GCD (5, 72)

q	r1	r2	r	t1	t2	t
---	----	----	---	----	----	---

0	5	72	5	0	1	0
14	72	5	2	1	0	1
2	5	2	1	0	1	-2

The inverse value cannot be negative, so add modulus into it to make it positive. $M1$ inverse = $-2 + 5 = 3$

To find $M2$ inverse, Solve for GCD ($m2$, $M2$) using Extended Euclidean Algorithm. GCD (8, 45)

q	r1	r2	r	t1	t2	t
0	8	45	8	0	1	0
5	45	8	5	1	0	1
1	8	5	3	0	1	-1
1	5	3	2	1	-1	2
1	3	2	1	-1	2	-3

$M2$ inverse = $-3 + 8 = 5$

To find the $M3$ inverse, Solve for GCD ($m3$, $M3$) using Extended Euclidean Algorithm. GCD (9, 40)

q	r1	r2	r	t1	t2	t
0	9	40	9	0	1	0
4	40	9	4	1	0	1
2	9	4	1	0	1	-2

$M3$ inverse = $-2 + 9 = 7$

Step IV: Put the values in the below equation to solve for X

$$X = (a1 \times M1 \times M1^{-1} + a2 \times M2 \times M2^{-1} + a3 \times M3 \times M3^{-1}) \bmod M \quad X = (4 \times 72 \times 3 + 6 \times 45 \times 5 + 8 \times 40 \times 7) \bmod 360$$

$$X = (864 + 1350 + 2240) \bmod 360$$

$$X = 4454 \bmod 360$$

$$X = 134$$

CODE:

```
// A C++ program to demonstrate working of Chinese remainder
// Theorem
#include<iostream.h>
using namespace std;

// k is the size of num[] and rem[]. Returns the smallest
// number x such that:
// x % num[0] = rem[0],
// x % num[1] = rem[1],
// .....
// x % num[k-2] = rem[k-1]
// Assumption: Numbers in num[] are pairwise coprime
// (gcd for every pair is 1)
int findMinX(int num[], int rem[], int k)
{
    int x = 1; // Initialize result

    // As per the Chinese remainder theorem,
    // this loop will always break.
    while (true)
    {
        // Check if remainder of x % num[j] is
        // rem[j] or not (for all j from 0 to k-1)
        int j;
        for (j=0; j<k; j++)
            if (x%num[j] != rem[j])
                break;

        // If all remainders matched, we found x
        if (j == k)
            return x;

        // Else try next number
        x++;
    }

    return x;
}
```

```
// Driver method
int main(void)
{
    int num[] = {3, 4, 5};
    int rem[] = {2, 3, 1};
    int k = sizeof(num)/sizeof(num[0]);
    cout << "x is " << findMinX(num, rem, k);
    return 0;
}
```

The screenshot shows a web browser at `tutorialspoint.com/compile_cpp_online.php` with an online C++ compiler. The code in the editor is as follows:

```
1 //C++ program to demonstrate working of Chinese remainder Theorem
2 #include<iostream>
3 using namespace std;
4
5 int findMinX(int num[], int rem[], int k)
6 {
7     int x = 1; // Initialize result
8     while (true)
9     {
10         int j;
11         for (j=0; j<k; j++)
12             if (x%num[j] != rem[j])
13                 break;
14         if (j == k)
15             return x;
16         x++;
17     }
18     return x;
19 }
20
21 // Driver method
22 int main(void)
23 {
24     int num[] = {3, 4, 5};
25     int rem[] = {2, 3, 1};
26     int k = sizeof(num)/sizeof(num[0]);
27     cout << "x is " << findMinX(num, rem, k);
28     return 0;
29 }
30
```

The terminal output on the right shows: `x is 11`.

Applications

The Chinese Remainder Theorem has several applications in cryptography. One is to solve the quadratic congruence and the other is to represent a very large number in terms of a list of small integers.

CONCLUSION:

We have studied & implemented the Chinese Remainder Theorem.

ASSIGNMENT NO.2

TITLE: Extended Euclidean Algorithm

PROBLEM STATEMENT: Implement Euclidean and Extended Euclidean algorithm to find out GCD and solve the inverse mod problem.

OBJECTIVES:

To study Euclidean & Extended Euclidean algorithm

THEORY:

The extended Euclidean algorithm is an extension to the Euclidean algorithm. Besides finding the greatest common divisor of integers a and b , as the Euclidean algorithm does, it also finds integers x and y (one of which is typically negative).

$ax + by = \gcd(a, b)$ or $sa + tb = \gcd(a, b)$

The extended Euclidean algorithm is particularly useful when a and b are coprime, since x is the multiplicative inverse of a modulo b , and y is the multiplicative inverse of b modulo a .




Figure: Extended Euclid's Algorithm Process

Algorithm:

Extend the algorithm to compute the integer coefficients x and y such that $\gcd(a, b) = ax + by$

Extended-Euclid (a, b)

```

 $r_1 \leftarrow a; \quad r_2 \leftarrow b;$ 
 $s_1 \leftarrow 1; \quad s_2 \leftarrow 0;$ 
 $t_1 \leftarrow 0; \quad t_2 \leftarrow 1;$ 
(Initialization)
while ( $r_2 > 0$ )
{
   $q \leftarrow r_1 / r_2;$ 
   $r \leftarrow r_1 - q \times r_2;$ 
   $r_1 \leftarrow r_2; \quad r_2 \leftarrow r;$ 
  (Updating  $r$ 's)
   $s \leftarrow s_1 - q \times s_2;$ 
   $s_1 \leftarrow s_2; \quad s_2 \leftarrow s;$ 
  (Updating  $s$ 's)
   $t \leftarrow t_1 - q \times t_2;$ 
   $t_1 \leftarrow t_2; \quad t_2 \leftarrow t;$ 
  (Updating  $t$ 's)
}
gcd( $a, b$ )  $\leftarrow r_1; \quad s \leftarrow s_1; \quad t \leftarrow t_1$ 

```

Example:

GCD (161, 28)

q	r1	r2	r	s1	s2	s	t1	t2	t
5	161	28	21	1	0	1	0	1	-5
1	28	21	7	0	1	-1	1	-5	6
3	21	7	0	1	-1	4	-5	6	-23
	7	0		-1	4		6	-23	

Here GCD value we are getting as 7. Value of s is -1 and value of t is 6. If we put these values into equation,

$$ax + by = \text{gcd}(a, b)$$

$$161 * (-1) + 28 * (6) = 7$$

This satisfies the equation for Extended Euclidean Algorithm

CODE:

// C++ program to demonstrate working of

```

// extended Euclidean Algorithm
#include <bits/stdc++.h>
using namespace std;

// Function for extended Euclidean Algorithm
int gcdExtended(int a, int b, int *x, int *y)
{
    // Base Case
    if (a == 0)
    {
        *x = 0;
        *y = 1;
        return b;
    }

    int x1, y1; // To store results of recursive call
    int gcd = gcdExtended(b%a, a, &x1, &y1);

    // Update x and y using results of
    // recursive call
    *x = y1 - (b/a) * x1;
    *y = x1;

    return gcd;
}

// Driver Code
int main()
{
    int x, y, a = 35, b = 15;
    int g = gcdExtended(a, b, &x, &y);
    cout << "GCD(" << a << ", " << b
        << ") = " << g << endl;
    return 0;
}

```

```
1 // C++ program to demonstrate working of
2 // extended Euclidean Algorithm
3 #include <bits/stdc++.h>
4 using namespace std;
5
6 // Function for extended Euclidean Algorithm
7 int gcdExtended(int a, int b, int *x, int *y)
8 {
9     // Base Case
10    if (a == 0)
11    {
12        *x = 0;
13        *y = 1;
14        return b;
15    }
16
17    int x1, y1; // To store results of recursive call
18    int gcd = gcdExtended(b%a, a, &x1, &y1);
19
20    // Update x and y using results of
21    // recursive call
22    *x = y1 - (b/a) * x1;
23    *y = x1;
24
25    return gcd;
26 }
27
28 // Driver Code
29 int main()
30 {
31     int x, y, a = 35, b = 15;
32     int g = gcdExtended(a, b, &x, &y);
33 }
```

GCD(35, 15) = 5

CONCLUSION:

We have studied and implemented the Extended Euclidean algorithm.

ASSIGNMENT NO.3

TITLE: RSA Algorithm

PROBLEM STATEMENT: Implement RSA public key cryptosystem for key generation and cipher verification.

OBJECTIVES:

To understand,

1. Public key algorithm.
2. RSA algorithm
3. Concept of Public key and Private Key

THEORY:

Public Key Algorithm:

Asymmetric algorithms rely on one key for encryption and a different but related key for decryption. These algorithms have the following important characteristics: · It is computationally infeasible to determine the decryption key given only knowledge of the cryptographic algorithm and the encryption key. In addition, some algorithms, such as RSA, also exhibit the following characteristics: · Either of the two related keys can be used for encryption, with the other used for decryption.

A public key encryption scheme has six ingredients:

- **Plaintext:** This is a readable message or data that is fed into the algorithm as input.
- **Encryption algorithm:** The encryption algorithm performs various transformations on the plaintext.
- **Public and private key:** This is a pair of keys that have been selected so that if one is used for encryption, the other is used for decryption. The exact transformations performed by the algorithm depend on the public or private key that is provided as input.
- **Cipher text:** This is the scrambled message produced as output. It depends on the plaintext and the key. For a given message, two different keys will produce two different cipher texts.
- **Decryption algorithm:** This algorithm accepts the ciphertext and the matching key and produces the original plaintext.

Bob's	Ted	Input
Public key	Plaintext	Encryption
Ring	Alice Private	algorithm
Joy	Key	Decryption Output
Alice	Transmitted	algorithm
Plaintext	cipher text	

Figure: Public key cryptography

The essential steps are as the following:

1. Each user generates a pair of keys to be used for the encryption and decryption of messages.
2. Each user places one of the two keys in a public register or the other accessible file. This is the public key. The companion key is kept private. As figure suggests, each user maintains a collection of public keys obtained from others.
3. If Bob wishes to send a confidential message to Alice, Bob encrypts the message using Alice's public key.

When Alice receives the message, she decrypts it using her private key. No other recipient can decrypt the message because only Alice knows Alice's private key.

The RSA Algorithm:

The scheme developed by Rivest, Shamir and Adleman makes use of an expression with exponentials. Plaintext is encrypted in blocks, with each block having a binary value less than some number n . That is the block size must be less than or equal to $\log_2(n)$; in practice the block size is l bits, where $2^l < n \leq 2^{l+1}$. Encryption and decryption are of the following form, for some plaintext block M and ciphertext block C :

$$C = M^e \bmod n$$

$$M = C^d \bmod n$$

Both sender and receiver must know the value of n . The sender knows the value of e , and only the receiver knows the value of d . Thus, this is a public-key encryption algorithm with a public key of $PU = \{e, n\}$ and a private key of $PR = \{d, n\}$. For this

algorithm to be satisfactory for public key encryption, the following requirements must meet:

1. It is possible to find values of e , d , n .
2. It is relatively easy to calculate $M^e \bmod n$ and $C^d \bmod n$ for all values of $M < n$.
3. It is feasible to determine d given e and n .

Key Generation

Select p , q p and q both prime, $p \neq q$

Calculate $n = p * q$

Calculate $\phi(n) = (p-1)(q-1)$

Select integer e $\gcd(\phi(n), e) = 1$; $1 < e < \phi(n)$

Calculate $d = e^{(-1)} \bmod \phi(n)$

Public key $PU = \{e, n\}$

Private key $PR = \{d, n\}$

Encryption

Plaintext $M < n$

Ciphertext $C = M^e \bmod n$

Decryption

Ciphertext C

Plaintext $M = C^d \bmod n$

Figure: The RSA Algorithm

Example 1:

1. Select two prime numbers, $p = 17$ and $q = 11$.
2. Calculate $n = pq = 17 * 11 = 187$.
3. Calculate $\phi(n) = (p-1)(q-1) = 16 * 10 = 160$.
4. Select e such that it is relatively prime to $\phi(n) = 160$ & less than $\phi(n)$; we choose $e = 7$.
5. Determine d such that $de \equiv 1 \pmod{160}$ and $d < 160$. The correct value is $d = 23$; d can be calculated using Euclid's extended algorithm.

The resulting keys are public key $PU = \{7, 187\}$ and private key $PR = \{23, 187\}$. The example shows the use of these keys for plaintext input of $M=88$.

Encryption Decryption

Plaintext	Ciphertext	PU=7,187 PR=23,187
88	11	Figure: Example of RSA.
	$88^{(7)} \bmod 187 = 11$	Plaintext 88
	$11^{(23)} \bmod 187 = 88$	

Example 2:

$P = 7$, $Q = 13$, $M = 10$.

Step I: $n = 3 * 11 = 33$

Step II: $\phi(n) = 2 * 10 = 20$

Step III: Select e , such that $\gcd(\phi(n), e) = 1$, $\gcd(20, 3) = 1$, So we can select $e = 3$ Step

IV: To calculate d , solve for $\gcd(\phi(n), e)$ using extended Euclid's algorithm and pick up the value of t .

q	r1	r2	r	t1	t2	t
6	20	3	2	0	1	-6
1	3	2	1	1	-6	7

$d = 7$

Step V: For Encryption,

$C = M^e \bmod n$

$= 2^3 \bmod 33$

$= 8 \bmod 33$

$= 8$

Step VI: For Decryption,

$M = C^d \bmod n$

$= 8^7 \bmod 33$

$= ((8^2 \bmod 33) (8^2 \bmod 33) (8^2 \bmod 33) (8^1 \bmod 33)) \bmod 33 = (31 * 31 * 31 * 8) \bmod 33$

$= (961 \bmod 33) (248 \bmod 33) \bmod 33$

$= 68 \bmod 33$

$= 2$

Advantages:

1. Easy to implement.

Disadvantages:

1. Anyone can announce the public key.

Algorithm:

1. Start
2. Input two prime numbers p and q.
3. Calculate $n = pq$.
4. Calculate $\phi(n) = (p-1)(q-1)$.
5. Input value of e.
6. Determine d.
7. Determine PU and PR.
8. Take input plaintext.
9. Encrypt the plaintext and show the output.
10. Stop.

CODE:

// C program for RSA asymmetric cryptographic

#include<stdio.h>

```

#include<math.h>
int gcd(int a, int h)
{
    int temp;
    while (1)
    {
        temp = a%h;
        if (temp == 0)
            return h;
        a = h;
        h = temp;
    }
}

// Code to demonstrate RSA algorithm
int main()
{
    // Two random prime numbers
    double p = 3;
    double q = 7;

    // First part of public key:
    double n = p*q;

    // Finding other part of public key.
    double e = 2;
    double phi = (p-1)*(q-1);
    while (e < phi)
    {
        if (gcd(e, phi)==1)
            break;
        else
            e++;
    }
    int k = 2;
    double d = (1 + (k*phi))/e;
    double msg = 20;
    printf("Message data = %lf", msg);
    double c = pow(msg, e);
    c = fmod(c, n);
}

```

```

printf("\nEncrypted data = %lf", c);
double m = pow(c, d);
m = fmod(m, n);
printf("\nOriginal Message Sent = %lf", m);

return 0;
}

```

The screenshot shows a web browser at tutorialspoint.com/compile_cpp_online.php with the 'Online C++ Compiler' interface. The code editor on the left contains a C program for RSA asymmetric cryptography. The terminal on the right displays the output of the program.

```

1 // C program for RSA asymmetric cryptographic
2
3 #include<stdio.h>
4 #include<math.h>
5 int gcd(int a, int b)
6 {
7     int temp;
8     while (1)
9     {
10        temp = a%b;
11        if (temp == 0)
12            return b;
13        a = b;
14        b = temp;
15    }
16 }
17
18 // Code to demonstrate RSA algorithm
19 int main()
20 {
21     // Two random prime numbers
22     double p = 3;
23     double q = 7;
24
25     // First part of public key:
26     double n = p*q;
27
28     // Finding other part of public key.
29     double e = 2;
30     double phi = (p-1)*(q-1);
31     while (e < phi)
32     {

```

Terminal Output:

```

Message data = 20.000000
Encrypted data = 20.000000
Original Message Sent = 20.000000

```

CONCLUSION:

We have studied and implemented the public key algorithm that is RSA algorithm.

ASSIGNMENT NO.4

TITLE: Diffie Hellman Key Exchange

PROBLEM STATEMENT: Implement Diffie Hellman key exchange algorithm for secret key generation and distribution of public key

OBJECTIVE:

1. To learn the basics of key management.
2. To study & implement Diffie Hellman key exchange algorithm.

THEORY:

The purpose of the algorithm is to enable two users to securely exchange a key that can then be used for subsequent encryption of messages. The algorithm itself is limited to the exchange of secret values.

Algorithm:

There are two publicly known numbers: a prime number q and an integer α that is a primitive root of q .

Suppose the users A and B wish to exchange a key.

User A selects a random integer $X_A < q$ and computes $Y_A = \alpha^{X_A} \bmod q$. Similarly User B independently selects a random integer $X_B < q$ and computes $Y_B = \alpha^{X_B} \bmod q$. Each side keeps the value X private and makes the value Y available publicly to the other side.

User A computes the key K as $K = Y_B^{X_A} \bmod q$

User B computes the key K as $K = Y_A^{X_B} \bmod q$

These two calculations produce identical results.

Eg.

1. Users Alice & Bob who wish to swap keys:

2. Agree on prime $q=353$ and $\alpha=3$

3. Select random secret keys:

– A chooses $X_A=97$, B chooses $X_B=233$

4. Compute public keys:

– $Y_A=3^{97} \bmod 353 = 40$ (Alice)

– $Y_B=3^{233} \bmod 353 = 248$ (Bob)

5. Compute shared session key as:

$K_{AB}=Y_B^{X_A} \bmod 353 = 248^{97} = 160$ (Alice)

$K_{AB}=Y_A^{X_B} \bmod 353 = 40^{233} = 160$ (Bob)




Figure: Diffie Hellman Process

CODE:

```

/* the Diffie-Hellman Key exchange algorithm using C++ */
#include <cmath>
#include <iostream>
using namespace std;
long long int power(long long int a, long long int b,
                    long long int P)
{
    if (b == 1)
        return a;

```

```

        else
            return (((long long int)pow(a, b)) % P);
    }

// Driver program
int main()
{
    long long int P, G, x, a, y, b, ka, kb;
    P = 23;
    cout << "The value of P : " << P << endl;


    G = 9;
    cout << "The value of G : " << G << endl;
    a = 4;
    cout << "The private key a for Preeti : " << a << endl;

    x = power(G, a, P);
    b = 3;
    cout << "The private key b for Kriti : " << b << endl;
    y = power(G, b, P);
    ka = power(y, a, P);
    kb = power(x, b, P);
    cout << "Secret key for the Preeti is : " << ka << endl;

    cout << "Secret key for the Kriti is : " << kb << endl;

    return 0;
}

```

The screenshot displays a web-based C++ compiler interface. The browser's address bar shows the URL `tutorialspoint.com/compile_cpp_online.php`. The compiler's header includes the text "Online C++ Compiler" and navigation links such as "Execute", "Beautify", "Share", "Source Code", and "Help". The main editor area contains the following C++ code:

```
5 long long int power(long long int a, long long int b,  
6 long long int P)  
7 {  
8     if (b == 1)  
9         return a;  
10    else  
11        return (((long long int)pow(a, b)) % P);  
12 }  
13  
14 // Driver program  
15 int main()  
16 {  
17     long long int P, G, x, a, y, b, ka, kb;  
18     P = 23;  
19     cout << "The value of P : " << P << endl;  
20  
21     G = 9;  
22     cout << "The value of G : " << G << endl;  
23     a = 4;  
24     cout << "The private key a for Preeti : " << a << endl;  
25  
26     x = power(G, a, P);  
27     b = 3;  
28     cout << "The private key b for Kriti : " << b << endl;  
29     y = power(G, b, P);  
30     ka = power(y, a, P);  
31     kb = power(x, b, P);  
32     cout << "Secret key for the Preeti is : " << ka << endl;  
33     cout << "Secret key for the Kriti is : " << kb << endl;  
34  
35     cout << "Secret key for the Kriti is : " << kb << endl;  
36 }
```

The output window on the right displays the following results:

```
The value of P : 23  
The value of G : 9  
The private key a for Preeti : 4  
The private key b for Kriti : 3  
Secret key for the Preeti is : 9  
Secret key for the Kriti is : 9
```

The bottom of the image shows a Windows taskbar with various application icons and a system tray indicating a temperature of 22°C and the time 01:03 AM on 27-09-22.

CONCLUSION:

We have studied & implemented the Diffie Hellman key exchange algorithm.