



TERRAFORM – 01

1 . install terraform on pc

- Download terraform file from terraform official site
- Now, downloads >> extract file using
- Now open it with winrar




- Click exe file




- Now copy the terraform file from downloads and paste it in c drive .

- Now add path
- Go to start button >
- Search for environmental variables




- Select path and hit edit



- Add the new path
- Add location of terraform

- C:\terraform_1.14.0_windows_386 (as we pasted terraform file in c drive)
- Now run terraform -v command in git from desktop location can see the version of terraform available in our local computer.



```

MINGW64:/c:/Users/guntu/OneDrive/Desktop
guntu@LAPTOP-14A29B5E MINGW64 ~/OneDrive/Desktop (master)
$ terraform -v
Terraform v1.14.0
on windows_386

guntu@LAPTOP-14A29B5E MINGW64 ~/OneDrive/Desktop (master)
$

```

2 . Execute all the templates shown in video.

- Create a folder in desktop > local machine
- Now, open vs code
- Add a folder in vs code
- And add extension “hashi crop ”
- Now add afile to that folder
- And write a template




```

main.tf
main.tf > resource "local_file" "my_pet"
1  resource "local_file" "my_pet" {
2  filename = "/c/Users/guntu/OneDrive/Desktop/terraform_basic/pet.txt"
3  content = "i love pets"
4  }

```

- Now, on the top click terminal

- And give command -- terraform init



The screenshot shows a Visual Studio Code editor with a file named `main.tf` open. The file contains a Terraform configuration for a local file resource. Below the editor, the `Terminal` panel is active, displaying the output of the `terraform init` command.

```
main.tf > resource "local_file" "my_pet"
1  resource "local_file" "my_pet" {
2    filename = "/c/Users/guntu/OneDrive/Desktop/terraform_basic/pet.txt"
3    content = "i love pets"
4  }
```

Terminal (Ctrl+`)

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS

you run "terraform init" in the future.


Terraform has been successfully initialized!

You may now begin working with Terraform. Try running "terraform plan" to see any changes that are required for your infrastructure. All Terraform commands should now work.

If you ever set or change modules or backend configuration for Terraform, rerun this command to reinitialize your working directory. If you forget, other commands will detect it and remind you to do so if necessary.

PS C:\Users\guntu\OneDrive\Desktop\terraform_basic>

- Can file will be added to folder .
- 3 . Note down below points, Terraform Init, Terraform Plan, Terraform Apply, Terraform Provider.
- Terra form init



The image shows a Visual Studio Code editor window with two tabs: 'main.tf' and '.terraform.lock.hcl'. The 'main.tf' tab is active, displaying a Terraform configuration for a local file resource named 'my_pet'. The configuration is as follows:

```
main.tf > resource "local_file" "my_pet"
1  resource "local_file" "my_pet" {
2    filename = "/c/Users/guntu/OneDrive/Desktop/terraform_basic/pet.txt"
3    content = "i love pets"
4  }
```

Below the editor, the 'TERMINAL' panel is open, showing the output of a Terraform command. The output indicates that Terraform has been successfully initialized and provides instructions on how to proceed with the workflow.

```
PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS

you run "terraform init" in the future.

Terraform has been successfully initialized!

You may now begin working with Terraform. Try running "terraform plan" to see
any changes that are required for your infrastructure. All Terraform commands
should now work.

If you ever set or change modules or backend configuration for Terraform,
rerun this command to reinitialize your working directory. If you forget, other
commands will detect it and remind you to do so if necessary.
PS C:\Users\guntu\OneDrive\Desktop\terraform_basic>
```

- Terraform plan

```
main.tf x terraform.lock.hcl
main.tf > resource "local_file" "my_pet"
1 resource "local_file" "my_pet" {
2   filename = "/c/Users/guntu/OneDrive/Desktop/terraform_basic/pet.txt"
3   content = "i love pets"
4 }

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS
commands will detect it and remind you to do so if necessary.
PS C:\Users\guntu\OneDrive\Desktop\terraform_basic> terraform plan

Terraform used the selected providers to generate the following execution plan. Resource actions are indicated with the following symbols:
+ create

Terraform will perform the following actions:

# local_file.my_pet will be created
+ resource "local_file" "my_pet" {
  + content          = "i love pets"
  + content_base64sha256 = (known after apply)
  + content_base64sha512 = (known after apply)
  + content_md5       = (known after apply)
  + content_sha1      = (known after apply)
  + content_sha256    = (known after apply)
  + content_sha512    = (known after apply)
  + directory_permission = "0777"
  + file_permission   = "0777"
  + filename          = "/c/Users/guntu/OneDrive/Desktop/terraform_basic/pet.txt"
  + id                = (known after apply)
```

- Terraform apply now ,

```
Plan: 1 to add, 0 to change, 0 to destroy.

Do you want to perform these actions?
  Terraform will perform the actions described above.
  Only 'yes' will be accepted to approve.

  Enter a value: yes


local_file.my_pet: Creating...
local_file.my_pet: Creation complete after 0s [id=24899fdea020fed9c33448b53811e17d15bb4f25]
App Focus folder in explorer (ctrl + click), 0 changed, 0 destroyed.
PS C:\Users\guntu\OneDrive\Desktop\terraform_basic> terraform apply
local_file.my_pet: Refreshing state... [id=24899fdea020fed9c33448b53811e17d15bb4f25]

No changes. Your infrastructure matches the configuration.

Terraform has compared your real infrastructure against your configuration and found no differences, so no changes are needed.

Apply complete! Resources: 0 added, 0 changed, 0 destroyed.
PS C:\Users\guntu\OneDrive\Desktop\terraform_basic>
```

- Terraform provider.
- Add new content to main.tf
- And then do terraform init



The screenshot shows a VS Code editor with two tabs: 'main.tf' and '.terraform.lock.hcl'. The 'main.tf' tab is active, displaying a Terraform configuration snippet:

```
1 provider "aws" {
2     region = "ap-south-1"
3 }
4
```

The bottom panel shows the 'TERMINAL' tab with the following output:

```
Initializing the backend...
Initializing provider plugins...
- Finding latest version of hashicorp/aws...
- Reusing previous version of hashicorp/local from the dependency lock file
- Installing hashicorp/aws v6.22.1...
- Installed hashicorp/aws v6.22.1 (signed by HashiCorp)
- Using previously-installed hashicorp/local v2.6.1
Terraform has made some changes to the provider dependency selections recorded
in the .terraform.lock.hcl file. Review those changes and commit them to your
version control system if they represent changes you intended to make.

Terraform has been successfully initialized!

You may now begin working with Terraform. Try running "terraform plan" to see
any changes that are required for your infrastructure. All Terraform commands
should now work.

If you ever set or change modules or backend configuration for Terraform,
rerun this command to reinitialize your working directory. If you forget, other
commands will detect it and remind you to do so if necessary.
PS C:\Users\guntu\OneDrive\Desktop\terraform_basic>
```

- Terraform plan
- And then terraform apply and give yes

```

main.tf
1 provider "aws" {
2   region = "ap-south-1"
3 }
4

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS
- content_sha512 = "7b0f700e8678ed63b2852536559b4a42ce8617c889796d76e6a9585dc30" -> null
- directory_permission = "0777" -> null
- file_permission = "0777" -> null
- filename = "/c:/Users/guntu/OneDrive/Desktop/terraform_basic/pet.png" -> null
- id = "24899fdea020fed9c33448b53811e17d15bb4f25" -> null
}

Plan: 0 to add, 0 to change, 1 to destroy.

Do you want to perform these actions?
Terraform will perform the actions described above.
Only 'yes' will be accepted to approve.

Enter a value: yes

local_file.my_pet: Destroying... [id=24899fdea020fed9c33448b53811e17d15bb4f25]
local_file.my_pet: Destruction complete after 0s

Apply complete! Resources: 0 added, 0 changed, 1 destroyed.
PS C:\Users\guntu\OneDrive\Desktop\terraform_basic>

```

- Terraform provider .
- Add a script
- Configure = aws configure
- Give access key and secret key

```

• resource "aws_instance" "webserver" {
•   ami           = "ami-0fa3fe0fa7920f68e"
•   subnet_id     = "subnet-022a5b6a074769fa4"
•   instance_type = "t3.micro"
•   tags = {
•     Name = "test"
•   }
• }

```

- Copy ami id from aws ec2 and give it here
- And open terminal hit terraform apply
- Ec2 instance will be launching

Instances (1/1) [Info](#) Last updated 5 minutes ago [Connect](#) [Instance state](#) [Actions](#)

[Running](#)

<input checked="" type="checkbox"/>	Name 🔗	Instance ID	Instance state	Instance type	Status check	Alarm
<input checked="" type="checkbox"/>	test	i-0f9ee3257889e124e	Running	t3.micro	Initializing	View

4 . Integrate a sample Terraform template in jenkins.

- Create a file called main.tf
- /var/lib/jenkins/terraform-demo/main.tf
- Add script to main.tf (it contains vpc, subnet id, aws-cred)
- terraform {
- required_providers {
- aws = {
- source = "hashicorp/aws"
- version = "~> 5.0"
- }
- }
- }
-
- provider "aws" {
- region = "us-east-1"
- }
-
- # -----
- # EC2 Instance
- # -----
- resource "aws_instance" "example" {
- ami = "ami-0c02fb55956c7d316"
- instance_type = "t2.micro"
-
- # REQUIRED → your subnet
- subnet_id = "subnet-022a5b6a074769fa4"
-
- # Optional tags
- tags = {

- Name = "jenkins-terraform-demo"
- }
- }

```
[root@ip-10-0-1-110 terraform-demo]# ls
main.tf  terraform.tfstate  terraform.tfstate.backup
[root@ip-10-0-1-110 terraform-demo]# cat main.tf
terraform {
  required_providers {
    aws = {
      source = "hashicorp/aws"
      version = "~> 5.0"
    }
  }
}

provider "aws" {
  region = "us-east-1"
}

# -----
# EC2 Instance
# -----
resource "aws_instance" "example" {
  ami           = "ami-0c02fb55956c7d316"
  instance_type = "t2.micro"
}
```

i-0a4cbcc0493321880 (Jenkins)

PublicIPs: 34.229.221.61 PrivateIPs: 10.0.1.110

- Configure aws with Jenkins and Jenkins server
- Add access key and secret to Jenkins
- Now, create job- terraform demo
- Free style job
- Go to configure
- Build environment

Configure settings and variables that define the context in which your build runs, like credenti

☐ Delete workspace before build starts

☒ Use secret text(s) or file(s) ?

Bindings

≡ Username and password (separated) ?

Username Variable ?

AWS_ACCESS_KEY_ID

Password Variable ?

AWS_SECRET_ACCESS_KEY

Credentials ?

☒ Specific credentials ☐ Parameter expression

AKIAWBDMQNPZVLM7NRFU/*****

+ Add

-
- Select use secret test or file
- Add created aws-creds tro this
- Now ,
- Go to
- Build steps
- Select execute shell



Configure

- General
- Source Code Management
- Triggers
- Environment
- Build Steps**
- Post-build Actions

Automate your build process with ordered tasks like code compilation, testing

Execute shell ?

Command

[See the list of available environment variables](#)

```
cd /var/lib/jenkins/terraform-demo

export AWS_ACCESS_KEY_ID=${AWS_ACCESS_KEY_ID}
export AWS_SECRET_ACCESS_KEY=${AWS_SECRET_ACCESS_KEY}

terraform init
terraform plan
terraform apply -auto-approve
```

-
- `cd /var/lib/jenkins/terraform-demo`
-
- `export AWS_ACCESS_KEY_ID=${AWS_ACCESS_KEY_ID}`
- `export`
`AWS_SECRET_ACCESS_KEY=${AWS_SECRET_ACCESS_KEY}`
-
- `terraform init`
- `terraform plan`
- `terraform apply -auto-approve`
- now run the job

```
}
```

```
[1mPlan:[0m 1 to add, 0 to change, 0 to destroy.
[0m[0m[1maws_instance.example: Creating...[0m[0m
[0m[0m[1maws_instance.example: Still creating... [10s elapsed][0m[0m
[0m[0m[1maws_instance.example: Creation complete after 13s [id=i-00e87feb4d34a1bda][0m
[0m[0m[1m[32m
Apply complete! Resources: 1 added, 0 changed, 0 destroyed.
[0m[0mFinished: SUCCESS
```

-
- Instance launched successfully

Instance summary for i-00e87feb4d34a1bda (jenkins-terraform-demo) [Info](#)



Connect

Instance state ▼

Actions ▼

Updated less than a minute ago

Instance ID

i-00e87feb4d34a1bda

IPv6 address

—

Hostname type

IP name: ip-172-30-0-20.ec2.internal

Answer private resource DNS name

—

Auto-assigned IP address

100.27.231.102 [Public IP]

Public IPv4 address

100.27.231.102 | [open address](#)

Instance state

Running

Private IP DNS name (IPv4 only)

ip-172-30-0-20.ec2.internal

Instance type

t2.micro

VPC ID

vpc-07b5a830e8b806343