
MOTORS AND GENERATORS

Low Voltage

General Performance

IE2 high efficiency cast iron motors





ABB offers a comprehensive range of reliable and high efficiency motors. ABB's general performance IE2 efficiency motors are best suited for applications where simplicity and off-the-shelf availability are paramount.

General performance IE2 high efficiency cast iron motors Sizes 71 to 355

04 - 07	Technical data
08	Dimension drawings
09 - 11	General performance motors in brief



Technical data

IE2 high efficiency cast iron motors

Technical data for totally enclosed squirrel cage three phase induction motors

IP 55 - IC 411 - Insulation class F, temperature rise class B, IE2 efficiency class according to IEC 60034-30-1:2014, IS 12615:2018

2-Pole, TEFC, 415V, 50Hz, IP55, IC411, Ambt. 50 deg, Rise Class B (70 deg)

Output KW	Frame Size	Speed r/min	Efficiency			Power factor cos Ø	Current		Torque			Moment of inertia J=1/4GD² kgm²	Weight kg
			Full load 100%	3/4 load 75%	1/2 load 50%		I _n , A	I _s /I _n	T _n Nm	T _s /T _n	T _b /T _n		
3000 r/min = 2 poles			415V, 50Hz										
0.37	M2BAX 71MA 2	2760	72.2	72.9	70.3	0.79	0.90	5.0	1.3	2.0	2.4	0.00033	9
0.55	M2BAX 71MB 2	2785	74.8	75.5	73.0	0.79	1.30	5.0	1.9	2.2	2.7	0.00041	10
0.75	M2BAX 80MA 2	2820	77.4	78.0	75.7	0.79	1.70	6.0	2.5	2.3	2.8	0.00067	13
1.1	M2BAX 80MB 2	2840	79.6	80.0	77.9	0.77	2.5	6.0	3.7	2.5	3.0	0.00088	14
1.5	M2BAX 90SA 2	2875	81.3	82.0	80.3	0.83	3.1	6.0	5.0	2.3	3.0	0.00208	20
2.2	M2BAX 90LA 2	2878	83.2	84.0	82.6	0.84	4.4	7.0	7.3	2.5	3.1	0.00274	23
3.7	M2BAX 100LC 2	2890	85.5	85.8	84.3	0.87	6.9	7.0	12.2	3.0	3.8	0.00561	34
5.5	M2BAX 132SA 2	2915	87.0	87.8	86.7	0.84	10.5	7.0	18.0	2.0	3.4	0.01170	54
7.5	M2BAX 132SB 2	2910	88.1	89.0	88.7	0.86	13.8	7.0	24.6	2.1	3.5	0.01320	58
9.3	M2BAX160MLJ2	2925	88.8	89.1	87.6	0.87	16.7	7.0	30.3	2.1	3.0	0.038	102
11	M2BAX160MLA2	2925	89.4	89.7	88.2	0.88	19.6	7.0	35.9	2.4	3.0	0.0415	105
15	M2BAX160MLB2	2928	90.3	90.7	90.0	0.87	26.5	7.0	48.9	2.1	3.0	0.0544	120
18.5	M2BAX160MLC2	2928	90.9	91.2	90.4	0.87	32.4	7.0	60.3	2.3	3.0	0.0581	131
22	M2BAX180MLA2	2932	91.3	91.7	91.0	0.88	38.0	7.0	71.6	3	3.5	0.0679	152
30	M2BAX200MLA2	2935	92.0	92.4	91.5	0.88	51.5	7.0	97.6	2.2	3.2	0.1077	198
37	M2BAX200MLB2	2950	92.5	92.8	91.7	0.87	64.0	7.0	119.7	3	3.8	0.1332	232
45	M2BAX225SMA2	2960	92.9	92.6	92.0	0.88	77.0	7.0	145.1	2.2	3.0	0.2443	295
55	M2BAX250SMA2	2965	93.2	93.8	92.8	0.89	92.0	7.0	177.1	2.5	3.0	0.316	344
75	E2HX280SMB2	2970	93.8	93.8	92.8	0.92	121.0	7.0	241.0	2.3	2.7	1.025	690
90	E2HX280SMC2	2970	94.1	94.1	93.1	0.92	145.0	7.0	289.0	2.3	2.5	1.2	685
110	E2BA315SMA2	2980	94.3	94.3	93.3	0.90	180.0	7.0	353.0	2.4	2.7	1.41	935
125	E2BA315SMB2k	2980	94.5	94.5	93.5	0.90	204.0	7.0	401.0	2.4	2.7	1.61	975
132	E2BA315SMB2	2980	94.6	94.6	93.6	0.90	216.0	7.0	423.0	2.4	2.7	1.61	975
160	E2BA315MLA2	2980	94.8	94.8	93.8	0.90	261.0	7.0	513.0	2.3	3.0	1.95	1150
180	E2BA315MLC2K	2980	94.9	94.9	93.9	0.91	290.0	7.0	577.0	2.3	2.8	2.55	1275
200	E2BA315MLC2	2980	95.0	95.0	94.0	0.90	325.0	7.0	641.0	2.6	3.0	2.55	1275
250	E2BA355SMA2	2980	95.0	95.0	94.0	0.90	407.0	7.0	801.0	1.6	3.0	4.25	1570
315	E2BA355MLA2	2980	95.0	95.0	94.0	0.91	507.0	7.0	1009.0	1.7	3.0	5.75	1805
355	E2BA355MLC2	2982	95.0	95.0	94.0	0.90	578.0	7.0	1137.0	1.7	3.2	6.525	2000
375	E2BA355MLD2	2982	95.0	95.0	94.0	0.90	610.0	7.0	1201.0	1.6	3.1	6.525	2070

Efficiency values are measured according to IEC 60034-2-1; 2007, IS 15999(Part2 Sec1):2011
Please note that the values are not comparable without knowing the testing method. ABB has calculated the efficiency values according to indirect method, stray load losses (additional losses) determined from measuring.

I_s / I_n = Starting current
T_s / T_n = Locked rotor torque
T_b / T_n = Breakdown

Technical data

IE2 high efficiency cast iron motors

Technical data for totally enclosed squirrel cage three phase induction motors

IP 55 - IC 411 - Insulation class F, temperature rise class B, IE2 efficiency class according to IEC 60034-30-1:2014, IS 12615:2018

4-Pole, TEFC, 415V, 50Hz, IP55, IC411, Ambt. 50 deg, Rise Class B (70 deg)

Output KW	Frame Size	Speed r/min	Efficiency			Power factor cos Ø	Current		Torque		Moment of inertia J=1/4GD² kgm²	Weight kg	
			Full load 100%	3/4 load 75%	1/2 load 50%		I _n , A	I _s /I _n	T _n Nm	T _s /T _n			T _b /T _n
1500 r/min = 4 poles			415V, 50Hz										
0.37	M2BAX 71MB 4	1395	72.7	72.0	67.0	0.65	1.10	5.0	2.5	1.9	2.2	0.00076	10
0.55	M2BAX 80MA 4	1415	77.1	76.0	71.0	0.71	1.40	5.0	3.7	2.2	2.8	0.00156	15
0.75	M2BAX 80MB 4	1425	79.6	78.5	74.3	0.67	1.97	6.0	5.0	3	3.5	0.00247	17
1.1	M2BAX 90SA 4	1430	81.4	80.6	76.8	0.74	2.55	6.0	7.3	3	3.5	0.00372	21
1.5	M2BAX 90LA 4	1430	82.8	82.2	79.4	0.73	3.47	6.0	10.0	3.0	3.5	0.00462	23
2.2	M2BAX 100LA 4	1435	84.3	84.2	82.1	0.76	4.8	7.0	14.6	2.6	3.3	0.00759	31
3.7	M2BAX 112MA 4	1435	86.3	86.9	85.9	0.80	7.5	7.0	24.6	2.8	3.3	0.01200	41
5.5	M2BAX 132SA 4	1450	87.7	88.4	87.6	0.79	11.1	6.0	36.2	1.7	2.8	0.02570	57
7.5	M2BAX 132MA 4	1455	88.7	89.2	88.3	0.77	15.3	6.0	49.2	1.7	3.0	0.03200	68
9.3	M2BAX160MLJ4	1455	89.3	89.8	88.0	0.81	17.9	7.0	61.0	2.0	2.9	0.0738	107
11	M2BAX160MLA4	1455	89.8	90.4	89.4	0.81	21.0	7.0	72.2	2.1	2.9	0.084	115
15	M2BAX160MLB4	1463	90.6	91.2	90.2	0.84	27.6	7.0	97.9	2.5	3.0	0.1025	134
18.5	M2BAX180MLA4	1457	91.2	91.8	90.9	0.81	35.0	7.0	121.2	2.7	3.5	0.1217	155
22	M2BAX180MLB4	1460	91.6	92.1	91.2	0.80	42.0	7.0	143.8	2.4	3.2	0.1396	171
30	M2BAX200MLA4	1474	92.3	92.5	91.8	0.81	55.5	7.0	194.3	2.5	3.5	0.2572	229
37	M2BAX225SMA4	1475	92.7	93.1	92.2	0.84	66.5	6.5	239.4	2.1	2.7	0.3605	267
45	M2BAX225SMB4	1478	93.1	93.5	92.6	0.83	81.5	7.0	290.6	2.2	2.9	0.4314	304
55	M2BAX250SMA4	1478	93.5	93.7	92.9	0.85	96.8	7.0	355.2	2.7	3.0	0.5331	342
75	E2HX280SMB4	1478	94.0	94.0	93.0	0.87	128.0	7.0	485.0	2.4	2.7	1.11	670
90	E2HX280SMC4	1479	94.2	94.2	93.2	0.85	156.0	7.0	581.0	2.6	2.8	1.425	730
110	E2BA315SMA4	1486	94.5	94.5	93.5	0.88	184.0	7.0	707.0	2.3	2.8	2.387	930
125	E2BA315SMB4k	1486	94.6	94.6	93.6	0.86	214.0	7.0	803.0	2.0	2.7	2.65	960
132	E2BA315SMB4	1486	94.7	94.7	93.7	0.86	225.0	7.0	848.0	2.3	2.7	2.65	960
160	E2BA315MLA4	1485	94.9	94.9	93.9	0.87	270.0	7.0	1029.0	2.3	2.6	3.375	1110
180	E2BA315MLB4	1485	95.0	95.0	94.0	0.87	303.0	7.0	1157.0	2.2	2.7	3.9	1150
200	E2BA315MLC4	1485	95.1	95.1	94.1	0.88	332.0	7.0	1286.0	2.4	2.8	4.25	1260
225	E2BA355SMA4K	1486	95.1	95.1	94.1	0.86	383.0	7.0	1446.0	2.1	2.7	6.084	1570
250	E2BA355SMA4	1486	95.1	95.1	94.1	0.87	420.0	7.0	1607.0	2.0	2.5	6.085	1570
315	E2BA355MLA4	1486	95.1	95.1	94.1	0.87	530.0	7.0	2024.0	2.5	3.0	8.25	1870
355	E2BA355MLB4	1486	95.1	95.1	94.1	0.87	597.0	7.0	2281.0	2.2	3.0	10	2110
400	E2BA355MLB4H	1486	95.1	95.1	94.1	0.86	680.0	7.0	2570.0	2.3	2.8	11.065	2430

Efficiency values are measured according to IEC 60034-2-1; 2007, IS 15999(Part2 Sec1):2011
Please note that the values are not comparable without knowing the testing method. ABB has calculated the efficiency values according to indirect method, stray load losses (additional losses) determined from measuring.

I_s / I_n = Starting current
T_s / T_n = Locked rotor torque
T_b / T_n = Breakdown

Technical data

IE2 high efficiency cast iron motors

Technical data for totally enclosed squirrel cage three phase induction motors

IP 55 - IC 411 - Insulation class F, temperature rise class B, IE2 efficiency class according to IEC 60034-30-1:2014, IS 12615:2018

6-Pole, TEFC, 415V, 50Hz, IP55, IC411, Ambt. 50 deg, Rise Class B (70 deg)

Output KW	Frame Size	Speed r/min	Efficiency			Power factor cos Ø	Current		Torque			Moment of inertia J=1/4GD² kgm²	Weight kg
			Full load 100%	3/4 load 75%	1/2 load 50%		I _n , A	I _s /I _n	T _n Nm	T _s /T _n	T _b /T _n		
1000 r/min = 6 poles			415V, 50Hz										
0.37	M2BAX 80MA 6	910	69.0	68.1	63.1	0.62	1.20	4.0	3.9	2	2.4	0.00173	13
0.55	M2BAX 80MB 6	910	73.1	72.8	69.2	0.66	1.60	4.0	5.8	2.1	2.5	0.00274	15
0.75	M2BAX 90SA 6	945	75.9	74.3	69.2	0.62	2.2	4.5	7.6	2.4	3.2	0.00438	21
1.1	M2BAX 90LA 6	935	78.1	77.3	73.3	0.63	3.1	4.5	11.2	2.3	2.9	0.00507	24
1.5	M2BAX 100LA 6	945	79.8	79.7	77.0	0.67	3.9	4.5	15.2	1.8	2.3	0.00795	31
2.2	M2BAX 112MA 6	950	81.8	81.7	79.0	0.68	5.5	5.0	22.1	1.8	2.6	0.01160	40
3.7	M2BAX 132SB 6	960	84.3	84.7	83.4	0.71	8.6	5.0	36.8	1.5	2.3	0.02830	60
5.5	M2BAX 132MB 6	965	86.0	86.0	84.2	0.70	12.7	5.0	54.4	1.5	2.8	0.03970	77
7.5	M2BAX160MLA6	957	87.2	88.0	86.8	0.77	15.6	6.5	74.8	1.7	2.6	0.089	122
9.3	M2BAX160MLJ6	965	88.0	88.6	87.8	0.77	19.1	6.5	92.0	2.0	2.8	0.119	141
11	M2BAX160MLB6	965	88.7	89.2	88.5	0.75	23.0	7.0	108.8	2.1	2.8	0.1293	147
15	M2BAX180MLA6	970	89.7	90.1	89.4	0.76	30.5	7.0	147.6	2.0	3.0	0.1522	173
18.5	M2BAX200MLA6	965	90.4	90.8	90.0	0.77	37.0	6.0	183.0	1.5	2.5	0.198	190
22	M2BAX200MLB6	970	90.9	91.2	90.6	0.77	43.7	6.0	216.5	1.5	2.5	0.2384	212
30	M2BAX225SMA6	981	91.7	92.0	91.2	0.82	55.8	6.5	291.9	2.1	2.8	0.5687	284
37	M2BAX250SMA6	981	92.2	92.4	91.9	0.81	68.9	6.0	360.0	2.0	2.6	0.8042	337
45	E2HX280SMA6	988	92.7	92.7	90.7	0.84	80.0	7.0	435.0	2.2	2.4	1.8	590
55	E2HX280SMB6	988	93.1	93.1	91.1	0.84	98.0	7.0	532.0	2.2	2.4	2.025	600
75	E2BA315SMA6	989	93.7	93.7	91.7	0.85	131.0	7.0	724.0	2.4	2.7	3.887	932
90	E2BA315SMB6	990	94.0	94.0	92.0	0.85	157.0	7.0	868.0	2.4	2.8	4.8	1005
110	E2BA315SMC6	990	94.3	94.3	92.3	0.85	191.0	7.0	1061.0	2.5	3.0	5.45	1072
125	E2BA315MLC6k	990	94.4	94.4	92.4	0.86	214.0	7.0	1206.0	2.5	3.0	7.05	1305
132	E2BA315MLC6	988	94.6	94.6	92.6	0.86	226.0	7.0	1276.0	2.3	2.6	7.05	1305
160	E2BA355SMA6	989	94.8	94.8	92.8	0.85	276.0	7.0	1545.0	2.0	2.7	9.8	1675
200	E2BA355SMB6	990	95.0	95.0	93.0	0.84	349.0	7.0	1929.0	2.5	2.8	11.68	1720
250	E2BA355MLA6	988	95.0	95.0	93.0	0.85	431.0	7.0	2416.0	2.3	2.7	13.75	1940
275	E2BA355MLB6K	990	95.0	95.0	93.0	0.82	491.0	7.0	2653.0	2.5	2.8	15.06	2040
315	E2BA355MLB6	990	95.0	95.0	93.0	0.84	549.0	7.0	3039.0	2.5	2.8	15.06	2040
355	E2BA355MLB6H**	990	95.0	95.0	93.0	0.84	619.0	7.0	3424.0	1.3	2.7	15.975	2250

** Temp. Rise Class F

Efficiency values are measured according to IEC 60034-2-1; 2007, IS 15999(Part2 Sec1):2011
Please note that the values are not comparable without knowing the testing method. ABB has
calculated the efficiency values according to indirect method, stray load losses (additional losses)
determined from measuring.

I_s / I_n = Starting current
T_s / T_n = Locked rotor torque
T_b / T_n = Breakdown

Technical data

IE2 high efficiency cast iron motors

Technical data for totally enclosed squirrel cage three phase induction motors

IP 55 - IC 411 - Insulation class F, temperature rise class B, IE2 efficiency class according to IEC 60034-30-1:2014, IS 12615:2018

8-Pole, TEFC, 415V, 50Hz, IP55, IC411, Ambt. 50 deg, Rise Class B (70 deg)

Output KW	Frame Size	Speed r/min	Efficiency			Power factor cos Ø	Current		Torque			Moment of inertia J=1/4GD² kgm²	Weight kg
			Full load 100%	3/4 load 75%	1/2 load 50%		I _n , A	I _s /I _n	T _n Nm	T _s /T _n	T _b /T _n		
750 r/min = 8 poles			415V, 50Hz										
0.12	M2BAX71MB8	680	39.8	34	24.9	0.60	0.70	3.0	1.7	2.6	2.7	0.0011	11
0.18	M2BAX80MA8	700	45.9	40.7	29.8	0.61	0.90	3.0	2.5	2.5	2.8	0.0019	15
0.25	M2BAX80MB8	690	50.6	46.8	38.2	0.62	1.10	3.0	3.5	2.3	2.4	0.0024	16
0.37	M2BAX90SA8	690	56.1	53	43.9	0.61	1.5	3.0	5.1	2.0	2.4	0.0044	22
0.55	M2BAX90LA8	680	61.7	61.1	55.8	0.62	2.0	3.0	7.7	1.7	1.9	0.0049	24
0.75	M2BAX100LA8	700	66.2	62.1	54.1	0.61	2.6	4.0	10.2	2.3	2.7	0.0072	30
1.1	M2BAX100LB8	695	70.8	70.6	66.2	0.64	3.4	4.0	15.1	2.0	2.2	0.0087	32
1.5	M2BAX112MA8	680	74.1	74.1	72.8	0.70	4.0	4.0	21.1	1.7	2	0.0118	40
2.2	M2BAX132SA8	710	77.6	76.2	72	0.65	6.1	4.5	29.6	1.5	2.3	0.0334	69
3.7	M2BAX160MLA8	715	81.4	81.4	80.4	0.64	9.8	5.0	49.4	1.5	2.3	0.0590	100
5.5	M2BAX160MLB8	720	83.8	83.8	82.8	0.66	13.8	5.0	73.0	1.5	2.3	0.0940	127
7.5	M2BAX160MLC8	720	85.3	85.3	83.3	0.64	19.0	5.0	99.5	1.5	2.3	0.1170	143
9.3	M2BAX180MLA8	720	86.3	86.3	83.6	0.61	24.6	5.0	123.4	1.7	2.6	0.1470	166
11	M2BAX180MLB8	720	86.9	86.9	84.5	0.68	26.0	5.0	145.9	1.5	2.2	0.2020	200
15	M2BAX200MLA8	725	88	88	85.8	0.68	35.0	5.0	197.6	1.4	2.1	0.2720	235
18.5	M2BAX225SMA8	735	88.6	88.6	87.6	0.73	40.0	5.0	240.4	2.1	2.3	0.4950	254
22	M2BAX225SMB8	735	89.1	89.1	88.1	0.75	45.7	5.0	285.9	1.9	2.2	0.5870	286
30	M2BAX250SMA8	735	89.8	89.8	88.8	0.74	62.8	5.0	389.8	1.9	2.2	0.8620	348
37	E2HX280SMB8	740	90.3	90.3	88.7	0.76	75.0	7.0	478.0	2.1	2.3	1.9100	590
45	E2HX280SMC8	740	90.7	90.7	88.7	0.76	90.8	7.0	581.0	2.1	2.3	1.9350	600
55	E2BA315SMA8	740	91	91	89	0.81	103.8	7.0	710.0	2.1	2.8	3.2500	830
75	E2BA315SMB8	740	91.6	91.6	89.6	0.82	138.9	7.0	968.0	2	2.7	4.7000	975
90	E2BA315SMC8	740	91.9	91.9	89.9	0.82	166.2	7.0	1161.0	2.2	2.8	5.5000	1055
110	E2BA315MLC8	740	92.3	92.3	90.3	0.82	202.2	7.0	1420.0	2.1	2.8	5.9000	1125
132	E2BA355SMA8	740	92.6	92.6	90.6	0.81	244.8	7.0	1704.0	2.1	2.3	10.5000	1590
150	E2BA355MLA8k	740	92.8	92.8	90.8	0.80	280.8	7.0	1936.0	2.1	2.7	13.7500	1945
160	E2BA355MLA8	740	93	93	91	0.80	299.2	7.0	2064.0	2	2.5	13.7500	1945
180	E2BA355MLB8I	740	93.3	93.3	91.3	0.74	363.1	7.0	2323.0	2	2.7	16.0500	2090
200	E2BA355MLB8	740	93.5	93.5	91.5	0.76	391.6	7.0	2581.0	1.7	2.6	16.0500	2090
225	E2BA355MLB8H	740	93.5	93.5	91.5	0.77	434.8	7.0	2904.0	1.7	2.6	16.0500	2100
250	E2BA355MLB8k**	740	93.5	93.5	91.5	0.81	460.0	7.0	3226.0	1.6	2.6	16.5000	2225

** Temp. Rise Class F


Efficiency values are measured according to IEC 60034-2-1; 2007, IS 15999(Part2 Sec1):2011
Please note that the values are not comparable without knowing the testing method. ABB has
calculated the efficiency values according to indirect method, stray load losses (additional losses)
determined from measuring.

I_s / I_n = Starting current
T_s / T_n = Locked rotor torque
T_b / T_n = Breakdown


Dimension drawings

General performance IE2 high efficiency cast iron motors Sizes 71 - 355

Foot-mounted motor IM1001, B3



Flange-mounted motor IM 3001, B5



Motor Size	D Poles		GA Poles		F Poles		E Poles		L max Poles		A	B	B'	C	HD	K	H	M	N	P	S	T
	2	4-8	2	4-8	2	4-8	2	4-8	2	4-8												
General performance cast iron motors																						
71M	14	14	16	16	5	5	30	30	257	257	112	90	-	45	175	7	71	130	110	160	10	3.5
80M	19	19	21.5	21.5	6	6	40	40	309	309	125	100	-	50	192	10	80	165	130	200	12	3.5
90SL	24	24	27	27	8	8	50	50	351	351 ⁵⁾	140	100	125	56	217	10	90	165	130	200	12	3.5
100L	28	28	31	31	8	8	60	60	376	376	160	140	-	63	240	12	100	215	180	250	15	4
112M	28	28	31	31	8	8	60	60	411	411	190	140	-	70	252	12	112	215	180	250	15	4
132SM	38	38	41	41	10	10	80	80	521	521 ⁶⁾	216	140	178	89	301	12	132	265	230	300	15	4
160	42	42	45	45	12	12	110	110	586	586 ^{1), 1)}	254	210	254	108	414	15	160	300	250	350	19	5
180	48	48	51.5	51.5	14	14	110	110	684	684 ²⁾	279	241	279	121	434	15	180	300	250	350	19	5
200	55	55	59	59	16	16	110	110	728	728 ³⁾	318	267	305	133	474	19	200	350	300	400	19	5
225	55	60	59	64	16	18	110	140	854	854 ⁴⁾	356	286	311	149	540	19	225	400	350	450	19	5
250	60	65	64	69	18	18	140	140	882	882	406	311	349	168	585	24	250	500	450	550	19	5
280	65	75	69	80	18	20	140	140	1040	1040	457	368	419	190	728	24	280	500	450	550	19	5
315SM	65	80	69	85	18	22	140	170	1169	1199	508	406	457	216	872	28	315	600	550	660	24	6
315ML	65	90	69	95	18	25	140	170	1215	1245	508	457	508	216	872	28	315	600	550	660	24	6
355SM	75	100	80	106	20	28	140	210	1399	1469	610	500	560	254	965	28	355	740	680	800	24	6
355ML	75	100	80	106	20	28	140	210	1504	1574	610	560	630	254	965	28	355	740	680	800	24	6
Motor	D		GA		F		E		L Max		A	B	B'	C	HD	K	H	M	N	P	S	T
355MLB4	100		106		28		210		1680		610	560	630	254	965	28	355	740	680	800	24	6
355MLC2	75		79.5		20		140		1610		610	560	630	254	965	28	355	740	680	800	24	6
355MLB8K	100		106		28		210		1680		610	560	630	254	965	28	355	740	680	800	24	6
355MLB4H	100		106		28		210		1680		610	560	630	254	995	28	355	740	680	800	24	6
355MLD2	75		79.5		20		140		1610		610	560	630	254	995	28	355	740	680	800	24	6
355MLB6H	100		106		28		210		1680		610	560	630	254	995	28	355	740	680	800	24	6

Above table gives the main dimensions in mm.

- 1) M2BAX160MLC2, B4, J6 L = 626
 1') M2BAX160MLB6 L = 646
 2) M2BAX180MLB4, A6 L = 704
 3) M2BAX200MLB2, A4, B6 L = 768
 4) M2BAX225SMB4, A6 L = 884
 5) M2BAX90SA2, SA4, SA6 L = 335
 6) M2BAX132SA2, B2, SA4, SB6 L = 479

General performance IE2 high efficiency cast iron motors in brief

Size		71	80	90	100	112	132
Stator	Material	Cast Iron Grade 150:ISO 185					
	Paint colour shade	Munsell blue 8B 4.5/3.25 / NCS 4822 B05G					
	Surface Treatment	C3 medium according to ISO / EN 12944-5					
Feet	Integrated with stator						
	Material	Cast iron grade 150 : ISO 185					
Bearing end shields	Material	Cast iron grade 150 : ISO 185					
	Paint colour shade	Munsell blue 8B 4.5/3.25/NCS 4822 B05G					
	Surface Treatment	C3 medium according to ISO / EN 12944-5					
Bearings	D-end	6203-2Z/C3	6204-2Z/C3	6205-2Z/C3	6206-2Z/C3	6206-2Z/C3	6208-2Z/C3
	N-end	6202-2Z/C3	6203-2Z/C3	6204-2Z/C3	6205-2Z/C3	6205-2Z/C3	6208-2Z/C3
Axially-locked	Retaining Ring	As standard, locked at D-end					
Bearing seals		Axial seal as standard, radial on request					
Lubrication		Permanently lubricated shielded bearings					
Rating plate	Material	Aluminium					
Terminal Box	Frame material	Cast Iron, Integral to stator frame					
	Cover material	Sheet of steel, Cold rolled					
	Cover screws material	Steel 8.8					
Connections	Cable entries	2xM16	2xM25		2xM32		
	Cable Sizes	2Rx3Cx4mm2	2Rx3Cx6mm2		2Rx3Cx10mm2		
	Terminal Stud Size	M4	M4		M5		
	Terminals	6 terminals for connection, cable lugs (not included)					
Fan	Material	Polypropylene, Reinforced with 20% glass fibre					
Fan Cover	Material	Sheet of steel, cold rolled					
	Paint Colour shade	Munsell blue 8B 4.5/3.25/NCS 4822 B05G					
	Surface Treatment	C3 medium according to ISO/EN 12944-5					
Stator winding	Material	Copper					
	Insulation	Insulation class F, Temperature rise class B unless otherwise stated					
	Winding protection	-					
Rotor winding	Material	Pressure diecast aluminum					
Balancing method		Half Key Balancing as Standard					
Key ways		Open Key Way					
Enclosure		IP 55, Higher protection on request					
Cooling method		IC 411					
Drain holes		Drain holes with closable plastic plugs, open on delivery					
Lifting lugs		Integrated with the stator					

Motors in brief

General performance IE2 high efficiency cast iron motors

Size		160	180	200	225	250
Stator	Material	Cast iron grade 200 : ISO 185				
	Paint colour shade	Munsell blue 8B 4.5/3.25 / NCS 4822 B05G				
	Surface Treatment	C3 medium according to ISO / EN 12944-5				
Feet		Integrated with stator				
	Material	Cast iron grade 200 : ISO 185				
Bearing end shields	Material	Cast iron grade 200 : ISO 185				
	Paint colour shade	Munsell blue 8B 4.5/3.25 / NCS 4822 B05G				
	Surface Treatment	Aliphatic polyurethane enamel paint_70µm				
Bearings	D-end	6209-2Z/C3	6310-2Z/C3	6312-2Z/C3	6313-2Z/C3	6315-2Z/C3
	N-end	6209-2Z/C3	6209-2Z/C3	6209-2Z/C3	6210-2Z/C3	6212-2Z/C3
Axially-locked	Inner Bearing Cover	As standard, locked at D-end				
Bearing seals	D-end	V-ring				
	N-end	V-ring				
Lubrication		Permanently lubricated shielded bearings				
Terminal Box	Material	Sheet of Steel, Cold Rolled				
	Surface	Treatment Similar to stator				
	Screws	Steel 8.8				
Connections	Cable Entries	2xM40, 1xM16			2xM50, 1xM16	
	Cable Sizes	2Rx3Cx70mm2			2Rx3Cx120mm2	
	Terminal Stud Size	M6			M10	
	Terminal Box	6 terminals for connection, cable lugs (not included)				
Fan	Material	Polypropylene, Reinforced with 20% glass fibre				
Fan Cover	Material	Sheet of Steel, Cold Rolled				
	Paint colour shade	Munsell blue 8B 4.5/3.25 / NCS 4822 B05G				
	Surface Treatment	Similar to stator				
Stator winding	Material	Copper				
	Insulation	Insulation class F				
Rotor winding	Material	Diecast aluminum				
Balancing method		Half Key Balancing as standarad				
Key ways		Open Key Way				
Enclosure		IP 55				
Cooling method		IC 411				
Drain holes		Drain holes with closable plastic plugs, open on delivery				
Lifting lugs		Integrated with the stator				

Motors in brief

General performance IE2 high efficiency cast iron motors

Size		280 2-8 Pole	315 2 Pole	315 4-8 Pole	355 2 Pole	355 4-8 Pole
Stator	Material	Cast iron grade 150, IS:210				
	Paint colour shade	Munsell blue 8B 4.5/3.25 / NCS 4822 B05G				
	Surface Treatment	C3 medium according to ISO / EN 12944-5				
Feet		Integrated with stator				
	Material	Cast iron grade 150, IS:210				
Bearing end shields	Material	Cast iron grade 150, IS:210				
	Paint colour shade	Munsell blue 8B 4.5/3.25 / NCS 4822 B05G				
	Surface Treatment	Aliphatic polyurethane paint ≥ 80µm				
Bearings	D-end	6316/C3	6316/C3	6319/C3	6319/C3	6322/C3
	N-end	6315/C3	6316/C3	6316/C3	6319/C3	6319/C3
Axially-locked	Inner Bearing Cover	As standard, locked at D-end				
Bearing seals	D-end	Oil Seal				
	N-end					
Lubrication		Regreasable Bearings, Regreasing nipple M10X1				
Terminal Box	Material	Cast iron grade 150, IS:210				
	Surface	Similar to stator				
	Screws	Steel				
Connections	Cable Entries	2 x 2” BSC		2 x 2-1/2” BSC*		
	Cable Sizes	280 : 2Rx3Cx185Sqmm Cu/Al Cable 315 : 2Rx3Cx240Sqmm Cu/Al Cable 355 : 2Rx3Cx240Sqmm Cu/Al Cable*				
	Terminal Stud Size	M12		M16		
	Terminal Box	6 terminals for connection, cable lugs (not included)				
	Fan	Material	Polypropylene, Reinforced with 20% glass fibre			Aluminium
Fan Cover	Material	Sheet of steel, Cold Rolled				
	Paint colour shade	Munsell blue 8B 4.5/3.25 / NCS 4822 B05G				
	Surface Treatment	Similar to stator				
	Stator winding	Material	Copper			
Insulation		Insulation class F				
Rotor winding	Material	Diecast aluminum				
Balancing method		Half Key Balancing as standarad				
Key ways		Open Key Way				
Enclosure		IP 55				
Cooling method		IC 411				
Drain holes		Drain holes with closable plastic plugs, open on delivery				
Lifting lugs		Bolted to the Stator				

*Cable Size for 355MLC2,355MLD2,355MLB4, 355MLB6H & 355MLB4H will be 2Rx3Cx300 Sqmm Cu/Al , Threaded opening 2x3" BSC

ABB India Limited

32, Industrial Area,
N.I.T., Faridabad - 121 001
Tel: +91 129 2448100
Helpline No. : 1800 425 0707

www.abb.co.in

We reserve the right to make technical changes or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. ABB does not accept any responsibility whatsoever for potential errors or possible lack of information in this document.

We reserve all rights in this document and in the subject matter and illustrations contained therein. Any reproduction, disclosure to third parties or utilization of its content - in whole or in parts - is forbidden without ABB's prior written consent.