

Project Executable Files

Date: 15 March 2026 **Team ID:** 6ab4ccd16f290be8a6b460f4 **Project Name:** aiblognest

Maximum Marks: 3 Marks

This section documents the executable/deployable project materials available for the AI BlogNest API and provides evaluator run instructions.

Step 1: Submission Checklist

S.No	Item to Submit	Status	Evidence / Notes
1	Complete source code (all files and folders)	Partial	Backend project documentation is available, but a complete source-code folder was not supplied with the submission.
2	README / Setup Guide	Yes	README.md is supplied with setup, environment, endpoints, and testing instructions.
3	requirements.txt / package.json / dependency file	Yes	package.json and package-lock.json are supplied.
4	Database schema / seed files (if applicable)	Partial	MongoDB/Mongoose is documented, but separate schema/seed submission was not supplied in the submission.
5	Environment configuration file (.env.example or similar)	Partial	Environment variables are documented; an actual .env exists in the working files. A safe .env.example file was not supplied.
6	Deployed application URL (if hosted)	No	No deployed URL was supplied.
7	APK / Executable binary (if applicable)	NA	Not applicable to this Node.js REST API project.
8	Dockerfile / Containerization config (if applicable)	NA	No Docker configuration was supplied; not required by the documented local setup.
9	Test files and test results	Partial	Postman/Thunder Client collection is supplied; executed performance-test results were not supplied.
10	Demo video or walkthrough (if required)	Not supplied	No demo video link was supplied.

Step 2: File / Folder Structure

Path / File	Purpose
package.json	Node.js project metadata, scripts, and dependencies.
package-lock.json	Locked npm dependency versions.
README.md	Project description, setup instructions, environment variables, API endpoints, and testing guidance.
src/	Documented application source directory following MVC architecture.
src/server.js	Documented server entry point referenced by npm start/npm run dev.
Postman / Thunder Client collection	API request collection covering authentication, blog CRUD, AI generation, and summarization.
thunder-client-env.json	API testing variables including base_url, token, and blogId.
.env / .env.example	Environment configuration for PORT, MONGO_URI, JWT_SECRET, GEMINI_API_KEY, and GEMINI_MODEL.

Note: The reviewed project materials document an MVC architecture and the server entry point, but the complete src folder was not included in the supplied file set.

Step 3: Deployment / Access Details

Field	Details
Hosted / Deployed URL	Not supplied. The documented environment is local development.
Login Credentials (Demo)	Not supplied. Do not place real credentials in this document.
Platform / Hosting Provider	Local Node.js / Express development environment documented. No external hosting provider supplied.
Repository Link	Not supplied.
Demo Video Link	Not supplied.

Step 4: Run Instructions

1. Install Node.js and npm.
2. Open the project folder in a terminal.
3. Copy the environment template to .env and provide valid MongoDB, JWT, and Gemini configuration values.
4. Run **npm install** to install dependencies.
5. Run **npm run dev** for development or **npm start** to start the server.
6. The documented local API uses port 5000 unless PORT is changed.
7. Use the supplied Postman/Thunder Client collection to test registration, login, profile, blog CRUD, AI blog generation, and summarization.
8. For protected requests, authenticate first and use the returned JWT token in the authorization configuration.

Step 5: Known Issues / Limitations

1	Complete source-code folder not supplied in submission	Submit the full submission tree so the evaluator can run the project directly	Open
2	No deployed URL or repository link supplied.	Add the live URL and repository link if available.	Open
3	No executed performance metrics/screenshots supplied	Run performance tests and attach measured response time, throughput, error rate, CPU, and memory res	Open

Submission safety: Do not upload the real .env file containing API keys or secrets. Submit a sanitized .env.example instead.