HTML - index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
<meta charset="UTF-8">
<meta name="viewport" content="width=device-width, initial-scale=1">
<title>College Event Registration Portal</title>
<link rel="stylesheet" href="style.css">
</head>
<body>
<header class="navbar">
  <h1>College Event Registration Portal</h1>
  <nav>
    <button id="tabEvents" class="tab active">Upcoming Events</button>
    <button id="tabMine" class="tab">My Registrations</button>
  </nav>
</header>

<section id="eventsView">
  <div class="filters">
    <input type="text" id="searchInput" placeholder="Search events by name...">
    <select id="categoryFilter"><option value="all">All Categories</option></select>
    <input type="date" id="dateFilter">
    <button id="clearBtn" class="btn-light">Clear</button>
  </div>
  <div id="eventList" class="grid"></div>
</section>

<section id="mineView" class="hidden">
  <div id="myList" class="grid"></div>
</section>

<div id="regModal" class="modal hidden">
  <div class="modal-box">
    <div class="field"><label>Full Name *</label>
      <input id="fName" type="text"><small class="err" id="eName"></small></div>
    <div class="field"><label>Email *</label>
      <input id="fEmail" type="text"><small class="err" id="eEmail"></small></div>
    <!-- Register Number and Department fields follow the same pattern -->
    <div class="field"><label>Register Number *</label>
      <input id="fReg" type="text"><small class="err" id="eReg"></small></div>
    <div class="field"><label>Department *</label>
      <input id="fDept" type="text"><small class="err" id="eDept"></small></div>
    <button id="submitReg" class="btn-primary">Submit Registration</button>
    <button id="cancelModal" class="btn-light">Cancel</button>
  </div>
</div>

<div id="toast" class="toast hidden"></div>
<script src="script.js"></script>
</body>
</html>
```