

Sort a linked list of 0s, 1s and 2s

Given a linked list of 0s, 1s and 2s, sort it.

Source: [Microsoft Interview | Set 1](#)

We strongly recommend that you click here and practice it, before moving on to the solution.

Following steps can be used to sort the given linked list.

- 1) Traverse the list and count the number of 0s, 1s and 2s. Let the counts be n1, n2 and n3 respectively.
- 2) Traverse the list again, fill the first n1 nodes with 0, then n2 nodes with 1 and finally n3 nodes with 2.

C/C++

```
// C Program to sort a linked list 0s, 1s or 2s
#include<stdio.h>
#include<stdlib.h>

/* Link list node */
struct node
{
    int data;
    struct node* next;
};

// Function to sort a linked list of 0s, 1s and 2s
void sortList(struct node *head)
{
    int count[3] = {0, 0, 0}; // Initialize count of '0', '1' and '2' as 0
    struct node *ptr = head;

    /* count total number of '0', '1' and '2'
    * count[0] will store total number of '0's
    * count[1] will store total number of '1's
    * count[2] will store total number of '2's */
    while (ptr != NULL)
    {
        count[ptr->data] += 1;
        ptr = ptr->next;
    }

    int i = 0;
    ptr = head;

    /* Let say count[0] = n1, count[1] = n2 and count[2] = n3
    * now start traversing list from head node,
    * 1) fill the list with 0, till n1 > 0
    * 2) fill the list with 1, till n2 > 0
    * 3) fill the list with 2, till n3 > 0 */
    while (ptr != NULL)
    {
        if (count[i] == 0)
            ++i;
        else
        {
            ptr->data = i;
            --count[i];
            ptr = ptr->next;
        }
    }
}
```

```

        }
    }
}

/* Function to push a node */
void push (struct node** head_ref, int new_data)
{
    /* allocate node */
    struct node* new_node =
        (struct node*) malloc(sizeof(struct node));

    /* put in the data */
    new_node->data = new_data;

    /* link the old list off the new node */
    new_node->next = (*head_ref);

    /* move the head to point to the new node */
    (*head_ref) = new_node;
}

/* Function to print linked list */
void printList(struct node *node)
{
    while (node != NULL)
    {
        printf("%d ", node->data);
        node = node->next;
    }
    printf("\n");
}

/* Driver program to test above function*/
int main(void)
{
    struct node *head = NULL;
    push(&head, 0);
    push(&head, 1);
    push(&head, 0);
    push(&head, 2);
    push(&head, 1);
    push(&head, 1);
    push(&head, 2);
    push(&head, 1);
    push(&head, 2);

    printf("Linked List Before Sorting\n");
    printList(head);

    sortList(head);

    printf("Linked List After Sorting\n");
    printList(head);

    return 0;
}

```

Java

```

// Java program to sort a linked list of 0, 1 and 2
class LinkedList
{
    Node head; // head of list

    /* Linked list Node*/
    class Node
    {
        int data;
        Node next;
        Node(int d) {data = d; next = null; }
    }
}

```

```

}

void sortList()
{
    // initialise count of 0 1 and 2 as 0
    int count[] = {0, 0, 0};

    Node ptr = head;

    /* count total number of '0', '1' and '2'
    * count[0] will store total number of '0's
    * count[1] will store total number of '1's
    * count[2] will store total number of '2's */
    while (ptr != null)
    {
        count[ptr.data]++;
        ptr = ptr.next;
    }

    int i = 0;
    ptr = head;

    /* Let say count[0] = n1, count[1] = n2 and count[2] = n3
    * now start traversing list from head node,
    * 1) fill the list with 0, till n1 > 0
    * 2) fill the list with 1, till n2 > 0
    * 3) fill the list with 2, till n3 > 0 */
    while (ptr != null)
    {
        if (count[i] == 0)
            i++;
        else
        {
            ptr.data = i;
            --count[i];
            ptr = ptr.next;
        }
    }
}

/* Utility functions */

/* Inserts a new Node at front of the list. */
public void push(int new_data)
{
    /* 1 & 2: Allocate the Node &
    Put in the data*/
    Node new_node = new Node(new_data);

    /* 3. Make next of new Node as head */
    new_node.next = head;

    /* 4. Move the head to point to new Node */
    head = new_node;
}

/* Function to print linked list */
void printList()
{
    Node temp = head;
    while (temp != null)
    {
        System.out.print(temp.data+" ");
        temp = temp.next;
    }
    System.out.println();
}

/* Drier program to test above functions */
public static void main(String args[])
{
    linkedList list = new linkedList();

```

```

LinkedList llist = new LinkedList();

/* Constructed Linked List is 1->2->3->4->5->6->7->
8->8->9->null */
llist.push(0);
llist.push(1);
llist.push(0);
llist.push(2);
llist.push(1);
llist.push(1);
llist.push(2);
llist.push(1);
llist.push(2);

System.out.println("Linked List before sorting");
llist.printList();

llist.sortList();

System.out.println("Linked List after sorting");
llist.printList();
}
}
/* This code is contributed by Rajat Mishra */

```

Python

```

# Python program to sort a linked list of 0, 1 and 2
class LinkedList(object):
    def __init__(self):

        # head of list
        self.head = None

# Linked list Node
class Node(object):
    def __init__(self, d):
        self.data = d
        self.next = None

def sortList(self):

    # initialise count of 0 1 and 2 as 0
    count = [0, 0, 0]

    ptr = self.head

    # count total number of '0', '1' and '2'
    # * count[0] will store total number of '0's
    # * count[1] will store total number of '1's
    # * count[2] will store total number of '2's
    while ptr != None:
        count[ptr.data] += 1
        ptr = ptr.next

    i = 0
    ptr = self.head

    # Let say count[0] = n1, count[1] = n2 and count[2] = n3
    # * now start traversing list from head node,
    # * 1) fill the list with 0, till n1 > 0
    # * 2) fill the list with 1, till n2 > 0
    # * 3) fill the list with 2, till n3 > 0
    while ptr != None:
        if count[i] == 0:
            i += 1
        else:
            ptr.data = i
            count[i] -= 1
            ptr = ptr.next

```

```

# Utility functions
# Inserts a new Node at front of the list.
def push(self, new_data):

    # 1 & 2: Allocate the Node &
    # Put in the data
    new_node = self.Node(new_data)

    # 3. Make next of new Node as head
    new_node.next = self.head

    # 4. Move the head to point to new Node
    self.head = new_node

# Function to print linked list
def printList(self):
    temp = self.head
    while temp != None:
        print str(temp.data),
        temp = temp.next
    print ''

# Driver program to test above functions
l1 = LinkedList()
l1.push(0)
l1.push(1)
l1.push(0)
l1.push(2)
l1.push(1)
l1.push(1)
l1.push(2)
l1.push(1)
l1.push(2)

print "Linked List before sorting"
l1.printList()

l1.sortList()

print "Linked List after sorting"
l1.printList()

# This code is contributed by BHAVYA JAIN

```

Output:

```

Linked List Before Sorting
2 1 2 1 1 2 0 1 0
Linked List After Sorting
0 0 1 1 1 1 2 2 2

```

Time Complexity: $O(n)$ where n is number of nodes in linked list.

Auxiliary Space: $O(1)$