

NovaBrew Coffee Machine - User Manual

NovaBrew Coffee Machine Model NB-200 User Manual.

Setup: Remove all packaging materials, place the machine on a flat surface, and fill the removable 1.5 liter water tank with fresh cold water. Do not exceed the MAX fill line.

Brewing a Cup: Press the power button and wait for the ready light to turn solid blue (approximately 30 seconds). Select your brew size (Small 150ml, Medium 250ml, Large 350ml) using the dial, then press Start. The machine automatically stops when the selected volume is reached.

Descaling: The NovaBrew should be descaled every 2 months, or when the descale indicator light flashes amber. Use the included descaling solution mixed with water in a 1:4 ratio, run it through the machine using the Descale cycle, then run two cycles of plain water to rinse.

Cleaning: The drip tray and water tank are dishwasher safe on the top rack. Wipe the exterior with a damp cloth only; never immerse the base unit in water.

Troubleshooting: If the machine will not turn on, check that it is plugged into a working outlet and that the water tank is properly seated -- the tank has a safety sensor that blocks power when it is missing. If brewing is unusually slow, this usually indicates mineral buildup and the unit should be descaled.

Warranty: The NovaBrew NB-200 carries a 2 year limited warranty covering manufacturing defects. Warranty does not cover damage from failure to descale the unit as recommended.