

Experiment - 01

Student Name: Kamal Sharma
Branch: CSE - AIML
Semester: 5
Subject Name: ADBMS

UID: 24BAI70380
Section/Group: 24AIT_KRG-1_B
Date of Performance: 11-07-26
Subject Code: 24CSP-310

(A)

Write an SQL solution to calculate the total number of bank accounts belonging to each salary category. The classification categories are:

1. **"Low Salary"**: All monthly salaries strictly less than \$20,000.
2. **"Average Salary"**: All monthly salaries in the inclusive range [\$20,000, \$50,000].
3. **"High Salary"**: All monthly salaries strictly greater than \$50,000. The final result table must report all three categories, even if a category contains zero accounts.

Output Table	
category	accounts_count
Low Salary	1
Average Salary	1
High Salary	3

Solution:

```
SELECT 'LOW CATEGORY' AS CATEGORY,  
COUNT(account_id) as ACCOUNT_COUNT  
FROM Accounts  
where income<20000
```

UNION ALL

```
SELECT 'AVERAGE CATEGORY' AS CATEGORY,  
COUNT(ACCOUNT_ID) AS ACCOUNT_COUNT  
FROM ACCOUNTS  
WHERE INCOME>20000 AND INCOME <= 50000
```

UNION ALL

```
SELECT 'HIGH CATEGORY' AS CATEGORY,
```

```
COUNT(account_id)      as ACCOUNT_COUNT
FROM Accounts
where income>50000;
```

(B)

Design an Employee Management System database architecture by implementing the following operations sequentially:

- 1.Create and populate structural tracking tables for Departments, Employees, and Salaries.
- 2.Query the system using multi-table Joins to pull clear department breakdowns of employees, department and salaries, apply a 10% salary enhancement across all members of the HR department, and delete any individual salary record dropping strictly below \$30,000.
- 3.List all remaining active employees whose personal salary exceeds the overall company-wide average salary.

Output Table:

name	dept_name	salary
Alice	HR	50000
Bob	HR	25000
Charlie	IT	80000
David	IT	40000
Emma	Sales	45000

Solution:

```
SELECT
E.*,D.*,S.*
FROM
EMPLOYEES AS E
JOIN
DEPARTMENTS AS D
ON E.DEPT_ID=D.DEPT_ID
JOIN
SALARIES AS S
ON
E.EMP_ID=S.EMP_ID;
```

```
UPDATE SALARIES
SET SALARY=SALARY+SALARY*0.10
WHERE
EMP_ID IN
(SELECT
FROM EMPLOYEES AS E
JOIN
DEPARTMENTS AS D
ON
E.DEPT_ID=D.DEPT_ID
```

```
WHERE D.DEPT_NAME='HR')
```

```
SELECT S.EMP_ID  
FROM SALARIES AS S  
WHERE SALARY>(  
SELECT AVG(SALARY) FROM SALARIES);
```

(C)

A pizza restaurant stores all the available pizza toppings and their ingredient costs in a table called pizza_toppings.

Every customer must choose **exactly 3 different toppings** to prepare a pizza.

Write a PostgreSQL query to generate **every possible 3-topping pizza combination** along with its **total ingredient cost**.

Requirements

Every pizza must contain **exactly 3 different toppings**.

The same topping **cannot appear more than once** in a pizza.

Different arrangements of the same toppings should be considered the **same pizza**.

Example:

Chicken, Pepperoni, Sausage

Pepperoni, Chicken, Sausage

Sausage, Chicken, Pepperoni

These are all the same pizza, so only **one** should appear.

Display the topping names separated by commas.

Display the total ingredient cost of each pizza.

Sort the output:

First by **highest total cost**

If two pizzas have the same cost, sort them alphabetically.

Solution:

```
SELECT  
CONCAT(T1.TOPPING_NAME,',',T2.TOPPING_NAME,',',T3.TOPPING_NAME  
)AS PIZZA,  
(T1.INGREDIENT_COST+T2.INGREDIENT_COST+T3.INGREDIENT_COST)  
AS TOTAL_COST  
FROM PIZZA_TOPPINGS AS T1  
JOIN  
PIZZA_TOPPINGS AS T2  
ON T1.TOPPING_NAME < T2.TOPPING_NAME  
JOIN  
PIZZA_TOPPINGS AS T3  
ON T2.TOPPING_NAME<T3.TOPPING_NAME  
ORDER BY TOTAL_COST DESC;
```

(D)

Amazon wants to identify **returning customers** who made another purchase shortly after their first purchase. Write a PostgreSQL query to find all users who made **another purchase within 1 to 7 days** of an earlier purchase.

Requirements

1. Compare purchases **made by the same user only**.
2. Ignore comparisons where the same transaction is matched with itself.
3. The second purchase must occur **after** the first purchase.
4. Same-day purchases must **not** be considered.
5. The second purchase must occur within **7 days** of the first purchase.
6. Display only the **unique User IDs** that satisfy the above conditions.
7. Sort the output in ascending order of user_id.

Output Table

user_id
101
103

Solution:

```
SELECT DISTINCT T1.USER_ID
```

```
FROM AMAZON_TRANSACTIONS AS T1
```

```
JOIN AMAZON_TRANSACTIONS AS T2
```

```
ON T1.USER_ID = T2.USER_ID
```

```
WHERE T2.CREATED_AT::DATE > T1.CREATED_AT::DATE
```

```
AND T2.CREATED_AT::DATE - T1.CREATED_AT::DATE <= 7
```

```
ORDER BY T1.USER_ID ASC;
```