

System Shutdown and Startup

This guide describes the proper procedures for bringing down an Interaction Analytics environment for system maintenance or patching, and bringing it back up again when the maintenance work is complete.

The components in an Interaction Analytics environment are designed to be stopped and started in a prescribed order. To ensure you observe the inter-dependencies between the system components, use the NxDeployer to bring your system components down in the correct sequence, and to then bring them back up in the correct sequence.

The system shutdown and startup workflow includes the following steps:

Step	Description
Enter Maintenance Mode	Before you shut down the system, put it into Maintenance Mode to temporarily disable Interaction Analytics system jobs.
Shut Down the System	Use NxDeployer to stop the services for all your Interaction Analytics products in the prescribed order.
Start Up the System	Use NxDeployer to start the services for all your Interaction Analytics products in the prescribed order.
Leave Maintenance Mode	Take the system out of Maintenance Mode to enable system jobs.

Prerequisites

- Before shutting down the system, ensure that:
- NxDeployer is installed, with the Agent service running on all system computers.
 - You have run product discovery for all agent computers for NxDeployer to know which products are installed on each computer.
- For details on installing NxDeployer and running product discovery for agent computers, see the NxDeployer User Guide.
- You have stopped or disabled any software designed to automatically restart product services or web applications that are found to be in a stopped state.

Failure to disable this type of software may run portions of the application while in a mismatched state and result in undefined behavior, including data corruption and other errors.

Enter Maintenance Mode

Before you shut down your system, put it into Maintenance Mode to temporarily disable Interaction Analytics system jobs. The system is only considered to be in Maintenance Mode when all job steps of currently running jobs are complete, so plan your schedule to allow sufficient time for these job steps to finish.

To enter Maintenance Mode:

1. In the NxDeployer Terminal window, go to Actions > Analytics > Enter Full Maintenance Mode

The Configure Analytics Enter Full Maintenance Mode MOP Parameters window opens.

2. Set the value of the ESI Database Connection String parameter to the database server or instance that hosts the NexidiaESI database. If this value is stored in the database, it will be populated automatically.
3. Click OK.

The Configure New MOP Run window appears.

4. (Optional) Change the maintenance window during which to run the MOP, or the name and description that will be displayed for this MOP in the NxDeployer Terminal window.
5. Click OK.

The MOP Runner window appears.

6. Click Play

NxDeployer executes the MOP.

Shut Down the System

You can use the NxDeployer to stop the services for all Interaction Analytics products in the prescribed order. If a product is not installed on a specific computer, the MoP will skip that computer and continue to the next.

To shut down Interaction Analytics from NxDeployer:

1. In the NxDeployer Terminal window, go to Actions > System > Stop.

The Configure System Stop MOP Parameters window appears, listing all the products NxDeployer has found on the agent computers.

2. By default, the value for each Interaction Analytics product is True, meaning that its services will be stopped. In most cases, all product services should be stopped when shutting down the system. If you need to leave services for a particular product running, change its value to False.
3. Set the value of the Disable Product Services parameter to True. This sets the startup mode for product services to disabled. When you run the System Start MOP to start the system back up, it will restore the original startup mode for the product services.
4. Click OK.

The Configure New MOP Run window appears.

5. (Optional) Change the maintenance window during which to run the MOP, or the name and description that will be displayed for this MOP in the NxDeployer Terminal window.
6. Click OK.

The MOP Runner window appears.

7. Click Play.

NxDeployer executes the MOP to stop the product services.

8. Use the Services Control Panel to confirm all product services are stopped and disabled.

Start Up the System

You can use the NxDeployer to start the services for all Interaction Analytics products in the prescribed order and set their startup mode to enabled. If a product is not installed on a specific computer, the MoP will skip that computer and continue to the next.

To start up Interaction Analytics from NxDeployer:

1. In the NxDeployer Terminal window, go to Actions > System > Start.

The Configure System Start MOP Parameters window appears, listing all the products NxDeployer has found on the agent computers.

2. By default, the value for each product is True, meaning that its services will be started. In most cases, all product services should be started when starting up the system. If you need to leave services for a particular product down, change its value to False.
3. Click OK.

The Configure New MOP Run window appears.

4. (Optional) Change the maintenance window during which to run the MOP, or the name and description that will be displayed for this MOP in the NxDeployer Terminal window.

5. Click OK.

The MOP Runner window appears.

6. Click Play.

NxDeployer executes the MOP to start the product services.

7. Use the Services Control Panel to confirm all product services are started and their original startup mode is restored.

Leave Maintenance Mode

Once the Interaction Analytics products are back up and running, the final step in restarting the system is to take it out of Maintenance Mode, which enables system jobs.

1. In the NxDeployer Terminal window, go to Actions > Analytics > Leave Maintenance Mode.

The Configure Analytics Leave Maintenance Mode MOP Parameters window opens.

2. Set the value of the ESI Database Connection String parameter to the database server or instance that hosts the NexidiaESI database. If this value is stored in the database, it will be populated automatically.

3. Click OK.

The Configure New MOP Run window appears.

4. (Optional) Change the maintenance window during which to run the MOP, or the name and description that will be displayed for this MOP in the NxDeployer Terminal window.

5. Click OK.

The MOP Runner window appears.

6. Click Play

NxDeployer executes the MOP.

Further Reading