

▽ giza: A Related Set of Bash Expansions of Relevance to AI

Arash Abadpour - arash@abadpour.com

January 14, 2024

Abstract

wip

In this paper, we discuss the Mathematics of building Machine Vision AI systems in Linux. We review the general challenge of translating the description of an AI operation in human language into a human-readable, machine-executable script. We select multiple Machine Vision AI challenges that we first describe in human language. Then, in each case, we build the language to convert the description in human language into one or more scripts we execute on machines. We use AWS SageMaker ¹ for development and training and AWS Batch ² for inference and discuss API calls. The main contribution of this paper is a mathematical framework for building an AI language for a practical use-case in Machine Vision. We hope that researchers in other fields of AI use and extend this framework in their disciplines. We present a reference implementation ³ of this framework and multiple use-cases ⁴ - *revision-1.143.1*

Contents

1	Introduction	3
2	Expansions	4
2.1	Command Substitution	4
2.2	@cache	4
2.3	@tag	5
2.4	@relations	5
2.5	options	5
2.6	Objects	6
2.7	Prefixing	8
2.8	@seed	8
2.9	@git	9
3	Conventions	10
3.1	\$<core>_<suffix>	10
3.2	dryrun	10
3.3	--<keyword> <value>	10
3.4	--delim space	11
3.5	@init	11
3.6	Plugins	11
3.7	@start	11
3.8	@conda	11
3.9	@publish	11

¹<https://aws.amazon.com/sagemaker/>

²<https://aws.amazon.com/batch/>

³<https://github.com/kamangir/awesome-bash-cli>, *awesome-bash-cli*, *abcli*.

⁴bird watching in downtown Vancouver with AI, <https://github.com/kamangir/Vancouver-Watching>, *Vancouver-Watching*, *vanwatch*.

4	Examples	12
4.1	<code>hubble</code>	12
4.2	<code>openai-cli</code>	12
4.3	<code>roofAI</code>	13
4.3.1	<code>roofAI dataset</code>	13
4.3.2	<code>roofAI semseg train</code>	13
4.3.3	<code>roofAI semseg predict</code>	13
4.4	Vancouver-Watching (<code>vanwatch</code>)	13
4.4.1	<code>vanwatch discover</code>	14
4.4.2	<code>vanwatch ingest</code>	14
4.4.3	<code>vanwatch process</code>	14
4.4.4	<code>tags</code>	14
A	Concepts	15
A.1	Machines and Shells	15
A.2	Operators	15
A.3	Commands	15
A.3.1	Callables	16
A.3.2	Command Templates	16
A.4	Computational Model	16
B	Background and Context	17

1 Introduction

Bash is a “Unix shell and command language first released in 1989 that has been used as the default login shell for most Linux distributions”⁵. A shell is a “macro processor that executes commands”⁶, where “macro processor means functionality where text and symbols are expanded to create larger expressions” (same reference). There are seven kinds of expansions in Bash⁷.

*Brace Expansion*⁸ is the first and the quickest to explain,

```
> bash$ echo a{d,c,b}e
ade ace abe
```

*Tilde Expansion*⁹ relates to words that begin with an unquoted tilde character (~). *Parameter and Variable Expansion*¹⁰ enable the use of variables, as `${variable}`, as well as more elaborate pattern matching forms such as `${parameter/#pattern/string}`. *Command Substitution* “allows the output of a command to replace the command itself”¹¹. *Arithmetic expansion*¹² enables arithmetic operations using the form `$((expression))` and *Word Splitting*¹³ governs the splitting of the command to words. Finally, *Filename Expansion*¹⁴ enables the familiar wildcard reference to filenames using ‘*’ and ‘?’. In Section 2 we propose a set of relevant expansions to AI operations that are implemented using Python¹⁵.

This work, first, proposes several novel Bash expansions based on command substitution 2.1. Then, using typed positional arguments, we propose `options` 2.5 and `objects` 2.6. Then, we discuss argument injection as a suffix 3.3 and *prefixing* 2.7 to transform `<command>` to `<prefix> <options> <command>`

Then, we discuss the `core` 3, which is the callable `??` that is `source`’d in a startup file¹⁶. The `core` loads the `plugins` 3.6 that add branches to the syntax, and `scripts` `??` that implement the last mile. We then discuss the `@seed` 2.8; the notion that code generates code that is transferred into another machine through the clipboard, a key, or a `scp`¹⁷-style protocol to terraform the machine and run a command A.3. `@start` `??` is a necessity; the first intelligent command to start the day with. `@start` behaves according to the machine it runs on and other aspects of the state A.1. On a MacBook, `@start` logs in and starts an `ssh` session to the default machine. On that machine, `@start` starts the docker container¹⁸. We then discuss `@git` `??`.

This work also contributes a set of conventions 3 that enable more effective use of the proposed expansions, such as `<command> help` 3 and `@init` 3.5.

⁵[https://en.wikipedia.org/wiki/Bash_\(Unix_shell\)](https://en.wikipedia.org/wiki/Bash_(Unix_shell))

⁶https://www.gnu.org/software/bash/manual/html_node/What-is-a-shell_003f.html

⁷https://www.gnu.org/software/bash/manual/html_node/Shell-Expansions.html

⁸https://www.gnu.org/software/bash/manual/html_node/Brace-Expansion.html

⁹https://www.gnu.org/software/bash/manual/html_node/Tilde-Expansion.html

¹⁰https://www.gnu.org/software/bash/manual/html_node/Shell-Parameter-Expansion.html

¹¹https://www.gnu.org/software/bash/manual/html_node/Command-Substitution.html

¹²https://www.gnu.org/software/bash/manual/html_node/Arithmetic-Expansion.html

¹³https://www.gnu.org/software/bash/manual/html_node/Word-Splitting.html

¹⁴https://www.gnu.org/software/bash/manual/html_node/Filename-Expansion.html

¹⁵<https://github.com/kamangir/awesome-bash-cli>

¹⁶https://www.gnu.org/software/bash/manual/html_node/Bash-Startup-Files.html

¹⁷<https://linux.die.net/man/1/scp>

¹⁸What `@start` does is decided by its immediate user; the tool is adapted to the tool user.

2 Expansions

2.1 Command Substitution

During the execution of the command `<part-1>$(<sub-command>)<part-2>`, `<sub-command>` is executed and its outcome, `<outcome>`, is used to generate the updated command as `<part-1><outcome><part-2>`, which is then executed ¹⁹. Here is an example from `roofAI 4.3`,

```
roofAI semseg predict \  
  profile=FULL,upload \  
  $(@ref roofAI_semseg_model_AIRS_full_v2) \  
  $(@ref roofAI_ingest_AIRS_v2) \  
  $(@timestamp)
```

Here, `@ref <keyword>` reads the value of `<keyword>` from the `cache 2.2` and `@timestamp` generates a unique timestamp for use as an `<object-name>`. Collectively, this command runs the “Pytorch Segmentation Model” ²⁰ that is cached as `roofAI_semseg_model_AIRS_full_v2` on the dataset that is cached as `roofAI_ingest_AIRS_v2` and uploads the results in a uniquely named objects `2.6`. `Tags 2.3` and `relations 2.4` are other object metadata relevant to this expansion.

Command substitution is useful for generating the command components through Python or Bash. For example, in the AWS Open Data Registry ²¹ there is the notion of datasets, such as `hst 22` for Hubble Space Telescope and the metadata the dataset is maintained in `yaml` files a git repository ²³.

For example, here is the command to access `ibrma2f2q_drc.jpg` in object `public/ibrm/ibrma2f2q` in the dataset `hst`,

```
aws s3 cp $auth $s3_uri$filename $path
```

Here, `$auth` and `$s3_uri` are generated as,

```
auth=$(abcli_hubble_get auth $dataset_name)  
s3_uri=$(abcli_hubble_get s3_uri $dataset_name $hubble_object_name)
```

Here, `abcli_hubble_get` is a Bash wrapper around a Python call.

```
function abcli_hubble_get() {  
  python3 -m hubble get \  
    --what "$1" \  
    --dataset_name "$2" \  
    --object_name "$3" \  
    "${@:4}"  
}
```

2.2 @cache

The cache is a keyword-value dictionary available on every `machine A.1` for reading, writing, and searching, that is enabled either through a SQL database ²⁴ or a tool such as `mlflow 25`.

```
value=$(@cache read <keyword>)
```

```
@cache write <keyword> <value>
```

```
value=@cache search <options>
```

When used for objects `2.6`, `@cache` provides a `tagging 2.3` mechanism,

¹⁹https://www.gnu.org/software/bash/manual/html_node/Command-Substitution.html

²⁰https://github.com/qubvel/segmentation_models.pytorch

²¹<https://registry.opendata.aws/>

²²<https://registry.opendata.aws/hst/>

²³<https://github.com/awslabs/open-data-registry/blob/main/datasets/hst.yaml>

²⁴<https://github.com/kamangir/awesome-bash-cli/blob/2023-06-aws-batch-a/abcli/plugins/tags/functions.py>

²⁵

<https://mlflow.org/>

```
@cache read <object-name>.<keyword>

@cache write <object-name>.<keyword> <value>

@cache clone <object-1> <object-2>
```

2.3 @tag

An objects [2.6](#) can have many tags. A tag is a boolean or valued property of the object and is `set` and `get`, and can be `searched`,

```
@tag set <object-name> <options>

@tag get <object-name>
@tag get <object-name> <keyword>

@tag search <options>
```

2.4 @relations

Two objects [2.6](#) can be related in several ways, each defined as a pair, to enable directional relations [26](#). Here is an example,

```
{
  "added-to": "contains",
  "cloned": "cloned-by",
  ...
  "trained": "trained-on"
}
```

relations can be `set`, `get`, and `searched`,

```
@relations set <object-name-1> <object-name-2> <relation>

@relations get <object-name-1> <object-name-2>
@relations get <object-name-1> <object-name-2> <relation>
@relations get <object-name-1>
@relations get <object-name-1> <relation>

@relation search <object-name> [--relation <relation>]
```

2.5 options

An `options` is a string representation of a dictionary, such as,

```
<keyword-1>=<value-1>,<keyword-2>=<value-2>,...,<keyword-3>,-<keyword-4>},...
```

`options` is implemented using basic Python [27](#) and, therefore, the *options expansion* is available to Bash commands through command substitution [2.1](#). In practice, a second `@option::int` expansion is defined to cover integers and booleans,

```
value=$(@option "$options" <keyword> <default>)

value=$(@option::int "$options" <keyword> 0|1|<int>)
```

Another useful expansion is the *options choice expansion* [28](#),

²⁶<https://github.com/kamangir/awesome-bash-cli/blob/2023-06-aws-batch-a/abcli/plugins/relations/relations.json>

²⁷<https://github.com/kamangir/awesome-bash-cli/blob/2023-06-aws-batch-a/abcli/options>

²⁸As an example, this expansion allows `abcli list cloud|local <object-name>` using `where=$(option::choice "$options" cloud,local cloud)`.

```
choice=$(@option::choice "$options" <comma,separated,list> <default>)
```

The following three operations are also useful on `options`.

default `default <options-1>` to the corresponding values in `<options-2>`. The keyword set of the output is the concatenation of the keyword sets of the two inputs, wherein the values from `<options-1>` take priority. For example, defaulting `x=1,y=2` to `x=3,z=4` yields `x=1,y=2,z=4`. This is the *default option expansion*, which is achieved through `<options-2>,<options-1>`.

subset return the `<options-subset>` subset of `<options>`. The keyword set of the output is the same as the keyword set of `<options-subset>`, wherein the values from `<options>` take priority. For example, the `x=1,y=2` subset of `x=3,z=4` yields `x=3,y=2`. This is the *option subset expansion*,

```
options=$(@option::subset <options> <options-subset>)
```

update `update <options-1>` to `<options-2>`. The keyword set of the output is the concatenation of the keyword sets of the two inputs, wherein the values from `<options-1>` take priority. For example, updating `x=1,y=2` to `x=3,z=4` yields `x=3,y=2,z=4`. This is the *option update expansion*, which is achieved through `<options-1>,<options-2>`.

29

2.6 Objects

Commands [A.3](#) consume and generate objects. Objects are accessible on any machine [A.1](#) by `<object-name>`, and an object may be *selected*,

```
@select <object-name>
```

```
@select <type> <typed-object-name>
```

When an object is selected, `.` expands to `<object-name>`. Similarly, `..`, `...`, and so on, as deep as needed, expand to the name of the previously selected object and the one before that. Commands default the objects they consume and modify to `.`, `..`, and so on. Because the commands in a script use the same objects, selecting the objects enables their names to be omitted in a script.

```
@select <object-1>
```

```
@select <object-2>
```

```
@download
```

²⁹An `options` can be

- read from,
 - a single keyword,
 - * that is an integer: `@option::int`
 - * that is not an integer: `option`.
 - a group of keywords: `option::choice`.
- written to,
 - `keywords=<options-1>.keywords`,
 - * priority: `<options-1>.values: <option-1>`
 - * priority: `<options-2>.values: @option::subset <options-1> <options-2>`
 - `keywords=<options-2>.keywords`,
 - * priority: `<options-1>.values: @option::subset <options-2> <options-1>`
 - * priority: `<options-2>.values: <option-2>`
 - `keywords=<options-1>.keywords + <options-2>.keywords`,
 - * priority: `<options-1>.values: <option-2>+<option-1>`
 - * priority: `<options-2>.values: <option-1>+<option-2>`

The list of expansions and the mathematical properties of a dictionary are related. The author wishes to understand this relationship better.

```

<command-1> # ., .. omitted for convenience
<command-2>
<command-3>
@upload

```

An object may have a *type*, such as model or dataset. Commands that consume objects specify a type for the argument. This enables the user to simultaneously select different types of objects and run commands on them. Here is an example from *hubble* ³⁰, wherein the user selects an object, then selects a hubble dataset, then selects an object in that dataset and downloads it.

```

@select
hubble select dataset hst
hubble select object public/u4ge/u4ge0106r
hubble download -dryrun

```

If <object-name> is not provided or is given as -, then an object with a unique name is created and used. An object points to an S3 bucket ³¹ ³². *Metadata* is information about **objects** 2.6, such as their tag 2.3 and relations 2.4, and the information cache 2.2d about them. Objects also carry metadata as a dictionary. More generally, any path, including within the code ³³, may carry metadata. One can get and post metadata related to a filename, an object, or a path,

```

@metadata get \
    delim=+,dict.keys,dict.values,key=<key>,filename \
    <filename.yaml>

@metadata get \
    delim=+,dict.keys,dict.values,key=<key>,filename=<metadata.yaml>,object \
    .|<object-name>

@metadata get \
    delim=+,dict.keys,dict.values,key=<key>,filename=<metadata.yaml>,path \
    <path>

@metadata post \
    <key> <value> \
    filename \
    <filename.yaml>

@metadata post \
    <key> <value> \
    object,filename=<metadata.yaml> \
    .|<object-name>

@metadata post \
    <key> <value> \
    path,filename=<metadata.yaml> \
    <path>

```

Objects can be downloaded, uploaded, and listed,

```

@download \
    [filename=<filename>,open] \
    [.|<object-name>]

```

³⁰<https://github.com/kamangir/hubble>

³¹<https://aws.amazon.com/s3/>

³²Special variables, such as \$abcli_object_name, \$abcli_object_path, \$abcli_hubble_dataset_object_name, \$abcli_object_name_prev2 carry the name of the selected object, its path, the name of current selected hubble dataset and the second previous selected object, respectively.

³³for example, <https://github.com/kamangir/notebooks-and-scripts/blob/main/scripts/meta.yaml>.

```
@upload \
  [filename=<filename>,&simopen,solid,&simwarn_if_exists] \
  [.&sim|<object-name>]
```

```
@list cloud|local <object_name>
```

It is recommended that additional `download` and `list` expansions are defined for typed objects. See [hubble 4.1](#) for examples. Objects can be cloned,

```
@clone [.&sim|<object-1>] [.&sim|<object-2>] \
  [&simcache,&simdownload,&simmeta,&simrelations,&simtags,upload]
```

2.7 Prefixing

The *prefixing expansion*,

```
<callable> <options> <command>
```

enables `<callable>` to execute `<command>` with certain `<options>`. This expansion enables submitting `<command>` to another machine, be it a docker container ³⁴ or AWS Batch. `@eval` ³⁵ uses this expansion to enable running `<command>` in a `<path>` with `dryrun` [3.2](#) and `log` options.

```
@eval [dryrun,-log,path=<path>] <command>
```

2.8 @seed

It is often necessary to continue the operation on another [machine A.1](#). Examples include `ssh`ing to another machine, continuing the work on AWS SageMaker and between different images, running the code in a docker container or submitting it to AWS Batch, or running commands inside the Python Console in QGIS ³⁶. The `@seed` expansion generates the code for the other machine to terraform and run a command or start accepting commands ³⁷.

```
@seed \
  [<target>|docker|ec2|jetson|headless_rpi|mac|rpi|sagemaker|sagemaker-system] \
  [clipboard|filename=<filename>|key|screen,cookie=<cookie-name>,plugin=<plugin-name>,-log]
```

The `seed` has been transferred through the clipboard, a USB key, and `scp`. Here is an example,

```
> @seed sagemaker screen
seed: abcli-7.2477.1.2023-06-aws-batch-a -sagemaker-> screen
run "bash" before pasting the seed.
#! /bin/bash
echo "abcli-7.2477.1.2023-06-aws-batch-a seed for sagemaker"

pip install --upgrade pip

cd git/awesome-bash-cli
pip3 install -e .

source ./bash/abcli.sh
```

³⁴<https://github.com/kamangir/notebooks-and-scripts/blob/main/.abcli/docker.sh>

³⁵<https://github.com/kamangir/awesome-bash-cli/blob/2023-06-aws-batch-a/bash/plugins/eval.sh>

³⁶https://docs.qgis.org/2.18/en/docs/user_manual/plugins/python_console.html

³⁷Does this concept exist in the literature?

2.9 @git

The [core 3](#) and the [plugins 3.6](#) are maintained in repositories. There are also other repositories of interest.

```
@git clone <repo-name> [init,install,object,<options>]
```

clones <repo-name> and,

```
@git <repo-name>
```

```
@git cd|pushd <repo-name>
```

change directory to <repo-name>.

```
@git <repo-name> <command>
```

runs <command> in <repo-name>. The following expansions show the status of a repository, create a branch in it, or push, or pull from it. In the absence of <repo-name>, `status` and `pull` default to all repositories ³⁸.

```
@git status [all|<repo-name>]
```

```
@git create_branch <branch-name> [.|<repo-name>]
```

```
@git pull [all|<repo-name>]
```

```
@git push [first,~status] [<message>] [.|<repo-name>]
```

³⁸This design is different from the implementation in <https://github.com/kamangir/awesome-bash-cli/blob/2023-06-aws-batch-a/bash/plugins/git.sh>.

3 Conventions

Conventions augment and enable [expansions 2](#) or are found to be helpful.

- The `core` loads the [plugins 3.6](#) and terraforms the [machine A.1](#).
- `<command> help` shows help about `command`.
- `@ref` is an alias for `@cache read` that enables `$(@ref <keyword>)` and, thus, object alias [39](#).

3.1 `$<core>_<suffix>`

During initialization, the `core 3` and the [plugins 3.6](#) set a series of variables to harmonize paths and other [machine A.1](#)-specific parameters to enable the same code to run on different machines simultaneously.

- `$<core>_git_<suffix>`: `@git 2.9`.
- `$<core>_<type>_name[_prev[n]]`: select [2.6ed](#) objects.
- `$<core>_<type>_path`: select [2.6ed](#) object path.
- `$<core>_is_<suffix>` describe the [machine A.1](#)
- `$<core>_path_<suffix>`: paths.

An alias of `env` lists these variables.

```
@env [<keyword>]
```

3.2 `dryrun`

In `dryrun` mode, the low-cost and fast aspects of the command are executed, and the rest of the operation is logged instead. `@eval` is used for this operation.

3.3 `--<keyword> <value>`

`argparse 40`, `click 41`, `fire 42`, and many other command line parsers support the `--<keyword> <value>` convention. By ending Python calls with `"$@:<number>"` the rest of the arguments are captured. Here is an example,

```
abcli message submit \  
  [--data <data>] \  
  [--filename <filename>] \  
  [--recipient <host_1,host_2>] \  
  [--subject <subject>]
```

This is achieved through [43](#),

```
python3 -m abcli.plugins.message \  
  submit_object \  
  --object_name "$object_name" \  
  --recipient "$recipient" \  
  "${@:5}"
```

³⁹Refer to <https://github.com/kamangir/roofAI/blob/main/roofAI/semseg/README.md> for an example.

⁴⁰<https://docs.python.org/3/library/argparse.html>

⁴¹<https://palletsprojects.com/p/click/>

⁴²<https://google.github.io/python-fire/>

⁴³<https://github.com/kamangir/awesome-bash-cli/blob/2023-06-aws-batch-a/bash/plugins/message.sh>

3.4 --delim space

Command substitution [2.1](#) is useful in for loops and other usages where a delimited list of keywords is consumed.

```
local object_name
for object_name in $(<command-1> --delim space); do
    <command-2> $object_name <args>
done
```

Here is one way to compose the .py cli,

```
...
parser.add_argument("--count", type=int, default=-1)
parser.add_argument("--delim", type=str, default=",")
...
delim = " " if args.delim == "space" else args.delim
...
elif args.task == "foo":
    output = foo()
    if count != -1:
        output = output[:count]
    print(delim.join(count))
...
```

3.5 @init

The following expansions initialize the [core 3](#), and therefore all [plugins 3.6](#), or <plugin-name>.

```
@init <options>
```

```
<plugin-name> init <options>
```

3.6 Plugins

A plugin generally defines one or more [callable A.3.1](#).

3.7 @start

```
@start <options>
```

3.8 @conda

```
@conda create_env [clone=<base>,name=<environment-name>,&tilde;recreate]
```

```
@conda exists [<environment-name>]
```

```
@conda list
```

```
@conda remove|rm [<environment-name>]
```

3.9 @publish

```
@publish [extension=<png>,filename=<filename-1+filename-2>,randomize,tar] \
    [.<object_name>]
```

copies select content from <object-name> into a publicly accessible bucket.

4 Examples

4.1 hubble

hubble ⁴⁴ is a callable [A.3.1](#) that selects, lists, and downloads data from AWS Open Data Registry ⁴⁵.

```
hubble select [dataset] <hubble-dataset-name>
hubble select [object] <hubble-object-name>

hubble list [dataset] [.|<hubble-dataset-name>]
hubble list [object] [.|<hubble-object-name>]

hubble download \
    [~dryrun,filename=<filename>|all,~ingest,upload] \
    [.|<hubble-object-name>] \
    [.|<object-name>]
```

4.2 openai-cli

openai-cli ⁴⁶ is a bash cli for the OpenAI API ⁴⁷. openai is a callable [A.3.1](#) that supports basic prompt completion through,

```
openai complete "<prompt>"
```

Image, <prompt> -[<previous-image>]-> <image>.png and input.txt|url -DALL-E-> output.png, and video, <filename.txt>|url -> video.mp4, generation are supported, as well as image transformation, <object-1> -<prompt>-> <object-2>,

```
openai generate image [height=<576>,width=<768>] \
    [<image>] [<previous-image>] \
    "<prompt>"
```

```
DALL-E render \
    [brush=tiling|randomwalk,brush_size=256|512|1024,lines=<5>,publish] \
    input.txt|https://allpoetry.com/16-bit-Intel-8088-chip \
    [output.png]
```

```
openai generate video [frame_count=16,url] \
    <filename.txt|url>
```

```
openai transform [extension=jpg] \
    [<object-1>] [<object-2>] \
    "<prompt>" \
```

The Vision API ⁴⁸ is supported,

```
openai vision "prompt" [auto|low|high,dryrun,~upload] \
    [Davie,~Bute,.jpg] \
    <.|object-name>
```

Tools for code generation,

```
openai completion describe <plugin-name>
```

⁴⁴<https://github.com/kamangir/hubble>

⁴⁵<https://registry.opendata.aws/>

⁴⁶<https://github.com/kamangir/openai>

⁴⁷<https://beta.openai.com/docs/introduction>

⁴⁸<https://platform.openai.com/docs/guides/vision>

4.3 roofAI

roofAI ⁴⁹ is a callable ?? that,

1. terraforms the machine and the shell 3.8.
2. ingests and reviews datasets 4.3.1.
3. train semantic segmentation ⁵⁰ models 4.3.2.
4. runs semantic segmentation predictions 4.3.3.

4.3.1 roofAI dataset

roofAI dataset ingest source=<source> <object-name> ingests a dataset from source into <object-name> and tags it for future discovery. roofAI dataset review - <object-name> reviews the dataset in <object-name>.

```
roofAI dataset ingest \  
    [source=AIRS|CamVid,register,suffix=<v1>] \  
    <object-name> \  
    [<args>]
```

```
roofAI dataset review \  
    [-] \  
    <object-name> \  
    [<args>]
```

4.3.2 roofAI semseg train

semseg train - <dataset-object-name> <model-object-name> trains a model on <dataset-object-name> that it stores in <model-object-name> and tags for future discovery.

```
semseg train \  
    [device=cpu|cuda,register,suffix=<v1>] \  
    <dataset-object-name> \  
    <model-object-name> \  
    [<args>]
```

4.3.3 roofAI semseg predict

semseg predict - <model-object-name> <dataset-object-name> runs a prediction on the dataset <dataset-object-name> using the model <model-object-name>.

```
semseg predict \  
    [device=cpu|cuda] \  
    <model-object-name> \  
    <dataset-object-name> \  
    <prediction-object-name>
```

4.4 Vancouver-Watching (vanwatch)

vanwatch ⁵¹ is a callable A.3.1 that,

1. terraforms the machine and the shell 3.8.
2. discovers the cameras in an area 4.4.1.
3. ingests images from the cameras discovered in an area 4.4.2.
4. detects the objects in the images ingested from an area and produces summary statistics 4.4.3.

⁴⁹<https://github.com/kamangir/roofAI>

⁵⁰semseg

⁵¹<https://github.com/kamangir/Vancouver-Watching>

4.4.1 vanwatch discover

Cameras are represented in different formats in different areas.

```
vanwatch discover [area=<area>] [-|<object-name>] [<args>]
```

discovers the cameras in <area> and stores them in <area>.geojson in the object 2.6 <object-name> and tags 2.3 the object for discovery by ingest 4.4.2 and list 4.4.4.

4.4.2 vanwatch ingest

```
vanwatch ingest \  
  [area=<area>,count=<-1>,model=<model-id>,<~process,publish>] \  
  [-|<object-name>]
```

finds the latest set of cameras discovered 4.4.1 in <area> through tag 2.3 search and ingests count images into <object-name> and then runs vanwatch process 4.4.3 unless -process. object-name is tagged for discovery by list 4.4.4.

4.4.3 vanwatch process

```
vanwatch process [model=<model-id>,publish] [.|<object-name>]
```

runs object detection ⁵² on the images ingested 4.4.3 into <object-name> and updates <area>.geojson. vanwatch process reuses the inference in the object and completes the missing pieces. +publish tags 2.3 object-name for discovery by update_QGIS and publishes 3.9 the object.

4.4.4 tags

The following commands,

```
vanwatch discover|ingest|process [publish] <object-name>
```

tag 2.3 <object-name> (and publish 3.9 it). Tagged objects 2.6 can be discovered by,

```
vanwatch list areas
```

```
vanwatch list [area=<area>,discovery|ingest]
```

```
vanwatch update|update_cache [area=<area>,push]
```

update_QGIS uses @git 2.9 to maintain a copy of geojsons in the repo ⁵³.

⁵²<https://hub.ultralytics.com/models/R6nMlK6kQjSsQ76MPqQM?tab=preview>

⁵³<https://github.com/kamangir/Vancouver-Watching/tree/main/QGIS>

A Concepts

A.1 Machines and Shells

A *machine* is a state machine that is connected to many other machines and shares some of its state with them for read and write. A *shell* is a stateful access mechanism to a machine that an *operator* A.2 uses to run *commands* A.3. Running a command in a shell can modify the state of the shell, the machine on which the shell is running, and potentially the states of all other machines.

Machines and shells may be restarted by an operator or by code. After a restart, machines and shells maintain some of their state.

Two examples of machines are a Raspberry Pi that runs Linux and is connected to AWS ⁵⁴ and a docker container running in AWS Batch. GNU Bash ⁵⁵ is an example of a shell.

A.2 Operators

The *operator* generates commands and runs them on different shells on different machines. The operator attempts to maximize an objective function that depends on the state of multiple machines.

A.3 Commands

A *command* is any Bash command ⁵⁶ and can be represented in a Python string of characters ⁵⁷. Here is an example command,

```
vanwatch ingest \
  vancouver \
  dryrun \
  . \
  --count 12
```

The above command and the one below are *identical*.

```
vanwatch ingest vancouver dryrun . --count 12
```

Two commands are identical if running them on two machines in identical states yields the same states. In theory, the state of any machine depends on the state of any other machine, and it is almost impossible to run two commands in identical states, including the time of execution. Therefore, when we refer to two identical commands, we either use a derivation-based proof of identity or consider a validation in a limited “relevant” subset of the state representation.

For any shell on any machine, at known states, there is a mapping between the set of all commands and $\{True, False\}$ that we address as “whether the command is found”. In Bash, for example, the following message is printed when a command “is not found”.

```
-bash: void: command not found
```

Note that writing to the standard streams *stdin* and *stdout* are examples of state changes in the shell and the machine.

Terraforming is the process of running commands that modify the state of the shell and the machine in ways that make additional commands found. Terraforming is also intended to modify the state change caused by a set of commands favourable to the interests of an operator. For convenience, we address a command “that is found” as a *valid* command and *invalid* otherwise. Terraforming may also ensure the states of the machine and the shell after a restart. Terraforming generally includes a modification of *bashrc*, *bash_profile*, *screenrc*, and *desktop* files.

Commands know the machine and the shell they are running in and adjust their operation accordingly. For example, a script that submits jobs inside a docker container may download the artifacts generated through previous submissions on a user-facing machine, such as a Macbook.

⁵⁴<https://aws.amazon.com/>

⁵⁵<https://www.gnu.org/software/bash/>

⁵⁶<https://www.gnu.org/software/bash/manual/bash.html#Shell-Syntax>

⁵⁷<https://docs.python.org/3/library/string.html>

The first word ⁵⁸ in a command is generally the **callable** A.3.1. The rest of the command is expected to follow the conventions of the callable. In this paper we propose guidelines that we later demonstrate lead to useful **expansions** 2.

A.3.1 Callables

A *callable* is a valid command with no space and control operators ⁵⁹. The list of callables depends on the machine’s state and is generally extended through terraforming. Some of the well-known callables are *git* ⁶⁰, *docker* ⁶¹, *pushd* ⁶², *nano* ⁶³.

Theorem 1 *For any callable <callable>, and any string <suffix>, <callable> <suffix> is a valid command.*

Theorem 2 *For any valid command <command>, and any string <suffix>, <command> <suffix> is a valid command.*

The **core** 3 is a callable. Many **plugins** 3.6 define their callable.

A.3.2 Command Templates

Commands can be similar when considered as strings of characters. Here is a command that is similar to the above,

```
vanwatch ingest toronto upload . --count 3
```

A *command template* is a representation that yields similar commands, given the following rules. First, <description> can be replaced with any string of characters that can be described as “description”. See **objects** 2.6, **options** 2.5, and **arguments** ??, for the next rules. Here is a command template for the two above,

```
vanwatch ingest \
  <area> \
  [dryrun,~upload] \
  [<object-name>] \
  [--count <-1>]
```

A.4 Computational Model

A group of operators create and modify a set of **scripts** ?? maintained in a code repository, such as **git** 2.9. The **core** 3 and the **plugins** 3.6 are also maintained in one or more repositories. Each operator can access a set of machines and create shells on them. Each operator can also access a set of repositories and clone them on the machines where they create shells and receive updates. The operator can modify any of the repositories that they have access to following a collective peer-reviewed **pull-request** ⁶⁴ process.

The operators act asynchronously while communicating with each other. Multiple operators may simultaneously use the same machine, and the same operator may simultaneously use multiple machines. Only one operator uses a shell at one time.

Some machines are exogenous to this model, yet the operators can access their states in read or write mode. Cloud storage and compute resources are examples of these machines.

⁵⁸https://www.gnu.org/software/bash/manual/html_node/Shell-Syntax.html

⁵⁹<https://www.gnu.org/software/bash/manual/bash.html#index-control-operator>

⁶⁰<https://git-scm.com/docs/git>

⁶¹<https://docs.docker.com/engine/reference/commandline/cli/>

⁶²<https://www.gnu.org/software/bash/manual/bash.html#Directory-Stack-Builtins>

⁶³<https://www.nano-editor.org/>

⁶⁴<https://docs.github.com/en/pull-requests/collaborating-with-pull-requests/proposing-changes-to-your-work-with-pull-requests/about-pull-requests>

B Background and Context

Almost five years ago, on Thursday, November 8, 2018, I acquired a Raspberry Pi ⁶⁵ on Amazon. Since then, my personal and professional lives have focused on Linux. Professionally, I do AI and, more recently, geospatial AI. In my personal life, I mix AI, cloud, and Mathematics into minimal forms that seek survival ⁶⁶. Over the years, I have built a set of mechanisms for building AI systems that I will document in this paper. Therefore, this is an attempt to produce formal mathematical definitions for the AI mechanisms that I will collectively refer to as *giza*. I seek to understand these mechanisms through this effort better to use them more optimally and along new dimensions.

This paper discusses concepts at the intersection of mathematics, software science, and computer science, and lacks scientific rigour in many places. I intend to push the practical development of this theory to fruition and hope to receive guidance along the way from experts in the field and solidify the theoretical foundations.

⁶⁵<https://www.raspberrypi.org/>

⁶⁶<https://github.com/kamangir>