

Name: Kamanisairam

Reg no:192312195

Ex.No 12: NB-IoT vs LTE-M Throughput Simulation Date

Objective 1:

To evaluate and compare the Throughput (Mbps) performance of NB-IoT and LTE-M under varying network conditions..

Program (Matlab Code)

```
clc;
clear;
close all;
% SNR values (dB)
SNR = 0:5:30;
% Simulated Throughput (Mbps)
NB_IoT = 0.05*(1-exp(-SNR/8));
LTE_M = 1.2*(1-exp(-SNR/8));

disp('SNR (dB) NB-IoT(Mbps) LTE-M(Mbps)')
disp([SNR' NB_IoT' LTE_M'])
figure
% ----- Graph 1 -----
subplot(2,1,1)
plot(SNR,NB_IoT,'-o','LineWidth',2)
title('NB-IoT Throughput vs SNR')
xlabel('Signal-to-Noise Ratio (dB)')
```




```

ylabel('Throughput (Mbps)')
grid on
% ----- Graph 2 -----
subplot(2,1,2)
plot(SNR,LTE_M,'-s','LineWidth',2)
title('LTE-M Throughput vs SNR')
xlabel('Signal-to-Noise Ratio (dB)')
ylabel('Throughput (Mbps)')
grid on

```

Output:



Objective 2:

To analyze the Latency (ms) characteristics of NB-IoT and LTE-M and study their impact on real-time communication.

Matlab Code

```
clc;
clear;
close all;
% SNR values (dB)
SNR = 0:5:30;
% Simulated Latency (ms)
NB_IoT = [180 160 145 130 120 110 100];
LTE_M = [90 80 70 60 50 45 40];
disp('SNR(dB) NB-IoT Latency(ms) LTE-M Latency(ms)')
disp([SNR' NB_IoT' LTE_M'])
figure
% ----- Graph 1 -----
subplot(2,1,1)
plot(SNR,NB_IoT,'-o','LineWidth',2)
title('NB-IoT Latency vs SNR')
xlabel('Signal-to-Noise Ratio (dB)')
ylabel('Latency (ms)')
```



grid on

% ----- Graph 2 -----

subplot(2,1,2)

plot(SNR,LTE_M,'-s','LineWidth',2)


title('LTE-M Latency vs SNR')

xlabel('Signal-to-Noise Ratio (dB)')

ylabel('Latency (ms)')

grid on

Output



Objective 3:

To measure and compare the Packet Delivery Ratio (%) of NB-IoT and LTE-M

systems for reliability assessment..

Matlab Code

```
clc;
clear;
close all;
% SNR values (dB)
SNR = 0:5:30;
% Simulated Packet Delivery Ratio (%)
NB_IoT = [82 86 89 92 95 97 99];
LTE_M = [88 91 94 96 98 99 100];
disp('SNR(dB) NB-IoT PDR(%) LTE-M PDR(%))')
disp([SNR' NB_IoT' LTE_M'])
figure
% ----- Graph 1 -----
```



```
subplot(2,1,1)
plot(SNR,NB_IoT,'-o','LineWidth',2)
title('NB-IoT Packet Delivery Ratio vs SNR')
xlabel('Signal-to-Noise Ratio (dB)')
ylabel('Packet Delivery Ratio (%)')
grid on
% ----- Graph 2 -----
```

```
subplot(2,1,2)
plot(SNR,LTE_M,'-s','LineWidth',2)
title('LTE-M Packet Delivery Ratio vs SNR')
xlabel('Signal-to-Noise Ratio (dB)')
ylabel('Packet Delivery Ratio (%)')
grid on
```

Output



