

# Statistik und Graphiken mit R

## [Termine 1 & 2]

Miguel Alvarez

28. Februar & 02. März 2023

**▶ Termin 1 & 2**

- ▶ Grundlagen
- ▶ Datentypen

**▶ Termin 3 & 4**

- ▶ Objekten
- ▶ Lesen und Schreiben

**▶ Termin 5 & 6**

- ▶ Statistiken
- ▶ Graphiken (1)

**▶ Termin 7 & 8**


- ▶ Graphiken (2)
- ▶ Fortgeschrittenes Programmieren
- ▶ Abschluss

18:00 – 20:30

Pause 19:15 – 19:30

- ▶ Methoden
  - ▶ Vortrag
  - ▶ Life-Codierung
  - ▶ Übungen

<https://kamapu.github.io/GrundkursR/>




## Miguel Alvarez



- ▶ Vegetationsökologist
- ▶ Data Scientist
- ▶ R-Programmierer
  - ▶ Umwelt und Biodiversität
  - ▶ Geographische Informationssysteme
  - ▶ Datenbanken
  - ▶ Reproduzierbarkeit

## Die Teilnehmer?

- ▶ Warum R?
- ▶ Erwartung von dem Kurs



## Geschichte

- ▶ S (1975)
  - ▶ S-PLUS
  - ▶ TIBCO Spotfire S+
- ▶ R (1992)

**R** ist die kostenlose Alternative zu **S**

Ross Ihaka

Robert Gentleman



## Was ist R?

- ▶ Programmiersprache
  - ▶ Open Source (offene Quelle)
  - ▶ Freeware (kostenlos)
- ▶ Statistische Umgebung
  - ▶ Interface
  - ▶ Terminal
  - ▶ Editoren

<https://www.r-project.org/>


[\[Home\]](#)

**Download**  
CRAN

**R Project**

About R  
Logo  
Contributors  
What's New?  
Reporting Bugs  
Conferences  
Search  
Get Involved: Mailing Lists  
Get Involved: Contributing  
Developer Pages  
R Blog

**R Foundation**

Foundation  
Board  
Members  
Donors  
Donate

**Help With R**

Getting Help

**Documentation**

Manuals  
FAQs  
The R Journal  
Books  
Certification

## The R Project for Statistical Computing

### Getting Started

R is a free software environment for statistical computing and graphics. It compiles and runs on a wide variety of UNIX platforms, Windows and MacOS. To [download R](#), please choose your preferred [CRAN mirror](#).

If you have questions about R like how to download and install the software, or what the license terms are, please read our [answers to frequently asked questions](#) before you send an email.

### News

- **R version 4.2.2 (Innocent and Trusting) prerelease versions** will appear starting Friday 2022-10-21. Final release is scheduled for Monday 2022-10-31.
- **R version 4.2.1 (Funny-Looking Kid)** has been released on 2022-06-23.
- **R version 4.1.3 (One Push-Up)** was released on 2022-03-10.
- Thanks to the organisers of useR! 2020 for a successful online conference. Recorded tutorials and talks from the conference are available on the [R Consortium YouTube channel](#).
- You can support the R Foundation with a renewable subscription as a [supporting member](#)

### News via Twitter

 The R Foundation Retweeted

 **R Contributo...** @R\_Contributo... · Oct 10  
R Contribution Working Group meeting Oct 18, 18:30 - 19:30 UTC

We'll discuss progress on current issues ([github.com/r-devel/rcontr...](https://github.com/r-devel/rcontr...)), including

- Translation hackathons (LatinR, AsiaR)
- Office hours
- Code of conduct

All welcome. Zoom registration:  
[us02web.zoom.us/joining/regist...](https://us02web.zoom.us/joining/regist...)

## Was ist R?

- ▶ Schwerpunkt
  - ▶ Mathematik
  - ▶ Grafiken
- ▶ Kommandozeilen
- ▶ REPL (Read-Eval-Print-Schleife)

```
(5 + 100) * 25
```

```
## [1] 2625
```

```
50/10
```


```
## [1] 5
```

```
60 > 15
```


```
## [1] TRUE
```




```
plot(iris[ , c("Sepal.Length",
               "Petal.Length")],
     pch = 16, col = iris$Species)
```



```
boxplot(Sepal.Length ~ Species,  
        data = iris)
```



```
library(ggplot2)
ggplot(iris,
      aes(x = Sepal.Length,
          y = Petal.Length,
          color = Species)) +
  geom_point()
```




## Warum R?

- ▶ Kostet nichts
- ▶ Steuerung von Analysen
- ▶ Skripten
  - ▶ Protokolle
  - ▶ Reproduzierbarkeit
- ▶ Vielseitig

## Jargon

- ▶ Konsole
- ▶ Sitzung
- ▶ Workspace (Environment)
- ▶ Arbeitsverzeichnis (working directory)
- ▶ Skript
- ▶ Paket (Package)


- ▶ Text Editor
- ▶ IDE (integrated development environment)



## eclipse (StatET)

The screenshot shows the Eclipse IDE with the following components:

- Project Explorer:** Displays a file tree for the project 'vhs-bonn - bonn-2022-r-intro'. The file 'FolienRKurs-12.Rmd' is selected.
- Main Editor:** Shows the R code for the presentation slide. The code includes a title 'RStudio', a subtitle 'R als Taschenrechner', and a list of topics: 'Mathematische Operatoren', 'Logische Operatoren', and 'Klammern'. It also includes a scatter plot of Sepal.Length vs Petal.Length.
- R Console:** Displays the R startup message, including the R version (4.0.0), the RStudio version (0.99.909), and the RStudio license.
- Scatter Plot:** A scatter plot showing the relationship between Sepal.Length (x-axis, ranging from 4.5 to 8.0) and Petal.Length (y-axis, ranging from 2.0 to 4.0). The plot shows a positive correlation between the two variables.



- ▶ Mathematische Operatoren
- ▶ Klammern

$5+6*11$

## [1] 71

$(5+6)*11$

## [1] 121

$(5-6)/11$

## [1] -0.09090909



## Zuweisung

`<-`

Zuweisung von einem Wert zu einem Objekt.

## Konvention

- ▶ Nutze `<-` anstatt `->`
- ▶ Reserviere `=` für Argumente in Funktionen
- ▶ Nutze Leerzeichen für eine bessere Übersicht in Quellcode
- ▶ Nutze Einrückungen für gebrochene Kommandozeilen

## Logische Operatoren

==

!=

&gt;

&gt;=

&lt;

&lt;=

&amp;

|

%in%

!

any()

all()

```
10 > 15
```

```
## [1] FALSE
```

```
10 < 15
```

```
## [1] TRUE
```

## Vektoren

Der Vektor ist die grundlegende Datenstruktur in **R**

- ▶ Länge `length()`
- ▶ Typ `class()`
- ▶ Evtl. Namen `names()`

```
c(1:10)
## [1] 1 2 3 4 5 6 7 8 9 10
rep(5, times = 10)
## [1] 5 5 5 5 5 5 5 5 5 5
LETTERS[1:5]
## [1] "A" "B" "C" "D" "E"
```

## Indexieren

- ▶ Eckige Klammern
- ▶ Index
  - ▶ integer
  - ▶ logical (Bedingung)
  - ▶ character (Namen)

```
# Mit integer
```

```
letters[15]
```

```
## [1] "o"
```

```
# Mit logischen Werten
```

```
letters[!letters %in% c("a", "b", "c")]
```

```
## [1] "d" "e" "f" "g" "h" "i" "j" "k" "l" "m"
```

```
## [20] "w" "x" "y" "z"
```

```
# Mit Namen
```

```
names(letters) <- letters
```

```
letters["m"]
```

```
## m
```

```
## "m"
```

## Datentypen

- ▶ integer
- ▶ numeric
- ▶ logical
- ▶ factor
- ▶ character

```
A <- c(1:10)
is.numeric(A)
## [1] TRUE
```

```
B <- as.character(A)
B
## [1] "1" "2" "3" "4" "5" "6" "7" "8"
is.numeric(B)
## [1] FALSE
```

## Sonderklassen

- ▶ NA
- ▶ NaN
- ▶ NULL
- ▶ Inf
- ▶ -Inf

```
5/0
```

```
## [1] Inf
```

```
log(0)
```

```
## [1] -Inf
```

```
sqrt(-1)
```

```
## Warning in sqrt(-1): NaNs produced
```

```
## [1] NaN
```

## Rückmeldungen

- ▶ Konsolenoutput
- ▶ Nachricht (message)
- ▶ Warnung (warning)
- ▶ Fehlermeldung (error)

Eine Warnung ist nicht zwingend ein Fehler.

```
sqrt(-1)
```

```
## Warning in sqrt(-1): NaNs produced
```

```
## [1] NaN
```

```
5 + "B"
```

```
## Error in 5 + "B": non-numeric argument to bin
```

## Fehlerbehebung

- ▶ Dokumentation
- ▶ Foren
- ▶ Programfehler melden

```
# help()
?mean
# help.search()
??"multinomial"
RSiteSearch("Import")
```



## Regeln für Hilfeanfrage

- ▶ Recherechiere vorher
- ▶ KESS (*keep it simple stupid*)
- ▶ Zeige ein **minimales Beispiel**
- ▶ Bleibe höflich
- ▶ Melde die Endlösung
- ▶ Lerne **markdown**

<https://stackoverflow.com/questions>  
<https://www.markdowntutorial.com/>

The screenshot shows a Stack Overflow page for a question titled "P-values from aov in R". The question is asked 7 years, 1 month ago and modified 6 years, 10 months ago. It has been viewed 2k times. The question text describes a simulation study in R using the `aov` function and difficulty extracting p-values. The user provides R code: `results <- summary(aov(dv={A*B*C*D*E}*Error(subj)/(A*B*C*D)), data = mdata)) # con`. The output shows ANOVA tables for subjects 'E' and 'A'. The user mentions truncating the output and wanting a list of p-values with effect names (A or A:E). A partial R function `get_p` is shown at the bottom.

stackoverflow Products Search...

Home

PUBLIC

Questions

Tags

Users

Companies

COLLECTIVES

Explore Collectives

TEAMS

Stack Overflow for Teams – Start collaborating and sharing organizational knowledge.

Create a free Team

Why Teams?

### P-values from aov in R

Asked 7 years, 1 month ago Modified 6 years, 10 months ago Viewed 2k times

stackoverflow Take this month's Pulse Survey Take the survey

I'm conducting a simulation study in R. Basically, I generate fake data sets and then run an ANOVA on the data using the `aov` function. But I'm having difficulty extracting p-values. Previous questionss do not help ([Extract p-value from aov](#)) -- I am running a mixed ANOVA.

First I have an ANOVA:

```
results <- summary(aov(dv={A*B*C*D*E}*Error(subj)/(A*B*C*D)), data = mdata)) # con
```

which generate this output:

```
Error: subj
      Df Sum Sq Mean Sq F value Pr(>F)
E       1 1039157 1039157   0.95  0.334
Residuals 58 63428016 1093586

Error: subj:A
      Df Sum Sq Mean Sq F value Pr(>F)
A       1 1996 1996 0.229  0.641
A:E     1 2294 2294 0.253  0.617
Residuals 58 526389 9076

...
```

I'm truncating the output for space. What I want list of p-values with the effect name (A or A:E). I have halfway succeeded, but it's messy. I can extract the p-values using this `get_p` function that I made.

```
#Function
get_p = function(results,headIf
```

## Weitere Dokumente

- ▶ Demos
  - ▶ `demo()`
- ▶ Beispielssitzungen
  - ▶ `browsevignette()`
  - ▶ `vignette()`
- ▶ Zahlreiche Tutorials

```
demo("graphics")  
vignette("ggplot2-specs")
```

# Vielen Dank!

```
library(fortunes)  
fortune(283)
```

```
##  
## The good way to do it is to include the following comment at the beginning:  
## # This is a holy Script, please edit it not  
## -- Kenn Konstabel (on "... how to protect R Script files from inadvertent  
## editing by users.")  
## R-help (April 2011)
```