

SOFTWARE REQUIREMENTS SPECIFICATION

GiftCompass

An AI-Assisted Personalised Gift Recommendation Platform
for the Jeddah Market, Kingdom of Saudi Arabia

Document	Software Requirements Specification (SRS)
Version	1.0
Status	Draft for Requirements Review
Project	GiftCompass
Course	CS4176
Instructor	Passent Elkafrawy
Institution	Effat University / College of Engineering
Team members	Layan Ziyadah Kamar Bdair Sedra Al-Jundi
Date	30 September 2026

This document specifies the requirements for the GiftCompass prototype developed as a university software engineering project. It describes required system behaviour; it does not describe a deployed commercial service.

Document Control

Version	Date	Description of change	Author
0.1	—	Initial draft: introduction and overall description	Project team
0.2	—	Functional and non-functional requirements added	Project team
1.0	30 September 2026	Consolidated draft issued for requirements review	Project team

Approval. This specification is issued for requirements review. On approval at project milestone M1 (Requirements completed) it will be baselined; changes made after that point follow the change procedure described in Section 6.

Contents

Document Control	1
1 Introduction	5
1.1 Purpose	5
1.2 Intended Audience	5
1.3 Intended Use	5
1.4 Product Scope	6
1.5 Risk Definition	7
1.6 References	7
2 Overall Description	9
2.1 Product Perspective	9
2.2 Product Functions	9
2.3 User Classes and Characteristics	10
2.4 User Needs	10
2.5 Operating Environment	11
2.6 Design and Implementation Constraints	11
2.7 Assumptions and Dependencies	12
3 System Requirements	14
3.1 Functional Requirements	14
3.1.1 User and Gift Request Requirements	14
3.1.2 Recipient Questionnaire Requirements	14
3.1.3 Recipient Profile Requirements	15
3.1.4 Product Catalogue Requirements	16
3.1.5 Gift Matching and Retrieval Requirements	16
3.1.6 Filtering Requirements	16
3.1.7 Ranking and Scoring Requirements	17
3.1.8 Recommendation Explanation Requirements	18
3.1.9 Results and Refinement Requirements	18
3.1.10 Feedback Requirements	18
3.1.11 TikTok Personalisation Requirements	19
3.1.12 Security, Privacy and Consent Requirements	20
3.2 External Interface Requirements	21
3.2.1 User Interface Requirements	21
3.2.2 Hardware Interface Requirements	22
3.2.3 Software Interface Requirements	22
3.2.4 Communications Interface Requirements	22
3.3 Data Requirements	23
3.3.1 Data Entities	23
3.3.2 Data Protection Requirements	24
3.4 Security and Privacy Requirements	24
3.5 Error Handling Requirements	25
3.6 Requirements Elicitation Techniques and Justification	26
3.6.1 Elicitation of the Functional Requirements	27
3.6.2 Elicitation of the Interface, Data, Security and Error Requirements	31
3.6.3 Elicitation of the Non-Functional Requirements	33

4	System Features	37
4.1	SF-1 — Gift Request	37
4.2	SF-2 — Recipient Questionnaire	37
4.3	SF-3 — Recipient Profile Builder	38
4.4	SF-4 — TikTok Personalisation (Gift Profile)	39
4.5	SF-5 — Product Catalogue	39
4.6	SF-6 — Gift Retrieval and Matching	40
4.7	SF-7 — Filtering	41
4.8	SF-8 — Ranking and Scoring	41
4.9	SF-9 — Recommendation Explanation	42
4.10	SF-10 — Results and Refinement	42
4.11	SF-11 — Feedback	43
4.12	SF-12 — Security, Privacy and Consent	44
5	Non-Functional Requirements	45
6	Verification and Traceability	47
6.1	Verification Methods	47
6.2	Traceability Approach	47
A	Glossary	48
B	Acronyms	49
C	Requirements Traceability Matrix	50
D	Use-Case Summary	52

List of Tables

1.1	Risks affecting the requirements	7
2.1	System modules and their governing requirements	9
2.2	User needs	10
3.1	Gift request requirements (module M1)	14
3.2	Questionnaire requirements (module M2)	15
3.3	Recipient Profile requirements (module M3)	15
3.4	Product catalogue requirements (module M4)	16
3.5	Matching and retrieval requirements (module M5)	16
3.6	Filtering requirements (module M6)	17
3.7	Ranking requirements (module M7)	17
3.8	Explanation requirements (module M8)	18
3.9	Results and refinement requirements (module M9)	18
3.10	Feedback requirements (module M10)	18
3.11	TikTok Gift Profile requirements (module M11)	19
3.12	Scope of the TikTok component	20
3.13	Security, privacy and consent requirements (module M12)	20
3.14	User interface requirements	21
3.15	Software interface requirements	22
3.16	Communications interface requirements	22
3.17	Principal data entities	23
3.18	Data requirements	24
3.19	Security and privacy requirements	25
3.20	Error handling requirements	25
3.21	Elicitation technique and justification — functional requirements	27
3.22	Elicitation technique and justification — interface, data, security and error re- quirements	32
3.23	Elicitation technique and justification — non-functional requirements	33
5.1	Non-functional requirements	45
6.1	Verification methods	47
C.1	Requirements traceability matrix	50
D.1	Use-case summary	52

Chapter 1

Introduction

1.1 Purpose

This Software Requirements Specification (SRS) defines the functional and non-functional requirements of **GiftCompass**, a web-based system that recommends gifts by first building a structured profile of the person who will receive the gift, and then matching that profile against a catalogue of products available in Jeddah, Saudi Arabia, within a budget set by the giver.

The document specifies:

- the behaviour required of all twelve system modules listed in Section 2.2;
- the external interfaces through which users and other software interact with the system;
- the data the system processes, and the constraints on processing personal data;
- the non-functional qualities the system must exhibit;
- the criteria by which each requirement can later be verified.

The document does *not* specify the internal design of the system, the choice of algorithms beyond what is required for observable behaviour, the database schema, or the test cases themselves. Those belong to the Software Design Document and the test specification respectively.

1.2 Intended Audience

Project team

Uses this document as the agreed statement of what is to be built and as the basis for effort estimation and task allocation.

Instructor and project supervisor

Uses it to assess the completeness, precision and feasibility of the requirements, and as the reference against which the delivered system is judged.

Developers

Use the functional requirements and system features as the specification to implement, and the external interface requirements as the contract between modules.

UI/UX designers

Use Sections 3.2.1 and 4 to design screens, flows, bilingual presentation and error states.

Testers

Use the requirement identifiers, the acceptance criteria in Chapter 6 and the traceability matrix in Appendix C to derive test cases and demonstrate coverage.

Project evaluators

Use the document to trace a stated user need through to a requirement, a feature and a verification method.

Readers are assumed to be familiar with general software engineering terminology. Terms specific to GiftCompass are defined in Appendix A.

1.3 Intended Use

The SRS is used across the project life cycle as follows.

- **Design.** Each module in the architecture is derived from a group of functional requirements in Section 3.1; no module is introduced that does not satisfy a stated requirement.
- **Implementation.** Developers implement against requirement identifiers, and commits reference the identifiers they address.
- **Testing.** Every requirement carries a verification method (Chapter 6). Test cases are derived from requirements, not from the implementation.
- **Change control.** The document is baselined at milestone M1. Subsequent changes are recorded in the Document Control table and propagated through the traceability matrix.
- **Assessment.** The document is the reference against which the completed project is evaluated.

1.4 Product Scope

In scope

GiftCompass is a web application that:

- collects the gift context from the giver: relationship to the recipient, occasion, budget in Saudi Riyals (SAR), and the time available before the occasion;
- collects information about the recipient through a short structured questionnaire, and optionally through a consent-based TikTok Gift Profile;
- constructs a *Recipient Profile*: a structured set of weighted interests, each supported by evidence, together with dislikes and style preferences;
- retrieves candidate products from a curated catalogue of items available in Jeddah;
- applies constraint filters (budget, delivery time, age suitability, relationship appropriateness, stated dislikes) before ranking;
- ranks the surviving candidates and presents up to five recommendations;
- explains, in one or two sentences per recommendation, why each item was selected;
- allows the giver to refine the result set and to record feedback;
- links the giver to an external seller to complete the purchase.

Out of scope

GiftCompass does not:

- process payments, hold stock, arrange delivery, or handle returns — the purchase is completed on the seller's own site;
- collect data about any person without that person's consent, or scrape any social media platform;
- provide social networking, messaging between users, or user-to-user gifting;
- guarantee that a recommended product is in stock or priced as displayed at the moment of purchase; the system reports catalogue data and links to the seller for confirmation;
- operate outside the Jeddah market in this version.

Development status

This SRS specifies the complete intended system. A prototype covering the recommendation pipeline has been implemented; the requirements in this document that are not yet implemented are stated as requirements on the system to be delivered, not as descriptions of existing behaviour. Section 2.7 distinguishes confirmed capability from planned capability.

1.5 Risk Definition

The following risks affect the requirements in this document. Each is stated with its effect on the specification rather than as a general project risk.

Table 1.1: Risks affecting the requirements

ID	Risk	Effect on the specification
RK-01	Official TikTok platform access may not be obtainable for a student project.	The TikTok requirements (FR-53 to FR-61) are written so that the system remains functional without any platform integration; the questionnaire is specified as a full alternative, not a degraded mode.
RK-02	Recommendations may not match the recipient.	Requirements specify observable behaviour (constraint satisfaction, explanation, refinement, feedback) rather than an accuracy guarantee. Recommendation quality is addressed as a measured target in NFR-13.
RK-03	Catalogue prices and availability drift from the seller’s actual values.	FR-22 and FR-23 require every catalogue record to carry a verification status and date, and FR-24 requires unverified records to be excluded from results shown to end users.
RK-04	Personal data of a third party (the recipient) is processed.	Consent, purpose limitation, data minimisation and deletion are specified as functional requirements (FR-62 to FR-68) and reinforced in Section 3.4.
RK-05	Recipient information may be sparse, noisy or contradictory.	FR-16, FR-17 and FR-46 require the system to report low confidence, to exclude weakly supported candidates, and to return fewer than five results rather than pad the list.
RK-06	An AI component may produce an unsupported or invented output.	FR-14 requires every inferred interest to carry evidence; FR-40 constrains any model-based re-ranking to the candidate set already retrieved and filtered.
RK-07	Integration between modules may fail late in the schedule.	Section 3.2.3 requires each module to expose a defined interface, so modules can be integrated and tested independently.
RK-08	The system depends on external services (hosting, model inference, seller sites).	ERR-09 and ERR-10 require the system to degrade predictably and to inform the user when an external dependency is unavailable.

1.6 References

- [R1] IEEE Std 830-1998, *IEEE Recommended Practice for Software Requirements Specifications*.
- [R2] Kingdom of Saudi Arabia, *Personal Data Protection Law*, Royal Decree No. M/19, and the Implementing Regulations issued by the Saudi Data and Artificial Intelligence Authority (SDAIA).
- [R3] GiftCompass Feasibility Study, version 1.0 (project document).

- [R4] GiftCompass Architecture and Data Model Report (project document).
- [R5] GiftCompass Prototype Evaluation Report (project document).
- [R6] TikTok for Developers, Display API and Login Kit documentation; Research API eligibility criteria.

Chapter 2

Overall Description

2.1 Product Perspective

GiftCompass is a new, self-contained web application. It is not a replacement for, nor a component of, an existing system. It sits between the giver and the retail market: it does not sell products, and it does not hold inventory. Its role is to reduce a large product space to a small, justified set of suggestions, and then hand the user to a seller.

Architecturally the system is organised as a pipeline of independently replaceable modules:

Gift context + recipient information → Recipient Profile → candidate retrieval →
constraint filtering → ranking → explanation → results, refinement, feedback

Two properties of this arrangement are requirements in themselves rather than design preferences. First, constraint filtering occurs *before* ranking (FR-29), so a product that violates a stated constraint can never be ranked or displayed. Second, every module communicates through a defined data contract (Section 3.2.3), so a module may be replaced without altering the others.

2.2 Product Functions

The system comprises twelve modules. Table 2.1 lists each module, its purpose and the functional requirements that specify it.

Table 2.1: System modules and their governing requirements

#	Module	Purpose	Requirements
M1	User / Gift Request	Captures relationship, occasion, budget and timing from the giver.	FR-01–FR-06
M2	Recipient Questionnaire	Collects recipient interests through short structured questions.	FR-07–FR-11
M3	Recipient Profile Builder	Converts collected signals into weighted, evidence-backed interests.	FR-12–FR-18
M4	Product Catalogue	Stores products available in Jeddah with price, availability and suitability attributes.	FR-19–FR-24
M5	Gift Matching / Retrieval	Selects candidate products relevant to the Recipient Profile.	FR-25–FR-28
M6	Filtering	Removes candidates that violate budget, timing, age, relationship or stated dislikes.	FR-29–FR-35
M7	Ranking and Scoring	Orders the surviving candidates and enforces variety.	FR-36–FR-40
M8	Recommendation Explanation	States why each recommendation was selected.	FR-41–FR-44

#	Module	Purpose	Requirements
M9	Results and Refinement	Presents results and lets the giver adjust them without restarting.	FR-45–FR-49
M10	Feedback	Records the giver’s judgement of each recommendation.	FR-50–FR-52
M11	TikTok Gift Profile	Optional consent-based enrichment of the Recipient Profile.	FR-53–FR-61
M12	Security, Privacy and Consent	Enforces consent, minimisation, retention and deletion.	FR-62–FR-68

2.3 User Classes and Characteristics

Three user classes are recognised. No further roles are introduced, because the system neither sells products nor hosts recipient accounts.

UC-1 — Gift giver (primary user)

An individual in Jeddah choosing a gift for another person. Assumed to be comfortable using a web application on a mobile device, to read Arabic or English, and to have no technical knowledge of the system. This class performs the entire main flow and is the actor for the majority of requirements.

UC-2 — Gift recipient (consenting data subject)

The person the gift is for. This class does not use the recommendation features. Its only interaction is optional: opening a Gift Profile invitation, deciding what to share, reviewing the interests the system inferred, and approving, editing or declining. This class is the data subject for all recipient personal data and holds the rights specified in FR-62 to FR-68.

UC-3 — Catalogue maintainer (project team role)

A member of the project team responsible for adding products, verifying prices and availability, and marking records as verified. This is an internal role exercised through project tooling rather than a public administrative interface.

2.4 User Needs

The requirements in this document trace to the following user needs, identified from the problem analysis. These identifiers are used in the traceability matrix (Appendix C).

Table 2.2: User needs

ID	Need
UN-1	The giver needs suggestions based on what the recipient actually likes, rather than on the occasion or on general popularity.
UN-2	The giver needs to reach a decision quickly, without searching several stores and comparing many products.
UN-3	The giver needs every suggestion to be affordable within a budget they set before seeing results.
UN-4	The giver needs to understand why a suggestion was made, in order to trust it.

ID	Need
UN-5	The giver needs suggestions that are appropriate to the relationship and the occasion, and that will not cause awkwardness.
UN-6	The giver needs a usable result when little is known about the recipient, and when the recipient does not participate.
UN-7	The recipient needs to control whether their information is used, to see what was inferred, and to have it deleted.
UN-8	Both users need the system in Arabic or English, with prices in SAR and products obtainable in Jeddah.

2.5 Operating Environment

Client

A current desktop or mobile web browser supporting HTML5, CSS3 and JavaScript. The system is used predominantly on mobile devices and the interface is specified as mobile-first (UIR-02). No installation is required.

Server

A web application server exposing the application and its internal service endpoints over HTTPS. The prototype is developed on a JavaScript/TypeScript application framework; the deployment platform is not fixed by this specification.

Data storage

Persistent storage for the product catalogue, Recipient Profiles, consent records and feedback. A relational database is required; a relational database with vector-similarity support is the proposed candidate, but this specification does not mandate a product.

Recommendation components

The Recipient Profile Builder and the ranking components are required to behave as specified in Section 3.1. The current prototype implements them deterministically; a language-model-based profile builder and a semantic retrieval component are planned substitutions behind the same interfaces (see Section 2.7).

Network

The system requires an internet connection at both client and server. It is not specified to operate offline.

External services

Outbound links to seller websites. No inbound dependency on an external service is required for the core recommendation flow to function.

2.6 Design and Implementation Constraints

C-1 Project scope and duration

The system is developed by a student team within a single academic year. Requirements are scoped to what such a team can deliver and verify.

C-2 Platform access

The system shall not depend on access to social media data that the project cannot lawfully and reliably obtain. This constrains the TikTok module (Section 3.1.11).

C-3 Product data

Product information is curated by the project team. The system shall not present product data as live retail data unless that record has been verified (FR-24).

C-4 Legal

Processing of personal data shall be designed to support the obligations of the Saudi Personal Data Protection Law, in particular consent, purpose limitation, data minimisation and the rights of the data subject.

C-5 Language

All user-facing text shall be available in Arabic and English (UIR-01), and the system shall handle recipient information expressed in either language (FR-26).

C-6 Currency and market

All monetary values shall be expressed in SAR, and product availability shall be assessed for delivery to or collection in Jeddah.

C-7 Budget

The project operates without a commercial budget; the system shall be operable on free or low-cost hosting and shall not require paid data feeds.

C-8 Connectivity

The system requires internet connectivity and is not specified for offline operation.

2.7 Assumptions and Dependencies

This section separates what is confirmed from what is assumed. Requirements elsewhere in the document are written so that no requirement depends on an unconfirmed item.

Confirmed

- The recommendation pipeline — profile construction, retrieval, filtering, ranking and explanation — has been implemented and exercised end to end in a prototype.
- A curated demonstration catalogue of Jeddah-market products exists, spanning multiple categories and budget bands, with prices in SAR.
- A controlled interest vocabulary shared by profiles and products exists, and is the join between the two.
- The questionnaire route operates without any external platform.
- Recipient data can be obtained lawfully only with the recipient's consent; no route that bypasses consent is available to the project.

Assumed, to be confirmed

- **A-1** A hosted language-model service will be available to the team at acceptable cost for profile construction and explanation generation. If it is not, the deterministic implementation satisfies the same requirements with reduced quality.
- **A-2** A multilingual sentence-embedding model can be integrated for semantic retrieval. If it is not, lexical retrieval satisfies FR-25 to FR-28.
- **A-3** Recipients who are invited will, in some proportion of cases, choose to create a Gift Profile. The system does not depend on this (FR-59).
- **A-4** Catalogue prices can be verified against seller listings at a cadence the team can sustain. FR-22 to FR-24 are written to make the verification state explicit rather than to assume freshness.
- **A-5** Users have a device and connection adequate for a standard responsive web application.

Dependencies

- Availability of the hosting platform and database service.

- Availability of seller websites for the outbound purchase link. A broken or changed seller link affects only the final step (ERR-06).
- For the optional TikTok route: the continued availability to the recipient of the platform's own user-data export function. No dependency on a platform API is specified.

Chapter 3

System Requirements

3.1 Functional Requirements

Requirements are stated using *shall*. Each requirement specifies one observable behaviour and is written so that it can be verified by the method recorded in Appendix C. Where a requirement refers to a configurable value, the value is named as a system parameter rather than fixed in this document, so that it can be tuned without amending the specification.

3.1.1 User and Gift Request Requirements

Table 3.1: Gift request requirements (module M1)

ID	Requirement
FR-01	The system shall allow the giver to specify the relationship to the recipient by selecting exactly one value from a defined list that includes at least: friend, best friend, partner, mother, father, sister, brother, relative, colleague, classmate and other.
FR-02	The system shall allow the giver to specify the occasion by selecting exactly one value from a defined list that includes at least: birthday, graduation, anniversary, wedding, achievement, thank you, Eid, new job and no specific occasion.
FR-03	The system shall require the giver to specify a maximum budget in SAR, either by selecting a predefined band or by entering a numeric value, and shall not proceed to recommendation without it.
FR-04	The system shall allow the giver to specify the number of days remaining before the occasion, and shall treat this value as a delivery constraint (FR-31).
FR-05	The system shall validate that a budget entered directly is a positive number within a configured permitted range, and shall reject non-numeric, zero, negative and out-of-range values with an explanatory message (ERR-02).
FR-06	The system shall retain the gift context (relationship, occasion, budget, days remaining) for the duration of the session so that it is reused on refinement without being re-entered (FR-48).

3.1.2 Recipient Questionnaire Requirements

Table 3.2: Questionnaire requirements (module M2)

ID	Requirement
FR-07	The system shall provide a structured questionnaire about the recipient consisting of no more than twelve questions, of which the majority shall be single- or multiple-choice rather than free text.
FR-08	The questionnaire shall collect, at minimum: the recipient's interests, how they spend free time, their style or aesthetic preference, whether they prefer practical or sentimental gifts, and anything they would not want to receive.
FR-09	The questionnaire shall not re-request the relationship, occasion or budget already captured by module M1.
FR-10	The system shall accept a completed questionnaire in which optional questions are unanswered, and shall construct a Recipient Profile from the answers provided (FR-16).
FR-11	The system shall record each questionnaire answer as an interest signal carrying its source and the date on which it was given, for use as evidence (FR-14).

3.1.3 Recipient Profile Requirements

Table 3.3: Recipient Profile requirements (module M3)

ID	Requirement
FR-12	The system shall construct a Recipient Profile consisting of weighted interests, dislikes, style attributes and, where stated, items the recipient already owns.
FR-13	Each interest in the Recipient Profile shall be drawn from the system's controlled interest vocabulary, so that interests join directly to product attributes (FR-20).
FR-14	Each interest shall carry at least one item of evidence recording the source, the signal type and the date. An interest without evidence shall not be added to the profile.
FR-15	The system shall assign each interest a numeric weight computed from the strength and the recency of its supporting signals, such that repeated and recent evidence yields a higher weight than a single or older signal, and shall classify the weight into a strength band.
FR-16	Where the available signals are insufficient to produce at least one interest, the system shall not fabricate an interest; it shall record the profile as incomplete and inform the giver (ERR-07).
FR-17	Where a signal expresses a negative sentiment toward a topic, the system shall record that topic as a dislike and shall not record it as an interest.
FR-18	The system shall not infer, derive or store any attribute relating to religion, health, political opinion, sexual orientation, ethnicity or financial status, irrespective of what the available signals would permit.

3.1.4 Product Catalogue Requirements

Table 3.4: Product catalogue requirements (module M4)

ID	Requirement
FR-19	The catalogue shall store, for each product: an identifier, a name in Arabic and English, a category, a price in SAR, an age range, the occasions it suits, the relationships it suits, delivery time in days, availability in Jeddah, and a seller reference.
FR-20	Each product shall be annotated with one or more interest keys drawn from the same controlled vocabulary used by the Recipient Profile (FR-13).
FR-21	Each product shall carry a numeric giftability attribute and a numeric social-appropriateness (embarrassment risk) attribute, for use in filtering and ranking (FR-34, FR-37).
FR-22	Each product record shall carry a verification status of either <i>verified</i> or <i>unverified</i> , and, where verified, the date of verification.
FR-23	The system shall support updating a product's price, availability and verification status without altering its identifier or its interest annotations.
FR-24	The system shall exclude unverified product records from results presented to an end user when operating in a mode configured for end-user use, and shall label any unverified data shown in development or demonstration mode.

3.1.5 Gift Matching and Retrieval Requirements

Table 3.5: Matching and retrieval requirements (module M5)

ID	Requirement
FR-25	The system shall retrieve a bounded set of candidate products by comparing the Recipient Profile against product records, using both the shared interest vocabulary and textual similarity.
FR-26	Retrieval shall operate on product and profile text expressed in Arabic or in English, and shall not require the two to be in the same language.
FR-27	The number of candidates retrieved shall be a configurable system parameter, and retrieval shall be performed before any constraint filtering is applied.
FR-28	Where retrieval returns no candidate, the system shall report that no match was found and shall offer the giver the refinement options defined in FR-47, rather than returning an empty page without explanation (ERR-03).

3.1.6 Filtering Requirements

Table 3.6: Filtering requirements (module M6)

ID	Requirement
FR-29	The system shall apply all constraint filters to the candidate set before ranking, so that no product violating a constraint is ranked or displayed.
FR-30	The system shall exclude any product whose price in SAR exceeds the maximum budget specified by the giver.
FR-31	The system shall exclude any product whose delivery time in days exceeds the days remaining before the occasion, where the giver has supplied that value.
FR-32	The system shall exclude any product whose stated age range does not overlap the recipient's age range, where an age range is known.
FR-33	The system shall exclude any product whose suitable-relationship list does not include the relationship specified by the giver.
FR-34	The system shall exclude any product whose social-appropriateness attribute exceeds the threshold configured for the specified relationship, where a closer relationship permits a higher threshold than a professional one.
FR-35	The system shall exclude any product annotated with an interest key recorded as a dislike in the Recipient Profile, and any product matching an item recorded as already owned.

3.1.7 Ranking and Scoring Requirements

Table 3.7: Ranking requirements (module M7)

ID	Requirement
FR-36	The system shall assign each surviving candidate a score computed from: the strength of its match to the Recipient Profile, its giftability, its fit to the stated budget, its novelty, and its social-appropriateness, with the relative weighting of these terms held as a configurable system parameter.
FR-37	The scoring function shall treat higher social-appropriateness risk as reducing the score, and shall never rank such an item above an otherwise equivalent item of lower risk.
FR-38	The system shall exclude from the result set any candidate whose match to the Recipient Profile falls below a configured relevance threshold, even where this reduces the number of results returned.
FR-39	The system shall limit the number of results drawn from any single product category to a configurable maximum, so that the result set presents distinct alternatives rather than variants of one item.
FR-40	Where a language model is used to re-order the ranked candidates, it shall be permitted only to reorder identifiers already present in the filtered candidate set; any identifier it returns that is not in that set shall be discarded, and any identifier it omits shall retain its position.

3.1.8 Recommendation Explanation Requirements

Table 3.8: Explanation requirements (module M8)

ID	Requirement
FR-41	The system shall present, with each recommendation, an explanation of no more than three sentences stating why the product was selected for this recipient.
FR-42	Each explanation shall refer to at least one interest recorded in the Recipient Profile, and shall refer only to interests actually present in that profile.
FR-43	Each explanation shall state the product price in SAR in relation to the budget the giver specified.
FR-44	Explanations shall not display internal scores, weights, confidence values or model identifiers to the end user.

3.1.9 Results and Refinement Requirements

Table 3.9: Results and refinement requirements (module M9)

ID	Requirement
FR-45	The system shall present at most five recommendations per request, ordered by score.
FR-46	Where fewer than five candidates satisfy the constraints and the relevance threshold, the system shall present only those candidates and shall state that fewer results were found; it shall not add candidates that fail the threshold in order to reach five.
FR-47	The system shall provide refinement controls allowing the giver to request results that are, at minimum: cheaper, more expensive, more practical, more sentimental, more unusual, from a different category, or additional to those already shown.
FR-48	On refinement the system shall reuse the existing Recipient Profile and gift context without requiring the giver to re-enter them.
FR-49	Each recommendation shall display the product name, its price in SAR, its category, the seller, and a control that opens the seller's page for that product.

3.1.10 Feedback Requirements

Table 3.10: Feedback requirements (module M10)

ID	Requirement
FR-50	The system shall allow the giver to record a positive or negative judgement on each individual recommendation.

ID	Requirement
FR-51	Where a negative judgement is recorded, the system shall allow the giver to select a reason from a defined list including at least: too expensive, wrong style, already owned, wrong category, and not personal enough.
FR-52	The system shall store feedback with a reference to the recommendation and the request that produced it, so that recommendation quality can later be analysed (NFR-13).

3.1.11 TikTok Personalisation Requirements

The requirements below are written so that the system functions fully without any TikTok integration. Table 3.12 distinguishes what the prototype demonstrates from what a production deployment would additionally require.

Table 3.11: TikTok Gift Profile requirements (module M11)

ID	Requirement
FR-53	The system shall allow the giver to generate a Gift Profile invitation, in the form of a shareable link addressed to the recipient, without transmitting any recipient personal data at the point of generation.
FR-54	The system shall present the recipient, on opening the invitation, with an explanation of what information is requested, the purpose for which it will be used, and a clearly available option to decline.
FR-55	The system shall accept recipient-supplied TikTok information only where the recipient has supplied it themselves and has recorded consent; the system shall provide no function that retrieves data about a recipient from any platform without that recipient's action.
FR-56	The system shall extract, from information the recipient supplies, only those signals that map to the controlled interest vocabulary, and shall discard content that does not, including private messages, location data, contact lists and device or login information.
FR-57	The system shall present the recipient with the complete list of interests it has inferred before any of them is stored, and shall allow the recipient to remove any entry.
FR-58	The system shall store a Recipient Profile derived from recipient-supplied information only after the recipient has explicitly approved the reviewed list.
FR-59	Where the recipient declines, does not respond, or supplies information that cannot be processed, the system shall construct the Recipient Profile from the questionnaire answers alone and shall continue to produce recommendations (ERR-07, ERR-08).
FR-60	The system shall weight interests derived from recipient-supplied signals according to signal strength and recency on the same basis as questionnaire answers (FR-15), so that both routes produce a profile of the same structure.
FR-61	The system shall delete the recipient-supplied source material once the Recipient Profile has been constructed, retaining only the approved profile, and shall record that the deletion has occurred.

Table 3.12: Scope of the TikTok component

Aspect	Position
A. Demonstrated by the prototype	Consent-based flow in which the recipient supplies their own information, reviews the inferred interests, approves or removes them, and has the source material deleted. Interest extraction and profile construction from those signals. Continued operation when the route is not used.
B. Requires official platform integration	Direct retrieval of a recipient's activity through a platform interface. This is not assumed by any requirement in this document. Any such integration would be an additional source feeding the same interest extraction specified in FR-56, and would be subject to the platform's own authorisation and terms.

3.1.12 Security, Privacy and Consent Requirements

Table 3.13: Security, privacy and consent requirements (module M12)

ID	Requirement
FR-62	The system shall record, for every Recipient Profile, the party who provided the basis for processing, the purpose, the sources covered and the date. The record shall distinguish two cases: (a) <i>recipient-provided</i> , where the recipient supplied information about themselves and gave consent; and (b) <i>giver-provided</i> , where the giver supplied their own knowledge of the recipient through the questionnaire. The two cases shall be distinguishable for every profile.
FR-63	The system shall refuse to use a Recipient Profile that does not carry a valid record under FR-62, and shall report the refusal rather than proceeding with recommendation. A profile marked <i>recipient-provided</i> shall additionally be refused where the recipient has not completed the approval step required by FR-58.
FR-64	The system shall process personal data only for the purpose of producing gift recommendations, and shall provide no function that uses it for another purpose.
FR-65	The system shall collect only those data items required by the modules specified in this document, and shall provide no function that requests unrelated personal information.
FR-66	The system shall assign each Recipient Profile a retention expiry, shall not use a profile after its expiry, and shall delete expired profiles. The retention period shall be a configurable system parameter set by the project team.
FR-67	The system shall allow the recipient to request deletion of their Recipient Profile, and shall delete it together with its evidence records on such a request.
FR-68	The system shall present its consent and privacy information in both Arabic and English (UIR-01).

Note on the two processing bases. The questionnaire route processes the giver's own

description of someone they know, which is the minimum information needed to produce a recommendation and is supplied by the person making the request. The Gift Profile route processes information originating from the recipient, and is therefore conditional on that recipient's consent and explicit approval (FR-55, FR-58). The system keeps the two cases distinguishable (FR-62) so that the correct rules can be applied to each, and so that a deletion request can be satisfied in either case (FR-67). This document states system requirements intended to support the obligations described in Section 3.4; it does not itself determine the legal basis for processing, which is assessed separately by the project team.

3.2 External Interface Requirements

3.2.1 User Interface Requirements

Table 3.14: User interface requirements

ID	Requirement
UIR-01	All user-facing text, including labels, validation messages, consent text and recommendation explanations, shall be available in Arabic and in English, and the user shall be able to switch language at any point without losing entered data.
UIR-02	The interface shall be responsive and shall be usable without horizontal scrolling on a viewport 360 pixels wide, this being the mobile-first case.
UIR-03	The gift request flow shall present relationship, occasion and budget as discrete steps with the current position in the flow visible, and shall allow the user to return to a previous step without losing entered values.
UIR-04	The questionnaire shall present one question or one small group of related questions at a time, shall indicate progress, and shall allow the user to skip an optional question.
UIR-05	The TikTok Gift Profile flow shall present, in order: an explanation of purpose, the consent decision, the supply of information, the review of inferred interests, and the approval step; and shall present the decline option with the same prominence as the accept option.
UIR-06	The results page shall display each recommendation with its image where available, its name, its price in SAR, its category, its seller and its explanation, in a consistent layout for all results.
UIR-07	Refinement controls shall be visible on the results page without navigation away from it, and their effect shall be described in plain language rather than by internal parameter names.
UIR-08	Validation messages shall identify the field concerned, state what is wrong, and state what an acceptable value is; they shall not display internal error codes or stack traces to the user.
UIR-09	Consent and privacy screens shall state what is collected, the purpose, the retention position and how to request deletion, in plain language in both supported languages.
UIR-10	Text and interactive elements shall meet a minimum contrast ratio of 4.5:1 against their background, and all interactive elements shall be reachable and operable by keyboard (NFR-10).

3.2.2 Hardware Interface Requirements

The system requires no special-purpose hardware. It does not interface with card readers, printers, scanners, sensors or embedded devices, and it does not require the camera, microphone, location services or any other device peripheral. The only hardware requirement is a general-purpose computer or mobile device capable of running a current web browser and connecting to the internet.

3.2.3 Software Interface Requirements

Table 3.15: Software interface requirements

ID	Requirement
SIR-01	The client shall operate in current versions of the major web browsers on desktop and mobile, without requiring a plug-in or extension.
SIR-02	The application server shall expose the recommendation function through a defined request/response interface accepting a Recipient Profile reference and a gift context, and returning an ordered set of recommendations with explanations.
SIR-03	Each pipeline module (M3, M5, M6, M7, M8) shall expose a defined interface with a documented input and output contract, so that a module may be replaced without modification to the others.
SIR-04	The Recipient Profile and the product record shall each conform to a published, machine-readable schema, and the system shall reject any instance that does not validate against its schema.
SIR-05	The system shall persist the product catalogue, Recipient Profiles, consent records and feedback in a database, and shall not depend on in-memory state for data that must survive a restart.
SIR-06	Where a language-model service is used, the system shall access it through an interface that permits the service to be replaced or disabled, and shall validate its output against the applicable schema before use (FR-40).
SIR-07	The system shall link to seller product pages by outbound URL only, and shall not require any programmatic interface to a seller system.

3.2.4 Communications Interface Requirements

Table 3.16: Communications interface requirements

ID	Requirement
CIR-01	All communication between the client and the server shall use HTTPS. The system shall not transmit personal data over an unencrypted channel.
CIR-02	Communication between the client and server shall use a structured data format over HTTP, with request and response shapes defined by the interfaces in SIR-02 and SIR-03.

ID	Requirement
CIR-03	The Gift Profile invitation shall be delivered as a URL that the giver may share through any channel of their choosing; the system shall not require access to the giver's contacts or messaging accounts.
CIR-04	Where an outbound request to an external service fails or does not complete within a configured timeout, the system shall handle the failure as specified in ERR-09 rather than leaving the request pending indefinitely.

3.3 Data Requirements

3.3.1 Data Entities

Table 3.17 lists the entities the system processes, the information each holds and the reason that information is required. No entity holds a data item that is not used by a requirement in this document; this is the data minimisation position stated in FR-65.

Table 3.17: Principal data entities

Entity	Information held	Why it is required
Gift Request	Identifier, relationship, occasion, budget in SAR, days until the occasion, delivery city.	Provides the constraints applied in filtering (FR-30–FR-34) and the context used in explanations (FR-43).
Recipient Profile	Identifier, coarse age range, language preference, interests, dislikes, style attributes, items already owned, completeness indicator, expiry.	The basis of matching and ranking. Deliberately holds no name, contact detail or account identifier for the recipient.
Interest	Interest key from the controlled vocabulary, weight, strength band, giftability.	Joins the Recipient Profile to product records (FR-13, FR-20).
Evidence	Source, signal type, date, short excerpt, count.	Supports FR-14 (no interest without evidence) and allows the recipient to review what was inferred (FR-57).
Dislike	Interest key, reason, source.	Used as an exclusion in filtering (FR-35).
Product	Identifier, bilingual name, category, interest keys, price in SAR, age range, suitable occasions, suitable relationships, giftability, social-appropriateness, delivery days, availability, seller reference, verification status and date.	The candidate set for retrieval, filtering and ranking.

Entity	Information held	Why it is required
Recommendation	Request reference, product reference, rank, score components, explanation text.	Presented to the giver and retained so feedback can be attributed (FR-52).
Feedback	Recommendation reference, judgement, reason code, date.	Supports later analysis of recommendation quality (NFR-13).
Consent Record	Party giving consent, purpose, sources covered, date given, review status, deletion status, expiry.	Required by FR-62 and checked by FR-63 before any profile is used.

3.3.2 Data Protection Requirements

Table 3.18: Data requirements

ID	Requirement
DR-01	The Recipient Profile shall not contain the recipient's name, telephone number, email address, postal address or social media account identifier.
DR-02	The system shall store the recipient's age only as a coarse range and never as a date of birth.
DR-03	The system shall hold no field, and shall create no derived field, representing religion, health, political opinion, sexual orientation, ethnicity or financial status (FR-18).
DR-04	Every entity holding personal data shall be linked to a consent record, and the system shall be able to identify all personal data associated with a given consent record in order to satisfy a deletion request (FR-67).
DR-05	Source material supplied by a recipient shall be deleted once the Recipient Profile has been constructed; only the approved profile shall persist (FR-61).
DR-06	Every Recipient Profile shall carry an expiry, and the system shall not use an expired profile (FR-66).
DR-07	The product catalogue shall carry no personal data.
DR-08	Feedback records shall reference a recommendation and shall not store free-text entered by the user about any identifiable person.

3.4 Security and Privacy Requirements

These requirements are stated as system requirements intended to support the obligations of the Saudi Personal Data Protection Law. Writing them does not by itself establish legal compliance; compliance is assessed separately by the project team with appropriate review.

Table 3.19: Security and privacy requirements

ID	Requirement
SEC-01	The system shall transmit all data between client and server over HTTPS (CIR-01), and shall reject requests received over an unencrypted channel.
SEC-02	The system shall validate and sanitise all input received from a client before processing or storing it, and shall reject input that does not conform to the expected type, range or format.
SEC-03	The system shall construct all database queries in a manner that prevents the injection of executable statements through user-supplied values.
SEC-04	The system shall encode all user-supplied and recipient-supplied content before rendering it, so that submitted content cannot execute in another user's browser.
SEC-05	Access to a Recipient Profile shall be restricted to the gift request that it belongs to; the system shall provide no function that lists or retrieves profiles belonging to other requests.
SEC-06	A Gift Profile invitation link shall use an unguessable identifier, shall be usable only for the purpose of creating the profile it refers to, and shall expire after a configured period.
SEC-07	Where a user account facility is provided, the system shall store authentication credentials only in salted, hashed form, and shall never store or log a password in recoverable form. Where no account facility is provided, the system shall operate without collecting credentials at all.
SEC-08	Recipient-supplied source material shall be processed in a manner that minimises exposure, shall not be retained beyond profile construction (FR-61), and shall not be written to application logs.
SEC-09	Error responses presented to a user shall not disclose stack traces, database messages, file paths, internal identifiers or configuration values (UIR-08, ERR-11).
SEC-10	The system shall log security-relevant events, including consent given, profile deletion and failed validation, without recording the personal data involved in those events.

3.5 Error Handling Requirements

Table 3.20: Error handling requirements

ID	Requirement
ERR-01	Where a required input is missing, the system shall identify the specific field, shall not proceed, and shall preserve all other values the user has already entered.
ERR-02	Where the budget entered is non-numeric, zero, negative or outside the permitted range, the system shall reject it, state the acceptable range, and allow immediate correction (FR-05).

ID	Requirement
ERR-03	Where no product satisfies the constraints, the system shall state which constraint eliminated the candidates and shall offer at least one specific relaxation, such as raising the budget or extending the delivery window (FR-28).
ERR-04	Where a product becomes unavailable between retrieval and display, the system shall omit it from the results rather than display an item that cannot be obtained.
ERR-05	Where a product's price has changed since verification, the system shall present the price as recorded together with its verification date, and shall direct the user to the seller for the current price.
ERR-06	Where a seller link cannot be opened, the system shall inform the user and shall continue to display the remaining recommendations.
ERR-07	Where recipient information is insufficient to construct a usable profile, the system shall state this, shall not fabricate interests, and shall offer the questionnaire as the route to continue (FR-16).
ERR-08	Where recipient-supplied TikTok information cannot be read or yields no usable signal, the system shall inform the recipient, shall retain nothing from the attempt, and shall allow the questionnaire route to proceed (FR-59).
ERR-09	Where an external service fails or exceeds its configured timeout, the system shall fall back to the behaviour that does not require that service where one exists, and shall otherwise inform the user that the function is temporarily unavailable.
ERR-10	Where the database or another essential internal service is unavailable, the system shall present a service-unavailable message and shall not present partial or inconsistent results as though they were complete.
ERR-11	The system shall handle any unanticipated error without terminating the user's session, shall record the diagnostic detail server-side, and shall present the user with a plain-language message only (SEC-09).

3.6 Requirements Elicitation Techniques and Justification

This section records, for each group of requirements in this document, the elicitation technique the requirement was derived from and the reason that technique was the appropriate one for it. It introduces no requirement and alters none: Sections 3.1 to 3.5 and Table 5.1 remain the statement of what the system shall do. Requirements are grouped where one technique and one justification apply to all of them, and listed separately where they do not.

Two statuses are used, and they are kept distinct throughout so that no activity is claimed that has not taken place.

Applied

The technique has been carried out and the requirement is derived from its result. The applied techniques are: analysis of research literature; analysis of regulatory and legal texts; analysis of platform developer documentation; analysis of published technical, security and accessibility guidance; analysis of the project's own documents [R3]–[R5]; benchmarking of comparable products and interfaces; and exploratory prototyping together with the prototype evaluation.

Planned for validation

The requirement has been derived by an applied technique and the named technique is scheduled to confirm or correct it before the requirement is baselined. **No user interview, survey, focus group or usability session has been conducted at the date of this document, and no requirement stated here rests on data from one.**

Where a row names both, the applied technique is the source of the requirement and the planned technique is the means by which it will be validated.

3.6.1 Elicitation of the Functional Requirements

Table 3.21: Elicitation technique and justification — functional requirements

Requirements	Elicitation technique	Justification
FR-01 – FR-06	Benchmarking and competitor analysis (<i>applied</i>)	The three inputs that open the flow are a settled interaction pattern. Marketplaces, occasion-based gift guides and retailer gift finders were examined to establish which fields such a tool consistently asks for and which value lists are conventional. Benchmarking was the right source because the pattern already exists in comparable products, so the fields could be fixed from observed practice rather than from speculation about how a giver would behave.
FR-07 – FR-11	Exploratory prototyping (<i>applied</i>) User interviews and a short survey of givers (<i>planned for validation</i>)	The question set was derived by building the questionnaire route and observing which answers produced a usable profile; the twelve-question ceiling (FR-07), the tolerance of unanswered questions (FR-10) and the prohibition on re-asking module M1 (FR-09) all follow from that. Because the wording of a question determines the quality of the answer, and no giver outside the team has yet completed the questionnaire, interviews and a short survey are planned to validate wording and ordering before the set is frozen.

Requirements	Elicitation technique	Justification
FR-12 – FR-17	Research literature analysis (<i>applied</i>), made concrete by prototyping	The structure of the profile — evidence attached to every interest, a weight derived from signal strength and recency, and a strength band — is taken from published work on gift recommendation and on preference modelling from behavioural signals, which is where the treatment of signal strength and recency decay is established. Literature analysis suited this group because no stakeholder can state how a preference weight ought to be computed. Prototyping then fixed the concrete values and produced the rule that an interest is never fabricated (FR-16), from observed sparse-input cases.
FR-18	Regulatory and legal document analysis (<i>applied</i>), supported by research literature	The prohibited attributes are those the Personal Data Protection Law and its implementing regulations [R2] treat as sensitive, so the boundary is set by law and is not open to stakeholder preference; legal-text analysis is therefore the only valid source. Published research showing that such attributes can be inferred from ordinary digital traces is the reason the prohibition is stated as a requirement on the system rather than left to implementation judgement.
FR-19 – FR-21	Document analysis of seller listings, carried out while constructing the catalogue (<i>applied</i>)	The mandatory field list was derived by examining the product information Jeddah sellers actually publish, and only attributes obtainable for every item were made mandatory. Document analysis was appropriate because the binding constraint is what data exists in the market, which is directly observable and would not be answered reliably by asking a user.
FR-22 – FR-24	Analysis of the project's own risk and feasibility documents (<i>applied</i>)	These requirements answer risk RK-03, catalogue drift, recorded in the feasibility study [R3]. The need was elicited by analysing that risk record rather than from a user, because a user cannot observe that a displayed price has gone stale; the requirement therefore makes the verification state explicit instead of assuming freshness.

Requirements	Elicitation technique	Justification
FR-25 – FR-28	Exploratory prototyping (<i>applied</i>)	The retrieval order — retrieve first, filter afterwards — the bounded candidate count and the obligation never to return an unexplained empty page were established by running the pipeline over the demonstration catalogue, including constraint combinations that eliminate every candidate. These are internal behaviours on which no external stakeholder holds an opinion, so observation of a working implementation was the only source that could settle them.
FR-29 – FR-33, FR-35	Document analysis of the gift context and the catalogue schema (<i>applied</i>)	Each of these exclusions is the direct consequence of a value already captured in module M1 or recorded in the Recipient Profile: budget, days remaining, age range, relationship, stated dislikes and items already owned. They were derived by tracing each captured field to the decision it must control, which is a documentary exercise; no elicitation from users was needed to establish that a gift over budget, or arriving after the occasion, is unusable.
FR-34	Research literature analysis (<i>applied</i>) Focus group with participants from the Jeddah market (<i>planned for validation</i>)	The idea of a social-appropriateness risk that varies with the closeness of the relationship is taken from published gift-recommendation research. That literature does not supply thresholds for this market: what is acceptable from a close friend but not from a colleague is culturally specific, and a focus group is the technique that surfaces shared social norms rather than individual taste. The requirement therefore fixes only that the threshold is relationship-dependent and configurable, and the values used in the prototype are provisional until that group is held.
FR-36 – FR-40	Research literature analysis (<i>applied</i>), tuned by prototype evaluation	Multi-criteria scoring that combines match strength, giftability, budget fit and social-appropriateness follows published gift-recommender work. The constraint on model-based re-ordering (FR-40) follows from published analysis of large language models used for recommendation, which documents the invention of item identifiers absent from the candidate set. Literature identified that failure mode before the project could encounter it, which is why it is specified in advance rather than discovered in testing.

Requirements	Elicitation technique	Justification
FR-41 – FR-44	Prototype evaluation <i>(applied)</i> User interviews <i>(planned for validation)</i>	The three-sentence limit and the obligation to name an interest actually present in the profile were derived from the prototype evaluation [R5], in which generated explanations were rated alongside the products they justified. FR-44 follows from the same exercise: the score components the prototype exposes are meaningful for development only. Whether an explanation increases a giver's confidence in a suggestion is a question about the user, so interviews are planned to validate it.
FR-45 – FR-49	Benchmarking of comparable interfaces <i>(applied)</i> Prototype evaluation <i>(applied)</i>	The refinement vocabulary — cheaper, more expensive, more practical, more sentimental, more unusual, different category — was drawn from the filter and sort controls comparable shopping interfaces expose, then reduced to the operations this pipeline can actually perform. The rule that a short result set is never padded (FR-46) came from the evaluation, where a weakly matched item included to fill the set was rated poor; a relevance gate (FR-38) was introduced in response.
FR-50 – FR-52	Analysis of the project's evaluation design <i>(applied)</i>	These fields exist to supply the measurement NFR-13 requires. They were elicited by working backwards from the evaluation method recorded in [R5] to the data that method consumes, rather than from a user asking to rate results. Document analysis was appropriate because the purpose of the requirement is internal measurement, not a user-facing function.
FR-53, FR-54, FR-57, FR-58, FR-61	Regulatory and legal document analysis <i>(applied)</i>	Each of these steps — an invitation carrying no recipient data, a stated purpose with a refusal offered as prominently as acceptance, review of every inferred interest before storage, explicit approval, and deletion of the source material afterwards — implements a specific obligation of the Personal Data Protection Law [R2] on consent, transparency and data minimisation. Those obligations are not negotiable with users, so the legal text is the authoritative source and a user-facing technique would have been the wrong instrument.

Requirements	Elicitation technique	Justification
FR-55, FR-56	Analysis of platform developer documentation (<i>applied</i>)	The TikTok developer documentation [R6] — the Display API, the Login Kit scopes and the eligibility criteria of the Research API — was analysed to establish what a project of this kind may lawfully obtain. It established that no route exists for retrieving a third party's activity without that person's own action, which is why FR-55 is written as a prohibition, and it established what a user-initiated export contains, which is the basis of the exclusion list in FR-56.
FR-59, FR-60	Exploratory prototyping (<i>applied</i>)	That the system continues to function when the recipient declines, and that both routes produce a profile of the same structure, were established by running the pipeline with and without recipient-supplied signals and comparing the profiles produced. Prototyping is the technique that demonstrates independence between components; no interview or survey could have shown it.
FR-62 – FR-68	Regulatory and legal document analysis (<i>applied</i>), with analysis of the project's own documents	The consent record, purpose limitation, data minimisation, retention expiry and deletion on request are each obligations drawn from the Personal Data Protection Law and its implementing regulations [R2]. The two-case distinction in FR-62 was obtained by applying those texts to the two routes this system actually offers, which required reading the legal text against the project's own architecture record [R4]. The bilingual requirement (FR-68) additionally follows from constraint C-5.

3.6.2 Elicitation of the Interface, Data, Security and Error Requirements

Table 3.22: Elicitation technique and justification — interface, data, security and error requirements

Requirements	Elicitation technique	Justification
UIR-01 – UIR-10	Benchmarking of comparable interfaces and analysis of published accessibility guidance (<i>applied</i>) Usability sessions with structured observation (<i>planned for validation</i>)	The step structure, the progress indication and the consistent results layout were derived by examining how comparable multi-step and results-based interfaces are built. The contrast and keyboard criteria in UIR-10 come from published accessibility guidance, which states them numerically and so makes them specifiable and checkable. Whether the flow is actually understood is a matter of observed behaviour rather than of design intent, so usability sessions are planned; none has been held.
SIR-01 – SIR-07	Analysis of the project’s architecture documentation (<i>applied</i>), confirmed by prototyping	The module contracts, the published schemas and the replaceability of the language-model service were derived from the architecture and data-model report [R4] and confirmed by implementing the pipeline as separate modules. These requirements concern internal structure, which is recorded by the team and held by no external stakeholder.
CIR-01 – CIR-04	Analysis of published technical standards and platform documentation (<i>applied</i>)	Transport encryption, a structured request and response format, and timeout handling follow established web practice as documented in the relevant specifications and in hosting-platform documentation. The share-by-URL position in CIR-03 follows from the same platform-documentation analysis that produced FR-53: no access to the giver’s contacts is needed, so none is requested.
DR-01 – DR-08	Regulatory and legal document analysis (<i>applied</i>), applied to the data model	Each restriction maps an obligation in [R2] onto a specific entity in Table 3.17: no direct identifier, an age range in place of a date of birth, no sensitive attribute, a consent link that makes a deletion request satisfiable, and an expiry. The requirements were elicited by walking the stored data model against the legal text field by field, which is the only technique that can show that a stored field has no lawful purpose.

Requirements	Elicitation technique	Justification
SEC-01 – SEC-10	Analysis of published secure-development guidance (<i>applied</i>), with regulatory analysis	Input validation, safe query construction, output encoding, credential storage and the suppression of diagnostic detail are standard controls documented in established secure-development guidance. The access restriction, the unguessable invitation link and the logging rule additionally implement the confidentiality expectations of [R2]. Security requirements are elicited from guidance and law because users do not state them and their absence is not visible in normal operation.
ERR-01 – ERR-11	Exploratory prototyping and analysis of the project risk register (<i>applied</i>)	The list was assembled from two sources. The first is the conditions encountered while running the pipeline over the demonstration catalogue: an empty candidate set, a profile with too few signals to be usable, and a candidate eliminated by a constraint the user could relax. The second is the failure modes already recorded as risks RK-03, RK-05 and RK-08, together with the validation rules stated in module M1. Observing a system fail is the most reliable way to enumerate the states it must handle; the risk register supplies the failures that have not yet occurred.

3.6.3 Elicitation of the Non-Functional Requirements

Table 3.23: Elicitation technique and justification — non-functional requirements

Requirements	Elicitation technique	Justification
NFR-01	Exploratory prototyping (<i>applied</i>) Instrumented measurement (<i>planned for validation</i>)	The response target was derived from the structure of the implemented pipeline — the number of stages a request passes through and the external model call each one may make — which prototyping made concrete. The systematic timing over at least twenty representative requests that the requirement itself specifies has not yet been carried out; it is the means by which the figure will be validated or corrected.

Requirements	Elicitation technique	Justification
NFR-02	Usability testing with structured observation <i>(planned for validation)</i>	The requirement names a completion time, an unassisted success rate and a participant count: it specifies the study to be run, and nothing is presented as already observed. Observation is the correct technique because what is being measured is whether a first-time user completes the flow, which users cannot reliably report about themselves. The three-minute figure is a target derived from the length of the implemented flow.
NFR-03	Document analysis of the error requirements <i>(applied)</i>	The reliability criterion is defined directly over the conditions enumerated in Section 3.5, so it was elicited by analysing that list rather than independently of it. Deriving it this way keeps the quality attribute checkable: every condition already has a defined behaviour to test against.
NFR-04	Analysis of the project constraints <i>(applied)</i>	No availability figure is claimed, because constraints C-1 and C-7 fix the system as a student prototype on free or low-cost hosting. The requirement was elicited by reading those constraints; benchmarking against commercial availability targets would have produced a number the project cannot honour.
NFR-05	Regulatory analysis and analysis of secure-development guidance <i>(applied)</i>	The requirement defers to SEC-01 to SEC-10, which were themselves elicited from published guidance and legal text. Stating it by reference avoids a second, weaker restatement of the same controls and leaves one verifiable source for them.
NFR-06	Regulatory and legal document analysis <i>(applied)</i> , with inspection of the data model	Data minimisation and the prohibited-attribute rule are obligations drawn from [R2]. The checkable form of the requirement was obtained by mapping those obligations onto the entity list in Table 3.17, a documentary exercise on the system's own design rather than an elicitation from any stakeholder.
NFR-07	Analysis of the architecture documentation <i>(applied)</i> , confirmed by prototyping	Module replaceability is an internal property stated in the architecture report [R4] and demonstrated during development by substituting one implementation of a pipeline module for another. It is elicited from the design record because no user ever experiences it directly.

Requirements	Elicitation technique	Justification
NFR-08	Analysis extrapolated from the prototype <i>(applied)</i>	The catalogue size and concurrency figures were obtained by extending the NFR-01 target to the largest catalogue this project would realistically curate, the demonstration catalogue being an order of magnitude smaller. They were not adopted from an industry figure, which the prototype could not be tested against; the requirement states explicitly that nothing is specified beyond that point.
NFR-09	Benchmarking of common platform-support practice <i>(applied)</i>	The support matrix — the current and immediately preceding release of three major browsers, on desktop and mobile — is the conventional baseline in web practice, adopted because it is both achievable and checkable by executing the main flow on each. Confirming it against usage statistics for the Jeddah market is planned before the requirement is baselined.
NFR-10	Analysis of published accessibility guidance <i>(applied)</i> Observation with assistive technology <i>(planned for validation)</i>	The contrast ratio and keyboard-operability criteria are taken from published accessibility guidance, which states them in a form an automated check can verify. Conformance to guidance is not the same as usability for a disabled user, which is why observation is named here as a planned validation rather than claimed as a result.
NFR-11	Analysis of the project constraints <i>(applied)</i> Review by native speakers <i>(planned for validation)</i>	Arabic and English coverage, right-to-left layout and display in SAR follow from constraints C-5 and C-6, which fix the market the system is built for. Constraint analysis establishes what must be present; whether the Arabic reads naturally is a judgement only a native speaker can give, and that review is planned rather than performed.
NFR-12	Document analysis of the published schemas <i>(applied)</i> , confirmed by prototyping	The requirement was elicited from the schemas the project already publishes for the Recipient Profile and the product record (SIR-04): once a schema exists, validate-before-store is the criterion that makes it meaningful. It was confirmed in development by validating the demonstration catalogue against its schema and rejecting the records that failed.

Requirements	Elicitation technique	Justification
NFR-13	Prototype evaluation (<i>applied</i>), first round completed	An evaluation of this form has been carried out once: recommendations for a set of test recipients were rated for relevance and for social appropriateness by a single human assessor, and the result was reported as measured. The requirement specifies the fuller measurement, with more than one independent assessor, to be repeated before release. No figure in this document is presented as the outcome of a larger study than the one conducted.

Chapter 4

System Features

Each feature below is described with its purpose, actors, preconditions, flows, governing requirements, inputs, outputs and constraints. Feature identifiers SF-1 to SF-12 are used in the traceability matrix (Appendix C).

4.1 SF-1 — Gift Request

Description

Captures the context of the gift: who it is for, why, how much may be spent and by when.

Purpose

Establishes the constraints that all later filtering and ranking must respect, before any product is considered.

Actors

Gift giver (UC-1).

Preconditions

The user has opened the application. No account is required.

Main flow

(1) The user starts a gift request. (2) The user selects the relationship. (3) The user selects the occasion. (4) The user sets a budget in SAR. (5) The user optionally states the days remaining before the occasion. (6) The system stores the gift context and proceeds to recipient information (SF-2 or SF-4).

Alternative and exception flows

(a) The user enters an invalid budget: ERR-02 applies and the step is repeated. (b) The user returns to an earlier step: UIR-03 requires previously entered values to be preserved. (c) The user abandons the flow: no personal data has been collected at this point.

Requirements

FR-01–FR-06, UIR-03, ERR-01, ERR-02.

Inputs

Relationship, occasion, budget (SAR), days remaining.

Outputs

A stored gift context for the session.

Constraints

The budget is mandatory (FR-03). Exactly one relationship and one occasion may be selected (FR-01, FR-02).

4.2 SF-2 — Recipient Questionnaire

Description

A short structured questionnaire about the recipient, answered by the giver.

Purpose

Provides the always-available route to recipient information, requiring no participation by the recipient and no external platform.

Actors

Gift giver (UC-1).

Preconditions

A gift context exists (SF-1).

Main flow

(1) The system presents the questions. (2) The user answers. (3) The system records each answer as an interest signal with source and date. (4) The system passes the signals to the Recipient Profile Builder (SF-3).

Alternative and exception flows

(a) The user skips optional questions: FR-10 requires the profile to be built from what was given. (b) Too few answers to yield any interest: ERR-07 applies and the user is invited to add more detail. (c) The user has also completed SF-4: both signal sets feed the same profile (FR-60).

Requirements

FR-07–FR-11, UIR-04, ERR-07.

Inputs

Answers about interests, free time, style, practical or sentimental preference, and anything unwanted.

Outputs

A set of interest signals.

Constraints

At most twelve questions, mostly closed-form (FR-07). No re-asking of relationship, occasion or budget (FR-09).

4.3 SF-3 — Recipient Profile Builder

Description

Converts interest signals, from whatever source, into a single structured Recipient Profile.

Purpose

Produces one profile format for the whole system, so that the rest of the pipeline is independent of how the information was collected.

Actors

System (invoked after SF-2 or SF-4).

Preconditions

At least one interest signal exists, with a consent record where the signal came from the recipient.

Main flow

(1) The system maps each signal to the controlled interest vocabulary. (2) It determines sentiment, routing negative mentions to dislikes. (3) It computes a weight per interest from signal strength and recency. (4) It classifies each weight into a strength band. (5) It attaches the supporting evidence to each interest. (6) It records the profile with a completeness indicator and an expiry.

Alternative and exception flows

(a) No signal maps to the vocabulary: FR-16 requires the profile to be recorded as incomplete, with no invented interest. (b) A topic appears with both positive and negative sentiment: FR-17 gives precedence to the dislike, and the topic is excluded from recommendation. (c) A signal would imply a prohibited attribute: FR-18 requires it to be discarded.

Requirements

FR-12–FR-18, FR-60, DR-01–DR-03, DR-06.

Inputs

Interest signals with source, type and date.

Outputs

A Recipient Profile: weighted interests with evidence, dislikes, style attributes, completeness, expiry.

Constraints

No interest without evidence (FR-14). No prohibited attribute, under any circumstances (FR-18).

4.4 SF-4 — TikTok Personalisation (Gift Profile)

Description

An optional route in which the recipient supplies their own TikTok-related information, reviews what the system inferred, and approves it.

Purpose

Enriches the Recipient Profile with interest signals the giver may not know, without the system obtaining data about anyone without their action and consent.

Actors

Gift giver (UC-1) creates the invitation; gift recipient (UC-2) decides and supplies.

Preconditions

A gift request exists. The recipient has received the invitation link.

Main flow

(1) The giver generates an invitation link. (2) The recipient opens it and is shown the purpose and the decline option. (3) The recipient consents. (4) The recipient supplies their information. (5) The system extracts only signals mapping to the interest vocabulary. (6) The system presents the inferred interests for review. (7) The recipient removes any entry and approves. (8) The system builds the profile (SF-3) and deletes the source material.

Alternative and exception flows

(a) The recipient declines or does not respond: FR-59 requires the questionnaire route to proceed. (b) The information cannot be processed: ERR-08 applies, nothing is retained, and the questionnaire route proceeds. (c) The recipient removes every inferred interest: the profile is treated as having no signals from this source. (d) The recipient later requests deletion: FR-67 applies.

Requirements

FR-53–FR-61, FR-62–FR-68, SEC-06, SEC-08, ERR-08, UIR-05.

Inputs

Recipient consent; recipient-supplied information.

Outputs

An approved set of interests contributing to the Recipient Profile; a consent record; confirmation that source material was deleted.

Constraints

No data is obtained about a recipient without that recipient's own action (FR-55). Nothing is stored before approval (FR-58). The system remains fully functional if this feature is never used (FR-59).

4.5 SF-5 — Product Catalogue

Description

The curated set of products available in the Jeddah market, with the attributes required for matching, filtering and ranking.

Purpose

Provides the candidate space. Without accurate attributes the rest of the pipeline cannot enforce its constraints.

Actors

Catalogue maintainer (UC-3); system (read access).

Preconditions

None for reading. Write access is restricted to the maintainer role.

Main flow

(1) The maintainer adds or edits a product record. (2) The maintainer supplies interest keys from the controlled vocabulary. (3) The maintainer verifies price and availability against the seller. (4) The maintainer marks the record verified with a date. (5) The record becomes eligible for end-user results.

Alternative and exception flows

(a) A record is unverified: FR-24 excludes it from end-user results. (b) A price changes: ERR-05 governs what is displayed. (c) A product becomes unavailable: ERR-04 omits it from results.

Requirements

FR-19–FR-24, DR-07, ERR-04, ERR-05.

Inputs

Product attributes; verification outcome.

Outputs

Catalogue records eligible for retrieval.

Constraints

Prices in SAR (C-6). Availability assessed for Jeddah. No personal data in the catalogue (DR-07).

4.6 SF-6 — Gift Retrieval and Matching

Description

Selects a bounded candidate set from the catalogue on the basis of the Recipient Profile.

Purpose

Reduces the catalogue to a set small enough to filter and rank, without discarding relevant products.

Actors

System.

Preconditions

A Recipient Profile exists and carries valid consent (FR-63).

Main flow

(1) The system forms a query from the profile's interests, weighted by strength. (2) It compares the query against product records by shared interest key and by textual similarity. (3) It returns the highest-scoring candidates up to the configured limit.

Alternative and exception flows

(a) No candidate is returned: FR-28 and ERR-03 apply. (b) The profile is in Arabic and products in English, or the reverse: FR-26 requires retrieval to operate across both.

Requirements

FR-25–FR-28, FR-63.

Inputs

Recipient Profile; catalogue.

Outputs

An ordered candidate set.

Constraints

Retrieval precedes filtering (FR-27).

4.7 SF-7 — Filtering

Description

Removes candidates that violate a stated constraint.

Purpose

Guarantees that no displayed recommendation breaches the budget, the timing, or the appropriateness of the relationship, regardless of how well it matches the profile.

Actors

System.

Preconditions

A candidate set exists; a gift context exists.

Main flow

(1) Remove candidates above budget. (2) Remove candidates that cannot arrive in time. (3) Remove candidates outside the recipient's age range. (4) Remove candidates not suitable for the relationship. (5) Remove candidates above the social-appropriateness threshold for that relationship. (6) Remove candidates matching a dislike or an item already owned. (7) Pass the remainder to ranking.

Alternative and exception flows

(a) All candidates are removed: ERR-03 applies, naming the constraint responsible and offering a relaxation. (b) No age range is known: the age filter is not applied. (c) No delivery deadline was given: the timing filter is not applied.

Requirements

FR-29–FR-35, ERR-03.

Inputs

Candidate set; gift context; Recipient Profile dislikes.

Outputs

A filtered candidate set, with a record of how many were removed by each constraint.

Constraints

Filtering is applied before ranking and is not overridable by score (FR-29).

4.8 SF-8 — Ranking and Scoring

Description

Orders the filtered candidates and enforces variety and a minimum relevance.

Purpose

Determines which of the acceptable products are presented, and in what order.

Actors

System.

Preconditions

A filtered candidate set exists.

Main flow

(1) Score each candidate on interest match, giftability, budget fit, novelty and social-appropriateness. (2) Discard candidates below the relevance threshold. (3) Apply the per-category limit. (4) Order by score. (5) Optionally re-order the leading candidates using a language model, constrained to the existing set. (6) Pass at most five to presentation.

Alternative and exception flows

- (a) Fewer than five candidates survive: FR-46 requires the shorter list to be presented as such.
- (b) The model re-ordering returns an unknown identifier: FR-40 requires it to be discarded.
- (c) The model service is unavailable: ERR-09 requires the deterministic order to stand.

Requirements

FR-36–FR-40, FR-45, FR-46, ERR-09.

Inputs

Filtered candidates; Recipient Profile; gift context.

Outputs

An ordered result set of at most five items with score components retained for analysis.

Constraints

A model may reorder but never introduce a candidate (FR-40). The list is never padded to reach five (FR-46).

4.9 SF-9 — Recommendation Explanation

Description

Produces a short statement of why each recommendation was selected.

Purpose

Allows the giver to judge the suggestion rather than accept it on trust; addresses UN-4.

Actors

System.

Preconditions

A ranked result set exists.

Main flow

- (1) For each recommendation, identify the interest that drove the match.
- (2) Compose a statement of at most three sentences referring to that interest and to the price in relation to the budget.
- (3) Present it with the recommendation.

Alternative and exception flows

- (a) No single interest dominates: the explanation refers to the general style recorded in the profile.
- (b) Explanation generation fails: ERR-09 applies and the recommendation is shown with its attributes, without a generated sentence.

Requirements

FR-41–FR-44, UIR-06.

Inputs

Recommendation; Recipient Profile; gift context.

Outputs

Explanation text in the user's selected language.

Constraints

Only interests present in the profile may be cited (FR-42). No internal scores are shown (FR-44).

4.10 SF-10 — Results and Refinement

Description

Presents the recommendations and allows the giver to adjust them without restarting.

Purpose

Converts a single ranked list into a short, directed search; addresses UN-2.

Actors

Gift giver (UC-1).

Preconditions

A result set exists.

Main flow

(1) The system displays up to five recommendations with explanations. (2) The user may open a seller page for any item. (3) The user may select a refinement. (4) The system re-runs retrieval, filtering and ranking with the adjusted parameter, reusing the existing profile and context. (5) The revised results are displayed.

Alternative and exception flows

(a) A refinement yields no result: ERR-03 applies and the previous results remain available. (b) A seller link fails: ERR-06 applies. (c) The user refines repeatedly: each refinement is applied to the original profile, not cumulatively, unless the user states otherwise.

Requirements

FR-45–FR-49, UIR-06, UIR-07, ERR-03, ERR-06.

Inputs

Result set; refinement selection.

Outputs

A displayed or revised result set; an outbound link to the seller.

Constraints

The profile and gift context are never re-requested on refinement (FR-48).

4.11 SF-11 — Feedback

Description

Records the giver's judgement of individual recommendations.

Purpose

Provides the evidence base for assessing and improving recommendation quality.

Actors

Gift giver (UC-1).

Preconditions

A recommendation has been displayed.

Main flow

(1) The user records a positive or negative judgement. (2) Where negative, the user selects a reason. (3) The system stores the judgement against the recommendation and request.

Alternative and exception flows

(a) The user gives no feedback: this is the normal case and no behaviour depends on it. (b) The user changes a judgement: the latest value is retained.

Requirements

FR-50–FR-52, DR-08, NFR-13.

Inputs

Judgement; optional reason code.

Outputs

A stored feedback record.

Constraints

Feedback is stored against a recommendation, not against a person (DR-08).

4.12 SF-12 — Security, Privacy and Consent

Description

The cross-cutting controls governing consent, minimisation, retention, deletion and protection of data.

Purpose

Ensures personal data is processed only with consent and only for the stated purpose; addresses UN-7 and constraint C-4.

Actors

Gift recipient (UC-2) as data subject; system as enforcement point.

Preconditions

Applies to every operation on a Recipient Profile.

Main flow

(1) Consent is recorded when given (FR-62). (2) The recommendation pipeline checks for valid consent before use (FR-63). (3) Only data required by a requirement is collected (FR-65). (4) Source material is deleted after profile construction (FR-61). (5) Profiles expire and are deleted (FR-66). (6) A deletion request is honoured (FR-67).

Alternative and exception flows

(a) Consent is absent or invalid: FR-63 requires the pipeline to refuse and report, not to proceed. (b) A profile has expired: FR-66 forbids its use. (c) A deletion request arrives while a request is in progress: deletion takes precedence and the recommendation request is terminated.

Requirements

FR-62–FR-68, SEC-01–SEC-10, DR-01–DR-08, NFR-05, NFR-06.

Inputs

Consent decisions; deletion requests.

Outputs

Consent records; deletion confirmations; security event log entries without personal data.

Constraints

The system provides no function that processes recipient data without a consent record (FR-63); this is a hard behaviour, not a configurable one.

Chapter 5

Non-Functional Requirements

Each requirement below states a criterion that can be checked. Where a numeric target is given, it is a target for the prototype under defined conditions, not a service-level guarantee. *Normal prototype operating conditions* means: a single concurrent user, the catalogue at its specified size, a broadband connection, and the application deployed on the hosting tier used by the project.

Table 5.1: Non-functional requirements

ID	Quality	Requirement
NFR-01	Performance	The system shall return a complete set of recommendations, including explanations, within 5 seconds for at least 95% of requests under normal prototype operating conditions. A page of the gift request flow shall become interactive within 3 seconds on a mobile connection. Measurement is by instrumented timing over a defined set of at least 20 representative requests.
NFR-02	Usability	A first-time user shall be able to complete the flow from the landing page to a displayed result set, using the questionnaire route, within 3 minutes and without assistance, in at least 80% of trials in a usability test of at least 8 participants.
NFR-03	Reliability	The system shall handle every error condition listed in Section 3.5 without terminating the user's session. In a test suite exercising each condition, the system shall present a defined message and remain operable in 100% of cases.
NFR-04	Availability	The system shall be available during scheduled demonstration and evaluation periods. Planned unavailability shall be announced in advance. No continuous availability target is claimed for a project prototype.
NFR-05	Security	The system shall satisfy every requirement in Section 3.4. Verification is by inspection of the implementation against SEC-01 to SEC-10 and by targeted testing of input validation, injection and output encoding.
NFR-06	Privacy	The system shall hold no personal data item that is not required by a stated requirement, and shall hold no prohibited attribute. Verification is by inspection of the stored data model against Table 3.17 and by an automated check that no prohibited attribute appears in a stored profile.

ID	Quality	Requirement
NFR-07	Maintainability	Each pipeline module shall be replaceable without modification to the others, as required by SIR-03. Verification is by demonstration: substituting one module implementation for another shall require no change outside that module.
NFR-08	Scalability	The system shall maintain the NFR-01 response target with a catalogue of at least 1,000 products and at least 5 concurrent users. Beyond this, scalability is not specified for the prototype.
NFR-09	Compatibility	The system shall function correctly in the current release, and the immediately preceding release, of at least three major browsers, on both desktop and mobile. Verification is by executing the main flow on each.
NFR-10	Accessibility	Interactive elements shall be operable by keyboard alone, every form control shall have an associated label, and text shall meet a contrast ratio of at least 4.5:1. Verification is by automated accessibility check plus manual keyboard traversal of the main flow.
NFR-11	Localisation	All user-facing text shall be present in Arabic and English with no untranslated string in either, layout shall adapt to right-to-left presentation for Arabic, and all monetary values shall display in SAR. Verification is by inspection of both language builds of every screen.
NFR-12	Data integrity	Every Recipient Profile and product record shall validate against its published schema before being stored or used; an instance failing validation shall be rejected rather than stored partially. Verification is by test with deliberately malformed instances.
NFR-13	Recommendation quality	Recommendation quality shall be evaluated against a defined baseline in which only questionnaire input is used. For a set of test recipients, independent assessors shall rate each recommendation for relevance on a three-point scale and record whether it would be socially inappropriate. The target is a mean relevance of at least 1.5 of 2.0 and no recommendation rated socially inappropriate. Where the target is not met, the result shall be reported as measured rather than adjusted.

Note on NFR-13. This requirement specifies how quality is to be measured and what target is being aimed at. It does not assert that the system will achieve the target, and no requirement in this document claims that a recommendation will be correct for any particular recipient. The elicitation technique from which each non-functional requirement is derived, and the justification for that technique, are recorded in Table 3.23 in Section 3.6.

Chapter 6

Verification and Traceability

6.1 Verification Methods

Every requirement is assigned one of four verification methods.

Table 6.1: Verification methods

Method	Definition
T — Test	The requirement is checked by executing the system with defined inputs and comparing the output against an expected result. Applies to most functional requirements.
I — Inspection	The requirement is checked by examining the implementation, the data model or the interface without executing it. Applies to structural and data-protection requirements.
D — Demonstration	The requirement is checked by operating the system and observing the behaviour, without instrumented measurement. Applies to flows and user interface behaviour.
A — Analysis	The requirement is checked by measurement over a sample and evaluation of the result. Applies to performance and quality requirements.

6.2 Traceability Approach

Traceability runs in both directions:

- **Forward:** each user need in Table 2.2 maps to one or more functional requirements, each functional requirement is realised by exactly one system feature, and each feature carries a verification method.
- **Backward:** every functional requirement traces to at least one user need. A requirement that traces to no need is removed at review; a need with no requirement indicates a gap in the specification.

Appendix C records the matrix. When a requirement changes after baselining, the change is recorded in the Document Control table, the matrix row is updated, and the associated verification activity is repeated.

Appendix A

Glossary

Artificial intelligence (AI)

In this document, software components that derive structured information from unstructured input, or that rank alternatives using a learned or computed model, rather than by a fixed rule stated by the developer.

Candidate retrieval

The step that selects a bounded subset of the catalogue for further processing, before any constraint is applied.

Controlled interest vocabulary

The fixed set of interest keys used by both Recipient Profiles and product records, which makes matching a direct join rather than a text comparison.

Evidence

The record of which signal, from which source and on which date, supports a given interest in a Recipient Profile.

Filtering

The removal of candidates that violate a stated constraint. Distinct from ranking: filtering is absolute, ranking is relative.

Giftability

An attribute expressing how well an interest or product works as a gift, as distinct from how well it matches the recipient.

Gift context

The relationship, occasion, budget and timing supplied by the giver.

Gift Profile

The consent-based route by which a recipient supplies their own information to enrich their Recipient Profile.

Interest signal

A single observation suggesting an interest, carrying a source, a type and a date.

Ranking

The ordering of candidates that have already satisfied every constraint.

Recipient Profile

The structured record of a recipient's weighted interests, dislikes and style attributes, with evidence for each interest.

Recommendation engine

The combination of the retrieval, filtering and ranking modules.

Signal strength

The relative evidential weight of a signal type; a deliberate action is treated as stronger evidence than a passive one.

Social-appropriateness (embarrassment risk)

An attribute expressing the risk that a product would be awkward given the stated relationship.

TikTok personalisation

The optional enrichment of a Recipient Profile from information the recipient supplies themselves, with consent.

Appendix B

Acronyms

Acronym	Expansion
AI	Artificial Intelligence
API	Application Programming Interface
CIR	Communications Interface Requirement (identifier prefix)
DR	Data Requirement (identifier prefix)
ERD	Entity Relationship Diagram
ERR	Error Handling Requirement (identifier prefix)
FR	Functional Requirement (identifier prefix)
HTTPS	Hypertext Transfer Protocol Secure
NFR	Non-Functional Requirement (identifier prefix)
PDPL	Personal Data Protection Law (Kingdom of Saudi Arabia)
RTM	Requirements Traceability Matrix
SAR	Saudi Riyal
SDAIA	Saudi Data and Artificial Intelligence Authority
SEC	Security and Privacy Requirement (identifier prefix)
SF	System Feature (identifier prefix)
SIR	Software Interface Requirement (identifier prefix)
SRS	Software Requirements Specification
UAT	User Acceptance Testing
UC	User Class (identifier prefix)
UIR	User Interface Requirement (identifier prefix)
UN	User Need (identifier prefix)

Appendix C

Requirements Traceability Matrix

Table C.1 traces each user need through the requirements that satisfy it, the feature that realises them, and the method by which they are verified.

Table C.1: Requirements traceability matrix

Need	Functional requirements	Feature	Non-functional	Method
UN-1	FR-07–FR-11	SF-2 Recipient Questionnaire	NFR-02	T, D
UN-1	FR-12–FR-18	SF-3 Recipient Profile Builder	NFR-12	T, I
UN-1	FR-25–FR-28	SF-6 Gift Retrieval and Matching	NFR-01	T, A
UN-1	FR-53–FR-61	SF-4 TikTok Personalisation	NFR-06	T, D
UN-2	FR-45–FR-49	SF-10 Results and Refinement	NFR-01, NFR-02	T, D, A
UN-2	FR-36–FR-40	SF-8 Ranking and Scoring	NFR-01	T, A
UN-3	FR-03, FR-05, FR-30	SF-1 Gift Request, SF-7 Filtering	NFR-03	T
UN-3	FR-19, FR-22–FR-24	SF-5 Product Catalogue	NFR-12	T, I
UN-4	FR-41–FR-44	SF-9 Recommendation Explanation	NFR-11	T, I
UN-5	FR-31–FR-35	SF-7 Filtering	NFR-13	T, A
UN-5	FR-37, FR-39	SF-8 Ranking and Scoring	NFR-13	T, A
UN-6	FR-10, FR-16, FR-46	SF-2, SF-3, SF-10	NFR-03	T
UN-6	FR-59	SF-4 TikTok Personalisation	NFR-03	T, D
UN-6	ERR-03, ERR-07, ERR-08	SF-7, SF-3, SF-4	NFR-03	T
UN-7	FR-54–FR-58, FR-61	SF-4 TikTok Personalisation	NFR-06	T, D, I
UN-7	FR-62–FR-68	SF-12 Security, Privacy and Consent	NFR-05, NFR-06	T, I
UN-7	DR-01–DR-08, SEC-01–SEC-10	SF-12 Security, Privacy and Consent	NFR-05, NFR-06	I, T
UN-8	UIR-01, UIR-09, FR-68	SF-1–SF-12 (all screens)	NFR-11	I, D

Need	Functional requirements	Feature	Non-functional	Method
UN-8	FR-19, FR-26, FR-43	SF-5, SF-6, SF-9	NFR-11	T, I
UN-8	UIR-02, UIR-10	SF-10 Results and Refinement	NFR-09, NFR-10	D, I
—	SIR-01–SIR-07, CIR-01–CIR-04	Cross-cutting	NFR-07, NFR-09	I, D
—	FR-50–FR-52	SF-11 Feedback	NFR-13	T, A

Appendix D

Use-Case Summary

Table D.1: Use-case summary

ID	Use case	Primary actor	Outcome
UC-A	Request gift recommendations	Gift giver	A result set of at most five recommendations with explanations.
UC-B	Describe the recipient by questionnaire	Gift giver	Interest signals from which a Recipient Profile is built.
UC-C	Invite the recipient to create a Gift Profile	Gift giver	An invitation link, shared by a channel of the giver's choosing.
UC-D	Create a Gift Profile	Gift recipient	An approved set of interests, or a recorded decline.
UC-E	Review and edit inferred interests	Gift recipient	A profile containing only what the recipient approved.
UC-F	Refine the result set	Gift giver	A revised result set, without re-entering context.
UC-G	Record feedback on a recommendation	Gift giver	A stored judgement with an optional reason.
UC-H	Open the seller page for a product	Gift giver	The seller's page for that product, in a new context.
UC-I	Request deletion of a Recipient Profile	Gift recipient	The profile and its evidence deleted, with confirmation.
UC-J	Add or verify a catalogue product	Catalogue maintainer	A product record eligible for end-user results.