

Package ‘bspam’

February 23, 2024

Type Package

Encoding UTF-8

Title Speed-Accuracy Psychometric Modeling for Binomial Count Outcome Data with R

Version 1.2.3

Author Akihito Kamata [aut, cre] (<<https://orcid.org/0000-0001-9570-1464>>),
Cornelis J. Potgieter [aut] (<<https://orcid.org/0000-0002-1995-6817>>),
Joseph F. T. Nese [aut] (<<https://orcid.org/0000-0002-9878-7395>>),
Yusuf Kara [aut] (<<https://orcid.org/0000-0003-0691-0630>>),
Sarunya Somsong [aut] (<<https://orcid.org/0000-0002-4974-7346>>),
Xin Qiao [aut] (<<https://orcid.org/0000-0002-3248-7859>>),
Kuo Wang [aut] (<<https://orcid.org/0000-0002-4925-0591>>)

Maintainer Akihito Kamata <akamata@gmail.com>

Description This is an R package that contains functions to fit the speed-accuracy psychometric model for count outcome data (Potgieter, Kamata & Kara, 2017; Kara, Kamata, Potgieter & Nese, 2020), where the accuracy is modeled by a binomial count latent variable model. For example, the use of this modeling technique allows model-based calibration and scoring for oral reading fluency (ORF) assessment data.

License GPL (>= 3)

Depends R (>= 3.5.0)

Imports tibble, rootSolve, tidyverse, tidyr, magrittr, doParallel, foreach,
futile.logger, mvtnorm, nleqslv, tryCatchLog, parallel, miscTools, psych, rstan

Suggests rjags, testthat (>= 3.5.0)

URL <https://github.com/kamataak/bspam>

BugReports <https://github.com/kamataak/bspam/issues>

RoxygenNote 7.2.3

LazyData yes

Config/testthat/edition 3

NeedsCompilation no

R topics documented:

bspam-package	2
bayes	3
bayes.wcpm	4

create_data_list	5
fit.model	6
fit.model.testlet	8
get.cases	9
getBootstrapSE	9
passage.calib.bayes	10
passage.calib.mcem	11
passage2	12
plot.person	13
plot.task	13
prep	14
run.mcem	15
run.scoring	16
scoring	17
scoring.passage	19
sentence.data	20
summary.bootstrap	21
summary.fit.model	22
summary.scoring	22
testlet_scoring_multi_obs_multi_cens	23

Index	24
--------------	-----------

bspam-package	<i>bspam : A package for fitting the speed-accuracy psychometric model for repeatedly measured count outcome data.</i>
---------------	--

Description

Purpose of this package

‘bspam’ is an R package that contains functions to fit the speed-accuracy psychometric model for repeatedly measured count outcome data (Potgieter, Kamata & Kara, 2017; Kara, Kamata, Potgieter & Nese, 2020), where the accuracy is modeled by a binomial count latent variable model. For example, the use of this modeling technique allows model-based calibration and scoring for oral reading fluency (ORF) assessment data.

Design philosophy

Write Design philosophy

Author(s)

Akihito Kamata <akamata@smu.edu>

Cornelis J. Potgieter <c.potgieter@tcu.edu>

Joseph F. T. Nese <jnese@uoregon.edu>

Yusuf Kara <ykara@mail.smu.edu>

Sarunya Somsong <sarunya.ss@hotmail.com>

Xin Qiao <xqiao@usf.edu>

Kuo Wang <>wangkuo@nifty.com>

bayes*Bayes function when running mcm with bayes setting*

Description

Bayes function when running mcm with bayes setting

Usage

```
bayes(  
  person.data = NA,  
  person.id = "",  
  task.id = "",  
  max.counts = "",  
  obs.counts = "",  
  time = "",  
  parallel = T,  
  n.chains = NA,  
  thin = 1,  
  iter = NA,  
  burn = NA  
)
```

Arguments

person.data	- student reading data
person.id	The column name in the data that represents the unique individual identifier.
task.id	The column name in the data that represents the unique task identifier.
max.counts	The column name in the data that represents the number of words in a task.
obs.counts	The column name in the data that represents the words read correctly for each case.
time	The column name in the data that represents the time, in seconds, for each case.
parallel	parallel=T, #logical, run in parallel? "T" or "F"
n.chains	int., number of the chains
thin	int, thinning interval, a.k.a, period of saving samples
iter	int., number of the iterations after the burn-in period
burn	int., number of the burn-in iterations

Value

list

bayes.wcpm

*Bayes function when running mcm with bayes setting***Description**

Bayes function when running mcm with bayes setting

Usage

```
bayes.wcpm(
  calib.data = NA,
  person.data = NA,
  person.id = NULL,
  task.id = NULL,
  occasion = NULL,
  group = NULL,
  max.counts = NULL,
  obs.counts = NULL,
  time = NULL,
  cases = NULL,
  external = NULL,
  type = NULL,
  parallel = T,
  n.chains = NA,
  iter = NA,
  burn = NA,
  thin = 1
)
```

Arguments

calib.data	- fit.model class object
person.data	- individual reading data
person.id	The column name in the data that represents the unique individual identifier.
task.id	The column name in the data that represents the unique task identifier.
occasion	The column name in the data that represents the unique occasion.
group	The column name in the data that represents the unique group.
max.counts	The column name in the data that represents the number of words in a task.
obs.counts	The column name in the data that represents the words read correctly for each case.
time	The column name in the data that represents the time, in seconds, for each case.
cases	- student id vectors, will directly use passage data if no calib.data provided
external	- if not NULL, will use not student read passages for estimating
type	- output type, "general" and "orf", default "general" only output tau & theta. "orf" will output wcpm
parallel	parallel=T, #logical, run in parallel? "T" or "F"
n.chains	int., number of the chains

iter	int., number of the iterations after the burn-in period
burn	int., number of the burn-in iteration
thin	int, thinning interval, a.k.a, period of saving samples

Value

list

create_data_list	<i>Scoring.Passage function</i>
------------------	---------------------------------

Description

Copyright (C) 2021-2024 The ORF Project Team

Usage

create_data_list(Count, logT10, MaxN, a, b, alpha, beta, sigma, rho, C)

Arguments

a,	b: Model parameters related to the count data model (K-dim)
alpha,	beta: Model parameters related to the time data model (K-dim)
Count:	A vector with the number of words correct per passage It should be K-dimensional
logT10:	The log-scale reading time per 10 words per passage It should be K-dimensional
MaxN:	A vector of passage lengths It should be K-dimensional
sigma:	The latent standard deviation of the time latent component
rho:	The correlation between count and time latent components
C:	A vector of indicators whether a specific passage was censored (0) or fully observed (1) – K-dim

Details

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 3 of the License, or (at your option) any later version. This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

A copy of the GNU General Public License is available at <http://www.gnu.org/licenses/>

Pre-processing data: Function prepares data for Stan model Enter a single student's data for preparation

Assume a student has read $K \geq 2$ passages

fit.model

*Estimate the model parameters***Description**

This is an interface function to estimate the model parameters based on the task-level (i.e., passage-level in ORF assessment context) accuracy and speed data by implementing the Monte Carlo EM algorithm described in Potgieter et al. (2017) or fully Bayesian method described in Kara et al. (2020).

Usage

```
fit.model(
  data = NA,
  person.data = NA,
  person.id = "",
  task.id = "",
  max.counts = "",
  obs.counts = "",
  time = "",
  k.in = 5,
  reps.in = 2,
  ests.in = NA,
  est = "mcm",
  se = "none",
  verbose = FALSE
)
```

Arguments

data	A data frame. A wide-format response data generated by the prep function. If this argument is used, the next 6 arguments person.data, person.id, task.id, max.counts, obs.counts, time should be skipped.
person.data	A data frame. A long-format response data object. If this this argument is used, the previous argument data should be skipped.
person.id	Quoted variable name in person.data that indicates the unique person identifier.
task.id	Quoted variable name in person.data that indicates the unique task identifier. In the ORF assessment context, it is the passage identifier.
max.counts	Quoted variable name in person.data that indicates the number of attempts in the task. In the ORF assessment context, it is the number of words in the passage.
obs.counts	Quoted variable name in person.data that indicates the number of successful attempts in each task. In the ORF assessment context, it is the number of words read correctly for the passage.
time	Quoted variable name in person.data that indicates the time in seconds took to complete the task. In the ORF context, it is the time took to complete reading the passage.
k.in	Numeric, indicating the number of imputations. Default is 5.

<code>reps.in</code>	Numeric, indicating the number of Monte-Carlo iterations. Default is 2.
<code>ests.in</code>	An optional list of numeric vectors, indicating initial values of the model parameters. If this argument is not given, <code>mom</code> function will be called to generate the initial values.
<code>est</code>	Quoted string, indicating the choice of the estimator. It has to be one of "mcm", "bayes". Default is "mcm".
<code>se</code>	Quoted string, indicating the choice of the standard errors. It has to be one of "none", "analytic", "bootstrap". Default is "none".
<code>verbose</code>	Boolean. If TRUE, the summary will be output. Default is FALSE.

Details

Additional details...

Value

MCEM list, bayes list

Note

More & more additional note...

References

Potgieter, N., Kamata, A., & Kara, Y. (2017). An EM algorithm for estimating an oral reading speed and accuracy model. Manuscript submitted for publication.

Kara, Y., Kamata, A., Potgieter, C., & Nese, J. F. (2020). Estimating model-based oral reading fluency: A bayesian approach with a binomial-lognormal joint latent model. *Educational and Psychological Measurement*, 1–25.

See Also

[scoring](#) for scoring.

Examples

```
# example code
MCEM_run <- fit.model(person.data = passage2,
                      person.id = "id.student",
                      task.id = "id.passage",
                      max.counts = "numwords.pass",
                      obs.counts = "wrc",
                      time = "sec",
                      k.in = 5,
                      reps.in = 50,
                      est = "mcm")
```

fit.model.testlet	<i>This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 3 of the License, or (at your option) any later version. This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details. A copy of the GNU General Public License is available at http://www.gnu.org/licenses/</i>
-------------------	--

Description

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 3 of the License, or (at your option) any later version. This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details. A copy of the GNU General Public License is available at <http://www.gnu.org/licenses/>

Usage

```
fit.model.testlet(
  data = NULL,
  person.id = "",
  sub.task.id = "",
  obs.count = "",
  time = "",
  task.id = "",
  max.counts = ""
)
```

Arguments

data	A data frame. It has the information of student, passage, sentence, obs.count and time.
person.id	each student's id.
sub.task.id	each sentence's id.
obs.count	The column name in the data that represents the words read correctly for each sentence
time	The column name in the data that represents the reading time for the sentence.
task.id	The column name in the data that represents the unique passage identifier.
max.counts	The column name in the data that represents the number of words in a sentence.

Details

Additional details...

Value

list

Note

Additional note...

Examples

```
# example code
fit.model.testlet <- function(data=NULL, person.id="", sub.task.id="", obs.count="", time="", task.id="", max.
```

get.cases	<i>Returns cases (person and occasion) applied in [fit.model] function.</i>
-----------	---

Description

Returns cases (person and occasion) applied in [fit.model] function.

Usage

```
get.cases(data)
```

Arguments

data = person response data

Value

cases vector

getBootstrapSE	<i>Get bootstrap SE case is a single stu_season_id</i>
----------------	--

Description

Added MAP function 07/14/2021 Modified a bug of MLE 07/23/2021 Modified EAP 10/28/2021

Usage

```
getBootstrapSE(
  object,
  person.data,
  case = NA,
  perfect.cases,
  est = "map",
  kappa = 1,
  bootstrap = 100,
  external = NULL
)
```

Arguments

object	- mcm class object
person.data	- individual response data
case	- case number
perfect.cases	- perfect accurate case
est	- SE type.(MLE, EAP, and MAP.) default MAP
kappa	- Default kappa = 1, better be 5
bootstrap	- K number of bootstrap, default is 100
external	- if not NULL, will use unread task for estimating

Value

SE dataset

passage.calib.bayes *Task calibration example output object by Bayes*

Description

This is an example output object from running the `fit.model.bayes` function by using the Bayesian estimator option. It is a result of calibrating an oral reading fluency data set from Nese and Kamata (2014-2018) with xxxx students on 150 passages.

Usage

```
passage.calib.bayes
```

Format

two lists: `$pass.param` with 150 rows and `$hyper.param` with 4 variables

`$pass.param`

a parameter controlling binomial success probabilities

b parameter controlling binomial success probabilities

alpha parameter controlling reading times

beta parameter controlling reading times

se_a standard error of a

se_b standard error of b

se_alpha standard error of alpha

se_beta standard error of beta

passage.id passage ID

nwords.p the total

`$hyper.param`

vartau variance of latent reading ability tau

rho correlation between two latent variables

se_vartau standard error of vartar

se_rho standard error of rho

Source

<https://jnese.github.io/core-blog/>

References

Nese, J. F. T. & Kamata, A. (2014-2018). Measuring Oral Reading Fluency: Computerized Oral Reading Evaluation (Project No. R305A140203) [Grant]. Institute of Education Sciences, U.S. Department of Education. <https://ies.ed.gov/funding/grantsearch/details.asp?ID=1492>

passage.calib.mcem	<i>Task calibration example output object by MCEM</i>
--------------------	---

Description

This is an example output object from running the `fit.model` function by using the MCEM estimator option. It is a result of calibrating an oral reading fluency data set from Nese and Kamata (2014-2018) with xxxx students on 150 passages.

Usage

```
passage.calib.mcem
```

Format

A list of two elements: `$pass.param` is a dataframe with 150 rows and 10 variables, and `$hyper.param` is a dataframe with 1 row and 4 variables

`$pass.param`

a parameter controlling binomial success probabilities

b parameter controlling binomial success probabilities

alpha parameter controlling reading times

beta parameter controlling reading times

se_a standard error of a

se_b standard error of b

se_alpha standard error of alpha

se_beta standard error of beta

passage.id passage ID

nwords.p the total number of words in the passage

`$hyper.param`

var_tau variance of latent reading ability tau

rho correlation between two latent variables

se_var_tau standard error of var_tau

se_rho standard error of rho

Source

<https://jnese.github.io/core-blog/> Nese, J. F. T. & Kamata, A. (2014-2018). Measuring Oral Reading Fluency: Computerized Oral Reading Evaluation (Project No. R305A140203) [Grant]. Institute of Education Sciences, U.S. Department of Education. <https://ies.ed.gov/funding/grantsearch/details.asp?ID=1492>

passage2

*Passage-level Oral Reading Fluency assessment data set***Description**

This is an example data set. It is a passage-level Oral Reading Fluency assessment data set for 85 students who were assigned to read 2 to 12 passages among the same 12 passages. The data is a small subset of the data collected by Nese and Kamata (2014-2018).

Usage

```
\code{data(passage2)}
```

Format

A data frame with 847 rows and 7 variables.

`id.student` unique student identifier

`occasion` identifier for longitudinal assessment occasions; here a triannual assessment administered in the fall, winter, and spring of a school year

`grade` student grade level

`id.passage` unique passage identifier

`numwords.pass` total number of words in the passage

`wrc` words read correct

`sec` seconds to read the passage

Source

<https://jnese.github.io/core-blog/>

References

Nese, J. F. T. & Kamata, A. (2014-2018). Measuring Oral Reading Fluency: Computerized Oral Reading Evaluation (Project No. R305A140203) [Grant]. Institute of Education Sciences, U.S. Department of Education. <https://ies.ed.gov/funding/grantsearch/details.asp?ID=1492>

plot.person	<i>Plot function to show graph of scoring class</i>
-------------	---

Description

Copyright (C) 2021-2024 The ORF Project Team

Usage

```
## S3 method for class 'person'
plot(object, person = NULL, parameter, show.se = T, sort = F)
```

Arguments

object	scoring object
person	person ids for plotting
parameter	model parameter for plotting, a,b,alpha,beta
show.se	standard error bar flag, TRUE for showing or FALSE for no showing
sort	sorting flag, TRUE or FALSE

Details

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 3 of the License, or (at your option) any later version. This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details. A copy of the GNU General Public License is available at <http://www.gnu.org/licenses/>

plot.task	<i>Plot function to show graph of fit.model class</i>
-----------	---

Description

Copyright (C) 2021-2024 The ORF Project Team

Usage

```
## S3 method for class 'task'
plot(object, task = NULL, parameter, sort = F)
```

Arguments

object	fit.model object
task	task ids for plotting
parameter	model parameter for plotting, a,b,alpha,beta
sort	sorting flag, TRUE or FALSE

Details

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 3 of the License, or (at your option) any later version. This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details. A copy of the GNU General Public License is available at <http://www.gnu.org/licenses/>

```
prep
```

This file includes utilities of bspam package.

Description

Copyright (C) 2021-2023 The ORF Project Team

Usage

```
prep(
  data = data,
  person.id = "",
  task.id = "",
  occasion = "",
  group = "",
  max.counts = "",
  obs.counts = "",
  time = ""
)
```

Arguments

data = student response data

Details

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 3 of the License, or (at your option) any later version. This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details. A copy of the GNU General Public License is available at <http://www.gnu.org/licenses/>

prep function prepares input data for fit.model function

Value

data list (data.long: data frame, data.wide: list of Y, logT10, N, I)

run.mcem

*Base function for fitting the speed-accuracy model by MCEM***Description**

This is a base function for fitting the speed-accuracy model to estimate the model parameters by the Monte Carlo EM algorithm described in Potgieter et al. (2017). This function is used by the [fit.model](#) function, which is recommended for the users to use.

Usage

```
run.mcem(Y, logT10, N, I, k.in = 5, reps.in = 2, ests.in = NA, verbose = FALSE)
```

Arguments

Y	Numeric data matrix of accuracy scores in the size of $n \times I$, where n is the number of tasks and I is the number of persons. Missing data are allowed.
logT10	Numeric data matrix of time in the size of $n \times I$ matrix, where n and I are defined above. The time data should be in the scale of $\log_{10}(\text{times})$. Missing data are allowed.
N	Numeric vector of passage lengths in the length of n .
I	Numeric, indicating the number of tasks.
k.in	Numeric, indicating the number of imputations. Default is 5.
reps.in	Numeric, indicating the number of Monte-Carlo iterations. Default is 2.
ests.in	An optional list of numeric vectors, indicating initial values of the model parameters. If this argument is not given, mom function will be called to generate the initial values.
verbose	Boolean. If TRUE, the summary will be output. Default is FALSE.

Details

If the user is desired to use this function, note that the response data file needs to be in the wide format, which can be reshaped from a long-format response data by the [prep.wide](#) function.

Value

mcem list

Note

Update Memo: 04/29/2021 Modified the mcem function based on Nelis's updated. 10/28/2021 Modified the mcem output

References

Potgieter, N., Kamata, A., & Kara, Y. (2017). An EM algorithm for estimating an oral reading speed and accuracy model. Manuscript submitted for publication.

See Also

[prep.wide](#) [fit.model](#).

run.scoring

*Base function for scoring by likelihood-based approaches***Description**

This is a base function for estimating factor scores by likelihood-based approaches described in Potgieter et al. (2024). This function is used by the [scoring](#) function, which is recommended for the users to use.

Usage

```
run.scoring(
  object,
  person.data,
  task.data,
  cases,
  perfect.cases,
  est = "map",
  lo = -4,
  hi = 4,
  q = 100,
  kappa = 1,
  external = NULL,
  type = NULL
)
```

Arguments

object	A class object. Output from calibration phase by fit.model function.
person.data	A data frame. A long-format response data object.
task.data	A data frame? Estimated task parameter values?
cases	A vector of individual id for which scoring is desired. If no information is specified, it will estimate scores for all cases in the person.data.
perfect.cases	A list? A list of perfect cases.
est	Quoted string, indicating the choice of the estimator. It has to be one of code/"mle", "map", "eap", "bayes". Default is "map".
lo	Numeric, indicating the lower bound of the quadratures. Default is -4.
hi	Numeric, indicating the upper bound of the quadratures. Default is 4.
q	Numeric, indicating the number of quadratures. Default is 100.
kappa	Numeric, indicating ?? Default is 1.
external	An optional vector of task ID's in strings. If NULL (default), the wcpm scores are derived with the tasks the individuals were assigned to. If not NULL, wcpm scores are derived with the tasks provided in the vector, rather than the tasks the individuals were assigned.
type	Quoted string, indication of the choice of output. If "general" (default), wcpm scores are not reported. If "orf", wcpm scores will be reported.

Details

Update Memo: 04/29/2021 Modified the wcpm function based on Nelis's updated. 06/01/2021 Modified based on Nelis's MAP function. 06/01/2021 Modified based on Sarunya's BiEAP function. 06/20/2021 Modified based on Nelis's updated for MLE and EAP 06/21/2021 Modified a bug of MAP function. 07/12/2021 Modified est.eqs function based on Nelis's code. 07/13/2021 Added Map function for bootstrap. 07/30/2021 Modified wcpm function based on Sarunya's update

Value

wcpm list

References

Qiao, X, Potgieter, N., & Kamata, A. (2023). Likelihood Estimation of Model-based Oral Reading Fluency. Manuscript submitted for publication.

scoring

Estimate factor scores with task-level model

Description

This is an interface function to estimated factor scores based on the task-level (i.e., passage-level in ORF assessment context) accuracy and speed data. It implements likelihood-based approaches (MLE, MAP, or EAP) described in Qiao et al. (under review) or fully Bayesian method described in Kara et al. (2020).

Usage

```
scoring(
  calib.data = NA,
  person.data = NA,
  person.id = "",
  task.id = "",
  occasion = "",
  group = "",
  max.counts = "",
  obs.counts = "",
  time = "",
  cases = NULL,
  est = "map",
  se = "analytic",
  failsafe = 0,
  bootstrap = 100,
  external = NULL,
  type = "general"
)
```

Arguments

<code>calib.data</code>	A class object. Output from calibration phase by <code>fit.model</code> function
<code>person.data</code>	A data frame. A long-format response data object.
<code>person.id</code>	Quoted variable name in <code>person.data</code> that indicates the unique individual identifier.
<code>task.id</code>	Quoted variable name in <code>person.data</code> that represents the unique task identifier. In the ORF assessment context, it is the passage identifier.
<code>occasion</code>	The column name in the data that represents the unique occasion.
<code>group</code>	The column name in the data that represents the unique group.
<code>max.counts</code>	Quoted variable name in <code>person.data</code> that represents the number of attempts in the task. In the ORF assessment context, it is the number of words in the passage.
<code>obs.counts</code>	The column name in the data that represents the words read correctly for each case.
<code>time</code>	The column name in the data that represents the time, in seconds, for each case.
<code>cases</code>	A vector of individual id for which scoring is desired. If no information is specified, it will estimate scores for all cases in the <code>person.data</code> .
<code>est</code>	Quoted string, indicating the choice of the estimator. It has to be one of <code>code/"mle"</code> , <code>"map"</code> , <code>"cap"</code> , <code>"bayes"</code> . Default is <code>"map"</code> .
<code>se</code>	Quoted string, indication the choice of the standard errors. It has to be one of <code>code/"analytic"</code> , <code>"bootstrap"</code> . Default is <code>"analytic"</code> .
<code>failsafe</code>	Numeric, indicating the number of retries for bootstrap, which can be set between 0 and 50. Default is 0.
<code>external</code>	An optional vector of task ID's in strings. If <code>NULL</code> (default), the <code>wcpm</code> scores are derived with the tasks the individuals were assigned to. If not <code>NULL</code> , <code>wcpm</code> scores are derived with the tasks provided in the vector, rather than the tasks the individuals were assigned.
<code>type</code>	Quoted string, indication of the choice of output. If <code>"general"</code> (default), <code>wcpm</code> scores are not reported. If <code>"orf"</code> , <code>wcpm</code> scores will be reported.
<code>bootstrp</code>	Numeric, indicating the number of bootstrap iterations. Default is 100.

Details

Additional details...

Value

scoring list or Bootstrap dataset

Note

More additional note...

References

- Qiao, X, Potgieter, N., & Kamata, A. (2023). Likelihood Estimation of Model-based Oral Reading Fluency. Manuscript submitted for publication.
- Kara, Y., Kamata, A., Potgieter, C., & Nese, J. F. (2020). Estimating model-based oral reading fluency: A bayesian approach with a binomial-lognormal joint latent model. *Educational and Psychological Measurement*, 1–25.

See Also

[fit.model](#) for model parameter estimation.

Examples

```
# example code
WCPM_all <- scoring(calib.data=MCEM_run,
                    person.data = passage2,
                    person.id = "id.student",
                    occasion = "occasion",
                    group = "grade",
                    task.id = "id.passage",
                    max.counts = "numwords.pass",
                    obs.counts = "wrc",
                    time = "sec",
                    est = "map",
                    se = "analytic",
                    type="general")
```

scoring.passage	<i>scoring.passage function</i>
-----------------	---------------------------------

Description

Copyright (C) 2021-2024 The ORF Project Team

Usage

```
scoring.passage(
  Count = NULL,
  logT10 = NULL,
  N = NULL,
  a = NULL,
  b = NULL,
  alpha = NULL,
  beta = NULL,
  sigma = NULL,
  rho = NULL,
  C = NULL
)
```

Arguments

- | | |
|---------|--|
| a, | b: Model parameters related to the count data model (K-dim) |
| alpha, | beta: Model parameters related to the time data model (K-dim) |
| Count: | A vector with the number of words correct per passage It should be K-dimensional |
| logT10: | The log-scale reading time per 10 words per passage It should be K-dimensional |
| N: | A vector of passage lengths It should be K-dimensional |
| sigma: | The latent standard deviation of the time latent component |

rho: The correlation between count and time latent components

C: A vector of indicators whether a specific passage was censored (0) or fully observed (1) – K-dim

Details

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 3 of the License, or (at your option) any later version. This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

A copy of the GNU General Public License is available at <http://www.gnu.org/licenses/>

Pre-processing data: Function prepares data for Stan model Enter a single student's data for preparation

Assume a student has read $K \geq 2$ passages

Value

list

sentence.data	<i>Sentence-level Oral Reading Fluency assessment data set</i>
---------------	--

Description

This is an example data set. It is a sentence-level Oral Reading Fluency assessment data set for 58 students who were assigned to read 4 passages with a total of 23 sentences. The data is a small subset of the data collected by Nese and Kamata (2014-2018).

Usage

sentence.data

Format

1334 rows and 8 variables:

id.student unique student identifier

grade student grade level

id.passage unique passage identifier

ind.passage passage index

id.sentence unique sentence identifier

numwords.sent the total number of words in the sentence

wrc the number of words read correct

sec time to read the sentence in seconds

Source

<https://jnese.github.io/core-blog/>

References

Nese, J. F. T. & Kamata, A. (2014-2018). Measuring Oral Reading Fluency: Computerized Oral Reading Evaluation (Project No. R305A140203) [Grant]. Institute of Education Sciences, U.S. Department of Education. <https://ies.ed.gov/funding/grantsearch/details.asp?ID=1492>

summary.bootstrap	<i>summary the information of bootstrap class</i>
-------------------	---

Description

Copyright (C) 2021-2023 The ORF Project Team

Usage

```
## S3 method for class 'bootstrap'
summary(
  object,
  digits = 4,
  geterror = FALSE,
  verbose = TRUE,
  factor.scores = FALSE
)
```

Arguments

object	= bootstrap object
digits	= print out numeric with specific digits
geterror,	summary error case, default FALSE
verbose	show summary on screen, default TRUE
factor.scores	- theta and tau output flag, default is FALSE

Details

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 3 of the License, or (at your option) any later version. This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details. A copy of the GNU General Public License is available at <http://www.gnu.org/licenses/>

Value

table

summary.fit.model	<i>summary the information of fit.model class</i>
-------------------	---

Description

Copyright (C) 2021-2023 The ORF Project Team

Usage

```
## S3 method for class 'fit.model'
summary(object, digits = 4, ...)
```

Arguments

object	= object
digits	= print out numeric with specific digits
...	= parameter

Details

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 3 of the License, or (at your option) any later version. This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details. A copy of the GNU General Public License is available at <http://www.gnu.org/licenses/>

Value

printing information

summary.scoring	<i>summary the information of wcpm class</i>
-----------------	--

Description

Copyright (C) 2021-2023 The ORF Project Team

Usage

```
## S3 method for class 'scoring'
summary(
  object,
  digits = 4,
  verbose = TRUE,
  factor.scores = TRUE,
  show = "short"
)
```

Arguments

object	= object
digits	= print out numeric with specific digits
verbose	- boolean, if TRUE, shows the summary, default is TRUE
factor.scores	- theta and tau output flag, default is TRUE # before was FALSE
show	- output flag, "long" and "short", default "short" only output estimate result. "long" will output estimate result and data.

Details

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 3 of the License, or (at your option) any later version. This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details. A copy of the GNU General Public License is available at <http://www.gnu.org/licenses/>

Value

scoring dataset with task information and estimated score

testlet_scoring_multi_obs_multi_cens

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 3 of the License, or (at your option) any later version. This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details. A copy of the GNU General Public License is available at <http://www.gnu.org/licenses/>

Description

Bayesian Sampling Models for Passage-Level Observations

Usage

testlet_scoring_multi_obs_multi_cens

Format

An object of class character of length 1.

Details

This code defines Bayesian sampling models for estimating latent variables based on passage-level observations for a specific student. The models are formulated differently depending on the number of censored (incomplete) and fully observed passages. The goal is to estimate latent variables such as accuracy (theta_acc) and speed (theta_spd) for the student's reading performance.

Index

* datasets

- passage.calib.bayes, [10](#)
- passage.calib.mcem, [11](#)
- passage2, [12](#)
- sentence.data, [20](#)
- testlet_scoring_multi_obs_multi_cens,
[23](#)

- bayes, [3](#)
- bayes.wcpm, [4](#)
- bspam-package, [2](#)

- create_data_list, [5](#)

- fit.model, [6](#), [15](#), [16](#), [18](#), [19](#)
- fit.model.testlet, [8](#)

- get.cases, [9](#)
- getBootstrapSE, [9](#)

- passage.calib.bayes, [10](#)
- passage.calib.mcem, [11](#)
- passage2, [12](#)
- plot.person, [13](#)
- plot.task, [13](#)
- prep, [14](#)
- prep.wide, [15](#)

- run.mcem, [15](#)
- run.scoring, [16](#)

- scoring, [7](#), [16](#), [17](#)
- scoring.passage, [19](#)
- sentence.data, [20](#)
- summary.bootstrap, [21](#)
- summary.fit.model, [22](#)
- summary.scoring, [22](#)

- testlet_scoring_multi_obs_multi_cens,
[23](#)