

Package ‘bspam’

September 1, 2023

Type Package

Encoding UTF-8

Title Speed-Accuracy Psychometric Modeling for Binomial Count Outcome Data with R

Version 1.2.2

Maintainer Akihito Kamata <akamata@gmail.com>

Description This is an R package that contains functions to fit the speed-accuracy psychometric model for count outcome data (Potgieter, Kamata & Kara, 2017; Kara, Kamata, Potgieter & Nese, 2020), where the accuracy is modeled by a binomial count latent variable model. For example, the use of this modeling technique allows model-based calibration and scoring for oral reading fluency (ORF) assessment data.

License GPL (>= 3)

Depends R (>= 3.5.0)

Imports tibble, rootSolve, tidyverse, tidyr, magrittr, doParallel, foreach, futile.logger, mvtnorm, nleqslv, tryCatchLog, parallel, miscTools

Suggests rjags, rstan, testthat (>= 3.5.0)

URL <https://github.com/kamataak/bspam>

BugReports <https://github.com/kamataak/bspam/issues>

RoxygenNote 7.2.3

LazyData true

Config/testthat/edition 3

Authors Akihito Kamata [aut, cre] <<https://orcid.org/0000-0001-9570-1464>>

Cornelis J. Potgieter [aut] <<https://orcid.org/0000-0002-1995-6817>>

Yusuf Kara [aut] <<https://orcid.org/0000-0003-0691-0630>>

Joseph F. T. Nese [aut] <<https://orcid.org/0000-0002-9878-7395>>

Sarynya Somsong [aut] <<https://orcid.org/0000-0002-4974-7346>>

Xin Qiao [aut] <<https://orcid.org/0000-0002-3248-7859>>

Kuo Wang [aut] <<https://orcid.org/0000-0002-4925-0591>>

R topics documented:

bspam-package	2
bayes	3
bayes.wcpm	4
exclude_passages	5

fit.model	5
get.cases	7
get.perfectcases	7
getBootstrapSE	8
get_errlist	8
log.initiating	9
MCEM	9
passage.calib.bayes	10
passage.calib.mcem	11
passage2	12
plot.mcem	12
prep	13
preplong	14
prepwide	14
run.mcem	15
run.scoring	16
scoring	17
summary.bootstrap	18
summary.fit.model	19
summary.scoring	19
Index	21

bspam-package	<i>bspam : A package for fitting the speed-accuracy psychometric model for count outcome data.</i>
---------------	--

Description

Purpose of this package

Write something here

Design philosophy

Write Design philosophy

Author(s)

Akihito Kamata <akamata@smu.edu>

Cornelis J. Potgieter <c.potgieter@tcu.edu>

Joseph F. T. Nese <jnese@uoregon.edu>

Yusuf Kara <ykara@mail.smu.edu>

Sarunya Somsong <sarunya.ss@hotmail.com>

Kuo Wang <>wangkuo@nifty.com>

bayes*Bayes function when running mcmc with bayes setting*

Description

Bayes function when running mcmc with bayes setting

Usage

```
bayes(  
  person.data = NA,  
  person.id = "",  
  task.id = "",  
  max.counts = "",  
  obs.counts = "",  
  time = "",  
  parallel = T,  
  n.chains = NA,  
  thin = 1,  
  iter = NA,  
  burn = NA  
)
```

Arguments

person.data	- student reading data
person.id	The column name in the data that represents the unique individual identifier.
task.id	The column name in the data that represents the unique task identifier.
max.counts	The column name in the data that represents the number of words in a task.
obs.counts	The column name in the data that represents the words read correctly for each case.
time	The column name in the data that represents the time, in seconds, for each case.
parallel	parallel=T, #logical, run in parallel? "T" or "F"
n.chains	int., number of the chains
thin	int, thinning interval, a.k.a, period of saving samples
iter	int., number of the iterations after the burn-in period
burn	int., number of the burn-in iterations

Value

list

bayes.wcpm

*Bayes function when running mcm with bayes setting***Description**

Bayes function when running mcm with bayes setting

Usage

```
bayes.wcpm(
  calib.data = NA,
  person.data = NA,
  person.id = NULL,
  task.id = NULL,
  occasion = NULL,
  group = NULL,
  max.counts = NULL,
  obs.counts = NULL,
  time = NULL,
  cases = NULL,
  external = NULL,
  parallel = T,
  n.chains = NA,
  iter = NA,
  burn = NA,
  thin = 1
)
```

Arguments

calib.data	- fit.model class object
person.data	- individual reading data
person.id	The column name in the data that represents the unique individual identifier.
task.id	The column name in the data that represents the unique task identifier.
occasion	The column name in the data that represents the unique occasion.
group	The column name in the data that represents the unique group.
max.counts	The column name in the data that represents the number of words in a task.
obs.counts	The column name in the data that represents the words read correctly for each case.
time	The column name in the data that represents the time, in seconds, for each case.
cases	- student id vectors, will directly use passage data if no calib.data provided
external	- if not NULL, will use not student read passages for estimating
parallel	parallel=T, #logical, run in parallel? "T" or "F"
n.chains	int., number of the chains
iter	int., number of the iterations after the burn-in period
burn	int., number of the burn-in iteration
thin	int, thinning interval, a.k.a, period of saving samples

Value

list

exclude_passages	<i>To exclude error passages</i>
------------------	----------------------------------

Description

To exclude error passages

Usage

```
exclude_passages(passage)
```

Arguments

passage

Value

passage data set without error passages

fit.model	<i>This is an interface function to estimate the model parameters.</i>
-----------	--

Description

This function estimates the model parameters by implementing the Monte Carlo EM algorithm described in Potgieter et al. (2017) or fully Bayesian method described in Kara et al. (2020).

Usage

```
fit.model(
  data = NA,
  person.data = NA,
  person.id = "",
  task.id = "",
  max.counts = "",
  obs.counts = "",
  time = "",
  k.in = 5,
  reps.in = 2,
  ests.in = NA,
  est = "mcm",
  se = "none",
  verbose = FALSE
)
```

Arguments

<code>data</code>	A data frame. It has to be a wide-format response data generated by the ‘prep’ function. If this argument is used, the next 6 arguments ‘person.data’, ‘person.id’, ‘task.id’, ‘max.counts’, ‘obs.counts’, and ‘time’ should be skipped.
<code>person.data</code>	A data frame. It has to be a long-format response data object. If this argument is used, the previous argument ‘data’ should be skipped.
<code>person.id</code>	The column name in ‘person.data’ that represents the unique person identifier.
<code>task.id</code>	The column name in the data that represents the unique passage identifier.
<code>max.counts</code>	The column name in the data that represents the number of words in a passage.
<code>obs.counts</code>	The column name in the data that represents the words read correctly for each case.
<code>time</code>	The column name in the data that represents the time, in seconds, for each case.
<code>k.in</code>	- number of imputations, default is 5
<code>reps.in</code>	- number of Monte-Carlo iterations, default is 2
<code>ests.in</code>	- if not given, mom function will be called and get est.in output
<code>est</code>	- estimator keyword, mcm or bayes, default is mcm
<code>se</code>	- standard error keyword / c("none", "analytic", "bootstrap"), default is none
<code>verbose</code>	- boolean, if shows the summary, default is FALSE

Details

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 3 of the License, or (at your option) any later version. This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details. A copy of the GNU General Public License is available at <http://www.gnu.org/licenses/>

Additional details...

Value

MCEM list, bayes list

Note

Additional note...

See Also

[scoring()] for the next step.

Examples

```
# example code
MCEM_run <- fit.model(person.data = passage2,
                      person.id = "id.student",
                      task.id = "id.passage",
                      max.counts = "numwords.pass",
                      obs.counts = "wrc",
                      time = "sec",
```

```
k.in = 5,  
reps.in = 50,  
est = "mcm")
```

`get.cases`*Returns cases (person and occasion) applied in [fit.model] function.*

Description

Returns cases (person and occasion) applied in [fit.model] function.

Usage

```
get.cases(data)
```

Arguments

`data` = person response data

Value

cases vector

`get.perfectcases`*Returns perfect cases (student and occasion) in which every word was read correctly.*

Description

Returns perfect cases (student and occasion) in which every word was read correctly.

Usage

```
get.perfectcases(data)
```

Arguments

`data` = person response data

Value

perfect accurate case vector

getBootstrapSE	<i>Get bootstrap SE case is a single stu_season_id</i>
----------------	--

Description

Added MAP function 07/14/2021 Modified a bug of MLE 07/23/2021 Modified EAP 10/28/2021

Usage

```
getBootstrapSE(
  object,
  person.data,
  case = NA,
  perfect.cases,
  est = "map",
  kappa = 1,
  bootstrap = 100,
  external = NULL
)
```

Arguments

object	- mcm class object
person.data	- individual response data
case	- case number
perfect.cases	- perfect accurate case
est	- SE type.(MLE, EAP, and MAP.) default MAP
kappa	- Default kappa = 1, better be 5
bootstrap	- K number of bootstrap, default is 100
external	- if not NULL, will use unread task for estimating

Value

SE dataset

get_errlist	<i>To get a string of error passages that have no at least two readers</i>
-------------	--

Description

To get a string of error passages that have no at least two readers

Usage

```
get_errlist(passage)
```


Arguments

passage

Value

a string of error passages

log.initiating	<i>This file includes the log functions of bspam package.</i>
----------------	---

Description

Copyright (C) 2021-2023 The ORF Project Team

Usage

```
## S3 method for class 'initiating'  
log()
```

Details

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 3 of the License, or (at your option) any later version. This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details. A copy of the GNU General Public License is available at <http://www.gnu.org/licenses/>

This is log.initiating function, which is used to log output.

MCEM	<i>Passage calibration data set</i>
------	-------------------------------------

Description

Passage calibration data set

Usage

MCEM

Format

An object of class mcem of length 2.

passage.calib.bayes	<i>Passage calibration data with bayes</i>
---------------------	--

Description

A data set calibrated with bayes.

Usage

```
passage.calib.bayes
```

Format

two lists: \$pass.param with 150 rows and \$hyper.param with 4 variables

\$pass.param

a parameter controlling binomial success probabilities

b parameter controlling binomial success probabilities

alpha parameter controlling reading times

beta parameter controlling reading times

se_a standard error of a

se_b standard error of b

se_alpha standard error of alpha

se_beta standard error of beta

passage.id passage ID

nwords.p the total

\$hyper.param

vartau variance of latent reading ability tau

rho correlation between two latent variables

se_vartau standard error of vartar

se_rho standard error of rho

Source

<https://jnese.github.io/core-blog/>

passage.calib.mcem	<i>Passage calibration data with MCEM</i>
--------------------	---

Description

A data set calibrated with MCEM.

Usage

```
passage.calib.mcem
```

Format

two lists: \$pass.param with 150 rows and \$hyper.param with 4 variables

\$pass.param

a parameter controlling binomial success probabilities

b parameter controlling binomial success probabilities

alpha parameter controlling reading times

beta parameter controlling reading times

se_a standard error of a

se_b standard error of b

se_alpha standard error of alpha

se_beta standard error of beta

passage.id passage ID

nwords.p the total

\$hyper.param

vartau variance of latent reading ability tau

rho correlation between two latent variables

se_vartau standard error of vartar

se_rho standard error of rho

Source

<https://jnese.github.io/core-blog/>

passage2	<i>Passage-level student data set</i>
----------	---------------------------------------

Description

A data set consisted of reading accuracy and time data for 12 passages from 85 students.

Usage

```
passage2
```

Format

847 rows and 7 variables:

id.student unique student identifier

occasion identifier for longitudinal assessment occasions; here a triannual assessment administered in the fall, winter, and spring of a school year

grade student grade level

id.passage unique passage identifier

numwords.pass total number of words in the passage

wrc words read correct

sec seconds to read the passage

Source

<https://jnese.github.io/core-blog/>

plot.mcem	<i>Plot function to show graph of mcem class</i>
-----------	--

Description

Copyright (C) 2021-2023 The ORF Project Team

Usage

```
## S3 method for class 'mcem'
plot(object, X)
```

Arguments

object	= mcem object
X	= dataset to plot
...	= parameter

Details

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 3 of the License, or (at your option) any later version. This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details. A copy of the GNU General Public License is available at <http://www.gnu.org/licenses/>

```
prep
```

This file includes utilities of bspam package.

Description

Copyright (C) 2021-2023 The ORF Project Team

Usage

```
prep(
  data = data,
  person.id = "",
  task.id = "",
  occasion = "",
  group = "",
  max.counts = "",
  obs.counts = "",
  time = ""
)
```

Arguments

data = student response data

Details

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 3 of the License, or (at your option) any later version. This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details. A copy of the GNU General Public License is available at <http://www.gnu.org/licenses/>

prep function prepares input data for fit.model function

Value

data list (data.long: data frame, data.wide: list of Y, logT10, N, I)

preplong	<i>Prepares data in a long format for [wcpm]</i>
----------	--

Description

Prepares data in a long format for [wcpm]

Usage

```
preplong(
  data,
  person.id,
  task.id,
  occasion,
  group,
  max.counts,
  obs.counts,
  time
)
```

Arguments

data = person response data

Value

data frame

prepwide	<i>Prepares data in a wide format for [mcm].</i>
----------	--

Description

This function will return a list with 5 elements: Y: a matrix of words read correctly, where rows represent cases (student and occasion) and columns represent passages logt10: a [tibble::tibble()] of words read correctly N: the number of cases per passage I: the number of passages

Usage

```
prepwide(data, person.id, task.id, max.counts, obs.counts, time)
```

Arguments

data	A data frame.
time	The column name in the data that represents the time, in seconds, for each case.
studentid	The column name in the data that represents the unique student identifier.
passageid	The column name in the data that represents the unique passage identifier.
numwords.p	The column name in the data that represents the number of words in a passage.
wrc	The column name in the data that represents the words read correctly for each case.

run.mcem

This file includes the Base functions of bspam package.

Description

Copyright (C) 2021-2023 The ORF Project Team

Usage

```
run.mcem(Y, logT10, N, I, k.in = 5, reps.in = 2, ests.in = NA, verbose = FALSE)
```

Arguments

Y	= n x I matrix of reading scores – missingness allowed
logT10	= n x I matrix of log10(reading times) – missingness allowed
N	= vector of passage lengths
I	= number of passages
k.in	= number of imputations, default is 5
reps.in	= number of Monte-Carlo iterations, default is 2
ests.in	= if not give, mom function will be called and get est.in output
verbose	- boolean, if shows the summary, default is FALSE

Details

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 3 of the License, or (at your option) any later version. This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details. A copy of the GNU General Public License is available at <http://www.gnu.org/licenses/>

This is run.mcem function. Update Memo: 04/29/2021 Modified the mcem function based on Nelis's updated. 10/28/2021 Modified the mcem output

Value

mcem list a,b = parameters controlling binomial success probabilities, each length I alpha,beta = parameters controlling reading times, each length I var_tau = variance of latent reading ability tau rho = correlation between two latent variables

run.scoring

This is run.scoring function.

Description

Update Memo: 04/29/2021 Modified the wcpm function based on Nelis's updated. 06/01/2021 Modified based on Nelis's MAP function. 06/01/2021 Modified based on Sarunya's BiEAP function. 06/20/2021 Modified based on Nelis's updated for MLE and EAP 06/21/2021 Modified a bug of MAP function. 07/12/2021 Modified est.eqs function based on Nelis's code. 07/13/2021 Added Map function for bootstrap. 07/30/2021 Modified wcpm function based on Sarunya's update

Usage

```
run.scoring(
  object,
  person.data,
  task.data,
  cases,
  perfect.cases,
  est = "map",
  lo = -4,
  hi = 4,
  q = 100,
  kappa = 1,
  external = NULL,
  type = NULL
)
```

Arguments

object	= fit.model object, if not be given will occur error and stop running
person.data	= individual response task data
task.data	= estimate parameters data
cases	= individual occasion id vector
perfect.cases	= perfect accurate case
est	= estimator, c("mle", "map", "eap", "bayes"), default "map"
lo	= default -4
hi	= default 4
q	= default 100
kappa	= default 1
external	= if not NULL, will use not student read passages for estimating
type	- output type, "general" and "orf", default "general" only output tau & theta. "orf" will output wcpm

Value

wcpm list

scoring

This is an interface function to call and run scoring or bootstrap.

Description

Copyright (C) 2021-2023 The ORF Project Team

Usage

```
scoring(
  calib.data = NA,
  person.data = NA,
  person.id = "",
  task.id = "",
  occasion = "",
  group = "",
  max.counts = "",
  obs.counts = "",
  time = "",
  cases = NULL,
  est = "map",
  se = "analytic",
  failsafe = 0,
  bootstrap = 100,
  external = NULL,
  type = "general"
)
```

Arguments

calib.data	- fit.model class object from calibration
person.data	- individual reading data
person.id	The column name in the data that represents the unique individual identifier.
task.id	The column name in the data that represents the unique task identifier.
occasion	The column name in the data that represents the unique occasion.
group	The column name in the data that represents the unique group.
max.counts	The column name in the data that represents the number of words in a task.
obs.counts	The column name in the data that represents the words read correctly for each case.
time	The column name in the data that represents the time, in seconds, for each case.
cases	- individual id vectors, will directly use task data if no calib.data provided
est	- estimator keyword / c("mle", "map", "eap", "bayes"), default is bayes
se	- standard error keyword / c("analytic", "bootstrap"), default is analytic
failsafe	- retry time for bootstrap / default 0, can set to 5 ~ 50
external	- if not NULL, will use not student read passages for estimating
type	- output type, "general" and "orf", default "general" only output tau & theta. "orf" will output wcpm
bootstrp	- set K number of bootstrap / default 100

Details

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 3 of the License, or (at your option) any later version. This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details. A copy of the GNU General Public License is available at <http://www.gnu.org/licenses/>

Value

scoring list or Bootstrap dataset

summary.bootstrap	<i>summary the information of bootstrap class</i>
-------------------	---

Description

Copyright (C) 2021-2023 The ORF Project Team

Usage

```
## S3 method for class 'bootstrap'
summary(
  object,
  digits = 4,
  geterror = FALSE,
  verbose = TRUE,
  factor.scores = FALSE
)
```

Arguments

object	= bootstrap object
digits	= print out numeric with specific digits
geterror,	summary error case, default FALSE
verbose	show summary on screen, default TRUE
factor.scores	- theta and tau output flag, default is FALSE

Details

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 3 of the License, or (at your option) any later version. This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details. A copy of the GNU General Public License is available at <http://www.gnu.org/licenses/>

Value

table

summary.fit.model	<i>summary the information of fit.model class</i>
-------------------	---

Description

Copyright (C) 2021-2023 The ORF Project Team

Usage

```
## S3 method for class 'fit.model'
summary(object, digits = 4, ...)
```

Arguments

object	= object
digits	= print out numeric with specific digits
...	= parameter

Details

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 3 of the License, or (at your option) any later version. This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details. A copy of the GNU General Public License is available at <http://www.gnu.org/licenses/>

Value

printing information

summary.scoring	<i>summary the information of wcpm class</i>
-----------------	--

Description

Copyright (C) 2021-2023 The ORF Project Team

Usage

```
## S3 method for class 'scoring'
summary(
  object,
  digits = 4,
  verbose = TRUE,
  factor.scores = FALSE,
  show = "short"
)
```

Arguments

<code>object</code>	= object
<code>digits</code>	= print out numeric with specific digits
<code>verbose</code>	- boolean, if TRUE, shows the summary, default is TRUE
<code>factor.scores</code>	- theta and tau output flag, default is FALSE
<code>show</code>	- output flag, "long" and "short", default "short" only output estimate result. "long" will output estimate result and data.

Details

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 3 of the License, or (at your option) any later version. This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details. A copy of the GNU General Public License is available at <http://www.gnu.org/licenses/>

Value

scoring dataset with task information and estimated score

Index

* datasets

- MCEM, [9](#)
- passage.calib.bayes, [10](#)
- passage.calib.mcem, [11](#)
- passage2, [12](#)

- bayes, [3](#)
- bayes.wcpm, [4](#)
- bspam-package, [2](#)

- exclude_passages, [5](#)

- fit.model, [5](#)

- get.cases, [7](#)
- get.perfectcases, [7](#)
- get_errlist, [8](#)
- getBootstrapSE, [8](#)

- log.initiating, [9](#)

- MCEM, [9](#)

- passage.calib.bayes, [10](#)
- passage.calib.mcem, [11](#)
- passage2, [12](#)
- plot.mcem, [12](#)
- prep, [13](#)
- preplong, [14](#)
- prepwid, [14](#)

- run.mcem, [15](#)
- run.scoring, [16](#)

- scoring, [17](#)
- summary.bootstrap, [18](#)
- summary.fit.model, [19](#)
- summary.scoring, [19](#)