

StockFlow API Documentation

Inventory Management System — Production API Guide

Production Base URL

```
https://stockflow-production-ba92.up.railway.app/api
```

StockFlow provides REST APIs for authentication, dashboard statistics, product management, user profiles, and organization settings.

Authentication

Protected endpoints require a JWT token in the Authorization header.

```
Authorization: Bearer YOUR_JWT_TOKEN
```

1. Authentication APIs

1.1 Create Account

Method: POST

Endpoint: /api/auth/signup

Authentication Required: No

Request Body

```
{
  "organizationName": "ABC Store",
  "email": "admin@example.com",
  "password": "password123"
}
```

Success Response

```
{
  "message": "Account created successfully",
  "token": "JWT_TOKEN",
  "user": {
    "id": 1,
    "email": "admin@example.com",
    "organizationId": 1,
    "organizationName": "ABC Store"
  }
}
```

Possible Errors

- 400 — Organization name, email and password are required
- 409 — User already exists
- 500 — Failed to create account

1.2 Login

Method: POST

Endpoint: /api/auth/login

Authentication Required: No

Request Body

```
{
  "email": "admin@example.com",
  "password": "password123"
}
```

Success Response

```
{
  "message": "Login successful",
  "token": "JWT_TOKEN",
  "user": {
    "id": 1,
    "email": "admin@example.com",
    "organizationId": 1,
    "organizationName": "ABC Store"
  }
}
```

Possible Errors

- 400 — Email and password are required
- 401 — Invalid email or password
- 500 — Failed to login

2. Dashboard API

2.1 Get Dashboard Data

Method: GET

Endpoint: /api/dashboard

Authentication Required: Yes

Returns total products, total stock quantity, low-stock count, and low-stock products.

Success Response

```
{
  "totalProducts": 3,
  "totalStock": 75,
  "lowStockCount": 1,
  "lowStockProducts": []
}
```

Possible Errors

- 401 — Authentication required
- 401 — Invalid or expired token
- 500 — Failed to load dashboard

3. Product APIs

3.1 Get All Products

Method: GET

Endpoint: /api/products

Authentication Required: Yes

Success Response

```
{
  "products": [
    {
      "id": 1,
      "name": "Wireless Mouse",
      "sku": "WM-001",
      "description": "Wireless Bluetooth mouse",
      "quantity": 10,
      "costPrice": 500,
      "sellingPrice": 799,
      "lowStockThreshold": 5,
      "organizationId": 1
    }
  ]
}
```

Possible Errors

- 401 — Authentication required
- 500 — Failed to fetch products

3.2 Create Product

Method: POST

Endpoint: /api/products

Authentication Required: Yes

Required fields: name and sku. If quantity is omitted, it defaults to 0.

Request Body

```
{
  "name": "Wireless Mouse",
  "sku": "WM-001",
  "description": "Wireless Bluetooth mouse",
  "quantity": 10,
  "costPrice": 500,
  "sellingPrice": 799,
  "lowStockThreshold": 5
}
```

Success Response

```
{
  "message": "Product created successfully",
  "product": {
    "id": 1,
    "name": "Wireless Mouse",
    "sku": "WM-001",
    "quantity": 10
  }
}
```

```
}  
}
```

Possible Errors

- 400 — Product name and SKU are required
- 409 — SKU already exists in your organization
- 500 — Failed to create product

3.3 Update Product

Method: PUT

Endpoint: /api/products/:id

Authentication Required: Yes

Example endpoint: /api/products/1. Any product fields can be updated.

Request Body

```
{  
  "name": "Updated Wireless Mouse",  
  "quantity": 20,  
  "sellingPrice": 899  
}
```

Success Response

```
{  
  "message": "Product updated successfully",  
  "product": {  
    "id": 1,  
    "name": "Updated Wireless Mouse",  
    "quantity": 20,  
    "sellingPrice": 899  
  }  
}
```

Possible Errors

- 404 — Product not found
- 500 — Failed to update product

3.4 Delete Product

Method: DELETE

Endpoint: /api/products/:id

Authentication Required: Yes

Example endpoint: /api/products/1.

Success Response

```
{  
  "message": "Product deleted successfully"  
}
```

Possible Errors

- 404 — Product not found
- 500 — Failed to delete product

4. Profile API

4.1 Get User Profile

Method: GET

Endpoint: /api/profile

Authentication Required: Yes

Success Response

```
{
  "user": {
    "id": 1,
    "email": "admin@example.com",
    "organizationId": 1,
    "organizationName": "ABC Store"
  }
}
```

Possible Errors

- 404 — User not found
- 500 — Failed to load profile

5. Settings APIs

5.1 Get Organization Settings

Method: GET

Endpoint: /api/settings

Authentication Required: Yes

Success Response

```
{
  "organization": {
    "id": 1,
    "name": "ABC Store",
    "defaultLowStockThreshold": 5
  }
}
```

Possible Errors

- 500 — Failed to fetch settings

5.2 Update Organization Settings

Method: PUT

Endpoint: /api/settings

Authentication Required: Yes

You can update one or both fields.

Request Body

```
{
  "name": "ABC Inventory Store",
```

```
"defaultLowStockThreshold": 10
}
```

Success Response

```
{
  "message": "Settings updated successfully",
  "organization": {
    "id": 1,
    "name": "ABC Inventory Store",
    "defaultLowStockThreshold": 10
  }
}
```

Possible Errors

- 404 — Organization not found
- 500 — Failed to update settings

API Endpoint Summary

Method	Endpoint	Description	Auth
POST	/api/auth/signup	Create an account	No
POST	/api/auth/login	Login	No
GET	/api/dashboard	Dashboard statistics	Yes
GET	/api/products	Get all products	Yes
POST	/api/products	Create a product	Yes
PUT	/api/products/:id	Update a product	Yes
DELETE	/api/products/:id	Delete a product	Yes
GET	/api/profile	Get user profile	Yes
GET	/api/settings	Get settings	Yes
PUT	/api/settings	Update settings	Yes

HTTP Status Codes

Status Code	Meaning
200	Request successful
201	Resource created successfully
400	Invalid or missing request data
401	Authentication failed
404	Resource not found
409	Resource already exists
500	Internal server error

Technology Stack

Node.js • Express.js • MySQL • Sequelize ORM • JWT Authentication • bcryptjs

Deployment

Backend API is deployed on Railway.

Backend URL: stockflow-production-ba92.up.railway.app

Frontend URL: <https://stock-flow-steel.vercel.app/login>