

Construction of a voxel-based mesoscopic mouse connectome

Kameron Decker Harris¹ (kamdh@uw.edu), Julie Harris², Hongkui Zeng², Stefan Mihalas², Eric Shea-Brown¹




¹Applied Mathematics, University of Washington, Seattle, WA USA; ²Allen Institute for Brain Science, Seattle, WA USA

Motivation

Improve the resolution of the weight matrix to voxel scale

Broadly, understand interplay of brain **structure** and **information representation** (coding). Examine functional correlations such as spatial maps in relation to structural connectivity.


Tracing experiments



Acknowledgements: ETSB and KDH acknowledge support from NSF Grant #1122106 and a Simons Fellowship in Mathematics. KDH was supported by a Boeing fellowship and the Big Data for Genomics and Neuroscience training grant (UW/NIH). We wish to thank the Allen Institute founders, Paul G. Allen and Jody Allen, for their vision, encouragement and support. Thanks also to the computational neuroscience community at UW and Joel Zylberberg for suggestions and discussions. This work was facilitated through the use of advanced computational, storage, and networking infrastructure provided by the Hyak supercomputer system at the University of Washington.

Previous work: regional model

Oh et al., 2014, Nature 508(7495):207-214



Fit the weight matrix $W^{(r)}$ via non-negative least squares


$$\min_W \|Y^{(r)} - W^{(r)} X^{(r)}\|_F^2$$

$$y^{(r)}_{i,j} = \int_{\text{region } i} \text{target signal of experiment } j$$

$$x^{(r)}_{i,j} = \int_{\text{region } i} \text{source signal of experiment } j$$

This is the same as choosing a voxel scale W where W_{ij} is constrained to be constant for all voxels i in region A and j in region B, for all regions A and B

Voxel model strategy: assume smoothness




Retinotopy (map representation of visual field) in primary visual cortex is maintained from V1 into deeper areas analogous to V2, etc.

Hypothesis:

- like connects strongest to like
- connection strength decreases as similarity decreases
- retinotopy (hence similarity) is smooth

Taken together, suggests connections vary smoothly in space



Smoothness regularized model

Find the voxel-resolution connection matrix W that balances goodness of fit and smoothness:

$$\min_{W \geq 0} \|Y - WX\|_F^2 + \lambda \|WL_x^T + L_y W\|_F^2$$


Goodness of fit (loss) term Smoothness (regularization) term

Data matrices:
 $Y = [y_1, \dots, y_{n_{\text{inj}}}]$
 $X = [x_1, \dots, x_{n_{\text{inj}}}]$


L_x, L_y : finite difference Laplacian matrices. The Laplacian penalty is analogous to so-called "thin-plate splines" radial basis functions for regression or interpolation

Voxel approach begins to reveal spatial connectivity maps

Regional



Voxel-based



Voxel approach yields more predictive connectivities

Regional model

	regional error	voxel error
ipsi:	23%	47%
contra:	83%	87%

Cross-validated mean square errors relative to $\|y^{\text{pred}}\|^2 + \|y^{\text{true}}\|^2$

To compute **regional error** for the voxel model, we integrate predicted expression over regions:
 $y^{\text{pred},r} = \int_{\text{region } r} y^{\text{pred}}$
then compute the error $\|y^{\text{pred},r} - y^{\text{true},r}\|^2$ in "regional space".

Voxel model

	regional error	voxel error
ipsi:	12%	32%
contra:	61%	75%

To compute **voxel error** for the regional model, we set all voxels in a region equal to the same value:
 $y^{\text{pred},i} = y^{\text{pred},r}_{\text{region } j} / |\text{region } j|$

for all voxels i in region j . Then the error is computed in "voxel space".

Challenges and future work

- Compare Cre cell type-specific connectivity
- Compare spatial maps of retinotopy to connectivity
- Fit entire mouse brain, requires massive parallelization