

Script 3b

Pain progression: individual data

Peter Kamerman

24 January 2020

Contents

| | |
|--|----------|
| Analysis notes | 1 |
| Definitions of missingness | 1 |
| Definition of data inconsistencies | 1 |
| Import data | 2 |
| Quick look | 2 |
| Basic clean | 2 |
| Quick tabulation | 2 |
| Analysis data set for the period 0 to 48 weeks | 2 |
| Pain per visit: | 3 |
| Plot summary data vs participant-level data | 3 |
| Tabulate pain progression patterns | 4 |
| Number of sequences with ‘yes’ in series | 5 |
| Session information | 7 |

Analysis notes

Definitions of missingness

Data were regarded as **missing** when *pain in the last week* data were not present for one or more of weeks 0, 12, 24, 36, 48. Data also were classified as **missing** when there were inconsistencies in the data across the variables collected within a week.

Definition of data inconsistencies

Pain was defined as *pain in the last week* being ‘Yes’, and *pain at its worst* being > 0 . These two measurements were then the “gatekeeper” measurements, such that the two measurements both had to be positive (‘Yes’ and ‘ > 0 ’, respectively) in order for there to be any entries for *site of pain* and *site of worst pain*. Were the data were inconsistent (e.g., when there was no *pain in the last week* and *pain at its worst* = 0, but there were entries for *site of pain* and *site of worst pain*), then the *site of pain* and *site of worst pain* entries were marked as **inconsistent**.

Data also were considered **inconsistent** when *pain in the last week* = ‘Yes’, but *site of worst pain* = ‘None’.

Lastly, data were considered **inconsistent** when *site of worst pain* was not listed as one of the pain locations for a given measurement week.

For analysis purposes, missing data in the *site of pain* columns were changed to ‘No’ (pain not present in the site). This approach was conservative, but we believed that the approach would have the least effect on the outcome, while still retaining as many participants as possible.

Import data

```
df <- read_rds('data-cleaned/data-ADVANCE.rds') %>%
  select(ranid, interval_name, pain_in_the_last_week,
         any_missing, interval_numeric)
```

Quick look

```
head(df)
```

```
## # A tibble: 6 x 5
##   ranid   interval_name pain_in_the_last_week any_missing interval_numeric
##   <chr>   <ord>          <chr>              <chr>          <dbl>
## 1 01-0001 0 weeks      No                No                0
## 2 01-0001 12 weeks   No                No                12
## 3 01-0001 24 weeks   No                No                24
## 4 01-0001 36 weeks   No                No                36
## 5 01-0001 48 weeks   No                No                48
## 6 01-0002 0 weeks    No                No                0
```

```
glimpse(df)
```

```
## Observations: 5,265
## Variables: 5
## $ ranid          <chr> "01-0001", "01-0001", "01-0001", "01-0001", "...
## $ interval_name  <ord> 0 weeks, 12 weeks, 24 weeks, 36 weeks, 48 wee...
## $ pain_in_the_last_week <chr> "No", "No", "No", "No", "No", "No", "Yes", "Y...
## $ any_missing     <chr> "No", "No", "No", "No", "No", "No", "No", "No...
## $ interval_numeric <dbl> 0, 12, 24, 36, 48, 0, 12, 24, 36, 48, 0, 12, ...
```

Basic clean

```
# Clean and process data
df %<>%
  filter(any_missing == 'No') %>%
  select(-any_missing) %>%
  rename(time_weeks = interval_numeric)
```

Quick tabulation

Analysis data set for the period 0 to 48 weeks


```
# Tabulate data
xtabs(~interval_name, data = df)
```

```
## interval_name
## 0 weeks 12 weeks 24 weeks 36 weeks 48 weeks
##      787      787      787      787      787
```

Pain per visit:

Plot summary data vs participant-level data

```
# Generate participant-level plot
plot_individual <- df %>%
  group_by(interval_name) %>%
  mutate(id = row_number()) %>%
  ggplot(.) +
  aes(x = factor(time_weeks),
      y = id) +
  geom_tile(aes(fill = pain_in_the_last_week),
            width = 1) +
  scale_fill_tableau(name = 'Pain in the last week: ') +
  labs(x = 'Time (weeks)',
       y = 'Number of participants') +
  theme_minimal(base_size = 16) +
  theme(legend.position = 'top',
        panel.grid.minor = element_blank()); plot_individual
```



Tabulate pain progression patterns

```
# Generate the pain sequences
df_sequence <- df %>%
  select(ranid, interval_name, pain_in_the_last_week) %>%
  mutate(pain_in_the_last_week = as.character(pain_in_the_last_week)) %>%
  pivot_wider(names_from = interval_name,
              values_from = pain_in_the_last_week) %>%
  unite(col = 'sequence', -ranid, sep = ' ') %>%
  mutate(any_pain = str_detect(sequence, pattern = 'Yes'))

# x-tabulate the sequences
df_xtab <- as.data.frame(xtabs(~sequence, data = df_sequence)) %>%
  arrange(desc(Freq)) %>%
  rename(frequency = Freq) %>%
  mutate(percent = round(100 * frequency / sum(frequency), 2))

# Print table
kable(df_xtab,
      caption = 'Pain in the last week for weeks 0, 12, 24, 36 and 48')
```

Table 1: Pain in the last week for weeks 0, 12, 24, 36 and 48

| sequence | frequency | percent |
|---------------------|-----------|---------|
| No No No No No | 393 | 49.94 |
| Yes No No No No | 67 | 8.51 |
| No Yes No No No | 50 | 6.35 |
| No No Yes No No | 44 | 5.59 |
| No No No Yes No | 32 | 4.07 |
| No No No No Yes | 28 | 3.56 |
| Yes Yes No No No | 22 | 2.80 |
| Yes No Yes No No | 16 | 2.03 |
| No Yes No Yes No | 15 | 1.91 |
| No No No Yes Yes | 13 | 1.65 |
| No No Yes Yes No | 13 | 1.65 |
| No Yes Yes No No | 13 | 1.65 |
| No Yes No No Yes | 10 | 1.27 |
| Yes No No No Yes | 10 | 1.27 |
| No Yes Yes Yes No | 9 | 1.14 |
| No No Yes No Yes | 8 | 1.02 |
| Yes No No Yes No | 6 | 0.76 |
| Yes Yes No Yes Yes | 6 | 0.76 |
| Yes No Yes No Yes | 4 | 0.51 |
| Yes No Yes Yes No | 4 | 0.51 |
| No No Yes Yes Yes | 3 | 0.38 |
| No Yes No Yes Yes | 3 | 0.38 |
| Yes Yes Yes No No | 3 | 0.38 |
| Yes Yes Yes No Yes | 3 | 0.38 |
| No Yes Yes Yes Yes | 2 | 0.25 |
| Yes No Yes Yes Yes | 2 | 0.25 |
| Yes Yes No No Yes | 2 | 0.25 |
| Yes Yes No Yes No | 2 | 0.25 |
| Yes Yes Yes Yes No | 2 | 0.25 |
| Yes No No Yes Yes | 1 | 0.13 |
| Yes Yes Yes Yes Yes | 1 | 0.13 |

Number of sequences with ‘yes’ in series

```

# Extract sequences
df_yes <- df_sequence %>%
  mutate(yes_2 = str_detect(sequence, pattern = 'Yes Yes')) %>%
  mutate(yes_3 = str_detect(sequence, pattern = 'Yes Yes Yes')) %>%
  mutate(yes_4 = str_detect(sequence, pattern = 'Yes Yes Yes Yes')) %>%
  mutate(yes_5 = str_detect(sequence, pattern = 'Yes Yes Yes Yes Yes'))

# Create filters
vec_filter_2yes <- df_yes %>%
  filter(yes_2 == TRUE) %>%
  .$ranid

vec_filter_3yes <- df_yes %>%
  filter(yes_3 == TRUE) %>%
  .$ranid

vec_filter_4yes <- df_yes %>%
  filter(yes_4 == TRUE) %>%
  .$ranid

```

```

vec_filter_5yes <- df_yes %>%
  filter(yes_5 == TRUE) %>%
  .$ranid

# Extract data
df_2yes <- df_yes %>%
  filter(!ranid %in% vec_filter_5yes) %>%
  filter(!ranid %in% vec_filter_4yes) %>%
  filter(!ranid %in% vec_filter_3yes) %>%
  filter(ranid %in% vec_filter_2yes)

df_3yes <- df_yes %>%
  filter(!ranid %in% vec_filter_5yes) %>%
  filter(!ranid %in% vec_filter_4yes) %>%
  filter(ranid %in% vec_filter_3yes)

df_4yes <- df_yes %>%
  filter(!ranid %in% vec_filter_5yes) %>%
  filter(ranid %in% vec_filter_4yes)

df_5yes <- df_yes %>%
  filter(ranid %in% vec_filter_5yes)

# Sequences with 2 'yes' in series ONLY
kable(data.frame('type' = c('Sequence count', 'Percent of total sequences'),
  'value' = c(round(sum(df_2yes$yes_2)),
    round(100 * (sum(df_2yes$yes_2) /
      sum(df_xtab$frequency)), 2))),
  caption = "Sequences with 2 'yes' (pain present) in series")

```

Table 2: Sequences with 2 ‘yes’ (pain present) in series

| type | value |
|----------------------------|-------|
| Sequence count | 79.00 |
| Percent of total sequences | 10.04 |

```

# Sequences with 3 'yes' (pain present) in series ONLY
kable(data.frame('type' = c('Sequence count', 'Percent of total sequences'),
  'value' = c(round(sum(df_3yes$yes_3)),
    round(100 * (sum(df_3yes$yes_3) /
      sum(df_xtab$frequency)), 2))),
  caption = "Sequences with 3 'yes' (pain present) in series")

```

Table 3: Sequences with 3 ‘yes’ (pain present) in series

| type | value |
|----------------------------|-------|
| Sequence count | 20.00 |
| Percent of total sequences | 2.54 |

```

# Sequences with 4 'yes' (pain present) in series ONLY
kable(data.frame('type' = c('Sequence count', 'Percent of total sequences'),
  'value' = c(round(sum(df_4yes$yes_4)),
    round(100 * (sum(df_4yes$yes_4) /
      sum(df_xtab$frequency)), 2))),
  caption = "Sequences with at least 4 'yes' (pain present) in series")

```

Table 4: Sequences with at least 4 ‘yes’ (pain present) in series

| type | value |
|----------------------------|-------|
| Sequence count | 4.00 |
| Percent of total sequences | 0.51 |

```
# Sequences with at least 5 'yes' (pain present) in series
kable(data.frame('type' = c('Sequence count', 'Percent of total sequences'),
  'value' = c(round(sum(df_5yes$yes_5)),
    round(100 * (sum(df_5yes$yes_5) /
      sum(df_xtab$frequency)), 2))),
  caption = "Sequences with at least 5 'yes' (pain present) in series")
```

Table 5: Sequences with at least 5 ‘yes’ (pain present) in series

| type | value |
|----------------------------|-------|
| Sequence count | 1.00 |
| Percent of total sequences | 0.13 |

```
# Number of participants with isolated pain
787 - sum(c(393,79, 20, 4, 1))

## [1] 290

# Proportion of participants with isolated pain
(787 - sum(c(393,79, 20, 4, 1)))/787

## [1] 0.3684879
```

Session information

```
sessionInfo()

## R version 3.6.1 (2019-07-05)
## Platform: x86_64-apple-darwin15.6.0 (64-bit)
## Running under: macOS Mojave 10.14.6
##
## Matrix products: default
## BLAS: /Library/Frameworks/R.framework/Versions/3.6/Resources/lib/libRblas.0.dylib
## LAPACK: /Library/Frameworks/R.framework/Versions/3.6/Resources/lib/libRlapack.dylib
##
## locale:
## [1] en_US.UTF-8/en_US.UTF-8/en_US.UTF-8/C/en_US.UTF-8/en_US.UTF-8
##
## attached base packages:
## [1] stats graphics grDevices utils datasets methods base
##
## other attached packages:
## [1] knitr_1.27 patchwork_1.0.0 ggthemes_4.2.0 magrittr_1.5
## [5] forcats_0.4.0 stringr_1.4.0 dplyr_0.8.3 purrr_0.3.3
## [9] readr_1.3.1 tidyr_1.0.0 tibble_2.1.3 ggplot2_3.2.1
## [13] tidyverse_1.3.0
##
## loaded via a namespace (and not attached):
```

```
## [1] tidyselect_0.2.5 xfun_0.12      haven_2.2.0      lattice_0.20-38
## [5] colorspace_1.4-1  vctrs_0.2.1     generics_0.0.2   htmltools_0.4.0
## [9] yaml_2.2.0        utf8_1.1.4      rlang_0.4.2      pillar_1.4.3
## [13] withr_2.1.2       glue_1.3.1      DBI_1.1.0        dbplyr_1.4.2
## [17] modelr_0.1.5      readxl_1.3.1    lifecycle_0.1.0  munsell_0.5.0
## [21] gtable_0.3.0      cellranger_1.1.0 rvest_0.3.5      evaluate_0.14
## [25] labeling_0.3      fansi_0.4.1     highr_0.8        broom_0.5.3
## [29] Rcpp_1.0.3        scales_1.1.0    backports_1.1.5  jsonlite_1.6
## [33] farver_2.0.3      fs_1.3.1        hms_0.5.3        digest_0.6.23
## [37] stringi_1.4.5     grid_3.6.1      cli_2.0.1        tools_3.6.1
## [41] lazyeval_0.2.2    crayon_1.3.4    pkgconfig_2.0.3  zeallot_0.1.0
## [45] ellipsis_0.3.0    xml2_1.2.2      reprex_0.3.0     lubridate_1.7.4
## [49] assertthat_0.2.1  rmarkdown_2.1   httr_1.4.1       rstudioapi_0.10
## [53] R6_2.4.1          nlme_3.1-143    compiler_3.6.1
```