

Supplement 3

Descriptive statistics on participant follow-up

Peter Kamerman and Prinisha Pillay

17 March 2019

Contents

Import data	1
Process data	1
Inspect data	2
Clinic visits	3
Whole cohort	3
By SN status	4
Analysis	7
Process data	7
Number of clinic visits	8
Time between first and last visit	11
Time between successive clinic visits	14
Session information	17

This analysis describes the follow-up pattern of participants in the study.

Import data

```
data <- read_rds('data-cleaned/clean_data.rds') %>%  
  # Select columns  
  select(ID, visit_number, visit_day, visit_months, hivsn_present)
```

Process data

Add a column indicating whether a participant developed SN at any time during the follow-up period.

```
# Identify and extract information on SN development (at anytime)  
# by looking at the presence of SN at the final visit  
data_sn <- data %>%  
  select(ID, visit_number, hivsn_present) %>%  
  group_by(ID) %>%  
  mutate(max_visit = max(visit_number)) %>%  
  filter(visit_number == max_visit) %>%  
  select(ID, hivsn_present) %>%  
  rename(sn = hivsn_present)
```

```
# Join data_sn to data
data %<>%
  left_join(data_sn)
```

Inspect data

```
# Dimensions
dim(data)

## [1] 371 6

# Column names
names(data)

## [1] "ID" "visit_number" "visit_day" "visit_months"
## [5] "hivsn_present" "sn"

# Head and tail
head(data)

## # A tibble: 6 x 6
##   ID visit_number visit_day visit_months hivsn_present sn
##   <chr>      <int>    <int>      <dbl> <fct>      <fct>
## 1 001          1         0          0 no        no
## 2 001          2        40          1 no        no
## 3 001          3       210          7 no        no
## 4 002          1         0          0 no        no
## 5 002          2        71          2 no        no
## 6 002          3       191          6 no        no

tail(data)

## # A tibble: 6 x 6
##   ID visit_number visit_day visit_months hivsn_present sn
##   <chr>      <int>    <int>      <dbl> <fct>      <fct>
## 1 119          1         0          0 no        no
## 2 119          2        72          2 no        no
## 3 119          3       132          4 no        no
## 4 120          1         0          0 no        no
## 5 120          2        88          3 no        no
## 6 120          3       124          4 no        no

# Data structure
glimpse(data)

## Observations: 371
## Variables: 6
## $ ID      <chr> "001", "001", "001", "002", "002", "002", "003", ...
## $ visit_number <int> 1, 2, 3, 1, 2, 3, 1, 2, 3, 1, 2, 3, 1, 2, 3, 1, ...
## $ visit_day   <int> 0, 40, 210, 0, 71, 191, 0, 57, 207, 0, 84, 189, ...
## $ visit_months <dbl> 0, 1, 7, 0, 2, 6, 0, 2, 7, 0, 3, 6, 0, 2, 6, 0, ...
## $ hivsn_present <fct> no, no, no, no, no, no, no, no, no, no, no, no, no, ...
## $ sn         <fct> no, no, no, no, no, no, no, no, no, no, no, no, no, ...
```

Clinic visits


Whole cohort

```
data %>%
  # Process data for plotting
  group_by(ID) %>%
  mutate(visit = ifelse(visit_day > 0,
                        yes = 1,
                        no = 0),
         visit_count = cumsum(visit),
         max_visits = max(visit_count),
         max_duration = max(visit_day)) %>%
  ungroup() %>%
  select(ID, visit_day, visit_months,
         visit_count, max_visits,
         max_duration) %>%
  # Clean-up and order dataframe
  arrange(max_duration, max_visits, desc(ID)) %>%
  mutate(ID = as_factor(ID),
         visit_count = as.character(visit_count)) %>%
  complete(ID, visit_months) %>%
  # Add a dummy variable for faceting
  bind_cols(facet = c(rep('Panel 1', 600), rep('Panel 2', 1202-600))) %>%
  # Clean-up and order dataframe
  filter(complete.cases(.)) %>%
  # Plot
  ggplot(data = .) +
  aes(x = visit_day,
      y = ID) +
  geom_path(colour = '#888888') +
  geom_point(aes(fill = visit_count),
             shape = 21,
             size = 3) +
  scale_x_continuous(breaks = seq(0, 250, 25)) +
  scale_fill_manual(name = 'Visit count: ', values = grey_pal) +
  labs(title = 'Timing of clinic visits',
       subtitle = 'Visit number coded by fill colour',
       y = 'Participant ID',
       x = 'Days') +
  facet_wrap(~facet,
            ncol = 2,
            scales = 'free_y') +
  theme(legend.position = 'top',
        legend.margin = margin(t = -0.3,
                                r = 0,
                                b = -0.3,
                                l = 0, 'lines'),
        panel.grid = element_blank(),
        strip.background = element_blank(),
        strip.text = element_blank())
```

Timing of clinic visits

Visit number coded by fill colour

Visit count: ○ 0 ● 1 ● 2 ● 3 ● 4



By SN status

```
data_plot <- data %>%
  # Process data for plotting
  group_by(ID) %>%
```

```

mutate(visit = ifelse(visit_day > 0,
                      yes = 1,
                      no = 0),
       visit_count = cumsum(visit),
       max_visits = max(visit_count),
       max_duration = max(visit_day)) %>%
ungroup() %>%
select(ID, hivsn_present, visit_day, visit_months,
       visit_count, max_visits,
       max_duration, sn) %>%
# Clean-up and order dataframe
arrange(max_duration, max_visits, desc(ID)) %>%
mutate(ID = as_factor(ID),
       visit_count = as.character(visit_count)) %>%
complete(ID, visit_months) %>%
# Clean-up and order dataframe
filter(complete.cases(.)) %>%
# Recode facetting column
mutate(sn = as.character(sn),
       sn = ifelse(sn == 'yes',
                   yes = 'Neuropathy developed',
                   no = 'No neuropathy'),
       sn = factor(sn,
                   levels = c('No neuropathy', 'Neuropathy developed'),
                   ordered = TRUE)) %>%
mutate(hivsn_present = str_to_title(hivsn_present))


# Plot
ggplot(data = data_plot) +
  aes(x = visit_day,
      y = ID) +
  geom_path(colour = '#888888') +
  geom_point(aes(fill = hivsn_present),
            shape = 21,
            size = 3) +
  labs(title = 'Timing of clinic visits, faceted by whether SN developed',
       subtitle = 'Time-points where SN was present are coded by fill colour',
       x = 'Days',
       y = 'Participant ID') +
  scale_x_continuous(breaks = seq(0, 250, 25)) +
  scale_fill_manual(name = 'Neuropathy present: ',
                   values = c('#FFFFFF', '#000000')) +
  facet_wrap(~ sn,
            ncol = 2,
            scales = 'free_y') +
  theme(legend.position = 'top',
       legend.margin = margin(t = -0.3,
                              r = 0,
                              b = -0.3,
                              l = 0, 'lines'),
       panel.grid = element_blank())

```

Timing of clinic visits, faceted by whether SN developed

Time-points where SN was present are coded by fill colour

Neuropathy present: ○ No ● Yes



```
# Publication plot
gg_plot <- data_plot %>%
  ggplot(data = .) +
  aes(x = visit_day,
      y = ID) +
  geom_path(colour = '#888888') +
```

```

geom_point(aes(fill = hivsn_present),
           shape = 21,
           size = 3) +
labs(x = 'Days',
     y = 'Participant ID') +
scale_x_continuous(breaks = seq(0, 250, 25)) +
scale_fill_manual(name = 'Neuropathy present: ',
                  values = c('#FFFFFF', '#000000')) +
facet_wrap(~ sn,
           ncol = 2,
           scales = 'free_y') +
theme(legend.position = 'top',
      legend.text = element_text(size = 11),
      legend.title = element_text(size = 11),
      axis.text.y = element_text(colour = '#000000'),
      axis.text.x = element_text(colour = '#000000',
                                size = 12),
      axis.title = element_text(size = 14),
      panel.grid = element_blank(),
      panel.border = element_rect(size = 1),
      strip.text = element_text(size = 12))

ggsave(filename = 'figures/follow-up.png',
       plot = gg_plot,
       width = 9,
       height = 11)

```

Analysis

Process data

```

# Generate visit data
data_v1 <- data %>%
  # Calculations per individual
  group_by(ID) %>%
  mutate(# Extract the max number of visits
         max_visits = max(visit_number),
         # Time from visit 1 to the last visit
         max_duration = max(visit_day),
         # Time between successive visits
         visit_break = visit_day - lag(visit_day),
         # Running mean time (days) between visits
         cumulative_mean = round(cummean(visit_day))) %>%
  ungroup() %>%
  # Select required columns
  select(ID, visit_number, visit_day, visit_break, max_visits,
         max_duration, cumulative_mean) %>%
  left_join(data_sn)

# Filter based on maximum number of visits
data_v2 <- data_v1 %>%

```

```

# Per individual
group_by(ID) %>%
# Get maximum number of visits
filter(visit_number == max_visits) %>%
ungroup()

```

Number of clinic visits

```

# Summary table
data_v2 %>%
  summarise(n = n(),
            Median.visits = median(max_visits),
            Q25 = quantile(max_visits, 0.25),
            Q75 = quantile(max_visits, 0.75),
            min = min(max_visits),
            max = max(max_visits))

## # A tibble: 1 x 6
##       n Median.visits   Q25   Q75   min   max
##   <int>         <dbl> <dbl> <dbl> <dbl> <dbl>
## 1   120             3     3     3     2     5

# Summary table (conditioned on sn)
data_v2 %>%
  group_by(sn) %>%
  summarise(n = n(),
            Median.visits = median(max_visits),
            Q25 = quantile(max_visits, 0.25),
            Q75 = quantile(max_visits, 0.75),
            min = min(max_visits),
            max = max(max_visits))

## # A tibble: 2 x 7
##       sn       n Median.visits   Q25   Q75   min   max
##   <fct> <int>         <dbl> <dbl> <dbl> <dbl> <dbl>
## 1 no     100             3     3     3     2     5
## 2 yes    20             3     3   3.25     3     5

# Plots
gg_v2a <- data_v2 %>%
  group_by(max_visits) %>%
  summarise(count = n()) %>%
  mutate(visits = fct_relevel(factor(max_visits), '5', '4', '3')) %>%
  ggplot(data = .) +
  aes(y = count,
      x = 'all',
      fill = visits) +
  geom_bar(stat = 'identity') +
  scale_fill_grey() +
  labs(title = 'Number of clinic visits (counts)',
       subtitle = '(All participants)',
       y = 'Count') +
  theme(axis.title.x = element_blank(),
        axis.text.x = element_blank())


```



```
gg_v2b <- data_v2 %>%
  group_by(max_visits) %>%
  summarise(count = n()) %>%
  mutate(visits = fct_relevel(factor(max_visits), '5', '4', '3')) %>%
  ggplot(data = .) +
  aes(y = count,
      x = 'all',
      fill = visits) +
  geom_bar(stat = 'identity',
          position = position_fill()) +
  scale_fill_grey() +
  labs(title = 'Number of clinic visits (proportion)',
       subtitle = '(All participants)',
       y = 'Proportion') +
  theme(axis.title.x = element_blank(),
        axis.text.x = element_blank())
```

Plot next to each other using patchwork package

```
gg_v2a + gg_v2b
```



```
## Conditional on SN
gg_v2c <- data_v2 %>%
  group_by(sn, max_visits) %>%
  summarise(count = n()) %>%
  mutate(visits = factor(max_visits,
                        levels = c('5', '4', '3', '2'),
                        ordered = TRUE)) %>%
```

```


ggplot(data = .) +
  aes(y = count,
       x = sn,
       fill = visits) +
  geom_bar(stat = 'identity') +
  scale_fill_grey() +
  labs(title = 'Number of clinic visits (proportion)',
       subtitle = '(All participants)',
       y = 'Proportion') +
  theme(axis.title.x = element_blank(),
       axis.text.x = element_blank())

gg_v2d <- data_v2 %>%
  group_by(sn, max_visits) %>%
  summarise(count = n()) %>%
  mutate(visits = factor(max_visits,
                        levels = c('5', '4', '3', '2'),
                        ordered = TRUE)) %>%

  ggplot(data = .) +
  aes(y = count,
       x = sn,
       fill = visits) +
  geom_bar(stat = 'identity',
           position = position_fill()) +
  scale_fill_grey() +
  labs(title = 'Number of clinic visits (proportion)',
       subtitle = '(All participants)',
       y = 'Proportion') +
  theme(axis.title.x = element_blank(),
       axis.text.x = element_blank())

# Plot next to each other using patchwork package
gg_v2c + gg_v2d

```



```
# Stats
chisq_test(xtabs(~ sn + visit_number,
  data = data_v2),
  distribution = approximate(B = 10000))
```

```
##
## Approximative Pearson Chi-Squared Test
##
## data: visit_number by sn (no, yes)
## chi-squared = 4.3515, p-value = 0.2209
```

Time between first and last visit

```
# Summary table
data_v2 %>%
  summarise(n = n(),
    Median.days = median(max_duration),
    Q25 = quantile(max_duration, 0.25),
    Q75 = quantile(max_duration, 0.75),
    min = min(max_duration),
    max = max(max_duration))


## # A tibble: 1 x 6
##       n Median.days   Q25   Q75   min   max
##   <int>      <dbl> <dbl> <dbl> <dbl> <dbl>
## 1   120        186  140.  201.   39   263
```

```
# Summary table (conditioned on sn)
data_v2 %>%
  group_by(sn) %>%
  summarise(n = n(),
            Median.days = median(max_duration),
            Q25 = quantile(max_duration, 0.25),
            Q75 = quantile(max_duration, 0.75),
            min = min(max_duration),
            max = max(max_duration))

## # A tibble: 2 x 7
##   sn      n Median.days  Q25   Q75   min   max
##   <fct> <int>      <dbl> <dbl> <dbl> <dbl> <dbl>
## 1 no     100      184  133.  199.   39  263
## 2 yes    20      195  182.  208.  166  243
```

```
# Plots
data_v2 %>%
  ggplot(data = .) +
  aes(y = max_duration,
      x = 'All patients') +
  geom_boxplot() +
  geom_jitter(height = 0) +
  labs(title = 'Number of days of follow-up',
       subtitle = '(All participants)',
       y = 'Days') +
  theme(axis.title.x = element_blank(),
        axis.text.x = element_blank())
```


Number of days of follow-up
(All participants)



```
## Conditional on SN
data_v2 %>%
  ggplot(data = .) +
  aes(y = max_duration,
      x = sn) +
  geom_boxplot() +
  geom_jitter(height = 0) +
  labs(title = 'Number of days of follow-up',
       subtitle = 'SN:yes vs SN:no',
       y = 'Days',
       x = 'SN present')
```

Number of days of follow-up

SN:yes vs SN:no



```
# Stats
normal_test(max_duration ~ factor(sn),
            data = data_v2,
            distribution = approximate(B = 10000))

##
## Approximative Two-Sample van der Waerden (Normal Quantile) Test
##
## data: max_duration by factor(sn) (no, yes)
## Z = -2.103, p-value = 0.0342
## alternative hypothesis: true mu is not equal to 0
```

Time between successive clinic visits

```
# Summary table
data_v1 %>%
  filter(visit_number != 1) %>%
  group_by(visit_number) %>%
  summarise(n = n(),
            Mean.days = mean(visit_break),
            Median.days = median(visit_break),
            SD = sd(visit_break),
            Q25 = quantile(visit_break, 0.25),
            Q75 = quantile(visit_break, 0.75),
            min = min(visit_break),
            max = max(visit_break))

## # A tibble: 4 x 9
##   visit_number     n Mean.days Median.days    SD    Q25    Q75    min    max
##   <int> <int>    <dbl>    <dbl> <dbl> <dbl> <dbl> <dbl> <dbl>
## 1         2    120     72.4     69.5  27.1   55    89     14    151
## 2         3    105    100.     102   44.4   60   135     14    204
## 3         4     19     54.9     50   34.4   27.5  80.5      9    132
## 4         5      7     57.7     61   21.8   46.5   63     28     96


# Summary table (conditioned on sn)
data_v1 %>%
  filter(visit_number != 1) %>%
  group_by(visit_number, sn) %>%
  summarise(n = n(),
            Mean.days = mean(visit_break),
            Median.days = median(visit_break),
            SD = sd(visit_break),
            Q25 = quantile(visit_break, 0.25),
            Q75 = quantile(visit_break, 0.75),
            min = min(visit_break),
            max = max(visit_break))

## # A tibble: 8 x 10
## # Groups:   visit_number [4]
##   visit_number sn      n Mean.days Median.days    SD    Q25    Q75    min
##   <int> <fct> <int>    <dbl>    <dbl> <dbl> <dbl> <dbl> <dbl>
## 1         2 no     100     71.4     69.5  25.8   56    87.2    14
## 2         2 yes      20     77.6      69   33.1   52   104.     28
## 3         3 no      85    100.     102   43.1   60   138     26
## 4         3 yes      20     99.2     102   50.7   66.8  120.     14
## 5         4 no      14     53.6      55   29.8   29.2  75.5      9
## 6         4 yes       5     58.6      28   49.2   27    87     19
## 7         5 no       5     62.6      61   21.3   56    63     37
## 8         5 yes       2     45.5     45.5  24.7   36.8   54.2     28
## # ... with 1 more variable: max <dbl>

# Plots
data_v1 %>%
  filter(visit_number != 1) %>%
  ggplot(data = .) +
  aes(y = visit_break,
      x = factor(visit_number)) +
```

```
geom_boxplot() +
geom_jitter(height = 0) +
scale_x_discrete(labels = c('1 to 2', '2 to 3',
                             '3 to 4', '4 to 5')) +
labs(title = 'Days between successive clinic visit ',
      subtitle = '(All participants)',
      y = 'Days',
      x = 'Visit interval')
```


Days between successive clinic visit
(All participants)



```
## Conditional on SN
data_v1 %>%
  filter(visit_number != 1) %>%
  ggplot(data = .) +
  aes(y = visit_break,
       x = factor(visit_number),
       fill = sn) +
  geom_boxplot(alpha = 0.6) +
  geom_point(position = position_jitterdodge(jitter.height = 0)) +
  scale_x_discrete(labels = c('1 to 2', '2 to 3',
                              '3 to 4', '4 to 5')) +
  scale_fill_grey(name = 'Neuropathy\npresent') +
  labs(title = 'Days between successive clinic visits',
        subtitle = 'SN:yes vs SN:no',
        y = 'Days',
        x = 'Visit interval')
```

Days between successive clinic visits

SN:yes vs SN:no




```
# Stats
## Generate data
data_lmer <- data_v1 %>%
  filter(visit_number != 1) %>%
  select(ID, visit_number, visit_break, sn)

## Generate model (ID included as random effects)
mod <- lm(visit_break ~ sn + visit_number,
  data = data_lmer)

## Analysis of Deviance Table (Type II Wald F tests with Kenward-Roger df)
Anova(mod = mod,
  type = 'II',
  test.statistic = 'F')

## Anova Table (Type II tests)
##
## Response: visit_break
##          Sum Sq Df F value Pr(>F)
## sn          43   1  0.0280  0.8673
## visit_number 730   1  0.4767  0.4906
## Residuals 379751 248

## Basic diagnostics
par(mfrow = c(2, 2))
plot(mod)
```

```
par(mfrow = c(1, 1))
```

Session information

```
sessionInfo()

## R version 3.5.2 (2018-12-20)
## Platform: x86_64-apple-darwin15.6.0 (64-bit)
## Running under: macOS Mojave 10.14.3
##
## Matrix products: default
## BLAS: /Library/Frameworks/R.framework/Versions/3.5/Resources/lib/libRblas.0.dylib
## LAPACK: /Library/Frameworks/R.framework/Versions/3.5/Resources/lib/libRlapack.dylib
##
## locale:
## [1] en_US.UTF-8/en_US.UTF-8/en_US.UTF-8/C/en_US.UTF-8/en_US.UTF-8
##
## attached base packages:
## [1] stats      graphics  grDevices  utils      datasets  methods   base
##
## other attached packages:
## [1] car_3.0-2      carData_3.0-2  lmerTest_3.1-0  lme4_1.1-20
## [5] Matrix_1.2-15  coin_1.2-2     survival_2.43-3 patchwork_0.0.1
## [9] forcats_0.4.0  stringr_1.4.0  dplyr_0.8.0.1  purrr_0.3.1
## [13] readr_1.3.1    tidyr_0.8.3    tibble_2.0.1   ggplot2_3.1.0
## [17] tidyverse_1.2.1 magrittr_1.5
##
```

```
## loaded via a namespace (and not attached):
## [1] httr_1.4.0          jsonlite_1.6        splines_3.5.2
## [4] modelr_0.1.4        assertthat_0.2.0    stats4_3.5.2
## [7] cellranger_1.1.0    yaml_2.2.0          numDeriv_2016.8-1
## [10] pillar_1.3.1        backports_1.1.3     lattice_0.20-38
## [13] glue_1.3.0          digest_0.6.18       rvest_0.3.2
## [16] minqa_1.2.4         colorspace_1.4-0    sandwich_2.5-0
## [19] htmltools_0.3.6     plyr_1.8.4          pkgconfig_2.0.2
## [22] broom_0.5.1         haven_2.1.0         mvtnorm_1.0-9
## [25] scales_1.0.0        openxlsx_4.1.0      rio_0.5.16
## [28] generics_0.0.2      ellipsis_0.1.0      TH.data_1.0-10
## [31] withr_2.1.2.9000    lazyeval_0.2.1      cli_1.0.1
## [34] crayon_1.3.4        readxl_1.3.0        evaluate_0.13
## [37] fansi_0.4.0         nlme_3.1-137        MASS_7.3-51.1
## [40] xml2_1.2.0          foreign_0.8-71      tools_3.5.2
## [43] data.table_1.12.0   hms_0.4.2           multcomp_1.4-8
## [46] munsell_0.5.0       zip_2.0.0           compiler_3.5.2
## [49] rlang_0.3.1         grid_3.5.2          nloptr_1.2.1
## [52] rstudioapi_0.9.0    labeling_0.3         rmarkdown_1.11
## [55] gtable_0.2.0        codetools_0.2-16    abind_1.4-5
## [58] curl_3.3            R6_2.4.0            zoo_1.8-4
## [61] lubridate_1.7.4     knitr_1.21          utf8_1.1.4
## [64] modeltools_0.2-22   stringi_1.3.1       Rcpp_1.0.0
## [67] tidyselect_0.2.5    xfun_0.5
```