

Angular

dr hab. inż. Robert Krupiński

app.html

```
1  <h1>My component</h1>
2
3  <div>{{myData.name}}</div>
4  <div>{{myData.surname}}</div>
5
6  <app-my-student></app-my-student>
7  <app-my-student></app-my-student>
8
9  <div>{{myData.name | lowercase}}</div>
10 <div>{{myData.name | uppercase}}</div>
11
12 <ul>
13   @for (building of vBuildings; track building){
14     <li>
15       {{building.name}} {{building.price | currency:"PLN"}}
16     </li>
17   }
18 </ul>
19
20 @if (selectedBuilding){
21   <p>
22     Wybrany={{selectedBuilding.name}}
23   </p>
24 }
25
26
27 <button (click)="onMyToggle()">MyToggle</button>
28 <h2>Licznik: {{ myCount() }}</h2>
29 <br/><br/>
30 <button [disabled]="bToggle">Attribute binding</button>
```

app.ts

```
1  import { Component, signal } from '@angular/core';
2  import { MyStudent } from './my-student/my-student';
3  import { UpperCasePipe, LowerCasePipe, CurrencyPipe } from '@angular/common';
4  import { MyBuilding } from './my-building';
5
6  @Component({
7    selector: 'app-root',
8    imports: [MyStudent, UpperCasePipe, LowerCasePipe, CurrencyPipe],
9    templateUrl: './app.html',
10   styleUrls: ['./app.css']
11 })
12 export class App {
13   protected readonly title = 'simple-app';
14
15   protected myData = {
16     name: "Robert",
17     surname: "Krupiński"
18   }
```

app.ts

```
20 protected vBuildings = [  
21   new MyBuilding(7, "Blue house"),  
22   new MyBuilding(12, "Village house"),  
23   new MyBuilding(24, "Apartment")  
24 ];  
25 protected selectedBuilding?: MyBuilding;  
26  
27 protected bToggle = false  
28  
29 protected myCount = signal(0);  
30  
31 onMyToggle() {  
32   this.bToggle = !this.bToggle  
33   console.log(this.bToggle)  
34  
35   this.myCount.set(this.myCount() + 1)  
36 }  
37  
38 constructor() {  
39   this.selectedBuilding = this.vBuildings[0]  
40 }  
41 }
```

app.css

```
h1 {  
  background-color:  aqua;  
}
```

my-building.ts

```
export class MyBuilding {  
  constructor(  
    public price: number,  
    public name: string) { }  
}
```

my-student.html

```
<p>my-student works!</p>
```

my-student. ts

```
1  import { Component } from '@angular/core';
2
3  @Component({
4    selector: 'app-my-student',
5    imports: [],
6    templateUrl: './my-student.html',
7    styleUrls: ['./my-student.css'],
8  })
9  export class MyStudent {}
```


File location

[.www.rmaes.com/students/2025_2026/Angular.pdf](http://www.rmaes.com/students/2025_2026/Angular.pdf)