

# TBS CROSSFIRE/ TRACER - Multi-bind

**-Deprecated-**


Revision 2021-10-14

The TBS CROSSFIRE/ TRACER now provides you the option to bind one receiver to many transmitters. With this feature, you can choose which transmitter you want to use without the need to rebind the receiver every time.

## What you need

- TBS CROSSFIRE/ TRACER transmitters on FW 3.70 (beta) or later **with WiFi module**
- [TBS Agent X](#) and a logged-in user account - [Agent X manual](#) -
- Internet connection (only once, on setup!)
- the WiFi module must be initiated - [How To](#)

## Setup



Update your CROSSFIRE/ TRACER TX to FW 3.71 (or later) by Agent X. If you can't see the required FW version, click on the 3 dots in the top right corner and check *"include beta releases"*.

Make sure that the WiFi module is powered up as well (standard TX).



After the update wait for Agent X to synchronize the device with your TBS account. This is done when the dot on the top of the device turns green



## XF Transmitter

### XF WIFI

Connect your CROSSFIRE/ TRACER to the internet via the built-in WiFi module. You can provide access point information from your nearest wifi hotspot or create a temporary one on your phone. Wait for it to switch to "Online" under *XF WIFI/ About*

	About
Firmware	V3.70
Hardware	V 1.01
Bootloader	V 3.05
Serial No	020-000002
RC Input	CRSFShot
User ID	123456

After a few seconds, you can navigate back to *Transmitter/ About*. Now you should see your user id. This user ID will be the unique binding ID. Each transmitter with this user ID can now bind to your receivers using the same firmware version.

Multi-Bind	Enable
Region	Open
Max Power	10mW
Dyn. Power	On
Frequency	868MHz
Op. Mode	Normal

Enable the Multi-bind option under *XF Transmitter/ General*

Repeat this step for every CROSSFIRE/ TRACER transmitter that you own (e.g. TX module, Tango 2, etc.)

## Binding

If you've got a bound receiver, just bind/ update it with Multi-bind turned off, and while it's connected, turn Multi-bind on. Wait for a few seconds, then the link will come back again. You can bind it on a new receiver by the button as usual.

On the other CROSSFIRE/ TRACER TX, just enable "Multi-bind". When the first TX is shut down, you can power up the second transmitter. It should bind to this receiver within a few seconds.

Model ID/ receiver number must be 00 for Multi-bind to work.



## Disable Multi-bind

To disable the Multi-bind option you just need to set the *Multi-bind* option to *disable*. If the link is running, just switch it off and wait a moment till the link regains. Otherwise, rebind the receiver by the button.

## Wrong ID/new ID

You may need a “new” id. To get a new ID, simply connect your CROSSFIRE/ TRACER to Agent X with the new/correct user account and let it synchronize with the TBS CLOUD.

The next time the WiFi module connects to the Internet, it will receive the new ID after a few seconds.

