
Liquid Line 40 SY | Floor

Variant code **QSY-M-A**



TECHNICAL DATA

Luminaire luminous flux	21,000 lm
Power consumption	138 W
Luminous efficacy	152 lm/W
Colour temperature	4000 K
CRI	> 80
Reference measurement conditions	840: 4000 K, CRI>80
Optical system	Microprismatic (A)
Light distribution	Direct-Indirect
Power class	Medium Power (M)
Size	L2940, L3140



Microprismatic | Direct-Indirect

Curve image from the catalogue — not an LDT measurement

ORDERING CODE

QSYA---M---

Product Family	**Q**: Liquid Line
Type	**SY**: Direct-Indirect
Optical System	**A**: Microprismatic
Surface Finish	**W**: Snow White, **V**: Ivory White, **S**: Radiant Silver, **A**: Satin Silver, **F**: Anodic Silver, **U**: Urban Graphite, **D**: Anodic Black, **B**: Jet Black, **H**: Anodic Champagne, **K**: Satin Copper, **X**: Satin Bronze, **M**: Satin Cloud, **R**: Special Surface (please specify)
Control Gear	**X**: Separately Dimmable, **M**: Multisensor, **R**: Swarm Control, **C**: Casambi
Colour Rendering	**8**: CRI>80, **9**: CRI>90, **F**: Full Spectrum
Colour Temperature	**27**: 2700K, **30**: 3000K, **35**: 3500K, **40**: 4000K, **65**: 6500K
Power	**M**: Medium Power
Size	**L2940**, **L3140**
Base	**H**: H-Shape, **D**: Double T-Shape
Reflector	**V**: Ivory White, **F**: Anodic Silver, **U**: Urban Graphite, **D**: Anodic Black, **H**: Anodic Champagne, **G**: Satin Gold, **K**: Satin Copper, **X**: Satin Bronze, **M**: Satin Cloud, **R**: Special Surface (please specify)
Plug	**A**: Schuko CEE7/7 (Type E+F), **B**: CH T12 (Type J), **C**: UK BS 1363 (Type G), **D**: Wieland, **E**: WAGO