
Liquid Line Compact G5/P5 | Suspended

Ordering code




TECHNICAL DATA

Luminaire luminous flux	980 lm
Power consumption	8 W
Luminous efficacy	123 lm/W
Reference measurement conditions	840: 4000 K, CRI>80
Optical system	Opal Diffuser (O)
Light distribution	Direct
Power class	High Power (H)
Size	L139



Opal Diffuser | Direct

Curve image from the catalogue — not an LDT measurement



Dimension drawing

ORDERING CODE

Product Family	Colour Temperature
Type	Power
Optical System	Size
Surface Finish	Suspension
Control Gear	Lens Louvre
Colour Rendering	

Liquid Line Compact G5/P5 | Suspended

Ordering code

DESCRIPTION

Customer / Project:

Note:

SPECIFICATIONS

Productname	Liquid Line-G5
Lamp	LED
Installation Type	Suspended
Surface finish	
Light characteristics	Direct light distribution
Colour temperature	
Colour Rendering Index (CRI)	
Optical system	Opal Diffuser
Control	
Length L/Diameter D (mm)	L=139mm
Width W (mm)	W=40mm
Height H (mm)	H=140mm
Current/Power	High Power
Luminous Flux	
Power consumption	
Suspension	
Ceiling rose colour	Ceiling rose to match luminaire body
Pendant length (mm)	Pendant length standard 1500mm, max on request
Degree of protection	IP20
Cable Colour	Current-carrying cord suspension without additional cables
LED lifetime	L87B10 (tq 25ºC) = 50.000h
Photobiological class	RG0 (EN62471)
Indoor/Outdoor	Indoor: ta [ambient] max. 25ºC
Weight (kg)	1,4kg