OpenProject Airgapped Setup

This setup is tested on ubuntu 22.04 jammy.

This documentation is based on OpenProject Official Documentation

Requirements

- Docker Engine
- Docker Compose Plugin
- Machine with docker installed and having internet.

Setup

OpenProject Docker Image

This step should be done on the machine that has docker installed and is connected to the internet.

1. Pull the docker image

```
docker pull openproject/openproject:14
```

2. Export the docker image to a tar:

```
docker save openproject/openproject:14 -o openproject.tar
```

Installing OpenProject:

1. Copy the tar from the online machine to the offline server (rsync,scp...)
2. Load the docker image:

```
docker load -i openproject.tar
```

3. Create a directory for the setup:

```
mkdir /opt/hosting/openproject
```

4. Create a docker-compose.yml file inside the directory with the following content:

```
services:
  openproject:
```

```
    ports:
    - 8090:80
    container_name: openproject
    environment:
    - OPENPROJECT_HOST__NAME=openproject.host.local ## the actual URL to
use it can be localhost:8090
    - OPENPROJECT_SECRET_KEY_BASE=secret ## this should be random
    - OPENPROJECT_RAILS__RELATIVE__URL__ROOT=/openproject ## the subpath
needed to access it
    - OPENPROJECT_HTTPS=false
    volumes:
    - ./pgdata:/var/openproject/pgdata
    - ./assets:/var/openproject/assets
    image: openproject/openproject:14
```

- OPENPROJECT_HOST__NAME should be updated to the final host it will respond to (this is for CSP purposes) it can be localhost:8090 or server_ip:port or an actual URL
- OPENPROJECT_SECRET_KEY_BASE should be a random value used by rails
- OPENPROJECT_RAILS__RELATIVE__URL__ROOT this can be used if openproject is hosted under a subpath and not "/".
- OPENPROJECT_HTTPS is to disable https behind the reverse proxy used to host the service.

Nginx Config snippet

Example nginx snippet:

```
  location /openproject {
    proxy_set_header Host $host;
    proxy_set_header X-Real-IP  $remote_addr;
    proxy_set_header X-Forwarded-For $proxy_add_x_forwarded_for;
    proxy_set_header X-Forwarded-Proto https;

    proxy_pass http://127.0.0.1:8090/openproject;
  }
```

Notes

Some extra configs might be needed to accomidate the specific infra but this is a general idea of the setup