

Section 3 過学習

In []:

In [21]:

```
import numpy as np
from collections import OrderedDict
from common import layers
from data.mnist import load_mnist
import matplotlib.pyplot as plt
from lesson_2.multi_layer_net import MultiLayerNet
from common import optimizer
```

In [9]:

```
(x_train, d_train), (x_test, d_test) = load_mnist(normalize=True)

print("データ読み込み完了")

# 過学習を再現するために、学習データを削減
x_train = x_train[:300]
d_train = d_train[:300]

network = MultiLayerNet(input_size=784, hidden_size_list=[100, 100, 100, 100, 100, 100])
optimizer = optimizer.SGD(learning_rate=0.01)

iters_num = 1000
train_size = x_train.shape[0]
batch_size = 100

train_loss_list = []
accuracies_train = []
accuracies_test = []

plot_interval=10

for i in range(iters_num):
    batch_mask = np.random.choice(train_size, batch_size)
    x_batch = x_train[batch_mask]
    d_batch = d_train[batch_mask]

    grad = network.gradient(x_batch, d_batch)
    optimizer.update(network.params, grad)

    loss = network.loss(x_batch, d_batch)
    train_loss_list.append(loss)


    if (i+1) % plot_interval == 0:
        accr_train = network.accuracy(x_train, d_train)
        accr_test = network.accuracy(x_test, d_test)
        accuracies_train.append(accr_train)
        accuracies_test.append(accr_test)

#         print('Generation: ' + str(i+1) + '. 正答率(トレーニング) = ' + str(accr_train))
#         print('                    : ' + str(i+1) + '. 正答率(テスト) = ' + str(accr_test))

lists = range(0, iters_num, plot_interval)
plt.plot(lists, accuracies_train, label="training set")
plt.plot(lists, accuracies_test, label="test set")
plt.legend(loc="lower right")
plt.title("accuracy")
plt.xlabel("count")
plt.ylabel("accuracy")
```

```
plt.ylim(0, 1.0)
# グラフの表示
plt.show()
```

データ読み込み完了



L2

```
In [29]: (x_train, d_train), (x_test, d_test) = load_mnist(normalize=True)

print("データ読み込み完了")

# 過学習を再現するために、学習データを削減
x_train = x_train[:300]
d_train = d_train[:300]

network = MultiLayerNet(input_size=784, hidden_size_list=[100, 100, 100, 100, 100, 100])

iters_num = 1000
train_size = x_train.shape[0]
batch_size = 100
learning_rate=0.01

train_loss_list = []
accuracies_train = []
accuracies_test = []

plot_interval=10
hidden_layer_num = network.hidden_layer_num

# 正則化強度設定 =====
weight_decay_lambda = 0.15
# =====

for i in range(iters_num):
    batch_mask = np.random.choice(train_size, batch_size)
    x_batch = x_train[batch_mask]
    d_batch = d_train[batch_mask]

    grad = network.gradient(x_batch, d_batch)
    weight_decay = 0

    for idx in range(1, hidden_layer_num+1):
        grad['W' + str(idx)] = network.layers['Affine' + str(idx)].dW + weight_decay_lambda
        grad['b' + str(idx)] = network.layers['Affine' + str(idx)].db
```

```

network.params['W' + str(idx)] -= learning_rate * grad['W' + str(idx)]
network.params['b' + str(idx)] -= learning_rate * grad['b' + str(idx)]
weight_decay += 0.5 * weight_decay_lambda * np.sqrt(np.sum(network.params['W'

loss = network.loss(x_batch, d_batch) + weight_decay
train_loss_list.append(loss)


if (i+1) % plot_interval == 0:
    accr_train = network.accuracy(x_train, d_train)
    accr_test = network.accuracy(x_test, d_test)
    accuracies_train.append(accr_train)
    accuracies_test.append(accr_test)

#         print('Generation: ' + str(i+1) + '. 正答率(トレーニング) = ' + str(accr_train))
#         print('                        : ' + str(i+1) + '. 正答率(テスト) = ' + str(accr_test))

lists = range(0, iters_num, plot_interval)
plt.plot(lists, accuracies_train, label="training set")
plt.plot(lists, accuracies_test, label="test set")
plt.legend(loc="lower right")
plt.title("accuracy")
plt.xlabel("count")
plt.ylabel("accuracy")
plt.ylim(0, 1.0)
# グラフの表示
plt.show()

```

データ読み込み完了



L1

```

In [18]: (x_train, d_train), (x_test, d_test) = load_mnist(normalize=True)

print("データ読み込み完了")

# 過学習を再現するために、学習データを削減
x_train = x_train[:300]
d_train = d_train[:300]

network = MultiLayerNet(input_size=784, hidden_size_list=[100, 100, 100, 100, 100, 100])

iters_num = 1000
train_size = x_train.shape[0]
batch_size = 100
learning_rate=0.1

```

```

train_loss_list = []
accuracies_train = []
accuracies_test = []

plot_interval=10
hidden_layer_num = network.hidden_layer_num

# 正則化強度設定 =====
weight_decay_lambda = 0.006
# =====

for i in range(iters_num):
    batch_mask = np.random.choice(train_size, batch_size)
    x_batch = x_train[batch_mask]
    d_batch = d_train[batch_mask]

    grad = network.gradient(x_batch, d_batch)
    weight_decay = 0

    for idx in range(1, hidden_layer_num+1):
        grad['W' + str(idx)] = network.layers['Affine' + str(idx)].dW + weight_decay_
        grad['b' + str(idx)] = network.layers['Affine' + str(idx)].db
        network.params['W' + str(idx)] -= learning_rate * grad['W' + str(idx)]
        network.params['b' + str(idx)] -= learning_rate * grad['b' + str(idx)]
        weight_decay += weight_decay_lambda * np.sum(np.abs(network.params['W' + str(

    loss = network.loss(x_batch, d_batch) + weight_decay
    train_loss_list.append(loss)


    if (i+1) % plot_interval == 0:
        accr_train = network.accuracy(x_train, d_train)
        accr_test = network.accuracy(x_test, d_test)
        accuracies_train.append(accr_train)
        accuracies_test.append(accr_test)

#         print('Generation: ' + str(i+1) + '. 正答率(トレーニング) = ' + str(accr_tra
#         print('                    : ' + str(i+1) + '. 正答率(テスト) = ' + str(accr_tes

lists = range(0, iters_num, plot_interval)
plt.plot(lists, accuracies_train, label="training set")
plt.plot(lists, accuracies_test, label="test set")
plt.legend(loc="lower right")
plt.title("accuracy")
plt.xlabel("count")
plt.ylabel("accuracy")
plt.ylim(0, 1.0)
# グラフの表示
plt.show()

```

データ読み込み完了



Dropout

In [19]:

```
class Dropout:
    def __init__(self, dropout_ratio=0.5):
        self.dropout_ratio = dropout_ratio
        self.mask = None

    def forward(self, x, train_flg=True):
        if train_flg:
            self.mask = np.random.rand(*x.shape) > self.dropout_ratio
            return x * self.mask
        else:
            return x * (1.0 - self.dropout_ratio)

    def backward(self, dout):
        return dout * self.mask
```

In [28]:

```
from common import optimizer
(x_train, d_train), (x_test, d_test) = load_mnist(normalize=True)

print("データ読み込み完了")

# 過学習を再現するために、学習データを削減
x_train = x_train[:300]
d_train = d_train[:300]

# ドロップアウト設定 =====
use_dropout = True
dropout_ratio = 0.3
# =====

network = MultiLayerNet(input_size=784, hidden_size_list=[100, 100, 100, 100, 100, 100],
                        weight_decay_lambda=weight_decay_lambda, use_dropout = use_dropout)
# optimizer = optimizer.SGD(learning_rate=0.01)
optimizer = optimizer.Momentum(learning_rate=0.01, momentum=0.9)
# optimizer = optimizer.AdaGrad(learning_rate=0.01)
# optimizer = optimizer.Adam()

iters_num = 1000
train_size = x_train.shape[0]
batch_size = 100

train_loss_list = []
accuracies_train = []
accuracies_test = []
```

```

plot_interval=10

for i in range(iters_num):
    batch_mask = np.random.choice(train_size, batch_size)
    x_batch = x_train[batch_mask]
    d_batch = d_train[batch_mask]

    grad = network.gradient(x_batch, d_batch)
    optimizer.update(network.params, grad)

    loss = network.loss(x_batch, d_batch)
    train_loss_list.append(loss)


    if (i+1) % plot_interval == 0:
        accr_train = network.accuracy(x_train, d_train)
        accr_test = network.accuracy(x_test, d_test)
        accuracies_train.append(accr_train)
        accuracies_test.append(accr_test)

#         print('Generation: ' + str(i+1) + '. 正答率(トレーニング) = ' + str(accr_train))
#         print('                        : ' + str(i+1) + '. 正答率(テスト) = ' + str(accr_test))

lists = range(0, iters_num, plot_interval)
plt.plot(lists, accuracies_train, label="training set")
plt.plot(lists, accuracies_test, label="test set")
plt.legend(loc="lower right")
plt.title("accuracy")
plt.xlabel("count")
plt.ylabel("accuracy")
plt.ylim(0, 1.0)
# グラフの表示
plt.show()

```

データ読み込み完了



何を以て過学習を防げているか評価することは難しいが、L2正則化は比較的うまくいったように思える。学習データを最高に上手に学習できた場合で、テストデータがどの程度正答させられるかは事前にわからないので、パラメトリックスタディの中で、モデルを表現するのに適切な重さを決定しなくてはならない。