

Q5. SET

ANSWER

```
s1={1,2,3,4,5,6,7,8,9}
s2={6,7,8,9,10,11,12,13,14}
print("union of sets:",s1|s2)
print("intersection of sets:",s1&s2)
print("difference of sets:"s1-s2)
#op: {1,2,3,4,5,6,9,8,7,10,11,12,13,14}
      {6,7,9}
      {5,2,3,4,1}
#all the output will be in random order rather than the exact order it was given!!
```

simatslab.saveetha.com/practice_app/classactivity/ajax/download_submissions.php

6

8/16/26, 8:24 PM

Student Submissions — CO3_AT3_Mock Interview

SIMATS Engineering • CSE • CSA0802 — Python Programming • 16-08-2026 • Category: CO3_AT3_Mock Interview • Student Submissions Report

Student 8 **Kampati Pavan Kumar** 192524333RC

5 / 5 subm

Q1. SET

ANSWER

```
A={1,2,3}
B={1,2,3,4,5}
```

SUBSET=A is said to be subset of B when all the elements in A is present in B
SUPERSET=B is said to be superset of A when all the elements in B is present in A and the number of elements in B should be greater than A

Q2. Tuple

ANSWER

since tuple cannot be changed after creation, they reduce the possibility of accidental modification when data is shared between threads and function

Q3. Tuple

ANSWER

```
tuple=(10,20,30,40,50)
a,b,*rest=tuple
print(a)
print(b)
print(rest)

a=10
b=20
rest=(30,40,50)
```

Q4. LIST

ANSWER

```
lst=[1,2,3,4,5]
a=[1,2,3,4,5]
b=[1,2,3,4,6]
```

Q5. Tuple

ANSWER

```
#tuples are immutable
#they are useful for fixed data
#they can be used as dictionary keys if their elements are hashable
#they are convenient for returning multiple values from function
```

simatslab.saveetha.com/practice_app/classactivity/ajax/download_submissions.php

7

8/16/26, 8:24 PM

Student Submissions — CO3_AT3_Mock Interview

SIMATS Engineering • CSE • CSA0802 — Python Programming • 16-08-2026 • Category: CO3_AT3_Mock Interview • Student Submissions Report

Student 9 **KARTHIGA S** 192319057RC

5 / 5 subm

Q1. Tuple

ANSWER

```
def calculate(a,b):
    sum=a+b
    product=a*b
    avg=(a+b)/2

a=10
b=20
```