SCENARIO 02 / TOOL + MEMORY

Fetch all USA customers

User prompt

Fetch all customers from USA.

Intent and applied tools

Intent: task / question. The prompt supplies country = USA. For this example, a retrieved Procedural rule adds the condition: **include only active customers**.

TOOL / INPUT	EXECUTION
get_customers Read	Organization-scoped customer lookup with country plus the active-only condition. Use limit/offset pagination until every matching page has been retrieved.
Request context	organizationId scopes the query; employeeId and userId remain metadata. The country value must match the database vocabulary or an explicit alias mapping.

Applied memories

TYPE	ROLE FOR THIS PROMPT
Procedural Applied example	Illustrative stored rule: "When fetching customers, include only active customers." This is a rule, so it belongs in Procedural Memory.
Semantic Optional	Relevant current-session facts/preferences, if present. No Semantic fact is required to infer USA; it is already in the prompt. Otherwise use [].
Episodic Optional	Prior successful query steps may advise execution. A past episode cannot establish whether a customer is active now; the business database must provide that value.

Highlighted execution path

Request/context -> prepare prompt + intent -> parallel memory search -> select get_customers -> resolve schema -> initial agent -> authorize read -> **executeRegisteredTools** -> PostgreSQL -> append actual rows -> agent reads results -> further pages when needed -> compose response -> recordEpisode -> completed.

The return loop lets the agent use actual rows and decide whether more pages are required. Completed, unchanged reads must not be repeated. "All" is valid only after pagination is exhausted.

Current prerequisites and response

Required addition: the current Customer schema has no active/status field or filter. Until this is added, report the limitation; unfiltered customers do not satisfy the active-only rule. Country filtering also does not normalize USA / United States automatically.

Return matching rows as structured results plus a readable summary. Zero matches is a successful result with customers: []. If retrieval stops early or fails, identify partial results instead of claiming completeness.

NEXT PAGE - Complete original chart. Orange identifies actual get_customers execution; the read loop may repeat for pagination.