SCENARIO 03 / MULTIPLE TOOLS + MULTIPLE MEMORIES

Fetch customers and their orders

User prompt

Fetch customers and their order details; make sure to apply appropriate rules.

Intent and applied tools

TOOL	INPUT AND OUTPUT DEPENDENCY
1. get_customers Existing read tool	Apply the request and retrieved rules; scope to organizationId. Retrieve every matching customer page and collect actual customer IDs.
2. get_orders Proposed read tool	Receive the actual customer IDs plus organization scope and applicable order filters. Return associated order details; paginate when needed. Batch IDs where supported.

get_orders must be registered with a schema, access/effect metadata and an organization-scoped handler. This capability is not present in the inspected branch.

Applied memories

TYPE	ROLE FOR THIS PROMPT
Semantic	Relevant facts/preferences for this organization + session, such as a current-session customer focus or output preference. Never restore Semantic facts from an earlier session.
Procedural	Organization-scoped customer and order handling rules. Apply only retrieved, relevant rules. For example, an active-only restriction requires the corresponding supported database field/filter.
Episodic	Advisory prior steps and outcomes, such as fetching customer IDs before associated orders. Verify against the current request, schemas and live results.

Highlighted execution path

1. Prepare the request, retrieve memories, select both tools and resolve their definitions.
2. Initial agent proposes get_customers; authorize and execute the read.
3. Append actual customer results. The result agent uses returned IDs to propose get_orders.
4. Authorize and execute order reads. Continue any required customer/order pagination.
5. Combine customers with their orders; preserve structured results, record the episode and complete.

The same orange executeRegisteredTools box handles both tool names on separate passes. The initial and result agent boxes represent the same logical agentModel at different times.

Response and empty results

No customers: return a successful empty customer result and skip get_orders. **Customer with no orders:** retain that customer with orders: []. **Tool failure:** distinguish missing data from retrieval failure and label partial results accurately.

Illustrative response shape: customers: [{ id, name, orders: [...] }]. No customer IDs or business rules are fabricated. No business write approval is needed.

NEXT PAGE - Complete original chart. All three memory-context branches and the dependent read loop are highlighted.