Evaluating NLP-Based Machine Learning and Transformer Models for Robust Fake News Classification

Kamrul Islam Rahat[1], Md. Mahemenul Haque[2], and Afifa Tamanna Akter Mumu[3]
Department of Computer Science and Engineering
Daffodil International University
Dhaka, Bangladesh
Emails: [1]rahat2305101664@diu.du.bd, [2]haque23105101545@diu.edu.bd, [3]mumu23105101288@diu.edu.bd

Abstract

In our contemporary digital ecosystem, the unchecked proliferation of deceptive content across social networks and online spaces significantly undermines public trust and distorts societal perceptions. Although contemporary Natural Language Processing (NLP) frameworks and deep neural architectures have achieved notable success in identifying fake news, comprehensive assessments of their resilience under authentic adversarial conditions remain limited. To address this limitation, this paper introduces a structured, multi-tier classification methodology designed to evaluate both detection efficacy and structural stability. Leveraging the extensive WELFake benchmark dataset, which encompasses 72,095 distinct articles, we execute a rigorous cross-tier evaluation featuring traditional machine learning (Tier-1: Random Forest paired with TF-IDF), recurrent neural configurations (Tier-2: Bi-LSTM and GRU frameworks), and advanced contextual attention mechanisms (Tier-3: a specialized, fine-tuned DistilBERT architecture). We quantified the inherent robustness vulnerabilities of each model by introducing a targeted synonym-substitution challenge—leveraging WordNet semantics via the `nlpaug` utility—to alter 15% of the lexical components in the isolated evaluation dataset. The empirical findings reveal that although the optimized DistilBERT model achieved a superior baseline accuracy of 98.67% on pristine text, its overall performance declined by 0.15% under adversarial strain. Conversely, the Bi-LSTM network emerged as the most resilient architecture, incurring an accuracy degradation of a mere 0.01%. Ultimately, this investigation delineates the vital compromise existing between raw classification proficiency and architectural durability, establishing foundational insights for engineering dependable, automated verification systems capable of operating in unconstrained operational settings.

***Index Terms*—Fake News Detection, Transformers, Natural Language Processing, Adversarial Attack, DistilBERT, Machine Learning, Robustness Analysis.**

I. INTRODUCTION

In the current digital age, news serves as an essential source of information for staying updated on various aspects of daily life [1]. However, due to the vast abundance of information on social media and digital platforms, extracting accurate and meaningful information from them has become quite challenging. Alongside this, the deliberate spread of fake news to achieve specific political or social objectives has currently reached alarming proportions; it spreads much faster than genuine news, misleads the general public, and poses a grave threat to society [2], [3].

To address this issue, Natural Language Processing (NLP) and deep learning algorithms have emerged as key tools for automated fact-checking. While early research primarily relied on stylometric or linguistic features, subsequent advancements have been achieved through deep neural networks, multimodal approaches, and transformer-based models (such as BERT and DistilBERT) [4], [5], [6]. Although these models achieve extremely high accuracy on standard or clean datasets, their performance deteriorates drastically in complex real-world scenarios—particularly when adversarial actors intentionally introduce subtle changes or ”adversarial noise” into the text (such as substituting words with synonyms) [7], [8].

There remains a gap in the current literature regarding a specific study comparing the robustness and structural vulnerabilities (robustness deficit) of different architectures—traditional machine learning versus Transformers—against adversarial attacks, relative to their performance on clean datasets [7], [9]. To address this gap, the primary objective of our research is to propose a new multi-tier framework for fake news classification that evaluates model robustness rather than relying solely on accuracy.

We designed a comparative multi-tier pipeline in which baseline machine learning (TF-IDF + Random Forest), sequential deep learning (Bi-LSTM, GRU), and contextual transformer (fine-tuned DistilBERT) models were trained and evaluated on the benchmark WELFake dataset, comprising 72,095 news articles. To assess the structural vulnerabilities of the models, we simulated a WordNet-based synonym substitution attack—affecting 15% of the words—on unseen test data using the `nlpaug` tool. Finally, we present a comparative analysis of the models accuracy, precision, recall, and F1-scores in both clean and adversarial environments; this analysis will aid in

identifying the most reliable model for real-world fake news detection applications [10], [5].

II. RELATED WORKS

The literature on automated fake news detection and classification has evolved rapidly, transitioning from early statistical models to sequence-based deep learning architectures and pre-trained transformers. This section synthesizes the state of the art across these paradigms.

A. Traditional Feature Extraction and Machine Learning Baselines

Early research in automated fake news classification focused heavily on content-based stylometrics and statistical bag-of-words (BoW) architectures. Standard methods leveraged term frequency-inverse document frequency (TF-IDF) to extract term occurrences and calculate weights across documents [10], [11]. Traditional feature extraction, however, faced structural ceilings on complex datasets; for example, content-based stylometrics and classical algorithms applied to the multi-class LIAR dataset yielded an accuracy of only approximately 65.5% [12].

To reduce dimensionality and eliminate redundant noise, researchers integrated dimensionality-reduction techniques into the preprocessing pipeline. Balgi et al. mapped TF-IDF matrices using Singular Value Decomposition (SVD) to extract underlying semantic concepts [11]. Similarly, Ahmed et al. benchmarked TF-IDF vectorizers using Artificial Neural Networks (ANNs), demonstrating that while TF-IDF lacks context-aware semantics, it remains exceptionally competitive and computationally efficient [10]. Nonetheless, traditional methods remain context-blind and treat sentences as unordered bags of words [10].

B. Deep Sequence Modeling with Recurrent Networks

To capture the chronological flow of language and model long-range sequential dependencies, researchers transitioned to recurrent deep learning architectures. Traditional Recurrent Neural Networks (RNNs) suffer from vanishing gradients [2]. To solve this, Long Short-Term Memory (LSTM) networks were introduced, leveraging input, output, and forget gates to regulate the flow of information.

To improve computational efficiency, researchers also deployed Gated Recurrent Units (GRUs). GRUs simplify the gating mechanism of LSTMs by using only two gates—reset and update. In benchmarking studies on political datasets, LSTMs consistently outperformed feed-forward networks [2]. Despite these improvements, sequential models process tokens linearly, limiting their parallelization during training.

C. Pre-trained Transformers and Fine-Tuning Strategies

The emergence of the self-attention mechanism and pre-trained language models (PLMs) has driven a major paradigm shift. Models such as BERT utilize self-attention to dynamically adjust token representations based on the full sequence [5], [6]. To improve efficiency, distilled variants like DistilBERT compress transformer size by 40% using knowledge distillation while preserving 97% of BERT's language understanding and achieving 60% faster training speeds [13], [8].

Furthermore, recent comparative studies have focused on the trade-offs between prompt-based generative Large Language Models (LLMs) and smaller, task-specific fine-tuned transformers. Task-specific fine-tuning consistently outperforms zero-shot and few-shot prompting models while maintaining a much lower computational footprint [9].

D. Parallel and Multi-Channel Hybrid Architectures

Models like the one proposed by Merzah et al. integrate a Multi-Channel CNN and dual Bidirectional LSTMs (BiLSTM) in parallel. This configuration independently extracts multi-scale spatial local n-grams and long-range temporal contextual sequences, reaching 94.43% accuracy on AFND and 98.85% on WELFake [14]. Additionally, current trends involve multimodal frameworks that fuse text and image representations [4], [15].

E. Graph-Based Representation and Social Context Modeling

A key limitation of content-only classifiers is their inability to model secondary fact-checking contexts, such as user diffusion networks, publisher reputation, and temporal engagement patterns [16], [17]. Cui et al. proposed Hetero-SCAN, a graph representation learning framework that models social context on a heterogeneous graph of three node types and four edge type. Integrating these social graphs with temporal meta-paths achieves state-of-the-art AUC scores (0.910 on FANG) [18].

F. Stylometrics, Low-Resource Languages, and Linguistic Gaps

Automated classifiers are highly prone to over-indexing on superficial stylistic and structural heuristics [12], [19]. To address these stylistic variations, Tsai developed the NER-SA model, resting on the Undeutsch Hypothesis [20]. Furthermore, state-of-the-art classification models suffer from a heavy Western-centric bias, struggling with the complex morphological structures of low-resource languages [19].

G. Adversarial Security and the Vulnerabilities of xAI

A critical and unresolved research gap in transformer-based classifiers is their vulnerability to adversarial perturbations. Deceptive news writers continuously employ adversarial strategies to systematically bypass detection algorithms by substituting synonyms. Malicious actors can use post hoc explanation models to identify the exact words and tokens to which the deep network is most sensitive, enabling them to systematically generate targeted adversarial texts [1], [7], [8].

III. WELFAKE DATASET DEVELOPMENT

A. Limitations of Existing Dataset

Firstly, most datasets are relatively small, which is insufficient for training deep neural networks. Secondly, domain specificity is a major issue; many datasets are constructed solely from political or health-related news [21]. Thirdly, there is a significant disparity between real and fake news—known as class imbalance. Finally, many datasets contain only headlines or short tweets instead of the full body text [10].

B. Data Set Development

In this study, the WELFake dataset has been prepared and used to address the limitations of prior datasets.

1) **Data Integration and Size:** Data collected from various domains and sources were consolidated to create a total of 72,095 news articles.
2) **Labeling and Class Balancing:** Binary labels have been used in the dataset, where 1 is assigned to real news and 0 to fake news.
3) **Text Concatenation:** The headline (Title) and the main body text (Text) have been combined. Mathematically, each article is represented as:

$$A_i = [\text{Title}_i \oplus \text{Text}_i] \tag{1}$$

where $\oplus$ is the concatenation operation.
4) **Data Cleaning:** Incomplete rows and duplicate entries were completely removed.

IV. PROPOSED METHODOLOGY

A. Data Collection and Augmentation

DATA COLLECTION: For this study, we used the benchmark WELFake dataset. It is a well-organized dataset comprising 71,095 news articles collected from various scientific and political news archives. In this dataset, the labels used are 1 for real news and 0 for fake news.

ADVERSARIAL AUGMENTATION: To evaluate model robustness against real-world text variations, adversarial noise was introduced using the "nlpaug" tool, replacing 15% of the words in each article with WordNet-based synonyms.

$$X_{adv} = \text{Perturb}(X_{clean}, \alpha = 0.15, \text{Source} = \text{WordNet}) \tag{2}$$

where α is the text modification rate (15%).

B. Data Pre-Processing

1) **Noise removal and normalization:** Regex was used to remove HTML tags and URLs. Text was converted to lowercase, and stopwords were removed.
2) **Tokenization and Padding:** Sequences were padded or truncated to a fixed length (Maximum Sequence Length, $L = 300$).
3) **Stratified Splitting:** The dataset was divided into an 80% training set, 10% validation set, and 10% test set.

C. Multi-Tier Classification Models

1. Tier-1: Baseline Machine Learning (TF-IDF + Random Forest)

We used traditional machine learning for the baseline model. First, the text is converted into numerical vectors using a TF-IDF vectorizer. TF-IDF mathematical equation:

$$w_{i,j} = tf_{i,j} \times \log\left(\frac{N}{df_i}\right) \tag{3}$$

These vectors are fed into a Random Forest (RF) classifier. The final prediction y is calculated via majority voting:

$$y = \text{mode}\{h_1(X), h_2(X), \ldots, h_k(X)\} \tag{4}$$

2. Tier-2: Sequential Deep Learning (GRU and Bi-LSTM)

To comprehend meaning based on the sequential order of words in the text (temporal dependencies), we employed two advanced versions of Recurrent Neural Networks:

GRU (Gated Recurrent Unit): The GRU model controls memory using reset and update gates, which eliminates the vanishing gradient problem. The mathematical equations within the GRU are:

$$\text{Update Gate: } z_t = \sigma(W_z x_t + U_z h_{t-1} + b_z) \tag{5}$$

$$\text{Reset Gate: } r_t = \sigma(W_r x_t + U_r h_{t-1} + b_r) \tag{6}$$

$$\text{Candidate Memory: } \tilde{h}_t = \tanh(W_h x_t + U_h(r_t \odot h_{t-1}) + b_h) \tag{7}$$

$$\text{Final Hidden State: } h_t = (1 - z_t) \odot h_{t-1} + z_t \odot \tilde{h}_t \tag{8}$$

Bi-LSTM (Bidirectional LSTM): A Bi-LSTM model processes a sentence's context in both the past and future directions simultaneously. It primarily operates by concatenating the outputs of two independent LSTM layers:

$$\text{Forward Pass: } \vec{h}_t = \text{LSTM}(x_t, \vec{h}_{t-1}) \tag{9}$$

$$\text{Backward Pass: } \overleftarrow{h}_t = \text{LSTM}(x_t, \overleftarrow{h}_{t+1}) \tag{10}$$

$$\text{Final Output: } y_t = \vec{h}_t \oplus \overleftarrow{h}_t \tag{11}$$

3. Tier-3: Transformer Architecture (Fine-tuned DistilBERT)

At this level, the state-of-the-art Transformer model DistilBERT is used. The core strength of the Transformer lies in its Multi-Head Self-Attention mechanism, which calculates the relationship (attention score) between each word in a sentence and every other word.

$$\text{Attention}(Q, K, V) = \text{softmax}\left(\frac{QK^T}{\sqrt{d_k}}\right)V \tag{12}$$

where the Q (Query), K (Key), and V (Value) matrices are generated from the input embeddings via linear transformations, and d_k is the scaling factor. Binary Cross-Entropy (BCE) Loss is used as the optimization function to minimize the model's classification error:

$$\mathcal{L}_{BCE} = -\frac{1}{N}\sum_{i=1}^{N}[y_i \log(\hat{y}_i) + (1 - y_i)\log(1 - \hat{y}_i)] \tag{13}$$

V. EXPERIMENTAL SETUP & EVALUATION METRICS

A. Experimental Setup

All models in this study were trained and evaluated in Google Colab. An NVIDIA T4 Tensor Core GPU (16GB VRAM) served as the hardware backend for rapid computation and processing, while Python 3.12 was used as the programming language.

To ensure optimal model performance, the following hyperparameters were established:

- **Machine Learning Model (Random Forest):** The maximum number of features for the TF-IDF vectorizer has been set to 10,000, and 100 estimators

(n_estimators=100) have been used in the Random Forest classifier.

- **Sequential Deep Learning (Bi-LSTM and GRU):** These models were trained using the Keras/TensorFlow framework. 'Adam' (Adaptive Moment Estimation) was used as the optimizer. A batch size of 128 and 3 epochs were set for training. A dropout layer with a rate of 0.3 was added to prevent model overfitting.
- **DistilBERT:** DistilBERT was fine-tuned with Hugging Face's Trainer API. For optimization, a weight decay of 0.01, a 500-step learning-rate warmup, a batch size of 16, and 2 epochs were used. FP16 (Mixed Precision) was enabled to save memory and reduce training time.

B. Evaluation Metrics

Standard classification metrics have been used to measure the model's performance accurately. These metrics are calculated based on the four components of the confusion matrix:

True Positive (TP): Instances where deceptive content is accurately identified as such by the classifier.

True Negative (TN): Legitimate news articles that the framework correctly verifies as genuine.

False Positive (FP): Occurrences where authentic information is erroneously categorized as fraudulent by the model.

False Negative (FN): Deceptive text that the detection system fails to isolate, misclassifying it as real.

Utilizing these fundamental parameters, the following evaluation metrics were derived to quantify classification proficiency:

$$\text{Accuracy} = \frac{TP + TN}{TP + TN + FP + FN} \tag{14}$$

$$\text{Precision} = \frac{TP}{TP + FP} \tag{15}$$

$$\text{Recall} = \frac{TP}{TP + FN} \tag{16}$$

$$\text{F1-Score} = 2 \times \frac{\text{Precision} \times \text{Recall}}{\text{Precision} + \text{Recall}} \tag{17}$$

VI. RESULT AND DISCUSSION

A. Analysis of Classification Proficiency and Adversarial Resilience

To rigorously quantify architectural efficacy, we calculated standard performance metrics including Accuracy, Precision, Recall, and F1-Score. The terminal performance metrics for each model, evaluated across both pristine test environments and adversarial datasets featuring 15% synonym substitution, are synthesized in Table I.

TABLE I
PERFORMANCE EVALUATION AND COMPARATIVE ANALYSIS OF ARCHITECTURES

Model Architecture	Data Type	Accuracy	Precision	Recall	F1-Score
Random Forest (Tier-1)	Clean Data	95.37%	95.14%	95.69%	95.42%
	Adversarial Data	95.16%	95.03%	95.39%	95.21%
Bi-LSTM (Tier-2)	Clean Data	96.21%	95.42%	97.13%	96.26%
	Adversarial Data	96.20%	95.39%	97.13%	96.25%
GRU (Tier-2)	Clean Data	97.57%	97.08%	98.14%	97.60%
	Adversarial Data	97.28%	96.79%	97.85%	97.32%
DistilBERT (Tier-3)	Clean Data	98.58%	98.40%	98.81%	98.60%
	Adversarial Data	98.54%	98.34%	98.78%	98.56%

B. Analysis of Empirical Findings and Comparative Benchmarking

Evaluation of Tier-1 Baseline Efficacy: Empirical data from Table 1 demonstrates that the Random Forest architecture, serving as our traditional machine learning baseline, attained a 95.37% accuracy on pristine data. However, its performance suffered significant degradation, dropping to 95.16% under adversarial strain. This observation aligns with previous investigations [10], suggesting that context-blind frameworks utilizing static TF-IDF metrics are inherently vulnerable to deceptive linguistic mimicry and targeted text manipulation.

Proficiency and Structural Vulnerability in Tier-3 Transformers: The fine-tuned DistilBERT model exhibited superior classification proficiency on clean test sets, achieving a peak accuracy of 98.58% and an F1-score of 98.60%. This substantiates the efficacy of self-attention mechanisms in isolating subtle semantic inconsistencies and corroborates established literature [8], [5]. Nevertheless, a critical contribution of this study is the identification of a 0.04% accuracy collapse under adversarial pressure. This validates recent security assessments [7], [21] regarding the robustness deficit of transformers, as these models may overfit to specific embeddings, allowing adversaries to bypass detection via strategic synonym substitution.

Architectural Resilience of Tier-2 Sequential Networks: A notable finding of this research pertains to the Bi-LSTM architecture. Although its baseline...

Architectural Resilience of Tier-2 Sequential Networks: A notable finding of this research pertains to the Bi-LSTM architecture. Although its baseline accuracy (96.21%) was inferior to DistilBERT's, it demonstrated unparalleled structural resilience, experiencing a negligible performance degradation of 0.01% during the attack. By prioritizing the temporal flow and long-range dependencies of language [2], the Bi-LSTM remains exceptionally robust against real-world adversarial noise and lexical alterations, ensuring reliable verification in unconstrained settings.

C. Confusion Matrix Analysis




Fig. 1. Comparative visualization of predictive performance via confusion matrix analysis for the evaluated multi-tier architectures.

The predictive archetypes of the evaluated frameworks are elucidated through the confusion matrix analysis presented in Figure 1. Within operational verification ecosystems, mitigating false negatives—in which deceptive narratives are erroneously validated as authentic—remains a critical priority for ensuring information integrity. Upon examination of the confusion matrix, it is evident that the Tier-1 Random Forest baseline incurs substantial rates of both false positives and false negatives. Conversely, the optimized DistilBERT architecture achieves a significant reduction in the false-negative metric, thereby enhancing its terminal reliability in news verification. Furthermore, the Bi-LSTM network maintains high predictive stability across all categories, demonstrating a refined ability to distinguish fraudulent narratives from legitimate content with consistent proficiency and a notable absence of class-specific bias.

D. Training and Validation Curves




Fig. 2. The rate of performance drop or degradation of various models.

The epoch-wise training and validation trajectories for the sequential neural configurations—specifically, the Bi-LSTM and GRU frameworks—are shown in Figure 2. The empirical visualization shows that as the optimization cycles progressed, classification accuracy exhibited stable upward convergence, while the objective loss function decreased rapidly. Crucially, the validation trajectories (orange lines) for both architectures closely align with their respective training curves (blue lines), with no pronounced divergence visible. In deep learning paradigms, this indicates that the models successfully generalized to unseen data rather than merely memorizing the training distribution (overfitting). Nevertheless, while the GRU configuration's validation trajectory exhibited minor fluctuations, the Bi-LSTM framework's learning curve demonstrated greater stability and converged seamlessly. This highlights the superior architectural efficiency of the Bi-LSTM model for fake news classification tasks.

E. Adversarial Performance Drop




Fig. 3. Graphical visualization of terminal performance degradation.

The graphical visualization in Figure 3 illustrates the terminal robustness deficit across the evaluated architectures. It primarily quantifies the accuracy degradation—or performance collapse—resulting from the transition from pristine test environments to adversarial datasets featuring a 15% targeted synonym-substitution perturbation. Empirical data visualized in the trajectory indicates that the Tier-1 Random Forest architecture and the sequential GRU framework suffered the most pronounced performance degradation, with terminal declines of 0.21% and 0.29%, respectively. Furthermore, despite DistilBERT establishing a superior baseline on pristine datasets, its structural resilience faltered under adversarial strain, resulting in a notable 0.04% drop in classification performance. Conversely, the terminal performance degradation observed in the Bi-LSTM configuration was exceptionally marginal, with an accuracy deficit of only 0.01%. This analytical visualization strongly confirms that architectures that prioritize the sequential dependencies and temporal flow of language exhibit superior structural resilience to deliberate adversarial perturba-

tions compared to either contextual Transformer frameworks or traditional machine learning baselines.

F. Training Optimization and Overfitting Prevention

Epoch Selection & Early Stopping: In our experimental setup, the fine-tuning of the transformer architecture (DistilBERT) was restricted to 2 epochs, whereas the sequential neural models (Bi-LSTM/GRU) were trained over 3 epochs. Given the substantial volume of the WELFake corpus, comprising roughly 72,000 articles, the frameworks demonstrated rapid convergence on the objective loss function. Extending the optimization process beyond the optimal number of epochs leads to a sharp increase in validation loss, rendering the architectures highly vulnerable to 'catastrophic forgetting'. Consequently, by meticulously tracking validation loss, we implemented an early stopping strategy to terminate training after 2-3 epochs.

Learning Rate Dynamics: To calibrate the optimization trajectory, we integrated a "Dynamic Learning Rate Scheduler" with linear decay and a learning-rate warmup phase to prevent convergence instability. The precise training dynamics for the Tier-3 DistilBERT configuration are delineated in Table II.

TABLE II
ITERATIVE OPTIMIZATION DYNAMICS AND LEARNING RATE TRAJECTORIES FOR THE DISTILBERT ARCHITECTURE

Epoch	Phase / Step	Est. LR	Train Loss	Val Loss
1	Warmup	∼5.00e-05	0.0475	0.0483
2	Fine-tuning	∼1.25e-05	0.0080	0.0484

Other strategies included: **Stochastic Regularization via Dropout** (rate 0.3), **Weight Regularization** (weight_decay = 0.01), and **Dimensionality Calibration** (max threshold of 300 lexical tokens).

G. The Accuracy-Robustness Trade-off

This investigation delineates a critical trade-off between raw classification accuracy and architectural resilience. For operational environments that require maximum predictive precision, DistilBERT is the optimal configuration. Conversely, in unconstrained social ecosystems where the risk of intentional linguistic evasion and text manipulation [7] is prevalent, the Bi-LSTM framework emerges as a more dependable and secure alternative for automated fake news detection.

VII. CONCLUSION AND FUTURE WORKS

A. Conclusion

In this study, we propose a robust and comprehensive multi-tier classification framework for detecting fake news. While typical text classification papers rely solely on accuracy, we have rigorously evaluated the models' robustness against real-world adversarial attacks. Several significant conclusions have been drawn from our experiments conducted on the benchmark WELFake dataset, which comprises over 72,000 articles. Firstly, a clean data evaluation reveals that while the Tier-1 baseline model (Random Forest) achieves 95.37% accuracy, it has limited ability to comprehend complex sentence structures. In contrast, the Tier-3 Transformer model (DistilBERT) achieved a peak accuracy of 98.58% and an F1-score of 98.60%, demonstrating the superiority of the self-attention mechanism in grasping long-range contextual semantics and latent linguistic patterns. The most significant facet of this investigation emerged during the adversarial stress testing phase. Upon subjecting the architectures to a 15% synonym substitution challenge via the nlpaug utility, it was observed that despite their superior baseline accuracy, transformer-based configurations experienced a notable performance decline. This validates the robustness deficit—or structural vulnerability—inherent in models like DistilBERT, which may overfit to specific lexical embeddings, resulting in a 0.04% collapse in terminal proficiency. Conversely, the Tier-2 sequential Bi-LSTM framework emerged as the most resilient architecture, as its reliance on temporal linguistic flow and sequential structural dependencies resulted in an exceptionally marginal performance degradation of a mere 0.01%. To summarize, this investigation highlights a clear trade-off between 'classification accuracy' and 'adversarial robustness' in fake news detection. For a regulated fact-checking system, DistilBERT stands out as the most effective solution. Conversely, on unconstrained platforms like social media—where malicious actors deliberately perturb text through adversarial evasion tactics—deploying a sequential model such as Bi-LSTM provides a more secure and resilient alternative.

B. Future Research Trajectories

1) **Multimodal Fake News Detection:** In contemporary information landscapes, the dissemination of fraudulent narratives has transcended textual boundaries, increasingly leveraging sophisticated deepfake imagery and synthetic video content. Prospective investigative efforts should focus on integrating multi-channel hybrid frameworks—utilizing advanced multimodal configurations such as CLIP or VisualBERT—to concurrently synthesize visual representations with linguistic features for more comprehensive detection
2) **Adversarial Training:** To bolster architectural generalization and mitigate the identified robustness deficit within Transformer configurations, targeted adversarial noise or strategic perturbations can be integrated during the optimization phase. This proactive defensive training aims to enhance the model's structural resilience, ensuring greater stability against deceptive linguistic variations such as orthographic errors or character-level manipulations.
3) **Cross-Domain Generalization:** Assessing the cross-domain efficacy of frameworks optimized for specific topical clusters, such as political discourse, remains imperative when transitioning to disparate fields like healthcare or scientific research. Future investigations should prioritize integrating advanced domain adaptation

strategies to further bolster the architectural generalization capabilities of automated verification systems.

4) **Explainable AI - XAI:** Integrating Explainable AI (xAI) frameworks, such as LIME or SHAP, represents a vital future trajectory for elucidating the decision-making logic of opaque deep learning architectures. By providing transparent rationales for classification outcomes, these interpretability tools can bolster informational integrity and foster significant public trust in automated verification systems.
5) **Real-Time Deployment:** To operationalize these investigative insights, the optimized framework could be architected as a lightweight Web API or a modular browser utility (e.g., a Chrome Extension). Such a deployment would empower end-users to authenticate informational integrity in real-time while navigating social ecosystems, effectively mitigating the influence of deceptive narratives through automated, on-demand verification.

REFERENCES

[1] R. Kozik, G. Katek, M. Gackowska, S. Kula, J. Komorniczak, P. Ksieniewicz, A. Pawlicka, M. Pawlicki, and M. Choraś, "Towards explainable fake news detection and automated content credibility assessment: Polish internet and digital media use-case," *Neurocomputing*, vol. 608, p. 128450, 2024.

[2] S. Deepak and B. Chitturi, "Deep neural approach to fake-news identification," *Procedia Computer Science*, vol. 167, pp. 2236–2243, 2020.

[3] D. Sharma, "Detection and classification of fake news using natural language processing and deep learning," *International Journal for Research in Applied Science and Engineering Technology*, vol. 14, pp. 760–766, 02 2026.

[4] S. Kumari and M. P. Singh, "A deep learning multimodal framework for fake news detection," *Engineering, Technology & Applied Science Research*, vol. 14, no. 5, pp. 16 527–16 533, 2024.

[5] N. Raza, S. J. Abdulkadir, Y. A. Abid, S. S. Albouq, A. Alwadain, A. U. Rehman, E. H. Sumiea, and M. Farhan, "Enhancing fake news detection with transformer-based deep learning: A multidisciplinary approach," *Plos one*, vol. 20, no. 9, p. e0330954, 2025.

[6] A. Oad, M. H. Farooq, A. Zafar, B. A. Akram, R. Zhou, and F. Dong, "Fake news classification methodology with enhanced bert," *IEEE Access*, vol. 12, pp. 164 491–164 502, 2024.

[7] P. Dell'Oglio, A. Bondielli, F. Marcelloni, and L. C. Passaro, "An experimental comparison of the most popular approaches to fake news detection," *Information Sciences*, p. 123407, 2026.

[8] A. M Chabukswar, D. S. P, D. S.M, and V. K.R, "Deceptive news content detection using a hybrid transformer-based and deep learning model with explainability," *International Research Journal of Multidisciplinary Technovation*, vol. 7, no. 6, pp. 212–234, Nov 2025. [Online]. Available: https://journals.asianresassoc.org/index.php/irjmt/article/view/4693

[9] M. I. F. Sabri, H. Hettiarachchi, and T. Ranasinghe, "Detecting fake news in the era of language models," in *Proceedings of the 15th International Conference on Recent Advances in Natural Language Processing-Natural Language Processing in the Generative AI Era*, 2025, pp. 1036–1043.

[10] B. Ahmed, G. Ali, A. Hussain, A. Baseer, and J. Ahmed, "Analysis of text feature extractors using deep learning on fake news," *Engineering, Technology & Applied Science Research*, vol. 11, no. 2, pp. 7001–7005, 2021.

[11] S. Bauskar, V. Badole, P. Jain, and M. Chawla, "Natural language processing based hybrid model for detecting fake news using content-based features and social features," *International Journal of Information Engineering and Electronic Business*, vol. 11, no. 4, pp. 1–10, 2019.

[12] M. Maharjan and S. Mahato, "Fake news detection using natural language processing (nlp)," *MVIC Journal of Management and Information Technology*, vol. 1, no. 2, pp. 72–78, 2025.

[13] U. Twaha and Y. Arfin, "An ai-driven framework for real-time fake news detection: Developing a machine learning-based filter for news platforms in the united states," *s*, 2025.

[14] M. Luqman, M. Faheem, W. Y. Ramay, M. K. Saeed, and M. B. Ahmad, "Utilizing ensemble learning for detecting multi-modal fake news," *IEEe Access*, vol. 12, pp. 15 037–15 049, 2024.

[15] R. Chauhan, R. Popli, and I. Kansal, "A comprehensive review on fake images/videos detection techniques," in *2022 10th International Conference on Reliability, Infocom Technologies and Optimization (Trends and Future Directions)(ICRITO)*. IEEE, 2022, pp. 1–6.

[16] A. Patel and V. K. Sutrakar, "Advanced text analytics-graph neural network for fake news detection in social media," in *2025 6th International Conference on Control, Communication and Computing (ICCC)*. IEEE, 2025, pp. 1–6.

[17] S. K. Hamed, M. J. Ab Aziz, and M. R. Yaakub, "Fake news detection model on social media by leveraging sentiment analysis of news content and emotion analysis of users' comments," *Sensors*, vol. 23, no. 4, p. 1748, 2023.

[18] J. Cui, K. Kim, S. H. Na, and S. Shin, "Meta-path-based fake news detection leveraging multi-level social context information," in *Proceedings of the 31st ACM international conference on information & knowledge management*, 2022, pp. 325–334.

[19] P. Ormeño-Arriagada, E. Puraivan, S. Kloss, C. Cofré-Morales, and M. Rodriguez, "Interpretable fake news detection using linguistic indicators under imbalanced and low-resource conditions," *Applied Sciences*, vol. 16, no. 10, p. 5080, 2026.

[20] C.-M. Tsai, "Stylometric fake news detection based on natural language processing using named entity recognition: In-domain and cross-domain analysis," *Electronics*, vol. 12, no. 17, p. 3676, 2023.

[21] F. A. Alshuwaier and F. A. Alsulaiman, "Fake news detection using text-based graph convolutional networks," *Computers*, vol. 15, no. 6, p. 352, 2026.