mp2_p2_code

October 6, 2022

```
[28]: import IPython
      from google.colab import files
      from IPython.display import Image
[29]: uploaded = files.upload()
     <IPython.core.display.HTML object>
     Saving bees.jpg to bees (1).jpg
     Saving butterfly.jpg to butterfly (1).jpg
     Saving candies.jpg to candies (1).jpg
     Saving einstein.jpg to einstein (1).jpg
     Saving fishes.jpg to fishes (1).jpg
     Saving joker.jpg to joker (1).jpg
     Saving stars.jpg to stars (1).jpg
     Saving sunflowers.jpg to sunflowers (1).jpg
[30]: import numpy as np
      import matplotlib.pyplot as plt
      import time
      import math
      import cv2 as cv
      from itertools import chain
      from skimage import io
      from skimage import color
      from skimage import transform
      from scipy.ndimage.filters import convolve
      from scipy.ndimage.filters import gaussian_laplace
      from scipy.ndimage.filters import generic_filter
      from scipy.ndimage.filters import rank_filter
      import matplotlib.pyplot as plt
      from matplotlib.patches import Circle
[31]: def load_and_preprocess(file):
        org_img = cv.imread
        img = cv.imread(file)
        img = cv.cvtColor(img, cv.COLOR_BGR2GRAY)
        return img/(255)
```

```
[32]: # Get squared Laplacian response in scale-space.
      def get_scale_space(img, init_sigma, levels, method):
        sigma = np.zeros(levels)
        sigma[0] = init_sigma
        k = 1.25
        h = img.shape[0]
        w = img.shape[1]
        scale_space = np.empty((h, w, levels))
        # find the size of the matrix
        def increase_matrix_size():
          for i in range(levels):
            size = int(round(6 * sigma[i]))
            if size % 2 == 0:
              size += 1
            #creste the filter
            center = int((size + 1)/2 - 1)
            filter = np.zeros((size, size))
            filter[center] [center] = 1
            LoG = sigma[i] * sigma[i] * gaussian_laplace(filter, sigma[i])
            scale_space[:, :, i] = convolve(img, LoG) ** 2
            #renew the sigma
            if (i+1 < levels):
              sigma[i+1] = sigma[i] * k
        def downsampling():
          size = int(round(6 * sigma[0]))
          if size % 2 == 0:
            size += 1
          center = int((size + 1)/2 - 1)
          filter = np.zeros((size, size))
          filter[center] [center] = 1
          LoG = gaussian_laplace(filter, sigma[0])
          #Down sampling the image
          for i in range(levels):
           new h = int(h * ((1/k) ** i))
            new_w = int(w * ((1/k) ** i))
            new_img = transform.rescale(img, (1/k) ** i, order = 3)
            tmp = convolve(new_img, LoG) ** 2
```

```
# Upscaling
            scale_space[:, :, i] = transform.resize(tmp, (h, w), order = 3)
            # renew sigmma
            if (i+1 < levels):
              sigma[i+1] = sigma[i] * k
        start_time = time.time()
        process = {'increase_matrix_size': increase_matrix_size, 'downsampling': __
       →downsampling}
        process[method]()
        print("Runtime: %.5s seconds" % (time.time() - start_time))
        return scale_space, sigma
[33]: def NMS_2D(scale_space):
       h = scale_space.shape[0]
        w = scale_space.shape[1]
        levels = scale_space.shape[2]
        local_max = np.empty((h, w, levels))
        for i in range(levels):
          curr_response = scale_space[:,:,i]
          local_max[:, :, i] = rank_filter(curr_response, -1, (3, 3))
        return local max
[34]: def NMS_3D(scale_space, sigma):
        local_max = NMS_2D(scale_space)
        h = local_max.shape[0]
        w = local_max.shape[1]
        levels = local_max.shape[2]
        global_max = np.zeros(local_max.shape)
        for i in range(h):
          for j in range(w):
            max_value = np.amax(local_max[i, j, :])
            max_index = np.argmax(local_max[i, j, :])
            global_max[i, j, max_index] = max_value
        for i in range(levels):
```

```
global_max[:, :, i] = np.where((global_max[:, :, i] == scale_space[:, :,_u
       →i]), global_max[:, :, i], 0)
        return global_max
[35]: def get_mask(h, w, levels, sigma):
        #make masks for the max points
        mask = np.zeros((h, w, levels))
        for i in range(levels):
          center = int(math.ceil(sigma[i] * math.sqrt(2)))
          mask[center + 1 : h - center, center + 1: w - center] = 1
        return mask
[36]: def get_radius(sigma, num_radius):
        return np.ones(num_radius) * math.sqrt(2) * sigma
[37]: def detect blob(global max, threshold, sigma):
        levels = global_max.shape[2]
        mask = get_mask(global_max.shape[0], global_max.shape[1], levels, sigma)
        row = []
        col = []
        radius = []
        for i in range(levels):
          global_max[:, :, i] = np.where((global_max[:, :, i] > threshold) & (mask[:, __
       \hookrightarrow:, i] == 1), 1, 0)
          row.append(list(np.where(global max[:, :, i] == 1)[0]))
          col.append(list(np.where(global_max[:, :, i] == 1)[1]))
          radius.append(list(get_radius(sigma[i], len(row[i]))))
        row = list(chain.from_iterable(row))
        col = list(chain.from_iterable(col))
        radius = list(chain.from_iterable(radius))
        return row, col, radius
[38]: def show_and_save_all_circles(img, dx, dy, radius, img_name, method, threshold,__

color='r'):
        fig, ax = plt.subplots()
        ax.imshow(img, cmap='gray')
        ax.xaxis.set_visible(False)
        ax.yaxis.set_visible(False)
        for x, y, r in zip(dx, dy, radius):
```

circle = Circle((x, y), r, color=color, fill=False)

```
ax.add_patch(circle)

plt.savefig(img_name.split('.')[0] + '_' + method + '.jpg')

plt.show()

: def run_detection(img_name, method, levels, threshold, init_sigma):
```

```
[39]: def run_detection(img_name, method, levels, threshold, init_sigma):
    k = 1.25

    file = img_name
    img = load_and_preprocess(file)

    scale_space, sigma = get_scale_space(img, init_sigma, levels, method)

    global_max = NMS_3D(scale_space, sigma)


    row_index, col_index, radius = detect_blob(global_max, threshold, sigma)

    show_and_save_all_circles(img, col_index, row_index, radius, img_name, under threshold)
```

```
[40]: methods = ['increase_matrix_size', 'downsampling']
levels = 12
init_sigma = 2
thresholds = np.array([0.0028, 0.00015])
```


```
[41]: image_name = 'butterfly.jpg'
run_detection(image_name, methods[0], levels, thresholds[0], init_sigma)
```

Runtime: 36.76 seconds




```
[43]: image_name = 'butterfly.jpg'
run_detection(image_name, methods[1], levels, thresholds[1], 2)
```

Runtime: 0.843 seconds




```
[44]: image_name = 'einstein.jpg'
run_detection(image_name, methods[0], levels, thresholds[0], 2)
image_name = 'einstein.jpg'
run_detection(image_name, methods[1], levels, thresholds[1], 2)
image_name = 'fishes.jpg'
run_detection(image_name, methods[0], levels, thresholds[0], 2)
image_name = 'fishes.jpg'
run_detection(image_name, methods[1], levels, thresholds[1], 2)
```


Runtime: 37.76 seconds




Runtime: 1.339 seconds



Runtime: 26.12 seconds




Runtime: 0.869 seconds




```
[45]: image_name = 'sunflowers.jpg'
run_detection(image_name, methods[0], levels, thresholds[0], 2)
image_name = 'sunflowers.jpg'
run_detection(image_name, methods[1], levels, thresholds[1], 2)
```

```
image_name = 'candies.jpg'
run_detection(image_name, methods[0], levels, thresholds[0], 2)
image_name = 'candies.jpg'
run_detection(image_name, methods[1], levels, thresholds[1], 2)
```


Runtime: 21.18 seconds




Runtime: 0.562 seconds



Runtime: 15.99 seconds




Runtime: 0.281 seconds




```
[46]: image_name = 'joker.jpg'
  run_detection(image_name, methods[0], levels, thresholds[0], 2)
  image_name = 'joker.jpg'
  run_detection(image_name, methods[1], levels, thresholds[1], 2)

image_name = 'bees.jpg'
  run_detection(image_name, methods[0], levels, thresholds[0], 2)
  image_name = 'bees.jpg'
  run_detection(image_name, methods[1], levels, thresholds[1], 2)
```


Runtime: 15.84 seconds




Runtime: 0.293 seconds



Runtime: 15.73 seconds




Runtime: 0.265 seconds



```
[47]: image_name = 'stars.jpg'
run_detection(image_name, methods[0], levels, thresholds[0], 2)
image_name = 'stars.jpg'
run_detection(image_name, methods[1], levels, thresholds[1], 2)
```

Runtime: 16.60 seconds



Runtime: 0.427 seconds

