

1.

```
#include<stdio.h>

int main()
{
    printf("Hello Linux\n");
    return 0;
}
```

```
[pooh@Kandulas-MacBook-Air ~ % gcc hello.c -o hello
[pooh@Kandulas-MacBook-Air ~ % ./hello
Hello Linux
```

2

```
#include<stdio.h>

int main()
{
    char name[30];

    printf("Enter your name: ");
    scanf("%s",name);

    printf("Welcome %s\n",name);

    return 0;
}
```

```
[pooh@Kandulas-MacBook-Air ~ % nano read_user_name.c
[pooh@Kandulas-MacBook-Air ~ % gcc read_user_name.c -o read_user_name
[pooh@Kandulas-MacBook-Air ~ % ./read_user_name
Enter your name: poojitha
Welcome poojitha
```

3

```
#include<stdio.h>
#include<unistd.h>

int main()
{
    printf("Process ID = %d\n",getpid());

    return 0;
}
```

```
[pooh@Kandulas-MacBook-Air ~ % nano process.c
[pooh@Kandulas-MacBook-Air ~ % gcc process.c
[pooh@Kandulas-MacBook-Air ~ % gcc process.c -o process
[pooh@Kandulas-MacBook-Air ~ % ./process
Process ID = 49767
```

4.

```
#include<stdio.h>
#include<unistd.h>

int main()
{
    fork();

    printf("Hello\n");

    return 0;
```

```
[pooh@Kandulas-MacBook-Air ~ % nano fork.c
[pooh@Kandulas-MacBook-Air ~ % gcc fork.c
[pooh@Kandulas-MacBook-Air ~ % gcc fork.c -o fork
[pooh@Kandulas-MacBook-Air ~ % ./fork
Hello
Hello
```

5

```
#include<stdio.h>
#include<unistd.h>

int main()
{
    pid_t pid;

    pid=fork();

    if(pid==0)
    {
        printf("I am Child Process\n");
    }
    else
    {
        printf("I am Parent Process\n");
    }

    return 0;
}
```

```
[pooh@Kandulas-MacBook-Air ~ % nano parent_child.c
[pooh@Kandulas-MacBook-Air ~ % gcc parent_child.c
[pooh@Kandulas-MacBook-Air ~ % gcc parent_child.c -o parent_child
clang: error: unknown argument: '-o'
clang: error: no such file or directory: 'parent_child'
[pooh@Kandulas-MacBook-Air ~ % gcc parent_child.c -o parent_child
[pooh@Kandulas-MacBook-Air ~ % ./parent_child
I am Parent Process
I am Child Process
```

6.

```
#include<stdio.h>
#include<unistd.h>

int main()
{
    pid_t pid;

    pid=fork();

    if(pid==0)
    {
        printf("Child PID = %d\n",getpid());
        printf("Parent PID = %d\n",getppid());
    }
    else
    {
        printf("Parent PID = %d\n",getpid());
    }

    return 0;
}
```

```
pooh@Kandulas-MacBook-Air ~ % nano PID.c
pooh@Kandulas-MacBook-Air ~ % gcc PID.c -o PID
pooh@Kandulas-MacBook-Air ~ % ./PID
Parent PID = 49914
Child PID = 49915
Parent PID = 49914
```

7.

```
#include<stdio.h>
#include<unistd.h>
#include<sys/wait.h>

int main()
{
    pid_t pid;

    pid=fork();

    if(pid==0)
    {
        printf("Child Running\n");
    }
    else
    {
        wait(NULL);

        printf("Parent Running After Child\n");
    }

    return 0;
}
```



```
[pooh@Kandulas-MacBook-Air ~ % nano wait.c
[pooh@Kandulas-MacBook-Air ~ % gcc wait.c -o wait
[pooh@Kandulas-MacBook-Air ~ % ./wait
Child Running
Parent Running After Child
```

9.

8

```
#include<stdio.h>
#include<unistd.h>

int main()
{
    printf("Before exec()\n");

    execlp("ls","ls",NULL);

    printf("After exec()\n");

    return 0;
}
```

```
[pooh@Kandulas-MacBook-Air ~ % nano example.c
[pooh@Kandulas-MacBook-Air ~ % gcc example.c -o example
[pooh@Kandulas-MacBook-Air ~ % ./example
Before exec()
a.out
blenderkit_data
class Nodef.java
CO-1.pdf
CO-2.pdf
CO-3.pdf
Completion certificate react.pages
Completion certificate react.pdf
Desktop
Documents
Downloads
example
example.c
fedf pdf 2.pdf
FEDF_lab_Programs insem .pdf
FEDF_lab_Programs pdf.pdf
FEDF_lab_Programs.pages
first.blend
fork
fork.c
hello
hello.c
import java.util.java
Library
Movies
Music
OS
parent_child
parent_child.c
pdf fedf.pdf
PharmaInventory.java
Pictures
PID
PID.c
Poojitha Resume.pages
process
process.c
Project abstract submission form-FEDF (2).pages
Project abstract submission form-FEDF (2).pdf
Public
PyCharmMiscProject
PycharmProjects
read_user_name
read_user_name.c
RetailMind - Smart Retail Inventory & Sales Analytics System
Untitled.ipynb
VF.html
wait
wait.c
```

9.

```
#include<stdio.h>
#include<unistd.h>
#include<sys/wait.h>

int main()
{
    pid_t pid;

    pid=fork();

    if(pid==0)
    {
        execlp("date","date",NULL);
    }
    else
    {
        wait(NULL);

        printf("Child Completed\n");
    }

    return 0;
}
```

wait.c

```
[pooh@Kandulas-MacBook-Air ~ % nano fork_exec.c
[pooh@Kandulas-MacBook-Air ~ % gcc fork_exec.c -o fork_exec
[pooh@Kandulas-MacBook-Air ~ % ./fork_exec
Tue Aug 11 10:53:29 IST 2026
Child Completed
```