

1 弯矩标准值应按下式计算:

$$M_k = \frac{F_{bk}L_0}{4} + \frac{q_kL_0^2}{8} \quad (\text{A. 0. 2-1})$$

2 抗弯强度应按下列公式计算:

$$\sigma_1 = \frac{\gamma_0 M}{W_n} \leq f_1 \quad (\text{A. 0. 2-2})$$

$$M = \sum \gamma_{Q_i} M_{k_i} \quad (\text{A. 0. 2-3})$$

$$\nu = \frac{F_{bk}l^3}{48EI} + \frac{5q_kl^4}{384EI} \leq [\nu] \quad (\text{A. 0. 2-4})$$

1 弯矩标准值应按下式计算:

$$M_{zk} = F_{zk}h + \frac{q_kh^2}{2} \quad (\text{A. 0. 3-1})$$

2 抗弯强度应按下列公式计算:

$$\sigma_1 = \frac{\lambda_0 M_z}{W_{zn}} \leq f_1 \quad (\text{A. 0. 3-2})$$

$$M_z = \sum \gamma_{Q_i} M_{zk_i} \quad (\text{A. 0. 3-3})$$

3 挠度应按下式计算:

$$\nu = \frac{F_{zk}h^3}{3EI} + \frac{q_kh^4}{8EI} \leq [\nu] \quad (\text{A. 0. 3-4})$$