

# **SORTING ALGORITHMS**

## **QUICKSORT**





# Quicksort

- ▶ It is an efficient sorting algorithm
- ▶ It was developed by Tony Hoare in 1959 // the same person who invented quickselect algorithm
- ▶ A well implemented quicksort can outperforms heapsort and merge sort → the main competitors of quicksort
- ▶ A comparison based algorithm → not able to be faster than linearithmic time complexity



# Quicksort

- ▶ The efficient implementation of quicksort is **NOT** stable → does not keep the relative order of items with equal value
- ▶ It is in-place → does not need any additional memory
- ▶ On average case it has  **$O(N \log N)$**  running time
- ▶ But the worst case running time is quadratic  **$O(N^2)$**  !!!<sup>2</sup>
- ▶ It is widely used in programming languages

Primitive types → usually quicksort is used

Reference types / objects → usually mergesort is used



# Quicksort

It is a **divide and conquer** algorithm

- pick an element from the array: this is the pivot item
- partition phase: rearrange the array so that all elements with values less than the pivot come before the pivot, while all elements with values greater than the pivot come after it // equal values can go either way
- recursively apply these steps on the subarrays

**BASE CASE FOR RECURSION:** arrays of size zero or one never need to be sorted

## Choosing the pivot item

It is very important → if we keep choosing bad pivots, the running time will be quadratic

- 1.) we can choose a pivot at random // usually it is working fine
- 2.) choose the middle index of the array as the pivot



## Pseudocode

quicksort(array,low,high)

    if low >= high return

    pivot = partition(array,low,high)

    quicksort(array,low,pivot-1)

    quicksort(array,pivot+1,high)

end

partition(array,low,high)

    pivotIndex = (low+high) / 2

    swap(pivotIndex,high)

    i = low

    for j=low to high

        if array[j] <= array[high]


            swap(i,j)

        i++

    swap (i,high)

    return i

end





## Pseudocode

quicksort(array,low,high)

    if low >= high return

    pivot = partition(array,low,high)

    quicksort(array,low,pivot-1)

    quicksort(array,pivot+1,high)

end

partition(array,low,high)

    pivotIndex = (low+high) / 2

    swap(pivotIndex,high)

    i = low

    for j=low to high

        if array[j] <= array[high]

            swap(i,j)

        i++

    swap (i,high)

    return i

end

This is the base case for recursion: to track  
when to terminate our algorithm !!!



## Pseudocode

quicksort(array,low,high)

    if low >= high return

    pivot = partition(array,low,high)

    quicksort(array,low,pivot-1)

    quicksort(array,pivot+1,high)

end

partition(array,low,high)

    pivotIndex = (low+high) / 2

    swap(pivotIndex,high)

    i = low

    for j=low to high

        if array[j] <= array[high]

            swap(i,j)

        i++

    swap (i,high)

    return i

end

We have to find a pivot item → we are going to partition the array according to this item !!!



## Pseudocode

quicksort(array,low,high)

    if low >= high return

    pivot = partition(array,low,high)

    quicksort(array,low,pivot-1)

    quicksort(array,pivot+1,high)

end

partition(array,low,high)

    pivotIndex = (low+high) / 2

    swap(pivotIndex,high)

    i = low

    for j=low to high

        if array[j] <= array[high]

            swap(i,j)

        i++

    swap (i,high)

    return i

end

We call the sort method recursively on the left subarray



## Pseudocode

quicksort(array,low,high)

    if low >= high return

    pivot = partition(array,low,high)

    quicksort(array,low,pivot-1)

    quicksort(array,pivot+1,high)

end

partition(array,low,high)

    pivotIndex = (low+high) / 2

    swap(pivotIndex,high)

    i = low

    for j=low to high

        if array[j] <= array[high]

            swap(i,j)

        i++

    swap (i,high)

    return i

end

We call the sort method recursively on the right subarray



## Pseudocode

quicksort(array,low,high)

    if low >= high return

    pivot = partition(array,low,high)

    quicksort(array,low,pivot-1)

    quicksort(array,pivot+1,high)

end

partition(array,low,high)

    pivotIndex = (low+high) / 2

    swap(pivotIndex,high)

    i = low

    for j=low to high

        if array[j] <= array[high]

            swap(i,j)

        i++

    swap (i,high)

    return i

end

We should generate a random index for the pivot ... OR we can have the middle item of the array as the pivot !!!



## Pseudocode

**quicksort(array,low,high)**

**if** low >= high **return**

**pivot** = partition(array,low,high)

    quicksort(array,low,pivot-1)

    quicksort(array,pivot+1,high)

**end**

**partition(array,low,high)**

**pivotIndex** = (low+high) / 2

**swap**(pivotIndex,high)

**i** = low

**for** j=low to high

**if** array[j] <= array[high]

**swap**(i,j)

**i**++

**swap** (i,high)

**return** i

**end**

We make the pivot to be the last item in the array !!!



## Pseudocode

**quicksort(array,low,high)**

**if** low >= high **return**

    pivot = partition(array,low,high)

    quicksort(array,low,pivot-1)

    quicksort(array,pivot+1,high)

**end**

**partition(array,low,high)**

    pivotIndex = (low+high) / 2

    swap(pivotIndex,high)

    i = low

**for** j=low to high

**if** array[j] <= array[high]

            swap(i,j)

            i++

    swap (i,high)

**return** i

**end**

This loop will decide what are the items that will be on the left side of the pivot or the right side of the pivot !!!



## Pseudocode

quicksort(array,low,high)

    if low >= high return

    pivot = partition(array,low,high)

    quicksort(array,low,pivot-1)

    quicksort(array,pivot+1,high)

end

partition(array,low,high)

    pivotIndex = (low+high) / 2

    swap(pivotIndex,high)

    i = low

    for j=low to high

        if array[j] <= array[high]

            swap(i,j)

        i++

    swap (i,high)

    return i

end

Variable i tracks the threshold item → separates items that are smaller / greater than the pivot !!!



## Pseudocode

quicksort(array,low,high)

    if low >= high return

    pivot = partition(array,low,high)

    quicksort(array,low,pivot-1)

    quicksort(array,pivot+1,high)

end

partition(array,low,high)

    pivotIndex = (low+high) / 2

    swap(pivotIndex,high)

    i = low

    for j=low to high

        if array[j] <= array[high]

            swap(i,j)

            i++


    swap (i,high)

    return i

end

We return the index of the pivot so the threshold index !!!







quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



23	6	4	-1	0	12	8	3	1
----	---	---	----	---	----	---	---	---



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



23	6	4	-1	0	12	8	3	1
----	---	---	----	---	----	---	---	---



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



23	6	4	-1	0	12	8	3	1
----	---	---	----	---	----	---	---	---



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end





quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



23	6	4	-1	1	12	8	3	0
----	---	---	----	---	----	---	---	---

i=0



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



23	6	4	-1	1	12	8	3	0
----	---	---	----	---	----	---	---	---

i=0



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=0



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=0



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=0



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=0



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]

swap(i,j)

i++

swap (i,high)

return i

end



i=0



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



-1	6	4	23	1	12	8	3	0
----	---	---	----	---	----	---	---	---

i=0



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=1



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=1



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=1



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=1



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=1



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



-1	6	4	23	1	12	8	3	0
----	---	---	----	---	----	---	---	---

i=1



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end





quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end





```
quicksort(array,low,high)
```

```
    if low >= high return
```

```
    pivot = partition(array,low,high)
```

```
    quicksort(array,low,pivot-1)
```

```
    quicksort(array,pivot+1,high)
```

```
end
```

So: we have managed to rearrange the array so that on the left side of the pivot → items that are smaller and on the right are the greater items

```
partition(array,low,high)
```

```
    pivotIndex = (low+high) / 2
```

```
    swap(pivotIndex,high)
```

```
    i = low
```

```
    for j=low to high
```

```
        if array[j] <= array[high]
```


```
            swap(i,j)
```

```
            i++
```

```
    swap (i,high)
```

```
    return i
```

```
end
```



i=1



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

AND we know for sure this item is  
in it's final position !!!

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



-1	0	4	23	1	12	8	3	6
----	---	---	----	---	----	---	---	---



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]

swap(i,j)


i++

swap (i,high)

return i

end

Sort left subarray  
recursively





```
quicksort(array,low,high)
```

```
    if low >= high return
```

```
    pivot = partition(array,low,high)
```

```
    quicksort(array,low,pivot-1)
```

```
    quicksort(array,pivot+1,high)
```

```
end
```

```
partition(array,low,high)
```

```
    pivotIndex = (low+high) / 2
```

```
    swap(pivotIndex,high)
```

```
    i = low
```

```
    for j=low to high
```

```
        if array[j] <= array[high]
```


```
            swap(i,j)
```

```
            i++
```

```
    swap (i,high)
```

```
    return i
```

```
end
```





quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



-1	0	4	23	1	12	8	3	6
----	---	---	----	---	----	---	---	---



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



Sort right subarray  
recursively



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



-1	0	4	23	1	12	8	3	6
----	---	---	----	---	----	---	---	---



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end





quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end





quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end





quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



-1	0	4	23	1	6	8	3	12
----	---	---	----	---	---	---	---	----



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end





quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=0



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=0



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=0



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=1



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=1



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=1



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=1



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=1



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end





quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=1



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=1



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=1



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=2



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=2



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=2



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=2



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=2



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=2



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=2



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=3



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=3



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=3



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=3



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=3



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=3



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=3



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=3



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=4



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=4



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=4



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=4



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=4



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=4



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=4



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=4



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=5



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=5



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end





quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end





**quicksort(array,low,high)**

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

**partition(array,low,high)**

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]

swap(i,j)


i++

swap (i,high)

return i

end

So: we have managed to rearrange the array so that on the left side of the pivot → items that are smaller and on the right are the greater items



i=5



**quicksort(array,low,high)**

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

So: we have managed to rearrange the array so that on the left side of the pivot → items that are smaller and on the right are the greater items

**partition(array,low,high)**

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



-1	0	4	1	6	8	3	12	23
----	---	---	---	---	---	---	----	----



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]

swap(i,j)


i++

swap (i,high)

return i

end

Sort left subarray  
recursively





quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]

swap(i,j)


i++

swap (i,high)

return i

end

Sort left subarray  
recursively





quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end





quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end





quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end





quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



-1	0	4	1	3	8	6	12	23
----	---	---	---	---	---	---	----	----



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end





quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=0



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=0



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=0



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=0



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=1



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=1



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=1



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end





quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=2



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=2



```
quicksort(array,low,high)
```

```
    if low >= high return
```

```
    pivot = partition(array,low,high)
```

```
    quicksort(array,low,pivot-1)
```

```
    quicksort(array,pivot+1,high)
```

```
end
```

```
partition(array,low,high)
```

```
    pivotIndex = (low+high) / 2
```

```
    swap(pivotIndex,high)
```

```
    i = low
```

```
    for j=low to high
```

```
        if array[j] <= array[high]
```


```
            swap(i,j)
```

```
            i++
```

```
    swap (i,high)
```

```
    return i
```

```
end
```



i=2



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=2



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=3



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=3



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=3



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=3



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=3



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end





quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=3



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=3



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end





quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]

swap(i,j)


i++

swap (i,high)

return i

end

Sort left subarray  
recursively





quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end





quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end





```
quicksort(array,low,high)
```

```
    if low >= high return
```

```
    pivot = partition(array,low,high)
```

```
    quicksort(array,low,pivot-1)
```

```
    quicksort(array,pivot+1,high)
```

```
end
```

```
partition(array,low,high)
```

```
    pivotIndex = (low+high) / 2
```

```
    swap(pivotIndex,high)
```

```
    i = low
```

```
    for j=low to high
```

```
        if array[j] <= array[high]
```

```
            swap(i,j)
```

```
            i++
```

```
    swap (i,high)
```

```
    return i
```

```
end
```





quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end





quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end





quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=0



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=0



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=0



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=0



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=0



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=0



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=0



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end





quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end





quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end





quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]

swap(i,j)


i++

swap (i,high)

return i

end

Sort right subarray  
recursively





quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end





quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end





quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end





quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end





quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end





quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=0



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=0



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=0



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=0



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=0



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=0



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=0



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=0



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



i=0



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end





quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]

swap(i,j)


i++

swap (i,high)

return i

end

Sort right subarray  
recursively





```
quicksort(array,low,high)
```

```
    if low >= high return
```

```
    pivot = partition(array,low,high)
```

```
    quicksort(array,low,pivot-1)
```

```
    quicksort(array,pivot+1,high)
```

```
end
```

```
partition(array,low,high)
```

```
    pivotIndex = (low+high) / 2
```

```
    swap(pivotIndex,high)
```

```
    i = low
```

```
    for j=low to high
```

```
        if array[j] <= array[high]
```


```
            swap(i,j)
```

```
            i++
```

```
    swap (i,high)
```

```
    return i
```

```
end
```





quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end





quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]

swap(i,j)


i++

swap (i,high)

return i

end

Sort right subarray  
recursively





```
quicksort(array,low,high)
```

```
    if low >= high return
```

```
    pivot = partition(array,low,high)
```

```
    quicksort(array,low,pivot-1)
```

```
    quicksort(array,pivot+1,high)
```

```
end
```

```
partition(array,low,high)
```

```
    pivotIndex = (low+high) / 2
```

```
    swap(pivotIndex,high)
```

```
    i = low
```

```
    for j=low to high
```

```
        if array[j] <= array[high]
```


```
            swap(i,j)
```

```
            i++
```

```
    swap (i,high)
```

```
    return i
```

```
end
```





quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



-1	0	1	3	4	6	8	12	23
----	---	---	---	---	---	---	----	----



quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]

swap(i,j)


i++

swap (i,high)

return i

end

Sort right subarray  
recursively





quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end





quicksort(array,low,high)

if low >= high return

pivot = partition(array,low,high)

quicksort(array,low,pivot-1)

quicksort(array,pivot+1,high)

end

partition(array,low,high)

pivotIndex = (low+high) / 2

swap(pivotIndex,high)

i = low

for j=low to high

if array[j] <= array[high]


swap(i,j)

i++

swap (i,high)

return i

end



-1	0	1	3	4	6	8	12	23
----	---	---	---	---	---	---	----	----



# Worst case

The most naive pivot selection algorithm is to choose the first element as the pivot

~ this results in worst case behavior if the data is already sorted

(the first element will always be the min)

$$O(N^2)$$

