DRAFT - NOT FINAL

Phylaxtag Warranty

Design & build guide, version 3.4

"The product owns its warranty."

This e-bike has its own warranty fund. Sell the bike, and the fund and the service book move with it.

Name: Phylaxtag (Greek φύλαξ, "guardian"). Repo: phylaxtag · X: @phylaxtag · phylaxtag.com (both to be registered)
NEAR Hackathon 2026 (1-14 Nov 2026) · Track: NFTs That Do Something (nfts), optionally Real-World Money (realworld)
Prototype on NEAR testnet

Project owner: pranesta kresa · Spec owner: Pharita (Grok team)
Draft date: 4 November 2026 (WIB) · Author: Pharita · Replaces: Phylaxtag Warranty v3.3 (4 Nov 2026)

How to use this document. Sections 1-4 are for everyone, including judges. Sections 5-8 are the technical spec the Cursor team builds from. Sections 9-13 are the team plan, schedule and submission material. Anything not yet checked is marked **[UNVERIFIED]**; any number that must come from a real run is marked **[TO BE MEASURED]**. **Submission deadline: 14 Nov 2026 23:59 UTC = 15 Nov 2026 06:59 WIB.** Target submit: around 12 Nov.

DRAFT - not final. Only Pharita edits this spec. Comments and change requests go to Pharita. This document contains no keys, seed phrases or other secrets, and none may be added.

Contents

Changes from v3.3 (v3.4)
Changes from v3.2 (v3.3)
Changes from v3.1 (v3.2)
Changes from v3 (v3.1)
Changes from v2
Changes from v1 (summary)
1. Pitch and one-line story
2. Problem
3. Solution and actors
4. End-to-end flow (example: e-bike EB-001)
5. Contract design
6. Threat model (incl. transfer threat model)
7. Test plan
8. Web pages
9. Team plan (three teams)
10. Day-by-day schedule
11. Demo video script (60-90 s)
12. Hackathon rules and submission checklist
13. Submission text (English)
14. Open items and unverified claims

Changes from v3.3 (v3.4)

#	Change	Where
1	Rename only, no design change: project is now **Phylaxtag** (Greek φύλαξ, "guardian"). Repo `phylaxtag`, X @phylaxtag and phylaxtag.com to be registered. O5 resolved.	All, 1, 12, 13, 14

Changes from v3.2 (v3.3)

#	Change (reviewer Jiwoo, user approved)	Where
1	T17: `total_locked` changes only via mint, pay/expire and their failed-payout callbacks (T10, T19, T21, T22); 5.1 rows for mint, pay_service and expire now state their `total_locked` effect; Day 0 says spec v3.3 and repo "new recommended"	7, 5.1, 10
2	S11 Test column: T28 covers same issuer only; cross-issuer duplicate is an accepted residual risk	6.2, 6.3

Changes from v3.1 (v3.2)

#	Change (reviewer Jiwoo, user approved)	Where
1	Failed-payout / failed-refund callbacks restore the token balance **and** `total_locked` by the same amount (keeps the T26 invariant); added to T10, T19, T21, T22	5.1, 7
2	Another allowlisted issuer could mint the same serial_hash: two warranty NFTs for one item. Accepted risk; asset page shows the issuer prominently	6.2 S11, 6.3, 8
3	Storage reserve top-up = plain NEAR transfer to the contract account (not the removed per-token `top_up`)	5.4
4	Nits: Day 0 "spec v3.2 approved"; Cursor row "one repo (new public repo recommended, not mandatory per Q-003)"; version labels	9, 10

Changes from v3 (v3.1)

Small edit pass applying five findings from reviewer **Jiwoo** (user approved).

#	Change	Where
1	`mint` wording: workshops must be 1..N accounts, none of them the issuer (empty list or issuer as workshop fails, as in T29)	5.1
2	New check: a workshop must not be the contract's own account (protects the T26 invariant); new test T39; total now 39 tests	5.1, 7
3	Accepted risk added: no `remove_issuer` / `set_admin` in the MVP	6.3, 14
4	"New repo" marked OPTIONAL, quoting live Q-003; new repo stays our recommended option	12
5	README outline #3 now names exact test counts	12.2

Changes from v2

v3 applies the red-team findings of reviewer **Jiwoo** (Hermes team), approved by the user and written by Pharita (spec owner).

#	Change	Where
A	Full submission API contract quoted verbatim from the live HACKATHON.md (fetched 2026-11-04): endpoint, every field rule, status codes, consent notice, spam-trap field, retry rules. Track ids re-verified (`nfts` is valid). Submission-text length recounted programmatically.	12, 13
B1	`mint` rejects `cooldown_ns == 0`. In-flight guard considered and **not** adopted (justified in 5.2); new tests T34, T35.	5.1, 5.2, 7
B2	`expire` always marks the token Expired after expiry, even with an empty fund (no transfer when nothing to refund). A second call is a defined no-op returning 0. `expire_in_flight` flag removed. New UI state "Empty (fund used up)". T09, T21, T22 updated; new T36.	5.1, 5.3, 8, 7
B3	Holder log can never block a transfer: drop-oldest ring buffer of the latest 50 entries + a total-transfers counter. New T37.	5.3, 5.4, 6, 7
B4	New residual risk: a seller can make a last claim right before selling, so the buyer waits a full cooldown. UI + README disclosure, no contract change. New web test T38.	6.3, 8
C	Similar-project check recorded (reviewer-reported, not independently verified); code-window rule and historic judging criteria recorded (reviewer-reported) and used as pitch ordering.	1, 12, 14
D	Open items split into Decided vs Still open.	14

Changes from v1 (summary)

#	Change	Why
1	`top_up` **removed entirely.** The fund is deposited once, at mint, by the issuer. No later deposits by anyone.	User decision 4 Nov 2026. Keeps the money flow simple: issuer in, workshops or issuer out. Removes the "who owns a top-up?" confusion.
2	**Claim limits are automatic and enforced only by the contract:** per-claim cap, cooldown between claims, cumulative cap = remaining fund, issuer-set workshop allowlist, expiry. **No issuer co-sign or approval step.**	User decision 4 Nov 2026. One-call claims stay; residual collusion risk is documented honestly (section 6.3).
3	**New transfer threat model** (every way a seller could keep money or access), each with mitigation and test; new tests for a sale in the middle of a payout, including the payout-callback failure path.	Required by the official NFT-track prompt (`prompts/10-nfts.md`).
4	**New web pages:** holder-only (gated) page, per-NFT history (funded / paid out / who held it), "Sell this item" demo button, demo mode with short cooldown and expiry.	Required by the NFT-track prompt; makes the transfer visible in the demo.
5	**Fully English**, renamed working document "Phylaxtag Warranty v2".	Judges, AI pre-screeners and README are in English.
6	**Three-team structure** (Cursor = only code writer; Grok = spec, schedule, rules, submission; Hermes = red team, README, newcomer test) and hard rules on who may change what.	Avoids conflicting edits and keeps secrets with the user only.

#	Change	Why
7	Smaller fixes: exact storage accounting (explicit `fund_amount`, excess refunded), salted serial hash, 50-record cap, `nft_transfer_call` disabled, claims blocked while the token is listed (has approvals), owner may not pay themselves, `expire` can be retried if a refund comes back.	Found while writing the transfer threat model.

1. Pitch and one-line story

One line for a newcomer: This e-bike has its own warranty fund. Sell the bike, and the fund and the service book move with it.

30-second pitch

Buying used goods is a trust problem. Warranties usually die when an item is resold, and service records are lost or live on paper.

Phylax (φύλαξ) is Greek for 'guardian': the warranty is a guardian that lives on the item and transfers with it.

Phylaxtag turns one physical item (MVP: one e-bike) into an NFT on NEAR. The NFT **carries a warranty fund and a service history**. The issuer (seller or manufacturer) deposits the fund once and chooses the approved workshops. The owner pays an approved workshop straight from the fund with one call, within limits the contract enforces. The owner can never withdraw the fund to their own wallet.

When the bike is sold, the NFT moves to the buyer, and the remaining fund and the full service history move with it. The seller loses access at that moment. After the warranty expires, the remaining fund goes back to the issuer.

Pitch ordering (suggestion). Reviewer Jiwoo reports that historic NEAR hackathon judging criteria were: technical implementation, design, impact, originality, sustainability **(reviewer-reported; not in the live HACKATHON.md)**. Order the pitch, README intro and video the same way: working contract + tests first, then the UX, then who benefits, then what is new, then how it could continue.

Key facts

Item	Value
Name	Phylaxtag. Phylax (φύλαξ) is Greek for 'guardian': the warranty is a guardian that lives on the item and transfers with it.
Repo / X / domain	`phylaxtag` / @phylaxtag / phylaxtag.com (X handle and domain to be registered)
Tagline	"The product owns its warranty."
Standards	NFT NEP-171 core, NEP-177 metadata, NEP-181 enumeration, NEP-178 approvals (restricted, see 5.6), NEP-297 events
Network	NEAR testnet (prototype)
MVP asset	One e-bike, token `EB-001`
Track	NFTs That Do Something (`nfts`); optionally Real-World Money (`realworld`)
Core calls	`mint`, `pay_service`, NEP-171 `nft_transfer`, `expire`; views `get_asset`, `get_service_history`, `get_holder_history`
Off-chain parts	No keeper or bot. Static web app + proof files off-chain (only hashes on-chain)
Claim to use	"To our knowledge, a working NFT-warranty implementation on NEAR." Never "the first" (section 14).

2. Problem

- **Warranties do not follow the item.** They are tied to the first buyer's name or receipt. On resale the warranty is effectively gone.
- **Service history cannot be checked.** A used-item buyer cannot see what was serviced, when, or where.
- **Warranty value is invisible.** Nobody can see how much repair budget is left.
- **Claims are slow.** Forms, approvals and waiting are too heavy for small repairs.
- **Fraud risk.** If a warranty fund could be cashed out freely, an owner could stage fake repairs with a friend and drain it.

MVP users: an e-bike seller (issuer), the bike owner, approved workshops, and used-bike buyers.

3. Solution and actors

The warranty fund is stored **per token** in the contract, not per owner. The money is attached to the item, whoever holds it. Control is simply "whoever `nft_token(id).owner_id` says right now".

Actors

Actor	Who	May	May not
Admin	Contract deployer (the user's testnet account)	Set the issuer allowlist at `new`; `add_issuer`	Touch any token's fund
Issuer	Allowlisted seller / manufacturer	Mint with a one-time deposit; set workshops, expiry, per-claim cap, cooldown; receive the remainder after expiry	Take the fund back before expiry; change limits or workshops after mint; add money later
Owner	Current NFT holder	Call `pay_service` to an approved workshop within limits; sell (transfer) the NFT; open the holder-only page	Withdraw the fund; pay a non-approved account; pay themselves; claim while the token is listed
Workshop	Account on the token's allowlist	Receive payments	Trigger a payment
Buyer	Next owner	Inspect fund and history before buying; becomes owner on transfer	-
Anyone	Any account	Call `expire` after expiry; read all views	Change asset data

Design principles

- **One call per service.** No submit/approve stages. The owner calls `pay_service` and the contract checks the limits.
- **Money never reaches the owner.** It can only go to an approved workshop, or back to the issuer after expiry.
- **No pending state.** Nothing is "in progress" between calls except an in-flight payout, whose result always lands back on the token (section 6.2).
- **Limits are code, not people.** Cap, cooldown, remaining fund, allowlist and expiry. No co-signer.
- **One deposit.** The issuer funds the warranty once at mint. No `top_up`.

Why not "Phylaxtag Lite" (owner-funded savings)

An owner-funded service wallet was considered and rejected: that is personal savings, not a warranty. The value of a warranty comes from the seller's promise, so the **issuer funds it**. With `top_up` removed in v2, nobody else can add money, so there is no confusion about who owns extra funds.

4. End-to-end flow (example: e-bike EB-001)

Example values: fund **10 NEAR**, one service **2 NEAR**, per-claim cap **3 NEAR**, cooldown **30 days** (demo token: short, e.g. 60 s), expiry **2027-11-03** (demo token: a few minutes). All example values are illustrative, not measured.

#	Step	Who	Call	Result
1	Admin allowlists the issuer	Admin	`new(admin, [issuer])` or `add_issuer`	Issuer may mint
2	Issuer mints EB-001 and deposits the fund	Issuer	`mint("EB-001", serial_hash, 10 NEAR, 2027-11-03, 3 NEAR, 30d, [ws-a, ws-b], meta)` + attached 10 NEAR + storage cost	Fund exactly 10 NEAR; storage paid from the deposit; excess refunded to issuer
3	Issuer transfers the NFT to the first buyer, Alice	Issuer	`nft_transfer(alice, "EB-001")`	Owner = Alice; holder log: Alice, fund 10
4	Alice services the bike at ws-a and pays from the fund	Alice	`pay_service("EB-001", ws-a, 2 NEAR, note_hash, "brakes")`	ws-a receives 2 NEAR; fund 8; 1 record; next claim after cooldown
5	Alice tries 4 NEAR, another workshop, or a second claim inside the cooldown	Alice	`pay_service(...)`	Rejected: "Over cap" / "Workshop not approved" / "Cooldown active"
6	Alice sells to Budi ("Sell this item" button)	Alice	`nft_transfer(budi, "EB-001")`	Owner = Budi; fund 8 and 1 record move; holder log: Budi, fund 8; Alice's holder page now says "not the holder"
7	Alice tries to pay again	Alice	`pay_service(...)`	Rejected: "Not owner". Budi can claim once the cooldown (which is per token) has passed
8	After 2027-11-03, anyone calls expire	Anyone	`expire("EB-001")`	Remaining fund (e.g. 8 NEAR) goes to issuer; status Expired; history stays readable

5. Contract design

Rust with `near-sdk` and `near-contract-standards`. **Pin exact versions on Day 0/1** in `Cargo.toml` (and commit `Cargo.lock`); exact versions are **to be verified on day 1** against the current docs and the `near-smart-contracts` agent skill. Fallback route: if the pinned SDK breaks the build or sandbox tests, the Cursor team switches to the previous stable release and records the reason in the README. All amounts are yoctoNEAR (1 NEAR = 10^24 yocto); all times are block timestamps in nanoseconds.

5.1 Function table

Function	Caller	Effect	Checks (in order)	Errors (examples)
`new(admin, issuers)` init	Deployer	Set admin and issuer allowlist	Once only	"Already initialized"
`add_issuer(account)`	Admin	Add an issuer	caller = admin	"Only admin"
`mint(token_id, serial_hash, fund_amount, expiry, claim_cap, cooldown_ns, workshops, metadata)` payable	Allowlisted issuer	Create NFT owned by issuer; store asset; balance = `fund_amount` (`total_locked` + same); storage paid from deposit; excess refunded to issuer	issuer allowlisted; token_id new (never reused); serial_hash new for this issuer; expiry > now; 0 < claim_cap ≤ fund; **cooldown_ns > 0**; workshops: 1..N accounts, none of them the issuer or the contract account (`env::current_account_id()`); deposit ≥ fund + storage cost	"Not an approved issuer", "Token exists", "Serial already used", "Bad expiry", "Bad cap", "Cooldown must be > 0", "Bad workshop list", "Deposit too small"
`pay_service(token_id, workshop, amount, note_hash, work_type)` payable 1 yocto	Current owner only	Deduct balance (and `total_locked`), append record, set `last_claim_at`, send NEAR to workshop, callback `on_payout`	exactly 1 yocto; caller = owner; not expired; no active approvals; workshop on list; workshop ≠ owner; 0 < amount ≤ cap; amount ≤ balance; now ≥ last_claim_at + cooldown; records < 50; string lengths	"Not owner", "Expired", "Token is listed", "Workshop not approved", "Cannot pay yourself", "Over cap", "Insufficient balance", "Cooldown active", "History full"

Function	Caller	Effect	Checks (in order)	Errors (examples)
`nft_transfer`	Owner or approved account	Standard NEP-171 move (`total_locked` unchanged); fund and records stay on the token; holder log written to the ring buffer (drop-oldest), `holder_total` + 1	Standard (1 yocto); approvals cleared; **never fails because of the log**	Standard
`nft_transfer_call`	-	**Disabled in MVP**	Always panics	"nft_transfer_call disabled in MVP"
`expire(token_id)` → U128 refunded	Anyone	Set status Expired (always). If balance > 0: balance → 0 (`total_locked` − same), send it to issuer, callback `on_expire_payout`. If balance = 0: no transfer	now ≥ expiry. Never fails for "empty" or "already expired"	"Not yet expired", "Token not found"
`on_payout` / `on_expire_payout`	Contract itself (`#[private]`)	On failure: add the amount back **to the token balance and to `total_locked`** (both by the same amount, else the T26 invariant breaks), mark record Failed (payout), emit event; status stays as is	`#[private]`; reads promise result	-
`get_asset(token_id)` view	Anyone	Asset + owner + balance + stored status + **display status** (Active / Empty / Expired, close pending / Expired) + next claim time	-	null if missing
`get_service_history(token_id, from, limit)` view	Anyone	Paginated service records	-	-
`get_holder_history(token_id)` view	Anyone	Latest ≤ 50 holders in time order (oldest first), with since and balance at transfer, plus `holder_total`	-	-
`get_storage_info()` view	Anyone	`storage_usage`, `total_locked`, contract balance (for the storage test)	-	-

There is **no** `top_up`, no owner withdrawal, and no function that changes workshops (so the workshop checks live only in `mint`; any future workshop-update function must repeat them), cap, cooldown or expiry after mint. The only payable entry points that keep money are `mint` (once per token) and the 1-yocto confirmations.

5.2 Claim-limit rules (automatic, contract-only)

Rule	Set by	Enforced in	Demo-mode value
Per-claim cap: `amount ≤ claim_cap`	Issuer at mint	`pay_service`	e.g. 3 NEAR
Cooldown: `now ≥ last_claim_at + cooldown_ns`, `cooldown_ns > 0` required at mint (per token, **not reset on transfer**)	Issuer at mint	`pay_service`	short, e.g. 60 s
Cumulative cap: total paid ≤ remaining fund (balance can never go negative; no top-ups)	Implicit	`pay_service`	10 NEAR fund
Workshop allowlist (fixed at mint; owner never on it as payee)	Issuer at mint	`pay_service`	2 test workshop accounts
Expiry: no claims at/after expiry; remainder returns to issuer	Issuer at mint	`pay_service`, `expire`	a few minutes
No claims while the token has active approvals (listed for sale)	Contract rule	`pay_service`	-

"Demo mode" is **not a contract flag**: it is just a demo token minted with short cooldown and expiry values. The contract has one code path for real and demo tokens. Upper bound on what an owner plus one colluding approved workshop can extract: `min(balance, claim_cap × (1 + floor((expiry − now) / cooldown)))`. The issuer chooses all three numbers; `cooldown_ns > 0` keeps the formula defined.

Concurrency: why cooldown_ns > 0 and no in-flight flag

Calls to one contract run one at a time, and `pay_service` deducts the balance, writes the record and sets `last_claim_at` **before** it creates the payout promise. With `cooldown_ns > 0`, a second claim in the same block (same timestamp) or before the cooldown ends is rejected, and the balance can never be spent twice. The only asynchronous part is the payout itself; if it fails, the callback returns the amount to the token.

Option	Pro	Con	Decision
Layer 1: require `cooldown_ns > 0` + state-before-promise	Simple; no extra state; nothing can get stuck	A very small cooldown still allows quick repeat claims (bounded by cap and balance)	**Adopted**
Layer 2: per-token `payout_pending` flag set in `pay_service`, cleared in `on_payout`	Blocks a new claim until the previous payout has settled	If the callback does not run as planned (e.g. a gas mistake), the token is frozen for claims; fixing that needs an admin unlock, which is a new trust and attack surface. Adds no money safety because the balance is already deducted	**Not adopted** in the MVP; the ServiceRecord `Pending` status is shown in the UI instead

Callbacks must reserve enough gas so they always run; T10 and T19 check this. A minimum cooldown value for real tokens (beyond `> 0`) is an open item (section 14).

5.3 Storage layout

```
struct Asset {
    issuer: AccountId,
    serial_hash: String,          // sha256(salt || serial), salt kept off-chain by issuer
    balance: NearToken,           // the warranty fund, stored per token
    expiry_ns: u64,
    claim_cap: NearToken,
    cooldown_ns: u64,
    last_claim_at_ns: u64,        // per token, survives transfers
    workshops: Vec<AccountId>,    // fixed at mint
    status: Active | Expired,     // display adds Empty / close pending
    holder_total: u32,            // all transfers ever, incl. mint
    holder_next: u32,             // ring-buffer write position
}
struct ServiceRecord { workshop, amount, work_type, note_hash, owner_at_claim,
                       timestamp_ns, block_height, status: Pending | Paid | Failed }
struct HolderRecord  { owner, since_ns, balance_at_transfer }
Contract {
    tokens: NonFungibleToken,                          // NEP-171/177/181/178
    assets: LookupMap<TokenId, Asset>,
    history: LookupMap<TokenId, Vector<ServiceRecord>>,   // max 50
    holders: LookupMap<TokenId, Vector<HolderRecord>>,    // ring, latest 50
    used_serials: LookupSet<(AccountId, String)>,
    issuers: LookupSet<AccountId>,  admin: AccountId,  total_locked: NearToken,
}
```

Holder log when full (decision): the log is a drop-oldest ring buffer. Entries 1-50 are appended; from the 51st transfer on, the oldest slot is overwritten and `holder_total` keeps counting. The issuer and mint time stay in `Asset`, and every transfer remains in the permanent `nft_transfer` events, so full history can still be rebuilt by an indexer. A transfer therefore **never** fails because of the log, so the bike always stays sellable.

Key point: `balance` lives inside `Asset`, looked up by `token_id`. There is no per-owner balance, so nothing has to "move" on transfer. Test T01 proves it.

5.4 Storage accounting (exact)

- `mint` takes an explicit `fund_amount`. The contract measures `env::storage_usage()` before and after writing the token, computes the exact storage cost, requires `deposit ≥ fund_amount + cost`, and refunds the excess to the issuer. The demo fund is therefore exactly 10 NEAR.
- Service records and holder records are paid from a contract storage reserve funded by the user at deploy. To add more reserve later, send a plain NEAR transfer to the contract account: no function is needed, and

the invariant stays safe because the balance only increases. This is **not** the removed `top_up` (which was per-token warranty funding); reserve money is never part of any token's fund. Both are capped at 50, so worst-case storage per token is bounded. After the holder ring is full, each transfer overwrites one slot: storage changes only by the size difference between the old and new account id, and never grows past 50 records of maximum account-id length.

- Invariant checked by test T26: `contract balance ≥ total_locked + storage_usage × storage_byte_cost`.
- Bytes per mint, per service record and per holder record, and the resulting NEAR cost: **[TO BE MEASURED]** by T26 (and holder-ring figures by T37) on Day 2, then copied into the README. No figures are given here on purpose.
- String limits: `work_type` ≤ 32 bytes, `note_hash` = 64 hex chars, `serial_hash` = 64 hex chars, `token_id` ≤ 32 bytes (proposed; Cursor may adjust with a PR note).

5.5 Events (NEP-297)

Event	When	Data
`nft_mint`, `nft_transfer` (standard)	Mint / transfer	standard fields
`warranty_funded`	Mint only (no top-ups exist)	token_id, amount, issuer
`service_paid`	`pay_service`	token_id, owner, workshop, amount, work_type, note_hash
`payout_failed`	`on_payout` sees failure	token_id, amount, workshop, record index
`warranty_expired` / `expire_refund_failed`	First `expire` (amount may be 0) and any later refund retry / callback on failure	token_id, amount, issuer

5.6 NEP notes

- **NEP-171:** use the standard `NonFungibleToken`; wrap `nft_transfer` only to append the holder log. Exact override hooks in the pinned SDK version: **[UNVERIFIED]**, check on Day 1.
- `nft_transfer_call` **disabled** in the MVP (panics). It would make the receiver the temporary owner until `nft_resolve_transfer`, which opens a claim-during-transfer window. Explained in the README.
- **NEP-178 approvals:** kept for standards compatibility but restricted: an approved account may transfer, never `pay_service`; `pay_service` is rejected while any approval exists ("Token is listed"); approvals are cleared on transfer (standard behaviour, tested in T24).
- **NEP-177:** `title` "E-bike EB-001", `description`, `extra` JSON (asset_type, serial_hash). No image required.
- **NEP-181:** `nft_tokens_for_owner` drives "My items" and the gated page.
- **No sub-accounts / access keys per token.** The track prompt suggests sub-accounts; we use a per-token ledger inside one contract instead, so there is no key for a seller to keep. This is a deliberate MVP choice, stated in the README.

6. Threat model

6.1 How control passes on transfer (README text)

This section is written so it can be pasted into the README as is.

1. There is exactly one source of truth for control: `nft_token(token_id).owner_id` in the NEP-171 contract.
2. Every money-moving owner action (`pay_service`) checks `predecessor == owner_id` **at call time**. Nothing is cached, and there is no session, allowance, sub-account or access key per token.
3. The warranty fund is a field of the token (`Asset.balance`), not of any account. A transfer changes `owner_id` and nothing else, so the fund, service history, cooldown clock and limits stay with the item.

4. Transfer clears all NEP-178 approvals, so a marketplace or helper the seller approved loses its right to move the token.
5. `nft_transfer_call` is disabled, so there is no window where a receiver contract is a temporary owner.
6. Money can only leave to an approved workshop (never the owner) or to the issuer after expiry. A failed payment returns to the **token**, so whoever owns the token then benefits, never the old owner.
7. The holder-only web page re-reads `owner_id` from the chain on every load and before every action, so the old owner sees "You are not the current holder" right after the sale.

What stops the old owner keeping money or access: they never had custody of the money (no withdrawal path), the only "key" is current ownership checked on every call, the per-token cooldown means they cannot burn a last claim and re-arm it by moving the token around, and claims are blocked while the token is listed.

6.2 Transfer threat model: how a seller could try to keep money or access

ID	Seller attack	Mitigation	Test
S1	Drain the fund with a colluding approved workshop right before the sale	Per-claim cap + per-token cooldown bound the drain; buyer sees balance, last claim and "next claim possible at" on the asset page before paying; holder log records `balance_at_transfer`	T01, T15, T25
S2	Front-run the sale: buyer pays off-chain, seller claims before transferring	Same bound as S1. Sale price is paid off-chain in the MVP (no on-chain escrow); README tells buyers to check the balance after transfer. Atomic escrow sale: out of scope	T15, T25
S3	Listing + claiming race: approve a marketplace, then claim before the buyer's purchase lands	`pay_service` rejected while any approval exists; to claim, the seller must revoke, which makes the listing fail	T23
S4	Keep an approval after the sale to pull the NFT back	Approvals cleared on every transfer (standard)	T24
S5	Claim through an approved (non-owner) account	`pay_service` is owner-only	T12
S6	`nft_transfer_call` tricks (seller-controlled receiver keeps temporary ownership, claims, then resolves the token back)	`nft_transfer_call` disabled in MVP	T13
S7	Keep calling `pay_service` after the sale	Owner checked at call time	T02
S8	Sell while a payout is in flight and hope a failed payout refunds to them	Callback restores the amount to the token balance, never to an account; record marked Failed	T19, T20
S9	Reset the cooldown by transferring to a second wallet	Cooldown stored per token, not reset on transfer	T16
S10	Owner is also an approved workshop and pays themselves	`workshop ≠ owner`; issuer picks workshops	T18
S11	Re-mint: create a second token for the same bike, or reuse a token_id; or **another** allowlisted issuer mints the same serial_hash (two warranty NFTs for one item)	token_id never reusable (no burn in MVP); serial_hash unique per issuer. Cross-issuer duplicate: residual risk; buyer checks the issuer shown prominently on the asset page matches the brand/seller	T28 (same issuer only); cross-issuer duplicate = accepted residual risk (see 6.3)
S12	Expire timing: claim just before expiry; or a failed payout lands after `expire`	Claims allowed only before expiry, within cap/cooldown; a refund that lands after expiry is sent to the issuer by calling `expire` again	T07, T11, T21, T36
S16	Hide previous holders by many self-transfers (push them out of the 50-entry log)	`holder_total` counter shown in UI ("55 transfers, showing last 50"); `nft_transfer` events are permanent; service records unaffected	T37
S17	Last-moment claim before selling so the buyer must wait a full cooldown	Not preventable without a contract change; "next claim possible at" shown on the asset page and in the Sell flow; README disclosure (6.3)	T38
S13	Keep using the holder-only page after the sale (cached session)	Page re-checks on-chain owner on each load and action	T31
S14	Keep a key that controls the item's wallet	No per-token sub-account or key exists in this design	Design review (Hermes)
S15	Add money later and claim it back (old `top_up` path)	`top_up` removed; mint excess refunded to issuer at mint only	T17

6.3 General threats and residual risk

Threat	Mitigation	Residual risk
Owner withdraws to own wallet	No withdrawal function; owner cannot be payee	Low
Owner colludes with an allowlisted workshop (fake repairs)	Cap + cooldown + allowlist + expiry; issuer chooses workshops and parameters	**Real and accepted.** Bounded by the formula in 5.2. No co-sign by design (user decision). Stated in README
Fake issuer mints fake items	Issuer allowlist	Admin is a trust point
A second allowlisted issuer mints the same serial_hash (two warranty NFTs for one bike)	Issuer shown prominently on the asset page; buyer checks it matches the brand/seller	**Accepted for MVP**; uniqueness is per issuer only
No `remove_issuer` / `set_admin` in the MVP	None in the MVP; disclosed in README	**Accepted for the testnet MVP.** A leaked issuer key can mint indefinitely; a lost admin key cannot be recovered. Post-hackathon item
Reentrancy / promise ordering	State changed before the transfer promise; `#[private]` callbacks	Low once T10/T19/T22/T35 pass
Workshop or issuer account deleted (transfer fails)	Callback restores balance; record Failed; `expire` retryable	Low
Contract account keys / code upgrade by deployer	Testnet only; README states the deployer could upgrade	Trust assumption. Production would need locked keys [decision later]
Personal data on-chain	Only salted serial hash and note hash	Low; salt must stay off-chain
NFT taken as proof of authenticity or legal title	Clear statement in UI and README	Depends on users reading it
Storage exhaustion	Exact storage at mint; 50-record caps; holder ring; reserve	Low for demo
Seller claims just before the sale; buyer waits a full cooldown for their first claim (cooldown is per token and never resets)	UI shows "next claim possible at" on the asset page and in the Sell flow; README disclosure. No contract change (resetting the cooldown would reopen S9)	**Accepted.** Buyer can see it before paying
Holder log hides holders older than the latest 50	Total counter + permanent events	Low; needs 50+ transfers (gas only)

Honest limits (must be in the README)

- Prototype on **NEAR testnet**, not a product.
- The NFT does **not** prove physical authenticity and is **not** a legal title.
- The link between NFT and bike (serial number / QR) is outside the contract.
- Nobody verifies that the repair really happened; an approved workshop can collude with an owner within the limits.
- No keeper or required off-chain component.

Deliberately NOT in the MVP

Own token, marketplace or on-chain escrow sale, IoT oracle, price oracle (the fund is denominated in NEAR, not USD), dispute system, multiple asset types, cross-chain, NEAR Intents, `top_up`, issuer co-sign.

7. Test plan

Unit tests for logic; integration tests in the NEAR sandbox (e.g. `near-workspaces`) for real transfers and callbacks; web end-to-end tests for pages. All contract tests must pass before the demo is recorded. IDs T01-T14 are the v1 tests, updated; T15-T33 were added in v2; T34-T38 in v3; T39 in v3.1.

ID	Test	What it proves	Pass criteria
T01	balance_moves_with_nft	Fund and history are per token	Mint 10, pay 2, transfer to Budi: owner Budi, balance 8, 1 record
T02	old_owner_cannot_pay	Control passes on transfer	Alice → Budi; Alice `pay_service` fails "Not owner"; Budi succeeds after cooldown

ID	Test	What it proves	Pass criteria
T03	non_approved_workshop_rejected	Allowlist enforced	Fails "Workshop not approved"
T04	cap_enforced	Per-claim cap	4 NEAR with cap 3 fails "Over cap"; 3 succeeds
T05	over_balance_rejected	Cumulative cap = remaining fund	Balance 1, pay 2 fails "Insufficient balance"
T06	expiry_returns_funds_to_issuer	Remainder goes to issuer only	After expiry, random account calls `expire`; issuer +remainder; balance 0; Expired
T07	pay_after_expiry_rejected	Expiry enforced	Fails "Expired"
T08	only_allowlisted_issuer_can_mint	Issuer allowlist	Fails "Not an approved issuer"
T09	second_expire_is_noop	No double refund; defined second call	Second `expire` returns 0, issuer balance unchanged, no event, status still Expired
T10	failed_payout_restores_balance	Callback failure path	Payee account missing: balance restored on token **and `total_locked` restored by the same amount**, T26 invariant holds, record Failed, `payout_failed` emitted
T11	expire_before_expiry_rejected	No early refund	Fails "Not yet expired"
T12	approved_account_cannot_pay	Approvals cannot claim	Fails "Not owner"
T13	transfer_call_disabled	No temporary-owner window	`nft_transfer_call` panics; owner unchanged
T14	history_view_paginated	History view correct	Order and count correct for from/limit
T15	cooldown_enforced	Automatic cooldown	Second claim inside cooldown fails "Cooldown active"; succeeds after
T16	cooldown_not_reset_by_transfer	S9 blocked	Claim, transfer to own 2nd account, claim again: fails "Cooldown active"
T17	no_top_up_path	`top_up` removed; no later deposits	Calling `top_up` fails (method not found); `total_locked` unchanged by any call except mint, pay/expire, and their failed-payout callbacks (T10, T19, T21, T22)
T18	owner_cannot_pay_self	S10 blocked	Owner who is on the workshop list pays self: fails "Cannot pay yourself"
T19	sale_mid_payout_failure_unit	Sale during payout, failure path (deterministic)	`pay_service` (balance 10→8) → `nft_transfer` to Budi → `on_payout` called with Failed: balance back to 10 on the token and `total_locked` +2 (invariant holds), Budi is owner, Alice received nothing, record Failed
T20	sale_mid_payout_sandbox	Same, on a real sandbox chain	Send `pay_service` (to a missing account) and `nft_transfer` without waiting; whatever the receipt order: final owner Budi, balance 10, Alice +0, record Failed. Also success variant: workshop +2, balance 8
T21	failed_payout_after_expire	S12 / callback after expiry	Payout fails after `expire` ran: amount restored on the Expired token (balance and `total_locked`); next `expire` returns that amount and sends it to issuer; balance 0; status Expired throughout
T22	failed_expire_refund_restores	Expire callback failure	Issuer account missing: balance **and `total_locked`** restored, T26 invariant holds, status stays Expired, `expire_refund_failed` emitted; a later `expire` retries the refund
T23	listed_token_blocks_claim	S3 blocked	`nft_approve(market)` then `pay_service` fails "Token is listed"; after revoke it works
T24	approvals_cleared_on_transfer	S4 blocked	After transfer, old approved account cannot transfer
T25	holder_history_records_transfers	"Who held it" view	Holder log = issuer, Alice, Budi with times and balances 10, 10, 8
T26	storage_accounting_exact	Exact demo numbers	Fund exactly 10 NEAR; excess refunded; invariant holds; bytes and cost per mint/record printed **[TO BE MEASURED]**
T27	history_cap_50	Bounded storage	51st `pay_service` fails "History full"
T28	no_remint	S11 blocked	Same token_id fails "Token exists"; same serial_hash for same issuer fails "Serial already used"
T29	mint_input_validation	Bad parameters rejected	Past expiry, cap 0, cap > fund, empty list, issuer as workshop, small deposit: each fails (cooldown 0: see T34)
T30	string_limits	Storage cannot be inflated	Over-long `work_type` / bad `note_hash` fail
T31	gated_page_access (web e2e)	Only current holder opens the page	Before sale Alice sees owner page; after sale Alice sees "not the current holder", Budi sees it
T32	sell_button_flow (web e2e)	Demo "Sell this item"	Click sell → Sell dialog shows "next claim possible at"; owner Budi, fund unchanged, holder log +1, Alice locked out
T33	readme_newcomer_run (manual)	README reproducible	Asa-Hermes follows README only; every "do X - see Y" step matches; failures filed as issues
T34	mint_rejects_zero_cooldown	B1 validation	`mint` with `cooldown_ns = 0` fails "Cooldown must be > 0"
T35	same_block_double_claim_rejected	No double spend without a pending flag	Two `pay_service` sent without waiting (same block where possible): exactly one succeeds, the other fails "Cooldown active"; balance deducted once
T36	expire_empty_fund_marks_expired	B2: empty token becomes Expired	Fund used to 0; after expiry `expire` returns 0, no transfer, status Expired, `warranty_expired` with amount 0

ID	Test	What it proves	Pass criteria
T37	holder_log_full_never_blocks_transfer	B3 ring buffer	55 transfers all succeed; log has 50 entries (latest, oldest first); `holder_total` = 56 incl. mint; storage stays bounded **[TO BE MEASURED]**
T38	ui_status_and_next_claim (web e2e)	B2/B4 UI	Labels Active / Empty (fund used up) / Expired, close pending / Expired shown correctly; "next claim possible at" on asset page and Sell dialog
T39	mint_rejects_contract_as_workshop	Payouts cannot loop back into the contract (T26 invariant)	`mint` with the contract's own account in `workshops` fails "Bad workshop list"

Mapping v2 → v3: T09 renamed (reject → no-op), T21/T22 updated, T29 points to T34; T34-T38 are new; T39 added in v3.1. **Total: 39 tests** (35 contract tests: T01-T30, T34-T37, T39; 3 web e2e: T31, T32, T38; 1 manual: T33).

8. Web pages

Static web app (e.g. Vite/React or Next.js static export) with NEAR Wallet Selector on testnet. Plain language for newcomers; technical details on a "How it works" page.

Page	Content	Notes
Asset page `/asset/EB-001` (public)	Name, **issuer (shown prominently)**, status (**Active / Empty (fund used up) / Expired, close pending / Expired**), remaining fund, expiry, cap, cooldown and "next claim possible at", approved workshops, last 5 services; "Close warranty" button for anyone when expired with balance > 0	Readable without login; this is the buyer's pre-purchase check
History `/asset/EB-001/history` (public)	**Funded** (mint deposit), **paid out** (each service: workshop, amount, type, status; expiry refund), **who held it** (latest 50 holders with dates and balance at transfer, plus "N transfers in total"), links to explorer	Reads `get_service_history` and `get_holder_history`
Holder-only page `/asset/EB-001/owner` (gated)	"Pay workshop from warranty fund" form, "Sell this item" button (dialog shows "next claim possible at" for the buyer), service note uploads (hash computed in browser)	Opens only if the signed-in account = on-chain owner, re-checked on each load and action. Others see "Only the current holder can open this page"
"Sell this item" (demo)	Enter buyer account → `nft_transfer`; then shows before/after: owner, fund, history count	Shows the fund moving to the new owner live
Issuer page	Mint form: ID, serial (salted and hashed in browser), fund, expiry, cap, cooldown, workshops; "Demo mode" preset fills short cooldown/expiry	Raw serial and salt never sent on-chain
Workshop page	Payments received	No required action
How it works	Section 6.1 text, function table, explorer links, honest limits	For judges and AI pre-screeners

Gate caveat: in a static site the gate controls the interface; the real lock is the on-chain owner check. If any content behind the gate must stay secret (e.g. service receipts), it needs a small verifier that checks a signed message against the on-chain owner. Not in the MVP unless decided (section 14).

9. Team plan (three teams)

Team	Lead / members	Owns	Does not
Cursor	Cursor coding agents	**Only code writer.** Contract, tests, web, deploy scripts, in **one repo with LICENSE** (new public repo recommended, not mandatory per Q-003); every change via pull request	Edit the spec; hold keys; deploy with keys it does not have; submit

Team	Lead / members	Owns	Does not
Grok	Lead **Pharita**; **Haerin** = testnet accounts and deploy, together with the user; **Asa-Grok** = demo video + X post draft	Spec document (this file), schedule, hackathon rules research, submission checklist	Write code; post or submit without the user
Hermes	Lead **Jiwoo** = red-team review of spec and code; **Sohee** = README, pitch, submission text, video script; **Asa-Hermes** = newcomer tester who follows the README step by step	Review findings (as issues/PR comments), README text (delivered to Cursor as PR content), T33	Edit the spec directly; merge code

Rules

- **The spec doc is changed only by Pharita.** Others send change requests.
- **Code is changed only by the Cursor team, via pull requests.** Hermes reviews; the user (or a reviewer the user names) merges.
- **Secrets and keys are held only by the user.** No agent receives a seed phrase or private key. Haerin works with the user, who signs transactions in their own wallet/CLI.
- **The user decides and presses the final submit**, after reading the exact payload. The user also publishes the X post and makes the repo public.
- Unknowns go into section 14 as [UNVERIFIED] until someone checks them; nobody invents versions, numbers or facts.

10. Day-by-day schedule

Target submit **around 12 Nov 2026**; start **no later than about 8 Nov**. Dates below are the latest-start plan; starting earlier just adds buffer. Deadline: 14 Nov 23:59 UTC = 15 Nov 06:59 WIB.

Day	Latest date	Focus	Owner(s)	Done when
0	≤ 8 Nov	User decisions recorded; spec v3.3 approved; repo (new public repo recommended) + LICENSE; testnet accounts (admin, issuer, Alice, Budi, 2 workshops) created by the user; pin near-sdk version and fallback	User, Pharita, Haerin, Cursor	Repo exists with LICENSE and pinned `Cargo.toml`; accounts listed (names only) in README draft
1	9 Nov	Core contract: `new`, `mint` (exact storage), `pay_service` with all limits, `nft_transfer` wrapper, views; basic tests	Cursor	Builds; T01-T05, T08, T12-T18, T28-T30, T34-T35, T39 pass
2	10 Nov	`expire` + callbacks; sale-mid-payout tests; storage accounting test; Jiwoo red-team review	Cursor, Jiwoo	T06-T11, T19-T27, T36-T37 pass; storage figures measured; review issues triaged
3	11 Nov	Web pages (asset, history, gated, sell, issuer); testnet deploy; README; video recording; X post draft	Cursor, Haerin + user, Sohee, Asa-Grok	T31-T32, T38 pass; demo runs on testnet; README "do X - see Y" complete
4	12 Nov	Buffer only: fixes, newcomer test, checklist, submit	Asa-Hermes, Pharita, user	T33 done; section 12 checklist ticked; user submits

11. Demo video script (60-90 s)

Time	Screen	Voice-over (draft)
0-6 s	Bike photo + title	"This e-bike has its own warranty fund. Sell the bike, and the fund and service book move with it."
6-14	Problem text	"Warranties usually die at resale. Service records get lost."
14-26	Issuer page: mint EB-001, 10 NEAR, cap 3, demo cooldown	"The seller mints an NFT and deposits 10 NEAR once. It picks the approved workshops and the limits."

Time	Screen	Voice-over (draft)
26-38	Holder page: pay 2 NEAR to workshop A; history updates	"The owner pays a workshop straight from the fund. One call. Balance: 8."
38-46	Try 4 NEAR / another workshop / again too soon → rejected	"Over the cap, a non-approved workshop, or too soon? The contract says no. The owner can never withdraw."
46-60	"Sell this item" → Budi; history shows new holder; Alice opens holder page → locked	"Alice sells to Budi. The 8 NEAR and the history move with the bike. Alice is locked out instantly."
60-72	Demo token past expiry → `expire` → issuer receives remainder	"When the warranty ends, anyone can close it. The rest goes back to the seller."
72-85	Test run (sale mid-payout passing), explorer, repo	"Tested even for a sale in the middle of a payout. Built on NEAR testnet."

Asa-Grok records; Sohee finalizes the script. The X post must say it was built at NEAR HACKATHON and tag @NEARProtocol and #NEARHackathon (optionally @NearLegion, @NearBuilders); the user publishes it.

12. Hackathon rules and submission checklist

Source: live HACKATHON.md fetched 2026-11-04 (local copy `/workspace/hk_now.md`). The live file may change; Pharita re-reads it before submit.

Requirement	Detail	✓
Code inside the window	Q-001: code written since the 19 Oct 2026 announcement counts; window ends 14 Nov 2026. Our build days (8-12 Nov) are inside the window. **New repo: OPTIONAL** (Q-003: "No. Dedicated branch, or tags pre-hackathon and hackathon-submission, plus a README section linking the diff."). Recommended for us: a new repo created in the window	☐
Public repo	Public before **14 Nov 23:59 UTC (15 Nov 06:59 WIB)**; stays public through judging; one submission per repo	☐
LICENSE	Any license (MIT fine); file in repo	☐
README "do X - see Y"	Claude Code and Codex pre-screen READMEs (Q-017): what it is, problem, how to try it as steps, no marketing	☐
Disclosure	Libraries used and AI-generated code disclosed in README (Q-005)	☐
X post with video	Built at NEAR HACKATHON, @NEARProtocol, #NEARHackathon, video attached; published by the user	☐
Reproducible demo	Local demo is OK only with public repo + reproducible README + X video; hosted demo is a plus (keep up to 18 Nov, ideally 25 Nov)	☐
Tracks	`nfts`, optionally `realworld` / `open` (ids verified against live HACKATHON.md on 2026-11-04)	☐
Payout account	Mainnet NEAR account created by the user; never invented	☐
Two-project rule	Max 2 different projects per person; each README names the other one if any	☐
One submission, no edits	Submit only when repo is public and post is live; the user confirms the exact JSON payload; same requestId on retry	☐
Human-decided fields	Project name, lead name, email, team size, tracks, payout account, repo link, post link, description (20-2000 chars), consent	☐

12.1 Submission API contract (verbatim from live HACKATHON.md, 2026-11-04)

`POST https://nearhackathon.com/api/applications` with `Content-Type: application/json`. Body up to 12000 bytes. Send exactly these fields:

Field	Type	Rule	For Phylaxtag (ours, not verbatim)
requestId	string	UUID, generated once per submission and reused on retries	Generated once by Pharita at submit time; reused on retries
projectName	string	2-80 characters	"Phylaxtag" (decided name; user confirms in the payload)
leadName	string	2-80 characters	User decides
email	string	valid email, max 160 characters, at most 2 submissions per email	User decides; not committed anywhere
size	string	one of `1`, `2 - 4`, `4 - 6`, `6 - 8`, `8+`, exactly as written	"1" unless the user says otherwise

Field	Type	Rule	For Phylaxtag (ours, not verbatim)
tracks	array of strings	one or more of `defi`, `thesis`, `privacy`, `business`, `swarms`, `security`, `agents`, `realworld`, `games`, `nfts`, `memecoins`, `social`, `open`, each listed once	["nfts"], optionally "realworld" / "open"
nearAddress	string	2-64 characters, lowercase, matching `^(([a-z\d]+[-_])*[a-z\d]+\.)*([a-z\d]+[-_])*[a-z\d]+$`	Mainnet account created by the user in their own wallet; agents never handle keys
projectUrl	string	http(s) URL of the public repository, max 300 characters, unique: each repository is submitted once	The public repo `phylaxtag` (URL set when created)
demoUrl	string	http(s) URL of the public demo post, max 300 characters	The X post with the video
idea	string	20-2000 characters	Section 13 text
consent	boolean	`true`, only after the human agreed to the contact notice	true only after the user agrees to the notice below

Do not add other fields. In particular `website` is a spam trap: any non-empty value rejects the submission.

Status	Meaning	What to do
201	Submission saved	Done. Tell the human.
400	A field failed validation	Fix the fields listed in `fields` of the response and resend with the same requestId.
403	Submissions are not open, or the request looked cross-site	Tell the human. Do not retry.
409	Repository already submitted, or this email already has 2 submissions	The project was already submitted, or the human reached the limit. Ask the human; do not change the link or the email to get around it.
413	Body too large	Shorten the description.
503	Storage temporarily unavailable	Wait a minute and resend with the same requestId.

Consent notice, to be read to the user verbatim:

"I agree that the organizers may use these details to review our submission and contact us about this hackathon."

Other verbatim rules:

- Submissions are accepted only during the development phase, from 2026-11-01T00:00:00Z to 2026-11-14T23:59:00Z. Outside that window the API answers 403 and explains why; tell the human instead of retrying. A submission cannot be edited, so send it when the repository is public and the demo post is up.
- Generate `requestId` once, with `uuidgen | tr A-Z a-z` or `node -e 'console.log(crypto.randomUUID())'`. Keep it: a retry after a network error or a 503 must reuse the same value, and the server then treats it as the same submission. Do not commit the payload; it contains personal data.
- Send the submission. Print the full JSON payload first and wait for a yes. A second submission of the same repository is rejected, so there is one attempt per project.
- The repository may stay private while the team builds, but it must be public by 2026-11-14T23:59:00Z. Judges cannot open a private one. Claude Code and Codex screen every project before the human jury decides (Q-017), so write the README for a machine reader as well as a human one: what the product is, the problem it solves, and how to try it as "do X - see Y" steps a judge can follow. No marketing.
- A 201 response means the submission is saved: tell the human. If they prefer the form, the same fields are at https://nearhackathon.com/#apply.

Notes (ours). Track ids verified against live HACKATHON.md on 2026-11-04; if the API returns 400 listing fields, fix and resend with same requestId. The reviewer report that validation "only accepts `open`" was **not** confirmed: the live file lists `nfts` as a valid id. Never commit the payload (personal data). Submit once, only after the user confirmed the exact payload; the submission cannot be edited. Repo must be public by 2026-11-14T23:59Z.

12.2 README outline

1. What it is (one paragraph + tagline), including: "Phylax (φύλαξ) is Greek for 'guardian': the warranty is a guardian that lives on the item and transfers with it."
2. Try it: "Open <link> - see EB-001 with 8 NEAR left and 1 service record"
3. Run tests: "Run `cargo test` in `contract/` - see 35 tests pass"; "Run the web e2e tests in `web/` - see 3 tests pass" (39 total with the manual newcomer run T33; exact web command set by Cursor)
4. Deploy: "Run `./scripts/deploy.sh <your-testnet-account>` - see the contract id"
5. How control passes on transfer (section 6.1) and transfer threat model (6.2)
6. Functions and limits; storage figures (measured)
7. Honest limits
8. Libraries used, AI-generated code disclosure, other project (if any)
9. License

13. Submission text (English)

Draft by Sohee, owned by the user. Recounted programmatically for v3 (Python `len()` on the exact string below): **972 characters** including the two blank-line paragraph breaks (4 newline characters), 972 UTF-8 bytes; **970** if paragraphs are separated by single newlines (this explains the reviewer count of 966). Target ≤ 1100; the API allows 20-2000. Count again on the exact `idea` string before submitting.

> Phylaxtag: the product owns its warranty.
>
> Phylaxtag turns a physical item (MVP: one e-bike) into a NEP-171 NFT on NEAR testnet that carries its own warranty fund and service history. The issuer mints the NFT with a one-time deposit and sets approved workshops, an expiry, a per-claim cap and a cooldown. The owner pays an approved workshop straight from the fund with one call; the contract enforces every limit, and the owner can never withdraw the fund. The fund is stored per token, not per owner, so when the NFT is sold the remaining fund and full history move to the buyer and the seller loses access at once. After expiry, anyone can return the remainder to the issuer. A holder-only page and a per-NFT history (funded, paid out, who held it) make this visible. Tests cover a sale in the middle of a payout, failed payouts and each seller trick in our threat model.
>
> Limits: testnet prototype. The NFT does not prove physical authenticity and is not a legal title.

14. Open items and unverified claims

14.1 Decided

#	Item	Decision
D1	`top_up`	Removed (user, 4 Nov 2026)
D2	Claim limits	Automatic, contract-only; no co-sign (user, 4 Nov 2026)
D3	Zero cooldown / in-flight guard	`cooldown_ns > 0` required; no pending flag (5.2)
D4	Expire on empty fund; second expire	Always marks Expired; second call is a no-op returning 0 (5.1)
D5	Holder log full	Drop-oldest ring of 50 + total counter; transfer never fails (5.3)
D6	Per-token balance vs sub-accounts	Per-token balance in one contract (justified in 5.6); disclose in README

14.2 Still open

#	Item	Status / owner
O1	Standing OK for Cursor to push PR branches (user rule: no push without the user's command)	**Open, user.** Making the repo public and merging stay with the user

#	Item	Status / owner
O2	Holder-only page: on-chain owner check in UI vs signed-message checker for secret content	**Open, user.** Proposed: UI gate + on-chain checks
O3	Holder list on-chain (capped ring) vs indexer	**Open, user.** Pharita recommends on-chain (as specified)
O4	Upgrade risk: the deployer can change contract code	**Open, user.** Proposed: disclose in README; no key locking on testnet
O5	Display name	**Decided (user, 4 Nov 2026): Phylaxtag.** Earlier candidates: CareTag (working name), Covered, WarrantyTag, ServiceBook; CareTag was dropped because of existing trademark use of "Caretag" in medical RFID. X @phylaxtag and phylaxtag.com still to be registered **[UNVERIFIED]**
O6	Service history full (50) blocks further claims; remainder returns at expiry	Open, Pharita. Kept for MVP (audit trail); alternative: higher cap
O7	Minimum cooldown for real tokens (beyond > 0)	Open, Pharita with issuer; demo uses a short value
O8	Team size and lead name for the form	User decides; default size "1"
O9	`remove_issuer` / `set_admin` (key leak / admin recovery)	Post-hackathon item; accepted for MVP (6.3)

14.3 Claims and facts

#	Claim	Status
F1	Similar projects	Reported by reviewer Jiwoo; not independently verified by Pharita: only EVM/Tezos prior art (aynp/nft-warranty, 2022, Goerli; tezos-warranty) and a 2024 SSRN paper about NFT warranties on NEAR; no working NEAR implementation found. Keep the wording "to our knowledge, a working NFT-warranty implementation on NEAR"; never "first". **[UNVERIFIED]**
F2	Code window	Q-001 in live HACKATHON.md: code since the 19 Oct 2026 announcement counts; work on 8-12 Nov is in the window (verified in the file)
F3	Historic judging criteria (technical implementation, design, impact, originality, sustainability)	Reviewer-reported; not in HACKATHON.md **[UNVERIFIED]**. Used only as pitch ordering
F4	"88 submissions" figure	**Do not use** anywhere **[UNVERIFIED]**
F5	near-sdk / near-contract-standards versions and NEP-171 override hooks	To be verified on day 1; pin + fallback route (section 5) **[UNVERIFIED]**
F6	Pyth stopped supporting NEAR (per Jiwoo)	**[UNVERIFIED]**. Not needed: the MVP uses no price oracle
F7	Storage cost per mint / record / holder slot	**[TO BE MEASURED]** by T26, T37
F8	Live validation "only accepts `open`" (reviewer)	Not confirmed: live HACKATHON.md lists `nfts`; handle a 400 per 12.1

Document safety: this file contains no keys, seed phrases or secrets. Do not add any to the repo or to agent prompts.