

# 일일업무보고 20240822

리눅스 서버OS설치


## Server OS 설치




### 사이트 들어가서 다운로드



③ [CD/DVD] (SATA)를 선택하고, [Use ISO image file: ]에서 앞서 파일 공유 해 주었던 ubuntu-20.04-live-server-amd64.iso 파일 위치를 선택하고 OK 클릭합니다.




Vmware들어가서 new Vmware-workspace/serverB에 다운로드받은파일 옮기기 ④ ▶ Player virtual machine 메뉴를 클릭하고 설치를 시작합니다.



- ISO 설치파일을 불러들이면서 설치를 진행하는 것을 확인할 수 있습니다.
- 중간 중간 오류 메시지가 뜨더라도 긴장하지 말고 그냥 무시해도 됩니다.
- 단지 하드웨어 적인 체크를 진행하고, 이에 따른 오류메세지가 발생할 수
   도 있다는 내용으로 확인하시면 됩니다.
- 다음 아래와 같이 설치 화면을 확인할 수 있습니다.


1. 언어 선택 화면 : 기본값 English 영어가 선택 된 상태에서 Enter를 선택합니다.




- Server(B)를 설치하는 과정은 오로지 텍스트모드 이기에, 방향키를 이용 해서 메뉴를 이동하며 선택합니다.
- Server(B)에서는 한글사용이 없기에 영문으로 설치합니다.
- 만일 VMware와 호스트PC와의 이동을 위한 마우스 포인터가 잘 보이지 않을 경우 키보드에 ctrl키 + alt키를 동시에 눌러서 화면간에 이동을 진행하시면 됩니다.

2. Install update available 화면이 뜨면

[Continue without updating] 메뉴가 선택된 상태에서 Enter를 선택합니다.



3. Keyboard configuration 화면이 뜨면 영어 키보 드가 선택된 기본설정이기에 그냥 ~ [ Done ] Enter를 선택합니다.




4. Network connection 화면이 뜨면 자동으로 IP 주소가 할당된 것을 확인 할 수 있습니다.


ens32 eth -

DHCPv4 192.168.111.129/24


[ Done ] Enter를 선택합니다.




5. Configure proxy 화면이 뜨면 기본 설정에서 Done Enter를 선택합니다.




6. Configure Ubuntu archive mirror 주소 화면이 뜨면 기본 설정에서 [ Done ] Enter를 선택합니다.



7. Guided storage configation 화면이 뜨면 기본 설정에서 키보드에 <u>Tab키를 4회정도</u> 눌러 서 [ Done ] 부분으로 이동하면 Enter를 선택합니 다.




8. Storage configation 화면이 뜨면 기본 설정 Done ] 부분에서 Enter를 선택합니다.



9. Storage configation 화면 가운데에 다음과 같이

Confirm destructive action 화면이 뜨면 Tab키 1 회정도 눌러서 [Continue] 부분에서 Enter를 선택합니다.



10. Profile Setup 화면이 뜨면 아래 내용을 각 칸을 채우고 칸을 이동할때는 Tab키를 눌러서 이동 합니다. 다 채워지면 [ Done ] 부분에서 Enter를 선택합니다.

- 다음 아래 내용으로 각 칸을 채워 줍니다.


Youer name: ubuntu

Your server's name : server-b

Pick a username : ubuntu

Choose a password: ubuntu1234\_

Confirm your password: ubuntu1234



Your name : guru


Pick a username : guru

Choose a password : guru

Confirm your password: guru


설정

11. SSH Setup 화면이 뜨면 Tab키를 눌러서 Done ] 부분으로 이동 후 Enter를 선택합니다.




12. Featured Server Snaps 화면이 뜨면 Tab키를 눌러서 [ Done ] 부분으로 이동 후 Enter를 선택합니다.


이 메뉴에서는 추가하고자 하는 프로그램을 선택하는 부분이나 선택없이 기본으로 진행하도록 합니다.



13. Installing system 화면이 뜨면서 설치진행 모습을 확인할 수 있습니다.



- 설치가 완료 되면, 맨 아래에 [Reboot] 라는 선택 버튼이 활성화 됩니다.




- 컴퓨터가 재부팅 후 "Please remove the installtion medium, then press ENTER" 메시지가 나오면 Enter키를 누룹니다.



- 설치DVD를 제거하라는 메시지인데, VMware가 자동으로 제거합니다.

#### 04-2. Server(B) 우분투 리눅스 설치 종료 및 로그인 하기

① Server(B)를 설치하고 재부팅하고난 다음에는 몇분동안 시스템에 대한 점검을 하고, 최종적인 로그인 화면을 띄워주기 전에 [ OK ] 라는 메시지가 나올때까지 기다려 줍니다.



②server-b login: 프롬프트가 뜨면 이제부터 설치시 작성했던 암호를 입력하고 로그인 합니다.

```
48.69 seconds
[ OK ] Finished Execute cloud user/final scripts.
[ OK ] Reached target Cloud-init target.
server-b login:
server-b login:
server-b login:
```

server-b login : ubuntu [아이디 입력]

- 08 -

server-b login : guru

#### Password: ubuntu1234 [비번 일러

```
To run a command as administrator (user "root"), use "sudo ⟨command⟩".
See "man sudo_root" for details.
ubuntu@server–b:~$
```

- 이제 로그인이 되었으면, 프롬프트가 server-b:~\$ 로 보일겁니다.
- 특히 앞서 로그인을 위한 아이디 까지는 눈으로 보였지만, 패스워드에서는 보이지 않는 부분은 텍스트모드에서의 보안성으로 인하여 보이지 않는 겁니다.
- 텍스트 모드로 부팅이 된 모습이 익숙하지 않겠지만 앞에서 설치해 보았던 우분 투 20.04LTD의 초기 소프트웨어만 설치되도록 설정해 보겠습니다.

- 99 -

password: guru

```
Setting up libwrap0:amd64 (7.6.g-30) ...
Setting up nourses-term (6.2-Oubuntu2.1) ...
Setting up openssh-server (1:8.2p1-4ubuntu0.11) ...
Creating config file /etc/ssh/sshd_config with new version
Created symlink /etc/systemd/system/sshd.service → /lib/systemd/system/ssh.service.
Created symlink /etc/systemd/system/multi-user.target.wants/ssh.service → /lib/systemd/system/ssh.se
rvice.
rescue-ssh.target is a disabled or a static unit, not starting it.
Processing triggers for ufw (0.36–6ubuntu1) ...
Processing triggers for systemd (245.4-4ubuntu3.20) ...
Processing triggers for man-db (2.9.1–1) ...
Processing triggers for libc-bin (2.31-Oubuntu9.16) ...
root@server-b:~# systemctl enable ssh
Synchronizing state of ssh.service with SysV service script with /lib/systemd/systemd-sysv-install.
Executing: /lib/systemd/systemd-sysv-install enable ssh
root@server-b:~# systemctl status ssh
• ssh.service – OpenBSD Secure Shell server
     Loaded: loaded (/lib/systemd/system/ssh.service; enabled; vendor preset: enabled)
    Active: active (running) since Thu 2024-08-22 06:41:29 UTC; 14s ago
      Docs: man:sshd(8)
            man:sshd_config(5)
  Main PID: 3218 (sshd)
      Tasks: 1 (limit: 4556)
     Memory: 1.3M
     CGroup: /system.slice/ssh.service
             └─3218 sshd: /usr/sbin/sshd -D [listener] 0 of 10–100 startups
Aug 22 06:41:29 server-b systemd[1]: Starting OpenBSD Secure Shell server...
Aug 22 06:41:29 server-b sshd[3218]: Server listening on 0.0.0.0 port 22.
Aug 22 06:41:29 server-b sshd[3218]: Server listening on :: port 22.
Aug 22 06:41:29 server-b systemd[1]: Started OpenBSD Secure Shell server.
root@server-b:~# cd /etc/netplan
root@server-b:/etc/netplan# ls -l
total 4
-rw-r--r-- 1 root root 116 Aug 22 06:12 00-installer-config.yaml
root@server–b:/etc/netplan# _
```

cd /etc/netplan 입력 ls –i nano 00-installer-config.yaml 입력

```
# This is the network config written by 'subiquity'
network:
  ethernets:
  version: 2
"00-installer-config.yaml" 6L, 116C
                                                                                1,1
```

들어가면 초기화면이

ens33:

dhcp4: true 로 되어있다 이 것은 ip를 자동할당으로 받겠다는 의미

```
# This is the network config written by 'subiquity'
network:
 ethernets:
    ens33:
      dhcp4: no
      addresses: [192.168.111.200/24]
      gateway4: 192.168.111.2
      nameservers:
          addresses: [192.168.111.2]
 version: 2
: wq!
```

```
화면처럼 설정하기
중요!
nameservers:
addresses:
처럼 꼭 names 밑 빈칸에 addresses
입력하기!
```

입력 끝나면 :wq! 입력

```
root@server-b:/etc/netplan# netplan aaply
usage: /usr/sbin/netplan [-h] [--debug] ...
/usr/sbin/netplan : error: argument : invalid choice: 'aaply' (choose from 'help', 'apply', 'generat
e', 'get', 'info', 'ip', 'set', 'rebind', 'try')
root@server-b:/etc/netplan# netplan aaplu
usage: /usr/sbin/netplan [-h] [--debug] ...
/usr/sbin/netplan : error: argument : invalid choice: 'aaply' (choose from 'help', 'apply', 'generat
e', 'get', 'info', 'ip', 'set', 'rebind', 'try')
root@server-b:/etc/netplan# ip a
1: lo: <LOOPBACK,UP,LOWER_UP> mtu 65536 qdisc noqueue state UNKNOWN group default glen 1000
    link/loopback 00:00:00:00:00:00 brd 00:0<u>0:00:00:00:00</u>
    inet 127.0.0.1/8 scope host lo
      valid_lft forever preferred_lft forever
    inet6 ::1/128 scope host
       valid_lft forever preferred_lft forever
2: ens33: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc fq_codel state UP group default glen 1000
    link/ether 00:0c:29:5a:71:ee brd ff:ff:ff:ff:ff:ff
    inet 192.168.111.130/24 brd 192.168.111.255 scope global dynamic ens33
       valid_lft 1295sec preferred_lft 1295sec
    inet6 fe80::20c:29ff:fe5a:71ee/64 scope link
       valid_lft forever preferred_lft forever
root@server-b:/etc/netplan# netplan apply
root@server-b:/etc/netplan# ip a
1: lo: <LOOPBACK,UP,LOWER_UP> mtu 65536 qdisc noqueue state UNKNOWN group default glen 1000
    link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00
    inet 127.0.0.1/8 scope host lo
       valid_lft forever preferred_lft forever
    inet6 ::1/128 scope host
       valid_lft_forever_preferred_lft_forever
2: ens33: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc fq_codel state UP group default qlen 1000
    link/ether 00:0c:29:5a:71:ee brd ff:ff:ff:ff:ff
    inet 192.168.111.200/24 brd 192.168.111.255 scope global ens33
       valid_lft forever preferred_lft forever
    inet6 fe80::20c:29ff:fe5a:71ee/64 scope link
      valid_lft forever preferred_lft forever
root@server-b:/etc/netplan# _
```

나와서 netplan apply 입력후 ip a 로 해서 ip주소가 바뀌었는지 확인

```
dhcp4: no
      addresses: [192.168.111.200/24]
      gateway4: 192.168.111.2
      nameservers:
          addresses: [192.168.111.2]
  version: 2
root@server-b:/etc/netplan#
root@server-b:/etc/netplan#
root@server-b:/etc/netplan#
root@server-b:/etc/netplan# ping 8.8.8.8
PING 8.8.8.8 (8.8.8.8) 56(84) bytes of data.
64 bytes from 8.8.8.8: icmp_seq=1 ttl=128 time=61.5 ms
64 bytes from 8.8.8.8: icmp_seq=2 ttl=128 time=61.3 ms
64 bytes from 8.8.8.8: icmp_seq=3 ttl=128 time=60.9 ms
64 bytes from 8.8.8.8: icmp_seq=4 ttl=128 time=61.1 ms
64 bytes from 8.8.8.8: icmp_seq=5 ttl=128 time=60.4 ms
64 bytes from 8.8.8.8: icmp_seq=6 ttl=128 time=82.0 ms
64 bytes from 8.8.8.8: icmp_seq=7 ttl=128 time=60.3 ms
64 bytes from 8.8.8.8: icmp_seq=8 ttl=128 time=61.1 ms
64 bytes from 8.8.8.8: icmp_seq=9 ttl=128 time=60.5 ms
64 bytes from 8.8.8.8: icmp_seg=10 ttl=128 time=60.8 ms
^c
--- 8.8.8.8 ping statistics ---
10 packets transmitted, 10 received, 0% packet loss, time 9015ms
rtt min/avg/max/mdev = 60.317/62.979/82.018/6.356 ms
root@server-b:/etc/netplan# ping -c 5 8.8.8.8
PING 8.8.8.8 (8.8.8.8) 56(84) bytes of data.
64 bytes from 8.8.8.8: icmp_seq=1 ttl=128 time=84.0 ms
64 bytes from 8.8.8.8: icmp_seq=2 ttl=128 time=60.4 ms
64 bytes from 8.8.8.8: icmp_seq=3 ttl=128 time=61.0 ms
64 bytes from 8.8.8.8: icmp_seg=4 ttl=128 time=61.1 ms
64 bytes from 8.8.8.8: icmp_seg=5 ttl=128 time=61.0 ms
--- 8.8.8.8 ping statistics ---
5 packets transmitted, 5 received, 0% packet loss, time 4006ms
rtt min/avg/max/mdev = 60.365/65.474/83.957/9.245 ms
root@server-b:/etc/netplan#
```

### ping 8.8.8.8의미는 icmp가 응답한다는 의미이다

```
COMMEDIED
                                                      20127
                                                               /run/dbus/
 unix 3
                           STREAM
                                       CONNECTED
                                                      36140
 root@server-b:/etc/netplan# apt install -y net-tools_
       unix 3
                                 STREAM
                                             CONNECTED
                                                            35700
                                                                     /run/dbus/sys
      unix 3
                                 STREAM
                                             CONNECTED
                                                            36137
      unix 3
                                 STREAM
                                             CONNECTED
                                                            36140
                                                                     /run/dbus/sys
      root@server-b:/etc/netplan# netstat -rn
                                        serverB
win-xp-user2
                                      Power on this virtual machine
      Ubuntu
                                      Edit virtual machine settings
       2008-s1
       Windows Server 2003 Enterprise Edit
       CentOS 7 64-bit
                                    ▼ Devices-
    Windows 10 x64
                                     Memory
                                                           1 GB
     win-xp-user2
                                                           2
                                     Processors
     SamVM15_Cent771908Class2

⊢ Hard Disk (SCSI)

                                                           50 GB
    Class1-Week
                                                           Using file ubuntu...
    EVE-COMM-VM
                                     O CD/DVD (SATA)
    SamVM15 Cent782003Class1
                                     □ Network Adapter
                                                           NAT

□ NYC-CL1

← USB Controller

                                                           Present

    □ NYC-Core

                                     Auto detect

□ NYC-DC1

                                     Display
                                                           Auto detect

□ NYC-SVR1

☐ NYC-SVR2

                                    ▼ Description
    ₩ NYC-CL1
    NYC-Core
    NYC-DC1
    NYC-SVR1
    NYC-SVR2
    Window_tescher
    mindow7 st1
    Client
    server |
    master master
    serverB
```

apt install -y net -tools 설치

netstat -rn 입력 halt -p 입력하면 화면이 종료된다.