Agenda :

1. Introduction
2. Module Description
3. Count Of Factors
4. Check if a number is prime
5. Sum of 1st N natural numbers.
6. No. of iterations
7. Comparing Algorithms.

Introduction:

Name : Harsha
From : Udupi
→ Maersk
→ SJCE Mysore

1. **PSP (Problem Solving Percentage) - Solved Assignment Problems / Total Open Assignment Problems**

- There are two types of section - Assignment and Additional. Assignment section consists of implementation of the problems done in class. PSP is calculated based on only Assignment Problems.
- Additional Problems are slight modifications of assignment problem, they are not part of PSP but once you're done with assignment, we highly recommend to complete additional problems as well.
- Try to keep PSP least 85% no matter what. It shall really help you to stay focused and we have seen in the past that people with >= 85%, do well in contests and mock Interviews

2. **Attendance**

- Try to maintain at-least 75% attendance either through live classes or by watching recording, though I will recommend you to come to classes regularly because otherwise it may create backlogs.
- So, I expect all of you to attend live classes and if for any reason you are unable to, then please send me a message stating the reason.

Approach:

1 → Watch recorded sessions at higher speeds
2 → Assignments
3 → Additional Problems.

	Mon	Tue	Wed	Thu	Fri	Sat	Sun
7-9.30 AM	✓	✓ P	✓	✓ P	✓	✓ P	R

Module Description

Time Complexity
Arrays
Prefix Sum
Carry Forward
Subarrays.
Matrices
Sorting Basics.
Hashing Basics.
Strings Basics.
Bit Manipulation Basics.
Interview Problems.
Contest

Objective : 1. Comfortable with writing programs.

Contests :

Points To Remember :

1
2.
3.

Question:

Given N, return the count of factors of N.

$N \geq 0$

$[1, N]$

What is a factor?

If x is a factor of $N \Rightarrow N \% x == 0$

Factors of 36 → 1 2 3 4 6 9 12 18 36 → 9

Factors of 24 → 1 2 3 4 6 8 12 24

Factors of 100 → 1 2 4 5 10 20 25 50 100 → 9

Approach 1:

```
int countFactors(int N)
{
    int count = 0;
    for (i → 1 to N)
    {
        if (N % i == 0)
        {
            count++;
        }
    }
    return count;
}
```

HW → Dry run this for 36, 16

N = 8

i	count(0)
~~1~~	~~1~~
~~2~~	~~2~~
~~3~~	~~2~~
~~4~~	~~3~~
~~5~~	~~3~~
~~6~~	~~4~~
~~7~~	~~4~~
~~8~~	4

Observations :

No. of iterations that a single core CPU can execute in one second $\simeq 10^8$

N	$\sqrt{N}$	Iterations	Execution Time
8	2	8	0.0000 ...
100	10	100	0.000001 s
10^9	10^4	10^9	10 secs. 0.0001
10^{18}	10^9	10^{18}	10^{10} secs. 10 seconds

$\frac{1}{10^8} \times 8$

$= 8/10^8 \simeq$

$1000000 = 10^6$

$1000000000 = 10^9$

$\frac{100}{10^8} = \frac{1}{10^6}$

$\frac{10^9}{10^8} = 10$

$\frac{10^{18}}{10^8} = 10^{10}$ secon

$10^{9/2} \simeq 10^4$

317 years. → 10 sec

$\frac{10^4}{10^8} = 10^{-4} = 0.0001$



Optimisation:

```
int countFactors(int N)
{
    int count = 0;
    for(i=1; i*i<=N; i++)
    {
        if(N%i==0)
        {
            if(i==N/i) {count++;}
            else {count = count+2;}
        }
    }
    return count;
}
```

`i=1; i*i<=N; i++`

`i <= √N`

`i*i <= N`

36	
1	36 → 2
2	18 → 4
3	12 → 6
4	9 → 8
6	6 → 10
9	4
12	3
18	2
36	1

63	
1	63
3	21
7	9
9	7
21	3
63	1

$\sqrt{N} \rightarrow 7$

24	
1	24
2	12
3	8
4	6
6	4
8	3
12	2
24	1

$\sqrt{24} = 4$

Break : till 8:53 AM

Question:

Given a no. N, check if N is prime or not.

Definition: Any number with exactly 2 factors.

31 → 1 and 31

7 → 1 and 7

3 → 1 and 3

HW

N → 1 to N

N = 100.

$S = 1 + 2 + 3 + 4 + 5 + \ldots\ldots + 100$

$S = 100 + 99 + 98 + 97 + 96 + \ldots\ldots + 1$

$$2S = \underbrace{(100+1) + (99+2) + (98+3) + (97+4) + \ldots\ldots + (1+100)}_{N}$$

$$= (N+1) * N$$

$$2S = N(N+1)$$

$$S = \frac{N(N+1)}{2}$$

$$S_N = \frac{N(N+1)}{2}$$

$$\frac{100(101)}{2} = 50 \times 101 = 5050$$

$[1, N] \rightarrow (N - 1 + 1) \rightarrow N$ iterations.

$[0, 100] \rightarrow (100 - 0 + 1) \rightarrow 101$

Basic Math:

1. $[a, b]$ → $b - a + 1$

2. (a, b) → $b - a - 1$

$[a, b]$ → Both a & b

$[a, b)$ → a but not b

(a, b) → excluding a & b

$[3, 10]$ → 3, 4, 5, 6, 7, 8, 9, 10

↳ $10 - 3 + 1$

Iterations:

$[1, N]$ → $(N - 1 + 1)$ → N iterations.

$[0, 100]$ → $(100 - 0 + 1)$ → 101

$i \rightarrow (1 \rightarrow N)$ → N

$j \rightarrow (1 \rightarrow M)$ → M

N + M.

Progressions :

$1 \rightarrow 2 \rightarrow 4 \rightarrow 8 \rightarrow 16 \rightarrow 32$

$4/2 = 2$

$16/8 = 2$

$CR = r = 2$

$3 \quad 9 \quad 27 \quad 81 \quad 243$

a

$r = 3$

a ↑ n terms

$3 + 9 + 27 + 81 + 243 \cdots$

r

$$S_n = \frac{a(r^n - 1)}{(r-1)}$$

$a = 5$

$r = 3$

$3 + 9 + 27 + 81 = 120$

$$S_4 = \frac{3(3^4 - 1)}{2} = \frac{3 \times (80)}{2}$$

$$= 3 \times 40 = 120.$$

Comparing Algorithms:

Virendra

32gb ram M2 chip 5

50°C

18°C 3.6s

Prashant

10 XP

3.5s 32gb ram M2 chip

18°C

Moral: Use # of iterations → Time Complexity.

NOT Execution Time

Next Class Content:

- Big O
- Logarithm
- TLE & Importance of Constraints