

IATF 16949:2016 — Internal Reference Excerpt

Selected clauses (§8.5.1.1, §10.2) prepared for internal use. This is a paraphrased reference; the controlling document is the IATF 16949:2016 standard published by the International Automotive Task Force.

```
--- METADATA ---
document_id: QMS-IATF-EXCERPT-001
title: IATF 16949:2016 – Internal Reference Excerpt
domain: quality
source_system: QMS
revision: Rev A
effective_date: 2024-02-01
owner: S. Okafor, Quality Manager – Cleveland
part_numbers: []
operation_numbers: []
machine_ids: []
controller_models: []
fault_codes: []
materials: []
standards: [IATF-16949-2016]
supplier_ids: []
jurisdictions: []
classification: internal
---
```

Clause 8.5.1.1 — Control plan (paraphrased)

The organization shall develop control plans at the system, subsystem, component, and/or material level (as appropriate) for the manufacturing site, including any bulk materials and parts produced.

Review frequency. The control plan shall be reviewed and updated when any change occurs affecting product, manufacturing process, measurement, logistics, supply sources, production volume, or risk analysis (FMEA). At minimum, the control plan shall be reviewed on an annual cadence.

Approval authority. The customer may require review and approval of control plans. Where customer-specific requirements (CSRs) apply (e.g. QMS-CSR-VTX-001 for Vortex Motors), the customer approval authority supersedes the internal default. The internal default approval authority is the Quality Manager and the Process Engineering Manager jointly; major process changes additionally require Plant Manager sign-off.

Content. The control plan shall list the controls used for the manufacturing process control, including but not limited to special characteristics, measurement methods, sample size and frequency, and reaction plans.

Clause 10.2 — Nonconformity and corrective action (paraphrased)

§10.2.1 — When a nonconformity occurs (including from a customer complaint), the organization shall react to it, evaluate the need for action to eliminate the cause, implement any action needed, and review the effectiveness of any corrective action taken.

Timing (internal interpretation per Contoso quality manual):

Step	Required completion
Initial containment and notification	Within 1 hour of detection
Engineering disposition / root cause	Within 4 hours of detection
Formal corrective action plan	Within 10 working days
Effectiveness verification	Within 90 days of corrective action close-out
Customer notification (if customer impact)	Within 24 hours

§10.2.3 — Problem-solving methodology. The organization shall use a documented problem-solving approach (e.g. 8D, A3) and shall retain records demonstrating that root cause has been identified and that the corrective action prevents recurrence.

Clause 7.2.3 — Auditor competency (summary)

Internal auditors shall be competent in process auditing, core tools (FMEA, SPC, MSA, Control Plans, PPAP), and the customer-specific requirements for the products audited. Auditor competency shall be reviewed annually.

Document control / sign-off

Role	Name	Signature	Date
Document Owner	S. Okafor, Quality Manager — Cleveland	(on file)	2024-02-01
Approver	S. Okafor, Quality Manager — Cleveland	(on file)	2024-02-01