

Tooling Sheet — Part 45621-B OP30

Aligned with work instruction [PLM-WI-45621B-OP30-RevC](#) . Carbide stack for Inconel 718 finish milling on DMU-14.

```
--- METADATA ---
document_id: PLM-TOOL-45621B-OP30
title: Tooling Sheet — Part 45621-B OP30
domain: process_specs
source_system: PLM
revision: Rev B
effective_date: 2025-03-10
owner: M. Tanaka, Process Engineering — Wichita
part_numbers: [45621-B]
operation_numbers: [OP30]
machine_ids: [DMU-14, DMU-22]
controller_models: []
fault_codes: []
materials: [MAT-INC718]
standards: []
supplier_ids: []
jurisdictions: []
classification: internal
---
```

Tool list

Pocket	Tool ID	Description	Holder	Set length (mm)
T05	EM-10-ALTiN-4F	Ø 10 mm 4-flute carbide end mill, ALTiN	HSK-A63 shrink-fit	110.0
T06	EM-08-ALTiN-4F	Ø 8 mm 4-flute carbide end mill, ALTiN	HSK-A63 shrink-fit	95.0
T07	BN-06-ALTiN-6F	Ø 6 mm 6-flute ball-nose carbide, ALTiN	HSK-A63 shrink-fit	85.0
T20	SPOT-08-90	Ø 8 mm 90° spot drill (setup probe origin)	HSK-A63	80.0

Tool-life rules and wear limits for these tools: see [PLM-PS-INC718-0042](#) §4. Cutting parameters: see [PLM-WI-45621B-OP30-RevC](#) §2.

Document control / sign-off

Role	Name	Signature	Date
------	------	-----------	------

Document Owner	M. Tanaka, Process Engineering — Wichita	(on file)	2025-03-10
Approver	M. Tanaka, Process Engineering — Wichita	(on file)	2025-03-10