

# Safety Data Sheet — EcoCut 7700

Semi-synthetic cutting fluid · manufacturer LubeMaster Industrial ( SUP-LUBE-MASTER ) · SDS format per GHS Rev 9.

```
--- METADATA ---
document_id: ERP-SDS-ECOCUT7700
title: Safety Data Sheet — EcoCut 7700 (Semi-Synthetic Cutting Fluid)
domain: materials
source_system: ERP
revision: Rev 4
effective_date: 2024-08-30
owner: K. Nakamura, EH&S Liaison / LubeMaster (manufacturer)
part_numbers: []
operation_numbers: []
machine_ids: [DMU-14, DMU-22, NLX-08, NLX-09, HMC-30, BSAW-03]
controller_models: []
fault_codes: []
materials: [MAT-CF-ECO]
standards: [GHS-Rev9]
supplier_ids: [SUP-LUBE-MASTER]
jurisdictions: [US, EU]
classification: internal
---
```

## Section 1 — Identification

Product: EcoCut 7700 semi-synthetic cutting fluid concentrate. Recommended use: metalworking fluid for ferrous and nickel alloys, diluted 8–10% in water. Manufacturer: LubeMaster Industrial, 1212 Refinery Rd, Houston, TX. Emergency telephone: +1-800-555-LUBE.

## Section 2 — Hazard identification (GHS)

### GHS classification (concentrate):

- Skin irritation, Category 2 (H315: Causes skin irritation)
- Eye irritation, Category 2A (H319: Causes serious eye irritation)
- Specific Target Organ Toxicity (STOT) — single exposure, Category 3 (H335: May cause respiratory irritation)

**Signal word:** Warning. **Pictograms:** GHS07 (exclamation mark).

**In-use dilution (8–10%) hazard:** reduced classification — skin irritation Category 2 retained; eye irritation reduced to Category 2B.

## Section 3 — Composition

| Component                          | CAS           | Concentration |
|------------------------------------|---------------|---------------|
| Mineral oil, severely hydrotreated | 64742-65-0    | 30–40%        |
| Alkanolamine (corrosion inhibitor) | 102-71-6      | 5–10%         |
| Non-ionic surfactant blend         | (proprietary) | 10–15%        |
| Biocide (isothiazolinone)          | 26172-55-4    | < 0.1%        |
| Water                              | 7732-18-5     | balance       |

## Section 4 — First aid

- **Skin:** wash with soap and water; remove contaminated clothing.
- **Eyes:** flush with water for 15 min; seek medical attention if irritation persists.
- **Inhalation (mist):** move to fresh air.
- **Ingestion:** rinse mouth; do not induce vomiting; seek medical attention.

## Sections 5–7 — Fire, accidental release, handling/storage (summary)

**Fire (§5):** not classified as flammable in use dilution; concentrate flashpoint > 150 °C. Use foam, CO<sub>2</sub>, or dry chemical.

**Accidental release (§6):** absorb with sand or vermiculite; collect into labelled waste container; do not flush to drain.

**Handling and storage (§7):** store concentrate in original container between 5 °C and 40 °C; avoid freezing. Sump concentration monitored daily by refractometer.

## Section 8 — Exposure controls / PPE

| Hazard          | Engineering control                           | PPE                                                     |
|-----------------|-----------------------------------------------|---------------------------------------------------------|
| Skin contact    | Splash guards on machine doors                | Nitrile gloves when handling concentrate or topping up. |
| Eye contact     | Door interlocks active during cutting         | Safety glasses at all times in cell.                    |
| Mist inhalation | Mist extraction on each machine (5 µm filter) | Respirator (P2) only required during sump cleaning.     |

## Sections 9–16 — Properties, stability, toxicology, ecology, disposal, transport, regulatory, other (summary)

**\$9 Physical properties:** amber liquid (concentrate), pH 9.2 ±0.3 (use dilution).

**\$10 Stability and reactivity:** stable under normal conditions; avoid strong oxidisers.

**\$11 Toxicology:** see Section 2 GHS classification.

**\$12 Ecological information:** harmful to aquatic life; do not release to surface water.

**\$13 Disposal:** spent fluid is RCRA non-hazardous; dispose per local regulation. Site contract: see EH&S manual.

**\$14 Transport (DOT, IMDG):** not regulated.

**\$15 Regulatory:** SARA 313 reportable components: none above threshold. OSHA HazCom 2012 compliant.

**\$16 Other:** revision history maintained by LubeMaster; current Rev 4 supersedes Rev 3 (2022-11-15). For cells where this fluid is in service ( DMU-14 , DMU-22 , NLX-08 , NLX-09 , HMC-30 , BSAW-03 ) see also LOTO procedure for that machine before any sump cleaning.

---

**Document control / sign-off**

| Role           | Name                                                  | Signature | Date       |
|----------------|-------------------------------------------------------|-----------|------------|
| Document Owner | K. Nakamura, EH&S Liaison / LubeMaster (manufacturer) | (on file) | 2024-08-30 |
| Approver       | K. Nakamura, EH&S Liaison / LubeMaster (manufacturer) | (on file) | 2024-08-30 |