

OSHA Machine-Guarding Compliance Summary — Wichita Plant

Plant 3 (Wichita, KS). Applicable federal standards: **29 CFR 1910.212** (general machine guarding), **29 CFR 1910.147** (control of hazardous energy / LOTO).

```
--- METADATA ---
document_id: SP-OSHA-MG-WICHITA
title: OSHA Machine-Guarding Compliance Summary – Wichita Plant
domain: compliance
source_system: SharePoint
revision: Rev B
effective_date: 2024-10-15
owner: J. Reyes, EH&S Officer – Wichita
part_numbers: []
operation_numbers: []
machine_ids: [BSAW-03, DMU-14, DMU-22]
controller_models: []
fault_codes: []
materials: []
standards: [29-CFR-1910.212, 29-CFR-1910.147]
supplier_ids: []
jurisdictions: [US-Federal-OSHA, KS-State]
classification: internal
safety_critical: true
---
```

1. Scope

This summary documents how Contoso's Wichita plant complies with the OSHA general machine-guarding standards. It covers the CNC machining centers (**DMU-14** , **DMU-22**) and the stock-prep horizontal band saw (**BSAW-03**). The compliance posture for each machine is documented below, with cross-references to the machine-specific LOTO procedure.

2. Applicable regulatory requirements

Standard	Requirement (paraphrased)
29 CFR 1910.212(a)(1)	One or more methods of machine guarding shall be provided to protect operators and other employees in the machine area from hazards such as those created by point of operation, ingoing nip points, rotating parts, flying chips and sparks.

29 CFR 1910.212(a)(3)(ii)	The point of operation of machines whose operation exposes an employee to injury shall be guarded. The guarding device shall be in conformity with any appropriate standards therefor.
29 CFR 1910.147(c)(4)	Procedures shall be developed, documented, and used for the control of potentially hazardous energy when employees are engaged in service or maintenance of machines or equipment.
29 CFR 1910.147(c)(7)	Each authorised employee shall receive training in the recognition of applicable hazardous energy sources, the type and magnitude of the energy available in the workplace, and the methods and means necessary for energy isolation and control.

Reference (non-binding): OSHA Publication 3170 (*Safeguarding Equipment and Protecting Employees from Amputations*) provides guidance on band-saw blade-guard requirements; we apply its recommendations as the practice baseline.

3. Machine-by-machine compliance posture

Machine	Guarding method	LOTO procedure
DMU-14	Fully enclosed work envelope with interlocked door; door open prevents spindle rotation. Light curtain on chip-evacuation conveyor.	Cell LOTO LP-DMU14-Rev2 (see EH&S binder).
DMU-22	Same as DMU-14 (identical machine).	Cell LOTO LP-DMU22-Rev2.
BSAW-03	Horizontal band saw. Blade fully enclosed within fixed and adjustable guards per 29 CFR 1910.212(a)(3)(ii). Adjustable guard self-positions to within 12 mm of the stock. Coolant guard prevents fluid splash.	Dedicated LOTO procedure SP-LOTO-BSAW03-RevB covers blade guard service. Per 29 CFR 1910.147(c)(4), the LOTO procedure must be followed before any task that opens the blade guard.

4. Audit history (Wichita plant)

- 2024-09-10 — OSHA voluntary self-audit (internal). Finding: blade-guard self-positioning latch sticky on BSAW-03 ; corrected within 48 h.
- 2025-04-22 — Internal EH&S audit. No machine-guarding findings.

Document control / sign-off

Role	Name	Signature	Date
Document Owner	J. Reyes, EH&S Officer — Wichita	(on file)	2024-10-15
Approver	J. Reyes, EH&S Officer — Wichita	(on file)	2024-10-15