

not Case sensitive HTML (Structure/Layout)

Hyper Text Markup Language

Level 1

HTML is the code that is used to structure a web page and its content.

The Component used to design the structure of websites are called HTML tags.

First HTML File

index.html
it is the default name for a website's homepage

HTML Tag

A Container for some content or other HTML tags

`<p> This is a Paragraph </p>`

Content

Element

Basic HTML Page

`<!DOCTYPE HTML>`

tells browser you are using HTML5

`<HTML>`

roots of an html document

`<head>`

Container for metadata

`<title> MY First Page </title>`

Page title

`</head>`

`<body>`

Contains all data rendered by the browser

`<p> hello world </p>`

Paragraph tag

`</body>`

`</HTML>`

Quick Points

HTML tags is Parent of head & body tag

Most of HTML elements have opening & closing tags with content in between.

Some tags have no content in between, eg - `<br>`

We can use inspect element / view page source to edit HTML.

Comments in HTML

This is Part of Code that should not be parsed.

`<!-- This is an HTML comment -->`

HTML is **NOT** Case Sensitive

`<html>` = `<HTML>`

`<p>` = `<P>`

`<head>` = `<HEAD>`

`<body>` = `<BODY>`

LEVEL 2

Basic HTML Tags

HTML Attributes

Attributes are used to add more information to the tag

`<html lang="en">`

Heading Tag

Used to display heading in HTML

`h1` (most important)

`h2`

`h3`

`h4`

`h5` (least important)

Paragraph Tag

Used to add Paragraph in HTML

`<p> This is a Sample Paragraph </p>`

Anchor Tag

Used to add links to your Page

`<a href="https://google.com"> Google </a>`

Image Tag

Used to add images to your Page

``

↑

relative url

Date :
P. No. :

Br Tag

used to add next line (line breaks) to your page

Bold, Italic & Underline Tags

used to highlight text in your page

 Bold

<i> Italic </i>

<u> Underline </u>

Big & Small Tags

used to display big & small text on your page

<big>

</big>

<small>

</small>

Hor Tag

used to display a horizontal ruler

used to separate content

<hr>

Subscript & Superscript tag

used to

_{subscript}

H₂O

^{superscript}

Aⁿ + B

Pre. Tag
used to display text as it is (without ignoring spaces & next line)

<pre>

this
is a
sample text.

</pre>

LEVEL 3

Page Layout Techniques

using Semantic tags for layout
using the right tags

<header>

<main>

<footer>

Inside main Tag

Section Tag

<section>

Article Tag

<article>

Aside Tag

<aside>

for a section on your page

for an section article on your page

for content aside main content (ads)

Revisiting Anchor Tag

Google<

↑
for new tab

↑
clickable Pic

Revisiting image tag

↑
Set height

↑
Set width

LEVEL 4 (PRO)

List in HTML are used to represent real life list data

unordered

```
<ul>
<li> Apple </li>
<li> Mango </li>
</ul>
```

ordered

```
<ol>
<li> Apple </li>
<li> mango </li>
</ol>
```

Tables in HTML

```
<table>
```

Name	Roll No
Shradha	1664

```
<tr>
```

```
<th> Name </th>
```

```
<th> Roll No </th>
```

```
</tr>
```

```
<tr>
```

```
<td> Shradha </td>
```

```
<td> 1664 </td>
```

```
</tr>
```

```
</table>
```

Caption in Tables

```
<caption> Student Data </caption>
```

Student Data

Name	Roll No
Shradha	1664

Thead & tbody in Tables

<thead> to wrap table head

<tbody> to wrap table body

Colspan attribute

Colspan = "n"

used to create cells which spans over multiple columns

Data	
Shradha	1664
Aman	1890

Form in HTML

Forms are used to collect data from the user

Eg - Sing up / login / help request / contact me

<form>

form content

</form>

Action in Form

Action Attribute is used to define what action needs to be performed when a form is submitted

<form action = "/action.php">

Form Element : Input

<input type = "text" Placeholder = "Enter Name">

Label

```
<label for="id1">  
  <input type="radio" value="class x"  
    name="class" id="id1">  
</label>
```

```
<label for="id2">  
  <input type="radio" value="class x" name=  
    "class" id="id2">  
</label>
```

Class & Id

```
<div id="id1" class="group1">  
</div>
```

```
<div id="id2" class="group1">  
</div>
```

Checkbox

```
<label for="id1">  
  <input type="checkbox" value="class x"  
    name="class" id="id1">  
</label>
```

```
<label for="id2">  
  <input type="checkbox" value="class x"  
    name="class" id="id2">  
</label>
```