LIGHT OIL BILL OF LADING AND/OR PRODUCT RECEIPT

NOT NEGOTIABLE

FOR CHEMICAL EMERGENCY SPILL, LEAK,FIRE EXPOSURE OR ACCIDENT CALL CHEMTREC 800-424-9300 CITGO Petroleum Corp CCN 4886

SEE EMERGENCY RESPONSE, HEALTH AND PHYSICAL HAZARDS

If or when this instrument constitutes a Bill of Lading, the property described below, in apparent good order, is received by the carrier shown herein, which carrier agrees to transport to the consignee and destination shown herein subject to the terms and conditions of the special contract between the carrier and the consignor in effect on the date of the issue of this Bill of Lading. In the absence of a special contract, transportation will be subject to all the terms and conditions of the carrier's tariffs legally on file. It is further agreed by the carrier that the transportation of this shipment will be performed in compliance with all applicable Rules, Regulations and Laws.

Any gasoline listed below and intended for use in the U.S. is in compliance with the applicable standards for volatility in effect at the time of product transfer and has been additized, except where otherwise noted.

This is to certify that the herein-named materials are properly classified, described, packaged, marked and labeled, and are in proper condition for transportation according to the applicable regulations of the Department of Transportation.

Except when indicated as Shipper, Supplier assumes no liability for freight and other charges. Shipper or its designee is liable for freight and other charges. Destination, if shown is designated by the Shipper.

BOL NUMBER 239680

RECEIVED BY CARRIER PER DRIVER
x JOE BIEBER

RECEIVED AT DESTINATION
CUSTOMER

SUPPLYING TERMINAL: CITGO Petroleum Corp, 495 River Road Glenmont, New York 12077 **EPA #:** 404481774 **TCN #:** T14NY1402 **SPLC #:** 173360 **PLANT #:** 3119 **TERMINAL PHONE NO:** 518.465.6517

D.O.T. HAZARDOUS MATERIAL DESCRIPTION

HM	UN/NA Number	DOT Shipping Name	Hazard Class	Packing Group	GALLONS LOADED (GL)
X	NA 1993	DIESEL FUEL	3	PGIII, 1 cargo tank	3000
				Total:	3000

CONSIGNEE (SOLD TO): MIRABITO HOLDINGS INC - BINGHAMTON, NY 13902
PO/CUST REF #:
LOAD RACK: Bay 3
LOAD START: 9/17/2026 05:22
LOAD END: 9/17/2026 05:31

DESIGNEE (SHIP TO): MIRABITO HOLDINGS INC - FPA ACCT/SPOT SALE (37231) , NY
CUSTOMER TYPE: UnBranded
CUSTOMER DEST: 224009
CUSTOMER CARD: 224009
CUSTOMER FEIN:

CARRIER: JAMES MIRABITO & SONS MIRABITO HOLDINGS INC BINGHAMTON, NY 139025306
SCAC: MRBT
CARRIER FEIN: 15-0552668
TRAILER: MRBT00073

SUPPLIER: 9901-CITGO PETROLEUM CORP-
SHIPPER: 9903-CITGO PETROLEUM UNBRANDED -
TAX LICENSE:
DRIVER CARD: 21091
DRIVER NAME: JOE BIEBER
VAPOR ID:

FINISHED PRODUCT

Product	Description	Gross (GL)	Net (GL)	API	Temp.(F)	OCT	RVP	Footnotes
13900	MV UNDYED 15 PPM Sulfur #2 DF	3000	2984	34.9	71.2	0	0	2,3,4,5
	Distillates:	3000	2984					

1.Blend arm on bay 4 is OUT OF SERVICE
2.*BD: This product may contain up to 5% biodiesel
3.* D2-U: 15 ppm sulfur (maximum) Undyed Ultra-Low Sulfur #2 Diesel Fuel.
4.*89: Minimum 40 cetane number. Maximum +15F Cloud Point (Sept-March). Minimum 40 cetane number. Maximum +20F Cloud Point (April-August)
5.* RIN No assigned RINs Transferred.

Shivaji Shaton Springs NY

EMERGENCY RESPONSE, HEALTH and PHYSICAL HAZARDS

GASOLINE....UN1203 (ALL GRADES) **ETHANOL AND GASOLINE MIXTURE, GREATER THAN 10%ETHANOL....UN3475 DANGER!** HIGHLY FLAMMABLE, HARMFUL OR FATAL IF SWALLOWED
FUEL OIL.... NA1993 **KEROSENE....UN1223** **FUEL AVIATION....UN1863 (TURBINE ENGINE)** **DANGER !** FLAMMABLE LIQUID, HARMFUL OR FATAL IF SWALLOWED
ETHANOL....UN1170 (DENATURED ETHANOL) DANGER ! FLAMMABLE LIQUID, HARMFUL OR FATAL IF SWALLOWED. CANNOT BE MADE NON-TOXIC

POTENTIAL HAZARDS

FIRE OR EXPLOSION: •HIGHLY FLAMMABLE: Will be easily ignited by heat, sparks or flames. •Vapors may form explosive mixtures with air. •Vapors may travel to source of ignition and flash back. •Most vapors are heavier than air, they will spread along ground and collect in low or confined areas (sewers, basements, tanks). •Vapor explosion hazard indoors, outdoors or in sewers. •Runoff to sewer may create fire or explosion hazard. •Containers may explode when heated. •Many liquids are lighter than water.
HEALTH: •Fire may produce irritating, corrosive and/or toxic gases. •Vapors may cause dizziness or suffocation. •Runoff from fire control or dilution water may cause pollution.

PUBLIC SAFETY (CALL EMERGENCY RESPONSE TELEPHONE NUMBER 800-424-9300)

•Isolate spill or leak area immediately for at least 25 to 50 meters (80 to 160 feet) in all directions. •Keep unauthorized personnel away. •Stay upwind. •Keep out of low areas. •Ventilate closed spaces before entering.
PROTECTIVE CLOTHING: •Wear positive pressure self-contained breathing apparatus (SCBA). •Structural firefighters' protective clothing will only provide limited protection.
EVACUATION: •**Large Spill:** •Consider initial downwind evaluation for at least 300 meters (1000 feet). •**FIRE:** If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meets (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.

EMERGENCY RESPONSE

FIRE: CAUTION: All of these products have a very low flash point: Use of water spray when fighting fire may be inefficient. •**Small Fires:** •Dry chemical, CO2, water spray or regular foam. Alcohol resistant foam is required for ethanol (Denatured Alcohol) and ethanol and gasoline mixtures. •**Large Fires:** Water, spray, fog or foam. •Do not use straight streams. •Move containers from fire area if you can do it without risk. •**Fire involving Tank or Car / Trailer loads:** Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. •Cool containers with flooding quantities of water until well after fire is out. •Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank. •ALWAYS stay away from the ends of tanks. •For massive fire, use unmanned hose holders or monitor nozzles: If this is impossible, withdraw from area and let fire burn.
SPILL OR LEAK: •ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). •All equipment used when handling the product must be grounded. •Do not touch or walk through spill material. •Stop leak if you can do it without risk. •Prevent entry into waterways, sewers, basements or confined areas. •A Vapor suppressing foam may be used to reduce vapors. •Absorb or cover with dry earth, sand or other non-combustible material, transfer to containers. •Use clean non-sparking tools to collect absorbed material. •**Large Spills:** •Dike far ahead of liquid spill for later disposal. •Water spray may reduce vapor; but may not prevent ignition in closed spaces.
FIRST AID: •Move victim to fresh air. •Call emergency medical care. •Apply artificial respiration if victim is not breathing. •Administer oxygen if breathing is difficult. •Remove and isolate contaminated clothing and shoes. •In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes. •Wash skin with soap and water. •Keep victim warm and quiet. •Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.