




DEPARTMENT OF

COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.



**CHANDIGARH
UNIVERSITY**
Discover. Learn. Empower.

UNIVERSITY INSTITUTE OF ENGINEERING
Department of Computer Science & Engineering

Subject Name: Internet of Things Lab

Subject Code: 20CSP358

Submitted to:

Mrs. Ramandeep Kaur

Submitted by:

Name: Kanishk Soni

UID: 20BCS9398

Section: 20BCS_DM-708

Group: B



DEPARTMENT OF

COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

INDEX

Ex. No	List of Experiments	Conduct (MM: 12)	Viva (MM: 10)	Record (MM: 8)	Total (MM: 30)	Remarks/Signature
1.1						
1.2						
1.3						
2.1						
2.2						
2.3						
2.4						
3.1						
3.2						
3.3						



DEPARTMENT OF

COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

Experiment 1.1

Student Name: Kanishk Soni

UID: 20BCS9398

Branch: CSE

Section/Group: 20BCS_DM-708B

Semester: 6th

Date of Performance: 23/2/2023

Subject Name: IOT Lab

Subject Code: 20CSP358

1. Aim:

write about Arduino, write about its pins along with its diagram.

2. Program and output:

Arduino is an open-source platform used for building electronics projects. Arduino consists of both a physical programmable circuit board (often referred to as a microcontroller) and a piece of software, or IDE (Integrated Development Environment) that runs on your computer, used to write and upload computer code to the physical board.

Vin: This is the input voltage pin of the Arduino board used to provide input supply from an external power source.

5V: This pin of the Arduino board is used as a regulated power supply voltage and it is used to give supply to the board as well as onboard components.

3.3V: This pin of the board is used to provide a supply of 3.3V which is generated from a voltage regulator on the board

GND: This pin of the board is used to ground the Arduino board.



DEPARTMENT OF

COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

Reset: This pin of the board is used to reset the microcontroller. It is used to Resets the microcontroller.

Analog Pins: The pins A0 to A5 are used as an analog input and it is in the range of 0-5V.

Digital Pins: The pins 0 to 13 are used as a digital input or output for the Arduino board.

Serial Pins: These pins are also known as a UART pin. It is used for communication between the Arduino board and a computer or other devices. The transmitter pin number 1 and receiver pin number 0 is used to transmit and receive the data resp.

External Interrupt Pins: This pin of the Arduino board is used to produce the External interrupt and it is done by pin numbers 2 and 3.

PWM Pins: This pins of the board is used to convert the digital signal into an analog by varying the width of the Pulse. The pin numbers 3,5,6,9,10 and 11 are used as a PWM pin.

SPI Pins: This is the Serial Peripheral Interface pin, it is used to maintain SPI communication with the help of the SPI library. SPI pins include:

SS: Pin number 10 is used as a Slave Select

MOSI: Pin number 11 is used as a Master Out Slave In

MISO: Pin number 12 is used as a Master In Slave Out

SCK: Pin number 13 is used as a Serial Clock

LED Pin: The board has an inbuilt LED using digital pin-13. The LED glows only when the digital pin becomes high.

AREF Pin: This is an analog reference pin of the Arduino board. It is used to provide a reference voltage from an external power supply.

3. PINOUT Diagram

