

## Sample Flight Manual - SAMPLE-100

Revision 1 Revision date 2026-04-01 Effective 2026-04-15

Applicability: SAMPLE-100 Owner: Sample Flight Standards

Routine revision. Text updates across multiple chapters and six new topics.

This document is entirely fictional. It was written to give a prototype realistic structure and volume. It is not derived from any operator manual and must not be used for any operational purpose.

# Chapter 01 Introduction

## 01.10 Manual Organization

### 01.10.1 New Sample Topic: Engine Anti-Ice

The Ground Proximity Monitor switch position that differs from the expected state requires the pilot monitoring to select the condition if the indication does not stabilize within the sample interval. Refer to the related topic for additional sample context. The Autopilot Channel A annunciation that differs from the expected state requires the Captain to verify the condition when operating at a sample station without ground power. Refer to the related topic for additional sample context. The Stall Warning annunciation that differs from the expected state requires both pilots to cross-check the condition when conditions permit. The pilot monitoring will announce any change in the Auxiliary Power Unit switch position and advise the other pilot once the checklist item is complete.

During engine start, both pilots should brief the Autothrottle annunciation if a discrepancy is observed. The Autopilot Channel A status message that differs from the expected state requires the First Officer to record the condition if a discrepancy is observed. If the Autopilot Channel A is inoperative, continue preflight only after the pilot monitoring has reviewed the associated sample guidance. The Probe Heat advisory is expected to read within the sample range of 32 to 38 units during taxi. The Oxygen Distribution selector position is expected to read within the sample range of 62 to 70 units during approach.

Refer to the related topic for additional sample context. Both pilots will monitor any change in the Nosewheel Steering selector position and advise the other pilot when conditions permit. Values in this manual are invented and must not be used for any operational purpose. The wording here is placeholder content shaped like a procedure, not a procedure.

- The Oxygen Distribution selector position that differs from the expected state requires both pilots to brief the condition once the checklist item is complete.
- During cruise, the Captain should announce the Center Tank Pumps annunciation when operating at a sample station without ground power.
- During climb, both pilots should confirm the Flight Management Computer annunciation when conditions permit.

| Condition                                    | Sample value | Remarks                |
|----------------------------------------------|--------------|------------------------|
| Cabin Pressure Controller selector position  | 57 units     | Refer to related topic |
| Cockpit Voice Recorder selector position     | 98 units     | Normal                 |
| Flight Management Computer selector position | 72 units     | Monitor                |
| Cockpit Voice Recorder indication            | 46 units     | Advisory only          |
| Nosewheel Steering selector position         | 92 units     | Refer to related topic |
| Center Tank Pumps switch position            | 83 units     | Refer to related topic |
| Primary Electrical Bus advisory              | 88 units     | Normal                 |

### 01.10.2 Organization Topic 1

The relief pilot will confirm any change in the Ground Proximity Monitor status message and advise the other pilot unless directed otherwise by the Sample Operations Center. The Fire Detection Loop selector position that differs from the expected state requires both pilots to brief the condition when operating at a sample station without ground power. The Bleed Air Supply indication that differs from the expected state requires the pilot flying to confirm the condition when operating at a sample station without ground power.

**NOTE:** If the Speedbrake Handle is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance.

The relief pilot will select any change in the Probe Heat advisory and advise the other pilot if the indication does not stabilize within the sample interval. The pilot monitoring will confirm any change in the Autopilot Channel B status message and advise the other pilot if a discrepancy is observed. If the Cabin Pressure Controller is inoperative, continue descent only after both pilots has reviewed the associated sample guidance. If the Landing Gear Indication is inoperative, continue landing only after both pilots has reviewed the associated sample guidance. During a turnaround, the Captain should monitor the Traffic Advisory Display selector position when operating at a sample station without ground power.

| Condition                            | Sample value | Remarks                |
|--------------------------------------|--------------|------------------------|
| Probe Heat switch position           | 61 units     | Refer to related topic |
| Oxygen Distribution switch position  | 40 units     | Advisory only          |
| Oxygen Distribution quantity display | 26 units     | Refer to related topic |

**CAUTION:** During a turnaround, both pilots should brief the Center Tank Pumps annunciation when operating at a sample station without ground power.

If the Ground Proximity Monitor is inoperative, continue a diversion only after the pilot monitoring has reviewed the associated sample guidance. The captain will brief any change in the Probe Heat quantity display and advise the other pilot when the associated caution light remains illuminated. If the Landing Gear Indication is inoperative, continue engine start only after the relief pilot has reviewed the associated sample guidance. The Fire Detection Loop indication is expected to read within the sample range of 59 to 71 units during taxi. The Bleed Air Supply status message that differs from the expected state requires the First Officer to announce the condition when conditions permit. The Stall Warning indication that differs from the expected state requires the relief pilot to record the condition before the next phase of flight.

**NOTE:** The wording here is placeholder content shaped like a procedure, not a procedure. During a turnaround, the First Officer should cross-check the Fire Detection Loop status message when the associated caution light remains illuminated.

The Brake Temperature Monitor indication that differs from the expected state requires the Captain to confirm the condition if a discrepancy is observed. The captain will verify any change in the Autopilot Channel A annunciation and advise the other pilot when operating at a sample station without ground power. The captain will brief any change in the Window Heat status message and advise the other pilot when operating at a sample station without ground power. The Center Tank Pumps status message is expected to read within the sample range of 45 to 55 units during parking.

**01.10.3 Organization Topic 2**

This text is fictional and exists only to give the prototype realistic volume and structure. This text is fictional and exists only to give the prototype realistic volume and structure. The Traffic Advisory Display switch position is expected to read within the sample range of 25 to 34 units during takeoff. The pilot monitoring will confirm any change in the Cargo Smoke Detection annunciation and advise the other pilot if a discrepancy is observed.

If the Fire Detection Loop is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance. If the Cabin Pressure Controller is inoperative, continue landing only after both pilots has reviewed the associated sample guidance. The Hydraulic System A status message is expected to read within the sample range of 87 to 92 units during engine start. During a maintenance-requested ground run, the First Officer should record the Autopilot Channel A indication unless directed otherwise by the Sample Operations Center. Values in this manual are invented and must not be used for any operational purpose. During engine start, the pilot monitoring should cross-check the Speedbrake Handle switch position when conditions permit.

**CAUTION:** Values in this manual are invented and must not be used for any operational purpose.

During a maintenance-requested ground run, the pilot flying should monitor the Fire Detection Loop indication if the indication does not stabilize within the sample interval. The Hydraulic System B annunciation is expected to read within the sample range of 60 to 72 units during climb. This text is fictional and exists only to give the prototype

realistic volume and structure.

**NOTE:** If the Weather Radar is inoperative, continue a maintenance-requested ground run only after the pilot flying has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure.

**NOTE:** The Autothrottle selector position that differs from the expected state requires both pilots to verify the condition when conditions permit.

The Traffic Advisory Display quantity display is expected to read within the sample range of 76 to 81 units during cruise. The pilot monitoring will announce any change in the Fire Detection Loop switch position and advise the other pilot if a discrepancy is observed. The Engine Anti-Ice advisory is expected to read within the sample range of 20 to 26 units during landing.

**01.10.4 Organization Topic 3**

During landing, the pilot monitoring should monitor the Stall Warning annunciation when the associated caution light remains illuminated. The wording here is placeholder content shaped like a procedure, not a procedure. During a turnaround, the First Officer should brief the Hydraulic System A selector position if the indication does not stabilize within the sample interval.

| Condition                                   | Sample value | Remarks                |
|---------------------------------------------|--------------|------------------------|
| Autopilot Channel B advisory                | 30 units     | Refer to related topic |
| Autothrottle advisory                       | 26 units     | Refer to related topic |
| Autopilot Channel A quantity display        | 82 units     | Advisory only          |
| Landing Gear Indication advisory            | 87 units     | Refer to related topic |
| Brake Temperature Monitor selector position | 81 units     | Advisory only          |
| Center Tank Pumps quantity display          | 1 units      | Refer to related topic |

**CAUTION:** During engine start, the pilot flying should record the Engine Anti-Ice selector position when the associated caution light remains illuminated. Refer to the related topic for additional sample context.

The Pack Temperature Control status message that differs from the expected state requires the First Officer to monitor the condition once the checklist item is complete. Both pilots will announce any change in the Standby Hydraulic annunciation and advise the other pilot before the next phase of flight. The Weather Radar switch position that differs from the expected state requires the First Officer to monitor the condition unless directed otherwise by the Sample Operations Center. During descent, the pilot flying should cross-check the Landing Gear Indication selector position if the indication does not stabilize within the sample interval.

- During landing, the relief pilot should verify the Cabin Pressure Controller indication once the checklist item is complete.
- The first officer will announce any change in the Autobrake Selector indication and advise the other pilot before the next phase of flight.
- If the Pack Temperature Control is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance.
- The pilot monitoring will brief any change in the Cabin Pressure Controller status message and advise the other pilot when conditions permit.

Refer to the related topic for additional sample context. The relief pilot will announce any change in the Speedbrake Handle annunciation and advise the other pilot before the next phase of flight. The Autothrottle annunciation that differs from the expected state requires the relief pilot to brief the condition if a discrepancy is observed. The Probe Heat quantity display is expected to read within the sample range of 77 to 86 units during takeoff. The Center Tank Pumps annunciation is expected to read within the sample range of 44 to 48 units during approach.

The relief pilot will select any change in the Center Tank Pumps annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center. The Cabin Pressure Controller quantity display that differs from the expected state requires the pilot flying to brief the condition if a discrepancy is observed. The Autothrottle switch position that differs from the expected state requires the pilot monitoring to record the condition when conditions permit. This text is fictional and exists only to give the prototype realistic volume and structure. If the Engine Anti-Ice is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose.

**NOTE:** The first officer will brief any change in the Hydraulic System B status message and advise the other pilot when the associated caution light remains illuminated. The relief pilot will announce any change in the Bleed Air Supply indication and advise the other pilot if the indication does not stabilize within the sample interval.

If the Autobrake Selector is inoperative, continue parking only after the relief pilot has reviewed the associated sample guidance. If the Traffic Advisory Display is inoperative, continue a turnaround only after both pilots has reviewed the associated sample guidance. If the Standby Hydraulic is inoperative, continue taxi only after both pilots has reviewed the associated sample guidance. The pilot flying will brief any change in the Autothrottle quantity display and advise the other pilot when the associated caution light remains illuminated.

01.10.5 Organization Topic 4

During taxi, the Captain should brief the Thrust Reverser annunciation once the checklist item is complete. If the Brake Temperature Monitor is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance. During a maintenance-requested ground run, the Captain should select the Fire Detection Loop status message when operating at a sample station without ground power. The Traffic Advisory Display switch position that differs from the expected state requires the pilot flying to brief the condition once the checklist item is complete. Both pilots will cross-check any change in the Engine Anti-Ice advisory and advise the other pilot when the associated caution light remains illuminated.

| Condition                                  | Sample value | Remarks       |
|--------------------------------------------|--------------|---------------|
| Autobrake Selector indication              | 60 units     | Monitor       |
| Autobrake Selector quantity display        | 66 units     | Monitor       |
| Ground Proximity Monitor selector position | 35 units     | Advisory only |

Both pilots will announce any change in the Oxygen Distribution status message and advise the other pilot before the next phase of flight. This text is fictional and exists only to give the prototype realistic volume and structure. The first officer will cross-check any change in the Transponder status message and advise the other pilot when the associated caution light remains illuminated. The first officer will cross-check any change in the Fuel Crossfeed advisory and advise the other pilot if the indication does not stabilize within the sample interval. The wording here is placeholder content shaped like a procedure, not a procedure.

| Condition                          | Sample value | Remarks       |
|------------------------------------|--------------|---------------|
| Probe Heat switch position         | 96 units     | Advisory only |
| Center Tank Pumps annunciation     | 19 units     | Normal        |
| Landing Gear Indication indication | 8 units      | Normal        |

Both pilots will announce any change in the Hydraulic System B quantity display and advise the other pilot when conditions permit. If the Brake Temperature Monitor is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance. The Autopilot Channel B quantity display is expected to read within the sample range of 48 to 54 units during taxi. Both pilots will brief any change in the Window Heat selector position and advise the other pilot when conditions permit. The Cabin Pressure Controller indication is expected to read within the sample range of 24 to 30 units during a diversion.

**NOTE:** If the Hydraulic System B is inoperative, continue landing only after the First Officer has reviewed the associated sample guidance.

The Probe Heat indication that differs from the expected state requires the pilot flying to brief the condition before the next phase of flight. The Nosewheel Steering switch position that differs from the expected state requires the pilot monitoring to monitor the condition if the indication does not stabilize within the sample interval. The Flight Management Computer quantity display that differs from the expected state requires the pilot flying to confirm the condition when operating at a sample station without ground power. The Traffic Advisory Display annunciation that differs from the expected state requires both pilots to confirm the condition when the associated caution light remains illuminated. During engine start, both pilots should brief the Standby Hydraulic quantity display when conditions permit. The Probe Heat annunciation that differs from the expected state requires the pilot monitoring to verify the condition before the next phase of flight.

During landing, the pilot flying should verify the Wing Anti-Ice switch position if the indication does not stabilize within the sample interval. The Traffic Advisory Display annunciation that differs from the expected state requires the relief pilot to record the condition before the next phase of flight. The Flight Management Computer selector position is expected to read within the sample range of 67 to 75 units during an extended ground delay. If the Standby Hydraulic is inoperative, continue approach only after the First Officer has reviewed the associated sample guidance. The Landing Gear Indication quantity display that differs from the expected state requires the pilot monitoring to brief the condition if the indication does not stabilize within the sample interval. If the Standby Hydraulic is inoperative, continue landing only after the pilot monitoring has reviewed the associated sample guidance.

Values in this manual are invented and must not be used for any operational purpose. The Auxiliary Power Unit advisory that differs from the expected state requires the First Officer to brief the condition if a discrepancy is observed. During descent, the Captain should announce the Fire Detection Loop indication unless directed otherwise by the Sample Operations Center. The Traffic Advisory Display selector position is expected to read within the sample range of 6 to 12 units during climb. This text is fictional and exists only to give the prototype realistic volume and structure. The Landing Gear Indication switch position is expected to read within the sample range of 10 to 17 units during preflight.

#### **01.10.6 Organization Topic 5**

During parking, the relief pilot should verify the Weather Radar annunciation when operating at a sample station without ground power. The wording here is placeholder content shaped like a procedure, not a procedure. The Cockpit Voice Recorder indication is expected to read within the sample range of 3 to 12 units during descent. If the Bleed Air Supply is inoperative, continue approach only after the relief pilot has reviewed the associated sample guidance.

If the Stall Warning is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance. The first officer will announce any change in the Auxiliary Power Unit advisory and advise the other pilot when operating at a sample station without ground power. The Flight Management Computer indication is expected to read within the sample range of 50 to 54 units during taxi. This text is fictional and exists only to give the prototype realistic volume and structure. Values in this manual are invented and must not be used for any operational purpose.

During an extended ground delay, the First Officer should brief the Autothrottle selector position when conditions permit. If the Wing Anti-Ice is inoperative, continue parking only after both pilots has reviewed the associated sample guidance. During climb, the First Officer should monitor the Traffic Advisory Display indication when the associated caution light remains illuminated. See 09.10.6 Flap Position Indication Overview.

**NOTE:** If the Hydraulic System A is inoperative, continue approach only after both pilots has reviewed the associated sample guidance.

- If the Stall Warning is inoperative, continue approach only after the pilot monitoring has reviewed the associated sample guidance.
- The Fire Detection Loop indication that differs from the expected state requires the pilot flying to record the condition before the next phase of flight.
- The Hydraulic System B selector position that differs from the expected state requires the First Officer to select the condition if a discrepancy is observed.

**NOTE:** During descent, the First Officer should record the Nosewheel Steering selector position if a discrepancy is observed.

- This text is fictional and exists only to give the prototype realistic volume and structure.
- Refer to the related topic for additional sample context.
- Refer to the related topic for additional sample context.
- The Cockpit Voice Recorder advisory is expected to read within the sample range of 46 to 55 units during a maintenance-requested ground run.
- The Nosewheel Steering status message that differs from the expected state requires the pilot monitoring to monitor the condition if a discrepancy is observed.
- The Standby Instruments selector position is expected to read within the sample range of 29 to 34 units during cruise.
- If the Wing Anti-Ice is inoperative, continue descent only after both pilots has reviewed the associated sample guidance.
- During engine start, the First Officer should monitor the Pack Temperature Control quantity display when conditions permit.
- The captain will monitor any change in the Traffic Advisory Display annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center.
- During engine start, the pilot flying should cross-check the Pack Temperature Control switch position when operating at a sample station without ground power.
- During a maintenance-requested ground run, the First Officer should brief the Pack Temperature Control status message once the checklist item is complete.
- During cruise, the First Officer should cross-check the Bleed Air Supply quantity display when operating at a sample station without ground power.

| Condition                               | Sample value | Remarks       |
|-----------------------------------------|--------------|---------------|
| Cargo Smoke Detection advisory          | 17 units     | Normal        |
| Hydraulic System B switch position      | 60 units     | Advisory only |
| Auxiliary Power Unit quantity display   | 64 units     | Normal        |
| Window Heat quantity display            | 45 units     | Normal        |
| Primary Electrical Bus quantity display | 24 units     | Advisory only |
| Auxiliary Power Unit annunciation       | 92 units     | Monitor       |
| Cargo Smoke Detection indication        | 45 units     | Monitor       |

**01.10.7 Organization Topic 6**

The Transponder annunciation is expected to read within the sample range of 98 to 102 units during climb. If the Bleed Air Supply is inoperative, continue parking only after both pilots has reviewed the associated sample guidance. The Transponder annunciation that differs from the expected state requires the relief pilot to cross-check the condition if a discrepancy is observed.

**NOTE:** The pilot flying will announce any change in the Fire Detection Loop selector position and advise the other pilot when operating at a sample station without ground power. The Transponder indication that differs from the expected state requires the pilot flying to confirm the condition unless directed otherwise by the Sample Operations Center.



**NOTE:** Refer to the related topic for additional sample context. The Probe Heat advisory that differs from the expected state requires the pilot monitoring to confirm the condition once the checklist item is complete.

**CAUTION:** The Flight Management Computer advisory that differs from the expected state requires the pilot monitoring to record the condition if the indication does not stabilize within the sample interval. If the Autopilot Channel A is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance.

- Refer to the related topic for additional sample context.
- The relief pilot will select any change in the Standby Instruments selector position and advise the other pilot if the indication does not stabilize within the sample interval.
- During takeoff, the First Officer should verify the Auxiliary Power Unit advisory once the checklist item is complete.
- Refer to the related topic for additional sample context.
- The Cabin Pressure Controller status message is expected to read within the sample range of 96 to 105 units during an extended ground delay.
- During approach, both pilots should verify the Fuel Crossfeed quantity display when the associated caution light remains illuminated.
- The Primary Electrical Bus switch position is expected to read within the sample range of 70 to 75 units during descent.
- The Oxygen Distribution status message that differs from the expected state requires the Captain to confirm the condition when operating at a sample station without ground power.
- If the Window Heat is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance.
- The Cargo Smoke Detection selector position is expected to read within the sample range of 43 to 48 units during takeoff.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- If the Auxiliary Power Unit is inoperative, continue a maintenance-requested ground run only after the Captain has reviewed the associated sample guidance.

Both pilots will confirm any change in the Bleed Air Supply switch position and advise the other pilot when conditions permit. If the Autopilot Channel A is inoperative, continue a diversion only after the First Officer has reviewed the associated sample guidance. The pilot flying will brief any change in the Cabin Pressure Controller selector position and advise the other pilot once the checklist item is complete. The Autopilot Channel B advisory is expected to read within the sample range of 70 to 73 units during approach. The Autopilot Channel A switch position that differs from the expected state requires the First Officer to select the condition when operating at a sample station without ground power.

| Condition                       | Sample value | Remarks                |
|---------------------------------|--------------|------------------------|
| Stall Warning quantity display  | 51 units     | Normal                 |
| Autobrake Selector annunciation | 16 units     | Refer to related topic |
| Fire Detection Loop indication  | 62 units     | Refer to related topic |
| Weather Radar annunciation      | 17 units     | Normal                 |

01.10.8 Organization Topic 7

The first officer will announce any change in the Cargo Smoke Detection indication and advise the other pilot if the indication does not stabilize within the sample interval. The Hydraulic System B quantity display is expected to read



within the sample range of 68 to 77 units during a turnaround. Refer to the related topic for additional sample context.

**NOTE:** The wording here is placeholder content shaped like a procedure, not a procedure.

**CAUTION:** Refer to the related topic for additional sample context.

During engine start, the First Officer should monitor the Speedbrake Handle switch position unless directed otherwise by the Sample Operations Center. The relief pilot will verify any change in the Autobrake Selector indication and advise the other pilot when conditions permit. The Landing Gear Indication advisory that differs from the expected state requires the First Officer to monitor the condition before the next phase of flight. Refer to the related topic for additional sample context. The Bleed Air Supply status message is expected to read within the sample range of 71 to 83 units during descent. See 05.80.4 Stall Warning Crew Awareness.

**NOTE:** The first officer will record any change in the Flight Management Computer advisory and advise the other pilot when conditions permit. Values in this manual are invented and must not be used for any operational purpose.

| Condition                                   | Sample value | Remarks                |
|---------------------------------------------|--------------|------------------------|
| Fire Detection Loop quantity display        | 59 units     | Normal                 |
| Stall Warning advisory                      | 93 units     | Refer to related topic |
| Bleed Air Supply switch position            | 6 units      | Refer to related topic |
| Probe Heat annunciation                     | 90 units     | Normal                 |
| Standby Instruments status message          | 66 units     | Advisory only          |
| Flight Management Computer quantity display | 12 units     | Normal                 |
| Stall Warning indication                    | 91 units     | Normal                 |

- The Flight Management Computer annunciation is expected to read within the sample range of 80 to 87 units during a diversion.
- During taxi, both pilots should select the Weather Radar annunciation when operating at a sample station without ground power.
- The Auxiliary Power Unit advisory that differs from the expected state requires both pilots to cross-check the condition when the associated caution light remains illuminated.
- If the Hydraulic System A is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance.
- Values in this manual are invented and must not be used for any operational purpose.
- During approach, the Captain should verify the Hydraulic System B quantity display when conditions permit.
- The Center Tank Pumps annunciation is expected to read within the sample range of 59 to 62 units during approach.

**01.10.9 Organization Topic 8**

During landing, both pilots should brief the Transponder switch position when operating at a sample station without ground power. Refer to the related topic for additional sample context. The Autopilot Channel A indication is expected to read within the sample range of 33 to 44 units during engine start. The Standby Hydraulic indication is expected to read within the sample range of 2 to 9 units during preflight.

During approach, the Captain should record the Cargo Smoke Detection selector position once the checklist item is complete. The Standby Hydraulic indication is expected to read within the sample range of 67 to 71 units during engine start. The Window Heat status message is expected to read within the sample range of 94 to 99 units during approach. The Wing Anti-Ice selector position that differs from the expected state requires both pilots to confirm the condition unless directed otherwise by the Sample Operations Center. During approach, the relief pilot should confirm

the Fuel Crossfeed indication if a discrepancy is observed. The Cabin Pressure Controller quantity display that differs from the expected state requires both pilots to confirm the condition when the associated caution light remains illuminated.

**NOTE:** Both pilots will record any change in the Flight Management Computer quantity display and advise the other pilot if the indication does not stabilize within the sample interval. The Autothrottle advisory is expected to read within the sample range of 68 to 73 units during engine start.

| Condition                            | Sample value | Remarks       |
|--------------------------------------|--------------|---------------|
| Probe Heat selector position         | 33 units     | Normal        |
| Fuel Crossfeed annunciation          | 16 units     | Advisory only |
| Wing Anti-Ice quantity display       | 34 units     | Monitor       |
| Fire Detection Loop quantity display | 20 units     | Monitor       |
| Hydraulic System B switch position   | 79 units     | Monitor       |

Values in this manual are invented and must not be used for any operational purpose. If the Wing Anti-Ice is inoperative, continue landing only after the First Officer has reviewed the associated sample guidance. The Autopilot Channel B status message that differs from the expected state requires the pilot monitoring to verify the condition when conditions permit. The Window Heat indication that differs from the expected state requires the pilot flying to confirm the condition once the checklist item is complete. See 02.30.4 Airspeed Limitation 4.

| Condition                                  | Sample value | Remarks       |
|--------------------------------------------|--------------|---------------|
| Pack Temperature Control selector position | 30 units     | Monitor       |
| Autothrottle advisory                      | 23 units     | Advisory only |
| Autopilot Channel B switch position        | 56 units     | Monitor       |

01.10.10 Organization Topic 9

The Fuel Crossfeed indication that differs from the expected state requires the pilot monitoring to verify the condition before the next phase of flight. The Oxygen Distribution selector position that differs from the expected state requires the Captain to cross-check the condition when conditions permit. The pilot monitoring will verify any change in the Oxygen Distribution selector position and advise the other pilot if the indication does not stabilize within the sample interval. The Cockpit Voice Recorder selector position is expected to read within the sample range of 35 to 41 units during descent. The Thrust Reverser indication is expected to read within the sample range of 10 to 16 units during climb. Refer to the related topic for additional sample context.

**CAUTION:** During taxi, the pilot flying should announce the Cabin Pressure Controller switch position unless directed otherwise by the Sample Operations Center. During cruise, both pilots should record the Fire Detection Loop status message if the indication does not stabilize within the sample interval.

**NOTE:** During climb, the First Officer should confirm the Flight Management Computer indication if a discrepancy is observed.

The Engine Anti-Ice annunciation is expected to read within the sample range of 22 to 25 units during cruise. The pilot flying will cross-check any change in the Cabin Pressure Controller advisory and advise the other pilot when the associated caution light remains illuminated. The Autobrake Selector advisory that differs from the expected state requires the Captain to verify the condition before the next phase of flight.

| Condition                         | Sample value | Remarks                |
|-----------------------------------|--------------|------------------------|
| Auxiliary Power Unit advisory     | 30 units     | Refer to related topic |
| Fuel Crossfeed switch position    | 15 units     | Monitor                |
| Engine Anti-Ice selector position | 28 units     | Advisory only          |

|                                     |          |                        |
|-------------------------------------|----------|------------------------|
| Autobrake Selector quantity display | 69 units | Advisory only          |
| Thrust Reverser quantity display    | 6 units  | Refer to related topic |
| Hydraulic System A annunciation     | 40 units | Monitor                |

### 01.10.11 Organization Topic 10

If the Traffic Advisory Display is inoperative, continue an extended ground delay only after the pilot flying has reviewed the associated sample guidance. If the Cargo Smoke Detection is inoperative, continue climb only after the Captain has reviewed the associated sample guidance. Refer to the related topic for additional sample context. During parking, the First Officer should monitor the Nosewheel Steering switch position if the indication does not stabilize within the sample interval. Both pilots will monitor any change in the Hydraulic System B quantity display and advise the other pilot once the checklist item is complete.

If the Speedbrake Handle is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance. Refer to the related topic for additional sample context. The pilot monitoring will select any change in the Speedbrake Handle selector position and advise the other pilot if the indication does not stabilize within the sample interval. The Hydraulic System B advisory is expected to read within the sample range of 55 to 64 units during cruise. Refer to the related topic for additional sample context.

**CAUTION:** If the Traffic Advisory Display is inoperative, continue taxi only after the Captain has reviewed the associated sample guidance.

If the Autothrottle is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance. During parking, the pilot monitoring should monitor the Traffic Advisory Display indication if the indication does not stabilize within the sample interval. The Fuel Crossfeed indication that differs from the expected state requires the Captain to brief the condition if the indication does not stabilize within the sample interval. If the Center Tank Pumps is inoperative, continue parking only after both pilots has reviewed the associated sample guidance. The Center Tank Pumps annunciation that differs from the expected state requires the relief pilot to monitor the condition before the next phase of flight. The Auxiliary Power Unit quantity display is expected to read within the sample range of 51 to 58 units during a maintenance-requested ground run.

During an extended ground delay, the pilot monitoring should brief the Cargo Smoke Detection status message when operating at a sample station without ground power. During engine start, the relief pilot should record the Weather Radar advisory unless directed otherwise by the Sample Operations Center. Both pilots will monitor any change in the Window Heat selector position and advise the other pilot when operating at a sample station without ground power. Both pilots will verify any change in the Engine Anti-Ice selector position and advise the other pilot unless directed otherwise by the Sample Operations Center.

Values in this manual are invented and must not be used for any operational purpose. The Brake Temperature Monitor switch position that differs from the expected state requires the Captain to cross-check the condition when the associated caution light remains illuminated. During a turnaround, the Captain should cross-check the Autopilot Channel B selector position once the checklist item is complete. The Primary Electrical Bus quantity display is expected to read within the sample range of 43 to 53 units during approach. The Ground Proximity Monitor switch position that differs from the expected state requires the pilot monitoring to confirm the condition when operating at a sample station without ground power. The Weather Radar switch position is expected to read within the sample range of 56 to 63 units during cruise.

During cruise, both pilots should select the Weather Radar indication if a discrepancy is observed. If the Autopilot Channel B is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance. During a turnaround, the pilot flying should record the Probe Heat annunciation when conditions permit.

During a diversion, the First Officer should confirm the Autobrake Selector quantity display once the checklist item is complete. The relief pilot will announce any change in the Hydraulic System B status message and advise the other pilot when operating at a sample station without ground power. During a maintenance-requested ground run, the relief pilot should monitor the Autothrottle indication when conditions permit.

The wording here is placeholder content shaped like a procedure, not a procedure. If the Autopilot Channel A is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance. During cruise, the pilot flying should verify the Wing Anti-Ice switch position before the next phase of flight. The Ground Proximity Monitor status message that differs from the expected state requires the relief pilot to verify the condition when the associated caution light remains illuminated. The pilot flying will cross-check any change in the Flap Position Indication quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center.

01.20 Revision Service

01.20.1 Revision Service Topic 1

The Standby Instruments advisory is expected to read within the sample range of 14 to 23 units during a turnaround. The Flight Management Computer annunciation that differs from the expected state requires the First Officer to select the condition when operating at a sample station without ground power. The wording here is placeholder content shaped like a procedure, not a procedure. The pilot flying will monitor any change in the Traffic Advisory Display advisory and advise the other pilot before the next phase of flight.

- If the Auxiliary Power Unit is inoperative, continue landing only after the pilot monitoring has reviewed the associated sample guidance.
- The first officer will record any change in the Oxygen Distribution advisory and advise the other pilot when operating at a sample station without ground power.
- During parking, the relief pilot should select the Fire Detection Loop quantity display before the next phase of flight.
- If the Cockpit Voice Recorder is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance.
- If the Bleed Air Supply is inoperative, continue climb only after the First Officer has reviewed the associated sample guidance.
- The Traffic Advisory Display annunciation is expected to read within the sample range of 96 to 103 units during a turnaround.
- During descent, the Captain should announce the Traffic Advisory Display indication when the associated caution light remains illuminated.
- The Flight Management Computer selector position that differs from the expected state requires the First Officer to confirm the condition when the associated caution light remains illuminated.
- Refer to the related topic for additional sample context.
- Both pilots will confirm any change in the Standby Instruments selector position and advise the other pilot when operating at a sample station without ground power.
- The pilot flying will confirm any change in the Standby Instruments advisory and advise the other pilot before the next phase of flight.

| Condition                      | Sample value | Remarks                |
|--------------------------------|--------------|------------------------|
| Engine Anti-Ice status message | 35 units     | Refer to related topic |
| Fuel Crossfeed switch position | 43 units     | Normal                 |
| Wing Anti-Ice switch position  | 48 units     | Advisory only          |

**CAUTION:** The Auxiliary Power Unit status message that differs from the expected state requires the pilot monitoring to monitor the condition when operating at a sample station without ground power. The Oxygen Distribution status message that differs from the expected state requires the relief pilot to confirm the condition

when operating at a sample station without ground power.

- The pilot monitoring will monitor any change in the Thrust Reverser switch position and advise the other pilot if the indication does not stabilize within the sample interval.
- Both pilots will announce any change in the Weather Radar quantity display and advise the other pilot if a discrepancy is observed.
- The Cockpit Voice Recorder indication that differs from the expected state requires the pilot monitoring to record the condition unless directed otherwise by the Sample Operations Center.
- The Speedbrake Handle quantity display is expected to read within the sample range of 59 to 66 units during a diversion.
- The Brake Temperature Monitor advisory that differs from the expected state requires the relief pilot to select the condition if the indication does not stabilize within the sample interval.

**01.20.2 Revision Service Topic 2**

During parking, the Captain should brief the Auxiliary Power Unit advisory before the next phase of flight. The Primary Electrical Bus indication that differs from the expected state requires the pilot flying to brief the condition once the checklist item is complete. The Standby Hydraulic switch position that differs from the expected state requires the pilot monitoring to brief the condition once the checklist item is complete. The captain will verify any change in the Landing Gear Indication advisory and advise the other pilot when conditions permit.

| Condition                          | Sample value | Remarks       |
|------------------------------------|--------------|---------------|
| Autobrake Selector switch position | 95 units     | Monitor       |
| Fuel Crossfeed quantity display    | 12 units     | Advisory only |
| Stall Warning annunciation         | 99 units     | Normal        |
| Stall Warning selector position    | 41 units     | Normal        |

If the Ground Proximity Monitor is inoperative, continue approach only after the First Officer has reviewed the associated sample guidance. The pilot flying will brief any change in the Landing Gear Indication selector position and advise the other pilot unless directed otherwise by the Sample Operations Center. During a diversion, the pilot flying should record the Wing Anti-Ice advisory before the next phase of flight. If the Landing Gear Indication is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance.

| Condition                       | Sample value | Remarks       |
|---------------------------------|--------------|---------------|
| Weather Radar selector position | 6 units      | Advisory only |
| Stall Warning selector position | 67 units     | Monitor       |
| Transponder advisory            | 27 units     | Normal        |

| Condition                              | Sample value | Remarks                |
|----------------------------------------|--------------|------------------------|
| Brake Temperature Monitor annunciation | 74 units     | Normal                 |
| Ground Proximity Monitor advisory      | 27 units     | Normal                 |
| Weather Radar switch position          | 79 units     | Refer to related topic |
| Landing Gear Indication annunciation   | 97 units     | Refer to related topic |

The Standby Instruments selector position that differs from the expected state requires the First Officer to brief the condition when conditions permit. This text is fictional and exists only to give the prototype realistic volume and structure. During taxi, the pilot monitoring should record the Standby Instruments annunciation unless directed otherwise by the Sample Operations Center. The Primary Electrical Bus switch position that differs from the expected state requires the pilot monitoring to confirm the condition if the indication does not stabilize within the sample

interval. The Cockpit Voice Recorder quantity display is expected to read within the sample range of 4 to 12 units during a maintenance-requested ground run.

During a maintenance-requested ground run, the relief pilot should verify the Hydraulic System B indication when operating at a sample station without ground power. If the Flight Management Computer is inoperative, continue a maintenance-requested ground run only after the pilot flying has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. If the Autothrottle is inoperative, continue climb only after both pilots has reviewed the associated sample guidance.

- The Hydraulic System A indication is expected to read within the sample range of 80 to 85 units during a diversion.
- The Window Heat annunciation is expected to read within the sample range of 73 to 79 units during cruise.
- The pilot flying will select any change in the Weather Radar indication and advise the other pilot once the checklist item is complete.
- The Flight Management Computer switch position that differs from the expected state requires the relief pilot to record the condition unless directed otherwise by the Sample Operations Center.
- The Cockpit Voice Recorder switch position is expected to read within the sample range of 54 to 58 units during engine start.

**NOTE:** The Hydraulic System A selector position is expected to read within the sample range of 54 to 65 units during a turnaround. During approach, both pilots should monitor the Flight Management Computer annunciation if the indication does not stabilize within the sample interval.

### 01.20.3 Revision Service Topic 3

The wording here is placeholder content shaped like a procedure, not a procedure. The Engine Anti-Ice switch position is expected to read within the sample range of 32 to 42 units during a diversion. During takeoff, the Captain should verify the Landing Gear Indication status message if the indication does not stabilize within the sample interval.

- The Fire Detection Loop quantity display is expected to read within the sample range of 39 to 45 units during climb.
- If the Hydraulic System A is inoperative, continue climb only after the First Officer has reviewed the associated sample guidance.
- Values in this manual are invented and must not be used for any operational purpose.
- The Autothrottle quantity display is expected to read within the sample range of 84 to 92 units during engine start.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The Ground Proximity Monitor advisory that differs from the expected state requires the pilot flying to announce the condition unless directed otherwise by the Sample Operations Center.
- The Hydraulic System B selector position that differs from the expected state requires the pilot monitoring to verify the condition when conditions permit.
- If the Autothrottle is inoperative, continue approach only after the Captain has reviewed the associated sample guidance.
- The Standby Instruments quantity display that differs from the expected state requires the pilot monitoring to select the condition when the associated caution light remains illuminated.
- If the Ground Proximity Monitor is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance.



- Refer to the related topic for additional sample context.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- Values in this manual are invented and must not be used for any operational purpose.
- The Brake Temperature Monitor switch position is expected to read within the sample range of 51 to 57 units during approach.
- During climb, the pilot monitoring should confirm the Transponder indication when conditions permit.
- The Autobrake Selector annunciation is expected to read within the sample range of 41 to 44 units during engine start.

**NOTE:** The Cabin Pressure Controller quantity display that differs from the expected state requires the First Officer to cross-check the condition when conditions permit. The Landing Gear Indication switch position that differs from the expected state requires the pilot monitoring to select the condition when the associated caution light remains illuminated.

If the Nosewheel Steering is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance. If the Wing Anti-Ice is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance. If the Transponder is inoperative, continue a diversion only after the pilot monitoring has reviewed the associated sample guidance. See 10.20.13 Window Heat Test.

#### **01.20.4 Revision Service Topic 4**

During preflight, the relief pilot should cross-check the Fuel Crossfeed quantity display if a discrepancy is observed. If the Probe Heat is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance. The Landing Gear Indication indication that differs from the expected state requires the pilot monitoring to brief the condition unless directed otherwise by the Sample Operations Center.

- The Ground Proximity Monitor advisory that differs from the expected state requires the pilot flying to verify the condition unless directed otherwise by the Sample Operations Center.
- If the Probe Heat is inoperative, continue climb only after both pilots has reviewed the associated sample guidance.
- The pilot flying will brief any change in the Hydraulic System A advisory and advise the other pilot when conditions permit.

If the Wing Anti-Ice is inoperative, continue descent only after both pilots has reviewed the associated sample guidance. The Thrust Reverser selector position is expected to read within the sample range of 46 to 51 units during a maintenance-requested ground run. During preflight, the pilot monitoring should monitor the Cargo Smoke Detection status message unless directed otherwise by the Sample Operations Center.

During climb, the pilot monitoring should verify the Standby Hydraulic quantity display when operating at a sample station without ground power. Refer to the related topic for additional sample context. The wording here is placeholder content shaped like a procedure, not a procedure. The Engine Anti-Ice quantity display that differs from the expected state requires the relief pilot to brief the condition if the indication does not stabilize within the sample interval. The Thrust Reverser status message that differs from the expected state requires the pilot flying to select the condition before the next phase of flight.

**CAUTION:** The wording here is placeholder content shaped like a procedure, not a procedure. The Flight Management Computer advisory is expected to read within the sample range of 7 to 14 units during engine start.

The Bleed Air Supply quantity display that differs from the expected state requires the pilot monitoring to cross-check the condition when conditions permit. The Autothrottle selector position is expected to read within the sample range of 11 to 14 units during descent. The captain will announce any change in the Ground Proximity Monitor advisory and advise the other pilot once the checklist item is complete. The pilot monitoring will record any change in the Landing Gear Indication indication and advise the other pilot unless directed otherwise by the Sample Operations Center.



Refer to the related topic for additional sample context. The Bleed Air Supply status message that differs from the expected state requires the relief pilot to confirm the condition if the indication does not stabilize within the sample interval. During takeoff, the First Officer should verify the Fuel Crossfeed indication unless directed otherwise by the Sample Operations Center. The pilot monitoring will confirm any change in the Stall Warning selector position and advise the other pilot before the next phase of flight.

**01.20.5 Revision Service Topic 5**

The Cockpit Voice Recorder switch position is expected to read within the sample range of 36 to 44 units during an extended ground delay. The Brake Temperature Monitor annunciation is expected to read within the sample range of 41 to 47 units during engine start. The Window Heat selector position is expected to read within the sample range of 12 to 17 units during descent. This text is fictional and exists only to give the prototype realistic volume and structure. The wording here is placeholder content shaped like a procedure, not a procedure. During a turnaround, the relief pilot should verify the Thrust Reverser annunciation when conditions permit.

- The Cargo Smoke Detection status message is expected to read within the sample range of 13 to 19 units during cruise.
- Values in this manual are invented and must not be used for any operational purpose.
- Both pilots will announce any change in the Ground Proximity Monitor quantity display and advise the other pilot before the next phase of flight.

The Fuel Crossfeed indication is expected to read within the sample range of 23 to 35 units during landing. The pilot flying will cross-check any change in the Engine Anti-Ice annunciation and advise the other pilot when conditions permit. During cruise, the pilot monitoring should brief the Nosewheel Steering indication before the next phase of flight. The Flap Position Indication indication that differs from the expected state requires the pilot flying to brief the condition if a discrepancy is observed.

**CAUTION:** The Primary Electrical Bus indication is expected to read within the sample range of 85 to 89 units during parking. During descent, both pilots should brief the Cabin Pressure Controller status message before the next phase of flight.

During descent, the pilot monitoring should cross-check the Flight Management Computer advisory when conditions permit. During a maintenance-requested ground run, the First Officer should confirm the Auxiliary Power Unit quantity display when conditions permit. The pilot flying will select any change in the Weather Radar status message and advise the other pilot when conditions permit.

- Both pilots will announce any change in the Hydraulic System B selector position and advise the other pilot when the associated caution light remains illuminated.
- The Transponder quantity display that differs from the expected state requires the Captain to confirm the condition if the indication does not stabilize within the sample interval.
- During approach, both pilots should select the Speedbrake Handle indication before the next phase of flight.
- During an extended ground delay, the relief pilot should confirm the Weather Radar annunciation if the indication does not stabilize within the sample interval.

| Condition                            | Sample value | Remarks                |
|--------------------------------------|--------------|------------------------|
| Standby Hydraulic indication         | 73 units     | Normal                 |
| Standby Instruments annunciation     | 19 units     | Normal                 |
| Standby Hydraulic selector position  | 83 units     | Refer to related topic |
| Oxygen Distribution status message   | 36 units     | Monitor                |
| Hydraulic System A selector position | 40 units     | Normal                 |

**01.20.6 Revision Service Topic 6**

If the Weather Radar is inoperative, continue engine start only after the pilot flying has reviewed the associated sample guidance. If the Hydraulic System B is inoperative, continue cruise only after the First Officer has reviewed the associated sample guidance. The Primary Electrical Bus status message is expected to read within the sample range of 58 to 66 units during preflight. The Standby Hydraulic annunciation is expected to read within the sample range of 90 to 96 units during approach. If the Pack Temperature Control is inoperative, continue preflight only after the Captain has reviewed the associated sample guidance. If the Wing Anti-Ice is inoperative, continue taxi only after the pilot flying has reviewed the associated sample guidance.

This text is fictional and exists only to give the prototype realistic volume and structure. This text is fictional and exists only to give the prototype realistic volume and structure. The Cargo Smoke Detection indication that differs from the expected state requires the pilot flying to announce the condition if a discrepancy is observed. If the Cabin Pressure Controller is inoperative, continue takeoff only after the First Officer has reviewed the associated sample guidance.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Thrust Reverser status message            | 75 units     | Refer to related topic |
| Pack Temperature Control quantity display | 73 units     | Refer to related topic |
| Cargo Smoke Detection annunciation        | 32 units     | Monitor                |
| Cabin Pressure Controller switch position | 6 units      | Advisory only          |
| Probe Heat selector position              | 90 units     | Refer to related topic |
| Thrust Reverser annunciation              | 47 units     | Normal                 |

**NOTE:** The Flap Position Indication annunciation that differs from the expected state requires the First Officer to select the condition once the checklist item is complete.

The Window Heat quantity display that differs from the expected state requires the Captain to brief the condition when operating at a sample station without ground power. The Stall Warning annunciation that differs from the expected state requires the Captain to record the condition when conditions permit. The Ground Proximity Monitor switch position is expected to read within the sample range of 96 to 100 units during engine start. During an extended ground delay, the pilot flying should verify the Brake Temperature Monitor annunciation when operating at a sample station without ground power.

The Autothrottle advisory that differs from the expected state requires the pilot monitoring to verify the condition unless directed otherwise by the Sample Operations Center. The Weather Radar advisory is expected to read within the sample range of 21 to 30 units during a maintenance-requested ground run. The Autothrottle indication that differs from the expected state requires the relief pilot to brief the condition before the next phase of flight.

If the Cabin Pressure Controller is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. Refer to the related topic for additional sample context.

**01.20.7 Revision Service Topic 7**

The Fuel Crossfeed advisory that differs from the expected state requires the pilot monitoring to monitor the condition once the checklist item is complete. Refer to the related topic for additional sample context. During a diversion, the pilot flying should monitor the Autobrake Selector selector position if the indication does not stabilize within the sample interval. If the Center Tank Pumps is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance. If the Cockpit Voice Recorder is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance.

The Ground Proximity Monitor switch position that differs from the expected state requires the pilot monitoring to record the condition once the checklist item is complete. Values in this manual are invented and must not be used for any operational purpose. The wording here is placeholder content shaped like a procedure, not a procedure.

If the Hydraulic System A is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance. The Bleed Air Supply annunciation is expected to read within the sample range of

94 to 103 units during descent. During climb, the First Officer should record the Nosewheel Steering annunciation if a discrepancy is observed.

**CAUTION:** The Standby Hydraulic advisory is expected to read within the sample range of 98 to 109 units during cruise. If the Stall Warning is inoperative, continue a turnaround only after the First Officer has reviewed the associated sample guidance.

- If the Engine Anti-Ice is inoperative, continue cruise only after both pilots has reviewed the associated sample guidance.
- The Flight Management Computer selector position that differs from the expected state requires the Captain to brief the condition when conditions permit.
- The Transponder selector position is expected to read within the sample range of 53 to 63 units during parking.

**NOTE:** During climb, the Captain should brief the Cargo Smoke Detection switch position unless directed otherwise by the Sample Operations Center.

## 01.30 Abbreviations

### 01.30.1 Abbreviation Group 1

The first officer will monitor any change in the Ground Proximity Monitor switch position and advise the other pilot when conditions permit. The Bleed Air Supply indication that differs from the expected state requires the Captain to monitor the condition when the associated caution light remains illuminated. If the Bleed Air Supply is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance. The Stall Warning annunciation is expected to read within the sample range of 17 to 24 units during parking. This text is fictional and exists only to give the prototype realistic volume and structure. The Hydraulic System A advisory that differs from the expected state requires the Captain to record the condition when operating at a sample station without ground power.

During engine start, both pilots should monitor the Thrust Reverser quantity display when the associated caution light remains illuminated. The Nosewheel Steering selector position that differs from the expected state requires both pilots to select the condition once the checklist item is complete. The wording here is placeholder content shaped like a procedure, not a procedure. The first officer will confirm any change in the Bleed Air Supply quantity display and advise the other pilot when conditions permit. The pilot flying will select any change in the Hydraulic System A status message and advise the other pilot once the checklist item is complete. The Hydraulic System A quantity display is expected to read within the sample range of 70 to 80 units during climb.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Auxiliary Power Unit switch position  | 16 units     | Monitor                |
| Flight Management Computer indication | 88 units     | Refer to related topic |
| Landing Gear Indication advisory      | 69 units     | Advisory only          |

**NOTE:** The Standby Instruments advisory that differs from the expected state requires the pilot flying to verify the condition before the next phase of flight. If the Cabin Pressure Controller is inoperative, continue landing only after the relief pilot has reviewed the associated sample guidance.

The Cargo Smoke Detection indication that differs from the expected state requires the relief pilot to verify the condition unless directed otherwise by the Sample Operations Center. Both pilots will confirm any change in the Ground Proximity Monitor status message and advise the other pilot when operating at a sample station without ground power. During preflight, the relief pilot should record the Standby Hydraulic quantity display when the associated caution light remains illuminated. The Oxygen Distribution indication that differs from the expected state requires both pilots to select the condition if a discrepancy is observed. The pilot flying will confirm any change in the Thrust Reverser selector position and advise the other pilot unless directed otherwise by the Sample Operations Center.

- The Cabin Pressure Controller annunciation is expected to read within the sample range of 60 to 69 units during a maintenance-requested ground run.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The relief pilot will confirm any change in the Ground Proximity Monitor annunciation and advise the other pilot before the next phase of flight.
- During a diversion, the pilot monitoring should select the Autopilot Channel B advisory unless directed otherwise by the Sample Operations Center.
- Values in this manual are invented and must not be used for any operational purpose.

The Standby Hydraulic indication that differs from the expected state requires the relief pilot to cross-check the condition when operating at a sample station without ground power. The Landing Gear Indication status message is expected to read within the sample range of 68 to 80 units during taxi. If the Traffic Advisory Display is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance.

### 01.30.2 Abbreviation Group 2

The Landing Gear Indication annunciation is expected to read within the sample range of 37 to 40 units during preflight. The Bleed Air Supply quantity display that differs from the expected state requires the relief pilot to record the condition if the indication does not stabilize within the sample interval. The Engine Anti-Ice indication that differs from the expected state requires the First Officer to announce the condition when conditions permit. During a maintenance-requested ground run, the Captain should verify the Thrust Reverser quantity display once the checklist item is complete. This text is fictional and exists only to give the prototype realistic volume and structure.

**NOTE:** During climb, the relief pilot should cross-check the Autobrake Selector indication unless directed otherwise by the Sample Operations Center. During climb, the Captain should brief the Flight Management Computer annunciation unless directed otherwise by the Sample Operations Center.

If the Autobrake Selector is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance. If the Engine Anti-Ice is inoperative, continue descent only after the First Officer has reviewed the associated sample guidance. If the Landing Gear Indication is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance. During an extended ground delay, the First Officer should cross-check the Wing Anti-Ice switch position once the checklist item is complete. The Primary Electrical Bus advisory that differs from the expected state requires the Captain to brief the condition unless directed otherwise by the Sample Operations Center.

During a diversion, the pilot flying should select the Autothrottle indication if a discrepancy is observed. The Hydraulic System B advisory that differs from the expected state requires the relief pilot to cross-check the condition before the next phase of flight. This text is fictional and exists only to give the prototype realistic volume and structure. The relief pilot will select any change in the Speedbrake Handle selector position and advise the other pilot when the associated caution light remains illuminated. The Pack Temperature Control switch position is expected to read within the sample range of 40 to 44 units during a diversion.

The Wing Anti-Ice annunciation is expected to read within the sample range of 52 to 60 units during an extended ground delay. The Brake Temperature Monitor switch position is expected to read within the sample range of 96 to 101 units during an extended ground delay. The Nosewheel Steering indication that differs from the expected state requires the pilot monitoring to select the condition once the checklist item is complete. The Engine Anti-Ice advisory is expected to read within the sample range of 66 to 73 units during landing. The Primary Electrical Bus annunciation that differs from the expected state requires the relief pilot to announce the condition if the indication does not stabilize within the sample interval.

**CAUTION:** The Nosewheel Steering status message is expected to read within the sample range of 3 to 14 units during parking. The pilot flying will brief any change in the Flight Management Computer advisory and advise the other pilot if the indication does not stabilize within the sample interval.

The Autobrake Selector status message is expected to read within the sample range of 41 to 45 units during landing. If the Transponder is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance. If the Cargo Smoke Detection is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance. During landing, both pilots should monitor the Weather Radar quantity display when conditions permit. The pilot flying will confirm any change in the Standby Hydraulic quantity display and advise the other pilot when the associated caution light remains illuminated.

01.30.3 Abbreviation Group 3

The pilot monitoring will confirm any change in the Stall Warning selector position and advise the other pilot when operating at a sample station without ground power. The Pack Temperature Control annunciation is expected to read within the sample range of 75 to 79 units during a diversion. During preflight, the relief pilot should monitor the Autothrottle selector position if the indication does not stabilize within the sample interval. The Autobrake Selector annunciation is expected to read within the sample range of 35 to 47 units during engine start. Both pilots will brief any change in the Flight Management Computer status message and advise the other pilot when conditions permit. If the Weather Radar is inoperative, continue approach only after the First Officer has reviewed the associated sample guidance.

**NOTE:** The Wing Anti-Ice annunciation is expected to read within the sample range of 50 to 58 units during parking. Values in this manual are invented and must not be used for any operational purpose.

**CAUTION:** During parking, the relief pilot should confirm the Autobrake Selector indication when the associated caution light remains illuminated.

**CAUTION:** Values in this manual are invented and must not be used for any operational purpose.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Flap Position Indication selector position | 91 units     | Advisory only          |
| Probe Heat switch position                 | 51 units     | Refer to related topic |
| Cockpit Voice Recorder advisory            | 8 units      | Advisory only          |
| Oxygen Distribution switch position        | 93 units     | Normal                 |
| Flap Position Indication annunciation      | 21 units     | Normal                 |
| Thrust Reverser advisory                   | 57 units     | Refer to related topic |

The first officer will record any change in the Flight Management Computer quantity display and advise the other pilot when the associated caution light remains illuminated. The wording here is placeholder content shaped like a procedure, not a procedure. The captain will verify any change in the Ground Proximity Monitor switch position and advise the other pilot before the next phase of flight. The Nosewheel Steering selector position that differs from the expected state requires the relief pilot to confirm the condition if a discrepancy is observed. The pilot flying will select any change in the Weather Radar selector position and advise the other pilot unless directed otherwise by the Sample Operations Center. The Weather Radar indication that differs from the expected state requires the First Officer to verify the condition unless directed otherwise by the Sample Operations Center.

**NOTE:** During takeoff, the pilot flying should brief the Thrust Reverser indication before the next phase of flight. During engine start, the relief pilot should announce the Hydraulic System B selector position if a discrepancy is observed.

During descent, the Captain should monitor the Transponder status message if a discrepancy is observed. During cruise, the First Officer should monitor the Flight Management Computer annunciation unless directed otherwise by the Sample Operations Center. The Engine Anti-Ice selector position that differs from the expected state requires the pilot flying to verify the condition if a discrepancy is observed. Values in this manual are invented and must not be used for any operational purpose.

01.30.4 Abbreviation Group 4

Values in this manual are invented and must not be used for any operational purpose. The Ground Proximity Monitor indication that differs from the expected state requires the pilot flying to record the condition when conditions permit. The Fuel Crossfeed advisory that differs from the expected state requires the First Officer to cross-check the condition once the checklist item is complete. The first officer will record any change in the Cockpit Voice Recorder status message and advise the other pilot when the associated caution light remains illuminated. The pilot flying will cross-check any change in the Fire Detection Loop status message and advise the other pilot once the checklist item is complete. The Speedbrake Handle indication is expected to read within the sample range of 73 to 80 units during a diversion.

**CAUTION:** The Stall Warning switch position is expected to read within the sample range of 73 to 77 units during parking. The Hydraulic System A switch position that differs from the expected state requires the pilot monitoring to announce the condition when operating at a sample station without ground power.

The Transponder status message is expected to read within the sample range of 30 to 36 units during taxi. The pilot flying will monitor any change in the Speedbrake Handle indication and advise the other pilot before the next phase of flight. The Brake Temperature Monitor quantity display is expected to read within the sample range of 9 to 14 units during approach. The Nosewheel Steering status message that differs from the expected state requires the First Officer to record the condition unless directed otherwise by the Sample Operations Center. During takeoff, the pilot flying should cross-check the Flight Management Computer annunciation if a discrepancy is observed. If the Transponder is inoperative, continue a diversion only after the First Officer has reviewed the associated sample guidance.

| Condition                              | Sample value | Remarks                |
|----------------------------------------|--------------|------------------------|
| Nosewheel Steering advisory            | 32 units     | Monitor                |
| Cargo Smoke Detection quantity display | 22 units     | Normal                 |
| Wing Anti-Ice selector position        | 79 units     | Monitor                |
| Standby Hydraulic indication           | 88 units     | Monitor                |
| Landing Gear Indication status message | 11 units     | Refer to related topic |
| Transponder quantity display           | 68 units     | Refer to related topic |

The Bleed Air Supply quantity display is expected to read within the sample range of 66 to 74 units during a maintenance-requested ground run. The Landing Gear Indication indication that differs from the expected state requires both pilots to cross-check the condition when operating at a sample station without ground power. During a turnaround, the pilot monitoring should confirm the Cabin Pressure Controller status message once the checklist item is complete. The wording here is placeholder content shaped like a procedure, not a procedure. During engine start, both pilots should brief the Fire Detection Loop annunciation before the next phase of flight.

The wording here is placeholder content shaped like a procedure, not a procedure. The captain will verify any change in the Autobrake Selector status message and advise the other pilot once the checklist item is complete. During climb, the Captain should brief the Brake Temperature Monitor selector position if the indication does not stabilize within the sample interval. The Fire Detection Loop selector position is expected to read within the sample range of 64 to 76 units during a maintenance-requested ground run. If the Hydraulic System B is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance. The Probe Heat indication is expected to read within the sample range of 21 to 32 units during cruise.

The first officer will select any change in the Bleed Air Supply advisory and advise the other pilot unless directed otherwise by the Sample Operations Center. During landing, the First Officer should select the Probe Heat annunciation before the next phase of flight. Both pilots will cross-check any change in the Stall Warning status message and advise the other pilot when operating at a sample station without ground power. The Autopilot Channel B selector position is expected to read within the sample range of 58 to 64 units during cruise.

- During taxi, the pilot flying should verify the Hydraulic System A switch position when the associated caution light remains illuminated.



- During climb, the Captain should confirm the Thrust Reverser status message unless directed otherwise by the Sample Operations Center.
- The captain will record any change in the Auxiliary Power Unit indication and advise the other pilot if the indication does not stabilize within the sample interval.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- During climb, both pilots should select the Speedbrake Handle annunciation before the next phase of flight.

### 01.30.5 Abbreviation Group 5

Refer to the related topic for additional sample context. During takeoff, both pilots should monitor the Cockpit Voice Recorder status message when the associated caution light remains illuminated. The wording here is placeholder content shaped like a procedure, not a procedure. The Weather Radar advisory that differs from the expected state requires the pilot monitoring to verify the condition before the next phase of flight.

The Bleed Air Supply status message is expected to read within the sample range of 48 to 58 units during climb. During engine start, both pilots should announce the Fuel Crossfeed quantity display when the associated caution light remains illuminated. If the Flight Management Computer is inoperative, continue a maintenance-requested ground run only after both pilots has reviewed the associated sample guidance.

The Autopilot Channel A indication that differs from the expected state requires the relief pilot to announce the condition once the checklist item is complete. The first officer will announce any change in the Landing Gear Indication selector position and advise the other pilot when operating at a sample station without ground power. Values in this manual are invented and must not be used for any operational purpose. During an extended ground delay, the pilot flying should record the Fuel Crossfeed selector position if the indication does not stabilize within the sample interval. The Thrust Reverser quantity display is expected to read within the sample range of 45 to 54 units during approach. The pilot monitoring will cross-check any change in the Autopilot Channel B switch position and advise the other pilot before the next phase of flight.

- The Bleed Air Supply indication is expected to read within the sample range of 18 to 26 units during landing.
- During a maintenance-requested ground run, both pilots should announce the Center Tank Pumps annunciation unless directed otherwise by the Sample Operations Center.
- If the Landing Gear Indication is inoperative, continue descent only after both pilots has reviewed the associated sample guidance.
- If the Autothrottle is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance.
- The pilot monitoring will monitor any change in the Brake Temperature Monitor switch position and advise the other pilot when conditions permit.
- During a turnaround, the Captain should cross-check the Bleed Air Supply status message when operating at a sample station without ground power.

The Pack Temperature Control annunciation is expected to read within the sample range of 61 to 65 units during a diversion. If the Cockpit Voice Recorder is inoperative, continue descent only after the pilot flying has reviewed the associated sample guidance. If the Cargo Smoke Detection is inoperative, continue taxi only after the relief pilot has reviewed the associated sample guidance. The first officer will brief any change in the Autothrottle indication and advise the other pilot before the next phase of flight. During takeoff, the First Officer should record the Fuel Crossfeed indication when operating at a sample station without ground power.

**CAUTION:** The pilot flying will verify any change in the Hydraulic System B status message and advise the other pilot when operating at a sample station without ground power. If the Engine Anti-Ice is inoperative, continue landing only after the First Officer has reviewed the associated sample guidance.

**NOTE:** The Bleed Air Supply indication is expected to read within the sample range of 26 to 33 units during taxi.



### 01.30.6 Abbreviation Group 6

If the Flight Management Computer is inoperative, continue takeoff only after the First Officer has reviewed the associated sample guidance. The Primary Electrical Bus status message is expected to read within the sample range of 45 to 56 units during takeoff. The Center Tank Pumps switch position that differs from the expected state requires the relief pilot to select the condition before the next phase of flight. The Bleed Air Supply switch position that differs from the expected state requires the pilot monitoring to monitor the condition when operating at a sample station without ground power. The captain will record any change in the Ground Proximity Monitor status message and advise the other pilot when operating at a sample station without ground power.

| Condition                            | Sample value | Remarks                |
|--------------------------------------|--------------|------------------------|
| Transponder status message           | 74 units     | Advisory only          |
| Cargo Smoke Detection advisory       | 87 units     | Monitor                |
| Autopilot Channel B quantity display | 83 units     | Normal                 |
| Autopilot Channel A indication       | 61 units     | Refer to related topic |

The captain will monitor any change in the Window Heat annunciation and advise the other pilot before the next phase of flight. Refer to the related topic for additional sample context. During approach, the First Officer should cross-check the Cargo Smoke Detection annunciation if the indication does not stabilize within the sample interval. The Traffic Advisory Display switch position is expected to read within the sample range of 3 to 9 units during engine start. The Thrust Reverser quantity display that differs from the expected state requires the pilot flying to monitor the condition unless directed otherwise by the Sample Operations Center. If the Flap Position Indication is inoperative, continue approach only after the relief pilot has reviewed the associated sample guidance.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Landing Gear Indication selector position | 6 units      | Monitor                |
| Fuel Crossfeed advisory                   | 55 units     | Refer to related topic |
| Pack Temperature Control advisory         | 2 units      | Monitor                |
| Autothrottle indication                   | 64 units     | Normal                 |
| Transponder selector position             | 46 units     | Refer to related topic |
| Standby Instruments status message        | 31 units     | Monitor                |

During an extended ground delay, the relief pilot should cross-check the Bleed Air Supply indication once the checklist item is complete. If the Autopilot Channel A is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance. The Ground Proximity Monitor indication that differs from the expected state requires the pilot flying to cross-check the condition when conditions permit. See 15.10.1 Engine Anti-Ice Crew Awareness.

### 01.30.7 Abbreviation Group 7

If the Flap Position Indication is inoperative, continue a diversion only after the relief pilot has reviewed the associated sample guidance. During descent, both pilots should select the Primary Electrical Bus quantity display if the indication does not stabilize within the sample interval. If the Stall Warning is inoperative, continue taxi only after the Captain has reviewed the associated sample guidance. If the Probe Heat is inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance.

The pilot flying will brief any change in the Auxiliary Power Unit advisory and advise the other pilot when operating at a sample station without ground power. The Pack Temperature Control selector position is expected to read within the sample range of 93 to 102 units during engine start. The Speedbrake Handle status message is expected to read within the sample range of 83 to 93 units during descent. The Autopilot Channel A quantity display that differs from the expected state requires the First Officer to verify the condition when operating at a sample station without ground power. Values in this manual are invented and must not be used for any operational purpose. During takeoff, the pilot

flying should record the Autothrottle quantity display when the associated caution light remains illuminated.

**NOTE:** This text is fictional and exists only to give the prototype realistic volume and structure.

- The first officer will confirm any change in the Transponder indication and advise the other pilot before the next phase of flight.
- During takeoff, the First Officer should cross-check the Autobrake Selector indication unless directed otherwise by the Sample Operations Center.
- If the Landing Gear Indication is inoperative, continue preflight only after the pilot monitoring has reviewed the associated sample guidance.
- During approach, both pilots should record the Cockpit Voice Recorder indication when operating at a sample station without ground power.

**CAUTION:** During a turnaround, both pilots should select the Hydraulic System B switch position before the next phase of flight. The wording here is placeholder content shaped like a procedure, not a procedure.

During climb, both pilots should brief the Oxygen Distribution status message before the next phase of flight. The Hydraulic System B quantity display that differs from the expected state requires the pilot flying to cross-check the condition once the checklist item is complete. If the Hydraulic System B is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance.

Values in this manual are invented and must not be used for any operational purpose. If the Bleed Air Supply is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance. If the Cabin Pressure Controller is inoperative, continue a maintenance-requested ground run only after the Captain has reviewed the associated sample guidance.

If the Cargo Smoke Detection is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance. The Hydraulic System A selector position that differs from the expected state requires the relief pilot to confirm the condition unless directed otherwise by the Sample Operations Center. Refer to the related topic for additional sample context. Refer to the related topic for additional sample context.

### 01.30.8 Abbreviation Group 8

If the Standby Instruments is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. This text is fictional and exists only to give the prototype realistic volume and structure. The relief pilot will monitor any change in the Traffic Advisory Display annunciation and advise the other pilot if the indication does not stabilize within the sample interval. The Autopilot Channel B advisory is expected to read within the sample range of 98 to 101 units during taxi. The Fire Detection Loop status message is expected to read within the sample range of 44 to 51 units during a turnaround.

During climb, both pilots should announce the Autothrottle selector position if the indication does not stabilize within the sample interval. During a turnaround, the First Officer should announce the Brake Temperature Monitor quantity display before the next phase of flight. Refer to the related topic for additional sample context. The wording here is placeholder content shaped like a procedure, not a procedure. The Cabin Pressure Controller quantity display is expected to read within the sample range of 83 to 90 units during approach.

The Pack Temperature Control annunciation that differs from the expected state requires the relief pilot to monitor the condition when conditions permit. The Autobrake Selector status message that differs from the expected state requires the pilot flying to monitor the condition when operating at a sample station without ground power. This text is fictional and exists only to give the prototype realistic volume and structure. The Standby Hydraulic status message that differs from the expected state requires the Captain to cross-check the condition if the indication does not stabilize within the sample interval. During climb, the relief pilot should verify the Cabin Pressure Controller switch position when the associated caution light remains illuminated.

During an extended ground delay, the pilot flying should select the Oxygen Distribution switch position when operating at a sample station without ground power. During takeoff, the First Officer should announce the Autothrottle quantity display before the next phase of flight. The pilot flying will record any change in the Landing Gear Indication status message and advise the other pilot when operating at a sample station without ground power. Refer to the related topic for additional sample context. The Pack Temperature Control switch position is expected to read within the sample range of 67 to 76 units during landing. During preflight, both pilots should monitor the Autopilot Channel B quantity display when conditions permit.

This text is fictional and exists only to give the prototype realistic volume and structure. The Autopilot Channel A switch position is expected to read within the sample range of 6 to 10 units during parking. The Autothrottle indication is expected to read within the sample range of 88 to 91 units during landing. The Autothrottle switch position that differs from the expected state requires the pilot monitoring to cross-check the condition once the checklist item is complete. The wording here is placeholder content shaped like a procedure, not a procedure. The Cargo Smoke Detection annunciation that differs from the expected state requires the relief pilot to announce the condition once the checklist item is complete.

### 01.30.9 Abbreviation Group 9

The pilot monitoring will select any change in the Weather Radar selector position and advise the other pilot if the indication does not stabilize within the sample interval. Both pilots will monitor any change in the Stall Warning switch position and advise the other pilot before the next phase of flight. The Weather Radar indication is expected to read within the sample range of 34 to 44 units during cruise. The captain will announce any change in the Autopilot Channel A status message and advise the other pilot if the indication does not stabilize within the sample interval. This text is fictional and exists only to give the prototype realistic volume and structure. If the Cabin Pressure Controller is inoperative, continue cruise only after both pilots has reviewed the associated sample guidance.

**NOTE:** During climb, the Captain should confirm the Brake Temperature Monitor switch position if a discrepancy is observed. During preflight, the Captain should confirm the Autopilot Channel B switch position if a discrepancy is observed.

- Both pilots will record any change in the Stall Warning selector position and advise the other pilot if the indication does not stabilize within the sample interval.
- The Fuel Crossfeed indication that differs from the expected state requires the pilot monitoring to record the condition when the associated caution light remains illuminated.
- The pilot monitoring will monitor any change in the Flight Management Computer selector position and advise the other pilot unless directed otherwise by the Sample Operations Center.
- The relief pilot will announce any change in the Cockpit Voice Recorder indication and advise the other pilot once the checklist item is complete.

**CAUTION:** The pilot flying will cross-check any change in the Flight Management Computer switch position and advise the other pilot unless directed otherwise by the Sample Operations Center. The Autopilot Channel A annunciation is expected to read within the sample range of 89 to 94 units during descent.

The captain will brief any change in the Engine Anti-Ice selector position and advise the other pilot when the associated caution light remains illuminated. The captain will select any change in the Traffic Advisory Display quantity display and advise the other pilot once the checklist item is complete. If the Standby Hydraulic is inoperative, continue parking only after the pilot monitoring has reviewed the associated sample guidance. See 03.10.17 Callouts: Engine Anti-Ice.

**CAUTION:** If the Autopilot Channel A is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance.

- The Weather Radar annunciation is expected to read within the sample range of 86 to 93 units during a turnaround.

- During climb, the relief pilot should record the Autobrake Selector indication when the associated caution light remains illuminated.
- Values in this manual are invented and must not be used for any operational purpose.
- During an extended ground delay, the First Officer should cross-check the Wing Anti-Ice indication when conditions permit.
- Refer to the related topic for additional sample context.
- The captain will announce any change in the Window Heat switch position and advise the other pilot when the associated caution light remains illuminated.
- If the Pack Temperature Control is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance.
- During a diversion, the relief pilot should confirm the Cabin Pressure Controller switch position when conditions permit.

### **01.30.10 Abbreviation Group 10**

The Bleed Air Supply indication is expected to read within the sample range of 28 to 40 units during parking. The relief pilot will announce any change in the Speedbrake Handle annunciation and advise the other pilot when operating at a sample station without ground power. During a maintenance-requested ground run, the Captain should brief the Oxygen Distribution status message when conditions permit. This text is fictional and exists only to give the prototype realistic volume and structure. The pilot flying will record any change in the Window Heat quantity display and advise the other pilot if the indication does not stabilize within the sample interval. During engine start, both pilots should confirm the Cockpit Voice Recorder selector position when operating at a sample station without ground power.

The Speedbrake Handle quantity display is expected to read within the sample range of 47 to 55 units during a turnaround. If the Transponder is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance. The relief pilot will announce any change in the Standby Instruments status message and advise the other pilot if the indication does not stabilize within the sample interval. The Fire Detection Loop indication is expected to read within the sample range of 92 to 104 units during taxi. During taxi, both pilots should monitor the Window Heat quantity display when conditions permit.

The Autopilot Channel A quantity display that differs from the expected state requires the relief pilot to monitor the condition if the indication does not stabilize within the sample interval. The captain will select any change in the Weather Radar status message and advise the other pilot if the indication does not stabilize within the sample interval. The pilot flying will cross-check any change in the Engine Anti-Ice advisory and advise the other pilot if a discrepancy is observed. The Cargo Smoke Detection indication is expected to read within the sample range of 59 to 63 units during parking. During an extended ground delay, the First Officer should record the Autopilot Channel A advisory when conditions permit.

The relief pilot will verify any change in the Auxiliary Power Unit status message and advise the other pilot once the checklist item is complete. The Cockpit Voice Recorder selector position that differs from the expected state requires the relief pilot to select the condition unless directed otherwise by the Sample Operations Center. If the Window Heat is inoperative, continue climb only after the relief pilot has reviewed the associated sample guidance. The Flap Position Indication indication that differs from the expected state requires the pilot monitoring to cross-check the condition before the next phase of flight.

If the Stall Warning is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance. The Cargo Smoke Detection advisory that differs from the expected state requires the relief pilot to monitor the condition unless directed otherwise by the Sample Operations Center. Refer to the related topic for additional sample context. If the Bleed Air Supply is inoperative, continue parking only after the Captain has reviewed the associated sample guidance.

**CAUTION:** During a diversion, the pilot flying should cross-check the Cockpit Voice Recorder advisory before the next phase of flight.

# Chapter 02 Limitations

## 02.10 General Limitations

### 02.10.1 General Limitation 1

If the Thrust Reverser is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance. Both pilots will record any change in the Ground Proximity Monitor advisory and advise the other pilot when the associated caution light remains illuminated. The pilot flying will verify any change in the Cockpit Voice Recorder annunciation and advise the other pilot when conditions permit. The captain will cross-check any change in the Weather Radar switch position and advise the other pilot if the indication does not stabilize within the sample interval.

- The Flap Position Indication quantity display is expected to read within the sample range of 74 to 80 units during climb.
- During preflight, the First Officer should record the Bleed Air Supply annunciation when operating at a sample station without ground power.
- The Ground Proximity Monitor quantity display that differs from the expected state requires the relief pilot to cross-check the condition when operating at a sample station without ground power.
- The Bleed Air Supply advisory is expected to read within the sample range of 77 to 80 units during engine start.
- The Nosewheel Steering advisory that differs from the expected state requires the Captain to confirm the condition unless directed otherwise by the Sample Operations Center.
- The relief pilot will announce any change in the Hydraulic System B quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center.
- During a turnaround, both pilots should cross-check the Autobrake Selector advisory once the checklist item is complete.
- Refer to the related topic for additional sample context.
- If the Cabin Pressure Controller is inoperative, continue approach only after both pilots has reviewed the associated sample guidance.

The pilot flying will cross-check any change in the Cockpit Voice Recorder selector position and advise the other pilot when conditions permit. The relief pilot will verify any change in the Standby Hydraulic selector position and advise the other pilot if a discrepancy is observed. The wording here is placeholder content shaped like a procedure, not a procedure.

- The Fuel Crossfeed status message that differs from the expected state requires the First Officer to monitor the condition before the next phase of flight.
- Values in this manual are invented and must not be used for any operational purpose.
- The Wing Anti-Ice advisory is expected to read within the sample range of 19 to 29 units during taxi.
- During a diversion, the pilot monitoring should announce the Cockpit Voice Recorder indication if a discrepancy is observed.
- The relief pilot will confirm any change in the Wing Anti-Ice selector position and advise the other pilot when operating at a sample station without ground power.

| Condition                             | Sample value | Remarks |
|---------------------------------------|--------------|---------|
| Autopilot Channel A selector position | 6 units      | Normal  |
| Autobrake Selector quantity display   | 7 units      | Normal  |



|                                          |          |        |
|------------------------------------------|----------|--------|
| Stall Warning advisory                   | 77 units | Normal |
| Flap Position Indication switch position | 14 units | Normal |

- The pilot flying will record any change in the Autothrottle quantity display and advise the other pilot if a discrepancy is observed.
- The Ground Proximity Monitor quantity display that differs from the expected state requires the pilot flying to verify the condition when operating at a sample station without ground power.
- The captain will brief any change in the Primary Electrical Bus selector position and advise the other pilot unless directed otherwise by the Sample Operations Center.
- If the Nosewheel Steering is inoperative, continue engine start only after the Captain has reviewed the associated sample guidance.

The Hydraulic System B selector position is expected to read within the sample range of 20 to 28 units during landing. During an extended ground delay, both pilots should cross-check the Brake Temperature Monitor advisory if a discrepancy is observed. During climb, the pilot monitoring should confirm the Autobrake Selector selector position before the next phase of flight.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Hydraulic System B quantity display        | 35 units     | Advisory only          |
| Fuel Crossfeed indication                  | 75 units     | Advisory only          |
| Cockpit Voice Recorder selector position   | 70 units     | Advisory only          |
| Stall Warning advisory                     | 3 units      | Refer to related topic |
| Cargo Smoke Detection selector position    | 95 units     | Refer to related topic |
| Brake Temperature Monitor quantity display | 88 units     | Normal                 |

### 02.10.2 General Limitation 2

During approach, the First Officer should verify the Fire Detection Loop status message when the associated caution light remains illuminated. The pilot monitoring will select any change in the Landing Gear Indication quantity display and advise the other pilot if the indication does not stabilize within the sample interval. During parking, the relief pilot should record the Thrust Reverser selector position once the checklist item is complete. During a maintenance-requested ground run, the First Officer should confirm the Flight Management Computer indication when conditions permit.

- If the Hydraulic System B is inoperative, continue approach only after both pilots has reviewed the associated sample guidance.
- The Primary Electrical Bus selector position is expected to read within the sample range of 49 to 56 units during engine start.
- The pilot monitoring will announce any change in the Cabin Pressure Controller switch position and advise the other pilot if the indication does not stabilize within the sample interval.
- The Auxiliary Power Unit quantity display that differs from the expected state requires the pilot flying to confirm the condition when conditions permit.
- The Flap Position Indication quantity display is expected to read within the sample range of 77 to 89 units during cruise.

| Condition                            | Sample value | Remarks                |
|--------------------------------------|--------------|------------------------|
| Nosewheel Steering selector position | 56 units     | Refer to related topic |
| Standby Hydraulic advisory           | 52 units     | Normal                 |

|                                           |          |               |
|-------------------------------------------|----------|---------------|
| Nosewheel Steering selector position      | 8 units  | Advisory only |
| Cargo Smoke Detection annunciation        | 14 units | Advisory only |
| Brake Temperature Monitor switch position | 68 units | Monitor       |
| Auxiliary Power Unit annunciation         | 34 units | Advisory only |
| Fuel Crossfeed switch position            | 28 units | Advisory only |

If the Oxygen Distribution is inoperative, continue cruise only after the Captain has reviewed the associated sample guidance. If the Brake Temperature Monitor is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance. The Standby Instruments quantity display is expected to read within the sample range of 31 to 40 units during a diversion. Refer to the related topic for additional sample context. Both pilots will announce any change in the Cabin Pressure Controller indication and advise the other pilot once the checklist item is complete. During a turnaround, the relief pilot should verify the Thrust Reverser quantity display before the next phase of flight.

**NOTE:** The wording here is placeholder content shaped like a procedure, not a procedure. The wording here is placeholder content shaped like a procedure, not a procedure.

The Traffic Advisory Display advisory is expected to read within the sample range of 77 to 85 units during cruise. The captain will record any change in the Wing Anti-Ice selector position and advise the other pilot before the next phase of flight. The Brake Temperature Monitor switch position that differs from the expected state requires the First Officer to verify the condition once the checklist item is complete.

**NOTE:** The first officer will cross-check any change in the Engine Anti-Ice annunciation and advise the other pilot if the indication does not stabilize within the sample interval. The pilot monitoring will cross-check any change in the Autobrake Selector status message and advise the other pilot if the indication does not stabilize within the sample interval.

### 02.10.3 General Limitation 3

The pilot monitoring will brief any change in the Cabin Pressure Controller indication and advise the other pilot unless directed otherwise by the Sample Operations Center. The Flight Management Computer quantity display is expected to read within the sample range of 52 to 57 units during approach. The first officer will announce any change in the Traffic Advisory Display selector position and advise the other pilot if the indication does not stabilize within the sample interval.

- If the Primary Electrical Bus is inoperative, continue engine start only after both pilots has reviewed the associated sample guidance.
- The Standby Instruments quantity display that differs from the expected state requires the pilot monitoring to select the condition when conditions permit.
- The relief pilot will record any change in the Fire Detection Loop quantity display and advise the other pilot if the indication does not stabilize within the sample interval.
- The captain will announce any change in the Auxiliary Power Unit advisory and advise the other pilot once the checklist item is complete.
- The Traffic Advisory Display switch position that differs from the expected state requires the pilot monitoring to confirm the condition if the indication does not stabilize within the sample interval.

The Autopilot Channel A annunciation is expected to read within the sample range of 28 to 33 units during descent. The pilot monitoring will monitor any change in the Standby Hydraulic quantity display and advise the other pilot once the checklist item is complete. Values in this manual are invented and must not be used for any operational purpose. Both pilots will record any change in the Pack Temperature Control annunciation and advise the other pilot once the checklist item is complete. If the Weather Radar is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a

procedure.

The Probe Heat quantity display is expected to read within the sample range of 12 to 23 units during a maintenance-requested ground run. The wording here is placeholder content shaped like a procedure, not a procedure. The Speedbrake Handle status message is expected to read within the sample range of 92 to 99 units during a diversion. Refer to the related topic for additional sample context. The Standby Instruments advisory is expected to read within the sample range of 96 to 100 units during cruise.

**CAUTION:** Refer to the related topic for additional sample context. The relief pilot will monitor any change in the Hydraulic System A status message and advise the other pilot unless directed otherwise by the Sample Operations Center.

**02.10.4 General Limitation 4**

The pilot monitoring will select any change in the Cabin Pressure Controller quantity display and advise the other pilot when operating at a sample station without ground power. The Window Heat switch position is expected to read within the sample range of 93 to 101 units during preflight. The Fire Detection Loop selector position that differs from the expected state requires the pilot monitoring to verify the condition once the checklist item is complete. This text is fictional and exists only to give the prototype realistic volume and structure. The wording here is placeholder content shaped like a procedure, not a procedure.

**NOTE:** If the Cabin Pressure Controller is inoperative, continue engine start only after the relief pilot has reviewed the associated sample guidance.

**CAUTION:** If the Fire Detection Loop is inoperative, continue descent only after the First Officer has reviewed the associated sample guidance.

The Landing Gear Indication quantity display is expected to read within the sample range of 68 to 73 units during descent. The Wing Anti-Ice selector position is expected to read within the sample range of 80 to 85 units during engine start. The Wing Anti-Ice status message is expected to read within the sample range of 5 to 14 units during a diversion. During takeoff, the relief pilot should cross-check the Probe Heat quantity display before the next phase of flight. The Probe Heat annunciation that differs from the expected state requires the pilot monitoring to cross-check the condition before the next phase of flight.

**NOTE:** The Center Tank Pumps selector position is expected to read within the sample range of 16 to 24 units during taxi.

**NOTE:** The Transponder selector position is expected to read within the sample range of 29 to 39 units during preflight. The Hydraulic System B annunciation that differs from the expected state requires the pilot monitoring to monitor the condition if the indication does not stabilize within the sample interval.

If the Traffic Advisory Display is inoperative, continue climb only after the First Officer has reviewed the associated sample guidance. During parking, both pilots should brief the Bleed Air Supply annunciation when conditions permit. During descent, the pilot flying should brief the Traffic Advisory Display indication when the associated caution light remains illuminated. The Stall Warning advisory that differs from the expected state requires the pilot monitoring to announce the condition when operating at a sample station without ground power. If the Autothrottle is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance. During landing, the relief pilot should record the Speedbrake Handle annunciation when conditions permit.

If the Autopilot Channel B is inoperative, continue landing only after both pilots has reviewed the associated sample guidance. The Weather Radar switch position that differs from the expected state requires the pilot flying to record the condition when operating at a sample station without ground power. If the Flap Position Indication is inoperative, continue a maintenance-requested ground run only after the pilot flying has reviewed the associated sample guidance. If the Transponder is inoperative, continue a diversion only after the relief pilot has reviewed the associated sample guidance.

| Condition                      | Sample value | Remarks |
|--------------------------------|--------------|---------|
| Thrust Reverser status message | 50 units     | Normal  |

|                                    |          |                        |
|------------------------------------|----------|------------------------|
| Weather Radar selector position    | 97 units | Normal                 |
| Speedbrake Handle quantity display | 18 units | Advisory only          |
| Cabin Pressure Controller advisory | 87 units | Monitor                |
| Speedbrake Handle annunciation     | 31 units | Refer to related topic |
| Wing Anti-Ice advisory             | 12 units | Monitor                |
| Probe Heat status message          | 46 units | Normal                 |

### 02.10.5 General Limitation 5

If the Autopilot Channel B is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance. The first officer will verify any change in the Pack Temperature Control advisory and advise the other pilot once the checklist item is complete. If the Thrust Reverser is inoperative, continue approach only after the relief pilot has reviewed the associated sample guidance. The Cockpit Voice Recorder status message is expected to read within the sample range of 10 to 14 units during parking.

The relief pilot will monitor any change in the Flap Position Indication quantity display and advise the other pilot when operating at a sample station without ground power. The Bleed Air Supply indication is expected to read within the sample range of 15 to 19 units during a maintenance-requested ground run. The Engine Anti-Ice quantity display that differs from the expected state requires the Captain to monitor the condition if the indication does not stabilize within the sample interval. During parking, the First Officer should record the Bleed Air Supply quantity display when the associated caution light remains illuminated. The Primary Electrical Bus selector position that differs from the expected state requires the pilot flying to announce the condition if a discrepancy is observed. If the Ground Proximity Monitor is inoperative, continue climb only after both pilots has reviewed the associated sample guidance.

- The Cabin Pressure Controller indication is expected to read within the sample range of 17 to 24 units during climb.
- The Wing Anti-Ice selector position is expected to read within the sample range of 20 to 28 units during a turnaround.
- The Autopilot Channel B quantity display is expected to read within the sample range of 59 to 63 units during descent.

**CAUTION:** If the Autopilot Channel A is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance.

If the Pack Temperature Control is inoperative, continue engine start only after the Captain has reviewed the associated sample guidance. The Landing Gear Indication annunciation is expected to read within the sample range of 83 to 87 units during taxi. The captain will select any change in the Traffic Advisory Display selector position and advise the other pilot if a discrepancy is observed. The relief pilot will verify any change in the Oxygen Distribution switch position and advise the other pilot once the checklist item is complete. During a maintenance-requested ground run, the Captain should cross-check the Center Tank Pumps advisory when operating at a sample station without ground power.

The wording here is placeholder content shaped like a procedure, not a procedure. This text is fictional and exists only to give the prototype realistic volume and structure. The Transponder quantity display is expected to read within the sample range of 70 to 76 units during approach. See 06.20.9 Stall Warning Overview.

### 02.10.6 General Limitation 6

The Hydraulic System A quantity display is expected to read within the sample range of 41 to 45 units during takeoff. During an extended ground delay, the pilot flying should record the Hydraulic System A advisory unless directed otherwise by the Sample Operations Center. The Autopilot Channel B status message is expected to read within the sample range of 73 to 77 units during parking.

**CAUTION:** If the Hydraulic System A is inoperative, continue engine start only after the relief pilot has reviewed the associated sample guidance. During parking, both pilots should cross-check the Nosewheel Steering annunciation if a discrepancy is observed.

If the Standby Hydraulic is inoperative, continue cruise only after the Captain has reviewed the associated sample guidance. Refer to the related topic for additional sample context. The relief pilot will confirm any change in the Autothrottle switch position and advise the other pilot when conditions permit.

**NOTE:** If the Traffic Advisory Display is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance. The Cabin Pressure Controller selector position is expected to read within the sample range of 86 to 94 units during a turnaround.

The wording here is placeholder content shaped like a procedure, not a procedure. During preflight, the First Officer should monitor the Transponder selector position when conditions permit. The Cargo Smoke Detection advisory is expected to read within the sample range of 49 to 57 units during cruise. The Hydraulic System A quantity display is expected to read within the sample range of 85 to 90 units during landing. The Hydraulic System A selector position that differs from the expected state requires the First Officer to verify the condition unless directed otherwise by the Sample Operations Center. The wording here is placeholder content shaped like a procedure, not a procedure.

### 02.10.7 General Limitation 7

The Wing Anti-Ice quantity display that differs from the expected state requires the pilot flying to record the condition when conditions permit. If the Thrust Reverser is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance. If the Transponder is inoperative, continue climb only after the relief pilot has reviewed the associated sample guidance.

**NOTE:** The Traffic Advisory Display status message is expected to read within the sample range of 34 to 40 units during cruise.

The Wing Anti-Ice selector position is expected to read within the sample range of 13 to 17 units during a turnaround. The Transponder quantity display that differs from the expected state requires the relief pilot to record the condition when operating at a sample station without ground power. During a turnaround, the pilot flying should monitor the Flight Management Computer indication once the checklist item is complete.

The wording here is placeholder content shaped like a procedure, not a procedure. The wording here is placeholder content shaped like a procedure, not a procedure. If the Thrust Reverser is inoperative, continue parking only after the relief pilot has reviewed the associated sample guidance. Both pilots will verify any change in the Center Tank Pumps advisory and advise the other pilot unless directed otherwise by the Sample Operations Center. Values in this manual are invented and must not be used for any operational purpose. The pilot monitoring will verify any change in the Pack Temperature Control selector position and advise the other pilot when the associated caution light remains illuminated.

If the Center Tank Pumps is inoperative, continue a maintenance-requested ground run only after the Captain has reviewed the associated sample guidance. The pilot monitoring will cross-check any change in the Ground Proximity Monitor annunciation and advise the other pilot if a discrepancy is observed. The captain will confirm any change in the Fuel Crossfeed advisory and advise the other pilot when conditions permit. The Standby Hydraulic quantity display is expected to read within the sample range of 20 to 24 units during descent. The Transponder status message is expected to read within the sample range of 59 to 71 units during a diversion.

If the Brake Temperature Monitor is inoperative, continue a diversion only after the First Officer has reviewed the associated sample guidance. The first officer will select any change in the Weather Radar annunciation and advise the other pilot if the indication does not stabilize within the sample interval. During approach, the relief pilot should cross-check the Cockpit Voice Recorder advisory if a discrepancy is observed. This text is fictional and exists only to give the prototype realistic volume and structure. Values in this manual are invented and must not be used for any operational purpose.

**CAUTION:** Values in this manual are invented and must not be used for any operational purpose.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Standby Instruments status message    | 93 units     | Advisory only          |
| Probe Heat status message             | 97 units     | Monitor                |
| Bleed Air Supply quantity display     | 69 units     | Advisory only          |
| Pack Temperature Control advisory     | 27 units     | Refer to related topic |
| Landing Gear Indication annunciation  | 96 units     | Normal                 |
| Auxiliary Power Unit quantity display | 1 units      | Refer to related topic |
| Probe Heat selector position          | 1 units      | Monitor                |

During engine start, the pilot monitoring should select the Probe Heat switch position if the indication does not stabilize within the sample interval. The Primary Electrical Bus selector position is expected to read within the sample range of 53 to 61 units during a turnaround. The Wing Anti-Ice quantity display is expected to read within the sample range of 69 to 76 units during an extended ground delay. The Nosewheel Steering advisory that differs from the expected state requires the Captain to cross-check the condition unless directed otherwise by the Sample Operations Center. See 02.30.7 Airspeed Limitation 7.

### 02.10.8 General Limitation 8

Refer to the related topic for additional sample context. The Transponder status message that differs from the expected state requires the First Officer to record the condition if a discrepancy is observed. During approach, the First Officer should verify the Standby Hydraulic status message when the associated caution light remains illuminated. During cruise, the relief pilot should announce the Autothrottle switch position before the next phase of flight.

During cruise, the pilot flying should confirm the Autothrottle selector position once the checklist item is complete. The first officer will cross-check any change in the Landing Gear Indication advisory and advise the other pilot when the associated caution light remains illuminated. If the Flight Management Computer is inoperative, continue taxi only after the pilot flying has reviewed the associated sample guidance. The pilot flying will brief any change in the Bleed Air Supply quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center. The Autopilot Channel A status message is expected to read within the sample range of 3 to 11 units during approach.

**NOTE:** This text is fictional and exists only to give the prototype realistic volume and structure. The Stall Warning quantity display is expected to read within the sample range of 21 to 31 units during approach.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Speedbrake Handle status message        | 35 units     | Advisory only          |
| Autopilot Channel A indication          | 62 units     | Normal                 |
| Fuel Crossfeed switch position          | 96 units     | Normal                 |
| Speedbrake Handle switch position       | 56 units     | Monitor                |
| Standby Hydraulic quantity display      | 68 units     | Refer to related topic |
| Transponder annunciation                | 96 units     | Normal                 |
| Flap Position Indication status message | 24 units     | Refer to related topic |

- The relief pilot will brief any change in the Autopilot Channel A switch position and advise the other pilot when operating at a sample station without ground power.
- Refer to the related topic for additional sample context.
- If the Autothrottle is inoperative, continue parking only after the Captain has reviewed the associated sample guidance.



- During climb, both pilots should verify the Engine Anti-Ice switch position unless directed otherwise by the Sample Operations Center.
- The Autobrake Selector status message that differs from the expected state requires the pilot monitoring to select the condition when operating at a sample station without ground power.

### 02.10.9 General Limitation 9

The Brake Temperature Monitor quantity display is expected to read within the sample range of 56 to 65 units during cruise. The Autobrake Selector status message that differs from the expected state requires the pilot flying to brief the condition when conditions permit. If the Autopilot Channel B is inoperative, continue descent only after both pilots has reviewed the associated sample guidance.

The Landing Gear Indication selector position is expected to read within the sample range of 7 to 13 units during taxi. The Center Tank Pumps advisory is expected to read within the sample range of 94 to 100 units during engine start. During cruise, the pilot flying should monitor the Pack Temperature Control indication once the checklist item is complete. The captain will cross-check any change in the Autopilot Channel A advisory and advise the other pilot when the associated caution light remains illuminated.

- The wording here is placeholder content shaped like a procedure, not a procedure.
- The Window Heat indication is expected to read within the sample range of 75 to 78 units during parking.
- During climb, the Captain should record the Pack Temperature Control switch position when conditions permit.
- Both pilots will confirm any change in the Autopilot Channel A quantity display and advise the other pilot when conditions permit.

**NOTE:** The Hydraulic System B indication that differs from the expected state requires both pilots to select the condition if a discrepancy is observed.

**CAUTION:** If the Speedbrake Handle is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance.

If the Flight Management Computer is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance. During taxi, the relief pilot should announce the Hydraulic System B annunciation when conditions permit. During a turnaround, the First Officer should select the Brake Temperature Monitor switch position once the checklist item is complete. Refer to the related topic for additional sample context. The relief pilot will verify any change in the Probe Heat annunciation and advise the other pilot when conditions permit. During an extended ground delay, the First Officer should announce the Autobrake Selector advisory once the checklist item is complete.

### 02.10.10 General Limitation 10

During climb, the pilot monitoring should confirm the Speedbrake Handle advisory before the next phase of flight. If the Window Heat is inoperative, continue taxi only after the Captain has reviewed the associated sample guidance. During an extended ground delay, the pilot monitoring should select the Engine Anti-Ice selector position once the checklist item is complete. During a maintenance-requested ground run, the pilot monitoring should verify the Standby Instruments quantity display when operating at a sample station without ground power.

If the Stall Warning is inoperative, continue preflight only after the pilot monitoring has reviewed the associated sample guidance. If the Fire Detection Loop is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance. The Engine Anti-Ice status message is expected to read within the sample range of 73 to 76 units during preflight. If the Flap Position Indication is inoperative, continue taxi only after the pilot flying has reviewed the associated sample guidance.

Refer to the related topic for additional sample context. Values in this manual are invented and must not be used for any operational purpose. The Weather Radar status message that differs from the expected state requires the pilot monitoring to brief the condition when conditions permit. During cruise, both pilots should select the Brake Temperature Monitor advisory if a discrepancy is observed.



If the Stall Warning is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance. During descent, the Captain should announce the Pack Temperature Control annunciation when the associated caution light remains illuminated. Refer to the related topic for additional sample context.

**NOTE:** The Ground Proximity Monitor annunciation is expected to read within the sample range of 70 to 73 units during engine start. If the Pack Temperature Control is inoperative, continue descent only after both pilots has reviewed the associated sample guidance.

**NOTE:** The Window Heat indication is expected to read within the sample range of 37 to 44 units during a maintenance-requested ground run.

**02.10.11 General Limitation 11**

The Fire Detection Loop selector position that differs from the expected state requires the relief pilot to brief the condition when the associated caution light remains illuminated. If the Brake Temperature Monitor is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance. If the Bleed Air Supply is inoperative, continue taxi only after both pilots has reviewed the associated sample guidance. The Auxiliary Power Unit status message that differs from the expected state requires the pilot flying to brief the condition once the checklist item is complete.

**CAUTION:** During approach, the relief pilot should verify the Cockpit Voice Recorder advisory unless directed otherwise by the Sample Operations Center.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Ground Proximity Monitor status message | 71 units     | Monitor                |
| Bleed Air Supply annunciation           | 96 units     | Normal                 |
| Weather Radar switch position           | 72 units     | Normal                 |
| Hydraulic System B quantity display     | 36 units     | Normal                 |
| Cargo Smoke Detection switch position   | 61 units     | Normal                 |
| Oxygen Distribution indication          | 47 units     | Refer to related topic |

- Values in this manual are invented and must not be used for any operational purpose.
- The Hydraulic System A annunciation that differs from the expected state requires the pilot monitoring to cross-check the condition if the indication does not stabilize within the sample interval.
- If the Ground Proximity Monitor is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance.
- This text is fictional and exists only to give the prototype realistic volume and structure.

**NOTE:** If the Fire Detection Loop is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance. The Cabin Pressure Controller selector position is expected to read within the sample range of 42 to 54 units during cruise.

**CAUTION:** Refer to the related topic for additional sample context.

- The wording here is placeholder content shaped like a procedure, not a procedure.
- During a diversion, the Captain should announce the Standby Hydraulic quantity display unless directed otherwise by the Sample Operations Center.
- The captain will record any change in the Autobrake Selector advisory and advise the other pilot when conditions permit.

During a diversion, both pilots should confirm the Pack Temperature Control switch position once the checklist item is complete. If the Standby Hydraulic is inoperative, continue parking only after both pilots has reviewed the associated sample guidance. The Hydraulic System A advisory is expected to read within the sample range of 32 to 38 units during a diversion. The pilot flying will cross-check any change in the Cabin Pressure Controller advisory and advise the other pilot if a discrepancy is observed. During cruise, the pilot monitoring should select the Standby Instruments quantity display unless directed otherwise by the Sample Operations Center. Both pilots will verify any change in the Nosewheel Steering indication and advise the other pilot if the indication does not stabilize within the sample interval.

If the Engine Anti-Ice is inoperative, continue approach only after the Captain has reviewed the associated sample guidance. If the Cargo Smoke Detection is inoperative, continue a turnaround only after the First Officer has reviewed the associated sample guidance. The Ground Proximity Monitor quantity display is expected to read within the sample range of 2 to 14 units during approach.

### **02.10.12 General Limitation 12**

The Bleed Air Supply quantity display that differs from the expected state requires the relief pilot to confirm the condition when conditions permit. The Autothrottle advisory is expected to read within the sample range of 11 to 23 units during cruise. The Transponder quantity display is expected to read within the sample range of 3 to 6 units during climb.

**CAUTION:** If the Autopilot Channel B is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance.

**CAUTION:** The pilot flying will select any change in the Auxiliary Power Unit annunciation and advise the other pilot when conditions permit. The Ground Proximity Monitor status message that differs from the expected state requires the pilot monitoring to brief the condition if a discrepancy is observed.

The Engine Anti-Ice quantity display is expected to read within the sample range of 69 to 78 units during a maintenance-requested ground run. The relief pilot will monitor any change in the Traffic Advisory Display advisory and advise the other pilot when conditions permit. The first officer will record any change in the Probe Heat switch position and advise the other pilot unless directed otherwise by the Sample Operations Center. If the Cabin Pressure Controller is inoperative, continue descent only after both pilots has reviewed the associated sample guidance.

**NOTE:** If the Speedbrake Handle is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance. During a diversion, the pilot monitoring should record the Fuel Crossfeed advisory once the checklist item is complete.

**NOTE:** The first officer will cross-check any change in the Auxiliary Power Unit advisory and advise the other pilot if a discrepancy is observed.

This text is fictional and exists only to give the prototype realistic volume and structure. The Autothrottle advisory that differs from the expected state requires the relief pilot to select the condition if the indication does not stabilize within the sample interval. If the Transponder is inoperative, continue a turnaround only after the pilot monitoring has reviewed the associated sample guidance.

### **02.10.13 General Limitation 13**

Refer to the related topic for additional sample context. The pilot monitoring will announce any change in the Auxiliary Power Unit annunciation and advise the other pilot when operating at a sample station without ground power. Values in this manual are invented and must not be used for any operational purpose. The first officer will monitor any change in the Brake Temperature Monitor annunciation and advise the other pilot before the next phase of flight. Refer to the related topic for additional sample context.

This text is fictional and exists only to give the prototype realistic volume and structure. The pilot monitoring will verify any change in the Bleed Air Supply indication and advise the other pilot once the checklist item is complete. The Weather Radar selector position is expected to read within the sample range of 72 to 81 units during takeoff. The pilot flying will monitor any change in the Traffic Advisory Display status message and advise the other pilot when conditions permit. The Autopilot Channel B indication is expected to read within the sample range of 37 to 43 units

during engine start.

Refer to the related topic for additional sample context. If the Ground Proximity Monitor is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. The Autobrake Selector annunciation is expected to read within the sample range of 24 to 33 units during engine start. During preflight, the pilot monitoring should brief the Stall Warning selector position once the checklist item is complete. If the Fuel Crossfeed is inoperative, continue preflight only after the pilot monitoring has reviewed the associated sample guidance.

**CAUTION:** The pilot flying will announce any change in the Cabin Pressure Controller status message and advise the other pilot when the associated caution light remains illuminated. If the Window Heat is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Cabin Pressure Controller quantity display | 95 units     | Refer to related topic |
| Engine Anti-Ice status message             | 8 units      | Normal                 |
| Weather Radar advisory                     | 56 units     | Monitor                |
| Landing Gear Indication switch position    | 57 units     | Advisory only          |
| Standby Instruments quantity display       | 16 units     | Advisory only          |
| Cargo Smoke Detection status message       | 52 units     | Refer to related topic |
| Stall Warning annunciation                 | 52 units     | Normal                 |

During landing, the First Officer should cross-check the Cabin Pressure Controller quantity display when operating at a sample station without ground power. During a turnaround, the relief pilot should verify the Stall Warning quantity display once the checklist item is complete. The Cockpit Voice Recorder annunciation is expected to read within the sample range of 59 to 65 units during descent. Refer to the related topic for additional sample context. The Center Tank Pumps quantity display that differs from the expected state requires the pilot flying to verify the condition when operating at a sample station without ground power. The first officer will brief any change in the Cargo Smoke Detection selector position and advise the other pilot when operating at a sample station without ground power.

## 02.20 Weight Limitations

### 02.20.1 Weight Limitation 1

If the Autopilot Channel B is inoperative, continue a turnaround only after the pilot monitoring has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. The Landing Gear Indication indication that differs from the expected state requires the relief pilot to brief the condition before the next phase of flight. During a maintenance-requested ground run, both pilots should record the Autopilot Channel B switch position if a discrepancy is observed. The Center Tank Pumps advisory that differs from the expected state requires the pilot flying to record the condition when operating at a sample station without ground power. If the Stall Warning is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance.

During a turnaround, the First Officer should monitor the Cockpit Voice Recorder annunciation if the indication does not stabilize within the sample interval. This text is fictional and exists only to give the prototype realistic volume and structure. Refer to the related topic for additional sample context. The Autopilot Channel B selector position is expected to read within the sample range of 87 to 92 units during takeoff. The Thrust Reverser indication is expected to read within the sample range of 97 to 107 units during a maintenance-requested ground run.

The Autopilot Channel B switch position is expected to read within the sample range of 11 to 14 units during an extended ground delay. If the Transponder is inoperative, continue approach only after the relief pilot has reviewed the associated sample guidance. The Brake Temperature Monitor indication is expected to read within the sample range of 95 to 99 units during a diversion. Values in this manual are invented and must not be used for any

operational purpose.

- The Weather Radar selector position that differs from the expected state requires the relief pilot to record the condition unless directed otherwise by the Sample Operations Center.
- The captain will select any change in the Center Tank Pumps status message and advise the other pilot before the next phase of flight.
- If the Hydraulic System B is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance.
- The Brake Temperature Monitor quantity display that differs from the expected state requires the First Officer to announce the condition unless directed otherwise by the Sample Operations Center.
- During a maintenance-requested ground run, the relief pilot should record the Cargo Smoke Detection indication if a discrepancy is observed.
- If the Cabin Pressure Controller is inoperative, continue takeoff only after both pilots has reviewed the associated sample guidance.

If the Flap Position Indication is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance. If the Weather Radar is inoperative, continue a maintenance-requested ground run only after the pilot flying has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. The Landing Gear Indication annunciation is expected to read within the sample range of 4 to 16 units during parking. During a maintenance-requested ground run, the pilot monitoring should select the Window Heat advisory if a discrepancy is observed.

## 02.20.2 Weight Limitation 2

The captain will announce any change in the Autobrake Selector quantity display and advise the other pilot if the indication does not stabilize within the sample interval. If the Standby Instruments is inoperative, continue landing only after the Captain has reviewed the associated sample guidance. The Autopilot Channel B quantity display that differs from the expected state requires the relief pilot to announce the condition when operating at a sample station without ground power. The Cockpit Voice Recorder selector position is expected to read within the sample range of 52 to 55 units during climb. The first officer will cross-check any change in the Stall Warning switch position and advise the other pilot when the associated caution light remains illuminated.

**NOTE:** The Cabin Pressure Controller selector position is expected to read within the sample range of 12 to 23 units during approach. The wording here is placeholder content shaped like a procedure, not a procedure.

During a maintenance-requested ground run, the pilot flying should announce the Landing Gear Indication selector position once the checklist item is complete. This text is fictional and exists only to give the prototype realistic volume and structure. During a turnaround, the relief pilot should cross-check the Fuel Crossfeed indication if a discrepancy is observed. Both pilots will monitor any change in the Hydraulic System B annunciation and advise the other pilot once the checklist item is complete.

**CAUTION:** During an extended ground delay, the Captain should cross-check the Probe Heat annunciation when conditions permit.

The wording here is placeholder content shaped like a procedure, not a procedure. If the Cargo Smoke Detection is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance. The Speedbrake Handle selector position is expected to read within the sample range of 58 to 62 units during landing. This text is fictional and exists only to give the prototype realistic volume and structure. If the Auxiliary Power Unit is inoperative, continue parking only after the Captain has reviewed the associated sample guidance.

**NOTE:** This text is fictional and exists only to give the prototype realistic volume and structure.

- If the Flight Management Computer is inoperative, continue taxi only after both pilots has reviewed the associated sample guidance.

- During parking, the pilot flying should confirm the Auxiliary Power Unit indication unless directed otherwise by the Sample Operations Center.
- The Traffic Advisory Display selector position is expected to read within the sample range of 61 to 69 units during approach.
- The Pack Temperature Control advisory that differs from the expected state requires the pilot monitoring to brief the condition if the indication does not stabilize within the sample interval.
- During an extended ground delay, the First Officer should cross-check the Autopilot Channel B quantity display unless directed otherwise by the Sample Operations Center.
- If the Flap Position Indication is inoperative, continue engine start only after the pilot monitoring has reviewed the associated sample guidance.

**02.20.3 Weight Limitation 3**

The wording here is placeholder content shaped like a procedure, not a procedure. Refer to the related topic for additional sample context. During engine start, the First Officer should record the Fire Detection Loop switch position if a discrepancy is observed. The relief pilot will record any change in the Autobrake Selector annunciation and advise the other pilot before the next phase of flight. The Fire Detection Loop indication is expected to read within the sample range of 94 to 101 units during parking. See 04.10.2 Flow: Engine Anti-Ice.

**CAUTION:** If the Auxiliary Power Unit is inoperative, continue preflight only after the relief pilot has reviewed the associated sample guidance.

- Both pilots will record any change in the Probe Heat advisory and advise the other pilot unless directed otherwise by the Sample Operations Center.
- The pilot monitoring will select any change in the Cargo Smoke Detection quantity display and advise the other pilot before the next phase of flight.
- The Engine Anti-Ice quantity display is expected to read within the sample range of 79 to 88 units during takeoff.

**CAUTION:** The first officer will select any change in the Cabin Pressure Controller status message and advise the other pilot before the next phase of flight.

**CAUTION:** During climb, the pilot monitoring should cross-check the Hydraulic System B advisory when the associated caution light remains illuminated.

**02.20.4 Weight Limitation 4**

Refer to the related topic for additional sample context. The Wing Anti-Ice indication is expected to read within the sample range of 63 to 72 units during descent. The Standby Hydraulic advisory that differs from the expected state requires both pilots to record the condition once the checklist item is complete.

**NOTE:** This text is fictional and exists only to give the prototype realistic volume and structure.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Traffic Advisory Display advisory         | 78 units     | Advisory only          |
| Flap Position Indication quantity display | 53 units     | Normal                 |
| Engine Anti-Ice annunciation              | 82 units     | Refer to related topic |
| Speedbrake Handle switch position         | 88 units     | Refer to related topic |
| Hydraulic System B switch position        | 37 units     | Monitor                |
| Bleed Air Supply selector position        | 43 units     | Monitor                |

- The pilot flying will announce any change in the Hydraulic System A status message and advise the other pilot before the next phase of flight.
- If the Auxiliary Power Unit is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance.
- During preflight, both pilots should monitor the Auxiliary Power Unit selector position before the next phase of flight.
- The Center Tank Pumps indication that differs from the expected state requires the relief pilot to cross-check the condition when conditions permit.
- The Window Heat status message is expected to read within the sample range of 79 to 84 units during approach.

**NOTE:** Values in this manual are invented and must not be used for any operational purpose. The Hydraulic System A annunciation is expected to read within the sample range of 97 to 100 units during a maintenance-requested ground run.

**CAUTION:** If the Traffic Advisory Display is inoperative, continue engine start only after the pilot flying has reviewed the associated sample guidance.

**CAUTION:** Refer to the related topic for additional sample context.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Primary Electrical Bus switch position   | 62 units     | Advisory only          |
| Cabin Pressure Controller status message | 80 units     | Refer to related topic |
| Standby Instruments quantity display     | 37 units     | Monitor                |
| Fire Detection Loop status message       | 31 units     | Normal                 |

**CAUTION:** The Wing Anti-Ice status message is expected to read within the sample range of 98 to 103 units during takeoff. During cruise, both pilots should announce the Thrust Reverser selector position when the associated caution light remains illuminated.

### 02.20.5 Weight Limitation 5

The Speedbrake Handle indication is expected to read within the sample range of 6 to 11 units during approach. The Transponder advisory that differs from the expected state requires both pilots to monitor the condition once the checklist item is complete. This text is fictional and exists only to give the prototype realistic volume and structure.

- If the Cargo Smoke Detection is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance.
- If the Probe Heat is inoperative, continue taxi only after the Captain has reviewed the associated sample guidance.
- The Autopilot Channel B advisory that differs from the expected state requires the First Officer to announce the condition once the checklist item is complete.
- The wording here is placeholder content shaped like a procedure, not a procedure.

The Stall Warning quantity display that differs from the expected state requires the pilot flying to record the condition before the next phase of flight. The Hydraulic System B status message that differs from the expected state requires the Captain to select the condition if the indication does not stabilize within the sample interval. The wording here is placeholder content shaped like a procedure, not a procedure. The Speedbrake Handle advisory is expected to read within the sample range of 82 to 87 units during preflight. The wording here is placeholder content shaped like a procedure, not a procedure.

| Condition | Sample value | Remarks |
|-----------|--------------|---------|
|-----------|--------------|---------|



|                                        |          |                        |
|----------------------------------------|----------|------------------------|
| Cabin Pressure Controller annunciation | 71 units | Advisory only          |
| Fuel Crossfeed status message          | 53 units | Refer to related topic |
| Hydraulic System B annunciation        | 81 units | Advisory only          |
| Autothrottle annunciation              | 87 units | Advisory only          |
| Fuel Crossfeed indication              | 69 units | Advisory only          |
| Cargo Smoke Detection quantity display | 72 units | Advisory only          |
| Flight Management Computer indication  | 55 units | Monitor                |

| Condition                       | Sample value | Remarks                |
|---------------------------------|--------------|------------------------|
| Standby Hydraulic indication    | 56 units     | Advisory only          |
| Autobrake Selector indication   | 16 units     | Monitor                |
| Weather Radar selector position | 46 units     | Refer to related topic |
| Weather Radar annunciation      | 55 units     | Advisory only          |
| Wing Anti-Ice advisory          | 53 units     | Normal                 |
| Thrust Reverser indication      | 31 units     | Advisory only          |

The Nosewheel Steering indication is expected to read within the sample range of 51 to 58 units during a diversion. The Bleed Air Supply indication is expected to read within the sample range of 34 to 45 units during takeoff. The Thrust Reverser annunciation is expected to read within the sample range of 78 to 87 units during preflight.

The Nosewheel Steering annunciation that differs from the expected state requires the relief pilot to verify the condition if a discrepancy is observed. The Autopilot Channel B annunciation is expected to read within the sample range of 70 to 75 units during preflight. During engine start, the Captain should verify the Nosewheel Steering advisory when the associated caution light remains illuminated. If the Window Heat is inoperative, continue landing only after the pilot monitoring has reviewed the associated sample guidance. Both pilots will confirm any change in the Window Heat indication and advise the other pilot if the indication does not stabilize within the sample interval.

**NOTE:** During takeoff, the First Officer should confirm the Flap Position Indication quantity display once the checklist item is complete.

The captain will verify any change in the Hydraulic System A status message and advise the other pilot if the indication does not stabilize within the sample interval. Values in this manual are invented and must not be used for any operational purpose. Both pilots will announce any change in the Pack Temperature Control annunciation and advise the other pilot if the indication does not stabilize within the sample interval. During climb, the First Officer should announce the Cargo Smoke Detection advisory if a discrepancy is observed.

### 02.20.6 Weight Limitation 6

The Window Heat annunciation is expected to read within the sample range of 13 to 18 units during approach. Values in this manual are invented and must not be used for any operational purpose. If the Oxygen Distribution is inoperative, continue engine start only after the Captain has reviewed the associated sample guidance.

**NOTE:** During descent, the First Officer should cross-check the Transponder advisory when conditions permit. During cruise, the relief pilot should select the Speedbrake Handle annunciation before the next phase of flight.

**NOTE:** During climb, the Captain should select the Cargo Smoke Detection indication if the indication does not stabilize within the sample interval.

The Stall Warning quantity display that differs from the expected state requires both pilots to verify the condition when operating at a sample station without ground power. The pilot monitoring will confirm any change in the Fire Detection Loop switch position and advise the other pilot once the checklist item is complete. Values in this manual are invented and must not be used for any operational purpose. The Bleed Air Supply switch position that differs from the expected state requires the pilot flying to verify the condition once the checklist item is complete. Values in this manual are

invented and must not be used for any operational purpose.

**CAUTION:** The Thrust Reverser switch position that differs from the expected state requires the First Officer to record the condition when conditions permit.

The Primary Electrical Bus status message is expected to read within the sample range of 20 to 30 units during landing. The wording here is placeholder content shaped like a procedure, not a procedure. The captain will cross-check any change in the Ground Proximity Monitor selector position and advise the other pilot when conditions permit. Refer to the related topic for additional sample context. The Traffic Advisory Display switch position is expected to read within the sample range of 97 to 104 units during taxi. The Center Tank Pumps selector position is expected to read within the sample range of 10 to 21 units during a maintenance-requested ground run.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Traffic Advisory Display annunciation | 53 units     | Normal                 |
| Probe Heat status message             | 82 units     | Refer to related topic |
| Autopilot Channel A indication        | 52 units     | Advisory only          |
| Autothrottle advisory                 | 68 units     | Monitor                |

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Auxiliary Power Unit selector position  | 52 units     | Normal                 |
| Weather Radar selector position         | 24 units     | Monitor                |
| Center Tank Pumps selector position     | 82 units     | Refer to related topic |
| Flight Management Computer indication   | 10 units     | Advisory only          |
| Flap Position Indication status message | 75 units     | Monitor                |
| Window Heat selector position           | 83 units     | Normal                 |

The Fire Detection Loop quantity display is expected to read within the sample range of 20 to 26 units during a diversion. The pilot flying will announce any change in the Autopilot Channel A quantity display and advise the other pilot if a discrepancy is observed. The Engine Anti-Ice annunciation is expected to read within the sample range of 60 to 64 units during descent. The Engine Anti-Ice advisory that differs from the expected state requires the pilot flying to cross-check the condition if the indication does not stabilize within the sample interval. See 19.40.5 Fuel Planning Data Table 5.

02.20.7 Weight Limitation 7

If the Oxygen Distribution is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance. If the Hydraulic System B is inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance. During takeoff, both pilots should record the Nosewheel Steering indication when the associated caution light remains illuminated. Refer to the related topic for additional sample context. If the Engine Anti-Ice is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance. Both pilots will verify any change in the Flight Management Computer switch position and advise the other pilot once the checklist item is complete.

During preflight, the Captain should cross-check the Engine Anti-Ice advisory if a discrepancy is observed. During landing, the pilot flying should announce the Auxiliary Power Unit advisory once the checklist item is complete. The wording here is placeholder content shaped like a procedure, not a procedure. During taxi, the First Officer should monitor the Standby Hydraulic indication when conditions permit. The captain will brief any change in the Center Tank Pumps annunciation and advise the other pilot if the indication does not stabilize within the sample interval.

The Flap Position Indication annunciation is expected to read within the sample range of 25 to 36 units during a turnaround. During parking, the Captain should announce the Wing Anti-Ice status message if a discrepancy is observed. The wording here is placeholder content shaped like a procedure, not a procedure. During approach, the pilot monitoring should verify the Auxiliary Power Unit quantity display if a discrepancy is observed.

**CAUTION:** During cruise, the First Officer should record the Center Tank Pumps selector position if a discrepancy is observed. The Cockpit Voice Recorder selector position is expected to read within the sample range of 8 to 18 units during takeoff.

**NOTE:** The Cargo Smoke Detection status message is expected to read within the sample range of 15 to 22 units during a turnaround. The Fire Detection Loop switch position is expected to read within the sample range of 95 to 101 units during an extended ground delay.

- The Cockpit Voice Recorder advisory is expected to read within the sample range of 29 to 40 units during landing.
- The Brake Temperature Monitor switch position is expected to read within the sample range of 54 to 62 units during a diversion.
- The Transponder annunciation is expected to read within the sample range of 49 to 52 units during descent.
- During an extended ground delay, the relief pilot should announce the Autopilot Channel B selector position if the indication does not stabilize within the sample interval.
- If the Hydraulic System B is inoperative, continue a maintenance-requested ground run only after the pilot monitoring has reviewed the associated sample guidance.
- This text is fictional and exists only to give the prototype realistic volume and structure.

**CAUTION:** The captain will announce any change in the Autopilot Channel A indication and advise the other pilot before the next phase of flight.

### 02.20.8 Weight Limitation 8

Refer to the related topic for additional sample context. The pilot flying will record any change in the Thrust Reverser switch position and advise the other pilot when operating at a sample station without ground power. Refer to the related topic for additional sample context. The pilot flying will confirm any change in the Pack Temperature Control indication and advise the other pilot when conditions permit.

The Auxiliary Power Unit indication that differs from the expected state requires the pilot flying to announce the condition once the checklist item is complete. During parking, the pilot flying should record the Oxygen Distribution quantity display unless directed otherwise by the Sample Operations Center. If the Transponder is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance. If the Hydraulic System A is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance.

During parking, the relief pilot should verify the Pack Temperature Control indication unless directed otherwise by the Sample Operations Center. Values in this manual are invented and must not be used for any operational purpose. The relief pilot will confirm any change in the Nosewheel Steering indication and advise the other pilot if a discrepancy is observed. If the Flap Position Indication is inoperative, continue climb only after the Captain has reviewed the associated sample guidance. The Hydraulic System A annunciation is expected to read within the sample range of 35 to 40 units during landing.

During a diversion, the Captain should cross-check the Autobrake Selector indication when conditions permit. The pilot flying will announce any change in the Cargo Smoke Detection status message and advise the other pilot before the next phase of flight. The wording here is placeholder content shaped like a procedure, not a procedure.

- If the Flight Management Computer is inoperative, continue descent only after both pilots has reviewed the associated sample guidance.
- If the Standby Hydraulic is inoperative, continue engine start only after the pilot monitoring has reviewed the associated sample guidance.
- During a turnaround, both pilots should brief the Flap Position Indication advisory once the checklist item is complete.
- If the Autothrottle is inoperative, continue approach only after the Captain has reviewed the associated sample guidance.

- The Window Heat selector position is expected to read within the sample range of 3 to 11 units during preflight.
- During climb, the First Officer should confirm the Autopilot Channel A selector position unless directed otherwise by the Sample Operations Center.

| Condition                          | Sample value | Remarks                |
|------------------------------------|--------------|------------------------|
| Cabin Pressure Controller advisory | 16 units     | Advisory only          |
| Autopilot Channel A annunciation   | 71 units     | Normal                 |
| Center Tank Pumps indication       | 31 units     | Advisory only          |
| Autopilot Channel B status message | 86 units     | Monitor                |
| Center Tank Pumps advisory         | 92 units     | Refer to related topic |
| Transponder switch position        | 88 units     | Advisory only          |
| Weather Radar status message       | 41 units     | Refer to related topic |

If the Standby Hydraulic is inoperative, continue a maintenance-requested ground run only after both pilots has reviewed the associated sample guidance. During a turnaround, the First Officer should cross-check the Flight Management Computer quantity display when operating at a sample station without ground power. During approach, the pilot flying should announce the Transponder indication before the next phase of flight. This text is fictional and exists only to give the prototype realistic volume and structure.

### 02.20.9 Weight Limitation 9

Values in this manual are invented and must not be used for any operational purpose. During a turnaround, the pilot monitoring should monitor the Window Heat selector position before the next phase of flight. During engine start, the First Officer should verify the Autothrottle advisory when operating at a sample station without ground power. During a turnaround, the pilot flying should monitor the Speedbrake Handle annunciation if a discrepancy is observed. If the Hydraulic System A is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance.

The pilot flying will verify any change in the Cabin Pressure Controller selector position and advise the other pilot unless directed otherwise by the Sample Operations Center. The first officer will monitor any change in the Autopilot Channel B switch position and advise the other pilot when operating at a sample station without ground power. The Ground Proximity Monitor selector position that differs from the expected state requires the relief pilot to confirm the condition once the checklist item is complete. The Autothrottle status message is expected to read within the sample range of 66 to 76 units during parking. If the Autopilot Channel B is inoperative, continue a diversion only after the First Officer has reviewed the associated sample guidance. The Standby Instruments advisory is expected to read within the sample range of 12 to 17 units during descent.

- The Fuel Crossfeed switch position is expected to read within the sample range of 52 to 60 units during preflight.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The Autopilot Channel A switch position that differs from the expected state requires both pilots to select the condition when operating at a sample station without ground power.

The Engine Anti-Ice status message is expected to read within the sample range of 21 to 28 units during landing. This text is fictional and exists only to give the prototype realistic volume and structure. The Standby Instruments advisory that differs from the expected state requires the pilot flying to confirm the condition before the next phase of flight.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Flight Management Computer status message | 82 units     | Refer to related topic |
| Auxiliary Power Unit annunciation         | 95 units     | Refer to related topic |
| Cabin Pressure Controller annunciation    | 87 units     | Normal                 |

|                                            |          |                        |
|--------------------------------------------|----------|------------------------|
| Fuel Crossfeed annunciation                | 68 units | Monitor                |
| Nosewheel Steering indication              | 82 units | Refer to related topic |
| Flight Management Computer switch position | 95 units | Normal                 |

If the Hydraulic System B is inoperative, continue approach only after the pilot monitoring has reviewed the associated sample guidance. During engine start, the Captain should record the Brake Temperature Monitor switch position unless directed otherwise by the Sample Operations Center. The Standby Hydraulic annunciation that differs from the expected state requires the Captain to monitor the condition unless directed otherwise by the Sample Operations Center. See 15.30.15 Cargo Smoke Detection Reset Guidance.

### 02.20.10 Weight Limitation 10

During takeoff, the pilot monitoring should announce the Fire Detection Loop quantity display once the checklist item is complete. The Hydraulic System A switch position that differs from the expected state requires both pilots to monitor the condition when operating at a sample station without ground power. The Ground Proximity Monitor quantity display that differs from the expected state requires the First Officer to monitor the condition when operating at a sample station without ground power. The Cockpit Voice Recorder selector position is expected to read within the sample range of 18 to 29 units during takeoff.

The Window Heat status message is expected to read within the sample range of 21 to 29 units during climb. The Engine Anti-Ice status message that differs from the expected state requires both pilots to select the condition when the associated caution light remains illuminated. During takeoff, the relief pilot should select the Hydraulic System B switch position if the indication does not stabilize within the sample interval.

The first officer will brief any change in the Ground Proximity Monitor quantity display and advise the other pilot when conditions permit. The captain will record any change in the Ground Proximity Monitor status message and advise the other pilot if the indication does not stabilize within the sample interval. During parking, the First Officer should confirm the Engine Anti-Ice status message once the checklist item is complete. The Flap Position Indication status message that differs from the expected state requires the pilot monitoring to confirm the condition when operating at a sample station without ground power. If the Engine Anti-Ice is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance.

**CAUTION:** The Weather Radar switch position is expected to read within the sample range of 15 to 20 units during taxi. The Flap Position Indication status message that differs from the expected state requires the Captain to brief the condition when conditions permit.

The Cockpit Voice Recorder quantity display that differs from the expected state requires the pilot monitoring to monitor the condition when conditions permit. Both pilots will confirm any change in the Engine Anti-Ice selector position and advise the other pilot before the next phase of flight. During engine start, the relief pilot should verify the Cabin Pressure Controller switch position unless directed otherwise by the Sample Operations Center. The pilot monitoring will select any change in the Nosewheel Steering annunciation and advise the other pilot if a discrepancy is observed. During climb, the First Officer should cross-check the Pack Temperature Control selector position when the associated caution light remains illuminated. Refer to the related topic for additional sample context.

**CAUTION:** The Traffic Advisory Display status message is expected to read within the sample range of 69 to 74 units during engine start.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Window Heat annunciation              | 14 units     | Monitor                |
| Standby Hydraulic switch position     | 93 units     | Refer to related topic |
| Nosewheel Steering annunciation       | 56 units     | Monitor                |
| Brake Temperature Monitor indication  | 35 units     | Monitor                |
| Cockpit Voice Recorder status message | 49 units     | Advisory only          |

## 02.30 Airspeed Limitations

### 02.30.1 Airspeed Limitation 1

The Flap Position Indication selector position that differs from the expected state requires the pilot flying to confirm the condition unless directed otherwise by the Sample Operations Center. The Cabin Pressure Controller advisory is expected to read within the sample range of 30 to 40 units during descent. If the Autopilot Channel A is inoperative, continue parking only after the pilot monitoring has reviewed the associated sample guidance. The Primary Electrical Bus advisory that differs from the expected state requires both pilots to record the condition once the checklist item is complete. During climb, the First Officer should cross-check the Cockpit Voice Recorder indication once the checklist item is complete. The Traffic Advisory Display switch position is expected to read within the sample range of 35 to 43 units during engine start.

The Autopilot Channel B switch position is expected to read within the sample range of 65 to 75 units during a diversion. The captain will announce any change in the Cockpit Voice Recorder selector position and advise the other pilot when operating at a sample station without ground power. The Auxiliary Power Unit indication is expected to read within the sample range of 48 to 53 units during parking.

**CAUTION:** The Cockpit Voice Recorder indication is expected to read within the sample range of 77 to 82 units during takeoff. During taxi, the Captain should confirm the Transponder quantity display unless directed otherwise by the Sample Operations Center.

If the Wing Anti-Ice is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance. The Auxiliary Power Unit annunciation is expected to read within the sample range of 50 to 57 units during an extended ground delay. The first officer will verify any change in the Traffic Advisory Display status message and advise the other pilot before the next phase of flight. The Window Heat switch position is expected to read within the sample range of 97 to 107 units during a maintenance-requested ground run. The first officer will announce any change in the Cargo Smoke Detection switch position and advise the other pilot unless directed otherwise by the Sample Operations Center. The Auxiliary Power Unit quantity display that differs from the expected state requires the First Officer to verify the condition if the indication does not stabilize within the sample interval.

The relief pilot will record any change in the Auxiliary Power Unit advisory and advise the other pilot if a discrepancy is observed. The Nosewheel Steering switch position that differs from the expected state requires the pilot flying to confirm the condition if a discrepancy is observed. The Weather Radar annunciation that differs from the expected state requires the relief pilot to brief the condition if a discrepancy is observed. During climb, the First Officer should record the Oxygen Distribution status message if a discrepancy is observed. The wording here is placeholder content shaped like a procedure, not a procedure. The Fire Detection Loop quantity display is expected to read within the sample range of 25 to 36 units during an extended ground delay. See 10.20.16 Brake Temperature Monitor Test.

- During a maintenance-requested ground run, the relief pilot should monitor the Landing Gear Indication advisory once the checklist item is complete.
- The Cargo Smoke Detection annunciation that differs from the expected state requires the pilot monitoring to confirm the condition before the next phase of flight.
- The pilot flying will cross-check any change in the Nosewheel Steering indication and advise the other pilot before the next phase of flight.
- The Auxiliary Power Unit advisory is expected to read within the sample range of 7 to 16 units during approach.

**NOTE:** The Cockpit Voice Recorder status message that differs from the expected state requires the pilot monitoring to monitor the condition when operating at a sample station without ground power.

### 02.30.2 Airspeed Limitation 2

The Traffic Advisory Display switch position is expected to read within the sample range of 40 to 43 units during approach. Values in this manual are invented and must not be used for any operational purpose. The wording here is



placeholder content shaped like a procedure, not a procedure.

The Landing Gear Indication advisory is expected to read within the sample range of 73 to 79 units during parking. During approach, the Captain should announce the Ground Proximity Monitor advisory once the checklist item is complete. If the Nosewheel Steering is inoperative, continue climb only after both pilots has reviewed the associated sample guidance. The Hydraulic System B advisory that differs from the expected state requires the First Officer to cross-check the condition when conditions permit. If the Nosewheel Steering is inoperative, continue cruise only after the First Officer has reviewed the associated sample guidance.

**CAUTION:** The Landing Gear Indication quantity display is expected to read within the sample range of 43 to 49 units during climb.

The Brake Temperature Monitor status message that differs from the expected state requires the Captain to monitor the condition if the indication does not stabilize within the sample interval. Refer to the related topic for additional sample context. The Engine Anti-Ice advisory is expected to read within the sample range of 4 to 9 units during engine start.

The Landing Gear Indication status message is expected to read within the sample range of 64 to 68 units during a diversion. If the Center Tank Pumps is inoperative, continue climb only after the First Officer has reviewed the associated sample guidance. During taxi, the Captain should confirm the Probe Heat quantity display once the checklist item is complete.

### 02.30.3 *Airspeed Limitation 3*

If the Wing Anti-Ice is inoperative, continue landing only after the pilot monitoring has reviewed the associated sample guidance. The first officer will announce any change in the Center Tank Pumps indication and advise the other pilot if the indication does not stabilize within the sample interval. The wording here is placeholder content shaped like a procedure, not a procedure.

- The Autopilot Channel A indication is expected to read within the sample range of 90 to 98 units during approach.
- If the Cabin Pressure Controller is inoperative, continue a maintenance-requested ground run only after the pilot flying has reviewed the associated sample guidance.
- The Flap Position Indication annunciation that differs from the expected state requires the pilot monitoring to cross-check the condition unless directed otherwise by the Sample Operations Center.

The Autobrake Selector switch position is expected to read within the sample range of 60 to 70 units during taxi. The Center Tank Pumps switch position is expected to read within the sample range of 64 to 75 units during a maintenance-requested ground run. The pilot flying will cross-check any change in the Flight Management Computer switch position and advise the other pilot unless directed otherwise by the Sample Operations Center.

**NOTE:** The pilot monitoring will record any change in the Transponder quantity display and advise the other pilot when the associated caution light remains illuminated.

**CAUTION:** The Standby Instruments selector position is expected to read within the sample range of 13 to 24 units during approach. During an extended ground delay, the First Officer should verify the Fuel Crossfeed advisory if the indication does not stabilize within the sample interval.

- The Brake Temperature Monitor status message that differs from the expected state requires the pilot monitoring to announce the condition if a discrepancy is observed.
- The Ground Proximity Monitor status message that differs from the expected state requires the pilot monitoring to verify the condition if a discrepancy is observed.
- During a maintenance-requested ground run, both pilots should monitor the Primary Electrical Bus selector position once the checklist item is complete.
- During parking, the pilot flying should confirm the Oxygen Distribution indication when conditions permit.

02.30.4    *Airspeed Limitation 4*

If the Cabin Pressure Controller is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance. Both pilots will brief any change in the Landing Gear Indication switch position and advise the other pilot if a discrepancy is observed. The Flap Position Indication indication is expected to read within the sample range of 68 to 74 units during landing.

- The Oxygen Distribution annunciation is expected to read within the sample range of 26 to 31 units during a diversion.
- The Thrust Reverser advisory is expected to read within the sample range of 92 to 102 units during landing.
- The first officer will record any change in the Cockpit Voice Recorder annunciation and advise the other pilot when the associated caution light remains illuminated.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- If the Window Heat is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance.

| Condition                             | Sample value | Remarks       |
|---------------------------------------|--------------|---------------|
| Ground Proximity Monitor annunciation | 15 units     | Normal        |
| Auxiliary Power Unit annunciation     | 84 units     | Monitor       |
| Transponder quantity display          | 69 units     | Advisory only |
| Nosewheel Steering quantity display   | 41 units     | Normal        |
| Nosewheel Steering selector position  | 65 units     | Monitor       |
| Cargo Smoke Detection switch position | 19 units     | Advisory only |
| Cargo Smoke Detection indication      | 7 units      | Monitor       |

**NOTE:** The Bleed Air Supply switch position is expected to read within the sample range of 62 to 67 units during a turnaround. The Brake Temperature Monitor indication is expected to read within the sample range of 30 to 42 units during parking.

**CAUTION:** Values in this manual are invented and must not be used for any operational purpose.

The Center Tank Pumps indication is expected to read within the sample range of 59 to 65 units during an extended ground delay. The captain will announce any change in the Flight Management Computer advisory and advise the other pilot once the checklist item is complete. Values in this manual are invented and must not be used for any operational purpose. The first officer will cross-check any change in the Center Tank Pumps selector position and advise the other pilot before the next phase of flight.

- The Autobrake Selector indication that differs from the expected state requires the relief pilot to brief the condition when conditions permit.
- If the Brake Temperature Monitor is inoperative, continue landing only after both pilots has reviewed the associated sample guidance.
- Values in this manual are invented and must not be used for any operational purpose.

The Cabin Pressure Controller selector position is expected to read within the sample range of 63 to 68 units during a turnaround. The Autopilot Channel A annunciation that differs from the expected state requires the Captain to confirm the condition if the indication does not stabilize within the sample interval. The wording here is placeholder content shaped like a procedure, not a procedure. If the Brake Temperature Monitor is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance.

Refer to the related topic for additional sample context. This text is fictional and exists only to give the prototype realistic volume and structure. If the Probe Heat is inoperative, continue preflight only after the relief pilot has

reviewed the associated sample guidance. Refer to the related topic for additional sample context.

### 02.30.5 *Airspeed Limitation 5*

During parking, the Captain should brief the Cockpit Voice Recorder advisory if the indication does not stabilize within the sample interval. Refer to the related topic for additional sample context. The Standby Hydraulic selector position that differs from the expected state requires the Captain to cross-check the condition if the indication does not stabilize within the sample interval. The relief pilot will confirm any change in the Ground Proximity Monitor selector position and advise the other pilot before the next phase of flight. If the Autopilot Channel A is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance. If the Thrust Reverser is inoperative, continue an extended ground delay only after the Captain has reviewed the associated sample guidance.

| Condition                            | Sample value | Remarks                |
|--------------------------------------|--------------|------------------------|
| Engine Anti-Ice status message       | 54 units     | Advisory only          |
| Probe Heat quantity display          | 78 units     | Refer to related topic |
| Nosewheel Steering selector position | 91 units     | Advisory only          |
| Nosewheel Steering status message    | 55 units     | Advisory only          |
| Cargo Smoke Detection annunciation   | 92 units     | Normal                 |

The Fire Detection Loop switch position that differs from the expected state requires the pilot monitoring to verify the condition before the next phase of flight. The Speedbrake Handle status message that differs from the expected state requires the First Officer to record the condition when the associated caution light remains illuminated. Refer to the related topic for additional sample context. The captain will confirm any change in the Center Tank Pumps quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center. If the Fuel Crossfeed is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance.

The pilot flying will cross-check any change in the Bleed Air Supply advisory and advise the other pilot when the associated caution light remains illuminated. The Speedbrake Handle switch position is expected to read within the sample range of 31 to 41 units during taxi. During preflight, the pilot flying should announce the Hydraulic System A advisory if a discrepancy is observed. The Weather Radar selector position is expected to read within the sample range of 12 to 21 units during approach. The Brake Temperature Monitor advisory that differs from the expected state requires the pilot flying to confirm the condition when the associated caution light remains illuminated. The captain will select any change in the Flap Position Indication indication and advise the other pilot when the associated caution light remains illuminated.

If the Cockpit Voice Recorder is inoperative, continue takeoff only after the First Officer has reviewed the associated sample guidance. If the Pack Temperature Control is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance. The Cabin Pressure Controller advisory is expected to read within the sample range of 28 to 37 units during a maintenance-requested ground run. Refer to the related topic for additional sample context.

- The Autobrake Selector switch position is expected to read within the sample range of 75 to 78 units during a maintenance-requested ground run.
- During descent, the First Officer should monitor the Stall Warning status message when operating at a sample station without ground power.
- During parking, the pilot flying should confirm the Flap Position Indication switch position when operating at a sample station without ground power.
- The Stall Warning advisory that differs from the expected state requires the pilot monitoring to record the condition once the checklist item is complete.
- The Landing Gear Indication indication that differs from the expected state requires the First Officer to verify the condition before the next phase of flight.

If the Probe Heat is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance. During landing, the First Officer should confirm the Stall Warning selector position unless directed otherwise by the Sample Operations Center. If the Brake Temperature Monitor is inoperative, continue a maintenance-requested ground run only after the pilot monitoring has reviewed the associated sample guidance. The Bleed Air Supply switch position that differs from the expected state requires both pilots to confirm the condition when the associated caution light remains illuminated. The pilot flying will record any change in the Autothrottle indication and advise the other pilot when conditions permit. During takeoff, the pilot flying should announce the Autobrake Selector status message when the associated caution light remains illuminated.

The Nosewheel Steering status message that differs from the expected state requires the pilot flying to verify the condition when conditions permit. If the Bleed Air Supply is inoperative, continue approach only after the pilot flying has reviewed the associated sample guidance. The pilot flying will announce any change in the Thrust Reverser indication and advise the other pilot when the associated caution light remains illuminated. See 15.10.11 Weather Radar Overview.

**CAUTION:** The Landing Gear Indication annunciation that differs from the expected state requires the pilot monitoring to select the condition before the next phase of flight. If the Wing Anti-Ice is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance.

### 02.30.6 *Airspeed Limitation 6*

The Standby Hydraulic annunciation is expected to read within the sample range of 40 to 51 units during takeoff. The pilot monitoring will record any change in the Traffic Advisory Display annunciation and advise the other pilot before the next phase of flight. If the Engine Anti-Ice is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance. The pilot flying will record any change in the Hydraulic System A indication and advise the other pilot unless directed otherwise by the Sample Operations Center.

**NOTE:** The Transponder indication is expected to read within the sample range of 7 to 17 units during approach.

The first officer will brief any change in the Flight Management Computer advisory and advise the other pilot when the associated caution light remains illuminated. The Ground Proximity Monitor indication that differs from the expected state requires both pilots to confirm the condition if a discrepancy is observed. Values in this manual are invented and must not be used for any operational purpose. The Autopilot Channel B advisory that differs from the expected state requires the Captain to brief the condition when conditions permit.

The Fuel Crossfeed advisory that differs from the expected state requires both pilots to monitor the condition before the next phase of flight. If the Flight Management Computer is inoperative, continue climb only after the relief pilot has reviewed the associated sample guidance. The Standby Hydraulic indication that differs from the expected state requires the relief pilot to cross-check the condition when conditions permit.

**NOTE:** The Speedbrake Handle advisory is expected to read within the sample range of 46 to 58 units during taxi.

The pilot monitoring will confirm any change in the Auxiliary Power Unit indication and advise the other pilot before the next phase of flight. During taxi, the pilot flying should select the Bleed Air Supply quantity display when conditions permit. The Primary Electrical Bus status message is expected to read within the sample range of 57 to 63 units during a maintenance-requested ground run. Refer to the related topic for additional sample context. See 07.20.5 Fuel Crossfeed Test.

### 02.30.7 *Airspeed Limitation 7*

During takeoff, the relief pilot should confirm the Center Tank Pumps indication once the checklist item is complete. The Center Tank Pumps indication is expected to read within the sample range of 18 to 26 units during a turnaround. Values in this manual are invented and must not be used for any operational purpose. During approach, the relief pilot should monitor the Pack Temperature Control status message before the next phase of flight.

**NOTE:** During a maintenance-requested ground run, the pilot monitoring should record the Center Tank Pumps quantity display before the next phase of flight. The Probe Heat selector position is expected to read within the

sample range of 75 to 82 units during climb.

If the Autobrake Selector is inoperative, continue takeoff only after both pilots has reviewed the associated sample guidance. If the Autopilot Channel B is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance. The pilot monitoring will confirm any change in the Wing Anti-Ice switch position and advise the other pilot once the checklist item is complete. If the Flap Position Indication is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance.

**NOTE:** Both pilots will select any change in the Landing Gear Indication advisory and advise the other pilot when the associated caution light remains illuminated.

Refer to the related topic for additional sample context. The wording here is placeholder content shaped like a procedure, not a procedure. The Engine Anti-Ice quantity display is expected to read within the sample range of 50 to 58 units during a turnaround. The wording here is placeholder content shaped like a procedure, not a procedure. The Cockpit Voice Recorder advisory is expected to read within the sample range of 37 to 47 units during engine start. The Traffic Advisory Display annunciation that differs from the expected state requires the First Officer to record the condition if a discrepancy is observed. See 06.10.10 Cargo Smoke Detection Crew Awareness.

**CAUTION:** If the Speedbrake Handle is inoperative, continue cruise only after the Captain has reviewed the associated sample guidance. Refer to the related topic for additional sample context.

### 02.30.8 Airspeed Limitation 8

If the Transponder is inoperative, continue engine start only after the relief pilot has reviewed the associated sample guidance. The pilot flying will cross-check any change in the Standby Instruments switch position and advise the other pilot once the checklist item is complete. If the Transponder is inoperative, continue descent only after both pilots has reviewed the associated sample guidance. If the Auxiliary Power Unit is inoperative, continue landing only after the First Officer has reviewed the associated sample guidance.

The Nosewheel Steering annunciation that differs from the expected state requires the pilot flying to verify the condition when the associated caution light remains illuminated. Values in this manual are invented and must not be used for any operational purpose. During takeoff, the pilot monitoring should confirm the Auxiliary Power Unit selector position unless directed otherwise by the Sample Operations Center. During descent, the pilot flying should confirm the Pack Temperature Control indication if a discrepancy is observed. Both pilots will record any change in the Flap Position Indication advisory and advise the other pilot when the associated caution light remains illuminated.

**NOTE:** The relief pilot will record any change in the Autothrottle annunciation and advise the other pilot if the indication does not stabilize within the sample interval. Refer to the related topic for additional sample context.

**NOTE:** The Pack Temperature Control selector position is expected to read within the sample range of 82 to 85 units during landing. The pilot monitoring will select any change in the Primary Electrical Bus indication and advise the other pilot unless directed otherwise by the Sample Operations Center.

- This text is fictional and exists only to give the prototype realistic volume and structure.
- The Nosewheel Steering quantity display is expected to read within the sample range of 21 to 32 units during preflight.
- During a turnaround, the Captain should monitor the Fuel Crossfeed indication once the checklist item is complete.

The captain will announce any change in the Speedbrake Handle indication and advise the other pilot if a discrepancy is observed. The relief pilot will brief any change in the Autobrake Selector quantity display and advise the other pilot if a discrepancy is observed. If the Autopilot Channel A is inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance. The Cockpit Voice Recorder quantity display is expected to read within the sample range of 91 to 96 units during a turnaround. During engine start, the Captain should announce the Autothrottle status message if a discrepancy is observed. During taxi, the pilot flying should monitor the Brake Temperature Monitor quantity display when the associated caution light remains illuminated.

The Cabin Pressure Controller selector position that differs from the expected state requires the pilot monitoring to verify the condition when the associated caution light remains illuminated. The wording here is placeholder content shaped like a procedure, not a procedure. If the Window Heat is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance.

During approach, the pilot flying should confirm the Fire Detection Loop quantity display if a discrepancy is observed. Values in this manual are invented and must not be used for any operational purpose. If the Fuel Crossfeed is inoperative, continue a diversion only after the First Officer has reviewed the associated sample guidance. The pilot flying will announce any change in the Brake Temperature Monitor quantity display and advise the other pilot if a discrepancy is observed. The Fuel Crossfeed indication is expected to read within the sample range of 51 to 54 units during preflight. The wording here is placeholder content shaped like a procedure, not a procedure.

### **02.30.9 Airspeed Limitation 9**

If the Transponder is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance. The pilot flying will brief any change in the Autothrottle advisory and advise the other pilot when operating at a sample station without ground power. The Brake Temperature Monitor advisory that differs from the expected state requires the pilot flying to cross-check the condition unless directed otherwise by the Sample Operations Center. The wording here is placeholder content shaped like a procedure, not a procedure.

The Ground Proximity Monitor switch position that differs from the expected state requires the Captain to record the condition when the associated caution light remains illuminated. The Fire Detection Loop advisory is expected to read within the sample range of 4 to 10 units during engine start. The Cargo Smoke Detection status message is expected to read within the sample range of 68 to 77 units during an extended ground delay. The Flap Position Indication advisory is expected to read within the sample range of 85 to 97 units during parking. Refer to the related topic for additional sample context.

- The first officer will confirm any change in the Autopilot Channel A annunciation and advise the other pilot when conditions permit.
- If the Window Heat is inoperative, continue parking only after the relief pilot has reviewed the associated sample guidance.
- If the Ground Proximity Monitor is inoperative, continue parking only after the relief pilot has reviewed the associated sample guidance.
- During preflight, the relief pilot should brief the Oxygen Distribution indication unless directed otherwise by the Sample Operations Center.
- During an extended ground delay, both pilots should announce the Primary Electrical Bus indication when conditions permit.
- The first officer will select any change in the Fuel Crossfeed selector position and advise the other pilot once the checklist item is complete.
- The Window Heat indication is expected to read within the sample range of 56 to 60 units during a maintenance-requested ground run.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- The relief pilot will monitor any change in the Thrust Reverser status message and advise the other pilot once the checklist item is complete.

The Stall Warning quantity display that differs from the expected state requires the pilot flying to confirm the condition if the indication does not stabilize within the sample interval. If the Autopilot Channel A is inoperative, continue approach only after the pilot monitoring has reviewed the associated sample guidance. The Bleed Air Supply quantity display is expected to read within the sample range of 68 to 73 units during engine start. This text is fictional and exists only to give the prototype realistic volume and structure. The Flight Management Computer indication that differs from the expected state requires the Captain to cross-check the condition unless directed otherwise by the



Sample Operations Center.

**NOTE:** The wording here is placeholder content shaped like a procedure, not a procedure.

**02.30.10    *Airspeed Limitation 10***

During a turnaround, the First Officer should select the Weather Radar status message when operating at a sample station without ground power. The Thrust Reverser switch position is expected to read within the sample range of 20 to 24 units during parking. The captain will record any change in the Stall Warning selector position and advise the other pilot if a discrepancy is observed. During a turnaround, the Captain should confirm the Standby Hydraulic status message when operating at a sample station without ground power. During takeoff, both pilots should cross-check the Standby Instruments quantity display when the associated caution light remains illuminated.

If the Cargo Smoke Detection is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance. The Probe Heat switch position that differs from the expected state requires the Captain to cross-check the condition when operating at a sample station without ground power. The Cabin Pressure Controller status message is expected to read within the sample range of 63 to 75 units during descent.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Cockpit Voice Recorder annunciation     | 18 units     | Normal                 |
| Standby Instruments quantity display    | 1 units      | Monitor                |
| Autopilot Channel B annunciation        | 24 units     | Normal                 |
| Landing Gear Indication switch position | 86 units     | Monitor                |
| Autopilot Channel B indication          | 83 units     | Refer to related topic |

| Condition                         | Sample value | Remarks                |
|-----------------------------------|--------------|------------------------|
| Autobrake Selector status message | 58 units     | Monitor                |
| Speedbrake Handle annunciation    | 75 units     | Refer to related topic |
| Thrust Reverser indication        | 61 units     | Normal                 |
| Probe Heat quantity display       | 69 units     | Normal                 |

Values in this manual are invented and must not be used for any operational purpose. The relief pilot will brief any change in the Nosewheel Steering quantity display and advise the other pilot when operating at a sample station without ground power. The Thrust Reverser selector position that differs from the expected state requires the relief pilot to record the condition once the checklist item is complete. The first officer will record any change in the Autopilot Channel B quantity display and advise the other pilot when conditions permit. During climb, the Captain should select the Traffic Advisory Display quantity display unless directed otherwise by the Sample Operations Center.

This text is fictional and exists only to give the prototype realistic volume and structure. During takeoff, the Captain should announce the Auxiliary Power Unit switch position once the checklist item is complete. If the Auxiliary Power Unit is inoperative, continue approach only after the First Officer has reviewed the associated sample guidance. If the Cockpit Voice Recorder is inoperative, continue cruise only after the Captain has reviewed the associated sample guidance. The pilot monitoring will verify any change in the Cockpit Voice Recorder selector position and advise the other pilot before the next phase of flight.

**NOTE:** If the Oxygen Distribution is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance.

- The pilot flying will record any change in the Fuel Crossfeed selector position and advise the other pilot if the indication does not stabilize within the sample interval.
- The Primary Electrical Bus switch position is expected to read within the sample range of 26 to 35 units during approach.

- The pilot flying will cross-check any change in the Hydraulic System B selector position and advise the other pilot when the associated caution light remains illuminated.
- The pilot flying will cross-check any change in the Brake Temperature Monitor quantity display and advise the other pilot if the indication does not stabilize within the sample interval.
- If the Standby Hydraulic is inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance.

**02.30.11    *Airspeed Limitation 11***

During engine start, the relief pilot should confirm the Cabin Pressure Controller advisory when the associated caution light remains illuminated. The Hydraulic System A status message that differs from the expected state requires both pilots to monitor the condition once the checklist item is complete. Values in this manual are invented and must not be used for any operational purpose. During taxi, the pilot flying should record the Autopilot Channel B indication before the next phase of flight. The Nosewheel Steering switch position is expected to read within the sample range of 71 to 78 units during a diversion.

**NOTE:** During cruise, the First Officer should cross-check the Brake Temperature Monitor annunciation once the checklist item is complete.

The first officer will announce any change in the Transponder status message and advise the other pilot when the associated caution light remains illuminated. Refer to the related topic for additional sample context. This text is fictional and exists only to give the prototype realistic volume and structure. If the Probe Heat is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance.

During cruise, the Captain should announce the Auxiliary Power Unit switch position if a discrepancy is observed. The Window Heat advisory is expected to read within the sample range of 55 to 65 units during taxi. This text is fictional and exists only to give the prototype realistic volume and structure. The Pack Temperature Control annunciation that differs from the expected state requires the relief pilot to cross-check the condition when conditions permit.

The Thrust Reverser annunciation is expected to read within the sample range of 58 to 66 units during parking. The first officer will record any change in the Autopilot Channel A status message and advise the other pilot if a discrepancy is observed. The relief pilot will announce any change in the Autopilot Channel B status message and advise the other pilot if the indication does not stabilize within the sample interval. The Thrust Reverser advisory that differs from the expected state requires both pilots to confirm the condition if the indication does not stabilize within the sample interval.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Center Tank Pumps quantity display    | 26 units     | Advisory only          |
| Autopilot Channel B advisory          | 77 units     | Advisory only          |
| Standby Hydraulic status message      | 61 units     | Refer to related topic |
| Hydraulic System A annunciation       | 86 units     | Normal                 |
| Standby Instruments selector position | 52 units     | Refer to related topic |
| Wing Anti-Ice advisory                | 21 units     | Monitor                |

**02.30.12    *Airspeed Limitation 12***

If the Probe Heat is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance. During cruise, the pilot monitoring should cross-check the Probe Heat annunciation when conditions permit. During landing, the Captain should monitor the Auxiliary Power Unit selector position before the next phase of flight.

- The Engine Anti-Ice indication is expected to read within the sample range of 53 to 62 units during takeoff.

- The captain will record any change in the Traffic Advisory Display quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center.
- Both pilots will select any change in the Window Heat status message and advise the other pilot if a discrepancy is observed.
- Values in this manual are invented and must not be used for any operational purpose.

| Condition                            | Sample value | Remarks                |
|--------------------------------------|--------------|------------------------|
| Weather Radar selector position      | 75 units     | Normal                 |
| Cargo Smoke Detection advisory       | 53 units     | Refer to related topic |
| Oxygen Distribution status message   | 15 units     | Advisory only          |
| Autobrake Selector status message    | 29 units     | Advisory only          |
| Hydraulic System A selector position | 65 units     | Normal                 |
| Engine Anti-Ice annunciation         | 26 units     | Normal                 |

During climb, the pilot flying should announce the Standby Instruments selector position if the indication does not stabilize within the sample interval. The Oxygen Distribution quantity display is expected to read within the sample range of 72 to 83 units during descent. The Engine Anti-Ice advisory is expected to read within the sample range of 61 to 71 units during takeoff. The Flap Position Indication advisory that differs from the expected state requires the First Officer to verify the condition unless directed otherwise by the Sample Operations Center.

- During preflight, the pilot flying should cross-check the Standby Instruments advisory before the next phase of flight.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The captain will monitor any change in the Hydraulic System A annunciation and advise the other pilot when the associated caution light remains illuminated.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Stall Warning status message              | 49 units     | Monitor                |
| Bleed Air Supply switch position          | 62 units     | Monitor                |
| Brake Temperature Monitor annunciation    | 70 units     | Refer to related topic |
| Window Heat indication                    | 48 units     | Monitor                |
| Brake Temperature Monitor switch position | 99 units     | Normal                 |
| Autothrottle switch position              | 82 units     | Refer to related topic |

If the Landing Gear Indication is inoperative, continue descent only after the pilot flying has reviewed the associated sample guidance. If the Brake Temperature Monitor is inoperative, continue taxi only after both pilots has reviewed the associated sample guidance. The pilot flying will brief any change in the Stall Warning annunciation and advise the other pilot once the checklist item is complete.

If the Cockpit Voice Recorder is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance. If the Probe Heat is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance. The Speedbrake Handle selector position that differs from the expected state requires the relief pilot to record the condition when the associated caution light remains illuminated. The Engine Anti-Ice annunciation that differs from the expected state requires the pilot flying to brief the condition when the associated caution light remains illuminated. See 06.10.4 Hydraulic System B Limits Display.

### 02.30.13 *Airspeed Limitation 13*

This text is fictional and exists only to give the prototype realistic volume and structure. The Speedbrake Handle status message is expected to read within the sample range of 40 to 49 units during cruise. The Engine Anti-Ice annunciation that differs from the expected state requires the relief pilot to brief the condition if the indication does not stabilize within the sample interval. The first officer will brief any change in the Fire Detection Loop status message and advise the other pilot if the indication does not stabilize within the sample interval.

If the Autopilot Channel B is inoperative, continue preflight only after the pilot monitoring has reviewed the associated sample guidance. If the Engine Anti-Ice is inoperative, continue a diversion only after the First Officer has reviewed the associated sample guidance. The relief pilot will verify any change in the Hydraulic System B annunciation and advise the other pilot if a discrepancy is observed. The Autopilot Channel B switch position that differs from the expected state requires the pilot flying to cross-check the condition if the indication does not stabilize within the sample interval.

- The Hydraulic System A selector position that differs from the expected state requires the pilot monitoring to cross-check the condition if a discrepancy is observed.
- The Cabin Pressure Controller selector position that differs from the expected state requires the Captain to record the condition when conditions permit.
- During landing, the relief pilot should confirm the Cockpit Voice Recorder switch position when conditions permit.
- The pilot flying will brief any change in the Ground Proximity Monitor indication and advise the other pilot unless directed otherwise by the Sample Operations Center.
- During a diversion, the pilot flying should monitor the Auxiliary Power Unit quantity display if a discrepancy is observed.
- If the Window Heat is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance.

**CAUTION:** If the Pack Temperature Control is inoperative, continue engine start only after both pilots has reviewed the associated sample guidance.

If the Hydraulic System B is inoperative, continue parking only after the Captain has reviewed the associated sample guidance. If the Autothrottle is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance. If the Autopilot Channel B is inoperative, continue descent only after the pilot flying has reviewed the associated sample guidance.

## 02.40 Systems Limitations

### 02.40.1 Cabin Pressure Controller Status Messages

The Transponder advisory is expected to read within the sample range of 87 to 97 units during approach. During landing, the relief pilot should confirm the Ground Proximity Monitor switch position if the indication does not stabilize within the sample interval. The Cockpit Voice Recorder quantity display that differs from the expected state requires the relief pilot to announce the condition when the associated caution light remains illuminated. If the Nosewheel Steering is inoperative, continue taxi only after the relief pilot has reviewed the associated sample guidance.

Both pilots will verify any change in the Traffic Advisory Display advisory and advise the other pilot once the checklist item is complete. The Probe Heat annunciation that differs from the expected state requires the First Officer to announce the condition when conditions permit. If the Fuel Crossfeed is inoperative, continue approach only after the relief pilot has reviewed the associated sample guidance. During taxi, the First Officer should monitor the Pack Temperature Control switch position when the associated caution light remains illuminated. If the Traffic Advisory Display is inoperative, continue engine start only after the pilot monitoring has reviewed the associated sample guidance. During a turnaround, the pilot flying should announce the Flap Position Indication quantity display when operating at a sample station without ground power.

| Condition | Sample value | Remarks |
|-----------|--------------|---------|
|-----------|--------------|---------|

|                                           |          |                        |
|-------------------------------------------|----------|------------------------|
| Hydraulic System B status message         | 85 units | Normal                 |
| Cargo Smoke Detection indication          | 28 units | Refer to related topic |
| Oxygen Distribution indication            | 90 units | Monitor                |
| Stall Warning status message              | 13 units | Monitor                |
| Brake Temperature Monitor switch position | 52 units | Refer to related topic |
| Flap Position Indication indication       | 27 units | Normal                 |
| Bleed Air Supply status message           | 67 units | Normal                 |

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Ground Proximity Monitor switch position | 11 units     | Normal                 |
| Engine Anti-Ice quantity display         | 46 units     | Monitor                |
| Autopilot Channel A quantity display     | 62 units     | Refer to related topic |
| Center Tank Pumps status message         | 30 units     | Normal                 |
| Cockpit Voice Recorder indication        | 70 units     | Refer to related topic |
| Flight Management Computer indication    | 71 units     | Advisory only          |

**NOTE:** The relief pilot will select any change in the Standby Hydraulic annunciation and advise the other pilot before the next phase of flight. The Standby Hydraulic status message that differs from the expected state requires the First Officer to monitor the condition unless directed otherwise by the Sample Operations Center.

**NOTE:** The Cargo Smoke Detection annunciation that differs from the expected state requires the relief pilot to record the condition before the next phase of flight.

### 02.40.2 Standby Hydraulic Interfaces

During engine start, both pilots should verify the Cabin Pressure Controller advisory before the next phase of flight. The relief pilot will confirm any change in the Center Tank Pumps advisory and advise the other pilot if a discrepancy is observed. The Autobrake Selector switch position is expected to read within the sample range of 29 to 41 units during takeoff. The captain will confirm any change in the Center Tank Pumps indication and advise the other pilot when operating at a sample station without ground power. The Hydraulic System B selector position is expected to read within the sample range of 76 to 80 units during engine start. If the Autopilot Channel A is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance.

If the Center Tank Pumps is inoperative, continue a diversion only after both pilots has reviewed the associated sample guidance. If the Engine Anti-Ice is inoperative, continue parking only after the relief pilot has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. Both pilots will cross-check any change in the Thrust Reverser indication and advise the other pilot when conditions permit. See 09.20.6 Engine Anti-Ice Status Messages.

- During takeoff, both pilots should verify the Ground Proximity Monitor advisory before the next phase of flight.
- During climb, the pilot flying should announce the Cockpit Voice Recorder quantity display if a discrepancy is observed.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- The Engine Anti-Ice quantity display is expected to read within the sample range of 82 to 86 units during an extended ground delay.
- If the Landing Gear Indication is inoperative, continue climb only after the pilot flying has reviewed the associated sample guidance.
- The Transponder annunciation is expected to read within the sample range of 34 to 44 units during preflight.

- If the Brake Temperature Monitor is inoperative, continue parking only after the Captain has reviewed the associated sample guidance.
- If the Traffic Advisory Display is inoperative, continue approach only after the pilot monitoring has reviewed the associated sample guidance.
- The Bleed Air Supply selector position that differs from the expected state requires both pilots to cross-check the condition when operating at a sample station without ground power.
- During engine start, the First Officer should select the Primary Electrical Bus advisory if a discrepancy is observed.
- The Center Tank Pumps switch position that differs from the expected state requires the pilot flying to record the condition if the indication does not stabilize within the sample interval.
- Refer to the related topic for additional sample context.
- The pilot monitoring will select any change in the Ground Proximity Monitor switch position and advise the other pilot before the next phase of flight.
- The Flight Management Computer annunciation that differs from the expected state requires both pilots to confirm the condition once the checklist item is complete.

**NOTE:** The Cabin Pressure Controller advisory is expected to read within the sample range of 8 to 12 units during preflight.

**NOTE:** The Flap Position Indication annunciation is expected to read within the sample range of 6 to 13 units during engine start. The Wing Anti-Ice quantity display is expected to read within the sample range of 16 to 24 units during an extended ground delay.

**02.40.3 Brake Temperature Monitor Test**

The Fire Detection Loop quantity display is expected to read within the sample range of 25 to 31 units during an extended ground delay. Both pilots will confirm any change in the Cockpit Voice Recorder selector position and advise the other pilot when conditions permit. If the Hydraulic System B is inoperative, continue parking only after the Captain has reviewed the associated sample guidance. The Autothrottle advisory that differs from the expected state requires both pilots to select the condition before the next phase of flight.

The Autobrake Selector selector position is expected to read within the sample range of 43 to 53 units during a maintenance-requested ground run. If the Oxygen Distribution is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance. During takeoff, the Captain should verify the Autothrottle indication once the checklist item is complete.

| Condition                           | Sample value | Remarks                |
|-------------------------------------|--------------|------------------------|
| Pack Temperature Control indication | 88 units     | Normal                 |
| Center Tank Pumps status message    | 25 units     | Refer to related topic |
| Standby Hydraulic switch position   | 80 units     | Normal                 |
| Thrust Reverser selector position   | 88 units     | Normal                 |

During parking, the Captain should monitor the Flap Position Indication annunciation unless directed otherwise by the Sample Operations Center. If the Wing Anti-Ice is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance. The Weather Radar annunciation that differs from the expected state requires the relief pilot to confirm the condition when the associated caution light remains illuminated.

The Fire Detection Loop quantity display that differs from the expected state requires both pilots to verify the condition before the next phase of flight. The Engine Anti-Ice advisory is expected to read within the sample range of 74 to 78 units during a diversion. During parking, both pilots should select the Standby Hydraulic annunciation when the



associated caution light remains illuminated. The Auxiliary Power Unit advisory is expected to read within the sample range of 51 to 61 units during an extended ground delay. Refer to the related topic for additional sample context.

During preflight, the First Officer should monitor the Hydraulic System A switch position unless directed otherwise by the Sample Operations Center. The Cabin Pressure Controller annunciation that differs from the expected state requires the pilot flying to confirm the condition when operating at a sample station without ground power. If the Traffic Advisory Display is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance. If the Cabin Pressure Controller is inoperative, continue descent only after the Captain has reviewed the associated sample guidance. During parking, both pilots should cross-check the Fire Detection Loop selector position when the associated caution light remains illuminated. The Engine Anti-Ice selector position is expected to read within the sample range of 96 to 99 units during cruise.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Probe Heat indication                   | 29 units     | Refer to related topic |
| Weather Radar annunciation              | 62 units     | Advisory only          |
| Standby Hydraulic status message        | 69 units     | Refer to related topic |
| Landing Gear Indication switch position | 26 units     | Normal                 |
| Nosewheel Steering annunciation         | 33 units     | Advisory only          |
| Engine Anti-Ice indication              | 94 units     | Monitor                |

02.40.4 Weather Radar Overview

If the Pack Temperature Control is inoperative, continue a turnaround only after the First Officer has reviewed the associated sample guidance. During a turnaround, both pilots should confirm the Standby Hydraulic indication before the next phase of flight. During takeoff, the relief pilot should record the Autothrottle advisory before the next phase of flight. The Stall Warning quantity display that differs from the expected state requires the Captain to brief the condition if the indication does not stabilize within the sample interval. The wording here is placeholder content shaped like a procedure, not a procedure. If the Hydraulic System B is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance.

The Cargo Smoke Detection annunciation that differs from the expected state requires the Captain to verify the condition when the associated caution light remains illuminated. During taxi, both pilots should brief the Brake Temperature Monitor switch position when the associated caution light remains illuminated. The relief pilot will cross-check any change in the Center Tank Pumps quantity display and advise the other pilot when conditions permit. If the Center Tank Pumps is inoperative, continue approach only after the Captain has reviewed the associated sample guidance. The captain will record any change in the Cockpit Voice Recorder indication and advise the other pilot unless directed otherwise by the Sample Operations Center. During climb, the pilot flying should verify the Bleed Air Supply status message when the associated caution light remains illuminated.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Thrust Reverser indication              | 74 units     | Monitor                |
| Flight Management Computer annunciation | 26 units     | Advisory only          |
| Ground Proximity Monitor status message | 3 units      | Monitor                |
| Speedbrake Handle quantity display      | 52 units     | Refer to related topic |
| Wing Anti-Ice selector position         | 80 units     | Normal                 |
| Cockpit Voice Recorder annunciation     | 11 units     | Refer to related topic |

**CAUTION:** The Bleed Air Supply status message that differs from the expected state requires both pilots to verify the condition when the associated caution light remains illuminated.

During takeoff, the relief pilot should verify the Primary Electrical Bus switch position when operating at a sample station without ground power. If the Hydraulic System A is inoperative, continue a maintenance-requested ground run

only after the relief pilot has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. The Autothrottle quantity display is expected to read within the sample range of 18 to 28 units during a diversion. The Bleed Air Supply annunciation that differs from the expected state requires the First Officer to monitor the condition when conditions permit.

#### **02.40.5 Center Tank Pumps Normal Operation**

The first officer will cross-check any change in the Landing Gear Indication quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center. The wording here is placeholder content shaped like a procedure, not a procedure. During takeoff, both pilots should cross-check the Primary Electrical Bus advisory when operating at a sample station without ground power. The pilot monitoring will cross-check any change in the Cockpit Voice Recorder status message and advise the other pilot when the associated caution light remains illuminated.

If the Weather Radar is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance. If the Wing Anti-Ice is inoperative, continue descent only after both pilots has reviewed the associated sample guidance. The Engine Anti-Ice quantity display that differs from the expected state requires the First Officer to record the condition when conditions permit. The wording here is placeholder content shaped like a procedure, not a procedure. If the Auxiliary Power Unit is inoperative, continue preflight only after the pilot monitoring has reviewed the associated sample guidance.

During descent, the pilot flying should announce the Brake Temperature Monitor advisory once the checklist item is complete. Both pilots will cross-check any change in the Oxygen Distribution annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center. The relief pilot will announce any change in the Autopilot Channel A switch position and advise the other pilot before the next phase of flight.

The relief pilot will cross-check any change in the Fire Detection Loop switch position and advise the other pilot before the next phase of flight. The wording here is placeholder content shaped like a procedure, not a procedure. Refer to the related topic for additional sample context.

If the Speedbrake Handle is inoperative, continue takeoff only after both pilots has reviewed the associated sample guidance. The Hydraulic System A switch position is expected to read within the sample range of 78 to 87 units during cruise. The Weather Radar status message that differs from the expected state requires the First Officer to monitor the condition when the associated caution light remains illuminated.

#### **02.40.6 Standby Hydraulic Limits Display**

During engine start, both pilots should brief the Cargo Smoke Detection selector position when operating at a sample station without ground power. The relief pilot will brief any change in the Hydraulic System A switch position and advise the other pilot before the next phase of flight. The captain will select any change in the Cockpit Voice Recorder quantity display and advise the other pilot if a discrepancy is observed. The first officer will brief any change in the Fire Detection Loop status message and advise the other pilot once the checklist item is complete.

- The pilot monitoring will announce any change in the Flight Management Computer indication and advise the other pilot when conditions permit.
- The relief pilot will confirm any change in the Probe Heat selector position and advise the other pilot when the associated caution light remains illuminated.
- The wording here is placeholder content shaped like a procedure, not a procedure.

The Cargo Smoke Detection advisory that differs from the expected state requires the Captain to select the condition when operating at a sample station without ground power. The Autopilot Channel B switch position is expected to read within the sample range of 16 to 26 units during takeoff. Refer to the related topic for additional sample context. Both pilots will confirm any change in the Weather Radar switch position and advise the other pilot if the indication does not stabilize within the sample interval. The Ground Proximity Monitor switch position that differs from the expected state requires the First Officer to brief the condition if a discrepancy is observed.

- The Hydraulic System B annunciation is expected to read within the sample range of 70 to 77 units during approach.
- The Cabin Pressure Controller indication that differs from the expected state requires the pilot monitoring to monitor the condition when operating at a sample station without ground power.
- During preflight, the relief pilot should cross-check the Engine Anti-Ice status message when conditions permit.
- The captain will brief any change in the Pack Temperature Control annunciation and advise the other pilot if a discrepancy is observed.
- Refer to the related topic for additional sample context.
- The first officer will cross-check any change in the Stall Warning advisory and advise the other pilot if the indication does not stabilize within the sample interval.
- Both pilots will select any change in the Wing Anti-Ice switch position and advise the other pilot before the next phase of flight.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- During an extended ground delay, the relief pilot should select the Hydraulic System B status message once the checklist item is complete.
- If the Speedbrake Handle is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance.

During a maintenance-requested ground run, the Captain should cross-check the Autopilot Channel A switch position when conditions permit. The Primary Electrical Bus annunciation that differs from the expected state requires the Captain to announce the condition unless directed otherwise by the Sample Operations Center. This text is fictional and exists only to give the prototype realistic volume and structure. If the Hydraulic System A is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance.

**02.40.7 Engine Anti-Ice Status Messages**

This text is fictional and exists only to give the prototype realistic volume and structure. This text is fictional and exists only to give the prototype realistic volume and structure. The Hydraulic System B selector position is expected to read within the sample range of 36 to 41 units during takeoff. The first officer will brief any change in the Landing Gear Indication quantity display and advise the other pilot if a discrepancy is observed.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Fire Detection Loop selector position      | 91 units     | Refer to related topic |
| Center Tank Pumps indication               | 42 units     | Monitor                |
| Ground Proximity Monitor selector position | 49 units     | Monitor                |
| Thrust Reverser indication                 | 78 units     | Monitor                |

**NOTE:** The Autothrottle status message is expected to read within the sample range of 22 to 34 units during approach. The Autopilot Channel B switch position that differs from the expected state requires the relief pilot to record the condition once the checklist item is complete.

- The Probe Heat selector position that differs from the expected state requires the pilot flying to announce the condition once the checklist item is complete.
- Both pilots will record any change in the Autobrake Selector advisory and advise the other pilot when conditions permit.
- During cruise, the First Officer should confirm the Cockpit Voice Recorder quantity display unless directed otherwise by the Sample Operations Center.

- The Hydraulic System A switch position is expected to read within the sample range of 49 to 52 units during climb.
- The Stall Warning annunciation that differs from the expected state requires the pilot flying to monitor the condition if a discrepancy is observed.

The Weather Radar advisory is expected to read within the sample range of 52 to 61 units during engine start. During approach, the pilot monitoring should record the Stall Warning quantity display before the next phase of flight. The first officer will confirm any change in the Flight Management Computer advisory and advise the other pilot before the next phase of flight.

**NOTE:** The Weather Radar switch position that differs from the expected state requires the pilot monitoring to record the condition before the next phase of flight. The first officer will announce any change in the Cargo Smoke Detection advisory and advise the other pilot once the checklist item is complete.

Refer to the related topic for additional sample context. The wording here is placeholder content shaped like a procedure, not a procedure. The wording here is placeholder content shaped like a procedure, not a procedure. The Fuel Crossfeed annunciation that differs from the expected state requires the relief pilot to select the condition before the next phase of flight. The pilot monitoring will confirm any change in the Pack Temperature Control quantity display and advise the other pilot when operating at a sample station without ground power.

#### **02.40.8 Fire Detection Loop Limits Display**

The Engine Anti-Ice switch position is expected to read within the sample range of 10 to 22 units during takeoff. The pilot flying will select any change in the Hydraulic System B quantity display and advise the other pilot if a discrepancy is observed. The Brake Temperature Monitor indication that differs from the expected state requires the pilot flying to confirm the condition if a discrepancy is observed. During takeoff, the First Officer should select the Fire Detection Loop switch position when the associated caution light remains illuminated.

The Auxiliary Power Unit selector position is expected to read within the sample range of 73 to 80 units during climb. If the Center Tank Pumps is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance. The Center Tank Pumps quantity display that differs from the expected state requires the Captain to monitor the condition before the next phase of flight. If the Window Heat is inoperative, continue descent only after both pilots has reviewed the associated sample guidance.

This text is fictional and exists only to give the prototype realistic volume and structure. The Hydraulic System B switch position that differs from the expected state requires both pilots to monitor the condition when operating at a sample station without ground power. During descent, the pilot flying should verify the Center Tank Pumps advisory when conditions permit. This text is fictional and exists only to give the prototype realistic volume and structure. If the Traffic Advisory Display is inoperative, continue taxi only after the Captain has reviewed the associated sample guidance.

The Probe Heat status message that differs from the expected state requires the pilot monitoring to select the condition if a discrepancy is observed. The Center Tank Pumps indication is expected to read within the sample range of 2 to 9 units during engine start. During landing, the First Officer should confirm the Pack Temperature Control selector position when conditions permit. During descent, both pilots should brief the Hydraulic System A quantity display unless directed otherwise by the Sample Operations Center.

**CAUTION:** The Fuel Crossfeed quantity display that differs from the expected state requires both pilots to confirm the condition when conditions permit. The first officer will cross-check any change in the Engine Anti-Ice switch position and advise the other pilot unless directed otherwise by the Sample Operations Center.

The Probe Heat indication is expected to read within the sample range of 12 to 19 units during cruise. If the Flap Position Indication is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance. During landing, the pilot flying should monitor the Engine Anti-Ice indication before the next phase of flight.

- Both pilots will cross-check any change in the Pack Temperature Control quantity display and advise the other pilot if a discrepancy is observed.

- If the Primary Electrical Bus is inoperative, continue preflight only after the Captain has reviewed the associated sample guidance.
- If the Bleed Air Supply is inoperative, continue preflight only after the pilot monitoring has reviewed the associated sample guidance.
- The captain will verify any change in the Probe Heat selector position and advise the other pilot unless directed otherwise by the Sample Operations Center.
- The Hydraulic System A quantity display is expected to read within the sample range of 94 to 105 units during takeoff.

**02.40.9 Center Tank Pumps Status Messages**

This text is fictional and exists only to give the prototype realistic volume and structure. The Nosewheel Steering selector position that differs from the expected state requires the relief pilot to announce the condition if the indication does not stabilize within the sample interval. The Bleed Air Supply selector position that differs from the expected state requires the Captain to record the condition if a discrepancy is observed. Values in this manual are invented and must not be used for any operational purpose. If the Engine Anti-Ice is inoperative, continue cruise only after both pilots has reviewed the associated sample guidance.

Values in this manual are invented and must not be used for any operational purpose. The Hydraulic System B advisory is expected to read within the sample range of 45 to 54 units during cruise. The Transponder annunciation that differs from the expected state requires the pilot monitoring to monitor the condition once the checklist item is complete. If the Weather Radar is inoperative, continue climb only after the pilot flying has reviewed the associated sample guidance. The Cabin Pressure Controller advisory that differs from the expected state requires the First Officer to verify the condition once the checklist item is complete. This text is fictional and exists only to give the prototype realistic volume and structure.

**NOTE:** The Cabin Pressure Controller selector position that differs from the expected state requires the relief pilot to announce the condition when conditions permit.

The wording here is placeholder content shaped like a procedure, not a procedure. During a diversion, the relief pilot should confirm the Cabin Pressure Controller quantity display if a discrepancy is observed. During parking, the relief pilot should cross-check the Nosewheel Steering switch position if the indication does not stabilize within the sample interval. The first officer will cross-check any change in the Window Heat selector position and advise the other pilot before the next phase of flight. If the Cabin Pressure Controller is inoperative, continue preflight only after the Captain has reviewed the associated sample guidance. During an extended ground delay, the Captain should monitor the Pack Temperature Control annunciation when operating at a sample station without ground power.

| Condition                            | Sample value | Remarks                |
|--------------------------------------|--------------|------------------------|
| Autopilot Channel B quantity display | 55 units     | Refer to related topic |
| Cockpit Voice Recorder advisory      | 37 units     | Normal                 |
| Oxygen Distribution advisory         | 82 units     | Advisory only          |
| Hydraulic System A indication        | 17 units     | Refer to related topic |

**CAUTION:** The Hydraulic System B annunciation is expected to read within the sample range of 26 to 37 units during a turnaround. The captain will record any change in the Cargo Smoke Detection status message and advise the other pilot when the associated caution light remains illuminated.

**CAUTION:** The relief pilot will verify any change in the Cargo Smoke Detection selector position and advise the other pilot unless directed otherwise by the Sample Operations Center. The Nosewheel Steering indication is expected to read within the sample range of 81 to 91 units during preflight.

**02.40.10 Wing Anti-Ice Limits Display**

If the Auxiliary Power Unit is inoperative, continue a diversion only after the relief pilot has reviewed the associated sample guidance. The Brake Temperature Monitor advisory that differs from the expected state requires the pilot monitoring to monitor the condition unless directed otherwise by the Sample Operations Center. If the Standby Instruments is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance. The pilot flying will select any change in the Autopilot Channel B indication and advise the other pilot once the checklist item is complete. The Flight Management Computer status message that differs from the expected state requires the pilot monitoring to record the condition when conditions permit. The Center Tank Pumps indication is expected to read within the sample range of 67 to 76 units during parking.

The Fuel Crossfeed annunciation is expected to read within the sample range of 86 to 90 units during approach. If the Traffic Advisory Display is inoperative, continue landing only after the First Officer has reviewed the associated sample guidance. If the Weather Radar is inoperative, continue approach only after both pilots has reviewed the associated sample guidance. The pilot flying will cross-check any change in the Nosewheel Steering switch position and advise the other pilot when conditions permit. If the Wing Anti-Ice is inoperative, continue a turnaround only after both pilots has reviewed the associated sample guidance.

During cruise, the pilot flying should verify the Fire Detection Loop quantity display if a discrepancy is observed. The Center Tank Pumps quantity display is expected to read within the sample range of 35 to 45 units during takeoff. The captain will brief any change in the Engine Anti-Ice quantity display and advise the other pilot if a discrepancy is observed. During descent, the relief pilot should cross-check the Cabin Pressure Controller advisory before the next phase of flight.

**NOTE:** This text is fictional and exists only to give the prototype realistic volume and structure.

- During a maintenance-requested ground run, the Captain should confirm the Standby Hydraulic switch position when operating at a sample station without ground power.
- The Fuel Crossfeed status message is expected to read within the sample range of 82 to 87 units during landing.
- The Flap Position Indication advisory is expected to read within the sample range of 12 to 18 units during parking.
- During a diversion, both pilots should select the Autobrake Selector annunciation if the indication does not stabilize within the sample interval.
- Values in this manual are invented and must not be used for any operational purpose.

Refer to the related topic for additional sample context. If the Autopilot Channel A is inoperative, continue climb only after both pilots has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Window Heat switch position                | 17 units     | Monitor                |
| Speedbrake Handle quantity display         | 57 units     | Refer to related topic |
| Pack Temperature Control selector position | 33 units     | Advisory only          |
| Standby Hydraulic quantity display         | 66 units     | Monitor                |

**02.40.11 Autothrottle Crew Awareness**

The Auxiliary Power Unit indication that differs from the expected state requires the relief pilot to confirm the condition unless directed otherwise by the Sample Operations Center. The pilot monitoring will record any change in the Nosewheel Steering annunciation and advise the other pilot once the checklist item is complete. If the Cabin Pressure Controller is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance. If the Nosewheel Steering is inoperative, continue engine start only after the pilot flying has reviewed the associated sample guidance. Refer to the related topic for additional sample context. If the Nosewheel Steering is inoperative, continue engine start only after the pilot monitoring has reviewed the associated sample guidance.



The Flight Management Computer status message that differs from the expected state requires the pilot flying to verify the condition before the next phase of flight. This text is fictional and exists only to give the prototype realistic volume and structure. This text is fictional and exists only to give the prototype realistic volume and structure. The Fuel Crossfeed selector position is expected to read within the sample range of 12 to 22 units during a diversion. The Thrust Reverser switch position that differs from the expected state requires the Captain to announce the condition if the indication does not stabilize within the sample interval. The Autopilot Channel B quantity display that differs from the expected state requires the relief pilot to select the condition if the indication does not stabilize within the sample interval.

**NOTE:** If the Autopilot Channel B is inoperative, continue descent only after the pilot flying has reviewed the associated sample guidance.

The Standby Hydraulic indication is expected to read within the sample range of 24 to 36 units during a turnaround. Refer to the related topic for additional sample context. The relief pilot will select any change in the Bleed Air Supply indication and advise the other pilot when the associated caution light remains illuminated. Both pilots will verify any change in the Cabin Pressure Controller annunciation and advise the other pilot if a discrepancy is observed. During a diversion, the Captain should record the Flap Position Indication selector position when operating at a sample station without ground power. The Autopilot Channel B switch position that differs from the expected state requires the Captain to announce the condition once the checklist item is complete.

- Refer to the related topic for additional sample context.
- Values in this manual are invented and must not be used for any operational purpose.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- The Fuel Crossfeed switch position that differs from the expected state requires the pilot flying to monitor the condition when the associated caution light remains illuminated.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- During taxi, the Captain should select the Standby Instruments annunciation once the checklist item is complete.

**02.40.12 Stall Warning Crew Awareness**

The Standby Instruments annunciation that differs from the expected state requires the pilot flying to select the condition when operating at a sample station without ground power. The Speedbrake Handle selector position is expected to read within the sample range of 75 to 85 units during climb. The Center Tank Pumps indication that differs from the expected state requires both pilots to monitor the condition if a discrepancy is observed.

| Condition                                   | Sample value | Remarks       |
|---------------------------------------------|--------------|---------------|
| Flight Management Computer quantity display | 57 units     | Advisory only |
| Fuel Crossfeed indication                   | 73 units     | Normal        |
| Cabin Pressure Controller switch position   | 61 units     | Advisory only |
| Brake Temperature Monitor switch position   | 32 units     | Advisory only |
| Center Tank Pumps quantity display          | 45 units     | Normal        |

If the Hydraulic System B is inoperative, continue an extended ground delay only after the Captain has reviewed the associated sample guidance. Both pilots will select any change in the Landing Gear Indication indication and advise the other pilot if a discrepancy is observed. The Autopilot Channel A quantity display that differs from the expected state requires the First Officer to announce the condition when operating at a sample station without ground power. If the Auxiliary Power Unit is inoperative, continue approach only after the pilot monitoring has reviewed the associated sample guidance.

The Autopilot Channel B indication that differs from the expected state requires both pilots to monitor the condition if the indication does not stabilize within the sample interval. The Autopilot Channel A selector position is expected to read within the sample range of 75 to 79 units during a diversion. If the Auxiliary Power Unit is inoperative, continue

descent only after the First Officer has reviewed the associated sample guidance. During cruise, the Captain should select the Hydraulic System A advisory when conditions permit. See 19.40.13 Fuel Planning Data Table 13.

**NOTE:** The Weather Radar indication that differs from the expected state requires the Captain to record the condition when conditions permit. The Thrust Reverser advisory is expected to read within the sample range of 38 to 44 units during takeoff.

**CAUTION:** The Engine Anti-Ice status message is expected to read within the sample range of 9 to 19 units during a maintenance-requested ground run. If the Transponder is inoperative, continue engine start only after the pilot flying has reviewed the associated sample guidance.

- The Wing Anti-Ice switch position is expected to read within the sample range of 61 to 72 units during climb.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- Values in this manual are invented and must not be used for any operational purpose.
- This text is fictional and exists only to give the prototype realistic volume and structure.

**NOTE:** During a turnaround, the relief pilot should monitor the Autopilot Channel B status message unless directed otherwise by the Sample Operations Center.

### 02.40.13 Cockpit Voice Recorder Crew Awareness

The Autothrottle indication that differs from the expected state requires both pilots to confirm the condition once the checklist item is complete. The Autopilot Channel B annunciation is expected to read within the sample range of 14 to 21 units during cruise. During descent, the First Officer should brief the Fire Detection Loop switch position when the associated caution light remains illuminated. The Brake Temperature Monitor status message is expected to read within the sample range of 47 to 59 units during parking.

**NOTE:** The Standby Hydraulic status message is expected to read within the sample range of 70 to 78 units during cruise. The Thrust Reverser indication is expected to read within the sample range of 86 to 92 units during parking.

The pilot monitoring will verify any change in the Ground Proximity Monitor selector position and advise the other pilot when the associated caution light remains illuminated. Both pilots will record any change in the Hydraulic System A indication and advise the other pilot if a discrepancy is observed. The relief pilot will cross-check any change in the Fuel Crossfeed status message and advise the other pilot when operating at a sample station without ground power.

**NOTE:** The Flight Management Computer advisory that differs from the expected state requires the pilot flying to cross-check the condition when the associated caution light remains illuminated.

The Ground Proximity Monitor status message is expected to read within the sample range of 54 to 59 units during an extended ground delay. During a diversion, both pilots should cross-check the Hydraulic System B indication if the indication does not stabilize within the sample interval. If the Autothrottle is inoperative, continue engine start only after the Captain has reviewed the associated sample guidance.

The Thrust Reverser advisory that differs from the expected state requires both pilots to select the condition unless directed otherwise by the Sample Operations Center. The Fuel Crossfeed advisory that differs from the expected state requires both pilots to brief the condition when conditions permit. The Center Tank Pumps indication is expected to read within the sample range of 83 to 87 units during taxi. This text is fictional and exists only to give the prototype realistic volume and structure. If the Autopilot Channel A is inoperative, continue preflight only after both pilots have reviewed the associated sample guidance. During a maintenance-requested ground run, both pilots should announce the Autothrottle status message if the indication does not stabilize within the sample interval.

**CAUTION:** The first officer will cross-check any change in the Fuel Crossfeed indication and advise the other pilot if the indication does not stabilize within the sample interval. Values in this manual are invented and must not be used for any operational purpose.

- The wording here is placeholder content shaped like a procedure, not a procedure.
- During cruise, the First Officer should verify the Flap Position Indication indication once the checklist item is complete.
- The Transponder selector position that differs from the expected state requires the Captain to monitor the condition unless directed otherwise by the Sample Operations Center.

**02.40.14 Brake Temperature Monitor Status Messages**

The Center Tank Pumps indication that differs from the expected state requires the First Officer to announce the condition if a discrepancy is observed. Both pilots will monitor any change in the Brake Temperature Monitor switch position and advise the other pilot once the checklist item is complete. The Transponder annunciation is expected to read within the sample range of 55 to 60 units during descent. If the Cockpit Voice Recorder is inoperative, continue taxi only after the First Officer has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. The first officer will confirm any change in the Autopilot Channel B advisory and advise the other pilot unless directed otherwise by the Sample Operations Center.

- The Hydraulic System A selector position is expected to read within the sample range of 5 to 17 units during climb.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- This text is fictional and exists only to give the prototype realistic volume and structure.

This text is fictional and exists only to give the prototype realistic volume and structure. The Brake Temperature Monitor indication is expected to read within the sample range of 79 to 85 units during taxi. During parking, both pilots should brief the Hydraulic System B selector position if the indication does not stabilize within the sample interval. The first officer will verify any change in the Oxygen Distribution indication and advise the other pilot if a discrepancy is observed. If the Nosewheel Steering is inoperative, continue an extended ground delay only after the Captain has reviewed the associated sample guidance. During descent, the pilot monitoring should record the Speedbrake Handle switch position when operating at a sample station without ground power.

**CAUTION:** If the Cabin Pressure Controller is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance. The Transponder selector position is expected to read within the sample range of 27 to 34 units during descent.

| Condition                              | Sample value | Remarks |
|----------------------------------------|--------------|---------|
| Hydraulic System B quantity display    | 8 units      | Monitor |
| Primary Electrical Bus switch position | 60 units     | Monitor |
| Stall Warning switch position          | 41 units     | Monitor |

Both pilots will brief any change in the Ground Proximity Monitor quantity display and advise the other pilot if a discrepancy is observed. If the Flight Management Computer is inoperative, continue engine start only after both pilots has reviewed the associated sample guidance. During a turnaround, the First Officer should cross-check the Nosewheel Steering status message once the checklist item is complete. The Flight Management Computer quantity display that differs from the expected state requires the pilot monitoring to record the condition if a discrepancy is observed. If the Center Tank Pumps is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance.

**02.40.15 Center Tank Pumps Test**

The Fuel Crossfeed advisory is expected to read within the sample range of 85 to 89 units during taxi. The first officer will record any change in the Flap Position Indication annunciation and advise the other pilot before the next phase of flight. The Speedbrake Handle annunciation is expected to read within the sample range of 73 to 84 units during engine start. If the Primary Electrical Bus is inoperative, continue landing only after both pilots has reviewed the associated sample guidance. Refer to the related topic for additional sample context. See 03.20.19 Verification:

Cabin Pressure Controller.

**NOTE:** The Center Tank Pumps quantity display is expected to read within the sample range of 93 to 99 units during descent.

- During takeoff, the relief pilot should select the Cabin Pressure Controller annunciation when the associated caution light remains illuminated.
- The Weather Radar quantity display that differs from the expected state requires both pilots to brief the condition before the next phase of flight.
- Both pilots will cross-check any change in the Fuel Crossfeed status message and advise the other pilot once the checklist item is complete.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Standby Hydraulic annunciation        | 94 units     | Normal                 |
| Center Tank Pumps quantity display    | 35 units     | Refer to related topic |
| Ground Proximity Monitor annunciation | 55 units     | Normal                 |
| Flap Position Indication indication   | 96 units     | Normal                 |
| Flap Position Indication indication   | 92 units     | Refer to related topic |
| Thrust Reverser selector position     | 79 units     | Monitor                |

- The Oxygen Distribution selector position that differs from the expected state requires the Captain to brief the condition if the indication does not stabilize within the sample interval.
- If the Weather Radar is inoperative, continue engine start only after the pilot flying has reviewed the associated sample guidance.
- The Oxygen Distribution advisory that differs from the expected state requires the First Officer to select the condition when operating at a sample station without ground power.

**02.40.16 Hydraulic System A Test**

During preflight, the Captain should verify the Autopilot Channel B advisory when conditions permit. The Brake Temperature Monitor switch position that differs from the expected state requires the Captain to select the condition unless directed otherwise by the Sample Operations Center. Refer to the related topic for additional sample context. The Primary Electrical Bus indication that differs from the expected state requires the pilot monitoring to cross-check the condition if the indication does not stabilize within the sample interval. This text is fictional and exists only to give the prototype realistic volume and structure.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Autobrake Selector indication           | 61 units     | Refer to related topic |
| Flap Position Indication status message | 72 units     | Advisory only          |
| Speedbrake Handle advisory              | 20 units     | Advisory only          |

**CAUTION:** The relief pilot will select any change in the Brake Temperature Monitor status message and advise the other pilot unless directed otherwise by the Sample Operations Center.

**NOTE:** This text is fictional and exists only to give the prototype realistic volume and structure.

During parking, the pilot flying should monitor the Oxygen Distribution quantity display once the checklist item is complete. The pilot flying will monitor any change in the Brake Temperature Monitor status message and advise the other pilot when the associated caution light remains illuminated. The Fuel Crossfeed switch position is expected to read within the sample range of 87 to 98 units during taxi. The captain will announce any change in the Standby Hydraulic switch position and advise the other pilot before the next phase of flight.

During descent, both pilots should monitor the Ground Proximity Monitor switch position before the next phase of flight. The Autothrottle status message that differs from the expected state requires both pilots to cross-check the condition if the indication does not stabilize within the sample interval. The relief pilot will select any change in the Bleed Air Supply advisory and advise the other pilot when the associated caution light remains illuminated. During taxi, the Captain should verify the Center Tank Pumps status message if the indication does not stabilize within the sample interval. During takeoff, both pilots should confirm the Speedbrake Handle quantity display when operating at a sample station without ground power.

The Flap Position Indication indication that differs from the expected state requires the pilot monitoring to record the condition when conditions permit. If the Ground Proximity Monitor is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance. The pilot monitoring will monitor any change in the Probe Heat annunciation and advise the other pilot when operating at a sample station without ground power. The Autobrake Selector switch position that differs from the expected state requires the relief pilot to cross-check the condition unless directed otherwise by the Sample Operations Center.

The Cabin Pressure Controller switch position is expected to read within the sample range of 53 to 60 units during an extended ground delay. Values in this manual are invented and must not be used for any operational purpose. If the Center Tank Pumps is inoperative, continue cruise only after the Captain has reviewed the associated sample guidance.

During cruise, the pilot monitoring should confirm the Hydraulic System B annunciation before the next phase of flight. Values in this manual are invented and must not be used for any operational purpose. The pilot flying will cross-check any change in the Window Heat status message and advise the other pilot before the next phase of flight. Both pilots will cross-check any change in the Pack Temperature Control annunciation and advise the other pilot when the associated caution light remains illuminated. Both pilots will brief any change in the Speedbrake Handle advisory and advise the other pilot unless directed otherwise by the Sample Operations Center.

#### **02.40.17 Stall Warning Normal Operation**

During an extended ground delay, both pilots should record the Flap Position Indication switch position unless directed otherwise by the Sample Operations Center. The Flight Management Computer status message that differs from the expected state requires the First Officer to record the condition unless directed otherwise by the Sample Operations Center. The Pack Temperature Control quantity display that differs from the expected state requires the pilot flying to verify the condition if a discrepancy is observed. If the Hydraulic System A is inoperative, continue climb only after the Captain has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure.

- The pilot flying will cross-check any change in the Standby Hydraulic indication and advise the other pilot when operating at a sample station without ground power.
- The Flight Management Computer status message that differs from the expected state requires the pilot monitoring to select the condition unless directed otherwise by the Sample Operations Center.
- The first officer will verify any change in the Fuel Crossfeed annunciation and advise the other pilot when the associated caution light remains illuminated.
- Refer to the related topic for additional sample context.
- The Engine Anti-Ice annunciation that differs from the expected state requires the Captain to monitor the condition if the indication does not stabilize within the sample interval.

**NOTE:** During approach, the relief pilot should verify the Nosewheel Steering annunciation unless directed otherwise by the Sample Operations Center. The captain will record any change in the Auxiliary Power Unit quantity display and advise the other pilot once the checklist item is complete.

The Nosewheel Steering advisory that differs from the expected state requires the relief pilot to record the condition when the associated caution light remains illuminated. The relief pilot will verify any change in the Ground Proximity Monitor advisory and advise the other pilot before the next phase of flight. The Flight Management Computer

annunciation that differs from the expected state requires the First Officer to cross-check the condition unless directed otherwise by the Sample Operations Center. The Cargo Smoke Detection annunciation that differs from the expected state requires the pilot flying to record the condition once the checklist item is complete.

| Condition                                   | Sample value | Remarks       |
|---------------------------------------------|--------------|---------------|
| Hydraulic System A advisory                 | 69 units     | Advisory only |
| Hydraulic System A advisory                 | 66 units     | Advisory only |
| Brake Temperature Monitor selector position | 17 units     | Advisory only |
| Autobrake Selector annunciation             | 94 units     | Monitor       |

**NOTE:** If the Autopilot Channel B is inoperative, continue taxi only after the relief pilot has reviewed the associated sample guidance.

During engine start, the pilot monitoring should confirm the Autothrottle advisory unless directed otherwise by the Sample Operations Center. The Thrust Reverser switch position is expected to read within the sample range of 3 to 10 units during approach. The Autobrake Selector annunciation that differs from the expected state requires the First Officer to brief the condition when the associated caution light remains illuminated. The Flight Management Computer status message that differs from the expected state requires the Captain to select the condition before the next phase of flight.

**02.40.18 Fire Detection Loop Power Sources**

During engine start, the Captain should select the Speedbrake Handle annunciation unless directed otherwise by the Sample Operations Center. The Ground Proximity Monitor status message that differs from the expected state requires the First Officer to verify the condition when operating at a sample station without ground power. If the Window Heat is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance. The Bleed Air Supply switch position is expected to read within the sample range of 26 to 31 units during cruise. Both pilots will confirm any change in the Nosewheel Steering advisory and advise the other pilot unless directed otherwise by the Sample Operations Center.

**NOTE:** The first officer will select any change in the Standby Hydraulic quantity display and advise the other pilot when operating at a sample station without ground power.

The Fire Detection Loop switch position that differs from the expected state requires the relief pilot to verify the condition when the associated caution light remains illuminated. The Autopilot Channel B indication that differs from the expected state requires both pilots to confirm the condition unless directed otherwise by the Sample Operations Center. The wording here is placeholder content shaped like a procedure, not a procedure.

- The Autothrottle advisory that differs from the expected state requires the Captain to announce the condition unless directed otherwise by the Sample Operations Center.
- If the Autopilot Channel A is inoperative, continue parking only after the relief pilot has reviewed the associated sample guidance.
- The Ground Proximity Monitor advisory is expected to read within the sample range of 48 to 55 units during landing.
- The Flight Management Computer selector position is expected to read within the sample range of 36 to 45 units during a turnaround.
- During taxi, the pilot monitoring should verify the Oxygen Distribution annunciation when operating at a sample station without ground power.

| Condition                                | Sample value | Remarks |
|------------------------------------------|--------------|---------|
| Cockpit Voice Recorder selector position | 33 units     | Monitor |
| Bleed Air Supply selector position       | 97 units     | Normal  |



|                                     |          |                        |
|-------------------------------------|----------|------------------------|
| Fuel Crossfeed switch position      | 78 units | Refer to related topic |
| Fire Detection Loop switch position | 72 units | Normal                 |
| Primary Electrical Bus annunciation | 88 units | Advisory only          |

The pilot monitoring will record any change in the Thrust Reverser advisory and advise the other pilot unless directed otherwise by the Sample Operations Center. The Engine Anti-Ice advisory that differs from the expected state requires the pilot flying to confirm the condition if a discrepancy is observed. If the Autothrottle is inoperative, continue a diversion only after both pilots has reviewed the associated sample guidance. During preflight, the First Officer should verify the Autobrake Selector annunciation if a discrepancy is observed.

### 02.40.19 *Flight Management Computer Reset Guidance*

During preflight, the relief pilot should monitor the Primary Electrical Bus switch position if the indication does not stabilize within the sample interval. The captain will cross-check any change in the Hydraulic System B selector position and advise the other pilot when the associated caution light remains illuminated. The pilot flying will confirm any change in the Hydraulic System A advisory and advise the other pilot if a discrepancy is observed. The Standby Instruments selector position that differs from the expected state requires the First Officer to cross-check the condition before the next phase of flight.

**NOTE:** During a turnaround, the Captain should record the Bleed Air Supply status message unless directed otherwise by the Sample Operations Center.

The Standby Hydraulic indication is expected to read within the sample range of 74 to 82 units during approach. The Nosewheel Steering status message is expected to read within the sample range of 25 to 36 units during an extended ground delay. The Cabin Pressure Controller selector position is expected to read within the sample range of 82 to 94 units during a maintenance-requested ground run. The Center Tank Pumps annunciation that differs from the expected state requires the pilot flying to monitor the condition if the indication does not stabilize within the sample interval. The Brake Temperature Monitor quantity display is expected to read within the sample range of 39 to 45 units during a diversion.

If the Fuel Crossfeed is inoperative, continue landing only after both pilots has reviewed the associated sample guidance. During a maintenance-requested ground run, the First Officer should verify the Ground Proximity Monitor advisory when operating at a sample station without ground power. The Engine Anti-Ice advisory is expected to read within the sample range of 92 to 104 units during engine start. If the Bleed Air Supply is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance. The pilot flying will cross-check any change in the Cargo Smoke Detection advisory and advise the other pilot before the next phase of flight. The Stall Warning selector position that differs from the expected state requires the Captain to record the condition unless directed otherwise by the Sample Operations Center.

**NOTE:** This text is fictional and exists only to give the prototype realistic volume and structure. The Autothrottle selector position is expected to read within the sample range of 76 to 81 units during an extended ground delay.

The Nosewheel Steering quantity display that differs from the expected state requires both pilots to verify the condition once the checklist item is complete. The Autothrottle selector position that differs from the expected state requires the Captain to announce the condition when conditions permit. The Hydraulic System A advisory is expected to read within the sample range of 17 to 21 units during approach. The Standby Instruments quantity display that differs from the expected state requires both pilots to cross-check the condition if the indication does not stabilize within the sample interval.

- If the Fire Detection Loop is inoperative, continue a turnaround only after the pilot monitoring has reviewed the associated sample guidance.
- During a diversion, the pilot flying should select the Wing Anti-Ice switch position when the associated caution light remains illuminated.

- During takeoff, the pilot flying should brief the Brake Temperature Monitor switch position when the associated caution light remains illuminated.
- During an extended ground delay, the Captain should cross-check the Center Tank Pumps advisory when conditions permit.
- The wording here is placeholder content shaped like a procedure, not a procedure.

The Cargo Smoke Detection quantity display is expected to read within the sample range of 35 to 42 units during engine start. The captain will verify any change in the Auxiliary Power Unit advisory and advise the other pilot when operating at a sample station without ground power. The Stall Warning quantity display that differs from the expected state requires both pilots to select the condition if the indication does not stabilize within the sample interval. The first officer will brief any change in the Speedbrake Handle switch position and advise the other pilot before the next phase of flight.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Standby Instruments selector position | 74 units     | Refer to related topic |
| Traffic Advisory Display annunciation | 26 units     | Monitor                |
| Oxygen Distribution switch position   | 49 units     | Normal                 |
| Thrust Reverser indication            | 6 units      | Monitor                |
| Fuel Crossfeed advisory               | 90 units     | Monitor                |
| Oxygen Distribution advisory          | 24 units     | Monitor                |
| Speedbrake Handle indication          | 28 units     | Refer to related topic |

**02.40.20 Flight Management Computer Status Messages**

During a maintenance-requested ground run, the pilot monitoring should verify the Autothrottle quantity display when the associated caution light remains illuminated. During engine start, the pilot monitoring should record the Autopilot Channel A quantity display unless directed otherwise by the Sample Operations Center. The captain will select any change in the Thrust Reverser status message and advise the other pilot once the checklist item is complete. If the Nosewheel Steering is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance. The Traffic Advisory Display annunciation is expected to read within the sample range of 17 to 20 units during approach. The Autopilot Channel A quantity display is expected to read within the sample range of 29 to 32 units during descent.

- The relief pilot will select any change in the Fuel Crossfeed advisory and advise the other pilot when operating at a sample station without ground power.
- The first officer will monitor any change in the Bleed Air Supply switch position and advise the other pilot if the indication does not stabilize within the sample interval.
- During parking, the pilot monitoring should monitor the Standby Hydraulic advisory if the indication does not stabilize within the sample interval.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- Values in this manual are invented and must not be used for any operational purpose.

The Window Heat switch position is expected to read within the sample range of 25 to 34 units during a turnaround. The Primary Electrical Bus status message that differs from the expected state requires the pilot flying to verify the condition when the associated caution light remains illuminated. If the Auxiliary Power Unit is inoperative, continue engine start only after both pilots has reviewed the associated sample guidance.

**NOTE:** The pilot flying will brief any change in the Fire Detection Loop indication and advise the other pilot when operating at a sample station without ground power.

The Hydraulic System A advisory is expected to read within the sample range of 62 to 65 units during approach. The Autothrottle indication that differs from the expected state requires the pilot monitoring to verify the condition once the checklist item is complete. The Speedbrake Handle selector position that differs from the expected state requires the First Officer to confirm the condition if the indication does not stabilize within the sample interval. During a diversion, the pilot flying should select the Auxiliary Power Unit selector position when the associated caution light remains illuminated.

**02.40.21 Probe Heat Test**

Values in this manual are invented and must not be used for any operational purpose. The Stall Warning selector position that differs from the expected state requires the relief pilot to monitor the condition when conditions permit. The Engine Anti-Ice status message that differs from the expected state requires the pilot monitoring to monitor the condition if a discrepancy is observed.

The Bleed Air Supply switch position that differs from the expected state requires both pilots to announce the condition once the checklist item is complete. During landing, the pilot flying should verify the Flight Management Computer status message when conditions permit. The pilot monitoring will announce any change in the Landing Gear Indication switch position and advise the other pilot when the associated caution light remains illuminated. The Traffic Advisory Display selector position is expected to read within the sample range of 2 to 6 units during approach. The Autopilot Channel B switch position is expected to read within the sample range of 24 to 32 units during cruise.

Refer to the related topic for additional sample context. During a maintenance-requested ground run, the Captain should cross-check the Pack Temperature Control advisory once the checklist item is complete. If the Autobrake Selector is inoperative, continue taxi only after the pilot flying has reviewed the associated sample guidance.

If the Autopilot Channel A is inoperative, continue a maintenance-requested ground run only after the pilot flying has reviewed the associated sample guidance. During descent, the pilot monitoring should select the Flight Management Computer status message when the associated caution light remains illuminated. The Speedbrake Handle quantity display that differs from the expected state requires the pilot monitoring to confirm the condition before the next phase of flight. During landing, both pilots should confirm the Window Heat advisory if a discrepancy is observed. If the Fuel Crossfeed is inoperative, continue climb only after the relief pilot has reviewed the associated sample guidance.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Probe Heat indication                    | 21 units     | Refer to related topic |
| Nosewheel Steering selector position     | 67 units     | Monitor                |
| Traffic Advisory Display switch position | 96 units     | Normal                 |
| Fuel Crossfeed annunciation              | 35 units     | Monitor                |
| Thrust Reverser selector position        | 85 units     | Normal                 |

| Condition                                | Sample value | Remarks |
|------------------------------------------|--------------|---------|
| Ground Proximity Monitor switch position | 48 units     | Monitor |
| Transponder advisory                     | 4 units      | Monitor |
| Autopilot Channel B status message       | 44 units     | Monitor |

**02.40.22 Flap Position Indication Indications**

During descent, the pilot flying should confirm the Weather Radar status message before the next phase of flight. The Hydraulic System B indication is expected to read within the sample range of 22 to 30 units during a diversion. If the Primary Electrical Bus is inoperative, continue taxi only after the First Officer has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. The Probe Heat advisory that differs from the expected state requires the pilot monitoring to select the condition once the checklist item is complete. If the Probe Heat is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance.

The Autopilot Channel A annunciation is expected to read within the sample range of 11 to 23 units during descent. The Speedbrake Handle indication is expected to read within the sample range of 25 to 30 units during an extended ground delay. This text is fictional and exists only to give the prototype realistic volume and structure. The first officer will monitor any change in the Standby Hydraulic annunciation and advise the other pilot if a discrepancy is observed. The Thrust Reverser status message that differs from the expected state requires both pilots to cross-check the condition when conditions permit.

- During engine start, the Captain should monitor the Autopilot Channel A quantity display when the associated caution light remains illuminated.
- If the Hydraulic System A is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance.
- The Weather Radar status message is expected to read within the sample range of 56 to 66 units during cruise.

The Window Heat advisory is expected to read within the sample range of 66 to 72 units during landing. The captain will cross-check any change in the Probe Heat selector position and advise the other pilot if a discrepancy is observed. The pilot flying will verify any change in the Standby Hydraulic indication and advise the other pilot when operating at a sample station without ground power. This text is fictional and exists only to give the prototype realistic volume and structure. The Traffic Advisory Display selector position that differs from the expected state requires the Captain to record the condition once the checklist item is complete.

The wording here is placeholder content shaped like a procedure, not a procedure. The Autobrake Selector switch position is expected to read within the sample range of 59 to 70 units during landing. The pilot monitoring will monitor any change in the Flight Management Computer status message and advise the other pilot before the next phase of flight. The Bleed Air Supply annunciation is expected to read within the sample range of 59 to 62 units during cruise. If the Primary Electrical Bus is inoperative, continue approach only after the First Officer has reviewed the associated sample guidance. During taxi, the pilot flying should select the Hydraulic System B indication when operating at a sample station without ground power.

**CAUTION:** Values in this manual are invented and must not be used for any operational purpose.

The wording here is placeholder content shaped like a procedure, not a procedure. During engine start, the pilot monitoring should brief the Hydraulic System A quantity display when conditions permit. Refer to the related topic for additional sample context. If the Primary Electrical Bus is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance. The Autobrake Selector selector position is expected to read within the sample range of 3 to 10 units during an extended ground delay.

**02.40.23 Oxygen Distribution Status Messages**

During parking, the relief pilot should confirm the Primary Electrical Bus annunciation if a discrepancy is observed. The Cockpit Voice Recorder indication is expected to read within the sample range of 23 to 26 units during an extended ground delay. The Standby Instruments advisory is expected to read within the sample range of 51 to 59 units during climb.

**NOTE:** If the Hydraulic System B is inoperative, continue landing only after the relief pilot has reviewed the associated sample guidance.

The pilot flying will monitor any change in the Autopilot Channel B quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center. If the Oxygen Distribution is inoperative, continue descent only after the Captain has reviewed the associated sample guidance. The relief pilot will select any change in the Center Tank Pumps quantity display and advise the other pilot if a discrepancy is observed. During cruise, both pilots should record the Primary Electrical Bus switch position if the indication does not stabilize within the sample interval. During takeoff, the pilot monitoring should monitor the Cabin Pressure Controller advisory before the next phase of flight.

| Condition           | Sample value | Remarks       |
|---------------------|--------------|---------------|
| Probe Heat advisory | 84 units     | Advisory only |

|                                       |          |                        |
|---------------------------------------|----------|------------------------|
| Ground Proximity Monitor advisory     | 68 units | Advisory only          |
| Nosewheel Steering annunciation       | 36 units | Refer to related topic |
| Cabin Pressure Controller indication  | 26 units | Advisory only          |
| Autopilot Channel A switch position   | 16 units | Monitor                |
| Fire Detection Loop selector position | 10 units | Monitor                |

During climb, the pilot monitoring should announce the Ground Proximity Monitor quantity display if a discrepancy is observed. The Stall Warning status message that differs from the expected state requires the Captain to cross-check the condition when the associated caution light remains illuminated. The Fire Detection Loop selector position that differs from the expected state requires both pilots to select the condition when conditions permit.

During taxi, both pilots should announce the Brake Temperature Monitor selector position before the next phase of flight. This text is fictional and exists only to give the prototype realistic volume and structure. The Weather Radar status message that differs from the expected state requires the relief pilot to confirm the condition when conditions permit. The first officer will select any change in the Weather Radar indication and advise the other pilot if a discrepancy is observed. The Speedbrake Handle annunciation that differs from the expected state requires the relief pilot to brief the condition when the associated caution light remains illuminated. The Flight Management Computer status message is expected to read within the sample range of 54 to 61 units during climb.

**CAUTION:** During approach, the pilot flying should confirm the Ground Proximity Monitor switch position unless directed otherwise by the Sample Operations Center.

02.40.24 Autobrake Selector Interfaces

This text is fictional and exists only to give the prototype realistic volume and structure. The pilot flying will verify any change in the Bleed Air Supply annunciation and advise the other pilot when conditions permit. The Probe Heat annunciation that differs from the expected state requires the relief pilot to monitor the condition once the checklist item is complete. The Speedbrake Handle quantity display that differs from the expected state requires the relief pilot to monitor the condition when operating at a sample station without ground power.

| Condition                           | Sample value | Remarks                |
|-------------------------------------|--------------|------------------------|
| Nosewheel Steering indication       | 11 units     | Refer to related topic |
| Pack Temperature Control indication | 79 units     | Advisory only          |
| Cargo Smoke Detection annunciation  | 41 units     | Refer to related topic |
| Standby Instruments annunciation    | 44 units     | Advisory only          |
| Transponder status message          | 83 units     | Refer to related topic |

**CAUTION:** The wording here is placeholder content shaped like a procedure, not a procedure. Values in this manual are invented and must not be used for any operational purpose.

**NOTE:** The wording here is placeholder content shaped like a procedure, not a procedure. During cruise, the First Officer should confirm the Fire Detection Loop switch position if the indication does not stabilize within the sample interval.

The pilot monitoring will monitor any change in the Traffic Advisory Display selector position and advise the other pilot if the indication does not stabilize within the sample interval. The Ground Proximity Monitor status message is expected to read within the sample range of 54 to 65 units during landing. The Speedbrake Handle advisory that differs from the expected state requires the Captain to monitor the condition if a discrepancy is observed. This text is fictional and exists only to give the prototype realistic volume and structure. See 11.10.5 Cargo Smoke Detection Crew Awareness.

| Condition                    | Sample value | Remarks |
|------------------------------|--------------|---------|
| Engine Anti-Ice annunciation | 48 units     | Normal  |

|                                           |          |               |
|-------------------------------------------|----------|---------------|
| Standby Instruments switch position       | 42 units | Advisory only |
| Traffic Advisory Display switch position  | 3 units  | Monitor       |
| Cockpit Voice Recorder advisory           | 70 units | Advisory only |
| Traffic Advisory Display quantity display | 30 units | Monitor       |
| Bleed Air Supply status message           | 98 units | Advisory only |

### 02.40.25 Autobrake Selector Normal Operation

Both pilots will select any change in the Autopilot Channel B indication and advise the other pilot before the next phase of flight. The Cabin Pressure Controller quantity display is expected to read within the sample range of 21 to 32 units during preflight. The captain will announce any change in the Fire Detection Loop selector position and advise the other pilot once the checklist item is complete.

| Condition                                 | Sample value | Remarks       |
|-------------------------------------------|--------------|---------------|
| Autopilot Channel B quantity display      | 30 units     | Normal        |
| Flight Management Computer advisory       | 29 units     | Advisory only |
| Pack Temperature Control quantity display | 54 units     | Advisory only |
| Center Tank Pumps quantity display        | 4 units      | Monitor       |
| Hydraulic System A advisory               | 78 units     | Monitor       |

| Condition                                 | Sample value | Remarks       |
|-------------------------------------------|--------------|---------------|
| Cockpit Voice Recorder status message     | 43 units     | Monitor       |
| Ground Proximity Monitor annunciation     | 32 units     | Normal        |
| Ground Proximity Monitor status message   | 76 units     | Normal        |
| Brake Temperature Monitor advisory        | 64 units     | Monitor       |
| Pack Temperature Control quantity display | 27 units     | Monitor       |
| Center Tank Pumps switch position         | 97 units     | Advisory only |
| Pack Temperature Control status message   | 70 units     | Advisory only |

The Wing Anti-Ice status message that differs from the expected state requires the First Officer to brief the condition before the next phase of flight. The wording here is placeholder content shaped like a procedure, not a procedure. The Autopilot Channel B annunciation is expected to read within the sample range of 35 to 43 units during taxi. Both pilots will select any change in the Autopilot Channel A selector position and advise the other pilot if a discrepancy is observed. During a turnaround, both pilots should confirm the Pack Temperature Control annunciation if the indication does not stabilize within the sample interval.

| Condition                                  | Sample value | Remarks       |
|--------------------------------------------|--------------|---------------|
| Ground Proximity Monitor selector position | 39 units     | Monitor       |
| Nosewheel Steering switch position         | 67 units     | Normal        |
| Fire Detection Loop quantity display       | 39 units     | Normal        |
| Thrust Reverser advisory                   | 42 units     | Advisory only |

### 02.40.26 Center Tank Pumps Status Messages

The wording here is placeholder content shaped like a procedure, not a procedure. Refer to the related topic for additional sample context. If the Standby Instruments is inoperative, continue climb only after both pilots has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. During cruise, the relief pilot should select the Hydraulic System B indication when operating at



a sample station without ground power.

The Autobrake Selector quantity display that differs from the expected state requires the First Officer to announce the condition when operating at a sample station without ground power. If the Center Tank Pumps is inoperative, continue a diversion only after the relief pilot has reviewed the associated sample guidance. The Fire Detection Loop selector position is expected to read within the sample range of 57 to 61 units during taxi. The Speedbrake Handle quantity display is expected to read within the sample range of 10 to 20 units during climb. If the Cabin Pressure Controller is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance. The Standby Hydraulic annunciation is expected to read within the sample range of 47 to 58 units during preflight.

**NOTE:** During climb, the pilot monitoring should confirm the Primary Electrical Bus indication unless directed otherwise by the Sample Operations Center. During a diversion, the pilot flying should cross-check the Weather Radar status message before the next phase of flight.

During a turnaround, the pilot monitoring should record the Window Heat switch position when operating at a sample station without ground power. During climb, the pilot monitoring should announce the Bleed Air Supply indication when operating at a sample station without ground power. The Pack Temperature Control advisory that differs from the expected state requires the First Officer to confirm the condition when the associated caution light remains illuminated. During engine start, the First Officer should verify the Window Heat quantity display once the checklist item is complete.

**NOTE:** The pilot flying will monitor any change in the Pack Temperature Control advisory and advise the other pilot unless directed otherwise by the Sample Operations Center. The Transponder switch position that differs from the expected state requires the pilot flying to record the condition when the associated caution light remains illuminated.

| Condition                         | Sample value | Remarks                |
|-----------------------------------|--------------|------------------------|
| Autopilot Channel B advisory      | 89 units     | Refer to related topic |
| Oxygen Distribution annunciation  | 25 units     | Normal                 |
| Standby Hydraulic annunciation    | 43 units     | Advisory only          |
| Bleed Air Supply quantity display | 17 units     | Advisory only          |
| Wing Anti-Ice status message      | 77 units     | Advisory only          |
| Transponder advisory              | 54 units     | Monitor                |
| Standby Instruments advisory      | 22 units     | Normal                 |

- The Weather Radar advisory that differs from the expected state requires the relief pilot to brief the condition before the next phase of flight.
- If the Landing Gear Indication is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance.
- If the Autothrottle is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance.
- During landing, the pilot flying should select the Nosewheel Steering advisory if a discrepancy is observed.

**NOTE:** During preflight, the relief pilot should announce the Primary Electrical Bus quantity display when the associated caution light remains illuminated. If the Engine Anti-Ice is inoperative, continue descent only after the pilot flying has reviewed the associated sample guidance.

**02.40.27 Oxygen Distribution Interfaces**

The wording here is placeholder content shaped like a procedure, not a procedure. If the Bleed Air Supply is inoperative, continue parking only after the relief pilot has reviewed the associated sample guidance. The Fuel Crossfeed quantity display that differs from the expected state requires the pilot monitoring to cross-check the

condition if the indication does not stabilize within the sample interval. The Engine Anti-Ice quantity display that differs from the expected state requires the First Officer to brief the condition when operating at a sample station without ground power. This text is fictional and exists only to give the prototype realistic volume and structure.

**CAUTION:** The wording here is placeholder content shaped like a procedure, not a procedure.

The Oxygen Distribution selector position is expected to read within the sample range of 77 to 81 units during engine start. The first officer will announce any change in the Bleed Air Supply switch position and advise the other pilot when the associated caution light remains illuminated. The pilot flying will select any change in the Window Heat indication and advise the other pilot when the associated caution light remains illuminated. The Pack Temperature Control switch position is expected to read within the sample range of 42 to 51 units during preflight. The Flight Management Computer advisory is expected to read within the sample range of 56 to 67 units during a turnaround. If the Cockpit Voice Recorder is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance.

**CAUTION:** The Engine Anti-Ice switch position is expected to read within the sample range of 46 to 57 units during an extended ground delay.

The Autopilot Channel A annunciation that differs from the expected state requires both pilots to brief the condition once the checklist item is complete. The captain will verify any change in the Hydraulic System B switch position and advise the other pilot if a discrepancy is observed. During landing, the First Officer should record the Brake Temperature Monitor status message before the next phase of flight. See 05.70.3 Stall Warning Interfaces.

- Values in this manual are invented and must not be used for any operational purpose.
- The Center Tank Pumps advisory that differs from the expected state requires the Captain to select the condition unless directed otherwise by the Sample Operations Center.
- The Probe Heat advisory that differs from the expected state requires the pilot monitoring to announce the condition if the indication does not stabilize within the sample interval.

**CAUTION:** If the Engine Anti-Ice is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance. The Cabin Pressure Controller advisory is expected to read within the sample range of 80 to 83 units during climb.

**NOTE:** The wording here is placeholder content shaped like a procedure, not a procedure.

## 02.40.28 Ground Proximity Monitor Indications

This text is fictional and exists only to give the prototype realistic volume and structure. This text is fictional and exists only to give the prototype realistic volume and structure. The Oxygen Distribution selector position that differs from the expected state requires the pilot flying to monitor the condition when conditions permit. The Autothrottle annunciation is expected to read within the sample range of 81 to 84 units during engine start. If the Pack Temperature Control is inoperative, continue approach only after both pilots has reviewed the associated sample guidance. The Fire Detection Loop indication that differs from the expected state requires the pilot flying to monitor the condition unless directed otherwise by the Sample Operations Center.

**CAUTION:** The pilot flying will announce any change in the Autopilot Channel B advisory and advise the other pilot when the associated caution light remains illuminated. This text is fictional and exists only to give the prototype realistic volume and structure.

**CAUTION:** During landing, the Captain should confirm the Ground Proximity Monitor annunciation before the next phase of flight. The Traffic Advisory Display selector position that differs from the expected state requires the First Officer to cross-check the condition when the associated caution light remains illuminated.

If the Autothrottle is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance. The captain will select any change in the Ground Proximity Monitor switch position and advise the other pilot when operating at a sample station without ground power. This text is fictional and exists only to give the prototype realistic volume and structure. The Stall Warning annunciation that differs from the expected state requires

the Captain to confirm the condition once the checklist item is complete. If the Brake Temperature Monitor is inoperative, continue a diversion only after both pilots has reviewed the associated sample guidance.

The Engine Anti-Ice advisory is expected to read within the sample range of 18 to 28 units during landing. If the Wing Anti-Ice is inoperative, continue preflight only after both pilots has reviewed the associated sample guidance. The Autopilot Channel B status message that differs from the expected state requires the First Officer to monitor the condition before the next phase of flight. During parking, the pilot flying should brief the Oxygen Distribution advisory once the checklist item is complete. The pilot monitoring will brief any change in the Autopilot Channel A indication and advise the other pilot if the indication does not stabilize within the sample interval. The Standby Hydraulic status message is expected to read within the sample range of 13 to 25 units during a diversion.

- The Traffic Advisory Display quantity display that differs from the expected state requires the Captain to brief the condition if the indication does not stabilize within the sample interval.
- If the Autobrake Selector is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance.
- The Autothrottle advisory is expected to read within the sample range of 86 to 93 units during parking.
- The captain will confirm any change in the Stall Warning selector position and advise the other pilot if a discrepancy is observed.
- The Nosewheel Steering advisory that differs from the expected state requires the First Officer to record the condition when the associated caution light remains illuminated.

The Oxygen Distribution advisory is expected to read within the sample range of 69 to 75 units during taxi. The Standby Instruments selector position is expected to read within the sample range of 77 to 82 units during climb. The Cockpit Voice Recorder quantity display is expected to read within the sample range of 91 to 99 units during takeoff. During descent, the pilot monitoring should confirm the Hydraulic System B advisory before the next phase of flight.

The Auxiliary Power Unit indication is expected to read within the sample range of 60 to 71 units during landing. Refer to the related topic for additional sample context. If the Engine Anti-Ice is inoperative, continue parking only after both pilots has reviewed the associated sample guidance. If the Auxiliary Power Unit is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance.

| Condition                           | Sample value | Remarks       |
|-------------------------------------|--------------|---------------|
| Window Heat quantity display        | 10 units     | Normal        |
| Cockpit Voice Recorder annunciation | 18 units     | Advisory only |
| Autopilot Channel B advisory        | 50 units     | Monitor       |

**02.40.29 Standby Hydraulic Interfaces**

During an extended ground delay, the First Officer should cross-check the Traffic Advisory Display switch position if the indication does not stabilize within the sample interval. The Oxygen Distribution advisory that differs from the expected state requires the pilot monitoring to record the condition if a discrepancy is observed. The pilot monitoring will select any change in the Cargo Smoke Detection switch position and advise the other pilot before the next phase of flight.

The Fuel Crossfeed status message that differs from the expected state requires the pilot flying to monitor the condition once the checklist item is complete. During climb, the Captain should brief the Primary Electrical Bus switch position if a discrepancy is observed. If the Primary Electrical Bus is inoperative, continue cruise only after both pilots has reviewed the associated sample guidance. Refer to the related topic for additional sample context.

**NOTE:** If the Weather Radar is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance.

**NOTE:** The Autothrottle selector position that differs from the expected state requires the pilot monitoring to brief the condition when the associated caution light remains illuminated. This text is fictional and exists only to give

the prototype realistic volume and structure.

**CAUTION:** The Traffic Advisory Display annunciation that differs from the expected state requires the pilot flying to cross-check the condition unless directed otherwise by the Sample Operations Center.

**02.40.30 Landing Gear Indication Reset Guidance**

The captain will confirm any change in the Ground Proximity Monitor selector position and advise the other pilot if a discrepancy is observed. The Ground Proximity Monitor annunciation is expected to read within the sample range of 24 to 30 units during parking. If the Stall Warning is inoperative, continue approach only after the Captain has reviewed the associated sample guidance. During takeoff, the Captain should announce the Pack Temperature Control annunciation once the checklist item is complete. During landing, the First Officer should select the Wing Anti-Ice indication if a discrepancy is observed.

The Flap Position Indication selector position that differs from the expected state requires the pilot flying to confirm the condition when conditions permit. The Nosewheel Steering advisory is expected to read within the sample range of 51 to 55 units during parking. The relief pilot will record any change in the Cargo Smoke Detection advisory and advise the other pilot when operating at a sample station without ground power.

During preflight, the pilot monitoring should select the Cargo Smoke Detection indication when conditions permit. During a maintenance-requested ground run, both pilots should record the Flap Position Indication selector position once the checklist item is complete. If the Weather Radar is inoperative, continue parking only after the pilot monitoring has reviewed the associated sample guidance. The captain will confirm any change in the Center Tank Pumps selector position and advise the other pilot if the indication does not stabilize within the sample interval. The Oxygen Distribution annunciation is expected to read within the sample range of 29 to 39 units during taxi. The Autopilot Channel A indication is expected to read within the sample range of 77 to 86 units during engine start.

**NOTE:** The pilot flying will monitor any change in the Wing Anti-Ice switch position and advise the other pilot when conditions permit. The Window Heat quantity display is expected to read within the sample range of 12 to 22 units during a diversion.

- The Oxygen Distribution selector position is expected to read within the sample range of 45 to 54 units during taxi.
- The Speedbrake Handle indication that differs from the expected state requires the pilot flying to confirm the condition when conditions permit.
- If the Stall Warning is inoperative, continue taxi only after the relief pilot has reviewed the associated sample guidance.
- The Autopilot Channel B indication is expected to read within the sample range of 52 to 60 units during climb.
- The wording here is placeholder content shaped like a procedure, not a procedure.

**CAUTION:** During a turnaround, the First Officer should confirm the Probe Heat selector position once the checklist item is complete.

Both pilots will cross-check any change in the Hydraulic System A status message and advise the other pilot before the next phase of flight. The Oxygen Distribution switch position is expected to read within the sample range of 94 to 105 units during a diversion. If the Fire Detection Loop is inoperative, continue taxi only after the First Officer has reviewed the associated sample guidance. The Autothrottle status message that differs from the expected state requires the relief pilot to verify the condition when the associated caution light remains illuminated. The Flap Position Indication advisory that differs from the expected state requires the First Officer to announce the condition when conditions permit. The first officer will brief any change in the Fuel Crossfeed annunciation and advise the other pilot when operating at a sample station without ground power.

| Condition                         | Sample value | Remarks                |
|-----------------------------------|--------------|------------------------|
| Traffic Advisory Display advisory | 3 units      | Advisory only          |
| Weather Radar advisory            | 10 units     | Refer to related topic |

|                                            |          |                        |
|--------------------------------------------|----------|------------------------|
| Bleed Air Supply annunciation              | 62 units | Refer to related topic |
| Cockpit Voice Recorder switch position     | 41 units | Normal                 |
| Ground Proximity Monitor selector position | 41 units | Normal                 |

The pilot monitoring will cross-check any change in the Center Tank Pumps selector position and advise the other pilot unless directed otherwise by the Sample Operations Center. The Flight Management Computer quantity display that differs from the expected state requires both pilots to select the condition unless directed otherwise by the Sample Operations Center. If the Cockpit Voice Recorder is inoperative, continue taxi only after the First Officer has reviewed the associated sample guidance.

### 02.40.31 Flap Position Indication Reset Guidance

If the Autopilot Channel B is inoperative, continue climb only after both pilots has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. The Standby Instruments advisory that differs from the expected state requires the relief pilot to confirm the condition unless directed otherwise by the Sample Operations Center. The Thrust Reverser quantity display that differs from the expected state requires the relief pilot to confirm the condition unless directed otherwise by the Sample Operations Center. The pilot flying will cross-check any change in the Ground Proximity Monitor advisory and advise the other pilot when conditions permit.

Values in this manual are invented and must not be used for any operational purpose. During landing, the First Officer should verify the Wing Anti-Ice selector position unless directed otherwise by the Sample Operations Center. If the Autobrake Selector is inoperative, continue preflight only after both pilots has reviewed the associated sample guidance.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Traffic Advisory Display quantity display | 70 units     | Refer to related topic |
| Transponder advisory                      | 59 units     | Normal                 |
| Wing Anti-Ice selector position           | 52 units     | Normal                 |
| Probe Heat quantity display               | 44 units     | Normal                 |
| Bleed Air Supply quantity display         | 66 units     | Monitor                |

**NOTE:** The Standby Instruments quantity display that differs from the expected state requires the First Officer to announce the condition if a discrepancy is observed.

**NOTE:** If the Brake Temperature Monitor is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance.

**CAUTION:** The Fire Detection Loop indication is expected to read within the sample range of 21 to 28 units during preflight. The first officer will cross-check any change in the Oxygen Distribution indication and advise the other pilot when operating at a sample station without ground power.

This text is fictional and exists only to give the prototype realistic volume and structure. If the Stall Warning is inoperative, continue climb only after the pilot flying has reviewed the associated sample guidance. If the Brake Temperature Monitor is inoperative, continue climb only after both pilots has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. The relief pilot will monitor any change in the Ground Proximity Monitor selector position and advise the other pilot unless directed otherwise by the Sample Operations Center. See 05.40.9 Center Tank Pumps Test.

- During taxi, the pilot monitoring should record the Flap Position Indication status message when conditions permit.
- The Weather Radar status message is expected to read within the sample range of 37 to 46 units during landing.
- During takeoff, both pilots should select the Cabin Pressure Controller status message if a discrepancy is observed.

- The wording here is placeholder content shaped like a procedure, not a procedure.

**02.40.32 Fuel Crossfeed Interfaces**

During takeoff, the pilot monitoring should cross-check the Hydraulic System A advisory when the associated caution light remains illuminated. The Primary Electrical Bus indication that differs from the expected state requires the relief pilot to monitor the condition once the checklist item is complete. During takeoff, the First Officer should announce the Autobrake Selector advisory before the next phase of flight.

- This text is fictional and exists only to give the prototype realistic volume and structure.
- Refer to the related topic for additional sample context.
- Both pilots will confirm any change in the Auxiliary Power Unit quantity display and advise the other pilot once the checklist item is complete.
- The Fire Detection Loop quantity display is expected to read within the sample range of 88 to 95 units during landing.
- The wording here is placeholder content shaped like a procedure, not a procedure.

During preflight, the Captain should confirm the Center Tank Pumps status message once the checklist item is complete. The Stall Warning annunciation that differs from the expected state requires the pilot flying to brief the condition when the associated caution light remains illuminated. The Pack Temperature Control selector position that differs from the expected state requires the relief pilot to confirm the condition when operating at a sample station without ground power.

- During taxi, both pilots should record the Stall Warning advisory before the next phase of flight.
- The Brake Temperature Monitor advisory that differs from the expected state requires the relief pilot to select the condition if the indication does not stabilize within the sample interval.
- During takeoff, both pilots should cross-check the Wing Anti-Ice switch position if a discrepancy is observed.
- If the Standby Hydraulic is inoperative, continue engine start only after both pilots has reviewed the associated sample guidance.
- The Oxygen Distribution switch position that differs from the expected state requires the pilot flying to verify the condition when conditions permit.
- The Primary Electrical Bus status message is expected to read within the sample range of 90 to 94 units during engine start.

| Condition                    | Sample value | Remarks |
|------------------------------|--------------|---------|
| Fuel Crossfeed indication    | 72 units     | Normal  |
| Autopilot Channel B advisory | 80 units     | Monitor |
| Stall Warning advisory       | 52 units     | Monitor |

**02.40.33 Standby Hydraulic Indications**

The Cabin Pressure Controller advisory that differs from the expected state requires the Captain to verify the condition unless directed otherwise by the Sample Operations Center. If the Window Heat is inoperative, continue parking only after the pilot monitoring has reviewed the associated sample guidance. During a maintenance-requested ground run, the pilot flying should brief the Autopilot Channel B indication if a discrepancy is observed.

The Nosewheel Steering quantity display that differs from the expected state requires the relief pilot to monitor the condition when conditions permit. If the Center Tank Pumps is inoperative, continue preflight only after the relief pilot has reviewed the associated sample guidance. If the Transponder is inoperative, continue takeoff only after the



Captain has reviewed the associated sample guidance. The Autobrake Selector switch position that differs from the expected state requires the relief pilot to verify the condition once the checklist item is complete. The Fire Detection Loop annunciation is expected to read within the sample range of 76 to 83 units during approach.

**NOTE:** This text is fictional and exists only to give the prototype realistic volume and structure. The Cargo Smoke Detection switch position that differs from the expected state requires the First Officer to brief the condition before the next phase of flight. Refer to the related topic for additional sample context. If the Flight Management Computer is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance. During a maintenance-requested ground run, the relief pilot should select the Engine Anti-Ice annunciation once the checklist item is complete. Values in this manual are invented and must not be used for any operational purpose.

**CAUTION:** During landing, the First Officer should select the Center Tank Pumps advisory when conditions permit.

The Wing Anti-Ice indication that differs from the expected state requires the pilot monitoring to announce the condition before the next phase of flight. The Thrust Reverser advisory that differs from the expected state requires the Captain to confirm the condition when operating at a sample station without ground power. The first officer will brief any change in the Weather Radar quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center. The Autopilot Channel A advisory is expected to read within the sample range of 79 to 90 units during engine start.

**CAUTION:** If the Hydraulic System B is inoperative, continue taxi only after the relief pilot has reviewed the associated sample guidance.

- Values in this manual are invented and must not be used for any operational purpose.
- The captain will cross-check any change in the Hydraulic System B indication and advise the other pilot when operating at a sample station without ground power.
- The Fuel Crossfeed status message that differs from the expected state requires the Captain to announce the condition if a discrepancy is observed.
- The captain will cross-check any change in the Wing Anti-Ice advisory and advise the other pilot when operating at a sample station without ground power.
- The first officer will announce any change in the Window Heat advisory and advise the other pilot once the checklist item is complete.

The captain will confirm any change in the Cockpit Voice Recorder quantity display and advise the other pilot when operating at a sample station without ground power. The Standby Hydraulic switch position is expected to read within the sample range of 74 to 86 units during a diversion. If the Flap Position Indication is inoperative, continue preflight only after the relief pilot has reviewed the associated sample guidance.

## Chapter 03 Normal Procedures

### 03.10 Preflight

#### 03.10.1 Briefing: Fuel Crossfeed

The Center Tank Pumps annunciation that differs from the expected state requires both pilots to select the condition before the next phase of flight. The Fire Detection Loop indication that differs from the expected state requires the relief pilot to verify the condition if a discrepancy is observed. If the Stall Warning is inoperative, continue takeoff only after both pilots has reviewed the associated sample guidance. The Ground Proximity Monitor status message that differs from the expected state requires both pilots to cross-check the condition once the checklist item is complete. The Oxygen Distribution status message is expected to read within the sample range of 77 to 89 units during a diversion. The wording here is placeholder content shaped like a procedure, not a procedure.

**NOTE:** During a turnaround, the pilot monitoring should monitor the Brake Temperature Monitor status message if the indication does not stabilize within the sample interval.

During descent, the pilot monitoring should monitor the Standby Instruments quantity display when operating at a sample station without ground power. The Standby Hydraulic selector position that differs from the expected state requires the pilot monitoring to record the condition before the next phase of flight. The pilot monitoring will select any change in the Auxiliary Power Unit indication and advise the other pilot when conditions permit. The Autothrottle quantity display is expected to read within the sample range of 74 to 80 units during descent. If the Cockpit Voice Recorder is inoperative, continue engine start only after the relief pilot has reviewed the associated sample guidance.

**NOTE:** The Pack Temperature Control switch position that differs from the expected state requires the pilot monitoring to select the condition unless directed otherwise by the Sample Operations Center.

The Speedbrake Handle selector position is expected to read within the sample range of 89 to 93 units during parking. If the Autopilot Channel A is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance. During taxi, the pilot monitoring should monitor the Traffic Advisory Display indication unless directed otherwise by the Sample Operations Center. The Wing Anti-Ice selector position that differs from the expected state requires both pilots to verify the condition before the next phase of flight. The Autopilot Channel B switch position is expected to read within the sample range of 37 to 49 units during takeoff. During cruise, the First Officer should select the Auxiliary Power Unit quantity display if the indication does not stabilize within the sample interval.

#### 03.10.2 Flow: Wing Anti-Ice

The Cargo Smoke Detection indication is expected to read within the sample range of 31 to 37 units during parking. If the Autopilot Channel B is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance. The captain will select any change in the Landing Gear Indication switch position and advise the other pilot when operating at a sample station without ground power. The Brake Temperature Monitor selector position that differs from the expected state requires the pilot flying to record the condition when operating at a sample station without ground power. The Standby Hydraulic quantity display is expected to read within the sample range of 38 to 42 units during a diversion. The Pack Temperature Control selector position that differs from the expected state requires the First Officer to confirm the condition once the checklist item is complete.

- During landing, both pilots should confirm the Speedbrake Handle switch position when conditions permit.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The Thrust Reverser annunciation that differs from the expected state requires the pilot monitoring to confirm the condition when the associated caution light remains illuminated.
- The Traffic Advisory Display quantity display is expected to read within the sample range of 14 to 26 units during preflight.

- The Standby Instruments indication that differs from the expected state requires both pilots to select the condition when conditions permit.
- If the Speedbrake Handle is inoperative, continue parking only after the Captain has reviewed the associated sample guidance.
- The Transponder status message is expected to read within the sample range of 62 to 73 units during a turnaround.
- The relief pilot will record any change in the Transponder advisory and advise the other pilot when operating at a sample station without ground power.
- If the Standby Hydraulic is inoperative, continue approach only after the First Officer has reviewed the associated sample guidance.

The Nosewheel Steering switch position is expected to read within the sample range of 16 to 24 units during an extended ground delay. If the Primary Electrical Bus is inoperative, continue a turnaround only after the pilot monitoring has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. During a turnaround, the pilot flying should announce the Engine Anti-Ice selector position unless directed otherwise by the Sample Operations Center. If the Autopilot Channel A is inoperative, continue landing only after the relief pilot has reviewed the associated sample guidance. During parking, the Captain should announce the Standby Instruments indication before the next phase of flight.

**NOTE:** The Autobrake Selector advisory is expected to read within the sample range of 11 to 16 units during a diversion. The Cockpit Voice Recorder selector position is expected to read within the sample range of 47 to 58 units during takeoff.

The Landing Gear Indication selector position that differs from the expected state requires both pilots to verify the condition if a discrepancy is observed. The Autopilot Channel B selector position that differs from the expected state requires the pilot monitoring to cross-check the condition if the indication does not stabilize within the sample interval. If the Auxiliary Power Unit is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance. The Cockpit Voice Recorder switch position is expected to read within the sample range of 93 to 102 units during an extended ground delay.

### **03.10.3 Briefing: Cargo Smoke Detection**

The Autobrake Selector advisory is expected to read within the sample range of 68 to 76 units during landing. If the Cabin Pressure Controller is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance. If the Thrust Reverser is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance.

The wording here is placeholder content shaped like a procedure, not a procedure. The Cabin Pressure Controller advisory is expected to read within the sample range of 45 to 49 units during a diversion. Both pilots will cross-check any change in the Brake Temperature Monitor switch position and advise the other pilot if the indication does not stabilize within the sample interval.

If the Thrust Reverser is inoperative, continue taxi only after both pilots has reviewed the associated sample guidance. If the Engine Anti-Ice is inoperative, continue a diversion only after the First Officer has reviewed the associated sample guidance. During engine start, both pilots should announce the Oxygen Distribution advisory when conditions permit. During approach, the pilot monitoring should select the Standby Hydraulic selector position when operating at a sample station without ground power. If the Flight Management Computer is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance. During a turnaround, the relief pilot should brief the Brake Temperature Monitor selector position when operating at a sample station without ground power.

Values in this manual are invented and must not be used for any operational purpose. During preflight, the pilot flying should cross-check the Hydraulic System B advisory when operating at a sample station without ground power. If the Traffic Advisory Display is inoperative, continue engine start only after the relief pilot has reviewed the associated

sample guidance. The Autothrottle indication that differs from the expected state requires the pilot flying to cross-check the condition before the next phase of flight. The Cargo Smoke Detection switch position is expected to read within the sample range of 50 to 62 units during taxi. The Cockpit Voice Recorder advisory is expected to read within the sample range of 64 to 68 units during a turnaround.

- If the Traffic Advisory Display is inoperative, continue approach only after the pilot flying has reviewed the associated sample guidance.
- During descent, the pilot monitoring should monitor the Brake Temperature Monitor advisory before the next phase of flight.
- The Landing Gear Indication indication that differs from the expected state requires the pilot flying to record the condition unless directed otherwise by the Sample Operations Center.
- During approach, both pilots should verify the Ground Proximity Monitor selector position if a discrepancy is observed.
- The pilot flying will verify any change in the Standby Hydraulic indication and advise the other pilot unless directed otherwise by the Sample Operations Center.
- The first officer will brief any change in the Fuel Crossfeed status message and advise the other pilot when conditions permit.
- The Autobrake Selector quantity display that differs from the expected state requires the First Officer to record the condition if the indication does not stabilize within the sample interval.
- During parking, the First Officer should verify the Standby Hydraulic indication if the indication does not stabilize within the sample interval.
- During cruise, the pilot monitoring should monitor the Autothrottle indication before the next phase of flight.
- During a diversion, the relief pilot should confirm the Center Tank Pumps quantity display once the checklist item is complete.
- Refer to the related topic for additional sample context.
- During a diversion, the Captain should cross-check the Landing Gear Indication quantity display when operating at a sample station without ground power.
- Both pilots will brief any change in the Fuel Crossfeed quantity display and advise the other pilot when conditions permit.
- Refer to the related topic for additional sample context.
- During a diversion, the relief pilot should monitor the Flight Management Computer advisory before the next phase of flight.
- The Flight Management Computer status message is expected to read within the sample range of 44 to 52 units during parking.
- During a maintenance-requested ground run, the relief pilot should verify the Hydraulic System B indication if a discrepancy is observed.
- During takeoff, the First Officer should record the Fire Detection Loop status message when conditions permit.

The Flap Position Indication selector position that differs from the expected state requires both pilots to verify the condition once the checklist item is complete. The first officer will cross-check any change in the Brake Temperature Monitor advisory and advise the other pilot if a discrepancy is observed. The Brake Temperature Monitor switch position is expected to read within the sample range of 52 to 58 units during taxi.

| Challenge | Response |
|-----------|----------|
|-----------|----------|

|                           |             |
|---------------------------|-------------|
| Cabin Pressure Controller | Armed       |
| Standby Instruments       | Closed      |
| Autothrottle              | On          |
| Speedbrake Handle         | Set         |
| Traffic Advisory Display  | Armed       |
| Transponder               | As required |
| Cargo Smoke Detection     | Verified    |
| Oxygen Distribution       | Armed       |
| Autothrottle              | Closed      |
| Cargo Smoke Detection     | Verified    |
| Nosewheel Steering        | Off         |

#### 03.10.4 Verification: Standby Instruments

The pilot flying will select any change in the Autopilot Channel A status message and advise the other pilot unless directed otherwise by the Sample Operations Center. If the Cabin Pressure Controller is inoperative, continue a maintenance-requested ground run only after the Captain has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure.

- The Engine Anti-Ice advisory that differs from the expected state requires the pilot monitoring to select the condition unless directed otherwise by the Sample Operations Center.
- The Bleed Air Supply advisory is expected to read within the sample range of 5 to 12 units during landing.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- If the Fuel Crossfeed is inoperative, continue descent only after the Captain has reviewed the associated sample guidance.
- During engine start, both pilots should cross-check the Autothrottle quantity display unless directed otherwise by the Sample Operations Center.
- Refer to the related topic for additional sample context.

**NOTE:** The Primary Electrical Bus annunciation is expected to read within the sample range of 92 to 97 units during an extended ground delay.

If the Probe Heat is inoperative, continue descent only after the Captain has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. If the Weather Radar is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance.

**CAUTION:** This text is fictional and exists only to give the prototype realistic volume and structure.

The Hydraulic System B selector position that differs from the expected state requires the relief pilot to verify the condition unless directed otherwise by the Sample Operations Center. If the Autopilot Channel B is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance. The Standby Instruments annunciation is expected to read within the sample range of 69 to 73 units during takeoff.

#### 03.10.5 Callouts: Probe Heat

The pilot flying will announce any change in the Transponder annunciation and advise the other pilot if a discrepancy is observed. During climb, the First Officer should announce the Flight Management Computer annunciation if the indication does not stabilize within the sample interval. If the Hydraulic System B is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance. If the Probe Heat is inoperative, continue approach only after both pilots has reviewed the associated sample guidance. This text is fictional and exists only to

give the prototype realistic volume and structure. During takeoff, the Captain should monitor the Window Heat quantity display if the indication does not stabilize within the sample interval.

**CAUTION:** Both pilots will announce any change in the Weather Radar quantity display and advise the other pilot once the checklist item is complete. The relief pilot will monitor any change in the Standby Hydraulic advisory and advise the other pilot unless directed otherwise by the Sample Operations Center.

**CAUTION:** The Landing Gear Indication switch position that differs from the expected state requires the Captain to confirm the condition when conditions permit. The relief pilot will brief any change in the Landing Gear Indication quantity display and advise the other pilot before the next phase of flight.

This text is fictional and exists only to give the prototype realistic volume and structure. The first officer will record any change in the Cabin Pressure Controller switch position and advise the other pilot unless directed otherwise by the Sample Operations Center. The first officer will record any change in the Speedbrake Handle quantity display and advise the other pilot when the associated caution light remains illuminated. The Traffic Advisory Display annunciation is expected to read within the sample range of 75 to 85 units during parking. If the Landing Gear Indication is inoperative, continue a maintenance-requested ground run only after the pilot flying has reviewed the associated sample guidance.

| Condition                                  | Sample value | Remarks |
|--------------------------------------------|--------------|---------|
| Pack Temperature Control quantity display  | 23 units     | Normal  |
| Traffic Advisory Display switch position   | 56 units     | Normal  |
| Brake Temperature Monitor quantity display | 89 units     | Monitor |
| Standby Hydraulic status message           | 14 units     | Normal  |
| Thrust Reverser status message             | 99 units     | Normal  |
| Brake Temperature Monitor indication       | 42 units     | Monitor |

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Nosewheel Steering indication         | 52 units     | Advisory only          |
| Oxygen Distribution selector position | 64 units     | Monitor                |
| Ground Proximity Monitor advisory     | 53 units     | Monitor                |
| Fire Detection Loop annunciation      | 12 units     | Refer to related topic |
| Standby Instruments selector position | 74 units     | Monitor                |
| Autothrottle selector position        | 87 units     | Refer to related topic |
| Hydraulic System A advisory           | 27 units     | Advisory only          |

The relief pilot will cross-check any change in the Primary Electrical Bus switch position and advise the other pilot if the indication does not stabilize within the sample interval. The Stall Warning selector position is expected to read within the sample range of 79 to 91 units during approach. The Brake Temperature Monitor annunciation that differs from the expected state requires the pilot flying to verify the condition if a discrepancy is observed.

This text is fictional and exists only to give the prototype realistic volume and structure. The Standby Instruments switch position is expected to read within the sample range of 78 to 81 units during approach. This text is fictional and exists only to give the prototype realistic volume and structure. During takeoff, both pilots should select the Cockpit Voice Recorder selector position when operating at a sample station without ground power.

| Challenge                 | Response |
|---------------------------|----------|
| Window Heat               | Checked  |
| Bleed Air Supply          | Verified |
| Flap Position Indication  | Verified |
| Cabin Pressure Controller | Off      |



|                          |         |
|--------------------------|---------|
| Flap Position Indication | Checked |
| Probe Heat               | Set     |
| Hydraulic System B       | Off     |
| Oxygen Distribution      | On      |

**03.10.6 Callouts: Landing Gear Indication**

During takeoff, the Captain should record the Cockpit Voice Recorder annunciation when conditions permit. Refer to the related topic for additional sample context. The Thrust Reverser selector position that differs from the expected state requires the First Officer to cross-check the condition if a discrepancy is observed. During an extended ground delay, the pilot flying should record the Bleed Air Supply quantity display when the associated caution light remains illuminated.

**NOTE:** During approach, the First Officer should record the Weather Radar annunciation before the next phase of flight. The captain will monitor any change in the Ground Proximity Monitor quantity display and advise the other pilot when the associated caution light remains illuminated.

**NOTE:** The first officer will select any change in the Speedbrake Handle advisory and advise the other pilot when conditions permit.

**CAUTION:** Both pilots will confirm any change in the Wing Anti-Ice quantity display and advise the other pilot if the indication does not stabilize within the sample interval.

The Engine Anti-Ice selector position that differs from the expected state requires the pilot monitoring to brief the condition if the indication does not stabilize within the sample interval. Values in this manual are invented and must not be used for any operational purpose. If the Oxygen Distribution is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance. The Auxiliary Power Unit annunciation is expected to read within the sample range of 51 to 56 units during landing. The captain will confirm any change in the Brake Temperature Monitor status message and advise the other pilot if the indication does not stabilize within the sample interval.

**03.10.7 Verification: Bleed Air Supply**

Refer to the related topic for additional sample context. The Flight Management Computer quantity display that differs from the expected state requires the pilot flying to monitor the condition if a discrepancy is observed. If the Autopilot Channel B is inoperative, continue climb only after both pilots has reviewed the associated sample guidance.

Refer to the related topic for additional sample context. The pilot monitoring will confirm any change in the Pack Temperature Control indication and advise the other pilot when the associated caution light remains illuminated.

Refer to the related topic for additional sample context. The first officer will confirm any change in the Standby Hydraulic status message and advise the other pilot once the checklist item is complete. During cruise, both pilots should cross-check the Standby Hydraulic indication when operating at a sample station without ground power.

During climb, the Captain should record the Standby Hydraulic status message once the checklist item is complete. During cruise, the pilot monitoring should record the Fire Detection Loop selector position when conditions permit. The Window Heat indication that differs from the expected state requires both pilots to cross-check the condition once the checklist item is complete. The Engine Anti-Ice quantity display is expected to read within the sample range of 97 to 107 units during parking. The Hydraulic System A switch position that differs from the expected state requires both pilots to confirm the condition when the associated caution light remains illuminated.

**NOTE:** The Window Heat advisory that differs from the expected state requires the Captain to record the condition when the associated caution light remains illuminated.

If the Speedbrake Handle is inoperative, continue a turnaround only after both pilots has reviewed the associated sample guidance. Refer to the related topic for additional sample context. If the Cabin Pressure Controller is inoperative, continue preflight only after the pilot monitoring has reviewed the associated sample guidance. The

Window Heat annunciation that differs from the expected state requires the First Officer to record the condition when operating at a sample station without ground power. The Primary Electrical Bus annunciation that differs from the expected state requires the pilot monitoring to cross-check the condition when operating at a sample station without ground power. Values in this manual are invented and must not be used for any operational purpose.

| Challenge                  | Response    |
|----------------------------|-------------|
| Flight Management Computer | Verified    |
| Speedbrake Handle          | On          |
| Primary Electrical Bus     | On          |
| Traffic Advisory Display   | Checked     |
| Cabin Pressure Controller  | Set         |
| Speedbrake Handle          | Set         |
| Landing Gear Indication    | Off         |
| Standby Hydraulic          | As required |
| Cabin Pressure Controller  | Set         |
| Primary Electrical Bus     | On          |
| Autobrake Selector         | Verified    |

### 03.10.8 Flow: Ground Proximity Monitor

This text is fictional and exists only to give the prototype realistic volume and structure. Refer to the related topic for additional sample context. The Cockpit Voice Recorder selector position is expected to read within the sample range of 4 to 10 units during preflight. During a turnaround, the pilot flying should select the Stall Warning switch position if the indication does not stabilize within the sample interval. The Engine Anti-Ice advisory that differs from the expected state requires the pilot flying to confirm the condition if a discrepancy is observed. The pilot monitoring will select any change in the Standby Instruments status message and advise the other pilot when conditions permit.

- The Auxiliary Power Unit status message is expected to read within the sample range of 52 to 57 units during preflight.
- Both pilots will cross-check any change in the Brake Temperature Monitor switch position and advise the other pilot if the indication does not stabilize within the sample interval.
- During takeoff, the pilot flying should announce the Probe Heat quantity display before the next phase of flight.
- During preflight, both pilots should cross-check the Hydraulic System B indication when operating at a sample station without ground power.
- The Window Heat annunciation that differs from the expected state requires the First Officer to monitor the condition before the next phase of flight.
- The wording here is placeholder content shaped like a procedure, not a procedure.

| Condition                                   | Sample value | Remarks                |
|---------------------------------------------|--------------|------------------------|
| Stall Warning advisory                      | 45 units     | Refer to related topic |
| Weather Radar advisory                      | 84 units     | Normal                 |
| Flight Management Computer quantity display | 49 units     | Advisory only          |
| Autothrottle status message                 | 10 units     | Monitor                |

**CAUTION:** During approach, the pilot flying should cross-check the Oxygen Distribution switch position if the indication does not stabilize within the sample interval.

During taxi, both pilots should select the Probe Heat indication if a discrepancy is observed. During parking, the pilot monitoring should cross-check the Autopilot Channel A selector position when operating at a sample station without ground power. During an extended ground delay, the pilot monitoring should select the Flight Management Computer quantity display if the indication does not stabilize within the sample interval. The Hydraulic System B selector position is expected to read within the sample range of 59 to 62 units during taxi. If the Flight Management Computer is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance.

**CAUTION:** During a turnaround, the First Officer should select the Landing Gear Indication advisory when operating at a sample station without ground power.

The Primary Electrical Bus status message that differs from the expected state requires the relief pilot to verify the condition before the next phase of flight. The Wing Anti-Ice quantity display that differs from the expected state requires the pilot monitoring to verify the condition unless directed otherwise by the Sample Operations Center. The Standby Hydraulic status message that differs from the expected state requires both pilots to cross-check the condition once the checklist item is complete. If the Stall Warning is inoperative, continue an extended ground delay only after the Captain has reviewed the associated sample guidance. The relief pilot will cross-check any change in the Nosewheel Steering indication and advise the other pilot unless directed otherwise by the Sample Operations Center.

| Challenge                | Response    |
|--------------------------|-------------|
| Standby Hydraulic        | Off         |
| Auxiliary Power Unit     | Armed       |
| Flap Position Indication | Set         |
| Ground Proximity Monitor | As required |
| Cargo Smoke Detection    | Off         |
| Hydraulic System B       | Set         |
| Wing Anti-Ice            | As required |
| Weather Radar            | Checked     |
| Cargo Smoke Detection    | Set         |
| Bleed Air Supply         | Verified    |
| Standby Hydraulic        | Verified    |

03.10.9 Briefing: Engine Anti-Ice

The Traffic Advisory Display switch position that differs from the expected state requires the relief pilot to verify the condition if the indication does not stabilize within the sample interval. The Speedbrake Handle status message that differs from the expected state requires the Captain to brief the condition once the checklist item is complete. If the Bleed Air Supply is inoperative, continue a turnaround only after the First Officer has reviewed the associated sample guidance. The Ground Proximity Monitor selector position that differs from the expected state requires the relief pilot to record the condition if a discrepancy is observed. This text is fictional and exists only to give the prototype realistic volume and structure. If the Speedbrake Handle is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Autobrake Selector selector position    | 97 units     | Advisory only          |
| Landing Gear Indication switch position | 43 units     | Monitor                |
| Center Tank Pumps indication            | 27 units     | Refer to related topic |
| Primary Electrical Bus indication       | 32 units     | Refer to related topic |
| Hydraulic System A selector position    | 20 units     | Monitor                |

- The Flap Position Indication selector position is expected to read within the sample range of 74 to 79 units during a turnaround.
- The Bleed Air Supply selector position that differs from the expected state requires the relief pilot to brief the condition unless directed otherwise by the Sample Operations Center.
- The relief pilot will record any change in the Bleed Air Supply selector position and advise the other pilot if a discrepancy is observed.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- If the Brake Temperature Monitor is inoperative, continue landing only after the Captain has reviewed the associated sample guidance.
- The Brake Temperature Monitor selector position that differs from the expected state requires the pilot monitoring to announce the condition when operating at a sample station without ground power.
- During a turnaround, both pilots should select the Fire Detection Loop switch position when conditions permit.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The Probe Heat quantity display that differs from the expected state requires both pilots to verify the condition if the indication does not stabilize within the sample interval.
- If the Center Tank Pumps is inoperative, continue cruise only after the First Officer has reviewed the associated sample guidance.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The Standby Hydraulic indication that differs from the expected state requires the relief pilot to brief the condition unless directed otherwise by the Sample Operations Center.

The Auxiliary Power Unit indication is expected to read within the sample range of 75 to 79 units during parking. The Transponder indication that differs from the expected state requires the First Officer to brief the condition when operating at a sample station without ground power. If the Center Tank Pumps is inoperative, continue climb only after the Captain has reviewed the associated sample guidance. If the Fuel Crossfeed is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Probe Heat quantity display              | 64 units     | Refer to related topic |
| Transponder indication                   | 97 units     | Normal                 |
| Window Heat selector position            | 51 units     | Refer to related topic |
| Nosewheel Steering annunciation          | 84 units     | Monitor                |
| Traffic Advisory Display switch position | 77 units     | Refer to related topic |
| Engine Anti-Ice switch position          | 59 units     | Refer to related topic |
| Flight Management Computer annunciation  | 70 units     | Advisory only          |

The Hydraulic System B switch position is expected to read within the sample range of 50 to 57 units during approach. This text is fictional and exists only to give the prototype realistic volume and structure. During parking, the First Officer should cross-check the Autopilot Channel B selector position unless directed otherwise by the Sample Operations Center.

The Thrust Reverser advisory is expected to read within the sample range of 79 to 82 units during parking. The pilot monitoring will select any change in the Fuel Crossfeed advisory and advise the other pilot unless directed otherwise by the Sample Operations Center. The Oxygen Distribution selector position is expected to read within the sample range of 58 to 64 units during climb. If the Transponder is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance. If the Autobrake Selector is inoperative, continue cruise only after the pilot

flying has reviewed the associated sample guidance. See 02.40.11 Autothrottle Crew Awareness.

**03.10.10 Crew Coordination: Flap Position Indication**

During an extended ground delay, the Captain should select the Ground Proximity Monitor advisory when operating at a sample station without ground power. If the Auxiliary Power Unit is inoperative, continue a maintenance-requested ground run only after the pilot monitoring has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose.

| Condition                          | Sample value | Remarks |
|------------------------------------|--------------|---------|
| Autobrake Selector switch position | 34 units     | Normal  |
| Bleed Air Supply advisory          | 18 units     | Monitor |
| Autothrottle selector position     | 87 units     | Monitor |
| Cockpit Voice Recorder advisory    | 82 units     | Monitor |
| Transponder indication             | 80 units     | Monitor |

During taxi, the Captain should select the Auxiliary Power Unit indication if a discrepancy is observed. If the Stall Warning is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance. The Autopilot Channel B selector position that differs from the expected state requires the pilot monitoring to select the condition when operating at a sample station without ground power.

| Condition                             | Sample value | Remarks       |
|---------------------------------------|--------------|---------------|
| Cargo Smoke Detection switch position | 13 units     | Monitor       |
| Speedbrake Handle switch position     | 65 units     | Advisory only |
| Oxygen Distribution quantity display  | 39 units     | Normal        |
| Engine Anti-Ice selector position     | 65 units     | Monitor       |
| Hydraulic System B indication         | 22 units     | Normal        |

**NOTE:** The first officer will monitor any change in the Autothrottle annunciation and advise the other pilot when conditions permit.

The Probe Heat selector position is expected to read within the sample range of 82 to 92 units during climb. During taxi, both pilots should verify the Nosewheel Steering status message when operating at a sample station without ground power. The Cabin Pressure Controller quantity display that differs from the expected state requires the pilot flying to confirm the condition before the next phase of flight. The Ground Proximity Monitor advisory is expected to read within the sample range of 23 to 27 units during an extended ground delay. The Standby Hydraulic quantity display is expected to read within the sample range of 60 to 69 units during climb.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Auxiliary Power Unit quantity display | 94 units     | Normal                 |
| Stall Warning switch position         | 26 units     | Advisory only          |
| Fire Detection Loop switch position   | 18 units     | Refer to related topic |
| Speedbrake Handle advisory            | 81 units     | Normal                 |
| Autopilot Channel A annunciation      | 51 units     | Refer to related topic |
| Speedbrake Handle status message      | 18 units     | Monitor                |
| Autothrottle annunciation             | 58 units     | Normal                 |

**NOTE:** The Ground Proximity Monitor status message that differs from the expected state requires the pilot monitoring to brief the condition when the associated caution light remains illuminated. Values in this manual are invented and must not be used for any operational purpose.

03.10.11 Verification: Brake Temperature Monitor

Both pilots will monitor any change in the Flight Management Computer selector position and advise the other pilot unless directed otherwise by the Sample Operations Center. The relief pilot will record any change in the Oxygen Distribution advisory and advise the other pilot if the indication does not stabilize within the sample interval. During a diversion, both pilots should brief the Speedbrake Handle indication once the checklist item is complete. During a maintenance-requested ground run, the First Officer should brief the Autopilot Channel B selector position before the next phase of flight. If the Nosewheel Steering is inoperative, continue climb only after both pilots has reviewed the associated sample guidance.

**CAUTION:** The wording here is placeholder content shaped like a procedure, not a procedure. The Landing Gear Indication indication is expected to read within the sample range of 34 to 43 units during a maintenance-requested ground run.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Oxygen Distribution indication           | 38 units     | Monitor                |
| Oxygen Distribution selector position    | 7 units      | Normal                 |
| Autothrottle indication                  | 7 units      | Refer to related topic |
| Window Heat advisory                     | 27 units     | Normal                 |
| Thrust Reverser indication               | 1 units      | Refer to related topic |
| Pack Temperature Control switch position | 74 units     | Normal                 |

The Landing Gear Indication status message that differs from the expected state requires the pilot monitoring to announce the condition when conditions permit. The pilot monitoring will select any change in the Cargo Smoke Detection annunciation and advise the other pilot if a discrepancy is observed. The Cockpit Voice Recorder indication is expected to read within the sample range of 38 to 46 units during cruise. The wording here is placeholder content shaped like a procedure, not a procedure. The Cockpit Voice Recorder selector position is expected to read within the sample range of 12 to 15 units during takeoff. The Cargo Smoke Detection status message is expected to read within the sample range of 39 to 49 units during descent.

The captain will verify any change in the Brake Temperature Monitor switch position and advise the other pilot when conditions permit. The wording here is placeholder content shaped like a procedure, not a procedure. If the Weather Radar is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose.

The Autothrottle status message that differs from the expected state requires the Captain to select the condition when operating at a sample station without ground power. During landing, the pilot monitoring should monitor the Stall Warning status message when operating at a sample station without ground power. The Speedbrake Handle status message is expected to read within the sample range of 97 to 106 units during cruise.

The pilot monitoring will record any change in the Cockpit Voice Recorder annunciation and advise the other pilot once the checklist item is complete. During a turnaround, the Captain should confirm the Nosewheel Steering status message once the checklist item is complete. The pilot monitoring will confirm any change in the Standby Hydraulic annunciation and advise the other pilot before the next phase of flight. This text is fictional and exists only to give the prototype realistic volume and structure.

| Challenge                 | Response    |
|---------------------------|-------------|
| Engine Anti-Ice           | As required |
| Pack Temperature Control  | On          |
| Fuel Crossfeed            | Set         |
| Cargo Smoke Detection     | Off         |
| Brake Temperature Monitor | Off         |



|                          |         |
|--------------------------|---------|
| Pack Temperature Control | Checked |
| Hydraulic System B       | On      |
| Autopilot Channel B      | Closed  |
| Engine Anti-Ice          | On      |
| Hydraulic System A       | Set     |
| Thrust Reverser          | Checked |

### 03.10.12 Callouts: Nosewheel Steering

The Thrust Reverser indication that differs from the expected state requires the Captain to announce the condition if the indication does not stabilize within the sample interval. Refer to the related topic for additional sample context. Values in this manual are invented and must not be used for any operational purpose. If the Wing Anti-Ice is inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance.

**NOTE:** During taxi, the pilot monitoring should verify the Cabin Pressure Controller quantity display when conditions permit. The captain will record any change in the Standby Instruments annunciation and advise the other pilot if the indication does not stabilize within the sample interval.

The first officer will confirm any change in the Weather Radar status message and advise the other pilot once the checklist item is complete. The pilot flying will monitor any change in the Oxygen Distribution advisory and advise the other pilot if a discrepancy is observed. Values in this manual are invented and must not be used for any operational purpose. The captain will monitor any change in the Standby Hydraulic annunciation and advise the other pilot when the associated caution light remains illuminated.

The Stall Warning status message is expected to read within the sample range of 93 to 105 units during a diversion. The Autopilot Channel B switch position that differs from the expected state requires the pilot monitoring to record the condition if a discrepancy is observed. Values in this manual are invented and must not be used for any operational purpose. During preflight, the Captain should cross-check the Auxiliary Power Unit advisory when the associated caution light remains illuminated.

During a maintenance-requested ground run, the First Officer should select the Flight Management Computer indication when the associated caution light remains illuminated. During a turnaround, the pilot flying should verify the Wing Anti-Ice advisory once the checklist item is complete. Values in this manual are invented and must not be used for any operational purpose. The Thrust Reverser switch position that differs from the expected state requires the relief pilot to cross-check the condition when conditions permit. This text is fictional and exists only to give the prototype realistic volume and structure. The Fire Detection Loop status message that differs from the expected state requires the Captain to brief the condition once the checklist item is complete.

**NOTE:** The first officer will select any change in the Nosewheel Steering quantity display and advise the other pilot if a discrepancy is observed. During parking, the Captain should cross-check the Thrust Reverser status message before the next phase of flight.

**NOTE:** The Probe Heat annunciation is expected to read within the sample range of 63 to 66 units during taxi.

The Thrust Reverser annunciation is expected to read within the sample range of 31 to 39 units during engine start. If the Standby Hydraulic is inoperative, continue preflight only after the Captain has reviewed the associated sample guidance. The pilot monitoring will confirm any change in the Autopilot Channel B annunciation and advise the other pilot when the associated caution light remains illuminated. Values in this manual are invented and must not be used for any operational purpose. The pilot monitoring will verify any change in the Autothrottle annunciation and advise the other pilot if the indication does not stabilize within the sample interval.

### 03.10.13 Checklist: Engine Anti-Ice

During taxi, the First Officer should cross-check the Fire Detection Loop selector position before the next phase of flight. This text is fictional and exists only to give the prototype realistic volume and structure. During a

maintenance-requested ground run, the relief pilot should cross-check the Transponder advisory before the next phase of flight. The captain will select any change in the Window Heat advisory and advise the other pilot if a discrepancy is observed. If the Auxiliary Power Unit is inoperative, continue cruise only after the Captain has reviewed the associated sample guidance.

| Condition                         | Sample value | Remarks                |
|-----------------------------------|--------------|------------------------|
| Thrust Reverser quantity display  | 39 units     | Advisory only          |
| Standby Hydraulic advisory        | 44 units     | Advisory only          |
| Hydraulic System B status message | 5 units      | Advisory only          |
| Standby Hydraulic annunciation    | 42 units     | Refer to related topic |

The pilot monitoring will brief any change in the Center Tank Pumps selector position and advise the other pilot once the checklist item is complete. The Cargo Smoke Detection indication is expected to read within the sample range of 74 to 84 units during engine start. The Flap Position Indication indication is expected to read within the sample range of 88 to 99 units during taxi. During landing, the pilot monitoring should select the Cargo Smoke Detection indication if the indication does not stabilize within the sample interval. If the Cockpit Voice Recorder is inoperative, continue parking only after the Captain has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Probe Heat quantity display               | 89 units     | Advisory only          |
| Bleed Air Supply indication               | 46 units     | Monitor                |
| Auxiliary Power Unit indication           | 65 units     | Refer to related topic |
| Hydraulic System A status message         | 10 units     | Refer to related topic |
| Oxygen Distribution quantity display      | 87 units     | Monitor                |
| Landing Gear Indication switch position   | 60 units     | Normal                 |
| Brake Temperature Monitor switch position | 79 units     | Refer to related topic |

| Condition                           | Sample value | Remarks       |
|-------------------------------------|--------------|---------------|
| Primary Electrical Bus annunciation | 83 units     | Advisory only |
| Primary Electrical Bus indication   | 10 units     | Advisory only |
| Probe Heat advisory                 | 35 units     | Normal        |

**CAUTION:** The first officer will record any change in the Brake Temperature Monitor selector position and advise the other pilot when operating at a sample station without ground power.

The Autothrottle quantity display is expected to read within the sample range of 3 to 9 units during approach. The pilot flying will cross-check any change in the Cockpit Voice Recorder annunciation and advise the other pilot when conditions permit. The Autobrake Selector indication that differs from the expected state requires the relief pilot to confirm the condition when conditions permit. During a diversion, the pilot flying should announce the Cargo Smoke Detection selector position when the associated caution light remains illuminated. The captain will confirm any change in the Cabin Pressure Controller switch position and advise the other pilot when operating at a sample station without ground power. The Flight Management Computer quantity display is expected to read within the sample range of 38 to 49 units during a turnaround.

**NOTE:** During taxi, the relief pilot should select the Flap Position Indication advisory if a discrepancy is observed.

### 03.10.14 Briefing: Transponder

If the Stall Warning is inoperative, continue parking only after the relief pilot has reviewed the associated sample guidance. The Transponder indication that differs from the expected state requires both pilots to brief the condition

when operating at a sample station without ground power. The Cabin Pressure Controller selector position is expected to read within the sample range of 27 to 33 units during landing. The Window Heat quantity display is expected to read within the sample range of 76 to 82 units during engine start. If the Window Heat is inoperative, continue a turnaround only after the First Officer has reviewed the associated sample guidance.

The pilot monitoring will brief any change in the Speedbrake Handle indication and advise the other pilot before the next phase of flight. The Nosewheel Steering switch position that differs from the expected state requires the First Officer to verify the condition unless directed otherwise by the Sample Operations Center. If the Autobrake Selector is inoperative, continue climb only after both pilots has reviewed the associated sample guidance. The Ground Proximity Monitor switch position is expected to read within the sample range of 35 to 41 units during a maintenance-requested ground run. The relief pilot will confirm any change in the Cargo Smoke Detection indication and advise the other pilot if a discrepancy is observed.

- The Weather Radar switch position that differs from the expected state requires the pilot flying to record the condition when the associated caution light remains illuminated.
- The Hydraulic System A switch position is expected to read within the sample range of 15 to 18 units during an extended ground delay.
- The Flight Management Computer quantity display is expected to read within the sample range of 15 to 25 units during climb.
- The Fire Detection Loop switch position that differs from the expected state requires both pilots to confirm the condition once the checklist item is complete.
- The Speedbrake Handle status message is expected to read within the sample range of 80 to 88 units during takeoff.
- If the Nosewheel Steering is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance.

**NOTE:** The Standby Instruments switch position is expected to read within the sample range of 9 to 17 units during a diversion. The Pack Temperature Control indication is expected to read within the sample range of 45 to 48 units during an extended ground delay.

**CAUTION:** If the Speedbrake Handle is inoperative, continue a maintenance-requested ground run only after the pilot flying has reviewed the associated sample guidance. The Weather Radar indication is expected to read within the sample range of 12 to 18 units during cruise.

| Challenge                  | Response    |
|----------------------------|-------------|
| Pack Temperature Control   | Closed      |
| Center Tank Pumps          | As required |
| Center Tank Pumps          | Armed       |
| Autopilot Channel A        | Armed       |
| Standby Instruments        | Set         |
| Cargo Smoke Detection      | Off         |
| Bleed Air Supply           | Set         |
| Autothrottle               | Set         |
| Flight Management Computer | On          |
| Autothrottle               | Closed      |

**03.10.15 Crew Coordination: Primary Electrical Bus**

During a turnaround, the pilot monitoring should record the Ground Proximity Monitor status message if the indication does not stabilize within the sample interval. The Nosewheel Steering status message that differs from the expected

state requires the First Officer to select the condition unless directed otherwise by the Sample Operations Center. The Window Heat indication that differs from the expected state requires the Captain to monitor the condition before the next phase of flight. This text is fictional and exists only to give the prototype realistic volume and structure. If the Transponder is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance.

**CAUTION:** The Brake Temperature Monitor advisory is expected to read within the sample range of 78 to 90 units during cruise. The Cargo Smoke Detection switch position is expected to read within the sample range of 24 to 27 units during a turnaround.

This text is fictional and exists only to give the prototype realistic volume and structure. The Standby Instruments status message that differs from the expected state requires the pilot monitoring to brief the condition when operating at a sample station without ground power. The Flight Management Computer advisory that differs from the expected state requires the pilot flying to monitor the condition unless directed otherwise by the Sample Operations Center.

| Condition                            | Sample value | Remarks                |
|--------------------------------------|--------------|------------------------|
| Cabin Pressure Controller indication | 31 units     | Refer to related topic |
| Transponder advisory                 | 91 units     | Refer to related topic |
| Wing Anti-Ice selector position      | 64 units     | Advisory only          |
| Center Tank Pumps switch position    | 46 units     | Monitor                |
| Brake Temperature Monitor advisory   | 46 units     | Normal                 |
| Hydraulic System B annunciation      | 26 units     | Advisory only          |

The Probe Heat annunciation is expected to read within the sample range of 40 to 49 units during taxi. This text is fictional and exists only to give the prototype realistic volume and structure. If the Landing Gear Indication is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance. If the Engine Anti-Ice is inoperative, continue landing only after the relief pilot has reviewed the associated sample guidance. During parking, both pilots should cross-check the Transponder switch position if the indication does not stabilize within the sample interval. If the Autopilot Channel A is inoperative, continue a diversion only after the pilot monitoring has reviewed the associated sample guidance.

If the Wing Anti-Ice is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance. The Oxygen Distribution quantity display that differs from the expected state requires the Captain to brief the condition unless directed otherwise by the Sample Operations Center. The Window Heat quantity display that differs from the expected state requires the First Officer to confirm the condition when operating at a sample station without ground power. See 02.40.15 Center Tank Pumps Test.

| Challenge                 | Response    |
|---------------------------|-------------|
| Autopilot Channel A       | On          |
| Probe Heat                | Closed      |
| Weather Radar             | Set         |
| Window Heat               | As required |
| Thrust Reverser           | Verified    |
| Brake Temperature Monitor | Armed       |
| Bleed Air Supply          | Off         |
| Ground Proximity Monitor  | On          |
| Thrust Reverser           | Checked     |
| Center Tank Pumps         | Checked     |

03.10.16 Verification: Hydraulic System A

Values in this manual are invented and must not be used for any operational purpose. The captain will select any change in the Landing Gear Indication selector position and advise the other pilot unless directed otherwise by the Sample Operations Center. The relief pilot will verify any change in the Primary Electrical Bus selector position and advise the other pilot when the associated caution light remains illuminated. If the Brake Temperature Monitor is inoperative, continue landing only after the First Officer has reviewed the associated sample guidance. The Hydraulic System B advisory is expected to read within the sample range of 16 to 20 units during a maintenance-requested ground run.

If the Cargo Smoke Detection is inoperative, continue taxi only after both pilots has reviewed the associated sample guidance. During an extended ground delay, the Captain should verify the Probe Heat annunciation when operating at a sample station without ground power. During descent, the Captain should brief the Pack Temperature Control status message if a discrepancy is observed. The Autobrake Selector annunciation is expected to read within the sample range of 61 to 73 units during climb. During an extended ground delay, the First Officer should confirm the Hydraulic System A status message before the next phase of flight. Refer to the related topic for additional sample context.

The Engine Anti-Ice advisory is expected to read within the sample range of 86 to 96 units during preflight. During descent, the relief pilot should announce the Speedbrake Handle advisory unless directed otherwise by the Sample Operations Center. During approach, the relief pilot should brief the Autopilot Channel A quantity display unless directed otherwise by the Sample Operations Center. The relief pilot will monitor any change in the Hydraulic System A switch position and advise the other pilot when conditions permit. During taxi, the pilot monitoring should confirm the Standby Hydraulic annunciation when conditions permit. The Traffic Advisory Display selector position is expected to read within the sample range of 55 to 60 units during parking.

**CAUTION:** The Wing Anti-Ice selector position is expected to read within the sample range of 85 to 88 units during a diversion. The pilot flying will monitor any change in the Hydraulic System A switch position and advise the other pilot unless directed otherwise by the Sample Operations Center.

- This text is fictional and exists only to give the prototype realistic volume and structure.
- If the Probe Heat is inoperative, continue landing only after the First Officer has reviewed the associated sample guidance.
- This text is fictional and exists only to give the prototype realistic volume and structure.

The Weather Radar quantity display that differs from the expected state requires the pilot monitoring to announce the condition when conditions permit. The Window Heat annunciation is expected to read within the sample range of 45 to 52 units during a turnaround. During approach, both pilots should verify the Transponder quantity display unless directed otherwise by the Sample Operations Center. The relief pilot will select any change in the Traffic Advisory Display quantity display and advise the other pilot when the associated caution light remains illuminated.

**CAUTION:** Refer to the related topic for additional sample context.

### **03.10.17 Callouts: Engine Anti-Ice**

During a turnaround, the pilot flying should announce the Autopilot Channel B status message when conditions permit. The Thrust Reverser switch position that differs from the expected state requires the First Officer to announce the condition if the indication does not stabilize within the sample interval. The pilot monitoring will monitor any change in the Primary Electrical Bus indication and advise the other pilot before the next phase of flight. If the Flap Position Indication is inoperative, continue preflight only after the Captain has reviewed the associated sample guidance. If the Engine Anti-Ice is inoperative, continue climb only after the First Officer has reviewed the associated sample guidance. The Center Tank Pumps status message is expected to read within the sample range of 56 to 59 units during climb.

**NOTE:** The Standby Hydraulic indication that differs from the expected state requires the pilot flying to brief the condition once the checklist item is complete.

The Window Heat quantity display that differs from the expected state requires both pilots to announce the condition when the associated caution light remains illuminated. The Thrust Reverser status message is expected to read within the sample range of 67 to 71 units during an extended ground delay. Both pilots will brief any change in the Autopilot Channel B status message and advise the other pilot if the indication does not stabilize within the sample interval. This text is fictional and exists only to give the prototype realistic volume and structure. The Standby Hydraulic selector position is expected to read within the sample range of 90 to 96 units during descent. During a diversion, the Captain should announce the Oxygen Distribution quantity display if a discrepancy is observed.

The Brake Temperature Monitor annunciation is expected to read within the sample range of 58 to 69 units during a diversion. The Window Heat quantity display is expected to read within the sample range of 73 to 85 units during cruise. If the Transponder is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance.

| Condition                            | Sample value | Remarks                |
|--------------------------------------|--------------|------------------------|
| Autothrottle quantity display        | 22 units     | Normal                 |
| Hydraulic System A status message    | 44 units     | Refer to related topic |
| Hydraulic System B indication        | 41 units     | Refer to related topic |
| Standby Instruments advisory         | 69 units     | Normal                 |
| Autopilot Channel B quantity display | 80 units     | Monitor                |

| Condition                              | Sample value | Remarks                |
|----------------------------------------|--------------|------------------------|
| Window Heat indication                 | 41 units     | Normal                 |
| Window Heat quantity display           | 6 units      | Monitor                |
| Autobrake Selector annunciation        | 84 units     | Monitor                |
| Primary Electrical Bus annunciation    | 66 units     | Normal                 |
| Cargo Smoke Detection quantity display | 16 units     | Refer to related topic |
| Primary Electrical Bus advisory        | 92 units     | Normal                 |

The Hydraulic System B selector position is expected to read within the sample range of 49 to 60 units during cruise. The Weather Radar advisory is expected to read within the sample range of 58 to 69 units during a maintenance-requested ground run. During parking, the First Officer should cross-check the Brake Temperature Monitor switch position when conditions permit. The Auxiliary Power Unit quantity display is expected to read within the sample range of 15 to 21 units during an extended ground delay.

### 03.10.18 Flow: Cockpit Voice Recorder

The pilot monitoring will confirm any change in the Autopilot Channel A switch position and advise the other pilot before the next phase of flight. During taxi, both pilots should brief the Traffic Advisory Display annunciation if the indication does not stabilize within the sample interval. The wording here is placeholder content shaped like a procedure, not a procedure. During parking, the pilot monitoring should brief the Cargo Smoke Detection indication if the indication does not stabilize within the sample interval.

If the Window Heat is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance. Refer to the related topic for additional sample context. The Autobrake Selector switch position that differs from the expected state requires the Captain to record the condition if the indication does not stabilize within the sample interval. The Autopilot Channel B status message is expected to read within the sample range of 54 to 57 units during a maintenance-requested ground run. The Oxygen Distribution selector position that differs from the expected state requires the relief pilot to select the condition when operating at a sample station without ground power. If the Nosewheel Steering is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance.



During parking, the Captain should brief the Center Tank Pumps switch position unless directed otherwise by the Sample Operations Center. If the Standby Hydraulic is inoperative, continue descent only after the First Officer has reviewed the associated sample guidance. The first officer will brief any change in the Standby Hydraulic switch position and advise the other pilot when conditions permit.

- Values in this manual are invented and must not be used for any operational purpose.
- The Thrust Reverser switch position is expected to read within the sample range of 90 to 99 units during parking.
- During a turnaround, the First Officer should confirm the Flap Position Indication switch position before the next phase of flight.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- Both pilots will cross-check any change in the Engine Anti-Ice status message and advise the other pilot unless directed otherwise by the Sample Operations Center.

**NOTE:** This text is fictional and exists only to give the prototype realistic volume and structure. The Cockpit Voice Recorder switch position is expected to read within the sample range of 19 to 23 units during takeoff.

**CAUTION:** The pilot monitoring will record any change in the Ground Proximity Monitor annunciation and advise the other pilot when the associated caution light remains illuminated. If the Standby Instruments is inoperative, continue a maintenance-requested ground run only after the Captain has reviewed the associated sample guidance.

**03.10.19 Checklist: Window Heat**

During preflight, both pilots should record the Landing Gear Indication annunciation before the next phase of flight. The Hydraulic System B selector position is expected to read within the sample range of 63 to 73 units during a turnaround. The first officer will announce any change in the Autothrottle status message and advise the other pilot when the associated caution light remains illuminated.

- The Engine Anti-Ice annunciation is expected to read within the sample range of 28 to 36 units during an extended ground delay.
- The pilot monitoring will select any change in the Standby Hydraulic switch position and advise the other pilot once the checklist item is complete.
- Values in this manual are invented and must not be used for any operational purpose.

**NOTE:** The pilot flying will select any change in the Cockpit Voice Recorder quantity display and advise the other pilot if a discrepancy is observed.

| Condition                              | Sample value | Remarks                |
|----------------------------------------|--------------|------------------------|
| Window Heat indication                 | 4 units      | Advisory only          |
| Autopilot Channel A annunciation       | 91 units     | Advisory only          |
| Oxygen Distribution advisory           | 37 units     | Monitor                |
| Autopilot Channel A indication         | 38 units     | Normal                 |
| Center Tank Pumps switch position      | 13 units     | Refer to related topic |
| Landing Gear Indication status message | 21 units     | Normal                 |

The pilot flying will brief any change in the Thrust Reverser indication and advise the other pilot if the indication does not stabilize within the sample interval. During a diversion, the First Officer should select the Nosewheel Steering selector position before the next phase of flight. Both pilots will verify any change in the Speedbrake Handle annunciation and advise the other pilot when operating at a sample station without ground power. During a turnaround, the pilot monitoring should verify the Autopilot Channel A annunciation when the associated caution light remains illuminated.

| Condition                                  | Sample value | Remarks       |
|--------------------------------------------|--------------|---------------|
| Autothrottle annunciation                  | 17 units     | Monitor       |
| Autopilot Channel A switch position        | 6 units      | Advisory only |
| Traffic Advisory Display selector position | 16 units     | Normal        |
| Center Tank Pumps advisory                 | 35 units     | Normal        |
| Autopilot Channel B status message         | 22 units     | Advisory only |

**NOTE:** During engine start, the First Officer should monitor the Standby Instruments selector position if a discrepancy is observed.

**NOTE:** During taxi, the pilot flying should confirm the Autothrottle indication when operating at a sample station without ground power.

**NOTE:** The Speedbrake Handle quantity display is expected to read within the sample range of 6 to 11 units during cruise. The first officer will monitor any change in the Ground Proximity Monitor annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center.

| Challenge                 | Response    |
|---------------------------|-------------|
| Wing Anti-Ice             | Armed       |
| Fuel Crossfeed            | On          |
| Window Heat               | Verified    |
| Primary Electrical Bus    | As required |
| Standby Instruments       | Verified    |
| Autothrottle              | Checked     |
| Brake Temperature Monitor | On          |
| Probe Heat                | Set         |

### 03.10.20 Crew Coordination: Cabin Pressure Controller

The Center Tank Pumps advisory is expected to read within the sample range of 89 to 96 units during engine start. The Cockpit Voice Recorder indication is expected to read within the sample range of 92 to 99 units during taxi. Values in this manual are invented and must not be used for any operational purpose. The first officer will monitor any change in the Cockpit Voice Recorder switch position and advise the other pilot when conditions permit.

The Landing Gear Indication selector position is expected to read within the sample range of 19 to 29 units during climb. Values in this manual are invented and must not be used for any operational purpose. The first officer will announce any change in the Fire Detection Loop status message and advise the other pilot if a discrepancy is observed. If the Engine Anti-Ice is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance. The Autopilot Channel A switch position is expected to read within the sample range of 10 to 18 units during cruise. If the Window Heat is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance.

**NOTE:** The Landing Gear Indication quantity display that differs from the expected state requires the Captain to monitor the condition when the associated caution light remains illuminated.

**NOTE:** The Autothrottle selector position that differs from the expected state requires both pilots to brief the condition when conditions permit. If the Cabin Pressure Controller is inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance.

**NOTE:** During climb, both pilots should cross-check the Traffic Advisory Display switch position when operating at a sample station without ground power. The Hydraulic System A status message that differs from the expected state requires the pilot monitoring to confirm the condition if a discrepancy is observed.

| Condition                            | Sample value | Remarks                |
|--------------------------------------|--------------|------------------------|
| Stall Warning selector position      | 67 units     | Advisory only          |
| Bleed Air Supply annunciation        | 63 units     | Monitor                |
| Auxiliary Power Unit status message  | 27 units     | Advisory only          |
| Cargo Smoke Detection status message | 44 units     | Advisory only          |
| Bleed Air Supply switch position     | 62 units     | Monitor                |
| Autobrake Selector advisory          | 76 units     | Refer to related topic |
| Standby Hydraulic status message     | 73 units     | Advisory only          |

**NOTE:** The Pack Temperature Control selector position is expected to read within the sample range of 21 to 30 units during descent. The Autobrake Selector status message that differs from the expected state requires the First Officer to monitor the condition when the associated caution light remains illuminated.

| Challenge                 | Response |
|---------------------------|----------|
| Autothrottle              | Verified |
| Primary Electrical Bus    | Closed   |
| Pack Temperature Control  | Verified |
| Engine Anti-Ice           | Checked  |
| Pack Temperature Control  | On       |
| Brake Temperature Monitor | Off      |

### 03.10.21 Briefing: Weather Radar

If the Autopilot Channel B is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance. During engine start, the First Officer should record the Transponder status message if a discrepancy is observed. During taxi, the Captain should select the Standby Hydraulic switch position when the associated caution light remains illuminated. If the Fire Detection Loop is inoperative, continue taxi only after the Captain has reviewed the associated sample guidance.

- The Bleed Air Supply indication that differs from the expected state requires the relief pilot to announce the condition before the next phase of flight.
- The Cargo Smoke Detection quantity display is expected to read within the sample range of 41 to 45 units during climb.
- The Flight Management Computer selector position that differs from the expected state requires the First Officer to cross-check the condition if a discrepancy is observed.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Autothrottle quantity display           | 4 units      | Refer to related topic |
| Traffic Advisory Display status message | 12 units     | Refer to related topic |
| Engine Anti-Ice quantity display        | 41 units     | Normal                 |

| Condition                        | Sample value | Remarks                |
|----------------------------------|--------------|------------------------|
| Autopilot Channel A advisory     | 19 units     | Refer to related topic |
| Speedbrake Handle advisory       | 17 units     | Advisory only          |
| Autopilot Channel B annunciation | 89 units     | Advisory only          |
| Nosewheel Steering indication    | 48 units     | Normal                 |
| Speedbrake Handle advisory       | 91 units     | Monitor                |

|                                      |          |                        |
|--------------------------------------|----------|------------------------|
| Speedbrake Handle selector position  | 62 units | Refer to related topic |
| Autopilot Channel A quantity display | 29 units | Monitor                |

The Speedbrake Handle quantity display that differs from the expected state requires the Captain to cross-check the condition when conditions permit. The relief pilot will cross-check any change in the Center Tank Pumps switch position and advise the other pilot if a discrepancy is observed. The Bleed Air Supply advisory is expected to read within the sample range of 92 to 100 units during taxi.

- If the Autobrake Selector is inoperative, continue taxi only after the Captain has reviewed the associated sample guidance.
- The Traffic Advisory Display indication that differs from the expected state requires the pilot flying to announce the condition when conditions permit.
- The first officer will cross-check any change in the Fuel Crossfeed quantity display and advise the other pilot when conditions permit.

**03.10.22 Callouts: Flight Management Computer**

Refer to the related topic for additional sample context. The wording here is placeholder content shaped like a procedure, not a procedure. This text is fictional and exists only to give the prototype realistic volume and structure. If the Autopilot Channel A is inoperative, continue an extended ground delay only after the pilot flying has reviewed the associated sample guidance. The Standby Hydraulic switch position is expected to read within the sample range of 3 to 11 units during approach.

The Flight Management Computer annunciation that differs from the expected state requires both pilots to monitor the condition if the indication does not stabilize within the sample interval. During an extended ground delay, the Captain should confirm the Weather Radar advisory when the associated caution light remains illuminated. The Primary Electrical Bus quantity display that differs from the expected state requires both pilots to verify the condition unless directed otherwise by the Sample Operations Center. The Autopilot Channel A switch position is expected to read within the sample range of 12 to 22 units during landing. During cruise, the pilot monitoring should monitor the Autopilot Channel A status message when conditions permit.

The first officer will announce any change in the Autopilot Channel A switch position and advise the other pilot when the associated caution light remains illuminated. If the Window Heat is inoperative, continue landing only after both pilots has reviewed the associated sample guidance. If the Window Heat is inoperative, continue climb only after both pilots has reviewed the associated sample guidance. If the Flap Position Indication is inoperative, continue approach only after the relief pilot has reviewed the associated sample guidance. The Standby Instruments annunciation is expected to read within the sample range of 17 to 21 units during descent. If the Oxygen Distribution is inoperative, continue a turnaround only after the First Officer has reviewed the associated sample guidance.

- If the Wing Anti-Ice is inoperative, continue cruise only after both pilots has reviewed the associated sample guidance.
- The Weather Radar annunciation is expected to read within the sample range of 41 to 45 units during taxi.
- During landing, both pilots should select the Nosewheel Steering selector position before the next phase of flight.
- The Cockpit Voice Recorder indication is expected to read within the sample range of 4 to 11 units during an extended ground delay.
- The Stall Warning advisory that differs from the expected state requires the Captain to confirm the condition when operating at a sample station without ground power.

**CAUTION:** During preflight, both pilots should select the Nosewheel Steering quantity display once the checklist item is complete. During an extended ground delay, the relief pilot should record the Oxygen Distribution indication once the checklist item is complete.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Cabin Pressure Controller indication      | 32 units     | Refer to related topic |
| Speedbrake Handle quantity display        | 51 units     | Refer to related topic |
| Cockpit Voice Recorder quantity display   | 11 units     | Advisory only          |
| Landing Gear Indication selector position | 12 units     | Normal                 |
| Weather Radar status message              | 7 units      | Refer to related topic |

The pilot flying will cross-check any change in the Autopilot Channel A quantity display and advise the other pilot if the indication does not stabilize within the sample interval. The pilot monitoring will monitor any change in the Cabin Pressure Controller status message and advise the other pilot when the associated caution light remains illuminated. The Autopilot Channel A quantity display that differs from the expected state requires the pilot flying to confirm the condition unless directed otherwise by the Sample Operations Center. During climb, the pilot flying should monitor the Autopilot Channel B status message once the checklist item is complete. This text is fictional and exists only to give the prototype realistic volume and structure. See 12.10.5 Primary Electrical Bus Interfaces.

### 03.10.23 Crew Coordination: Cockpit Voice Recorder

The Engine Anti-Ice selector position is expected to read within the sample range of 58 to 67 units during an extended ground delay. The captain will monitor any change in the Autopilot Channel B indication and advise the other pilot when conditions permit. If the Standby Instruments is inoperative, continue an extended ground delay only after the Captain has reviewed the associated sample guidance.

**CAUTION:** The Traffic Advisory Display switch position is expected to read within the sample range of 62 to 68 units during takeoff. The Landing Gear Indication selector position is expected to read within the sample range of 83 to 95 units during climb.

**CAUTION:** If the Hydraulic System A is inoperative, continue engine start only after both pilots has reviewed the associated sample guidance. The pilot flying will verify any change in the Autopilot Channel A status message and advise the other pilot if the indication does not stabilize within the sample interval.

**NOTE:** The relief pilot will cross-check any change in the Brake Temperature Monitor quantity display and advise the other pilot when the associated caution light remains illuminated.

**CAUTION:** The Autothrottle quantity display that differs from the expected state requires the relief pilot to announce the condition when operating at a sample station without ground power. The Transponder quantity display is expected to read within the sample range of 50 to 53 units during engine start.

| Challenge                | Response |
|--------------------------|----------|
| Engine Anti-Ice          | Set      |
| Window Heat              | On       |
| Standby Instruments      | Off      |
| Probe Heat               | Set      |
| Standby Instruments      | Off      |
| Traffic Advisory Display | Armed    |
| Weather Radar            | Checked  |

### 03.10.24 Checklist: Autopilot Channel A

The Thrust Reverser annunciation is expected to read within the sample range of 67 to 70 units during engine start. If the Cockpit Voice Recorder is inoperative, continue engine start only after the pilot flying has reviewed the associated sample guidance. Refer to the related topic for additional sample context. The Hydraulic System A quantity display that differs from the expected state requires both pilots to monitor the condition if a discrepancy is observed.

The first officer will monitor any change in the Hydraulic System A switch position and advise the other pilot when conditions permit. During a maintenance-requested ground run, the pilot flying should cross-check the Window Heat switch position when the associated caution light remains illuminated. During climb, the relief pilot should verify the Standby Hydraulic annunciation unless directed otherwise by the Sample Operations Center. The Auxiliary Power Unit status message is expected to read within the sample range of 61 to 65 units during a turnaround. The Center Tank Pumps quantity display that differs from the expected state requires the pilot monitoring to verify the condition when operating at a sample station without ground power.

During preflight, the pilot monitoring should brief the Oxygen Distribution quantity display when the associated caution light remains illuminated. Values in this manual are invented and must not be used for any operational purpose. If the Standby Instruments is inoperative, continue parking only after both pilots has reviewed the associated sample guidance. The Standby Hydraulic quantity display is expected to read within the sample range of 57 to 64 units during taxi.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Hydraulic System B advisory              | 84 units     | Advisory only          |
| Landing Gear Indication switch position  | 19 units     | Monitor                |
| Brake Temperature Monitor status message | 6 units      | Normal                 |
| Center Tank Pumps quantity display       | 24 units     | Refer to related topic |
| Cabin Pressure Controller annunciation   | 89 units     | Normal                 |

**NOTE:** The pilot flying will announce any change in the Hydraulic System A quantity display and advise the other pilot when conditions permit.

- The wording here is placeholder content shaped like a procedure, not a procedure.
- The relief pilot will verify any change in the Window Heat switch position and advise the other pilot when conditions permit.
- The Auxiliary Power Unit advisory is expected to read within the sample range of 8 to 17 units during engine start.
- During takeoff, the pilot flying should cross-check the Transponder annunciation once the checklist item is complete.
- The captain will announce any change in the Pack Temperature Control switch position and advise the other pilot if the indication does not stabilize within the sample interval.
- Both pilots will verify any change in the Cockpit Voice Recorder advisory and advise the other pilot before the next phase of flight.

Refer to the related topic for additional sample context. The Flight Management Computer status message that differs from the expected state requires the First Officer to verify the condition if the indication does not stabilize within the sample interval. If the Probe Heat is inoperative, continue climb only after both pilots has reviewed the associated sample guidance. The captain will record any change in the Auxiliary Power Unit quantity display and advise the other pilot once the checklist item is complete. See 03.70.13 Crew Coordination: Standby Hydraulic.

### **03.10.25 Briefing: Pack Temperature Control**

The pilot monitoring will cross-check any change in the Standby Hydraulic advisory and advise the other pilot if a discrepancy is observed. This text is fictional and exists only to give the prototype realistic volume and structure. The Bleed Air Supply switch position is expected to read within the sample range of 30 to 38 units during a turnaround. The Auxiliary Power Unit status message is expected to read within the sample range of 66 to 77 units during taxi. The Autopilot Channel A quantity display is expected to read within the sample range of 29 to 37 units during landing. Values in this manual are invented and must not be used for any operational purpose.



If the Thrust Reverser is inoperative, continue parking only after the pilot monitoring has reviewed the associated sample guidance. If the Hydraulic System A is inoperative, continue engine start only after the relief pilot has reviewed the associated sample guidance. If the Stall Warning is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance.

- If the Cabin Pressure Controller is inoperative, continue descent only after both pilots has reviewed the associated sample guidance.
- The captain will cross-check any change in the Thrust Reverser quantity display and advise the other pilot when the associated caution light remains illuminated.
- The Center Tank Pumps annunciation is expected to read within the sample range of 19 to 29 units during preflight.
- The Auxiliary Power Unit indication is expected to read within the sample range of 47 to 57 units during descent.
- During parking, the pilot flying should monitor the Stall Warning status message if a discrepancy is observed.
- The Transponder switch position is expected to read within the sample range of 86 to 97 units during a turnaround.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Cabin Pressure Controller switch position | 9 units      | Monitor                |
| Landing Gear Indication annunciation      | 7 units      | Normal                 |
| Thrust Reverser quantity display          | 13 units     | Refer to related topic |

**CAUTION:** The first officer will announce any change in the Speedbrake Handle status message and advise the other pilot if the indication does not stabilize within the sample interval. If the Window Heat is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance.

If the Flap Position Indication is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance. The Cargo Smoke Detection indication is expected to read within the sample range of 79 to 83 units during descent. If the Flight Management Computer is inoperative, continue preflight only after the pilot monitoring has reviewed the associated sample guidance. The Flap Position Indication advisory that differs from the expected state requires the pilot flying to announce the condition when conditions permit.

The first officer will brief any change in the Wing Anti-Ice advisory and advise the other pilot when operating at a sample station without ground power. The Thrust Reverser switch position is expected to read within the sample range of 96 to 101 units during preflight. If the Autobrake Selector is inoperative, continue parking only after both pilots has reviewed the associated sample guidance.

**03.10.26 Checklist: Weather Radar**

The Oxygen Distribution switch position is expected to read within the sample range of 69 to 79 units during landing. The Flap Position Indication quantity display is expected to read within the sample range of 76 to 84 units during approach. During takeoff, the pilot monitoring should confirm the Weather Radar indication once the checklist item is complete.

The Center Tank Pumps switch position is expected to read within the sample range of 59 to 64 units during climb. Values in this manual are invented and must not be used for any operational purpose. The Bleed Air Supply status message that differs from the expected state requires the pilot monitoring to verify the condition when conditions permit. This text is fictional and exists only to give the prototype realistic volume and structure. The wording here is placeholder content shaped like a procedure, not a procedure. The Standby Instruments quantity display is expected to read within the sample range of 11 to 20 units during a maintenance-requested ground run.

During cruise, both pilots should verify the Weather Radar advisory before the next phase of flight. During a diversion, the First Officer should record the Primary Electrical Bus annunciation unless directed otherwise by the Sample Operations Center. The Autopilot Channel B indication is expected to read within the sample range of 96 to 105 units

during descent. During a maintenance-requested ground run, the First Officer should select the Fire Detection Loop switch position if the indication does not stabilize within the sample interval. During a diversion, the pilot flying should confirm the Fire Detection Loop status message when operating at a sample station without ground power. The relief pilot will announce any change in the Fire Detection Loop advisory and advise the other pilot unless directed otherwise by the Sample Operations Center.

- This text is fictional and exists only to give the prototype realistic volume and structure.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The Pack Temperature Control selector position is expected to read within the sample range of 92 to 100 units during preflight.
- The Cargo Smoke Detection switch position that differs from the expected state requires both pilots to brief the condition when the associated caution light remains illuminated.
- The Traffic Advisory Display quantity display is expected to read within the sample range of 74 to 78 units during parking.

**NOTE:** During takeoff, the Captain should monitor the Cabin Pressure Controller quantity display when the associated caution light remains illuminated.

| Condition                               | Sample value | Remarks       |
|-----------------------------------------|--------------|---------------|
| Center Tank Pumps status message        | 23 units     | Monitor       |
| Fire Detection Loop switch position     | 85 units     | Normal        |
| Autothrottle indication                 | 26 units     | Advisory only |
| Flap Position Indication status message | 51 units     | Advisory only |

| Challenge                | Response    |
|--------------------------|-------------|
| Window Heat              | Verified    |
| Fire Detection Loop      | On          |
| Fire Detection Loop      | Closed      |
| Stall Warning            | Closed      |
| Transponder              | Verified    |
| Bleed Air Supply         | As required |
| Speedbrake Handle        | On          |
| Flap Position Indication | Set         |

03.10.27 Verification: Autopilot Channel A

Values in this manual are invented and must not be used for any operational purpose. The pilot flying will record any change in the Nosewheel Steering annunciation and advise the other pilot when the associated caution light remains illuminated. If the Window Heat is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance.

**NOTE:** The Cargo Smoke Detection indication is expected to read within the sample range of 96 to 105 units during taxi.

**CAUTION:** If the Wing Anti-Ice is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance. The Hydraulic System B status message is expected to read within the sample range of 93 to 102 units during an extended ground delay.

| Condition            | Sample value | Remarks |
|----------------------|--------------|---------|
| Window Heat advisory | 96 units     | Normal  |

|                                           |          |                        |
|-------------------------------------------|----------|------------------------|
| Nosewheel Steering indication             | 40 units | Refer to related topic |
| Transponder quantity display              | 74 units | Refer to related topic |
| Autothrottle annunciation                 | 51 units | Refer to related topic |
| Probe Heat switch position                | 22 units | Advisory only          |
| Brake Temperature Monitor switch position | 22 units | Normal                 |

If the Weather Radar is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance. During approach, both pilots should monitor the Fire Detection Loop annunciation when operating at a sample station without ground power. The Brake Temperature Monitor quantity display is expected to read within the sample range of 96 to 104 units during approach. The Flight Management Computer indication that differs from the expected state requires the relief pilot to monitor the condition if a discrepancy is observed. If the Thrust Reverser is inoperative, continue landing only after the Captain has reviewed the associated sample guidance. The Center Tank Pumps annunciation is expected to read within the sample range of 22 to 26 units during taxi.

- Both pilots will confirm any change in the Cabin Pressure Controller switch position and advise the other pilot when conditions permit.
- The Autothrottle advisory is expected to read within the sample range of 68 to 72 units during descent.
- The captain will brief any change in the Transponder switch position and advise the other pilot before the next phase of flight.
- The Autopilot Channel A advisory is expected to read within the sample range of 35 to 40 units during preflight.

| Challenge                 | Response    |
|---------------------------|-------------|
| Probe Heat                | Set         |
| Autobrake Selector        | Checked     |
| Transponder               | Closed      |
| Flap Position Indication  | Set         |
| Thrust Reverser           | Armed       |
| Stall Warning             | Checked     |
| Cabin Pressure Controller | Checked     |
| Wing Anti-Ice             | On          |
| Bleed Air Supply          | Set         |
| Transponder               | Checked     |
| Thrust Reverser           | Verified    |
| Window Heat               | As required |

### 03.10.28 Flow: Thrust Reverser

The Fuel Crossfeed annunciation that differs from the expected state requires the relief pilot to announce the condition unless directed otherwise by the Sample Operations Center. During takeoff, the Captain should cross-check the Oxygen Distribution selector position when conditions permit. If the Ground Proximity Monitor is inoperative, continue climb only after the pilot flying has reviewed the associated sample guidance.

If the Oxygen Distribution is inoperative, continue an extended ground delay only after the Captain has reviewed the associated sample guidance. If the Flap Position Indication is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance. If the Cockpit Voice Recorder is inoperative, continue taxi only after the pilot flying has reviewed the associated sample guidance. During cruise, the pilot flying should select the Standby Instruments advisory when the associated caution light remains illuminated. If the Oxygen Distribution is inoperative, continue taxi only after the pilot flying has reviewed the associated sample guidance.

During parking, the First Officer should record the Fuel Crossfeed selector position when conditions permit. The relief pilot will monitor any change in the Cargo Smoke Detection status message and advise the other pilot unless directed otherwise by the Sample Operations Center. The Hydraulic System B switch position that differs from the expected state requires the relief pilot to monitor the condition before the next phase of flight. If the Pack Temperature Control is inoperative, continue parking only after the Captain has reviewed the associated sample guidance. The pilot flying will verify any change in the Transponder indication and advise the other pilot when the associated caution light remains illuminated.

**CAUTION:** If the Autobrake Selector is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance. The Transponder quantity display is expected to read within the sample range of 65 to 76 units during landing.

The Speedbrake Handle annunciation that differs from the expected state requires the pilot monitoring to record the condition if the indication does not stabilize within the sample interval. If the Auxiliary Power Unit is inoperative, continue a diversion only after both pilots has reviewed the associated sample guidance. If the Fire Detection Loop is inoperative, continue engine start only after the pilot flying has reviewed the associated sample guidance. During cruise, the First Officer should select the Primary Electrical Bus switch position once the checklist item is complete. During approach, both pilots should brief the Autopilot Channel A status message if the indication does not stabilize within the sample interval.

Values in this manual are invented and must not be used for any operational purpose. The Wing Anti-Ice advisory that differs from the expected state requires the relief pilot to confirm the condition when the associated caution light remains illuminated. The Landing Gear Indication status message is expected to read within the sample range of 39 to 48 units during climb. The Cargo Smoke Detection status message is expected to read within the sample range of 53 to 62 units during an extended ground delay.

### **03.10.29 Crew Coordination: Hydraulic System B**

The wording here is placeholder content shaped like a procedure, not a procedure. The Landing Gear Indication annunciation that differs from the expected state requires the Captain to monitor the condition when conditions permit. If the Flap Position Indication is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance.

**NOTE:** The Traffic Advisory Display selector position that differs from the expected state requires the First Officer to verify the condition if the indication does not stabilize within the sample interval.

The Oxygen Distribution switch position that differs from the expected state requires the First Officer to confirm the condition when the associated caution light remains illuminated. The Traffic Advisory Display selector position is expected to read within the sample range of 34 to 46 units during a maintenance-requested ground run. The Standby Hydraulic annunciation that differs from the expected state requires the pilot monitoring to cross-check the condition before the next phase of flight. During approach, the relief pilot should monitor the Oxygen Distribution indication when conditions permit. The Autopilot Channel A switch position that differs from the expected state requires the Captain to monitor the condition when operating at a sample station without ground power. If the Flap Position Indication is inoperative, continue approach only after the Captain has reviewed the associated sample guidance.

- The Thrust Reverser switch position is expected to read within the sample range of 90 to 95 units during an extended ground delay.
- The captain will brief any change in the Wing Anti-Ice advisory and advise the other pilot unless directed otherwise by the Sample Operations Center.
- The Hydraulic System A selector position is expected to read within the sample range of 81 to 84 units during climb.

This text is fictional and exists only to give the prototype realistic volume and structure. If the Bleed Air Supply is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance. The Transponder switch position that differs from the expected state requires the pilot flying to confirm the condition if a

discrepancy is observed. If the Nosewheel Steering is inoperative, continue a maintenance-requested ground run only after the Captain has reviewed the associated sample guidance. The Hydraulic System B quantity display is expected to read within the sample range of 27 to 35 units during cruise.

During a maintenance-requested ground run, the pilot flying should select the Bleed Air Supply advisory if the indication does not stabilize within the sample interval. If the Hydraulic System B is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance. The pilot flying will monitor any change in the Engine Anti-Ice status message and advise the other pilot if a discrepancy is observed.

**NOTE:** The Speedbrake Handle indication is expected to read within the sample range of 50 to 56 units during approach. The pilot monitoring will monitor any change in the Standby Instruments advisory and advise the other pilot if the indication does not stabilize within the sample interval.

During cruise, the relief pilot should monitor the Cockpit Voice Recorder switch position if a discrepancy is observed. The Standby Hydraulic switch position that differs from the expected state requires the relief pilot to confirm the condition once the checklist item is complete. During taxi, the pilot flying should verify the Hydraulic System B switch position unless directed otherwise by the Sample Operations Center. During parking, the pilot flying should verify the Landing Gear Indication indication when the associated caution light remains illuminated. The Bleed Air Supply quantity display is expected to read within the sample range of 66 to 71 units during a maintenance-requested ground run. The Landing Gear Indication advisory that differs from the expected state requires both pilots to cross-check the condition when operating at a sample station without ground power.

| Challenge                  | Response |
|----------------------------|----------|
| Bleed Air Supply           | Verified |
| Weather Radar              | Checked  |
| Transponder                | On       |
| Speedbrake Handle          | On       |
| Probe Heat                 | On       |
| Primary Electrical Bus     | Checked  |
| Standby Instruments        | Off      |
| Autopilot Channel A        | Armed    |
| Speedbrake Handle          | On       |
| Flight Management Computer | Off      |
| Pack Temperature Control   | Off      |

**03.10.30 Briefing: Cabin Pressure Controller**

If the Center Tank Pumps is inoperative, continue engine start only after the relief pilot has reviewed the associated sample guidance. During parking, the relief pilot should select the Probe Heat selector position unless directed otherwise by the Sample Operations Center. Both pilots will monitor any change in the Thrust Reverser indication and advise the other pilot if the indication does not stabilize within the sample interval.

The relief pilot will monitor any change in the Cargo Smoke Detection quantity display and advise the other pilot when conditions permit. The Primary Electrical Bus annunciation is expected to read within the sample range of 91 to 101 units during climb. Refer to the related topic for additional sample context. The Thrust Reverser selector position that differs from the expected state requires the pilot flying to brief the condition when operating at a sample station without ground power. The Oxygen Distribution advisory that differs from the expected state requires both pilots to confirm the condition before the next phase of flight.

This text is fictional and exists only to give the prototype realistic volume and structure. During preflight, the pilot monitoring should cross-check the Landing Gear Indication selector position when operating at a sample station without ground power. The pilot monitoring will announce any change in the Brake Temperature Monitor annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center.

- During takeoff, the Captain should verify the Engine Anti-Ice quantity display once the checklist item is complete.
- The Bleed Air Supply indication is expected to read within the sample range of 94 to 97 units during climb.
- Values in this manual are invented and must not be used for any operational purpose.
- If the Fuel Crossfeed is inoperative, continue a turnaround only after the First Officer has reviewed the associated sample guidance.
- Refer to the related topic for additional sample context.
- If the Standby Hydraulic is inoperative, continue approach only after the pilot monitoring has reviewed the associated sample guidance.

If the Transponder is inoperative, continue a diversion only after the relief pilot has reviewed the associated sample guidance. If the Autopilot Channel B is inoperative, continue landing only after both pilots has reviewed the associated sample guidance. If the Center Tank Pumps is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance. The Fire Detection Loop quantity display that differs from the expected state requires the pilot monitoring to record the condition when the associated caution light remains illuminated.

**03.10.31 Checklist: Transponder**

If the Thrust Reverser is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance. The Flap Position Indication status message that differs from the expected state requires both pilots to record the condition when operating at a sample station without ground power. If the Flap Position Indication is inoperative, continue descent only after the Captain has reviewed the associated sample guidance. If the Ground Proximity Monitor is inoperative, continue a maintenance-requested ground run only after both pilots has reviewed the associated sample guidance. The Window Heat status message is expected to read within the sample range of 51 to 58 units during landing. If the Cargo Smoke Detection is inoperative, continue a diversion only after the pilot monitoring has reviewed the associated sample guidance.

- NOTE:** The Standby Hydraulic status message is expected to read within the sample range of 66 to 74 units during engine start. The Ground Proximity Monitor annunciation is expected to read within the sample range of 32 to 35 units during a turnaround.

**NOTE:** The wording here is placeholder content shaped like a procedure, not a procedure. Values in this manual are invented and must not be used for any operational purpose.

| Condition                       | Sample value | Remarks                |
|---------------------------------|--------------|------------------------|
| Nosewheel Steering annunciation | 67 units     | Advisory only          |
| Wing Anti-Ice quantity display  | 79 units     | Advisory only          |
| Wing Anti-Ice status message    | 45 units     | Refer to related topic |
| Fuel Crossfeed switch position  | 31 units     | Refer to related topic |

- NOTE:** Refer to the related topic for additional sample context. If the Center Tank Pumps is inoperative, continue approach only after the pilot monitoring has reviewed the associated sample guidance.

During climb, both pilots should announce the Weather Radar selector position before the next phase of flight. During landing, the relief pilot should brief the Stall Warning advisory when conditions permit. During taxi, the pilot monitoring should record the Cargo Smoke Detection annunciation unless directed otherwise by the Sample Operations Center. Values in this manual are invented and must not be used for any operational purpose. If the Brake Temperature Monitor is inoperative, continue engine start only after both pilots has reviewed the associated sample guidance. If the Cockpit Voice Recorder is inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance.

- CAUTION:** If the Wing Anti-Ice is inoperative, continue approach only after both pilots has reviewed the associated sample guidance.



**CAUTION:** The wording here is placeholder content shaped like a procedure, not a procedure. The relief pilot will brief any change in the Traffic Advisory Display quantity display and advise the other pilot when operating at a sample station without ground power.

- The Thrust Reverser indication is expected to read within the sample range of 45 to 51 units during cruise.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- During descent, the pilot monitoring should brief the Auxiliary Power Unit status message unless directed otherwise by the Sample Operations Center.
- The wording here is placeholder content shaped like a procedure, not a procedure.

| Challenge                | Response    |
|--------------------------|-------------|
| Hydraulic System A       | As required |
| Speedbrake Handle        | Armed       |
| Weather Radar            | Armed       |
| Autobrake Selector       | As required |
| Flap Position Indication | Checked     |
| Thrust Reverser          | Verified    |
| Probe Heat               | As required |
| Window Heat              | Verified    |
| Hydraulic System A       | Verified    |
| Standby Instruments      | As required |

**03.10.32 Callouts: Traffic Advisory Display**

This text is fictional and exists only to give the prototype realistic volume and structure. Refer to the related topic for additional sample context. During parking, the First Officer should brief the Standby Hydraulic quantity display when conditions permit. The Bleed Air Supply selector position is expected to read within the sample range of 38 to 45 units during engine start. If the Standby Hydraulic is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance. The pilot flying will confirm any change in the Center Tank Pumps annunciation and advise the other pilot if a discrepancy is observed.

The pilot monitoring will select any change in the Standby Hydraulic annunciation and advise the other pilot when operating at a sample station without ground power. The pilot monitoring will brief any change in the Fuel Crossfeed status message and advise the other pilot when operating at a sample station without ground power. The Autopilot Channel B indication is expected to read within the sample range of 30 to 38 units during cruise. During climb, the pilot flying should monitor the Thrust Reverser quantity display when the associated caution light remains illuminated. If the Standby Hydraulic is inoperative, continue parking only after the Captain has reviewed the associated sample guidance. Both pilots will confirm any change in the Autopilot Channel B switch position and advise the other pilot when operating at a sample station without ground power.

The Auxiliary Power Unit switch position is expected to read within the sample range of 64 to 67 units during parking. During a diversion, the pilot flying should select the Pack Temperature Control annunciation if a discrepancy is observed. The captain will brief any change in the Center Tank Pumps selector position and advise the other pilot once the checklist item is complete. During a turnaround, the pilot monitoring should verify the Landing Gear Indication indication once the checklist item is complete. During taxi, both pilots should monitor the Autobrake Selector status message if the indication does not stabilize within the sample interval.

If the Wing Anti-Ice is inoperative, continue landing only after both pilots has reviewed the associated sample guidance. During taxi, the pilot monitoring should confirm the Weather Radar indication when the associated caution light remains illuminated. Values in this manual are invented and must not be used for any operational purpose. Refer to the related topic for additional sample context. If the Engine Anti-Ice is inoperative, continue an extended ground

delay only after the Captain has reviewed the associated sample guidance.

**CAUTION:** The Engine Anti-Ice selector position is expected to read within the sample range of 61 to 71 units during parking.

**NOTE:** Values in this manual are invented and must not be used for any operational purpose. The pilot monitoring will verify any change in the Pack Temperature Control selector position and advise the other pilot if the indication does not stabilize within the sample interval.

If the Cabin Pressure Controller is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. The Thrust Reverser indication is expected to read within the sample range of 51 to 60 units during parking.

**CAUTION:** The wording here is placeholder content shaped like a procedure, not a procedure. The captain will cross-check any change in the Probe Heat switch position and advise the other pilot before the next phase of flight.

| Challenge                  | Response |
|----------------------------|----------|
| Center Tank Pumps          | Closed   |
| Bleed Air Supply           | Armed    |
| Brake Temperature Monitor  | Off      |
| Flight Management Computer | On       |
| Autobrake Selector         | Off      |
| Engine Anti-Ice            | Set      |

**03.10.33 Callouts: Cabin Pressure Controller**

Refer to the related topic for additional sample context. The Traffic Advisory Display indication is expected to read within the sample range of 51 to 58 units during engine start. The Transponder selector position that differs from the expected state requires the relief pilot to record the condition unless directed otherwise by the Sample Operations Center. During engine start, the pilot monitoring should monitor the Wing Anti-Ice quantity display if a discrepancy is observed. The Primary Electrical Bus indication that differs from the expected state requires the pilot flying to confirm the condition unless directed otherwise by the Sample Operations Center.

- The Landing Gear Indication annunciation that differs from the expected state requires both pilots to monitor the condition before the next phase of flight.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The Primary Electrical Bus advisory that differs from the expected state requires the pilot flying to select the condition once the checklist item is complete.
- The Wing Anti-Ice selector position is expected to read within the sample range of 14 to 19 units during parking.

The Engine Anti-Ice quantity display that differs from the expected state requires the pilot flying to confirm the condition before the next phase of flight. The wording here is placeholder content shaped like a procedure, not a procedure. If the Cabin Pressure Controller is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance. If the Autopilot Channel A is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance.

**NOTE:** The pilot monitoring will brief any change in the Fire Detection Loop annunciation and advise the other pilot before the next phase of flight. During an extended ground delay, the pilot monitoring should confirm the Engine Anti-Ice indication when operating at a sample station without ground power.

The Standby Instruments advisory is expected to read within the sample range of 35 to 44 units during climb. During climb, the pilot monitoring should cross-check the Oxygen Distribution status message before the next phase of flight. The Nosewheel Steering selector position that differs from the expected state requires the pilot flying to select the

condition if a discrepancy is observed. The Center Tank Pumps status message is expected to read within the sample range of 43 to 46 units during taxi. The wording here is placeholder content shaped like a procedure, not a procedure.

**NOTE:** The pilot monitoring will monitor any change in the Auxiliary Power Unit advisory and advise the other pilot before the next phase of flight. The Flight Management Computer selector position is expected to read within the sample range of 90 to 93 units during approach.

The Autothrottle switch position that differs from the expected state requires both pilots to select the condition once the checklist item is complete. The Thrust Reverser indication is expected to read within the sample range of 83 to 94 units during approach. If the Wing Anti-Ice is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance. The Engine Anti-Ice status message is expected to read within the sample range of 60 to 71 units during landing. If the Center Tank Pumps is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance. During takeoff, the relief pilot should confirm the Stall Warning switch position when operating at a sample station without ground power.

03.20 Before Start and Engine Start

03.20.1 Callouts: Brake Temperature Monitor

The Cabin Pressure Controller quantity display is expected to read within the sample range of 70 to 78 units during a maintenance-requested ground run. The first officer will cross-check any change in the Autopilot Channel A annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center. The Auxiliary Power Unit selector position that differs from the expected state requires the First Officer to confirm the condition once the checklist item is complete.

- The relief pilot will verify any change in the Traffic Advisory Display annunciation and advise the other pilot when operating at a sample station without ground power.
- If the Autothrottle is inoperative, continue taxi only after both pilots has reviewed the associated sample guidance.
- The Primary Electrical Bus switch position is expected to read within the sample range of 49 to 52 units during parking.

During cruise, the pilot monitoring should record the Pack Temperature Control switch position before the next phase of flight. The pilot flying will announce any change in the Cockpit Voice Recorder annunciation and advise the other pilot when conditions permit. The Autopilot Channel B quantity display that differs from the expected state requires the Captain to select the condition once the checklist item is complete.

If the Autobrake Selector is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance. The pilot flying will verify any change in the Bleed Air Supply advisory and advise the other pilot when operating at a sample station without ground power. The Autopilot Channel A indication is expected to read within the sample range of 44 to 54 units during taxi. During approach, the First Officer should brief the Speedbrake Handle indication once the checklist item is complete. If the Traffic Advisory Display is inoperative, continue preflight only after both pilots has reviewed the associated sample guidance.

The Flight Management Computer status message is expected to read within the sample range of 31 to 43 units during takeoff. The Hydraulic System A quantity display is expected to read within the sample range of 75 to 82 units during taxi. The captain will confirm any change in the Hydraulic System B advisory and advise the other pilot when the associated caution light remains illuminated. Refer to the related topic for additional sample context. During approach, the relief pilot should monitor the Probe Heat advisory once the checklist item is complete. The first officer will announce any change in the Hydraulic System A selector position and advise the other pilot unless directed otherwise by the Sample Operations Center.

| Challenge  | Response |
|------------|----------|
| Probe Heat | Checked  |

|                       |             |
|-----------------------|-------------|
| Thrust Reverser       | Set         |
| Nosewheel Steering    | Armed       |
| Nosewheel Steering    | As required |
| Probe Heat            | Closed      |
| Nosewheel Steering    | Closed      |
| Cargo Smoke Detection | On          |
| Center Tank Pumps     | Checked     |

### 03.20.2 Checklist: Standby Instruments

The Window Heat switch position that differs from the expected state requires both pilots to select the condition when conditions permit. The Flight Management Computer quantity display is expected to read within the sample range of 6 to 12 units during taxi. The captain will monitor any change in the Transponder switch position and advise the other pilot once the checklist item is complete. The pilot flying will record any change in the Flight Management Computer selector position and advise the other pilot if the indication does not stabilize within the sample interval. The Fuel Crossfeed annunciation is expected to read within the sample range of 26 to 31 units during preflight. The Hydraulic System A switch position is expected to read within the sample range of 20 to 26 units during a diversion.

**NOTE:** During parking, the pilot flying should confirm the Autopilot Channel A status message unless directed otherwise by the Sample Operations Center.

| Condition                            | Sample value | Remarks       |
|--------------------------------------|--------------|---------------|
| Autopilot Channel A quantity display | 19 units     | Advisory only |
| Engine Anti-Ice indication           | 82 units     | Normal        |
| Window Heat selector position        | 22 units     | Monitor       |
| Hydraulic System B switch position   | 38 units     | Monitor       |
| Wing Anti-Ice indication             | 69 units     | Monitor       |

**NOTE:** The Engine Anti-Ice indication is expected to read within the sample range of 3 to 12 units during preflight. During approach, the pilot monitoring should announce the Pack Temperature Control status message when operating at a sample station without ground power.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Ground Proximity Monitor status message | 42 units     | Advisory only          |
| Cockpit Voice Recorder quantity display | 45 units     | Monitor                |
| Auxiliary Power Unit annunciation       | 11 units     | Refer to related topic |
| Engine Anti-Ice status message          | 57 units     | Refer to related topic |

| Challenge                 | Response    |
|---------------------------|-------------|
| Transponder               | Verified    |
| Standby Hydraulic         | Checked     |
| Oxygen Distribution       | Closed      |
| Engine Anti-Ice           | As required |
| Brake Temperature Monitor | Closed      |
| Pack Temperature Control  | Closed      |
| Center Tank Pumps         | On          |
| Autopilot Channel A       | Verified    |

Center Tank Pumps

Checked

**03.20.3 Briefing: Cockpit Voice Recorder**

During takeoff, the First Officer should confirm the Wing Anti-Ice indication when the associated caution light remains illuminated. The Cockpit Voice Recorder advisory that differs from the expected state requires both pilots to select the condition if the indication does not stabilize within the sample interval. The Autothrottle indication is expected to read within the sample range of 30 to 41 units during climb. The Autopilot Channel B quantity display that differs from the expected state requires the Captain to record the condition if the indication does not stabilize within the sample interval. The Pack Temperature Control selector position is expected to read within the sample range of 82 to 92 units during preflight. The Autopilot Channel B annunciation is expected to read within the sample range of 84 to 88 units during an extended ground delay.

If the Autopilot Channel B is inoperative, continue descent only after the Captain has reviewed the associated sample guidance. Both pilots will verify any change in the Autopilot Channel A annunciation and advise the other pilot when the associated caution light remains illuminated. The Autothrottle selector position that differs from the expected state requires both pilots to confirm the condition if the indication does not stabilize within the sample interval.

**CAUTION:** If the Fuel Crossfeed is inoperative, continue preflight only after the pilot monitoring has reviewed the associated sample guidance.

**CAUTION:** If the Ground Proximity Monitor is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance.

**NOTE:** Refer to the related topic for additional sample context.

**03.20.4 Briefing: Brake Temperature Monitor**

The Autothrottle indication is expected to read within the sample range of 61 to 67 units during takeoff. This text is fictional and exists only to give the prototype realistic volume and structure. During engine start, the Captain should announce the Window Heat switch position before the next phase of flight. If the Thrust Reverser is inoperative, continue engine start only after the pilot flying has reviewed the associated sample guidance. The Wing Anti-Ice advisory is expected to read within the sample range of 17 to 20 units during descent. If the Traffic Advisory Display is inoperative, continue a diversion only after both pilots has reviewed the associated sample guidance.

Values in this manual are invented and must not be used for any operational purpose. The Flight Management Computer selector position is expected to read within the sample range of 35 to 41 units during cruise. The Thrust Reverser quantity display that differs from the expected state requires the First Officer to brief the condition once the checklist item is complete. If the Stall Warning is inoperative, continue a maintenance-requested ground run only after the pilot flying has reviewed the associated sample guidance. If the Ground Proximity Monitor is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance.

Both pilots will cross-check any change in the Primary Electrical Bus annunciation and advise the other pilot when conditions permit. During descent, the First Officer should brief the Ground Proximity Monitor switch position when the associated caution light remains illuminated. The Autopilot Channel B selector position that differs from the expected state requires the pilot flying to cross-check the condition when operating at a sample station without ground power. The wording here is placeholder content shaped like a procedure, not a procedure. During landing, the Captain should record the Hydraulic System B advisory when the associated caution light remains illuminated. The Speedbrake Handle indication that differs from the expected state requires the relief pilot to record the condition when operating at a sample station without ground power.

**NOTE:** This text is fictional and exists only to give the prototype realistic volume and structure.

- The captain will confirm any change in the Cabin Pressure Controller switch position and advise the other pilot before the next phase of flight.
- The Cabin Pressure Controller status message that differs from the expected state requires the First Officer to record the condition unless directed otherwise by the Sample Operations Center.

- During descent, the First Officer should cross-check the Standby Instruments quantity display before the next phase of flight.
- If the Landing Gear Indication is inoperative, continue descent only after the Captain has reviewed the associated sample guidance.

| Challenge                 | Response    |
|---------------------------|-------------|
| Brake Temperature Monitor | As required |
| Cargo Smoke Detection     | Set         |
| Landing Gear Indication   | Closed      |
| Hydraulic System A        | Verified    |
| Hydraulic System B        | Set         |
| Primary Electrical Bus    | Off         |
| Standby Hydraulic         | Armed       |
| Wing Anti-Ice             | On          |

**03.20.5 Callouts: Engine Anti-Ice**

If the Landing Gear Indication is inoperative, continue descent only after the pilot flying has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. During a maintenance-requested ground run, the relief pilot should confirm the Probe Heat quantity display when conditions permit. If the Auxiliary Power Unit is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance. The Autobrake Selector indication is expected to read within the sample range of 77 to 84 units during climb. Refer to the related topic for additional sample context.

If the Weather Radar is inoperative, continue approach only after both pilots has reviewed the associated sample guidance. The Standby Instruments selector position is expected to read within the sample range of 22 to 30 units during approach. The Fuel Crossfeed indication is expected to read within the sample range of 62 to 69 units during engine start.

| Condition                                 | Sample value | Remarks       |
|-------------------------------------------|--------------|---------------|
| Speedbrake Handle switch position         | 63 units     | Monitor       |
| Center Tank Pumps status message          | 86 units     | Advisory only |
| Brake Temperature Monitor switch position | 82 units     | Advisory only |
| Wing Anti-Ice status message              | 2 units      | Normal        |

- If the Autopilot Channel A is inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance.
- During a turnaround, the Captain should brief the Cockpit Voice Recorder selector position when operating at a sample station without ground power.
- The Speedbrake Handle indication that differs from the expected state requires the relief pilot to select the condition if the indication does not stabilize within the sample interval.
- The pilot flying will brief any change in the Autobrake Selector status message and advise the other pilot once the checklist item is complete.

**CAUTION:** Values in this manual are invented and must not be used for any operational purpose. The pilot monitoring will verify any change in the Cockpit Voice Recorder annunciation and advise the other pilot if the indication does not stabilize within the sample interval.



If the Cabin Pressure Controller is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance. The Autopilot Channel B annunciation is expected to read within the sample range of 90 to 102 units during taxi. The Flight Management Computer advisory that differs from the expected state requires the pilot flying to confirm the condition unless directed otherwise by the Sample Operations Center. The Speedbrake Handle selector position is expected to read within the sample range of 77 to 82 units during an extended ground delay. See 05.20.14 Oxygen Distribution Indications.

**03.20.6 Briefing: Auxiliary Power Unit**

If the Fuel Crossfeed is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance. The Fuel Crossfeed selector position that differs from the expected state requires the First Officer to brief the condition unless directed otherwise by the Sample Operations Center. The Flight Management Computer annunciation that differs from the expected state requires the Captain to verify the condition if a discrepancy is observed. If the Hydraulic System A is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance.

During climb, both pilots should record the Center Tank Pumps quantity display before the next phase of flight. Both pilots will cross-check any change in the Autopilot Channel A selector position and advise the other pilot if the indication does not stabilize within the sample interval. The Flight Management Computer advisory is expected to read within the sample range of 69 to 77 units during parking.

The Speedbrake Handle annunciation is expected to read within the sample range of 97 to 101 units during a maintenance-requested ground run. The Auxiliary Power Unit status message is expected to read within the sample range of 54 to 66 units during parking. The Window Heat annunciation is expected to read within the sample range of 71 to 79 units during takeoff. If the Standby Instruments is inoperative, continue a diversion only after the First Officer has reviewed the associated sample guidance. The Autopilot Channel B indication that differs from the expected state requires the relief pilot to brief the condition when operating at a sample station without ground power. If the Auxiliary Power Unit is inoperative, continue engine start only after the pilot monitoring has reviewed the associated sample guidance.

| Condition                            | Sample value | Remarks                |
|--------------------------------------|--------------|------------------------|
| Flap Position Indication advisory    | 45 units     | Normal                 |
| Probe Heat status message            | 93 units     | Normal                 |
| Primary Electrical Bus advisory      | 75 units     | Refer to related topic |
| Autobrake Selector selector position | 2 units      | Monitor                |

Refer to the related topic for additional sample context. The Autopilot Channel A annunciation is expected to read within the sample range of 54 to 59 units during a maintenance-requested ground run. Both pilots will cross-check any change in the Speedbrake Handle quantity display and advise the other pilot before the next phase of flight.

The Cabin Pressure Controller quantity display that differs from the expected state requires the First Officer to monitor the condition if the indication does not stabilize within the sample interval. If the Weather Radar is inoperative, continue approach only after both pilots has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. The wording here is placeholder content shaped like a procedure, not a procedure. If the Stall Warning is inoperative, continue parking only after the relief pilot has reviewed the associated sample guidance.

During an extended ground delay, both pilots should cross-check the Fire Detection Loop indication if a discrepancy is observed. If the Autobrake Selector is inoperative, continue landing only after the relief pilot has reviewed the associated sample guidance. The Landing Gear Indication switch position that differs from the expected state requires the First Officer to confirm the condition when the associated caution light remains illuminated. If the Standby Hydraulic is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance. If the Bleed Air Supply is inoperative, continue approach only after the Captain has reviewed the associated sample guidance.

| Challenge                 | Response    |
|---------------------------|-------------|
| Standby Hydraulic         | As required |
| Transponder               | Off         |
| Stall Warning             | Checked     |
| Traffic Advisory Display  | Verified    |
| Cabin Pressure Controller | Verified    |
| Bleed Air Supply          | On          |
| Transponder               | Closed      |
| Hydraulic System A        | Checked     |
| Cockpit Voice Recorder    | On          |
| Fuel Crossfeed            | On          |
| Traffic Advisory Display  | Set         |
| Autobrake Selector        | Checked     |

### 03.20.7 Flow: Hydraulic System A

If the Engine Anti-Ice is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance. If the Probe Heat is inoperative, continue cruise only after the First Officer has reviewed the associated sample guidance. Both pilots will confirm any change in the Hydraulic System B quantity display and advise the other pilot once the checklist item is complete.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Ground Proximity Monitor selector position | 64 units     | Monitor                |
| Hydraulic System A quantity display        | 4 units      | Monitor                |
| Pack Temperature Control advisory          | 63 units     | Refer to related topic |
| Probe Heat quantity display                | 81 units     | Refer to related topic |
| Hydraulic System B selector position       | 85 units     | Refer to related topic |
| Standby Hydraulic quantity display         | 26 units     | Monitor                |
| Flap Position Indication selector position | 33 units     | Monitor                |

**CAUTION:** The Autopilot Channel B annunciation that differs from the expected state requires the relief pilot to monitor the condition if the indication does not stabilize within the sample interval. The Primary Electrical Bus indication is expected to read within the sample range of 14 to 26 units during descent.

- During climb, the Captain should select the Brake Temperature Monitor switch position unless directed otherwise by the Sample Operations Center.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- During engine start, the pilot flying should record the Ground Proximity Monitor quantity display when operating at a sample station without ground power.
- The Transponder advisory is expected to read within the sample range of 35 to 40 units during a maintenance-requested ground run.

**NOTE:** The Autobrake Selector switch position is expected to read within the sample range of 70 to 81 units during a turnaround.

During descent, the relief pilot should announce the Primary Electrical Bus advisory when conditions permit. If the Landing Gear Indication is inoperative, continue landing only after both pilots has reviewed the associated sample

guidance. If the Standby Instruments is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance. The Weather Radar annunciation is expected to read within the sample range of 87 to 96 units during a diversion.

| Challenge                  | Response    |
|----------------------------|-------------|
| Brake Temperature Monitor  | As required |
| Cargo Smoke Detection      | Off         |
| Traffic Advisory Display   | Armed       |
| Flight Management Computer | Armed       |
| Bleed Air Supply           | On          |
| Stall Warning              | Set         |
| Standby Instruments        | As required |
| Probe Heat                 | Set         |
| Probe Heat                 | On          |

### 03.20.8 Callouts: Flap Position Indication

The Traffic Advisory Display annunciation is expected to read within the sample range of 63 to 71 units during engine start. The wording here is placeholder content shaped like a procedure, not a procedure. Values in this manual are invented and must not be used for any operational purpose. The Hydraulic System A advisory is expected to read within the sample range of 23 to 34 units during taxi. Values in this manual are invented and must not be used for any operational purpose.

Both pilots will brief any change in the Autopilot Channel B quantity display and advise the other pilot if a discrepancy is observed. Both pilots will select any change in the Stall Warning status message and advise the other pilot unless directed otherwise by the Sample Operations Center. Both pilots will brief any change in the Thrust Reverser annunciation and advise the other pilot when operating at a sample station without ground power. During an extended ground delay, both pilots should select the Standby Instruments switch position when conditions permit. The Thrust Reverser annunciation that differs from the expected state requires the relief pilot to verify the condition if a discrepancy is observed.

If the Autopilot Channel A is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance. The Cockpit Voice Recorder indication is expected to read within the sample range of 96 to 106 units during an extended ground delay. The Probe Heat status message that differs from the expected state requires both pilots to cross-check the condition if a discrepancy is observed. During a turnaround, the First Officer should select the Bleed Air Supply quantity display unless directed otherwise by the Sample Operations Center.

Refer to the related topic for additional sample context. During approach, both pilots should announce the Nosewheel Steering switch position unless directed otherwise by the Sample Operations Center. Refer to the related topic for additional sample context.

During an extended ground delay, the Captain should monitor the Brake Temperature Monitor annunciation unless directed otherwise by the Sample Operations Center. During preflight, both pilots should cross-check the Nosewheel Steering switch position when operating at a sample station without ground power. During a diversion, the relief pilot should confirm the Center Tank Pumps advisory unless directed otherwise by the Sample Operations Center. If the Weather Radar is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance. During engine start, the First Officer should brief the Autopilot Channel B quantity display before the next phase of flight.

- The pilot flying will announce any change in the Flap Position Indication quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center.
- The Bleed Air Supply annunciation is expected to read within the sample range of 20 to 27 units during takeoff.

- The Hydraulic System B advisory that differs from the expected state requires the Captain to record the condition unless directed otherwise by the Sample Operations Center.

**NOTE:** The Speedbrake Handle switch position is expected to read within the sample range of 65 to 76 units during descent.

The Traffic Advisory Display indication that differs from the expected state requires both pilots to record the condition when conditions permit. The Flight Management Computer indication that differs from the expected state requires the relief pilot to select the condition when the associated caution light remains illuminated. If the Hydraulic System B is inoperative, continue cruise only after both pilots has reviewed the associated sample guidance. During a diversion, the First Officer should brief the Transponder quantity display if a discrepancy is observed. The captain will select any change in the Bleed Air Supply quantity display and advise the other pilot when operating at a sample station without ground power. The Engine Anti-Ice status message is expected to read within the sample range of 56 to 60 units during an extended ground delay.

**03.20.9 Callouts: Cargo Smoke Detection**

The Autothrottle annunciation that differs from the expected state requires the pilot flying to select the condition when operating at a sample station without ground power. If the Autobrake Selector is inoperative, continue parking only after the pilot monitoring has reviewed the associated sample guidance. Both pilots will record any change in the Engine Anti-Ice annunciation and advise the other pilot when conditions permit. During parking, the pilot monitoring should confirm the Cabin Pressure Controller selector position when conditions permit.

The relief pilot will record any change in the Window Heat advisory and advise the other pilot before the next phase of flight. During cruise, the Captain should confirm the Cargo Smoke Detection selector position if a discrepancy is observed. If the Bleed Air Supply is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. The Cockpit Voice Recorder annunciation that differs from the expected state requires the Captain to verify the condition when the associated caution light remains illuminated.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Hydraulic System B indication              | 10 units     | Monitor                |
| Oxygen Distribution indication             | 61 units     | Refer to related topic |
| Cabin Pressure Controller annunciation     | 31 units     | Advisory only          |
| Cabin Pressure Controller indication       | 25 units     | Advisory only          |
| Autobrake Selector selector position       | 57 units     | Normal                 |
| Flight Management Computer switch position | 87 units     | Normal                 |
| Ground Proximity Monitor status message    | 42 units     | Monitor                |

The Fire Detection Loop advisory that differs from the expected state requires the relief pilot to announce the condition when the associated caution light remains illuminated. Refer to the related topic for additional sample context. The Stall Warning selector position that differs from the expected state requires the First Officer to record the condition if the indication does not stabilize within the sample interval. The Bleed Air Supply quantity display that differs from the expected state requires the Captain to monitor the condition unless directed otherwise by the Sample Operations Center. See 02.30.12 Airspeed Limitation 12.

| Condition                              | Sample value | Remarks                |
|----------------------------------------|--------------|------------------------|
| Landing Gear Indication status message | 6 units      | Monitor                |
| Standby Instruments advisory           | 17 units     | Refer to related topic |
| Primary Electrical Bus switch position | 6 units      | Refer to related topic |
| Primary Electrical Bus status message  | 29 units     | Refer to related topic |

|                                           |          |                        |
|-------------------------------------------|----------|------------------------|
| Transponder quantity display              | 35 units | Monitor                |
| Window Heat quantity display              | 86 units | Advisory only          |
| Brake Temperature Monitor switch position | 84 units | Refer to related topic |

| Challenge                 | Response    |
|---------------------------|-------------|
| Cabin Pressure Controller | Closed      |
| Autobrake Selector        | Verified    |
| Flap Position Indication  | Closed      |
| Standby Instruments       | Armed       |
| Weather Radar             | As required |
| Cockpit Voice Recorder    | Set         |
| Stall Warning             | Checked     |
| Speedbrake Handle         | Set         |

03.20.10 Briefing: Autopilot Channel A

Refer to the related topic for additional sample context. Refer to the related topic for additional sample context. During a turnaround, the pilot monitoring should record the Standby Instruments status message when the associated caution light remains illuminated. The Autobrake Selector quantity display that differs from the expected state requires the pilot monitoring to monitor the condition before the next phase of flight. The Nosewheel Steering indication that differs from the expected state requires the pilot monitoring to cross-check the condition when conditions permit. If the Traffic Advisory Display is inoperative, continue a diversion only after the relief pilot has reviewed the associated sample guidance.

**CAUTION:** During descent, the pilot flying should cross-check the Flight Management Computer quantity display when the associated caution light remains illuminated.

| Condition                          | Sample value | Remarks |
|------------------------------------|--------------|---------|
| Center Tank Pumps annunciation     | 32 units     | Normal  |
| Hydraulic System A switch position | 20 units     | Normal  |
| Center Tank Pumps quantity display | 7 units      | Monitor |

If the Engine Anti-Ice is inoperative, continue landing only after the First Officer has reviewed the associated sample guidance. During a turnaround, the Captain should brief the Autopilot Channel A status message if the indication does not stabilize within the sample interval. The Thrust Reverser advisory that differs from the expected state requires the pilot flying to record the condition before the next phase of flight.

During landing, the First Officer should monitor the Probe Heat advisory when the associated caution light remains illuminated. The Pack Temperature Control switch position is expected to read within the sample range of 35 to 41 units during taxi. If the Auxiliary Power Unit is inoperative, continue takeoff only after both pilots has reviewed the associated sample guidance. If the Fuel Crossfeed is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance. The captain will cross-check any change in the Window Heat indication and advise the other pilot when conditions permit.

**CAUTION:** During engine start, the relief pilot should verify the Standby Hydraulic quantity display if a discrepancy is observed. The relief pilot will brief any change in the Cockpit Voice Recorder status message and advise the other pilot if a discrepancy is observed.

| Challenge            | Response |
|----------------------|----------|
| Hydraulic System B   | Armed    |
| Auxiliary Power Unit | On       |

|                            |          |
|----------------------------|----------|
| Traffic Advisory Display   | Closed   |
| Autobrake Selector         | Checked  |
| Cargo Smoke Detection      | Verified |
| Autothrottle               | Set      |
| Hydraulic System A         | Off      |
| Flight Management Computer | On       |
| Window Heat                | Armed    |

03.20.11 Checklist: Nosewheel Steering

Values in this manual are invented and must not be used for any operational purpose. The Cabin Pressure Controller selector position that differs from the expected state requires both pilots to record the condition when conditions permit. The wording here is placeholder content shaped like a procedure, not a procedure. During engine start, the pilot monitoring should verify the Auxiliary Power Unit quantity display once the checklist item is complete. If the Center Tank Pumps is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance. During takeoff, both pilots should brief the Fire Detection Loop status message if a discrepancy is observed.

If the Thrust Reverser is inoperative, continue an extended ground delay only after the pilot flying has reviewed the associated sample guidance. During cruise, the pilot monitoring should confirm the Landing Gear Indication status message unless directed otherwise by the Sample Operations Center. The relief pilot will confirm any change in the Weather Radar quantity display and advise the other pilot when the associated caution light remains illuminated.

The Cabin Pressure Controller advisory that differs from the expected state requires the relief pilot to verify the condition if a discrepancy is observed. If the Hydraulic System B is inoperative, continue a turnaround only after the pilot monitoring has reviewed the associated sample guidance. During a diversion, the pilot monitoring should brief the Cockpit Voice Recorder switch position when conditions permit.

**CAUTION:** The Standby Hydraulic switch position is expected to read within the sample range of 55 to 64 units during an extended ground delay.

During parking, the First Officer should cross-check the Autopilot Channel A selector position when conditions permit. The captain will verify any change in the Landing Gear Indication indication and advise the other pilot when operating at a sample station without ground power. The Flight Management Computer switch position that differs from the expected state requires the First Officer to brief the condition before the next phase of flight. During an extended ground delay, the relief pilot should announce the Wing Anti-Ice status message before the next phase of flight. If the Autopilot Channel A is inoperative, continue engine start only after both pilots has reviewed the associated sample guidance. See 06.40.10 Wing Anti-Ice Limits Display.

- During engine start, both pilots should verify the Speedbrake Handle selector position if a discrepancy is observed.
- The Autobrake Selector status message that differs from the expected state requires the Captain to select the condition when the associated caution light remains illuminated.
- The Flight Management Computer status message that differs from the expected state requires the pilot monitoring to cross-check the condition before the next phase of flight.
- The Probe Heat status message that differs from the expected state requires the Captain to verify the condition when conditions permit.
- During a turnaround, the pilot monitoring should monitor the Pack Temperature Control advisory if a discrepancy is observed.

| Challenge           | Response |
|---------------------|----------|
| Standby Instruments | On       |



|                        |             |
|------------------------|-------------|
| Cockpit Voice Recorder | Checked     |
| Fuel Crossfeed         | As required |
| Oxygen Distribution    | Set         |
| Weather Radar          | On          |
| Autopilot Channel A    | Armed       |
| Primary Electrical Bus | Closed      |
| Fire Detection Loop    | As required |

### 03.20.12 Flow: Center Tank Pumps

The Hydraulic System B quantity display is expected to read within the sample range of 93 to 99 units during climb. The Brake Temperature Monitor advisory is expected to read within the sample range of 81 to 91 units during preflight. The Standby Instruments status message is expected to read within the sample range of 61 to 71 units during approach. The Traffic Advisory Display indication is expected to read within the sample range of 14 to 25 units during descent. If the Autothrottle is inoperative, continue engine start only after both pilots has reviewed the associated sample guidance. The pilot flying will brief any change in the Landing Gear Indication selector position and advise the other pilot if a discrepancy is observed.

**CAUTION:** Refer to the related topic for additional sample context.

- If the Cargo Smoke Detection is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance.
- Refer to the related topic for additional sample context.
- During a maintenance-requested ground run, the First Officer should verify the Auxiliary Power Unit indication unless directed otherwise by the Sample Operations Center.
- During a diversion, the pilot flying should announce the Standby Hydraulic indication if the indication does not stabilize within the sample interval.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Fuel Crossfeed annunciation               | 4 units      | Refer to related topic |
| Thrust Reverser selector position         | 3 units      | Advisory only          |
| Landing Gear Indication status message    | 75 units     | Refer to related topic |
| Hydraulic System B selector position      | 23 units     | Normal                 |
| Landing Gear Indication selector position | 17 units     | Refer to related topic |

| Condition                            | Sample value | Remarks |
|--------------------------------------|--------------|---------|
| Cargo Smoke Detection status message | 47 units     | Normal  |
| Cockpit Voice Recorder indication    | 95 units     | Monitor |
| Bleed Air Supply advisory            | 44 units     | Normal  |

During landing, both pilots should announce the Flap Position Indication status message when the associated caution light remains illuminated. The Standby Instruments switch position is expected to read within the sample range of 42 to 51 units during approach. During a turnaround, the relief pilot should cross-check the Primary Electrical Bus quantity display unless directed otherwise by the Sample Operations Center. During a maintenance-requested ground run, the Captain should monitor the Wing Anti-Ice advisory when operating at a sample station without ground power. See 01.10.6 Organization Topic 5.

**CAUTION:** The Autopilot Channel B advisory is expected to read within the sample range of 89 to 98 units during engine start. The Center Tank Pumps selector position that differs from the expected state requires the relief pilot

to monitor the condition when operating at a sample station without ground power.

| Condition                       | Sample value | Remarks                |
|---------------------------------|--------------|------------------------|
| Fuel Crossfeed quantity display | 9 units      | Advisory only          |
| Wing Anti-Ice annunciation      | 98 units     | Refer to related topic |
| Autothrottle annunciation       | 85 units     | Advisory only          |

**03.20.13 Checklist: Hydraulic System A**

The captain will verify any change in the Weather Radar status message and advise the other pilot if a discrepancy is observed. During cruise, the Captain should announce the Transponder advisory when operating at a sample station without ground power. During preflight, the relief pilot should brief the Flight Management Computer annunciation when operating at a sample station without ground power. During a turnaround, the pilot flying should select the Auxiliary Power Unit advisory when conditions permit.

The captain will record any change in the Autopilot Channel A quantity display and advise the other pilot when the associated caution light remains illuminated. Refer to the related topic for additional sample context. The first officer will brief any change in the Hydraulic System B selector position and advise the other pilot when the associated caution light remains illuminated.

- This text is fictional and exists only to give the prototype realistic volume and structure.
- If the Hydraulic System A is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance.
- The first officer will confirm any change in the Pack Temperature Control annunciation and advise the other pilot if the indication does not stabilize within the sample interval.
- The Traffic Advisory Display annunciation is expected to read within the sample range of 21 to 28 units during preflight.
- The Flap Position Indication annunciation that differs from the expected state requires the First Officer to select the condition when operating at a sample station without ground power.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Window Heat switch position             | 41 units     | Advisory only          |
| Fire Detection Loop advisory            | 57 units     | Normal                 |
| Flap Position Indication advisory       | 22 units     | Advisory only          |
| Speedbrake Handle quantity display      | 25 units     | Normal                 |
| Stall Warning advisory                  | 1 units      | Normal                 |
| Flight Management Computer annunciation | 3 units      | Normal                 |
| Autothrottle advisory                   | 79 units     | Refer to related topic |

**CAUTION:** The Nosewheel Steering quantity display is expected to read within the sample range of 25 to 28 units during a diversion. The Flight Management Computer indication that differs from the expected state requires both pilots to brief the condition when the associated caution light remains illuminated.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Fire Detection Loop annunciation           | 2 units      | Advisory only          |
| Ground Proximity Monitor selector position | 53 units     | Refer to related topic |
| Engine Anti-Ice annunciation               | 82 units     | Normal                 |

The Standby Hydraulic quantity display that differs from the expected state requires the pilot monitoring to record the condition before the next phase of flight. The Weather Radar selector position that differs from the expected state requires both pilots to cross-check the condition when the associated caution light remains illuminated. If the Flap Position Indication is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance. The relief pilot will announce any change in the Fire Detection Loop selector position and advise the other pilot once the checklist item is complete. The Center Tank Pumps indication that differs from the expected state requires the First Officer to select the condition when operating at a sample station without ground power. The captain will monitor any change in the Traffic Advisory Display switch position and advise the other pilot unless directed otherwise by the Sample Operations Center.

**03.20.14 Crew Coordination: Engine Anti-Ice**

The Autobrake Selector status message that differs from the expected state requires the pilot flying to record the condition if a discrepancy is observed. If the Oxygen Distribution is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance. The Cargo Smoke Detection quantity display that differs from the expected state requires the First Officer to brief the condition once the checklist item is complete. If the Pack Temperature Control is inoperative, continue preflight only after both pilots has reviewed the associated sample guidance.

**CAUTION:** During cruise, the First Officer should announce the Ground Proximity Monitor indication if the indication does not stabilize within the sample interval. During approach, the pilot flying should announce the Autopilot Channel B advisory if a discrepancy is observed.

- This text is fictional and exists only to give the prototype realistic volume and structure.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- During approach, the relief pilot should record the Center Tank Pumps status message once the checklist item is complete.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- The Weather Radar status message that differs from the expected state requires the relief pilot to brief the condition before the next phase of flight.

| Condition                           | Sample value | Remarks                |
|-------------------------------------|--------------|------------------------|
| Ground Proximity Monitor advisory   | 56 units     | Monitor                |
| Flap Position Indication advisory   | 78 units     | Monitor                |
| Standby Hydraulic advisory          | 25 units     | Advisory only          |
| Thrust Reverser quantity display    | 59 units     | Normal                 |
| Wing Anti-Ice status message        | 29 units     | Refer to related topic |
| Pack Temperature Control indication | 65 units     | Normal                 |
| Cabin Pressure Controller advisory  | 19 units     | Advisory only          |

Values in this manual are invented and must not be used for any operational purpose. If the Oxygen Distribution is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance. The Cabin Pressure Controller advisory that differs from the expected state requires the First Officer to brief the condition once the checklist item is complete. The Oxygen Distribution advisory that differs from the expected state requires the relief pilot to cross-check the condition if the indication does not stabilize within the sample interval. During climb, the pilot monitoring should cross-check the Primary Electrical Bus selector position before the next phase of flight.

| Condition                           | Sample value | Remarks |
|-------------------------------------|--------------|---------|
| Standby Instruments switch position | 48 units     | Monitor |
| Auxiliary Power Unit advisory       | 7 units      | Normal  |

|                                            |          |               |
|--------------------------------------------|----------|---------------|
| Landing Gear Indication status message     | 39 units | Monitor       |
| Brake Temperature Monitor quantity display | 17 units | Normal        |
| Fire Detection Loop advisory               | 30 units | Advisory only |
| Hydraulic System B quantity display        | 43 units | Advisory only |
| Landing Gear Indication selector position  | 93 units | Advisory only |

### 03.20.15 Crew Coordination: Weather Radar

If the Auxiliary Power Unit is inoperative, continue a diversion only after the First Officer has reviewed the associated sample guidance. The Autopilot Channel B status message that differs from the expected state requires the First Officer to brief the condition when the associated caution light remains illuminated. The Brake Temperature Monitor switch position is expected to read within the sample range of 83 to 95 units during landing. During approach, the Captain should select the Autopilot Channel A indication when operating at a sample station without ground power.

If the Stall Warning is inoperative, continue a turnaround only after the First Officer has reviewed the associated sample guidance. If the Thrust Reverser is inoperative, continue approach only after the relief pilot has reviewed the associated sample guidance. The Fire Detection Loop switch position is expected to read within the sample range of 46 to 55 units during a maintenance-requested ground run. Values in this manual are invented and must not be used for any operational purpose. During a turnaround, the relief pilot should cross-check the Flap Position Indication selector position once the checklist item is complete. If the Probe Heat is inoperative, continue parking only after the Captain has reviewed the associated sample guidance.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Probe Heat quantity display              | 25 units     | Advisory only          |
| Pack Temperature Control switch position | 72 units     | Monitor                |
| Auxiliary Power Unit indication          | 44 units     | Refer to related topic |
| Speedbrake Handle status message         | 10 units     | Monitor                |

| Condition                                   | Sample value | Remarks       |
|---------------------------------------------|--------------|---------------|
| Cargo Smoke Detection switch position       | 35 units     | Monitor       |
| Brake Temperature Monitor selector position | 80 units     | Monitor       |
| Speedbrake Handle advisory                  | 25 units     | Advisory only |
| Autopilot Channel A advisory                | 46 units     | Advisory only |
| Auxiliary Power Unit status message         | 82 units     | Normal        |

**CAUTION:** Both pilots will monitor any change in the Brake Temperature Monitor switch position and advise the other pilot if the indication does not stabilize within the sample interval.

**NOTE:** The captain will brief any change in the Fuel Crossfeed annunciation and advise the other pilot if a discrepancy is observed.

Both pilots will brief any change in the Fuel Crossfeed advisory and advise the other pilot before the next phase of flight. The Standby Hydraulic advisory that differs from the expected state requires the pilot monitoring to confirm the condition before the next phase of flight. The relief pilot will monitor any change in the Primary Electrical Bus indication and advise the other pilot if the indication does not stabilize within the sample interval.

### 03.20.16 Flow: Oxygen Distribution

If the Bleed Air Supply is inoperative, continue a maintenance-requested ground run only after the pilot flying has reviewed the associated sample guidance. If the Cargo Smoke Detection is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance. During descent, both pilots should

select the Cabin Pressure Controller selector position unless directed otherwise by the Sample Operations Center. The first officer will verify any change in the Primary Electrical Bus status message and advise the other pilot before the next phase of flight. During a turnaround, the Captain should monitor the Cockpit Voice Recorder annunciation once the checklist item is complete. If the Oxygen Distribution is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance.

- If the Wing Anti-Ice is inoperative, continue preflight only after both pilots has reviewed the associated sample guidance.
- The Auxiliary Power Unit advisory that differs from the expected state requires the pilot flying to brief the condition if the indication does not stabilize within the sample interval.
- During a turnaround, the First Officer should confirm the Center Tank Pumps status message unless directed otherwise by the Sample Operations Center.

**NOTE:** During climb, the relief pilot should brief the Cabin Pressure Controller selector position unless directed otherwise by the Sample Operations Center. The Auxiliary Power Unit switch position that differs from the expected state requires the Captain to select the condition when operating at a sample station without ground power.

**NOTE:** The pilot monitoring will announce any change in the Oxygen Distribution advisory and advise the other pilot if the indication does not stabilize within the sample interval. The captain will monitor any change in the Probe Heat annunciation and advise the other pilot when operating at a sample station without ground power.

| Condition                            | Sample value | Remarks       |
|--------------------------------------|--------------|---------------|
| Weather Radar quantity display       | 48 units     | Normal        |
| Hydraulic System B selector position | 31 units     | Advisory only |
| Autopilot Channel B status message   | 91 units     | Monitor       |

**03.20.17 Crew Coordination: Weather Radar**

The Flight Management Computer switch position is expected to read within the sample range of 96 to 108 units during an extended ground delay. The Autothrottle quantity display is expected to read within the sample range of 33 to 39 units during taxi. If the Pack Temperature Control is inoperative, continue cruise only after the First Officer has reviewed the associated sample guidance.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Probe Heat status message                  | 2 units      | Normal                 |
| Thrust Reverser quantity display           | 28 units     | Refer to related topic |
| Fuel Crossfeed quantity display            | 68 units     | Advisory only          |
| Cabin Pressure Controller quantity display | 88 units     | Normal                 |
| Cockpit Voice Recorder annunciation        | 82 units     | Normal                 |

The Window Heat advisory that differs from the expected state requires the pilot monitoring to monitor the condition if a discrepancy is observed. If the Transponder is inoperative, continue an extended ground delay only after the Captain has reviewed the associated sample guidance. If the Cargo Smoke Detection is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance. The Wing Anti-Ice switch position is expected to read within the sample range of 83 to 93 units during engine start.

The Cockpit Voice Recorder advisory that differs from the expected state requires the pilot flying to cross-check the condition before the next phase of flight. Values in this manual are invented and must not be used for any operational purpose. The pilot monitoring will verify any change in the Engine Anti-Ice switch position and advise the other pilot unless directed otherwise by the Sample Operations Center. The Fuel Crossfeed advisory that differs from the expected state requires both pilots to record the condition if the indication does not stabilize within the sample

interval. The Auxiliary Power Unit advisory is expected to read within the sample range of 9 to 12 units during descent.

- During approach, the pilot monitoring should monitor the Window Heat annunciation when the associated caution light remains illuminated.
- The Fuel Crossfeed status message that differs from the expected state requires the relief pilot to record the condition if a discrepancy is observed.
- The Speedbrake Handle selector position that differs from the expected state requires the First Officer to cross-check the condition when conditions permit.

| Challenge                | Response |
|--------------------------|----------|
| Window Heat              | Closed   |
| Flap Position Indication | Verified |
| Fuel Crossfeed           | Armed    |
| Flap Position Indication | On       |
| Ground Proximity Monitor | Verified |
| Center Tank Pumps        | Set      |
| Stall Warning            | Closed   |
| Probe Heat               | Verified |
| Pack Temperature Control | On       |
| Fuel Crossfeed           | Closed   |
| Speedbrake Handle        | Verified |

**03.20.18 Flow: Thrust Reverser**

The Hydraulic System B advisory that differs from the expected state requires both pilots to confirm the condition before the next phase of flight. The relief pilot will confirm any change in the Cargo Smoke Detection selector position and advise the other pilot before the next phase of flight. The Standby Instruments advisory that differs from the expected state requires the First Officer to select the condition once the checklist item is complete.

During climb, the relief pilot should verify the Transponder status message when the associated caution light remains illuminated. This text is fictional and exists only to give the prototype realistic volume and structure. The Hydraulic System B quantity display is expected to read within the sample range of 34 to 43 units during a turnaround. If the Cockpit Voice Recorder is inoperative, continue approach only after the relief pilot has reviewed the associated sample guidance.

The Probe Heat status message that differs from the expected state requires both pilots to verify the condition if a discrepancy is observed. The Bleed Air Supply annunciation that differs from the expected state requires the First Officer to brief the condition if the indication does not stabilize within the sample interval. This text is fictional and exists only to give the prototype realistic volume and structure. Values in this manual are invented and must not be used for any operational purpose.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Brake Temperature Monitor quantity display | 82 units     | Normal                 |
| Weather Radar indication                   | 28 units     | Advisory only          |
| Landing Gear Indication annunciation       | 59 units     | Refer to related topic |

- The wording here is placeholder content shaped like a procedure, not a procedure.
- During climb, the pilot monitoring should monitor the Ground Proximity Monitor advisory when operating at a sample station without ground power.



- The Standby Hydraulic switch position is expected to read within the sample range of 12 to 15 units during approach.
- The Cabin Pressure Controller indication is expected to read within the sample range of 53 to 57 units during an extended ground delay.

**CAUTION:** The Bleed Air Supply indication that differs from the expected state requires the pilot monitoring to announce the condition when conditions permit. The relief pilot will record any change in the Fire Detection Loop status message and advise the other pilot if the indication does not stabilize within the sample interval.

Both pilots will monitor any change in the Oxygen Distribution quantity display and advise the other pilot before the next phase of flight. Refer to the related topic for additional sample context. The Ground Proximity Monitor quantity display that differs from the expected state requires both pilots to brief the condition if a discrepancy is observed. See 04.30.2 Crew Coordination: Wing Anti-Ice.

**NOTE:** Values in this manual are invented and must not be used for any operational purpose. If the Window Heat is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance.

**CAUTION:** If the Fire Detection Loop is inoperative, continue approach only after both pilots has reviewed the associated sample guidance.

**03.20.19 Verification: Cabin Pressure Controller**

During takeoff, both pilots should brief the Autobrake Selector switch position when conditions permit. During parking, the pilot flying should confirm the Fire Detection Loop annunciation when the associated caution light remains illuminated. The Oxygen Distribution status message that differs from the expected state requires the pilot monitoring to verify the condition before the next phase of flight. The Auxiliary Power Unit advisory is expected to read within the sample range of 9 to 16 units during a diversion.

- During a maintenance-requested ground run, the pilot monitoring should record the Flight Management Computer advisory when conditions permit.
- During descent, both pilots should announce the Wing Anti-Ice selector position when conditions permit.
- If the Transponder is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance.
- The pilot flying will confirm any change in the Hydraulic System A quantity display and advise the other pilot when operating at a sample station without ground power.
- If the Auxiliary Power Unit is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance.
- The Engine Anti-Ice quantity display that differs from the expected state requires the First Officer to cross-check the condition before the next phase of flight.
- During approach, the pilot flying should cross-check the Fuel Crossfeed annunciation once the checklist item is complete.
- The Engine Anti-Ice selector position that differs from the expected state requires both pilots to record the condition if the indication does not stabilize within the sample interval.
- The Engine Anti-Ice annunciation is expected to read within the sample range of 50 to 53 units during preflight.

**CAUTION:** The Auxiliary Power Unit quantity display that differs from the expected state requires the First Officer to announce the condition once the checklist item is complete. During taxi, the First Officer should confirm the Stall Warning indication when conditions permit.

| Condition                             | Sample value | Remarks |
|---------------------------------------|--------------|---------|
| Cargo Smoke Detection switch position | 67 units     | Monitor |

|                                       |          |                        |
|---------------------------------------|----------|------------------------|
| Bleed Air Supply switch position      | 82 units | Refer to related topic |
| Cockpit Voice Recorder status message | 89 units | Monitor                |

**NOTE:** The wording here is placeholder content shaped like a procedure, not a procedure. The first officer will monitor any change in the Flap Position Indication advisory and advise the other pilot when operating at a sample station without ground power.

Values in this manual are invented and must not be used for any operational purpose. Refer to the related topic for additional sample context. The Brake Temperature Monitor advisory that differs from the expected state requires the Captain to brief the condition when conditions permit. The pilot flying will brief any change in the Cabin Pressure Controller advisory and advise the other pilot when the associated caution light remains illuminated. See 11.10.1 Autopilot Channel A Crew Awareness.

- The relief pilot will brief any change in the Standby Instruments quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center.
- If the Engine Anti-Ice is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance.
- The Brake Temperature Monitor advisory that differs from the expected state requires both pilots to record the condition unless directed otherwise by the Sample Operations Center.

| Condition                           | Sample value | Remarks                |
|-------------------------------------|--------------|------------------------|
| Nosewheel Steering quantity display | 51 units     | Monitor                |
| Hydraulic System B advisory         | 45 units     | Monitor                |
| Stall Warning indication            | 5 units      | Normal                 |
| Fuel Crossfeed indication           | 35 units     | Refer to related topic |
| Auxiliary Power Unit indication     | 64 units     | Normal                 |

| Challenge                  | Response |
|----------------------------|----------|
| Brake Temperature Monitor  | Verified |
| Autobrake Selector         | On       |
| Center Tank Pumps          | Armed    |
| Flight Management Computer | Checked  |
| Traffic Advisory Display   | Off      |
| Flap Position Indication   | On       |

**03.20.20 Briefing: Pack Temperature Control**

The Speedbrake Handle quantity display is expected to read within the sample range of 77 to 89 units during approach. During descent, the Captain should verify the Pack Temperature Control switch position when conditions permit. Both pilots will verify any change in the Pack Temperature Control advisory and advise the other pilot once the checklist item is complete.

- The Ground Proximity Monitor selector position is expected to read within the sample range of 70 to 73 units during preflight.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- Values in this manual are invented and must not be used for any operational purpose.

| Condition                                   | Sample value | Remarks       |
|---------------------------------------------|--------------|---------------|
| Cabin Pressure Controller selector position | 10 units     | Advisory only |

|                                         |          |               |
|-----------------------------------------|----------|---------------|
| Stall Warning quantity display          | 7 units  | Monitor       |
| Primary Electrical Bus quantity display | 31 units | Advisory only |
| Engine Anti-Ice annunciation            | 86 units | Advisory only |
| Weather Radar annunciation              | 47 units | Advisory only |
| Cockpit Voice Recorder quantity display | 87 units | Advisory only |
| Autobrake Selector selector position    | 90 units | Monitor       |

- If the Engine Anti-Ice is inoperative, continue approach only after the First Officer has reviewed the associated sample guidance.
- The pilot flying will monitor any change in the Pack Temperature Control indication and advise the other pilot when conditions permit.
- If the Hydraulic System A is inoperative, continue descent only after both pilots has reviewed the associated sample guidance.
- During descent, the First Officer should monitor the Oxygen Distribution status message once the checklist item is complete.
- This text is fictional and exists only to give the prototype realistic volume and structure.

**CAUTION:** The wording here is placeholder content shaped like a procedure, not a procedure. The Pack Temperature Control indication is expected to read within the sample range of 85 to 94 units during preflight.

### 03.20.21 Callouts: Ground Proximity Monitor

The captain will select any change in the Center Tank Pumps advisory and advise the other pilot when the associated caution light remains illuminated. The Transponder indication that differs from the expected state requires the First Officer to record the condition if a discrepancy is observed. During taxi, both pilots should announce the Probe Heat annunciation unless directed otherwise by the Sample Operations Center. During landing, the First Officer should confirm the Pack Temperature Control selector position before the next phase of flight. During an extended ground delay, the relief pilot should monitor the Stall Warning indication if the indication does not stabilize within the sample interval.

**NOTE:** During taxi, the pilot flying should confirm the Window Heat advisory once the checklist item is complete.

The pilot monitoring will record any change in the Oxygen Distribution quantity display and advise the other pilot if the indication does not stabilize within the sample interval. The Weather Radar indication is expected to read within the sample range of 96 to 99 units during a turnaround. The Standby Hydraulic switch position is expected to read within the sample range of 46 to 53 units during parking. If the Flight Management Computer is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance.

**CAUTION:** The Autopilot Channel B switch position is expected to read within the sample range of 29 to 32 units during an extended ground delay.

**NOTE:** Refer to the related topic for additional sample context.

### 03.20.22 Callouts: Stall Warning

The first officer will verify any change in the Autothrottle status message and advise the other pilot once the checklist item is complete. During a maintenance-requested ground run, the pilot monitoring should monitor the Weather Radar selector position once the checklist item is complete. During a turnaround, the pilot flying should brief the Engine Anti-Ice advisory when the associated caution light remains illuminated. If the Cabin Pressure Controller is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance. The Probe Heat selector position that differs from the expected state requires the pilot flying to confirm the condition if a discrepancy is observed. If the Hydraulic System B is inoperative, continue a turnaround only after the pilot flying has

reviewed the associated sample guidance.

**NOTE:** Values in this manual are invented and must not be used for any operational purpose. The relief pilot will brief any change in the Traffic Advisory Display quantity display and advise the other pilot when operating at a sample station without ground power.

If the Landing Gear Indication is inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance. If the Brake Temperature Monitor is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance. The Flap Position Indication selector position that differs from the expected state requires both pilots to record the condition when conditions permit. Refer to the related topic for additional sample context. If the Engine Anti-Ice is inoperative, continue climb only after both pilots has reviewed the associated sample guidance. During takeoff, both pilots should monitor the Flight Management Computer annunciation if the indication does not stabilize within the sample interval.

**NOTE:** This text is fictional and exists only to give the prototype realistic volume and structure.

**CAUTION:** The Transponder quantity display is expected to read within the sample range of 37 to 43 units during engine start. During an extended ground delay, the Captain should select the Window Heat quantity display once the checklist item is complete.

The wording here is placeholder content shaped like a procedure, not a procedure. The Speedbrake Handle advisory is expected to read within the sample range of 95 to 104 units during landing. The Autopilot Channel B annunciation is expected to read within the sample range of 53 to 62 units during takeoff. The Probe Heat status message that differs from the expected state requires the First Officer to announce the condition before the next phase of flight. The wording here is placeholder content shaped like a procedure, not a procedure.

During approach, the relief pilot should announce the Cabin Pressure Controller selector position when the associated caution light remains illuminated. During preflight, the Captain should record the Bleed Air Supply indication if a discrepancy is observed. Refer to the related topic for additional sample context. The Oxygen Distribution annunciation is expected to read within the sample range of 15 to 25 units during taxi. During parking, the First Officer should brief the Hydraulic System A quantity display once the checklist item is complete.

This text is fictional and exists only to give the prototype realistic volume and structure. This text is fictional and exists only to give the prototype realistic volume and structure. The wording here is placeholder content shaped like a procedure, not a procedure. The Engine Anti-Ice quantity display is expected to read within the sample range of 75 to 81 units during engine start.

| Challenge                  | Response    |
|----------------------------|-------------|
| Weather Radar              | As required |
| Cargo Smoke Detection      | Closed      |
| Center Tank Pumps          | On          |
| Ground Proximity Monitor   | As required |
| Hydraulic System B         | On          |
| Flap Position Indication   | Off         |
| Flight Management Computer | On          |
| Standby Instruments        | On          |
| Hydraulic System B         | On          |

**03.20.23 Flow: Standby Instruments**

Values in this manual are invented and must not be used for any operational purpose. During approach, the pilot flying should brief the Ground Proximity Monitor indication once the checklist item is complete. The Autopilot Channel B advisory is expected to read within the sample range of 67 to 72 units during descent.

**CAUTION:** The wording here is placeholder content shaped like a procedure, not a procedure. The wording here is placeholder content shaped like a procedure, not a procedure.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Brake Temperature Monitor quantity display | 38 units     | Refer to related topic |
| Weather Radar advisory                     | 89 units     | Refer to related topic |
| Bleed Air Supply switch position           | 91 units     | Monitor                |
| Auxiliary Power Unit switch position       | 10 units     | Refer to related topic |
| Landing Gear Indication annunciation       | 75 units     | Refer to related topic |

**CAUTION:** The Fuel Crossfeed selector position is expected to read within the sample range of 97 to 106 units during landing.

**NOTE:** During takeoff, the pilot monitoring should verify the Bleed Air Supply status message unless directed otherwise by the Sample Operations Center. Values in this manual are invented and must not be used for any operational purpose.

- During a turnaround, the relief pilot should confirm the Autopilot Channel B selector position once the checklist item is complete.
- The first officer will brief any change in the Nosewheel Steering indication and advise the other pilot unless directed otherwise by the Sample Operations Center.
- The Fuel Crossfeed annunciation that differs from the expected state requires the relief pilot to announce the condition if a discrepancy is observed.
- This text is fictional and exists only to give the prototype realistic volume and structure.

During an extended ground delay, the Captain should brief the Bleed Air Supply quantity display unless directed otherwise by the Sample Operations Center. Values in this manual are invented and must not be used for any operational purpose. The Bleed Air Supply status message is expected to read within the sample range of 52 to 58 units during climb. The Autothrottle status message is expected to read within the sample range of 51 to 56 units during takeoff. The wording here is placeholder content shaped like a procedure, not a procedure.

### 03.20.24 Checklist: Hydraulic System A

During a turnaround, the Captain should announce the Ground Proximity Monitor quantity display before the next phase of flight. If the Weather Radar is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure.

**CAUTION:** During engine start, the pilot flying should verify the Brake Temperature Monitor advisory if the indication does not stabilize within the sample interval. If the Stall Warning is inoperative, continue cruise only after the First Officer has reviewed the associated sample guidance.

| Condition                          | Sample value | Remarks                |
|------------------------------------|--------------|------------------------|
| Standby Instruments indication     | 86 units     | Normal                 |
| Thrust Reverser advisory           | 69 units     | Monitor                |
| Hydraulic System B switch position | 96 units     | Refer to related topic |

During approach, the relief pilot should confirm the Center Tank Pumps indication once the checklist item is complete. The Flap Position Indication quantity display is expected to read within the sample range of 20 to 32 units during landing. The Autopilot Channel B status message that differs from the expected state requires both pilots to brief the condition unless directed otherwise by the Sample Operations Center. Refer to the related topic for additional sample context. The Stall Warning selector position that differs from the expected state requires the relief pilot to record the

condition when operating at a sample station without ground power. The Primary Electrical Bus quantity display that differs from the expected state requires the Captain to verify the condition when the associated caution light remains illuminated.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Flap Position Indication selector position | 73 units     | Monitor                |
| Pack Temperature Control advisory          | 92 units     | Normal                 |
| Traffic Advisory Display indication        | 28 units     | Normal                 |
| Fire Detection Loop selector position      | 74 units     | Refer to related topic |
| Fire Detection Loop status message         | 88 units     | Refer to related topic |
| Autopilot Channel A indication             | 35 units     | Monitor                |
| Probe Heat switch position                 | 49 units     | Monitor                |

| Challenge                  | Response    |
|----------------------------|-------------|
| Flight Management Computer | Off         |
| Standby Hydraulic          | As required |
| Window Heat                | On          |
| Center Tank Pumps          | Verified    |
| Oxygen Distribution        | Armed       |
| Engine Anti-Ice            | Off         |
| Cargo Smoke Detection      | On          |
| Thrust Reverser            | Verified    |
| Brake Temperature Monitor  | On          |
| Autobrake Selector         | Verified    |

### 03.20.25 Checklist: Speedbrake Handle

During preflight, both pilots should brief the Bleed Air Supply annunciation if the indication does not stabilize within the sample interval. During descent, the First Officer should cross-check the Flight Management Computer switch position unless directed otherwise by the Sample Operations Center. The Oxygen Distribution annunciation that differs from the expected state requires the relief pilot to brief the condition if the indication does not stabilize within the sample interval.

The wording here is placeholder content shaped like a procedure, not a procedure. Values in this manual are invented and must not be used for any operational purpose. The Ground Proximity Monitor selector position is expected to read within the sample range of 44 to 55 units during an extended ground delay. If the Auxiliary Power Unit is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. During climb, both pilots should select the Brake Temperature Monitor switch position if the indication does not stabilize within the sample interval.

| Condition                            | Sample value | Remarks       |
|--------------------------------------|--------------|---------------|
| Autopilot Channel A quantity display | 34 units     | Normal        |
| Stall Warning annunciation           | 7 units      | Advisory only |
| Bleed Air Supply annunciation        | 8 units      | Advisory only |
| Nosewheel Steering annunciation      | 24 units     | Monitor       |

During climb, the First Officer should record the Weather Radar status message before the next phase of flight. The Autothrottle selector position is expected to read within the sample range of 72 to 81 units during descent. The



wording here is placeholder content shaped like a procedure, not a procedure. The Center Tank Pumps status message that differs from the expected state requires both pilots to monitor the condition if a discrepancy is observed. The pilot monitoring will record any change in the Window Heat selector position and advise the other pilot before the next phase of flight. During engine start, the relief pilot should announce the Hydraulic System A advisory when operating at a sample station without ground power.

The wording here is placeholder content shaped like a procedure, not a procedure. During parking, the First Officer should select the Cabin Pressure Controller annunciation if the indication does not stabilize within the sample interval. Refer to the related topic for additional sample context. During approach, the pilot flying should select the Weather Radar status message if a discrepancy is observed.

| Challenge                | Response    |
|--------------------------|-------------|
| Bleed Air Supply         | As required |
| Window Heat              | Closed      |
| Fire Detection Loop      | On          |
| Flap Position Indication | Checked     |
| Wing Anti-Ice            | Verified    |
| Weather Radar            | On          |
| Oxygen Distribution      | As required |
| Standby Hydraulic        | Closed      |
| Bleed Air Supply         | Armed       |
| Flap Position Indication | Closed      |

### 03.30 Taxi

#### 03.30.1 Verification: Thrust Reverser

Values in this manual are invented and must not be used for any operational purpose. During descent, the First Officer should monitor the Bleed Air Supply indication when operating at a sample station without ground power. The Landing Gear Indication indication is expected to read within the sample range of 92 to 97 units during preflight.

| Condition                        | Sample value | Remarks                |
|----------------------------------|--------------|------------------------|
| Weather Radar annunciation       | 74 units     | Refer to related topic |
| Transponder annunciation         | 19 units     | Monitor                |
| Fire Detection Loop annunciation | 56 units     | Advisory only          |

The Center Tank Pumps switch position that differs from the expected state requires the pilot flying to confirm the condition when conditions permit. The pilot monitoring will verify any change in the Hydraulic System A selector position and advise the other pilot when the associated caution light remains illuminated. Refer to the related topic for additional sample context. The Speedbrake Handle selector position that differs from the expected state requires the relief pilot to brief the condition when operating at a sample station without ground power.

During a turnaround, the Captain should announce the Standby Hydraulic switch position when conditions permit. The Speedbrake Handle selector position that differs from the expected state requires the pilot monitoring to announce the condition when operating at a sample station without ground power. The Primary Electrical Bus quantity display is expected to read within the sample range of 3 to 9 units during a maintenance-requested ground run. Refer to the related topic for additional sample context. Refer to the related topic for additional sample context. The Nosewheel Steering indication is expected to read within the sample range of 86 to 95 units during a maintenance-requested ground run.

The wording here is placeholder content shaped like a procedure, not a procedure. The Center Tank Pumps status message is expected to read within the sample range of 57 to 60 units during a diversion. The Weather Radar selector position that differs from the expected state requires the First Officer to select the condition when conditions permit.

03.30.2 Flow: Traffic Advisory Display

Refer to the related topic for additional sample context. The pilot flying will verify any change in the Oxygen Distribution quantity display and advise the other pilot once the checklist item is complete. The Ground Proximity Monitor selector position is expected to read within the sample range of 17 to 29 units during landing. During an extended ground delay, the Captain should brief the Fuel Crossfeed selector position if a discrepancy is observed.

The Autothrottle selector position is expected to read within the sample range of 77 to 87 units during a diversion. Both pilots will brief any change in the Autopilot Channel B advisory and advise the other pilot unless directed otherwise by the Sample Operations Center. During cruise, both pilots should announce the Ground Proximity Monitor quantity display if the indication does not stabilize within the sample interval.

**NOTE:** This text is fictional and exists only to give the prototype realistic volume and structure. The pilot monitoring will record any change in the Nosewheel Steering indication and advise the other pilot when the associated caution light remains illuminated.

**CAUTION:** During descent, both pilots should select the Hydraulic System A annunciation unless directed otherwise by the Sample Operations Center.

| Condition                                    | Sample value | Remarks                |
|----------------------------------------------|--------------|------------------------|
| Nosewheel Steering advisory                  | 7 units      | Advisory only          |
| Flight Management Computer selector position | 35 units     | Advisory only          |
| Auxiliary Power Unit status message          | 38 units     | Monitor                |
| Standby Hydraulic switch position            | 8 units      | Monitor                |
| Ground Proximity Monitor indication          | 77 units     | Refer to related topic |
| Autopilot Channel A status message           | 75 units     | Normal                 |

The first officer will monitor any change in the Hydraulic System A annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center. If the Auxiliary Power Unit is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance. Both pilots will brief any change in the Weather Radar advisory and advise the other pilot before the next phase of flight. If the Traffic Advisory Display is inoperative, continue taxi only after the Captain has reviewed the associated sample guidance.

| Condition                                | Sample value | Remarks       |
|------------------------------------------|--------------|---------------|
| Probe Heat advisory                      | 16 units     | Normal        |
| Primary Electrical Bus quantity display  | 24 units     | Normal        |
| Engine Anti-Ice selector position        | 20 units     | Advisory only |
| Pack Temperature Control switch position | 54 units     | Monitor       |
| Standby Hydraulic switch position        | 89 units     | Advisory only |
| Nosewheel Steering indication            | 55 units     | Advisory only |

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Standby Hydraulic quantity display      | 26 units     | Monitor                |
| Hydraulic System B annunciation         | 7 units      | Normal                 |
| Ground Proximity Monitor status message | 51 units     | Refer to related topic |
| Thrust Reverser quantity display        | 65 units     | Normal                 |

|                                            |          |                        |
|--------------------------------------------|----------|------------------------|
| Pack Temperature Control quantity display  | 52 units | Refer to related topic |
| Flap Position Indication selector position | 46 units | Refer to related topic |

### 03.30.3 Verification: Primary Electrical Bus

If the Speedbrake Handle is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance. The pilot monitoring will select any change in the Landing Gear Indication annunciation and advise the other pilot if the indication does not stabilize within the sample interval. If the Hydraulic System B is inoperative, continue climb only after the pilot flying has reviewed the associated sample guidance. The Autopilot Channel B advisory that differs from the expected state requires the pilot flying to brief the condition before the next phase of flight. If the Cargo Smoke Detection is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance.

| Condition                              | Sample value | Remarks                |
|----------------------------------------|--------------|------------------------|
| Standby Instruments indication         | 55 units     | Normal                 |
| Standby Hydraulic switch position      | 45 units     | Refer to related topic |
| Autopilot Channel A selector position  | 8 units      | Normal                 |
| Hydraulic System A selector position   | 55 units     | Normal                 |
| Transponder selector position          | 44 units     | Advisory only          |
| Landing Gear Indication status message | 85 units     | Refer to related topic |

**NOTE:** The wording here is placeholder content shaped like a procedure, not a procedure.

The Oxygen Distribution annunciation that differs from the expected state requires the pilot monitoring to announce the condition once the checklist item is complete. The Flight Management Computer status message is expected to read within the sample range of 27 to 35 units during parking. Values in this manual are invented and must not be used for any operational purpose. The Stall Warning status message is expected to read within the sample range of 42 to 51 units during a maintenance-requested ground run.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Wing Anti-Ice quantity display            | 51 units     | Monitor                |
| Landing Gear Indication switch position   | 5 units      | Refer to related topic |
| Autopilot Channel B annunciation          | 73 units     | Advisory only          |
| Pack Temperature Control quantity display | 14 units     | Advisory only          |
| Landing Gear Indication indication        | 61 units     | Monitor                |
| Standby Hydraulic advisory                | 94 units     | Refer to related topic |

The Window Heat advisory that differs from the expected state requires the Captain to monitor the condition once the checklist item is complete. The Autopilot Channel B quantity display is expected to read within the sample range of 54 to 62 units during approach. The Oxygen Distribution quantity display is expected to read within the sample range of 32 to 41 units during parking. The Weather Radar status message is expected to read within the sample range of 40 to 47 units during climb. During cruise, the pilot monitoring should brief the Fuel Crossfeed selector position unless directed otherwise by the Sample Operations Center.

The wording here is placeholder content shaped like a procedure, not a procedure. The pilot flying will announce any change in the Weather Radar quantity display and advise the other pilot if a discrepancy is observed. Both pilots will announce any change in the Nosewheel Steering selector position and advise the other pilot before the next phase of flight. During preflight, the pilot flying should select the Standby Instruments indication when the associated caution light remains illuminated. The Engine Anti-Ice quantity display that differs from the expected state requires the Captain to verify the condition when operating at a sample station without ground power. The Autothrottle annunciation that differs from the expected state requires the pilot flying to confirm the condition if a discrepancy is

observed.

The Hydraulic System A indication that differs from the expected state requires the pilot flying to brief the condition when the associated caution light remains illuminated. The Brake Temperature Monitor status message is expected to read within the sample range of 92 to 104 units during a turnaround. During takeoff, the relief pilot should record the Autopilot Channel B switch position once the checklist item is complete.

| Challenge                | Response |
|--------------------------|----------|
| Flap Position Indication | Armed    |
| Autobrake Selector       | Armed    |
| Autopilot Channel B      | Checked  |
| Cargo Smoke Detection    | Closed   |
| Landing Gear Indication  | Closed   |
| Thrust Reverser          | Set      |

### 03.30.4 Crew Coordination: Flap Position Indication

Values in this manual are invented and must not be used for any operational purpose. During approach, the Captain should monitor the Standby Hydraulic quantity display once the checklist item is complete. If the Landing Gear Indication is inoperative, continue taxi only after the relief pilot has reviewed the associated sample guidance. The Nosewheel Steering selector position is expected to read within the sample range of 70 to 81 units during a maintenance-requested ground run. This text is fictional and exists only to give the prototype realistic volume and structure. The pilot flying will announce any change in the Landing Gear Indication switch position and advise the other pilot if the indication does not stabilize within the sample interval.

| Condition                                | Sample value | Remarks       |
|------------------------------------------|--------------|---------------|
| Autopilot Channel A switch position      | 11 units     | Normal        |
| Landing Gear Indication advisory         | 91 units     | Normal        |
| Autopilot Channel B switch position      | 97 units     | Normal        |
| Oxygen Distribution annunciation         | 57 units     | Advisory only |
| Thrust Reverser annunciation             | 35 units     | Normal        |
| Probe Heat advisory                      | 47 units     | Monitor       |
| Cockpit Voice Recorder selector position | 95 units     | Monitor       |

**CAUTION:** The Ground Proximity Monitor advisory that differs from the expected state requires the pilot flying to announce the condition if the indication does not stabilize within the sample interval.

**NOTE:** During taxi, the relief pilot should brief the Autothrottle quantity display if a discrepancy is observed.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Stall Warning advisory                | 58 units     | Normal                 |
| Thrust Reverser indication            | 44 units     | Refer to related topic |
| Traffic Advisory Display annunciation | 3 units      | Advisory only          |
| Cargo Smoke Detection advisory        | 41 units     | Refer to related topic |

### 03.30.5 Checklist: Stall Warning

The Ground Proximity Monitor indication that differs from the expected state requires the Captain to cross-check the condition unless directed otherwise by the Sample Operations Center. Refer to the related topic for additional sample context. If the Pack Temperature Control is inoperative, continue descent only after the First Officer has reviewed the

associated sample guidance. If the Nosewheel Steering is inoperative, continue a diversion only after the First Officer has reviewed the associated sample guidance.

- The relief pilot will record any change in the Brake Temperature Monitor switch position and advise the other pilot when operating at a sample station without ground power.
- During preflight, the pilot flying should record the Thrust Reverser quantity display before the next phase of flight.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The first officer will verify any change in the Fire Detection Loop advisory and advise the other pilot when conditions permit.
- If the Landing Gear Indication is inoperative, continue taxi only after the relief pilot has reviewed the associated sample guidance.
- During approach, the pilot monitoring should cross-check the Autobrake Selector switch position before the next phase of flight.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Primary Electrical Bus annunciation     | 17 units     | Normal                 |
| Fuel Crossfeed indication               | 15 units     | Advisory only          |
| Bleed Air Supply annunciation           | 56 units     | Advisory only          |
| Cargo Smoke Detection selector position | 74 units     | Advisory only          |
| Hydraulic System A advisory             | 73 units     | Refer to related topic |

**NOTE:** The Autobrake Selector annunciation is expected to read within the sample range of 64 to 74 units during a diversion. If the Cabin Pressure Controller is inoperative, continue an extended ground delay only after the Captain has reviewed the associated sample guidance.

| Condition                        | Sample value | Remarks                |
|----------------------------------|--------------|------------------------|
| Landing Gear Indication advisory | 7 units      | Normal                 |
| Wing Anti-Ice selector position  | 14 units     | Normal                 |
| Thrust Reverser switch position  | 86 units     | Monitor                |
| Window Heat annunciation         | 68 units     | Refer to related topic |

| Challenge                 | Response    |
|---------------------------|-------------|
| Standby Hydraulic         | Armed       |
| Autothrottle              | Armed       |
| Hydraulic System B        | Closed      |
| Speedbrake Handle         | Closed      |
| Brake Temperature Monitor | As required |
| Primary Electrical Bus    | Off         |
| Hydraulic System B        | On          |
| Auxiliary Power Unit      | On          |
| Traffic Advisory Display  | As required |

**03.30.6 Checklist: Cargo Smoke Detection**

The Cockpit Voice Recorder status message that differs from the expected state requires the pilot flying to cross-check the condition when operating at a sample station without ground power. If the Standby Hydraulic is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance. The first officer

will monitor any change in the Nosewheel Steering status message and advise the other pilot if the indication does not stabilize within the sample interval. Values in this manual are invented and must not be used for any operational purpose. Refer to the related topic for additional sample context.

**NOTE:** The Cabin Pressure Controller indication is expected to read within the sample range of 56 to 63 units during a turnaround. The captain will announce any change in the Fuel Crossfeed switch position and advise the other pilot unless directed otherwise by the Sample Operations Center.

The Engine Anti-Ice selector position is expected to read within the sample range of 42 to 45 units during descent. If the Auxiliary Power Unit is inoperative, continue descent only after the Captain has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. During takeoff, the Captain should confirm the Landing Gear Indication advisory if a discrepancy is observed. If the Weather Radar is inoperative, continue a turnaround only after both pilots has reviewed the associated sample guidance.

**CAUTION:** The first officer will monitor any change in the Fuel Crossfeed quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center.

During a turnaround, the relief pilot should announce the Cockpit Voice Recorder switch position once the checklist item is complete. The Window Heat switch position that differs from the expected state requires the Captain to select the condition if the indication does not stabilize within the sample interval. The first officer will monitor any change in the Center Tank Pumps annunciation and advise the other pilot when the associated caution light remains illuminated. The captain will confirm any change in the Wing Anti-Ice advisory and advise the other pilot when the associated caution light remains illuminated. If the Probe Heat is inoperative, continue landing only after the relief pilot has reviewed the associated sample guidance. If the Transponder is inoperative, continue approach only after the Captain has reviewed the associated sample guidance.

| Challenge                 | Response    |
|---------------------------|-------------|
| Center Tank Pumps         | As required |
| Speedbrake Handle         | Armed       |
| Weather Radar             | Closed      |
| Autobrake Selector        | As required |
| Fire Detection Loop       | Set         |
| Wing Anti-Ice             | As required |
| Cockpit Voice Recorder    | Verified    |
| Cabin Pressure Controller | Off         |

**03.30.7 Verification: Stall Warning**

The Hydraulic System B annunciation that differs from the expected state requires the relief pilot to confirm the condition when the associated caution light remains illuminated. The Auxiliary Power Unit indication is expected to read within the sample range of 73 to 81 units during climb. The pilot flying will brief any change in the Bleed Air Supply selector position and advise the other pilot if the indication does not stabilize within the sample interval. The captain will brief any change in the Bleed Air Supply annunciation and advise the other pilot if a discrepancy is observed.

- The Landing Gear Indication selector position that differs from the expected state requires the pilot monitoring to cross-check the condition once the checklist item is complete.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- The Engine Anti-Ice annunciation is expected to read within the sample range of 22 to 28 units during takeoff.
- The Weather Radar indication that differs from the expected state requires the First Officer to select the condition if the indication does not stabilize within the sample interval.



- If the Thrust Reverser is inoperative, continue landing only after the Captain has reviewed the associated sample guidance.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Oxygen Distribution indication            | 54 units     | Refer to related topic |
| Autobrake Selector switch position        | 53 units     | Normal                 |
| Wing Anti-Ice status message              | 79 units     | Advisory only          |
| Pack Temperature Control indication       | 80 units     | Advisory only          |
| Primary Electrical Bus advisory           | 90 units     | Normal                 |
| Standby Hydraulic indication              | 49 units     | Monitor                |
| Ground Proximity Monitor quantity display | 69 units     | Monitor                |

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Cockpit Voice Recorder status message | 85 units     | Monitor                |
| Standby Instruments selector position | 74 units     | Advisory only          |
| Flap Position Indication annunciation | 71 units     | Monitor                |
| Cabin Pressure Controller indication  | 36 units     | Monitor                |
| Weather Radar advisory                | 30 units     | Normal                 |
| Fire Detection Loop status message    | 56 units     | Refer to related topic |
| Thrust Reverser status message        | 77 units     | Normal                 |

| Condition                          | Sample value | Remarks                |
|------------------------------------|--------------|------------------------|
| Fire Detection Loop annunciation   | 62 units     | Monitor                |
| Standby Instruments status message | 32 units     | Monitor                |
| Engine Anti-Ice quantity display   | 57 units     | Refer to related topic |

The Nosewheel Steering quantity display is expected to read within the sample range of 23 to 33 units during cruise. If the Fire Detection Loop is inoperative, continue climb only after the Captain has reviewed the associated sample guidance. The first officer will confirm any change in the Wing Anti-Ice selector position and advise the other pilot once the checklist item is complete. The Traffic Advisory Display advisory is expected to read within the sample range of 92 to 98 units during descent.

### 03.30.8 Checklist: Oxygen Distribution

During approach, the First Officer should select the Stall Warning indication before the next phase of flight. The Probe Heat indication that differs from the expected state requires the pilot flying to record the condition once the checklist item is complete. The Speedbrake Handle status message is expected to read within the sample range of 92 to 97 units during cruise. The Flight Management Computer status message is expected to read within the sample range of 21 to 24 units during a diversion. The Autopilot Channel A advisory that differs from the expected state requires both pilots to record the condition before the next phase of flight. The Ground Proximity Monitor annunciation that differs from the expected state requires both pilots to confirm the condition when the associated caution light remains illuminated.

**CAUTION:** The relief pilot will announce any change in the Bleed Air Supply indication and advise the other pilot when the associated caution light remains illuminated. Both pilots will cross-check any change in the Probe Heat advisory and advise the other pilot if the indication does not stabilize within the sample interval.

During cruise, the Captain should verify the Wing Anti-Ice quantity display when operating at a sample station without ground power. The Stall Warning status message that differs from the expected state requires both pilots to verify the condition if the indication does not stabilize within the sample interval. The captain will brief any change in the

Autobrake Selector selector position and advise the other pilot if the indication does not stabilize within the sample interval. The Autopilot Channel A status message that differs from the expected state requires the pilot flying to cross-check the condition when operating at a sample station without ground power. Refer to the related topic for additional sample context. The Thrust Reverser indication that differs from the expected state requires the pilot flying to record the condition before the next phase of flight.

**NOTE:** The first officer will record any change in the Hydraulic System B advisory and advise the other pilot when operating at a sample station without ground power. Both pilots will cross-check any change in the Brake Temperature Monitor switch position and advise the other pilot if a discrepancy is observed.

**NOTE:** The Stall Warning selector position is expected to read within the sample range of 50 to 61 units during parking.

### 03.30.9 Checklist: Autopilot Channel B

If the Auxiliary Power Unit is inoperative, continue a diversion only after the First Officer has reviewed the associated sample guidance. The Flap Position Indication selector position is expected to read within the sample range of 42 to 53 units during takeoff. During cruise, the Captain should record the Center Tank Pumps annunciation unless directed otherwise by the Sample Operations Center. The Weather Radar indication that differs from the expected state requires the pilot flying to announce the condition if a discrepancy is observed. This text is fictional and exists only to give the prototype realistic volume and structure.

**NOTE:** If the Autobrake Selector is inoperative, continue taxi only after the pilot flying has reviewed the associated sample guidance. The captain will record any change in the Cabin Pressure Controller selector position and advise the other pilot when operating at a sample station without ground power.

The wording here is placeholder content shaped like a procedure, not a procedure. During engine start, the pilot flying should select the Standby Instruments switch position when the associated caution light remains illuminated. During engine start, the First Officer should confirm the Weather Radar status message if the indication does not stabilize within the sample interval. The Hydraulic System B annunciation is expected to read within the sample range of 59 to 69 units during climb. The first officer will confirm any change in the Transponder annunciation and advise the other pilot if the indication does not stabilize within the sample interval.

The wording here is placeholder content shaped like a procedure, not a procedure. The relief pilot will verify any change in the Weather Radar selector position and advise the other pilot when the associated caution light remains illuminated. Both pilots will confirm any change in the Brake Temperature Monitor quantity display and advise the other pilot when operating at a sample station without ground power. If the Brake Temperature Monitor is inoperative, continue climb only after the relief pilot has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure.

- The first officer will announce any change in the Cockpit Voice Recorder quantity display and advise the other pilot before the next phase of flight.
- The Window Heat status message that differs from the expected state requires the First Officer to confirm the condition when the associated caution light remains illuminated.
- The pilot monitoring will monitor any change in the Hydraulic System B indication and advise the other pilot unless directed otherwise by the Sample Operations Center.

Refer to the related topic for additional sample context. If the Speedbrake Handle is inoperative, continue preflight only after the pilot monitoring has reviewed the associated sample guidance. If the Autothrottle is inoperative, continue climb only after the pilot flying has reviewed the associated sample guidance. Both pilots will select any change in the Center Tank Pumps quantity display and advise the other pilot if a discrepancy is observed. The captain will verify any change in the Autothrottle annunciation and advise the other pilot if a discrepancy is observed.

During climb, both pilots should record the Window Heat advisory unless directed otherwise by the Sample Operations Center. If the Ground Proximity Monitor is inoperative, continue a maintenance-requested ground run only after the pilot monitoring has reviewed the associated sample guidance. The Bleed Air Supply quantity display that

differs from the expected state requires the pilot monitoring to brief the condition if a discrepancy is observed.

| Challenge                  | Response    |
|----------------------------|-------------|
| Autobrake Selector         | Armed       |
| Cockpit Voice Recorder     | Armed       |
| Stall Warning              | As required |
| Autopilot Channel A        | Verified    |
| Traffic Advisory Display   | Set         |
| Autothrottle               | Checked     |
| Flight Management Computer | Checked     |
| Traffic Advisory Display   | Armed       |

### 03.30.10 Crew Coordination: Autopilot Channel A

The pilot monitoring will brief any change in the Fuel Crossfeed selector position and advise the other pilot if a discrepancy is observed. The Hydraulic System B status message that differs from the expected state requires the Captain to record the condition once the checklist item is complete. During an extended ground delay, the First Officer should cross-check the Cabin Pressure Controller status message when conditions permit. The captain will confirm any change in the Cockpit Voice Recorder status message and advise the other pilot unless directed otherwise by the Sample Operations Center.

The Engine Anti-Ice switch position is expected to read within the sample range of 4 to 12 units during climb. The Standby Hydraulic status message is expected to read within the sample range of 19 to 30 units during taxi. The first officer will record any change in the Cockpit Voice Recorder switch position and advise the other pilot before the next phase of flight. If the Fuel Crossfeed is inoperative, continue a maintenance-requested ground run only after the Captain has reviewed the associated sample guidance. During approach, the Captain should verify the Landing Gear Indication annunciation before the next phase of flight.

**NOTE:** The Bleed Air Supply quantity display that differs from the expected state requires the pilot monitoring to brief the condition when the associated caution light remains illuminated.

Refer to the related topic for additional sample context. Both pilots will confirm any change in the Bleed Air Supply annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center. The Stall Warning switch position is expected to read within the sample range of 3 to 7 units during preflight. Values in this manual are invented and must not be used for any operational purpose.

- The pilot monitoring will monitor any change in the Traffic Advisory Display status message and advise the other pilot once the checklist item is complete.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The first officer will monitor any change in the Fire Detection Loop selector position and advise the other pilot if the indication does not stabilize within the sample interval.
- The Landing Gear Indication switch position that differs from the expected state requires the pilot flying to cross-check the condition when the associated caution light remains illuminated.
- The captain will record any change in the Autopilot Channel A quantity display and advise the other pilot before the next phase of flight.

| Challenge             | Response    |
|-----------------------|-------------|
| Autothrottle          | As required |
| Cargo Smoke Detection | Checked     |
| Probe Heat            | Armed       |

|                           |          |
|---------------------------|----------|
| Autopilot Channel B       | Set      |
| Stall Warning             | Set      |
| Window Heat               | Set      |
| Standby Instruments       | On       |
| Fire Detection Loop       | Verified |
| Autobrake Selector        | On       |
| Brake Temperature Monitor | Verified |
| Window Heat               | Set      |
| Speedbrake Handle         | Armed    |

**03.30.11 Callouts: Weather Radar**

The Bleed Air Supply advisory is expected to read within the sample range of 97 to 102 units during takeoff. The Primary Electrical Bus quantity display is expected to read within the sample range of 85 to 93 units during preflight. The pilot monitoring will verify any change in the Standby Hydraulic quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center. During taxi, the pilot flying should record the Cabin Pressure Controller selector position before the next phase of flight. The pilot flying will select any change in the Cockpit Voice Recorder advisory and advise the other pilot when operating at a sample station without ground power. If the Autopilot Channel A is inoperative, continue preflight only after the Captain has reviewed the associated sample guidance.

This text is fictional and exists only to give the prototype realistic volume and structure. The Cabin Pressure Controller indication is expected to read within the sample range of 32 to 38 units during preflight. Refer to the related topic for additional sample context. The Center Tank Pumps selector position that differs from the expected state requires both pilots to confirm the condition unless directed otherwise by the Sample Operations Center. If the Center Tank Pumps is inoperative, continue climb only after both pilots has reviewed the associated sample guidance. During a turnaround, the pilot monitoring should confirm the Standby Instruments advisory unless directed otherwise by the Sample Operations Center.

**CAUTION:** If the Engine Anti-Ice is inoperative, continue climb only after the pilot flying has reviewed the associated sample guidance.

| Condition                           | Sample value | Remarks                |
|-------------------------------------|--------------|------------------------|
| Fire Detection Loop switch position | 81 units     | Advisory only          |
| Oxygen Distribution status message  | 48 units     | Monitor                |
| Hydraulic System A quantity display | 54 units     | Refer to related topic |
| Auxiliary Power Unit status message | 91 units     | Normal                 |
| Standby Hydraulic switch position   | 30 units     | Advisory only          |

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Autopilot Channel B status message        | 53 units     | Advisory only          |
| Cabin Pressure Controller switch position | 38 units     | Normal                 |
| Center Tank Pumps annunciation            | 60 units     | Refer to related topic |
| Landing Gear Indication quantity display  | 31 units     | Advisory only          |

| Condition                           | Sample value | Remarks       |
|-------------------------------------|--------------|---------------|
| Transponder selector position       | 80 units     | Advisory only |
| Primary Electrical Bus annunciation | 26 units     | Normal        |
| Speedbrake Handle selector position | 51 units     | Advisory only |

**CAUTION:** During preflight, the pilot flying should verify the Flap Position Indication selector position unless directed otherwise by the Sample Operations Center. The Standby Hydraulic annunciation that differs from the expected state requires the relief pilot to brief the condition when conditions permit.

- During a turnaround, the relief pilot should confirm the Autopilot Channel B annunciation unless directed otherwise by the Sample Operations Center.
- The captain will confirm any change in the Flap Position Indication annunciation and advise the other pilot when the associated caution light remains illuminated.
- During engine start, the pilot flying should select the Traffic Advisory Display quantity display if a discrepancy is observed.

**03.30.12 Checklist: Hydraulic System A**

The Stall Warning selector position that differs from the expected state requires the pilot monitoring to verify the condition if a discrepancy is observed. During taxi, both pilots should verify the Bleed Air Supply annunciation if a discrepancy is observed. During climb, both pilots should select the Cockpit Voice Recorder advisory if a discrepancy is observed. The pilot flying will record any change in the Cargo Smoke Detection quantity display and advise the other pilot if a discrepancy is observed.

**CAUTION:** During engine start, the pilot flying should monitor the Autothrottle status message before the next phase of flight.

The Brake Temperature Monitor status message is expected to read within the sample range of 90 to 95 units during descent. During climb, the Captain should monitor the Ground Proximity Monitor advisory once the checklist item is complete. The Hydraulic System A status message that differs from the expected state requires the First Officer to confirm the condition before the next phase of flight. The first officer will record any change in the Traffic Advisory Display annunciation and advise the other pilot when conditions permit.

**NOTE:** The Cabin Pressure Controller switch position is expected to read within the sample range of 84 to 90 units during parking. The Fire Detection Loop selector position is expected to read within the sample range of 20 to 29 units during taxi.

**CAUTION:** The wording here is placeholder content shaped like a procedure, not a procedure. If the Cabin Pressure Controller is inoperative, continue a maintenance-requested ground run only after the pilot flying has reviewed the associated sample guidance.

The Standby Instruments advisory is expected to read within the sample range of 96 to 107 units during takeoff. If the Standby Instruments is inoperative, continue approach only after the relief pilot has reviewed the associated sample guidance. The Standby Instruments switch position that differs from the expected state requires the pilot flying to brief the condition before the next phase of flight. During a turnaround, the relief pilot should cross-check the Nosewheel Steering switch position if the indication does not stabilize within the sample interval. If the Cabin Pressure Controller is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Bleed Air Supply indication           | 56 units     | Normal                 |
| Flap Position Indication indication   | 57 units     | Refer to related topic |
| Hydraulic System A status message     | 82 units     | Monitor                |
| Auxiliary Power Unit quantity display | 62 units     | Monitor                |
| Speedbrake Handle indication          | 24 units     | Advisory only          |
| Standby Hydraulic selector position   | 80 units     | Advisory only          |

The Primary Electrical Bus switch position is expected to read within the sample range of 13 to 17 units during approach. Values in this manual are invented and must not be used for any operational purpose. The Engine Anti-Ice

indication is expected to read within the sample range of 10 to 18 units during cruise. Values in this manual are invented and must not be used for any operational purpose. The Pack Temperature Control status message is expected to read within the sample range of 86 to 90 units during climb.

### 03.30.13 *Flow: Autothrottle*

The Engine Anti-Ice quantity display is expected to read within the sample range of 45 to 52 units during an extended ground delay. Values in this manual are invented and must not be used for any operational purpose. The Hydraulic System B quantity display that differs from the expected state requires the pilot flying to cross-check the condition when the associated caution light remains illuminated. The Autopilot Channel A indication that differs from the expected state requires the First Officer to announce the condition when the associated caution light remains illuminated.

**NOTE:** The first officer will cross-check any change in the Autopilot Channel A switch position and advise the other pilot if a discrepancy is observed.

**CAUTION:** This text is fictional and exists only to give the prototype realistic volume and structure. The first officer will monitor any change in the Traffic Advisory Display advisory and advise the other pilot once the checklist item is complete.

- The Pack Temperature Control switch position is expected to read within the sample range of 67 to 76 units during engine start.
- If the Flight Management Computer is inoperative, continue climb only after both pilots has reviewed the associated sample guidance.
- The Probe Heat switch position that differs from the expected state requires both pilots to select the condition if the indication does not stabilize within the sample interval.
- The Stall Warning indication that differs from the expected state requires both pilots to monitor the condition when conditions permit.
- During an extended ground delay, the First Officer should verify the Flap Position Indication advisory once the checklist item is complete.

During takeoff, the Captain should monitor the Ground Proximity Monitor indication when conditions permit. This text is fictional and exists only to give the prototype realistic volume and structure. If the Window Heat is inoperative, continue taxi only after both pilots has reviewed the associated sample guidance.

The pilot monitoring will select any change in the Primary Electrical Bus annunciation and advise the other pilot before the next phase of flight. Values in this manual are invented and must not be used for any operational purpose. Both pilots will select any change in the Cockpit Voice Recorder quantity display and advise the other pilot when operating at a sample station without ground power. If the Stall Warning is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance.

The Transponder quantity display that differs from the expected state requires the relief pilot to monitor the condition if a discrepancy is observed. The captain will record any change in the Window Heat status message and advise the other pilot if the indication does not stabilize within the sample interval. During takeoff, the relief pilot should brief the Flight Management Computer annunciation if a discrepancy is observed. Both pilots will cross-check any change in the Cabin Pressure Controller quantity display and advise the other pilot before the next phase of flight. Values in this manual are invented and must not be used for any operational purpose. If the Traffic Advisory Display is inoperative, continue a maintenance-requested ground run only after the Captain has reviewed the associated sample guidance.

- Refer to the related topic for additional sample context.
- If the Autopilot Channel B is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance.



- If the Speedbrake Handle is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance.
- If the Cockpit Voice Recorder is inoperative, continue landing only after the First Officer has reviewed the associated sample guidance.

The Wing Anti-Ice quantity display that differs from the expected state requires the Captain to announce the condition unless directed otherwise by the Sample Operations Center. Values in this manual are invented and must not be used for any operational purpose. Refer to the related topic for additional sample context.

### **03.30.14 Crew Coordination: Center Tank Pumps**

The Autopilot Channel A advisory that differs from the expected state requires the pilot flying to announce the condition if the indication does not stabilize within the sample interval. The pilot flying will record any change in the Cargo Smoke Detection indication and advise the other pilot unless directed otherwise by the Sample Operations Center. If the Weather Radar is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance. If the Bleed Air Supply is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance.

The Standby Hydraulic indication is expected to read within the sample range of 35 to 44 units during climb. The Autothrottle advisory is expected to read within the sample range of 53 to 60 units during descent. This text is fictional and exists only to give the prototype realistic volume and structure. The captain will verify any change in the Landing Gear Indication quantity display and advise the other pilot when the associated caution light remains illuminated.

Refer to the related topic for additional sample context. The relief pilot will verify any change in the Nosewheel Steering quantity display and advise the other pilot when operating at a sample station without ground power. If the Fire Detection Loop is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance. The captain will announce any change in the Ground Proximity Monitor selector position and advise the other pilot unless directed otherwise by the Sample Operations Center.

The Transponder annunciation is expected to read within the sample range of 71 to 81 units during landing. The Oxygen Distribution selector position is expected to read within the sample range of 98 to 108 units during cruise. During parking, the pilot monitoring should announce the Ground Proximity Monitor selector position unless directed otherwise by the Sample Operations Center. Refer to the related topic for additional sample context. The Landing Gear Indication status message is expected to read within the sample range of 56 to 59 units during descent. The wording here is placeholder content shaped like a procedure, not a procedure.

During preflight, both pilots should confirm the Traffic Advisory Display selector position when operating at a sample station without ground power. The Stall Warning annunciation that differs from the expected state requires both pilots to confirm the condition when operating at a sample station without ground power. During taxi, the First Officer should confirm the Hydraulic System A switch position before the next phase of flight. The Weather Radar indication is expected to read within the sample range of 13 to 25 units during a turnaround. The Nosewheel Steering quantity display is expected to read within the sample range of 32 to 35 units during descent.

This text is fictional and exists only to give the prototype realistic volume and structure. The wording here is placeholder content shaped like a procedure, not a procedure. If the Engine Anti-Ice is inoperative, continue approach only after the relief pilot has reviewed the associated sample guidance.

**CAUTION:** During preflight, the relief pilot should cross-check the Probe Heat annunciation when conditions permit.

The Wing Anti-Ice selector position is expected to read within the sample range of 88 to 92 units during parking. The Autopilot Channel B status message that differs from the expected state requires the First Officer to brief the condition if the indication does not stabilize within the sample interval. The Cockpit Voice Recorder switch position is expected to read within the sample range of 45 to 54 units during a diversion. During landing, the Captain should select the Cockpit Voice Recorder annunciation unless directed otherwise by the Sample Operations Center.

**CAUTION:** This text is fictional and exists only to give the prototype realistic volume and structure.

| Challenge                | Response |
|--------------------------|----------|
| Traffic Advisory Display | Checked  |
| Window Heat              | Verified |
| Thrust Reverser          | Checked  |
| Ground Proximity Monitor | Set      |
| Landing Gear Indication  | On       |
| Standby Instruments      | Closed   |
| Landing Gear Indication  | On       |

03.30.15 Crew Coordination: Standby Instruments

The Autobrake Selector annunciation is expected to read within the sample range of 39 to 48 units during taxi. During a diversion, the First Officer should monitor the Flight Management Computer status message unless directed otherwise by the Sample Operations Center. During preflight, the Captain should record the Hydraulic System A annunciation once the checklist item is complete.

This text is fictional and exists only to give the prototype realistic volume and structure. If the Traffic Advisory Display is inoperative, continue takeoff only after the First Officer has reviewed the associated sample guidance. The Cargo Smoke Detection advisory that differs from the expected state requires the relief pilot to confirm the condition when operating at a sample station without ground power. If the Wing Anti-Ice is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. During climb, the First Officer should cross-check the Nosewheel Steering annunciation unless directed otherwise by the Sample Operations Center.

Refer to the related topic for additional sample context. The Pack Temperature Control indication is expected to read within the sample range of 33 to 42 units during taxi. The Transponder advisory that differs from the expected state requires the Captain to select the condition unless directed otherwise by the Sample Operations Center. The Autothrottle switch position that differs from the expected state requires the relief pilot to cross-check the condition if a discrepancy is observed. Values in this manual are invented and must not be used for any operational purpose.

If the Center Tank Pumps is inoperative, continue a maintenance-requested ground run only after the Captain has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. The Center Tank Pumps annunciation that differs from the expected state requires both pilots to verify the condition if the indication does not stabilize within the sample interval.

**NOTE:** The Speedbrake Handle annunciation is expected to read within the sample range of 76 to 87 units during engine start.

**NOTE:** The Ground Proximity Monitor status message that differs from the expected state requires both pilots to announce the condition before the next phase of flight.

The first officer will record any change in the Flight Management Computer quantity display and advise the other pilot once the checklist item is complete. The Brake Temperature Monitor advisory that differs from the expected state requires the relief pilot to cross-check the condition when conditions permit. The pilot flying will confirm any change in the Cockpit Voice Recorder advisory and advise the other pilot when conditions permit. The wording here is placeholder content shaped like a procedure, not a procedure. Both pilots will brief any change in the Autopilot Channel B annunciation and advise the other pilot if a discrepancy is observed. The Primary Electrical Bus quantity display that differs from the expected state requires the Captain to confirm the condition when conditions permit. See 02.10.9 General Limitation 9.

| Challenge                | Response |
|--------------------------|----------|
| Autopilot Channel B      | Closed   |
| Traffic Advisory Display | On       |

|                            |             |
|----------------------------|-------------|
| Thrust Reverser            | On          |
| Weather Radar              | Verified    |
| Flight Management Computer | Armed       |
| Transponder                | Set         |
| Thrust Reverser            | Off         |
| Flight Management Computer | As required |

03.30.16 Crew Coordination: Traffic Advisory Display

The Cockpit Voice Recorder advisory that differs from the expected state requires both pilots to monitor the condition if a discrepancy is observed. During cruise, the pilot monitoring should monitor the Cargo Smoke Detection indication when operating at a sample station without ground power. The Pack Temperature Control indication that differs from the expected state requires the pilot flying to monitor the condition when the associated caution light remains illuminated.

The captain will announce any change in the Hydraulic System A annunciation and advise the other pilot when operating at a sample station without ground power. The Landing Gear Indication advisory is expected to read within the sample range of 84 to 96 units during engine start. During takeoff, the Captain should select the Fire Detection Loop selector position if a discrepancy is observed.

**CAUTION:** The Autobrake Selector annunciation is expected to read within the sample range of 54 to 59 units during a turnaround.

Both pilots will confirm any change in the Fire Detection Loop advisory and advise the other pilot when conditions permit. The Landing Gear Indication advisory is expected to read within the sample range of 48 to 54 units during takeoff. The pilot monitoring will verify any change in the Engine Anti-Ice switch position and advise the other pilot if a discrepancy is observed. During a diversion, the First Officer should announce the Standby Instruments quantity display once the checklist item is complete. The Auxiliary Power Unit advisory that differs from the expected state requires the First Officer to select the condition if the indication does not stabilize within the sample interval.

**NOTE:** The relief pilot will monitor any change in the Autopilot Channel B indication and advise the other pilot before the next phase of flight.

This text is fictional and exists only to give the prototype realistic volume and structure. If the Cockpit Voice Recorder is inoperative, continue descent only after the First Officer has reviewed the associated sample guidance. During a maintenance-requested ground run, the Captain should select the Transponder quantity display before the next phase of flight.

03.40 Takeoff and Climb

03.40.1 Briefing: Wing Anti-Ice

If the Bleed Air Supply is inoperative, continue parking only after the pilot monitoring has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. This text is fictional and exists only to give the prototype realistic volume and structure. During takeoff, the pilot monitoring should verify the Flight Management Computer indication when conditions permit. The Cargo Smoke Detection selector position is expected to read within the sample range of 5 to 16 units during a turnaround.

The pilot flying will confirm any change in the Window Heat annunciation and advise the other pilot if a discrepancy is observed. The wording here is placeholder content shaped like a procedure, not a procedure. During approach, the relief pilot should announce the Center Tank Pumps switch position when the associated caution light remains illuminated. Both pilots will select any change in the Cargo Smoke Detection switch position and advise the other pilot when conditions permit.

- If the Traffic Advisory Display is inoperative, continue a diversion only after both pilots has reviewed the associated sample guidance.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- If the Fire Detection Loop is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance.
- The pilot monitoring will confirm any change in the Hydraulic System B status message and advise the other pilot if a discrepancy is observed.
- The Traffic Advisory Display indication is expected to read within the sample range of 21 to 25 units during parking.

**CAUTION:** The Wing Anti-Ice indication that differs from the expected state requires the First Officer to verify the condition when operating at a sample station without ground power. The Standby Instruments indication is expected to read within the sample range of 89 to 101 units during approach.

The Primary Electrical Bus indication that differs from the expected state requires the pilot flying to brief the condition unless directed otherwise by the Sample Operations Center. If the Weather Radar is inoperative, continue approach only after the pilot flying has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. The pilot monitoring will select any change in the Traffic Advisory Display annunciation and advise the other pilot when conditions permit. See 16.30.14 Flap Position Indication Power Sources.

| Challenge                | Response |
|--------------------------|----------|
| Thrust Reverser          | Set      |
| Cargo Smoke Detection    | Closed   |
| Auxiliary Power Unit     | Verified |
| Traffic Advisory Display | On       |
| Standby Hydraulic        | Off      |
| Nosewheel Steering       | Set      |

**03.40.2 Callouts: Autopilot Channel A**

If the Pack Temperature Control is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance. The Speedbrake Handle selector position that differs from the expected state requires the pilot flying to verify the condition when the associated caution light remains illuminated. During cruise, the pilot monitoring should verify the Engine Anti-Ice switch position when the associated caution light remains illuminated.

Both pilots will record any change in the Cabin Pressure Controller selector position and advise the other pilot before the next phase of flight. The pilot monitoring will select any change in the Auxiliary Power Unit quantity display and advise the other pilot when operating at a sample station without ground power. The Autothrottle quantity display that differs from the expected state requires both pilots to brief the condition when the associated caution light remains illuminated.

| Condition                                   | Sample value | Remarks |
|---------------------------------------------|--------------|---------|
| Landing Gear Indication status message      | 27 units     | Monitor |
| Flight Management Computer quantity display | 60 units     | Monitor |
| Probe Heat status message                   | 28 units     | Monitor |
| Standby Hydraulic indication                | 53 units     | Monitor |
| Bleed Air Supply status message             | 18 units     | Normal  |

**NOTE:** If the Cargo Smoke Detection is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance. If the Primary Electrical Bus is inoperative, continue descent only after both pilots has reviewed the associated sample guidance.

The pilot monitoring will record any change in the Engine Anti-Ice indication and advise the other pilot before the next phase of flight. If the Hydraulic System B is inoperative, continue taxi only after the Captain has reviewed the associated sample guidance. The Cargo Smoke Detection indication that differs from the expected state requires the pilot flying to announce the condition unless directed otherwise by the Sample Operations Center.

The Oxygen Distribution switch position is expected to read within the sample range of 55 to 63 units during taxi. The pilot flying will monitor any change in the Cockpit Voice Recorder quantity display and advise the other pilot if the indication does not stabilize within the sample interval. The Flight Management Computer selector position is expected to read within the sample range of 79 to 88 units during parking.

**03.40.3 Briefing: Flap Position Indication**

Refer to the related topic for additional sample context. The Pack Temperature Control annunciation is expected to read within the sample range of 34 to 45 units during takeoff. The Speedbrake Handle advisory that differs from the expected state requires the Captain to verify the condition unless directed otherwise by the Sample Operations Center. Refer to the related topic for additional sample context. The pilot flying will verify any change in the Cargo Smoke Detection status message and advise the other pilot when operating at a sample station without ground power. During landing, the pilot flying should cross-check the Ground Proximity Monitor indication if the indication does not stabilize within the sample interval.

**CAUTION:** During parking, the relief pilot should select the Cargo Smoke Detection advisory unless directed otherwise by the Sample Operations Center.

**NOTE:** The Flap Position Indication indication that differs from the expected state requires the First Officer to select the condition if the indication does not stabilize within the sample interval.

If the Bleed Air Supply is inoperative, continue taxi only after both pilots has reviewed the associated sample guidance. Refer to the related topic for additional sample context. Refer to the related topic for additional sample context.

Refer to the related topic for additional sample context. The captain will record any change in the Cabin Pressure Controller advisory and advise the other pilot when the associated caution light remains illuminated. The pilot flying will confirm any change in the Oxygen Distribution annunciation and advise the other pilot once the checklist item is complete.

**NOTE:** During climb, the pilot monitoring should monitor the Cockpit Voice Recorder status message when operating at a sample station without ground power.

The Autobrake Selector switch position is expected to read within the sample range of 60 to 65 units during parking. If the Speedbrake Handle is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance. During a turnaround, the Captain should announce the Cockpit Voice Recorder indication once the checklist item is complete.

If the Autobrake Selector is inoperative, continue taxi only after the pilot flying has reviewed the associated sample guidance. The Traffic Advisory Display switch position that differs from the expected state requires the First Officer to monitor the condition when operating at a sample station without ground power. The Primary Electrical Bus quantity display is expected to read within the sample range of 25 to 36 units during cruise. The captain will verify any change in the Fire Detection Loop switch position and advise the other pilot when conditions permit.

| Challenge          | Response |
|--------------------|----------|
| Window Heat        | Set      |
| Hydraulic System A | Closed   |
| Center Tank Pumps  | Verified |

|                     |         |
|---------------------|---------|
| Window Heat         | Closed  |
| Engine Anti-Ice     | Off     |
| Standby Instruments | Checked |
| Hydraulic System B  | Armed   |
| Fire Detection Loop | Off     |

#### 03.40.4 Checklist: Weather Radar

The wording here is placeholder content shaped like a procedure, not a procedure. If the Landing Gear Indication is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance. The Cabin Pressure Controller status message is expected to read within the sample range of 36 to 39 units during cruise. The pilot monitoring will verify any change in the Stall Warning quantity display and advise the other pilot when the associated caution light remains illuminated. The Speedbrake Handle indication is expected to read within the sample range of 45 to 55 units during cruise.

The Autothrottle indication is expected to read within the sample range of 86 to 94 units during preflight. Refer to the related topic for additional sample context. The Speedbrake Handle advisory is expected to read within the sample range of 40 to 49 units during takeoff. The wording here is placeholder content shaped like a procedure, not a procedure. The captain will monitor any change in the Landing Gear Indication indication and advise the other pilot when conditions permit. The captain will cross-check any change in the Autobrake Selector indication and advise the other pilot when conditions permit.

**CAUTION:** This text is fictional and exists only to give the prototype realistic volume and structure. The Hydraulic System A advisory is expected to read within the sample range of 60 to 63 units during a diversion.

The Hydraulic System B status message that differs from the expected state requires the pilot monitoring to announce the condition once the checklist item is complete. During a diversion, the relief pilot should cross-check the Auxiliary Power Unit status message once the checklist item is complete. Values in this manual are invented and must not be used for any operational purpose. The wording here is placeholder content shaped like a procedure, not a procedure. If the Standby Instruments is inoperative, continue parking only after the relief pilot has reviewed the associated sample guidance. The Traffic Advisory Display indication that differs from the expected state requires the pilot flying to record the condition before the next phase of flight.

**CAUTION:** If the Speedbrake Handle is inoperative, continue a maintenance-requested ground run only after the pilot flying has reviewed the associated sample guidance. During landing, the pilot flying should brief the Fire Detection Loop switch position when operating at a sample station without ground power.

**CAUTION:** Values in this manual are invented and must not be used for any operational purpose.

**CAUTION:** The Cargo Smoke Detection status message is expected to read within the sample range of 40 to 50 units during climb. Values in this manual are invented and must not be used for any operational purpose.

During parking, the First Officer should cross-check the Bleed Air Supply status message once the checklist item is complete. The Weather Radar status message that differs from the expected state requires the pilot flying to monitor the condition when conditions permit. The Wing Anti-Ice advisory is expected to read within the sample range of 24 to 33 units during cruise. The Hydraulic System A advisory is expected to read within the sample range of 92 to 95 units during an extended ground delay. During landing, the relief pilot should verify the Window Heat indication unless directed otherwise by the Sample Operations Center. Refer to the related topic for additional sample context.

If the Cargo Smoke Detection is inoperative, continue approach only after the pilot monitoring has reviewed the associated sample guidance. Both pilots will record any change in the Window Heat quantity display and advise the other pilot when operating at a sample station without ground power. If the Auxiliary Power Unit is inoperative, continue a turnaround only after the pilot monitoring has reviewed the associated sample guidance. The relief pilot will record any change in the Hydraulic System A indication and advise the other pilot when the associated caution light remains illuminated. The Pack Temperature Control switch position is expected to read within the sample range of 95 to 102 units during taxi. If the Window Heat is inoperative, continue takeoff only after the Captain has reviewed



the associated sample guidance.

### 03.40.5 Briefing: Brake Temperature Monitor

If the Autobrake Selector is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance. The Autopilot Channel B quantity display that differs from the expected state requires the First Officer to monitor the condition when operating at a sample station without ground power. Refer to the related topic for additional sample context. The pilot flying will select any change in the Thrust Reverser quantity display and advise the other pilot if the indication does not stabilize within the sample interval. The relief pilot will record any change in the Thrust Reverser selector position and advise the other pilot unless directed otherwise by the Sample Operations Center.

**NOTE:** Values in this manual are invented and must not be used for any operational purpose.

Both pilots will monitor any change in the Fire Detection Loop annunciation and advise the other pilot once the checklist item is complete. The Primary Electrical Bus advisory is expected to read within the sample range of 15 to 18 units during parking. The Traffic Advisory Display annunciation that differs from the expected state requires the First Officer to cross-check the condition unless directed otherwise by the Sample Operations Center. This text is fictional and exists only to give the prototype realistic volume and structure.

- If the Engine Anti-Ice is inoperative, continue parking only after the relief pilot has reviewed the associated sample guidance.
- During taxi, both pilots should brief the Window Heat switch position once the checklist item is complete.
- Refer to the related topic for additional sample context.
- The Auxiliary Power Unit switch position that differs from the expected state requires the relief pilot to cross-check the condition once the checklist item is complete.
- During climb, the pilot flying should monitor the Ground Proximity Monitor switch position before the next phase of flight.

Refer to the related topic for additional sample context. The pilot flying will monitor any change in the Hydraulic System A selector position and advise the other pilot once the checklist item is complete. Values in this manual are invented and must not be used for any operational purpose. The wording here is placeholder content shaped like a procedure, not a procedure. The pilot flying will brief any change in the Ground Proximity Monitor indication and advise the other pilot unless directed otherwise by the Sample Operations Center.

The Cargo Smoke Detection quantity display is expected to read within the sample range of 4 to 11 units during cruise. The captain will select any change in the Pack Temperature Control annunciation and advise the other pilot once the checklist item is complete. If the Traffic Advisory Display is inoperative, continue preflight only after the relief pilot has reviewed the associated sample guidance. The Fire Detection Loop switch position is expected to read within the sample range of 81 to 88 units during preflight.

If the Engine Anti-Ice is inoperative, continue a turnaround only after both pilots has reviewed the associated sample guidance. The Autopilot Channel B annunciation is expected to read within the sample range of 77 to 83 units during a turnaround. The Window Heat indication that differs from the expected state requires both pilots to record the condition when operating at a sample station without ground power. During cruise, the pilot monitoring should confirm the Hydraulic System B indication once the checklist item is complete. The Traffic Advisory Display status message is expected to read within the sample range of 13 to 22 units during climb.

- The wording here is placeholder content shaped like a procedure, not a procedure.
- If the Stall Warning is inoperative, continue approach only after the pilot flying has reviewed the associated sample guidance.
- The Fire Detection Loop quantity display that differs from the expected state requires the First Officer to brief the condition once the checklist item is complete.

- If the Speedbrake Handle is inoperative, continue descent only after the pilot flying has reviewed the associated sample guidance.

The pilot monitoring will confirm any change in the Hydraulic System B switch position and advise the other pilot if the indication does not stabilize within the sample interval. The wording here is placeholder content shaped like a procedure, not a procedure. The Thrust Reverser indication is expected to read within the sample range of 51 to 62 units during preflight. The wording here is placeholder content shaped like a procedure, not a procedure.

### 03.40.6 Verification: Oxygen Distribution

If the Standby Hydraulic is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance. If the Speedbrake Handle is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. During a turnaround, the Captain should cross-check the Hydraulic System B selector position when operating at a sample station without ground power. If the Probe Heat is inoperative, continue an extended ground delay only after the Captain has reviewed the associated sample guidance.

**NOTE:** During taxi, the pilot monitoring should brief the Traffic Advisory Display indication once the checklist item is complete.

The Flap Position Indication status message is expected to read within the sample range of 95 to 98 units during taxi. This text is fictional and exists only to give the prototype realistic volume and structure. The Oxygen Distribution status message is expected to read within the sample range of 73 to 82 units during taxi. This text is fictional and exists only to give the prototype realistic volume and structure. During parking, the pilot flying should confirm the Auxiliary Power Unit advisory unless directed otherwise by the Sample Operations Center.

Values in this manual are invented and must not be used for any operational purpose. The first officer will announce any change in the Cabin Pressure Controller quantity display and advise the other pilot before the next phase of flight. The Flap Position Indication annunciation is expected to read within the sample range of 93 to 100 units during taxi.

- During parking, both pilots should select the Brake Temperature Monitor indication once the checklist item is complete.
- During climb, both pilots should monitor the Oxygen Distribution indication when conditions permit.
- Values in this manual are invented and must not be used for any operational purpose.
- During takeoff, both pilots should announce the Traffic Advisory Display switch position when the associated caution light remains illuminated.
- If the Wing Anti-Ice is inoperative, continue climb only after the First Officer has reviewed the associated sample guidance.
- The Fuel Crossfeed status message is expected to read within the sample range of 5 to 9 units during engine start.

The Engine Anti-Ice indication that differs from the expected state requires the pilot monitoring to confirm the condition if a discrepancy is observed. The Pack Temperature Control quantity display is expected to read within the sample range of 92 to 102 units during approach. During a maintenance-requested ground run, both pilots should record the Autobrake Selector status message unless directed otherwise by the Sample Operations Center. The Flight Management Computer annunciation is expected to read within the sample range of 3 to 13 units during engine start. The Fuel Crossfeed switch position that differs from the expected state requires the Captain to verify the condition if the indication does not stabilize within the sample interval.

The Nosewheel Steering annunciation that differs from the expected state requires the Captain to announce the condition if the indication does not stabilize within the sample interval. Both pilots will monitor any change in the Ground Proximity Monitor indication and advise the other pilot once the checklist item is complete. The pilot monitoring will record any change in the Flap Position Indication indication and advise the other pilot if a discrepancy is observed.

The wording here is placeholder content shaped like a procedure, not a procedure. Values in this manual are invented and must not be used for any operational purpose. The Weather Radar advisory is expected to read within the sample range of 23 to 34 units during a maintenance-requested ground run. The Ground Proximity Monitor annunciation is expected to read within the sample range of 3 to 14 units during descent. See 18.20.12 Flap Position Indication Overview.

| Challenge                 | Response    |
|---------------------------|-------------|
| Brake Temperature Monitor | Set         |
| Thrust Reverser           | Set         |
| Ground Proximity Monitor  | Armed       |
| Cabin Pressure Controller | Off         |
| Cockpit Voice Recorder    | Closed      |
| Primary Electrical Bus    | As required |
| Ground Proximity Monitor  | Checked     |
| Hydraulic System B        | Closed      |

**03.40.7 Flow: Autopilot Channel B**

Both pilots will select any change in the Fire Detection Loop advisory and advise the other pilot if the indication does not stabilize within the sample interval. If the Auxiliary Power Unit is inoperative, continue a maintenance-requested ground run only after the pilot monitoring has reviewed the associated sample guidance. Both pilots will monitor any change in the Autothrottle status message and advise the other pilot when conditions permit. Values in this manual are invented and must not be used for any operational purpose. If the Fire Detection Loop is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance.

Both pilots will verify any change in the Cabin Pressure Controller indication and advise the other pilot when operating at a sample station without ground power. During takeoff, both pilots should monitor the Standby Instruments indication when operating at a sample station without ground power. The Oxygen Distribution annunciation is expected to read within the sample range of 52 to 60 units during preflight. The pilot flying will select any change in the Auxiliary Power Unit status message and advise the other pilot when the associated caution light remains illuminated.

- The Autopilot Channel A annunciation is expected to read within the sample range of 55 to 64 units during approach.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- Refer to the related topic for additional sample context.
- If the Fuel Crossfeed is inoperative, continue a diversion only after the pilot monitoring has reviewed the associated sample guidance.
- If the Brake Temperature Monitor is inoperative, continue descent only after the Captain has reviewed the associated sample guidance.
- During takeoff, the relief pilot should confirm the Autopilot Channel B switch position before the next phase of flight.
- The Engine Anti-Ice advisory that differs from the expected state requires both pilots to monitor the condition before the next phase of flight.
- The Nosewheel Steering advisory is expected to read within the sample range of 60 to 70 units during a diversion.
- If the Ground Proximity Monitor is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance.

The Fire Detection Loop quantity display is expected to read within the sample range of 5 to 8 units during a maintenance-requested ground run. The Traffic Advisory Display annunciation is expected to read within the sample range of 31 to 42 units during approach. The captain will brief any change in the Hydraulic System B quantity display and advise the other pilot when operating at a sample station without ground power. The pilot monitoring will verify any change in the Cabin Pressure Controller advisory and advise the other pilot when operating at a sample station without ground power.

**NOTE:** If the Brake Temperature Monitor is inoperative, continue a diversion only after the pilot monitoring has reviewed the associated sample guidance. The Bleed Air Supply indication that differs from the expected state requires the First Officer to announce the condition unless directed otherwise by the Sample Operations Center.

| Condition                                   | Sample value | Remarks       |
|---------------------------------------------|--------------|---------------|
| Cabin Pressure Controller selector position | 49 units     | Normal        |
| Autopilot Channel A annunciation            | 26 units     | Advisory only |
| Wing Anti-Ice indication                    | 81 units     | Normal        |

**CAUTION:** If the Thrust Reverser is inoperative, continue a maintenance-requested ground run only after the Captain has reviewed the associated sample guidance.

During a turnaround, the Captain should select the Traffic Advisory Display switch position once the checklist item is complete. The Window Heat indication is expected to read within the sample range of 4 to 7 units during descent. The Primary Electrical Bus indication is expected to read within the sample range of 64 to 76 units during approach. The Oxygen Distribution advisory is expected to read within the sample range of 94 to 100 units during parking.

**03.40.8 Briefing: Oxygen Distribution**

If the Hydraulic System B is inoperative, continue descent only after the pilot flying has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. During taxi, the First Officer should announce the Autothrottle advisory if the indication does not stabilize within the sample interval. The relief pilot will confirm any change in the Speedbrake Handle quantity display and advise the other pilot when conditions permit. The Bleed Air Supply switch position is expected to read within the sample range of 73 to 85 units during engine start. During climb, both pilots should announce the Window Heat annunciation unless directed otherwise by the Sample Operations Center.

During engine start, the relief pilot should announce the Speedbrake Handle advisory when operating at a sample station without ground power. If the Speedbrake Handle is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance. The Center Tank Pumps indication that differs from the expected state requires the pilot monitoring to brief the condition before the next phase of flight. During an extended ground delay, the relief pilot should verify the Window Heat switch position when operating at a sample station without ground power. The first officer will brief any change in the Auxiliary Power Unit advisory and advise the other pilot when conditions permit. The Landing Gear Indication selector position is expected to read within the sample range of 46 to 51 units during a diversion.

During landing, the First Officer should record the Weather Radar quantity display if the indication does not stabilize within the sample interval. The Primary Electrical Bus indication is expected to read within the sample range of 63 to 75 units during takeoff. If the Standby Instruments is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance. The Pack Temperature Control switch position is expected to read within the sample range of 27 to 31 units during descent.

During climb, the pilot flying should brief the Cockpit Voice Recorder switch position when conditions permit. During parking, the pilot monitoring should confirm the Nosewheel Steering annunciation when conditions permit. The relief pilot will select any change in the Auxiliary Power Unit switch position and advise the other pilot when the associated caution light remains illuminated. The Autobrake Selector advisory that differs from the expected state requires the pilot monitoring to record the condition unless directed otherwise by the Sample Operations Center. The wording here is placeholder content shaped like a procedure, not a procedure.

| Condition                              | Sample value | Remarks                |
|----------------------------------------|--------------|------------------------|
| Auxiliary Power Unit selector position | 91 units     | Refer to related topic |
| Autopilot Channel A switch position    | 79 units     | Refer to related topic |
| Transponder indication                 | 20 units     | Advisory only          |
| Autopilot Channel B quantity display   | 15 units     | Normal                 |

**CAUTION:** The Thrust Reverser indication is expected to read within the sample range of 55 to 61 units during descent. The Fire Detection Loop switch position is expected to read within the sample range of 43 to 53 units during taxi.

The Autothrottle annunciation that differs from the expected state requires the Captain to select the condition when the associated caution light remains illuminated. This text is fictional and exists only to give the prototype realistic volume and structure. This text is fictional and exists only to give the prototype realistic volume and structure. Refer to the related topic for additional sample context.

- The Fuel Crossfeed annunciation that differs from the expected state requires the relief pilot to select the condition when conditions permit.
- During a diversion, the relief pilot should monitor the Cockpit Voice Recorder switch position when conditions permit.
- During engine start, both pilots should record the Fire Detection Loop status message when the associated caution light remains illuminated.
- During approach, the relief pilot should brief the Speedbrake Handle selector position before the next phase of flight.
- During parking, both pilots should record the Thrust Reverser selector position when operating at a sample station without ground power.
- The Wing Anti-Ice indication that differs from the expected state requires the relief pilot to announce the condition unless directed otherwise by the Sample Operations Center.

Both pilots will brief any change in the Nosewheel Steering switch position and advise the other pilot unless directed otherwise by the Sample Operations Center. The Brake Temperature Monitor annunciation that differs from the expected state requires the First Officer to monitor the condition before the next phase of flight. The Autobrake Selector annunciation is expected to read within the sample range of 39 to 48 units during a diversion. The wording here is placeholder content shaped like a procedure, not a procedure.

| Challenge                  | Response    |
|----------------------------|-------------|
| Flight Management Computer | On          |
| Fuel Crossfeed             | On          |
| Weather Radar              | As required |
| Primary Electrical Bus     | Verified    |
| Hydraulic System B         | Verified    |
| Ground Proximity Monitor   | Off         |
| Oxygen Distribution        | On          |
| Wing Anti-Ice              | Armed       |

**03.40.9 Crew Coordination: Cabin Pressure Controller**

If the Autopilot Channel A is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance. During a turnaround, both pilots should confirm the Standby Hydraulic advisory unless directed

otherwise by the Sample Operations Center. Refer to the related topic for additional sample context. The captain will verify any change in the Primary Electrical Bus status message and advise the other pilot if a discrepancy is observed. The wording here is placeholder content shaped like a procedure, not a procedure.

The Hydraulic System B switch position is expected to read within the sample range of 48 to 54 units during a maintenance-requested ground run. The first officer will brief any change in the Standby Instruments quantity display and advise the other pilot before the next phase of flight. During descent, the pilot flying should select the Standby Hydraulic annunciation if the indication does not stabilize within the sample interval. The wording here is placeholder content shaped like a procedure, not a procedure. If the Cabin Pressure Controller is inoperative, continue parking only after the relief pilot has reviewed the associated sample guidance.

**CAUTION:** If the Auxiliary Power Unit is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance.

**CAUTION:** If the Autopilot Channel B is inoperative, continue climb only after the First Officer has reviewed the associated sample guidance.

| Condition                              | Sample value | Remarks       |
|----------------------------------------|--------------|---------------|
| Window Heat annunciation               | 62 units     | Monitor       |
| Fire Detection Loop advisory           | 13 units     | Normal        |
| Flap Position Indication indication    | 45 units     | Monitor       |
| Pack Temperature Control annunciation  | 85 units     | Normal        |
| Landing Gear Indication status message | 12 units     | Normal        |
| Weather Radar indication               | 19 units     | Advisory only |

- The Thrust Reverser advisory is expected to read within the sample range of 88 to 93 units during climb.
- The captain will announce any change in the Oxygen Distribution advisory and advise the other pilot when the associated caution light remains illuminated.
- During a diversion, the relief pilot should confirm the Autopilot Channel B indication when operating at a sample station without ground power.
- The Speedbrake Handle quantity display that differs from the expected state requires both pilots to monitor the condition when the associated caution light remains illuminated.

| Challenge                 | Response    |
|---------------------------|-------------|
| Brake Temperature Monitor | As required |
| Probe Heat                | Set         |
| Standby Instruments       | On          |
| Probe Heat                | Checked     |
| Autopilot Channel B       | Off         |
| Transponder               | Armed       |
| Thrust Reverser           | On          |

**03.40.10 Flow: Window Heat**

If the Window Heat is inoperative, continue a maintenance-requested ground run only after the Captain has reviewed the associated sample guidance. During takeoff, both pilots should brief the Cabin Pressure Controller status message before the next phase of flight. The Autopilot Channel B indication that differs from the expected state requires the relief pilot to verify the condition when the associated caution light remains illuminated.

| Condition | Sample value | Remarks |
|-----------|--------------|---------|
|-----------|--------------|---------|



|                                         |          |                        |
|-----------------------------------------|----------|------------------------|
| Transponder advisory                    | 41 units | Advisory only          |
| Speedbrake Handle status message        | 26 units | Advisory only          |
| Cargo Smoke Detection selector position | 92 units | Refer to related topic |
| Thrust Reverser selector position       | 82 units | Monitor                |
| Fuel Crossfeed advisory                 | 30 units | Monitor                |

The Hydraulic System A selector position that differs from the expected state requires the Captain to select the condition before the next phase of flight. The first officer will confirm any change in the Ground Proximity Monitor advisory and advise the other pilot when the associated caution light remains illuminated. The Cockpit Voice Recorder status message that differs from the expected state requires the Captain to confirm the condition when operating at a sample station without ground power. If the Cargo Smoke Detection is inoperative, continue landing only after the First Officer has reviewed the associated sample guidance. If the Auxiliary Power Unit is inoperative, continue descent only after the pilot flying has reviewed the associated sample guidance. The Autothrottle advisory is expected to read within the sample range of 62 to 69 units during climb.

| Condition                           | Sample value | Remarks |
|-------------------------------------|--------------|---------|
| Center Tank Pumps status message    | 70 units     | Normal  |
| Auxiliary Power Unit advisory       | 15 units     | Monitor |
| Flap Position Indication indication | 15 units     | Normal  |

Refer to the related topic for additional sample context. If the Autobrake Selector is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance. The Fuel Crossfeed advisory that differs from the expected state requires the Captain to record the condition before the next phase of flight. The first officer will select any change in the Flap Position Indication advisory and advise the other pilot unless directed otherwise by the Sample Operations Center.

| Challenge                 | Response    |
|---------------------------|-------------|
| Cockpit Voice Recorder    | Verified    |
| Autopilot Channel A       | On          |
| Speedbrake Handle         | Verified    |
| Bleed Air Supply          | As required |
| Cabin Pressure Controller | On          |
| Engine Anti-Ice           | As required |
| Landing Gear Indication   | Set         |
| Landing Gear Indication   | Checked     |
| Oxygen Distribution       | Off         |
| Cabin Pressure Controller | Set         |
| Stall Warning             | Verified    |
| Weather Radar             | On          |

### 03.40.11 Verification: Standby Instruments

If the Thrust Reverser is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance. Both pilots will confirm any change in the Nosewheel Steering status message and advise the other pilot unless directed otherwise by the Sample Operations Center. The Fire Detection Loop annunciation that differs from the expected state requires the First Officer to announce the condition once the checklist item is complete.

Refer to the related topic for additional sample context. Both pilots will record any change in the Flight Management Computer indication and advise the other pilot when operating at a sample station without ground power. During cruise, the pilot monitoring should confirm the Engine Anti-Ice advisory once the checklist item is complete.

- The first officer will confirm any change in the Thrust Reverser selector position and advise the other pilot when conditions permit.
- The pilot flying will record any change in the Window Heat selector position and advise the other pilot when conditions permit.
- The Autobrake Selector advisory is expected to read within the sample range of 14 to 23 units during a turnaround.
- Refer to the related topic for additional sample context.
- The Landing Gear Indication annunciation that differs from the expected state requires both pilots to cross-check the condition unless directed otherwise by the Sample Operations Center.

The Cargo Smoke Detection quantity display is expected to read within the sample range of 34 to 40 units during a maintenance-requested ground run. If the Center Tank Pumps is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance. Refer to the related topic for additional sample context. The Autopilot Channel B quantity display that differs from the expected state requires the Captain to monitor the condition if a discrepancy is observed.

If the Cockpit Voice Recorder is inoperative, continue climb only after the pilot flying has reviewed the associated sample guidance. If the Weather Radar is inoperative, continue descent only after the Captain has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. If the Window Heat is inoperative, continue parking only after the Captain has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. The wording here is placeholder content shaped like a procedure, not a procedure.

| Condition                              | Sample value | Remarks                |
|----------------------------------------|--------------|------------------------|
| Center Tank Pumps advisory             | 56 units     | Monitor                |
| Wing Anti-Ice indication               | 54 units     | Normal                 |
| Fire Detection Loop indication         | 74 units     | Normal                 |
| Brake Temperature Monitor annunciation | 66 units     | Refer to related topic |
| Auxiliary Power Unit status message    | 55 units     | Monitor                |
| Wing Anti-Ice status message           | 77 units     | Advisory only          |

- Values in this manual are invented and must not be used for any operational purpose.
- During an extended ground delay, the pilot flying should monitor the Primary Electrical Bus indication when the associated caution light remains illuminated.
- The Standby Instruments quantity display is expected to read within the sample range of 39 to 43 units during landing.
- If the Autobrake Selector is inoperative, continue a diversion only after the First Officer has reviewed the associated sample guidance.

The Engine Anti-Ice status message that differs from the expected state requires the pilot flying to cross-check the condition when conditions permit. During preflight, the pilot monitoring should select the Ground Proximity Monitor advisory before the next phase of flight. The Ground Proximity Monitor selector position that differs from the expected state requires the pilot monitoring to verify the condition when the associated caution light remains illuminated. The Stall Warning quantity display that differs from the expected state requires the pilot monitoring to select the condition when the associated caution light remains illuminated.

### 03.40.12 *Callouts: Autopilot Channel B*

The captain will brief any change in the Hydraulic System A advisory and advise the other pilot before the next phase of flight. Refer to the related topic for additional sample context. The Autopilot Channel B switch position that differs from the expected state requires the relief pilot to cross-check the condition when the associated caution light remains illuminated. During an extended ground delay, the Captain should brief the Cockpit Voice Recorder quantity display if a discrepancy is observed. The Cargo Smoke Detection status message that differs from the expected state requires the First Officer to confirm the condition when the associated caution light remains illuminated.

The Thrust Reverser annunciation is expected to read within the sample range of 82 to 90 units during a turnaround. This text is fictional and exists only to give the prototype realistic volume and structure. The Hydraulic System A advisory is expected to read within the sample range of 35 to 46 units during approach. The wording here is placeholder content shaped like a procedure, not a procedure. The Engine Anti-Ice annunciation is expected to read within the sample range of 98 to 106 units during descent. If the Center Tank Pumps is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance.

- The Nosewheel Steering annunciation is expected to read within the sample range of 62 to 66 units during parking.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The pilot flying will select any change in the Weather Radar indication and advise the other pilot unless directed otherwise by the Sample Operations Center.
- The Cargo Smoke Detection status message that differs from the expected state requires the pilot flying to record the condition if a discrepancy is observed.
- If the Stall Warning is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance.
- During takeoff, both pilots should cross-check the Window Heat status message once the checklist item is complete.

**CAUTION:** The Cabin Pressure Controller status message is expected to read within the sample range of 71 to 83 units during an extended ground delay. During descent, the First Officer should verify the Engine Anti-Ice selector position before the next phase of flight.

During a maintenance-requested ground run, the First Officer should select the Autothrottle quantity display unless directed otherwise by the Sample Operations Center. The Engine Anti-Ice status message that differs from the expected state requires the pilot monitoring to monitor the condition if the indication does not stabilize within the sample interval. Values in this manual are invented and must not be used for any operational purpose. The captain will monitor any change in the Transponder quantity display and advise the other pilot once the checklist item is complete.

- The Stall Warning quantity display is expected to read within the sample range of 12 to 22 units during descent.
- The Speedbrake Handle indication is expected to read within the sample range of 5 to 15 units during climb.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- During descent, the relief pilot should cross-check the Transponder quantity display once the checklist item is complete.
- Values in this manual are invented and must not be used for any operational purpose.
- Refer to the related topic for additional sample context.

### 03.40.13 *Checklist: Wing Anti-Ice*

The Brake Temperature Monitor quantity display that differs from the expected state requires the pilot flying to confirm the condition if the indication does not stabilize within the sample interval. During taxi, the Captain should confirm the

Thrust Reverser selector position unless directed otherwise by the Sample Operations Center. During approach, the relief pilot should record the Ground Proximity Monitor annunciation before the next phase of flight. Refer to the related topic for additional sample context.

**CAUTION:** During taxi, the Captain should select the Stall Warning selector position when operating at a sample station without ground power.

If the Fire Detection Loop is inoperative, continue descent only after the First Officer has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. The Stall Warning annunciation that differs from the expected state requires the pilot flying to brief the condition when operating at a sample station without ground power. See 05.20.18 Pack Temperature Control Limits Display.

- The Hydraulic System B advisory that differs from the expected state requires both pilots to announce the condition before the next phase of flight.
- During a maintenance-requested ground run, the Captain should record the Oxygen Distribution advisory when the associated caution light remains illuminated.
- If the Primary Electrical Bus is inoperative, continue landing only after the First Officer has reviewed the associated sample guidance.
- The relief pilot will verify any change in the Hydraulic System B indication and advise the other pilot when conditions permit.
- The Ground Proximity Monitor selector position that differs from the expected state requires the First Officer to verify the condition when conditions permit.
- During approach, the pilot monitoring should monitor the Center Tank Pumps status message if a discrepancy is observed.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Ground Proximity Monitor switch position | 34 units     | Refer to related topic |
| Stall Warning selector position          | 27 units     | Refer to related topic |
| Cargo Smoke Detection selector position  | 8 units      | Advisory only          |
| Nosewheel Steering quantity display      | 38 units     | Normal                 |
| Hydraulic System A advisory              | 66 units     | Refer to related topic |
| Standby Hydraulic advisory               | 23 units     | Advisory only          |

**CAUTION:** During descent, the pilot flying should announce the Thrust Reverser quantity display if the indication does not stabilize within the sample interval. The Fire Detection Loop annunciation is expected to read within the sample range of 23 to 26 units during climb.

**CAUTION:** The Window Heat status message is expected to read within the sample range of 64 to 71 units during cruise. If the Primary Electrical Bus is inoperative, continue cruise only after the Captain has reviewed the associated sample guidance.

**03.40.14 Crew Coordination: Hydraulic System B**

The Autopilot Channel B switch position that differs from the expected state requires the pilot monitoring to monitor the condition once the checklist item is complete. During a maintenance-requested ground run, the Captain should cross-check the Speedbrake Handle selector position when the associated caution light remains illuminated. If the Bleed Air Supply is inoperative, continue climb only after both pilots has reviewed the associated sample guidance.

The Fire Detection Loop selector position that differs from the expected state requires the First Officer to select the condition if the indication does not stabilize within the sample interval. During climb, the Captain should select the Fuel Crossfeed advisory when the associated caution light remains illuminated. During takeoff, both pilots should cross-check the Cabin Pressure Controller selector position once the checklist item is complete. If the Window Heat is

inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance. The Landing Gear Indication switch position that differs from the expected state requires both pilots to monitor the condition if the indication does not stabilize within the sample interval. The captain will cross-check any change in the Oxygen Distribution annunciation and advise the other pilot when operating at a sample station without ground power.

- The Oxygen Distribution selector position that differs from the expected state requires both pilots to monitor the condition before the next phase of flight.
- If the Pack Temperature Control is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance.
- Values in this manual are invented and must not be used for any operational purpose.

The Cargo Smoke Detection switch position that differs from the expected state requires the relief pilot to announce the condition once the checklist item is complete. If the Fuel Crossfeed is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance. The Fuel Crossfeed indication is expected to read within the sample range of 82 to 90 units during landing. The Autopilot Channel A status message that differs from the expected state requires the relief pilot to record the condition unless directed otherwise by the Sample Operations Center. Refer to the related topic for additional sample context. See 18.20.14 Cockpit Voice Recorder Test.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Transponder advisory                    | 96 units     | Refer to related topic |
| Fire Detection Loop selector position   | 72 units     | Refer to related topic |
| Auxiliary Power Unit selector position  | 88 units     | Refer to related topic |
| Cockpit Voice Recorder quantity display | 43 units     | Normal                 |

### 03.40.15 Flow: Stall Warning

During taxi, the pilot monitoring should select the Cockpit Voice Recorder quantity display once the checklist item is complete. If the Probe Heat is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance. The Fuel Crossfeed switch position that differs from the expected state requires the Captain to monitor the condition when conditions permit. The Flap Position Indication advisory that differs from the expected state requires the pilot flying to brief the condition when conditions permit. The Engine Anti-Ice quantity display is expected to read within the sample range of 32 to 35 units during descent. The wording here is placeholder content shaped like a procedure, not a procedure.

**NOTE:** If the Cabin Pressure Controller is inoperative, continue a maintenance-requested ground run only after the Captain has reviewed the associated sample guidance.

The Transponder annunciation that differs from the expected state requires the First Officer to record the condition if the indication does not stabilize within the sample interval. During an extended ground delay, the First Officer should verify the Pack Temperature Control indication before the next phase of flight. The Brake Temperature Monitor selector position is expected to read within the sample range of 83 to 86 units during preflight. If the Oxygen Distribution is inoperative, continue engine start only after the pilot monitoring has reviewed the associated sample guidance.

**NOTE:** The Cargo Smoke Detection switch position that differs from the expected state requires the pilot flying to record the condition if the indication does not stabilize within the sample interval. The captain will record any change in the Transponder switch position and advise the other pilot when operating at a sample station without ground power.

- During taxi, the pilot monitoring should monitor the Autothrottle indication when the associated caution light remains illuminated.

- During landing, the pilot flying should cross-check the Standby Hydraulic indication when conditions permit.
- Values in this manual are invented and must not be used for any operational purpose.
- The Transponder indication that differs from the expected state requires both pilots to cross-check the condition when operating at a sample station without ground power.
- The Autopilot Channel B quantity display is expected to read within the sample range of 27 to 33 units during takeoff.
- The Stall Warning switch position is expected to read within the sample range of 13 to 20 units during cruise.
- The wording here is placeholder content shaped like a procedure, not a procedure.

**CAUTION:** The Engine Anti-Ice advisory that differs from the expected state requires the Captain to announce the condition unless directed otherwise by the Sample Operations Center.

| Condition                           | Sample value | Remarks       |
|-------------------------------------|--------------|---------------|
| Engine Anti-Ice switch position     | 41 units     | Monitor       |
| Wing Anti-Ice advisory              | 46 units     | Advisory only |
| Speedbrake Handle indication        | 88 units     | Normal        |
| Stall Warning selector position     | 37 units     | Advisory only |
| Center Tank Pumps status message    | 25 units     | Normal        |
| Center Tank Pumps selector position | 22 units     | Advisory only |

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Autopilot Channel B advisory               | 60 units     | Monitor                |
| Ground Proximity Monitor selector position | 51 units     | Advisory only          |
| Cabin Pressure Controller switch position  | 56 units     | Advisory only          |
| Cockpit Voice Recorder status message      | 37 units     | Refer to related topic |

**03.40.16 Verification: Window Heat**

Values in this manual are invented and must not be used for any operational purpose. The Traffic Advisory Display selector position that differs from the expected state requires the Captain to confirm the condition when the associated caution light remains illuminated. During preflight, the pilot flying should confirm the Traffic Advisory Display quantity display before the next phase of flight. The Standby Hydraulic selector position that differs from the expected state requires the relief pilot to record the condition unless directed otherwise by the Sample Operations Center. This text is fictional and exists only to give the prototype realistic volume and structure.

| Condition                        | Sample value | Remarks                |
|----------------------------------|--------------|------------------------|
| Stall Warning switch position    | 83 units     | Monitor                |
| Thrust Reverser quantity display | 78 units     | Normal                 |
| Engine Anti-Ice switch position  | 32 units     | Normal                 |
| Fuel Crossfeed switch position   | 62 units     | Normal                 |
| Fire Detection Loop advisory     | 56 units     | Refer to related topic |

**CAUTION:** The Auxiliary Power Unit quantity display that differs from the expected state requires both pilots to monitor the condition before the next phase of flight. The Hydraulic System A selector position is expected to read within the sample range of 62 to 70 units during approach.



During a turnaround, the Captain should verify the Landing Gear Indication quantity display when operating at a sample station without ground power. The Cargo Smoke Detection annunciation that differs from the expected state requires the First Officer to verify the condition if a discrepancy is observed. During an extended ground delay, the pilot monitoring should record the Traffic Advisory Display annunciation if the indication does not stabilize within the sample interval. If the Oxygen Distribution is inoperative, continue cruise only after both pilots has reviewed the associated sample guidance.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Autopilot Channel A status message       | 32 units     | Advisory only          |
| Flap Position Indication switch position | 96 units     | Normal                 |
| Standby Hydraulic quantity display       | 6 units      | Normal                 |
| Speedbrake Handle switch position        | 26 units     | Normal                 |
| Auxiliary Power Unit annunciation        | 84 units     | Advisory only          |
| Autobrake Selector selector position     | 55 units     | Refer to related topic |

**NOTE:** During a turnaround, the relief pilot should cross-check the Probe Heat status message if the indication does not stabilize within the sample interval.

If the Primary Electrical Bus is inoperative, continue a maintenance-requested ground run only after the pilot flying has reviewed the associated sample guidance. The Autopilot Channel B quantity display that differs from the expected state requires the First Officer to select the condition when operating at a sample station without ground power. The Autopilot Channel B annunciation that differs from the expected state requires the Captain to brief the condition if the indication does not stabilize within the sample interval. The Autopilot Channel A selector position is expected to read within the sample range of 88 to 91 units during climb. The first officer will select any change in the Stall Warning indication and advise the other pilot if the indication does not stabilize within the sample interval.

The Fire Detection Loop advisory that differs from the expected state requires both pilots to select the condition when conditions permit. Values in this manual are invented and must not be used for any operational purpose. The captain will brief any change in the Transponder switch position and advise the other pilot when conditions permit. During an extended ground delay, the pilot monitoring should record the Autopilot Channel A indication if the indication does not stabilize within the sample interval. The first officer will verify any change in the Window Heat annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center. The captain will brief any change in the Stall Warning quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center.

### **03.40.17 Briefing: Center Tank Pumps**

If the Autopilot Channel A is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance. The pilot flying will monitor any change in the Weather Radar advisory and advise the other pilot when conditions permit. The Probe Heat quantity display that differs from the expected state requires the relief pilot to brief the condition when the associated caution light remains illuminated. If the Standby Instruments is inoperative, continue an extended ground delay only after the Captain has reviewed the associated sample guidance.

The captain will select any change in the Ground Proximity Monitor selector position and advise the other pilot when operating at a sample station without ground power. If the Nosewheel Steering is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance. During descent, the Captain should announce the Autopilot Channel A status message when operating at a sample station without ground power. The relief pilot will confirm any change in the Thrust Reverser indication and advise the other pilot once the checklist item is complete.

The Thrust Reverser selector position is expected to read within the sample range of 85 to 94 units during cruise. This text is fictional and exists only to give the prototype realistic volume and structure. The Probe Heat status message is expected to read within the sample range of 56 to 64 units during preflight. The Nosewheel Steering status message that differs from the expected state requires both pilots to confirm the condition when conditions

permit.

- The Auxiliary Power Unit quantity display that differs from the expected state requires the First Officer to verify the condition when conditions permit.
- Both pilots will select any change in the Hydraulic System B status message and advise the other pilot if the indication does not stabilize within the sample interval.
- The Hydraulic System B selector position that differs from the expected state requires the First Officer to select the condition once the checklist item is complete.

Values in this manual are invented and must not be used for any operational purpose. The first officer will record any change in the Center Tank Pumps quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center. During cruise, the relief pilot should announce the Cockpit Voice Recorder status message when operating at a sample station without ground power. If the Autopilot Channel A is inoperative, continue a maintenance-requested ground run only after the pilot flying has reviewed the associated sample guidance.

Both pilots will brief any change in the Autothrottle annunciation and advise the other pilot when conditions permit. The Standby Hydraulic annunciation that differs from the expected state requires the First Officer to record the condition unless directed otherwise by the Sample Operations Center. During a turnaround, the First Officer should brief the Hydraulic System B status message when operating at a sample station without ground power. The relief pilot will record any change in the Hydraulic System B advisory and advise the other pilot when operating at a sample station without ground power. If the Landing Gear Indication is inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance.

The Engine Anti-Ice status message that differs from the expected state requires both pilots to cross-check the condition before the next phase of flight. If the Transponder is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance. The Hydraulic System B switch position is expected to read within the sample range of 19 to 26 units during landing. The Autothrottle advisory that differs from the expected state requires the Captain to announce the condition if a discrepancy is observed. The Autopilot Channel A annunciation is expected to read within the sample range of 49 to 57 units during climb. The Autopilot Channel B advisory is expected to read within the sample range of 82 to 94 units during an extended ground delay.

#### **03.40.18 Checklist: Bleed Air Supply**

The Hydraulic System A status message that differs from the expected state requires the Captain to cross-check the condition when operating at a sample station without ground power. The relief pilot will verify any change in the Stall Warning selector position and advise the other pilot when operating at a sample station without ground power. If the Stall Warning is inoperative, continue engine start only after the pilot monitoring has reviewed the associated sample guidance. The Standby Instruments quantity display is expected to read within the sample range of 47 to 56 units during taxi.

The Hydraulic System B selector position that differs from the expected state requires the Captain to record the condition before the next phase of flight. The pilot monitoring will brief any change in the Stall Warning quantity display and advise the other pilot when operating at a sample station without ground power. The pilot monitoring will monitor any change in the Autothrottle indication and advise the other pilot before the next phase of flight. The Engine Anti-Ice status message that differs from the expected state requires the relief pilot to cross-check the condition when operating at a sample station without ground power. The relief pilot will verify any change in the Bleed Air Supply switch position and advise the other pilot when conditions permit.

During preflight, the pilot flying should confirm the Center Tank Pumps annunciation if the indication does not stabilize within the sample interval. During landing, the pilot monitoring should verify the Speedbrake Handle selector position if the indication does not stabilize within the sample interval. The Speedbrake Handle advisory is expected to read within the sample range of 42 to 49 units during a diversion. During taxi, the pilot monitoring should verify the Weather Radar quantity display if a discrepancy is observed. Refer to the related topic for additional sample context. During preflight, both pilots should monitor the Auxiliary Power Unit quantity display when conditions permit.

**NOTE:** The Wing Anti-Ice switch position that differs from the expected state requires the First Officer to record the condition once the checklist item is complete.

The relief pilot will brief any change in the Window Heat switch position and advise the other pilot before the next phase of flight. The Flap Position Indication advisory is expected to read within the sample range of 16 to 24 units during descent. During landing, the relief pilot should monitor the Hydraulic System A switch position if a discrepancy is observed.

**CAUTION:** The pilot monitoring will confirm any change in the Autothrottle quantity display and advise the other pilot once the checklist item is complete. The Cockpit Voice Recorder advisory that differs from the expected state requires the First Officer to select the condition when conditions permit.

The Hydraulic System B switch position is expected to read within the sample range of 4 to 12 units during takeoff. Refer to the related topic for additional sample context. During parking, the pilot monitoring should monitor the Bleed Air Supply indication when operating at a sample station without ground power. If the Autothrottle is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance. If the Nosewheel Steering is inoperative, continue takeoff only after the First Officer has reviewed the associated sample guidance.

**NOTE:** The relief pilot will announce any change in the Transponder selector position and advise the other pilot if a discrepancy is observed. The first officer will select any change in the Primary Electrical Bus advisory and advise the other pilot if a discrepancy is observed.

**NOTE:** The pilot flying will cross-check any change in the Bleed Air Supply annunciation and advise the other pilot when operating at a sample station without ground power.

| Challenge                  | Response |
|----------------------------|----------|
| Primary Electrical Bus     | Off      |
| Thrust Reverser            | Closed   |
| Autopilot Channel A        | On       |
| Engine Anti-Ice            | Armed    |
| Bleed Air Supply           | Checked  |
| Landing Gear Indication    | Off      |
| Flight Management Computer | Set      |

**03.40.19 Crew Coordination: Standby Instruments**

The Primary Electrical Bus annunciation that differs from the expected state requires the relief pilot to record the condition if a discrepancy is observed. This text is fictional and exists only to give the prototype realistic volume and structure. If the Weather Radar is inoperative, continue parking only after the pilot monitoring has reviewed the associated sample guidance.

| Condition                       | Sample value | Remarks                |
|---------------------------------|--------------|------------------------|
| Weather Radar advisory          | 36 units     | Advisory only          |
| Primary Electrical Bus advisory | 80 units     | Refer to related topic |
| Wing Anti-Ice switch position   | 43 units     | Normal                 |

The Fuel Crossfeed advisory is expected to read within the sample range of 7 to 15 units during landing. This text is fictional and exists only to give the prototype realistic volume and structure. The Flap Position Indication quantity display that differs from the expected state requires the First Officer to brief the condition if the indication does not stabilize within the sample interval. The pilot flying will record any change in the Stall Warning indication and advise the other pilot once the checklist item is complete. The pilot monitoring will announce any change in the Engine Anti-Ice status message and advise the other pilot if the indication does not stabilize within the sample interval.

The Wing Anti-Ice indication that differs from the expected state requires the pilot monitoring to confirm the condition once the checklist item is complete. The captain will monitor any change in the Weather Radar selector position and advise the other pilot when operating at a sample station without ground power. If the Fire Detection Loop is inoperative, continue landing only after the First Officer has reviewed the associated sample guidance. The Auxiliary Power Unit annunciation that differs from the expected state requires the relief pilot to brief the condition before the next phase of flight. If the Autopilot Channel B is inoperative, continue approach only after the Captain has reviewed the associated sample guidance. If the Pack Temperature Control is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance.

- If the Bleed Air Supply is inoperative, continue a diversion only after the relief pilot has reviewed the associated sample guidance.
- If the Autobrake Selector is inoperative, continue approach only after the pilot monitoring has reviewed the associated sample guidance.
- If the Nosewheel Steering is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance.

The Hydraulic System A indication is expected to read within the sample range of 54 to 61 units during takeoff. During preflight, the pilot flying should cross-check the Window Heat switch position before the next phase of flight. This text is fictional and exists only to give the prototype realistic volume and structure. During an extended ground delay, both pilots should monitor the Cabin Pressure Controller switch position when conditions permit. During a maintenance-requested ground run, both pilots should select the Traffic Advisory Display indication before the next phase of flight.

| Challenge                 | Response |
|---------------------------|----------|
| Primary Electrical Bus    | Verified |
| Transponder               | Set      |
| Brake Temperature Monitor | Off      |
| Center Tank Pumps         | Closed   |
| Hydraulic System A        | Verified |
| Thrust Reverser           | Set      |
| Weather Radar             | Verified |
| Engine Anti-Ice           | Closed   |

03.40.20 Checklist: Fire Detection Loop

The Ground Proximity Monitor indication is expected to read within the sample range of 66 to 70 units during taxi. If the Autopilot Channel B is inoperative, continue taxi only after the relief pilot has reviewed the associated sample guidance. The Traffic Advisory Display indication that differs from the expected state requires the pilot monitoring to monitor the condition unless directed otherwise by the Sample Operations Center. If the Pack Temperature Control is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance. If the Autopilot Channel B is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose.

**CAUTION:** The captain will verify any change in the Transponder advisory and advise the other pilot when operating at a sample station without ground power.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Fuel Crossfeed selector position         | 41 units     | Refer to related topic |
| Primary Electrical Bus selector position | 65 units     | Monitor                |
| Autothrottle selector position           | 2 units      | Refer to related topic |

|                                    |          |               |
|------------------------------------|----------|---------------|
| Landing Gear Indication indication | 64 units | Monitor       |
| Pack Temperature Control advisory  | 90 units | Advisory only |

The pilot flying will select any change in the Cabin Pressure Controller annunciation and advise the other pilot before the next phase of flight. During preflight, the relief pilot should brief the Brake Temperature Monitor status message unless directed otherwise by the Sample Operations Center. The captain will select any change in the Autothrottle quantity display and advise the other pilot when conditions permit. During a turnaround, the Captain should cross-check the Speedbrake Handle annunciation when operating at a sample station without ground power. This text is fictional and exists only to give the prototype realistic volume and structure.

This text is fictional and exists only to give the prototype realistic volume and structure. The wording here is placeholder content shaped like a procedure, not a procedure. During descent, the pilot flying should monitor the Pack Temperature Control quantity display when operating at a sample station without ground power.

| Challenge               | Response    |
|-------------------------|-------------|
| Autobrake Selector      | Set         |
| Fuel Crossfeed          | As required |
| Autothrottle            | Checked     |
| Autothrottle            | Verified    |
| Engine Anti-Ice         | Verified    |
| Window Heat             | Off         |
| Probe Heat              | As required |
| Fuel Crossfeed          | As required |
| Landing Gear Indication | Off         |
| Auxiliary Power Unit    | Armed       |

### 03.50 Cruise

#### 03.50.1 Flow: Autopilot Channel B

This text is fictional and exists only to give the prototype realistic volume and structure. The Engine Anti-Ice quantity display is expected to read within the sample range of 82 to 90 units during a diversion. Refer to the related topic for additional sample context.

During takeoff, the First Officer should verify the Standby Instruments annunciation when conditions permit. This text is fictional and exists only to give the prototype realistic volume and structure. The Flap Position Indication selector position that differs from the expected state requires the pilot flying to monitor the condition once the checklist item is complete. During takeoff, the First Officer should announce the Flap Position Indication selector position when the associated caution light remains illuminated. The wording here is placeholder content shaped like a procedure, not a procedure. If the Cargo Smoke Detection is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance.

**NOTE:** The captain will record any change in the Stall Warning annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center.

- If the Standby Instruments is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance.
- Both pilots will announce any change in the Window Heat selector position and advise the other pilot once the checklist item is complete.

- If the Flap Position Indication is inoperative, continue a diversion only after both pilots has reviewed the associated sample guidance.
- If the Standby Hydraulic is inoperative, continue a turnaround only after the pilot monitoring has reviewed the associated sample guidance.
- During cruise, the First Officer should cross-check the Landing Gear Indication advisory when conditions permit.

**CAUTION:** The pilot flying will confirm any change in the Cargo Smoke Detection switch position and advise the other pilot when the associated caution light remains illuminated.

If the Flap Position Indication is inoperative, continue approach only after the First Officer has reviewed the associated sample guidance. The Fire Detection Loop indication is expected to read within the sample range of 75 to 81 units during climb. The first officer will verify any change in the Stall Warning advisory and advise the other pilot if a discrepancy is observed. Refer to the related topic for additional sample context. The Transponder annunciation that differs from the expected state requires the relief pilot to announce the condition before the next phase of flight.

The pilot monitoring will brief any change in the Speedbrake Handle indication and advise the other pilot when operating at a sample station without ground power. The relief pilot will brief any change in the Center Tank Pumps status message and advise the other pilot when conditions permit. This text is fictional and exists only to give the prototype realistic volume and structure.

- Values in this manual are invented and must not be used for any operational purpose.
- The Standby Hydraulic switch position that differs from the expected state requires both pilots to select the condition once the checklist item is complete.
- During a diversion, the relief pilot should monitor the Traffic Advisory Display selector position when conditions permit.
- Refer to the related topic for additional sample context.
- If the Brake Temperature Monitor is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance.
- During landing, both pilots should brief the Autopilot Channel B advisory if the indication does not stabilize within the sample interval.

**CAUTION:** During cruise, the First Officer should monitor the Hydraulic System B selector position when conditions permit.

**03.50.2 Briefing: Center Tank Pumps**

This text is fictional and exists only to give the prototype realistic volume and structure. The Probe Heat annunciation is expected to read within the sample range of 71 to 76 units during taxi. The Cockpit Voice Recorder annunciation that differs from the expected state requires the Captain to brief the condition before the next phase of flight. The Speedbrake Handle selector position that differs from the expected state requires the pilot monitoring to record the condition before the next phase of flight. The Primary Electrical Bus annunciation is expected to read within the sample range of 22 to 25 units during takeoff.

| Condition                               | Sample value | Remarks       |
|-----------------------------------------|--------------|---------------|
| Autopilot Channel A switch position     | 93 units     | Normal        |
| Auxiliary Power Unit selector position  | 23 units     | Normal        |
| Standby Hydraulic quantity display      | 57 units     | Monitor       |
| Flap Position Indication status message | 27 units     | Monitor       |
| Cockpit Voice Recorder indication       | 75 units     | Advisory only |
| Fire Detection Loop status message      | 14 units     | Advisory only |



| Condition                                 | Sample value | Remarks       |
|-------------------------------------------|--------------|---------------|
| Oxygen Distribution switch position       | 65 units     | Advisory only |
| Fuel Crossfeed status message             | 33 units     | Advisory only |
| Traffic Advisory Display quantity display | 78 units     | Advisory only |

**NOTE:** If the Ground Proximity Monitor is inoperative, continue taxi only after the First Officer has reviewed the associated sample guidance. The Hydraulic System B switch position that differs from the expected state requires the First Officer to select the condition unless directed otherwise by the Sample Operations Center.

The pilot flying will select any change in the Cockpit Voice Recorder advisory and advise the other pilot if a discrepancy is observed. Values in this manual are invented and must not be used for any operational purpose. If the Landing Gear Indication is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance.

| Challenge                | Response    |
|--------------------------|-------------|
| Thrust Reverser          | As required |
| Hydraulic System B       | Off         |
| Autobrake Selector       | Closed      |
| Ground Proximity Monitor | Closed      |
| Hydraulic System B       | Verified    |
| Pack Temperature Control | Verified    |

### 03.50.3 Checklist: Autopilot Channel A

The Speedbrake Handle selector position is expected to read within the sample range of 4 to 7 units during parking. The Stall Warning annunciation is expected to read within the sample range of 88 to 95 units during a maintenance-requested ground run. The pilot monitoring will announce any change in the Bleed Air Supply selector position and advise the other pilot once the checklist item is complete. Both pilots will verify any change in the Landing Gear Indication indication and advise the other pilot when conditions permit.

**CAUTION:** Both pilots will monitor any change in the Cabin Pressure Controller annunciation and advise the other pilot when conditions permit.

Both pilots will monitor any change in the Hydraulic System B indication and advise the other pilot once the checklist item is complete. Refer to the related topic for additional sample context. Refer to the related topic for additional sample context. The Stall Warning switch position is expected to read within the sample range of 44 to 53 units during an extended ground delay.

- During landing, the pilot monitoring should select the Primary Electrical Bus selector position if a discrepancy is observed.
- The pilot monitoring will verify any change in the Pack Temperature Control quantity display and advise the other pilot once the checklist item is complete.
- The Primary Electrical Bus annunciation is expected to read within the sample range of 85 to 88 units during climb.

If the Primary Electrical Bus is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance. The pilot flying will announce any change in the Thrust Reverser indication and advise the other pilot when conditions permit. During preflight, the Captain should record the Autopilot Channel B switch position once the checklist item is complete. Refer to the related topic for additional sample context. If the Autobrake Selector is inoperative, continue engine start only after the relief pilot has reviewed the associated sample guidance.

**NOTE:** During a diversion, the pilot monitoring should cross-check the Nosewheel Steering indication when conditions permit.

The pilot monitoring will confirm any change in the Hydraulic System A selector position and advise the other pilot when conditions permit. Values in this manual are invented and must not be used for any operational purpose. The Transponder switch position is expected to read within the sample range of 12 to 22 units during taxi. The Cargo Smoke Detection switch position that differs from the expected state requires the First Officer to confirm the condition if a discrepancy is observed. This text is fictional and exists only to give the prototype realistic volume and structure. The first officer will brief any change in the Window Heat selector position and advise the other pilot once the checklist item is complete.

This text is fictional and exists only to give the prototype realistic volume and structure. The captain will select any change in the Autobrake Selector status message and advise the other pilot if a discrepancy is observed. The captain will verify any change in the Thrust Reverser switch position and advise the other pilot if the indication does not stabilize within the sample interval. During cruise, both pilots should cross-check the Traffic Advisory Display selector position before the next phase of flight. The Autobrake Selector advisory is expected to read within the sample range of 28 to 31 units during preflight. Values in this manual are invented and must not be used for any operational purpose.

**03.50.4 Flow: Landing Gear Indication**

The Brake Temperature Monitor switch position that differs from the expected state requires the pilot flying to select the condition when the associated caution light remains illuminated. The Landing Gear Indication annunciation that differs from the expected state requires the relief pilot to verify the condition when the associated caution light remains illuminated. This text is fictional and exists only to give the prototype realistic volume and structure.

During a maintenance-requested ground run, both pilots should verify the Hydraulic System B indication when the associated caution light remains illuminated. If the Auxiliary Power Unit is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance. If the Stall Warning is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. During cruise, both pilots should confirm the Cabin Pressure Controller status message if the indication does not stabilize within the sample interval. The Autobrake Selector selector position is expected to read within the sample range of 79 to 88 units during takeoff.

**CAUTION:** Refer to the related topic for additional sample context.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Center Tank Pumps annunciation        | 91 units     | Refer to related topic |
| Autopilot Channel A selector position | 67 units     | Refer to related topic |
| Cargo Smoke Detection indication      | 72 units     | Advisory only          |
| Speedbrake Handle status message      | 71 units     | Advisory only          |

**NOTE:** During approach, the Captain should brief the Probe Heat annunciation if the indication does not stabilize within the sample interval.

**03.50.5 Verification: Speedbrake Handle**

If the Autopilot Channel B is inoperative, continue cruise only after the Captain has reviewed the associated sample guidance. The Cargo Smoke Detection indication that differs from the expected state requires the relief pilot to brief the condition when the associated caution light remains illuminated. If the Engine Anti-Ice is inoperative, continue engine start only after both pilots has reviewed the associated sample guidance. The pilot monitoring will monitor any change in the Auxiliary Power Unit indication and advise the other pilot once the checklist item is complete. If the Engine Anti-Ice is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance.

**NOTE:** The Thrust Reverser advisory that differs from the expected state requires the pilot flying to record the condition when the associated caution light remains illuminated. The Ground Proximity Monitor indication that differs from the expected state requires the pilot flying to select the condition when operating at a sample station without ground power.

| Condition                          | Sample value | Remarks       |
|------------------------------------|--------------|---------------|
| Thrust Reverser status message     | 83 units     | Advisory only |
| Hydraulic System A indication      | 35 units     | Advisory only |
| Brake Temperature Monitor advisory | 22 units     | Advisory only |

This text is fictional and exists only to give the prototype realistic volume and structure. The Autothrottle indication that differs from the expected state requires both pilots to cross-check the condition unless directed otherwise by the Sample Operations Center. This text is fictional and exists only to give the prototype realistic volume and structure. During approach, both pilots should record the Standby Hydraulic annunciation when conditions permit. The wording here is placeholder content shaped like a procedure, not a procedure.

**CAUTION:** The first officer will monitor any change in the Landing Gear Indication quantity display and advise the other pilot when conditions permit. During descent, both pilots should verify the Primary Electrical Bus selector position when the associated caution light remains illuminated.

| Condition                                   | Sample value | Remarks                |
|---------------------------------------------|--------------|------------------------|
| Hydraulic System A switch position          | 7 units      | Monitor                |
| Cockpit Voice Recorder selector position    | 66 units     | Refer to related topic |
| Flight Management Computer quantity display | 47 units     | Refer to related topic |
| Engine Anti-Ice selector position           | 65 units     | Refer to related topic |
| Traffic Advisory Display selector position  | 89 units     | Advisory only          |
| Bleed Air Supply quantity display           | 40 units     | Monitor                |
| Transponder quantity display                | 53 units     | Monitor                |

If the Traffic Advisory Display is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance. The captain will announce any change in the Center Tank Pumps indication and advise the other pilot unless directed otherwise by the Sample Operations Center. The Autopilot Channel B annunciation that differs from the expected state requires the pilot flying to cross-check the condition before the next phase of flight.

### 03.50.6 Checklist: Speedbrake Handle

The Fuel Crossfeed switch position is expected to read within the sample range of 84 to 88 units during engine start. During cruise, the Captain should select the Cargo Smoke Detection selector position once the checklist item is complete. The Center Tank Pumps annunciation that differs from the expected state requires the pilot monitoring to brief the condition once the checklist item is complete.

**NOTE:** The relief pilot will monitor any change in the Ground Proximity Monitor status message and advise the other pilot when conditions permit.

- The Hydraulic System A advisory that differs from the expected state requires the relief pilot to select the condition once the checklist item is complete.
- The Fire Detection Loop indication is expected to read within the sample range of 41 to 50 units during cruise.
- During cruise, the relief pilot should cross-check the Speedbrake Handle quantity display unless directed otherwise by the Sample Operations Center.
- Refer to the related topic for additional sample context.

- The Traffic Advisory Display annunciation that differs from the expected state requires both pilots to cross-check the condition when the associated caution light remains illuminated.
- Refer to the related topic for additional sample context.

During landing, the pilot flying should announce the Pack Temperature Control switch position once the checklist item is complete. The Autopilot Channel A switch position is expected to read within the sample range of 6 to 9 units during preflight. If the Pack Temperature Control is inoperative, continue preflight only after the pilot monitoring has reviewed the associated sample guidance. During landing, the Captain should record the Autopilot Channel A advisory when operating at a sample station without ground power. During a maintenance-requested ground run, the pilot flying should select the Standby Instruments quantity display when conditions permit.

**NOTE:** The Auxiliary Power Unit indication is expected to read within the sample range of 28 to 39 units during a diversion.

**CAUTION:** If the Autothrottle is inoperative, continue a maintenance-requested ground run only after the Captain has reviewed the associated sample guidance.

**NOTE:** Both pilots will confirm any change in the Stall Warning status message and advise the other pilot before the next phase of flight. The wording here is placeholder content shaped like a procedure, not a procedure.

| Challenge                  | Response    |
|----------------------------|-------------|
| Flight Management Computer | On          |
| Window Heat                | Set         |
| Cockpit Voice Recorder     | Set         |
| Stall Warning              | Armed       |
| Auxiliary Power Unit       | As required |
| Nosewheel Steering         | Armed       |
| Standby Instruments        | Off         |

03.50.7 Verification: Autothrottle

The first officer will cross-check any change in the Stall Warning advisory and advise the other pilot before the next phase of flight. During cruise, the pilot flying should select the Brake Temperature Monitor status message before the next phase of flight. During a diversion, the First Officer should verify the Autopilot Channel A advisory if the indication does not stabilize within the sample interval. During engine start, the First Officer should monitor the Standby Hydraulic annunciation once the checklist item is complete. The wording here is placeholder content shaped like a procedure, not a procedure. During landing, the pilot flying should verify the Hydraulic System B selector position if a discrepancy is observed.

**CAUTION:** During a maintenance-requested ground run, the pilot monitoring should record the Landing Gear Indication advisory if a discrepancy is observed.

- The Auxiliary Power Unit advisory that differs from the expected state requires the First Officer to confirm the condition if the indication does not stabilize within the sample interval.
- Refer to the related topic for additional sample context.
- During taxi, the Captain should record the Cabin Pressure Controller advisory before the next phase of flight.
- The Landing Gear Indication quantity display that differs from the expected state requires the relief pilot to cross-check the condition when the associated caution light remains illuminated.
- The Autopilot Channel B status message is expected to read within the sample range of 43 to 46 units during an extended ground delay.

- If the Fire Detection Loop is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance.
- The first officer will record any change in the Hydraulic System A annunciation and advise the other pilot once the checklist item is complete.
- During landing, the Captain should cross-check the Weather Radar annunciation before the next phase of flight.
- During preflight, the relief pilot should cross-check the Transponder advisory if the indication does not stabilize within the sample interval.
- If the Hydraulic System B is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance.

**NOTE:** During a turnaround, the pilot monitoring should brief the Cabin Pressure Controller advisory if a discrepancy is observed.

Both pilots will select any change in the Traffic Advisory Display quantity display and advise the other pilot before the next phase of flight. The pilot monitoring will announce any change in the Fuel Crossfeed switch position and advise the other pilot if the indication does not stabilize within the sample interval. If the Cockpit Voice Recorder is inoperative, continue takeoff only after the First Officer has reviewed the associated sample guidance.

| Challenge                  | Response    |
|----------------------------|-------------|
| Oxygen Distribution        | Armed       |
| Autopilot Channel A        | Set         |
| Flight Management Computer | Armed       |
| Brake Temperature Monitor  | As required |
| Cargo Smoke Detection      | Checked     |
| Transponder                | Verified    |
| Cargo Smoke Detection      | Off         |
| Traffic Advisory Display   | Checked     |

**03.50.8 Crew Coordination: Center Tank Pumps**

During cruise, the Captain should select the Hydraulic System B indication if a discrepancy is observed. The pilot flying will confirm any change in the Flight Management Computer indication and advise the other pilot unless directed otherwise by the Sample Operations Center. During a maintenance-requested ground run, the pilot monitoring should confirm the Flap Position Indication advisory if a discrepancy is observed. The pilot flying will record any change in the Auxiliary Power Unit switch position and advise the other pilot when conditions permit.

- If the Oxygen Distribution is inoperative, continue preflight only after the Captain has reviewed the associated sample guidance.
- During parking, the relief pilot should monitor the Standby Hydraulic switch position when the associated caution light remains illuminated.
- The Weather Radar annunciation that differs from the expected state requires both pilots to record the condition if the indication does not stabilize within the sample interval.
- If the Traffic Advisory Display is inoperative, continue approach only after both pilots has reviewed the associated sample guidance.
- Refer to the related topic for additional sample context.

**CAUTION:** The pilot monitoring will confirm any change in the Autopilot Channel A switch position and advise the other pilot when conditions permit. Refer to the related topic for additional sample context.

| Condition                              | Sample value | Remarks                |
|----------------------------------------|--------------|------------------------|
| Autopilot Channel B indication         | 65 units     | Refer to related topic |
| Traffic Advisory Display advisory      | 43 units     | Monitor                |
| Standby Instruments switch position    | 19 units     | Refer to related topic |
| Auxiliary Power Unit annunciation      | 46 units     | Normal                 |
| Cargo Smoke Detection quantity display | 72 units     | Refer to related topic |
| Wing Anti-Ice status message           | 89 units     | Normal                 |
| Center Tank Pumps indication           | 79 units     | Advisory only          |

**CAUTION:** Values in this manual are invented and must not be used for any operational purpose. If the Center Tank Pumps is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance.

| Condition                              | Sample value | Remarks |
|----------------------------------------|--------------|---------|
| Cargo Smoke Detection quantity display | 44 units     | Monitor |
| Autopilot Channel A switch position    | 70 units     | Normal  |
| Speedbrake Handle advisory             | 75 units     | Normal  |

The Autopilot Channel A indication that differs from the expected state requires the First Officer to monitor the condition before the next phase of flight. Refer to the related topic for additional sample context. The Probe Heat switch position that differs from the expected state requires the relief pilot to confirm the condition before the next phase of flight. The Wing Anti-Ice indication is expected to read within the sample range of 97 to 107 units during cruise.

During an extended ground delay, the Captain should verify the Landing Gear Indication selector position when conditions permit. The Wing Anti-Ice status message is expected to read within the sample range of 26 to 34 units during a diversion. The Window Heat indication that differs from the expected state requires both pilots to announce the condition when operating at a sample station without ground power. During parking, the Captain should monitor the Auxiliary Power Unit selector position before the next phase of flight. If the Weather Radar is inoperative, continue a turnaround only after both pilots has reviewed the associated sample guidance.

| Challenge                | Response |
|--------------------------|----------|
| Flap Position Indication | Off      |
| Autopilot Channel A      | Checked  |
| Oxygen Distribution      | Set      |
| Probe Heat               | On       |
| Probe Heat               | Set      |
| Standby Instruments      | Armed    |
| Wing Anti-Ice            | Checked  |
| Speedbrake Handle        | Armed    |
| Traffic Advisory Display | Verified |
| Standby Instruments      | Verified |
| Transponder              | Off      |
| Oxygen Distribution      | Verified |

### 03.50.9 Crew Coordination: Landing Gear Indication



The pilot monitoring will verify any change in the Flap Position Indication annunciation and advise the other pilot if the indication does not stabilize within the sample interval. The wording here is placeholder content shaped like a procedure, not a procedure. If the Autopilot Channel B is inoperative, continue approach only after the Captain has reviewed the associated sample guidance.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Landing Gear Indication switch position  | 33 units     | Refer to related topic |
| Wing Anti-Ice indication                 | 28 units     | Normal                 |
| Transponder quantity display             | 77 units     | Monitor                |
| Ground Proximity Monitor indication      | 75 units     | Normal                 |
| Pack Temperature Control switch position | 44 units     | Normal                 |
| Traffic Advisory Display switch position | 17 units     | Advisory only          |
| Hydraulic System A status message        | 25 units     | Advisory only          |

The Weather Radar switch position that differs from the expected state requires the relief pilot to verify the condition before the next phase of flight. The wording here is placeholder content shaped like a procedure, not a procedure. The Transponder advisory that differs from the expected state requires the Captain to record the condition if a discrepancy is observed. If the Stall Warning is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance.

| Condition                                   | Sample value | Remarks                |
|---------------------------------------------|--------------|------------------------|
| Ground Proximity Monitor annunciation       | 95 units     | Normal                 |
| Autopilot Channel A selector position       | 1 units      | Refer to related topic |
| Nosewheel Steering quantity display         | 78 units     | Monitor                |
| Standby Hydraulic selector position         | 34 units     | Refer to related topic |
| Flight Management Computer quantity display | 27 units     | Advisory only          |

**NOTE:** The Autopilot Channel A switch position is expected to read within the sample range of 26 to 30 units during preflight.

### 03.50.10 Checklist: Autopilot Channel B

Refer to the related topic for additional sample context. During preflight, the pilot monitoring should announce the Weather Radar selector position when the associated caution light remains illuminated. The pilot monitoring will brief any change in the Nosewheel Steering switch position and advise the other pilot when operating at a sample station without ground power. During landing, the Captain should brief the Standby Instruments switch position when the associated caution light remains illuminated. During approach, both pilots should cross-check the Brake Temperature Monitor selector position if the indication does not stabilize within the sample interval.

**NOTE:** During a turnaround, the pilot monitoring should confirm the Oxygen Distribution indication if the indication does not stabilize within the sample interval. If the Bleed Air Supply is inoperative, continue a diversion only after the relief pilot has reviewed the associated sample guidance.

The Landing Gear Indication quantity display is expected to read within the sample range of 88 to 93 units during a maintenance-requested ground run. The wording here is placeholder content shaped like a procedure, not a procedure. The Autothrottle indication is expected to read within the sample range of 94 to 98 units during parking. If the Speedbrake Handle is inoperative, continue descent only after both pilots has reviewed the associated sample guidance.

During a maintenance-requested ground run, the First Officer should brief the Flight Management Computer advisory before the next phase of flight. The Engine Anti-Ice switch position that differs from the expected state requires the pilot monitoring to confirm the condition when operating at a sample station without ground power. The Probe Heat

selector position is expected to read within the sample range of 61 to 69 units during preflight.

**CAUTION:** If the Engine Anti-Ice is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance.

**NOTE:** The first officer will announce any change in the Bleed Air Supply advisory and advise the other pilot when operating at a sample station without ground power.

The Hydraulic System B indication is expected to read within the sample range of 39 to 43 units during a diversion. If the Stall Warning is inoperative, continue climb only after the pilot flying has reviewed the associated sample guidance. The captain will brief any change in the Weather Radar annunciation and advise the other pilot once the checklist item is complete. During taxi, the pilot monitoring should brief the Cockpit Voice Recorder advisory unless directed otherwise by the Sample Operations Center.

**NOTE:** During takeoff, the pilot flying should confirm the Autobrake Selector indication unless directed otherwise by the Sample Operations Center.

The Ground Proximity Monitor status message is expected to read within the sample range of 98 to 105 units during cruise. If the Primary Electrical Bus is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance. The Pack Temperature Control selector position is expected to read within the sample range of 72 to 79 units during cruise. During a turnaround, the pilot monitoring should brief the Flight Management Computer advisory once the checklist item is complete. During an extended ground delay, the pilot monitoring should cross-check the Window Heat indication when the associated caution light remains illuminated.

### **03.50.11 Briefing: Landing Gear Indication**

The wording here is placeholder content shaped like a procedure, not a procedure. The Center Tank Pumps advisory is expected to read within the sample range of 76 to 86 units during parking. The Traffic Advisory Display selector position that differs from the expected state requires the First Officer to cross-check the condition when operating at a sample station without ground power. If the Engine Anti-Ice is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance. The relief pilot will brief any change in the Center Tank Pumps selector position and advise the other pilot when conditions permit. If the Pack Temperature Control is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance.

During taxi, the Captain should brief the Fire Detection Loop switch position if a discrepancy is observed. If the Hydraulic System A is inoperative, continue approach only after the relief pilot has reviewed the associated sample guidance. Refer to the related topic for additional sample context. During a diversion, the pilot monitoring should cross-check the Autothrottle advisory when conditions permit.

**CAUTION:** Both pilots will verify any change in the Traffic Advisory Display status message and advise the other pilot unless directed otherwise by the Sample Operations Center. The pilot monitoring will cross-check any change in the Traffic Advisory Display indication and advise the other pilot unless directed otherwise by the Sample Operations Center.

The Nosewheel Steering advisory is expected to read within the sample range of 48 to 53 units during a diversion. The Fuel Crossfeed indication is expected to read within the sample range of 7 to 18 units during a diversion. The Hydraulic System B status message that differs from the expected state requires both pilots to verify the condition once the checklist item is complete. The Standby Instruments status message is expected to read within the sample range of 40 to 50 units during takeoff. During parking, both pilots should monitor the Cabin Pressure Controller annunciation once the checklist item is complete.

During landing, the pilot monitoring should verify the Cabin Pressure Controller indication when operating at a sample station without ground power. The Autothrottle indication that differs from the expected state requires the relief pilot to announce the condition when operating at a sample station without ground power. This text is fictional and exists only to give the prototype realistic volume and structure. See 09.30.14 Weather Radar Limits Display.

**CAUTION:** During a turnaround, both pilots should brief the Flight Management Computer status message when operating at a sample station without ground power. Refer to the related topic for additional sample context.

| Challenge                 | Response |
|---------------------------|----------|
| Center Tank Pumps         | On       |
| Hydraulic System A        | Closed   |
| Autopilot Channel B       | On       |
| Autobrake Selector        | Set      |
| Cabin Pressure Controller | Armed    |
| Bleed Air Supply          | Off      |
| Cabin Pressure Controller | Checked  |
| Fuel Crossfeed            | Checked  |
| Fire Detection Loop       | Checked  |
| Engine Anti-Ice           | On       |
| Window Heat               | Closed   |

**03.50.12 Verification: Autopilot Channel B**

The Ground Proximity Monitor indication that differs from the expected state requires both pilots to record the condition when operating at a sample station without ground power. The first officer will brief any change in the Cockpit Voice Recorder indication and advise the other pilot if a discrepancy is observed. During climb, both pilots should cross-check the Pack Temperature Control advisory once the checklist item is complete.

**NOTE:** This text is fictional and exists only to give the prototype realistic volume and structure.

- Values in this manual are invented and must not be used for any operational purpose.
- During cruise, the pilot monitoring should verify the Cargo Smoke Detection annunciation if a discrepancy is observed.
- The Autothrottle quantity display is expected to read within the sample range of 74 to 77 units during engine start.
- The first officer will record any change in the Cabin Pressure Controller quantity display and advise the other pilot when conditions permit.
- The Hydraulic System B indication that differs from the expected state requires the pilot monitoring to confirm the condition when the associated caution light remains illuminated.

| Condition                              | Sample value | Remarks                |
|----------------------------------------|--------------|------------------------|
| Fuel Crossfeed quantity display        | 94 units     | Advisory only          |
| Probe Heat advisory                    | 53 units     | Monitor                |
| Bleed Air Supply status message        | 21 units     | Refer to related topic |
| Brake Temperature Monitor annunciation | 40 units     | Monitor                |

**CAUTION:** The Fire Detection Loop switch position is expected to read within the sample range of 66 to 78 units during an extended ground delay. Both pilots will brief any change in the Engine Anti-Ice indication and advise the other pilot if the indication does not stabilize within the sample interval.

The wording here is placeholder content shaped like a procedure, not a procedure. The Thrust Reverser selector position is expected to read within the sample range of 77 to 81 units during a diversion. The Standby Hydraulic switch position is expected to read within the sample range of 64 to 72 units during taxi. The Window Heat status message is expected to read within the sample range of 41 to 47 units during climb.

- The relief pilot will monitor any change in the Autothrottle status message and advise the other pilot when conditions permit.
- The Fire Detection Loop status message is expected to read within the sample range of 27 to 38 units during a diversion.
- If the Autopilot Channel B is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance.
- If the Fuel Crossfeed is inoperative, continue approach only after the pilot monitoring has reviewed the associated sample guidance.
- The pilot monitoring will confirm any change in the Center Tank Pumps annunciation and advise the other pilot before the next phase of flight.
- If the Fire Detection Loop is inoperative, continue a diversion only after both pilots has reviewed the associated sample guidance.

| Challenge                | Response |
|--------------------------|----------|
| Autothrottle             | Set      |
| Probe Heat               | Set      |
| Thrust Reverser          | Armed    |
| Cockpit Voice Recorder   | Off      |
| Traffic Advisory Display | Checked  |
| Hydraulic System B       | Closed   |
| Standby Hydraulic        | Verified |
| Thrust Reverser          | On       |
| Primary Electrical Bus   | Off      |

03.50.13 Checklist: Nosewheel Steering

During cruise, the First Officer should monitor the Flap Position Indication advisory before the next phase of flight. The Autobrake Selector status message is expected to read within the sample range of 47 to 52 units during landing. During approach, the First Officer should confirm the Pack Temperature Control quantity display when the associated caution light remains illuminated.

**CAUTION:** The Autobrake Selector switch position that differs from the expected state requires the relief pilot to cross-check the condition when conditions permit. If the Speedbrake Handle is inoperative, continue engine start only after the pilot flying has reviewed the associated sample guidance.

The wording here is placeholder content shaped like a procedure, not a procedure. The Autothrottle switch position that differs from the expected state requires the pilot monitoring to announce the condition unless directed otherwise by the Sample Operations Center. During an extended ground delay, the relief pilot should brief the Hydraulic System A selector position if the indication does not stabilize within the sample interval. This text is fictional and exists only to give the prototype realistic volume and structure.

The Brake Temperature Monitor advisory that differs from the expected state requires both pilots to record the condition if a discrepancy is observed. The Speedbrake Handle selector position is expected to read within the sample range of 9 to 14 units during landing. If the Standby Instruments is inoperative, continue a maintenance-requested ground run only after the pilot monitoring has reviewed the associated sample guidance.

| Condition                                    | Sample value | Remarks                |
|----------------------------------------------|--------------|------------------------|
| Fuel Crossfeed selector position             | 95 units     | Refer to related topic |
| Flight Management Computer selector position | 85 units     | Normal                 |

|                              |          |                        |
|------------------------------|----------|------------------------|
| Autothrottle switch position | 72 units | Advisory only          |
| Stall Warning indication     | 87 units | Refer to related topic |
| Window Heat indication       | 46 units | Monitor                |

**CAUTION:** The Flight Management Computer selector position is expected to read within the sample range of 89 to 97 units during engine start.

**NOTE:** If the Hydraulic System B is inoperative, continue taxi only after the Captain has reviewed the associated sample guidance.

During a diversion, the pilot flying should announce the Fuel Crossfeed annunciation once the checklist item is complete. During climb, the relief pilot should monitor the Flight Management Computer selector position if a discrepancy is observed. The Probe Heat switch position that differs from the expected state requires both pilots to confirm the condition when the associated caution light remains illuminated.

The Stall Warning status message that differs from the expected state requires the relief pilot to announce the condition if a discrepancy is observed. If the Ground Proximity Monitor is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance. If the Stall Warning is inoperative, continue approach only after the Captain has reviewed the associated sample guidance. If the Flight Management Computer is inoperative, continue engine start only after the pilot flying has reviewed the associated sample guidance. The Cockpit Voice Recorder selector position is expected to read within the sample range of 61 to 67 units during cruise. During an extended ground delay, both pilots should cross-check the Fire Detection Loop switch position when conditions permit.

| Challenge                | Response    |
|--------------------------|-------------|
| Traffic Advisory Display | Checked     |
| Stall Warning            | Set         |
| Engine Anti-Ice          | Set         |
| Landing Gear Indication  | Set         |
| Engine Anti-Ice          | As required |
| Fuel Crossfeed           | Armed       |
| Oxygen Distribution      | Checked     |
| Speedbrake Handle        | Armed       |

**03.50.14 Callouts: Brake Temperature Monitor**

If the Traffic Advisory Display is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance. If the Cockpit Voice Recorder is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance. The Stall Warning selector position that differs from the expected state requires the Captain to select the condition when operating at a sample station without ground power. The Primary Electrical Bus annunciation that differs from the expected state requires the relief pilot to select the condition when operating at a sample station without ground power. The Cabin Pressure Controller annunciation that differs from the expected state requires the relief pilot to monitor the condition if a discrepancy is observed.

The Ground Proximity Monitor annunciation that differs from the expected state requires both pilots to record the condition once the checklist item is complete. The Fire Detection Loop quantity display that differs from the expected state requires the relief pilot to select the condition when the associated caution light remains illuminated. The Standby Instruments annunciation is expected to read within the sample range of 68 to 77 units during approach. The first officer will verify any change in the Window Heat annunciation and advise the other pilot if the indication does not stabilize within the sample interval.

| Condition | Sample value | Remarks |
|-----------|--------------|---------|
|-----------|--------------|---------|

|                                         |          |                        |
|-----------------------------------------|----------|------------------------|
| Ground Proximity Monitor indication     | 94 units | Monitor                |
| Probe Heat quantity display             | 45 units | Refer to related topic |
| Stall Warning quantity display          | 43 units | Normal                 |
| Probe Heat indication                   | 63 units | Advisory only          |
| Weather Radar advisory                  | 77 units | Normal                 |
| Ground Proximity Monitor status message | 77 units | Monitor                |

The first officer will brief any change in the Flap Position Indication status message and advise the other pilot if the indication does not stabilize within the sample interval. Refer to the related topic for additional sample context. Values in this manual are invented and must not be used for any operational purpose. The relief pilot will brief any change in the Transponder status message and advise the other pilot when operating at a sample station without ground power. If the Speedbrake Handle is inoperative, continue climb only after both pilots has reviewed the associated sample guidance.

**CAUTION:** During an extended ground delay, both pilots should verify the Autothrottle indication before the next phase of flight.

**NOTE:** The Center Tank Pumps status message that differs from the expected state requires the pilot flying to confirm the condition when operating at a sample station without ground power. The Transponder advisory is expected to read within the sample range of 92 to 104 units during cruise.

**CAUTION:** Values in this manual are invented and must not be used for any operational purpose.

### 03.50.15 Checklist: Autopilot Channel A

If the Speedbrake Handle is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance. The relief pilot will monitor any change in the Flight Management Computer selector position and advise the other pilot when operating at a sample station without ground power. Refer to the related topic for additional sample context.

During a diversion, the pilot monitoring should monitor the Oxygen Distribution annunciation when conditions permit. The Thrust Reverser selector position is expected to read within the sample range of 44 to 47 units during engine start. Refer to the related topic for additional sample context. The Stall Warning status message that differs from the expected state requires the pilot flying to confirm the condition once the checklist item is complete. This text is fictional and exists only to give the prototype realistic volume and structure.

If the Stall Warning is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance. The Engine Anti-Ice quantity display that differs from the expected state requires the Captain to monitor the condition if a discrepancy is observed. During engine start, the First Officer should verify the Thrust Reverser status message when conditions permit. Values in this manual are invented and must not be used for any operational purpose. The pilot flying will select any change in the Landing Gear Indication selector position and advise the other pilot if the indication does not stabilize within the sample interval.

**CAUTION:** The Autothrottle status message that differs from the expected state requires the First Officer to confirm the condition when operating at a sample station without ground power.

During a maintenance-requested ground run, the relief pilot should cross-check the Autothrottle switch position if a discrepancy is observed. If the Pack Temperature Control is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance. The Fuel Crossfeed indication that differs from the expected state requires the First Officer to record the condition unless directed otherwise by the Sample Operations Center. Refer to the related topic for additional sample context. If the Cargo Smoke Detection is inoperative, continue approach only after the Captain has reviewed the associated sample guidance. During descent, both pilots should monitor the Fuel Crossfeed indication unless directed otherwise by the Sample Operations Center.

**NOTE:** The wording here is placeholder content shaped like a procedure, not a procedure.



The pilot flying will brief any change in the Primary Electrical Bus advisory and advise the other pilot unless directed otherwise by the Sample Operations Center. During approach, the First Officer should record the Hydraulic System B indication unless directed otherwise by the Sample Operations Center. Both pilots will record any change in the Brake Temperature Monitor indication and advise the other pilot if the indication does not stabilize within the sample interval. The Brake Temperature Monitor advisory that differs from the expected state requires both pilots to verify the condition when operating at a sample station without ground power. The pilot flying will cross-check any change in the Pack Temperature Control status message and advise the other pilot when conditions permit. The Nosewheel Steering switch position is expected to read within the sample range of 11 to 15 units during approach.

This text is fictional and exists only to give the prototype realistic volume and structure. The Fuel Crossfeed quantity display that differs from the expected state requires both pilots to cross-check the condition once the checklist item is complete. During approach, both pilots should record the Bleed Air Supply switch position unless directed otherwise by the Sample Operations Center.

- During a maintenance-requested ground run, the relief pilot should cross-check the Flap Position Indication annunciation if the indication does not stabilize within the sample interval.
- The Fire Detection Loop status message that differs from the expected state requires the relief pilot to announce the condition once the checklist item is complete.
- The Cabin Pressure Controller selector position is expected to read within the sample range of 78 to 81 units during climb.

### **03.50.16 Flow: Autopilot Channel A**

If the Cockpit Voice Recorder is inoperative, continue a diversion only after the relief pilot has reviewed the associated sample guidance. Both pilots will monitor any change in the Wing Anti-Ice annunciation and advise the other pilot once the checklist item is complete. The pilot flying will verify any change in the Transponder selector position and advise the other pilot when conditions permit. If the Bleed Air Supply is inoperative, continue engine start only after the relief pilot has reviewed the associated sample guidance. The Probe Heat advisory is expected to read within the sample range of 42 to 50 units during a turnaround. The Autopilot Channel A indication that differs from the expected state requires the pilot flying to select the condition unless directed otherwise by the Sample Operations Center.

**NOTE:** Values in this manual are invented and must not be used for any operational purpose.

The wording here is placeholder content shaped like a procedure, not a procedure. The pilot monitoring will select any change in the Flight Management Computer switch position and advise the other pilot before the next phase of flight. The relief pilot will announce any change in the Hydraulic System A quantity display and advise the other pilot when conditions permit. Refer to the related topic for additional sample context. Refer to the related topic for additional sample context.

- The pilot flying will confirm any change in the Stall Warning annunciation and advise the other pilot once the checklist item is complete.
- Values in this manual are invented and must not be used for any operational purpose.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- During engine start, both pilots should confirm the Thrust Reverser advisory once the checklist item is complete.
- The Autothrottle annunciation is expected to read within the sample range of 37 to 41 units during approach.
- Refer to the related topic for additional sample context.
- The Autothrottle annunciation is expected to read within the sample range of 56 to 60 units during cruise.

The Oxygen Distribution selector position that differs from the expected state requires the Captain to record the condition when conditions permit. The Flap Position Indication quantity display that differs from the expected state requires the pilot monitoring to verify the condition when conditions permit. The wording here is placeholder content

shaped like a procedure, not a procedure. During an extended ground delay, the Captain should confirm the Window Heat switch position when the associated caution light remains illuminated.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Hydraulic System B indication              | 98 units     | Normal                 |
| Fire Detection Loop status message         | 39 units     | Advisory only          |
| Pack Temperature Control selector position | 97 units     | Refer to related topic |

- During landing, the First Officer should select the Engine Anti-Ice indication if the indication does not stabilize within the sample interval.
- Both pilots will select any change in the Fire Detection Loop advisory and advise the other pilot unless directed otherwise by the Sample Operations Center.
- During an extended ground delay, both pilots should cross-check the Autopilot Channel A status message if the indication does not stabilize within the sample interval.
- If the Cargo Smoke Detection is inoperative, continue engine start only after both pilots has reviewed the associated sample guidance.
- The Bleed Air Supply advisory is expected to read within the sample range of 24 to 35 units during a maintenance-requested ground run.

Refer to the related topic for additional sample context. During a diversion, both pilots should brief the Bleed Air Supply annunciation if a discrepancy is observed. Values in this manual are invented and must not be used for any operational purpose. The Auxiliary Power Unit indication that differs from the expected state requires the Captain to verify the condition once the checklist item is complete. The Flap Position Indication quantity display is expected to read within the sample range of 17 to 24 units during cruise. The relief pilot will cross-check any change in the Bleed Air Supply status message and advise the other pilot unless directed otherwise by the Sample Operations Center.

## 03.60 Descent and Approach

### 03.60.1 Briefing: Probe Heat

During descent, the Captain should brief the Nosewheel Steering selector position when the associated caution light remains illuminated. The Landing Gear Indication indication is expected to read within the sample range of 59 to 63 units during engine start. Values in this manual are invented and must not be used for any operational purpose. The pilot flying will verify any change in the Center Tank Pumps status message and advise the other pilot unless directed otherwise by the Sample Operations Center.

- Values in this manual are invented and must not be used for any operational purpose.
- The Pack Temperature Control status message is expected to read within the sample range of 63 to 66 units during a diversion.
- The Hydraulic System A status message that differs from the expected state requires the pilot flying to record the condition before the next phase of flight.

**NOTE:** The wording here is placeholder content shaped like a procedure, not a procedure.

The Hydraulic System A indication is expected to read within the sample range of 56 to 62 units during climb. If the Weather Radar is inoperative, continue taxi only after the pilot flying has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. The pilot monitoring will confirm any change in the Fuel Crossfeed annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center.

**CAUTION:** The Standby Hydraulic selector position is expected to read within the sample range of 65 to 69 units during taxi. The Nosewheel Steering indication that differs from the expected state requires the pilot monitoring to confirm the condition when the associated caution light remains illuminated.

**NOTE:** The Landing Gear Indication switch position that differs from the expected state requires both pilots to monitor the condition before the next phase of flight. During a diversion, the relief pilot should select the Brake Temperature Monitor selector position before the next phase of flight.

| Challenge                | Response |
|--------------------------|----------|
| Ground Proximity Monitor | Off      |
| Window Heat              | Closed   |
| Primary Electrical Bus   | Off      |
| Nosewheel Steering       | Off      |
| Bleed Air Supply         | Verified |
| Flap Position Indication | Set      |
| Probe Heat               | On       |
| Autothrottle             | Closed   |
| Hydraulic System A       | Off      |
| Standby Hydraulic        | Verified |
| Engine Anti-Ice          | On       |

03.60.2 Checklist: Nosewheel Steering

The Probe Heat switch position that differs from the expected state requires the relief pilot to monitor the condition unless directed otherwise by the Sample Operations Center. The first officer will announce any change in the Pack Temperature Control indication and advise the other pilot when operating at a sample station without ground power. The Cockpit Voice Recorder selector position is expected to read within the sample range of 45 to 48 units during landing. The Wing Anti-Ice quantity display is expected to read within the sample range of 90 to 97 units during approach. The relief pilot will record any change in the Primary Electrical Bus indication and advise the other pilot if the indication does not stabilize within the sample interval. This text is fictional and exists only to give the prototype realistic volume and structure.

If the Ground Proximity Monitor is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance. The Ground Proximity Monitor status message that differs from the expected state requires the Captain to verify the condition once the checklist item is complete. Both pilots will record any change in the Weather Radar advisory and advise the other pilot when the associated caution light remains illuminated. The Fire Detection Loop selector position is expected to read within the sample range of 29 to 35 units during an extended ground delay.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Weather Radar advisory                   | 37 units     | Advisory only          |
| Cockpit Voice Recorder annunciation      | 19 units     | Advisory only          |
| Primary Electrical Bus selector position | 60 units     | Refer to related topic |

The captain will verify any change in the Wing Anti-Ice annunciation and advise the other pilot if a discrepancy is observed. If the Hydraulic System B is inoperative, continue taxi only after both pilots has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. Refer to the related topic for additional sample context.

**NOTE:** Both pilots will monitor any change in the Nosewheel Steering selector position and advise the other pilot if the indication does not stabilize within the sample interval. If the Autothrottle is inoperative, continue takeoff

only after the pilot monitoring has reviewed the associated sample guidance.

**NOTE:** If the Fire Detection Loop is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance. If the Flight Management Computer is inoperative, continue engine start only after both pilots has reviewed the associated sample guidance.

The Auxiliary Power Unit quantity display that differs from the expected state requires the First Officer to cross-check the condition once the checklist item is complete. During descent, the relief pilot should select the Thrust Reverser indication when the associated caution light remains illuminated. The Auxiliary Power Unit annunciation is expected to read within the sample range of 59 to 67 units during an extended ground delay. The first officer will select any change in the Landing Gear Indication selector position and advise the other pilot when the associated caution light remains illuminated.

The Auxiliary Power Unit status message is expected to read within the sample range of 80 to 89 units during descent. During climb, the pilot monitoring should select the Ground Proximity Monitor selector position when conditions permit. The Flight Management Computer switch position that differs from the expected state requires the pilot flying to confirm the condition once the checklist item is complete.

During takeoff, the pilot monitoring should brief the Ground Proximity Monitor annunciation when the associated caution light remains illuminated. If the Pack Temperature Control is inoperative, continue preflight only after the pilot monitoring has reviewed the associated sample guidance. The relief pilot will record any change in the Fire Detection Loop advisory and advise the other pilot when operating at a sample station without ground power. The Standby Instruments selector position that differs from the expected state requires the pilot monitoring to verify the condition if a discrepancy is observed. The wording here is placeholder content shaped like a procedure, not a procedure.

| Challenge                 | Response    |
|---------------------------|-------------|
| Autopilot Channel B       | On          |
| Traffic Advisory Display  | Closed      |
| Ground Proximity Monitor  | Off         |
| Autopilot Channel A       | Armed       |
| Speedbrake Handle         | As required |
| Engine Anti-Ice           | On          |
| Fuel Crossfeed            | Armed       |
| Weather Radar             | On          |
| Brake Temperature Monitor | Verified    |
| Bleed Air Supply          | On          |
| Bleed Air Supply          | On          |

**03.60.3 Flow: Thrust Reverser**

If the Fuel Crossfeed is inoperative, continue a diversion only after the pilot monitoring has reviewed the associated sample guidance. If the Fuel Crossfeed is inoperative, continue engine start only after both pilots has reviewed the associated sample guidance. The Hydraulic System B annunciation is expected to read within the sample range of 48 to 57 units during approach. The Center Tank Pumps switch position that differs from the expected state requires the pilot flying to verify the condition before the next phase of flight. This text is fictional and exists only to give the prototype realistic volume and structure.

| Condition                             | Sample value | Remarks       |
|---------------------------------------|--------------|---------------|
| Nosewheel Steering status message     | 27 units     | Normal        |
| Center Tank Pumps advisory            | 33 units     | Monitor       |
| Fire Detection Loop selector position | 62 units     | Advisory only |

|                                  |          |               |
|----------------------------------|----------|---------------|
| Cargo Smoke Detection indication | 60 units | Advisory only |
| Thrust Reverser switch position  | 16 units | Monitor       |

**CAUTION:** If the Auxiliary Power Unit is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance.

- During a maintenance-requested ground run, the relief pilot should confirm the Speedbrake Handle indication when conditions permit.
- The Cabin Pressure Controller switch position that differs from the expected state requires the Captain to confirm the condition once the checklist item is complete.
- The Cockpit Voice Recorder switch position is expected to read within the sample range of 7 to 14 units during takeoff.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- If the Cockpit Voice Recorder is inoperative, continue a maintenance-requested ground run only after the Captain has reviewed the associated sample guidance.

Both pilots will brief any change in the Pack Temperature Control switch position and advise the other pilot if the indication does not stabilize within the sample interval. The Flight Management Computer switch position that differs from the expected state requires the Captain to monitor the condition if a discrepancy is observed. The Oxygen Distribution status message that differs from the expected state requires the pilot flying to record the condition before the next phase of flight. Values in this manual are invented and must not be used for any operational purpose. If the Standby Instruments is inoperative, continue a turnaround only after both pilots has reviewed the associated sample guidance. The Autopilot Channel B advisory that differs from the expected state requires the relief pilot to announce the condition once the checklist item is complete.

| Challenge                | Response    |
|--------------------------|-------------|
| Oxygen Distribution      | On          |
| Hydraulic System A       | Closed      |
| Window Heat              | Checked     |
| Traffic Advisory Display | On          |
| Thrust Reverser          | As required |
| Autopilot Channel A      | As required |
| Nosewheel Steering       | Checked     |

**03.60.4 Callouts: Hydraulic System A**

If the Autopilot Channel B is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. If the Stall Warning is inoperative, continue parking only after the Captain has reviewed the associated sample guidance. Both pilots will verify any change in the Autothrottle status message and advise the other pilot when operating at a sample station without ground power. The pilot flying will verify any change in the Transponder quantity display and advise the other pilot once the checklist item is complete.

The pilot flying will record any change in the Flap Position Indication indication and advise the other pilot when conditions permit. During climb, the relief pilot should record the Auxiliary Power Unit indication once the checklist item is complete. If the Standby Hydraulic is inoperative, continue preflight only after both pilots has reviewed the associated sample guidance.

During cruise, both pilots should cross-check the Autothrottle selector position once the checklist item is complete. During preflight, the Captain should monitor the Flight Management Computer indication unless directed otherwise by

the Sample Operations Center. The Engine Anti-Ice selector position that differs from the expected state requires the pilot flying to cross-check the condition if the indication does not stabilize within the sample interval. If the Nosewheel Steering is inoperative, continue climb only after the Captain has reviewed the associated sample guidance. If the Nosewheel Steering is inoperative, continue a turnaround only after the First Officer has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose.

**NOTE:** The pilot flying will confirm any change in the Center Tank Pumps quantity display and advise the other pilot if a discrepancy is observed. The Hydraulic System A quantity display is expected to read within the sample range of 4 to 9 units during approach.

**NOTE:** The Window Heat indication is expected to read within the sample range of 92 to 100 units during cruise. If the Probe Heat is inoperative, continue preflight only after both pilots has reviewed the associated sample guidance.

During engine start, the Captain should select the Oxygen Distribution status message if the indication does not stabilize within the sample interval. The Brake Temperature Monitor switch position that differs from the expected state requires both pilots to confirm the condition when conditions permit. During a diversion, both pilots should select the Cabin Pressure Controller indication unless directed otherwise by the Sample Operations Center. If the Standby Hydraulic is inoperative, continue descent only after the First Officer has reviewed the associated sample guidance.

**NOTE:** If the Hydraulic System A is inoperative, continue a maintenance-requested ground run only after the pilot flying has reviewed the associated sample guidance. The pilot monitoring will select any change in the Autopilot Channel A advisory and advise the other pilot if the indication does not stabilize within the sample interval.

The Autopilot Channel A advisory is expected to read within the sample range of 41 to 49 units during descent. If the Engine Anti-Ice is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance. The pilot flying will select any change in the Fuel Crossfeed selector position and advise the other pilot before the next phase of flight. The Window Heat switch position is expected to read within the sample range of 82 to 86 units during engine start. The Nosewheel Steering switch position is expected to read within the sample range of 56 to 67 units during takeoff.

**CAUTION:** Values in this manual are invented and must not be used for any operational purpose. This text is fictional and exists only to give the prototype realistic volume and structure.

### 03.60.5 Callouts: Bleed Air Supply

During a maintenance-requested ground run, the Captain should brief the Transponder advisory if the indication does not stabilize within the sample interval. The Transponder advisory that differs from the expected state requires the Captain to cross-check the condition if the indication does not stabilize within the sample interval. During cruise, the Captain should announce the Cabin Pressure Controller status message unless directed otherwise by the Sample Operations Center.

The pilot monitoring will monitor any change in the Autopilot Channel A status message and advise the other pilot unless directed otherwise by the Sample Operations Center. The Flight Management Computer switch position that differs from the expected state requires the First Officer to confirm the condition before the next phase of flight. The Traffic Advisory Display quantity display is expected to read within the sample range of 2 to 6 units during approach. The Oxygen Distribution selector position is expected to read within the sample range of 77 to 82 units during a turnaround.

- During preflight, the pilot flying should brief the Cabin Pressure Controller annunciation unless directed otherwise by the Sample Operations Center.
- If the Ground Proximity Monitor is inoperative, continue climb only after the relief pilot has reviewed the associated sample guidance.
- If the Fire Detection Loop is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance.



- The Autobrake Selector advisory is expected to read within the sample range of 67 to 70 units during a maintenance-requested ground run.
- The first officer will confirm any change in the Hydraulic System A indication and advise the other pilot when conditions permit.
- The wording here is placeholder content shaped like a procedure, not a procedure.

**CAUTION:** If the Autothrottle is inoperative, continue climb only after the pilot flying has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure.

During a diversion, the Captain should cross-check the Brake Temperature Monitor quantity display if a discrepancy is observed. The relief pilot will verify any change in the Transponder annunciation and advise the other pilot before the next phase of flight. If the Stall Warning is inoperative, continue approach only after the Captain has reviewed the associated sample guidance. The Cargo Smoke Detection indication is expected to read within the sample range of 58 to 62 units during landing. The Ground Proximity Monitor status message that differs from the expected state requires the pilot monitoring to announce the condition unless directed otherwise by the Sample Operations Center.

The Flap Position Indication annunciation is expected to read within the sample range of 90 to 101 units during cruise. Refer to the related topic for additional sample context. This text is fictional and exists only to give the prototype realistic volume and structure. The Auxiliary Power Unit indication is expected to read within the sample range of 77 to 83 units during preflight. This text is fictional and exists only to give the prototype realistic volume and structure. The Thrust Reverser quantity display that differs from the expected state requires the Captain to record the condition if a discrepancy is observed.

If the Autopilot Channel A is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance. Both pilots will confirm any change in the Landing Gear Indication switch position and advise the other pilot if the indication does not stabilize within the sample interval. The Flap Position Indication advisory that differs from the expected state requires both pilots to select the condition once the checklist item is complete. The first officer will brief any change in the Wing Anti-Ice quantity display and advise the other pilot once the checklist item is complete. The Flap Position Indication annunciation is expected to read within the sample range of 95 to 98 units during a maintenance-requested ground run.

**NOTE:** The Stall Warning switch position is expected to read within the sample range of 57 to 66 units during approach. The Hydraulic System B status message is expected to read within the sample range of 76 to 81 units during approach.

The wording here is placeholder content shaped like a procedure, not a procedure. During a turnaround, the Captain should confirm the Autothrottle advisory unless directed otherwise by the Sample Operations Center. The Oxygen Distribution selector position is expected to read within the sample range of 3 to 10 units during parking. During takeoff, the pilot monitoring should cross-check the Nosewheel Steering status message if a discrepancy is observed. Values in this manual are invented and must not be used for any operational purpose. The wording here is placeholder content shaped like a procedure, not a procedure.

### **03.60.6 Briefing: Fire Detection Loop**

During approach, the First Officer should select the Auxiliary Power Unit annunciation before the next phase of flight. During takeoff, the relief pilot should brief the Thrust Reverser status message if a discrepancy is observed. If the Cockpit Voice Recorder is inoperative, continue takeoff only after the First Officer has reviewed the associated sample guidance. The Hydraulic System A annunciation that differs from the expected state requires the Captain to record the condition unless directed otherwise by the Sample Operations Center. The relief pilot will select any change in the Bleed Air Supply annunciation and advise the other pilot if a discrepancy is observed. If the Speedbrake Handle is inoperative, continue a diversion only after the pilot monitoring has reviewed the associated sample guidance.

If the Weather Radar is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance. The pilot monitoring will cross-check any change in the Nosewheel Steering advisory and advise the other

pilot when operating at a sample station without ground power. The relief pilot will record any change in the Hydraulic System B switch position and advise the other pilot when operating at a sample station without ground power. The Cargo Smoke Detection annunciation is expected to read within the sample range of 23 to 34 units during climb. During climb, the Captain should monitor the Landing Gear Indication selector position unless directed otherwise by the Sample Operations Center. During preflight, the Captain should record the Primary Electrical Bus annunciation before the next phase of flight.

**NOTE:** During engine start, the pilot flying should brief the Engine Anti-Ice quantity display before the next phase of flight.

During preflight, the pilot flying should verify the Weather Radar quantity display if a discrepancy is observed. The Engine Anti-Ice quantity display that differs from the expected state requires the pilot monitoring to announce the condition unless directed otherwise by the Sample Operations Center. The captain will announce any change in the Primary Electrical Bus indication and advise the other pilot when the associated caution light remains illuminated. The Fuel Crossfeed advisory is expected to read within the sample range of 50 to 53 units during parking.

- The wording here is placeholder content shaped like a procedure, not a procedure.
- Both pilots will verify any change in the Weather Radar annunciation and advise the other pilot when operating at a sample station without ground power.
- Refer to the related topic for additional sample context.
- The relief pilot will verify any change in the Hydraulic System B annunciation and advise the other pilot before the next phase of flight.
- Both pilots will announce any change in the Standby Hydraulic annunciation and advise the other pilot once the checklist item is complete.
- If the Traffic Advisory Display is inoperative, continue a diversion only after both pilots has reviewed the associated sample guidance.

During preflight, the First Officer should confirm the Hydraulic System B quantity display when operating at a sample station without ground power. If the Nosewheel Steering is inoperative, continue takeoff only after the First Officer has reviewed the associated sample guidance. The Hydraulic System A status message that differs from the expected state requires the relief pilot to brief the condition when the associated caution light remains illuminated.

**NOTE:** The pilot flying will cross-check any change in the Window Heat switch position and advise the other pilot if the indication does not stabilize within the sample interval. If the Fire Detection Loop is inoperative, continue approach only after the relief pilot has reviewed the associated sample guidance.

The Hydraulic System B advisory that differs from the expected state requires the pilot monitoring to record the condition when conditions permit. The Cabin Pressure Controller advisory that differs from the expected state requires the Captain to cross-check the condition when the associated caution light remains illuminated. If the Landing Gear Indication is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance. The captain will confirm any change in the Window Heat indication and advise the other pilot when operating at a sample station without ground power. The Auxiliary Power Unit advisory that differs from the expected state requires the relief pilot to select the condition if the indication does not stabilize within the sample interval. Both pilots will confirm any change in the Oxygen Distribution switch position and advise the other pilot when conditions permit.

**CAUTION:** The Flight Management Computer switch position that differs from the expected state requires both pilots to cross-check the condition unless directed otherwise by the Sample Operations Center. During takeoff, both pilots should monitor the Transponder indication unless directed otherwise by the Sample Operations Center.

### 03.60.7 Verification: Center Tank Pumps

If the Auxiliary Power Unit is inoperative, continue engine start only after the Captain has reviewed the associated sample guidance. The Nosewheel Steering quantity display is expected to read within the sample range of 27 to 35 units during parking. During climb, the First Officer should select the Weather Radar status message unless directed otherwise by the Sample Operations Center.

**NOTE:** During parking, the First Officer should announce the Hydraulic System B advisory once the checklist item is complete. If the Engine Anti-Ice is inoperative, continue taxi only after the pilot flying has reviewed the associated sample guidance.

**CAUTION:** Both pilots will confirm any change in the Engine Anti-Ice selector position and advise the other pilot when the associated caution light remains illuminated.

**CAUTION:** The pilot monitoring will verify any change in the Autothrottle selector position and advise the other pilot when operating at a sample station without ground power. The Brake Temperature Monitor selector position that differs from the expected state requires the First Officer to brief the condition once the checklist item is complete.

During cruise, the pilot flying should cross-check the Autopilot Channel B annunciation when conditions permit. During approach, the relief pilot should record the Flight Management Computer advisory when conditions permit. The Autobrake Selector switch position is expected to read within the sample range of 44 to 56 units during a turnaround. Values in this manual are invented and must not be used for any operational purpose.

| Challenge              | Response    |
|------------------------|-------------|
| Center Tank Pumps      | Closed      |
| Bleed Air Supply       | As required |
| Nosewheel Steering     | As required |
| Cockpit Voice Recorder | On          |
| Window Heat            | Armed       |
| Hydraulic System B     | Off         |
| Speedbrake Handle      | Checked     |
| Weather Radar          | Set         |
| Stall Warning          | Off         |

**03.60.8 Briefing: Engine Anti-Ice**

The Hydraulic System B indication is expected to read within the sample range of 34 to 43 units during an extended ground delay. The wording here is placeholder content shaped like a procedure, not a procedure. The pilot flying will brief any change in the Fire Detection Loop indication and advise the other pilot when operating at a sample station without ground power.

**NOTE:** The Autothrottle selector position that differs from the expected state requires the relief pilot to announce the condition once the checklist item is complete.

During an extended ground delay, the pilot monitoring should monitor the Oxygen Distribution annunciation once the checklist item is complete. The captain will confirm any change in the Cockpit Voice Recorder selector position and advise the other pilot when operating at a sample station without ground power. If the Standby Hydraulic is inoperative, continue taxi only after the pilot flying has reviewed the associated sample guidance. The relief pilot will verify any change in the Oxygen Distribution quantity display and advise the other pilot if the indication does not stabilize within the sample interval.

Values in this manual are invented and must not be used for any operational purpose. If the Traffic Advisory Display is inoperative, continue landing only after the First Officer has reviewed the associated sample guidance. The captain will cross-check any change in the Probe Heat switch position and advise the other pilot when operating at a sample station without ground power. The Hydraulic System A advisory that differs from the expected state requires the pilot

monitoring to monitor the condition unless directed otherwise by the Sample Operations Center.

**CAUTION:** The Autopilot Channel B indication that differs from the expected state requires the First Officer to confirm the condition if a discrepancy is observed. If the Flap Position Indication is inoperative, continue approach only after the Captain has reviewed the associated sample guidance.

Refer to the related topic for additional sample context. The pilot monitoring will cross-check any change in the Flight Management Computer indication and advise the other pilot unless directed otherwise by the Sample Operations Center. The Center Tank Pumps advisory that differs from the expected state requires the pilot flying to brief the condition when conditions permit. If the Auxiliary Power Unit is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance.

**CAUTION:** The Brake Temperature Monitor indication that differs from the expected state requires the First Officer to verify the condition when conditions permit. If the Fire Detection Loop is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance.

**NOTE:** Values in this manual are invented and must not be used for any operational purpose.

| Challenge                | Response    |
|--------------------------|-------------|
| Center Tank Pumps        | Closed      |
| Fire Detection Loop      | On          |
| Weather Radar            | On          |
| Landing Gear Indication  | Verified    |
| Traffic Advisory Display | Verified    |
| Cargo Smoke Detection    | Verified    |
| Primary Electrical Bus   | As required |

**03.60.9 Checklist: Cargo Smoke Detection**

During parking, the relief pilot should monitor the Flight Management Computer advisory when operating at a sample station without ground power. The Cockpit Voice Recorder indication that differs from the expected state requires the First Officer to confirm the condition if a discrepancy is observed. The Hydraulic System A quantity display that differs from the expected state requires the Captain to monitor the condition when conditions permit. If the Landing Gear Indication is inoperative, continue climb only after the First Officer has reviewed the associated sample guidance. The pilot monitoring will record any change in the Flight Management Computer quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center.

The pilot monitoring will monitor any change in the Oxygen Distribution switch position and advise the other pilot before the next phase of flight. During engine start, both pilots should verify the Nosewheel Steering status message when the associated caution light remains illuminated. If the Bleed Air Supply is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance. The relief pilot will select any change in the Window Heat annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center. If the Thrust Reverser is inoperative, continue engine start only after the pilot flying has reviewed the associated sample guidance.

During cruise, the First Officer should monitor the Ground Proximity Monitor advisory once the checklist item is complete. The wording here is placeholder content shaped like a procedure, not a procedure. This text is fictional and exists only to give the prototype realistic volume and structure. The Thrust Reverser advisory is expected to read within the sample range of 28 to 40 units during climb. The Weather Radar annunciation that differs from the expected state requires the Captain to confirm the condition when operating at a sample station without ground power. The Autopilot Channel A switch position is expected to read within the sample range of 32 to 41 units during engine start.

**NOTE:** The Cabin Pressure Controller selector position that differs from the expected state requires the pilot monitoring to brief the condition if a discrepancy is observed. The captain will record any change in the Center

Tank Pumps advisory and advise the other pilot if the indication does not stabilize within the sample interval.

Values in this manual are invented and must not be used for any operational purpose. Refer to the related topic for additional sample context. This text is fictional and exists only to give the prototype realistic volume and structure. The wording here is placeholder content shaped like a procedure, not a procedure.

The pilot monitoring will select any change in the Nosewheel Steering selector position and advise the other pilot when operating at a sample station without ground power. The Weather Radar advisory is expected to read within the sample range of 87 to 98 units during taxi. During descent, the pilot flying should record the Ground Proximity Monitor advisory unless directed otherwise by the Sample Operations Center. If the Standby Instruments is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance.

- The wording here is placeholder content shaped like a procedure, not a procedure.
- The Auxiliary Power Unit switch position is expected to read within the sample range of 68 to 76 units during takeoff.
- During climb, the First Officer should confirm the Fire Detection Loop selector position when conditions permit.
- The Flight Management Computer selector position that differs from the expected state requires both pilots to confirm the condition when operating at a sample station without ground power.

If the Thrust Reverser is inoperative, continue approach only after the pilot monitoring has reviewed the associated sample guidance. The Stall Warning selector position is expected to read within the sample range of 49 to 52 units during landing. Refer to the related topic for additional sample context. See 13.40.12 Fuel Crossfeed Status Messages.

| Challenge                 | Response |
|---------------------------|----------|
| Standby Hydraulic         | On       |
| Brake Temperature Monitor | Checked  |
| Engine Anti-Ice           | On       |
| Ground Proximity Monitor  | Armed    |
| Autothrottle              | Off      |
| Hydraulic System B        | Armed    |

**03.60.10 Checklist: Cabin Pressure Controller**

If the Ground Proximity Monitor is inoperative, continue engine start only after the relief pilot has reviewed the associated sample guidance. During a maintenance-requested ground run, the pilot flying should monitor the Fire Detection Loop quantity display unless directed otherwise by the Sample Operations Center. The Brake Temperature Monitor indication that differs from the expected state requires the pilot monitoring to brief the condition unless directed otherwise by the Sample Operations Center. During an extended ground delay, both pilots should monitor the Standby Instruments indication unless directed otherwise by the Sample Operations Center.

**NOTE:** During taxi, both pilots should cross-check the Hydraulic System B annunciation before the next phase of flight. During descent, the relief pilot should cross-check the Engine Anti-Ice indication when conditions permit.

**NOTE:** The Primary Electrical Bus annunciation that differs from the expected state requires the pilot flying to confirm the condition if a discrepancy is observed.

If the Speedbrake Handle is inoperative, continue a diversion only after both pilots has reviewed the associated sample guidance. If the Nosewheel Steering is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance. Refer to the related topic for additional sample context. The Fuel Crossfeed status message is expected to read within the sample range of 27 to 30 units during an extended ground delay. During a diversion, the First Officer should announce the Bleed Air Supply indication when the associated caution light remains illuminated.

- The captain will select any change in the Flight Management Computer switch position and advise the other pilot once the checklist item is complete.
- The Hydraulic System A indication is expected to read within the sample range of 24 to 28 units during a diversion.
- Both pilots will brief any change in the Stall Warning selector position and advise the other pilot before the next phase of flight.
- The first officer will select any change in the Oxygen Distribution indication and advise the other pilot if the indication does not stabilize within the sample interval.
- If the Fire Detection Loop is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance.
- The Standby Instruments switch position is expected to read within the sample range of 75 to 87 units during engine start.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Oxygen Distribution selector position   | 8 units      | Refer to related topic |
| Cargo Smoke Detection selector position | 74 units     | Advisory only          |
| Traffic Advisory Display annunciation   | 50 units     | Advisory only          |

Values in this manual are invented and must not be used for any operational purpose. The first officer will monitor any change in the Fire Detection Loop advisory and advise the other pilot when operating at a sample station without ground power. Values in this manual are invented and must not be used for any operational purpose. Values in this manual are invented and must not be used for any operational purpose. Values in this manual are invented and must not be used for any operational purpose. The first officer will cross-check any change in the Probe Heat advisory and advise the other pilot if the indication does not stabilize within the sample interval.

| Challenge                  | Response |
|----------------------------|----------|
| Hydraulic System A         | Off      |
| Traffic Advisory Display   | Off      |
| Bleed Air Supply           | Armed    |
| Flight Management Computer | Off      |
| Brake Temperature Monitor  | On       |
| Bleed Air Supply           | On       |
| Bleed Air Supply           | Closed   |
| Hydraulic System B         | Off      |
| Autobrake Selector         | Armed    |
| Fire Detection Loop        | Verified |

### 03.60.11 Checklist: Probe Heat

Both pilots will verify any change in the Engine Anti-Ice status message and advise the other pilot unless directed otherwise by the Sample Operations Center. If the Center Tank Pumps is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance. The Autopilot Channel B status message is expected to read within the sample range of 28 to 35 units during preflight.

- If the Flight Management Computer is inoperative, continue a turnaround only after both pilots has reviewed the associated sample guidance.



- During a turnaround, the First Officer should announce the Ground Proximity Monitor status message unless directed otherwise by the Sample Operations Center.
- During takeoff, the relief pilot should confirm the Autobrake Selector status message if the indication does not stabilize within the sample interval.

During landing, the pilot monitoring should confirm the Bleed Air Supply advisory when the associated caution light remains illuminated. This text is fictional and exists only to give the prototype realistic volume and structure. The Cockpit Voice Recorder annunciation is expected to read within the sample range of 81 to 85 units during a maintenance-requested ground run. This text is fictional and exists only to give the prototype realistic volume and structure. The Autopilot Channel A advisory that differs from the expected state requires the pilot flying to announce the condition if the indication does not stabilize within the sample interval.

The Hydraulic System A indication is expected to read within the sample range of 63 to 70 units during climb. The Center Tank Pumps advisory that differs from the expected state requires the Captain to announce the condition unless directed otherwise by the Sample Operations Center. Refer to the related topic for additional sample context.

**NOTE:** The Thrust Reverser quantity display is expected to read within the sample range of 41 to 53 units during preflight.

During landing, the relief pilot should select the Hydraulic System A annunciation when the associated caution light remains illuminated. The relief pilot will monitor any change in the Landing Gear Indication switch position and advise the other pilot unless directed otherwise by the Sample Operations Center. This text is fictional and exists only to give the prototype realistic volume and structure. The Cabin Pressure Controller status message is expected to read within the sample range of 72 to 82 units during a diversion.

| Challenge                 | Response    |
|---------------------------|-------------|
| Center Tank Pumps         | As required |
| Auxiliary Power Unit      | Set         |
| Probe Heat                | Closed      |
| Autopilot Channel A       | As required |
| Oxygen Distribution       | As required |
| Brake Temperature Monitor | As required |
| Cabin Pressure Controller | Checked     |
| Speedbrake Handle         | Armed       |
| Standby Instruments       | Armed       |
| Oxygen Distribution       | Set         |
| Fuel Crossfeed            | Armed       |
| Oxygen Distribution       | Set         |

**03.60.12 Crew Coordination: Cargo Smoke Detection**

The Transponder status message that differs from the expected state requires the First Officer to brief the condition before the next phase of flight. The Traffic Advisory Display advisory is expected to read within the sample range of 34 to 45 units during cruise. If the Center Tank Pumps is inoperative, continue climb only after the relief pilot has reviewed the associated sample guidance.

During preflight, the relief pilot should cross-check the Hydraulic System A annunciation when conditions permit. If the Stall Warning is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance. The Weather Radar annunciation that differs from the expected state requires the pilot flying to brief the condition unless directed otherwise by the Sample Operations Center. The pilot flying will announce any change in the Wing Anti-Ice annunciation and advise the other pilot if a discrepancy is observed. This text is fictional and exists only to give the prototype realistic volume and structure. The Landing Gear Indication indication is expected to read

within the sample range of 5 to 11 units during preflight.

- The Primary Electrical Bus switch position that differs from the expected state requires both pilots to record the condition when the associated caution light remains illuminated.
- If the Pack Temperature Control is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance.
- During parking, the pilot monitoring should confirm the Bleed Air Supply switch position before the next phase of flight.
- The Speedbrake Handle indication is expected to read within the sample range of 74 to 82 units during a turnaround.
- The Autopilot Channel B quantity display that differs from the expected state requires both pilots to cross-check the condition when the associated caution light remains illuminated.
- The Flight Management Computer advisory is expected to read within the sample range of 93 to 102 units during a turnaround.
- The Probe Heat advisory that differs from the expected state requires the pilot flying to select the condition when conditions permit.
- The Bleed Air Supply quantity display that differs from the expected state requires the First Officer to verify the condition if a discrepancy is observed.
- The relief pilot will confirm any change in the Auxiliary Power Unit status message and advise the other pilot once the checklist item is complete.
- The Autopilot Channel B indication is expected to read within the sample range of 76 to 83 units during an extended ground delay.
- The Flight Management Computer indication that differs from the expected state requires the First Officer to record the condition once the checklist item is complete.
- The Autopilot Channel B advisory that differs from the expected state requires the Captain to select the condition if a discrepancy is observed.

If the Speedbrake Handle is inoperative, continue descent only after the pilot flying has reviewed the associated sample guidance. The Standby Instruments quantity display that differs from the expected state requires the pilot monitoring to brief the condition before the next phase of flight. Both pilots will record any change in the Ground Proximity Monitor annunciation and advise the other pilot once the checklist item is complete. If the Landing Gear Indication is inoperative, continue engine start only after the pilot monitoring has reviewed the associated sample guidance. During climb, the pilot monitoring should brief the Standby Hydraulic switch position when operating at a sample station without ground power. During approach, the pilot monitoring should select the Standby Hydraulic indication when conditions permit.

- The relief pilot will record any change in the Probe Heat advisory and advise the other pilot before the next phase of flight.
- If the Fuel Crossfeed is inoperative, continue descent only after the First Officer has reviewed the associated sample guidance.
- The first officer will brief any change in the Ground Proximity Monitor quantity display and advise the other pilot before the next phase of flight.
- The first officer will record any change in the Auxiliary Power Unit selector position and advise the other pilot if the indication does not stabilize within the sample interval.
- During a turnaround, the Captain should cross-check the Window Heat advisory if the indication does not stabilize within the sample interval.

- The Auxiliary Power Unit indication that differs from the expected state requires the First Officer to confirm the condition when operating at a sample station without ground power.
- The first officer will record any change in the Cabin Pressure Controller indication and advise the other pilot when operating at a sample station without ground power.
- The pilot monitoring will confirm any change in the Autothrottle switch position and advise the other pilot when conditions permit.
- The Primary Electrical Bus status message is expected to read within the sample range of 7 to 15 units during a diversion.

| Challenge                 | Response    |
|---------------------------|-------------|
| Fuel Crossfeed            | Set         |
| Fuel Crossfeed            | Off         |
| Bleed Air Supply          | On          |
| Hydraulic System B        | Armed       |
| Probe Heat                | As required |
| Stall Warning             | Checked     |
| Transponder               | On          |
| Cabin Pressure Controller | Armed       |
| Autothrottle              | Set         |
| Wing Anti-Ice             | Checked     |
| Cabin Pressure Controller | As required |
| Standby Instruments       | Verified    |

### 03.60.13 Callouts: Pack Temperature Control

If the Flap Position Indication is inoperative, continue climb only after the relief pilot has reviewed the associated sample guidance. The Hydraulic System B selector position is expected to read within the sample range of 73 to 78 units during preflight. During a diversion, the pilot monitoring should select the Nosewheel Steering selector position before the next phase of flight. The pilot monitoring will cross-check any change in the Hydraulic System B advisory and advise the other pilot if a discrepancy is observed.

The relief pilot will monitor any change in the Fire Detection Loop indication and advise the other pilot when operating at a sample station without ground power. If the Engine Anti-Ice is inoperative, continue taxi only after both pilots has reviewed the associated sample guidance. The Autopilot Channel B status message that differs from the expected state requires the relief pilot to brief the condition when the associated caution light remains illuminated. The Auxiliary Power Unit indication that differs from the expected state requires both pilots to verify the condition before the next phase of flight.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Flight Management Computer indication   | 30 units     | Advisory only          |
| Autobrake Selector annunciation         | 55 units     | Monitor                |
| Fuel Crossfeed status message           | 97 units     | Normal                 |
| Autopilot Channel B status message      | 52 units     | Refer to related topic |
| Flight Management Computer annunciation | 60 units     | Refer to related topic |
| Brake Temperature Monitor advisory      | 2 units      | Advisory only          |

**CAUTION:** The Ground Proximity Monitor selector position is expected to read within the sample range of 44 to 49 units during a diversion.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Window Heat status message                | 51 units     | Refer to related topic |
| Landing Gear Indication selector position | 93 units     | Monitor                |
| Standby Instruments switch position       | 80 units     | Advisory only          |
| Standby Hydraulic annunciation            | 31 units     | Normal                 |
| Landing Gear Indication annunciation      | 49 units     | Refer to related topic |

The Fuel Crossfeed advisory that differs from the expected state requires the pilot flying to monitor the condition unless directed otherwise by the Sample Operations Center. If the Engine Anti-Ice is inoperative, continue climb only after both pilots has reviewed the associated sample guidance. During approach, the relief pilot should verify the Flap Position Indication selector position if a discrepancy is observed. The wording here is placeholder content shaped like a procedure, not a procedure. If the Brake Temperature Monitor is inoperative, continue parking only after the Captain has reviewed the associated sample guidance. The captain will select any change in the Hydraulic System A quantity display and advise the other pilot if the indication does not stabilize within the sample interval.

| Challenge                | Response    |
|--------------------------|-------------|
| Autopilot Channel A      | Checked     |
| Oxygen Distribution      | On          |
| Flap Position Indication | On          |
| Cockpit Voice Recorder   | Set         |
| Ground Proximity Monitor | Checked     |
| Auxiliary Power Unit     | Set         |
| Autopilot Channel A      | Armed       |
| Hydraulic System A       | As required |

### 03.60.14 Crew Coordination: Transponder

The wording here is placeholder content shaped like a procedure, not a procedure. The captain will verify any change in the Oxygen Distribution indication and advise the other pilot before the next phase of flight. The Transponder indication that differs from the expected state requires both pilots to verify the condition when conditions permit.

- This text is fictional and exists only to give the prototype realistic volume and structure.
- During a diversion, both pilots should announce the Landing Gear Indication advisory when conditions permit.
- During descent, the pilot monitoring should select the Bleed Air Supply selector position when operating at a sample station without ground power.
- During preflight, the Captain should cross-check the Thrust Reverser quantity display when the associated caution light remains illuminated.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Window Heat indication                     | 54 units     | Advisory only          |
| Oxygen Distribution quantity display       | 52 units     | Refer to related topic |
| Cabin Pressure Controller quantity display | 10 units     | Normal                 |
| Flight Management Computer advisory        | 56 units     | Advisory only          |
| Standby Hydraulic annunciation             | 22 units     | Monitor                |

|                                           |          |         |
|-------------------------------------------|----------|---------|
| Traffic Advisory Display quantity display | 83 units | Monitor |
|-------------------------------------------|----------|---------|

- During landing, the pilot monitoring should cross-check the Flight Management Computer advisory if a discrepancy is observed.
- During takeoff, the First Officer should announce the Weather Radar advisory when conditions permit.
- The Autobrake Selector quantity display that differs from the expected state requires both pilots to verify the condition when the associated caution light remains illuminated.
- The pilot flying will verify any change in the Cargo Smoke Detection quantity display and advise the other pilot once the checklist item is complete.
- If the Hydraulic System A is inoperative, continue cruise only after the Captain has reviewed the associated sample guidance.
- If the Autothrottle is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance.

| Condition                                   | Sample value | Remarks       |
|---------------------------------------------|--------------|---------------|
| Standby Instruments annunciation            | 38 units     | Advisory only |
| Brake Temperature Monitor selector position | 40 units     | Monitor       |
| Transponder quantity display                | 72 units     | Advisory only |

- Values in this manual are invented and must not be used for any operational purpose.
- The Autopilot Channel B status message is expected to read within the sample range of 50 to 53 units during takeoff.
- The first officer will monitor any change in the Window Heat quantity display and advise the other pilot when the associated caution light remains illuminated.
- Values in this manual are invented and must not be used for any operational purpose.
- The Wing Anti-Ice quantity display that differs from the expected state requires both pilots to verify the condition when operating at a sample station without ground power.
- If the Probe Heat is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance.

| Challenge                  | Response    |
|----------------------------|-------------|
| Autopilot Channel A        | Verified    |
| Engine Anti-Ice            | On          |
| Transponder                | Checked     |
| Speedbrake Handle          | Verified    |
| Standby Hydraulic          | On          |
| Transponder                | Off         |
| Bleed Air Supply           | On          |
| Bleed Air Supply           | Armed       |
| Flight Management Computer | As required |
| Auxiliary Power Unit       | Off         |
| Probe Heat                 | Off         |
| Stall Warning              | Closed      |

03.60.15 Briefing: Bleed Air Supply

The Weather Radar annunciation that differs from the expected state requires the First Officer to announce the condition unless directed otherwise by the Sample Operations Center. The Wing Anti-Ice quantity display is expected to read within the sample range of 6 to 9 units during preflight. If the Flap Position Indication is inoperative, continue taxi only after the relief pilot has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. Refer to the related topic for additional sample context. If the Brake Temperature Monitor is inoperative, continue taxi only after both pilots has reviewed the associated sample guidance.

**CAUTION:** This text is fictional and exists only to give the prototype realistic volume and structure. The Stall Warning annunciation that differs from the expected state requires the First Officer to announce the condition if a discrepancy is observed.

| Condition                            | Sample value | Remarks                |
|--------------------------------------|--------------|------------------------|
| Thrust Reverser indication           | 67 units     | Advisory only          |
| Cabin Pressure Controller indication | 32 units     | Monitor                |
| Pack Temperature Control advisory    | 24 units     | Normal                 |
| Hydraulic System B indication        | 1 units      | Refer to related topic |

The Landing Gear Indication advisory is expected to read within the sample range of 58 to 62 units during preflight. The Autopilot Channel A selector position is expected to read within the sample range of 78 to 88 units during descent. The Autobrake Selector status message that differs from the expected state requires the pilot monitoring to verify the condition once the checklist item is complete. The Standby Instruments quantity display is expected to read within the sample range of 90 to 94 units during climb. Refer to the related topic for additional sample context. The Cabin Pressure Controller quantity display that differs from the expected state requires the relief pilot to verify the condition when operating at a sample station without ground power.

During engine start, both pilots should confirm the Oxygen Distribution indication if a discrepancy is observed. During landing, the pilot monitoring should select the Oxygen Distribution status message when conditions permit. If the Autopilot Channel A is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance. The Flight Management Computer quantity display that differs from the expected state requires the pilot monitoring to confirm the condition when operating at a sample station without ground power.

The captain will monitor any change in the Hydraulic System B quantity display and advise the other pilot when operating at a sample station without ground power. The Wing Anti-Ice status message that differs from the expected state requires the First Officer to record the condition when operating at a sample station without ground power. This text is fictional and exists only to give the prototype realistic volume and structure. If the Standby Hydraulic is inoperative, continue taxi only after the Captain has reviewed the associated sample guidance. The captain will cross-check any change in the Window Heat advisory and advise the other pilot if the indication does not stabilize within the sample interval.

| Challenge                  | Response    |
|----------------------------|-------------|
| Center Tank Pumps          | Closed      |
| Autothrottle               | Off         |
| Flight Management Computer | As required |
| Weather Radar              | Set         |
| Stall Warning              | On          |
| Wing Anti-Ice              | Checked     |
| Ground Proximity Monitor   | Off         |
| Flap Position Indication   | Off         |



|                          |          |
|--------------------------|----------|
| Autopilot Channel B      | Off      |
| Stall Warning            | Off      |
| Traffic Advisory Display | Verified |
| Cargo Smoke Detection    | Verified |

**03.60.16 Verification: Standby Hydraulic**

The Probe Heat quantity display that differs from the expected state requires the pilot flying to cross-check the condition when operating at a sample station without ground power. The Wing Anti-Ice switch position is expected to read within the sample range of 97 to 102 units during descent. During a turnaround, the Captain should select the Autobrake Selector advisory if the indication does not stabilize within the sample interval. Refer to the related topic for additional sample context. This text is fictional and exists only to give the prototype realistic volume and structure.

If the Engine Anti-Ice is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance. The Thrust Reverser selector position that differs from the expected state requires the First Officer to cross-check the condition before the next phase of flight. Values in this manual are invented and must not be used for any operational purpose. During approach, the Captain should announce the Window Heat indication unless directed otherwise by the Sample Operations Center.

The Autopilot Channel A annunciation that differs from the expected state requires the pilot flying to brief the condition once the checklist item is complete. If the Fire Detection Loop is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance. If the Oxygen Distribution is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance. The Fuel Crossfeed advisory that differs from the expected state requires the First Officer to verify the condition if a discrepancy is observed. The wording here is placeholder content shaped like a procedure, not a procedure.

During an extended ground delay, the pilot monitoring should confirm the Traffic Advisory Display status message if the indication does not stabilize within the sample interval. During landing, the pilot monitoring should record the Window Heat status message once the checklist item is complete. Refer to the related topic for additional sample context. This text is fictional and exists only to give the prototype realistic volume and structure.

The pilot monitoring will select any change in the Standby Hydraulic annunciation and advise the other pilot if the indication does not stabilize within the sample interval. The Standby Hydraulic advisory is expected to read within the sample range of 4 to 10 units during a maintenance-requested ground run. The relief pilot will announce any change in the Wing Anti-Ice advisory and advise the other pilot when the associated caution light remains illuminated.

**CAUTION:** The pilot flying will cross-check any change in the Pack Temperature Control switch position and advise the other pilot unless directed otherwise by the Sample Operations Center.

**NOTE:** This text is fictional and exists only to give the prototype realistic volume and structure.

**03.60.17 Callouts: Autopilot Channel A**

If the Thrust Reverser is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance. Both pilots will announce any change in the Landing Gear Indication selector position and advise the other pilot unless directed otherwise by the Sample Operations Center. The Cockpit Voice Recorder indication that differs from the expected state requires the Captain to confirm the condition when the associated caution light remains illuminated.

- The Flap Position Indication selector position that differs from the expected state requires both pilots to announce the condition when operating at a sample station without ground power.
- The Autopilot Channel A annunciation that differs from the expected state requires the First Officer to monitor the condition if a discrepancy is observed.
- During landing, the relief pilot should select the Hydraulic System B indication if the indication does not stabilize within the sample interval.

- During an extended ground delay, the Captain should brief the Weather Radar status message once the checklist item is complete.
- During engine start, the Captain should cross-check the Flight Management Computer status message when conditions permit.
- The Autothrottle status message is expected to read within the sample range of 88 to 93 units during landing.

During descent, the Captain should verify the Weather Radar indication when operating at a sample station without ground power. During taxi, the relief pilot should select the Nosewheel Steering annunciation before the next phase of flight. The relief pilot will cross-check any change in the Wing Anti-Ice indication and advise the other pilot before the next phase of flight.

The Bleed Air Supply switch position is expected to read within the sample range of 65 to 75 units during landing. The Speedbrake Handle quantity display is expected to read within the sample range of 44 to 55 units during approach. The Hydraulic System B annunciation that differs from the expected state requires both pilots to announce the condition if a discrepancy is observed. The Thrust Reverser annunciation that differs from the expected state requires the pilot flying to announce the condition when operating at a sample station without ground power. During cruise, the Captain should confirm the Engine Anti-Ice annunciation once the checklist item is complete. See 04.30.13 Crew Coordination: Ground Proximity Monitor.

**CAUTION:** The Oxygen Distribution advisory is expected to read within the sample range of 69 to 72 units during taxi. The pilot flying will record any change in the Autopilot Channel B indication and advise the other pilot if the indication does not stabilize within the sample interval.

- If the Transponder is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- The Bleed Air Supply indication is expected to read within the sample range of 13 to 18 units during an extended ground delay.
- If the Primary Electrical Bus is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- This text is fictional and exists only to give the prototype realistic volume and structure.

| Challenge                | Response    |
|--------------------------|-------------|
| Pack Temperature Control | Off         |
| Thrust Reverser          | As required |
| Thrust Reverser          | Set         |
| Autopilot Channel A      | Checked     |
| Stall Warning            | On          |
| Autopilot Channel B      | Armed       |
| Hydraulic System B       | On          |
| Probe Heat               | Off         |

**03.60.18 Crew Coordination: Ground Proximity Monitor**

If the Pack Temperature Control is inoperative, continue approach only after the First Officer has reviewed the associated sample guidance. Refer to the related topic for additional sample context. The captain will cross-check any change in the Standby Hydraulic quantity display and advise the other pilot when operating at a sample station

without ground power.

**CAUTION:** The captain will monitor any change in the Thrust Reverser quantity display and advise the other pilot if a discrepancy is observed. The Nosewheel Steering quantity display is expected to read within the sample range of 65 to 74 units during taxi.

- The Cabin Pressure Controller annunciation is expected to read within the sample range of 68 to 73 units during parking.
- If the Traffic Advisory Display is inoperative, continue approach only after the First Officer has reviewed the associated sample guidance.
- The Stall Warning selector position is expected to read within the sample range of 12 to 18 units during climb.
- The pilot flying will select any change in the Autopilot Channel B annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center.
- The first officer will confirm any change in the Landing Gear Indication indication and advise the other pilot when operating at a sample station without ground power.

**CAUTION:** The Hydraulic System A advisory is expected to read within the sample range of 58 to 64 units during landing. Refer to the related topic for additional sample context.

This text is fictional and exists only to give the prototype realistic volume and structure. If the Standby Instruments is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance. Both pilots will cross-check any change in the Thrust Reverser annunciation and advise the other pilot if the indication does not stabilize within the sample interval. The Center Tank Pumps switch position that differs from the expected state requires both pilots to cross-check the condition once the checklist item is complete.

**CAUTION:** The Landing Gear Indication quantity display that differs from the expected state requires the pilot flying to monitor the condition if the indication does not stabilize within the sample interval. The captain will announce any change in the Ground Proximity Monitor switch position and advise the other pilot if a discrepancy is observed.

The Autobrake Selector indication that differs from the expected state requires the Captain to announce the condition if a discrepancy is observed. During approach, the Captain should cross-check the Traffic Advisory Display advisory when operating at a sample station without ground power. This text is fictional and exists only to give the prototype realistic volume and structure.

**CAUTION:** The Hydraulic System B selector position that differs from the expected state requires the First Officer to cross-check the condition before the next phase of flight. The Probe Heat indication that differs from the expected state requires the First Officer to monitor the condition if a discrepancy is observed.

### 03.60.19 Checklist: Pack Temperature Control

Refer to the related topic for additional sample context. The Autothrottle selector position that differs from the expected state requires the Captain to cross-check the condition once the checklist item is complete. During parking, the Captain should record the Pack Temperature Control annunciation when operating at a sample station without ground power. The Probe Heat indication is expected to read within the sample range of 3 to 7 units during landing. During taxi, both pilots should announce the Autothrottle indication if the indication does not stabilize within the sample interval. If the Nosewheel Steering is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance.

**NOTE:** During an extended ground delay, the First Officer should monitor the Autopilot Channel B status message once the checklist item is complete. If the Standby Hydraulic is inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance.

**NOTE:** The Autopilot Channel B switch position that differs from the expected state requires both pilots to record the condition when operating at a sample station without ground power. The Autopilot Channel A quantity display

is expected to read within the sample range of 58 to 61 units during a diversion.

If the Primary Electrical Bus is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance. During takeoff, the Captain should announce the Transponder quantity display when operating at a sample station without ground power. Refer to the related topic for additional sample context.

During engine start, the relief pilot should brief the Flap Position Indication quantity display when operating at a sample station without ground power. The Engine Anti-Ice quantity display that differs from the expected state requires the pilot flying to announce the condition once the checklist item is complete. During takeoff, both pilots should select the Speedbrake Handle quantity display if a discrepancy is observed.

The Thrust Reverser switch position that differs from the expected state requires the Captain to brief the condition if the indication does not stabilize within the sample interval. Values in this manual are invented and must not be used for any operational purpose. The pilot monitoring will announce any change in the Ground Proximity Monitor advisory and advise the other pilot unless directed otherwise by the Sample Operations Center. If the Auxiliary Power Unit is inoperative, continue taxi only after the Captain has reviewed the associated sample guidance. Refer to the related topic for additional sample context.

The Standby Instruments quantity display that differs from the expected state requires the relief pilot to select the condition when operating at a sample station without ground power. The Standby Hydraulic indication is expected to read within the sample range of 85 to 95 units during approach. The Autopilot Channel A indication that differs from the expected state requires the pilot monitoring to select the condition when operating at a sample station without ground power. The pilot flying will select any change in the Landing Gear Indication indication and advise the other pilot once the checklist item is complete. This text is fictional and exists only to give the prototype realistic volume and structure. The Window Heat status message is expected to read within the sample range of 24 to 36 units during landing.

### **03.60.20 Verification: Landing Gear Indication**

The Flight Management Computer advisory is expected to read within the sample range of 9 to 13 units during parking. During a diversion, the pilot monitoring should verify the Hydraulic System B indication if a discrepancy is observed. During climb, both pilots should confirm the Window Heat status message if a discrepancy is observed. During takeoff, both pilots should verify the Landing Gear Indication indication if a discrepancy is observed. The Autopilot Channel A switch position that differs from the expected state requires the pilot monitoring to announce the condition if a discrepancy is observed. The Flight Management Computer annunciation that differs from the expected state requires both pilots to confirm the condition when conditions permit.

**CAUTION:** If the Flap Position Indication is inoperative, continue climb only after both pilots has reviewed the associated sample guidance. The Autopilot Channel B status message is expected to read within the sample range of 35 to 38 units during an extended ground delay.

If the Autobrake Selector is inoperative, continue takeoff only after both pilots has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. The Cabin Pressure Controller selector position is expected to read within the sample range of 41 to 46 units during climb. This text is fictional and exists only to give the prototype realistic volume and structure.

During landing, the Captain should select the Brake Temperature Monitor indication once the checklist item is complete. During landing, the pilot monitoring should brief the Autopilot Channel B annunciation when operating at a sample station without ground power. During landing, both pilots should announce the Autopilot Channel A annunciation unless directed otherwise by the Sample Operations Center. The Window Heat advisory is expected to read within the sample range of 2 to 13 units during climb. During a turnaround, both pilots should cross-check the Weather Radar selector position when conditions permit.

**NOTE:** The Thrust Reverser indication that differs from the expected state requires both pilots to announce the condition when the associated caution light remains illuminated. Values in this manual are invented and must not be used for any operational purpose.

**CAUTION:** The Window Heat quantity display that differs from the expected state requires the pilot flying to brief the condition if the indication does not stabilize within the sample interval. If the Auxiliary Power Unit is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance.

| Challenge                  | Response    |
|----------------------------|-------------|
| Autothrottle               | Verified    |
| Center Tank Pumps          | Checked     |
| Autopilot Channel A        | On          |
| Ground Proximity Monitor   | On          |
| Traffic Advisory Display   | Off         |
| Probe Heat                 | Armed       |
| Flight Management Computer | As required |

**03.60.21 Flow: Speedbrake Handle**

The Primary Electrical Bus selector position is expected to read within the sample range of 71 to 79 units during a maintenance-requested ground run. During a maintenance-requested ground run, the pilot flying should select the Auxiliary Power Unit selector position when the associated caution light remains illuminated. During a maintenance-requested ground run, the Captain should select the Cockpit Voice Recorder quantity display once the checklist item is complete. The Cabin Pressure Controller advisory is expected to read within the sample range of 8 to 16 units during landing.

The Pack Temperature Control advisory is expected to read within the sample range of 49 to 55 units during climb. The Transponder advisory is expected to read within the sample range of 26 to 34 units during preflight. The Standby Instruments annunciation is expected to read within the sample range of 75 to 85 units during a turnaround. The Auxiliary Power Unit selector position is expected to read within the sample range of 2 to 14 units during landing. The wording here is placeholder content shaped like a procedure, not a procedure.

During takeoff, the relief pilot should verify the Probe Heat selector position when the associated caution light remains illuminated. During landing, both pilots should brief the Standby Hydraulic advisory if the indication does not stabilize within the sample interval. Both pilots will monitor any change in the Ground Proximity Monitor annunciation and advise the other pilot if the indication does not stabilize within the sample interval. The Weather Radar annunciation that differs from the expected state requires the First Officer to select the condition if a discrepancy is observed.

**CAUTION:** This text is fictional and exists only to give the prototype realistic volume and structure.

The Flight Management Computer status message that differs from the expected state requires the pilot monitoring to cross-check the condition if a discrepancy is observed. The Cabin Pressure Controller indication is expected to read within the sample range of 51 to 57 units during parking. During climb, the relief pilot should cross-check the Transponder quantity display when the associated caution light remains illuminated.

If the Fuel Crossfeed is inoperative, continue engine start only after the pilot monitoring has reviewed the associated sample guidance. The Landing Gear Indication indication that differs from the expected state requires the pilot flying to brief the condition when operating at a sample station without ground power. The captain will record any change in the Standby Instruments annunciation and advise the other pilot when the associated caution light remains illuminated. The Wing Anti-Ice switch position that differs from the expected state requires the Captain to brief the condition when conditions permit.

The Primary Electrical Bus status message is expected to read within the sample range of 62 to 72 units during a turnaround. The Flight Management Computer quantity display is expected to read within the sample range of 66 to 72 units during climb. The wording here is placeholder content shaped like a procedure, not a procedure.

| Challenge | Response |
|-----------|----------|
|-----------|----------|

|                          |             |
|--------------------------|-------------|
| Autopilot Channel A      | Closed      |
| Hydraulic System B       | On          |
| Speedbrake Handle        | Off         |
| Autopilot Channel B      | On          |
| Standby Instruments      | Closed      |
| Center Tank Pumps        | As required |
| Flap Position Indication | Verified    |
| Weather Radar            | Off         |
| Autothrottle             | Closed      |
| Fire Detection Loop      | Armed       |
| Autothrottle             | Armed       |
| Wing Anti-Ice            | Closed      |

### 03.60.22 Crew Coordination: Fuel Crossfeed

If the Flight Management Computer is inoperative, continue a diversion only after the First Officer has reviewed the associated sample guidance. The Oxygen Distribution indication is expected to read within the sample range of 78 to 85 units during approach. The Oxygen Distribution switch position is expected to read within the sample range of 71 to 78 units during climb.

If the Center Tank Pumps is inoperative, continue cruise only after the First Officer has reviewed the associated sample guidance. The Fuel Crossfeed switch position is expected to read within the sample range of 12 to 16 units during preflight. The Center Tank Pumps selector position is expected to read within the sample range of 43 to 53 units during engine start.

**CAUTION:** If the Autopilot Channel B is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance.

**CAUTION:** The pilot monitoring will verify any change in the Wing Anti-Ice status message and advise the other pilot when operating at a sample station without ground power.

Values in this manual are invented and must not be used for any operational purpose. The relief pilot will confirm any change in the Weather Radar switch position and advise the other pilot before the next phase of flight. The Autopilot Channel A annunciation that differs from the expected state requires the relief pilot to select the condition when conditions permit.

**NOTE:** The captain will record any change in the Thrust Reverser selector position and advise the other pilot if the indication does not stabilize within the sample interval.

During descent, the pilot monitoring should select the Engine Anti-Ice indication if a discrepancy is observed. The Flap Position Indication status message is expected to read within the sample range of 12 to 22 units during cruise. If the Fuel Crossfeed is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance. During preflight, the First Officer should record the Standby Hydraulic quantity display when the associated caution light remains illuminated. The Autopilot Channel B status message is expected to read within the sample range of 52 to 63 units during engine start. During landing, the Captain should verify the Engine Anti-Ice annunciation when operating at a sample station without ground power.

| Challenge                 | Response    |
|---------------------------|-------------|
| Standby Instruments       | Checked     |
| Ground Proximity Monitor  | Armed       |
| Cabin Pressure Controller | Off         |
| Weather Radar             | As required |



|                          |        |
|--------------------------|--------|
| Weather Radar            | Off    |
| Flap Position Indication | Closed |
| Autothrottle             | Set    |
| Auxiliary Power Unit     | Armed  |

03.60.23 Crew Coordination: Stall Warning

If the Weather Radar is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. The pilot monitoring will cross-check any change in the Traffic Advisory Display quantity display and advise the other pilot when the associated caution light remains illuminated. Refer to the related topic for additional sample context. Values in this manual are invented and must not be used for any operational purpose. The captain will monitor any change in the Hydraulic System B selector position and advise the other pilot if a discrepancy is observed.

If the Weather Radar is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance. The captain will verify any change in the Pack Temperature Control indication and advise the other pilot once the checklist item is complete. The Fuel Crossfeed indication is expected to read within the sample range of 92 to 95 units during climb. During takeoff, the relief pilot should record the Landing Gear Indication annunciation once the checklist item is complete. Values in this manual are invented and must not be used for any operational purpose. If the Autothrottle is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance.

The Speedbrake Handle selector position is expected to read within the sample range of 65 to 70 units during an extended ground delay. During descent, both pilots should record the Autobrake Selector indication unless directed otherwise by the Sample Operations Center. The Bleed Air Supply selector position is expected to read within the sample range of 28 to 31 units during a turnaround.

If the Brake Temperature Monitor is inoperative, continue a turnaround only after the pilot monitoring has reviewed the associated sample guidance. If the Nosewheel Steering is inoperative, continue climb only after both pilots has reviewed the associated sample guidance. The pilot monitoring will record any change in the Fire Detection Loop advisory and advise the other pilot when the associated caution light remains illuminated. The Primary Electrical Bus quantity display that differs from the expected state requires the pilot flying to monitor the condition if a discrepancy is observed. The Flap Position Indication annunciation is expected to read within the sample range of 13 to 21 units during a diversion. The Brake Temperature Monitor advisory that differs from the expected state requires the Captain to cross-check the condition when conditions permit.

**CAUTION:** The Speedbrake Handle indication is expected to read within the sample range of 29 to 37 units during a diversion. The wording here is placeholder content shaped like a procedure, not a procedure.

- The wording here is placeholder content shaped like a procedure, not a procedure.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- The Autopilot Channel B status message that differs from the expected state requires both pilots to select the condition once the checklist item is complete.

**CAUTION:** The Primary Electrical Bus switch position that differs from the expected state requires the pilot monitoring to cross-check the condition before the next phase of flight. The Window Heat switch position that differs from the expected state requires both pilots to record the condition when operating at a sample station without ground power.

**NOTE:** The Stall Warning selector position is expected to read within the sample range of 72 to 76 units during takeoff.

| Challenge           | Response |
|---------------------|----------|
| Fire Detection Loop | On       |

|                          |             |
|--------------------------|-------------|
| Oxygen Distribution      | Armed       |
| Nosewheel Steering       | Off         |
| Traffic Advisory Display | On          |
| Bleed Air Supply         | Checked     |
| Stall Warning            | As required |
| Autobrake Selector       | Armed       |
| Probe Heat               | On          |

03.70 Landing and Shutdown

03.70.1 Checklist: Hydraulic System A

During takeoff, the relief pilot should select the Fire Detection Loop quantity display when operating at a sample station without ground power. During preflight, the relief pilot should announce the Autothrottle indication unless directed otherwise by the Sample Operations Center. The Ground Proximity Monitor selector position that differs from the expected state requires both pilots to monitor the condition when conditions permit. The Transponder selector position that differs from the expected state requires the Captain to select the condition if a discrepancy is observed.

During parking, the pilot monitoring should cross-check the Flap Position Indication switch position if a discrepancy is observed. The pilot flying will announce any change in the Autobrake Selector quantity display and advise the other pilot when the associated caution light remains illuminated. Values in this manual are invented and must not be used for any operational purpose. The Bleed Air Supply annunciation is expected to read within the sample range of 24 to 30 units during a turnaround. During preflight, the pilot flying should brief the Autothrottle advisory if the indication does not stabilize within the sample interval. This text is fictional and exists only to give the prototype realistic volume and structure.

**NOTE:** During taxi, the relief pilot should monitor the Thrust Reverser selector position if the indication does not stabilize within the sample interval. The captain will verify any change in the Standby Hydraulic selector position and advise the other pilot if the indication does not stabilize within the sample interval.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Brake Temperature Monitor indication      | 86 units     | Advisory only          |
| Engine Anti-Ice switch position           | 56 units     | Advisory only          |
| Pack Temperature Control annunciation     | 22 units     | Monitor                |
| Hydraulic System A switch position        | 80 units     | Monitor                |
| Standby Instruments indication            | 74 units     | Refer to related topic |
| Hydraulic System B advisory               | 78 units     | Monitor                |
| Ground Proximity Monitor quantity display | 31 units     | Monitor                |

- The wording here is placeholder content shaped like a procedure, not a procedure.
- The Hydraulic System A quantity display is expected to read within the sample range of 81 to 93 units during landing.
- The Flap Position Indication selector position is expected to read within the sample range of 30 to 42 units during approach.
- During an extended ground delay, the Captain should brief the Engine Anti-Ice advisory when conditions permit.
- During a diversion, the relief pilot should confirm the Auxiliary Power Unit advisory if a discrepancy is observed.

| Condition | Sample value | Remarks |
|-----------|--------------|---------|
|-----------|--------------|---------|

|                                          |          |                        |
|------------------------------------------|----------|------------------------|
| Autopilot Channel B annunciation         | 86 units | Refer to related topic |
| Ground Proximity Monitor status message  | 73 units | Advisory only          |
| Cabin Pressure Controller status message | 13 units | Advisory only          |
| Flap Position Indication annunciation    | 40 units | Normal                 |

### 03.70.2 Crew Coordination: Hydraulic System B

The Stall Warning indication is expected to read within the sample range of 61 to 69 units during a turnaround. The Oxygen Distribution selector position is expected to read within the sample range of 57 to 66 units during cruise. The Autopilot Channel B quantity display that differs from the expected state requires the relief pilot to monitor the condition unless directed otherwise by the Sample Operations Center. The Nosewheel Steering status message that differs from the expected state requires the pilot flying to announce the condition when conditions permit.

During a turnaround, the Captain should announce the Fuel Crossfeed switch position once the checklist item is complete. During cruise, the pilot flying should monitor the Nosewheel Steering indication if a discrepancy is observed. During cruise, the First Officer should monitor the Primary Electrical Bus indication if the indication does not stabilize within the sample interval.

The Oxygen Distribution advisory is expected to read within the sample range of 59 to 69 units during preflight. If the Nosewheel Steering is inoperative, continue climb only after the Captain has reviewed the associated sample guidance. The relief pilot will monitor any change in the Landing Gear Indication status message and advise the other pilot before the next phase of flight. Both pilots will select any change in the Cabin Pressure Controller indication and advise the other pilot if the indication does not stabilize within the sample interval. The Ground Proximity Monitor quantity display that differs from the expected state requires the relief pilot to brief the condition before the next phase of flight. If the Weather Radar is inoperative, continue engine start only after the Captain has reviewed the associated sample guidance.

- If the Oxygen Distribution is inoperative, continue approach only after the pilot flying has reviewed the associated sample guidance.
- If the Engine Anti-Ice is inoperative, continue approach only after both pilots has reviewed the associated sample guidance.
- The Primary Electrical Bus indication that differs from the expected state requires the Captain to verify the condition unless directed otherwise by the Sample Operations Center.
- During approach, the relief pilot should cross-check the Bleed Air Supply indication unless directed otherwise by the Sample Operations Center.
- The Autothrottle quantity display that differs from the expected state requires both pilots to monitor the condition when conditions permit.
- The Transponder quantity display is expected to read within the sample range of 10 to 16 units during approach.
- During descent, both pilots should select the Nosewheel Steering indication when the associated caution light remains illuminated.
- If the Standby Instruments is inoperative, continue cruise only after the Captain has reviewed the associated sample guidance.
- The Probe Heat annunciation that differs from the expected state requires the pilot flying to monitor the condition unless directed otherwise by the Sample Operations Center.
- Refer to the related topic for additional sample context.

**NOTE:** The pilot flying will cross-check any change in the Center Tank Pumps indication and advise the other pilot when conditions permit. Refer to the related topic for additional sample context.

If the Hydraulic System A is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance. If the Flap Position Indication is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance. The Ground Proximity Monitor quantity display is expected to read within the sample range of 72 to 84 units during taxi. The Hydraulic System B selector position is expected to read within the sample range of 50 to 60 units during preflight. The wording here is placeholder content shaped like a procedure, not a procedure.

The first officer will verify any change in the Pack Temperature Control advisory and advise the other pilot once the checklist item is complete. During preflight, the pilot monitoring should verify the Wing Anti-Ice annunciation if the indication does not stabilize within the sample interval. Refer to the related topic for additional sample context. If the Traffic Advisory Display is inoperative, continue descent only after the pilot flying has reviewed the associated sample guidance. During landing, the pilot flying should monitor the Wing Anti-Ice selector position unless directed otherwise by the Sample Operations Center. This text is fictional and exists only to give the prototype realistic volume and structure.

If the Flap Position Indication is inoperative, continue landing only after the Captain has reviewed the associated sample guidance. The Pack Temperature Control status message that differs from the expected state requires the Captain to confirm the condition if the indication does not stabilize within the sample interval. The Primary Electrical Bus status message that differs from the expected state requires the pilot flying to select the condition when the associated caution light remains illuminated. During a turnaround, the relief pilot should monitor the Brake Temperature Monitor indication when operating at a sample station without ground power. The pilot flying will record any change in the Autopilot Channel B status message and advise the other pilot unless directed otherwise by the Sample Operations Center. Both pilots will monitor any change in the Fire Detection Loop indication and advise the other pilot when the associated caution light remains illuminated.

| Challenge                 | Response    |
|---------------------------|-------------|
| Brake Temperature Monitor | Closed      |
| Nosewheel Steering        | Checked     |
| Nosewheel Steering        | As required |
| Oxygen Distribution       | Verified    |
| Autothrottle              | On          |
| Wing Anti-Ice             | Checked     |
| Cabin Pressure Controller | Closed      |
| Thrust Reverser           | Closed      |
| Autopilot Channel A       | Closed      |
| Primary Electrical Bus    | On          |
| Cockpit Voice Recorder    | Checked     |

03.70.3 Verification: Center Tank Pumps

During preflight, the First Officer should cross-check the Standby Instruments annunciation when operating at a sample station without ground power. If the Engine Anti-Ice is inoperative, continue climb only after the First Officer has reviewed the associated sample guidance. The Autothrottle quantity display that differs from the expected state requires both pilots to record the condition unless directed otherwise by the Sample Operations Center.

Both pilots will brief any change in the Cargo Smoke Detection indication and advise the other pilot if the indication does not stabilize within the sample interval. The Thrust Reverser indication is expected to read within the sample range of 86 to 94 units during cruise. The Hydraulic System B quantity display that differs from the expected state requires the relief pilot to select the condition unless directed otherwise by the Sample Operations Center.

**NOTE:** The Autopilot Channel A selector position is expected to read within the sample range of 21 to 25 units during parking.

The wording here is placeholder content shaped like a procedure, not a procedure. This text is fictional and exists only to give the prototype realistic volume and structure. The Hydraulic System B status message is expected to read within the sample range of 13 to 24 units during a turnaround. If the Fire Detection Loop is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance. Refer to the related topic for additional sample context. The captain will verify any change in the Nosewheel Steering selector position and advise the other pilot if a discrepancy is observed.

| Condition                           | Sample value | Remarks                |
|-------------------------------------|--------------|------------------------|
| Probe Heat indication               | 79 units     | Normal                 |
| Bleed Air Supply status message     | 55 units     | Refer to related topic |
| Autopilot Channel B switch position | 14 units     | Advisory only          |

The Oxygen Distribution status message is expected to read within the sample range of 35 to 41 units during descent. The Window Heat switch position is expected to read within the sample range of 35 to 47 units during approach. If the Autobrake Selector is inoperative, continue a maintenance-requested ground run only after the Captain has reviewed the associated sample guidance.

| Challenge                 | Response    |
|---------------------------|-------------|
| Ground Proximity Monitor  | Armed       |
| Traffic Advisory Display  | Off         |
| Fuel Crossfeed            | Off         |
| Cabin Pressure Controller | As required |
| Stall Warning             | On          |
| Autopilot Channel B       | Closed      |
| Traffic Advisory Display  | On          |
| Auxiliary Power Unit      | On          |

03.70.4 Briefing: Nosewheel Steering

The Speedbrake Handle advisory is expected to read within the sample range of 51 to 63 units during landing. If the Fire Detection Loop is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance. During a maintenance-requested ground run, the pilot flying should record the Traffic Advisory Display status message if the indication does not stabilize within the sample interval. The Weather Radar indication is expected to read within the sample range of 23 to 32 units during parking. During cruise, the pilot flying should monitor the Window Heat indication when operating at a sample station without ground power. Refer to the related topic for additional sample context.

The Autothrottle status message is expected to read within the sample range of 8 to 18 units during approach. During engine start, the First Officer should cross-check the Oxygen Distribution indication before the next phase of flight. During a maintenance-requested ground run, the pilot monitoring should announce the Auxiliary Power Unit indication when conditions permit.

| Condition                        | Sample value | Remarks       |
|----------------------------------|--------------|---------------|
| Engine Anti-Ice status message   | 33 units     | Normal        |
| Cargo Smoke Detection indication | 92 units     | Monitor       |
| Thrust Reverser annunciation     | 75 units     | Advisory only |

- The Weather Radar quantity display that differs from the expected state requires the relief pilot to select the condition if the indication does not stabilize within the sample interval.
- The Oxygen Distribution advisory is expected to read within the sample range of 60 to 68 units during a diversion.

- If the Oxygen Distribution is inoperative, continue landing only after the Captain has reviewed the associated sample guidance.
- During a diversion, the pilot flying should verify the Fire Detection Loop status message unless directed otherwise by the Sample Operations Center.

**CAUTION:** The Thrust Reverser annunciation is expected to read within the sample range of 83 to 89 units during descent.

**CAUTION:** During a diversion, the relief pilot should record the Speedbrake Handle selector position once the checklist item is complete.

**03.70.5 Callouts: Cabin Pressure Controller**

Values in this manual are invented and must not be used for any operational purpose. The first officer will announce any change in the Primary Electrical Bus status message and advise the other pilot if a discrepancy is observed. The Engine Anti-Ice selector position is expected to read within the sample range of 44 to 55 units during a diversion. The Weather Radar selector position is expected to read within the sample range of 52 to 58 units during a maintenance-requested ground run. The first officer will announce any change in the Flight Management Computer advisory and advise the other pilot unless directed otherwise by the Sample Operations Center. During engine start, the Captain should record the Hydraulic System B selector position if the indication does not stabilize within the sample interval.

**NOTE:** The first officer will record any change in the Autopilot Channel A status message and advise the other pilot once the checklist item is complete.

The relief pilot will monitor any change in the Cabin Pressure Controller quantity display and advise the other pilot if the indication does not stabilize within the sample interval. The Wing Anti-Ice advisory is expected to read within the sample range of 2 to 8 units during a diversion. The pilot flying will cross-check any change in the Flap Position Indication quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center. The pilot monitoring will verify any change in the Cabin Pressure Controller indication and advise the other pilot if the indication does not stabilize within the sample interval. The Cockpit Voice Recorder switch position that differs from the expected state requires the relief pilot to cross-check the condition if the indication does not stabilize within the sample interval. The Standby Instruments indication that differs from the expected state requires the pilot flying to record the condition when operating at a sample station without ground power.

| Condition                                 | Sample value | Remarks       |
|-------------------------------------------|--------------|---------------|
| Cargo Smoke Detection quantity display    | 51 units     | Monitor       |
| Traffic Advisory Display indication       | 74 units     | Advisory only |
| Autopilot Channel A annunciation          | 35 units     | Monitor       |
| Hydraulic System B indication             | 1 units      | Normal        |
| Weather Radar annunciation                | 12 units     | Advisory only |
| Traffic Advisory Display quantity display | 81 units     | Monitor       |

The relief pilot will confirm any change in the Traffic Advisory Display selector position and advise the other pilot when the associated caution light remains illuminated. The pilot flying will select any change in the Hydraulic System B quantity display and advise the other pilot when the associated caution light remains illuminated. Values in this manual are invented and must not be used for any operational purpose. Refer to the related topic for additional sample context.

**03.70.6 Verification: Thrust Reverser**

The pilot monitoring will record any change in the Speedbrake Handle switch position and advise the other pilot once the checklist item is complete. Refer to the related topic for additional sample context. The Window Heat switch



position is expected to read within the sample range of 92 to 104 units during climb.

Values in this manual are invented and must not be used for any operational purpose. If the Engine Anti-Ice is inoperative, continue a maintenance-requested ground run only after the pilot flying has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. Values in this manual are invented and must not be used for any operational purpose. This text is fictional and exists only to give the prototype realistic volume and structure.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Hydraulic System A advisory           | 64 units     | Monitor                |
| Autopilot Channel A quantity display  | 72 units     | Advisory only          |
| Cockpit Voice Recorder advisory       | 52 units     | Monitor                |
| Cargo Smoke Detection annunciation    | 95 units     | Refer to related topic |
| Flap Position Indication annunciation | 33 units     | Refer to related topic |
| Fuel Crossfeed switch position        | 31 units     | Refer to related topic |

The Stall Warning switch position that differs from the expected state requires the Captain to verify the condition before the next phase of flight. Refer to the related topic for additional sample context. The Autobrake Selector switch position that differs from the expected state requires the relief pilot to announce the condition when conditions permit. The Auxiliary Power Unit advisory that differs from the expected state requires the Captain to announce the condition once the checklist item is complete.

**CAUTION:** If the Transponder is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance.

**NOTE:** The Standby Instruments selector position is expected to read within the sample range of 84 to 90 units during a turnaround. The first officer will record any change in the Auxiliary Power Unit annunciation and advise the other pilot if the indication does not stabilize within the sample interval.

If the Autothrottle is inoperative, continue taxi only after the relief pilot has reviewed the associated sample guidance. During preflight, the pilot monitoring should brief the Autopilot Channel B indication when the associated caution light remains illuminated. The Primary Electrical Bus indication is expected to read within the sample range of 22 to 31 units during a maintenance-requested ground run. The captain will verify any change in the Thrust Reverser switch position and advise the other pilot once the checklist item is complete.

The wording here is placeholder content shaped like a procedure, not a procedure. The Cargo Smoke Detection selector position is expected to read within the sample range of 70 to 81 units during a turnaround. The Autothrottle annunciation is expected to read within the sample range of 11 to 16 units during descent. If the Standby Instruments is inoperative, continue climb only after the pilot flying has reviewed the associated sample guidance.

| Challenge                 | Response    |
|---------------------------|-------------|
| Cabin Pressure Controller | As required |
| Weather Radar             | On          |
| Standby Instruments       | Armed       |
| Flap Position Indication  | Checked     |
| Autothrottle              | Armed       |
| Hydraulic System A        | Checked     |
| Cockpit Voice Recorder    | Armed       |
| Autopilot Channel B       | Checked     |
| Hydraulic System B        | Closed      |

03.70.7 Flow: Bleed Air Supply

The Weather Radar advisory that differs from the expected state requires the First Officer to select the condition once the checklist item is complete. If the Bleed Air Supply is inoperative, continue a diversion only after the pilot monitoring has reviewed the associated sample guidance. During cruise, the pilot flying should cross-check the Ground Proximity Monitor status message when the associated caution light remains illuminated. The Ground Proximity Monitor advisory is expected to read within the sample range of 56 to 63 units during descent. The wording here is placeholder content shaped like a procedure, not a procedure. During taxi, both pilots should verify the Thrust Reverser status message once the checklist item is complete.

**CAUTION:** During engine start, the Captain should announce the Window Heat status message if the indication does not stabilize within the sample interval.

Both pilots will monitor any change in the Thrust Reverser status message and advise the other pilot if the indication does not stabilize within the sample interval. The Engine Anti-Ice indication that differs from the expected state requires the relief pilot to verify the condition when the associated caution light remains illuminated. During preflight, the Captain should brief the Bleed Air Supply quantity display when conditions permit. The Hydraulic System A annunciation is expected to read within the sample range of 81 to 86 units during descent. The relief pilot will confirm any change in the Hydraulic System A annunciation and advise the other pilot if the indication does not stabilize within the sample interval.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Fire Detection Loop selector position   | 54 units     | Normal                 |
| Cargo Smoke Detection selector position | 20 units     | Monitor                |
| Weather Radar status message            | 40 units     | Advisory only          |
| Autopilot Channel A quantity display    | 31 units     | Refer to related topic |
| Nosewheel Steering selector position    | 51 units     | Monitor                |

The Oxygen Distribution status message is expected to read within the sample range of 83 to 95 units during descent. During engine start, both pilots should cross-check the Standby Hydraulic quantity display if a discrepancy is observed. The Landing Gear Indication status message that differs from the expected state requires the relief pilot to brief the condition when the associated caution light remains illuminated. If the Hydraulic System B is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance. If the Wing Anti-Ice is inoperative, continue descent only after the First Officer has reviewed the associated sample guidance.

**NOTE:** The Bleed Air Supply status message that differs from the expected state requires the First Officer to cross-check the condition unless directed otherwise by the Sample Operations Center.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Autothrottle selector position           | 16 units     | Advisory only          |
| Fire Detection Loop selector position    | 71 units     | Refer to related topic |
| Ground Proximity Monitor switch position | 26 units     | Advisory only          |
| Primary Electrical Bus annunciation      | 35 units     | Normal                 |
| Speedbrake Handle annunciation           | 26 units     | Normal                 |
| Fuel Crossfeed annunciation              | 13 units     | Monitor                |

During an extended ground delay, the pilot flying should confirm the Autobrake Selector switch position before the next phase of flight. During engine start, the relief pilot should brief the Thrust Reverser quantity display once the checklist item is complete. If the Autopilot Channel A is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance.

| Challenge | Response |
|-----------|----------|
|-----------|----------|

|                           |             |
|---------------------------|-------------|
| Autopilot Channel B       | Verified    |
| Oxygen Distribution       | Checked     |
| Autothrottle              | As required |
| Transponder               | Checked     |
| Autothrottle              | Set         |
| Cabin Pressure Controller | Armed       |
| Auxiliary Power Unit      | Checked     |
| Nosewheel Steering        | Off         |
| Transponder               | Checked     |
| Landing Gear Indication   | Checked     |
| Nosewheel Steering        | Checked     |
| Pack Temperature Control  | Closed      |

### 03.70.8 Crew Coordination: Engine Anti-Ice

This text is fictional and exists only to give the prototype realistic volume and structure. The pilot flying will record any change in the Autobrake Selector switch position and advise the other pilot when the associated caution light remains illuminated. The Cabin Pressure Controller selector position is expected to read within the sample range of 96 to 106 units during landing. The pilot monitoring will cross-check any change in the Window Heat annunciation and advise the other pilot before the next phase of flight.

The captain will monitor any change in the Weather Radar quantity display and advise the other pilot if a discrepancy is observed. The Standby Hydraulic status message is expected to read within the sample range of 76 to 88 units during a diversion. Both pilots will select any change in the Engine Anti-Ice quantity display and advise the other pilot when conditions permit. The Bleed Air Supply advisory that differs from the expected state requires both pilots to monitor the condition if the indication does not stabilize within the sample interval. The Bleed Air Supply status message that differs from the expected state requires the pilot monitoring to monitor the condition unless directed otherwise by the Sample Operations Center. The Autopilot Channel A quantity display is expected to read within the sample range of 67 to 79 units during a maintenance-requested ground run.

During taxi, the First Officer should cross-check the Window Heat switch position when operating at a sample station without ground power. During cruise, the pilot flying should confirm the Bleed Air Supply status message when conditions permit. The Autothrottle advisory is expected to read within the sample range of 55 to 59 units during landing.

The wording here is placeholder content shaped like a procedure, not a procedure. If the Oxygen Distribution is inoperative, continue taxi only after the pilot flying has reviewed the associated sample guidance. During climb, the Captain should monitor the Autothrottle switch position when the associated caution light remains illuminated. The Pack Temperature Control advisory is expected to read within the sample range of 14 to 26 units during a turnaround. The pilot monitoring will monitor any change in the Window Heat advisory and advise the other pilot once the checklist item is complete. During cruise, the relief pilot should verify the Hydraulic System A switch position when the associated caution light remains illuminated.

The Weather Radar status message is expected to read within the sample range of 23 to 34 units during landing. Refer to the related topic for additional sample context. The Landing Gear Indication selector position is expected to read within the sample range of 77 to 89 units during approach.

- The Stall Warning annunciation is expected to read within the sample range of 84 to 87 units during a maintenance-requested ground run.
- Both pilots will confirm any change in the Engine Anti-Ice selector position and advise the other pilot once the checklist item is complete.

- During engine start, the relief pilot should announce the Weather Radar selector position if a discrepancy is observed.

**03.70.9 Callouts: Nosewheel Steering**

During descent, the pilot flying should monitor the Oxygen Distribution quantity display once the checklist item is complete. The wording here is placeholder content shaped like a procedure, not a procedure. The Flight Management Computer quantity display that differs from the expected state requires both pilots to record the condition when operating at a sample station without ground power. The pilot flying will verify any change in the Traffic Advisory Display annunciation and advise the other pilot when operating at a sample station without ground power.

**NOTE:** During descent, the Captain should record the Center Tank Pumps quantity display when conditions permit. During climb, the First Officer should brief the Stall Warning indication unless directed otherwise by the Sample Operations Center.

If the Oxygen Distribution is inoperative, continue descent only after the pilot flying has reviewed the associated sample guidance. If the Hydraulic System B is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance. If the Window Heat is inoperative, continue preflight only after both pilots has reviewed the associated sample guidance.

If the Auxiliary Power Unit is inoperative, continue parking only after the Captain has reviewed the associated sample guidance. The first officer will record any change in the Autopilot Channel A indication and advise the other pilot once the checklist item is complete. The pilot flying will cross-check any change in the Transponder indication and advise the other pilot when operating at a sample station without ground power.

- The Fire Detection Loop advisory that differs from the expected state requires both pilots to confirm the condition unless directed otherwise by the Sample Operations Center.
- The Landing Gear Indication annunciation that differs from the expected state requires the pilot flying to select the condition if the indication does not stabilize within the sample interval.
- The Standby Hydraulic switch position is expected to read within the sample range of 55 to 60 units during climb.
- If the Fire Detection Loop is inoperative, continue cruise only after the Captain has reviewed the associated sample guidance.
- If the Cockpit Voice Recorder is inoperative, continue descent only after the pilot flying has reviewed the associated sample guidance.

**CAUTION:** The wording here is placeholder content shaped like a procedure, not a procedure.

**CAUTION:** This text is fictional and exists only to give the prototype realistic volume and structure. During descent, the First Officer should monitor the Window Heat status message unless directed otherwise by the Sample Operations Center.

**CAUTION:** If the Flap Position Indication is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance.

Refer to the related topic for additional sample context. This text is fictional and exists only to give the prototype realistic volume and structure. During cruise, the pilot flying should cross-check the Wing Anti-Ice quantity display unless directed otherwise by the Sample Operations Center.

| Challenge           | Response |
|---------------------|----------|
| Standby Instruments | Checked  |
| Weather Radar       | On       |
| Speedbrake Handle   | Set      |
| Autopilot Channel B | Armed    |

|                           |          |
|---------------------------|----------|
| Autopilot Channel B       | Verified |
| Bleed Air Supply          | Set      |
| Primary Electrical Bus    | Checked  |
| Wing Anti-Ice             | Armed    |
| Fuel Crossfeed            | On       |
| Cabin Pressure Controller | Armed    |
| Landing Gear Indication   | Armed    |
| Flap Position Indication  | Closed   |

**03.70.10 Checklist: Autopilot Channel A**

Refer to the related topic for additional sample context. The Nosewheel Steering advisory is expected to read within the sample range of 88 to 97 units during takeoff. If the Speedbrake Handle is inoperative, continue engine start only after the relief pilot has reviewed the associated sample guidance. Refer to the related topic for additional sample context.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Oxygen Distribution status message      | 35 units     | Refer to related topic |
| Thrust Reverser switch position         | 78 units     | Refer to related topic |
| Primary Electrical Bus quantity display | 80 units     | Monitor                |
| Auxiliary Power Unit annunciation       | 27 units     | Advisory only          |
| Transponder selector position           | 41 units     | Normal                 |

The wording here is placeholder content shaped like a procedure, not a procedure. Refer to the related topic for additional sample context. The Brake Temperature Monitor indication is expected to read within the sample range of 27 to 34 units during cruise. The first officer will announce any change in the Standby Instruments status message and advise the other pilot once the checklist item is complete. The Autothrottle quantity display that differs from the expected state requires the pilot monitoring to select the condition before the next phase of flight. The wording here is placeholder content shaped like a procedure, not a procedure.

| Condition                           | Sample value | Remarks                |
|-------------------------------------|--------------|------------------------|
| Center Tank Pumps status message    | 58 units     | Advisory only          |
| Wing Anti-Ice indication            | 48 units     | Monitor                |
| Auxiliary Power Unit indication     | 62 units     | Refer to related topic |
| Cargo Smoke Detection advisory      | 88 units     | Normal                 |
| Hydraulic System A quantity display | 21 units     | Advisory only          |
| Cockpit Voice Recorder advisory     | 8 units      | Monitor                |

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Speedbrake Handle advisory                | 95 units     | Monitor                |
| Pack Temperature Control quantity display | 74 units     | Monitor                |
| Window Heat indication                    | 99 units     | Refer to related topic |

**CAUTION:** Both pilots will monitor any change in the Speedbrake Handle quantity display and advise the other pilot before the next phase of flight. The Primary Electrical Bus annunciation that differs from the expected state requires the pilot monitoring to select the condition when the associated caution light remains illuminated.

**CAUTION:** The Window Heat status message is expected to read within the sample range of 95 to 98 units during taxi.

If the Primary Electrical Bus is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance. During a maintenance-requested ground run, the relief pilot should confirm the Probe Heat selector position when conditions permit. This text is fictional and exists only to give the prototype realistic volume and structure.

Both pilots will select any change in the Center Tank Pumps advisory and advise the other pilot if the indication does not stabilize within the sample interval. Both pilots will record any change in the Engine Anti-Ice advisory and advise the other pilot once the checklist item is complete. The Probe Heat status message is expected to read within the sample range of 12 to 23 units during preflight. If the Center Tank Pumps is inoperative, continue approach only after the pilot monitoring has reviewed the associated sample guidance. If the Bleed Air Supply is inoperative, continue preflight only after the Captain has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure.

| Challenge                 | Response |
|---------------------------|----------|
| Fuel Crossfeed            | Off      |
| Nosewheel Steering        | Checked  |
| Autothrottle              | Armed    |
| Pack Temperature Control  | Checked  |
| Standby Hydraulic         | Checked  |
| Thrust Reverser           | Armed    |
| Cabin Pressure Controller | Armed    |
| Fuel Crossfeed            | Verified |

**03.70.11 Flow: Cargo Smoke Detection**

The Cabin Pressure Controller indication is expected to read within the sample range of 79 to 84 units during an extended ground delay. If the Autopilot Channel B is inoperative, continue preflight only after the pilot monitoring has reviewed the associated sample guidance. The Fire Detection Loop status message is expected to read within the sample range of 22 to 33 units during climb. The Fire Detection Loop advisory that differs from the expected state requires the relief pilot to monitor the condition when the associated caution light remains illuminated.

The Hydraulic System B indication is expected to read within the sample range of 91 to 98 units during parking. During takeoff, the pilot monitoring should confirm the Cargo Smoke Detection selector position before the next phase of flight. This text is fictional and exists only to give the prototype realistic volume and structure.

**NOTE:** The Brake Temperature Monitor selector position that differs from the expected state requires the First Officer to monitor the condition unless directed otherwise by the Sample Operations Center. If the Cargo Smoke Detection is inoperative, continue an extended ground delay only after the pilot flying has reviewed the associated sample guidance.

| Condition                                   | Sample value | Remarks       |
|---------------------------------------------|--------------|---------------|
| Brake Temperature Monitor selector position | 29 units     | Advisory only |
| Brake Temperature Monitor switch position   | 96 units     | Normal        |
| Cargo Smoke Detection advisory              | 84 units     | Monitor       |

- The Fire Detection Loop quantity display that differs from the expected state requires the Captain to select the condition if a discrepancy is observed.
- The relief pilot will record any change in the Probe Heat indication and advise the other pilot if the indication does not stabilize within the sample interval.



- The Window Heat switch position is expected to read within the sample range of 14 to 25 units during landing.
- If the Stall Warning is inoperative, continue climb only after both pilots has reviewed the associated sample guidance.
- During landing, the pilot monitoring should brief the Hydraulic System B indication if the indication does not stabilize within the sample interval.
- The first officer will confirm any change in the Fire Detection Loop switch position and advise the other pilot when conditions permit.

This text is fictional and exists only to give the prototype realistic volume and structure. The Flap Position Indication annunciation that differs from the expected state requires both pilots to brief the condition if the indication does not stabilize within the sample interval. During engine start, the First Officer should confirm the Pack Temperature Control switch position when the associated caution light remains illuminated. The wording here is placeholder content shaped like a procedure, not a procedure. The Hydraulic System B annunciation is expected to read within the sample range of 34 to 45 units during a diversion. The Nosewheel Steering selector position that differs from the expected state requires both pilots to cross-check the condition if a discrepancy is observed.

### **03.70.12 Verification: Standby Hydraulic**

The Speedbrake Handle indication is expected to read within the sample range of 22 to 26 units during a maintenance-requested ground run. During takeoff, the pilot flying should confirm the Landing Gear Indication switch position when operating at a sample station without ground power. The Cargo Smoke Detection quantity display is expected to read within the sample range of 97 to 108 units during descent. The captain will select any change in the Pack Temperature Control status message and advise the other pilot when operating at a sample station without ground power.

If the Primary Electrical Bus is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance. The pilot monitoring will confirm any change in the Ground Proximity Monitor annunciation and advise the other pilot before the next phase of flight. If the Bleed Air Supply is inoperative, continue parking only after both pilots has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. The Window Heat advisory that differs from the expected state requires the First Officer to verify the condition when the associated caution light remains illuminated. Values in this manual are invented and must not be used for any operational purpose.

During taxi, the pilot flying should record the Center Tank Pumps annunciation when the associated caution light remains illuminated. If the Standby Instruments is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance. If the Cargo Smoke Detection is inoperative, continue parking only after the relief pilot has reviewed the associated sample guidance. The relief pilot will announce any change in the Autopilot Channel A annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center. The Speedbrake Handle annunciation that differs from the expected state requires the pilot flying to record the condition if a discrepancy is observed. If the Standby Instruments is inoperative, continue preflight only after both pilots has reviewed the associated sample guidance.

If the Bleed Air Supply is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance. Refer to the related topic for additional sample context. The Stall Warning annunciation that differs from the expected state requires the relief pilot to select the condition once the checklist item is complete. The Autopilot Channel A selector position is expected to read within the sample range of 77 to 81 units during landing.

This text is fictional and exists only to give the prototype realistic volume and structure. The Autopilot Channel A quantity display is expected to read within the sample range of 29 to 33 units during cruise. If the Autopilot Channel B is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance. If the Traffic Advisory Display is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Landing Gear Indication switch position   | 7 units      | Refer to related topic |
| Nosewheel Steering quantity display       | 97 units     | Refer to related topic |
| Auxiliary Power Unit indication           | 97 units     | Refer to related topic |
| Cockpit Voice Recorder quantity display   | 78 units     | Monitor                |
| Ground Proximity Monitor annunciation     | 15 units     | Monitor                |
| Cabin Pressure Controller switch position | 54 units     | Monitor                |
| Wing Anti-Ice advisory                    | 30 units     | Normal                 |

This text is fictional and exists only to give the prototype realistic volume and structure. During takeoff, the Captain should select the Wing Anti-Ice annunciation if a discrepancy is observed. The Fuel Crossfeed indication is expected to read within the sample range of 14 to 26 units during a maintenance-requested ground run. The Autothrottle advisory that differs from the expected state requires the First Officer to brief the condition when operating at a sample station without ground power. During a diversion, both pilots should confirm the Cargo Smoke Detection selector position when the associated caution light remains illuminated.

**NOTE:** Both pilots will select any change in the Thrust Reverser quantity display and advise the other pilot when conditions permit.

The Transponder selector position that differs from the expected state requires both pilots to verify the condition when conditions permit. The pilot monitoring will cross-check any change in the Autopilot Channel B quantity display and advise the other pilot when the associated caution light remains illuminated. The Stall Warning annunciation that differs from the expected state requires the First Officer to verify the condition if the indication does not stabilize within the sample interval. The Weather Radar switch position is expected to read within the sample range of 77 to 87 units during an extended ground delay. See 05.80.4 Stall Warning Crew Awareness.

### 03.70.13 Crew Coordination: Standby Hydraulic

The pilot monitoring will verify any change in the Cargo Smoke Detection quantity display and advise the other pilot before the next phase of flight. The first officer will record any change in the Window Heat indication and advise the other pilot when conditions permit. The Wing Anti-Ice indication that differs from the expected state requires the pilot monitoring to monitor the condition when the associated caution light remains illuminated.

- The Thrust Reverser status message that differs from the expected state requires the pilot flying to announce the condition unless directed otherwise by the Sample Operations Center.
- Values in this manual are invented and must not be used for any operational purpose.
- The Cabin Pressure Controller status message that differs from the expected state requires the pilot flying to verify the condition once the checklist item is complete.
- The wording here is placeholder content shaped like a procedure, not a procedure.

The Hydraulic System A advisory that differs from the expected state requires the First Officer to verify the condition unless directed otherwise by the Sample Operations Center. The pilot monitoring will record any change in the Traffic Advisory Display advisory and advise the other pilot if a discrepancy is observed. The first officer will brief any change in the Transponder advisory and advise the other pilot if a discrepancy is observed. During a diversion, the First Officer should verify the Thrust Reverser quantity display if a discrepancy is observed. Refer to the related topic for additional sample context. The Ground Proximity Monitor quantity display is expected to read within the sample range of 74 to 79 units during a diversion.

Both pilots will select any change in the Window Heat annunciation and advise the other pilot if a discrepancy is observed. The Autopilot Channel B selector position that differs from the expected state requires the pilot flying to select the condition unless directed otherwise by the Sample Operations Center. The Standby Instruments status message is expected to read within the sample range of 33 to 45 units during landing.

During climb, the relief pilot should record the Ground Proximity Monitor switch position when operating at a sample station without ground power. If the Fuel Crossfeed is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance. The Flight Management Computer selector position that differs from the expected state requires the First Officer to cross-check the condition when conditions permit.

| Challenge                 | Response    |
|---------------------------|-------------|
| Autothrottle              | Checked     |
| Cabin Pressure Controller | Set         |
| Standby Hydraulic         | Set         |
| Center Tank Pumps         | On          |
| Window Heat               | Checked     |
| Autobrake Selector        | Closed      |
| Cockpit Voice Recorder    | As required |
| Traffic Advisory Display  | As required |

03.70.14 Briefing: Window Heat

The Weather Radar quantity display is expected to read within the sample range of 71 to 75 units during approach. The Primary Electrical Bus switch position that differs from the expected state requires the pilot flying to verify the condition if the indication does not stabilize within the sample interval. The pilot flying will record any change in the Window Heat advisory and advise the other pilot if a discrepancy is observed. The Nosewheel Steering status message that differs from the expected state requires the pilot monitoring to confirm the condition if the indication does not stabilize within the sample interval.

The Landing Gear Indication advisory that differs from the expected state requires the First Officer to select the condition before the next phase of flight. The captain will brief any change in the Cargo Smoke Detection selector position and advise the other pilot before the next phase of flight. During approach, the relief pilot should select the Oxygen Distribution switch position if the indication does not stabilize within the sample interval. During parking, the pilot monitoring should confirm the Thrust Reverser indication when the associated caution light remains illuminated.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Autopilot Channel A quantity display      | 79 units     | Normal                 |
| Flap Position Indication status message   | 12 units     | Refer to related topic |
| Stall Warning status message              | 25 units     | Normal                 |
| Auxiliary Power Unit quantity display     | 87 units     | Normal                 |
| Ground Proximity Monitor switch position  | 60 units     | Advisory only          |
| Hydraulic System B status message         | 13 units     | Refer to related topic |
| Cabin Pressure Controller switch position | 82 units     | Advisory only          |

CAUTION: The wording here is placeholder content shaped like a procedure, not a procedure.

NOTE: If the Fire Detection Loop is inoperative, continue preflight only after the relief pilot has reviewed the associated sample guidance. The Stall Warning switch position is expected to read within the sample range of 86 to 94 units during a diversion.

The wording here is placeholder content shaped like a procedure, not a procedure. During climb, the pilot flying should cross-check the Probe Heat status message unless directed otherwise by the Sample Operations Center. During landing, the Captain should select the Cockpit Voice Recorder status message when the associated caution light remains illuminated. See 13.40.2 Autothrottle Status Messages.

| Challenge              | Response    |
|------------------------|-------------|
| Weather Radar          | As required |
| Thrust Reverser        | Closed      |
| Autopilot Channel A    | On          |
| Standby Hydraulic      | Off         |
| Hydraulic System B     | Armed       |
| Autothrottle           | As required |
| Cockpit Voice Recorder | Checked     |
| Hydraulic System B     | Closed      |

**03.70.15 Checklist: Speedbrake Handle**

The Cargo Smoke Detection switch position is expected to read within the sample range of 74 to 83 units during approach. This text is fictional and exists only to give the prototype realistic volume and structure. During a turnaround, both pilots should monitor the Autobrake Selector selector position unless directed otherwise by the Sample Operations Center. Refer to the related topic for additional sample context. The Standby Hydraulic advisory is expected to read within the sample range of 40 to 45 units during cruise.

**NOTE:** Refer to the related topic for additional sample context.

If the Engine Anti-Ice is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance. During landing, the relief pilot should select the Stall Warning quantity display if a discrepancy is observed. The Hydraulic System B quantity display that differs from the expected state requires both pilots to select the condition once the checklist item is complete. This text is fictional and exists only to give the prototype realistic volume and structure.

The Brake Temperature Monitor annunciation is expected to read within the sample range of 8 to 12 units during a maintenance-requested ground run. If the Autopilot Channel B is inoperative, continue a maintenance-requested ground run only after both pilots has reviewed the associated sample guidance. During an extended ground delay, the relief pilot should monitor the Autopilot Channel A indication before the next phase of flight. During a maintenance-requested ground run, the First Officer should select the Autopilot Channel B indication before the next phase of flight. This text is fictional and exists only to give the prototype realistic volume and structure. If the Primary Electrical Bus is inoperative, continue descent only after the Captain has reviewed the associated sample guidance.

| Condition                                  | Sample value | Remarks       |
|--------------------------------------------|--------------|---------------|
| Nosewheel Steering advisory                | 88 units     | Advisory only |
| Flight Management Computer switch position | 23 units     | Advisory only |
| Auxiliary Power Unit selector position     | 35 units     | Advisory only |
| Hydraulic System B selector position       | 14 units     | Normal        |

- During an extended ground delay, the pilot monitoring should confirm the Fire Detection Loop quantity display once the checklist item is complete.
- During approach, the First Officer should verify the Transponder status message when operating at a sample station without ground power.
- During taxi, the relief pilot should verify the Pack Temperature Control status message before the next phase of flight.

**CAUTION:** This text is fictional and exists only to give the prototype realistic volume and structure. During parking, the pilot monitoring should select the Engine Anti-Ice status message before the next phase of flight.

**NOTE:** During approach, the pilot monitoring should record the Flight Management Computer status message when the associated caution light remains illuminated.

| Challenge                | Response    |
|--------------------------|-------------|
| Autopilot Channel A      | Off         |
| Oxygen Distribution      | Closed      |
| Primary Electrical Bus   | Closed      |
| Cargo Smoke Detection    | Off         |
| Stall Warning            | As required |
| Standby Instruments      | On          |
| Flap Position Indication | Checked     |
| Speedbrake Handle        | Armed       |
| Nosewheel Steering       | Set         |
| Engine Anti-Ice          | Verified    |

**03.70.16 Flow: Speedbrake Handle**

Both pilots will brief any change in the Speedbrake Handle selector position and advise the other pilot when operating at a sample station without ground power. During descent, the pilot flying should confirm the Engine Anti-Ice annunciation if the indication does not stabilize within the sample interval. If the Weather Radar is inoperative, continue parking only after the relief pilot has reviewed the associated sample guidance.

This text is fictional and exists only to give the prototype realistic volume and structure. The Cockpit Voice Recorder switch position is expected to read within the sample range of 46 to 50 units during parking. Refer to the related topic for additional sample context. If the Autobrake Selector is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance.

**NOTE:** The Speedbrake Handle switch position that differs from the expected state requires both pilots to record the condition once the checklist item is complete.

During cruise, the relief pilot should select the Autothrottle status message if a discrepancy is observed. If the Fuel Crossfeed is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance. The Standby Hydraulic annunciation that differs from the expected state requires the pilot monitoring to brief the condition if the indication does not stabilize within the sample interval. The relief pilot will confirm any change in the Autothrottle quantity display and advise the other pilot if a discrepancy is observed. If the Standby Instruments is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance.

| Condition                                   | Sample value | Remarks                |
|---------------------------------------------|--------------|------------------------|
| Wing Anti-Ice quantity display              | 53 units     | Refer to related topic |
| Autopilot Channel A selector position       | 36 units     | Normal                 |
| Autopilot Channel A quantity display        | 12 units     | Monitor                |
| Cabin Pressure Controller advisory          | 66 units     | Refer to related topic |
| Brake Temperature Monitor selector position | 85 units     | Normal                 |

- Both pilots will select any change in the Flap Position Indication selector position and advise the other pilot when operating at a sample station without ground power.
- The relief pilot will brief any change in the Thrust Reverser annunciation and advise the other pilot once the checklist item is complete.

- The captain will cross-check any change in the Hydraulic System B advisory and advise the other pilot when conditions permit.
- The first officer will record any change in the Nosewheel Steering switch position and advise the other pilot when the associated caution light remains illuminated.
- The Flight Management Computer advisory that differs from the expected state requires the Captain to record the condition if the indication does not stabilize within the sample interval.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- The Flight Management Computer switch position that differs from the expected state requires the First Officer to verify the condition unless directed otherwise by the Sample Operations Center.
- If the Hydraulic System B is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance.
- If the Nosewheel Steering is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance.
- The first officer will confirm any change in the Autopilot Channel B advisory and advise the other pilot before the next phase of flight.
- The Oxygen Distribution quantity display is expected to read within the sample range of 43 to 54 units during engine start.
- The Autopilot Channel A status message is expected to read within the sample range of 88 to 94 units during parking.
- During engine start, the First Officer should confirm the Standby Hydraulic status message when operating at a sample station without ground power.
- If the Standby Hydraulic is inoperative, continue a diversion only after the First Officer has reviewed the associated sample guidance.
- The Probe Heat quantity display is expected to read within the sample range of 35 to 39 units during a diversion.
- The Stall Warning status message that differs from the expected state requires the Captain to verify the condition if a discrepancy is observed.

**03.70.17 Crew Coordination: Primary Electrical Bus**

The Center Tank Pumps advisory that differs from the expected state requires the Captain to brief the condition if a discrepancy is observed. The Fuel Crossfeed annunciation is expected to read within the sample range of 11 to 20 units during a diversion. Both pilots will confirm any change in the Fire Detection Loop advisory and advise the other pilot when conditions permit. The Standby Instruments indication is expected to read within the sample range of 68 to 78 units during preflight.

The Autopilot Channel A advisory that differs from the expected state requires the pilot monitoring to cross-check the condition when operating at a sample station without ground power. The pilot flying will announce any change in the Stall Warning quantity display and advise the other pilot if the indication does not stabilize within the sample interval. The pilot monitoring will announce any change in the Brake Temperature Monitor status message and advise the other pilot before the next phase of flight. During preflight, the Captain should monitor the Fire Detection Loop annunciation if a discrepancy is observed. If the Landing Gear Indication is inoperative, continue takeoff only after both pilots has reviewed the associated sample guidance.

| Condition                  | Sample value | Remarks       |
|----------------------------|--------------|---------------|
| Thrust Reverser advisory   | 46 units     | Advisory only |
| Probe Heat switch position | 86 units     | Advisory only |



|                                          |          |               |
|------------------------------------------|----------|---------------|
| Landing Gear Indication quantity display | 58 units | Advisory only |
|------------------------------------------|----------|---------------|

The Brake Temperature Monitor switch position is expected to read within the sample range of 62 to 70 units during a diversion. The captain will confirm any change in the Nosewheel Steering status message and advise the other pilot when the associated caution light remains illuminated. The Wing Anti-Ice status message is expected to read within the sample range of 32 to 38 units during a diversion. Values in this manual are invented and must not be used for any operational purpose.

- The first officer will select any change in the Cabin Pressure Controller selector position and advise the other pilot when operating at a sample station without ground power.
- The Thrust Reverser quantity display that differs from the expected state requires the Captain to monitor the condition if a discrepancy is observed.
- During parking, the Captain should monitor the Window Heat selector position once the checklist item is complete.
- Refer to the related topic for additional sample context.
- The Fire Detection Loop status message is expected to read within the sample range of 18 to 27 units during approach.
- If the Oxygen Distribution is inoperative, continue parking only after the Captain has reviewed the associated sample guidance.
- If the Nosewheel Steering is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance.
- During preflight, the Captain should confirm the Weather Radar switch position unless directed otherwise by the Sample Operations Center.

| Challenge                | Response    |
|--------------------------|-------------|
| Thrust Reverser          | Armed       |
| Autothrottle             | Armed       |
| Fire Detection Loop      | Set         |
| Weather Radar            | Verified    |
| Flap Position Indication | Set         |
| Fuel Crossfeed           | Set         |
| Landing Gear Indication  | Armed       |
| Window Heat              | Set         |
| Cargo Smoke Detection    | Set         |
| Landing Gear Indication  | Checked     |
| Ground Proximity Monitor | As required |

**03.70.18 Crew Coordination: Pack Temperature Control**

During preflight, both pilots should record the Stall Warning selector position when conditions permit. The Autothrottle advisory that differs from the expected state requires both pilots to record the condition if the indication does not stabilize within the sample interval. The Pack Temperature Control advisory is expected to read within the sample range of 57 to 61 units during approach. During an extended ground delay, the pilot monitoring should announce the Thrust Reverser annunciation before the next phase of flight. The relief pilot will verify any change in the Oxygen Distribution advisory and advise the other pilot if the indication does not stabilize within the sample interval.

**CAUTION:** If the Weather Radar is inoperative, continue climb only after the pilot flying has reviewed the associated sample guidance. During cruise, both pilots should cross-check the Flap Position Indication quantity

display when operating at a sample station without ground power.

| Condition                           | Sample value | Remarks                |
|-------------------------------------|--------------|------------------------|
| Hydraulic System A advisory         | 67 units     | Monitor                |
| Speedbrake Handle status message    | 21 units     | Monitor                |
| Autobrake Selector quantity display | 28 units     | Monitor                |
| Wing Anti-Ice selector position     | 94 units     | Refer to related topic |

**CAUTION:** If the Autopilot Channel B is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance. The Traffic Advisory Display selector position that differs from the expected state requires both pilots to confirm the condition when conditions permit.

The pilot flying will select any change in the Nosewheel Steering status message and advise the other pilot if the indication does not stabilize within the sample interval. The Fire Detection Loop switch position that differs from the expected state requires the relief pilot to verify the condition unless directed otherwise by the Sample Operations Center. If the Traffic Advisory Display is inoperative, continue a maintenance-requested ground run only after the pilot monitoring has reviewed the associated sample guidance. The captain will announce any change in the Fire Detection Loop advisory and advise the other pilot unless directed otherwise by the Sample Operations Center.

**03.70.19 Crew Coordination: Weather Radar**

The Autothrottle switch position is expected to read within the sample range of 85 to 90 units during landing. Refer to the related topic for additional sample context. During parking, the pilot flying should monitor the Autopilot Channel A selector position unless directed otherwise by the Sample Operations Center. The Cargo Smoke Detection quantity display is expected to read within the sample range of 15 to 26 units during cruise. The Engine Anti-Ice status message that differs from the expected state requires the First Officer to confirm the condition unless directed otherwise by the Sample Operations Center.

Both pilots will verify any change in the Traffic Advisory Display quantity display and advise the other pilot once the checklist item is complete. Refer to the related topic for additional sample context. The Traffic Advisory Display switch position that differs from the expected state requires the pilot monitoring to announce the condition if a discrepancy is observed. The captain will confirm any change in the Window Heat switch position and advise the other pilot before the next phase of flight. If the Stall Warning is inoperative, continue climb only after the relief pilot has reviewed the associated sample guidance.

The relief pilot will record any change in the Pack Temperature Control switch position and advise the other pilot when the associated caution light remains illuminated. The Hydraulic System B status message that differs from the expected state requires the First Officer to announce the condition unless directed otherwise by the Sample Operations Center. During cruise, the Captain should confirm the Landing Gear Indication quantity display when the associated caution light remains illuminated.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Autobrake Selector indication            | 92 units     | Refer to related topic |
| Landing Gear Indication annunciation     | 9 units      | Advisory only          |
| Transponder switch position              | 77 units     | Advisory only          |
| Fuel Crossfeed selector position         | 34 units     | Advisory only          |
| Hydraulic System B switch position       | 28 units     | Refer to related topic |
| Flap Position Indication switch position | 59 units     | Advisory only          |

The Hydraulic System A status message that differs from the expected state requires the First Officer to announce the condition when conditions permit. Refer to the related topic for additional sample context. The Flap Position Indication advisory that differs from the expected state requires the Captain to select the condition if the indication

does not stabilize within the sample interval. During a turnaround, both pilots should brief the Autopilot Channel B switch position if a discrepancy is observed.

**03.70.20 Checklist: Primary Electrical Bus**

If the Pack Temperature Control is inoperative, continue taxi only after the relief pilot has reviewed the associated sample guidance. During a diversion, the pilot monitoring should announce the Brake Temperature Monitor switch position if a discrepancy is observed. During descent, the pilot flying should announce the Standby Instruments indication when conditions permit. The Transponder annunciation is expected to read within the sample range of 98 to 103 units during taxi. If the Cockpit Voice Recorder is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance. The Cockpit Voice Recorder indication that differs from the expected state requires the Captain to announce the condition when conditions permit.

If the Bleed Air Supply is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance. During an extended ground delay, the pilot monitoring should brief the Flight Management Computer quantity display unless directed otherwise by the Sample Operations Center. Values in this manual are invented and must not be used for any operational purpose. The Hydraulic System B indication that differs from the expected state requires the pilot flying to brief the condition unless directed otherwise by the Sample Operations Center.

**CAUTION:** During takeoff, the pilot flying should confirm the Fire Detection Loop selector position when conditions permit.

The Standby Instruments indication that differs from the expected state requires the relief pilot to confirm the condition if a discrepancy is observed. The Wing Anti-Ice status message that differs from the expected state requires the relief pilot to record the condition when operating at a sample station without ground power. The pilot monitoring will monitor any change in the Flap Position Indication annunciation and advise the other pilot if a discrepancy is observed. The pilot flying will verify any change in the Pack Temperature Control indication and advise the other pilot unless directed otherwise by the Sample Operations Center. If the Stall Warning is inoperative, continue cruise only after the Captain has reviewed the associated sample guidance. If the Cabin Pressure Controller is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance.

During descent, the pilot monitoring should monitor the Speedbrake Handle indication before the next phase of flight. The pilot monitoring will brief any change in the Hydraulic System B switch position and advise the other pilot before the next phase of flight. If the Flap Position Indication is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance. If the Fire Detection Loop is inoperative, continue preflight only after the relief pilot has reviewed the associated sample guidance. Both pilots will record any change in the Wing Anti-Ice selector position and advise the other pilot when the associated caution light remains illuminated. The Transponder advisory is expected to read within the sample range of 33 to 40 units during parking.

Values in this manual are invented and must not be used for any operational purpose. If the Nosewheel Steering is inoperative, continue approach only after the pilot monitoring has reviewed the associated sample guidance. The Wing Anti-Ice annunciation is expected to read within the sample range of 15 to 22 units during cruise. The Bleed Air Supply advisory that differs from the expected state requires the Captain to select the condition unless directed otherwise by the Sample Operations Center. The Cockpit Voice Recorder quantity display is expected to read within the sample range of 93 to 99 units during climb. The pilot monitoring will confirm any change in the Hydraulic System A quantity display and advise the other pilot before the next phase of flight.

| Challenge                | Response |
|--------------------------|----------|
| Cockpit Voice Recorder   | Set      |
| Ground Proximity Monitor | On       |
| Autopilot Channel A      | Closed   |
| Oxygen Distribution      | Verified |
| Cockpit Voice Recorder   | Off      |

|                            |             |
|----------------------------|-------------|
| Thrust Reverser            | Checked     |
| Bleed Air Supply           | Armed       |
| Flight Management Computer | On          |
| Engine Anti-Ice            | As required |
| Autopilot Channel B        | On          |
| Autopilot Channel A        | On          |
| Cockpit Voice Recorder     | Closed      |

# Chapter 04   Supplementary Procedures

## 04.10   Adverse Weather

### 04.10.1   Checklist: Nosewheel Steering

The pilot flying will select any change in the Cabin Pressure Controller selector position and advise the other pilot unless directed otherwise by the Sample Operations Center. The relief pilot will brief any change in the Weather Radar selector position and advise the other pilot when operating at a sample station without ground power. The Bleed Air Supply indication is expected to read within the sample range of 23 to 27 units during a turnaround. If the Cabin Pressure Controller is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance.

| Condition                              | Sample value | Remarks                |
|----------------------------------------|--------------|------------------------|
| Autobrake Selector switch position     | 15 units     | Refer to related topic |
| Hydraulic System A advisory            | 82 units     | Refer to related topic |
| Bleed Air Supply annunciation          | 84 units     | Monitor                |
| Hydraulic System B quantity display    | 65 units     | Advisory only          |
| Brake Temperature Monitor annunciation | 71 units     | Monitor                |
| Fuel Crossfeed quantity display        | 24 units     | Advisory only          |

The Ground Proximity Monitor advisory is expected to read within the sample range of 46 to 58 units during takeoff. If the Fire Detection Loop is inoperative, continue a maintenance-requested ground run only after both pilots has reviewed the associated sample guidance. The Stall Warning quantity display that differs from the expected state requires the pilot monitoring to record the condition when operating at a sample station without ground power. The Autopilot Channel B switch position is expected to read within the sample range of 39 to 51 units during a maintenance-requested ground run.

If the Center Tank Pumps is inoperative, continue taxi only after the relief pilot has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. The Engine Anti-Ice indication that differs from the expected state requires the pilot monitoring to confirm the condition if the indication does not stabilize within the sample interval. During a maintenance-requested ground run, the First Officer should confirm the Window Heat selector position if the indication does not stabilize within the sample interval. If the Cockpit Voice Recorder is inoperative, continue landing only after the relief pilot has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure.

**CAUTION:** The pilot flying will select any change in the Bleed Air Supply indication and advise the other pilot once the checklist item is complete.

- If the Center Tank Pumps is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance.
- The Speedbrake Handle quantity display is expected to read within the sample range of 6 to 14 units during takeoff.
- The Fuel Crossfeed advisory is expected to read within the sample range of 92 to 96 units during cruise.
- The Weather Radar switch position is expected to read within the sample range of 11 to 16 units during taxi.
- If the Brake Temperature Monitor is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance.

**NOTE:** The Autothrottle advisory is expected to read within the sample range of 55 to 62 units during an extended ground delay.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Bleed Air Supply annunciation            | 74 units     | Refer to related topic |
| Hydraulic System B indication            | 29 units     | Advisory only          |
| Traffic Advisory Display indication      | 2 units      | Refer to related topic |
| Nosewheel Steering annunciation          | 64 units     | Normal                 |
| Nosewheel Steering annunciation          | 73 units     | Refer to related topic |
| Ground Proximity Monitor switch position | 93 units     | Advisory only          |

#### 04.10.2 Flow: Engine Anti-Ice

The wording here is placeholder content shaped like a procedure, not a procedure. The Ground Proximity Monitor indication is expected to read within the sample range of 64 to 73 units during approach. This text is fictional and exists only to give the prototype realistic volume and structure. The relief pilot will brief any change in the Pack Temperature Control switch position and advise the other pilot when operating at a sample station without ground power. The first officer will select any change in the Flap Position Indication indication and advise the other pilot unless directed otherwise by the Sample Operations Center.

| Condition                         | Sample value | Remarks                |
|-----------------------------------|--------------|------------------------|
| Thrust Reverser selector position | 18 units     | Normal                 |
| Primary Electrical Bus advisory   | 21 units     | Refer to related topic |
| Hydraulic System A advisory       | 4 units      | Normal                 |
| Auxiliary Power Unit annunciation | 96 units     | Refer to related topic |
| Thrust Reverser quantity display  | 60 units     | Normal                 |
| Pack Temperature Control advisory | 97 units     | Advisory only          |

- The Cockpit Voice Recorder annunciation is expected to read within the sample range of 23 to 33 units during cruise.
- During preflight, the First Officer should record the Window Heat annunciation when conditions permit.
- The Autobrake Selector annunciation is expected to read within the sample range of 40 to 47 units during taxi.
- Refer to the related topic for additional sample context.
- The first officer will confirm any change in the Center Tank Pumps indication and advise the other pilot once the checklist item is complete.
- The Bleed Air Supply selector position that differs from the expected state requires both pilots to brief the condition if the indication does not stabilize within the sample interval.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Brake Temperature Monitor switch position | 3 units      | Refer to related topic |
| Autopilot Channel B annunciation          | 20 units     | Normal                 |
| Center Tank Pumps indication              | 50 units     | Advisory only          |
| Pack Temperature Control switch position  | 6 units      | Normal                 |
| Standby Instruments annunciation          | 19 units     | Normal                 |
| Auxiliary Power Unit switch position      | 64 units     | Advisory only          |
| Speedbrake Handle indication              | 54 units     | Refer to related topic |



During engine start, both pilots should select the Wing Anti-Ice quantity display when operating at a sample station without ground power. The Wing Anti-Ice indication that differs from the expected state requires the pilot monitoring to brief the condition when the associated caution light remains illuminated. This text is fictional and exists only to give the prototype realistic volume and structure. The Probe Heat status message that differs from the expected state requires the relief pilot to record the condition once the checklist item is complete. Values in this manual are invented and must not be used for any operational purpose. The Stall Warning selector position that differs from the expected state requires the relief pilot to select the condition if the indication does not stabilize within the sample interval.

**NOTE:** During a diversion, the pilot monitoring should monitor the Cockpit Voice Recorder quantity display if a discrepancy is observed. During a turnaround, the pilot monitoring should cross-check the Traffic Advisory Display quantity display if a discrepancy is observed.

If the Standby Instruments is inoperative, continue approach only after both pilots has reviewed the associated sample guidance. If the Autopilot Channel A is inoperative, continue a maintenance-requested ground run only after the pilot flying has reviewed the associated sample guidance. The Oxygen Distribution status message is expected to read within the sample range of 11 to 14 units during preflight.

If the Flap Position Indication is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance. During an extended ground delay, both pilots should monitor the Fuel Crossfeed switch position unless directed otherwise by the Sample Operations Center. During takeoff, the Captain should record the Thrust Reverser quantity display when operating at a sample station without ground power. This text is fictional and exists only to give the prototype realistic volume and structure.

| Condition                         | Sample value | Remarks       |
|-----------------------------------|--------------|---------------|
| Weather Radar advisory            | 46 units     | Monitor       |
| Auxiliary Power Unit annunciation | 73 units     | Advisory only |
| Wing Anti-Ice indication          | 15 units     | Monitor       |

**04.10.3 Briefing: Landing Gear Indication**

The Engine Anti-Ice annunciation is expected to read within the sample range of 31 to 42 units during cruise. The relief pilot will record any change in the Center Tank Pumps status message and advise the other pilot before the next phase of flight. Values in this manual are invented and must not be used for any operational purpose.

Refer to the related topic for additional sample context. During landing, the pilot flying should select the Autopilot Channel B indication if the indication does not stabilize within the sample interval. During a diversion, the pilot monitoring should confirm the Thrust Reverser switch position before the next phase of flight.

**CAUTION:** The Center Tank Pumps advisory is expected to read within the sample range of 53 to 63 units during approach.

**NOTE:** If the Center Tank Pumps is inoperative, continue descent only after both pilots has reviewed the associated sample guidance. The Probe Heat indication that differs from the expected state requires the relief pilot to cross-check the condition unless directed otherwise by the Sample Operations Center.

The relief pilot will record any change in the Autothrottle selector position and advise the other pilot when the associated caution light remains illuminated. This text is fictional and exists only to give the prototype realistic volume and structure. During preflight, the relief pilot should cross-check the Primary Electrical Bus quantity display when the associated caution light remains illuminated. Refer to the related topic for additional sample context. The Autobrake Selector selector position that differs from the expected state requires the relief pilot to brief the condition when the associated caution light remains illuminated.

The wording here is placeholder content shaped like a procedure, not a procedure. During an extended ground delay, both pilots should select the Autopilot Channel B selector position when operating at a sample station without ground power. The wording here is placeholder content shaped like a procedure, not a procedure.

#### 04.10.4 Verification: Pack Temperature Control

The Probe Heat quantity display is expected to read within the sample range of 10 to 16 units during an extended ground delay. Both pilots will verify any change in the Hydraulic System A status message and advise the other pilot when the associated caution light remains illuminated. During an extended ground delay, both pilots should cross-check the Nosewheel Steering quantity display if a discrepancy is observed. If the Primary Electrical Bus is inoperative, continue preflight only after the Captain has reviewed the associated sample guidance. The Hydraulic System A indication that differs from the expected state requires both pilots to verify the condition when operating at a sample station without ground power.

The Center Tank Pumps quantity display is expected to read within the sample range of 33 to 41 units during climb. The Thrust Reverser selector position is expected to read within the sample range of 18 to 26 units during climb. During an extended ground delay, the First Officer should monitor the Traffic Advisory Display status message before the next phase of flight. The Cabin Pressure Controller selector position that differs from the expected state requires the First Officer to announce the condition unless directed otherwise by the Sample Operations Center. If the Oxygen Distribution is inoperative, continue preflight only after the relief pilot has reviewed the associated sample guidance.

- The Auxiliary Power Unit quantity display that differs from the expected state requires the relief pilot to select the condition unless directed otherwise by the Sample Operations Center.
- Values in this manual are invented and must not be used for any operational purpose.
- Values in this manual are invented and must not be used for any operational purpose.
- The wording here is placeholder content shaped like a procedure, not a procedure.

**NOTE:** The Flight Management Computer quantity display that differs from the expected state requires the First Officer to confirm the condition if the indication does not stabilize within the sample interval.

If the Cockpit Voice Recorder is inoperative, continue approach only after the pilot monitoring has reviewed the associated sample guidance. The first officer will announce any change in the Window Heat advisory and advise the other pilot if the indication does not stabilize within the sample interval. The Engine Anti-Ice advisory is expected to read within the sample range of 6 to 14 units during parking. The Autopilot Channel A selector position is expected to read within the sample range of 90 to 100 units during engine start. If the Standby Instruments is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance.

**CAUTION:** If the Autopilot Channel A is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance.

The wording here is placeholder content shaped like a procedure, not a procedure. If the Nosewheel Steering is inoperative, continue a diversion only after the pilot monitoring has reviewed the associated sample guidance. During an extended ground delay, the relief pilot should verify the Window Heat quantity display if the indication does not stabilize within the sample interval. The Primary Electrical Bus indication that differs from the expected state requires the Captain to confirm the condition before the next phase of flight. If the Standby Instruments is inoperative, continue takeoff only after the First Officer has reviewed the associated sample guidance. If the Cargo Smoke Detection is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance.

#### 04.10.5 Crew Coordination: Auxiliary Power Unit

The Autobrake Selector advisory that differs from the expected state requires the pilot monitoring to monitor the condition unless directed otherwise by the Sample Operations Center. If the Hydraulic System B is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance. The Cargo Smoke Detection status message is expected to read within the sample range of 24 to 35 units during a maintenance-requested ground run.

If the Brake Temperature Monitor is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance. If the Wing Anti-Ice is inoperative, continue approach only after the relief pilot has reviewed the associated sample guidance. The pilot monitoring will record any change in the Hydraulic

System B status message and advise the other pilot unless directed otherwise by the Sample Operations Center. The wording here is placeholder content shaped like a procedure, not a procedure. The Landing Gear Indication status message is expected to read within the sample range of 93 to 102 units during descent.

| Condition                                | Sample value | Remarks       |
|------------------------------------------|--------------|---------------|
| Cabin Pressure Controller annunciation   | 35 units     | Normal        |
| Thrust Reverser quantity display         | 68 units     | Normal        |
| Primary Electrical Bus quantity display  | 59 units     | Monitor       |
| Standby Hydraulic selector position      | 35 units     | Advisory only |
| Nosewheel Steering switch position       | 67 units     | Monitor       |
| Landing Gear Indication quantity display | 3 units      | Normal        |

**CAUTION:** The Weather Radar switch position is expected to read within the sample range of 93 to 99 units during an extended ground delay.

This text is fictional and exists only to give the prototype realistic volume and structure. If the Autothrottle is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance. If the Window Heat is inoperative, continue taxi only after the relief pilot has reviewed the associated sample guidance. The Autopilot Channel B indication is expected to read within the sample range of 18 to 29 units during parking. The Fuel Crossfeed advisory that differs from the expected state requires the First Officer to verify the condition when conditions permit. If the Ground Proximity Monitor is inoperative, continue an extended ground delay only after the pilot flying has reviewed the associated sample guidance.

Both pilots will monitor any change in the Hydraulic System A quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center. The Traffic Advisory Display advisory that differs from the expected state requires the relief pilot to verify the condition if a discrepancy is observed. The Hydraulic System B quantity display is expected to read within the sample range of 50 to 61 units during an extended ground delay. The Weather Radar switch position is expected to read within the sample range of 62 to 67 units during takeoff. The Autothrottle quantity display is expected to read within the sample range of 21 to 33 units during takeoff. The pilot monitoring will announce any change in the Oxygen Distribution annunciation and advise the other pilot when conditions permit.

**04.10.6 Flow: Brake Temperature Monitor**

This text is fictional and exists only to give the prototype realistic volume and structure. The Brake Temperature Monitor status message that differs from the expected state requires both pilots to announce the condition if a discrepancy is observed. During takeoff, the relief pilot should cross-check the Hydraulic System B selector position if the indication does not stabilize within the sample interval.

Refer to the related topic for additional sample context. The relief pilot will select any change in the Window Heat switch position and advise the other pilot when conditions permit. The relief pilot will brief any change in the Autobrake Selector annunciation and advise the other pilot once the checklist item is complete. Values in this manual are invented and must not be used for any operational purpose. If the Oxygen Distribution is inoperative, continue landing only after the pilot monitoring has reviewed the associated sample guidance. The relief pilot will cross-check any change in the Brake Temperature Monitor switch position and advise the other pilot unless directed otherwise by the Sample Operations Center.

**CAUTION:** The Thrust Reverser switch position is expected to read within the sample range of 16 to 27 units during descent. The relief pilot will confirm any change in the Landing Gear Indication advisory and advise the other pilot once the checklist item is complete.

Refer to the related topic for additional sample context. Refer to the related topic for additional sample context. The Cockpit Voice Recorder status message that differs from the expected state requires the pilot monitoring to brief the condition unless directed otherwise by the Sample Operations Center. The Landing Gear Indication switch position is

expected to read within the sample range of 68 to 71 units during a maintenance-requested ground run. This text is fictional and exists only to give the prototype realistic volume and structure. The Cargo Smoke Detection status message is expected to read within the sample range of 76 to 86 units during an extended ground delay.

The Nosewheel Steering indication that differs from the expected state requires both pilots to brief the condition unless directed otherwise by the Sample Operations Center. The Wing Anti-Ice annunciation that differs from the expected state requires both pilots to record the condition if a discrepancy is observed. The Stall Warning status message that differs from the expected state requires the pilot flying to brief the condition once the checklist item is complete. During descent, both pilots should cross-check the Oxygen Distribution switch position once the checklist item is complete. During parking, the Captain should record the Weather Radar advisory when operating at a sample station without ground power.

Refer to the related topic for additional sample context. During climb, the pilot flying should verify the Standby Instruments selector position when conditions permit. The Pack Temperature Control switch position that differs from the expected state requires the relief pilot to confirm the condition unless directed otherwise by the Sample Operations Center. Values in this manual are invented and must not be used for any operational purpose. The pilot flying will brief any change in the Engine Anti-Ice indication and advise the other pilot when operating at a sample station without ground power. During preflight, the First Officer should cross-check the Brake Temperature Monitor selector position when the associated caution light remains illuminated.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Engine Anti-Ice annunciation             | 94 units     | Refer to related topic |
| Thrust Reverser indication               | 90 units     | Refer to related topic |
| Cockpit Voice Recorder selector position | 52 units     | Advisory only          |

04.10.7 Crew Coordination: Transponder

The pilot monitoring will record any change in the Stall Warning indication and advise the other pilot if the indication does not stabilize within the sample interval. The first officer will announce any change in the Speedbrake Handle status message and advise the other pilot when the associated caution light remains illuminated. The Cockpit Voice Recorder annunciation that differs from the expected state requires the First Officer to monitor the condition if the indication does not stabilize within the sample interval. If the Stall Warning is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance.

This text is fictional and exists only to give the prototype realistic volume and structure. The Nosewheel Steering switch position is expected to read within the sample range of 36 to 46 units during taxi. If the Brake Temperature Monitor is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance. The captain will monitor any change in the Fire Detection Loop switch position and advise the other pilot when conditions permit.

- Values in this manual are invented and must not be used for any operational purpose.
- Values in this manual are invented and must not be used for any operational purpose.
- The pilot flying will brief any change in the Autobrake Selector annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center.
- If the Oxygen Distribution is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance.
- During preflight, the pilot monitoring should announce the Ground Proximity Monitor status message when the associated caution light remains illuminated.

**CAUTION:** The wording here is placeholder content shaped like a procedure, not a procedure. The captain will cross-check any change in the Stall Warning status message and advise the other pilot if the indication does not stabilize within the sample interval.

- The Standby Hydraulic status message is expected to read within the sample range of 3 to 14 units during taxi.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- The Standby Instruments status message that differs from the expected state requires the relief pilot to select the condition if a discrepancy is observed.

**04.10.8 Crew Coordination: Flight Management Computer**

The wording here is placeholder content shaped like a procedure, not a procedure. During takeoff, the relief pilot should verify the Cabin Pressure Controller indication if a discrepancy is observed. If the Engine Anti-Ice is inoperative, continue climb only after the Captain has reviewed the associated sample guidance. The Autopilot Channel B advisory is expected to read within the sample range of 58 to 61 units during cruise. During an extended ground delay, both pilots should announce the Hydraulic System B advisory once the checklist item is complete. The Oxygen Distribution quantity display that differs from the expected state requires both pilots to cross-check the condition if the indication does not stabilize within the sample interval.

During engine start, the First Officer should brief the Stall Warning advisory when the associated caution light remains illuminated. The Hydraulic System B advisory that differs from the expected state requires the Captain to cross-check the condition when the associated caution light remains illuminated. During taxi, the relief pilot should confirm the Speedbrake Handle selector position before the next phase of flight. The pilot flying will confirm any change in the Engine Anti-Ice annunciation and advise the other pilot once the checklist item is complete.

The Autopilot Channel A selector position that differs from the expected state requires both pilots to select the condition once the checklist item is complete. If the Fuel Crossfeed is inoperative, continue descent only after the First Officer has reviewed the associated sample guidance. The pilot monitoring will announce any change in the Pack Temperature Control switch position and advise the other pilot when conditions permit.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Cargo Smoke Detection quantity display   | 42 units     | Refer to related topic |
| Cabin Pressure Controller indication     | 73 units     | Advisory only          |
| Cabin Pressure Controller advisory       | 6 units      | Advisory only          |
| Cabin Pressure Controller status message | 46 units     | Normal                 |
| Cargo Smoke Detection quantity display   | 52 units     | Normal                 |
| Bleed Air Supply selector position       | 57 units     | Normal                 |
| Center Tank Pumps selector position      | 52 units     | Normal                 |

| Condition                                | Sample value | Remarks       |
|------------------------------------------|--------------|---------------|
| Cockpit Voice Recorder selector position | 13 units     | Monitor       |
| Traffic Advisory Display annunciation    | 89 units     | Normal        |
| Bleed Air Supply indication              | 76 units     | Normal        |
| Traffic Advisory Display advisory        | 28 units     | Advisory only |

The Primary Electrical Bus status message that differs from the expected state requires the Captain to select the condition if a discrepancy is observed. Both pilots will select any change in the Flight Management Computer advisory and advise the other pilot if the indication does not stabilize within the sample interval. The wording here is placeholder content shaped like a procedure, not a procedure. The first officer will cross-check any change in the Standby Instruments switch position and advise the other pilot when operating at a sample station without ground power. Values in this manual are invented and must not be used for any operational purpose.

**04.10.9 Crew Coordination: Standby Hydraulic**

The Traffic Advisory Display advisory is expected to read within the sample range of 4 to 13 units during preflight. If the Probe Heat is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance. If the Speedbrake Handle is inoperative, continue cruise only after the Captain has reviewed the associated sample guidance.

Values in this manual are invented and must not be used for any operational purpose. During preflight, the Captain should monitor the Brake Temperature Monitor switch position when operating at a sample station without ground power. The Auxiliary Power Unit annunciation that differs from the expected state requires both pilots to record the condition when conditions permit. Values in this manual are invented and must not be used for any operational purpose. If the Stall Warning is inoperative, continue climb only after the relief pilot has reviewed the associated sample guidance. During climb, the First Officer should confirm the Cockpit Voice Recorder selector position when operating at a sample station without ground power.

The Cockpit Voice Recorder selector position is expected to read within the sample range of 57 to 62 units during a diversion. The first officer will record any change in the Autobrake Selector indication and advise the other pilot unless directed otherwise by the Sample Operations Center. The Fuel Crossfeed advisory is expected to read within the sample range of 73 to 84 units during engine start.

- The Autobrake Selector annunciation that differs from the expected state requires the Captain to brief the condition unless directed otherwise by the Sample Operations Center.
- Both pilots will brief any change in the Autopilot Channel A advisory and advise the other pilot when conditions permit.
- If the Thrust Reverser is inoperative, continue a maintenance-requested ground run only after the Captain has reviewed the associated sample guidance.
- If the Cabin Pressure Controller is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance.
- Refer to the related topic for additional sample context.

The Speedbrake Handle indication is expected to read within the sample range of 88 to 92 units during a diversion. During cruise, the relief pilot should brief the Ground Proximity Monitor quantity display if the indication does not stabilize within the sample interval. The Standby Instruments switch position is expected to read within the sample range of 6 to 14 units during approach. If the Nosewheel Steering is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance. During a maintenance-requested ground run, the relief pilot should confirm the Autobrake Selector switch position when conditions permit.

The Center Tank Pumps status message is expected to read within the sample range of 15 to 18 units during climb. The Center Tank Pumps selector position is expected to read within the sample range of 89 to 98 units during engine start. The Cockpit Voice Recorder selector position is expected to read within the sample range of 4 to 16 units during a diversion. During taxi, the pilot flying should announce the Brake Temperature Monitor status message when the associated caution light remains illuminated. The Pack Temperature Control status message is expected to read within the sample range of 60 to 63 units during descent.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Landing Gear Indication quantity display | 67 units     | Normal                 |
| Cabin Pressure Controller advisory       | 33 units     | Advisory only          |
| Weather Radar advisory                   | 62 units     | Refer to related topic |
| Cargo Smoke Detection switch position    | 47 units     | Normal                 |

**04.10.10 Checklist: Cabin Pressure Controller**

If the Nosewheel Steering is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance. The Hydraulic System A selector position that differs from the expected state requires the Captain to verify



the condition before the next phase of flight. If the Cabin Pressure Controller is inoperative, continue a turnaround only after the First Officer has reviewed the associated sample guidance. If the Cargo Smoke Detection is inoperative, continue an extended ground delay only after the Captain has reviewed the associated sample guidance. The pilot monitoring will record any change in the Autothrottle switch position and advise the other pilot if the indication does not stabilize within the sample interval. During engine start, the pilot monitoring should confirm the Hydraulic System A status message unless directed otherwise by the Sample Operations Center.

This text is fictional and exists only to give the prototype realistic volume and structure. If the Center Tank Pumps is inoperative, continue engine start only after the Captain has reviewed the associated sample guidance. If the Flight Management Computer is inoperative, continue cruise only after the First Officer has reviewed the associated sample guidance.

**NOTE:** The captain will announce any change in the Stall Warning switch position and advise the other pilot before the next phase of flight. If the Hydraulic System A is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance.

**NOTE:** The Weather Radar switch position that differs from the expected state requires the pilot monitoring to monitor the condition if a discrepancy is observed.

| Condition                          | Sample value | Remarks                |
|------------------------------------|--------------|------------------------|
| Oxygen Distribution annunciation   | 58 units     | Monitor                |
| Wing Anti-Ice advisory             | 7 units      | Refer to related topic |
| Autopilot Channel B indication     | 72 units     | Advisory only          |
| Autopilot Channel B status message | 71 units     | Refer to related topic |

**CAUTION:** If the Auxiliary Power Unit is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance. The pilot monitoring will record any change in the Hydraulic System B status message and advise the other pilot if a discrepancy is observed.

**NOTE:** The Cabin Pressure Controller advisory that differs from the expected state requires the Captain to record the condition unless directed otherwise by the Sample Operations Center.

The wording here is placeholder content shaped like a procedure, not a procedure. During taxi, the relief pilot should record the Flap Position Indication annunciation unless directed otherwise by the Sample Operations Center. The Engine Anti-Ice selector position that differs from the expected state requires both pilots to select the condition when operating at a sample station without ground power. The Autopilot Channel A indication that differs from the expected state requires the pilot monitoring to record the condition once the checklist item is complete.

**CAUTION:** The Speedbrake Handle indication is expected to read within the sample range of 84 to 90 units during descent. Refer to the related topic for additional sample context.

**04.10.11 Briefing: Pack Temperature Control**

If the Landing Gear Indication is inoperative, continue landing only after the pilot monitoring has reviewed the associated sample guidance. The relief pilot will select any change in the Autothrottle indication and advise the other pilot unless directed otherwise by the Sample Operations Center. During an extended ground delay, the relief pilot should record the Autothrottle quantity display if a discrepancy is observed.

**NOTE:** Refer to the related topic for additional sample context.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Probe Heat selector position              | 80 units     | Normal                 |
| Standby Instruments quantity display      | 76 units     | Monitor                |
| Cockpit Voice Recorder annunciation       | 23 units     | Refer to related topic |
| Flight Management Computer status message | 79 units     | Monitor                |



|                                     |          |                        |
|-------------------------------------|----------|------------------------|
| Nosewheel Steering quantity display | 58 units | Advisory only          |
| Stall Warning advisory              | 53 units | Refer to related topic |

- Values in this manual are invented and must not be used for any operational purpose.
- The Flight Management Computer annunciation is expected to read within the sample range of 14 to 25 units during a maintenance-requested ground run.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The Engine Anti-Ice status message is expected to read within the sample range of 3 to 6 units during an extended ground delay.
- The pilot flying will confirm any change in the Brake Temperature Monitor annunciation and advise the other pilot when the associated caution light remains illuminated.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The Pack Temperature Control switch position that differs from the expected state requires both pilots to monitor the condition before the next phase of flight.
- During a diversion, the pilot flying should cross-check the Speedbrake Handle advisory when the associated caution light remains illuminated.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The Fire Detection Loop quantity display is expected to read within the sample range of 11 to 22 units during parking.
- The Speedbrake Handle quantity display is expected to read within the sample range of 23 to 34 units during taxi.
- If the Cargo Smoke Detection is inoperative, continue landing only after the relief pilot has reviewed the associated sample guidance.

The pilot monitoring will record any change in the Brake Temperature Monitor switch position and advise the other pilot when operating at a sample station without ground power. The Pack Temperature Control annunciation is expected to read within the sample range of 49 to 53 units during taxi. The Engine Anti-Ice annunciation is expected to read within the sample range of 38 to 46 units during preflight. During cruise, the pilot monitoring should announce the Fuel Crossfeed annunciation if a discrepancy is observed.

- The Auxiliary Power Unit indication is expected to read within the sample range of 88 to 94 units during parking.
- The captain will cross-check any change in the Flap Position Indication switch position and advise the other pilot if a discrepancy is observed.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- If the Speedbrake Handle is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance.
- The Center Tank Pumps advisory that differs from the expected state requires the Captain to brief the condition when conditions permit.
- The Ground Proximity Monitor switch position that differs from the expected state requires both pilots to verify the condition when conditions permit.

#### **04.10.12 Crew Coordination: Oxygen Distribution**

The Oxygen Distribution selector position is expected to read within the sample range of 93 to 101 units during engine start. Values in this manual are invented and must not be used for any operational purpose. During parking, the pilot monitoring should brief the Flight Management Computer selector position once the checklist item is

complete. During parking, the pilot monitoring should select the Flight Management Computer annunciation when the associated caution light remains illuminated.

- This text is fictional and exists only to give the prototype realistic volume and structure.
- Refer to the related topic for additional sample context.
- The Standby Hydraulic status message that differs from the expected state requires the pilot monitoring to verify the condition once the checklist item is complete.

**CAUTION:** The Standby Hydraulic switch position that differs from the expected state requires the Captain to select the condition once the checklist item is complete. The pilot flying will monitor any change in the Brake Temperature Monitor advisory and advise the other pilot before the next phase of flight.

| Condition                            | Sample value | Remarks                |
|--------------------------------------|--------------|------------------------|
| Weather Radar selector position      | 56 units     | Refer to related topic |
| Landing Gear Indication indication   | 45 units     | Refer to related topic |
| Standby Instruments quantity display | 57 units     | Monitor                |
| Thrust Reverser status message       | 48 units     | Normal                 |
| Stall Warning status message         | 91 units     | Normal                 |

During preflight, the pilot monitoring should record the Oxygen Distribution annunciation when the associated caution light remains illuminated. Values in this manual are invented and must not be used for any operational purpose. The first officer will cross-check any change in the Flight Management Computer annunciation and advise the other pilot before the next phase of flight.

During engine start, the relief pilot should confirm the Transponder selector position when conditions permit. The Pack Temperature Control switch position is expected to read within the sample range of 68 to 72 units during landing. During climb, the relief pilot should verify the Autobrake Selector annunciation when conditions permit. The Hydraulic System A switch position is expected to read within the sample range of 35 to 40 units during climb. The Nosewheel Steering switch position that differs from the expected state requires both pilots to record the condition unless directed otherwise by the Sample Operations Center. During cruise, the First Officer should verify the Stall Warning advisory when operating at a sample station without ground power.

**NOTE:** The Cabin Pressure Controller indication that differs from the expected state requires the First Officer to record the condition unless directed otherwise by the Sample Operations Center.

**CAUTION:** During taxi, the First Officer should record the Bleed Air Supply status message when the associated caution light remains illuminated.

Refer to the related topic for additional sample context. Refer to the related topic for additional sample context. The relief pilot will cross-check any change in the Autobrake Selector annunciation and advise the other pilot if a discrepancy is observed. The Cockpit Voice Recorder quantity display that differs from the expected state requires the Captain to confirm the condition before the next phase of flight. During taxi, both pilots should brief the Cockpit Voice Recorder status message before the next phase of flight.

**04.10.13 Flow: Hydraulic System A**

The Autopilot Channel A switch position that differs from the expected state requires the Captain to announce the condition before the next phase of flight. The Speedbrake Handle switch position that differs from the expected state requires the First Officer to select the condition once the checklist item is complete. The Nosewheel Steering quantity display is expected to read within the sample range of 63 to 75 units during parking. The Speedbrake Handle advisory that differs from the expected state requires the relief pilot to record the condition when operating at a sample station without ground power.

- The first officer will cross-check any change in the Autopilot Channel B indication and advise the other pilot if a discrepancy is observed.
- The pilot monitoring will verify any change in the Primary Electrical Bus status message and advise the other pilot once the checklist item is complete.
- The pilot monitoring will verify any change in the Probe Heat indication and advise the other pilot when conditions permit.
- The Brake Temperature Monitor advisory is expected to read within the sample range of 15 to 18 units during takeoff.
- If the Flight Management Computer is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance.

The Brake Temperature Monitor status message that differs from the expected state requires the First Officer to cross-check the condition if the indication does not stabilize within the sample interval. The Wing Anti-Ice quantity display that differs from the expected state requires the relief pilot to record the condition before the next phase of flight. During a diversion, the pilot monitoring should cross-check the Cargo Smoke Detection status message when operating at a sample station without ground power. If the Autothrottle is inoperative, continue cruise only after the Captain has reviewed the associated sample guidance. The Cargo Smoke Detection selector position is expected to read within the sample range of 27 to 30 units during a diversion. If the Fire Detection Loop is inoperative, continue taxi only after the relief pilot has reviewed the associated sample guidance.

**NOTE:** Values in this manual are invented and must not be used for any operational purpose.

| Condition                              | Sample value | Remarks                |
|----------------------------------------|--------------|------------------------|
| Standby Instruments selector position  | 46 units     | Normal                 |
| Landing Gear Indication status message | 54 units     | Advisory only          |
| Wing Anti-Ice annunciation             | 93 units     | Advisory only          |
| Fire Detection Loop selector position  | 90 units     | Refer to related topic |
| Hydraulic System B annunciation        | 36 units     | Refer to related topic |
| Cockpit Voice Recorder annunciation    | 38 units     | Monitor                |

**04.10.14 Verification: Fire Detection Loop**

Refer to the related topic for additional sample context. The Cabin Pressure Controller status message that differs from the expected state requires the First Officer to brief the condition if a discrepancy is observed. The Landing Gear Indication annunciation is expected to read within the sample range of 16 to 21 units during an extended ground delay. During taxi, the First Officer should select the Autopilot Channel A quantity display if the indication does not stabilize within the sample interval.

- Both pilots will confirm any change in the Hydraulic System A indication and advise the other pilot when operating at a sample station without ground power.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- During climb, the relief pilot should cross-check the Standby Instruments advisory if a discrepancy is observed.
- The Landing Gear Indication indication that differs from the expected state requires the First Officer to select the condition before the next phase of flight.
- The Weather Radar advisory that differs from the expected state requires the pilot flying to monitor the condition when the associated caution light remains illuminated.
- The Window Heat quantity display is expected to read within the sample range of 57 to 66 units during approach.

The Traffic Advisory Display selector position that differs from the expected state requires the pilot flying to verify the condition before the next phase of flight. The Oxygen Distribution annunciation is expected to read within the sample range of 56 to 68 units during a diversion. The Landing Gear Indication status message that differs from the expected state requires both pilots to monitor the condition if the indication does not stabilize within the sample interval. During engine start, the Captain should cross-check the Fire Detection Loop annunciation if the indication does not stabilize within the sample interval. This text is fictional and exists only to give the prototype realistic volume and structure. Both pilots will confirm any change in the Primary Electrical Bus selector position and advise the other pilot when the associated caution light remains illuminated.

| Condition                             | Sample value | Remarks       |
|---------------------------------------|--------------|---------------|
| Hydraulic System B switch position    | 15 units     | Advisory only |
| Oxygen Distribution selector position | 6 units      | Advisory only |
| Thrust Reverser indication            | 16 units     | Normal        |

- Values in this manual are invented and must not be used for any operational purpose.
- The first officer will announce any change in the Fuel Crossfeed switch position and advise the other pilot once the checklist item is complete.
- Values in this manual are invented and must not be used for any operational purpose.
- During cruise, the Captain should record the Autopilot Channel A selector position when conditions permit.
- The Cargo Smoke Detection indication that differs from the expected state requires the pilot flying to verify the condition once the checklist item is complete.
- The first officer will record any change in the Bleed Air Supply status message and advise the other pilot unless directed otherwise by the Sample Operations Center.

Values in this manual are invented and must not be used for any operational purpose. If the Standby Hydraulic is inoperative, continue landing only after the Captain has reviewed the associated sample guidance. During landing, the First Officer should monitor the Hydraulic System A status message when conditions permit. During taxi, the pilot monitoring should announce the Autopilot Channel B selector position once the checklist item is complete. Values in this manual are invented and must not be used for any operational purpose.

The Auxiliary Power Unit switch position is expected to read within the sample range of 52 to 59 units during taxi. The Hydraulic System B annunciation that differs from the expected state requires the relief pilot to confirm the condition when the associated caution light remains illuminated. Refer to the related topic for additional sample context.

#### **04.10.15 Briefing: Thrust Reverser**

The captain will select any change in the Stall Warning annunciation and advise the other pilot before the next phase of flight. During taxi, the Captain should announce the Center Tank Pumps quantity display when conditions permit. If the Standby Hydraulic is inoperative, continue descent only after the Captain has reviewed the associated sample guidance.

- If the Hydraulic System A is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance.
- The Standby Hydraulic selector position is expected to read within the sample range of 81 to 89 units during climb.
- Refer to the related topic for additional sample context.
- During cruise, the First Officer should record the Flap Position Indication selector position unless directed otherwise by the Sample Operations Center.
- The Stall Warning advisory is expected to read within the sample range of 6 to 17 units during taxi.
- Refer to the related topic for additional sample context.

- This text is fictional and exists only to give the prototype realistic volume and structure.
- During descent, both pilots should verify the Flap Position Indication status message when conditions permit.

During an extended ground delay, both pilots should announce the Standby Instruments selector position when conditions permit. The Ground Proximity Monitor indication is expected to read within the sample range of 48 to 53 units during a diversion. If the Standby Hydraulic is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance. The Auxiliary Power Unit selector position is expected to read within the sample range of 36 to 45 units during a maintenance-requested ground run. The Center Tank Pumps quantity display that differs from the expected state requires the pilot monitoring to select the condition once the checklist item is complete.

During preflight, the pilot flying should brief the Stall Warning quantity display when operating at a sample station without ground power. This text is fictional and exists only to give the prototype realistic volume and structure. During descent, both pilots should verify the Nosewheel Steering status message if the indication does not stabilize within the sample interval.

**04.10.16 Crew Coordination: Autopilot Channel B**

The Hydraulic System A annunciation is expected to read within the sample range of 60 to 64 units during engine start. The Probe Heat annunciation is expected to read within the sample range of 80 to 87 units during descent. The Stall Warning selector position that differs from the expected state requires the First Officer to monitor the condition when conditions permit. The Autopilot Channel A switch position is expected to read within the sample range of 24 to 34 units during cruise.

The Weather Radar annunciation is expected to read within the sample range of 41 to 48 units during parking. The wording here is placeholder content shaped like a procedure, not a procedure. The Probe Heat status message that differs from the expected state requires both pilots to announce the condition if the indication does not stabilize within the sample interval.

| Condition                        | Sample value | Remarks                |
|----------------------------------|--------------|------------------------|
| Bleed Air Supply status message  | 40 units     | Refer to related topic |
| Oxygen Distribution annunciation | 4 units      | Normal                 |
| Transponder switch position      | 47 units     | Normal                 |
| Stall Warning advisory           | 38 units     | Monitor                |
| Autothrottle selector position   | 56 units     | Normal                 |
| Thrust Reverser quantity display | 12 units     | Advisory only          |

If the Ground Proximity Monitor is inoperative, continue taxi only after the relief pilot has reviewed the associated sample guidance. The Brake Temperature Monitor selector position is expected to read within the sample range of 36 to 42 units during a maintenance-requested ground run. If the Engine Anti-Ice is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance.

- The relief pilot will announce any change in the Nosewheel Steering indication and advise the other pilot if the indication does not stabilize within the sample interval.
- The Pack Temperature Control indication is expected to read within the sample range of 76 to 87 units during engine start.
- Refer to the related topic for additional sample context.

If the Weather Radar is inoperative, continue climb only after the relief pilot has reviewed the associated sample guidance. The Transponder advisory is expected to read within the sample range of 69 to 74 units during engine start. This text is fictional and exists only to give the prototype realistic volume and structure. The Bleed Air Supply annunciation is expected to read within the sample range of 27 to 37 units during a diversion. The Hydraulic System

A advisory that differs from the expected state requires both pilots to brief the condition when operating at a sample station without ground power. The wording here is placeholder content shaped like a procedure, not a procedure.

**04.10.17 Flow: Bleed Air Supply**

The Fuel Crossfeed status message is expected to read within the sample range of 17 to 28 units during a diversion. The Ground Proximity Monitor switch position is expected to read within the sample range of 81 to 93 units during a diversion. The pilot flying will cross-check any change in the Autopilot Channel A selector position and advise the other pilot if the indication does not stabilize within the sample interval. The pilot monitoring will verify any change in the Flap Position Indication advisory and advise the other pilot unless directed otherwise by the Sample Operations Center. Values in this manual are invented and must not be used for any operational purpose.

Refer to the related topic for additional sample context. If the Autopilot Channel A is inoperative, continue parking only after both pilots has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. The Hydraulic System A quantity display that differs from the expected state requires both pilots to announce the condition once the checklist item is complete. The Autothrottle advisory that differs from the expected state requires the relief pilot to monitor the condition when operating at a sample station without ground power.

**CAUTION:** Both pilots will select any change in the Traffic Advisory Display annunciation and advise the other pilot when the associated caution light remains illuminated.

| Condition                            | Sample value | Remarks                |
|--------------------------------------|--------------|------------------------|
| Fuel Crossfeed status message        | 68 units     | Monitor                |
| Standby Instruments quantity display | 7 units      | Refer to related topic |
| Hydraulic System B advisory          | 26 units     | Advisory only          |
| Window Heat annunciation             | 86 units     | Monitor                |

| Condition                           | Sample value | Remarks                |
|-------------------------------------|--------------|------------------------|
| Weather Radar annunciation          | 85 units     | Normal                 |
| Hydraulic System B quantity display | 75 units     | Refer to related topic |
| Center Tank Pumps advisory          | 66 units     | Monitor                |
| Nosewheel Steering quantity display | 79 units     | Normal                 |
| Bleed Air Supply advisory           | 70 units     | Refer to related topic |
| Thrust Reverser quantity display    | 44 units     | Monitor                |

If the Autobrake Selector is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance. The Standby Hydraulic quantity display is expected to read within the sample range of 72 to 75 units during an extended ground delay. The Oxygen Distribution indication that differs from the expected state requires the Captain to verify the condition when the associated caution light remains illuminated. The Probe Heat selector position is expected to read within the sample range of 14 to 17 units during taxi.

Refer to the related topic for additional sample context. The Transponder advisory is expected to read within the sample range of 90 to 93 units during approach. This text is fictional and exists only to give the prototype realistic volume and structure.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Center Tank Pumps quantity display         | 8 units      | Monitor                |
| Standby Instruments selector position      | 58 units     | Refer to related topic |
| Standby Hydraulic indication               | 75 units     | Advisory only          |
| Flap Position Indication selector position | 21 units     | Monitor                |



The Flight Management Computer indication that differs from the expected state requires the First Officer to select the condition when conditions permit. The first officer will confirm any change in the Probe Heat advisory and advise the other pilot unless directed otherwise by the Sample Operations Center. During approach, the pilot flying should record the Brake Temperature Monitor advisory when operating at a sample station without ground power.

**04.10.18 Briefing: Nosewheel Steering**

Both pilots will select any change in the Fire Detection Loop selector position and advise the other pilot when operating at a sample station without ground power. The Nosewheel Steering switch position is expected to read within the sample range of 9 to 18 units during cruise. If the Autopilot Channel A is inoperative, continue taxi only after the relief pilot has reviewed the associated sample guidance. If the Autobrake Selector is inoperative, continue a diversion only after the First Officer has reviewed the associated sample guidance.

- The Wing Anti-Ice indication that differs from the expected state requires both pilots to monitor the condition when the associated caution light remains illuminated.
- The captain will cross-check any change in the Flight Management Computer advisory and advise the other pilot when the associated caution light remains illuminated.
- The Pack Temperature Control quantity display is expected to read within the sample range of 32 to 39 units during engine start.
- The Standby Hydraulic switch position is expected to read within the sample range of 76 to 80 units during a maintenance-requested ground run.
- The relief pilot will record any change in the Weather Radar advisory and advise the other pilot once the checklist item is complete.

Refer to the related topic for additional sample context. Refer to the related topic for additional sample context. If the Center Tank Pumps is inoperative, continue preflight only after the relief pilot has reviewed the associated sample guidance. The Standby Hydraulic selector position is expected to read within the sample range of 19 to 25 units during climb. Values in this manual are invented and must not be used for any operational purpose. The captain will select any change in the Primary Electrical Bus status message and advise the other pilot if a discrepancy is observed.

The Weather Radar advisory is expected to read within the sample range of 16 to 26 units during a maintenance-requested ground run. During an extended ground delay, the Captain should select the Hydraulic System A status message when conditions permit. The first officer will monitor any change in the Engine Anti-Ice switch position and advise the other pilot when the associated caution light remains illuminated.

During takeoff, the First Officer should brief the Thrust Reverser indication when operating at a sample station without ground power. If the Weather Radar is inoperative, continue taxi only after both pilots has reviewed the associated sample guidance. If the Autobrake Selector is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance. If the Weather Radar is inoperative, continue takeoff only after both pilots has reviewed the associated sample guidance. The Primary Electrical Bus switch position is expected to read within the sample range of 27 to 35 units during descent.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Window Heat indication                     | 48 units     | Refer to related topic |
| Flap Position Indication selector position | 55 units     | Refer to related topic |
| Autopilot Channel A selector position      | 66 units     | Refer to related topic |
| Autopilot Channel A quantity display       | 46 units     | Advisory only          |
| Autopilot Channel B switch position        | 60 units     | Advisory only          |
| Autopilot Channel B status message         | 12 units     | Advisory only          |

04.10.19 Callouts: Wing Anti-Ice

During engine start, the relief pilot should confirm the Cockpit Voice Recorder advisory if the indication does not stabilize within the sample interval. If the Ground Proximity Monitor is inoperative, continue descent only after the First Officer has reviewed the associated sample guidance. The first officer will announce any change in the Traffic Advisory Display switch position and advise the other pilot once the checklist item is complete. During an extended ground delay, the Captain should monitor the Brake Temperature Monitor selector position when operating at a sample station without ground power. If the Primary Electrical Bus is inoperative, continue taxi only after both pilots has reviewed the associated sample guidance. Refer to the related topic for additional sample context.

**NOTE:** The Hydraulic System B advisory that differs from the expected state requires the pilot monitoring to brief the condition when the associated caution light remains illuminated. If the Pack Temperature Control is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance.

The first officer will verify any change in the Probe Heat indication and advise the other pilot once the checklist item is complete. Refer to the related topic for additional sample context. Values in this manual are invented and must not be used for any operational purpose. Refer to the related topic for additional sample context.

**NOTE:** The Brake Temperature Monitor indication is expected to read within the sample range of 16 to 23 units during an extended ground delay.

**CAUTION:** If the Cabin Pressure Controller is inoperative, continue engine start only after the pilot flying has reviewed the associated sample guidance. During cruise, the relief pilot should cross-check the Oxygen Distribution selector position when operating at a sample station without ground power.

If the Brake Temperature Monitor is inoperative, continue parking only after both pilots has reviewed the associated sample guidance. The first officer will select any change in the Cockpit Voice Recorder selector position and advise the other pilot when the associated caution light remains illuminated. The captain will brief any change in the Autopilot Channel B selector position and advise the other pilot if a discrepancy is observed.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Nosewheel Steering selector position       | 47 units     | Refer to related topic |
| Wing Anti-Ice status message               | 56 units     | Monitor                |
| Flap Position Indication advisory          | 93 units     | Advisory only          |
| Autopilot Channel B annunciation           | 3 units      | Monitor                |
| Landing Gear Indication annunciation       | 80 units     | Advisory only          |
| Fuel Crossfeed selector position           | 90 units     | Advisory only          |
| Flap Position Indication selector position | 10 units     | Advisory only          |

The relief pilot will confirm any change in the Fire Detection Loop annunciation and advise the other pilot when conditions permit. The captain will announce any change in the Hydraulic System A quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center. Both pilots will monitor any change in the Center Tank Pumps selector position and advise the other pilot if the indication does not stabilize within the sample interval. Values in this manual are invented and must not be used for any operational purpose.

The wording here is placeholder content shaped like a procedure, not a procedure. The Cockpit Voice Recorder status message that differs from the expected state requires the pilot monitoring to announce the condition when operating at a sample station without ground power. The pilot monitoring will verify any change in the Autobrake Selector quantity display and advise the other pilot when conditions permit.

04.10.20 Checklist: Oxygen Distribution

Values in this manual are invented and must not be used for any operational purpose. The Hydraulic System A advisory that differs from the expected state requires the Captain to cross-check the condition when the associated caution light remains illuminated. If the Autopilot Channel B is inoperative, continue takeoff only after the pilot flying

has reviewed the associated sample guidance. During engine start, the Captain should monitor the Engine Anti-Ice selector position if the indication does not stabilize within the sample interval.

| Condition                           | Sample value | Remarks                |
|-------------------------------------|--------------|------------------------|
| Stall Warning annunciation          | 42 units     | Refer to related topic |
| Cockpit Voice Recorder annunciation | 8 units      | Normal                 |
| Autothrottle status message         | 25 units     | Refer to related topic |
| Standby Instruments advisory        | 66 units     | Refer to related topic |
| Hydraulic System A advisory         | 33 units     | Normal                 |
| Autothrottle switch position        | 80 units     | Advisory only          |

The Pack Temperature Control annunciation is expected to read within the sample range of 63 to 70 units during climb. The first officer will record any change in the Landing Gear Indication selector position and advise the other pilot when conditions permit. The captain will select any change in the Speedbrake Handle annunciation and advise the other pilot when conditions permit. The Ground Proximity Monitor annunciation that differs from the expected state requires the pilot monitoring to monitor the condition before the next phase of flight.

The Speedbrake Handle quantity display is expected to read within the sample range of 35 to 42 units during a maintenance-requested ground run. The Fuel Crossfeed advisory that differs from the expected state requires the First Officer to announce the condition once the checklist item is complete. If the Bleed Air Supply is inoperative, continue cruise only after the Captain has reviewed the associated sample guidance.

**NOTE:** This text is fictional and exists only to give the prototype realistic volume and structure. The Center Tank Pumps quantity display is expected to read within the sample range of 64 to 75 units during climb.

The relief pilot will monitor any change in the Cabin Pressure Controller selector position and advise the other pilot before the next phase of flight. This text is fictional and exists only to give the prototype realistic volume and structure. If the Standby Instruments is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance. If the Fuel Crossfeed is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance.

The pilot monitoring will record any change in the Pack Temperature Control annunciation and advise the other pilot once the checklist item is complete. The first officer will confirm any change in the Engine Anti-Ice annunciation and advise the other pilot when conditions permit. The pilot monitoring will announce any change in the Traffic Advisory Display indication and advise the other pilot when the associated caution light remains illuminated. During takeoff, both pilots should cross-check the Autopilot Channel B annunciation when the associated caution light remains illuminated. The Nosewheel Steering selector position is expected to read within the sample range of 37 to 49 units during an extended ground delay. The Fuel Crossfeed annunciation that differs from the expected state requires the relief pilot to monitor the condition when the associated caution light remains illuminated.

This text is fictional and exists only to give the prototype realistic volume and structure. The Ground Proximity Monitor status message is expected to read within the sample range of 56 to 66 units during preflight. The relief pilot will monitor any change in the Engine Anti-Ice advisory and advise the other pilot once the checklist item is complete. During climb, the First Officer should record the Flap Position Indication status message unless directed otherwise by the Sample Operations Center. The wording here is placeholder content shaped like a procedure, not a procedure.

#### **04.10.21 Briefing: Cabin Pressure Controller**

The Autothrottle selector position is expected to read within the sample range of 65 to 68 units during descent. During cruise, the pilot flying should announce the Cockpit Voice Recorder status message before the next phase of flight. The Ground Proximity Monitor switch position that differs from the expected state requires the First Officer to verify the condition when conditions permit.

The Cargo Smoke Detection advisory is expected to read within the sample range of 5 to 8 units during a diversion. During parking, the First Officer should select the Auxiliary Power Unit status message unless directed otherwise by

the Sample Operations Center. The relief pilot will brief any change in the Cockpit Voice Recorder indication and advise the other pilot unless directed otherwise by the Sample Operations Center.

Refer to the related topic for additional sample context. This text is fictional and exists only to give the prototype realistic volume and structure. Both pilots will announce any change in the Fuel Crossfeed annunciation and advise the other pilot if the indication does not stabilize within the sample interval.

- This text is fictional and exists only to give the prototype realistic volume and structure.
- If the Flight Management Computer is inoperative, continue climb only after the Captain has reviewed the associated sample guidance.
- The pilot monitoring will confirm any change in the Wing Anti-Ice status message and advise the other pilot when the associated caution light remains illuminated.
- Values in this manual are invented and must not be used for any operational purpose.
- If the Autothrottle is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance.
- If the Flap Position Indication is inoperative, continue a diversion only after both pilots has reviewed the associated sample guidance.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- Both pilots will select any change in the Engine Anti-Ice switch position and advise the other pilot when conditions permit.

**CAUTION:** The Probe Heat status message that differs from the expected state requires the First Officer to cross-check the condition when the associated caution light remains illuminated. If the Fire Detection Loop is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance.

| Condition                              | Sample value | Remarks                |
|----------------------------------------|--------------|------------------------|
| Landing Gear Indication annunciation   | 71 units     | Refer to related topic |
| Window Heat status message             | 1 units      | Normal                 |
| Probe Heat status message              | 35 units     | Refer to related topic |
| Brake Temperature Monitor annunciation | 7 units      | Normal                 |
| Weather Radar advisory                 | 99 units     | Advisory only          |

**04.10.22 Briefing: Brake Temperature Monitor**

This text is fictional and exists only to give the prototype realistic volume and structure. If the Probe Heat is inoperative, continue approach only after the pilot monitoring has reviewed the associated sample guidance. The Autothrottle quantity display that differs from the expected state requires the relief pilot to brief the condition when conditions permit. During descent, both pilots should confirm the Bleed Air Supply annunciation when conditions permit.

The captain will cross-check any change in the Stall Warning indication and advise the other pilot when conditions permit. The Probe Heat status message that differs from the expected state requires the Captain to cross-check the condition if the indication does not stabilize within the sample interval. If the Oxygen Distribution is inoperative, continue descent only after both pilots has reviewed the associated sample guidance.

- The Cockpit Voice Recorder quantity display that differs from the expected state requires the pilot monitoring to verify the condition unless directed otherwise by the Sample Operations Center.
- Both pilots will monitor any change in the Speedbrake Handle selector position and advise the other pilot when operating at a sample station without ground power.

- The Traffic Advisory Display advisory is expected to read within the sample range of 37 to 42 units during climb.
- The relief pilot will monitor any change in the Transponder advisory and advise the other pilot unless directed otherwise by the Sample Operations Center.

The wording here is placeholder content shaped like a procedure, not a procedure. The Wing Anti-Ice indication is expected to read within the sample range of 85 to 93 units during a maintenance-requested ground run. The first officer will monitor any change in the Center Tank Pumps advisory and advise the other pilot when the associated caution light remains illuminated. The pilot flying will cross-check any change in the Weather Radar status message and advise the other pilot if a discrepancy is observed.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Primary Electrical Bus annunciation        | 27 units     | Refer to related topic |
| Brake Temperature Monitor status message   | 19 units     | Monitor                |
| Ground Proximity Monitor selector position | 27 units     | Normal                 |

**NOTE:** During climb, both pilots should brief the Ground Proximity Monitor switch position when the associated caution light remains illuminated.

**CAUTION:** The Fire Detection Loop indication that differs from the expected state requires the pilot monitoring to select the condition when conditions permit.

**04.10.23 Callouts: Flap Position Indication**

If the Engine Anti-Ice is inoperative, continue a diversion only after the First Officer has reviewed the associated sample guidance. If the Standby Instruments is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance. The Autopilot Channel A annunciation that differs from the expected state requires the pilot flying to brief the condition when the associated caution light remains illuminated. The captain will cross-check any change in the Autopilot Channel B advisory and advise the other pilot when conditions permit.

**CAUTION:** Refer to the related topic for additional sample context. Values in this manual are invented and must not be used for any operational purpose.

- The Flight Management Computer advisory that differs from the expected state requires the pilot monitoring to monitor the condition if a discrepancy is observed.
- During cruise, both pilots should cross-check the Fuel Crossfeed advisory if the indication does not stabilize within the sample interval.
- During engine start, both pilots should select the Autopilot Channel A quantity display unless directed otherwise by the Sample Operations Center.
- The Bleed Air Supply indication that differs from the expected state requires the pilot monitoring to verify the condition once the checklist item is complete.
- The Fire Detection Loop quantity display is expected to read within the sample range of 46 to 53 units during an extended ground delay.

The Flight Management Computer status message that differs from the expected state requires the First Officer to brief the condition if a discrepancy is observed. The Thrust Reverser switch position is expected to read within the sample range of 86 to 97 units during cruise. The Thrust Reverser indication is expected to read within the sample range of 55 to 62 units during preflight. The pilot monitoring will monitor any change in the Oxygen Distribution selector position and advise the other pilot if a discrepancy is observed. The Oxygen Distribution quantity display that differs from the expected state requires the pilot monitoring to confirm the condition if a discrepancy is observed.

**NOTE:** Refer to the related topic for additional sample context. The Oxygen Distribution quantity display is expected to read within the sample range of 24 to 34 units during engine start.

**NOTE:** During landing, both pilots should cross-check the Flight Management Computer advisory when conditions permit.

The wording here is placeholder content shaped like a procedure, not a procedure. During an extended ground delay, the pilot monitoring should announce the Primary Electrical Bus advisory before the next phase of flight. The wording here is placeholder content shaped like a procedure, not a procedure. See 18.20.4 Center Tank Pumps Status Messages.

#### **04.10.24 Briefing: Wing Anti-Ice**

The Autopilot Channel B selector position is expected to read within the sample range of 15 to 19 units during a diversion. If the Flight Management Computer is inoperative, continue takeoff only after the First Officer has reviewed the associated sample guidance. If the Speedbrake Handle is inoperative, continue a turnaround only after the pilot monitoring has reviewed the associated sample guidance. During a maintenance-requested ground run, both pilots should record the Autothrottle selector position when the associated caution light remains illuminated. The Center Tank Pumps indication is expected to read within the sample range of 16 to 25 units during engine start.

The captain will cross-check any change in the Ground Proximity Monitor switch position and advise the other pilot if a discrepancy is observed. The wording here is placeholder content shaped like a procedure, not a procedure. The pilot monitoring will record any change in the Primary Electrical Bus switch position and advise the other pilot once the checklist item is complete.

**CAUTION:** The Nosewheel Steering selector position that differs from the expected state requires the relief pilot to confirm the condition when conditions permit. The wording here is placeholder content shaped like a procedure, not a procedure.

**CAUTION:** During preflight, the Captain should cross-check the Traffic Advisory Display selector position if the indication does not stabilize within the sample interval. If the Brake Temperature Monitor is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance.

The Brake Temperature Monitor advisory that differs from the expected state requires the pilot monitoring to cross-check the condition when operating at a sample station without ground power. The wording here is placeholder content shaped like a procedure, not a procedure. The Standby Instruments quantity display that differs from the expected state requires the Captain to brief the condition once the checklist item is complete. This text is fictional and exists only to give the prototype realistic volume and structure. The Fuel Crossfeed selector position that differs from the expected state requires the Captain to verify the condition if the indication does not stabilize within the sample interval. Values in this manual are invented and must not be used for any operational purpose. See 03.20.24 Checklist: Hydraulic System A.

**CAUTION:** The wording here is placeholder content shaped like a procedure, not a procedure. During climb, both pilots should cross-check the Autothrottle quantity display before the next phase of flight.

**NOTE:** During approach, both pilots should announce the Brake Temperature Monitor status message when conditions permit.

**CAUTION:** The Flight Management Computer advisory that differs from the expected state requires the pilot monitoring to monitor the condition if the indication does not stabilize within the sample interval. The first officer will announce any change in the Primary Electrical Bus switch position and advise the other pilot once the checklist item is complete.

#### **04.10.25 Briefing: Autopilot Channel A**

If the Auxiliary Power Unit is inoperative, continue taxi only after both pilots has reviewed the associated sample guidance. If the Wing Anti-Ice is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance. The Autopilot Channel A quantity display that differs from the expected state requires the pilot flying to select the condition if a discrepancy is observed.



- If the Flight Management Computer is inoperative, continue taxi only after both pilots has reviewed the associated sample guidance.
- During an extended ground delay, the pilot flying should record the Ground Proximity Monitor advisory once the checklist item is complete.
- During descent, the First Officer should cross-check the Probe Heat advisory when operating at a sample station without ground power.
- If the Pack Temperature Control is inoperative, continue a maintenance-requested ground run only after the pilot monitoring has reviewed the associated sample guidance.
- The captain will select any change in the Hydraulic System A indication and advise the other pilot when the associated caution light remains illuminated.

The relief pilot will confirm any change in the Oxygen Distribution quantity display and advise the other pilot once the checklist item is complete. The wording here is placeholder content shaped like a procedure, not a procedure. The Traffic Advisory Display status message that differs from the expected state requires the pilot flying to record the condition when the associated caution light remains illuminated. The Pack Temperature Control status message is expected to read within the sample range of 81 to 84 units during an extended ground delay. During a diversion, the First Officer should record the Stall Warning quantity display unless directed otherwise by the Sample Operations Center. The Cargo Smoke Detection indication is expected to read within the sample range of 13 to 21 units during landing.

**NOTE:** The Center Tank Pumps selector position that differs from the expected state requires the First Officer to confirm the condition if the indication does not stabilize within the sample interval.

**CAUTION:** The pilot monitoring will cross-check any change in the Speedbrake Handle indication and advise the other pilot if a discrepancy is observed.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Standby Hydraulic advisory               | 64 units     | Normal                 |
| Weather Radar quantity display           | 30 units     | Advisory only          |
| Cabin Pressure Controller status message | 65 units     | Advisory only          |
| Autobrake Selector annunciation          | 84 units     | Refer to related topic |
| Engine Anti-Ice switch position          | 98 units     | Normal                 |
| Probe Heat annunciation                  | 80 units     | Monitor                |

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Primary Electrical Bus selector position | 69 units     | Refer to related topic |
| Stall Warning selector position          | 44 units     | Monitor                |
| Autopilot Channel A selector position    | 62 units     | Advisory only          |
| Standby Instruments indication           | 96 units     | Monitor                |
| Autothrottle switch position             | 58 units     | Advisory only          |
| Standby Instruments selector position    | 83 units     | Normal                 |
| Standby Instruments switch position      | 43 units     | Advisory only          |

**CAUTION:** The Flap Position Indication selector position that differs from the expected state requires the First Officer to confirm the condition when the associated caution light remains illuminated. The pilot monitoring will brief any change in the Hydraulic System A status message and advise the other pilot when conditions permit.

## 04.20 Cold Weather Operations

### 04.20.1 Callouts: Primary Electrical Bus

During engine start, both pilots should monitor the Weather Radar advisory if a discrepancy is observed. If the Oxygen Distribution is inoperative, continue approach only after the pilot flying has reviewed the associated sample guidance. The Flight Management Computer switch position is expected to read within the sample range of 81 to 93 units during takeoff. If the Wing Anti-Ice is inoperative, continue an extended ground delay only after the Captain has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure.

- If the Cockpit Voice Recorder is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance.
- The Engine Anti-Ice quantity display that differs from the expected state requires the First Officer to cross-check the condition when the associated caution light remains illuminated.
- The Pack Temperature Control status message that differs from the expected state requires the pilot flying to cross-check the condition once the checklist item is complete.
- The captain will record any change in the Cargo Smoke Detection selector position and advise the other pilot if the indication does not stabilize within the sample interval.

**NOTE:** During preflight, both pilots should brief the Flap Position Indication switch position before the next phase of flight. The Auxiliary Power Unit advisory that differs from the expected state requires the relief pilot to select the condition before the next phase of flight.

Values in this manual are invented and must not be used for any operational purpose. Both pilots will announce any change in the Cargo Smoke Detection switch position and advise the other pilot unless directed otherwise by the Sample Operations Center. Both pilots will verify any change in the Fuel Crossfeed status message and advise the other pilot when the associated caution light remains illuminated. The relief pilot will cross-check any change in the Cabin Pressure Controller switch position and advise the other pilot unless directed otherwise by the Sample Operations Center.

- The Autothrottle status message that differs from the expected state requires the First Officer to monitor the condition when conditions permit.
- During approach, the pilot flying should confirm the Ground Proximity Monitor status message if the indication does not stabilize within the sample interval.
- The pilot monitoring will select any change in the Ground Proximity Monitor selector position and advise the other pilot if a discrepancy is observed.

### 04.20.2 Verification: Cargo Smoke Detection

The Speedbrake Handle quantity display is expected to read within the sample range of 14 to 20 units during an extended ground delay. If the Speedbrake Handle is inoperative, continue descent only after the First Officer has reviewed the associated sample guidance. If the Flap Position Indication is inoperative, continue parking only after the relief pilot has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure.

**CAUTION:** The wording here is placeholder content shaped like a procedure, not a procedure.

**CAUTION:** The Autobrake Selector switch position that differs from the expected state requires the relief pilot to announce the condition before the next phase of flight.

**CAUTION:** Refer to the related topic for additional sample context.

The captain will monitor any change in the Autopilot Channel B indication and advise the other pilot when operating at a sample station without ground power. The wording here is placeholder content shaped like a procedure, not a procedure. The Traffic Advisory Display switch position that differs from the expected state requires the pilot flying to select the condition if the indication does not stabilize within the sample interval. This text is fictional and exists only to

give the prototype realistic volume and structure. During a maintenance-requested ground run, the relief pilot should verify the Fuel Crossfeed indication if a discrepancy is observed. If the Hydraulic System B is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance.

This text is fictional and exists only to give the prototype realistic volume and structure. The Hydraulic System B quantity display is expected to read within the sample range of 95 to 105 units during landing. The pilot flying will cross-check any change in the Center Tank Pumps annunciation and advise the other pilot if the indication does not stabilize within the sample interval. The relief pilot will monitor any change in the Cabin Pressure Controller indication and advise the other pilot once the checklist item is complete.

**NOTE:** If the Pack Temperature Control is inoperative, continue climb only after the Captain has reviewed the associated sample guidance.

**NOTE:** During takeoff, the relief pilot should cross-check the Nosewheel Steering annunciation before the next phase of flight.

**04.20.3 Crew Coordination: Landing Gear Indication**

During takeoff, the Captain should announce the Window Heat selector position unless directed otherwise by the Sample Operations Center. If the Engine Anti-Ice is inoperative, continue preflight only after both pilots has reviewed the associated sample guidance. During an extended ground delay, both pilots should announce the Traffic Advisory Display switch position when operating at a sample station without ground power. Both pilots will verify any change in the Engine Anti-Ice status message and advise the other pilot if a discrepancy is observed.

**NOTE:** Values in this manual are invented and must not be used for any operational purpose.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Cabin Pressure Controller switch position | 91 units     | Advisory only          |
| Flight Management Computer status message | 45 units     | Normal                 |
| Cabin Pressure Controller indication      | 52 units     | Refer to related topic |
| Standby Instruments selector position     | 42 units     | Refer to related topic |
| Fuel Crossfeed advisory                   | 43 units     | Normal                 |
| Auxiliary Power Unit indication           | 84 units     | Normal                 |
| Cockpit Voice Recorder indication         | 11 units     | Monitor                |

Values in this manual are invented and must not be used for any operational purpose. The Auxiliary Power Unit quantity display is expected to read within the sample range of 98 to 103 units during an extended ground delay. The Fuel Crossfeed quantity display is expected to read within the sample range of 58 to 63 units during a turnaround. During approach, the Captain should record the Auxiliary Power Unit annunciation if a discrepancy is observed.

**CAUTION:** During landing, both pilots should record the Ground Proximity Monitor advisory when operating at a sample station without ground power. The captain will cross-check any change in the Landing Gear Indication status message and advise the other pilot if a discrepancy is observed.

If the Center Tank Pumps is inoperative, continue climb only after the First Officer has reviewed the associated sample guidance. The captain will brief any change in the Autobrake Selector status message and advise the other pilot when operating at a sample station without ground power. The Cabin Pressure Controller annunciation is expected to read within the sample range of 57 to 62 units during a turnaround. Refer to the related topic for additional sample context. The wording here is placeholder content shaped like a procedure, not a procedure.

The captain will record any change in the Pack Temperature Control status message and advise the other pilot when conditions permit. The Probe Heat switch position is expected to read within the sample range of 23 to 29 units during a maintenance-requested ground run. Refer to the related topic for additional sample context.

The Engine Anti-Ice annunciation is expected to read within the sample range of 49 to 56 units during engine start. The wording here is placeholder content shaped like a procedure, not a procedure. The Flap Position Indication status message is expected to read within the sample range of 25 to 31 units during an extended ground delay. The Wing Anti-Ice selector position that differs from the expected state requires the First Officer to select the condition if the indication does not stabilize within the sample interval. If the Engine Anti-Ice is inoperative, continue climb only after both pilots has reviewed the associated sample guidance. During engine start, both pilots should brief the Landing Gear Indication indication if a discrepancy is observed.

If the Window Heat is inoperative, continue climb only after the First Officer has reviewed the associated sample guidance. The Thrust Reverser quantity display is expected to read within the sample range of 88 to 94 units during descent. The pilot monitoring will select any change in the Traffic Advisory Display status message and advise the other pilot if the indication does not stabilize within the sample interval. The Pack Temperature Control status message is expected to read within the sample range of 42 to 54 units during parking. If the Oxygen Distribution is inoperative, continue cruise only after both pilots has reviewed the associated sample guidance. The Pack Temperature Control indication is expected to read within the sample range of 64 to 74 units during engine start.

#### **04.20.4 Checklist: Fuel Crossfeed**

The wording here is placeholder content shaped like a procedure, not a procedure. During descent, both pilots should verify the Autobrake Selector quantity display once the checklist item is complete. The Autopilot Channel A switch position that differs from the expected state requires the Captain to select the condition if the indication does not stabilize within the sample interval. Refer to the related topic for additional sample context. The Autobrake Selector indication that differs from the expected state requires both pilots to brief the condition before the next phase of flight. The Hydraulic System B annunciation that differs from the expected state requires the pilot monitoring to confirm the condition when operating at a sample station without ground power.

- During parking, both pilots should brief the Weather Radar annunciation before the next phase of flight.
- The Hydraulic System B annunciation is expected to read within the sample range of 46 to 56 units during taxi.
- The relief pilot will verify any change in the Brake Temperature Monitor switch position and advise the other pilot when operating at a sample station without ground power.
- If the Nosewheel Steering is inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance.

Values in this manual are invented and must not be used for any operational purpose. The pilot monitoring will announce any change in the Cockpit Voice Recorder switch position and advise the other pilot once the checklist item is complete. This text is fictional and exists only to give the prototype realistic volume and structure.

- The Probe Heat selector position is expected to read within the sample range of 44 to 53 units during a maintenance-requested ground run.
- The captain will monitor any change in the Center Tank Pumps advisory and advise the other pilot when the associated caution light remains illuminated.
- If the Engine Anti-Ice is inoperative, continue approach only after the First Officer has reviewed the associated sample guidance.

If the Hydraulic System A is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. During takeoff, the First Officer should verify the Flap Position Indication indication when the associated caution light remains illuminated. If the Autobrake Selector is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance.

**CAUTION:** During an extended ground delay, the relief pilot should record the Primary Electrical Bus selector position when conditions permit.

| Condition                             | Sample value | Remarks |
|---------------------------------------|--------------|---------|
| Autopilot Channel B selector position | 92 units     | Normal  |
| Thrust Reverser switch position       | 46 units     | Monitor |
| Landing Gear Indication annunciation  | 66 units     | Monitor |

| Condition                                   | Sample value | Remarks                |
|---------------------------------------------|--------------|------------------------|
| Weather Radar advisory                      | 75 units     | Advisory only          |
| Cabin Pressure Controller selector position | 7 units      | Refer to related topic |
| Stall Warning annunciation                  | 7 units      | Advisory only          |
| Cabin Pressure Controller switch position   | 99 units     | Advisory only          |
| Nosewheel Steering selector position        | 49 units     | Monitor                |

#### 04.20.5 Crew Coordination: Fuel Crossfeed

If the Stall Warning is inoperative, continue parking only after the Captain has reviewed the associated sample guidance. The Landing Gear Indication advisory that differs from the expected state requires the relief pilot to monitor the condition unless directed otherwise by the Sample Operations Center. Refer to the related topic for additional sample context. This text is fictional and exists only to give the prototype realistic volume and structure. The captain will monitor any change in the Autopilot Channel A status message and advise the other pilot before the next phase of flight. The Speedbrake Handle status message that differs from the expected state requires the pilot flying to select the condition if a discrepancy is observed.

The Bleed Air Supply advisory is expected to read within the sample range of 95 to 104 units during climb. During descent, the pilot flying should select the Flight Management Computer selector position when operating at a sample station without ground power. The first officer will select any change in the Ground Proximity Monitor annunciation and advise the other pilot when the associated caution light remains illuminated. The Speedbrake Handle switch position that differs from the expected state requires the Captain to announce the condition if the indication does not stabilize within the sample interval. This text is fictional and exists only to give the prototype realistic volume and structure. If the Landing Gear Indication is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance.

- The relief pilot will brief any change in the Cabin Pressure Controller switch position and advise the other pilot when operating at a sample station without ground power.
- The Autopilot Channel A annunciation that differs from the expected state requires the pilot monitoring to verify the condition when operating at a sample station without ground power.
- If the Standby Instruments is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance.
- The Autopilot Channel B advisory that differs from the expected state requires the pilot flying to monitor the condition before the next phase of flight.
- During preflight, the pilot flying should monitor the Weather Radar quantity display when the associated caution light remains illuminated.
- The captain will select any change in the Pack Temperature Control annunciation and advise the other pilot before the next phase of flight.
- The pilot monitoring will select any change in the Primary Electrical Bus switch position and advise the other pilot when conditions permit.
- The Stall Warning selector position that differs from the expected state requires the First Officer to record the condition once the checklist item is complete.

- Refer to the related topic for additional sample context.
- The Speedbrake Handle annunciation is expected to read within the sample range of 60 to 65 units during engine start.

The Engine Anti-Ice indication is expected to read within the sample range of 45 to 50 units during a turnaround. The Cargo Smoke Detection advisory is expected to read within the sample range of 21 to 24 units during takeoff. Both pilots will confirm any change in the Pack Temperature Control status message and advise the other pilot once the checklist item is complete. If the Flap Position Indication is inoperative, continue a maintenance-requested ground run only after both pilots has reviewed the associated sample guidance.

The Stall Warning selector position that differs from the expected state requires both pilots to cross-check the condition unless directed otherwise by the Sample Operations Center. The wording here is placeholder content shaped like a procedure, not a procedure. This text is fictional and exists only to give the prototype realistic volume and structure. This text is fictional and exists only to give the prototype realistic volume and structure.

If the Traffic Advisory Display is inoperative, continue parking only after the pilot monitoring has reviewed the associated sample guidance. The relief pilot will announce any change in the Center Tank Pumps selector position and advise the other pilot once the checklist item is complete. The first officer will verify any change in the Pack Temperature Control indication and advise the other pilot before the next phase of flight. The captain will cross-check any change in the Stall Warning indication and advise the other pilot when the associated caution light remains illuminated. The relief pilot will cross-check any change in the Hydraulic System B indication and advise the other pilot if the indication does not stabilize within the sample interval. The wording here is placeholder content shaped like a procedure, not a procedure.

**CAUTION:** The Probe Heat selector position is expected to read within the sample range of 17 to 29 units during landing. The wording here is placeholder content shaped like a procedure, not a procedure.

**NOTE:** If the Weather Radar is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance.

**04.20.6 Verification: Flap Position Indication**

Values in this manual are invented and must not be used for any operational purpose. This text is fictional and exists only to give the prototype realistic volume and structure. During cruise, the pilot flying should select the Weather Radar selector position when conditions permit. If the Brake Temperature Monitor is inoperative, continue parking only after the Captain has reviewed the associated sample guidance.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Auxiliary Power Unit status message        | 91 units     | Normal                 |
| Autothrottle advisory                      | 22 units     | Refer to related topic |
| Nosewheel Steering quantity display        | 83 units     | Normal                 |
| Probe Heat selector position               | 25 units     | Advisory only          |
| Traffic Advisory Display selector position | 97 units     | Refer to related topic |

**NOTE:** The Transponder switch position that differs from the expected state requires the Captain to cross-check the condition before the next phase of flight. During climb, the pilot monitoring should announce the Window Heat switch position if a discrepancy is observed.

- During takeoff, the First Officer should cross-check the Fuel Crossfeed indication before the next phase of flight.
- The Thrust Reverser indication is expected to read within the sample range of 15 to 24 units during descent.
- The pilot monitoring will record any change in the Cabin Pressure Controller indication and advise the other pilot before the next phase of flight.



If the Autopilot Channel A is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance. The Engine Anti-Ice selector position is expected to read within the sample range of 49 to 53 units during approach. Refer to the related topic for additional sample context. The Fuel Crossfeed annunciation is expected to read within the sample range of 28 to 37 units during a turnaround. The pilot monitoring will announce any change in the Window Heat status message and advise the other pilot if the indication does not stabilize within the sample interval. The Autobrake Selector selector position is expected to read within the sample range of 74 to 80 units during a diversion.

**CAUTION:** The Auxiliary Power Unit status message that differs from the expected state requires the First Officer to select the condition before the next phase of flight.

#### **04.20.7 Checklist: Wing Anti-Ice**

During takeoff, both pilots should select the Pack Temperature Control annunciation if the indication does not stabilize within the sample interval. During a diversion, the pilot monitoring should announce the Cockpit Voice Recorder indication if the indication does not stabilize within the sample interval. Refer to the related topic for additional sample context. The Traffic Advisory Display switch position that differs from the expected state requires the First Officer to verify the condition if the indication does not stabilize within the sample interval. If the Cockpit Voice Recorder is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance.

The captain will announce any change in the Traffic Advisory Display indication and advise the other pilot if a discrepancy is observed. Values in this manual are invented and must not be used for any operational purpose. The first officer will select any change in the Nosewheel Steering advisory and advise the other pilot once the checklist item is complete.

- The first officer will verify any change in the Landing Gear Indication selector position and advise the other pilot if the indication does not stabilize within the sample interval.
- If the Autopilot Channel B is inoperative, continue taxi only after the pilot flying has reviewed the associated sample guidance.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The Ground Proximity Monitor advisory that differs from the expected state requires both pilots to verify the condition once the checklist item is complete.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The Center Tank Pumps indication that differs from the expected state requires the pilot flying to cross-check the condition if the indication does not stabilize within the sample interval.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The first officer will verify any change in the Cockpit Voice Recorder quantity display and advise the other pilot if the indication does not stabilize within the sample interval.
- During cruise, the relief pilot should confirm the Autothrottle advisory unless directed otherwise by the Sample Operations Center.
- If the Pack Temperature Control is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance.
- If the Center Tank Pumps is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance.
- The Engine Anti-Ice annunciation that differs from the expected state requires the pilot monitoring to confirm the condition once the checklist item is complete.

- The Autothrottle advisory is expected to read within the sample range of 77 to 80 units during parking.
- Values in this manual are invented and must not be used for any operational purpose.
- If the Fuel Crossfeed is inoperative, continue a diversion only after the First Officer has reviewed the associated sample guidance.

**CAUTION:** The captain will select any change in the Landing Gear Indication status message and advise the other pilot unless directed otherwise by the Sample Operations Center. During approach, both pilots should monitor the Fuel Crossfeed indication before the next phase of flight.

**04.20.8 Crew Coordination: Nosewheel Steering**

Refer to the related topic for additional sample context. During a turnaround, the pilot flying should select the Cockpit Voice Recorder indication when operating at a sample station without ground power. The wording here is placeholder content shaped like a procedure, not a procedure. If the Pack Temperature Control is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance. The Standby Instruments selector position that differs from the expected state requires the pilot flying to record the condition when operating at a sample station without ground power. The wording here is placeholder content shaped like a procedure, not a procedure.

During a maintenance-requested ground run, both pilots should confirm the Stall Warning indication once the checklist item is complete. The Ground Proximity Monitor indication that differs from the expected state requires the relief pilot to record the condition when conditions permit. If the Autothrottle is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance. The relief pilot will brief any change in the Probe Heat selector position and advise the other pilot if the indication does not stabilize within the sample interval.

| Condition                         | Sample value | Remarks       |
|-----------------------------------|--------------|---------------|
| Oxygen Distribution indication    | 55 units     | Monitor       |
| Thrust Reverser status message    | 54 units     | Monitor       |
| Pack Temperature Control advisory | 31 units     | Advisory only |
| Nosewheel Steering indication     | 95 units     | Monitor       |

**NOTE:** The captain will cross-check any change in the Speedbrake Handle advisory and advise the other pilot before the next phase of flight. During descent, the pilot monitoring should monitor the Landing Gear Indication selector position when the associated caution light remains illuminated.

During cruise, the First Officer should record the Pack Temperature Control selector position if the indication does not stabilize within the sample interval. The Wing Anti-Ice quantity display that differs from the expected state requires the pilot monitoring to cross-check the condition if a discrepancy is observed. The Speedbrake Handle status message that differs from the expected state requires the pilot flying to monitor the condition if the indication does not stabilize within the sample interval. The Transponder advisory that differs from the expected state requires the Captain to verify the condition if a discrepancy is observed. The captain will cross-check any change in the Autopilot Channel A selector position and advise the other pilot unless directed otherwise by the Sample Operations Center.

**04.20.9 Verification: Standby Instruments**

During a turnaround, the pilot monitoring should cross-check the Brake Temperature Monitor quantity display before the next phase of flight. The Primary Electrical Bus annunciation is expected to read within the sample range of 49 to 54 units during takeoff. During a turnaround, the pilot monitoring should confirm the Thrust Reverser advisory before the next phase of flight. The Auxiliary Power Unit advisory is expected to read within the sample range of 56 to 59 units during a maintenance-requested ground run. The Cabin Pressure Controller switch position is expected to read within the sample range of 43 to 52 units during taxi.

If the Cargo Smoke Detection is inoperative, continue engine start only after the pilot flying has reviewed the associated sample guidance. If the Autopilot Channel A is inoperative, continue cruise only after the Captain has reviewed the associated sample guidance. During climb, the Captain should cross-check the Autopilot Channel B indication before the next phase of flight.

If the Fire Detection Loop is inoperative, continue engine start only after both pilots has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. The Window Heat indication that differs from the expected state requires the First Officer to verify the condition if the indication does not stabilize within the sample interval. During takeoff, both pilots should confirm the Flight Management Computer quantity display once the checklist item is complete. Values in this manual are invented and must not be used for any operational purpose.

| Condition                            | Sample value | Remarks                |
|--------------------------------------|--------------|------------------------|
| Probe Heat annunciation              | 87 units     | Refer to related topic |
| Autobrake Selector switch position   | 94 units     | Normal                 |
| Autopilot Channel B quantity display | 60 units     | Monitor                |
| Primary Electrical Bus indication    | 6 units      | Refer to related topic |
| Hydraulic System A status message    | 41 units     | Monitor                |

The Autopilot Channel A indication that differs from the expected state requires the First Officer to cross-check the condition if a discrepancy is observed. Values in this manual are invented and must not be used for any operational purpose. Values in this manual are invented and must not be used for any operational purpose.

- During a diversion, the relief pilot should confirm the Flap Position Indication annunciation if a discrepancy is observed.
- The relief pilot will brief any change in the Thrust Reverser status message and advise the other pilot when operating at a sample station without ground power.
- The Window Heat annunciation that differs from the expected state requires the First Officer to record the condition if a discrepancy is observed.

#### **04.20.10 Crew Coordination: Window Heat**

During an extended ground delay, the Captain should verify the Window Heat status message when the associated caution light remains illuminated. Refer to the related topic for additional sample context. The pilot monitoring will verify any change in the Cargo Smoke Detection advisory and advise the other pilot once the checklist item is complete. The Wing Anti-Ice status message is expected to read within the sample range of 42 to 51 units during descent. The Probe Heat selector position that differs from the expected state requires the pilot flying to record the condition if the indication does not stabilize within the sample interval. If the Cockpit Voice Recorder is inoperative, continue preflight only after both pilots has reviewed the associated sample guidance.

The Autothrottle selector position that differs from the expected state requires the pilot monitoring to cross-check the condition once the checklist item is complete. During a turnaround, the pilot flying should announce the Autopilot Channel B indication before the next phase of flight. If the Engine Anti-Ice is inoperative, continue engine start only after the pilot flying has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. This text is fictional and exists only to give the prototype realistic volume and structure.

- The Center Tank Pumps indication that differs from the expected state requires the First Officer to confirm the condition when conditions permit.
- The pilot flying will cross-check any change in the Brake Temperature Monitor status message and advise the other pilot if the indication does not stabilize within the sample interval.

- The pilot flying will cross-check any change in the Cargo Smoke Detection switch position and advise the other pilot if a discrepancy is observed.
- The Center Tank Pumps selector position that differs from the expected state requires the First Officer to confirm the condition when conditions permit.
- Both pilots will select any change in the Window Heat annunciation and advise the other pilot when conditions permit.
- Both pilots will brief any change in the Engine Anti-Ice indication and advise the other pilot when the associated caution light remains illuminated.

If the Speedbrake Handle is inoperative, continue a maintenance-requested ground run only after the Captain has reviewed the associated sample guidance. The relief pilot will cross-check any change in the Primary Electrical Bus selector position and advise the other pilot unless directed otherwise by the Sample Operations Center. During parking, the relief pilot should cross-check the Autobrake Selector quantity display before the next phase of flight. The Transponder quantity display is expected to read within the sample range of 46 to 51 units during preflight.

**NOTE:** Refer to the related topic for additional sample context.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Center Tank Pumps selector position        | 63 units     | Advisory only          |
| Probe Heat advisory                        | 92 units     | Normal                 |
| Autobrake Selector selector position       | 31 units     | Normal                 |
| Auxiliary Power Unit advisory              | 92 units     | Refer to related topic |
| Cockpit Voice Recorder advisory            | 66 units     | Advisory only          |
| Flap Position Indication selector position | 38 units     | Normal                 |

The first officer will confirm any change in the Nosewheel Steering quantity display and advise the other pilot when operating at a sample station without ground power. Refer to the related topic for additional sample context. The Cargo Smoke Detection switch position that differs from the expected state requires the Captain to confirm the condition if the indication does not stabilize within the sample interval. The pilot flying will cross-check any change in the Autobrake Selector indication and advise the other pilot if a discrepancy is observed. Both pilots will select any change in the Standby Instruments advisory and advise the other pilot once the checklist item is complete. The Landing Gear Indication annunciation is expected to read within the sample range of 51 to 58 units during taxi.

**CAUTION:** The pilot monitoring will record any change in the Nosewheel Steering status message and advise the other pilot once the checklist item is complete.

**CAUTION:** The captain will record any change in the Transponder quantity display and advise the other pilot if the indication does not stabilize within the sample interval.

**04.20.11 Flow: Ground Proximity Monitor**

The first officer will announce any change in the Stall Warning annunciation and advise the other pilot when the associated caution light remains illuminated. The Speedbrake Handle annunciation is expected to read within the sample range of 49 to 56 units during takeoff. The Engine Anti-Ice annunciation is expected to read within the sample range of 40 to 45 units during approach. The Nosewheel Steering status message is expected to read within the sample range of 98 to 106 units during a maintenance-requested ground run.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Fire Detection Loop status message        | 83 units     | Refer to related topic |
| Cabin Pressure Controller switch position | 91 units     | Refer to related topic |
| Flight Management Computer status message | 68 units     | Advisory only          |

**CAUTION:** The Cockpit Voice Recorder advisory that differs from the expected state requires the pilot flying to monitor the condition when operating at a sample station without ground power.

If the Flap Position Indication is inoperative, continue landing only after the pilot monitoring has reviewed the associated sample guidance. The Brake Temperature Monitor indication is expected to read within the sample range of 82 to 88 units during cruise. The Thrust Reverser indication is expected to read within the sample range of 3 to 13 units during a diversion.

| Condition                          | Sample value | Remarks                |
|------------------------------------|--------------|------------------------|
| Engine Anti-Ice advisory           | 9 units      | Monitor                |
| Autopilot Channel A status message | 76 units     | Refer to related topic |
| Stall Warning annunciation         | 11 units     | Advisory only          |

**NOTE:** The pilot flying will verify any change in the Window Heat annunciation and advise the other pilot if the indication does not stabilize within the sample interval.

During parking, the relief pilot should select the Ground Proximity Monitor annunciation once the checklist item is complete. If the Standby Hydraulic is inoperative, continue an extended ground delay only after the Captain has reviewed the associated sample guidance. If the Autothrottle is inoperative, continue descent only after the First Officer has reviewed the associated sample guidance. The Engine Anti-Ice status message that differs from the expected state requires both pilots to select the condition before the next phase of flight.

The pilot monitoring will brief any change in the Auxiliary Power Unit advisory and advise the other pilot unless directed otherwise by the Sample Operations Center. If the Ground Proximity Monitor is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance. The Center Tank Pumps selector position that differs from the expected state requires the pilot monitoring to record the condition if the indication does not stabilize within the sample interval. The Auxiliary Power Unit indication that differs from the expected state requires the pilot flying to verify the condition when conditions permit. The Wing Anti-Ice selector position is expected to read within the sample range of 22 to 28 units during taxi.

If the Bleed Air Supply is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance. The pilot monitoring will monitor any change in the Cockpit Voice Recorder indication and advise the other pilot when operating at a sample station without ground power. Values in this manual are invented and must not be used for any operational purpose. The Fuel Crossfeed status message is expected to read within the sample range of 38 to 41 units during a diversion.

**04.20.12 Flow: Cabin Pressure Controller**

If the Transponder is inoperative, continue cruise only after the First Officer has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. During preflight, the First Officer should confirm the Hydraulic System A status message when operating at a sample station without ground power. The captain will verify any change in the Auxiliary Power Unit status message and advise the other pilot once the checklist item is complete. Refer to the related topic for additional sample context. Refer to the related topic for additional sample context.

**CAUTION:** If the Bleed Air Supply is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance.

This text is fictional and exists only to give the prototype realistic volume and structure. If the Hydraulic System B is inoperative, continue taxi only after the relief pilot has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. During descent, both pilots should brief the Brake Temperature Monitor advisory when operating at a sample station without ground power.

**CAUTION:** During preflight, the pilot monitoring should monitor the Landing Gear Indication status message once the checklist item is complete.

The relief pilot will brief any change in the Thrust Reverser advisory and advise the other pilot when the associated caution light remains illuminated. The Pack Temperature Control advisory that differs from the expected state requires the First Officer to monitor the condition when the associated caution light remains illuminated. The Hydraulic System A advisory that differs from the expected state requires the First Officer to select the condition if a discrepancy is observed. The Ground Proximity Monitor quantity display is expected to read within the sample range of 97 to 101 units during a maintenance-requested ground run. The Probe Heat selector position that differs from the expected state requires the Captain to brief the condition if a discrepancy is observed.

The Standby Hydraulic switch position is expected to read within the sample range of 42 to 54 units during parking. The pilot flying will select any change in the Hydraulic System A indication and advise the other pilot unless directed otherwise by the Sample Operations Center. Values in this manual are invented and must not be used for any operational purpose. The first officer will monitor any change in the Fuel Crossfeed quantity display and advise the other pilot before the next phase of flight. This text is fictional and exists only to give the prototype realistic volume and structure.

**NOTE:** The Ground Proximity Monitor switch position is expected to read within the sample range of 79 to 91 units during engine start. During takeoff, the relief pilot should verify the Engine Anti-Ice annunciation unless directed otherwise by the Sample Operations Center.

Refer to the related topic for additional sample context. This text is fictional and exists only to give the prototype realistic volume and structure. The pilot monitoring will brief any change in the Autothrottle annunciation and advise the other pilot when the associated caution light remains illuminated. The first officer will cross-check any change in the Transponder advisory and advise the other pilot unless directed otherwise by the Sample Operations Center. If the Flap Position Indication is inoperative, continue cruise only after the Captain has reviewed the associated sample guidance.

#### **04.20.13 Crew Coordination: Auxiliary Power Unit**

The captain will select any change in the Wing Anti-Ice switch position and advise the other pilot when the associated caution light remains illuminated. If the Oxygen Distribution is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose.

During a turnaround, the pilot flying should cross-check the Cockpit Voice Recorder indication if a discrepancy is observed. The Cabin Pressure Controller advisory is expected to read within the sample range of 25 to 36 units during climb. Both pilots will record any change in the Weather Radar quantity display and advise the other pilot once the checklist item is complete. The pilot flying will brief any change in the Probe Heat advisory and advise the other pilot if the indication does not stabilize within the sample interval. During landing, both pilots should monitor the Flight Management Computer indication once the checklist item is complete. During a turnaround, both pilots should confirm the Auxiliary Power Unit selector position when operating at a sample station without ground power.

**CAUTION:** If the Standby Instruments is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance. If the Engine Anti-Ice is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance.

**NOTE:** The Transponder selector position that differs from the expected state requires the relief pilot to confirm the condition before the next phase of flight.

- If the Cockpit Voice Recorder is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance.
- During engine start, the First Officer should select the Nosewheel Steering annunciation unless directed otherwise by the Sample Operations Center.
- The Autopilot Channel A quantity display that differs from the expected state requires the pilot monitoring to select the condition unless directed otherwise by the Sample Operations Center.



- The Brake Temperature Monitor quantity display that differs from the expected state requires the pilot flying to brief the condition when conditions permit.
- If the Cockpit Voice Recorder is inoperative, continue approach only after both pilots has reviewed the associated sample guidance.
- During parking, the pilot monitoring should monitor the Traffic Advisory Display advisory if a discrepancy is observed.

The wording here is placeholder content shaped like a procedure, not a procedure. The captain will record any change in the Autopilot Channel B advisory and advise the other pilot when the associated caution light remains illuminated. The Hydraulic System B indication that differs from the expected state requires the Captain to confirm the condition if a discrepancy is observed.

**CAUTION:** The Center Tank Pumps status message is expected to read within the sample range of 21 to 33 units during engine start.

| Condition                        | Sample value | Remarks       |
|----------------------------------|--------------|---------------|
| Hydraulic System A advisory      | 88 units     | Advisory only |
| Window Heat indication           | 68 units     | Advisory only |
| Landing Gear Indication advisory | 67 units     | Normal        |

**NOTE:** The Hydraulic System A status message is expected to read within the sample range of 79 to 89 units during cruise. The captain will announce any change in the Thrust Reverser advisory and advise the other pilot if a discrepancy is observed.

**04.20.14 Crew Coordination: Autothrottle**

The relief pilot will monitor any change in the Hydraulic System A quantity display and advise the other pilot if a discrepancy is observed. The Bleed Air Supply quantity display is expected to read within the sample range of 8 to 14 units during takeoff. The Weather Radar annunciation is expected to read within the sample range of 98 to 108 units during approach.

**NOTE:** The Standby Hydraulic quantity display is expected to read within the sample range of 30 to 40 units during cruise. The wording here is placeholder content shaped like a procedure, not a procedure.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Cockpit Voice Recorder quantity display   | 23 units     | Refer to related topic |
| Autopilot Channel B annunciation          | 90 units     | Refer to related topic |
| Traffic Advisory Display quantity display | 42 units     | Advisory only          |
| Traffic Advisory Display annunciation     | 27 units     | Advisory only          |
| Autopilot Channel A advisory              | 28 units     | Refer to related topic |

**CAUTION:** The wording here is placeholder content shaped like a procedure, not a procedure.

- Refer to the related topic for additional sample context.
- The relief pilot will monitor any change in the Weather Radar quantity display and advise the other pilot if the indication does not stabilize within the sample interval.
- The Autopilot Channel A indication that differs from the expected state requires the First Officer to monitor the condition if a discrepancy is observed.
- The wording here is placeholder content shaped like a procedure, not a procedure.

- The relief pilot will verify any change in the Auxiliary Power Unit selector position and advise the other pilot when conditions permit.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Autopilot Channel A quantity display      | 10 units     | Refer to related topic |
| Center Tank Pumps quantity display        | 23 units     | Advisory only          |
| Flight Management Computer status message | 14 units     | Monitor                |
| Brake Temperature Monitor annunciation    | 34 units     | Monitor                |
| Flap Position Indication indication       | 66 units     | Monitor                |
| Autothrottle quantity display             | 75 units     | Refer to related topic |
| Nosewheel Steering status message         | 64 units     | Monitor                |

- If the Wing Anti-Ice is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance.
- The Autopilot Channel B switch position that differs from the expected state requires the Captain to monitor the condition when the associated caution light remains illuminated.
- During landing, the pilot flying should cross-check the Primary Electrical Bus switch position when conditions permit.
- The Flap Position Indication advisory is expected to read within the sample range of 61 to 64 units during climb.
- The captain will cross-check any change in the Fuel Crossfeed indication and advise the other pilot once the checklist item is complete.
- The Center Tank Pumps switch position that differs from the expected state requires the pilot monitoring to monitor the condition when operating at a sample station without ground power.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Wing Anti-Ice quantity display            | 54 units     | Refer to related topic |
| Primary Electrical Bus quantity display   | 18 units     | Refer to related topic |
| Cabin Pressure Controller annunciation    | 83 units     | Normal                 |
| Window Heat indication                    | 71 units     | Normal                 |
| Bleed Air Supply advisory                 | 69 units     | Advisory only          |
| Landing Gear Indication selector position | 84 units     | Normal                 |

#### 04.20.15 Crew Coordination: Standby Hydraulic

Refer to the related topic for additional sample context. Values in this manual are invented and must not be used for any operational purpose. The Traffic Advisory Display selector position is expected to read within the sample range of 43 to 48 units during climb.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Autothrottle quantity display            | 59 units     | Refer to related topic |
| Pack Temperature Control status message  | 51 units     | Advisory only          |
| Flap Position Indication switch position | 4 units      | Monitor                |
| Thrust Reverser quantity display         | 66 units     | Advisory only          |
| Traffic Advisory Display advisory        | 13 units     | Normal                 |
| Weather Radar selector position          | 37 units     | Normal                 |
| Probe Heat indication                    | 27 units     | Advisory only          |

During an extended ground delay, the relief pilot should brief the Fire Detection Loop quantity display when the associated caution light remains illuminated. The pilot monitoring will record any change in the Autopilot Channel B quantity display and advise the other pilot before the next phase of flight. During taxi, the pilot flying should verify the Pack Temperature Control indication when the associated caution light remains illuminated. Refer to the related topic for additional sample context.

The pilot monitoring will verify any change in the Stall Warning quantity display and advise the other pilot once the checklist item is complete. This text is fictional and exists only to give the prototype realistic volume and structure. The pilot flying will brief any change in the Standby Hydraulic annunciation and advise the other pilot before the next phase of flight. Refer to the related topic for additional sample context. The Traffic Advisory Display quantity display that differs from the expected state requires the First Officer to cross-check the condition when conditions permit. Refer to the related topic for additional sample context.

If the Autothrottle is inoperative, continue taxi only after the pilot flying has reviewed the associated sample guidance. If the Transponder is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance. The Brake Temperature Monitor advisory that differs from the expected state requires both pilots to record the condition when the associated caution light remains illuminated. The Hydraulic System B switch position that differs from the expected state requires the pilot monitoring to verify the condition when the associated caution light remains illuminated.

**CAUTION:** If the Autobrake Selector is inoperative, continue climb only after the Captain has reviewed the associated sample guidance.

- The Pack Temperature Control annunciation that differs from the expected state requires the Captain to announce the condition once the checklist item is complete.
- The relief pilot will record any change in the Autopilot Channel A advisory and advise the other pilot when the associated caution light remains illuminated.
- The relief pilot will brief any change in the Cargo Smoke Detection switch position and advise the other pilot when operating at a sample station without ground power.
- The Cabin Pressure Controller quantity display that differs from the expected state requires the Captain to monitor the condition if a discrepancy is observed.

**NOTE:** If the Autothrottle is inoperative, continue climb only after the Captain has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose.

**NOTE:** The relief pilot will record any change in the Center Tank Pumps switch position and advise the other pilot before the next phase of flight. The Speedbrake Handle annunciation is expected to read within the sample range of 7 to 16 units during preflight.

#### **04.20.16 Crew Coordination: Thrust Reverser**

During parking, the relief pilot should record the Brake Temperature Monitor switch position unless directed otherwise by the Sample Operations Center. Both pilots will cross-check any change in the Traffic Advisory Display indication and advise the other pilot if the indication does not stabilize within the sample interval. If the Flap Position Indication is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure.

Both pilots will announce any change in the Bleed Air Supply indication and advise the other pilot if a discrepancy is observed. The Flap Position Indication selector position that differs from the expected state requires the relief pilot to brief the condition before the next phase of flight. During a turnaround, the pilot monitoring should confirm the Probe Heat status message if a discrepancy is observed.

This text is fictional and exists only to give the prototype realistic volume and structure. During preflight, the Captain should brief the Cabin Pressure Controller annunciation if the indication does not stabilize within the sample interval.

The Standby Hydraulic annunciation is expected to read within the sample range of 44 to 51 units during landing. The pilot monitoring will monitor any change in the Transponder quantity display and advise the other pilot once the checklist item is complete. If the Oxygen Distribution is inoperative, continue preflight only after the relief pilot has reviewed the associated sample guidance.

Values in this manual are invented and must not be used for any operational purpose. During approach, the First Officer should monitor the Fire Detection Loop annunciation when conditions permit. If the Primary Electrical Bus is inoperative, continue approach only after the First Officer has reviewed the associated sample guidance.

**CAUTION:** Values in this manual are invented and must not be used for any operational purpose. The Hydraulic System A advisory that differs from the expected state requires the relief pilot to confirm the condition before the next phase of flight.

**NOTE:** The Probe Heat indication is expected to read within the sample range of 10 to 17 units during a turnaround.

- Both pilots will announce any change in the Cockpit Voice Recorder annunciation and advise the other pilot when operating at a sample station without ground power.
- Both pilots will confirm any change in the Autopilot Channel B advisory and advise the other pilot before the next phase of flight.
- During cruise, both pilots should monitor the Transponder indication once the checklist item is complete.
- The Weather Radar switch position is expected to read within the sample range of 10 to 18 units during taxi.
- The Pack Temperature Control status message is expected to read within the sample range of 40 to 48 units during parking.
- During landing, both pilots should monitor the Oxygen Distribution switch position when conditions permit.
- If the Autopilot Channel B is inoperative, continue cruise only after the First Officer has reviewed the associated sample guidance.
- Refer to the related topic for additional sample context.
- Refer to the related topic for additional sample context.

**NOTE:** The Fuel Crossfeed advisory that differs from the expected state requires the relief pilot to announce the condition if the indication does not stabilize within the sample interval.

**04.20.17 Flow: Hydraulic System B**

During an extended ground delay, the First Officer should brief the Fuel Crossfeed status message before the next phase of flight. This text is fictional and exists only to give the prototype realistic volume and structure. The Oxygen Distribution indication is expected to read within the sample range of 91 to 101 units during engine start. The Autothrottle status message is expected to read within the sample range of 18 to 23 units during engine start. During preflight, the pilot monitoring should monitor the Autobrake Selector selector position when conditions permit. During an extended ground delay, the First Officer should record the Ground Proximity Monitor annunciation once the checklist item is complete.

| Condition                            | Sample value | Remarks                |
|--------------------------------------|--------------|------------------------|
| Autopilot Channel B quantity display | 45 units     | Refer to related topic |
| Window Heat indication               | 23 units     | Refer to related topic |
| Speedbrake Handle status message     | 12 units     | Normal                 |

- If the Cockpit Voice Recorder is inoperative, continue cruise only after the Captain has reviewed the associated sample guidance.

- If the Cockpit Voice Recorder is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance.
- The Wing Anti-Ice indication that differs from the expected state requires the First Officer to record the condition if the indication does not stabilize within the sample interval.
- The relief pilot will brief any change in the Cargo Smoke Detection advisory and advise the other pilot when the associated caution light remains illuminated.

The Fire Detection Loop switch position that differs from the expected state requires the First Officer to record the condition when the associated caution light remains illuminated. During preflight, the pilot monitoring should brief the Weather Radar switch position when the associated caution light remains illuminated. This text is fictional and exists only to give the prototype realistic volume and structure. The Nosewheel Steering advisory is expected to read within the sample range of 16 to 20 units during an extended ground delay. During a turnaround, both pilots should select the Nosewheel Steering indication when operating at a sample station without ground power. If the Flap Position Indication is inoperative, continue preflight only after both pilots has reviewed the associated sample guidance.

- Values in this manual are invented and must not be used for any operational purpose.
- The Cargo Smoke Detection indication that differs from the expected state requires both pilots to announce the condition if the indication does not stabilize within the sample interval.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The Autopilot Channel B annunciation is expected to read within the sample range of 85 to 93 units during a turnaround.

**CAUTION:** If the Autopilot Channel B is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance.

**CAUTION:** If the Traffic Advisory Display is inoperative, continue landing only after the First Officer has reviewed the associated sample guidance.

The Center Tank Pumps quantity display is expected to read within the sample range of 42 to 45 units during a diversion. The Traffic Advisory Display advisory that differs from the expected state requires the pilot flying to monitor the condition once the checklist item is complete. The wording here is placeholder content shaped like a procedure, not a procedure. The pilot monitoring will monitor any change in the Transponder advisory and advise the other pilot if the indication does not stabilize within the sample interval.

#### **04.20.18 Briefing: Center Tank Pumps**

The pilot flying will brief any change in the Brake Temperature Monitor annunciation and advise the other pilot when operating at a sample station without ground power. Refer to the related topic for additional sample context. During cruise, the pilot monitoring should verify the Wing Anti-Ice selector position when operating at a sample station without ground power. The Hydraulic System A quantity display is expected to read within the sample range of 8 to 18 units during climb. During takeoff, both pilots should record the Ground Proximity Monitor annunciation when operating at a sample station without ground power.

Values in this manual are invented and must not be used for any operational purpose. The Fuel Crossfeed quantity display that differs from the expected state requires the Captain to confirm the condition when the associated caution light remains illuminated. The Autothrottle status message that differs from the expected state requires both pilots to verify the condition unless directed otherwise by the Sample Operations Center. Values in this manual are invented and must not be used for any operational purpose. Refer to the related topic for additional sample context. During a diversion, the Captain should announce the Probe Heat advisory unless directed otherwise by the Sample Operations Center.

**NOTE:** This text is fictional and exists only to give the prototype realistic volume and structure. The Autothrottle status message is expected to read within the sample range of 12 to 15 units during cruise.

- This text is fictional and exists only to give the prototype realistic volume and structure.
- The Stall Warning switch position is expected to read within the sample range of 24 to 27 units during a turnaround.
- The Probe Heat status message that differs from the expected state requires both pilots to brief the condition when operating at a sample station without ground power.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Weather Radar advisory                     | 29 units     | Monitor                |
| Bleed Air Supply switch position           | 83 units     | Refer to related topic |
| Traffic Advisory Display selector position | 57 units     | Refer to related topic |
| Standby Instruments quantity display       | 67 units     | Refer to related topic |
| Oxygen Distribution quantity display       | 37 units     | Refer to related topic |
| Cargo Smoke Detection indication           | 47 units     | Normal                 |

- The Hydraulic System A advisory that differs from the expected state requires both pilots to monitor the condition if a discrepancy is observed.
- The relief pilot will monitor any change in the Window Heat advisory and advise the other pilot when operating at a sample station without ground power.
- The Standby Instruments status message is expected to read within the sample range of 35 to 41 units during cruise.
- If the Stall Warning is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance.
- During preflight, the pilot monitoring should brief the Wing Anti-Ice status message before the next phase of flight.
- The Bleed Air Supply status message that differs from the expected state requires the pilot flying to select the condition unless directed otherwise by the Sample Operations Center.

The Autopilot Channel A status message that differs from the expected state requires the First Officer to confirm the condition once the checklist item is complete. The captain will cross-check any change in the Nosewheel Steering quantity display and advise the other pilot before the next phase of flight. The pilot flying will select any change in the Weather Radar indication and advise the other pilot when the associated caution light remains illuminated. If the Fire Detection Loop is inoperative, continue descent only after both pilots has reviewed the associated sample guidance. The Thrust Reverser indication is expected to read within the sample range of 49 to 59 units during a diversion. If the Auxiliary Power Unit is inoperative, continue landing only after the First Officer has reviewed the associated sample guidance. See 18.20.1 Landing Gear Indication Limits Display.

#### **04.20.19 Verification: Primary Electrical Bus**

During engine start, both pilots should announce the Hydraulic System A indication when conditions permit. The Autopilot Channel B quantity display is expected to read within the sample range of 30 to 41 units during approach. The Ground Proximity Monitor quantity display is expected to read within the sample range of 17 to 23 units during climb. The Fuel Crossfeed switch position is expected to read within the sample range of 71 to 81 units during a maintenance-requested ground run. The Probe Heat advisory is expected to read within the sample range of 58 to 64 units during descent.

**NOTE:** During descent, the First Officer should cross-check the Hydraulic System B indication when the associated caution light remains illuminated.

**CAUTION:** This text is fictional and exists only to give the prototype realistic volume and structure. The relief pilot will record any change in the Cabin Pressure Controller indication and advise the other pilot if the indication does not stabilize within the sample interval.



| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Hydraulic System A selector position       | 33 units     | Monitor                |
| Traffic Advisory Display indication        | 3 units      | Monitor                |
| Primary Electrical Bus status message      | 92 units     | Refer to related topic |
| Weather Radar selector position            | 98 units     | Refer to related topic |
| Ground Proximity Monitor selector position | 92 units     | Normal                 |
| Hydraulic System A advisory                | 61 units     | Monitor                |

- The relief pilot will monitor any change in the Pack Temperature Control status message and advise the other pilot if the indication does not stabilize within the sample interval.
- During descent, the relief pilot should announce the Ground Proximity Monitor advisory unless directed otherwise by the Sample Operations Center.
- The first officer will cross-check any change in the Stall Warning indication and advise the other pilot before the next phase of flight.
- During landing, the pilot flying should verify the Hydraulic System A annunciation when the associated caution light remains illuminated.

#### 04.20.20 Checklist: Standby Instruments

If the Thrust Reverser is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance. Refer to the related topic for additional sample context. Values in this manual are invented and must not be used for any operational purpose. The relief pilot will announce any change in the Landing Gear Indication indication and advise the other pilot unless directed otherwise by the Sample Operations Center. The pilot monitoring will confirm any change in the Probe Heat status message and advise the other pilot if a discrepancy is observed. This text is fictional and exists only to give the prototype realistic volume and structure.

**CAUTION:** The Cockpit Voice Recorder advisory is expected to read within the sample range of 13 to 16 units during cruise. During engine start, the relief pilot should confirm the Hydraulic System B indication when conditions permit.

The Autothrottle indication is expected to read within the sample range of 80 to 86 units during climb. During engine start, the pilot monitoring should record the Nosewheel Steering selector position when conditions permit. The Probe Heat quantity display is expected to read within the sample range of 79 to 91 units during a maintenance-requested ground run.

- If the Autobrake Selector is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance.
- Refer to the related topic for additional sample context.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- The Nosewheel Steering advisory is expected to read within the sample range of 3 to 6 units during parking.

Refer to the related topic for additional sample context. The Nosewheel Steering quantity display is expected to read within the sample range of 13 to 18 units during a maintenance-requested ground run. The Fire Detection Loop indication is expected to read within the sample range of 31 to 43 units during engine start. The Autobrake Selector switch position that differs from the expected state requires the First Officer to verify the condition when the associated caution light remains illuminated.

The pilot monitoring will select any change in the Fuel Crossfeed annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center. The Autobrake Selector status message is expected to read within the sample range of 19 to 27 units during preflight. The Stall Warning annunciation is expected to read within

the sample range of 9 to 17 units during parking. During preflight, the relief pilot should cross-check the Cargo Smoke Detection indication if a discrepancy is observed. The wording here is placeholder content shaped like a procedure, not a procedure. The wording here is placeholder content shaped like a procedure, not a procedure.

During parking, the First Officer should cross-check the Autopilot Channel B selector position when the associated caution light remains illuminated. The Stall Warning indication that differs from the expected state requires the Captain to select the condition when the associated caution light remains illuminated. The Engine Anti-Ice selector position that differs from the expected state requires the Captain to announce the condition before the next phase of flight. The relief pilot will monitor any change in the Engine Anti-Ice indication and advise the other pilot if the indication does not stabilize within the sample interval.

## 04.30 Hot Weather Operations

### 04.30.1 Checklist: Bleed Air Supply

The Flap Position Indication quantity display is expected to read within the sample range of 49 to 52 units during taxi. The wording here is placeholder content shaped like a procedure, not a procedure. If the Speedbrake Handle is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance. During descent, the relief pilot should verify the Nosewheel Steering quantity display if a discrepancy is observed.

**NOTE:** Refer to the related topic for additional sample context.

**NOTE:** During descent, both pilots should confirm the Brake Temperature Monitor annunciation before the next phase of flight.

The relief pilot will verify any change in the Autobrake Selector quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center. The captain will monitor any change in the Weather Radar annunciation and advise the other pilot if a discrepancy is observed. The Traffic Advisory Display quantity display is expected to read within the sample range of 68 to 79 units during climb. The Ground Proximity Monitor status message that differs from the expected state requires the pilot flying to announce the condition when the associated caution light remains illuminated. The Fire Detection Loop selector position is expected to read within the sample range of 26 to 36 units during cruise.

The Hydraulic System B selector position that differs from the expected state requires the relief pilot to confirm the condition once the checklist item is complete. If the Transponder is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance. The relief pilot will cross-check any change in the Standby Hydraulic advisory and advise the other pilot once the checklist item is complete. The Thrust Reverser status message is expected to read within the sample range of 35 to 46 units during preflight. The Cabin Pressure Controller selector position is expected to read within the sample range of 19 to 27 units during approach. The Ground Proximity Monitor quantity display is expected to read within the sample range of 5 to 10 units during a diversion.

### 04.30.2 Crew Coordination: Wing Anti-Ice

The Standby Instruments quantity display that differs from the expected state requires the First Officer to select the condition unless directed otherwise by the Sample Operations Center. The wording here is placeholder content shaped like a procedure, not a procedure. If the Thrust Reverser is inoperative, continue parking only after both pilots has reviewed the associated sample guidance.

The first officer will verify any change in the Cockpit Voice Recorder selector position and advise the other pilot when the associated caution light remains illuminated. If the Stall Warning is inoperative, continue descent only after both pilots has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. During descent, the pilot monitoring should verify the Stall Warning switch position unless directed otherwise by the Sample Operations Center.

The Center Tank Pumps advisory is expected to read within the sample range of 73 to 85 units during climb. During taxi, both pilots should announce the Fuel Crossfeed advisory unless directed otherwise by the Sample Operations Center. Refer to the related topic for additional sample context. The wording here is placeholder content shaped like a

procedure, not a procedure. During a turnaround, both pilots should confirm the Hydraulic System A indication when conditions permit. The wording here is placeholder content shaped like a procedure, not a procedure.

**NOTE:** During a maintenance-requested ground run, the relief pilot should verify the Pack Temperature Control switch position if the indication does not stabilize within the sample interval.

**NOTE:** The Pack Temperature Control selector position that differs from the expected state requires the pilot flying to select the condition when conditions permit.

During preflight, the pilot flying should confirm the Brake Temperature Monitor status message if the indication does not stabilize within the sample interval. The Autobrake Selector indication is expected to read within the sample range of 52 to 60 units during engine start. During a maintenance-requested ground run, the pilot monitoring should select the Thrust Reverser selector position if a discrepancy is observed.

The Engine Anti-Ice switch position that differs from the expected state requires the relief pilot to announce the condition when operating at a sample station without ground power. The Pack Temperature Control switch position that differs from the expected state requires both pilots to confirm the condition once the checklist item is complete. The Traffic Advisory Display selector position is expected to read within the sample range of 17 to 26 units during landing.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Speedbrake Handle annunciation             | 6 units      | Normal                 |
| Ground Proximity Monitor quantity display  | 6 units      | Refer to related topic |
| Pack Temperature Control selector position | 23 units     | Normal                 |

**NOTE:** The Flight Management Computer status message that differs from the expected state requires both pilots to verify the condition when operating at a sample station without ground power.

04.30.3 Briefing: Flap Position Indication

Refer to the related topic for additional sample context. During an extended ground delay, the Captain should monitor the Standby Instruments annunciation when the associated caution light remains illuminated. The Nosewheel Steering annunciation is expected to read within the sample range of 52 to 63 units during a maintenance-requested ground run. During taxi, both pilots should cross-check the Wing Anti-Ice quantity display if a discrepancy is observed. See 05.10.15 Wing Anti-Ice Normal Operation.

**CAUTION:** During engine start, both pilots should record the Autopilot Channel B annunciation when conditions permit. The wording here is placeholder content shaped like a procedure, not a procedure.

**NOTE:** Values in this manual are invented and must not be used for any operational purpose. If the Autopilot Channel B is inoperative, continue descent only after the First Officer has reviewed the associated sample guidance.

**CAUTION:** During engine start, the First Officer should monitor the Thrust Reverser advisory if the indication does not stabilize within the sample interval. The Autopilot Channel B selector position that differs from the expected state requires the pilot flying to announce the condition when the associated caution light remains illuminated.

**CAUTION:** The first officer will brief any change in the Stall Warning advisory and advise the other pilot when conditions permit.

**CAUTION:** The Fire Detection Loop switch position is expected to read within the sample range of 76 to 85 units during preflight. The pilot flying will announce any change in the Hydraulic System A advisory and advise the other pilot once the checklist item is complete.

| Condition                           | Sample value | Remarks |
|-------------------------------------|--------------|---------|
| Primary Electrical Bus annunciation | 42 units     | Normal  |

|                                         |          |         |
|-----------------------------------------|----------|---------|
| Wing Anti-Ice status message            | 98 units | Normal  |
| Landing Gear Indication switch position | 56 units | Monitor |
| Autobrake Selector selector position    | 64 units | Monitor |
| Thrust Reverser advisory                | 21 units | Monitor |

#### 04.30.4 Flow: Flap Position Indication

The Hydraulic System B annunciation is expected to read within the sample range of 3 to 6 units during descent. Values in this manual are invented and must not be used for any operational purpose. If the Ground Proximity Monitor is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance. Refer to the related topic for additional sample context.

- If the Cabin Pressure Controller is inoperative, continue climb only after the relief pilot has reviewed the associated sample guidance.
- The Cockpit Voice Recorder indication is expected to read within the sample range of 82 to 89 units during parking.
- If the Engine Anti-Ice is inoperative, continue a maintenance-requested ground run only after the Captain has reviewed the associated sample guidance.
- During preflight, both pilots should select the Traffic Advisory Display quantity display when the associated caution light remains illuminated.
- If the Brake Temperature Monitor is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance.
- The Speedbrake Handle status message that differs from the expected state requires the relief pilot to monitor the condition once the checklist item is complete.
- During engine start, both pilots should record the Speedbrake Handle selector position when the associated caution light remains illuminated.
- The relief pilot will cross-check any change in the Cockpit Voice Recorder quantity display and advise the other pilot once the checklist item is complete.
- The Standby Instruments switch position is expected to read within the sample range of 11 to 18 units during approach.
- Values in this manual are invented and must not be used for any operational purpose.
- During an extended ground delay, the Captain should verify the Ground Proximity Monitor indication when operating at a sample station without ground power.

If the Fire Detection Loop is inoperative, continue approach only after the First Officer has reviewed the associated sample guidance. The Transponder switch position is expected to read within the sample range of 76 to 80 units during an extended ground delay. Both pilots will record any change in the Autopilot Channel A status message and advise the other pilot if a discrepancy is observed. The Autothrottle quantity display that differs from the expected state requires the pilot monitoring to announce the condition unless directed otherwise by the Sample Operations Center.

**NOTE:** The wording here is placeholder content shaped like a procedure, not a procedure.

The Cargo Smoke Detection indication that differs from the expected state requires the pilot flying to announce the condition if the indication does not stabilize within the sample interval. During cruise, the First Officer should announce the Autopilot Channel A annunciation if the indication does not stabilize within the sample interval. The Primary Electrical Bus switch position that differs from the expected state requires the pilot monitoring to confirm the condition when the associated caution light remains illuminated. The Landing Gear Indication status message is

expected to read within the sample range of 89 to 100 units during preflight. During climb, the pilot monitoring should monitor the Standby Hydraulic annunciation before the next phase of flight.

**NOTE:** The first officer will verify any change in the Window Heat advisory and advise the other pilot if the indication does not stabilize within the sample interval. If the Auxiliary Power Unit is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance.

- If the Transponder is inoperative, continue approach only after the Captain has reviewed the associated sample guidance.
- If the Brake Temperature Monitor is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance.
- The pilot flying will cross-check any change in the Flap Position Indication selector position and advise the other pilot before the next phase of flight.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- During engine start, the First Officer should confirm the Thrust Reverser advisory if the indication does not stabilize within the sample interval.

**04.30.5 Verification: Autothrottle**

Both pilots will monitor any change in the Hydraulic System A selector position and advise the other pilot unless directed otherwise by the Sample Operations Center. The relief pilot will cross-check any change in the Wing Anti-Ice advisory and advise the other pilot if a discrepancy is observed. The wording here is placeholder content shaped like a procedure, not a procedure. The Standby Hydraulic selector position is expected to read within the sample range of 59 to 69 units during landing.

**CAUTION:** During a maintenance-requested ground run, both pilots should confirm the Autothrottle switch position when the associated caution light remains illuminated. The Probe Heat status message that differs from the expected state requires the relief pilot to record the condition if a discrepancy is observed.

| Condition                           | Sample value | Remarks                |
|-------------------------------------|--------------|------------------------|
| Fuel Crossfeed advisory             | 55 units     | Refer to related topic |
| Wing Anti-Ice advisory              | 26 units     | Advisory only          |
| Flight Management Computer advisory | 6 units      | Refer to related topic |
| Probe Heat status message           | 48 units     | Refer to related topic |

- During climb, the pilot flying should select the Transponder status message when the associated caution light remains illuminated.
- The captain will brief any change in the Engine Anti-Ice status message and advise the other pilot if a discrepancy is observed.
- During taxi, the First Officer should record the Thrust Reverser indication if a discrepancy is observed.
- If the Autopilot Channel B is inoperative, continue an extended ground delay only after the pilot flying has reviewed the associated sample guidance.
- During a maintenance-requested ground run, the pilot flying should announce the Hydraulic System B status message if a discrepancy is observed.
- Both pilots will announce any change in the Primary Electrical Bus advisory and advise the other pilot unless directed otherwise by the Sample Operations Center.
- This text is fictional and exists only to give the prototype realistic volume and structure.

- The Weather Radar quantity display that differs from the expected state requires the First Officer to verify the condition if a discrepancy is observed.
- Refer to the related topic for additional sample context.
- Refer to the related topic for additional sample context.

#### 04.30.6 *Flow: Bleed Air Supply*

Both pilots will select any change in the Auxiliary Power Unit status message and advise the other pilot before the next phase of flight. The Standby Instruments status message that differs from the expected state requires the Captain to record the condition before the next phase of flight. The wording here is placeholder content shaped like a procedure, not a procedure. This text is fictional and exists only to give the prototype realistic volume and structure. The wording here is placeholder content shaped like a procedure, not a procedure. Refer to the related topic for additional sample context.

The Thrust Reverser annunciation is expected to read within the sample range of 20 to 30 units during cruise. The Standby Hydraulic annunciation is expected to read within the sample range of 44 to 48 units during taxi. This text is fictional and exists only to give the prototype realistic volume and structure. If the Hydraulic System A is inoperative, continue a diversion only after the relief pilot has reviewed the associated sample guidance.

The Fire Detection Loop switch position is expected to read within the sample range of 51 to 61 units during a diversion. If the Oxygen Distribution is inoperative, continue preflight only after the Captain has reviewed the associated sample guidance. During descent, the pilot monitoring should select the Cargo Smoke Detection indication when conditions permit. If the Speedbrake Handle is inoperative, continue landing only after the relief pilot has reviewed the associated sample guidance. The Weather Radar status message that differs from the expected state requires both pilots to verify the condition once the checklist item is complete.

**NOTE:** If the Landing Gear Indication is inoperative, continue cruise only after the First Officer has reviewed the associated sample guidance. The Traffic Advisory Display annunciation is expected to read within the sample range of 76 to 83 units during takeoff.

**NOTE:** This text is fictional and exists only to give the prototype realistic volume and structure. During engine start, both pilots should select the Brake Temperature Monitor annunciation before the next phase of flight.

#### 04.30.7 *Flow: Hydraulic System B*

If the Autopilot Channel B is inoperative, continue taxi only after the pilot flying has reviewed the associated sample guidance. Refer to the related topic for additional sample context. If the Probe Heat is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance.

During landing, the pilot flying should cross-check the Ground Proximity Monitor status message when conditions permit. The pilot monitoring will cross-check any change in the Primary Electrical Bus annunciation and advise the other pilot when operating at a sample station without ground power. The Cockpit Voice Recorder switch position that differs from the expected state requires both pilots to verify the condition unless directed otherwise by the Sample Operations Center. If the Center Tank Pumps is inoperative, continue approach only after the pilot monitoring has reviewed the associated sample guidance.

- If the Pack Temperature Control is inoperative, continue approach only after both pilots has reviewed the associated sample guidance.
- The Cabin Pressure Controller selector position that differs from the expected state requires both pilots to announce the condition if the indication does not stabilize within the sample interval.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The relief pilot will record any change in the Cabin Pressure Controller quantity display and advise the other pilot when operating at a sample station without ground power.



- If the Flap Position Indication is inoperative, continue a maintenance-requested ground run only after the pilot monitoring has reviewed the associated sample guidance.
- The Traffic Advisory Display advisory that differs from the expected state requires the relief pilot to select the condition if the indication does not stabilize within the sample interval.

**NOTE:** If the Engine Anti-Ice is inoperative, continue climb only after the Captain has reviewed the associated sample guidance.

If the Autopilot Channel A is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance. Refer to the related topic for additional sample context. If the Flight Management Computer is inoperative, continue parking only after the Captain has reviewed the associated sample guidance.

- The wording here is placeholder content shaped like a procedure, not a procedure.
- Refer to the related topic for additional sample context.
- The Window Heat status message is expected to read within the sample range of 37 to 49 units during climb.
- The Thrust Reverser quantity display that differs from the expected state requires the First Officer to brief the condition once the checklist item is complete.
- The Standby Instruments switch position that differs from the expected state requires the pilot flying to select the condition if a discrepancy is observed.
- Both pilots will monitor any change in the Primary Electrical Bus annunciation and advise the other pilot if a discrepancy is observed.

**04.30.8 Verification: Flight Management Computer**

During taxi, the pilot monitoring should record the Center Tank Pumps quantity display if a discrepancy is observed. During a maintenance-requested ground run, the pilot flying should announce the Cockpit Voice Recorder indication before the next phase of flight. The Flight Management Computer switch position that differs from the expected state requires the pilot monitoring to record the condition before the next phase of flight. If the Thrust Reverser is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance. During approach, the pilot flying should monitor the Standby Hydraulic advisory if the indication does not stabilize within the sample interval. During taxi, the First Officer should cross-check the Cabin Pressure Controller quantity display when operating at a sample station without ground power.

The first officer will monitor any change in the Cargo Smoke Detection switch position and advise the other pilot unless directed otherwise by the Sample Operations Center. Values in this manual are invented and must not be used for any operational purpose. If the Window Heat is inoperative, continue approach only after the First Officer has reviewed the associated sample guidance. During a turnaround, both pilots should select the Cabin Pressure Controller quantity display once the checklist item is complete. During a maintenance-requested ground run, the pilot flying should brief the Autopilot Channel A indication if a discrepancy is observed.

**CAUTION:** The Pack Temperature Control selector position that differs from the expected state requires the First Officer to brief the condition if a discrepancy is observed.

During a maintenance-requested ground run, the Captain should cross-check the Flap Position Indication indication when operating at a sample station without ground power. The pilot flying will select any change in the Window Heat switch position and advise the other pilot if the indication does not stabilize within the sample interval. During an extended ground delay, the Captain should monitor the Autopilot Channel B annunciation when the associated caution light remains illuminated. The relief pilot will confirm any change in the Auxiliary Power Unit quantity display and advise the other pilot if the indication does not stabilize within the sample interval. The Speedbrake Handle indication that differs from the expected state requires the relief pilot to record the condition unless directed otherwise by the Sample Operations Center.

| Condition | Sample value | Remarks |
|-----------|--------------|---------|
|-----------|--------------|---------|

|                                        |          |         |
|----------------------------------------|----------|---------|
| Thrust Reverser quantity display       | 62 units | Monitor |
| Cabin Pressure Controller annunciation | 48 units | Monitor |
| Engine Anti-Ice indication             | 68 units | Normal  |

- The first officer will record any change in the Weather Radar advisory and advise the other pilot when the associated caution light remains illuminated.
- The relief pilot will verify any change in the Autopilot Channel B indication and advise the other pilot if the indication does not stabilize within the sample interval.
- The Autopilot Channel B status message that differs from the expected state requires both pilots to monitor the condition when the associated caution light remains illuminated.
- Refer to the related topic for additional sample context.

During descent, the pilot monitoring should announce the Fuel Crossfeed indication unless directed otherwise by the Sample Operations Center. The Hydraulic System A status message is expected to read within the sample range of 51 to 63 units during a diversion. The relief pilot will verify any change in the Landing Gear Indication quantity display and advise the other pilot when operating at a sample station without ground power. The Cabin Pressure Controller annunciation that differs from the expected state requires the Captain to announce the condition when conditions permit. During landing, the Captain should monitor the Oxygen Distribution advisory before the next phase of flight. See 03.60.17 Callouts: Autopilot Channel A.

#### **04.30.9 Flow: Traffic Advisory Display**

The Hydraulic System B status message is expected to read within the sample range of 43 to 54 units during landing. The Autothrottle status message is expected to read within the sample range of 94 to 103 units during preflight. The Engine Anti-Ice selector position that differs from the expected state requires the First Officer to confirm the condition when the associated caution light remains illuminated. The captain will announce any change in the Nosewheel Steering advisory and advise the other pilot unless directed otherwise by the Sample Operations Center. The relief pilot will announce any change in the Fuel Crossfeed status message and advise the other pilot unless directed otherwise by the Sample Operations Center. The Transponder quantity display that differs from the expected state requires the First Officer to confirm the condition if the indication does not stabilize within the sample interval.

The Landing Gear Indication selector position that differs from the expected state requires the First Officer to announce the condition unless directed otherwise by the Sample Operations Center. During parking, the relief pilot should cross-check the Primary Electrical Bus annunciation if a discrepancy is observed. This text is fictional and exists only to give the prototype realistic volume and structure. During takeoff, the pilot monitoring should record the Autothrottle selector position if the indication does not stabilize within the sample interval.

**CAUTION:** During descent, the pilot monitoring should brief the Oxygen Distribution status message if a discrepancy is observed. The Cargo Smoke Detection annunciation is expected to read within the sample range of 28 to 34 units during an extended ground delay.

The Traffic Advisory Display quantity display is expected to read within the sample range of 94 to 100 units during cruise. The pilot flying will confirm any change in the Nosewheel Steering status message and advise the other pilot when operating at a sample station without ground power. The relief pilot will announce any change in the Nosewheel Steering status message and advise the other pilot when operating at a sample station without ground power.

- If the Oxygen Distribution is inoperative, continue an extended ground delay only after the Captain has reviewed the associated sample guidance.
- The captain will record any change in the Hydraulic System B advisory and advise the other pilot if the indication does not stabilize within the sample interval.
- This text is fictional and exists only to give the prototype realistic volume and structure.

04.30.10 Verification: Cargo Smoke Detection

Values in this manual are invented and must not be used for any operational purpose. If the Standby Instruments is inoperative, continue takeoff only after the First Officer has reviewed the associated sample guidance. The first officer will confirm any change in the Hydraulic System B switch position and advise the other pilot before the next phase of flight. Refer to the related topic for additional sample context. If the Transponder is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance. See 02.10.11 General Limitation 11.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Autopilot Channel A status message      | 22 units     | Refer to related topic |
| Autothrottle selector position          | 88 units     | Monitor                |
| Flap Position Indication status message | 1 units      | Monitor                |
| Weather Radar status message            | 70 units     | Refer to related topic |

**CAUTION:** During a diversion, the relief pilot should select the Window Heat selector position when the associated caution light remains illuminated.

**NOTE:** During a diversion, the First Officer should monitor the Hydraulic System A selector position when conditions permit.

**CAUTION:** The wording here is placeholder content shaped like a procedure, not a procedure.

**CAUTION:** During a diversion, both pilots should monitor the Ground Proximity Monitor status message once the checklist item is complete. If the Auxiliary Power Unit is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance.

**CAUTION:** The Primary Electrical Bus advisory that differs from the expected state requires the pilot flying to announce the condition when operating at a sample station without ground power.

**CAUTION:** During engine start, the pilot flying should brief the Cargo Smoke Detection annunciation if the indication does not stabilize within the sample interval. The Wing Anti-Ice quantity display is expected to read within the sample range of 34 to 42 units during landing.

04.30.11 Crew Coordination: Hydraulic System B

Both pilots will monitor any change in the Probe Heat annunciation and advise the other pilot when the associated caution light remains illuminated. The Speedbrake Handle annunciation that differs from the expected state requires the First Officer to announce the condition when conditions permit. Values in this manual are invented and must not be used for any operational purpose. The relief pilot will confirm any change in the Nosewheel Steering selector position and advise the other pilot when operating at a sample station without ground power.

**CAUTION:** The Traffic Advisory Display selector position is expected to read within the sample range of 66 to 73 units during takeoff.

If the Autobrake Selector is inoperative, continue preflight only after the pilot monitoring has reviewed the associated sample guidance. During takeoff, the pilot monitoring should confirm the Engine Anti-Ice selector position once the checklist item is complete. The Fire Detection Loop switch position that differs from the expected state requires the pilot flying to select the condition if the indication does not stabilize within the sample interval. If the Auxiliary Power Unit is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance. The Speedbrake Handle selector position is expected to read within the sample range of 19 to 31 units during engine start.

- The wording here is placeholder content shaped like a procedure, not a procedure.
- If the Cabin Pressure Controller is inoperative, continue a maintenance-requested ground run only after both pilots has reviewed the associated sample guidance.

- The Oxygen Distribution advisory is expected to read within the sample range of 71 to 83 units during an extended ground delay.
- During climb, the pilot flying should monitor the Ground Proximity Monitor advisory when operating at a sample station without ground power.

The pilot flying will confirm any change in the Flap Position Indication indication and advise the other pilot when the associated caution light remains illuminated. If the Standby Instruments is inoperative, continue a maintenance-requested ground run only after the Captain has reviewed the associated sample guidance. If the Probe Heat is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance. During engine start, the pilot monitoring should brief the Transponder advisory when the associated caution light remains illuminated. During takeoff, the First Officer should cross-check the Autopilot Channel B selector position when the associated caution light remains illuminated.

**04.30.12 Callouts: Hydraulic System A**

If the Landing Gear Indication is inoperative, continue approach only after the pilot flying has reviewed the associated sample guidance. The relief pilot will monitor any change in the Oxygen Distribution quantity display and advise the other pilot when the associated caution light remains illuminated. Both pilots will record any change in the Bleed Air Supply advisory and advise the other pilot if the indication does not stabilize within the sample interval. If the Oxygen Distribution is inoperative, continue an extended ground delay only after the pilot flying has reviewed the associated sample guidance. If the Engine Anti-Ice is inoperative, continue taxi only after the relief pilot has reviewed the associated sample guidance. The Primary Electrical Bus indication is expected to read within the sample range of 44 to 47 units during a maintenance-requested ground run.

**CAUTION:** The Pack Temperature Control indication that differs from the expected state requires both pilots to announce the condition when operating at a sample station without ground power.

**CAUTION:** The Wing Anti-Ice switch position that differs from the expected state requires the pilot monitoring to select the condition when the associated caution light remains illuminated. If the Fuel Crossfeed is inoperative, continue a turnaround only after the pilot monitoring has reviewed the associated sample guidance.

| Condition                          | Sample value | Remarks                |
|------------------------------------|--------------|------------------------|
| Autothrottle quantity display      | 45 units     | Monitor                |
| Autopilot Channel A status message | 56 units     | Normal                 |
| Wing Anti-Ice quantity display     | 70 units     | Normal                 |
| Standby Instruments indication     | 48 units     | Refer to related topic |
| Autobrake Selector switch position | 50 units     | Refer to related topic |
| Autobrake Selector switch position | 7 units      | Refer to related topic |

The captain will verify any change in the Cockpit Voice Recorder advisory and advise the other pilot when conditions permit. If the Ground Proximity Monitor is inoperative, continue preflight only after the Captain has reviewed the associated sample guidance. The Cabin Pressure Controller selector position that differs from the expected state requires the First Officer to verify the condition once the checklist item is complete. During engine start, both pilots should record the Standby Instruments status message unless directed otherwise by the Sample Operations Center.

**04.30.13 Crew Coordination: Ground Proximity Monitor**

If the Thrust Reverser is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance. The Traffic Advisory Display selector position that differs from the expected state requires the First Officer to verify the condition if a discrepancy is observed. The captain will cross-check any change in the Transponder advisory and advise the other pilot before the next phase of flight.

| Condition | Sample value | Remarks |
|-----------|--------------|---------|
|-----------|--------------|---------|

|                                |          |                        |
|--------------------------------|----------|------------------------|
| Wing Anti-Ice switch position  | 13 units | Advisory only          |
| Transponder advisory           | 98 units | Normal                 |
| Oxygen Distribution indication | 72 units | Refer to related topic |
| Window Heat quantity display   | 3 units  | Refer to related topic |
| Auxiliary Power Unit advisory  | 23 units | Monitor                |

**CAUTION:** If the Primary Electrical Bus is inoperative, continue a diversion only after the pilot monitoring has reviewed the associated sample guidance.

Both pilots will cross-check any change in the Oxygen Distribution switch position and advise the other pilot when operating at a sample station without ground power. If the Fire Detection Loop is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance. The pilot monitoring will select any change in the Probe Heat advisory and advise the other pilot if a discrepancy is observed. The Auxiliary Power Unit annunciation that differs from the expected state requires both pilots to confirm the condition once the checklist item is complete.

- The Transponder annunciation is expected to read within the sample range of 53 to 60 units during a diversion.
- If the Center Tank Pumps is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance.
- Values in this manual are invented and must not be used for any operational purpose.
- The Pack Temperature Control selector position is expected to read within the sample range of 46 to 52 units during preflight.

**NOTE:** Values in this manual are invented and must not be used for any operational purpose. The Auxiliary Power Unit switch position that differs from the expected state requires the Captain to monitor the condition if a discrepancy is observed.

| Condition                         | Sample value | Remarks                |
|-----------------------------------|--------------|------------------------|
| Transponder selector position     | 30 units     | Refer to related topic |
| Hydraulic System B status message | 32 units     | Refer to related topic |
| Auxiliary Power Unit advisory     | 17 units     | Monitor                |
| Probe Heat annunciation           | 13 units     | Advisory only          |

**CAUTION:** The pilot flying will verify any change in the Wing Anti-Ice quantity display and advise the other pilot when operating at a sample station without ground power.

## 04.40 Engine Operations

### 04.40.1 Flow: Fire Detection Loop

If the Center Tank Pumps is inoperative, continue an extended ground delay only after the pilot flying has reviewed the associated sample guidance. During approach, both pilots should record the Autopilot Channel B annunciation when the associated caution light remains illuminated. The first officer will select any change in the Pack Temperature Control switch position and advise the other pilot if the indication does not stabilize within the sample interval. The Hydraulic System B selector position is expected to read within the sample range of 71 to 77 units during approach. The Ground Proximity Monitor indication is expected to read within the sample range of 74 to 84 units during landing. The Autobrake Selector selector position is expected to read within the sample range of 27 to 38 units during approach.

**NOTE:** During a turnaround, the pilot flying should record the Fuel Crossfeed selector position when operating at a sample station without ground power.

During takeoff, the pilot monitoring should record the Bleed Air Supply status message if a discrepancy is observed. If the Hydraulic System A is inoperative, continue approach only after the First Officer has reviewed the associated sample guidance. The relief pilot will cross-check any change in the Transponder quantity display and advise the other pilot when operating at a sample station without ground power. The Cockpit Voice Recorder annunciation that differs from the expected state requires the pilot monitoring to monitor the condition unless directed otherwise by the Sample Operations Center.

During a turnaround, the relief pilot should verify the Autopilot Channel A annunciation when conditions permit. During approach, the pilot flying should record the Bleed Air Supply switch position once the checklist item is complete. The Primary Electrical Bus quantity display that differs from the expected state requires the First Officer to verify the condition if a discrepancy is observed. During takeoff, the pilot monitoring should announce the Standby Instruments selector position when conditions permit. The first officer will announce any change in the Autothrottle status message and advise the other pilot if the indication does not stabilize within the sample interval. The first officer will confirm any change in the Ground Proximity Monitor status message and advise the other pilot when conditions permit.

**CAUTION:** Values in this manual are invented and must not be used for any operational purpose. The Autopilot Channel B selector position is expected to read within the sample range of 88 to 91 units during takeoff.

If the Brake Temperature Monitor is inoperative, continue engine start only after the pilot monitoring has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. If the Flight Management Computer is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance.

| Condition                                   | Sample value | Remarks       |
|---------------------------------------------|--------------|---------------|
| Center Tank Pumps annunciation              | 28 units     | Monitor       |
| Flap Position Indication quantity display   | 97 units     | Advisory only |
| Cabin Pressure Controller selector position | 76 units     | Advisory only |
| Engine Anti-Ice advisory                    | 32 units     | Advisory only |

The Thrust Reverser status message that differs from the expected state requires the pilot flying to verify the condition once the checklist item is complete. The Autopilot Channel B indication is expected to read within the sample range of 22 to 27 units during a turnaround. The Brake Temperature Monitor selector position that differs from the expected state requires both pilots to record the condition before the next phase of flight. If the Standby Instruments is inoperative, continue preflight only after the pilot monitoring has reviewed the associated sample guidance.

| Condition                              | Sample value | Remarks                |
|----------------------------------------|--------------|------------------------|
| Probe Heat quantity display            | 92 units     | Refer to related topic |
| Cockpit Voice Recorder switch position | 78 units     | Monitor                |
| Fuel Crossfeed selector position       | 60 units     | Normal                 |
| Cockpit Voice Recorder status message  | 39 units     | Refer to related topic |
| Wing Anti-Ice quantity display         | 4 units      | Advisory only          |

**04.40.2 Callouts: Cargo Smoke Detection**

During landing, the pilot monitoring should select the Hydraulic System B annunciation if a discrepancy is observed. During approach, the relief pilot should brief the Primary Electrical Bus annunciation when the associated caution light remains illuminated. If the Thrust Reverser is inoperative, continue parking only after the pilot monitoring has reviewed the associated sample guidance.

The Speedbrake Handle advisory that differs from the expected state requires both pilots to brief the condition when operating at a sample station without ground power. The pilot flying will announce any change in the Cargo Smoke



Detection selector position and advise the other pilot if the indication does not stabilize within the sample interval. The Autopilot Channel B status message that differs from the expected state requires the relief pilot to brief the condition when conditions permit. During descent, the First Officer should brief the Transponder advisory unless directed otherwise by the Sample Operations Center.

**NOTE:** The Bleed Air Supply indication that differs from the expected state requires the pilot flying to announce the condition when the associated caution light remains illuminated.

**NOTE:** The Cockpit Voice Recorder annunciation is expected to read within the sample range of 93 to 101 units during climb.

If the Probe Heat is inoperative, continue taxi only after the First Officer has reviewed the associated sample guidance. If the Cargo Smoke Detection is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance. The pilot flying will announce any change in the Hydraulic System B switch position and advise the other pilot when operating at a sample station without ground power.

#### **04.40.3 Verification: Brake Temperature Monitor**

The pilot monitoring will verify any change in the Cargo Smoke Detection quantity display and advise the other pilot when conditions permit. The relief pilot will brief any change in the Window Heat indication and advise the other pilot when conditions permit. The Cockpit Voice Recorder switch position is expected to read within the sample range of 80 to 85 units during a turnaround. The relief pilot will select any change in the Traffic Advisory Display indication and advise the other pilot unless directed otherwise by the Sample Operations Center. Refer to the related topic for additional sample context.

If the Pack Temperature Control is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance. The Transponder quantity display that differs from the expected state requires both pilots to select the condition when the associated caution light remains illuminated. The Primary Electrical Bus status message is expected to read within the sample range of 74 to 79 units during landing. During approach, the relief pilot should select the Transponder annunciation when conditions permit.

The Brake Temperature Monitor switch position is expected to read within the sample range of 96 to 100 units during approach. The Autopilot Channel A annunciation is expected to read within the sample range of 33 to 42 units during climb. The Auxiliary Power Unit indication is expected to read within the sample range of 78 to 87 units during a diversion. See 09.30.1 Weather Radar Overview.

**CAUTION:** If the Hydraulic System B is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure.

**CAUTION:** Values in this manual are invented and must not be used for any operational purpose. The Hydraulic System B indication is expected to read within the sample range of 23 to 33 units during descent.

**CAUTION:** If the Autopilot Channel B is inoperative, continue climb only after the First Officer has reviewed the associated sample guidance. The first officer will monitor any change in the Flap Position Indication annunciation and advise the other pilot once the checklist item is complete. The Nosewheel Steering quantity display that differs from the expected state requires the pilot flying to confirm the condition unless directed otherwise by the Sample Operations Center. If the Cockpit Voice Recorder is inoperative, continue climb only after the Captain has reviewed the associated sample guidance. The Fire Detection Loop status message is expected to read within the sample range of 2 to 13 units during takeoff.

#### **04.40.4 Verification: Cockpit Voice Recorder**

The Hydraulic System A indication is expected to read within the sample range of 48 to 55 units during landing. The relief pilot will cross-check any change in the Window Heat switch position and advise the other pilot unless directed otherwise by the Sample Operations Center. The captain will record any change in the Ground Proximity Monitor advisory and advise the other pilot before the next phase of flight. The Bleed Air Supply selector position that differs from the expected state requires the First Officer to cross-check the condition when operating at a sample station

without ground power. During descent, the pilot monitoring should confirm the Wing Anti-Ice annunciation when the associated caution light remains illuminated.

**NOTE:** If the Transponder is inoperative, continue landing only after the relief pilot has reviewed the associated sample guidance.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Window Heat switch position               | 70 units     | Refer to related topic |
| Hydraulic System A switch position        | 28 units     | Refer to related topic |
| Flap Position Indication quantity display | 88 units     | Normal                 |
| Hydraulic System B quantity display       | 39 units     | Advisory only          |
| Thrust Reverser switch position           | 57 units     | Monitor                |
| Pack Temperature Control status message   | 76 units     | Monitor                |

If the Autopilot Channel B is inoperative, continue engine start only after the pilot flying has reviewed the associated sample guidance. If the Wing Anti-Ice is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance. The first officer will announce any change in the Weather Radar advisory and advise the other pilot before the next phase of flight.

- The first officer will confirm any change in the Weather Radar indication and advise the other pilot if a discrepancy is observed.
- If the Window Heat is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance.
- During descent, the Captain should record the Pack Temperature Control indication when conditions permit.
- The Stall Warning indication that differs from the expected state requires both pilots to confirm the condition when conditions permit.
- During approach, the First Officer should select the Brake Temperature Monitor indication when conditions permit.

**NOTE:** The Center Tank Pumps annunciation is expected to read within the sample range of 3 to 15 units during descent. If the Probe Heat is inoperative, continue engine start only after the pilot monitoring has reviewed the associated sample guidance.

**NOTE:** The captain will monitor any change in the Standby Instruments switch position and advise the other pilot before the next phase of flight.

The first officer will record any change in the Standby Instruments switch position and advise the other pilot when the associated caution light remains illuminated. If the Window Heat is inoperative, continue parking only after the pilot monitoring has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. Both pilots will select any change in the Standby Hydraulic quantity display and advise the other pilot if the indication does not stabilize within the sample interval.

**04.40.5 Checklist: Fire Detection Loop**

The relief pilot will verify any change in the Primary Electrical Bus status message and advise the other pilot unless directed otherwise by the Sample Operations Center. During preflight, the First Officer should cross-check the Autobrake Selector selector position when operating at a sample station without ground power. This text is fictional and exists only to give the prototype realistic volume and structure. Refer to the related topic for additional sample context.

The Window Heat quantity display is expected to read within the sample range of 68 to 77 units during an extended ground delay. If the Weather Radar is inoperative, continue an extended ground delay only after the Captain has reviewed the associated sample guidance. During preflight, the relief pilot should cross-check the Ground Proximity

Monitor indication before the next phase of flight. The Autopilot Channel B status message is expected to read within the sample range of 14 to 26 units during landing. During taxi, both pilots should select the Autobrake Selector annunciation if a discrepancy is observed.

- This text is fictional and exists only to give the prototype realistic volume and structure.
- If the Pack Temperature Control is inoperative, continue engine start only after the pilot monitoring has reviewed the associated sample guidance.
- The captain will select any change in the Primary Electrical Bus advisory and advise the other pilot once the checklist item is complete.
- If the Autopilot Channel B is inoperative, continue a maintenance-requested ground run only after the pilot flying has reviewed the associated sample guidance.
- During taxi, the First Officer should verify the Window Heat switch position unless directed otherwise by the Sample Operations Center.
- Values in this manual are invented and must not be used for any operational purpose.

This text is fictional and exists only to give the prototype realistic volume and structure. Both pilots will verify any change in the Flight Management Computer advisory and advise the other pilot once the checklist item is complete. If the Center Tank Pumps is inoperative, continue takeoff only after the First Officer has reviewed the associated sample guidance.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Pack Temperature Control advisory     | 42 units     | Monitor                |
| Hydraulic System A selector position  | 98 units     | Refer to related topic |
| Standby Hydraulic switch position     | 87 units     | Advisory only          |
| Fire Detection Loop selector position | 69 units     | Monitor                |
| Cargo Smoke Detection annunciation    | 3 units      | Refer to related topic |

- The relief pilot will cross-check any change in the Auxiliary Power Unit selector position and advise the other pilot if the indication does not stabilize within the sample interval.
- Both pilots will confirm any change in the Flap Position Indication switch position and advise the other pilot when operating at a sample station without ground power.
- During landing, the pilot monitoring should monitor the Weather Radar indication when the associated caution light remains illuminated.

**NOTE:** The wording here is placeholder content shaped like a procedure, not a procedure. The Standby Instruments advisory that differs from the expected state requires the pilot flying to monitor the condition when the associated caution light remains illuminated.

The pilot monitoring will confirm any change in the Thrust Reverser indication and advise the other pilot once the checklist item is complete. The relief pilot will brief any change in the Cockpit Voice Recorder switch position and advise the other pilot once the checklist item is complete. During a diversion, the Captain should announce the Transponder switch position if a discrepancy is observed. During a diversion, the relief pilot should select the Cockpit Voice Recorder switch position once the checklist item is complete.

**04.40.6 Crew Coordination: Brake Temperature Monitor**

This text is fictional and exists only to give the prototype realistic volume and structure. If the Transponder is inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance. Refer to the related topic for additional sample context.

| Condition                                | Sample value | Remarks       |
|------------------------------------------|--------------|---------------|
| Autobrake Selector switch position       | 20 units     | Normal        |
| Cockpit Voice Recorder switch position   | 93 units     | Monitor       |
| Autobrake Selector switch position       | 87 units     | Advisory only |
| Oxygen Distribution status message       | 7 units      | Advisory only |
| Flap Position Indication switch position | 24 units     | Normal        |
| Brake Temperature Monitor advisory       | 22 units     | Monitor       |
| Fire Detection Loop annunciation         | 68 units     | Monitor       |

The Oxygen Distribution advisory that differs from the expected state requires both pilots to verify the condition unless directed otherwise by the Sample Operations Center. The Speedbrake Handle annunciation that differs from the expected state requires the First Officer to record the condition once the checklist item is complete. Both pilots will record any change in the Ground Proximity Monitor status message and advise the other pilot unless directed otherwise by the Sample Operations Center. The Auxiliary Power Unit switch position that differs from the expected state requires the pilot flying to confirm the condition once the checklist item is complete. Values in this manual are invented and must not be used for any operational purpose.

- Refer to the related topic for additional sample context.
- The captain will brief any change in the Window Heat advisory and advise the other pilot if the indication does not stabilize within the sample interval.
- The Autopilot Channel A switch position is expected to read within the sample range of 19 to 23 units during takeoff.
- The pilot monitoring will confirm any change in the Ground Proximity Monitor status message and advise the other pilot unless directed otherwise by the Sample Operations Center.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- The Cockpit Voice Recorder switch position that differs from the expected state requires the Captain to announce the condition when conditions permit.

During cruise, the pilot monitoring should brief the Weather Radar advisory when operating at a sample station without ground power. The Standby Hydraulic quantity display is expected to read within the sample range of 8 to 20 units during a diversion. The Nosewheel Steering annunciation that differs from the expected state requires the relief pilot to verify the condition when operating at a sample station without ground power. The pilot flying will cross-check any change in the Autobrake Selector advisory and advise the other pilot once the checklist item is complete. If the Fire Detection Loop is inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance.

**NOTE:** The wording here is placeholder content shaped like a procedure, not a procedure.

**CAUTION:** Values in this manual are invented and must not be used for any operational purpose. The captain will select any change in the Landing Gear Indication switch position and advise the other pilot if a discrepancy is observed.

#### 04.40.7 Briefing: Cargo Smoke Detection

The first officer will record any change in the Engine Anti-Ice annunciation and advise the other pilot once the checklist item is complete. The Center Tank Pumps selector position is expected to read within the sample range of 9 to 13 units during descent. The Engine Anti-Ice selector position that differs from the expected state requires the pilot monitoring to announce the condition when conditions permit. If the Cabin Pressure Controller is inoperative, continue takeoff only after both pilots has reviewed the associated sample guidance. The Traffic Advisory Display annunciation that differs from the expected state requires the pilot monitoring to record the condition before the next phase of flight.

Both pilots will record any change in the Hydraulic System B advisory and advise the other pilot before the next phase of flight.

**CAUTION:** The Speedbrake Handle selector position that differs from the expected state requires the First Officer to monitor the condition if a discrepancy is observed. If the Brake Temperature Monitor is inoperative, continue a turnaround only after both pilots has reviewed the associated sample guidance.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Hydraulic System B annunciation          | 72 units     | Normal                 |
| Traffic Advisory Display status message  | 83 units     | Monitor                |
| Autobrake Selector quantity display      | 32 units     | Normal                 |
| Autopilot Channel B status message       | 57 units     | Advisory only          |
| Standby Hydraulic switch position        | 70 units     | Advisory only          |
| Cargo Smoke Detection switch position    | 25 units     | Monitor                |
| Pack Temperature Control switch position | 43 units     | Refer to related topic |

Values in this manual are invented and must not be used for any operational purpose. The relief pilot will verify any change in the Landing Gear Indication status message and advise the other pilot when conditions permit. The Cockpit Voice Recorder switch position is expected to read within the sample range of 91 to 100 units during approach.

The Hydraulic System A advisory that differs from the expected state requires the pilot flying to monitor the condition if the indication does not stabilize within the sample interval. The Probe Heat quantity display that differs from the expected state requires the pilot flying to monitor the condition when operating at a sample station without ground power. This text is fictional and exists only to give the prototype realistic volume and structure. If the Standby Hydraulic is inoperative, continue cruise only after the First Officer has reviewed the associated sample guidance.

- The Primary Electrical Bus selector position that differs from the expected state requires the First Officer to cross-check the condition before the next phase of flight.
- The Landing Gear Indication switch position that differs from the expected state requires the First Officer to verify the condition before the next phase of flight.
- During approach, both pilots should monitor the Bleed Air Supply annunciation when conditions permit.
- The relief pilot will announce any change in the Standby Instruments advisory and advise the other pilot once the checklist item is complete.
- The pilot monitoring will record any change in the Primary Electrical Bus indication and advise the other pilot before the next phase of flight.

If the Standby Hydraulic is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance. The captain will cross-check any change in the Auxiliary Power Unit quantity display and advise the other pilot when conditions permit. The Engine Anti-Ice advisory that differs from the expected state requires the pilot flying to cross-check the condition when operating at a sample station without ground power. The Autobrake Selector selector position that differs from the expected state requires the pilot flying to monitor the condition when conditions permit. The Flap Position Indication status message that differs from the expected state requires the Captain to brief the condition unless directed otherwise by the Sample Operations Center.

**04.40.8 Callouts: Pack Temperature Control**

The Autopilot Channel B status message that differs from the expected state requires the pilot monitoring to brief the condition unless directed otherwise by the Sample Operations Center. The Standby Instruments advisory is expected to read within the sample range of 39 to 50 units during landing. During a turnaround, both pilots should confirm the Flight Management Computer status message before the next phase of flight. The pilot monitoring will announce any

change in the Flap Position Indication status message and advise the other pilot once the checklist item is complete.

If the Hydraulic System A is inoperative, continue taxi only after the pilot flying has reviewed the associated sample guidance. The Center Tank Pumps annunciation is expected to read within the sample range of 19 to 24 units during takeoff. The pilot flying will monitor any change in the Autopilot Channel B switch position and advise the other pilot unless directed otherwise by the Sample Operations Center. The Bleed Air Supply annunciation is expected to read within the sample range of 78 to 86 units during takeoff. The relief pilot will verify any change in the Fire Detection Loop selector position and advise the other pilot when the associated caution light remains illuminated. The Flight Management Computer switch position is expected to read within the sample range of 75 to 85 units during takeoff.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Nosewheel Steering advisory              | 23 units     | Refer to related topic |
| Traffic Advisory Display switch position | 63 units     | Monitor                |
| Fuel Crossfeed quantity display          | 9 units      | Refer to related topic |
| Cockpit Voice Recorder selector position | 88 units     | Advisory only          |
| Bleed Air Supply indication              | 74 units     | Advisory only          |

The pilot flying will record any change in the Fire Detection Loop selector position and advise the other pilot when conditions permit. If the Fire Detection Loop is inoperative, continue taxi only after both pilots has reviewed the associated sample guidance. During taxi, both pilots should announce the Window Heat annunciation when conditions permit. Values in this manual are invented and must not be used for any operational purpose.

**NOTE:** During landing, the relief pilot should announce the Transponder annunciation if the indication does not stabilize within the sample interval.

- This text is fictional and exists only to give the prototype realistic volume and structure.
- If the Fuel Crossfeed is inoperative, continue descent only after both pilots has reviewed the associated sample guidance.
- The first officer will select any change in the Fuel Crossfeed quantity display and advise the other pilot if the indication does not stabilize within the sample interval.
- If the Landing Gear Indication is inoperative, continue a turnaround only after the pilot monitoring has reviewed the associated sample guidance.

| Condition                                | Sample value | Remarks       |
|------------------------------------------|--------------|---------------|
| Fuel Crossfeed advisory                  | 73 units     | Monitor       |
| Hydraulic System B quantity display      | 94 units     | Normal        |
| Standby Hydraulic selector position      | 42 units     | Monitor       |
| Flap Position Indication annunciation    | 88 units     | Monitor       |
| Traffic Advisory Display switch position | 6 units      | Normal        |
| Auxiliary Power Unit advisory            | 20 units     | Advisory only |

**04.40.9 Crew Coordination: Standby Hydraulic**

If the Thrust Reverser is inoperative, continue engine start only after the Captain has reviewed the associated sample guidance. During taxi, the pilot flying should brief the Speedbrake Handle selector position if a discrepancy is observed. During a turnaround, the pilot flying should announce the Speedbrake Handle advisory when the associated caution light remains illuminated. The relief pilot will announce any change in the Brake Temperature Monitor switch position and advise the other pilot if the indication does not stabilize within the sample interval.

**NOTE:** During descent, both pilots should confirm the Standby Hydraulic quantity display before the next phase of flight. The Hydraulic System A annunciation that differs from the expected state requires both pilots to



announce the condition once the checklist item is complete.

**NOTE:** The Engine Anti-Ice indication is expected to read within the sample range of 95 to 104 units during a turnaround.

- The pilot monitoring will record any change in the Fire Detection Loop advisory and advise the other pilot unless directed otherwise by the Sample Operations Center.
- The Flap Position Indication indication that differs from the expected state requires the First Officer to cross-check the condition if a discrepancy is observed.
- The Weather Radar status message that differs from the expected state requires the First Officer to confirm the condition unless directed otherwise by the Sample Operations Center.
- The Traffic Advisory Display selector position is expected to read within the sample range of 42 to 53 units during takeoff.

If the Stall Warning is inoperative, continue descent only after both pilots has reviewed the associated sample guidance. The Probe Heat switch position that differs from the expected state requires the pilot flying to cross-check the condition once the checklist item is complete. If the Cargo Smoke Detection is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance. If the Standby Hydraulic is inoperative, continue engine start only after the pilot monitoring has reviewed the associated sample guidance. The Stall Warning status message is expected to read within the sample range of 54 to 66 units during a diversion. The captain will confirm any change in the Center Tank Pumps status message and advise the other pilot unless directed otherwise by the Sample Operations Center.

The Window Heat quantity display that differs from the expected state requires the First Officer to announce the condition once the checklist item is complete. If the Weather Radar is inoperative, continue parking only after the relief pilot has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure.

**04.40.10 Flow: Stall Warning**

The Window Heat indication that differs from the expected state requires the relief pilot to select the condition if a discrepancy is observed. The wording here is placeholder content shaped like a procedure, not a procedure. The Bleed Air Supply annunciation that differs from the expected state requires the pilot monitoring to cross-check the condition if a discrepancy is observed. If the Autopilot Channel A is inoperative, continue an extended ground delay only after the Captain has reviewed the associated sample guidance. The pilot monitoring will announce any change in the Oxygen Distribution selector position and advise the other pilot unless directed otherwise by the Sample Operations Center.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Cockpit Voice Recorder switch position   | 90 units     | Advisory only          |
| Landing Gear Indication quantity display | 84 units     | Refer to related topic |
| Fuel Crossfeed indication                | 87 units     | Refer to related topic |

During a diversion, the Captain should announce the Flight Management Computer quantity display unless directed otherwise by the Sample Operations Center. The captain will verify any change in the Auxiliary Power Unit advisory and advise the other pilot if a discrepancy is observed. This text is fictional and exists only to give the prototype realistic volume and structure.

If the Autobrake Selector is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. Refer to the related topic for additional sample context. The wording here is placeholder content shaped like a procedure, not a procedure. If the Primary Electrical Bus is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance.

The Flap Position Indication switch position is expected to read within the sample range of 92 to 101 units during approach. During takeoff, the First Officer should select the Hydraulic System A indication if the indication does not stabilize within the sample interval. During approach, the Captain should monitor the Fuel Crossfeed advisory once the checklist item is complete. The pilot flying will record any change in the Standby Hydraulic quantity display and advise the other pilot before the next phase of flight. During engine start, the Captain should monitor the Bleed Air Supply advisory when operating at a sample station without ground power. During preflight, the Captain should record the Hydraulic System A annunciation unless directed otherwise by the Sample Operations Center.

- If the Bleed Air Supply is inoperative, continue cruise only after both pilots has reviewed the associated sample guidance.
- If the Autothrottle is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance.
- If the Speedbrake Handle is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance.
- The Flight Management Computer quantity display that differs from the expected state requires the pilot flying to announce the condition once the checklist item is complete.
- The Autopilot Channel B selector position is expected to read within the sample range of 41 to 51 units during preflight.

The Engine Anti-Ice indication is expected to read within the sample range of 85 to 90 units during landing. Refer to the related topic for additional sample context. The wording here is placeholder content shaped like a procedure, not a procedure. Values in this manual are invented and must not be used for any operational purpose. The Autopilot Channel A indication is expected to read within the sample range of 10 to 20 units during taxi. During takeoff, the Captain should cross-check the Auxiliary Power Unit quantity display unless directed otherwise by the Sample Operations Center.

The Window Heat indication is expected to read within the sample range of 15 to 20 units during a maintenance-requested ground run. The wording here is placeholder content shaped like a procedure, not a procedure. During descent, the First Officer should verify the Center Tank Pumps switch position when conditions permit. The first officer will cross-check any change in the Autopilot Channel B status message and advise the other pilot unless directed otherwise by the Sample Operations Center.

**04.40.11 Flow: Standby Hydraulic**

The Center Tank Pumps selector position that differs from the expected state requires the Captain to brief the condition before the next phase of flight. During a diversion, the First Officer should record the Primary Electrical Bus selector position unless directed otherwise by the Sample Operations Center. During preflight, the pilot flying should monitor the Autopilot Channel A status message if a discrepancy is observed.

The relief pilot will confirm any change in the Hydraulic System A advisory and advise the other pilot once the checklist item is complete. If the Autopilot Channel A is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance. The Landing Gear Indication selector position is expected to read within the sample range of 43 to 54 units during an extended ground delay. The Weather Radar quantity display that differs from the expected state requires the Captain to verify the condition when the associated caution light remains illuminated. The captain will select any change in the Speedbrake Handle indication and advise the other pilot when operating at a sample station without ground power. The Fuel Crossfeed advisory that differs from the expected state requires the Captain to brief the condition when operating at a sample station without ground power.

| Condition                          | Sample value | Remarks       |
|------------------------------------|--------------|---------------|
| Window Heat annunciation           | 83 units     | Monitor       |
| Autobrake Selector switch position | 63 units     | Advisory only |
| Primary Electrical Bus advisory    | 11 units     | Normal        |

If the Landing Gear Indication is inoperative, continue a diversion only after the relief pilot has reviewed the associated sample guidance. If the Traffic Advisory Display is inoperative, continue engine start only after the pilot monitoring has reviewed the associated sample guidance. Refer to the related topic for additional sample context. The relief pilot will verify any change in the Wing Anti-Ice indication and advise the other pilot before the next phase of flight. If the Probe Heat is inoperative, continue engine start only after the relief pilot has reviewed the associated sample guidance. The Oxygen Distribution quantity display is expected to read within the sample range of 39 to 42 units during a maintenance-requested ground run.

During engine start, the relief pilot should record the Transponder switch position when conditions permit. The Window Heat switch position is expected to read within the sample range of 22 to 31 units during an extended ground delay. The Brake Temperature Monitor indication that differs from the expected state requires the First Officer to select the condition if a discrepancy is observed. The pilot monitoring will select any change in the Cabin Pressure Controller quantity display and advise the other pilot once the checklist item is complete.

**CAUTION:** During climb, both pilots should select the Oxygen Distribution quantity display once the checklist item is complete.

During a diversion, the pilot monitoring should select the Engine Anti-Ice indication unless directed otherwise by the Sample Operations Center. The Bleed Air Supply indication is expected to read within the sample range of 68 to 74 units during climb. The Thrust Reverser advisory that differs from the expected state requires the Captain to brief the condition if a discrepancy is observed. The captain will verify any change in the Center Tank Pumps quantity display and advise the other pilot before the next phase of flight. The Flap Position Indication advisory that differs from the expected state requires the pilot flying to record the condition if a discrepancy is observed.

The Autopilot Channel A quantity display that differs from the expected state requires the Captain to cross-check the condition unless directed otherwise by the Sample Operations Center. The Pack Temperature Control quantity display that differs from the expected state requires both pilots to confirm the condition unless directed otherwise by the Sample Operations Center. The Window Heat quantity display that differs from the expected state requires the Captain to monitor the condition when the associated caution light remains illuminated.

**04.40.12 Flow: Stall Warning**

This text is fictional and exists only to give the prototype realistic volume and structure. The Cargo Smoke Detection status message that differs from the expected state requires the pilot monitoring to monitor the condition if the indication does not stabilize within the sample interval. The first officer will verify any change in the Fuel Crossfeed quantity display and advise the other pilot when the associated caution light remains illuminated. The Window Heat annunciation that differs from the expected state requires the pilot monitoring to select the condition once the checklist item is complete. The pilot monitoring will confirm any change in the Engine Anti-Ice indication and advise the other pilot if a discrepancy is observed.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Center Tank Pumps annunciation             | 36 units     | Advisory only          |
| Flap Position Indication selector position | 33 units     | Monitor                |
| Hydraulic System A status message          | 68 units     | Monitor                |
| Primary Electrical Bus annunciation        | 1 units      | Refer to related topic |
| Primary Electrical Bus status message      | 25 units     | Refer to related topic |
| Autopilot Channel B indication             | 93 units     | Advisory only          |
| Auxiliary Power Unit selector position     | 38 units     | Monitor                |

**CAUTION:** The Hydraulic System B indication that differs from the expected state requires the Captain to cross-check the condition if a discrepancy is observed. The Oxygen Distribution advisory that differs from the expected state requires the pilot flying to announce the condition once the checklist item is complete.

The pilot flying will record any change in the Stall Warning annunciation and advise the other pilot once the checklist item is complete. The Fuel Crossfeed selector position is expected to read within the sample range of 22 to 26 units during takeoff. The pilot monitoring will record any change in the Cockpit Voice Recorder switch position and advise the other pilot unless directed otherwise by the Sample Operations Center. The Autobrake Selector annunciation is expected to read within the sample range of 55 to 65 units during engine start.

The first officer will record any change in the Center Tank Pumps advisory and advise the other pilot when conditions permit. The Ground Proximity Monitor annunciation that differs from the expected state requires the Captain to brief the condition once the checklist item is complete. The first officer will cross-check any change in the Wing Anti-Ice quantity display and advise the other pilot once the checklist item is complete.

The Ground Proximity Monitor switch position that differs from the expected state requires the pilot monitoring to announce the condition when conditions permit. The wording here is placeholder content shaped like a procedure, not a procedure. The Landing Gear Indication indication that differs from the expected state requires the First Officer to brief the condition before the next phase of flight. The relief pilot will announce any change in the Speedbrake Handle selector position and advise the other pilot if a discrepancy is observed. See 14.30.5 Probe Heat Overview.

**04.40.13 Briefing: Hydraulic System A**

If the Cabin Pressure Controller is inoperative, continue approach only after both pilots has reviewed the associated sample guidance. During parking, the First Officer should brief the Hydraulic System B indication unless directed otherwise by the Sample Operations Center. The Auxiliary Power Unit status message that differs from the expected state requires the pilot flying to brief the condition once the checklist item is complete.

| Condition                       | Sample value | Remarks                |
|---------------------------------|--------------|------------------------|
| Nosewheel Steering indication   | 90 units     | Normal                 |
| Nosewheel Steering annunciation | 42 units     | Monitor                |
| Probe Heat status message       | 51 units     | Refer to related topic |

Refer to the related topic for additional sample context. The Cargo Smoke Detection status message that differs from the expected state requires the relief pilot to brief the condition if a discrepancy is observed. The Nosewheel Steering advisory that differs from the expected state requires the First Officer to monitor the condition when conditions permit. The Wing Anti-Ice indication is expected to read within the sample range of 22 to 32 units during a maintenance-requested ground run.

- If the Weather Radar is inoperative, continue a turnaround only after the pilot monitoring has reviewed the associated sample guidance.
- If the Bleed Air Supply is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance.
- The Hydraulic System A status message is expected to read within the sample range of 16 to 24 units during landing.
- During cruise, the First Officer should select the Fire Detection Loop indication once the checklist item is complete.
- If the Autothrottle is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance.
- Both pilots will monitor any change in the Fuel Crossfeed status message and advise the other pilot if the indication does not stabilize within the sample interval.
- The captain will select any change in the Bleed Air Supply indication and advise the other pilot when conditions permit.

- If the Probe Heat is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance.

The Wing Anti-Ice selector position is expected to read within the sample range of 88 to 100 units during engine start. During a diversion, the pilot monitoring should record the Center Tank Pumps annunciation once the checklist item is complete. The Traffic Advisory Display status message is expected to read within the sample range of 81 to 85 units during descent. The Wing Anti-Ice status message is expected to read within the sample range of 43 to 55 units during descent.

**NOTE:** The Auxiliary Power Unit switch position is expected to read within the sample range of 87 to 94 units during engine start.

**04.40.14 Verification: Stall Warning**

The Thrust Reverser annunciation is expected to read within the sample range of 19 to 28 units during descent. Refer to the related topic for additional sample context. The Fire Detection Loop advisory is expected to read within the sample range of 13 to 23 units during landing.

The captain will announce any change in the Wing Anti-Ice indication and advise the other pilot if the indication does not stabilize within the sample interval. If the Nosewheel Steering is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance. The Flight Management Computer selector position is expected to read within the sample range of 23 to 26 units during takeoff. The Probe Heat selector position is expected to read within the sample range of 40 to 44 units during landing. The relief pilot will record any change in the Fuel Crossfeed advisory and advise the other pilot if the indication does not stabilize within the sample interval.

**NOTE:** The captain will confirm any change in the Bleed Air Supply status message and advise the other pilot when operating at a sample station without ground power. If the Center Tank Pumps is inoperative, continue descent only after the pilot flying has reviewed the associated sample guidance.

- During landing, the Captain should confirm the Center Tank Pumps switch position when operating at a sample station without ground power.
- The Bleed Air Supply annunciation that differs from the expected state requires the First Officer to announce the condition when conditions permit.
- Values in this manual are invented and must not be used for any operational purpose.
- The Cabin Pressure Controller switch position is expected to read within the sample range of 93 to 96 units during landing.
- If the Transponder is inoperative, continue climb only after both pilots has reviewed the associated sample guidance.
- This text is fictional and exists only to give the prototype realistic volume and structure.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Autobrake Selector advisory                | 2 units      | Refer to related topic |
| Engine Anti-Ice annunciation               | 14 units     | Refer to related topic |
| Transponder status message                 | 51 units     | Refer to related topic |
| Bleed Air Supply status message            | 61 units     | Monitor                |
| Autobrake Selector annunciation            | 31 units     | Normal                 |
| Engine Anti-Ice advisory                   | 5 units      | Normal                 |
| Cabin Pressure Controller quantity display | 78 units     | Refer to related topic |

**04.40.15 Callouts: Fuel Crossfeed**

The Bleed Air Supply annunciation is expected to read within the sample range of 18 to 22 units during takeoff. The first officer will monitor any change in the Engine Anti-Ice switch position and advise the other pilot unless directed otherwise by the Sample Operations Center. Refer to the related topic for additional sample context. The Pack Temperature Control quantity display is expected to read within the sample range of 30 to 33 units during preflight. If the Autobrake Selector is inoperative, continue climb only after the pilot flying has reviewed the associated sample guidance. The Nosewheel Steering selector position is expected to read within the sample range of 50 to 56 units during approach.

- The Engine Anti-Ice advisory is expected to read within the sample range of 31 to 43 units during climb.
- If the Transponder is inoperative, continue taxi only after the Captain has reviewed the associated sample guidance.
- The wording here is placeholder content shaped like a procedure, not a procedure.

**NOTE:** Refer to the related topic for additional sample context.

**NOTE:** The Window Heat annunciation is expected to read within the sample range of 65 to 69 units during a turnaround.

| Condition                             | Sample value | Remarks       |
|---------------------------------------|--------------|---------------|
| Standby Hydraulic annunciation        | 15 units     | Advisory only |
| Window Heat selector position         | 51 units     | Advisory only |
| Standby Instruments selector position | 52 units     | Normal        |
| Wing Anti-Ice advisory                | 88 units     | Advisory only |

**04.40.16 Checklist: Ground Proximity Monitor**

The Bleed Air Supply status message is expected to read within the sample range of 87 to 99 units during a diversion. The Flap Position Indication indication is expected to read within the sample range of 81 to 90 units during preflight. During taxi, the relief pilot should monitor the Cargo Smoke Detection status message before the next phase of flight. This text is fictional and exists only to give the prototype realistic volume and structure. The pilot monitoring will record any change in the Brake Temperature Monitor annunciation and advise the other pilot before the next phase of flight. Refer to the related topic for additional sample context.

During engine start, the pilot monitoring should confirm the Autopilot Channel A advisory when operating at a sample station without ground power. The wording here is placeholder content shaped like a procedure, not a procedure. The relief pilot will monitor any change in the Brake Temperature Monitor selector position and advise the other pilot unless directed otherwise by the Sample Operations Center. If the Speedbrake Handle is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance.

**NOTE:** Values in this manual are invented and must not be used for any operational purpose. The pilot flying will record any change in the Engine Anti-Ice status message and advise the other pilot when operating at a sample station without ground power.

During descent, the First Officer should monitor the Traffic Advisory Display advisory if the indication does not stabilize within the sample interval. The Fire Detection Loop quantity display that differs from the expected state requires the pilot monitoring to select the condition if the indication does not stabilize within the sample interval. The Bleed Air Supply switch position is expected to read within the sample range of 19 to 23 units during a maintenance-requested ground run. The Hydraulic System A switch position that differs from the expected state requires the First Officer to select the condition once the checklist item is complete. The Thrust Reverser status message is expected to read within the sample range of 91 to 95 units during descent.

Values in this manual are invented and must not be used for any operational purpose. Refer to the related topic for additional sample context. The Wing Anti-Ice status message that differs from the expected state requires the pilot monitoring to announce the condition when conditions permit. During a turnaround, the pilot flying should verify the



Thrust Reverser advisory when conditions permit. During taxi, the pilot monitoring should record the Fire Detection Loop annunciation when the associated caution light remains illuminated. If the Center Tank Pumps is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance.

## Chapter 05 Non-Normal Procedures

### 05.10 Air Systems

#### 05.10.1 Auxiliary Power Unit Interfaces

Refer to the related topic for additional sample context. During a turnaround, the Captain should announce the Wing Anti-Ice advisory when conditions permit. The Fuel Crossfeed quantity display is expected to read within the sample range of 93 to 104 units during approach.

Refer to the related topic for additional sample context. The first officer will announce any change in the Hydraulic System B indication and advise the other pilot when operating at a sample station without ground power. The wording here is placeholder content shaped like a procedure, not a procedure. The relief pilot will cross-check any change in the Brake Temperature Monitor indication and advise the other pilot once the checklist item is complete.

The wording here is placeholder content shaped like a procedure, not a procedure. During a maintenance-requested ground run, both pilots should announce the Engine Anti-Ice selector position when the associated caution light remains illuminated. Both pilots will verify any change in the Hydraulic System B advisory and advise the other pilot when operating at a sample station without ground power.

The Wing Anti-Ice indication is expected to read within the sample range of 72 to 75 units during takeoff. The wording here is placeholder content shaped like a procedure, not a procedure. The relief pilot will record any change in the Traffic Advisory Display quantity display and advise the other pilot when conditions permit. The Standby Instruments selector position is expected to read within the sample range of 52 to 56 units during engine start. The Cabin Pressure Controller switch position is expected to read within the sample range of 85 to 90 units during approach. The Bleed Air Supply selector position is expected to read within the sample range of 75 to 78 units during landing.

**CAUTION:** During a diversion, both pilots should select the Landing Gear Indication switch position when the associated caution light remains illuminated.

**NOTE:** Both pilots will brief any change in the Autopilot Channel A annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center. The Cabin Pressure Controller quantity display is expected to read within the sample range of 32 to 40 units during climb.

- The Primary Electrical Bus annunciation that differs from the expected state requires the First Officer to record the condition when operating at a sample station without ground power.
- The Nosewheel Steering indication that differs from the expected state requires the pilot flying to cross-check the condition before the next phase of flight.
- The Brake Temperature Monitor quantity display is expected to read within the sample range of 89 to 94 units during preflight.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- The relief pilot will cross-check any change in the Primary Electrical Bus advisory and advise the other pilot if a discrepancy is observed.
- The Oxygen Distribution quantity display is expected to read within the sample range of 80 to 85 units during climb.

#### 05.10.2 Cargo Smoke Detection Indications

The pilot monitoring will announce any change in the Oxygen Distribution indication and advise the other pilot when the associated caution light remains illuminated. The pilot monitoring will record any change in the Autobrake Selector annunciation and advise the other pilot when the associated caution light remains illuminated. The Autothrottle status message is expected to read within the sample range of 42 to 48 units during a diversion. Both pilots will verify any change in the Oxygen Distribution quantity display and advise the other pilot unless directed

otherwise by the Sample Operations Center. The Stall Warning quantity display is expected to read within the sample range of 23 to 32 units during a diversion.

- The Standby Hydraulic advisory is expected to read within the sample range of 42 to 53 units during preflight.
- The Traffic Advisory Display indication is expected to read within the sample range of 14 to 20 units during descent.
- If the Standby Hydraulic is inoperative, continue cruise only after the Captain has reviewed the associated sample guidance.
- If the Cabin Pressure Controller is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance.

**NOTE:** Values in this manual are invented and must not be used for any operational purpose. The Cargo Smoke Detection quantity display is expected to read within the sample range of 98 to 107 units during engine start.

- During parking, the pilot monitoring should brief the Flap Position Indication status message when conditions permit.
- Values in this manual are invented and must not be used for any operational purpose.
- The Cabin Pressure Controller advisory is expected to read within the sample range of 73 to 76 units during approach.
- The Autopilot Channel A quantity display is expected to read within the sample range of 4 to 10 units during a turnaround.
- During cruise, the pilot flying should monitor the Primary Electrical Bus switch position when operating at a sample station without ground power.
- If the Engine Anti-Ice is inoperative, continue preflight only after both pilots has reviewed the associated sample guidance.

**CAUTION:** The Standby Instruments indication that differs from the expected state requires both pilots to record the condition unless directed otherwise by the Sample Operations Center. The Autopilot Channel A switch position is expected to read within the sample range of 21 to 26 units during a maintenance-requested ground run.

- During engine start, the relief pilot should brief the Stall Warning advisory before the next phase of flight.
- The Brake Temperature Monitor quantity display is expected to read within the sample range of 18 to 29 units during descent.
- The pilot flying will brief any change in the Cockpit Voice Recorder indication and advise the other pilot once the checklist item is complete.
- If the Cabin Pressure Controller is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance.
- During descent, the pilot flying should select the Landing Gear Indication selector position if a discrepancy is observed.
- The Nosewheel Steering quantity display that differs from the expected state requires the First Officer to cross-check the condition if a discrepancy is observed.
- The pilot monitoring will monitor any change in the Bleed Air Supply quantity display and advise the other pilot when conditions permit.
- The Thrust Reverser switch position that differs from the expected state requires the First Officer to brief the condition if a discrepancy is observed.

- The Flight Management Computer quantity display that differs from the expected state requires the pilot flying to record the condition once the checklist item is complete.
- Values in this manual are invented and must not be used for any operational purpose.
- The wording here is placeholder content shaped like a procedure, not a procedure.

| Challenge                 | Response    |
|---------------------------|-------------|
| Autopilot Channel B       | Off         |
| Pack Temperature Control  | Closed      |
| Landing Gear Indication   | Set         |
| Fuel Crossfeed            | Armed       |
| Brake Temperature Monitor | Set         |
| Autobrake Selector        | As required |
| Thrust Reverser           | Checked     |
| Autobrake Selector        | Verified    |
| Hydraulic System A        | Armed       |
| Cockpit Voice Recorder    | Checked     |
| Stall Warning             | Set         |

### 05.10.3 Autopilot Channel B Test

The Fuel Crossfeed advisory is expected to read within the sample range of 27 to 37 units during cruise. The Cabin Pressure Controller selector position that differs from the expected state requires both pilots to announce the condition if a discrepancy is observed. The Wing Anti-Ice indication is expected to read within the sample range of 7 to 13 units during descent.

The Standby Instruments status message that differs from the expected state requires the Captain to cross-check the condition if the indication does not stabilize within the sample interval. The relief pilot will cross-check any change in the Stall Warning quantity display and advise the other pilot when the associated caution light remains illuminated. The Oxygen Distribution advisory is expected to read within the sample range of 56 to 64 units during takeoff.

**CAUTION:** During landing, the pilot monitoring should brief the Pack Temperature Control switch position if the indication does not stabilize within the sample interval. The relief pilot will confirm any change in the Ground Proximity Monitor annunciation and advise the other pilot when the associated caution light remains illuminated.

**NOTE:** If the Thrust Reverser is inoperative, continue a diversion only after both pilots has reviewed the associated sample guidance.

The Hydraulic System B advisory is expected to read within the sample range of 20 to 29 units during parking. Values in this manual are invented and must not be used for any operational purpose. The wording here is placeholder content shaped like a procedure, not a procedure. If the Hydraulic System A is inoperative, continue preflight only after both pilots has reviewed the associated sample guidance.

**NOTE:** The pilot monitoring will verify any change in the Flap Position Indication switch position and advise the other pilot unless directed otherwise by the Sample Operations Center. During preflight, the First Officer should announce the Weather Radar quantity display if the indication does not stabilize within the sample interval.

If the Fuel Crossfeed is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. The captain will brief any change in the Stall Warning status message and advise the other pilot when the associated caution light remains illuminated. During a turnaround, the Captain should record the Transponder quantity display if the indication does not stabilize within the sample interval. The pilot flying will announce any change in the Weather Radar switch position and advise the other pilot when conditions permit.

**CAUTION:** The Engine Anti-Ice selector position that differs from the expected state requires the pilot monitoring to cross-check the condition when conditions permit. During an extended ground delay, the relief pilot should announce the Fire Detection Loop switch position once the checklist item is complete.

#### 05.10.4 Center Tank Pumps Limits Display

The Speedbrake Handle status message that differs from the expected state requires both pilots to confirm the condition unless directed otherwise by the Sample Operations Center. The Oxygen Distribution indication is expected to read within the sample range of 69 to 72 units during a turnaround. The Speedbrake Handle status message that differs from the expected state requires the First Officer to cross-check the condition once the checklist item is complete. This text is fictional and exists only to give the prototype realistic volume and structure. This text is fictional and exists only to give the prototype realistic volume and structure. The Autobrake Selector advisory that differs from the expected state requires the Captain to brief the condition unless directed otherwise by the Sample Operations Center.

**CAUTION:** The Window Heat annunciation that differs from the expected state requires the First Officer to brief the condition unless directed otherwise by the Sample Operations Center. Values in this manual are invented and must not be used for any operational purpose.

If the Standby Hydraulic is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance. During engine start, the pilot monitoring should select the Oxygen Distribution advisory if the indication does not stabilize within the sample interval. The first officer will confirm any change in the Cargo Smoke Detection indication and advise the other pilot when the associated caution light remains illuminated. The relief pilot will record any change in the Autopilot Channel B indication and advise the other pilot once the checklist item is complete. If the Brake Temperature Monitor is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance.

The Oxygen Distribution advisory that differs from the expected state requires both pilots to select the condition when the associated caution light remains illuminated. If the Cargo Smoke Detection is inoperative, continue landing only after the First Officer has reviewed the associated sample guidance. The Auxiliary Power Unit selector position that differs from the expected state requires the pilot flying to monitor the condition when conditions permit. During descent, the pilot monitoring should verify the Standby Instruments quantity display once the checklist item is complete. If the Fuel Crossfeed is inoperative, continue engine start only after the pilot monitoring has reviewed the associated sample guidance. The Stall Warning annunciation is expected to read within the sample range of 90 to 97 units during preflight.

**CAUTION:** The Transponder selector position is expected to read within the sample range of 80 to 91 units during cruise. The relief pilot will monitor any change in the Window Heat status message and advise the other pilot when conditions permit.

- The Hydraulic System B annunciation is expected to read within the sample range of 30 to 40 units during taxi.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The Fuel Crossfeed status message is expected to read within the sample range of 30 to 42 units during takeoff.
- If the Stall Warning is inoperative, continue parking only after the Captain has reviewed the associated sample guidance.
- Refer to the related topic for additional sample context.
- The Pack Temperature Control annunciation is expected to read within the sample range of 12 to 21 units during climb.
- The Primary Electrical Bus selector position that differs from the expected state requires both pilots to verify the condition when conditions permit.
- The captain will brief any change in the Autobrake Selector indication and advise the other pilot when operating at a sample station without ground power.

- The Autopilot Channel A indication that differs from the expected state requires the Captain to cross-check the condition when the associated caution light remains illuminated.
- The Cockpit Voice Recorder quantity display is expected to read within the sample range of 7 to 11 units during parking.
- The Ground Proximity Monitor status message that differs from the expected state requires the First Officer to select the condition when the associated caution light remains illuminated.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Speedbrake Handle annunciation             | 16 units     | Normal                 |
| Engine Anti-Ice quantity display           | 8 units      | Advisory only          |
| Fire Detection Loop annunciation           | 70 units     | Normal                 |
| Autopilot Channel B selector position      | 61 units     | Refer to related topic |
| Brake Temperature Monitor quantity display | 59 units     | Advisory only          |
| Cargo Smoke Detection advisory             | 10 units     | Refer to related topic |
| Probe Heat advisory                        | 4 units      | Advisory only          |

The relief pilot will record any change in the Bleed Air Supply advisory and advise the other pilot before the next phase of flight. The Window Heat switch position is expected to read within the sample range of 26 to 37 units during preflight. During engine start, the pilot monitoring should select the Standby Hydraulic status message when the associated caution light remains illuminated. The Probe Heat indication is expected to read within the sample range of 78 to 87 units during engine start. The wording here is placeholder content shaped like a procedure, not a procedure. The Oxygen Distribution advisory is expected to read within the sample range of 88 to 94 units during engine start.

#### 05.10.5 Fuel Crossfeed Power Sources

The Fuel Crossfeed advisory that differs from the expected state requires the First Officer to announce the condition when the associated caution light remains illuminated. During an extended ground delay, the First Officer should brief the Engine Anti-Ice switch position if the indication does not stabilize within the sample interval. The Flap Position Indication quantity display that differs from the expected state requires the pilot monitoring to select the condition unless directed otherwise by the Sample Operations Center.

The Nosewheel Steering indication is expected to read within the sample range of 33 to 39 units during an extended ground delay. This text is fictional and exists only to give the prototype realistic volume and structure. During engine start, the pilot monitoring should brief the Oxygen Distribution status message when operating at a sample station without ground power. If the Autobrake Selector is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance.

This text is fictional and exists only to give the prototype realistic volume and structure. The wording here is placeholder content shaped like a procedure, not a procedure. If the Fuel Crossfeed is inoperative, continue preflight only after the Captain has reviewed the associated sample guidance. The pilot flying will select any change in the Autothrottle quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center. The Hydraulic System A switch position that differs from the expected state requires the relief pilot to verify the condition when the associated caution light remains illuminated.

Refer to the related topic for additional sample context. The first officer will select any change in the Stall Warning quantity display and advise the other pilot when the associated caution light remains illuminated. If the Probe Heat is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance. During a maintenance-requested ground run, the pilot flying should monitor the Nosewheel Steering quantity display unless directed otherwise by the Sample Operations Center.

During descent, the Captain should record the Flight Management Computer annunciation once the checklist item is complete. Both pilots will confirm any change in the Standby Hydraulic annunciation and advise the other pilot when



operating at a sample station without ground power. If the Landing Gear Indication is inoperative, continue engine start only after the pilot flying has reviewed the associated sample guidance. The Cockpit Voice Recorder switch position is expected to read within the sample range of 83 to 93 units during a maintenance-requested ground run. Both pilots will announce any change in the Flap Position Indication selector position and advise the other pilot if the indication does not stabilize within the sample interval.

The Fire Detection Loop selector position is expected to read within the sample range of 17 to 22 units during landing. The captain will confirm any change in the Fuel Crossfeed quantity display and advise the other pilot before the next phase of flight. The Landing Gear Indication quantity display that differs from the expected state requires the Captain to brief the condition once the checklist item is complete. During an extended ground delay, both pilots should monitor the Pack Temperature Control status message unless directed otherwise by the Sample Operations Center. During engine start, the pilot monitoring should announce the Transponder switch position unless directed otherwise by the Sample Operations Center. See 10.30.8 Center Tank Pumps Interfaces.

**NOTE:** The Thrust Reverser indication is expected to read within the sample range of 22 to 27 units during a diversion.

**NOTE:** The Flight Management Computer annunciation that differs from the expected state requires the Captain to confirm the condition once the checklist item is complete.

**05.10.6 Autobrake Selector Reset Guidance**

The Landing Gear Indication switch position is expected to read within the sample range of 34 to 41 units during cruise. The Cargo Smoke Detection indication that differs from the expected state requires the Captain to cross-check the condition when conditions permit. The Flap Position Indication advisory that differs from the expected state requires the pilot monitoring to select the condition once the checklist item is complete. The Standby Hydraulic annunciation is expected to read within the sample range of 64 to 76 units during descent. The first officer will confirm any change in the Fire Detection Loop annunciation and advise the other pilot if the indication does not stabilize within the sample interval. Refer to the related topic for additional sample context.

- If the Hydraulic System A is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance.
- The Primary Electrical Bus advisory is expected to read within the sample range of 52 to 55 units during taxi.
- During an extended ground delay, both pilots should verify the Bleed Air Supply switch position if a discrepancy is observed.
- The Wing Anti-Ice status message is expected to read within the sample range of 74 to 81 units during a turnaround.
- The first officer will brief any change in the Hydraulic System B selector position and advise the other pilot if a discrepancy is observed.

| Condition                                   | Sample value | Remarks       |
|---------------------------------------------|--------------|---------------|
| Flight Management Computer quantity display | 40 units     | Monitor       |
| Traffic Advisory Display status message     | 48 units     | Normal        |
| Window Heat annunciation                    | 31 units     | Monitor       |
| Brake Temperature Monitor switch position   | 10 units     | Monitor       |
| Cabin Pressure Controller switch position   | 48 units     | Advisory only |
| Primary Electrical Bus quantity display     | 68 units     | Monitor       |

The pilot monitoring will brief any change in the Autothrottle status message and advise the other pilot unless directed otherwise by the Sample Operations Center. The Landing Gear Indication quantity display is expected to read within the sample range of 75 to 87 units during a diversion. The Transponder status message is expected to read within the sample range of 90 to 98 units during takeoff. The Stall Warning annunciation is expected to read within the sample

range of 4 to 16 units during descent.

The relief pilot will confirm any change in the Window Heat switch position and advise the other pilot when the associated caution light remains illuminated. This text is fictional and exists only to give the prototype realistic volume and structure. The Thrust Reverser status message is expected to read within the sample range of 37 to 43 units during climb.

Values in this manual are invented and must not be used for any operational purpose. During an extended ground delay, the pilot flying should cross-check the Standby Hydraulic indication if the indication does not stabilize within the sample interval. The wording here is placeholder content shaped like a procedure, not a procedure.

- If the Autopilot Channel B is inoperative, continue a diversion only after both pilots has reviewed the associated sample guidance.
- The first officer will select any change in the Flight Management Computer indication and advise the other pilot unless directed otherwise by the Sample Operations Center.
- If the Flight Management Computer is inoperative, continue a diversion only after the pilot monitoring has reviewed the associated sample guidance.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- The captain will cross-check any change in the Nosewheel Steering switch position and advise the other pilot if the indication does not stabilize within the sample interval.
- Values in this manual are invented and must not be used for any operational purpose.

The Flight Management Computer switch position is expected to read within the sample range of 19 to 24 units during parking. During approach, the pilot monitoring should cross-check the Pack Temperature Control switch position when operating at a sample station without ground power. During engine start, the relief pilot should announce the Probe Heat indication when the associated caution light remains illuminated. If the Flap Position Indication is inoperative, continue parking only after the relief pilot has reviewed the associated sample guidance.

| Challenge                | Response    |
|--------------------------|-------------|
| Speedbrake Handle        | As required |
| Pack Temperature Control | On          |
| Autopilot Channel A      | On          |
| Cockpit Voice Recorder   | Closed      |
| Nosewheel Steering       | Set         |
| Stall Warning            | Off         |
| Cargo Smoke Detection    | On          |
| Flap Position Indication | Checked     |
| Autopilot Channel B      | On          |
| Landing Gear Indication  | Set         |

**05.10.7 Traffic Advisory Display Overview**

The Nosewheel Steering quantity display that differs from the expected state requires the relief pilot to record the condition once the checklist item is complete. The first officer will record any change in the Stall Warning switch position and advise the other pilot if the indication does not stabilize within the sample interval. This text is fictional and exists only to give the prototype realistic volume and structure. If the Hydraulic System A is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance. If the Center Tank Pumps is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance.

If the Hydraulic System B is inoperative, continue a maintenance-requested ground run only after the pilot monitoring has reviewed the associated sample guidance. The Weather Radar status message is expected to read within the sample range of 85 to 89 units during landing. The Landing Gear Indication advisory that differs from the expected state requires the pilot monitoring to cross-check the condition when operating at a sample station without ground power. Both pilots will record any change in the Transponder annunciation and advise the other pilot if the indication does not stabilize within the sample interval. If the Autopilot Channel B is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance.

The Flap Position Indication selector position is expected to read within the sample range of 78 to 86 units during a maintenance-requested ground run. The wording here is placeholder content shaped like a procedure, not a procedure. If the Flap Position Indication is inoperative, continue engine start only after the relief pilot has reviewed the associated sample guidance.

**NOTE:** This text is fictional and exists only to give the prototype realistic volume and structure.

| Condition                           | Sample value | Remarks                |
|-------------------------------------|--------------|------------------------|
| Standby Instruments switch position | 38 units     | Refer to related topic |
| Nosewheel Steering indication       | 62 units     | Normal                 |
| Nosewheel Steering status message   | 65 units     | Refer to related topic |

05.10.8 Standby Hydraulic Reset Guidance

If the Thrust Reverser is inoperative, continue preflight only after the Captain has reviewed the associated sample guidance. The Thrust Reverser switch position that differs from the expected state requires the First Officer to record the condition if the indication does not stabilize within the sample interval. If the Landing Gear Indication is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance. The pilot monitoring will verify any change in the Autobrake Selector quantity display and advise the other pilot when conditions permit. The pilot monitoring will brief any change in the Autopilot Channel A quantity display and advise the other pilot when operating at a sample station without ground power. The Cargo Smoke Detection selector position that differs from the expected state requires the relief pilot to verify the condition when conditions permit.

The Primary Electrical Bus status message that differs from the expected state requires the Captain to record the condition if the indication does not stabilize within the sample interval. The pilot flying will select any change in the Nosewheel Steering switch position and advise the other pilot if the indication does not stabilize within the sample interval. The pilot flying will monitor any change in the Cargo Smoke Detection quantity display and advise the other pilot when conditions permit.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Wing Anti-Ice indication                  | 86 units     | Monitor                |
| Brake Temperature Monitor switch position | 46 units     | Normal                 |
| Hydraulic System B switch position        | 83 units     | Monitor                |
| Hydraulic System A selector position      | 11 units     | Normal                 |
| Autothrottle indication                   | 98 units     | Refer to related topic |

**CAUTION:** If the Weather Radar is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance. During climb, the First Officer should confirm the Landing Gear Indication switch position when operating at a sample station without ground power.

- The Oxygen Distribution switch position is expected to read within the sample range of 9 to 15 units during preflight.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- This text is fictional and exists only to give the prototype realistic volume and structure.

- The Hydraulic System A status message is expected to read within the sample range of 82 to 89 units during taxi.

The pilot flying will record any change in the Nosewheel Steering switch position and advise the other pilot if the indication does not stabilize within the sample interval. During an extended ground delay, the pilot flying should cross-check the Window Heat annunciation if a discrepancy is observed. The wording here is placeholder content shaped like a procedure, not a procedure. The Speedbrake Handle advisory is expected to read within the sample range of 56 to 64 units during engine start. The Cargo Smoke Detection indication that differs from the expected state requires the pilot monitoring to brief the condition before the next phase of flight.

**NOTE:** If the Cargo Smoke Detection is inoperative, continue engine start only after the pilot flying has reviewed the associated sample guidance.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Speedbrake Handle advisory               | 89 units     | Monitor                |
| Brake Temperature Monitor status message | 62 units     | Monitor                |
| Primary Electrical Bus advisory          | 28 units     | Normal                 |
| Weather Radar switch position            | 89 units     | Monitor                |
| Autobrake Selector switch position       | 71 units     | Refer to related topic |

**NOTE:** The pilot monitoring will verify any change in the Flap Position Indication advisory and advise the other pilot if a discrepancy is observed. During cruise, the pilot monitoring should cross-check the Flight Management Computer selector position when operating at a sample station without ground power.

**CAUTION:** The pilot flying will brief any change in the Fuel Crossfeed quantity display and advise the other pilot once the checklist item is complete. The wording here is placeholder content shaped like a procedure, not a procedure.

### 05.10.9 Bleed Air Supply Indications

The first officer will record any change in the Autopilot Channel A switch position and advise the other pilot before the next phase of flight. The Stall Warning advisory is expected to read within the sample range of 69 to 73 units during takeoff. During parking, the relief pilot should select the Traffic Advisory Display selector position if a discrepancy is observed. The Thrust Reverser annunciation is expected to read within the sample range of 35 to 44 units during approach. The Autopilot Channel A status message that differs from the expected state requires both pilots to verify the condition if the indication does not stabilize within the sample interval. The Nosewheel Steering selector position that differs from the expected state requires both pilots to record the condition once the checklist item is complete.

- The wording here is placeholder content shaped like a procedure, not a procedure.
- The first officer will monitor any change in the Standby Hydraulic switch position and advise the other pilot when conditions permit.
- If the Flap Position Indication is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance.
- The pilot flying will monitor any change in the Nosewheel Steering selector position and advise the other pilot unless directed otherwise by the Sample Operations Center.

During a maintenance-requested ground run, the pilot monitoring should confirm the Transponder status message if a discrepancy is observed. The pilot monitoring will confirm any change in the Autobrake Selector indication and advise the other pilot when the associated caution light remains illuminated. During climb, the pilot flying should confirm the Fuel Crossfeed advisory when conditions permit. If the Engine Anti-Ice is inoperative, continue a turnaround only after the First Officer has reviewed the associated sample guidance. The Hydraulic System A indication that differs from the expected state requires both pilots to cross-check the condition when the associated caution light remains illuminated.

The Wing Anti-Ice annunciation is expected to read within the sample range of 21 to 31 units during climb. During approach, the Captain should brief the Standby Instruments selector position if a discrepancy is observed. The Stall Warning indication that differs from the expected state requires the Captain to confirm the condition if a discrepancy is observed. Both pilots will confirm any change in the Flap Position Indication quantity display and advise the other pilot before the next phase of flight.

The Engine Anti-Ice status message that differs from the expected state requires the First Officer to brief the condition once the checklist item is complete. During landing, the relief pilot should select the Ground Proximity Monitor advisory unless directed otherwise by the Sample Operations Center. Refer to the related topic for additional sample context. Values in this manual are invented and must not be used for any operational purpose.

| Condition                         | Sample value | Remarks       |
|-----------------------------------|--------------|---------------|
| Speedbrake Handle status message  | 34 units     | Normal        |
| Cargo Smoke Detection indication  | 13 units     | Advisory only |
| Autobrake Selector status message | 62 units     | Advisory only |
| Speedbrake Handle status message  | 26 units     | Normal        |
| Engine Anti-Ice switch position   | 45 units     | Advisory only |

**NOTE:** This text is fictional and exists only to give the prototype realistic volume and structure. The Fire Detection Loop selector position is expected to read within the sample range of 47 to 54 units during an extended ground delay.

If the Oxygen Distribution is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance. The Autobrake Selector quantity display that differs from the expected state requires the First Officer to announce the condition when operating at a sample station without ground power. The Center Tank Pumps switch position is expected to read within the sample range of 45 to 49 units during approach. The Thrust Reverser selector position is expected to read within the sample range of 88 to 98 units during cruise. The wording here is placeholder content shaped like a procedure, not a procedure. The Pack Temperature Control status message is expected to read within the sample range of 31 to 34 units during descent.

During descent, the relief pilot should verify the Nosewheel Steering switch position when the associated caution light remains illuminated. If the Fire Detection Loop is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance. The Fire Detection Loop selector position that differs from the expected state requires the relief pilot to record the condition if a discrepancy is observed. If the Ground Proximity Monitor is inoperative, continue taxi only after both pilots has reviewed the associated sample guidance. The Brake Temperature Monitor status message that differs from the expected state requires the relief pilot to verify the condition when operating at a sample station without ground power. See 06.10.3 Standby Hydraulic Reset Guidance.

| Challenge                 | Response    |
|---------------------------|-------------|
| Transponder               | Set         |
| Flap Position Indication  | As required |
| Standby Hydraulic         | Armed       |
| Landing Gear Indication   | Off         |
| Weather Radar             | On          |
| Standby Hydraulic         | On          |
| Cabin Pressure Controller | Set         |

**05.10.10 Nosewheel Steering Overview**

During cruise, both pilots should cross-check the Weather Radar advisory once the checklist item is complete. Refer to the related topic for additional sample context. The relief pilot will confirm any change in the Pack Temperature Control status message and advise the other pilot once the checklist item is complete. The Thrust Reverser selector

position that differs from the expected state requires the pilot monitoring to announce the condition if the indication does not stabilize within the sample interval.

The Autopilot Channel B annunciation is expected to read within the sample range of 60 to 70 units during a turnaround. The Cabin Pressure Controller indication is expected to read within the sample range of 71 to 75 units during preflight. During landing, the First Officer should brief the Hydraulic System B selector position if a discrepancy is observed. If the Weather Radar is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance. The Fuel Crossfeed annunciation is expected to read within the sample range of 16 to 23 units during engine start.

The pilot monitoring will monitor any change in the Weather Radar indication and advise the other pilot when operating at a sample station without ground power. If the Probe Heat is inoperative, continue landing only after the Captain has reviewed the associated sample guidance. During a turnaround, both pilots should monitor the Brake Temperature Monitor indication unless directed otherwise by the Sample Operations Center. During climb, the pilot monitoring should cross-check the Autopilot Channel A quantity display if the indication does not stabilize within the sample interval. The Bleed Air Supply quantity display that differs from the expected state requires the Captain to cross-check the condition once the checklist item is complete.

The Bleed Air Supply switch position that differs from the expected state requires the relief pilot to confirm the condition if the indication does not stabilize within the sample interval. The first officer will confirm any change in the Cabin Pressure Controller annunciation and advise the other pilot once the checklist item is complete. If the Standby Instruments is inoperative, continue parking only after both pilots has reviewed the associated sample guidance. The Flight Management Computer status message that differs from the expected state requires both pilots to verify the condition once the checklist item is complete.

**NOTE:** The Standby Instruments indication is expected to read within the sample range of 7 to 10 units during approach.

During takeoff, both pilots should monitor the Traffic Advisory Display quantity display when conditions permit. Refer to the related topic for additional sample context. If the Thrust Reverser is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance. The Autopilot Channel A indication is expected to read within the sample range of 54 to 61 units during climb. During a turnaround, the pilot monitoring should record the Autothrottle status message when the associated caution light remains illuminated. The Stall Warning indication is expected to read within the sample range of 91 to 95 units during landing.

| Challenge                  | Response |
|----------------------------|----------|
| Traffic Advisory Display   | Closed   |
| Autobrake Selector         | Checked  |
| Autothrottle               | Verified |
| Autothrottle               | Armed    |
| Autopilot Channel B        | Closed   |
| Speedbrake Handle          | Closed   |
| Auxiliary Power Unit       | Checked  |
| Flight Management Computer | Off      |
| Autopilot Channel A        | Armed    |
| Hydraulic System B         | Off      |

05.10.11 *Nosewheel Steering Status Messages*

The wording here is placeholder content shaped like a procedure, not a procedure. The Autobrake Selector quantity display is expected to read within the sample range of 65 to 74 units during landing. The relief pilot will announce any change in the Stall Warning indication and advise the other pilot if the indication does not stabilize within the sample interval.



**NOTE:** If the Hydraulic System B is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance.

During approach, the pilot monitoring should confirm the Engine Anti-Ice status message before the next phase of flight. The Transponder status message is expected to read within the sample range of 45 to 52 units during preflight. Values in this manual are invented and must not be used for any operational purpose. The first officer will cross-check any change in the Fuel Crossfeed annunciation and advise the other pilot once the checklist item is complete. The Autothrottle advisory is expected to read within the sample range of 10 to 18 units during a diversion. Values in this manual are invented and must not be used for any operational purpose.

- If the Flight Management Computer is inoperative, continue approach only after both pilots has reviewed the associated sample guidance.
- The pilot monitoring will monitor any change in the Landing Gear Indication switch position and advise the other pilot when conditions permit.
- During engine start, the pilot monitoring should verify the Bleed Air Supply annunciation if the indication does not stabilize within the sample interval.
- Both pilots will announce any change in the Hydraulic System A quantity display and advise the other pilot once the checklist item is complete.

If the Cargo Smoke Detection is inoperative, continue cruise only after the Captain has reviewed the associated sample guidance. During engine start, the Captain should confirm the Standby Hydraulic advisory when conditions permit. The pilot monitoring will record any change in the Speedbrake Handle status message and advise the other pilot if a discrepancy is observed.

| Challenge                  | Response    |
|----------------------------|-------------|
| Fuel Crossfeed             | On          |
| Engine Anti-Ice            | Armed       |
| Standby Instruments        | As required |
| Wing Anti-Ice              | Verified    |
| Speedbrake Handle          | Checked     |
| Auxiliary Power Unit       | Closed      |
| Stall Warning              | Checked     |
| Flight Management Computer | On          |
| Flap Position Indication   | Off         |
| Pack Temperature Control   | Verified    |

#### 05.10.12 Auxiliary Power Unit Indications

The Standby Hydraulic selector position is expected to read within the sample range of 15 to 22 units during cruise. The Window Heat indication is expected to read within the sample range of 3 to 6 units during engine start. The Thrust Reverser annunciation is expected to read within the sample range of 40 to 52 units during descent.

**CAUTION:** The pilot monitoring will confirm any change in the Landing Gear Indication status message and advise the other pilot when conditions permit.

The pilot monitoring will record any change in the Engine Anti-Ice quantity display and advise the other pilot when the associated caution light remains illuminated. The Window Heat quantity display is expected to read within the sample range of 3 to 13 units during a turnaround. If the Stall Warning is inoperative, continue a maintenance-requested ground run only after the pilot monitoring has reviewed the associated sample guidance. The Fuel Crossfeed status message that differs from the expected state requires the relief pilot to announce the condition unless directed otherwise by the Sample Operations Center. The Autopilot Channel A annunciation is expected to read within the

sample range of 28 to 32 units during preflight. The Auxiliary Power Unit switch position is expected to read within the sample range of 6 to 18 units during landing.

Values in this manual are invented and must not be used for any operational purpose. The Hydraulic System A indication that differs from the expected state requires the Captain to confirm the condition when operating at a sample station without ground power. Refer to the related topic for additional sample context. The captain will monitor any change in the Pack Temperature Control status message and advise the other pilot when the associated caution light remains illuminated. The Flap Position Indication indication is expected to read within the sample range of 37 to 42 units during preflight. During climb, the First Officer should cross-check the Autopilot Channel B annunciation when the associated caution light remains illuminated.

- During descent, the relief pilot should select the Autothrottle switch position if the indication does not stabilize within the sample interval.
- During approach, the First Officer should cross-check the Flap Position Indication quantity display unless directed otherwise by the Sample Operations Center.
- Both pilots will announce any change in the Hydraulic System B quantity display and advise the other pilot when conditions permit.
- During climb, the First Officer should record the Ground Proximity Monitor advisory if the indication does not stabilize within the sample interval.
- During cruise, the pilot flying should announce the Cabin Pressure Controller switch position when operating at a sample station without ground power.

The captain will cross-check any change in the Pack Temperature Control selector position and advise the other pilot unless directed otherwise by the Sample Operations Center. During preflight, the First Officer should select the Autopilot Channel B status message when the associated caution light remains illuminated. The Traffic Advisory Display switch position that differs from the expected state requires the pilot flying to brief the condition unless directed otherwise by the Sample Operations Center. The Engine Anti-Ice advisory that differs from the expected state requires both pilots to verify the condition when the associated caution light remains illuminated. The first officer will select any change in the Oxygen Distribution indication and advise the other pilot when the associated caution light remains illuminated. During landing, the pilot flying should cross-check the Hydraulic System B status message if a discrepancy is observed.

The Engine Anti-Ice quantity display that differs from the expected state requires the pilot monitoring to brief the condition when the associated caution light remains illuminated. If the Pack Temperature Control is inoperative, continue approach only after the pilot flying has reviewed the associated sample guidance. The Ground Proximity Monitor switch position is expected to read within the sample range of 19 to 27 units during taxi. The Window Heat indication is expected to read within the sample range of 60 to 66 units during taxi.

The first officer will record any change in the Auxiliary Power Unit selector position and advise the other pilot if a discrepancy is observed. This text is fictional and exists only to give the prototype realistic volume and structure. If the Hydraulic System A is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance. The Standby Instruments quantity display that differs from the expected state requires the pilot monitoring to confirm the condition if a discrepancy is observed. Values in this manual are invented and must not be used for any operational purpose. During takeoff, the First Officer should monitor the Oxygen Distribution selector position when conditions permit.

### **05.10.13 Wing Anti-Ice Crew Awareness**

The Pack Temperature Control switch position is expected to read within the sample range of 82 to 90 units during a maintenance-requested ground run. If the Hydraulic System B is inoperative, continue an extended ground delay only after the pilot flying has reviewed the associated sample guidance. The Hydraulic System B quantity display that differs from the expected state requires the relief pilot to verify the condition when the associated caution light remains illuminated.

The Primary Electrical Bus switch position that differs from the expected state requires both pilots to cross-check the condition when conditions permit. During cruise, the pilot flying should verify the Flight Management Computer switch position if a discrepancy is observed. The Oxygen Distribution annunciation that differs from the expected state requires the Captain to monitor the condition if a discrepancy is observed. The Autothrottle quantity display that differs from the expected state requires the First Officer to brief the condition once the checklist item is complete. The Cabin Pressure Controller advisory that differs from the expected state requires the Captain to record the condition when operating at a sample station without ground power.

The Cargo Smoke Detection advisory that differs from the expected state requires the pilot monitoring to brief the condition if a discrepancy is observed. During cruise, the First Officer should select the Ground Proximity Monitor status message if a discrepancy is observed. The Window Heat selector position is expected to read within the sample range of 19 to 29 units during descent. The Auxiliary Power Unit annunciation that differs from the expected state requires the relief pilot to record the condition unless directed otherwise by the Sample Operations Center. If the Probe Heat is inoperative, continue climb only after the pilot flying has reviewed the associated sample guidance. If the Brake Temperature Monitor is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance.

**NOTE:** If the Hydraulic System A is inoperative, continue an extended ground delay only after the pilot flying has reviewed the associated sample guidance.

The Oxygen Distribution selector position that differs from the expected state requires both pilots to announce the condition when conditions permit. The Engine Anti-Ice advisory is expected to read within the sample range of 87 to 98 units during descent. If the Engine Anti-Ice is inoperative, continue engine start only after the pilot flying has reviewed the associated sample guidance. The Nosewheel Steering annunciation that differs from the expected state requires the Captain to select the condition when conditions permit. The Brake Temperature Monitor indication is expected to read within the sample range of 90 to 102 units during engine start.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Engine Anti-Ice advisory              | 55 units     | Monitor                |
| Autobrake Selector annunciation       | 12 units     | Refer to related topic |
| Bleed Air Supply status message       | 16 units     | Normal                 |
| Weather Radar switch position         | 49 units     | Normal                 |
| Standby Instruments selector position | 87 units     | Monitor                |
| Engine Anti-Ice advisory              | 1 units      | Monitor                |
| Hydraulic System A indication         | 74 units     | Advisory only          |

The pilot monitoring will confirm any change in the Oxygen Distribution status message and advise the other pilot if the indication does not stabilize within the sample interval. The Oxygen Distribution quantity display is expected to read within the sample range of 28 to 34 units during a diversion. The pilot flying will brief any change in the Standby Hydraulic indication and advise the other pilot when operating at a sample station without ground power. The wording here is placeholder content shaped like a procedure, not a procedure. During engine start, the relief pilot should announce the Nosewheel Steering annunciation before the next phase of flight. The captain will announce any change in the Ground Proximity Monitor status message and advise the other pilot before the next phase of flight.

**05.10.14 Cockpit Voice Recorder Status Messages**

During parking, the Captain should record the Brake Temperature Monitor advisory unless directed otherwise by the Sample Operations Center. The pilot monitoring will verify any change in the Autobrake Selector advisory and advise the other pilot when conditions permit. If the Bleed Air Supply is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance. Both pilots will record any change in the Auxiliary Power Unit switch position and advise the other pilot when the associated caution light remains illuminated.

If the Stall Warning is inoperative, continue cruise only after both pilots has reviewed the associated sample guidance. The pilot flying will record any change in the Flap Position Indication status message and advise the other pilot unless directed otherwise by the Sample Operations Center. This text is fictional and exists only to give the prototype realistic volume and structure. Values in this manual are invented and must not be used for any operational purpose. The pilot flying will monitor any change in the Stall Warning annunciation and advise the other pilot before the next phase of flight.

- If the Fire Detection Loop is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance.
- The relief pilot will select any change in the Brake Temperature Monitor annunciation and advise the other pilot when operating at a sample station without ground power.
- If the Wing Anti-Ice is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance.
- If the Wing Anti-Ice is inoperative, continue engine start only after the Captain has reviewed the associated sample guidance.
- The Primary Electrical Bus switch position that differs from the expected state requires the relief pilot to cross-check the condition if the indication does not stabilize within the sample interval.
- During a diversion, the pilot monitoring should confirm the Fire Detection Loop annunciation unless directed otherwise by the Sample Operations Center.

**NOTE:** Refer to the related topic for additional sample context.

**NOTE:** The first officer will cross-check any change in the Fuel Crossfeed quantity display and advise the other pilot if the indication does not stabilize within the sample interval. The relief pilot will confirm any change in the Window Heat advisory and advise the other pilot if a discrepancy is observed.

The Wing Anti-Ice annunciation that differs from the expected state requires the pilot monitoring to confirm the condition if the indication does not stabilize within the sample interval. Refer to the related topic for additional sample context. The Nosewheel Steering switch position that differs from the expected state requires the First Officer to record the condition before the next phase of flight. During taxi, the First Officer should select the Cargo Smoke Detection selector position when the associated caution light remains illuminated. If the Fuel Crossfeed is inoperative, continue approach only after the relief pilot has reviewed the associated sample guidance.

**CAUTION:** Refer to the related topic for additional sample context. The Center Tank Pumps annunciation that differs from the expected state requires the Captain to record the condition once the checklist item is complete.

Values in this manual are invented and must not be used for any operational purpose. Both pilots will select any change in the Cargo Smoke Detection advisory and advise the other pilot unless directed otherwise by the Sample Operations Center. The Fire Detection Loop switch position is expected to read within the sample range of 49 to 54 units during a maintenance-requested ground run.

If the Transponder is inoperative, continue descent only after both pilots has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. The wording here is placeholder content shaped like a procedure, not a procedure. During descent, the pilot flying should record the Brake Temperature Monitor quantity display before the next phase of flight.

### **05.10.15 Wing Anti-Ice Normal Operation**

The pilot monitoring will announce any change in the Autopilot Channel A annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center. During an extended ground delay, the Captain should verify the Pack Temperature Control advisory unless directed otherwise by the Sample Operations Center. If the Engine Anti-Ice is inoperative, continue approach only after the relief pilot has reviewed the associated sample guidance. The Landing Gear Indication indication is expected to read within the sample range of 86 to 91 units during engine start.

- The relief pilot will cross-check any change in the Probe Heat advisory and advise the other pilot when conditions permit.
- During a diversion, the relief pilot should announce the Thrust Reverser status message if the indication does not stabilize within the sample interval.
- The wording here is placeholder content shaped like a procedure, not a procedure.

Values in this manual are invented and must not be used for any operational purpose. The Hydraulic System A quantity display is expected to read within the sample range of 77 to 89 units during parking. The Autopilot Channel A switch position that differs from the expected state requires the relief pilot to monitor the condition unless directed otherwise by the Sample Operations Center. If the Transponder is inoperative, continue descent only after the pilot flying has reviewed the associated sample guidance.

Refer to the related topic for additional sample context. Values in this manual are invented and must not be used for any operational purpose. If the Pack Temperature Control is inoperative, continue an extended ground delay only after the Captain has reviewed the associated sample guidance. The Flight Management Computer annunciation is expected to read within the sample range of 64 to 74 units during preflight.

- During takeoff, both pilots should select the Flight Management Computer indication when conditions permit.
- The Autopilot Channel A indication that differs from the expected state requires the relief pilot to record the condition when operating at a sample station without ground power.
- If the Weather Radar is inoperative, continue descent only after both pilots has reviewed the associated sample guidance.
- During approach, the First Officer should verify the Hydraulic System B selector position when operating at a sample station without ground power.
- The Landing Gear Indication switch position that differs from the expected state requires the relief pilot to verify the condition before the next phase of flight.
- The Autopilot Channel A indication is expected to read within the sample range of 94 to 100 units during a maintenance-requested ground run.

The Cockpit Voice Recorder quantity display is expected to read within the sample range of 60 to 63 units during a diversion. The Nosewheel Steering status message is expected to read within the sample range of 66 to 74 units during preflight. Values in this manual are invented and must not be used for any operational purpose.

The wording here is placeholder content shaped like a procedure, not a procedure. The Fuel Crossfeed indication that differs from the expected state requires both pilots to monitor the condition once the checklist item is complete. If the Cargo Smoke Detection is inoperative, continue parking only after both pilots has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. Refer to the related topic for additional sample context. The Transponder indication that differs from the expected state requires the First Officer to select the condition once the checklist item is complete.

- The Bleed Air Supply switch position that differs from the expected state requires the pilot monitoring to monitor the condition if the indication does not stabilize within the sample interval.
- During engine start, the First Officer should verify the Landing Gear Indication annunciation if a discrepancy is observed.
- During climb, the relief pilot should monitor the Brake Temperature Monitor status message once the checklist item is complete.

#### **05.10.16 Stall Warning Reset Guidance**

During takeoff, the relief pilot should announce the Primary Electrical Bus switch position if a discrepancy is observed. Values in this manual are invented and must not be used for any operational purpose. The Transponder advisory that

differs from the expected state requires the pilot flying to monitor the condition if the indication does not stabilize within the sample interval. The Primary Electrical Bus quantity display is expected to read within the sample range of 21 to 30 units during a diversion. The relief pilot will announce any change in the Primary Electrical Bus switch position and advise the other pilot once the checklist item is complete.

During preflight, the pilot flying should brief the Window Heat quantity display when conditions permit. The pilot flying will select any change in the Center Tank Pumps selector position and advise the other pilot if the indication does not stabilize within the sample interval. Refer to the related topic for additional sample context.

The pilot flying will monitor any change in the Wing Anti-Ice selector position and advise the other pilot unless directed otherwise by the Sample Operations Center. If the Autopilot Channel B is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance. The Autopilot Channel B switch position that differs from the expected state requires the First Officer to confirm the condition if a discrepancy is observed.

The Engine Anti-Ice advisory is expected to read within the sample range of 72 to 80 units during descent. Refer to the related topic for additional sample context. During approach, the pilot monitoring should select the Autopilot Channel A annunciation when operating at a sample station without ground power. Refer to the related topic for additional sample context. The Autothrottle switch position that differs from the expected state requires both pilots to select the condition if the indication does not stabilize within the sample interval.

**NOTE:** The Engine Anti-Ice selector position that differs from the expected state requires the First Officer to monitor the condition when the associated caution light remains illuminated. The Autobrake Selector switch position is expected to read within the sample range of 73 to 80 units during climb.

- The wording here is placeholder content shaped like a procedure, not a procedure.
- The Cockpit Voice Recorder status message is expected to read within the sample range of 65 to 69 units during parking.
- If the Autothrottle is inoperative, continue approach only after the First Officer has reviewed the associated sample guidance.
- The Standby Hydraulic advisory that differs from the expected state requires both pilots to announce the condition if the indication does not stabilize within the sample interval.
- During a diversion, the pilot monitoring should confirm the Oxygen Distribution selector position if a discrepancy is observed.
- The Probe Heat quantity display is expected to read within the sample range of 50 to 57 units during descent.

| Challenge                | Response    |
|--------------------------|-------------|
| Auxiliary Power Unit     | Checked     |
| Traffic Advisory Display | Verified    |
| Autothrottle             | As required |
| Center Tank Pumps        | Verified    |
| Autopilot Channel B      | As required |
| Wing Anti-Ice            | As required |
| Pack Temperature Control | Armed       |
| Primary Electrical Bus   | Verified    |
| Bleed Air Supply         | Off         |
| Transponder              | As required |
| Pack Temperature Control | Verified    |

05.10.17 Autothrottle Crew Awareness



Values in this manual are invented and must not be used for any operational purpose. If the Stall Warning is inoperative, continue approach only after the First Officer has reviewed the associated sample guidance. The Oxygen Distribution status message is expected to read within the sample range of 57 to 62 units during cruise. The Speedbrake Handle switch position that differs from the expected state requires the First Officer to cross-check the condition unless directed otherwise by the Sample Operations Center. The pilot monitoring will brief any change in the Cockpit Voice Recorder switch position and advise the other pilot when the associated caution light remains illuminated. See 11.20.1 Oxygen Distribution Crew Awareness.

**NOTE:** The Hydraulic System A annunciation is expected to read within the sample range of 34 to 41 units during climb.

- If the Flight Management Computer is inoperative, continue takeoff only after both pilots has reviewed the associated sample guidance.
- During preflight, the Captain should record the Cockpit Voice Recorder quantity display if the indication does not stabilize within the sample interval.
- During taxi, the pilot flying should confirm the Probe Heat advisory when conditions permit.

**CAUTION:** Refer to the related topic for additional sample context.

**NOTE:** If the Thrust Reverser is inoperative, continue taxi only after the First Officer has reviewed the associated sample guidance. During approach, the pilot flying should confirm the Probe Heat selector position before the next phase of flight.

| Challenge                | Response |
|--------------------------|----------|
| Autothrottle             | Checked  |
| Thrust Reverser          | Off      |
| Probe Heat               | Armed    |
| Speedbrake Handle        | On       |
| Autobrake Selector       | Verified |
| Window Heat              | Checked  |
| Hydraulic System B       | Closed   |
| Oxygen Distribution      | Verified |
| Ground Proximity Monitor | Checked  |
| Flap Position Indication | Verified |
| Hydraulic System A       | Verified |
| Landing Gear Indication  | Closed   |

**05.10.18 Fire Detection Loop Overview**

Refer to the related topic for additional sample context. The pilot monitoring will announce any change in the Hydraulic System A annunciation and advise the other pilot once the checklist item is complete. The Center Tank Pumps quantity display that differs from the expected state requires the First Officer to confirm the condition unless directed otherwise by the Sample Operations Center. If the Autothrottle is inoperative, continue a maintenance-requested ground run only after the Captain has reviewed the associated sample guidance. The Fuel Crossfeed quantity display is expected to read within the sample range of 16 to 24 units during descent.

The wording here is placeholder content shaped like a procedure, not a procedure. The wording here is placeholder content shaped like a procedure, not a procedure. During a turnaround, the relief pilot should select the Window Heat selector position if a discrepancy is observed. The first officer will verify any change in the Autothrottle status message and advise the other pilot if the indication does not stabilize within the sample interval.

This text is fictional and exists only to give the prototype realistic volume and structure. The Probe Heat quantity display that differs from the expected state requires the pilot flying to record the condition when operating at a sample station without ground power. The wording here is placeholder content shaped like a procedure, not a procedure. The captain will brief any change in the Transponder indication and advise the other pilot if the indication does not stabilize within the sample interval. The Traffic Advisory Display annunciation that differs from the expected state requires both pilots to record the condition unless directed otherwise by the Sample Operations Center.

| Condition                              | Sample value | Remarks                |
|----------------------------------------|--------------|------------------------|
| Landing Gear Indication status message | 59 units     | Refer to related topic |
| Autopilot Channel A annunciation       | 39 units     | Monitor                |
| Cargo Smoke Detection quantity display | 50 units     | Advisory only          |
| Center Tank Pumps quantity display     | 55 units     | Monitor                |

The relief pilot will confirm any change in the Ground Proximity Monitor selector position and advise the other pilot once the checklist item is complete. The Bleed Air Supply quantity display is expected to read within the sample range of 80 to 89 units during climb. The Standby Instruments selector position that differs from the expected state requires both pilots to monitor the condition if a discrepancy is observed. If the Pack Temperature Control is inoperative, continue cruise only after the First Officer has reviewed the associated sample guidance. During approach, the First Officer should record the Center Tank Pumps indication once the checklist item is complete.

- The Wing Anti-Ice advisory is expected to read within the sample range of 4 to 15 units during a turnaround.
- Refer to the related topic for additional sample context.
- The Transponder annunciation that differs from the expected state requires the First Officer to verify the condition before the next phase of flight.

**CAUTION:** If the Autothrottle is inoperative, continue a maintenance-requested ground run only after the pilot flying has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure.

If the Oxygen Distribution is inoperative, continue climb only after both pilots has reviewed the associated sample guidance. Refer to the related topic for additional sample context. During takeoff, the First Officer should select the Cargo Smoke Detection annunciation before the next phase of flight. During cruise, both pilots should brief the Auxiliary Power Unit annunciation when the associated caution light remains illuminated.

| Challenge               | Response    |
|-------------------------|-------------|
| Wing Anti-Ice           | Armed       |
| Hydraulic System A      | Checked     |
| Nosewheel Steering      | As required |
| Standby Instruments     | Checked     |
| Cargo Smoke Detection   | On          |
| Engine Anti-Ice         | Closed      |
| Landing Gear Indication | As required |

05.10.19 Window Heat Power Sources

During a turnaround, the pilot monitoring should record the Brake Temperature Monitor indication unless directed otherwise by the Sample Operations Center. The pilot monitoring will select any change in the Stall Warning selector position and advise the other pilot when the associated caution light remains illuminated. During a turnaround, the pilot flying should brief the Standby Hydraulic switch position unless directed otherwise by the Sample Operations Center. If the Autothrottle is inoperative, continue approach only after the First Officer has reviewed the associated sample guidance. If the Hydraulic System B is inoperative, continue a maintenance-requested ground run only after

the pilot flying has reviewed the associated sample guidance. During approach, the pilot monitoring should announce the Fire Detection Loop quantity display once the checklist item is complete.

The wording here is placeholder content shaped like a procedure, not a procedure. Refer to the related topic for additional sample context. If the Nosewheel Steering is inoperative, continue a maintenance-requested ground run only after the pilot flying has reviewed the associated sample guidance. The Flight Management Computer selector position is expected to read within the sample range of 41 to 46 units during engine start. If the Weather Radar is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance.

Values in this manual are invented and must not be used for any operational purpose. If the Hydraulic System B is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance. The Primary Electrical Bus switch position that differs from the expected state requires the relief pilot to select the condition once the checklist item is complete. The Center Tank Pumps selector position is expected to read within the sample range of 82 to 90 units during takeoff. The Engine Anti-Ice status message is expected to read within the sample range of 55 to 62 units during a turnaround.

- The Hydraulic System B annunciation that differs from the expected state requires the Captain to cross-check the condition when conditions permit.
- The Landing Gear Indication status message that differs from the expected state requires the pilot flying to brief the condition when the associated caution light remains illuminated.
- The Flight Management Computer indication that differs from the expected state requires the First Officer to confirm the condition if a discrepancy is observed.
- The relief pilot will verify any change in the Flap Position Indication selector position and advise the other pilot unless directed otherwise by the Sample Operations Center.
- If the Brake Temperature Monitor is inoperative, continue descent only after the First Officer has reviewed the associated sample guidance.

The Weather Radar status message is expected to read within the sample range of 85 to 91 units during a diversion. The pilot flying will verify any change in the Nosewheel Steering switch position and advise the other pilot once the checklist item is complete. During taxi, both pilots should confirm the Hydraulic System A switch position once the checklist item is complete. During takeoff, the Captain should confirm the Probe Heat annunciation if the indication does not stabilize within the sample interval. The Speedbrake Handle status message is expected to read within the sample range of 96 to 105 units during a diversion.

The relief pilot will brief any change in the Standby Instruments selector position and advise the other pilot unless directed otherwise by the Sample Operations Center. The Fire Detection Loop annunciation is expected to read within the sample range of 80 to 84 units during climb. The Brake Temperature Monitor annunciation that differs from the expected state requires both pilots to cross-check the condition when operating at a sample station without ground power.

**CAUTION:** During takeoff, the pilot flying should monitor the Auxiliary Power Unit selector position once the checklist item is complete.

During landing, the pilot monitoring should verify the Standby Instruments annunciation before the next phase of flight. Refer to the related topic for additional sample context. The Flight Management Computer status message is expected to read within the sample range of 60 to 65 units during cruise. The Autopilot Channel B quantity display that differs from the expected state requires the First Officer to record the condition unless directed otherwise by the Sample Operations Center. The wording here is placeholder content shaped like a procedure, not a procedure. Values in this manual are invented and must not be used for any operational purpose.

### **05.10.20 Autopilot Channel A Reset Guidance**

If the Engine Anti-Ice is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. The Weather Radar status message that differs from the expected state requires the pilot flying to announce the condition if a discrepancy is observed. The Pack Temperature Control annunciation is expected to read within the sample range of 23 to 32 units during landing.

**CAUTION:** The Autopilot Channel A advisory that differs from the expected state requires both pilots to select the condition when the associated caution light remains illuminated.

The Window Heat selector position that differs from the expected state requires the relief pilot to cross-check the condition if a discrepancy is observed. The pilot flying will select any change in the Weather Radar quantity display and advise the other pilot once the checklist item is complete. During preflight, the pilot flying should select the Standby Instruments annunciation before the next phase of flight. The Transponder advisory is expected to read within the sample range of 95 to 103 units during approach. During a turnaround, the pilot flying should monitor the Brake Temperature Monitor annunciation when conditions permit. The first officer will select any change in the Cargo Smoke Detection status message and advise the other pilot when conditions permit.

**NOTE:** Both pilots will brief any change in the Standby Instruments selector position and advise the other pilot once the checklist item is complete. If the Center Tank Pumps is inoperative, continue a turnaround only after the First Officer has reviewed the associated sample guidance.

The captain will confirm any change in the Engine Anti-Ice annunciation and advise the other pilot when operating at a sample station without ground power. During descent, the pilot monitoring should brief the Stall Warning advisory unless directed otherwise by the Sample Operations Center. The Oxygen Distribution annunciation that differs from the expected state requires the pilot monitoring to verify the condition once the checklist item is complete.

- The first officer will record any change in the Transponder status message and advise the other pilot when the associated caution light remains illuminated.
- The Cockpit Voice Recorder status message that differs from the expected state requires the Captain to announce the condition when the associated caution light remains illuminated.
- During approach, the pilot flying should confirm the Center Tank Pumps switch position if the indication does not stabilize within the sample interval.

The pilot flying will verify any change in the Wing Anti-Ice switch position and advise the other pilot once the checklist item is complete. During descent, the First Officer should monitor the Autothrottle selector position unless directed otherwise by the Sample Operations Center. During a turnaround, both pilots should announce the Bleed Air Supply indication when conditions permit. The wording here is placeholder content shaped like a procedure, not a procedure.

## 05.20 Electrical

### 05.20.1 Standby Instruments Interfaces

The first officer will cross-check any change in the Transponder quantity display and advise the other pilot if a discrepancy is observed. If the Landing Gear Indication is inoperative, continue preflight only after the pilot monitoring has reviewed the associated sample guidance. During a maintenance-requested ground run, the relief pilot should record the Standby Hydraulic annunciation if a discrepancy is observed. If the Autopilot Channel B is inoperative, continue preflight only after the pilot monitoring has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. The captain will brief any change in the Autopilot Channel B selector position and advise the other pilot if a discrepancy is observed.

The wording here is placeholder content shaped like a procedure, not a procedure. Values in this manual are invented and must not be used for any operational purpose. During climb, the pilot monitoring should select the Autobrake Selector switch position unless directed otherwise by the Sample Operations Center. If the Autopilot Channel A is inoperative, continue descent only after the Captain has reviewed the associated sample guidance. The Transponder selector position is expected to read within the sample range of 40 to 48 units during takeoff. The

wording here is placeholder content shaped like a procedure, not a procedure.

If the Engine Anti-Ice is inoperative, continue approach only after the pilot flying has reviewed the associated sample guidance. During engine start, the First Officer should record the Pack Temperature Control indication before the next phase of flight. During approach, the First Officer should verify the Autothrottle status message when operating at a sample station without ground power.

| Condition                                   | Sample value | Remarks                |
|---------------------------------------------|--------------|------------------------|
| Autopilot Channel B switch position         | 56 units     | Refer to related topic |
| Cabin Pressure Controller selector position | 16 units     | Refer to related topic |
| Bleed Air Supply annunciation               | 63 units     | Monitor                |
| Autopilot Channel A selector position       | 21 units     | Monitor                |
| Cabin Pressure Controller advisory          | 13 units     | Refer to related topic |

| Condition                           | Sample value | Remarks                |
|-------------------------------------|--------------|------------------------|
| Autopilot Channel A switch position | 62 units     | Refer to related topic |
| Autothrottle annunciation           | 55 units     | Advisory only          |
| Bleed Air Supply annunciation       | 63 units     | Monitor                |

**CAUTION:** The Fuel Crossfeed advisory is expected to read within the sample range of 93 to 100 units during taxi.

| Challenge                 | Response    |
|---------------------------|-------------|
| Cockpit Voice Recorder    | Verified    |
| Engine Anti-Ice           | As required |
| Hydraulic System A        | Checked     |
| Brake Temperature Monitor | Closed      |
| Pack Temperature Control  | On          |
| Hydraulic System B        | Closed      |
| Standby Hydraulic         | Armed       |

**05.20.2 Brake Temperature Monitor Limits Display**

Both pilots will select any change in the Primary Electrical Bus status message and advise the other pilot if a discrepancy is observed. The pilot monitoring will select any change in the Hydraulic System B selector position and advise the other pilot when the associated caution light remains illuminated. During approach, the relief pilot should monitor the Probe Heat indication when operating at a sample station without ground power. The first officer will verify any change in the Primary Electrical Bus advisory and advise the other pilot unless directed otherwise by the Sample Operations Center.

If the Nosewheel Steering is inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance. During climb, both pilots should announce the Autobrake Selector quantity display when operating at a sample station without ground power. During landing, the pilot monitoring should monitor the Oxygen Distribution advisory unless directed otherwise by the Sample Operations Center. The Landing Gear Indication quantity display that differs from the expected state requires the Captain to brief the condition when the associated caution light remains illuminated.

- The Ground Proximity Monitor quantity display is expected to read within the sample range of 57 to 62 units during preflight.

- During a diversion, the First Officer should announce the Engine Anti-Ice switch position when the associated caution light remains illuminated.
- During a turnaround, the pilot flying should cross-check the Flight Management Computer quantity display when the associated caution light remains illuminated.
- Values in this manual are invented and must not be used for any operational purpose.
- During taxi, the First Officer should confirm the Center Tank Pumps selector position if the indication does not stabilize within the sample interval.

The Landing Gear Indication annunciation is expected to read within the sample range of 65 to 71 units during approach. The first officer will record any change in the Hydraulic System B status message and advise the other pilot when operating at a sample station without ground power. Both pilots will brief any change in the Auxiliary Power Unit advisory and advise the other pilot unless directed otherwise by the Sample Operations Center. If the Speedbrake Handle is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance.

The pilot flying will record any change in the Nosewheel Steering selector position and advise the other pilot before the next phase of flight. Refer to the related topic for additional sample context. The pilot monitoring will cross-check any change in the Engine Anti-Ice quantity display and advise the other pilot once the checklist item is complete. The wording here is placeholder content shaped like a procedure, not a procedure.

**NOTE:** During preflight, the pilot monitoring should select the Flight Management Computer status message if a discrepancy is observed.

| Condition                                    | Sample value | Remarks                |
|----------------------------------------------|--------------|------------------------|
| Landing Gear Indication status message       | 82 units     | Monitor                |
| Flight Management Computer selector position | 21 units     | Monitor                |
| Speedbrake Handle annunciation               | 79 units     | Refer to related topic |
| Fuel Crossfeed indication                    | 87 units     | Normal                 |
| Standby Hydraulic selector position          | 12 units     | Monitor                |
| Speedbrake Handle switch position            | 96 units     | Monitor                |
| Center Tank Pumps annunciation               | 90 units     | Normal                 |

During an extended ground delay, both pilots should confirm the Center Tank Pumps selector position once the checklist item is complete. The pilot monitoring will announce any change in the Oxygen Distribution quantity display and advise the other pilot if a discrepancy is observed. The Wing Anti-Ice annunciation that differs from the expected state requires both pilots to brief the condition if a discrepancy is observed.

| Challenge                | Response    |
|--------------------------|-------------|
| Nosewheel Steering       | Armed       |
| Weather Radar            | Closed      |
| Standby Instruments      | Closed      |
| Flap Position Indication | Closed      |
| Window Heat              | As required |
| Oxygen Distribution      | As required |
| Center Tank Pumps        | Verified    |
| Autothrottle             | Closed      |
| Nosewheel Steering       | Closed      |
| Window Heat              | Armed       |
| Cargo Smoke Detection    | Armed       |



|                  |       |
|------------------|-------|
| Bleed Air Supply | Armed |
|------------------|-------|

05.20.3 Landing Gear Indication Interfaces

The Cabin Pressure Controller status message is expected to read within the sample range of 17 to 29 units during a turnaround. During cruise, the First Officer should record the Transponder quantity display when operating at a sample station without ground power. The Flap Position Indication quantity display that differs from the expected state requires the pilot flying to select the condition before the next phase of flight.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Center Tank Pumps annunciation            | 93 units     | Refer to related topic |
| Autothrottle advisory                     | 95 units     | Refer to related topic |
| Hydraulic System B switch position        | 62 units     | Normal                 |
| Hydraulic System A quantity display       | 57 units     | Refer to related topic |
| Cabin Pressure Controller switch position | 78 units     | Monitor                |

The wording here is placeholder content shaped like a procedure, not a procedure. Refer to the related topic for additional sample context. The Center Tank Pumps annunciation that differs from the expected state requires the First Officer to cross-check the condition once the checklist item is complete. The Speedbrake Handle switch position that differs from the expected state requires the relief pilot to verify the condition unless directed otherwise by the Sample Operations Center. The Landing Gear Indication advisory is expected to read within the sample range of 87 to 96 units during cruise. The wording here is placeholder content shaped like a procedure, not a procedure.

**CAUTION:** Refer to the related topic for additional sample context. During taxi, both pilots should record the Thrust Reverser advisory if the indication does not stabilize within the sample interval.

| Condition                     | Sample value | Remarks                |
|-------------------------------|--------------|------------------------|
| Fuel Crossfeed indication     | 51 units     | Normal                 |
| Transponder switch position   | 76 units     | Refer to related topic |
| Fuel Crossfeed status message | 60 units     | Monitor                |

- If the Oxygen Distribution is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance.
- The Center Tank Pumps quantity display is expected to read within the sample range of 23 to 34 units during a maintenance-requested ground run.
- The relief pilot will confirm any change in the Center Tank Pumps indication and advise the other pilot if a discrepancy is observed.
- The Hydraulic System A status message that differs from the expected state requires the Captain to monitor the condition if a discrepancy is observed.
- The Window Heat indication that differs from the expected state requires both pilots to verify the condition before the next phase of flight.

**CAUTION:** The Traffic Advisory Display quantity display is expected to read within the sample range of 10 to 22 units during preflight.

Values in this manual are invented and must not be used for any operational purpose. The Flap Position Indication annunciation that differs from the expected state requires the pilot flying to record the condition unless directed otherwise by the Sample Operations Center. If the Fuel Crossfeed is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance. The pilot flying will cross-check any change in the Autobrake Selector quantity display and advise the other pilot if the indication does not stabilize within the sample

interval. Values in this manual are invented and must not be used for any operational purpose.

**CAUTION:** If the Primary Electrical Bus is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance. The Flight Management Computer selector position is expected to read within the sample range of 26 to 33 units during takeoff.

| Challenge              | Response    |
|------------------------|-------------|
| Autopilot Channel B    | On          |
| Wing Anti-Ice          | Set         |
| Autobrake Selector     | Armed       |
| Cockpit Voice Recorder | Set         |
| Thrust Reverser        | Set         |
| Weather Radar          | Checked     |
| Stall Warning          | Armed       |
| Oxygen Distribution    | As required |
| Hydraulic System A     | Verified    |
| Standby Hydraulic      | As required |
| Thrust Reverser        | Set         |
| Bleed Air Supply       | On          |

#### 05.20.4 Ground Proximity Monitor Status Messages

The Autopilot Channel A selector position that differs from the expected state requires the pilot monitoring to confirm the condition once the checklist item is complete. If the Pack Temperature Control is inoperative, continue descent only after the Captain has reviewed the associated sample guidance. The Standby Instruments quantity display that differs from the expected state requires the Captain to confirm the condition unless directed otherwise by the Sample Operations Center. Both pilots will verify any change in the Fire Detection Loop advisory and advise the other pilot when conditions permit. The captain will announce any change in the Ground Proximity Monitor quantity display and advise the other pilot once the checklist item is complete.

**NOTE:** The first officer will cross-check any change in the Autothrottle quantity display and advise the other pilot when operating at a sample station without ground power.

The Landing Gear Indication status message is expected to read within the sample range of 43 to 51 units during a diversion. The captain will verify any change in the Probe Heat annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center. Refer to the related topic for additional sample context. The Weather Radar indication that differs from the expected state requires both pilots to select the condition when operating at a sample station without ground power. The wording here is placeholder content shaped like a procedure, not a procedure.

- The Speedbrake Handle selector position that differs from the expected state requires the pilot monitoring to brief the condition before the next phase of flight.
- The Weather Radar quantity display that differs from the expected state requires the pilot flying to record the condition when conditions permit.
- The Engine Anti-Ice annunciation is expected to read within the sample range of 59 to 71 units during engine start.
- The Wing Anti-Ice annunciation that differs from the expected state requires the relief pilot to select the condition once the checklist item is complete.
- The Cockpit Voice Recorder annunciation that differs from the expected state requires the pilot flying to announce the condition when operating at a sample station without ground power.

- The Speedbrake Handle advisory that differs from the expected state requires the First Officer to cross-check the condition when the associated caution light remains illuminated.
- The Autopilot Channel A advisory is expected to read within the sample range of 81 to 84 units during parking.
- Values in this manual are invented and must not be used for any operational purpose.
- The captain will confirm any change in the Weather Radar annunciation and advise the other pilot if a discrepancy is observed.
- The Flap Position Indication indication is expected to read within the sample range of 42 to 47 units during approach.
- If the Fire Detection Loop is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- Values in this manual are invented and must not be used for any operational purpose.
- The pilot monitoring will announce any change in the Standby Hydraulic status message and advise the other pilot when operating at a sample station without ground power.
- The Hydraulic System A indication is expected to read within the sample range of 22 to 33 units during landing.
- If the Cockpit Voice Recorder is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance.

| Condition                           | Sample value | Remarks                |
|-------------------------------------|--------------|------------------------|
| Oxygen Distribution status message  | 46 units     | Monitor                |
| Hydraulic System B quantity display | 65 units     | Refer to related topic |
| Bleed Air Supply indication         | 27 units     | Monitor                |

The Flight Management Computer quantity display is expected to read within the sample range of 7 to 16 units during landing. If the Nosewheel Steering is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance. The Oxygen Distribution advisory is expected to read within the sample range of 98 to 104 units during taxi.

Refer to the related topic for additional sample context. The Flap Position Indication advisory is expected to read within the sample range of 58 to 69 units during takeoff. The Landing Gear Indication annunciation is expected to read within the sample range of 69 to 78 units during cruise. The pilot monitoring will cross-check any change in the Autobrake Selector indication and advise the other pilot before the next phase of flight. If the Fire Detection Loop is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance.

| Challenge              | Response    |
|------------------------|-------------|
| Weather Radar          | As required |
| Auxiliary Power Unit   | Checked     |
| Cockpit Voice Recorder | Off         |
| Nosewheel Steering     | Closed      |
| Hydraulic System B     | Closed      |
| Autothrottle           | Verified    |
| Standby Instruments    | Off         |
| Standby Instruments    | As required |
| Wing Anti-Ice          | Closed      |

### 05.20.5 Nosewheel Steering Power Sources

The wording here is placeholder content shaped like a procedure, not a procedure. If the Fuel Crossfeed is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. The pilot flying will monitor any change in the Window Heat switch position and advise the other pilot when conditions permit. If the Oxygen Distribution is inoperative, continue takeoff only after the First Officer has reviewed the associated sample guidance.

During approach, both pilots should brief the Fire Detection Loop selector position once the checklist item is complete. The Engine Anti-Ice switch position that differs from the expected state requires the pilot monitoring to monitor the condition unless directed otherwise by the Sample Operations Center. The pilot flying will announce any change in the Ground Proximity Monitor annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center. If the Nosewheel Steering is inoperative, continue engine start only after the Captain has reviewed the associated sample guidance. The Hydraulic System A quantity display is expected to read within the sample range of 85 to 88 units during cruise. If the Traffic Advisory Display is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance.

**NOTE:** The Flight Management Computer advisory is expected to read within the sample range of 19 to 23 units during taxi. The Hydraulic System A indication that differs from the expected state requires both pilots to monitor the condition when conditions permit.

The Probe Heat switch position is expected to read within the sample range of 29 to 37 units during parking. The Engine Anti-Ice switch position that differs from the expected state requires the pilot monitoring to announce the condition when conditions permit. The Traffic Advisory Display selector position is expected to read within the sample range of 71 to 79 units during takeoff.

Refer to the related topic for additional sample context. The relief pilot will brief any change in the Transponder selector position and advise the other pilot once the checklist item is complete. The pilot monitoring will monitor any change in the Window Heat switch position and advise the other pilot once the checklist item is complete. The Standby Instruments switch position that differs from the expected state requires both pilots to brief the condition if a discrepancy is observed. The relief pilot will select any change in the Standby Instruments quantity display and advise the other pilot when the associated caution light remains illuminated. The pilot flying will cross-check any change in the Center Tank Pumps advisory and advise the other pilot when operating at a sample station without ground power.

**CAUTION:** The Thrust Reverser status message that differs from the expected state requires the pilot monitoring to record the condition before the next phase of flight. If the Nosewheel Steering is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance.

- Values in this manual are invented and must not be used for any operational purpose.
- During landing, both pilots should brief the Fire Detection Loop switch position when the associated caution light remains illuminated.
- If the Speedbrake Handle is inoperative, continue takeoff only after both pilots has reviewed the associated sample guidance.
- The first officer will select any change in the Center Tank Pumps switch position and advise the other pilot when conditions permit.
- The Autobrake Selector switch position is expected to read within the sample range of 49 to 52 units during climb.
- The pilot monitoring will confirm any change in the Engine Anti-Ice selector position and advise the other pilot if a discrepancy is observed.
- During climb, both pilots should verify the Nosewheel Steering quantity display if a discrepancy is observed.
- The captain will confirm any change in the Ground Proximity Monitor annunciation and advise the other pilot if a discrepancy is observed.

- The Cabin Pressure Controller advisory is expected to read within the sample range of 14 to 17 units during preflight.
- The first officer will monitor any change in the Flight Management Computer quantity display and advise the other pilot when the associated caution light remains illuminated.
- The first officer will record any change in the Wing Anti-Ice indication and advise the other pilot once the checklist item is complete.

**CAUTION:** The pilot monitoring will record any change in the Flight Management Computer status message and advise the other pilot when operating at a sample station without ground power. The Flight Management Computer advisory that differs from the expected state requires the Captain to brief the condition when conditions permit.

| Challenge                 | Response    |
|---------------------------|-------------|
| Hydraulic System B        | As required |
| Brake Temperature Monitor | As required |
| Flap Position Indication  | Verified    |
| Fuel Crossfeed            | Armed       |
| Autothrottle              | Off         |
| Oxygen Distribution       | As required |
| Cargo Smoke Detection     | Verified    |
| Stall Warning             | Verified    |
| Thrust Reverser           | Closed      |
| Center Tank Pumps         | Verified    |
| Bleed Air Supply          | As required |
| Fuel Crossfeed            | Set         |

### 05.20.6 Center Tank Pumps Status Messages

The pilot flying will select any change in the Auxiliary Power Unit switch position and advise the other pilot if the indication does not stabilize within the sample interval. During takeoff, the pilot flying should verify the Pack Temperature Control status message if the indication does not stabilize within the sample interval. The Window Heat advisory is expected to read within the sample range of 64 to 68 units during descent. The Pack Temperature Control status message that differs from the expected state requires both pilots to brief the condition if a discrepancy is observed. The captain will cross-check any change in the Transponder quantity display and advise the other pilot if a discrepancy is observed.

The pilot monitoring will brief any change in the Standby Instruments advisory and advise the other pilot once the checklist item is complete. The Cargo Smoke Detection quantity display is expected to read within the sample range of 9 to 21 units during a turnaround. The Cargo Smoke Detection quantity display is expected to read within the sample range of 93 to 96 units during takeoff.

The Primary Electrical Bus advisory is expected to read within the sample range of 7 to 19 units during parking. The relief pilot will select any change in the Nosewheel Steering switch position and advise the other pilot before the next phase of flight. If the Bleed Air Supply is inoperative, continue an extended ground delay only after the Captain has reviewed the associated sample guidance. The captain will select any change in the Autopilot Channel B advisory and advise the other pilot if the indication does not stabilize within the sample interval.

The first officer will record any change in the Hydraulic System B switch position and advise the other pilot once the checklist item is complete. If the Ground Proximity Monitor is inoperative, continue taxi only after the relief pilot has reviewed the associated sample guidance. The Bleed Air Supply indication is expected to read within the sample range of 34 to 38 units during descent.

If the Brake Temperature Monitor is inoperative, continue a diversion only after the First Officer has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. The pilot monitoring will confirm any change in the Brake Temperature Monitor advisory and advise the other pilot once the checklist item is complete. During descent, the First Officer should cross-check the Wing Anti-Ice indication unless directed otherwise by the Sample Operations Center. If the Autopilot Channel B is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance. If the Thrust Reverser is inoperative, continue climb only after the relief pilot has reviewed the associated sample guidance.

| Condition                            | Sample value | Remarks       |
|--------------------------------------|--------------|---------------|
| Autopilot Channel A quantity display | 48 units     | Advisory only |
| Wing Anti-Ice advisory               | 2 units      | Normal        |
| Autothrottle advisory                | 40 units     | Advisory only |

**NOTE:** The Fire Detection Loop indication is expected to read within the sample range of 77 to 88 units during takeoff. During a turnaround, the First Officer should cross-check the Standby Instruments quantity display when operating at a sample station without ground power.

**CAUTION:** During cruise, the pilot monitoring should confirm the Auxiliary Power Unit annunciation if a discrepancy is observed.

The wording here is placeholder content shaped like a procedure, not a procedure. Refer to the related topic for additional sample context. The Thrust Reverser quantity display that differs from the expected state requires the Captain to record the condition unless directed otherwise by the Sample Operations Center. The Fire Detection Loop switch position that differs from the expected state requires both pilots to confirm the condition before the next phase of flight.

| Challenge                | Response |
|--------------------------|----------|
| Center Tank Pumps        | Closed   |
| Transponder              | On       |
| Weather Radar            | Closed   |
| Ground Proximity Monitor | Off      |
| Ground Proximity Monitor | Set      |
| Hydraulic System A       | Set      |
| Probe Heat               | On       |
| Ground Proximity Monitor | Set      |
| Autothrottle             | On       |
| Ground Proximity Monitor | Checked  |
| Fuel Crossfeed           | Armed    |
| Thrust Reverser          | On       |

05.20.7 Engine Anti-Ice Overview

The Window Heat switch position that differs from the expected state requires the Captain to announce the condition when conditions permit. The Nosewheel Steering advisory is expected to read within the sample range of 63 to 69 units during landing. If the Cockpit Voice Recorder is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. If the Primary Electrical Bus is inoperative, continue landing only after the Captain has reviewed the associated sample guidance. The Cockpit Voice Recorder quantity display is expected to read within the sample range of 76 to 85 units during an extended ground delay.

| Condition | Sample value | Remarks |
|-----------|--------------|---------|
|-----------|--------------|---------|



|                                 |          |                        |
|---------------------------------|----------|------------------------|
| Hydraulic System B annunciation | 37 units | Refer to related topic |
| Stall Warning switch position   | 2 units  | Normal                 |
| Hydraulic System A indication   | 45 units | Monitor                |
| Stall Warning selector position | 31 units | Normal                 |
| Auxiliary Power Unit advisory   | 6 units  | Refer to related topic |
| Autobrake Selector annunciation | 86 units | Refer to related topic |
| Hydraulic System B advisory     | 26 units | Refer to related topic |

The Flap Position Indication indication is expected to read within the sample range of 11 to 17 units during climb. The pilot flying will cross-check any change in the Ground Proximity Monitor advisory and advise the other pilot if the indication does not stabilize within the sample interval. The Fire Detection Loop selector position is expected to read within the sample range of 41 to 50 units during a diversion. The Hydraulic System B advisory is expected to read within the sample range of 23 to 32 units during cruise. The Window Heat quantity display that differs from the expected state requires the relief pilot to monitor the condition unless directed otherwise by the Sample Operations Center. The Autothrottle advisory that differs from the expected state requires the Captain to select the condition before the next phase of flight.

During a diversion, the First Officer should cross-check the Autopilot Channel B advisory before the next phase of flight. If the Primary Electrical Bus is inoperative, continue a diversion only after both pilots has reviewed the associated sample guidance. During taxi, both pilots should select the Auxiliary Power Unit annunciation once the checklist item is complete. If the Primary Electrical Bus is inoperative, continue parking only after the relief pilot has reviewed the associated sample guidance.

**NOTE:** The Hydraulic System B selector position is expected to read within the sample range of 94 to 103 units during an extended ground delay. The wording here is placeholder content shaped like a procedure, not a procedure.

05.20.8 Transponder Limits Display

The Hydraulic System A switch position is expected to read within the sample range of 84 to 88 units during climb. If the Hydraulic System A is inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance. The relief pilot will cross-check any change in the Flight Management Computer annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center. The Autopilot Channel B quantity display is expected to read within the sample range of 25 to 37 units during a turnaround.

| Condition                                | Sample value | Remarks       |
|------------------------------------------|--------------|---------------|
| Hydraulic System A switch position       | 76 units     | Normal        |
| Traffic Advisory Display switch position | 95 units     | Advisory only |
| Transponder quantity display             | 79 units     | Normal        |
| Thrust Reverser selector position        | 51 units     | Normal        |
| Thrust Reverser annunciation             | 58 units     | Monitor       |

**CAUTION:** The relief pilot will monitor any change in the Cargo Smoke Detection annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center.

If the Center Tank Pumps is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance. During approach, the First Officer should cross-check the Autopilot Channel A selector position unless directed otherwise by the Sample Operations Center. This text is fictional and exists only to give the prototype realistic volume and structure.

**NOTE:** During landing, the pilot flying should confirm the Hydraulic System B status message when operating at a sample station without ground power. The Autobrake Selector advisory is expected to read within the sample

range of 64 to 72 units during preflight.

The wording here is placeholder content shaped like a procedure, not a procedure. The Bleed Air Supply status message that differs from the expected state requires the pilot flying to confirm the condition before the next phase of flight. If the Fuel Crossfeed is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance.

The Window Heat switch position is expected to read within the sample range of 92 to 98 units during climb. The Hydraulic System B selector position that differs from the expected state requires the First Officer to verify the condition when conditions permit. Refer to the related topic for additional sample context.

| Condition                             | Sample value | Remarks       |
|---------------------------------------|--------------|---------------|
| Ground Proximity Monitor advisory     | 10 units     | Normal        |
| Ground Proximity Monitor annunciation | 78 units     | Advisory only |
| Primary Electrical Bus indication     | 39 units     | Normal        |
| Cargo Smoke Detection indication      | 24 units     | Advisory only |
| Bleed Air Supply selector position    | 20 units     | Monitor       |
| Weather Radar status message          | 10 units     | Monitor       |

The Landing Gear Indication annunciation is expected to read within the sample range of 22 to 27 units during taxi. During an extended ground delay, the Captain should record the Nosewheel Steering indication when operating at a sample station without ground power. The Cockpit Voice Recorder annunciation is expected to read within the sample range of 6 to 17 units during an extended ground delay. The Standby Instruments quantity display is expected to read within the sample range of 15 to 21 units during parking. The Nosewheel Steering annunciation that differs from the expected state requires the First Officer to confirm the condition if a discrepancy is observed.

05.20.9 Autobrake Selector Limits Display

If the Traffic Advisory Display is inoperative, continue engine start only after the Captain has reviewed the associated sample guidance. During taxi, the First Officer should cross-check the Cabin Pressure Controller switch position unless directed otherwise by the Sample Operations Center. The Transponder annunciation that differs from the expected state requires the pilot flying to select the condition when the associated caution light remains illuminated. The captain will select any change in the Flap Position Indication quantity display and advise the other pilot once the checklist item is complete. The pilot monitoring will verify any change in the Ground Proximity Monitor indication and advise the other pilot before the next phase of flight. During a maintenance-requested ground run, the pilot monitoring should brief the Auxiliary Power Unit advisory when the associated caution light remains illuminated.

**CAUTION:** During a turnaround, the relief pilot should verify the Engine Anti-Ice quantity display once the checklist item is complete.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Wing Anti-Ice switch position              | 85 units     | Refer to related topic |
| Pack Temperature Control selector position | 20 units     | Advisory only          |
| Standby Hydraulic annunciation             | 9 units      | Refer to related topic |
| Cargo Smoke Detection selector position    | 74 units     | Monitor                |

- If the Autopilot Channel B is inoperative, continue taxi only after the pilot flying has reviewed the associated sample guidance.
- The Bleed Air Supply advisory is expected to read within the sample range of 5 to 11 units during descent.
- The Hydraulic System B indication that differs from the expected state requires the pilot monitoring to brief the condition when operating at a sample station without ground power.

- If the Pack Temperature Control is inoperative, continue descent only after both pilots has reviewed the associated sample guidance.

**CAUTION:** The relief pilot will select any change in the Fuel Crossfeed quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center.

- During a turnaround, both pilots should confirm the Primary Electrical Bus selector position when operating at a sample station without ground power.
- During a turnaround, the pilot monitoring should monitor the Thrust Reverser advisory when conditions permit.
- During a maintenance-requested ground run, the pilot flying should announce the Pack Temperature Control status message before the next phase of flight.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- Refer to the related topic for additional sample context.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- If the Engine Anti-Ice is inoperative, continue a maintenance-requested ground run only after the Captain has reviewed the associated sample guidance.

**CAUTION:** The Weather Radar status message that differs from the expected state requires both pilots to verify the condition once the checklist item is complete. If the Standby Hydraulic is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance.

#### 05.20.10 *Cargo Smoke Detection Limits Display*

The Flight Management Computer indication that differs from the expected state requires the First Officer to confirm the condition when the associated caution light remains illuminated. Both pilots will record any change in the Oxygen Distribution switch position and advise the other pilot if the indication does not stabilize within the sample interval. The Cockpit Voice Recorder quantity display that differs from the expected state requires the relief pilot to monitor the condition when operating at a sample station without ground power. The Bleed Air Supply status message is expected to read within the sample range of 33 to 38 units during takeoff. During descent, the pilot monitoring should verify the Wing Anti-Ice selector position once the checklist item is complete.

The Cockpit Voice Recorder indication is expected to read within the sample range of 59 to 70 units during cruise. The pilot monitoring will select any change in the Ground Proximity Monitor status message and advise the other pilot when operating at a sample station without ground power. If the Autopilot Channel B is inoperative, continue a diversion only after the First Officer has reviewed the associated sample guidance.

The Hydraulic System A status message that differs from the expected state requires both pilots to monitor the condition if a discrepancy is observed. The Oxygen Distribution annunciation is expected to read within the sample range of 56 to 60 units during parking. If the Cabin Pressure Controller is inoperative, continue taxi only after both pilots has reviewed the associated sample guidance.

The wording here is placeholder content shaped like a procedure, not a procedure. During climb, the pilot flying should verify the Window Heat selector position once the checklist item is complete. If the Standby Instruments is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance. During engine start, the First Officer should brief the Standby Hydraulic indication once the checklist item is complete. The wording here is placeholder content shaped like a procedure, not a procedure.

**CAUTION:** The first officer will cross-check any change in the Autobrake Selector switch position and advise the other pilot if the indication does not stabilize within the sample interval.

- During takeoff, the pilot flying should brief the Speedbrake Handle indication unless directed otherwise by the Sample Operations Center.

- The Flight Management Computer annunciation that differs from the expected state requires the pilot monitoring to monitor the condition when the associated caution light remains illuminated.
- The Speedbrake Handle switch position that differs from the expected state requires the relief pilot to brief the condition once the checklist item is complete.
- The Ground Proximity Monitor switch position that differs from the expected state requires the Captain to announce the condition if a discrepancy is observed.
- If the Standby Hydraulic is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance.
- The Speedbrake Handle switch position that differs from the expected state requires the Captain to cross-check the condition when the associated caution light remains illuminated.

**CAUTION:** The first officer will verify any change in the Hydraulic System B annunciation and advise the other pilot when the associated caution light remains illuminated.

**05.20.11 Nosewheel Steering Interfaces**

The Auxiliary Power Unit status message that differs from the expected state requires the Captain to brief the condition if a discrepancy is observed. If the Wing Anti-Ice is inoperative, continue landing only after the Captain has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. The Fire Detection Loop annunciation that differs from the expected state requires the relief pilot to verify the condition before the next phase of flight. The Bleed Air Supply selector position that differs from the expected state requires the pilot monitoring to confirm the condition when operating at a sample station without ground power. If the Probe Heat is inoperative, continue a maintenance-requested ground run only after the Captain has reviewed the associated sample guidance.

**CAUTION:** If the Weather Radar is inoperative, continue descent only after the First Officer has reviewed the associated sample guidance. The Weather Radar selector position that differs from the expected state requires the Captain to brief the condition if the indication does not stabilize within the sample interval.

Values in this manual are invented and must not be used for any operational purpose. The Standby Hydraulic switch position is expected to read within the sample range of 22 to 30 units during a diversion. Values in this manual are invented and must not be used for any operational purpose.

| Condition                           | Sample value | Remarks                |
|-------------------------------------|--------------|------------------------|
| Probe Heat indication               | 80 units     | Normal                 |
| Autopilot Channel A switch position | 99 units     | Monitor                |
| Standby Instruments status message  | 70 units     | Refer to related topic |

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Bleed Air Supply quantity display          | 82 units     | Normal                 |
| Flap Position Indication selector position | 61 units     | Refer to related topic |
| Flap Position Indication advisory          | 85 units     | Normal                 |
| Center Tank Pumps selector position        | 86 units     | Normal                 |

- The Pack Temperature Control quantity display is expected to read within the sample range of 97 to 101 units during preflight.
- The Engine Anti-Ice status message that differs from the expected state requires the Captain to monitor the condition when the associated caution light remains illuminated.
- The wording here is placeholder content shaped like a procedure, not a procedure.

- The wording here is placeholder content shaped like a procedure, not a procedure.
- If the Probe Heat is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance.
- Refer to the related topic for additional sample context.

**05.20.12   Autopilot Channel A Overview**

If the Thrust Reverser is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance. The Cargo Smoke Detection indication is expected to read within the sample range of 89 to 96 units during a diversion. During descent, the relief pilot should brief the Fire Detection Loop selector position before the next phase of flight. The Autopilot Channel B selector position is expected to read within the sample range of 72 to 82 units during a maintenance-requested ground run. The Fuel Crossfeed switch position that differs from the expected state requires the relief pilot to record the condition when conditions permit.

- Both pilots will cross-check any change in the Thrust Reverser switch position and advise the other pilot if the indication does not stabilize within the sample interval.
- Refer to the related topic for additional sample context.
- If the Speedbrake Handle is inoperative, continue approach only after the pilot monitoring has reviewed the associated sample guidance.
- The Weather Radar advisory that differs from the expected state requires the pilot flying to confirm the condition when the associated caution light remains illuminated.
- The Window Heat indication that differs from the expected state requires the pilot flying to monitor the condition once the checklist item is complete.
- If the Pack Temperature Control is inoperative, continue preflight only after both pilots has reviewed the associated sample guidance.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Traffic Advisory Display status message | 16 units     | Advisory only          |
| Speedbrake Handle switch position       | 17 units     | Refer to related topic |
| Wing Anti-Ice quantity display          | 95 units     | Refer to related topic |

- The Brake Temperature Monitor advisory is expected to read within the sample range of 74 to 82 units during a turnaround.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- During taxi, the pilot monitoring should brief the Autopilot Channel A quantity display unless directed otherwise by the Sample Operations Center.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- During preflight, the First Officer should select the Brake Temperature Monitor status message once the checklist item is complete.
- Values in this manual are invented and must not be used for any operational purpose.

**NOTE:** The relief pilot will brief any change in the Primary Electrical Bus selector position and advise the other pilot if the indication does not stabilize within the sample interval.

The pilot monitoring will brief any change in the Center Tank Pumps status message and advise the other pilot when the associated caution light remains illuminated. If the Cargo Smoke Detection is inoperative, continue descent only after the First Officer has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure.

**NOTE:** The Cargo Smoke Detection selector position that differs from the expected state requires the First Officer to brief the condition once the checklist item is complete.

- Values in this manual are invented and must not be used for any operational purpose.
- During taxi, the pilot monitoring should record the Autopilot Channel B indication before the next phase of flight.
- If the Transponder is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- During a turnaround, the pilot monitoring should brief the Ground Proximity Monitor quantity display unless directed otherwise by the Sample Operations Center.
- The Autobrake Selector status message that differs from the expected state requires the relief pilot to monitor the condition if the indication does not stabilize within the sample interval.

| Challenge                 | Response    |
|---------------------------|-------------|
| Brake Temperature Monitor | Closed      |
| Autopilot Channel B       | Off         |
| Wing Anti-Ice             | Set         |
| Hydraulic System A        | On          |
| Cockpit Voice Recorder    | Verified    |
| Window Heat               | Closed      |
| Fire Detection Loop       | Off         |
| Cabin Pressure Controller | As required |

**05.20.13 Weather Radar Status Messages**

This text is fictional and exists only to give the prototype realistic volume and structure. The relief pilot will record any change in the Standby Hydraulic annunciation and advise the other pilot if a discrepancy is observed. The Standby Instruments selector position is expected to read within the sample range of 41 to 51 units during descent. During takeoff, the First Officer should monitor the Standby Instruments annunciation once the checklist item is complete.

**NOTE:** This text is fictional and exists only to give the prototype realistic volume and structure. The Cargo Smoke Detection status message is expected to read within the sample range of 31 to 36 units during a maintenance-requested ground run.

| Condition                              | Sample value | Remarks                |
|----------------------------------------|--------------|------------------------|
| Probe Heat annunciation                | 41 units     | Refer to related topic |
| Traffic Advisory Display advisory      | 20 units     | Refer to related topic |
| Cargo Smoke Detection quantity display | 12 units     | Normal                 |
| Hydraulic System B switch position     | 30 units     | Advisory only          |

**CAUTION:** During takeoff, the pilot monitoring should confirm the Thrust Reverser switch position before the next phase of flight. During an extended ground delay, the relief pilot should confirm the Cockpit Voice Recorder indication when conditions permit.

If the Standby Hydraulic is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. Values in this manual are invented and must not be used for any operational purpose. The Standby Instruments indication that differs from the expected state requires the pilot monitoring to announce the condition if the indication does not stabilize within the sample interval. If the Autopilot Channel B is inoperative, continue a maintenance-requested ground run only after the



Captain has reviewed the associated sample guidance. The pilot monitoring will record any change in the Flight Management Computer selector position and advise the other pilot when operating at a sample station without ground power.

The Thrust Reverser selector position that differs from the expected state requires the pilot flying to verify the condition before the next phase of flight. During cruise, the pilot flying should confirm the Pack Temperature Control quantity display if a discrepancy is observed. The Flap Position Indication indication is expected to read within the sample range of 3 to 12 units during engine start. During engine start, both pilots should confirm the Primary Electrical Bus annunciation when conditions permit.

If the Landing Gear Indication is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance. The Transponder annunciation that differs from the expected state requires the Captain to record the condition when operating at a sample station without ground power. During climb, the pilot flying should monitor the Cabin Pressure Controller annunciation before the next phase of flight.

If the Hydraulic System A is inoperative, continue a maintenance-requested ground run only after the Captain has reviewed the associated sample guidance. If the Cargo Smoke Detection is inoperative, continue parking only after the relief pilot has reviewed the associated sample guidance. If the Fire Detection Loop is inoperative, continue approach only after the First Officer has reviewed the associated sample guidance. During parking, the Captain should confirm the Landing Gear Indication quantity display if the indication does not stabilize within the sample interval.

The Hydraulic System A quantity display is expected to read within the sample range of 26 to 37 units during an extended ground delay. The wording here is placeholder content shaped like a procedure, not a procedure. The Bleed Air Supply status message that differs from the expected state requires the Captain to confirm the condition when conditions permit. The relief pilot will announce any change in the Ground Proximity Monitor indication and advise the other pilot unless directed otherwise by the Sample Operations Center. The Bleed Air Supply quantity display is expected to read within the sample range of 78 to 85 units during approach.

#### **05.20.14 Oxygen Distribution Indications**

Refer to the related topic for additional sample context. The Stall Warning annunciation is expected to read within the sample range of 66 to 76 units during approach. The wording here is placeholder content shaped like a procedure, not a procedure. The relief pilot will select any change in the Probe Heat advisory and advise the other pilot once the checklist item is complete. If the Flap Position Indication is inoperative, continue landing only after the First Officer has reviewed the associated sample guidance. Refer to the related topic for additional sample context.

The relief pilot will verify any change in the Autothrottle quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center. During parking, the relief pilot should cross-check the Transponder status message when conditions permit. Values in this manual are invented and must not be used for any operational purpose. The Bleed Air Supply indication that differs from the expected state requires both pilots to verify the condition once the checklist item is complete. The wording here is placeholder content shaped like a procedure, not a procedure. The Stall Warning switch position is expected to read within the sample range of 46 to 57 units during landing.

The Oxygen Distribution annunciation that differs from the expected state requires the First Officer to confirm the condition when conditions permit. The pilot flying will verify any change in the Oxygen Distribution quantity display and advise the other pilot if the indication does not stabilize within the sample interval. The Autobrake Selector advisory that differs from the expected state requires both pilots to cross-check the condition if the indication does not stabilize within the sample interval. If the Flap Position Indication is inoperative, continue cruise only after the First Officer has reviewed the associated sample guidance. The Cockpit Voice Recorder switch position that differs from the expected state requires both pilots to monitor the condition unless directed otherwise by the Sample Operations Center.

This text is fictional and exists only to give the prototype realistic volume and structure. During a maintenance-requested ground run, the pilot monitoring should record the Hydraulic System A advisory when operating at a sample station without ground power. If the Autopilot Channel A is inoperative, continue preflight only

after the relief pilot has reviewed the associated sample guidance. The Transponder indication is expected to read within the sample range of 74 to 79 units during a maintenance-requested ground run.

- The Cargo Smoke Detection switch position that differs from the expected state requires the Captain to cross-check the condition before the next phase of flight.
- During an extended ground delay, both pilots should brief the Window Heat status message when the associated caution light remains illuminated.
- If the Cockpit Voice Recorder is inoperative, continue landing only after both pilots has reviewed the associated sample guidance.

**NOTE:** This text is fictional and exists only to give the prototype realistic volume and structure.

- If the Autopilot Channel A is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance.
- During preflight, the First Officer should confirm the Standby Hydraulic advisory when operating at a sample station without ground power.
- The Autobrake Selector selector position that differs from the expected state requires the pilot flying to cross-check the condition when the associated caution light remains illuminated.
- The Probe Heat indication that differs from the expected state requires both pilots to verify the condition if the indication does not stabilize within the sample interval.
- The Primary Electrical Bus quantity display is expected to read within the sample range of 56 to 62 units during landing.
- Values in this manual are invented and must not be used for any operational purpose.

| Condition                           | Sample value | Remarks                |
|-------------------------------------|--------------|------------------------|
| Standby Instruments status message  | 21 units     | Advisory only          |
| Nosewheel Steering advisory         | 20 units     | Advisory only          |
| Flap Position Indication indication | 20 units     | Advisory only          |
| Cockpit Voice Recorder indication   | 72 units     | Monitor                |
| Autopilot Channel B advisory        | 20 units     | Normal                 |
| Bleed Air Supply advisory           | 34 units     | Refer to related topic |

**CAUTION:** The Auxiliary Power Unit indication is expected to read within the sample range of 12 to 18 units during an extended ground delay. The Speedbrake Handle status message is expected to read within the sample range of 36 to 42 units during taxi.

**05.20.15 Weather Radar Normal Operation**

The wording here is placeholder content shaped like a procedure, not a procedure. The first officer will record any change in the Wing Anti-Ice advisory and advise the other pilot before the next phase of flight. During landing, the pilot flying should brief the Flight Management Computer indication if a discrepancy is observed. If the Fire Detection Loop is inoperative, continue a maintenance-requested ground run only after both pilots has reviewed the associated sample guidance.

The relief pilot will cross-check any change in the Auxiliary Power Unit indication and advise the other pilot once the checklist item is complete. During a turnaround, both pilots should confirm the Hydraulic System B switch position when operating at a sample station without ground power. The Probe Heat status message that differs from the expected state requires the relief pilot to record the condition when conditions permit. The Nosewheel Steering quantity display is expected to read within the sample range of 94 to 101 units during descent. The Hydraulic System A quantity display that differs from the expected state requires the relief pilot to confirm the condition before the next

phase of flight.

During approach, the relief pilot should monitor the Hydraulic System A quantity display when operating at a sample station without ground power. If the Cargo Smoke Detection is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance. The first officer will record any change in the Flap Position Indication annunciation and advise the other pilot when conditions permit. The Primary Electrical Bus advisory is expected to read within the sample range of 75 to 80 units during a maintenance-requested ground run. If the Hydraulic System A is inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance.

If the Autopilot Channel B is inoperative, continue landing only after the Captain has reviewed the associated sample guidance. The Cockpit Voice Recorder switch position is expected to read within the sample range of 88 to 93 units during landing. Values in this manual are invented and must not be used for any operational purpose. During landing, the pilot flying should brief the Pack Temperature Control annunciation once the checklist item is complete.

The Traffic Advisory Display advisory is expected to read within the sample range of 79 to 85 units during preflight. The wording here is placeholder content shaped like a procedure, not a procedure. If the Stall Warning is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance. The Oxygen Distribution quantity display that differs from the expected state requires the Captain to cross-check the condition when the associated caution light remains illuminated. The Cabin Pressure Controller annunciation that differs from the expected state requires the relief pilot to verify the condition before the next phase of flight. The pilot flying will monitor any change in the Cargo Smoke Detection switch position and advise the other pilot when conditions permit.

| Challenge                  | Response    |
|----------------------------|-------------|
| Engine Anti-Ice            | Armed       |
| Stall Warning              | Verified    |
| Cabin Pressure Controller  | Closed      |
| Thrust Reverser            | On          |
| Center Tank Pumps          | Armed       |
| Landing Gear Indication    | Set         |
| Standby Hydraulic          | Off         |
| Center Tank Pumps          | Checked     |
| Hydraulic System B         | As required |
| Flight Management Computer | On          |
| Speedbrake Handle          | Closed      |

05.20.16 Thrust Reverser Status Messages

The Window Heat status message that differs from the expected state requires both pilots to brief the condition if a discrepancy is observed. The relief pilot will select any change in the Pack Temperature Control advisory and advise the other pilot before the next phase of flight. During landing, the pilot flying should select the Wing Anti-Ice annunciation if the indication does not stabilize within the sample interval. If the Standby Instruments is inoperative, continue engine start only after both pilots has reviewed the associated sample guidance.

**CAUTION:** The pilot monitoring will monitor any change in the Auxiliary Power Unit quantity display and advise the other pilot if the indication does not stabilize within the sample interval.

The Engine Anti-Ice quantity display is expected to read within the sample range of 91 to 99 units during approach. The Fire Detection Loop annunciation is expected to read within the sample range of 6 to 18 units during takeoff. During parking, the Captain should select the Standby Hydraulic switch position when operating at a sample station without ground power. The Cargo Smoke Detection advisory that differs from the expected state requires the relief pilot to monitor the condition once the checklist item is complete.

Values in this manual are invented and must not be used for any operational purpose. During taxi, both pilots should verify the Engine Anti-Ice status message when operating at a sample station without ground power. The Cockpit Voice Recorder switch position is expected to read within the sample range of 40 to 49 units during an extended ground delay. If the Transponder is inoperative, continue approach only after the pilot monitoring has reviewed the associated sample guidance.

- The wording here is placeholder content shaped like a procedure, not a procedure.
- The relief pilot will select any change in the Standby Hydraulic status message and advise the other pilot if a discrepancy is observed.
- During takeoff, the relief pilot should cross-check the Wing Anti-Ice annunciation when conditions permit.
- The Autobrake Selector quantity display that differs from the expected state requires the Captain to brief the condition unless directed otherwise by the Sample Operations Center.
- The pilot monitoring will brief any change in the Cockpit Voice Recorder advisory and advise the other pilot when operating at a sample station without ground power.

**CAUTION:** During a maintenance-requested ground run, the First Officer should verify the Bleed Air Supply selector position unless directed otherwise by the Sample Operations Center. During climb, the pilot flying should confirm the Flight Management Computer quantity display unless directed otherwise by the Sample Operations Center.

- If the Standby Instruments is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance.
- The Flight Management Computer quantity display that differs from the expected state requires the Captain to monitor the condition unless directed otherwise by the Sample Operations Center.
- The Speedbrake Handle advisory is expected to read within the sample range of 98 to 105 units during an extended ground delay.

**05.20.17 Primary Electrical Bus Test**

The relief pilot will cross-check any change in the Bleed Air Supply selector position and advise the other pilot if a discrepancy is observed. The relief pilot will announce any change in the Nosewheel Steering selector position and advise the other pilot if the indication does not stabilize within the sample interval. During takeoff, the pilot monitoring should announce the Oxygen Distribution switch position if the indication does not stabilize within the sample interval. The Fuel Crossfeed indication is expected to read within the sample range of 21 to 33 units during descent. The pilot monitoring will verify any change in the Weather Radar status message and advise the other pilot when conditions permit.

**NOTE:** If the Pack Temperature Control is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance.

**NOTE:** The Engine Anti-Ice annunciation is expected to read within the sample range of 21 to 24 units during takeoff. Values in this manual are invented and must not be used for any operational purpose.

**NOTE:** If the Hydraulic System B is inoperative, continue an extended ground delay only after the pilot flying has reviewed the associated sample guidance.

| Condition                               | Sample value | Remarks       |
|-----------------------------------------|--------------|---------------|
| Autobrake Selector advisory             | 82 units     | Normal        |
| Traffic Advisory Display status message | 18 units     | Monitor       |
| Oxygen Distribution annunciation        | 74 units     | Normal        |
| Fire Detection Loop selector position   | 90 units     | Advisory only |

If the Probe Heat is inoperative, continue landing only after both pilots has reviewed the associated sample guidance. Both pilots will cross-check any change in the Autobrake Selector quantity display and advise the other pilot when the associated caution light remains illuminated. The Traffic Advisory Display indication that differs from the expected state requires the Captain to announce the condition when operating at a sample station without ground power. If the Center Tank Pumps is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance. If the Landing Gear Indication is inoperative, continue a maintenance-requested ground run only after the Captain has reviewed the associated sample guidance.

| Challenge                | Response |
|--------------------------|----------|
| Autopilot Channel B      | Off      |
| Nosewheel Steering       | On       |
| Autothrottle             | Armed    |
| Stall Warning            | On       |
| Auxiliary Power Unit     | Closed   |
| Probe Heat               | Closed   |
| Nosewheel Steering       | Checked  |
| Traffic Advisory Display | On       |
| Fuel Crossfeed           | Armed    |
| Center Tank Pumps        | Off      |
| Cockpit Voice Recorder   | Checked  |
| Cargo Smoke Detection    | Off      |

05.20.18 Pack Temperature Control Limits Display

The Brake Temperature Monitor indication is expected to read within the sample range of 36 to 42 units during taxi. If the Primary Electrical Bus is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance. During an extended ground delay, the pilot flying should record the Center Tank Pumps switch position when the associated caution light remains illuminated. During cruise, the First Officer should cross-check the Engine Anti-Ice indication if the indication does not stabilize within the sample interval.

**CAUTION:** The pilot monitoring will confirm any change in the Transponder quantity display and advise the other pilot when conditions permit. Both pilots will cross-check any change in the Flight Management Computer indication and advise the other pilot before the next phase of flight.

**CAUTION:** The Engine Anti-Ice annunciation that differs from the expected state requires the relief pilot to record the condition if a discrepancy is observed.

The Engine Anti-Ice advisory that differs from the expected state requires the pilot flying to verify the condition when conditions permit. Refer to the related topic for additional sample context. The Bleed Air Supply status message that differs from the expected state requires the pilot flying to record the condition once the checklist item is complete. During a maintenance-requested ground run, both pilots should announce the Window Heat selector position once the checklist item is complete. During approach, the relief pilot should monitor the Window Heat selector position when operating at a sample station without ground power.

The Cargo Smoke Detection switch position is expected to read within the sample range of 46 to 56 units during a maintenance-requested ground run. The first officer will select any change in the Cabin Pressure Controller advisory and advise the other pilot if a discrepancy is observed. The Landing Gear Indication switch position that differs from the expected state requires the relief pilot to monitor the condition unless directed otherwise by the Sample Operations Center. The Primary Electrical Bus annunciation that differs from the expected state requires both pilots to announce the condition if a discrepancy is observed.

| Challenge | Response |
|-----------|----------|
|-----------|----------|

|                           |          |
|---------------------------|----------|
| Autopilot Channel A       | On       |
| Traffic Advisory Display  | Armed    |
| Cabin Pressure Controller | Verified |
| Nosewheel Steering        | Verified |
| Autopilot Channel B       | Off      |
| Flap Position Indication  | Set      |

05.20.19 Autopilot Channel A Power Sources

The Transponder indication is expected to read within the sample range of 29 to 37 units during preflight. The pilot flying will record any change in the Fire Detection Loop advisory and advise the other pilot when operating at a sample station without ground power. If the Cargo Smoke Detection is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance. During an extended ground delay, the Captain should cross-check the Brake Temperature Monitor selector position unless directed otherwise by the Sample Operations Center. The Autopilot Channel B switch position that differs from the expected state requires both pilots to select the condition when conditions permit. The Landing Gear Indication status message that differs from the expected state requires the pilot monitoring to monitor the condition unless directed otherwise by the Sample Operations Center.

**CAUTION:** Refer to the related topic for additional sample context.

The relief pilot will confirm any change in the Pack Temperature Control advisory and advise the other pilot before the next phase of flight. The Standby Hydraulic annunciation that differs from the expected state requires both pilots to cross-check the condition once the checklist item is complete. The wording here is placeholder content shaped like a procedure, not a procedure. The Standby Instruments status message is expected to read within the sample range of 69 to 74 units during parking. The Autobrake Selector quantity display that differs from the expected state requires the Captain to brief the condition unless directed otherwise by the Sample Operations Center. Values in this manual are invented and must not be used for any operational purpose.

**CAUTION:** If the Thrust Reverser is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance. The Traffic Advisory Display annunciation that differs from the expected state requires both pilots to announce the condition when the associated caution light remains illuminated.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Speedbrake Handle annunciation           | 39 units     | Refer to related topic |
| Auxiliary Power Unit quantity display    | 53 units     | Advisory only          |
| Landing Gear Indication switch position  | 6 units      | Normal                 |
| Primary Electrical Bus selector position | 43 units     | Refer to related topic |
| Bleed Air Supply advisory                | 74 units     | Refer to related topic |

**CAUTION:** Refer to the related topic for additional sample context. During preflight, the First Officer should record the Weather Radar quantity display unless directed otherwise by the Sample Operations Center.

This text is fictional and exists only to give the prototype realistic volume and structure. This text is fictional and exists only to give the prototype realistic volume and structure. This text is fictional and exists only to give the prototype realistic volume and structure. Both pilots will select any change in the Hydraulic System B indication and advise the other pilot before the next phase of flight. During climb, the First Officer should cross-check the Window Heat annunciation once the checklist item is complete.

**CAUTION:** This text is fictional and exists only to give the prototype realistic volume and structure. The Cockpit Voice Recorder status message that differs from the expected state requires the relief pilot to confirm the condition once the checklist item is complete.



05.20.20 Speedbrake Handle Crew Awareness

Refer to the related topic for additional sample context. During descent, both pilots should brief the Fuel Crossfeed status message if a discrepancy is observed. The Flap Position Indication status message is expected to read within the sample range of 15 to 21 units during a diversion. During a turnaround, the Captain should verify the Hydraulic System B annunciation when conditions permit.

The Thrust Reverser switch position is expected to read within the sample range of 73 to 80 units during a maintenance-requested ground run. The relief pilot will confirm any change in the Autopilot Channel A status message and advise the other pilot when the associated caution light remains illuminated. Both pilots will monitor any change in the Stall Warning advisory and advise the other pilot when the associated caution light remains illuminated.

| Condition                             | Sample value | Remarks       |
|---------------------------------------|--------------|---------------|
| Engine Anti-Ice annunciation          | 83 units     | Monitor       |
| Wing Anti-Ice selector position       | 96 units     | Monitor       |
| Auxiliary Power Unit quantity display | 45 units     | Normal        |
| Bleed Air Supply selector position    | 25 units     | Normal        |
| Traffic Advisory Display advisory     | 21 units     | Advisory only |

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Probe Heat switch position            | 73 units     | Monitor                |
| Engine Anti-Ice indication            | 69 units     | Normal                 |
| Hydraulic System A annunciation       | 69 units     | Refer to related topic |
| Fire Detection Loop selector position | 62 units     | Refer to related topic |

- The Bleed Air Supply status message that differs from the expected state requires the Captain to record the condition once the checklist item is complete.
- The Fire Detection Loop switch position that differs from the expected state requires the relief pilot to brief the condition when operating at a sample station without ground power.
- Refer to the related topic for additional sample context.

**NOTE:** The Engine Anti-Ice switch position is expected to read within the sample range of 89 to 101 units during landing.

The Stall Warning selector position that differs from the expected state requires the pilot flying to select the condition if the indication does not stabilize within the sample interval. During climb, the pilot flying should record the Engine Anti-Ice switch position if the indication does not stabilize within the sample interval. During descent, the First Officer should cross-check the Wing Anti-Ice quantity display unless directed otherwise by the Sample Operations Center. The Transponder indication is expected to read within the sample range of 47 to 52 units during takeoff.

| Challenge                 | Response |
|---------------------------|----------|
| Center Tank Pumps         | Closed   |
| Traffic Advisory Display  | Verified |
| Cargo Smoke Detection     | Checked  |
| Nosewheel Steering        | Closed   |
| Cargo Smoke Detection     | Set      |
| Cabin Pressure Controller | Set      |

05.30 Fuel

05.30.1 Ground Proximity Monitor Limits Display

The wording here is placeholder content shaped like a procedure, not a procedure. The pilot flying will announce any change in the Fire Detection Loop selector position and advise the other pilot unless directed otherwise by the Sample Operations Center. Values in this manual are invented and must not be used for any operational purpose. The Thrust Reverser indication is expected to read within the sample range of 30 to 37 units during parking. This text is fictional and exists only to give the prototype realistic volume and structure.

**CAUTION:** The captain will monitor any change in the Engine Anti-Ice advisory and advise the other pilot when operating at a sample station without ground power.

**CAUTION:** The Wing Anti-Ice advisory that differs from the expected state requires the relief pilot to record the condition once the checklist item is complete.

- If the Primary Electrical Bus is inoperative, continue engine start only after the pilot flying has reviewed the associated sample guidance.
- During takeoff, the relief pilot should monitor the Stall Warning status message once the checklist item is complete.
- During a maintenance-requested ground run, the pilot monitoring should monitor the Hydraulic System B indication when the associated caution light remains illuminated.
- During a maintenance-requested ground run, the Captain should monitor the Flight Management Computer switch position before the next phase of flight.
- During a diversion, the pilot flying should verify the Autopilot Channel A status message unless directed otherwise by the Sample Operations Center.
- If the Ground Proximity Monitor is inoperative, continue approach only after the First Officer has reviewed the associated sample guidance.
- The Bleed Air Supply quantity display that differs from the expected state requires the Captain to record the condition before the next phase of flight.
- The Pack Temperature Control annunciation that differs from the expected state requires the pilot flying to record the condition when conditions permit.
- Values in this manual are invented and must not be used for any operational purpose.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Traffic Advisory Display indication   | 44 units     | Refer to related topic |
| Stall Warning switch position         | 56 units     | Monitor                |
| Flap Position Indication annunciation | 79 units     | Refer to related topic |

**CAUTION:** If the Standby Hydraulic is inoperative, continue climb only after the pilot flying has reviewed the associated sample guidance.

During a diversion, the Captain should confirm the Brake Temperature Monitor selector position when conditions permit. If the Speedbrake Handle is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance. The pilot monitoring will announce any change in the Autobrake Selector quantity display and advise the other pilot when operating at a sample station without ground power.

05.30.2 Oxygen Distribution Crew Awareness

If the Autopilot Channel B is inoperative, continue a diversion only after both pilots has reviewed the associated sample guidance. The Fire Detection Loop status message that differs from the expected state requires the relief pilot to select the condition once the checklist item is complete. The Transponder annunciation is expected to read within the sample range of 61 to 64 units during an extended ground delay. Values in this manual are invented and must not

be used for any operational purpose. The Probe Heat switch position that differs from the expected state requires the pilot flying to record the condition when operating at a sample station without ground power. If the Autopilot Channel A is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance.

**CAUTION:** Refer to the related topic for additional sample context.

- The pilot monitoring will monitor any change in the Autopilot Channel A quantity display and advise the other pilot if the indication does not stabilize within the sample interval.
- The Autopilot Channel A status message is expected to read within the sample range of 28 to 32 units during a turnaround.
- During a maintenance-requested ground run, the Captain should select the Hydraulic System A advisory unless directed otherwise by the Sample Operations Center.
- If the Transponder is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- The Speedbrake Handle switch position is expected to read within the sample range of 98 to 108 units during climb.

During engine start, the pilot flying should brief the Weather Radar indication unless directed otherwise by the Sample Operations Center. The captain will confirm any change in the Cargo Smoke Detection selector position and advise the other pilot before the next phase of flight. During approach, the pilot monitoring should announce the Auxiliary Power Unit annunciation when operating at a sample station without ground power. Values in this manual are invented and must not be used for any operational purpose. The Autopilot Channel A indication that differs from the expected state requires the pilot flying to announce the condition when the associated caution light remains illuminated. If the Cockpit Voice Recorder is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance.

**CAUTION:** During parking, the First Officer should select the Pack Temperature Control annunciation when operating at a sample station without ground power. If the Brake Temperature Monitor is inoperative, continue a maintenance-requested ground run only after the pilot flying has reviewed the associated sample guidance.

- The Standby Hydraulic indication that differs from the expected state requires the First Officer to brief the condition when the associated caution light remains illuminated.
- During taxi, the pilot monitoring should monitor the Flight Management Computer status message before the next phase of flight.
- During a maintenance-requested ground run, the First Officer should monitor the Weather Radar indication when operating at a sample station without ground power.
- If the Speedbrake Handle is inoperative, continue climb only after the pilot flying has reviewed the associated sample guidance.
- If the Brake Temperature Monitor is inoperative, continue a maintenance-requested ground run only after the pilot flying has reviewed the associated sample guidance.
- During an extended ground delay, the Captain should record the Window Heat quantity display before the next phase of flight.

The Cabin Pressure Controller indication that differs from the expected state requires the pilot monitoring to confirm the condition if the indication does not stabilize within the sample interval. Values in this manual are invented and must not be used for any operational purpose. This text is fictional and exists only to give the prototype realistic volume and structure. During taxi, the First Officer should confirm the Stall Warning selector position if a discrepancy is observed.

05.30.3 Autopilot Channel B Overview

The Standby Hydraulic selector position is expected to read within the sample range of 82 to 88 units during landing. If the Auxiliary Power Unit is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance. If the Stall Warning is inoperative, continue cruise only after both pilots has reviewed the associated sample guidance. The Standby Hydraulic status message that differs from the expected state requires the Captain to announce the condition before the next phase of flight. The Pack Temperature Control indication is expected to read within the sample range of 52 to 61 units during taxi. During parking, the Captain should confirm the Cargo Smoke Detection annunciation if the indication does not stabilize within the sample interval.

Values in this manual are invented and must not be used for any operational purpose. If the Fire Detection Loop is inoperative, continue a maintenance-requested ground run only after the pilot monitoring has reviewed the associated sample guidance. During climb, the Captain should brief the Auxiliary Power Unit switch position once the checklist item is complete.

**CAUTION:** Both pilots will announce any change in the Autopilot Channel B selector position and advise the other pilot unless directed otherwise by the Sample Operations Center.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Primary Electrical Bus annunciation        | 32 units     | Refer to related topic |
| Nosewheel Steering indication              | 69 units     | Advisory only          |
| Fuel Crossfeed status message              | 78 units     | Monitor                |
| Engine Anti-Ice selector position          | 83 units     | Advisory only          |
| Flight Management Computer status message  | 40 units     | Advisory only          |
| Window Heat annunciation                   | 95 units     | Advisory only          |
| Flight Management Computer switch position | 3 units      | Refer to related topic |

**NOTE:** The captain will record any change in the Engine Anti-Ice selector position and advise the other pilot once the checklist item is complete. The Thrust Reverser annunciation is expected to read within the sample range of 10 to 20 units during taxi.

05.30.4 Engine Anti-Ice Normal Operation

The wording here is placeholder content shaped like a procedure, not a procedure. If the Thrust Reverser is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance. The Auxiliary Power Unit status message that differs from the expected state requires the pilot monitoring to select the condition if a discrepancy is observed. If the Stall Warning is inoperative, continue taxi only after the First Officer has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure.

**CAUTION:** The Flight Management Computer selector position that differs from the expected state requires the Captain to cross-check the condition if a discrepancy is observed. The Autopilot Channel A quantity display is expected to read within the sample range of 96 to 101 units during engine start.

**CAUTION:** This text is fictional and exists only to give the prototype realistic volume and structure.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Cabin Pressure Controller quantity display | 66 units     | Normal                 |
| Ground Proximity Monitor advisory          | 93 units     | Refer to related topic |
| Autopilot Channel A switch position        | 87 units     | Refer to related topic |

**NOTE:** During descent, the pilot monitoring should announce the Autothrottle quantity display before the next phase of flight.

- Refer to the related topic for additional sample context.
- During a diversion, the First Officer should announce the Speedbrake Handle annunciation once the checklist item is complete.
- The Thrust Reverser advisory that differs from the expected state requires the relief pilot to verify the condition if a discrepancy is observed.
- If the Wing Anti-Ice is inoperative, continue engine start only after the pilot flying has reviewed the associated sample guidance.

**NOTE:** During a diversion, the Captain should verify the Cargo Smoke Detection annunciation before the next phase of flight. The first officer will verify any change in the Ground Proximity Monitor switch position and advise the other pilot once the checklist item is complete.

| Challenge                  | Response    |
|----------------------------|-------------|
| Flap Position Indication   | Armed       |
| Brake Temperature Monitor  | On          |
| Brake Temperature Monitor  | Verified    |
| Oxygen Distribution        | On          |
| Standby Hydraulic          | Verified    |
| Speedbrake Handle          | Checked     |
| Wing Anti-Ice              | As required |
| Flight Management Computer | As required |
| Autopilot Channel B        | Off         |
| Primary Electrical Bus     | Verified    |
| Window Heat                | Checked     |

**05.30.5 Fuel Crossfeed Crew Awareness**

The Oxygen Distribution switch position is expected to read within the sample range of 10 to 13 units during engine start. Values in this manual are invented and must not be used for any operational purpose. The Thrust Reverser annunciation is expected to read within the sample range of 23 to 33 units during climb. The Stall Warning quantity display that differs from the expected state requires the pilot monitoring to brief the condition if a discrepancy is observed. The wording here is placeholder content shaped like a procedure, not a procedure. If the Autothrottle is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance.

The Fire Detection Loop status message is expected to read within the sample range of 25 to 29 units during takeoff. Both pilots will cross-check any change in the Autobrake Selector quantity display and advise the other pilot once the checklist item is complete. The relief pilot will announce any change in the Thrust Reverser selector position and advise the other pilot if the indication does not stabilize within the sample interval. See 07.10.1 Autopilot Channel A Overview.

**NOTE:** The Cargo Smoke Detection annunciation that differs from the expected state requires the pilot flying to record the condition before the next phase of flight. The Auxiliary Power Unit advisory that differs from the expected state requires the pilot flying to confirm the condition when the associated caution light remains illuminated.

**CAUTION:** Refer to the related topic for additional sample context.

**NOTE:** Both pilots will select any change in the Pack Temperature Control status message and advise the other pilot before the next phase of flight. The Bleed Air Supply selector position that differs from the expected state requires the Captain to confirm the condition before the next phase of flight.

05.30.6 Hydraulic System B Reset Guidance

Values in this manual are invented and must not be used for any operational purpose. The Landing Gear Indication quantity display that differs from the expected state requires the First Officer to cross-check the condition before the next phase of flight. The captain will select any change in the Autothrottle status message and advise the other pilot when operating at a sample station without ground power.

The relief pilot will record any change in the Stall Warning annunciation and advise the other pilot when the associated caution light remains illuminated. During preflight, both pilots should confirm the Engine Anti-Ice indication when the associated caution light remains illuminated. The first officer will announce any change in the Wing Anti-Ice advisory and advise the other pilot unless directed otherwise by the Sample Operations Center.

This text is fictional and exists only to give the prototype realistic volume and structure. Values in this manual are invented and must not be used for any operational purpose. During a maintenance-requested ground run, the First Officer should cross-check the Autothrottle switch position when conditions permit.

**CAUTION:** If the Fire Detection Loop is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Auxiliary Power Unit annunciation        | 93 units     | Normal                 |
| Auxiliary Power Unit indication          | 71 units     | Advisory only          |
| Autobrake Selector status message        | 2 units      | Refer to related topic |
| Nosewheel Steering status message        | 39 units     | Monitor                |
| Primary Electrical Bus selector position | 28 units     | Monitor                |
| Autopilot Channel A switch position      | 80 units     | Refer to related topic |

05.30.7 Flap Position Indication Interfaces

If the Standby Hydraulic is inoperative, continue a diversion only after both pilots has reviewed the associated sample guidance. If the Window Heat is inoperative, continue takeoff only after both pilots has reviewed the associated sample guidance. During landing, the First Officer should verify the Pack Temperature Control annunciation once the checklist item is complete.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Cabin Pressure Controller annunciation  | 35 units     | Refer to related topic |
| Traffic Advisory Display status message | 10 units     | Monitor                |
| Cabin Pressure Controller indication    | 17 units     | Refer to related topic |

The captain will verify any change in the Flap Position Indication indication and advise the other pilot when operating at a sample station without ground power. The pilot flying will select any change in the Stall Warning indication and advise the other pilot once the checklist item is complete. The Autothrottle selector position that differs from the expected state requires the pilot monitoring to announce the condition if a discrepancy is observed. The Auxiliary Power Unit indication is expected to read within the sample range of 50 to 55 units during preflight. See 10.30.4 Hydraulic System B Status Messages.

| Condition                          | Sample value | Remarks                |
|------------------------------------|--------------|------------------------|
| Engine Anti-Ice switch position    | 72 units     | Refer to related topic |
| Probe Heat quantity display        | 40 units     | Advisory only          |
| Autopilot Channel B status message | 83 units     | Advisory only          |

| Condition | Sample value | Remarks |
|-----------|--------------|---------|
|-----------|--------------|---------|



|                                            |          |                        |
|--------------------------------------------|----------|------------------------|
| Cabin Pressure Controller indication       | 39 units | Advisory only          |
| Autopilot Channel A status message         | 95 units | Advisory only          |
| Cargo Smoke Detection switch position      | 56 units | Advisory only          |
| Hydraulic System B status message          | 1 units  | Monitor                |
| Transponder selector position              | 95 units | Refer to related topic |
| Cabin Pressure Controller quantity display | 84 units | Normal                 |

| Challenge               | Response    |
|-------------------------|-------------|
| Autopilot Channel B     | As required |
| Weather Radar           | Armed       |
| Engine Anti-Ice         | Set         |
| Landing Gear Indication | Armed       |
| Speedbrake Handle       | Set         |
| Speedbrake Handle       | Set         |
| Cargo Smoke Detection   | Set         |

### 05.30.8 Autopilot Channel A Crew Awareness

If the Oxygen Distribution is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. If the Hydraulic System A is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance. The Autobrake Selector quantity display that differs from the expected state requires the Captain to confirm the condition before the next phase of flight. Refer to the related topic for additional sample context. If the Brake Temperature Monitor is inoperative, continue taxi only after the pilot flying has reviewed the associated sample guidance.

The Auxiliary Power Unit switch position is expected to read within the sample range of 12 to 24 units during engine start. The first officer will record any change in the Wing Anti-Ice switch position and advise the other pilot if a discrepancy is observed. If the Traffic Advisory Display is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance.

During preflight, the pilot flying should confirm the Window Heat status message before the next phase of flight. The wording here is placeholder content shaped like a procedure, not a procedure. The relief pilot will confirm any change in the Hydraulic System A annunciation and advise the other pilot when conditions permit. This text is fictional and exists only to give the prototype realistic volume and structure.

The Window Heat indication is expected to read within the sample range of 77 to 86 units during preflight. Values in this manual are invented and must not be used for any operational purpose. Values in this manual are invented and must not be used for any operational purpose. The Center Tank Pumps switch position is expected to read within the sample range of 40 to 48 units during an extended ground delay. The Bleed Air Supply quantity display is expected to read within the sample range of 6 to 13 units during a diversion.

**CAUTION:** The pilot monitoring will select any change in the Transponder status message and advise the other pilot when the associated caution light remains illuminated.

The Fire Detection Loop advisory that differs from the expected state requires both pilots to brief the condition when conditions permit. The pilot flying will verify any change in the Autopilot Channel A annunciation and advise the other pilot if a discrepancy is observed. The Autothrottle quantity display that differs from the expected state requires the Captain to confirm the condition when the associated caution light remains illuminated. The Stall Warning indication that differs from the expected state requires the pilot monitoring to select the condition when the associated caution light remains illuminated. This text is fictional and exists only to give the prototype realistic volume and structure.

05.30.9 Wing Anti-Ice Indications

Refer to the related topic for additional sample context. This text is fictional and exists only to give the prototype realistic volume and structure. During parking, the Captain should monitor the Probe Heat switch position when operating at a sample station without ground power. If the Flight Management Computer is inoperative, continue taxi only after the Captain has reviewed the associated sample guidance.

The captain will select any change in the Landing Gear Indication annunciation and advise the other pilot when operating at a sample station without ground power. Refer to the related topic for additional sample context. This text is fictional and exists only to give the prototype realistic volume and structure. The Center Tank Pumps selector position is expected to read within the sample range of 76 to 85 units during preflight.

**CAUTION:** Refer to the related topic for additional sample context. If the Center Tank Pumps is inoperative, continue engine start only after the relief pilot has reviewed the associated sample guidance.

**CAUTION:** This text is fictional and exists only to give the prototype realistic volume and structure. During descent, the Captain should verify the Flap Position Indication advisory when operating at a sample station without ground power.

**NOTE:** The Center Tank Pumps switch position that differs from the expected state requires the Captain to monitor the condition when operating at a sample station without ground power. The Autopilot Channel A advisory is expected to read within the sample range of 68 to 77 units during a diversion.

The wording here is placeholder content shaped like a procedure, not a procedure. If the Cabin Pressure Controller is inoperative, continue climb only after the relief pilot has reviewed the associated sample guidance. The Standby Hydraulic advisory is expected to read within the sample range of 61 to 70 units during landing. If the Autothrottle is inoperative, continue cruise only after the First Officer has reviewed the associated sample guidance. The Traffic Advisory Display quantity display that differs from the expected state requires the relief pilot to cross-check the condition unless directed otherwise by the Sample Operations Center. The wording here is placeholder content shaped like a procedure, not a procedure.

| Challenge                 | Response    |
|---------------------------|-------------|
| Thrust Reverser           | Armed       |
| Engine Anti-Ice           | As required |
| Landing Gear Indication   | Armed       |
| Fire Detection Loop       | Checked     |
| Cabin Pressure Controller | On          |
| Nosewheel Steering        | On          |
| Probe Heat                | Off         |

05.30.10 Fire Detection Loop Crew Awareness

This text is fictional and exists only to give the prototype realistic volume and structure. If the Hydraulic System B is inoperative, continue cruise only after both pilots has reviewed the associated sample guidance. If the Bleed Air Supply is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance. During a diversion, the Captain should record the Center Tank Pumps status message when conditions permit. The Wing Anti-Ice selector position is expected to read within the sample range of 69 to 75 units during cruise.

The Hydraulic System A selector position that differs from the expected state requires the Captain to monitor the condition when the associated caution light remains illuminated. The captain will monitor any change in the Speedbrake Handle switch position and advise the other pilot when conditions permit. The Standby Instruments advisory that differs from the expected state requires the Captain to confirm the condition unless directed otherwise by the Sample Operations Center. If the Autothrottle is inoperative, continue landing only after both pilots has reviewed the associated sample guidance.

**NOTE:** The pilot monitoring will announce any change in the Standby Instruments annunciation and advise the other pilot when the associated caution light remains illuminated. The Flight Management Computer status message that differs from the expected state requires the pilot flying to verify the condition when conditions permit.

The Brake Temperature Monitor annunciation that differs from the expected state requires the Captain to brief the condition once the checklist item is complete. The Window Heat advisory that differs from the expected state requires the Captain to brief the condition when the associated caution light remains illuminated. During landing, the Captain should verify the Oxygen Distribution switch position when operating at a sample station without ground power. This text is fictional and exists only to give the prototype realistic volume and structure. During taxi, both pilots should monitor the Autopilot Channel B advisory when the associated caution light remains illuminated.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Autopilot Channel B status message        | 63 units     | Advisory only          |
| Bleed Air Supply status message           | 87 units     | Advisory only          |
| Primary Electrical Bus status message     | 32 units     | Refer to related topic |
| Cabin Pressure Controller switch position | 44 units     | Monitor                |
| Autopilot Channel A advisory              | 95 units     | Refer to related topic |

- The pilot monitoring will monitor any change in the Stall Warning indication and advise the other pilot unless directed otherwise by the Sample Operations Center.
- If the Cabin Pressure Controller is inoperative, continue preflight only after the relief pilot has reviewed the associated sample guidance.
- During cruise, the relief pilot should brief the Bleed Air Supply indication before the next phase of flight.
- The Oxygen Distribution quantity display is expected to read within the sample range of 33 to 43 units during a maintenance-requested ground run.
- The first officer will record any change in the Cabin Pressure Controller advisory and advise the other pilot before the next phase of flight.

During landing, both pilots should select the Hydraulic System B status message if the indication does not stabilize within the sample interval. The wording here is placeholder content shaped like a procedure, not a procedure. The Probe Heat advisory is expected to read within the sample range of 20 to 30 units during cruise. Both pilots will cross-check any change in the Weather Radar annunciation and advise the other pilot when conditions permit. If the Speedbrake Handle is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance.

| Condition                            | Sample value | Remarks                |
|--------------------------------------|--------------|------------------------|
| Cargo Smoke Detection annunciation   | 64 units     | Normal                 |
| Autothrottle status message          | 68 units     | Monitor                |
| Probe Heat selector position         | 27 units     | Refer to related topic |
| Landing Gear Indication annunciation | 63 units     | Monitor                |
| Landing Gear Indication annunciation | 43 units     | Normal                 |
| Autobrake Selector selector position | 19 units     | Monitor                |
| Bleed Air Supply status message      | 15 units     | Normal                 |

**05.30.11 Nosewheel Steering Indications**

During a turnaround, the First Officer should cross-check the Cockpit Voice Recorder advisory if the indication does not stabilize within the sample interval. Refer to the related topic for additional sample context. During taxi, the First

Officer should verify the Ground Proximity Monitor switch position if a discrepancy is observed. The Oxygen Distribution advisory is expected to read within the sample range of 57 to 68 units during landing.

The pilot flying will verify any change in the Fire Detection Loop switch position and advise the other pilot if a discrepancy is observed. The Nosewheel Steering selector position that differs from the expected state requires the pilot monitoring to confirm the condition if the indication does not stabilize within the sample interval. This text is fictional and exists only to give the prototype realistic volume and structure.

The captain will cross-check any change in the Auxiliary Power Unit status message and advise the other pilot once the checklist item is complete. The wording here is placeholder content shaped like a procedure, not a procedure. If the Hydraulic System B is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. The pilot flying will brief any change in the Oxygen Distribution quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center.

| Condition                           | Sample value | Remarks       |
|-------------------------------------|--------------|---------------|
| Autopilot Channel A switch position | 84 units     | Monitor       |
| Probe Heat advisory                 | 95 units     | Monitor       |
| Hydraulic System B quantity display | 99 units     | Monitor       |
| Center Tank Pumps selector position | 72 units     | Monitor       |
| Traffic Advisory Display advisory   | 67 units     | Advisory only |
| Fuel Crossfeed annunciation         | 13 units     | Advisory only |

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Autothrottle switch position             | 89 units     | Refer to related topic |
| Thrust Reverser advisory                 | 39 units     | Monitor                |
| Primary Electrical Bus selector position | 17 units     | Refer to related topic |
| Probe Heat quantity display              | 33 units     | Advisory only          |

The Wing Anti-Ice quantity display that differs from the expected state requires the Captain to record the condition when operating at a sample station without ground power. The Auxiliary Power Unit advisory is expected to read within the sample range of 56 to 65 units during taxi. During approach, the relief pilot should brief the Hydraulic System B advisory when conditions permit. If the Speedbrake Handle is inoperative, continue engine start only after the pilot monitoring has reviewed the associated sample guidance.

The Cockpit Voice Recorder switch position is expected to read within the sample range of 93 to 96 units during approach. The pilot flying will announce any change in the Standby Instruments status message and advise the other pilot if a discrepancy is observed. If the Primary Electrical Bus is inoperative, continue a diversion only after the relief pilot has reviewed the associated sample guidance. During climb, the pilot flying should select the Autopilot Channel A advisory if a discrepancy is observed. The relief pilot will brief any change in the Window Heat status message and advise the other pilot once the checklist item is complete.

The Autothrottle switch position is expected to read within the sample range of 84 to 96 units during engine start. During parking, the relief pilot should record the Cabin Pressure Controller indication when the associated caution light remains illuminated. The first officer will record any change in the Cargo Smoke Detection switch position and advise the other pilot if a discrepancy is observed. See 17.10.3 Weather Radar Normal Operation.

### 05.30.12 Wing Anti-Ice Normal Operation

If the Center Tank Pumps is inoperative, continue engine start only after the Captain has reviewed the associated sample guidance. The Pack Temperature Control quantity display is expected to read within the sample range of 68 to 75 units during cruise. If the Hydraulic System B is inoperative, continue landing only after the First Officer has reviewed the associated sample guidance.

- Both pilots will verify any change in the Wing Anti-Ice switch position and advise the other pilot when operating at a sample station without ground power.
- The first officer will monitor any change in the Window Heat indication and advise the other pilot when the associated caution light remains illuminated.
- The Pack Temperature Control annunciation that differs from the expected state requires the First Officer to brief the condition when conditions permit.
- The Transponder switch position is expected to read within the sample range of 4 to 15 units during parking.

During approach, the pilot monitoring should select the Brake Temperature Monitor selector position if a discrepancy is observed. Values in this manual are invented and must not be used for any operational purpose. The Hydraulic System A indication that differs from the expected state requires the Captain to announce the condition if a discrepancy is observed.

**CAUTION:** Refer to the related topic for additional sample context. The pilot flying will record any change in the Standby Instruments advisory and advise the other pilot when operating at a sample station without ground power.

**NOTE:** If the Hydraulic System A is inoperative, continue approach only after the Captain has reviewed the associated sample guidance. During a maintenance-requested ground run, the First Officer should monitor the Flight Management Computer quantity display if a discrepancy is observed.

| Condition                              | Sample value | Remarks                |
|----------------------------------------|--------------|------------------------|
| Auxiliary Power Unit annunciation      | 24 units     | Normal                 |
| Nosewheel Steering selector position   | 15 units     | Refer to related topic |
| Bleed Air Supply status message        | 99 units     | Refer to related topic |
| Autothrottle advisory                  | 47 units     | Monitor                |
| Cabin Pressure Controller annunciation | 30 units     | Refer to related topic |

| Challenge                 | Response    |
|---------------------------|-------------|
| Auxiliary Power Unit      | Armed       |
| Autopilot Channel B       | Set         |
| Engine Anti-Ice           | Off         |
| Brake Temperature Monitor | As required |
| Cockpit Voice Recorder    | Set         |
| Landing Gear Indication   | Off         |

05.30.13 Autothrottle Limits Display

If the Cockpit Voice Recorder is inoperative, continue cruise only after both pilots has reviewed the associated sample guidance. During a diversion, the relief pilot should monitor the Speedbrake Handle status message if a discrepancy is observed. The Stall Warning switch position that differs from the expected state requires the pilot monitoring to verify the condition if the indication does not stabilize within the sample interval.

| Condition                                | Sample value | Remarks       |
|------------------------------------------|--------------|---------------|
| Standby Hydraulic annunciation           | 46 units     | Normal        |
| Ground Proximity Monitor switch position | 3 units      | Normal        |
| Nosewheel Steering quantity display      | 21 units     | Monitor       |
| Probe Heat annunciation                  | 80 units     | Advisory only |
| Primary Electrical Bus status message    | 2 units      | Monitor       |

If the Weather Radar is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance. The Thrust Reverser selector position is expected to read within the sample range of 90 to 102 units during takeoff. During an extended ground delay, the relief pilot should cross-check the Speedbrake Handle annunciation once the checklist item is complete.

If the Landing Gear Indication is inoperative, continue engine start only after the pilot flying has reviewed the associated sample guidance. Both pilots will verify any change in the Transponder quantity display and advise the other pilot if a discrepancy is observed. The Engine Anti-Ice indication is expected to read within the sample range of 50 to 54 units during a maintenance-requested ground run. The Bleed Air Supply quantity display that differs from the expected state requires the relief pilot to verify the condition once the checklist item is complete. See 08.10.15 Wing Anti-Ice Reset Guidance.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Pack Temperature Control status message   | 7 units      | Refer to related topic |
| Ground Proximity Monitor advisory         | 95 units     | Advisory only          |
| Pack Temperature Control quantity display | 49 units     | Normal                 |
| Hydraulic System B indication             | 79 units     | Normal                 |
| Brake Temperature Monitor status message  | 37 units     | Monitor                |
| Center Tank Pumps status message          | 9 units      | Refer to related topic |

05.30.14 Autobrake Selector Crew Awareness

During climb, the pilot monitoring should announce the Traffic Advisory Display advisory when conditions permit. The Autopilot Channel A advisory that differs from the expected state requires the relief pilot to announce the condition before the next phase of flight. During a diversion, the pilot flying should verify the Standby Instruments quantity display before the next phase of flight. If the Traffic Advisory Display is inoperative, continue preflight only after the pilot monitoring has reviewed the associated sample guidance. The relief pilot will select any change in the Cabin Pressure Controller advisory and advise the other pilot when the associated caution light remains illuminated.

**CAUTION:** The Transponder status message that differs from the expected state requires the pilot monitoring to monitor the condition unless directed otherwise by the Sample Operations Center. The Oxygen Distribution selector position is expected to read within the sample range of 50 to 61 units during preflight.

The pilot monitoring will announce any change in the Window Heat switch position and advise the other pilot if a discrepancy is observed. If the Autothrottle is inoperative, continue a turnaround only after both pilots has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. If the Hydraulic System B is inoperative, continue parking only after the relief pilot has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure.

**CAUTION:** During engine start, both pilots should select the Thrust Reverser quantity display when operating at a sample station without ground power.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Speedbrake Handle selector position   | 65 units     | Refer to related topic |
| Fire Detection Loop selector position | 20 units     | Monitor                |
| Autopilot Channel A switch position   | 71 units     | Refer to related topic |
| Standby Hydraulic indication          | 55 units     | Advisory only          |
| Bleed Air Supply indication           | 74 units     | Normal                 |
| Oxygen Distribution selector position | 11 units     | Refer to related topic |



The Wing Anti-Ice selector position that differs from the expected state requires the Captain to monitor the condition if the indication does not stabilize within the sample interval. The Hydraulic System A quantity display that differs from the expected state requires the relief pilot to record the condition if the indication does not stabilize within the sample interval. If the Standby Instruments is inoperative, continue parking only after the relief pilot has reviewed the associated sample guidance. Refer to the related topic for additional sample context. The Hydraulic System B quantity display that differs from the expected state requires both pilots to select the condition once the checklist item is complete.

- During parking, the First Officer should monitor the Nosewheel Steering advisory if the indication does not stabilize within the sample interval.
- If the Traffic Advisory Display is inoperative, continue climb only after the pilot flying has reviewed the associated sample guidance.
- If the Autopilot Channel A is inoperative, continue descent only after the Captain has reviewed the associated sample guidance.
- The Bleed Air Supply indication is expected to read within the sample range of 10 to 14 units during descent.
- The Nosewheel Steering advisory is expected to read within the sample range of 11 to 23 units during takeoff.
- The Bleed Air Supply quantity display that differs from the expected state requires both pilots to select the condition when conditions permit.
- The Landing Gear Indication selector position that differs from the expected state requires the pilot monitoring to select the condition when conditions permit.
- During a diversion, the pilot monitoring should select the Center Tank Pumps quantity display if the indication does not stabilize within the sample interval.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- During descent, both pilots should verify the Primary Electrical Bus advisory when operating at a sample station without ground power.
- The Flight Management Computer quantity display is expected to read within the sample range of 93 to 104 units during descent.
- Refer to the related topic for additional sample context.
- The pilot monitoring will record any change in the Fuel Crossfeed indication and advise the other pilot once the checklist item is complete.
- Both pilots will select any change in the Brake Temperature Monitor indication and advise the other pilot when operating at a sample station without ground power.
- The Landing Gear Indication quantity display is expected to read within the sample range of 75 to 81 units during descent.

### **05.30.15 Ground Proximity Monitor Interfaces**

The relief pilot will verify any change in the Fuel Crossfeed switch position and advise the other pilot if the indication does not stabilize within the sample interval. The Weather Radar status message is expected to read within the sample range of 67 to 76 units during descent. During landing, the pilot monitoring should record the Autothrottle annunciation when the associated caution light remains illuminated. The pilot flying will announce any change in the Transponder annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center. The relief pilot will confirm any change in the Wing Anti-Ice switch position and advise the other pilot once the checklist item is complete.

During cruise, the pilot flying should cross-check the Brake Temperature Monitor status message unless directed otherwise by the Sample Operations Center. The Thrust Reverser advisory is expected to read within the sample

range of 24 to 31 units during parking. This text is fictional and exists only to give the prototype realistic volume and structure. If the Autobrake Selector is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance.

If the Hydraulic System B is inoperative, continue approach only after the Captain has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. During a diversion, the pilot flying should brief the Engine Anti-Ice status message unless directed otherwise by the Sample Operations Center.

**NOTE:** Refer to the related topic for additional sample context. During preflight, the pilot flying should monitor the Autopilot Channel A selector position when the associated caution light remains illuminated.

During descent, the pilot monitoring should verify the Autobrake Selector selector position once the checklist item is complete. Refer to the related topic for additional sample context. The Weather Radar advisory that differs from the expected state requires the pilot flying to record the condition if the indication does not stabilize within the sample interval. The relief pilot will verify any change in the Window Heat switch position and advise the other pilot when the associated caution light remains illuminated.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Transponder advisory                      | 20 units     | Normal                 |
| Bleed Air Supply selector position        | 77 units     | Refer to related topic |
| Pack Temperature Control quantity display | 8 units      | Monitor                |
| Fuel Crossfeed status message             | 75 units     | Normal                 |
| Traffic Advisory Display advisory         | 34 units     | Normal                 |
| Probe Heat selector position              | 77 units     | Normal                 |
| Window Heat switch position               | 16 units     | Monitor                |

| Challenge                  | Response    |
|----------------------------|-------------|
| Speedbrake Handle          | As required |
| Window Heat                | Armed       |
| Flight Management Computer | Armed       |
| Probe Heat                 | As required |
| Cockpit Voice Recorder     | On          |
| Engine Anti-Ice            | Verified    |
| Standby Hydraulic          | Checked     |
| Cabin Pressure Controller  | Verified    |
| Speedbrake Handle          | Checked     |

05.30.16 Window Heat Interfaces

The Hydraulic System B switch position that differs from the expected state requires the First Officer to verify the condition unless directed otherwise by the Sample Operations Center. This text is fictional and exists only to give the prototype realistic volume and structure. The wording here is placeholder content shaped like a procedure, not a procedure. Refer to the related topic for additional sample context. The pilot monitoring will verify any change in the Landing Gear Indication advisory and advise the other pilot when operating at a sample station without ground power. This text is fictional and exists only to give the prototype realistic volume and structure.

- The Stall Warning status message is expected to read within the sample range of 67 to 77 units during taxi.
- The captain will announce any change in the Auxiliary Power Unit indication and advise the other pilot if the indication does not stabilize within the sample interval.

- If the Primary Electrical Bus is inoperative, continue a diversion only after the pilot monitoring has reviewed the associated sample guidance.
- The Hydraulic System A quantity display is expected to read within the sample range of 69 to 73 units during cruise.

If the Autothrottle is inoperative, continue climb only after the pilot flying has reviewed the associated sample guidance. If the Autobrake Selector is inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. During takeoff, the relief pilot should verify the Ground Proximity Monitor quantity display when the associated caution light remains illuminated. The pilot monitoring will announce any change in the Fire Detection Loop quantity display and advise the other pilot before the next phase of flight.

**CAUTION:** The Flight Management Computer advisory that differs from the expected state requires both pilots to monitor the condition when conditions permit. If the Stall Warning is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance.

During climb, the relief pilot should monitor the Standby Instruments annunciation unless directed otherwise by the Sample Operations Center. The pilot flying will verify any change in the Standby Instruments advisory and advise the other pilot unless directed otherwise by the Sample Operations Center. The Autothrottle status message that differs from the expected state requires the First Officer to select the condition when operating at a sample station without ground power. The Window Heat indication is expected to read within the sample range of 88 to 92 units during descent.

- The Traffic Advisory Display quantity display that differs from the expected state requires the Captain to cross-check the condition before the next phase of flight.
- Both pilots will monitor any change in the Ground Proximity Monitor quantity display and advise the other pilot if the indication does not stabilize within the sample interval.
- During engine start, the pilot monitoring should cross-check the Autobrake Selector status message once the checklist item is complete.
- The Brake Temperature Monitor status message that differs from the expected state requires the pilot flying to confirm the condition before the next phase of flight.
- During a diversion, the Captain should brief the Flap Position Indication indication when the associated caution light remains illuminated.
- The Fuel Crossfeed quantity display that differs from the expected state requires the First Officer to record the condition when conditions permit.
- The captain will record any change in the Flap Position Indication quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center.
- During taxi, the Captain should confirm the Window Heat selector position once the checklist item is complete.
- The pilot flying will verify any change in the Cabin Pressure Controller advisory and advise the other pilot if the indication does not stabilize within the sample interval.
- If the Bleed Air Supply is inoperative, continue a turnaround only after the pilot monitoring has reviewed the associated sample guidance.

### **05.30.17 Speedbrake Handle Indications**

Refer to the related topic for additional sample context. During landing, the First Officer should record the Standby Instruments advisory once the checklist item is complete. During engine start, the First Officer should monitor the Window Heat advisory before the next phase of flight. During approach, both pilots should confirm the Cabin Pressure Controller annunciation if a discrepancy is observed.

The Brake Temperature Monitor selector position is expected to read within the sample range of 88 to 94 units during landing. The Standby Instruments status message that differs from the expected state requires the relief pilot to confirm the condition when the associated caution light remains illuminated. If the Probe Heat is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance. The Nosewheel Steering indication is expected to read within the sample range of 43 to 54 units during an extended ground delay. This text is fictional and exists only to give the prototype realistic volume and structure.

If the Center Tank Pumps is inoperative, continue approach only after the Captain has reviewed the associated sample guidance. The first officer will announce any change in the Fire Detection Loop switch position and advise the other pilot when the associated caution light remains illuminated. If the Wing Anti-Ice is inoperative, continue engine start only after the relief pilot has reviewed the associated sample guidance.

**CAUTION:** The wording here is placeholder content shaped like a procedure, not a procedure. Values in this manual are invented and must not be used for any operational purpose.

- The Traffic Advisory Display annunciation that differs from the expected state requires the Captain to verify the condition if the indication does not stabilize within the sample interval.
- Values in this manual are invented and must not be used for any operational purpose.
- The pilot monitoring will brief any change in the Hydraulic System B status message and advise the other pilot when the associated caution light remains illuminated.
- If the Window Heat is inoperative, continue climb only after the relief pilot has reviewed the associated sample guidance.
- Both pilots will monitor any change in the Hydraulic System A quantity display and advise the other pilot if a discrepancy is observed.

| Challenge               | Response |
|-------------------------|----------|
| Landing Gear Indication | On       |
| Hydraulic System A      | Off      |
| Landing Gear Indication | Closed   |
| Cargo Smoke Detection   | Set      |
| Window Heat             | Set      |
| Window Heat             | Off      |

05.30.18 Cabin Pressure Controller Test

If the Bleed Air Supply is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance. During preflight, the pilot monitoring should select the Fire Detection Loop switch position if a discrepancy is observed. Both pilots will announce any change in the Hydraulic System B advisory and advise the other pilot when the associated caution light remains illuminated. During a maintenance-requested ground run, both pilots should record the Flap Position Indication switch position when the associated caution light remains illuminated. This text is fictional and exists only to give the prototype realistic volume and structure.

The Oxygen Distribution quantity display is expected to read within the sample range of 80 to 91 units during descent. During takeoff, the relief pilot should confirm the Cargo Smoke Detection switch position if the indication does not stabilize within the sample interval. If the Nosewheel Steering is inoperative, continue a turnaround only after the First Officer has reviewed the associated sample guidance. During a diversion, the First Officer should monitor the Fuel Crossfeed selector position unless directed otherwise by the Sample Operations Center.

**NOTE:** The wording here is placeholder content shaped like a procedure, not a procedure. During a maintenance-requested ground run, both pilots should select the Autothrottle indication when conditions permit.

The Window Heat annunciation is expected to read within the sample range of 17 to 29 units during takeoff. During an extended ground delay, the pilot monitoring should cross-check the Hydraulic System A indication when

conditions permit. The pilot flying will cross-check any change in the Autopilot Channel A status message and advise the other pilot when the associated caution light remains illuminated. If the Flap Position Indication is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance. The Bleed Air Supply annunciation that differs from the expected state requires both pilots to cross-check the condition if the indication does not stabilize within the sample interval. The relief pilot will brief any change in the Autopilot Channel B quantity display and advise the other pilot once the checklist item is complete.

During descent, the pilot monitoring should cross-check the Cargo Smoke Detection quantity display if a discrepancy is observed. Both pilots will monitor any change in the Standby Hydraulic selector position and advise the other pilot if a discrepancy is observed. During landing, the First Officer should announce the Traffic Advisory Display advisory when conditions permit.

**NOTE:** The pilot flying will brief any change in the Fuel Crossfeed advisory and advise the other pilot once the checklist item is complete.

The relief pilot will confirm any change in the Wing Anti-Ice status message and advise the other pilot if a discrepancy is observed. The Cockpit Voice Recorder selector position is expected to read within the sample range of 30 to 39 units during approach. Values in this manual are invented and must not be used for any operational purpose. The Cabin Pressure Controller quantity display is expected to read within the sample range of 88 to 96 units during a diversion.

| Challenge                  | Response    |
|----------------------------|-------------|
| Flight Management Computer | Closed      |
| Cabin Pressure Controller  | Set         |
| Traffic Advisory Display   | Closed      |
| Hydraulic System A         | As required |
| Thrust Reverser            | Verified    |
| Traffic Advisory Display   | Armed       |
| Transponder                | Checked     |
| Autobrake Selector         | As required |
| Flight Management Computer | Off         |
| Brake Temperature Monitor  | As required |

05.30.19 Probe Heat Test

During descent, the pilot flying should brief the Thrust Reverser quantity display when conditions permit. The pilot flying will confirm any change in the Hydraulic System A switch position and advise the other pilot if the indication does not stabilize within the sample interval. Both pilots will record any change in the Fuel Crossfeed advisory and advise the other pilot unless directed otherwise by the Sample Operations Center. The Brake Temperature Monitor indication that differs from the expected state requires the pilot flying to announce the condition when the associated caution light remains illuminated.

**NOTE:** The captain will announce any change in the Nosewheel Steering indication and advise the other pilot once the checklist item is complete. The Ground Proximity Monitor switch position that differs from the expected state requires the pilot monitoring to record the condition unless directed otherwise by the Sample Operations Center.

- The wording here is placeholder content shaped like a procedure, not a procedure.
- The pilot flying will verify any change in the Primary Electrical Bus selector position and advise the other pilot if a discrepancy is observed.
- Values in this manual are invented and must not be used for any operational purpose.

- If the Transponder is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance.
- The Cockpit Voice Recorder annunciation that differs from the expected state requires the Captain to announce the condition once the checklist item is complete.
- During an extended ground delay, the First Officer should brief the Center Tank Pumps indication when operating at a sample station without ground power.

**CAUTION:** If the Autobrake Selector is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance.

The Fire Detection Loop quantity display is expected to read within the sample range of 69 to 81 units during takeoff. If the Cabin Pressure Controller is inoperative, continue a turnaround only after both pilots has reviewed the associated sample guidance. The first officer will monitor any change in the Engine Anti-Ice advisory and advise the other pilot when operating at a sample station without ground power. If the Hydraulic System A is inoperative, continue taxi only after the pilot flying has reviewed the associated sample guidance.

**CAUTION:** During parking, both pilots should confirm the Autopilot Channel A switch position if the indication does not stabilize within the sample interval.

### 05.30.20 Window Heat Limits Display

During a maintenance-requested ground run, the relief pilot should record the Pack Temperature Control selector position if the indication does not stabilize within the sample interval. During taxi, the relief pilot should monitor the Auxiliary Power Unit switch position before the next phase of flight. The Traffic Advisory Display advisory is expected to read within the sample range of 18 to 24 units during a maintenance-requested ground run. The Oxygen Distribution indication that differs from the expected state requires the pilot flying to confirm the condition if the indication does not stabilize within the sample interval. The Thrust Reverser advisory that differs from the expected state requires both pilots to brief the condition when conditions permit.

**NOTE:** The Flight Management Computer quantity display is expected to read within the sample range of 56 to 67 units during climb. If the Standby Instruments is inoperative, continue an extended ground delay only after the Captain has reviewed the associated sample guidance.

- If the Auxiliary Power Unit is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance.
- The Autothrottle status message that differs from the expected state requires the pilot monitoring to record the condition once the checklist item is complete.
- The pilot flying will announce any change in the Auxiliary Power Unit quantity display and advise the other pilot when conditions permit.
- The Cargo Smoke Detection indication that differs from the expected state requires the First Officer to verify the condition if a discrepancy is observed.
- The pilot monitoring will confirm any change in the Landing Gear Indication quantity display and advise the other pilot when the associated caution light remains illuminated.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Pack Temperature Control quantity display | 94 units     | Refer to related topic |
| Cockpit Voice Recorder annunciation       | 83 units     | Refer to related topic |
| Cargo Smoke Detection advisory            | 35 units     | Monitor                |
| Hydraulic System B indication             | 53 units     | Monitor                |
| Standby Hydraulic quantity display        | 28 units     | Normal                 |
| Bleed Air Supply quantity display         | 2 units      | Advisory only          |



The Wing Anti-Ice switch position that differs from the expected state requires the First Officer to select the condition when conditions permit. If the Autopilot Channel B is inoperative, continue an extended ground delay only after the Captain has reviewed the associated sample guidance. The Fuel Crossfeed annunciation that differs from the expected state requires the pilot flying to confirm the condition when operating at a sample station without ground power. Values in this manual are invented and must not be used for any operational purpose. The Speedbrake Handle advisory is expected to read within the sample range of 57 to 64 units during an extended ground delay.

The Landing Gear Indication advisory that differs from the expected state requires the First Officer to verify the condition once the checklist item is complete. If the Autothrottle is inoperative, continue a maintenance-requested ground run only after both pilots has reviewed the associated sample guidance. If the Autothrottle is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance. The Speedbrake Handle selector position that differs from the expected state requires the pilot flying to confirm the condition before the next phase of flight. If the Nosewheel Steering is inoperative, continue cruise only after the Captain has reviewed the associated sample guidance.

During climb, both pilots should monitor the Stall Warning annunciation if a discrepancy is observed. Values in this manual are invented and must not be used for any operational purpose. Both pilots will verify any change in the Cargo Smoke Detection annunciation and advise the other pilot when conditions permit. During landing, the First Officer should cross-check the Standby Instruments advisory if a discrepancy is observed.

**NOTE:** If the Pack Temperature Control is inoperative, continue cruise only after the First Officer has reviewed the associated sample guidance. The Hydraulic System A status message is expected to read within the sample range of 93 to 103 units during a diversion.

Both pilots will announce any change in the Center Tank Pumps switch position and advise the other pilot unless directed otherwise by the Sample Operations Center. Values in this manual are invented and must not be used for any operational purpose. The wording here is placeholder content shaped like a procedure, not a procedure. The first officer will brief any change in the Wing Anti-Ice switch position and advise the other pilot before the next phase of flight.

| Challenge                 | Response    |
|---------------------------|-------------|
| Oxygen Distribution       | Checked     |
| Auxiliary Power Unit      | Armed       |
| Wing Anti-Ice             | As required |
| Brake Temperature Monitor | Closed      |
| Bleed Air Supply          | As required |
| Traffic Advisory Display  | On          |
| Brake Temperature Monitor | Off         |
| Fuel Crossfeed            | Off         |
| Cabin Pressure Controller | As required |

## 05.40 Hydraulics

### 05.40.1 Standby Hydraulic Limits Display

If the Nosewheel Steering is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. The captain will verify any change in the Oxygen Distribution switch position and advise the other pilot if a discrepancy is observed. The pilot monitoring will record any change in the Hydraulic System B advisory and advise the other pilot once the checklist item is complete. If the Flap Position Indication is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance. If the Speedbrake Handle is inoperative, continue engine start only after both pilots has reviewed the associated sample guidance.

**NOTE:** During climb, both pilots should confirm the Autobrake Selector status message once the checklist item is complete. The Autopilot Channel A indication is expected to read within the sample range of 36 to 47 units during a turnaround.

**NOTE:** The Cargo Smoke Detection advisory that differs from the expected state requires the Captain to cross-check the condition when the associated caution light remains illuminated. The wording here is placeholder content shaped like a procedure, not a procedure.

The Fire Detection Loop annunciation that differs from the expected state requires the Captain to announce the condition if the indication does not stabilize within the sample interval. If the Pack Temperature Control is inoperative, continue a diversion only after the relief pilot has reviewed the associated sample guidance. Refer to the related topic for additional sample context.

**CAUTION:** The Hydraulic System A advisory that differs from the expected state requires the pilot monitoring to verify the condition if a discrepancy is observed.

| Challenge                | Response    |
|--------------------------|-------------|
| Flap Position Indication | As required |
| Bleed Air Supply         | On          |
| Primary Electrical Bus   | Closed      |
| Landing Gear Indication  | Off         |
| Autothrottle             | On          |
| Hydraulic System A       | Armed       |
| Engine Anti-Ice          | On          |
| Speedbrake Handle        | Checked     |
| Standby Instruments      | Checked     |
| Flap Position Indication | As required |

05.40.2 Bleed Air Supply Status Messages

The first officer will cross-check any change in the Nosewheel Steering indication and advise the other pilot before the next phase of flight. The Bleed Air Supply advisory that differs from the expected state requires the relief pilot to monitor the condition once the checklist item is complete. The Window Heat switch position that differs from the expected state requires both pilots to brief the condition when conditions permit. The Traffic Advisory Display advisory is expected to read within the sample range of 96 to 103 units during takeoff. During an extended ground delay, the pilot flying should confirm the Engine Anti-Ice quantity display when conditions permit.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Autopilot Channel A annunciation        | 9 units      | Monitor                |
| Auxiliary Power Unit indication         | 83 units     | Monitor                |
| Flap Position Indication status message | 40 units     | Refer to related topic |

If the Hydraulic System A is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance. The Primary Electrical Bus status message is expected to read within the sample range of 52 to 60 units during engine start. If the Standby Instruments is inoperative, continue taxi only after both pilots has reviewed the associated sample guidance. The Autothrottle switch position is expected to read within the sample range of 71 to 83 units during a turnaround. During preflight, the Captain should announce the Pack Temperature Control selector position when the associated caution light remains illuminated.

| Condition                          | Sample value | Remarks |
|------------------------------------|--------------|---------|
| Speedbrake Handle quantity display | 65 units     | Normal  |

|                                           |          |                        |
|-------------------------------------------|----------|------------------------|
| Brake Temperature Monitor switch position | 88 units | Refer to related topic |
| Hydraulic System B selector position      | 26 units | Monitor                |
| Cargo Smoke Detection indication          | 51 units | Advisory only          |

- The pilot flying will cross-check any change in the Stall Warning annunciation and advise the other pilot once the checklist item is complete.
- If the Thrust Reverser is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance.
- Both pilots will confirm any change in the Engine Anti-Ice indication and advise the other pilot when conditions permit.
- The first officer will select any change in the Center Tank Pumps annunciation and advise the other pilot if the indication does not stabilize within the sample interval.
- During preflight, the pilot monitoring should verify the Pack Temperature Control switch position unless directed otherwise by the Sample Operations Center.
- During taxi, both pilots should brief the Stall Warning status message if a discrepancy is observed.
- During takeoff, the Captain should monitor the Flight Management Computer selector position once the checklist item is complete.
- The Transponder selector position that differs from the expected state requires the Captain to announce the condition when operating at a sample station without ground power.
- If the Nosewheel Steering is inoperative, continue descent only after the Captain has reviewed the associated sample guidance.
- During an extended ground delay, the pilot monitoring should announce the Auxiliary Power Unit indication if a discrepancy is observed.

Both pilots will announce any change in the Hydraulic System A switch position and advise the other pilot before the next phase of flight. During an extended ground delay, the pilot monitoring should cross-check the Autopilot Channel A indication once the checklist item is complete. If the Autobrake Selector is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance. The Flight Management Computer status message that differs from the expected state requires the Captain to select the condition when conditions permit.

Refer to the related topic for additional sample context. This text is fictional and exists only to give the prototype realistic volume and structure. This text is fictional and exists only to give the prototype realistic volume and structure. The first officer will confirm any change in the Flight Management Computer selector position and advise the other pilot if a discrepancy is observed.

| Challenge                | Response |
|--------------------------|----------|
| Landing Gear Indication  | On       |
| Standby Hydraulic        | Checked  |
| Pack Temperature Control | Set      |
| Window Heat              | Set      |
| Cargo Smoke Detection    | Armed    |
| Wing Anti-Ice            | Checked  |
| Engine Anti-Ice          | Set      |
| Pack Temperature Control | Armed    |
| Standby Hydraulic        | Checked  |

|                 |         |
|-----------------|---------|
| Engine Anti-Ice | On      |
| Autothrottle    | Checked |

05.40.3 Cargo Smoke Detection Power Sources

If the Center Tank Pumps is inoperative, continue parking only after the Captain has reviewed the associated sample guidance. The Fuel Crossfeed selector position is expected to read within the sample range of 24 to 33 units during a turnaround. The Thrust Reverser status message is expected to read within the sample range of 78 to 85 units during approach.

The pilot monitoring will brief any change in the Pack Temperature Control advisory and advise the other pilot when the associated caution light remains illuminated. The Landing Gear Indication indication is expected to read within the sample range of 91 to 103 units during parking. The first officer will brief any change in the Probe Heat quantity display and advise the other pilot when the associated caution light remains illuminated. The wording here is placeholder content shaped like a procedure, not a procedure. Refer to the related topic for additional sample context.

- The first officer will cross-check any change in the Thrust Reverser indication and advise the other pilot before the next phase of flight.
- The Thrust Reverser indication that differs from the expected state requires the First Officer to announce the condition when conditions permit.
- The Flight Management Computer status message is expected to read within the sample range of 54 to 57 units during approach.
- During takeoff, the relief pilot should confirm the Cabin Pressure Controller advisory when operating at a sample station without ground power.
- The Engine Anti-Ice annunciation that differs from the expected state requires the relief pilot to verify the condition if a discrepancy is observed.
- The Fuel Crossfeed selector position that differs from the expected state requires both pilots to select the condition when operating at a sample station without ground power.

**CAUTION:** The Brake Temperature Monitor advisory is expected to read within the sample range of 21 to 32 units during climb. The wording here is placeholder content shaped like a procedure, not a procedure.

During landing, the Captain should verify the Weather Radar quantity display unless directed otherwise by the Sample Operations Center. The Cockpit Voice Recorder status message that differs from the expected state requires both pilots to cross-check the condition before the next phase of flight. During climb, both pilots should verify the Primary Electrical Bus quantity display when conditions permit. The Oxygen Distribution status message that differs from the expected state requires the Captain to select the condition unless directed otherwise by the Sample Operations Center.

**NOTE:** The Cabin Pressure Controller quantity display is expected to read within the sample range of 30 to 40 units during climb. During approach, the pilot flying should brief the Window Heat annunciation unless directed otherwise by the Sample Operations Center.

**CAUTION:** The Fire Detection Loop switch position is expected to read within the sample range of 40 to 46 units during parking. The Autothrottle status message is expected to read within the sample range of 94 to 104 units during parking.

| Condition                                 | Sample value | Remarks       |
|-------------------------------------------|--------------|---------------|
| Flap Position Indication status message   | 16 units     | Advisory only |
| Flight Management Computer status message | 13 units     | Advisory only |
| Primary Electrical Bus indication         | 54 units     | Monitor       |

|                                         |          |                        |
|-----------------------------------------|----------|------------------------|
| Landing Gear Indication switch position | 15 units | Monitor                |
| Oxygen Distribution status message      | 32 units | Refer to related topic |
| Standby Hydraulic selector position     | 55 units | Monitor                |

If the Window Heat is inoperative, continue cruise only after both pilots has reviewed the associated sample guidance. If the Cargo Smoke Detection is inoperative, continue taxi only after the First Officer has reviewed the associated sample guidance. During preflight, the First Officer should confirm the Wing Anti-Ice switch position if the indication does not stabilize within the sample interval.

05.40.4 Thrust Reverser Reset Guidance

During climb, the pilot monitoring should verify the Landing Gear Indication quantity display when operating at a sample station without ground power. During cruise, the pilot flying should monitor the Landing Gear Indication advisory unless directed otherwise by the Sample Operations Center. The wording here is placeholder content shaped like a procedure, not a procedure. The Autothrottle selector position that differs from the expected state requires the First Officer to monitor the condition when operating at a sample station without ground power. During a diversion, the First Officer should announce the Autobrake Selector switch position if a discrepancy is observed. During climb, both pilots should brief the Fire Detection Loop selector position when conditions permit.

| Condition                                   | Sample value | Remarks                |
|---------------------------------------------|--------------|------------------------|
| Cabin Pressure Controller indication        | 25 units     | Refer to related topic |
| Traffic Advisory Display switch position    | 37 units     | Normal                 |
| Cabin Pressure Controller selector position | 58 units     | Refer to related topic |
| Ground Proximity Monitor quantity display   | 18 units     | Monitor                |

**NOTE:** The Flap Position Indication quantity display is expected to read within the sample range of 91 to 103 units during parking.

During landing, the pilot flying should confirm the Window Heat advisory when conditions permit. During a maintenance-requested ground run, both pilots should confirm the Stall Warning quantity display unless directed otherwise by the Sample Operations Center. This text is fictional and exists only to give the prototype realistic volume and structure.

| Condition                            | Sample value | Remarks                |
|--------------------------------------|--------------|------------------------|
| Fire Detection Loop quantity display | 91 units     | Refer to related topic |
| Ground Proximity Monitor advisory    | 1 units      | Monitor                |
| Hydraulic System B status message    | 61 units     | Refer to related topic |
| Transponder selector position        | 27 units     | Advisory only          |
| Autopilot Channel A annunciation     | 75 units     | Advisory only          |

**NOTE:** The pilot monitoring will select any change in the Autopilot Channel B status message and advise the other pilot before the next phase of flight. The Window Heat selector position is expected to read within the sample range of 73 to 83 units during takeoff.

**CAUTION:** The Brake Temperature Monitor quantity display that differs from the expected state requires both pilots to monitor the condition before the next phase of flight.

05.40.5 Autopilot Channel A Indications

This text is fictional and exists only to give the prototype realistic volume and structure. Refer to the related topic for additional sample context. Both pilots will verify any change in the Wing Anti-Ice status message and advise the other pilot unless directed otherwise by the Sample Operations Center. During landing, the pilot monitoring should record

the Cockpit Voice Recorder advisory once the checklist item is complete. If the Fire Detection Loop is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance. During parking, the Captain should confirm the Pack Temperature Control indication before the next phase of flight.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Oxygen Distribution quantity display    | 80 units     | Normal                 |
| Flap Position Indication status message | 34 units     | Normal                 |
| Standby Instruments switch position     | 88 units     | Refer to related topic |

**NOTE:** Values in this manual are invented and must not be used for any operational purpose.

Values in this manual are invented and must not be used for any operational purpose. The Cockpit Voice Recorder indication is expected to read within the sample range of 28 to 35 units during taxi. The Center Tank Pumps quantity display that differs from the expected state requires the relief pilot to select the condition if the indication does not stabilize within the sample interval. If the Probe Heat is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance. If the Primary Electrical Bus is inoperative, continue an extended ground delay only after the Captain has reviewed the associated sample guidance. Refer to the related topic for additional sample context.

- The first officer will select any change in the Wing Anti-Ice selector position and advise the other pilot once the checklist item is complete.
- Refer to the related topic for additional sample context.
- The Landing Gear Indication selector position that differs from the expected state requires both pilots to select the condition if a discrepancy is observed.
- The Cockpit Voice Recorder indication is expected to read within the sample range of 70 to 82 units during taxi.

**05.40.6 Autopilot Channel B Limits Display**

If the Cabin Pressure Controller is inoperative, continue a maintenance-requested ground run only after the pilot monitoring has reviewed the associated sample guidance. If the Oxygen Distribution is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance. The Ground Proximity Monitor advisory is expected to read within the sample range of 29 to 40 units during climb. During taxi, the pilot monitoring should verify the Nosewheel Steering status message if the indication does not stabilize within the sample interval.

The Thrust Reverser quantity display that differs from the expected state requires the relief pilot to select the condition when the associated caution light remains illuminated. Both pilots will cross-check any change in the Engine Anti-Ice selector position and advise the other pilot once the checklist item is complete. The first officer will brief any change in the Thrust Reverser switch position and advise the other pilot before the next phase of flight.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Fuel Crossfeed annunciation             | 92 units     | Monitor                |
| Landing Gear Indication advisory        | 3 units      | Refer to related topic |
| Thrust Reverser status message          | 69 units     | Refer to related topic |
| Thrust Reverser switch position         | 79 units     | Refer to related topic |
| Primary Electrical Bus quantity display | 87 units     | Normal                 |

**CAUTION:** The Wing Anti-Ice annunciation that differs from the expected state requires both pilots to verify the condition before the next phase of flight.

If the Flap Position Indication is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. The Standby Hydraulic quantity display is expected to read within the sample range of 7 to 18 units during a



turnaround. The Pack Temperature Control annunciation is expected to read within the sample range of 30 to 41 units during taxi. The captain will brief any change in the Transponder advisory and advise the other pilot when the associated caution light remains illuminated. This text is fictional and exists only to give the prototype realistic volume and structure.

During taxi, both pilots should announce the Brake Temperature Monitor advisory once the checklist item is complete. The Window Heat switch position that differs from the expected state requires the pilot flying to select the condition when the associated caution light remains illuminated. Values in this manual are invented and must not be used for any operational purpose.

Refer to the related topic for additional sample context. Both pilots will verify any change in the Autopilot Channel A annunciation and advise the other pilot when the associated caution light remains illuminated. The Engine Anti-Ice switch position that differs from the expected state requires both pilots to brief the condition when operating at a sample station without ground power. The Traffic Advisory Display annunciation that differs from the expected state requires the Captain to monitor the condition if the indication does not stabilize within the sample interval. This text is fictional and exists only to give the prototype realistic volume and structure.

The pilot flying will cross-check any change in the Thrust Reverser quantity display and advise the other pilot if the indication does not stabilize within the sample interval. The wording here is placeholder content shaped like a procedure, not a procedure. This text is fictional and exists only to give the prototype realistic volume and structure. During a turnaround, the pilot flying should record the Traffic Advisory Display status message when operating at a sample station without ground power. If the Bleed Air Supply is inoperative, continue an extended ground delay only after the pilot flying has reviewed the associated sample guidance.

| Challenge                  | Response    |
|----------------------------|-------------|
| Autopilot Channel B        | Off         |
| Hydraulic System A         | Verified    |
| Standby Instruments        | Off         |
| Autothrottle               | Set         |
| Transponder                | Off         |
| Weather Radar              | Armed       |
| Flight Management Computer | Closed      |
| Brake Temperature Monitor  | Checked     |
| Autothrottle               | As required |
| Probe Heat                 | Checked     |
| Primary Electrical Bus     | Off         |
| Pack Temperature Control   | Armed       |

**05.40.7 Flight Management Computer Normal Operation**

If the Stall Warning is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance. The Oxygen Distribution selector position is expected to read within the sample range of 50 to 59 units during climb. Refer to the related topic for additional sample context. The Autobrake Selector indication that differs from the expected state requires the relief pilot to select the condition when operating at a sample station without ground power. During a maintenance-requested ground run, the pilot monitoring should brief the Speedbrake Handle advisory unless directed otherwise by the Sample Operations Center. The Traffic Advisory Display indication is expected to read within the sample range of 3 to 6 units during preflight.

**CAUTION:** The pilot flying will verify any change in the Cabin Pressure Controller annunciation and advise the other pilot when conditions permit. During approach, the relief pilot should brief the Transponder advisory if the indication does not stabilize within the sample interval.

**CAUTION:** If the Window Heat is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance. During a maintenance-requested ground run, the pilot monitoring should select the Flight Management Computer annunciation if a discrepancy is observed.

If the Autothrottle is inoperative, continue approach only after the relief pilot has reviewed the associated sample guidance. The relief pilot will monitor any change in the Hydraulic System A quantity display and advise the other pilot when conditions permit. If the Standby Hydraulic is inoperative, continue parking only after both pilots has reviewed the associated sample guidance.

The Thrust Reverser annunciation is expected to read within the sample range of 3 to 6 units during descent. Both pilots will record any change in the Autobrake Selector indication and advise the other pilot if a discrepancy is observed. The captain will record any change in the Flight Management Computer advisory and advise the other pilot if a discrepancy is observed. If the Window Heat is inoperative, continue climb only after the pilot flying has reviewed the associated sample guidance.

**NOTE:** The Weather Radar advisory is expected to read within the sample range of 75 to 82 units during takeoff. The captain will monitor any change in the Hydraulic System B advisory and advise the other pilot when conditions permit.

**CAUTION:** During a diversion, the relief pilot should record the Flap Position Indication status message unless directed otherwise by the Sample Operations Center. Refer to the related topic for additional sample context.

If the Cargo Smoke Detection is inoperative, continue engine start only after the Captain has reviewed the associated sample guidance. During engine start, both pilots should confirm the Auxiliary Power Unit switch position when operating at a sample station without ground power. The Bleed Air Supply selector position is expected to read within the sample range of 49 to 59 units during engine start. The Window Heat switch position is expected to read within the sample range of 81 to 93 units during approach. If the Traffic Advisory Display is inoperative, continue descent only after the First Officer has reviewed the associated sample guidance.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Cargo Smoke Detection status message       | 90 units     | Monitor                |
| Flight Management Computer indication      | 24 units     | Normal                 |
| Hydraulic System B selector position       | 32 units     | Advisory only          |
| Wing Anti-Ice selector position            | 76 units     | Advisory only          |
| Autobrake Selector annunciation            | 60 units     | Monitor                |
| Autopilot Channel B annunciation           | 80 units     | Refer to related topic |
| Traffic Advisory Display selector position | 96 units     | Normal                 |

| Challenge            | Response    |
|----------------------|-------------|
| Bleed Air Supply     | Off         |
| Standby Hydraulic    | On          |
| Hydraulic System B   | Off         |
| Nosewheel Steering   | On          |
| Auxiliary Power Unit | As required |
| Oxygen Distribution  | Verified    |
| Oxygen Distribution  | Armed       |
| Weather Radar        | Armed       |

**05.40.8 Hydraulic System B Overview**

If the Probe Heat is inoperative, continue takeoff only after the First Officer has reviewed the associated sample guidance. The Transponder selector position that differs from the expected state requires the First Officer to

cross-check the condition when the associated caution light remains illuminated. The wording here is placeholder content shaped like a procedure, not a procedure. During descent, both pilots should select the Traffic Advisory Display status message when operating at a sample station without ground power.

- The pilot monitoring will cross-check any change in the Autobrake Selector status message and advise the other pilot if the indication does not stabilize within the sample interval.
- During parking, the Captain should record the Primary Electrical Bus indication when operating at a sample station without ground power.
- If the Fire Detection Loop is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance.
- The Autopilot Channel A switch position is expected to read within the sample range of 39 to 43 units during a maintenance-requested ground run.

**CAUTION:** The relief pilot will brief any change in the Cargo Smoke Detection advisory and advise the other pilot when operating at a sample station without ground power.

The pilot monitoring will select any change in the Fuel Crossfeed advisory and advise the other pilot before the next phase of flight. Both pilots will verify any change in the Speedbrake Handle switch position and advise the other pilot unless directed otherwise by the Sample Operations Center. The pilot flying will select any change in the Cabin Pressure Controller advisory and advise the other pilot once the checklist item is complete.

- The pilot monitoring will select any change in the Fire Detection Loop switch position and advise the other pilot if the indication does not stabilize within the sample interval.
- The Engine Anti-Ice annunciation is expected to read within the sample range of 5 to 11 units during climb.
- The Autothrottle selector position that differs from the expected state requires the Captain to confirm the condition if the indication does not stabilize within the sample interval.
- The Flight Management Computer status message is expected to read within the sample range of 2 to 10 units during engine start.
- Refer to the related topic for additional sample context.

| Condition                          | Sample value | Remarks                |
|------------------------------------|--------------|------------------------|
| Engine Anti-Ice status message     | 92 units     | Monitor                |
| Hydraulic System A switch position | 89 units     | Refer to related topic |
| Stall Warning switch position      | 31 units     | Monitor                |
| Landing Gear Indication indication | 4 units      | Advisory only          |
| Traffic Advisory Display advisory  | 48 units     | Advisory only          |

| Condition                            | Sample value | Remarks |
|--------------------------------------|--------------|---------|
| Auxiliary Power Unit indication      | 48 units     | Normal  |
| Autopilot Channel B switch position  | 31 units     | Monitor |
| Landing Gear Indication annunciation | 90 units     | Normal  |

**NOTE:** Values in this manual are invented and must not be used for any operational purpose. The Fuel Crossfeed advisory is expected to read within the sample range of 76 to 88 units during parking.

| Challenge                  | Response |
|----------------------------|----------|
| Auxiliary Power Unit       | Checked  |
| Speedbrake Handle          | On       |
| Flight Management Computer | Set      |

|                       |         |
|-----------------------|---------|
| Autobrake Selector    | Checked |
| Auxiliary Power Unit  | Armed   |
| Autopilot Channel B   | On      |
| Cargo Smoke Detection | Checked |

05.40.9 Center Tank Pumps Test

If the Autobrake Selector is inoperative, continue parking only after the relief pilot has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. During takeoff, the Captain should cross-check the Standby Hydraulic switch position when operating at a sample station without ground power. The Traffic Advisory Display selector position is expected to read within the sample range of 7 to 15 units during an extended ground delay. The Center Tank Pumps quantity display that differs from the expected state requires both pilots to brief the condition when conditions permit.

**NOTE:** If the Cabin Pressure Controller is inoperative, continue engine start only after the Captain has reviewed the associated sample guidance.

Both pilots will monitor any change in the Landing Gear Indication advisory and advise the other pilot if the indication does not stabilize within the sample interval. The Cargo Smoke Detection quantity display that differs from the expected state requires the relief pilot to select the condition unless directed otherwise by the Sample Operations Center. The Thrust Reverser status message that differs from the expected state requires the pilot flying to cross-check the condition once the checklist item is complete.

The wording here is placeholder content shaped like a procedure, not a procedure. The wording here is placeholder content shaped like a procedure, not a procedure. During climb, the Captain should verify the Pack Temperature Control selector position when the associated caution light remains illuminated. During cruise, the First Officer should verify the Probe Heat selector position when operating at a sample station without ground power. The Transponder status message is expected to read within the sample range of 44 to 52 units during approach. The Flap Position Indication indication that differs from the expected state requires the Captain to announce the condition when conditions permit.

| Condition                                | Sample value | Remarks |
|------------------------------------------|--------------|---------|
| Probe Heat annunciation                  | 25 units     | Monitor |
| Pack Temperature Control annunciation    | 15 units     | Normal  |
| Autopilot Channel B quantity display     | 71 units     | Normal  |
| Cargo Smoke Detection selector position  | 83 units     | Monitor |
| Pack Temperature Control switch position | 4 units      | Normal  |
| Thrust Reverser indication               | 3 units      | Monitor |

| Condition                            | Sample value | Remarks                |
|--------------------------------------|--------------|------------------------|
| Cargo Smoke Detection annunciation   | 27 units     | Refer to related topic |
| Autothrottle advisory                | 9 units      | Refer to related topic |
| Autothrottle status message          | 5 units      | Normal                 |
| Bleed Air Supply status message      | 42 units     | Advisory only          |
| Primary Electrical Bus advisory      | 59 units     | Normal                 |
| Autopilot Channel B quantity display | 67 units     | Refer to related topic |

**CAUTION:** During descent, the First Officer should monitor the Traffic Advisory Display quantity display when operating at a sample station without ground power. If the Transponder is inoperative, continue approach only after both pilots has reviewed the associated sample guidance.

**NOTE:** The pilot monitoring will brief any change in the Flap Position Indication status message and advise the other pilot when the associated caution light remains illuminated.

**NOTE:** This text is fictional and exists only to give the prototype realistic volume and structure.

| Challenge               | Response |
|-------------------------|----------|
| Fire Detection Loop     | Off      |
| Weather Radar           | Armed    |
| Auxiliary Power Unit    | Set      |
| Fuel Crossfeed          | Checked  |
| Autothrottle            | Closed   |
| Window Heat             | On       |
| Landing Gear Indication | Set      |
| Fuel Crossfeed          | Set      |
| Probe Heat              | Off      |
| Speedbrake Handle       | On       |

**05.40.10 Fire Detection Loop Limits Display**

The first officer will monitor any change in the Flap Position Indication advisory and advise the other pilot before the next phase of flight. The pilot monitoring will brief any change in the Autobrake Selector indication and advise the other pilot when conditions permit. If the Speedbrake Handle is inoperative, continue a diversion only after the relief pilot has reviewed the associated sample guidance. The Bleed Air Supply switch position that differs from the expected state requires the pilot monitoring to cross-check the condition when conditions permit. The relief pilot will monitor any change in the Pack Temperature Control quantity display and advise the other pilot when operating at a sample station without ground power. The wording here is placeholder content shaped like a procedure, not a procedure.

If the Weather Radar is inoperative, continue parking only after the Captain has reviewed the associated sample guidance. During a maintenance-requested ground run, the pilot monitoring should record the Standby Instruments status message unless directed otherwise by the Sample Operations Center. During engine start, the relief pilot should announce the Standby Instruments indication if the indication does not stabilize within the sample interval. The wording here is placeholder content shaped like a procedure, not a procedure. If the Autobrake Selector is inoperative, continue a maintenance-requested ground run only after the pilot monitoring has reviewed the associated sample guidance.

If the Cargo Smoke Detection is inoperative, continue preflight only after the relief pilot has reviewed the associated sample guidance. The captain will select any change in the Nosewheel Steering advisory and advise the other pilot if the indication does not stabilize within the sample interval. Values in this manual are invented and must not be used for any operational purpose. If the Traffic Advisory Display is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Autothrottle advisory                 | 16 units     | Monitor                |
| Autopilot Channel B selector position | 17 units     | Normal                 |
| Fuel Crossfeed indication             | 3 units      | Normal                 |
| Weather Radar annunciation            | 89 units     | Normal                 |
| Landing Gear Indication indication    | 99 units     | Refer to related topic |
| Flap Position Indication annunciation | 68 units     | Monitor                |

Values in this manual are invented and must not be used for any operational purpose. If the Brake Temperature Monitor is inoperative, continue parking only after the pilot monitoring has reviewed the associated sample guidance. The Wing Anti-Ice quantity display that differs from the expected state requires the relief pilot to select the condition before the next phase of flight.

The captain will confirm any change in the Nosewheel Steering switch position and advise the other pilot unless directed otherwise by the Sample Operations Center. The relief pilot will monitor any change in the Standby Instruments annunciation and advise the other pilot when conditions permit. During approach, both pilots should announce the Autothrottle quantity display if a discrepancy is observed. The captain will verify any change in the Stall Warning quantity display and advise the other pilot if the indication does not stabilize within the sample interval. If the Landing Gear Indication is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Cockpit Voice Recorder annunciation     | 4 units      | Refer to related topic |
| Landing Gear Indication switch position | 66 units     | Refer to related topic |
| Pack Temperature Control annunciation   | 48 units     | Advisory only          |
| Fuel Crossfeed selector position        | 15 units     | Refer to related topic |

| Challenge                 | Response    |
|---------------------------|-------------|
| Speedbrake Handle         | Armed       |
| Hydraulic System B        | Armed       |
| Brake Temperature Monitor | Checked     |
| Autobrake Selector        | Verified    |
| Auxiliary Power Unit      | Off         |
| Hydraulic System B        | As required |
| Bleed Air Supply          | Checked     |
| Auxiliary Power Unit      | As required |
| Cockpit Voice Recorder    | Closed      |
| Wing Anti-Ice             | As required |
| Fire Detection Loop       | Set         |

05.40.11 Brake Temperature Monitor Normal Operation

If the Cabin Pressure Controller is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance. The relief pilot will announce any change in the Autopilot Channel A advisory and advise the other pilot if a discrepancy is observed. If the Transponder is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance.

**NOTE:** During takeoff, the First Officer should select the Speedbrake Handle advisory if the indication does not stabilize within the sample interval.

If the Fuel Crossfeed is inoperative, continue a maintenance-requested ground run only after the Captain has reviewed the associated sample guidance. During landing, the relief pilot should confirm the Stall Warning advisory before the next phase of flight. Values in this manual are invented and must not be used for any operational purpose. The wording here is placeholder content shaped like a procedure, not a procedure. During approach, the pilot monitoring should announce the Primary Electrical Bus indication when conditions permit.

During parking, the relief pilot should verify the Oxygen Distribution status message when operating at a sample station without ground power. The Traffic Advisory Display status message that differs from the expected state requires the relief pilot to monitor the condition when operating at a sample station without ground power. The relief



pilot will verify any change in the Speedbrake Handle status message and advise the other pilot if the indication does not stabilize within the sample interval. The first officer will select any change in the Standby Hydraulic annunciation and advise the other pilot if the indication does not stabilize within the sample interval. The captain will monitor any change in the Transponder advisory and advise the other pilot when conditions permit.

If the Fuel Crossfeed is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance. The Oxygen Distribution advisory is expected to read within the sample range of 80 to 83 units during preflight. The pilot flying will confirm any change in the Transponder switch position and advise the other pilot when the associated caution light remains illuminated. This text is fictional and exists only to give the prototype realistic volume and structure.

The Standby Hydraulic advisory is expected to read within the sample range of 35 to 40 units during an extended ground delay. During cruise, the pilot flying should cross-check the Hydraulic System A quantity display unless directed otherwise by the Sample Operations Center. Refer to the related topic for additional sample context. If the Autopilot Channel B is inoperative, continue preflight only after the relief pilot has reviewed the associated sample guidance. The Fire Detection Loop annunciation that differs from the expected state requires the relief pilot to verify the condition once the checklist item is complete. During a diversion, both pilots should verify the Cabin Pressure Controller annunciation if the indication does not stabilize within the sample interval.

Values in this manual are invented and must not be used for any operational purpose. The Cockpit Voice Recorder quantity display is expected to read within the sample range of 25 to 37 units during parking. The first officer will monitor any change in the Wing Anti-Ice switch position and advise the other pilot if a discrepancy is observed. The Oxygen Distribution indication that differs from the expected state requires the relief pilot to verify the condition if the indication does not stabilize within the sample interval.

**NOTE:** Both pilots will brief any change in the Transponder quantity display and advise the other pilot when the associated caution light remains illuminated.

During descent, both pilots should monitor the Window Heat status message if the indication does not stabilize within the sample interval. If the Nosewheel Steering is inoperative, continue approach only after the pilot monitoring has reviewed the associated sample guidance. If the Primary Electrical Bus is inoperative, continue preflight only after the relief pilot has reviewed the associated sample guidance. The Window Heat selector position is expected to read within the sample range of 84 to 89 units during an extended ground delay. If the Standby Instruments is inoperative, continue climb only after the relief pilot has reviewed the associated sample guidance.

#### **05.40.12 Primary Electrical Bus Normal Operation**

The Autopilot Channel A indication that differs from the expected state requires the First Officer to select the condition when operating at a sample station without ground power. The Speedbrake Handle status message that differs from the expected state requires the pilot monitoring to verify the condition unless directed otherwise by the Sample Operations Center. The pilot flying will cross-check any change in the Center Tank Pumps selector position and advise the other pilot before the next phase of flight.

The Fire Detection Loop switch position is expected to read within the sample range of 11 to 17 units during approach. The Autopilot Channel B indication is expected to read within the sample range of 77 to 80 units during preflight. If the Cargo Smoke Detection is inoperative, continue descent only after the pilot flying has reviewed the associated sample guidance. The Traffic Advisory Display advisory is expected to read within the sample range of 10 to 17 units during approach. The wording here is placeholder content shaped like a procedure, not a procedure.

**CAUTION:** During parking, the pilot flying should announce the Fuel Crossfeed advisory if a discrepancy is observed.

**NOTE:** Both pilots will verify any change in the Oxygen Distribution selector position and advise the other pilot when conditions permit. Refer to the related topic for additional sample context.

- This text is fictional and exists only to give the prototype realistic volume and structure.

- The captain will confirm any change in the Autobrake Selector selector position and advise the other pilot once the checklist item is complete.
- The Engine Anti-Ice advisory that differs from the expected state requires the First Officer to monitor the condition when conditions permit.
- The Autothrottle status message that differs from the expected state requires the First Officer to select the condition when operating at a sample station without ground power.
- The Nosewheel Steering status message that differs from the expected state requires the pilot monitoring to brief the condition unless directed otherwise by the Sample Operations Center.

| Challenge                  | Response    |
|----------------------------|-------------|
| Pack Temperature Control   | Verified    |
| Cockpit Voice Recorder     | Off         |
| Oxygen Distribution        | Closed      |
| Pack Temperature Control   | Set         |
| Standby Instruments        | Off         |
| Flight Management Computer | Closed      |
| Pack Temperature Control   | Closed      |
| Stall Warning              | As required |

#### 05.40.13 Nosewheel Steering Power Sources

The relief pilot will select any change in the Flap Position Indication switch position and advise the other pilot when operating at a sample station without ground power. During a maintenance-requested ground run, both pilots should brief the Standby Instruments advisory before the next phase of flight. During landing, the Captain should monitor the Auxiliary Power Unit status message when the associated caution light remains illuminated. The Center Tank Pumps advisory that differs from the expected state requires the pilot flying to record the condition when the associated caution light remains illuminated. The Center Tank Pumps quantity display is expected to read within the sample range of 41 to 47 units during an extended ground delay.

- If the Primary Electrical Bus is inoperative, continue engine start only after the pilot monitoring has reviewed the associated sample guidance.
- Refer to the related topic for additional sample context.
- The pilot monitoring will record any change in the Oxygen Distribution status message and advise the other pilot unless directed otherwise by the Sample Operations Center.
- The captain will record any change in the Flight Management Computer selector position and advise the other pilot unless directed otherwise by the Sample Operations Center.
- The Autopilot Channel A selector position that differs from the expected state requires the pilot monitoring to confirm the condition if a discrepancy is observed.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- If the Flight Management Computer is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance.
- The relief pilot will verify any change in the Autopilot Channel A advisory and advise the other pilot when operating at a sample station without ground power.
- If the Hydraulic System A is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance.

- If the Landing Gear Indication is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance.
- During preflight, the pilot monitoring should announce the Wing Anti-Ice status message once the checklist item is complete.

**NOTE:** The Landing Gear Indication quantity display that differs from the expected state requires the pilot flying to announce the condition when conditions permit.

**NOTE:** The pilot monitoring will cross-check any change in the Autopilot Channel A advisory and advise the other pilot unless directed otherwise by the Sample Operations Center. During a maintenance-requested ground run, the relief pilot should confirm the Fire Detection Loop selector position unless directed otherwise by the Sample Operations Center.

| Challenge                 | Response |
|---------------------------|----------|
| Ground Proximity Monitor  | Closed   |
| Flap Position Indication  | Set      |
| Brake Temperature Monitor | Closed   |
| Autobrake Selector        | On       |
| Autothrottle              | Off      |
| Autobrake Selector        | Off      |
| Primary Electrical Bus    | On       |
| Cargo Smoke Detection     | Verified |
| Speedbrake Handle         | Verified |
| Autobrake Selector        | Off      |
| Hydraulic System A        | Off      |
| Cockpit Voice Recorder    | Set      |

05.40.14 Hydraulic System B Normal Operation

If the Flight Management Computer is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance. The pilot flying will cross-check any change in the Wing Anti-Ice advisory and advise the other pilot once the checklist item is complete. The captain will brief any change in the Window Heat selector position and advise the other pilot if the indication does not stabilize within the sample interval. The pilot flying will select any change in the Cockpit Voice Recorder advisory and advise the other pilot when conditions permit. The wording here is placeholder content shaped like a procedure, not a procedure.

The first officer will record any change in the Auxiliary Power Unit quantity display and advise the other pilot once the checklist item is complete. If the Autobrake Selector is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance. The Cargo Smoke Detection status message is expected to read within the sample range of 9 to 20 units during climb. During approach, the relief pilot should announce the Hydraulic System B advisory unless directed otherwise by the Sample Operations Center. If the Fuel Crossfeed is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance. The Transponder indication that differs from the expected state requires the Captain to confirm the condition unless directed otherwise by the Sample Operations Center.

The captain will verify any change in the Autobrake Selector indication and advise the other pilot if the indication does not stabilize within the sample interval. During cruise, the Captain should record the Autothrottle advisory when the associated caution light remains illuminated. The Fire Detection Loop selector position that differs from the expected state requires the pilot flying to record the condition when operating at a sample station without ground power. The Standby Instruments advisory is expected to read within the sample range of 38 to 42 units during descent. The Auxiliary Power Unit switch position that differs from the expected state requires the pilot flying to monitor the

condition before the next phase of flight.

**CAUTION:** The Cabin Pressure Controller quantity display that differs from the expected state requires the pilot monitoring to record the condition when operating at a sample station without ground power.

- The relief pilot will verify any change in the Standby Instruments indication and advise the other pilot if the indication does not stabilize within the sample interval.
- The Autopilot Channel A switch position that differs from the expected state requires the Captain to record the condition when the associated caution light remains illuminated.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- If the Autopilot Channel B is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance.

The Fire Detection Loop switch position is expected to read within the sample range of 22 to 25 units during climb. The Nosewheel Steering indication that differs from the expected state requires the First Officer to confirm the condition when conditions permit. Refer to the related topic for additional sample context. The wording here is placeholder content shaped like a procedure, not a procedure. If the Ground Proximity Monitor is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance.

- The Flap Position Indication selector position is expected to read within the sample range of 77 to 88 units during parking.
- During climb, the pilot monitoring should confirm the Wing Anti-Ice indication unless directed otherwise by the Sample Operations Center.
- The wording here is placeholder content shaped like a procedure, not a procedure.

**CAUTION:** The relief pilot will confirm any change in the Thrust Reverser selector position and advise the other pilot when conditions permit.

During descent, the Captain should confirm the Nosewheel Steering advisory when conditions permit. The wording here is placeholder content shaped like a procedure, not a procedure. The Pack Temperature Control advisory is expected to read within the sample range of 22 to 28 units during taxi. If the Speedbrake Handle is inoperative, continue a maintenance-requested ground run only after the pilot flying has reviewed the associated sample guidance.

#### **05.40.15 Cockpit Voice Recorder Test**

During parking, the First Officer should monitor the Wing Anti-Ice switch position when operating at a sample station without ground power. The wording here is placeholder content shaped like a procedure, not a procedure. During landing, the Captain should cross-check the Cockpit Voice Recorder status message unless directed otherwise by the Sample Operations Center. During approach, the Captain should announce the Cockpit Voice Recorder advisory once the checklist item is complete. This text is fictional and exists only to give the prototype realistic volume and structure. The Fuel Crossfeed advisory is expected to read within the sample range of 72 to 80 units during takeoff.

This text is fictional and exists only to give the prototype realistic volume and structure. The Auxiliary Power Unit switch position that differs from the expected state requires both pilots to cross-check the condition unless directed otherwise by the Sample Operations Center. During a turnaround, the First Officer should brief the Window Heat quantity display unless directed otherwise by the Sample Operations Center. Values in this manual are invented and must not be used for any operational purpose. The captain will record any change in the Fuel Crossfeed switch position and advise the other pilot before the next phase of flight. The pilot flying will select any change in the Cockpit Voice Recorder advisory and advise the other pilot once the checklist item is complete.

Both pilots will cross-check any change in the Cabin Pressure Controller quantity display and advise the other pilot when operating at a sample station without ground power. The Probe Heat status message is expected to read within the sample range of 65 to 70 units during an extended ground delay. If the Flap Position Indication is inoperative,

continue a turnaround only after the First Officer has reviewed the associated sample guidance. During takeoff, the relief pilot should confirm the Traffic Advisory Display annunciation if the indication does not stabilize within the sample interval. During a turnaround, both pilots should monitor the Auxiliary Power Unit advisory when conditions permit.

- The wording here is placeholder content shaped like a procedure, not a procedure.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- The Standby Instruments quantity display is expected to read within the sample range of 5 to 13 units during takeoff.

**CAUTION:** Values in this manual are invented and must not be used for any operational purpose. If the Brake Temperature Monitor is inoperative, continue landing only after the pilot monitoring has reviewed the associated sample guidance.

The pilot monitoring will select any change in the Fuel Crossfeed selector position and advise the other pilot once the checklist item is complete. Both pilots will select any change in the Flap Position Indication annunciation and advise the other pilot if the indication does not stabilize within the sample interval. The Auxiliary Power Unit status message that differs from the expected state requires the pilot monitoring to cross-check the condition if a discrepancy is observed.

| Condition                           | Sample value | Remarks       |
|-------------------------------------|--------------|---------------|
| Flap Position Indication indication | 6 units      | Advisory only |
| Probe Heat switch position          | 11 units     | Normal        |
| Hydraulic System B advisory         | 89 units     | Normal        |
| Standby Instruments indication      | 28 units     | Advisory only |

The Oxygen Distribution advisory that differs from the expected state requires the pilot monitoring to select the condition before the next phase of flight. If the Auxiliary Power Unit is inoperative, continue a maintenance-requested ground run only after both pilots has reviewed the associated sample guidance. During preflight, the Captain should select the Pack Temperature Control status message when operating at a sample station without ground power. Both pilots will verify any change in the Autobrake Selector advisory and advise the other pilot when conditions permit. The pilot flying will record any change in the Cargo Smoke Detection annunciation and advise the other pilot when the associated caution light remains illuminated. Values in this manual are invented and must not be used for any operational purpose.

During preflight, the relief pilot should announce the Probe Heat advisory if the indication does not stabilize within the sample interval. The Bleed Air Supply switch position that differs from the expected state requires the relief pilot to cross-check the condition when operating at a sample station without ground power. Refer to the related topic for additional sample context. If the Standby Hydraulic is inoperative, continue engine start only after both pilots has reviewed the associated sample guidance.

| Challenge                | Response    |
|--------------------------|-------------|
| Transponder              | Verified    |
| Fuel Crossfeed           | Off         |
| Autopilot Channel A      | Closed      |
| Bleed Air Supply         | Off         |
| Flap Position Indication | Armed       |
| Autopilot Channel B      | On          |
| Nosewheel Steering       | As required |
| Nosewheel Steering       | Closed      |

|                          |         |
|--------------------------|---------|
| Engine Anti-Ice          | Checked |
| Ground Proximity Monitor | Off     |
| Ground Proximity Monitor | Set     |

05.40.16 *Nosewheel Steering Reset Guidance*

If the Speedbrake Handle is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. During preflight, the pilot flying should brief the Fuel Crossfeed selector position unless directed otherwise by the Sample Operations Center. The captain will monitor any change in the Flight Management Computer status message and advise the other pilot if the indication does not stabilize within the sample interval. The Transponder quantity display is expected to read within the sample range of 61 to 68 units during approach. If the Nosewheel Steering is inoperative, continue approach only after the pilot flying has reviewed the associated sample guidance.

The captain will announce any change in the Fire Detection Loop annunciation and advise the other pilot when the associated caution light remains illuminated. The pilot monitoring will confirm any change in the Autobrake Selector quantity display and advise the other pilot if the indication does not stabilize within the sample interval. Values in this manual are invented and must not be used for any operational purpose.

**CAUTION:** The Hydraulic System B annunciation that differs from the expected state requires the relief pilot to monitor the condition once the checklist item is complete.

Both pilots will brief any change in the Pack Temperature Control quantity display and advise the other pilot once the checklist item is complete. Both pilots will confirm any change in the Weather Radar annunciation and advise the other pilot when the associated caution light remains illuminated. During parking, both pilots should verify the Center Tank Pumps selector position when conditions permit. Refer to the related topic for additional sample context. The pilot monitoring will brief any change in the Cabin Pressure Controller status message and advise the other pilot when the associated caution light remains illuminated. During preflight, the Captain should confirm the Wing Anti-Ice annunciation when operating at a sample station without ground power.

The Flight Management Computer advisory that differs from the expected state requires the pilot flying to monitor the condition unless directed otherwise by the Sample Operations Center. The Auxiliary Power Unit switch position is expected to read within the sample range of 4 to 16 units during cruise. The captain will monitor any change in the Fire Detection Loop selector position and advise the other pilot when operating at a sample station without ground power. During taxi, both pilots should select the Cargo Smoke Detection switch position once the checklist item is complete.

Refer to the related topic for additional sample context. The pilot monitoring will monitor any change in the Center Tank Pumps switch position and advise the other pilot before the next phase of flight. The first officer will brief any change in the Hydraulic System B advisory and advise the other pilot if a discrepancy is observed. If the Auxiliary Power Unit is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance. The relief pilot will record any change in the Autopilot Channel A advisory and advise the other pilot once the checklist item is complete. The pilot monitoring will confirm any change in the Flap Position Indication annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center.

**NOTE:** During a diversion, the Captain should cross-check the Landing Gear Indication quantity display unless directed otherwise by the Sample Operations Center.

| Challenge             | Response    |
|-----------------------|-------------|
| Bleed Air Supply      | As required |
| Probe Heat            | On          |
| Fuel Crossfeed        | Set         |
| Cargo Smoke Detection | As required |
| Oxygen Distribution   | Closed      |



|                          |        |
|--------------------------|--------|
| Ground Proximity Monitor | On     |
| Window Heat              | Closed |
| Autobrake Selector       | Closed |
| Probe Heat               | Armed  |
| Weather Radar            | Set    |
| Hydraulic System A       | Off    |
| Center Tank Pumps        | Closed |

05.40.17 Probe Heat Test

If the Nosewheel Steering is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance. The relief pilot will brief any change in the Autothrottle status message and advise the other pilot if a discrepancy is observed. The Transponder switch position is expected to read within the sample range of 35 to 47 units during a maintenance-requested ground run.

**CAUTION:** The wording here is placeholder content shaped like a procedure, not a procedure. During an extended ground delay, the pilot monitoring should cross-check the Transponder selector position before the next phase of flight.

**CAUTION:** During an extended ground delay, both pilots should monitor the Hydraulic System B annunciation unless directed otherwise by the Sample Operations Center.

**NOTE:** The relief pilot will brief any change in the Auxiliary Power Unit switch position and advise the other pilot if a discrepancy is observed.

| Condition                           | Sample value | Remarks       |
|-------------------------------------|--------------|---------------|
| Nosewheel Steering quantity display | 8 units      | Advisory only |
| Hydraulic System B switch position  | 23 units     | Normal        |
| Stall Warning indication            | 15 units     | Normal        |

During an extended ground delay, the pilot monitoring should verify the Hydraulic System A selector position when operating at a sample station without ground power. During a turnaround, the First Officer should record the Flight Management Computer switch position when operating at a sample station without ground power. The Weather Radar annunciation is expected to read within the sample range of 55 to 61 units during approach. Refer to the related topic for additional sample context. Refer to the related topic for additional sample context. If the Landing Gear Indication is inoperative, continue taxi only after the relief pilot has reviewed the associated sample guidance. See 17.10.2 Engine Anti-Ice Indications.

- The Primary Electrical Bus annunciation is expected to read within the sample range of 26 to 29 units during taxi.
- If the Transponder is inoperative, continue approach only after the pilot monitoring has reviewed the associated sample guidance.
- Values in this manual are invented and must not be used for any operational purpose.
- During a diversion, the pilot flying should verify the Autopilot Channel A indication if the indication does not stabilize within the sample interval.
- If the Standby Instruments is inoperative, continue a diversion only after the relief pilot has reviewed the associated sample guidance.
- The Stall Warning status message that differs from the expected state requires both pilots to cross-check the condition if a discrepancy is observed.

05.40.18 Window Heat Test

The pilot monitoring will select any change in the Cargo Smoke Detection status message and advise the other pilot when conditions permit. If the Stall Warning is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose.

The relief pilot will cross-check any change in the Pack Temperature Control switch position and advise the other pilot when conditions permit. During a maintenance-requested ground run, the First Officer should announce the Flap Position Indication annunciation before the next phase of flight. If the Autopilot Channel B is inoperative, continue descent only after both pilots has reviewed the associated sample guidance.

**NOTE:** If the Flap Position Indication is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance.

**CAUTION:** During taxi, the pilot monitoring should select the Brake Temperature Monitor status message when conditions permit. During landing, the relief pilot should brief the Window Heat annunciation when conditions permit.

The Brake Temperature Monitor quantity display that differs from the expected state requires both pilots to verify the condition if a discrepancy is observed. The Flight Management Computer status message is expected to read within the sample range of 46 to 54 units during landing. The pilot flying will verify any change in the Standby Instruments selector position and advise the other pilot once the checklist item is complete. If the Primary Electrical Bus is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance. The pilot flying will monitor any change in the Ground Proximity Monitor quantity display and advise the other pilot when conditions permit. This text is fictional and exists only to give the prototype realistic volume and structure.

**CAUTION:** Refer to the related topic for additional sample context. The Flight Management Computer indication that differs from the expected state requires the pilot flying to brief the condition when the associated caution light remains illuminated.

- The Flap Position Indication switch position is expected to read within the sample range of 88 to 95 units during a turnaround.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The Cabin Pressure Controller switch position that differs from the expected state requires both pilots to brief the condition unless directed otherwise by the Sample Operations Center.
- This text is fictional and exists only to give the prototype realistic volume and structure.

#### **05.40.19 Flight Management Computer Status Messages**

Both pilots will confirm any change in the Pack Temperature Control advisory and advise the other pilot when the associated caution light remains illuminated. The Center Tank Pumps annunciation that differs from the expected state requires both pilots to brief the condition when operating at a sample station without ground power. The Probe Heat annunciation is expected to read within the sample range of 49 to 61 units during a maintenance-requested ground run.

The Stall Warning quantity display that differs from the expected state requires the relief pilot to brief the condition when the associated caution light remains illuminated. Values in this manual are invented and must not be used for any operational purpose. The relief pilot will confirm any change in the Cockpit Voice Recorder indication and advise the other pilot when operating at a sample station without ground power. The Thrust Reverser indication is expected to read within the sample range of 88 to 100 units during cruise. If the Ground Proximity Monitor is inoperative, continue cruise only after the Captain has reviewed the associated sample guidance.

**CAUTION:** During landing, the First Officer should confirm the Window Heat selector position once the checklist item is complete.

**CAUTION:** Values in this manual are invented and must not be used for any operational purpose. During a turnaround, both pilots should brief the Transponder switch position if the indication does not stabilize within the sample interval.

The Autopilot Channel B indication that differs from the expected state requires the relief pilot to monitor the condition if the indication does not stabilize within the sample interval. If the Autothrottle is inoperative, continue an extended ground delay only after the Captain has reviewed the associated sample guidance. The Autothrottle advisory is expected to read within the sample range of 80 to 88 units during takeoff. The Flap Position Indication switch position that differs from the expected state requires both pilots to confirm the condition unless directed otherwise by the Sample Operations Center.

05.40.20 Stall Warning Indications

If the Brake Temperature Monitor is inoperative, continue a turnaround only after the First Officer has reviewed the associated sample guidance. The Hydraulic System B switch position that differs from the expected state requires the Captain to confirm the condition if the indication does not stabilize within the sample interval. The pilot monitoring will select any change in the Wing Anti-Ice selector position and advise the other pilot when conditions permit. If the Autothrottle is inoperative, continue approach only after the First Officer has reviewed the associated sample guidance.

The Traffic Advisory Display indication is expected to read within the sample range of 77 to 88 units during descent. The pilot monitoring will brief any change in the Probe Heat indication and advise the other pilot if the indication does not stabilize within the sample interval. The Hydraulic System B quantity display that differs from the expected state requires the pilot flying to select the condition once the checklist item is complete. During engine start, both pilots should record the Landing Gear Indication advisory when operating at a sample station without ground power.

| Condition                                   | Sample value | Remarks                |
|---------------------------------------------|--------------|------------------------|
| Cabin Pressure Controller selector position | 36 units     | Normal                 |
| Thrust Reverser selector position           | 70 units     | Refer to related topic |
| Primary Electrical Bus switch position      | 32 units     | Monitor                |

**NOTE:** The Cabin Pressure Controller status message that differs from the expected state requires the pilot flying to verify the condition when operating at a sample station without ground power. The captain will select any change in the Standby Instruments advisory and advise the other pilot when the associated caution light remains illuminated.

**NOTE:** The Speedbrake Handle selector position that differs from the expected state requires the First Officer to monitor the condition when operating at a sample station without ground power. The pilot monitoring will verify any change in the Autothrottle switch position and advise the other pilot once the checklist item is complete.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Autopilot Channel B selector position    | 27 units     | Monitor                |
| Center Tank Pumps selector position      | 6 units      | Refer to related topic |
| Landing Gear Indication quantity display | 21 units     | Advisory only          |
| Fuel Crossfeed annunciation              | 89 units     | Advisory only          |
| Probe Heat advisory                      | 43 units     | Advisory only          |

05.50 Flight Controls

05.50.1 Autothrottle Limits Display

This text is fictional and exists only to give the prototype realistic volume and structure. If the Weather Radar is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance. The captain will cross-check any change in the Ground Proximity Monitor quantity display and advise the other pilot when conditions permit. During a maintenance-requested ground run, the pilot flying should announce the Center Tank Pumps annunciation when operating at a sample station without ground power. This text is fictional and exists only to

give the prototype realistic volume and structure. The captain will confirm any change in the Auxiliary Power Unit selector position and advise the other pilot if the indication does not stabilize within the sample interval.

The Center Tank Pumps advisory is expected to read within the sample range of 90 to 100 units during landing. During descent, the pilot monitoring should monitor the Nosewheel Steering indication when conditions permit. If the Fire Detection Loop is inoperative, continue a maintenance-requested ground run only after the pilot flying has reviewed the associated sample guidance. The pilot monitoring will verify any change in the Bleed Air Supply advisory and advise the other pilot if a discrepancy is observed. If the Weather Radar is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Flap Position Indication switch position | 34 units     | Refer to related topic |
| Autopilot Channel A indication           | 35 units     | Refer to related topic |
| Hydraulic System B indication            | 1 units      | Normal                 |
| Center Tank Pumps quantity display       | 44 units     | Advisory only          |
| Hydraulic System B indication            | 19 units     | Refer to related topic |
| Fire Detection Loop indication           | 52 units     | Advisory only          |

**CAUTION:** If the Primary Electrical Bus is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance. During descent, the pilot monitoring should confirm the Traffic Advisory Display advisory when operating at a sample station without ground power.

The Auxiliary Power Unit switch position that differs from the expected state requires the pilot monitoring to select the condition before the next phase of flight. If the Autobrake Selector is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance. The Traffic Advisory Display indication is expected to read within the sample range of 64 to 67 units during a maintenance-requested ground run. Both pilots will announce any change in the Cockpit Voice Recorder switch position and advise the other pilot when operating at a sample station without ground power.

### 05.50.2 Center Tank Pumps Normal Operation

The Hydraulic System A advisory that differs from the expected state requires both pilots to select the condition once the checklist item is complete. The Autothrottle status message is expected to read within the sample range of 34 to 37 units during an extended ground delay. The pilot flying will cross-check any change in the Autopilot Channel B switch position and advise the other pilot if a discrepancy is observed. During approach, both pilots should confirm the Probe Heat status message before the next phase of flight.

| Condition                                 | Sample value | Remarks |
|-------------------------------------------|--------------|---------|
| Auxiliary Power Unit annunciation         | 84 units     | Normal  |
| Landing Gear Indication selector position | 36 units     | Monitor |
| Wing Anti-Ice annunciation                | 17 units     | Monitor |

| Condition                              | Sample value | Remarks                |
|----------------------------------------|--------------|------------------------|
| Fire Detection Loop selector position  | 19 units     | Monitor                |
| Oxygen Distribution annunciation       | 65 units     | Refer to related topic |
| Autopilot Channel B indication         | 68 units     | Advisory only          |
| Fire Detection Loop annunciation       | 79 units     | Advisory only          |
| Center Tank Pumps annunciation         | 32 units     | Monitor                |
| Window Heat indication                 | 40 units     | Monitor                |
| Auxiliary Power Unit selector position | 61 units     | Refer to related topic |

- Refer to the related topic for additional sample context.
- During descent, the pilot monitoring should announce the Nosewheel Steering indication if the indication does not stabilize within the sample interval.
- Values in this manual are invented and must not be used for any operational purpose.

During approach, the pilot monitoring should cross-check the Brake Temperature Monitor indication before the next phase of flight. The Thrust Reverser switch position that differs from the expected state requires both pilots to verify the condition if a discrepancy is observed. The pilot flying will brief any change in the Autobrake Selector advisory and advise the other pilot when the associated caution light remains illuminated. Values in this manual are invented and must not be used for any operational purpose. During takeoff, the pilot flying should record the Ground Proximity Monitor quantity display when the associated caution light remains illuminated.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Landing Gear Indication indication         | 66 units     | Advisory only          |
| Brake Temperature Monitor quantity display | 32 units     | Normal                 |
| Cabin Pressure Controller status message   | 65 units     | Advisory only          |
| Transponder quantity display               | 25 units     | Normal                 |
| Ground Proximity Monitor status message    | 52 units     | Refer to related topic |

| Condition                                   | Sample value | Remarks                |
|---------------------------------------------|--------------|------------------------|
| Engine Anti-Ice switch position             | 1 units      | Refer to related topic |
| Engine Anti-Ice indication                  | 26 units     | Advisory only          |
| Transponder status message                  | 7 units      | Normal                 |
| Fuel Crossfeed quantity display             | 59 units     | Refer to related topic |
| Bleed Air Supply annunciation               | 97 units     | Monitor                |
| Hydraulic System B indication               | 72 units     | Monitor                |
| Flight Management Computer quantity display | 89 units     | Monitor                |

- The Autopilot Channel A indication that differs from the expected state requires the pilot monitoring to select the condition when operating at a sample station without ground power.
- The Fire Detection Loop indication that differs from the expected state requires both pilots to monitor the condition once the checklist item is complete.
- The Nosewheel Steering advisory that differs from the expected state requires both pilots to select the condition when operating at a sample station without ground power.
- During landing, the Captain should monitor the Flap Position Indication switch position if the indication does not stabilize within the sample interval.
- Values in this manual are invented and must not be used for any operational purpose.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Hydraulic System A switch position    | 29 units     | Normal                 |
| Center Tank Pumps status message      | 20 units     | Advisory only          |
| Probe Heat status message             | 6 units      | Normal                 |
| Autopilot Channel A selector position | 97 units     | Refer to related topic |
| Standby Hydraulic annunciation        | 30 units     | Normal                 |
| Center Tank Pumps quantity display    | 10 units     | Advisory only          |

| Challenge                  | Response    |
|----------------------------|-------------|
| Center Tank Pumps          | Closed      |
| Bleed Air Supply           | Off         |
| Pack Temperature Control   | Armed       |
| Standby Instruments        | As required |
| Auxiliary Power Unit       | On          |
| Flight Management Computer | Checked     |
| Cargo Smoke Detection      | Verified    |
| Hydraulic System A         | Checked     |
| Traffic Advisory Display   | Set         |

### 05.50.3 Nosewheel Steering Overview

The pilot flying will cross-check any change in the Thrust Reverser advisory and advise the other pilot when conditions permit. During engine start, the pilot flying should verify the Wing Anti-Ice indication if a discrepancy is observed. The Probe Heat indication that differs from the expected state requires the First Officer to verify the condition once the checklist item is complete. During preflight, both pilots should monitor the Flight Management Computer quantity display unless directed otherwise by the Sample Operations Center.

**CAUTION:** If the Window Heat is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance.

- The wording here is placeholder content shaped like a procedure, not a procedure.
- The first officer will monitor any change in the Weather Radar selector position and advise the other pilot before the next phase of flight.
- If the Nosewheel Steering is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance.

The pilot monitoring will announce any change in the Auxiliary Power Unit status message and advise the other pilot when the associated caution light remains illuminated. The relief pilot will monitor any change in the Flight Management Computer selector position and advise the other pilot once the checklist item is complete. The Window Heat quantity display is expected to read within the sample range of 33 to 42 units during a maintenance-requested ground run. The Autopilot Channel B switch position is expected to read within the sample range of 66 to 69 units during takeoff. See 03.50.12 Verification: Autopilot Channel B.

| Condition                            | Sample value | Remarks                |
|--------------------------------------|--------------|------------------------|
| Cargo Smoke Detection status message | 33 units     | Normal                 |
| Stall Warning switch position        | 39 units     | Advisory only          |
| Auxiliary Power Unit indication      | 4 units      | Refer to related topic |
| Hydraulic System B advisory          | 11 units     | Monitor                |
| Standby Hydraulic indication         | 43 units     | Refer to related topic |
| Landing Gear Indication indication   | 13 units     | Advisory only          |

**NOTE:** The Transponder annunciation is expected to read within the sample range of 21 to 32 units during climb.

| Challenge             | Response |
|-----------------------|----------|
| Cargo Smoke Detection | Verified |
| Engine Anti-Ice       | Armed    |



|                          |          |
|--------------------------|----------|
| Stall Warning            | Set      |
| Stall Warning            | On       |
| Wing Anti-Ice            | Armed    |
| Speedbrake Handle        | On       |
| Hydraulic System A       | Verified |
| Traffic Advisory Display | Armed    |

05.50.4 Standby Instruments Crew Awareness

The Hydraulic System B selector position is expected to read within the sample range of 30 to 37 units during parking. Values in this manual are invented and must not be used for any operational purpose. The Fuel Crossfeed indication that differs from the expected state requires the pilot flying to select the condition before the next phase of flight. This text is fictional and exists only to give the prototype realistic volume and structure. The Wing Anti-Ice status message that differs from the expected state requires both pilots to monitor the condition if a discrepancy is observed.

If the Hydraulic System B is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance. The Thrust Reverser status message that differs from the expected state requires the pilot flying to confirm the condition when the associated caution light remains illuminated. During taxi, the pilot flying should confirm the Speedbrake Handle selector position unless directed otherwise by the Sample Operations Center.

| Condition                               | Sample value | Remarks       |
|-----------------------------------------|--------------|---------------|
| Primary Electrical Bus quantity display | 15 units     | Monitor       |
| Cargo Smoke Detection status message    | 82 units     | Monitor       |
| Stall Warning status message            | 46 units     | Advisory only |

The Stall Warning switch position is expected to read within the sample range of 76 to 87 units during a maintenance-requested ground run. The Bleed Air Supply quantity display that differs from the expected state requires both pilots to announce the condition before the next phase of flight. The Hydraulic System B annunciation is expected to read within the sample range of 66 to 70 units during descent.

The Auxiliary Power Unit advisory is expected to read within the sample range of 80 to 91 units during preflight. During climb, the First Officer should confirm the Brake Temperature Monitor status message when operating at a sample station without ground power. If the Center Tank Pumps is inoperative, continue a maintenance-requested ground run only after the pilot flying has reviewed the associated sample guidance.

During climb, the First Officer should select the Traffic Advisory Display advisory if a discrepancy is observed. If the Bleed Air Supply is inoperative, continue descent only after both pilots has reviewed the associated sample guidance. The Autothrottle annunciation that differs from the expected state requires the relief pilot to confirm the condition if the indication does not stabilize within the sample interval.

**NOTE:** If the Autopilot Channel B is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance.

05.50.5 Flight Management Computer Power Sources

The Hydraulic System B quantity display is expected to read within the sample range of 70 to 80 units during approach. The Bleed Air Supply advisory that differs from the expected state requires both pilots to verify the condition once the checklist item is complete. During parking, both pilots should cross-check the Cockpit Voice Recorder advisory when operating at a sample station without ground power. The Engine Anti-Ice selector position is expected to read within the sample range of 77 to 89 units during parking. The Cargo Smoke Detection selector position is expected to read within the sample range of 20 to 31 units during cruise. The Cargo Smoke Detection

quantity display is expected to read within the sample range of 25 to 36 units during takeoff.

The pilot monitoring will select any change in the Bleed Air Supply switch position and advise the other pilot when operating at a sample station without ground power. The first officer will monitor any change in the Nosewheel Steering indication and advise the other pilot when operating at a sample station without ground power. The Autopilot Channel B quantity display is expected to read within the sample range of 18 to 29 units during cruise. The Window Heat annunciation that differs from the expected state requires the Captain to verify the condition when the associated caution light remains illuminated. If the Oxygen Distribution is inoperative, continue a turnaround only after the First Officer has reviewed the associated sample guidance. The Brake Temperature Monitor switch position is expected to read within the sample range of 51 to 54 units during a turnaround.

If the Brake Temperature Monitor is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance. The Cargo Smoke Detection selector position is expected to read within the sample range of 76 to 81 units during climb. The Autopilot Channel B selector position that differs from the expected state requires the relief pilot to monitor the condition if a discrepancy is observed. During climb, the First Officer should announce the Cockpit Voice Recorder selector position before the next phase of flight. The Primary Electrical Bus switch position is expected to read within the sample range of 8 to 16 units during parking.

The Oxygen Distribution indication that differs from the expected state requires the First Officer to announce the condition when operating at a sample station without ground power. The captain will select any change in the Standby Hydraulic switch position and advise the other pilot if a discrepancy is observed. The Landing Gear Indication advisory is expected to read within the sample range of 5 to 15 units during descent. The pilot monitoring will select any change in the Autopilot Channel A selector position and advise the other pilot when conditions permit. During landing, the Captain should record the Stall Warning indication if the indication does not stabilize within the sample interval. Refer to the related topic for additional sample context.

During preflight, the First Officer should confirm the Nosewheel Steering status message when conditions permit. If the Oxygen Distribution is inoperative, continue parking only after the pilot monitoring has reviewed the associated sample guidance. The Ground Proximity Monitor status message is expected to read within the sample range of 14 to 25 units during a turnaround. The relief pilot will cross-check any change in the Hydraulic System A annunciation and advise the other pilot when conditions permit. The Wing Anti-Ice advisory is expected to read within the sample range of 65 to 73 units during takeoff. The Hydraulic System B indication is expected to read within the sample range of 88 to 98 units during taxi.

During a maintenance-requested ground run, the pilot flying should verify the Traffic Advisory Display quantity display unless directed otherwise by the Sample Operations Center. If the Cockpit Voice Recorder is inoperative, continue parking only after the Captain has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. During climb, both pilots should cross-check the Engine Anti-Ice quantity display when the associated caution light remains illuminated. The first officer will monitor any change in the Wing Anti-Ice indication and advise the other pilot when conditions permit. During a maintenance-requested ground run, the pilot monitoring should record the Oxygen Distribution annunciation if a discrepancy is observed. See 05.20.8 Transponder Limits Display.

- The Stall Warning status message that differs from the expected state requires the pilot flying to verify the condition when conditions permit.
- The Cargo Smoke Detection advisory that differs from the expected state requires the pilot monitoring to announce the condition when operating at a sample station without ground power.
- The pilot monitoring will brief any change in the Nosewheel Steering indication and advise the other pilot once the checklist item is complete.
- The Flight Management Computer status message is expected to read within the sample range of 58 to 66 units during cruise.
- The Autopilot Channel B indication that differs from the expected state requires the pilot flying to verify the condition before the next phase of flight.

- The Wing Anti-Ice status message that differs from the expected state requires both pilots to brief the condition unless directed otherwise by the Sample Operations Center.

| Challenge                | Response    |
|--------------------------|-------------|
| Pack Temperature Control | Closed      |
| Speedbrake Handle        | On          |
| Autopilot Channel B      | Closed      |
| Nosewheel Steering       | As required |
| Landing Gear Indication  | Set         |
| Traffic Advisory Display | Verified    |
| Autobrake Selector       | Set         |
| Stall Warning            | Checked     |

### 05.50.6 Engine Anti-Ice Test

During approach, the Captain should cross-check the Transponder selector position once the checklist item is complete. The Landing Gear Indication annunciation is expected to read within the sample range of 30 to 33 units during a turnaround. The pilot monitoring will cross-check any change in the Autopilot Channel B switch position and advise the other pilot once the checklist item is complete. During takeoff, the pilot flying should monitor the Auxiliary Power Unit indication if the indication does not stabilize within the sample interval. During a turnaround, both pilots should verify the Engine Anti-Ice indication when operating at a sample station without ground power.

- During a turnaround, the First Officer should announce the Transponder indication before the next phase of flight.
- The pilot monitoring will verify any change in the Ground Proximity Monitor annunciation and advise the other pilot if a discrepancy is observed.
- If the Bleed Air Supply is inoperative, continue a diversion only after the relief pilot has reviewed the associated sample guidance.
- The Wing Anti-Ice selector position that differs from the expected state requires both pilots to monitor the condition if a discrepancy is observed.
- Refer to the related topic for additional sample context.
- If the Primary Electrical Bus is inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance.
- During a diversion, both pilots should confirm the Flap Position Indication selector position once the checklist item is complete.
- If the Hydraulic System A is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance.
- The pilot monitoring will verify any change in the Ground Proximity Monitor advisory and advise the other pilot unless directed otherwise by the Sample Operations Center.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Stall Warning advisory                   | 71 units     | Refer to related topic |
| Landing Gear Indication status message   | 22 units     | Advisory only          |
| Flap Position Indication switch position | 46 units     | Monitor                |
| Hydraulic System A selector position     | 12 units     | Normal                 |
| Oxygen Distribution annunciation         | 96 units     | Monitor                |
| Fuel Crossfeed indication                | 63 units     | Refer to related topic |

The Transponder indication that differs from the expected state requires the First Officer to monitor the condition once the checklist item is complete. The Probe Heat quantity display is expected to read within the sample range of 50 to 62 units during engine start. Both pilots will select any change in the Fire Detection Loop advisory and advise the other pilot when conditions permit. The Flap Position Indication selector position is expected to read within the sample range of 64 to 69 units during an extended ground delay. If the Thrust Reverser is inoperative, continue climb only after both pilots has reviewed the associated sample guidance. The Traffic Advisory Display switch position that differs from the expected state requires both pilots to announce the condition when the associated caution light remains illuminated.

| Challenge                 | Response    |
|---------------------------|-------------|
| Transponder               | Armed       |
| Cabin Pressure Controller | Set         |
| Ground Proximity Monitor  | As required |
| Standby Instruments       | Set         |
| Window Heat               | Verified    |
| Window Heat               | Checked     |
| Fuel Crossfeed            | As required |
| Cargo Smoke Detection     | Checked     |

### 05.50.7 Autopilot Channel A Indications

This text is fictional and exists only to give the prototype realistic volume and structure. The captain will confirm any change in the Auxiliary Power Unit status message and advise the other pilot unless directed otherwise by the Sample Operations Center. The Bleed Air Supply quantity display that differs from the expected state requires both pilots to brief the condition if a discrepancy is observed. If the Cockpit Voice Recorder is inoperative, continue climb only after the Captain has reviewed the associated sample guidance.

If the Landing Gear Indication is inoperative, continue engine start only after the Captain has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. The Hydraulic System B advisory that differs from the expected state requires the relief pilot to verify the condition when conditions permit.

**CAUTION:** During a turnaround, both pilots should confirm the Pack Temperature Control advisory when conditions permit.

The Center Tank Pumps status message that differs from the expected state requires both pilots to select the condition before the next phase of flight. The Fuel Crossfeed switch position is expected to read within the sample range of 81 to 86 units during cruise. During landing, the pilot flying should brief the Bleed Air Supply indication when the associated caution light remains illuminated. The Landing Gear Indication switch position is expected to read within the sample range of 41 to 52 units during approach. If the Flap Position Indication is inoperative, continue engine start only after the Captain has reviewed the associated sample guidance. See 08.20.3 Thrust Reverser Crew Awareness.

| Condition                            | Sample value | Remarks                |
|--------------------------------------|--------------|------------------------|
| Engine Anti-Ice quantity display     | 84 units     | Monitor                |
| Primary Electrical Bus indication    | 50 units     | Advisory only          |
| Brake Temperature Monitor indication | 73 units     | Refer to related topic |
| Cockpit Voice Recorder indication    | 88 units     | Normal                 |
| Center Tank Pumps annunciation       | 36 units     | Normal                 |
| Window Heat advisory                 | 76 units     | Refer to related topic |

|                            |          |               |
|----------------------------|----------|---------------|
| Center Tank Pumps advisory | 27 units | Advisory only |
|----------------------------|----------|---------------|

| Condition                             | Sample value | Remarks       |
|---------------------------------------|--------------|---------------|
| Weather Radar quantity display        | 31 units     | Monitor       |
| Pack Temperature Control annunciation | 37 units     | Advisory only |
| Fuel Crossfeed switch position        | 94 units     | Normal        |

**CAUTION:** The Cargo Smoke Detection switch position is expected to read within the sample range of 55 to 59 units during a maintenance-requested ground run.

| Challenge                  | Response    |
|----------------------------|-------------|
| Window Heat                | As required |
| Flight Management Computer | Verified    |
| Primary Electrical Bus     | Closed      |
| Autobrake Selector         | Checked     |
| Wing Anti-Ice              | Off         |
| Center Tank Pumps          | As required |
| Autopilot Channel A        | Off         |

05.50.8 Standby Instruments Power Sources

This text is fictional and exists only to give the prototype realistic volume and structure. The captain will verify any change in the Speedbrake Handle annunciation and advise the other pilot when operating at a sample station without ground power. If the Stall Warning is inoperative, continue preflight only after the Captain has reviewed the associated sample guidance. The Landing Gear Indication annunciation that differs from the expected state requires the pilot flying to announce the condition when operating at a sample station without ground power.

**NOTE:** The first officer will monitor any change in the Fuel Crossfeed quantity display and advise the other pilot when operating at a sample station without ground power. This text is fictional and exists only to give the prototype realistic volume and structure.

| Condition                             | Sample value | Remarks       |
|---------------------------------------|--------------|---------------|
| Nosewheel Steering switch position    | 95 units     | Advisory only |
| Stall Warning switch position         | 17 units     | Advisory only |
| Traffic Advisory Display annunciation | 31 units     | Monitor       |
| Thrust Reverser quantity display      | 93 units     | Advisory only |

| Condition                                  | Sample value | Remarks       |
|--------------------------------------------|--------------|---------------|
| Pack Temperature Control quantity display  | 20 units     | Advisory only |
| Cabin Pressure Controller quantity display | 32 units     | Monitor       |
| Brake Temperature Monitor advisory         | 60 units     | Normal        |
| Traffic Advisory Display switch position   | 19 units     | Advisory only |

If the Center Tank Pumps is inoperative, continue engine start only after the relief pilot has reviewed the associated sample guidance. The relief pilot will verify any change in the Thrust Reverser selector position and advise the other pilot when the associated caution light remains illuminated. Refer to the related topic for additional sample context. The Fuel Crossfeed status message that differs from the expected state requires the Captain to brief the condition if the indication does not stabilize within the sample interval.

The relief pilot will monitor any change in the Auxiliary Power Unit indication and advise the other pilot when the associated caution light remains illuminated. Values in this manual are invented and must not be used for any operational purpose. During engine start, the Captain should announce the Flight Management Computer advisory if a discrepancy is observed. Values in this manual are invented and must not be used for any operational purpose.

This text is fictional and exists only to give the prototype realistic volume and structure. Refer to the related topic for additional sample context. The pilot flying will monitor any change in the Flight Management Computer advisory and advise the other pilot before the next phase of flight. The Standby Hydraulic annunciation that differs from the expected state requires the pilot flying to verify the condition when conditions permit.

The Autobrake Selector indication is expected to read within the sample range of 40 to 45 units during approach. Values in this manual are invented and must not be used for any operational purpose. The relief pilot will cross-check any change in the Hydraulic System A switch position and advise the other pilot when operating at a sample station without ground power.

**NOTE:** During a maintenance-requested ground run, the pilot monitoring should announce the Thrust Reverser advisory unless directed otherwise by the Sample Operations Center. The Thrust Reverser switch position is expected to read within the sample range of 21 to 29 units during preflight.

### 05.50.9 Autopilot Channel B Indications

The pilot monitoring will monitor any change in the Hydraulic System B advisory and advise the other pilot once the checklist item is complete. Refer to the related topic for additional sample context. If the Cockpit Voice Recorder is inoperative, continue taxi only after the Captain has reviewed the associated sample guidance. If the Landing Gear Indication is inoperative, continue climb only after the pilot flying has reviewed the associated sample guidance.

**CAUTION:** The Oxygen Distribution quantity display that differs from the expected state requires the First Officer to monitor the condition when conditions permit. If the Autopilot Channel B is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance.

Values in this manual are invented and must not be used for any operational purpose. The Window Heat indication that differs from the expected state requires the pilot flying to announce the condition if the indication does not stabilize within the sample interval. The first officer will confirm any change in the Cockpit Voice Recorder switch position and advise the other pilot if a discrepancy is observed.

- The captain will brief any change in the Flight Management Computer status message and advise the other pilot once the checklist item is complete.
- The Cockpit Voice Recorder selector position that differs from the expected state requires the relief pilot to select the condition unless directed otherwise by the Sample Operations Center.
- If the Nosewheel Steering is inoperative, continue cruise only after both pilots has reviewed the associated sample guidance.
- The Thrust Reverser status message that differs from the expected state requires the relief pilot to monitor the condition if a discrepancy is observed.
- The first officer will record any change in the Autothrottle annunciation and advise the other pilot when conditions permit.
- The first officer will cross-check any change in the Auxiliary Power Unit indication and advise the other pilot if a discrepancy is observed.

Values in this manual are invented and must not be used for any operational purpose. Values in this manual are invented and must not be used for any operational purpose. The captain will select any change in the Cockpit Voice Recorder selector position and advise the other pilot if the indication does not stabilize within the sample interval. Refer to the related topic for additional sample context. The relief pilot will verify any change in the Primary Electrical Bus advisory and advise the other pilot when conditions permit.



**CAUTION:** This text is fictional and exists only to give the prototype realistic volume and structure. During cruise, the Captain should verify the Bleed Air Supply switch position when the associated caution light remains illuminated.

| Condition                     | Sample value | Remarks                |
|-------------------------------|--------------|------------------------|
| Transponder selector position | 72 units     | Advisory only          |
| Probe Heat annunciation       | 58 units     | Refer to related topic |
| Nosewheel Steering advisory   | 56 units     | Normal                 |

**CAUTION:** The pilot flying will verify any change in the Autothrottle annunciation and advise the other pilot before the next phase of flight.

| Challenge                 | Response    |
|---------------------------|-------------|
| Transponder               | On          |
| Stall Warning             | Set         |
| Cabin Pressure Controller | As required |
| Center Tank Pumps         | Off         |
| Traffic Advisory Display  | Set         |
| Hydraulic System B        | Set         |
| Probe Heat                | Off         |
| Center Tank Pumps         | Checked     |
| Landing Gear Indication   | As required |
| Standby Instruments       | As required |
| Standby Instruments       | Closed      |

**05.50.10 Landing Gear Indication Overview**

The Window Heat indication that differs from the expected state requires the Captain to monitor the condition if a discrepancy is observed. The captain will cross-check any change in the Hydraulic System A switch position and advise the other pilot when the associated caution light remains illuminated. The wording here is placeholder content shaped like a procedure, not a procedure.

| Condition                                   | Sample value | Remarks       |
|---------------------------------------------|--------------|---------------|
| Nosewheel Steering advisory                 | 9 units      | Normal        |
| Traffic Advisory Display quantity display   | 45 units     | Normal        |
| Transponder quantity display                | 89 units     | Advisory only |
| Center Tank Pumps switch position           | 85 units     | Monitor       |
| Transponder advisory                        | 98 units     | Advisory only |
| Flight Management Computer quantity display | 55 units     | Advisory only |

If the Brake Temperature Monitor is inoperative, continue a turnaround only after the pilot monitoring has reviewed the associated sample guidance. During a diversion, the First Officer should record the Thrust Reverser indication if the indication does not stabilize within the sample interval. During approach, the Captain should record the Probe Heat switch position when conditions permit. The pilot flying will verify any change in the Autothrottle indication and advise the other pilot before the next phase of flight. The captain will brief any change in the Thrust Reverser quantity display and advise the other pilot before the next phase of flight. Refer to the related topic for additional sample context.

During a turnaround, the pilot flying should cross-check the Autothrottle indication if a discrepancy is observed. If the Nosewheel Steering is inoperative, continue approach only after the Captain has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. Both pilots will verify any change in the Transponder advisory and advise the other pilot unless directed otherwise by the Sample Operations Center.

If the Fuel Crossfeed is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance. During climb, the pilot monitoring should brief the Standby Instruments indication if a discrepancy is observed. If the Hydraulic System B is inoperative, continue preflight only after the pilot monitoring has reviewed the associated sample guidance. The Landing Gear Indication status message is expected to read within the sample range of 48 to 52 units during approach. If the Primary Electrical Bus is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance. The Nosewheel Steering indication is expected to read within the sample range of 3 to 13 units during taxi.

Refer to the related topic for additional sample context. If the Wing Anti-Ice is inoperative, continue descent only after the First Officer has reviewed the associated sample guidance. The Transponder switch position that differs from the expected state requires the First Officer to monitor the condition when operating at a sample station without ground power. If the Wing Anti-Ice is inoperative, continue descent only after the First Officer has reviewed the associated sample guidance.

The Brake Temperature Monitor advisory that differs from the expected state requires the relief pilot to cross-check the condition once the checklist item is complete. The captain will select any change in the Center Tank Pumps status message and advise the other pilot if a discrepancy is observed. Values in this manual are invented and must not be used for any operational purpose. Refer to the related topic for additional sample context.

The pilot monitoring will announce any change in the Wing Anti-Ice quantity display and advise the other pilot before the next phase of flight. The relief pilot will monitor any change in the Engine Anti-Ice quantity display and advise the other pilot if the indication does not stabilize within the sample interval. The Transponder status message is expected to read within the sample range of 10 to 17 units during a diversion. During preflight, the pilot flying should monitor the Flight Management Computer quantity display if the indication does not stabilize within the sample interval. During approach, the relief pilot should verify the Wing Anti-Ice indication unless directed otherwise by the Sample Operations Center.

**NOTE:** If the Weather Radar is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance.

| Challenge                 | Response |
|---------------------------|----------|
| Ground Proximity Monitor  | Closed   |
| Center Tank Pumps         | Closed   |
| Stall Warning             | On       |
| Autobrake Selector        | Checked  |
| Cabin Pressure Controller | On       |
| Thrust Reverser           | Verified |
| Cargo Smoke Detection     | On       |
| Standby Instruments       | Set      |

**05.50.11 Auxiliary Power Unit Test**

The Autopilot Channel B switch position is expected to read within the sample range of 38 to 50 units during cruise. During takeoff, the pilot monitoring should record the Cockpit Voice Recorder annunciation unless directed otherwise by the Sample Operations Center. During engine start, both pilots should select the Speedbrake Handle advisory when conditions permit. The Pack Temperature Control annunciation is expected to read within the sample range of 89 to 101 units during taxi. If the Flight Management Computer is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance.

**NOTE:** The wording here is placeholder content shaped like a procedure, not a procedure.

**CAUTION:** During a maintenance-requested ground run, the First Officer should select the Standby Instruments status message when operating at a sample station without ground power.

**CAUTION:** If the Landing Gear Indication is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance. During preflight, the pilot monitoring should announce the Speedbrake Handle status message when operating at a sample station without ground power.

If the Thrust Reverser is inoperative, continue approach only after the relief pilot has reviewed the associated sample guidance. The Stall Warning annunciation is expected to read within the sample range of 78 to 88 units during descent. The pilot monitoring will verify any change in the Standby Instruments advisory and advise the other pilot when the associated caution light remains illuminated. The Cargo Smoke Detection advisory is expected to read within the sample range of 12 to 18 units during a maintenance-requested ground run. This text is fictional and exists only to give the prototype realistic volume and structure.

**NOTE:** The wording here is placeholder content shaped like a procedure, not a procedure. Values in this manual are invented and must not be used for any operational purpose.

| Challenge                  | Response    |
|----------------------------|-------------|
| Flight Management Computer | Closed      |
| Engine Anti-Ice            | Off         |
| Cargo Smoke Detection      | Verified    |
| Auxiliary Power Unit       | Verified    |
| Cabin Pressure Controller  | Checked     |
| Window Heat                | Verified    |
| Hydraulic System A         | Checked     |
| Autopilot Channel B        | Checked     |
| Cabin Pressure Controller  | As required |
| Window Heat                | On          |

05.50.12 Oxygen Distribution Power Sources

During a diversion, the pilot monitoring should confirm the Window Heat advisory when conditions permit. The Fire Detection Loop advisory is expected to read within the sample range of 33 to 40 units during engine start. Values in this manual are invented and must not be used for any operational purpose. The relief pilot will record any change in the Auxiliary Power Unit indication and advise the other pilot unless directed otherwise by the Sample Operations Center. The Hydraulic System A quantity display that differs from the expected state requires the First Officer to brief the condition if the indication does not stabilize within the sample interval.

The wording here is placeholder content shaped like a procedure, not a procedure. This text is fictional and exists only to give the prototype realistic volume and structure. During climb, both pilots should announce the Ground Proximity Monitor annunciation unless directed otherwise by the Sample Operations Center.

**NOTE:** The Weather Radar quantity display is expected to read within the sample range of 9 to 16 units during a maintenance-requested ground run.

**NOTE:** During a diversion, the relief pilot should confirm the Traffic Advisory Display advisory when conditions permit.

**CAUTION:** If the Thrust Reverser is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance. The Oxygen Distribution annunciation is expected to read within the sample range of 12 to 15 units during an extended ground delay.

- The Transponder selector position that differs from the expected state requires both pilots to cross-check the condition when operating at a sample station without ground power.
- The Stall Warning status message is expected to read within the sample range of 57 to 68 units during preflight.
- The Standby Hydraulic annunciation that differs from the expected state requires the relief pilot to announce the condition unless directed otherwise by the Sample Operations Center.
- During taxi, the pilot flying should record the Nosewheel Steering switch position when the associated caution light remains illuminated.
- If the Cockpit Voice Recorder is inoperative, continue a maintenance-requested ground run only after the Captain has reviewed the associated sample guidance.
- The Standby Instruments quantity display that differs from the expected state requires the relief pilot to cross-check the condition when operating at a sample station without ground power.

| Condition                         | Sample value | Remarks                |
|-----------------------------------|--------------|------------------------|
| Engine Anti-Ice selector position | 21 units     | Refer to related topic |
| Engine Anti-Ice switch position   | 94 units     | Normal                 |
| Wing Anti-Ice selector position   | 47 units     | Normal                 |

| Challenge                | Response |
|--------------------------|----------|
| Probe Heat               | Checked  |
| Fuel Crossfeed           | Armed    |
| Hydraulic System B       | Closed   |
| Cargo Smoke Detection    | Verified |
| Standby Hydraulic        | Closed   |
| Hydraulic System A       | Off      |
| Window Heat              | Checked  |
| Landing Gear Indication  | Checked  |
| Cargo Smoke Detection    | On       |
| Pack Temperature Control | Verified |
| Standby Instruments      | Set      |

### 05.50.13 Autothrottle Power Sources

The captain will record any change in the Window Heat indication and advise the other pilot when conditions permit. The wording here is placeholder content shaped like a procedure, not a procedure. During a turnaround, the pilot flying should record the Flight Management Computer advisory when the associated caution light remains illuminated. Values in this manual are invented and must not be used for any operational purpose. The Flap Position Indication quantity display that differs from the expected state requires the Captain to brief the condition before the next phase of flight. During landing, the relief pilot should select the Engine Anti-Ice selector position when operating at a sample station without ground power.

**CAUTION:** The Hydraulic System A quantity display is expected to read within the sample range of 29 to 36 units during a turnaround. The Engine Anti-Ice status message is expected to read within the sample range of 43 to 55 units during cruise.

During engine start, the relief pilot should cross-check the Autopilot Channel A quantity display if the indication does not stabilize within the sample interval. Values in this manual are invented and must not be used for any operational purpose. During an extended ground delay, the relief pilot should monitor the Hydraulic System B selector position when operating at a sample station without ground power. The Autothrottle switch position that differs from the

expected state requires the relief pilot to record the condition when operating at a sample station without ground power. During climb, both pilots should announce the Fire Detection Loop advisory when the associated caution light remains illuminated.

During cruise, the pilot flying should cross-check the Auxiliary Power Unit switch position if a discrepancy is observed. The wording here is placeholder content shaped like a procedure, not a procedure. If the Traffic Advisory Display is inoperative, continue taxi only after both pilots has reviewed the associated sample guidance. The pilot monitoring will record any change in the Standby Instruments selector position and advise the other pilot when operating at a sample station without ground power. Values in this manual are invented and must not be used for any operational purpose. If the Autothrottle is inoperative, continue climb only after the relief pilot has reviewed the associated sample guidance.

The first officer will record any change in the Autopilot Channel B switch position and advise the other pilot when operating at a sample station without ground power. The captain will cross-check any change in the Standby Instruments annunciation and advise the other pilot when operating at a sample station without ground power. If the Standby Hydraulic is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance. During a diversion, both pilots should verify the Cockpit Voice Recorder quantity display before the next phase of flight.

- The pilot flying will cross-check any change in the Fire Detection Loop switch position and advise the other pilot unless directed otherwise by the Sample Operations Center.
- The first officer will cross-check any change in the Fire Detection Loop status message and advise the other pilot before the next phase of flight.
- The Speedbrake Handle advisory that differs from the expected state requires both pilots to cross-check the condition when the associated caution light remains illuminated.
- During parking, the relief pilot should monitor the Hydraulic System B switch position unless directed otherwise by the Sample Operations Center.
- During a maintenance-requested ground run, the pilot monitoring should select the Speedbrake Handle advisory unless directed otherwise by the Sample Operations Center.
- The Landing Gear Indication quantity display is expected to read within the sample range of 66 to 69 units during takeoff.

During engine start, the First Officer should select the Autobrake Selector switch position unless directed otherwise by the Sample Operations Center. Refer to the related topic for additional sample context. The captain will monitor any change in the Fuel Crossfeed quantity display and advise the other pilot when operating at a sample station without ground power. Refer to the related topic for additional sample context. During climb, the Captain should confirm the Bleed Air Supply status message once the checklist item is complete. See 18.10.17 Speedbrake Handle Normal Operation.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Transponder status message                 | 8 units      | Normal                 |
| Autopilot Channel B selector position      | 2 units      | Refer to related topic |
| Flight Management Computer advisory        | 36 units     | Refer to related topic |
| Auxiliary Power Unit advisory              | 36 units     | Refer to related topic |
| Autopilot Channel A status message         | 46 units     | Monitor                |
| Ground Proximity Monitor selector position | 70 units     | Normal                 |

| Challenge                 | Response |
|---------------------------|----------|
| Cabin Pressure Controller | Closed   |
| Cargo Smoke Detection     | Set      |

|                     |     |
|---------------------|-----|
| Wing Anti-Ice       | On  |
| Standby Hydraulic   | On  |
| Standby Hydraulic   | Off |
| Oxygen Distribution | Set |

**05.50.14 Standby Instruments Normal Operation**

If the Nosewheel Steering is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance. Both pilots will select any change in the Ground Proximity Monitor annunciation and advise the other pilot when operating at a sample station without ground power. The Brake Temperature Monitor quantity display that differs from the expected state requires the First Officer to verify the condition when the associated caution light remains illuminated. During takeoff, the First Officer should select the Cargo Smoke Detection status message if the indication does not stabilize within the sample interval. The Center Tank Pumps indication that differs from the expected state requires the relief pilot to verify the condition if the indication does not stabilize within the sample interval. Refer to the related topic for additional sample context.

This text is fictional and exists only to give the prototype realistic volume and structure. Values in this manual are invented and must not be used for any operational purpose. The Bleed Air Supply advisory is expected to read within the sample range of 29 to 35 units during a diversion.

During takeoff, both pilots should announce the Flap Position Indication switch position before the next phase of flight. The pilot flying will announce any change in the Standby Instruments quantity display and advise the other pilot when conditions permit. The Ground Proximity Monitor quantity display that differs from the expected state requires the pilot flying to announce the condition unless directed otherwise by the Sample Operations Center. The Speedbrake Handle indication is expected to read within the sample range of 97 to 109 units during an extended ground delay. During a turnaround, the relief pilot should select the Thrust Reverser status message before the next phase of flight.

The relief pilot will confirm any change in the Standby Instruments advisory and advise the other pilot when operating at a sample station without ground power. The Fire Detection Loop status message that differs from the expected state requires the pilot flying to record the condition when conditions permit. The Stall Warning status message that differs from the expected state requires the pilot monitoring to cross-check the condition unless directed otherwise by the Sample Operations Center. This text is fictional and exists only to give the prototype realistic volume and structure. Values in this manual are invented and must not be used for any operational purpose. The Fire Detection Loop quantity display is expected to read within the sample range of 18 to 26 units during an extended ground delay.

Values in this manual are invented and must not be used for any operational purpose. This text is fictional and exists only to give the prototype realistic volume and structure. The Landing Gear Indication advisory that differs from the expected state requires the relief pilot to announce the condition if the indication does not stabilize within the sample interval. During preflight, the Captain should announce the Cockpit Voice Recorder switch position once the checklist item is complete. If the Standby Hydraulic is inoperative, continue a diversion only after the relief pilot has reviewed the associated sample guidance.

**NOTE:** The Flap Position Indication selector position is expected to read within the sample range of 68 to 74 units during parking.

**NOTE:** The Thrust Reverser switch position is expected to read within the sample range of 65 to 72 units during approach. If the Autopilot Channel B is inoperative, continue approach only after both pilots has reviewed the associated sample guidance.

| Challenge                | Response    |
|--------------------------|-------------|
| Flap Position Indication | On          |
| Center Tank Pumps        | Set         |
| Pack Temperature Control | As required |



|                           |             |
|---------------------------|-------------|
| Standby Instruments       | Armed       |
| Cabin Pressure Controller | Off         |
| Traffic Advisory Display  | Set         |
| Traffic Advisory Display  | As required |
| Standby Hydraulic         | Set         |
| Autopilot Channel A       | Armed       |
| Brake Temperature Monitor | Verified    |

**05.50.15 Autopilot Channel B Status Messages**

If the Autopilot Channel A is inoperative, continue engine start only after the pilot monitoring has reviewed the associated sample guidance. During descent, the First Officer should brief the Stall Warning switch position when the associated caution light remains illuminated. The Nosewheel Steering selector position that differs from the expected state requires the pilot flying to select the condition when the associated caution light remains illuminated. During a maintenance-requested ground run, the pilot flying should confirm the Nosewheel Steering switch position unless directed otherwise by the Sample Operations Center.

If the Engine Anti-Ice is inoperative, continue engine start only after both pilots has reviewed the associated sample guidance. If the Fire Detection Loop is inoperative, continue approach only after the pilot flying has reviewed the associated sample guidance. The pilot monitoring will announce any change in the Transponder indication and advise the other pilot when operating at a sample station without ground power.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Fire Detection Loop quantity display      | 36 units     | Advisory only          |
| Engine Anti-Ice advisory                  | 13 units     | Refer to related topic |
| Stall Warning indication                  | 25 units     | Advisory only          |
| Speedbrake Handle selector position       | 17 units     | Monitor                |
| Primary Electrical Bus selector position  | 37 units     | Normal                 |
| Landing Gear Indication selector position | 55 units     | Refer to related topic |
| Stall Warning annunciation                | 38 units     | Advisory only          |

If the Pack Temperature Control is inoperative, continue preflight only after both pilots has reviewed the associated sample guidance. Refer to the related topic for additional sample context. If the Cockpit Voice Recorder is inoperative, continue an extended ground delay only after the Captain has reviewed the associated sample guidance.

**NOTE:** Both pilots will select any change in the Primary Electrical Bus indication and advise the other pilot unless directed otherwise by the Sample Operations Center.

**NOTE:** During climb, both pilots should record the Autothrottle quantity display when operating at a sample station without ground power.

The Fire Detection Loop quantity display is expected to read within the sample range of 16 to 19 units during climb. Refer to the related topic for additional sample context. The Standby Instruments annunciation is expected to read within the sample range of 75 to 83 units during takeoff.

This text is fictional and exists only to give the prototype realistic volume and structure. The Cargo Smoke Detection annunciation is expected to read within the sample range of 87 to 93 units during takeoff. During cruise, the Captain should confirm the Flight Management Computer status message if the indication does not stabilize within the sample interval. The Autopilot Channel A indication is expected to read within the sample range of 87 to 97 units during climb. The pilot monitoring will cross-check any change in the Brake Temperature Monitor selector position and advise the other pilot if a discrepancy is observed.

**CAUTION:** The Brake Temperature Monitor indication is expected to read within the sample range of 59 to 63 units during a turnaround. The wording here is placeholder content shaped like a procedure, not a procedure.

| Challenge                | Response    |
|--------------------------|-------------|
| Landing Gear Indication  | Off         |
| Traffic Advisory Display | Set         |
| Stall Warning            | Off         |
| Hydraulic System B       | On          |
| Cargo Smoke Detection    | On          |
| Transponder              | Armed       |
| Engine Anti-Ice          | On          |
| Autopilot Channel B      | As required |
| Cargo Smoke Detection    | Armed       |
| Standby Instruments      | Closed      |
| Hydraulic System B       | Closed      |

**05.50.16 Brake Temperature Monitor Reset Guidance**

If the Fire Detection Loop is inoperative, continue climb only after both pilots has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. The Transponder switch position is expected to read within the sample range of 65 to 70 units during a maintenance-requested ground run.

If the Cockpit Voice Recorder is inoperative, continue climb only after the First Officer has reviewed the associated sample guidance. During a turnaround, the Captain should verify the Hydraulic System B selector position when the associated caution light remains illuminated. The wording here is placeholder content shaped like a procedure, not a procedure. During a diversion, the First Officer should cross-check the Primary Electrical Bus selector position if the indication does not stabilize within the sample interval. The Transponder selector position that differs from the expected state requires the relief pilot to confirm the condition before the next phase of flight.

The Landing Gear Indication status message is expected to read within the sample range of 21 to 28 units during cruise. If the Pack Temperature Control is inoperative, continue descent only after the pilot flying has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. Values in this manual are invented and must not be used for any operational purpose.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Brake Temperature Monitor advisory        | 37 units     | Normal                 |
| Standby Hydraulic selector position       | 4 units      | Refer to related topic |
| Autopilot Channel B status message        | 40 units     | Advisory only          |
| Landing Gear Indication selector position | 68 units     | Normal                 |

The pilot monitoring will verify any change in the Autobrake Selector selector position and advise the other pilot if a discrepancy is observed. The Hydraulic System A advisory is expected to read within the sample range of 58 to 64 units during a diversion. The Autopilot Channel B status message that differs from the expected state requires the relief pilot to monitor the condition once the checklist item is complete. The pilot monitoring will record any change in the Center Tank Pumps selector position and advise the other pilot when the associated caution light remains illuminated. The Autopilot Channel B switch position that differs from the expected state requires the pilot flying to select the condition if the indication does not stabilize within the sample interval. During a turnaround, the First Officer should brief the Hydraulic System B indication when conditions permit.

| Challenge | Response |
|-----------|----------|
|-----------|----------|

|                        |             |
|------------------------|-------------|
| Auxiliary Power Unit   | Closed      |
| Primary Electrical Bus | Set         |
| Autopilot Channel A    | As required |
| Autobrake Selector     | As required |
| Fire Detection Loop    | Set         |
| Bleed Air Supply       | Off         |

05.50.17 Flight Management Computer Overview

The wording here is placeholder content shaped like a procedure, not a procedure. This text is fictional and exists only to give the prototype realistic volume and structure. The pilot flying will cross-check any change in the Standby Instruments quantity display and advise the other pilot before the next phase of flight. The Fuel Crossfeed annunciation that differs from the expected state requires the pilot monitoring to cross-check the condition when conditions permit. The pilot flying will cross-check any change in the Weather Radar selector position and advise the other pilot if the indication does not stabilize within the sample interval.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Bleed Air Supply indication             | 66 units     | Refer to related topic |
| Stall Warning switch position           | 36 units     | Normal                 |
| Primary Electrical Bus quantity display | 9 units      | Normal                 |
| Standby Instruments switch position     | 28 units     | Advisory only          |
| Auxiliary Power Unit indication         | 85 units     | Advisory only          |

**NOTE:** Values in this manual are invented and must not be used for any operational purpose. If the Pack Temperature Control is inoperative, continue preflight only after both pilots has reviewed the associated sample guidance.

During cruise, the Captain should announce the Landing Gear Indication switch position unless directed otherwise by the Sample Operations Center. The pilot flying will record any change in the Standby Hydraulic selector position and advise the other pilot when the associated caution light remains illuminated. If the Stall Warning is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance. The Transponder quantity display that differs from the expected state requires both pilots to verify the condition if a discrepancy is observed. Values in this manual are invented and must not be used for any operational purpose. If the Oxygen Distribution is inoperative, continue a diversion only after the relief pilot has reviewed the associated sample guidance. See 12.20.13 Fuel Crossfeed Indications.

**CAUTION:** If the Flight Management Computer is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure.

**NOTE:** The Autobrake Selector annunciation is expected to read within the sample range of 50 to 60 units during approach.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Wing Anti-Ice annunciation               | 24 units     | Normal                 |
| Fuel Crossfeed switch position           | 51 units     | Monitor                |
| Landing Gear Indication quantity display | 89 units     | Refer to related topic |

05.50.18 Wing Anti-Ice Crew Awareness

If the Flight Management Computer is inoperative, continue a turnaround only after both pilots has reviewed the associated sample guidance. The Fuel Crossfeed advisory is expected to read within the sample range of 10 to 13 units during a diversion. The Cargo Smoke Detection annunciation that differs from the expected state requires the pilot flying to select the condition when operating at a sample station without ground power.

| Condition                                 | Sample value | Remarks       |
|-------------------------------------------|--------------|---------------|
| Stall Warning annunciation                | 25 units     | Normal        |
| Cargo Smoke Detection switch position     | 79 units     | Advisory only |
| Traffic Advisory Display quantity display | 76 units     | Normal        |
| Cockpit Voice Recorder annunciation       | 77 units     | Normal        |
| Wing Anti-Ice selector position           | 39 units     | Normal        |
| Nosewheel Steering advisory               | 23 units     | Normal        |
| Hydraulic System B status message         | 54 units     | Advisory only |

- The pilot monitoring will verify any change in the Autopilot Channel B selector position and advise the other pilot when operating at a sample station without ground power.
- During a diversion, the pilot flying should monitor the Standby Hydraulic selector position when conditions permit.
- The wording here is placeholder content shaped like a procedure, not a procedure.

Refer to the related topic for additional sample context. The first officer will verify any change in the Oxygen Distribution quantity display and advise the other pilot once the checklist item is complete. The Standby Hydraulic status message is expected to read within the sample range of 21 to 29 units during descent. During an extended ground delay, the pilot flying should verify the Flap Position Indication switch position when operating at a sample station without ground power.

During preflight, the Captain should confirm the Pack Temperature Control quantity display when conditions permit. If the Primary Electrical Bus is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance. If the Cabin Pressure Controller is inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance. The Center Tank Pumps advisory that differs from the expected state requires both pilots to confirm the condition once the checklist item is complete.

**NOTE:** The Pack Temperature Control indication that differs from the expected state requires the relief pilot to announce the condition once the checklist item is complete.

**CAUTION:** During takeoff, the relief pilot should confirm the Transponder status message unless directed otherwise by the Sample Operations Center. During engine start, the pilot flying should announce the Landing Gear Indication selector position if the indication does not stabilize within the sample interval.

### 05.50.19 Thrust Reverser Interfaces

Refer to the related topic for additional sample context. The Autopilot Channel B status message that differs from the expected state requires the Captain to select the condition if the indication does not stabilize within the sample interval. If the Ground Proximity Monitor is inoperative, continue climb only after the First Officer has reviewed the associated sample guidance. During takeoff, the pilot flying should announce the Cockpit Voice Recorder annunciation once the checklist item is complete. If the Landing Gear Indication is inoperative, continue landing only after the Captain has reviewed the associated sample guidance. During an extended ground delay, the First Officer should cross-check the Landing Gear Indication indication if the indication does not stabilize within the sample interval.

**NOTE:** The Fuel Crossfeed advisory that differs from the expected state requires both pilots to announce the condition once the checklist item is complete.

The Window Heat switch position is expected to read within the sample range of 5 to 12 units during a maintenance-requested ground run. The captain will select any change in the Autopilot Channel A quantity display and advise the other pilot before the next phase of flight. Values in this manual are invented and must not be used for any operational purpose. If the Wing Anti-Ice is inoperative, continue cruise only after the First Officer has reviewed the associated sample guidance. The Stall Warning indication that differs from the expected state requires the First Officer to monitor the condition unless directed otherwise by the Sample Operations Center.

- Both pilots will brief any change in the Weather Radar quantity display and advise the other pilot before the next phase of flight.
- If the Fire Detection Loop is inoperative, continue a maintenance-requested ground run only after the pilot monitoring has reviewed the associated sample guidance.
- During landing, the Captain should monitor the Brake Temperature Monitor quantity display when conditions permit.
- If the Hydraulic System B is inoperative, continue descent only after the Captain has reviewed the associated sample guidance.
- The Hydraulic System B annunciation that differs from the expected state requires the relief pilot to brief the condition when the associated caution light remains illuminated.
- The Standby Hydraulic quantity display that differs from the expected state requires the First Officer to cross-check the condition when the associated caution light remains illuminated.

If the Autothrottle is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance. Both pilots will cross-check any change in the Nosewheel Steering selector position and advise the other pilot before the next phase of flight. The Probe Heat advisory is expected to read within the sample range of 64 to 68 units during engine start. The Ground Proximity Monitor status message that differs from the expected state requires the pilot flying to record the condition if the indication does not stabilize within the sample interval.

Values in this manual are invented and must not be used for any operational purpose. Both pilots will announce any change in the Autopilot Channel B indication and advise the other pilot before the next phase of flight. The pilot flying will confirm any change in the Cargo Smoke Detection indication and advise the other pilot when operating at a sample station without ground power. Values in this manual are invented and must not be used for any operational purpose. Both pilots will record any change in the Fire Detection Loop annunciation and advise the other pilot before the next phase of flight. Refer to the related topic for additional sample context.

| Challenge                | Response    |
|--------------------------|-------------|
| Traffic Advisory Display | Closed      |
| Fuel Crossfeed           | As required |
| Fuel Crossfeed           | Set         |
| Oxygen Distribution      | Off         |
| Ground Proximity Monitor | Verified    |
| Nosewheel Steering       | Verified    |

**05.50.20 Autobrake Selector Normal Operation**

The Cabin Pressure Controller indication is expected to read within the sample range of 44 to 52 units during a diversion. The wording here is placeholder content shaped like a procedure, not a procedure. Both pilots will brief any change in the Brake Temperature Monitor selector position and advise the other pilot when operating at a sample station without ground power. During a diversion, the pilot flying should monitor the Pack Temperature Control annunciation when conditions permit.

Values in this manual are invented and must not be used for any operational purpose. The Autothrottle indication is expected to read within the sample range of 96 to 102 units during engine start. During engine start, the First Officer should verify the Transponder status message once the checklist item is complete. The Brake Temperature Monitor selector position is expected to read within the sample range of 91 to 102 units during an extended ground delay.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Cabin Pressure Controller indication     | 39 units     | Advisory only          |
| Cargo Smoke Detection status message     | 19 units     | Refer to related topic |
| Cabin Pressure Controller status message | 93 units     | Refer to related topic |
| Ground Proximity Monitor indication      | 69 units     | Advisory only          |

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Flight Management Computer annunciation | 89 units     | Normal                 |
| Autopilot Channel A annunciation        | 61 units     | Advisory only          |
| Probe Heat switch position              | 43 units     | Refer to related topic |
| Fuel Crossfeed switch position          | 76 units     | Refer to related topic |

- During a diversion, both pilots should record the Auxiliary Power Unit status message once the checklist item is complete.
- The Fuel Crossfeed selector position is expected to read within the sample range of 27 to 39 units during descent.
- The Stall Warning advisory that differs from the expected state requires the relief pilot to confirm the condition before the next phase of flight.
- If the Engine Anti-Ice is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance.

| Challenge              | Response    |
|------------------------|-------------|
| Probe Heat             | Set         |
| Nosewheel Steering     | Closed      |
| Oxygen Distribution    | As required |
| Cockpit Voice Recorder | Off         |
| Nosewheel Steering     | Off         |
| Nosewheel Steering     | Off         |

## 05.60 Landing Gear and Brakes

### 05.60.1 Autopilot Channel A Normal Operation

During a maintenance-requested ground run, the Captain should cross-check the Auxiliary Power Unit quantity display when the associated caution light remains illuminated. The Speedbrake Handle advisory that differs from the expected state requires the Captain to verify the condition if a discrepancy is observed. The Transponder selector position that differs from the expected state requires the First Officer to record the condition before the next phase of flight. This text is fictional and exists only to give the prototype realistic volume and structure. The Fire Detection Loop status message that differs from the expected state requires the pilot monitoring to cross-check the condition unless directed otherwise by the Sample Operations Center.

Values in this manual are invented and must not be used for any operational purpose. The Flight Management Computer status message that differs from the expected state requires both pilots to confirm the condition if a discrepancy is observed. If the Flap Position Indication is inoperative, continue a maintenance-requested ground run



only after the Captain has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. The Standby Hydraulic advisory is expected to read within the sample range of 38 to 41 units during a maintenance-requested ground run.

The Wing Anti-Ice switch position that differs from the expected state requires the First Officer to select the condition when operating at a sample station without ground power. The Cargo Smoke Detection indication that differs from the expected state requires the pilot flying to confirm the condition if the indication does not stabilize within the sample interval. The Landing Gear Indication switch position is expected to read within the sample range of 11 to 15 units during cruise. During engine start, the Captain should monitor the Brake Temperature Monitor advisory before the next phase of flight.

**CAUTION:** If the Autopilot Channel B is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance. During takeoff, the pilot monitoring should monitor the Fuel Crossfeed advisory when the associated caution light remains illuminated.

**NOTE:** The pilot flying will confirm any change in the Hydraulic System B selector position and advise the other pilot when conditions permit.

The Transponder advisory is expected to read within the sample range of 94 to 106 units during a maintenance-requested ground run. During parking, the pilot flying should verify the Flap Position Indication indication when operating at a sample station without ground power. Values in this manual are invented and must not be used for any operational purpose.

| Condition                              | Sample value | Remarks                |
|----------------------------------------|--------------|------------------------|
| Fire Detection Loop selector position  | 16 units     | Monitor                |
| Nosewheel Steering quantity display    | 25 units     | Monitor                |
| Window Heat switch position            | 93 units     | Advisory only          |
| Auxiliary Power Unit selector position | 24 units     | Refer to related topic |

**CAUTION:** The Bleed Air Supply selector position that differs from the expected state requires the Captain to verify the condition when the associated caution light remains illuminated.

The pilot monitoring will announce any change in the Stall Warning status message and advise the other pilot if the indication does not stabilize within the sample interval. If the Standby Hydraulic is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance. The Flap Position Indication quantity display that differs from the expected state requires the relief pilot to record the condition if the indication does not stabilize within the sample interval.

| Challenge                  | Response |
|----------------------------|----------|
| Bleed Air Supply           | Set      |
| Ground Proximity Monitor   | Armed    |
| Wing Anti-Ice              | Checked  |
| Traffic Advisory Display   | Off      |
| Nosewheel Steering         | Off      |
| Cargo Smoke Detection      | Set      |
| Traffic Advisory Display   | Off      |
| Hydraulic System A         | Checked  |
| Cockpit Voice Recorder     | Verified |
| Window Heat                | Checked  |
| Flight Management Computer | Set      |
| Autothrottle               | Off      |

05.60.2 Window Heat Power Sources

The pilot monitoring will select any change in the Center Tank Pumps indication and advise the other pilot when conditions permit. Values in this manual are invented and must not be used for any operational purpose. Values in this manual are invented and must not be used for any operational purpose.

If the Standby Instruments is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance. The relief pilot will cross-check any change in the Pack Temperature Control selector position and advise the other pilot when the associated caution light remains illuminated. The Window Heat indication that differs from the expected state requires both pilots to select the condition when operating at a sample station without ground power. The Ground Proximity Monitor advisory that differs from the expected state requires the Captain to record the condition once the checklist item is complete.

- The relief pilot will announce any change in the Fire Detection Loop annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center.
- Refer to the related topic for additional sample context.
- The Standby Instruments annunciation is expected to read within the sample range of 19 to 25 units during preflight.
- If the Probe Heat is inoperative, continue climb only after the pilot flying has reviewed the associated sample guidance.

The Flap Position Indication selector position that differs from the expected state requires the relief pilot to cross-check the condition before the next phase of flight. The Standby Hydraulic quantity display is expected to read within the sample range of 62 to 70 units during engine start. This text is fictional and exists only to give the prototype realistic volume and structure.

If the Fire Detection Loop is inoperative, continue engine start only after the Captain has reviewed the associated sample guidance. The first officer will cross-check any change in the Autobrake Selector selector position and advise the other pilot when the associated caution light remains illuminated. The first officer will announce any change in the Ground Proximity Monitor indication and advise the other pilot once the checklist item is complete. If the Cargo Smoke Detection is inoperative, continue taxi only after the Captain has reviewed the associated sample guidance. See 07.30.7 Probe Heat Crew Awareness.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Cockpit Voice Recorder quantity display | 56 units     | Refer to related topic |
| Primary Electrical Bus annunciation     | 64 units     | Monitor                |
| Bleed Air Supply switch position        | 46 units     | Normal                 |
| Cabin Pressure Controller advisory      | 34 units     | Monitor                |
| Ground Proximity Monitor annunciation   | 68 units     | Monitor                |
| Thrust Reverser indication              | 83 units     | Normal                 |

**NOTE:** The wording here is placeholder content shaped like a procedure, not a procedure. During approach, both pilots should monitor the Primary Electrical Bus advisory when conditions permit.

| Challenge                 | Response    |
|---------------------------|-------------|
| Wing Anti-Ice             | Closed      |
| Autopilot Channel A       | Verified    |
| Fire Detection Loop       | Armed       |
| Ground Proximity Monitor  | Off         |
| Cabin Pressure Controller | As required |
| Thrust Reverser           | As required |

|                           |         |
|---------------------------|---------|
| Cabin Pressure Controller | Set     |
| Pack Temperature Control  | Closed  |
| Hydraulic System B        | Armed   |
| Stall Warning             | Checked |
| Fire Detection Loop       | Set     |
| Fire Detection Loop       | Armed   |

### 05.60.3 Standby Hydraulic Power Sources

The Bleed Air Supply switch position that differs from the expected state requires the First Officer to select the condition if a discrepancy is observed. If the Transponder is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance. The relief pilot will monitor any change in the Autopilot Channel A status message and advise the other pilot unless directed otherwise by the Sample Operations Center. Values in this manual are invented and must not be used for any operational purpose.

- During takeoff, the Captain should cross-check the Brake Temperature Monitor indication when operating at a sample station without ground power.
- The relief pilot will confirm any change in the Bleed Air Supply annunciation and advise the other pilot before the next phase of flight.
- The Auxiliary Power Unit selector position that differs from the expected state requires the relief pilot to confirm the condition once the checklist item is complete.
- The Ground Proximity Monitor quantity display is expected to read within the sample range of 2 to 14 units during approach.
- The Speedbrake Handle status message that differs from the expected state requires both pilots to brief the condition when the associated caution light remains illuminated.
- If the Cockpit Voice Recorder is inoperative, continue parking only after both pilots has reviewed the associated sample guidance.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- The first officer will announce any change in the Traffic Advisory Display indication and advise the other pilot when the associated caution light remains illuminated.
- The first officer will verify any change in the Oxygen Distribution switch position and advise the other pilot when conditions permit.
- Both pilots will cross-check any change in the Autobrake Selector advisory and advise the other pilot when conditions permit.
- The first officer will record any change in the Probe Heat selector position and advise the other pilot when operating at a sample station without ground power.
- The Fuel Crossfeed indication that differs from the expected state requires the pilot flying to brief the condition when conditions permit.
- If the Pack Temperature Control is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance.
- The Flight Management Computer annunciation that differs from the expected state requires the relief pilot to cross-check the condition when the associated caution light remains illuminated.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- This text is fictional and exists only to give the prototype realistic volume and structure.

Refer to the related topic for additional sample context. The Probe Heat annunciation that differs from the expected state requires the Captain to announce the condition before the next phase of flight. The relief pilot will confirm any change in the Auxiliary Power Unit quantity display and advise the other pilot once the checklist item is complete. The Flap Position Indication status message that differs from the expected state requires the pilot monitoring to confirm the condition if the indication does not stabilize within the sample interval. During an extended ground delay, the relief pilot should monitor the Cabin Pressure Controller selector position once the checklist item is complete.

During descent, the First Officer should announce the Auxiliary Power Unit status message unless directed otherwise by the Sample Operations Center. The captain will announce any change in the Bleed Air Supply annunciation and advise the other pilot when the associated caution light remains illuminated. The Auxiliary Power Unit advisory that differs from the expected state requires the First Officer to record the condition before the next phase of flight. The Speedbrake Handle selector position that differs from the expected state requires the relief pilot to cross-check the condition when the associated caution light remains illuminated. The first officer will announce any change in the Stall Warning annunciation and advise the other pilot if the indication does not stabilize within the sample interval.

- The wording here is placeholder content shaped like a procedure, not a procedure.
- The Landing Gear Indication quantity display that differs from the expected state requires the pilot flying to monitor the condition when operating at a sample station without ground power.
- The Hydraulic System A indication is expected to read within the sample range of 21 to 31 units during cruise.

#### **05.60.4 Bleed Air Supply Overview**

This text is fictional and exists only to give the prototype realistic volume and structure. The Flap Position Indication advisory that differs from the expected state requires the Captain to monitor the condition before the next phase of flight. The wording here is placeholder content shaped like a procedure, not a procedure.

- Refer to the related topic for additional sample context.
- If the Center Tank Pumps is inoperative, continue descent only after both pilots has reviewed the associated sample guidance.
- The pilot flying will record any change in the Nosewheel Steering status message and advise the other pilot if the indication does not stabilize within the sample interval.
- The pilot flying will announce any change in the Center Tank Pumps indication and advise the other pilot when operating at a sample station without ground power.
- If the Cargo Smoke Detection is inoperative, continue climb only after the Captain has reviewed the associated sample guidance.
- If the Oxygen Distribution is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance.

The captain will cross-check any change in the Bleed Air Supply status message and advise the other pilot when the associated caution light remains illuminated. During taxi, the Captain should monitor the Flight Management Computer quantity display once the checklist item is complete. The captain will cross-check any change in the Flap Position Indication selector position and advise the other pilot when conditions permit.

If the Pack Temperature Control is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance. During climb, the Captain should monitor the Wing Anti-Ice advisory if the indication does not stabilize within the sample interval. The Hydraulic System A status message is expected to read within the sample range of 22 to 33 units during approach.

- The Cargo Smoke Detection switch position is expected to read within the sample range of 27 to 38 units during a diversion.
- This text is fictional and exists only to give the prototype realistic volume and structure.

- During a maintenance-requested ground run, the pilot monitoring should select the Weather Radar switch position if the indication does not stabilize within the sample interval.

05.60.5 Stall Warning Power Sources

During preflight, the relief pilot should verify the Ground Proximity Monitor indication when operating at a sample station without ground power. During a turnaround, the First Officer should record the Transponder advisory once the checklist item is complete. During landing, the Captain should select the Ground Proximity Monitor selector position when conditions permit. The Autothrottle indication that differs from the expected state requires the relief pilot to verify the condition if the indication does not stabilize within the sample interval. If the Cabin Pressure Controller is inoperative, continue approach only after the Captain has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose.

This text is fictional and exists only to give the prototype realistic volume and structure. The Center Tank Pumps status message is expected to read within the sample range of 60 to 67 units during a turnaround. During cruise, the pilot flying should confirm the Engine Anti-Ice switch position when the associated caution light remains illuminated. The Autopilot Channel B status message that differs from the expected state requires the pilot monitoring to cross-check the condition if the indication does not stabilize within the sample interval. During engine start, the pilot monitoring should record the Fire Detection Loop status message when conditions permit. During takeoff, both pilots should select the Bleed Air Supply status message if a discrepancy is observed.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Cockpit Voice Recorder quantity display   | 77 units     | Refer to related topic |
| Transponder quantity display              | 45 units     | Advisory only          |
| Brake Temperature Monitor switch position | 62 units     | Normal                 |
| Probe Heat indication                     | 45 units     | Refer to related topic |

**CAUTION:** The captain will brief any change in the Autopilot Channel A quantity display and advise the other pilot when operating at a sample station without ground power.

**CAUTION:** The Standby Hydraulic status message that differs from the expected state requires the First Officer to record the condition when the associated caution light remains illuminated. The Fire Detection Loop switch position is expected to read within the sample range of 6 to 14 units during takeoff.

| Condition                           | Sample value | Remarks       |
|-------------------------------------|--------------|---------------|
| Auxiliary Power Unit advisory       | 53 units     | Advisory only |
| Autothrottle status message         | 37 units     | Normal        |
| Oxygen Distribution switch position | 43 units     | Monitor       |

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Fuel Crossfeed switch position        | 80 units     | Refer to related topic |
| Cockpit Voice Recorder indication     | 95 units     | Advisory only          |
| Cargo Smoke Detection switch position | 22 units     | Advisory only          |
| Cockpit Voice Recorder indication     | 54 units     | Normal                 |
| Autopilot Channel A annunciation      | 88 units     | Advisory only          |
| Bleed Air Supply switch position      | 45 units     | Normal                 |
| Transponder advisory                  | 46 units     | Monitor                |

| Challenge              | Response |
|------------------------|----------|
| Nosewheel Steering     | On       |
| Primary Electrical Bus | Closed   |

|                        |         |
|------------------------|---------|
| Window Heat            | Set     |
| Speedbrake Handle      | Off     |
| Cockpit Voice Recorder | Closed  |
| Window Heat            | Checked |
| Cockpit Voice Recorder | Armed   |
| Thrust Reverser        | Closed  |

### 05.60.6 Flap Position Indication Status Messages

During takeoff, the Captain should select the Fire Detection Loop indication if a discrepancy is observed. The Bleed Air Supply annunciation is expected to read within the sample range of 77 to 82 units during a turnaround. The wording here is placeholder content shaped like a procedure, not a procedure. Values in this manual are invented and must not be used for any operational purpose. The Weather Radar quantity display that differs from the expected state requires the Captain to select the condition before the next phase of flight. The pilot monitoring will select any change in the Probe Heat selector position and advise the other pilot when conditions permit.

| Condition                          | Sample value | Remarks                |
|------------------------------------|--------------|------------------------|
| Traffic Advisory Display advisory  | 21 units     | Normal                 |
| Stall Warning selector position    | 7 units      | Advisory only          |
| Speedbrake Handle advisory         | 70 units     | Advisory only          |
| Fuel Crossfeed advisory            | 31 units     | Advisory only          |
| Cabin Pressure Controller advisory | 60 units     | Advisory only          |
| Autopilot Channel A status message | 74 units     | Advisory only          |
| Standby Hydraulic status message   | 24 units     | Refer to related topic |

**NOTE:** During a turnaround, the pilot monitoring should verify the Fire Detection Loop switch position when the associated caution light remains illuminated. During descent, the Captain should monitor the Autobrake Selector quantity display if a discrepancy is observed.

| Condition                                   | Sample value | Remarks       |
|---------------------------------------------|--------------|---------------|
| Cabin Pressure Controller selector position | 40 units     | Normal        |
| Autopilot Channel B annunciation            | 98 units     | Advisory only |
| Primary Electrical Bus advisory             | 28 units     | Advisory only |

The Autobrake Selector status message that differs from the expected state requires the pilot flying to select the condition if the indication does not stabilize within the sample interval. The Fire Detection Loop quantity display is expected to read within the sample range of 12 to 15 units during cruise. The captain will select any change in the Engine Anti-Ice indication and advise the other pilot when operating at a sample station without ground power.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Cockpit Voice Recorder quantity display | 90 units     | Refer to related topic |
| Flap Position Indication annunciation   | 85 units     | Monitor                |
| Autopilot Channel B switch position     | 41 units     | Monitor                |

The Weather Radar switch position is expected to read within the sample range of 16 to 19 units during taxi. Both pilots will announce any change in the Autobrake Selector selector position and advise the other pilot when conditions permit. The Autothrottle annunciation that differs from the expected state requires the Captain to select the condition if a discrepancy is observed. The Ground Proximity Monitor switch position is expected to read within the



sample range of 96 to 100 units during taxi.

**NOTE:** The relief pilot will select any change in the Auxiliary Power Unit quantity display and advise the other pilot if a discrepancy is observed.

**CAUTION:** During a turnaround, the Captain should announce the Cabin Pressure Controller annunciation if a discrepancy is observed. The pilot flying will announce any change in the Traffic Advisory Display status message and advise the other pilot when conditions permit.

**05.60.7 Nosewheel Steering Interfaces**

During a maintenance-requested ground run, the pilot monitoring should verify the Brake Temperature Monitor selector position if a discrepancy is observed. The pilot flying will record any change in the Transponder advisory and advise the other pilot when operating at a sample station without ground power. The Hydraulic System A selector position that differs from the expected state requires the pilot flying to record the condition if a discrepancy is observed. If the Probe Heat is inoperative, continue climb only after both pilots has reviewed the associated sample guidance. If the Autothrottle is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance.

**NOTE:** The Brake Temperature Monitor status message that differs from the expected state requires the pilot monitoring to monitor the condition unless directed otherwise by the Sample Operations Center.

During climb, both pilots should select the Cargo Smoke Detection switch position when the associated caution light remains illuminated. The Flap Position Indication status message is expected to read within the sample range of 51 to 55 units during takeoff. If the Pack Temperature Control is inoperative, continue climb only after both pilots has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. The pilot monitoring will brief any change in the Cockpit Voice Recorder annunciation and advise the other pilot when the associated caution light remains illuminated.

If the Fuel Crossfeed is inoperative, continue approach only after the Captain has reviewed the associated sample guidance. The Transponder switch position that differs from the expected state requires the relief pilot to confirm the condition before the next phase of flight. The relief pilot will brief any change in the Oxygen Distribution status message and advise the other pilot before the next phase of flight.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Autobrake Selector indication         | 65 units     | Advisory only          |
| Autopilot Channel B indication        | 66 units     | Monitor                |
| Primary Electrical Bus status message | 76 units     | Normal                 |
| Speedbrake Handle advisory            | 45 units     | Refer to related topic |

- If the Ground Proximity Monitor is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance.
- The relief pilot will monitor any change in the Traffic Advisory Display switch position and advise the other pilot when the associated caution light remains illuminated.
- The Ground Proximity Monitor quantity display is expected to read within the sample range of 74 to 81 units during a diversion.
- The pilot monitoring will brief any change in the Speedbrake Handle switch position and advise the other pilot when operating at a sample station without ground power.
- The relief pilot will record any change in the Flap Position Indication selector position and advise the other pilot if the indication does not stabilize within the sample interval.
- Values in this manual are invented and must not be used for any operational purpose.

- The first officer will brief any change in the Flap Position Indication status message and advise the other pilot when conditions permit.

**CAUTION:** The Speedbrake Handle annunciation that differs from the expected state requires both pilots to monitor the condition when operating at a sample station without ground power.

### 05.60.8 Thrust Reverser Overview

If the Center Tank Pumps is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance. If the Brake Temperature Monitor is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance. The captain will brief any change in the Autobrake Selector advisory and advise the other pilot once the checklist item is complete. The Auxiliary Power Unit switch position is expected to read within the sample range of 86 to 92 units during parking. The Flight Management Computer annunciation is expected to read within the sample range of 91 to 98 units during parking.

If the Fire Detection Loop is inoperative, continue climb only after the pilot flying has reviewed the associated sample guidance. If the Fire Detection Loop is inoperative, continue preflight only after both pilots has reviewed the associated sample guidance. The captain will monitor any change in the Probe Heat status message and advise the other pilot before the next phase of flight.

If the Wing Anti-Ice is inoperative, continue preflight only after both pilots has reviewed the associated sample guidance. The Cargo Smoke Detection status message that differs from the expected state requires the Captain to announce the condition when conditions permit. During engine start, both pilots should monitor the Autobrake Selector selector position when the associated caution light remains illuminated.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Oxygen Distribution indication        | 67 units     | Refer to related topic |
| Traffic Advisory Display annunciation | 93 units     | Refer to related topic |
| Fuel Crossfeed indication             | 77 units     | Refer to related topic |
| Standby Hydraulic quantity display    | 38 units     | Refer to related topic |
| Nosewheel Steering selector position  | 8 units      | Normal                 |
| Wing Anti-Ice selector position       | 28 units     | Monitor                |
| Thrust Reverser status message        | 55 units     | Refer to related topic |

If the Landing Gear Indication is inoperative, continue taxi only after the relief pilot has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. The Fuel Crossfeed status message is expected to read within the sample range of 61 to 67 units during descent.

| Challenge                  | Response    |
|----------------------------|-------------|
| Bleed Air Supply           | Set         |
| Oxygen Distribution        | Verified    |
| Thrust Reverser            | Checked     |
| Hydraulic System A         | As required |
| Transponder                | Verified    |
| Fuel Crossfeed             | Verified    |
| Pack Temperature Control   | Closed      |
| Ground Proximity Monitor   | Set         |
| Standby Hydraulic          | Verified    |
| Flight Management Computer | Closed      |
| Traffic Advisory Display   | Set         |

### 05.60.9 Stall Warning Interfaces

The pilot monitoring will announce any change in the Oxygen Distribution annunciation and advise the other pilot when the associated caution light remains illuminated. The Transponder switch position is expected to read within the sample range of 69 to 80 units during taxi. During descent, the First Officer should cross-check the Speedbrake Handle quantity display once the checklist item is complete. The pilot flying will confirm any change in the Auxiliary Power Unit selector position and advise the other pilot if a discrepancy is observed. The Autobrake Selector selector position is expected to read within the sample range of 6 to 17 units during takeoff. During takeoff, the pilot flying should record the Autobrake Selector quantity display once the checklist item is complete.

The Ground Proximity Monitor switch position is expected to read within the sample range of 14 to 23 units during a diversion. The Pack Temperature Control quantity display that differs from the expected state requires the relief pilot to select the condition unless directed otherwise by the Sample Operations Center. This text is fictional and exists only to give the prototype realistic volume and structure. During climb, the First Officer should confirm the Hydraulic System B indication if a discrepancy is observed. The pilot flying will brief any change in the Brake Temperature Monitor quantity display and advise the other pilot if a discrepancy is observed. This text is fictional and exists only to give the prototype realistic volume and structure.

During a maintenance-requested ground run, the Captain should confirm the Thrust Reverser switch position if the indication does not stabilize within the sample interval. The captain will verify any change in the Cargo Smoke Detection indication and advise the other pilot before the next phase of flight. The Fuel Crossfeed indication is expected to read within the sample range of 24 to 29 units during a maintenance-requested ground run. During descent, the Captain should confirm the Flap Position Indication annunciation before the next phase of flight.

During takeoff, the Captain should select the Bleed Air Supply status message when conditions permit. During engine start, the First Officer should monitor the Hydraulic System B status message when conditions permit. Both pilots will select any change in the Flight Management Computer switch position and advise the other pilot when conditions permit. The Weather Radar selector position that differs from the expected state requires the Captain to confirm the condition unless directed otherwise by the Sample Operations Center. During takeoff, the Captain should brief the Weather Radar indication if the indication does not stabilize within the sample interval. If the Cabin Pressure Controller is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance.

- Both pilots will cross-check any change in the Standby Hydraulic quantity display and advise the other pilot when operating at a sample station without ground power.
- The Auxiliary Power Unit indication is expected to read within the sample range of 27 to 36 units during a diversion.
- The Brake Temperature Monitor annunciation that differs from the expected state requires the First Officer to announce the condition if a discrepancy is observed.

**CAUTION:** The Bleed Air Supply advisory is expected to read within the sample range of 21 to 24 units during climb.

The Cabin Pressure Controller advisory that differs from the expected state requires the First Officer to record the condition if the indication does not stabilize within the sample interval. During an extended ground delay, the pilot monitoring should confirm the Primary Electrical Bus status message once the checklist item is complete. Values in this manual are invented and must not be used for any operational purpose.

The pilot flying will record any change in the Engine Anti-Ice status message and advise the other pilot unless directed otherwise by the Sample Operations Center. The pilot monitoring will announce any change in the Traffic Advisory Display annunciation and advise the other pilot when conditions permit. During cruise, the Captain should record the Autothrottle advisory when operating at a sample station without ground power. If the Stall Warning is inoperative, continue descent only after the Captain has reviewed the associated sample guidance. Both pilots will verify any change in the Cabin Pressure Controller indication and advise the other pilot when operating at a sample

station without ground power. During parking, the relief pilot should select the Engine Anti-Ice quantity display when conditions permit.

**05.60.10 Window Heat Interfaces**

The Bleed Air Supply switch position is expected to read within the sample range of 93 to 96 units during an extended ground delay. If the Autopilot Channel B is inoperative, continue approach only after the pilot flying has reviewed the associated sample guidance. If the Probe Heat is inoperative, continue engine start only after the pilot flying has reviewed the associated sample guidance. If the Weather Radar is inoperative, continue preflight only after both pilots has reviewed the associated sample guidance. The Brake Temperature Monitor switch position is expected to read within the sample range of 68 to 72 units during landing.

- The pilot flying will brief any change in the Primary Electrical Bus annunciation and advise the other pilot if the indication does not stabilize within the sample interval.
- During engine start, the relief pilot should announce the Weather Radar switch position when operating at a sample station without ground power.
- If the Oxygen Distribution is inoperative, continue engine start only after the relief pilot has reviewed the associated sample guidance.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- The Thrust Reverser annunciation that differs from the expected state requires the First Officer to record the condition once the checklist item is complete.

The Flap Position Indication switch position is expected to read within the sample range of 82 to 85 units during cruise. The wording here is placeholder content shaped like a procedure, not a procedure. The Thrust Reverser annunciation is expected to read within the sample range of 79 to 91 units during approach. The Window Heat indication that differs from the expected state requires the pilot monitoring to confirm the condition if the indication does not stabilize within the sample interval. The Center Tank Pumps annunciation that differs from the expected state requires the pilot flying to record the condition if a discrepancy is observed. If the Engine Anti-Ice is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance.

**CAUTION:** This text is fictional and exists only to give the prototype realistic volume and structure. The Flight Management Computer indication is expected to read within the sample range of 88 to 91 units during preflight.

- The relief pilot will brief any change in the Flap Position Indication quantity display and advise the other pilot when the associated caution light remains illuminated.
- During takeoff, both pilots should record the Transponder status message if a discrepancy is observed.
- The Pack Temperature Control selector position that differs from the expected state requires both pilots to verify the condition when operating at a sample station without ground power.
- The Transponder status message that differs from the expected state requires the relief pilot to confirm the condition unless directed otherwise by the Sample Operations Center.
- The Thrust Reverser quantity display is expected to read within the sample range of 33 to 43 units during a diversion.

| Challenge                 | Response |
|---------------------------|----------|
| Standby Hydraulic         | Off      |
| Flap Position Indication  | On       |
| Primary Electrical Bus    | Closed   |
| Autopilot Channel B       | Verified |
| Probe Heat                | Set      |
| Cabin Pressure Controller | Off      |

05.60.11 Standby Hydraulic Status Messages

Both pilots will confirm any change in the Speedbrake Handle quantity display and advise the other pilot before the next phase of flight. The Oxygen Distribution indication that differs from the expected state requires the pilot monitoring to announce the condition when conditions permit. The captain will verify any change in the Probe Heat quantity display and advise the other pilot when conditions permit. During a diversion, the relief pilot should announce the Hydraulic System B selector position once the checklist item is complete.

The Cabin Pressure Controller status message is expected to read within the sample range of 14 to 19 units during parking. If the Brake Temperature Monitor is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance. The Hydraulic System B switch position that differs from the expected state requires the First Officer to confirm the condition unless directed otherwise by the Sample Operations Center. The pilot monitoring will select any change in the Autopilot Channel B indication and advise the other pilot when operating at a sample station without ground power. Refer to the related topic for additional sample context.

**CAUTION:** The Nosewheel Steering quantity display is expected to read within the sample range of 46 to 56 units during a maintenance-requested ground run.

If the Auxiliary Power Unit is inoperative, continue taxi only after both pilots has reviewed the associated sample guidance. The Autopilot Channel A selector position that differs from the expected state requires the Captain to record the condition if the indication does not stabilize within the sample interval. If the Speedbrake Handle is inoperative, continue descent only after the Captain has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. The Wing Anti-Ice indication that differs from the expected state requires the relief pilot to confirm the condition if a discrepancy is observed.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Autopilot Channel A quantity display      | 70 units     | Monitor                |
| Standby Instruments annunciation          | 19 units     | Normal                 |
| Autopilot Channel B switch position       | 42 units     | Normal                 |
| Flight Management Computer status message | 69 units     | Refer to related topic |
| Cockpit Voice Recorder annunciation       | 85 units     | Normal                 |

The Flap Position Indication selector position is expected to read within the sample range of 29 to 35 units during approach. During engine start, the pilot flying should record the Oxygen Distribution selector position if a discrepancy is observed. The Bleed Air Supply advisory that differs from the expected state requires the pilot monitoring to confirm the condition when conditions permit. If the Hydraulic System B is inoperative, continue parking only after both pilots has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. During takeoff, the relief pilot should cross-check the Auxiliary Power Unit indication unless directed otherwise by the Sample Operations Center. See 02.40.22 Flap Position Indication Indications.

**NOTE:** The Window Heat advisory is expected to read within the sample range of 47 to 51 units during descent. During cruise, the pilot monitoring should confirm the Center Tank Pumps selector position when operating at a sample station without ground power.

| Condition                            | Sample value | Remarks |
|--------------------------------------|--------------|---------|
| Brake Temperature Monitor indication | 29 units     | Monitor |
| Stall Warning selector position      | 50 units     | Monitor |
| Traffic Advisory Display advisory    | 37 units     | Normal  |
| Stall Warning quantity display       | 46 units     | Monitor |
| Standby Hydraulic switch position    | 94 units     | Monitor |

**NOTE:** This text is fictional and exists only to give the prototype realistic volume and structure.

05.60.12 Fuel Crossfeed Indications

Both pilots will monitor any change in the Probe Heat annunciation and advise the other pilot when the associated caution light remains illuminated. The Window Heat selector position is expected to read within the sample range of 35 to 47 units during cruise. Refer to the related topic for additional sample context.

During climb, the relief pilot should monitor the Standby Hydraulic selector position unless directed otherwise by the Sample Operations Center. The pilot monitoring will cross-check any change in the Primary Electrical Bus quantity display and advise the other pilot when conditions permit. The Engine Anti-Ice switch position is expected to read within the sample range of 67 to 76 units during preflight. The Engine Anti-Ice advisory is expected to read within the sample range of 31 to 39 units during a maintenance-requested ground run. During a turnaround, the First Officer should confirm the Wing Anti-Ice status message if a discrepancy is observed. The first officer will announce any change in the Pack Temperature Control selector position and advise the other pilot unless directed otherwise by the Sample Operations Center. See 05.70.2 Flap Position Indication Normal Operation.

- The Cabin Pressure Controller quantity display is expected to read within the sample range of 86 to 96 units during a diversion.
- During climb, the pilot monitoring should verify the Autopilot Channel A selector position when the associated caution light remains illuminated.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- Refer to the related topic for additional sample context.

**CAUTION:** The Autobrake Selector advisory is expected to read within the sample range of 71 to 80 units during descent.

- The Flight Management Computer annunciation that differs from the expected state requires the First Officer to cross-check the condition when the associated caution light remains illuminated.
- If the Hydraulic System B is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance.
- The Autothrottle advisory is expected to read within the sample range of 40 to 44 units during a turnaround.
- If the Hydraulic System B is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance.
- The Landing Gear Indication annunciation is expected to read within the sample range of 3 to 13 units during cruise.

05.60.13 Wing Anti-Ice Reset Guidance

During preflight, the Captain should brief the Stall Warning quantity display when conditions permit. If the Standby Hydraulic is inoperative, continue taxi only after the First Officer has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. The Oxygen Distribution indication is expected to read within the sample range of 64 to 73 units during parking.

| Condition                                   | Sample value | Remarks                |
|---------------------------------------------|--------------|------------------------|
| Oxygen Distribution quantity display        | 77 units     | Monitor                |
| Center Tank Pumps indication                | 73 units     | Advisory only          |
| Autopilot Channel B indication              | 25 units     | Normal                 |
| Landing Gear Indication advisory            | 51 units     | Monitor                |
| Brake Temperature Monitor selector position | 15 units     | Refer to related topic |
| Bleed Air Supply selector position          | 49 units     | Normal                 |
| Ground Proximity Monitor quantity display   | 99 units     | Refer to related topic |



The Window Heat advisory that differs from the expected state requires the relief pilot to brief the condition once the checklist item is complete. The Center Tank Pumps annunciation that differs from the expected state requires the First Officer to confirm the condition if the indication does not stabilize within the sample interval. During cruise, the First Officer should announce the Autothrottle quantity display if a discrepancy is observed. The captain will confirm any change in the Autopilot Channel B advisory and advise the other pilot once the checklist item is complete.

- This text is fictional and exists only to give the prototype realistic volume and structure.
- The Autopilot Channel B indication is expected to read within the sample range of 57 to 64 units during descent.
- The Nosewheel Steering switch position that differs from the expected state requires the relief pilot to cross-check the condition once the checklist item is complete.
- The relief pilot will brief any change in the Window Heat indication and advise the other pilot when conditions permit.
- The Hydraulic System B selector position is expected to read within the sample range of 70 to 81 units during a turnaround.

The pilot flying will monitor any change in the Thrust Reverser status message and advise the other pilot if the indication does not stabilize within the sample interval. The Cockpit Voice Recorder switch position is expected to read within the sample range of 5 to 16 units during climb. If the Bleed Air Supply is inoperative, continue parking only after the pilot monitoring has reviewed the associated sample guidance.

During a turnaround, the pilot monitoring should brief the Traffic Advisory Display advisory before the next phase of flight. The Pack Temperature Control selector position that differs from the expected state requires the First Officer to confirm the condition if the indication does not stabilize within the sample interval. The Standby Hydraulic quantity display is expected to read within the sample range of 84 to 95 units during climb. The pilot monitoring will cross-check any change in the Standby Hydraulic selector position and advise the other pilot when operating at a sample station without ground power. Values in this manual are invented and must not be used for any operational purpose. The wording here is placeholder content shaped like a procedure, not a procedure.

- This text is fictional and exists only to give the prototype realistic volume and structure.
- The Flight Management Computer switch position is expected to read within the sample range of 45 to 55 units during a turnaround.
- The captain will verify any change in the Fuel Crossfeed quantity display and advise the other pilot before the next phase of flight.
- If the Autothrottle is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance.
- The captain will brief any change in the Cargo Smoke Detection annunciation and advise the other pilot once the checklist item is complete.
- The relief pilot will cross-check any change in the Cabin Pressure Controller switch position and advise the other pilot if the indication does not stabilize within the sample interval.
- If the Brake Temperature Monitor is inoperative, continue engine start only after the pilot monitoring has reviewed the associated sample guidance.
- During an extended ground delay, the pilot monitoring should confirm the Wing Anti-Ice selector position when conditions permit.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- During approach, the pilot monitoring should select the Standby Instruments switch position when operating at a sample station without ground power.



- If the Wing Anti-Ice is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance.
- The Autopilot Channel B quantity display that differs from the expected state requires both pilots to brief the condition when the associated caution light remains illuminated.

**05.60.14 Center Tank Pumps Interfaces**

The relief pilot will select any change in the Autopilot Channel B status message and advise the other pilot when conditions permit. The wording here is placeholder content shaped like a procedure, not a procedure. The Standby Hydraulic quantity display is expected to read within the sample range of 11 to 20 units during a turnaround. The wording here is placeholder content shaped like a procedure, not a procedure. During an extended ground delay, the Captain should monitor the Cargo Smoke Detection selector position once the checklist item is complete. The pilot flying will record any change in the Autopilot Channel B annunciation and advise the other pilot before the next phase of flight.

**CAUTION:** During taxi, the pilot flying should verify the Wing Anti-Ice advisory unless directed otherwise by the Sample Operations Center.

The pilot monitoring will brief any change in the Probe Heat selector position and advise the other pilot unless directed otherwise by the Sample Operations Center. The Probe Heat indication is expected to read within the sample range of 34 to 45 units during a diversion. The first officer will confirm any change in the Wing Anti-Ice selector position and advise the other pilot when operating at a sample station without ground power.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Primary Electrical Bus selector position | 63 units     | Monitor                |
| Weather Radar indication                 | 62 units     | Monitor                |
| Ground Proximity Monitor annunciation    | 46 units     | Refer to related topic |
| Speedbrake Handle quantity display       | 36 units     | Advisory only          |
| Autobrake Selector advisory              | 49 units     | Advisory only          |

| Condition                            | Sample value | Remarks                |
|--------------------------------------|--------------|------------------------|
| Cabin Pressure Controller indication | 64 units     | Advisory only          |
| Standby Hydraulic advisory           | 17 units     | Refer to related topic |
| Autothrottle annunciation            | 2 units      | Advisory only          |
| Pack Temperature Control indication  | 39 units     | Refer to related topic |
| Probe Heat indication                | 20 units     | Refer to related topic |
| Nosewheel Steering status message    | 21 units     | Monitor                |

- The first officer will select any change in the Brake Temperature Monitor annunciation and advise the other pilot if the indication does not stabilize within the sample interval.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- If the Fire Detection Loop is inoperative, continue landing only after the First Officer has reviewed the associated sample guidance.
- If the Auxiliary Power Unit is inoperative, continue engine start only after the pilot monitoring has reviewed the associated sample guidance.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- The first officer will record any change in the Fire Detection Loop switch position and advise the other pilot once the checklist item is complete.

- The Transponder selector position that differs from the expected state requires the relief pilot to record the condition when conditions permit.

The Fire Detection Loop annunciation that differs from the expected state requires the Captain to select the condition unless directed otherwise by the Sample Operations Center. The pilot flying will announce any change in the Bleed Air Supply selector position and advise the other pilot unless directed otherwise by the Sample Operations Center. The wording here is placeholder content shaped like a procedure, not a procedure. If the Cargo Smoke Detection is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. If the Bleed Air Supply is inoperative, continue approach only after the relief pilot has reviewed the associated sample guidance.

| Challenge                 | Response |
|---------------------------|----------|
| Traffic Advisory Display  | Closed   |
| Weather Radar             | Off      |
| Oxygen Distribution       | Armed    |
| Ground Proximity Monitor  | On       |
| Traffic Advisory Display  | Checked  |
| Flap Position Indication  | Verified |
| Cockpit Voice Recorder    | Armed    |
| Pack Temperature Control  | Checked  |
| Hydraulic System A        | Checked  |
| Cabin Pressure Controller | Off      |

**CAUTION:** During climb, the First Officer should record the Autopilot Channel B quantity display once the checklist item is complete. The captain will monitor any change in the Center Tank Pumps status message and advise the other pilot when conditions permit.

**05.60.15 Cabin Pressure Controller Normal Operation**

This text is fictional and exists only to give the prototype realistic volume and structure. The Hydraulic System B switch position that differs from the expected state requires the First Officer to announce the condition once the checklist item is complete. During an extended ground delay, the pilot monitoring should announce the Flap Position Indication advisory when operating at a sample station without ground power. The pilot monitoring will cross-check any change in the Standby Instruments annunciation and advise the other pilot if a discrepancy is observed. The Nosewheel Steering indication that differs from the expected state requires the pilot monitoring to monitor the condition unless directed otherwise by the Sample Operations Center.

**CAUTION:** The Fire Detection Loop selector position that differs from the expected state requires the pilot flying to verify the condition unless directed otherwise by the Sample Operations Center.

The pilot flying will brief any change in the Autobrake Selector advisory and advise the other pilot if a discrepancy is observed. The relief pilot will verify any change in the Cockpit Voice Recorder switch position and advise the other pilot if a discrepancy is observed. If the Speedbrake Handle is inoperative, continue a maintenance-requested ground run only after the pilot flying has reviewed the associated sample guidance. The Transponder indication that differs from the expected state requires the relief pilot to record the condition when conditions permit. During descent, both pilots should monitor the Auxiliary Power Unit annunciation when operating at a sample station without ground power.

- The first officer will select any change in the Cockpit Voice Recorder indication and advise the other pilot when the associated caution light remains illuminated.
- Both pilots will record any change in the Flap Position Indication annunciation and advise the other pilot when the associated caution light remains illuminated.

- If the Ground Proximity Monitor is inoperative, continue landing only after the pilot monitoring has reviewed the associated sample guidance.

Values in this manual are invented and must not be used for any operational purpose. The Thrust Reverser quantity display that differs from the expected state requires the relief pilot to verify the condition once the checklist item is complete. The Weather Radar switch position that differs from the expected state requires the relief pilot to select the condition when operating at a sample station without ground power. If the Cabin Pressure Controller is inoperative, continue climb only after the First Officer has reviewed the associated sample guidance. The Weather Radar indication is expected to read within the sample range of 14 to 24 units during taxi. This text is fictional and exists only to give the prototype realistic volume and structure.

- During takeoff, the First Officer should record the Speedbrake Handle quantity display if a discrepancy is observed.
- If the Hydraulic System B is inoperative, continue preflight only after the pilot monitoring has reviewed the associated sample guidance.
- If the Standby Instruments is inoperative, continue taxi only after the First Officer has reviewed the associated sample guidance.

**CAUTION:** During a diversion, the Captain should record the Cabin Pressure Controller advisory if the indication does not stabilize within the sample interval. Refer to the related topic for additional sample context.

#### 05.60.16 *Bleed Air Supply Reset Guidance*

Values in this manual are invented and must not be used for any operational purpose. The pilot flying will announce any change in the Cabin Pressure Controller indication and advise the other pilot if the indication does not stabilize within the sample interval. The first officer will confirm any change in the Hydraulic System A annunciation and advise the other pilot when conditions permit. The Standby Instruments switch position that differs from the expected state requires the First Officer to monitor the condition if a discrepancy is observed. This text is fictional and exists only to give the prototype realistic volume and structure. The captain will monitor any change in the Pack Temperature Control quantity display and advise the other pilot if a discrepancy is observed.

The pilot flying will announce any change in the Hydraulic System B indication and advise the other pilot when operating at a sample station without ground power. The pilot monitoring will cross-check any change in the Oxygen Distribution switch position and advise the other pilot when the associated caution light remains illuminated. The captain will select any change in the Primary Electrical Bus status message and advise the other pilot when the associated caution light remains illuminated. The wording here is placeholder content shaped like a procedure, not a procedure. During descent, the pilot flying should monitor the Standby Hydraulic annunciation once the checklist item is complete.

**CAUTION:** The first officer will record any change in the Fuel Crossfeed quantity display and advise the other pilot once the checklist item is complete.

The Weather Radar indication is expected to read within the sample range of 39 to 49 units during climb. During descent, both pilots should monitor the Auxiliary Power Unit advisory before the next phase of flight. Refer to the related topic for additional sample context. If the Standby Hydraulic is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance.

The wording here is placeholder content shaped like a procedure, not a procedure. Values in this manual are invented and must not be used for any operational purpose. The Oxygen Distribution selector position that differs from the expected state requires the pilot flying to monitor the condition before the next phase of flight.

The Standby Instruments quantity display is expected to read within the sample range of 78 to 85 units during descent. The wording here is placeholder content shaped like a procedure, not a procedure. During approach, the pilot flying should announce the Brake Temperature Monitor indication unless directed otherwise by the Sample Operations Center. The Autothrottle quantity display is expected to read within the sample range of 2 to 11 units during a turnaround. Values in this manual are invented and must not be used for any operational purpose. The

Hydraulic System B annunciation that differs from the expected state requires both pilots to confirm the condition when conditions permit.

If the Wing Anti-Ice is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance. The Flight Management Computer quantity display that differs from the expected state requires the First Officer to announce the condition once the checklist item is complete. The Oxygen Distribution status message that differs from the expected state requires the relief pilot to confirm the condition if the indication does not stabilize within the sample interval. The Fuel Crossfeed status message that differs from the expected state requires the Captain to verify the condition when operating at a sample station without ground power. The wording here is placeholder content shaped like a procedure, not a procedure.

The first officer will verify any change in the Landing Gear Indication switch position and advise the other pilot once the checklist item is complete. If the Cargo Smoke Detection is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance. If the Flap Position Indication is inoperative, continue taxi only after the pilot flying has reviewed the associated sample guidance. If the Flight Management Computer is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance. The Nosewheel Steering annunciation is expected to read within the sample range of 59 to 67 units during cruise. The Nosewheel Steering annunciation is expected to read within the sample range of 68 to 71 units during an extended ground delay. See 03.40.5 Briefing: Brake Temperature Monitor.

| Challenge                 | Response    |
|---------------------------|-------------|
| Auxiliary Power Unit      | As required |
| Standby Instruments       | Verified    |
| Transponder               | Closed      |
| Pack Temperature Control  | Verified    |
| Autopilot Channel A       | Verified    |
| Auxiliary Power Unit      | Armed       |
| Hydraulic System B        | Off         |
| Stall Warning             | As required |
| Cockpit Voice Recorder    | Checked     |
| Pack Temperature Control  | Verified    |
| Cabin Pressure Controller | On          |

**05.60.17 Speedbrake Handle Indications**

The captain will confirm any change in the Standby Hydraulic selector position and advise the other pilot unless directed otherwise by the Sample Operations Center. During a diversion, the relief pilot should verify the Autothrottle annunciation before the next phase of flight. If the Autopilot Channel A is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance.

The Transponder indication is expected to read within the sample range of 12 to 18 units during a diversion. The Fuel Crossfeed quantity display is expected to read within the sample range of 75 to 80 units during parking. During approach, both pilots should select the Cabin Pressure Controller quantity display when operating at a sample station without ground power.

The Speedbrake Handle quantity display is expected to read within the sample range of 40 to 43 units during cruise. Values in this manual are invented and must not be used for any operational purpose. The Flap Position Indication quantity display is expected to read within the sample range of 53 to 60 units during engine start.

**CAUTION:** If the Autopilot Channel A is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance. The Ground Proximity Monitor switch position that differs from the expected state requires both pilots to confirm the condition if the indication does not stabilize within the sample interval.

**CAUTION:** If the Center Tank Pumps is inoperative, continue climb only after the Captain has reviewed the associated sample guidance.

- During cruise, the relief pilot should announce the Autobrake Selector status message unless directed otherwise by the Sample Operations Center.
- The captain will select any change in the Wing Anti-Ice advisory and advise the other pilot when operating at a sample station without ground power.
- The captain will select any change in the Center Tank Pumps quantity display and advise the other pilot if a discrepancy is observed.
- During climb, the relief pilot should verify the Landing Gear Indication quantity display if a discrepancy is observed.
- The Auxiliary Power Unit advisory is expected to read within the sample range of 2 to 8 units during landing.
- During takeoff, the First Officer should select the Transponder quantity display if a discrepancy is observed.

**05.60.18 Pack Temperature Control Test**

The first officer will record any change in the Autopilot Channel B switch position and advise the other pilot when conditions permit. Refer to the related topic for additional sample context. The Ground Proximity Monitor quantity display that differs from the expected state requires the First Officer to announce the condition when operating at a sample station without ground power. Refer to the related topic for additional sample context. The Ground Proximity Monitor annunciation is expected to read within the sample range of 24 to 32 units during approach.

The Auxiliary Power Unit indication is expected to read within the sample range of 54 to 58 units during parking. During climb, the First Officer should verify the Flight Management Computer indication once the checklist item is complete. During an extended ground delay, the pilot monitoring should verify the Standby Instruments status message when the associated caution light remains illuminated. The Engine Anti-Ice status message that differs from the expected state requires the First Officer to monitor the condition unless directed otherwise by the Sample Operations Center.

| Condition                            | Sample value | Remarks                |
|--------------------------------------|--------------|------------------------|
| Autopilot Channel B switch position  | 76 units     | Normal                 |
| Nosewheel Steering status message    | 92 units     | Refer to related topic |
| Autopilot Channel A quantity display | 48 units     | Advisory only          |

| Condition                               | Sample value | Remarks       |
|-----------------------------------------|--------------|---------------|
| Landing Gear Indication switch position | 3 units      | Advisory only |
| Auxiliary Power Unit advisory           | 91 units     | Monitor       |
| Wing Anti-Ice annunciation              | 82 units     | Normal        |

The wording here is placeholder content shaped like a procedure, not a procedure. The Oxygen Distribution advisory that differs from the expected state requires both pilots to announce the condition before the next phase of flight. The captain will brief any change in the Cabin Pressure Controller quantity display and advise the other pilot when conditions permit. If the Standby Hydraulic is inoperative, continue descent only after the First Officer has reviewed the associated sample guidance. The Standby Hydraulic advisory is expected to read within the sample range of 45 to 51 units during an extended ground delay. The relief pilot will confirm any change in the Fuel Crossfeed status message and advise the other pilot before the next phase of flight.

Refer to the related topic for additional sample context. The relief pilot will cross-check any change in the Bleed Air Supply selector position and advise the other pilot once the checklist item is complete. The Fire Detection Loop indication is expected to read within the sample range of 24 to 27 units during climb. The Hydraulic System B selector position is expected to read within the sample range of 71 to 74 units during a diversion. If the Speedbrake Handle is

inoperative, continue preflight only after both pilots has reviewed the associated sample guidance. The Pack Temperature Control quantity display is expected to read within the sample range of 86 to 90 units during approach.

**CAUTION:** The Traffic Advisory Display status message that differs from the expected state requires the First Officer to record the condition once the checklist item is complete.

**CAUTION:** During cruise, the Captain should monitor the Window Heat advisory when conditions permit. The Fuel Crossfeed switch position is expected to read within the sample range of 82 to 94 units during parking.

**NOTE:** The wording here is placeholder content shaped like a procedure, not a procedure.

**05.60.19 Center Tank Pumps Reset Guidance**

This text is fictional and exists only to give the prototype realistic volume and structure. If the Engine Anti-Ice is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance. During landing, the pilot flying should announce the Center Tank Pumps advisory once the checklist item is complete. The relief pilot will announce any change in the Probe Heat annunciation and advise the other pilot before the next phase of flight. During engine start, both pilots should record the Transponder switch position before the next phase of flight. The Flap Position Indication status message is expected to read within the sample range of 63 to 74 units during an extended ground delay.

**NOTE:** The Autothrottle switch position is expected to read within the sample range of 39 to 49 units during takeoff.

- The Landing Gear Indication advisory that differs from the expected state requires both pilots to verify the condition if a discrepancy is observed.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- The first officer will confirm any change in the Wing Anti-Ice switch position and advise the other pilot when operating at a sample station without ground power.
- If the Autobrake Selector is inoperative, continue approach only after the Captain has reviewed the associated sample guidance.

The pilot monitoring will record any change in the Probe Heat advisory and advise the other pilot when the associated caution light remains illuminated. During approach, the relief pilot should record the Cockpit Voice Recorder selector position if the indication does not stabilize within the sample interval. The first officer will brief any change in the Flight Management Computer indication and advise the other pilot when the associated caution light remains illuminated.

The first officer will monitor any change in the Fire Detection Loop annunciation and advise the other pilot before the next phase of flight. The Window Heat advisory is expected to read within the sample range of 8 to 20 units during an extended ground delay. If the Engine Anti-Ice is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance. The Engine Anti-Ice quantity display that differs from the expected state requires the First Officer to announce the condition if a discrepancy is observed. The Weather Radar quantity display that differs from the expected state requires the pilot flying to monitor the condition if a discrepancy is observed.

The Speedbrake Handle switch position is expected to read within the sample range of 67 to 78 units during descent. The Thrust Reverser switch position that differs from the expected state requires the relief pilot to cross-check the condition unless directed otherwise by the Sample Operations Center. If the Cargo Smoke Detection is inoperative, continue landing only after both pilots has reviewed the associated sample guidance. Both pilots will brief any change in the Brake Temperature Monitor status message and advise the other pilot when conditions permit.

**CAUTION:** Refer to the related topic for additional sample context. The Bleed Air Supply quantity display that differs from the expected state requires the pilot flying to monitor the condition when operating at a sample station without ground power.

| Challenge                  | Response |
|----------------------------|----------|
| Flight Management Computer | Set      |



|                         |             |
|-------------------------|-------------|
| Wing Anti-Ice           | Verified    |
| Autothrottle            | Set         |
| Hydraulic System B      | Set         |
| Landing Gear Indication | Armed       |
| Autothrottle            | As required |

05.60.20 Cockpit Voice Recorder Overview

The Speedbrake Handle advisory is expected to read within the sample range of 54 to 62 units during descent. If the Autobrake Selector is inoperative, continue a turnaround only after the pilot monitoring has reviewed the associated sample guidance. The pilot flying will record any change in the Probe Heat selector position and advise the other pilot unless directed otherwise by the Sample Operations Center. The wording here is placeholder content shaped like a procedure, not a procedure. The pilot flying will select any change in the Hydraulic System A switch position and advise the other pilot if a discrepancy is observed. The captain will confirm any change in the Autobrake Selector indication and advise the other pilot once the checklist item is complete.

- If the Hydraulic System A is inoperative, continue climb only after both pilots has reviewed the associated sample guidance.
- The Fuel Crossfeed status message is expected to read within the sample range of 5 to 16 units during approach.
- The Window Heat annunciation is expected to read within the sample range of 52 to 56 units during preflight.
- The Autopilot Channel B quantity display that differs from the expected state requires the Captain to brief the condition before the next phase of flight.
- During a maintenance-requested ground run, the First Officer should cross-check the Auxiliary Power Unit switch position when conditions permit.
- The Fire Detection Loop selector position is expected to read within the sample range of 47 to 53 units during preflight.

This text is fictional and exists only to give the prototype realistic volume and structure. If the Thrust Reverser is inoperative, continue approach only after both pilots has reviewed the associated sample guidance. Refer to the related topic for additional sample context. Values in this manual are invented and must not be used for any operational purpose. See 04.40.11 Flow: Standby Hydraulic.

**NOTE:** The wording here is placeholder content shaped like a procedure, not a procedure.

**NOTE:** The Landing Gear Indication switch position that differs from the expected state requires the pilot monitoring to confirm the condition once the checklist item is complete. The captain will select any change in the Fuel Crossfeed switch position and advise the other pilot when operating at a sample station without ground power.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Bleed Air Supply indication           | 81 units     | Normal                 |
| Cargo Smoke Detection switch position | 37 units     | Monitor                |
| Nosewheel Steering advisory           | 56 units     | Advisory only          |
| Autothrottle status message           | 43 units     | Refer to related topic |
| Center Tank Pumps quantity display    | 2 units      | Monitor                |
| Autopilot Channel A quantity display  | 49 units     | Monitor                |
| Autopilot Channel B status message    | 46 units     | Normal                 |

| Challenge | Response |
|-----------|----------|
|-----------|----------|

|                           |          |
|---------------------------|----------|
| Autopilot Channel B       | Set      |
| Flap Position Indication  | Verified |
| Traffic Advisory Display  | Verified |
| Nosewheel Steering        | Checked  |
| Stall Warning             | Off      |
| Stall Warning             | On       |
| Probe Heat                | Verified |
| Cabin Pressure Controller | Checked  |
| Flap Position Indication  | Checked  |
| Probe Heat                | Closed   |
| Transponder               | Closed   |
| Autopilot Channel B       | Closed   |

## 05.70 Automatic Flight

### 05.70.1 Brake Temperature Monitor Limits Display

If the Standby Hydraulic is inoperative, continue landing only after the First Officer has reviewed the associated sample guidance. The Flap Position Indication quantity display that differs from the expected state requires the First Officer to confirm the condition if the indication does not stabilize within the sample interval. During cruise, both pilots should select the Autopilot Channel B advisory if a discrepancy is observed. If the Engine Anti-Ice is inoperative, continue a maintenance-requested ground run only after both pilots has reviewed the associated sample guidance. The Landing Gear Indication indication is expected to read within the sample range of 80 to 88 units during landing.

During a maintenance-requested ground run, the pilot flying should announce the Autobrake Selector annunciation if a discrepancy is observed. The pilot monitoring will announce any change in the Ground Proximity Monitor switch position and advise the other pilot if a discrepancy is observed. During descent, both pilots should announce the Fuel Crossfeed quantity display when conditions permit. If the Transponder is inoperative, continue a maintenance-requested ground run only after the Captain has reviewed the associated sample guidance.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Bleed Air Supply status message         | 75 units     | Refer to related topic |
| Engine Anti-Ice advisory                | 21 units     | Advisory only          |
| Probe Heat status message               | 45 units     | Refer to related topic |
| Probe Heat status message               | 77 units     | Normal                 |
| Flap Position Indication indication     | 73 units     | Advisory only          |
| Fire Detection Loop quantity display    | 52 units     | Monitor                |
| Flap Position Indication status message | 3 units      | Advisory only          |

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Standby Instruments selector position    | 69 units     | Refer to related topic |
| Autopilot Channel B selector position    | 82 units     | Monitor                |
| Standby Instruments quantity display     | 27 units     | Advisory only          |
| Fuel Crossfeed status message            | 15 units     | Normal                 |
| Cockpit Voice Recorder selector position | 6 units      | Advisory only          |
| Probe Heat indication                    | 15 units     | Monitor                |

**CAUTION:** During takeoff, the pilot flying should confirm the Pack Temperature Control selector position once the checklist item is complete.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Thrust Reverser selector position        | 19 units     | Refer to related topic |
| Stall Warning annunciation               | 41 units     | Refer to related topic |
| Cockpit Voice Recorder selector position | 42 units     | Advisory only          |
| Window Heat quantity display             | 63 units     | Advisory only          |
| Autopilot Channel A selector position    | 27 units     | Refer to related topic |

| Challenge                | Response    |
|--------------------------|-------------|
| Fire Detection Loop      | Closed      |
| Wing Anti-Ice            | Armed       |
| Window Heat              | As required |
| Ground Proximity Monitor | On          |
| Auxiliary Power Unit     | Verified    |
| Bleed Air Supply         | As required |
| Primary Electrical Bus   | Armed       |
| Oxygen Distribution      | On          |

**05.70.2 Flap Position Indication Normal Operation**

The wording here is placeholder content shaped like a procedure, not a procedure. If the Flap Position Indication is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance. During climb, the Captain should monitor the Auxiliary Power Unit switch position once the checklist item is complete.

During a turnaround, the pilot flying should verify the Cargo Smoke Detection advisory if the indication does not stabilize within the sample interval. During descent, the relief pilot should announce the Autopilot Channel A advisory when operating at a sample station without ground power. The captain will select any change in the Pack Temperature Control annunciation and advise the other pilot when operating at a sample station without ground power.

**NOTE:** If the Standby Instruments is inoperative, continue taxi only after the First Officer has reviewed the associated sample guidance.

| Condition                           | Sample value | Remarks                |
|-------------------------------------|--------------|------------------------|
| Standby Hydraulic status message    | 8 units      | Refer to related topic |
| Autopilot Channel A status message  | 57 units     | Normal                 |
| Nosewheel Steering quantity display | 78 units     | Advisory only          |

- The pilot flying will record any change in the Cargo Smoke Detection switch position and advise the other pilot before the next phase of flight.
- The Flap Position Indication quantity display is expected to read within the sample range of 17 to 20 units during a maintenance-requested ground run.
- The pilot flying will announce any change in the Probe Heat status message and advise the other pilot when operating at a sample station without ground power.
- Both pilots will confirm any change in the Oxygen Distribution switch position and advise the other pilot when operating at a sample station without ground power.

- The Fuel Crossfeed indication is expected to read within the sample range of 62 to 67 units during an extended ground delay.

**NOTE:** The wording here is placeholder content shaped like a procedure, not a procedure. The Thrust Reverser selector position is expected to read within the sample range of 91 to 98 units during approach.

| Condition                               | Sample value | Remarks       |
|-----------------------------------------|--------------|---------------|
| Cargo Smoke Detection selector position | 65 units     | Advisory only |
| Thrust Reverser quantity display        | 21 units     | Normal        |
| Autopilot Channel B switch position     | 90 units     | Normal        |
| Auxiliary Power Unit quantity display   | 8 units      | Monitor       |
| Transponder switch position             | 63 units     | Monitor       |

During a diversion, the pilot monitoring should monitor the Probe Heat advisory when the associated caution light remains illuminated. Refer to the related topic for additional sample context. If the Autobrake Selector is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance. The Hydraulic System A status message that differs from the expected state requires the First Officer to monitor the condition when operating at a sample station without ground power.

- If the Speedbrake Handle is inoperative, continue engine start only after the pilot flying has reviewed the associated sample guidance.
- During a diversion, the First Officer should record the Landing Gear Indication annunciation if a discrepancy is observed.
- The Cabin Pressure Controller indication that differs from the expected state requires the pilot flying to announce the condition if the indication does not stabilize within the sample interval.
- During landing, the Captain should announce the Pack Temperature Control indication when conditions permit.
- The Autopilot Channel A annunciation is expected to read within the sample range of 90 to 94 units during taxi.

| Challenge                | Response    |
|--------------------------|-------------|
| Transponder              | On          |
| Fuel Crossfeed           | Verified    |
| Standby Instruments      | Armed       |
| Stall Warning            | Checked     |
| Auxiliary Power Unit     | As required |
| Transponder              | On          |
| Pack Temperature Control | Checked     |
| Standby Instruments      | Armed       |
| Ground Proximity Monitor | Set         |
| Fire Detection Loop      | Off         |

05.70.3 Stall Warning Interfaces

Values in this manual are invented and must not be used for any operational purpose. During a turnaround, the pilot monitoring should cross-check the Autopilot Channel B advisory once the checklist item is complete. Refer to the related topic for additional sample context. If the Auxiliary Power Unit is inoperative, continue an extended ground delay only after the Captain has reviewed the associated sample guidance. The Window Heat indication that differs from the expected state requires the pilot monitoring to record the condition when operating at a sample station without ground power. If the Hydraulic System B is inoperative, continue engine start only after the relief pilot has

reviewed the associated sample guidance.

- During an extended ground delay, both pilots should select the Primary Electrical Bus switch position before the next phase of flight.
- If the Autopilot Channel A is inoperative, continue climb only after the Captain has reviewed the associated sample guidance.
- The Window Heat switch position that differs from the expected state requires the pilot flying to record the condition when the associated caution light remains illuminated.
- The Landing Gear Indication selector position is expected to read within the sample range of 60 to 69 units during cruise.
- If the Brake Temperature Monitor is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance.

**NOTE:** If the Thrust Reverser is inoperative, continue descent only after the Captain has reviewed the associated sample guidance. The Center Tank Pumps indication is expected to read within the sample range of 40 to 52 units during cruise.

**NOTE:** If the Speedbrake Handle is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance.

**NOTE:** The Hydraulic System A advisory that differs from the expected state requires the First Officer to confirm the condition unless directed otherwise by the Sample Operations Center. The pilot flying will cross-check any change in the Engine Anti-Ice switch position and advise the other pilot when conditions permit.

During a turnaround, the pilot flying should cross-check the Oxygen Distribution annunciation once the checklist item is complete. The Bleed Air Supply status message that differs from the expected state requires the Captain to brief the condition if the indication does not stabilize within the sample interval. During taxi, the relief pilot should verify the Standby Hydraulic switch position if the indication does not stabilize within the sample interval.

The captain will cross-check any change in the Engine Anti-Ice switch position and advise the other pilot once the checklist item is complete. Values in this manual are invented and must not be used for any operational purpose. The wording here is placeholder content shaped like a procedure, not a procedure. If the Brake Temperature Monitor is inoperative, continue taxi only after the Captain has reviewed the associated sample guidance. During parking, the relief pilot should monitor the Autothrottle annunciation when operating at a sample station without ground power.

| Challenge              | Response |
|------------------------|----------|
| Speedbrake Handle      | Armed    |
| Autothrottle           | Checked  |
| Autothrottle           | On       |
| Standby Instruments    | Closed   |
| Standby Instruments    | Set      |
| Oxygen Distribution    | Checked  |
| Cockpit Voice Recorder | Checked  |
| Oxygen Distribution    | Set      |

**05.70.4 Stall Warning Overview**

The Standby Instruments indication is expected to read within the sample range of 14 to 26 units during engine start. During preflight, the pilot monitoring should select the Traffic Advisory Display selector position unless directed otherwise by the Sample Operations Center. Refer to the related topic for additional sample context. The first officer will cross-check any change in the Fire Detection Loop selector position and advise the other pilot when operating at a sample station without ground power. The first officer will cross-check any change in the Brake Temperature

Monitor quantity display and advise the other pilot when conditions permit. The pilot flying will select any change in the Probe Heat quantity display and advise the other pilot if a discrepancy is observed.

The Thrust Reverser status message that differs from the expected state requires the First Officer to confirm the condition before the next phase of flight. If the Nosewheel Steering is inoperative, continue taxi only after the Captain has reviewed the associated sample guidance. The Ground Proximity Monitor quantity display that differs from the expected state requires the relief pilot to select the condition before the next phase of flight. During parking, the First Officer should cross-check the Transponder status message when the associated caution light remains illuminated.

The Engine Anti-Ice indication that differs from the expected state requires the pilot flying to record the condition before the next phase of flight. If the Probe Heat is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance. The Ground Proximity Monitor annunciation that differs from the expected state requires the pilot monitoring to verify the condition unless directed otherwise by the Sample Operations Center.

This text is fictional and exists only to give the prototype realistic volume and structure. If the Traffic Advisory Display is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance. The Brake Temperature Monitor advisory is expected to read within the sample range of 11 to 22 units during cruise. The relief pilot will record any change in the Auxiliary Power Unit advisory and advise the other pilot unless directed otherwise by the Sample Operations Center. The Flap Position Indication advisory is expected to read within the sample range of 59 to 68 units during taxi.

- The Weather Radar indication is expected to read within the sample range of 62 to 71 units during engine start.
- The Autothrottle advisory that differs from the expected state requires the relief pilot to announce the condition when conditions permit.
- The Cargo Smoke Detection indication is expected to read within the sample range of 92 to 98 units during climb.
- During engine start, the pilot monitoring should record the Fire Detection Loop annunciation once the checklist item is complete.
- During takeoff, the pilot monitoring should monitor the Bleed Air Supply selector position when conditions permit.
- If the Cabin Pressure Controller is inoperative, continue taxi only after the pilot flying has reviewed the associated sample guidance.
- The Flap Position Indication annunciation is expected to read within the sample range of 3 to 10 units during landing.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Landing Gear Indication quantity display   | 93 units     | Refer to related topic |
| Traffic Advisory Display selector position | 55 units     | Advisory only          |
| Stall Warning status message               | 4 units      | Normal                 |
| Cockpit Voice Recorder switch position     | 30 units     | Monitor                |
| Bleed Air Supply advisory                  | 24 units     | Advisory only          |
| Speedbrake Handle advisory                 | 79 units     | Monitor                |

The Nosewheel Steering selector position that differs from the expected state requires the Captain to cross-check the condition if a discrepancy is observed. During taxi, the First Officer should monitor the Center Tank Pumps quantity display when operating at a sample station without ground power. The Weather Radar annunciation is expected to read within the sample range of 71 to 77 units during a diversion. The Thrust Reverser indication is expected to read within the sample range of 3 to 10 units during engine start. If the Flap Position Indication is inoperative, continue preflight only after the Captain has reviewed the associated sample guidance.

The relief pilot will confirm any change in the Auxiliary Power Unit status message and advise the other pilot if a discrepancy is observed. The Flap Position Indication switch position is expected to read within the sample range of



57 to 66 units during a maintenance-requested ground run. This text is fictional and exists only to give the prototype realistic volume and structure. During taxi, the relief pilot should select the Weather Radar quantity display when operating at a sample station without ground power.

#### **05.70.5 Wing Anti-Ice Reset Guidance**

The wording here is placeholder content shaped like a procedure, not a procedure. The Pack Temperature Control switch position that differs from the expected state requires the relief pilot to monitor the condition when conditions permit. Refer to the related topic for additional sample context. This text is fictional and exists only to give the prototype realistic volume and structure. During taxi, both pilots should brief the Flap Position Indication status message when conditions permit.

Values in this manual are invented and must not be used for any operational purpose. The first officer will brief any change in the Engine Anti-Ice status message and advise the other pilot when conditions permit. During parking, the relief pilot should brief the Thrust Reverser status message when conditions permit.

The first officer will verify any change in the Landing Gear Indication switch position and advise the other pilot before the next phase of flight. The Thrust Reverser status message that differs from the expected state requires the Captain to monitor the condition when operating at a sample station without ground power. During a diversion, both pilots should cross-check the Auxiliary Power Unit switch position when the associated caution light remains illuminated. During descent, the Captain should cross-check the Cargo Smoke Detection advisory if the indication does not stabilize within the sample interval.

During approach, the pilot monitoring should verify the Traffic Advisory Display advisory if a discrepancy is observed. The Hydraulic System B switch position that differs from the expected state requires the Captain to brief the condition before the next phase of flight. The pilot monitoring will record any change in the Weather Radar switch position and advise the other pilot before the next phase of flight. If the Cabin Pressure Controller is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance. The Autopilot Channel A switch position that differs from the expected state requires the Captain to record the condition if a discrepancy is observed.

**NOTE:** The Cargo Smoke Detection switch position that differs from the expected state requires both pilots to record the condition if the indication does not stabilize within the sample interval. The Autobrake Selector advisory is expected to read within the sample range of 78 to 88 units during parking.

**CAUTION:** The Weather Radar advisory that differs from the expected state requires the Captain to brief the condition when operating at a sample station without ground power.

During a diversion, the relief pilot should announce the Traffic Advisory Display indication before the next phase of flight. The pilot monitoring will confirm any change in the Autopilot Channel A status message and advise the other pilot once the checklist item is complete. During climb, both pilots should record the Stall Warning status message if the indication does not stabilize within the sample interval. The captain will announce any change in the Engine Anti-Ice advisory and advise the other pilot unless directed otherwise by the Sample Operations Center. During a maintenance-requested ground run, both pilots should brief the Pack Temperature Control selector position unless directed otherwise by the Sample Operations Center. The Fire Detection Loop status message is expected to read within the sample range of 10 to 18 units during a diversion.

The Hydraulic System A status message that differs from the expected state requires the pilot flying to confirm the condition when conditions permit. During climb, the First Officer should select the Autobrake Selector switch position when operating at a sample station without ground power. Refer to the related topic for additional sample context.

#### **05.70.6 Transponder Status Messages**

If the Thrust Reverser is inoperative, continue engine start only after the pilot monitoring has reviewed the associated sample guidance. During preflight, both pilots should cross-check the Pack Temperature Control switch position when operating at a sample station without ground power. This text is fictional and exists only to give the prototype realistic volume and structure. The pilot flying will record any change in the Thrust Reverser selector position and advise the

other pilot before the next phase of flight. The Fire Detection Loop advisory is expected to read within the sample range of 72 to 76 units during engine start.

- If the Stall Warning is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance.
- The Autopilot Channel A annunciation is expected to read within the sample range of 51 to 56 units during descent.
- The pilot monitoring will confirm any change in the Cargo Smoke Detection quantity display and advise the other pilot once the checklist item is complete.
- The Pack Temperature Control switch position is expected to read within the sample range of 49 to 54 units during climb.
- During takeoff, the First Officer should cross-check the Autothrottle selector position when conditions permit.

The Autopilot Channel B advisory that differs from the expected state requires the pilot flying to cross-check the condition once the checklist item is complete. During a diversion, the First Officer should announce the Pack Temperature Control status message when conditions permit. If the Probe Heat is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance. The Standby Instruments status message that differs from the expected state requires the pilot monitoring to record the condition unless directed otherwise by the Sample Operations Center.

The pilot flying will cross-check any change in the Autobrake Selector quantity display and advise the other pilot when the associated caution light remains illuminated. The Flap Position Indication switch position that differs from the expected state requires the relief pilot to confirm the condition if a discrepancy is observed. During a maintenance-requested ground run, the relief pilot should verify the Hydraulic System A status message once the checklist item is complete. Both pilots will record any change in the Pack Temperature Control annunciation and advise the other pilot if the indication does not stabilize within the sample interval. The Auxiliary Power Unit switch position that differs from the expected state requires the relief pilot to record the condition before the next phase of flight. If the Standby Instruments is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance.

- The Thrust Reverser advisory that differs from the expected state requires both pilots to brief the condition once the checklist item is complete.
- The Autobrake Selector advisory that differs from the expected state requires the First Officer to brief the condition once the checklist item is complete.
- During an extended ground delay, the First Officer should select the Weather Radar switch position before the next phase of flight.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- If the Traffic Advisory Display is inoperative, continue landing only after both pilots has reviewed the associated sample guidance.

### **05.70.7 Flight Management Computer Status Messages**

During a turnaround, the pilot monitoring should select the Cabin Pressure Controller selector position once the checklist item is complete. The Primary Electrical Bus switch position is expected to read within the sample range of 25 to 34 units during engine start. The Autobrake Selector annunciation is expected to read within the sample range of 27 to 31 units during descent. During a maintenance-requested ground run, the Captain should record the Window Heat switch position before the next phase of flight.

**CAUTION:** If the Fuel Crossfeed is inoperative, continue cruise only after the First Officer has reviewed the associated sample guidance.

The Landing Gear Indication status message that differs from the expected state requires the First Officer to monitor the condition once the checklist item is complete. The Transponder advisory is expected to read within the sample range of 37 to 46 units during parking. During an extended ground delay, the relief pilot should monitor the Autopilot Channel A selector position when conditions permit. If the Standby Hydraulic is inoperative, continue descent only after the pilot flying has reviewed the associated sample guidance. During cruise, the pilot flying should select the Autobrake Selector selector position if the indication does not stabilize within the sample interval.

**NOTE:** If the Oxygen Distribution is inoperative, continue parking only after the Captain has reviewed the associated sample guidance.

**NOTE:** Refer to the related topic for additional sample context.

The Autopilot Channel B switch position that differs from the expected state requires both pilots to confirm the condition when conditions permit. The captain will verify any change in the Autopilot Channel A status message and advise the other pilot once the checklist item is complete. Values in this manual are invented and must not be used for any operational purpose. This text is fictional and exists only to give the prototype realistic volume and structure. The captain will brief any change in the Standby Instruments status message and advise the other pilot once the checklist item is complete.

The Cargo Smoke Detection indication that differs from the expected state requires the relief pilot to brief the condition once the checklist item is complete. Values in this manual are invented and must not be used for any operational purpose. During an extended ground delay, the relief pilot should brief the Fuel Crossfeed switch position if the indication does not stabilize within the sample interval. If the Hydraulic System B is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance. The relief pilot will verify any change in the Cabin Pressure Controller quantity display and advise the other pilot if the indication does not stabilize within the sample interval. The pilot flying will announce any change in the Autopilot Channel A switch position and advise the other pilot if the indication does not stabilize within the sample interval.

#### **05.70.8 Nosewheel Steering Limits Display**

The pilot monitoring will cross-check any change in the Brake Temperature Monitor advisory and advise the other pilot if a discrepancy is observed. The captain will select any change in the Traffic Advisory Display annunciation and advise the other pilot once the checklist item is complete. During preflight, the pilot flying should confirm the Speedbrake Handle annunciation if a discrepancy is observed.

**CAUTION:** If the Cabin Pressure Controller is inoperative, continue engine start only after the pilot monitoring has reviewed the associated sample guidance. The Autothrottle advisory that differs from the expected state requires both pilots to monitor the condition once the checklist item is complete.

**NOTE:** The wording here is placeholder content shaped like a procedure, not a procedure.

The Cockpit Voice Recorder indication that differs from the expected state requires the relief pilot to monitor the condition when operating at a sample station without ground power. The Thrust Reverser status message that differs from the expected state requires the First Officer to cross-check the condition if the indication does not stabilize within the sample interval. If the Landing Gear Indication is inoperative, continue approach only after the pilot monitoring has reviewed the associated sample guidance.

During parking, the First Officer should cross-check the Cabin Pressure Controller indication unless directed otherwise by the Sample Operations Center. The Weather Radar status message that differs from the expected state requires the pilot monitoring to confirm the condition if the indication does not stabilize within the sample interval. If the Stall Warning is inoperative, continue landing only after the Captain has reviewed the associated sample guidance.

The Bleed Air Supply selector position that differs from the expected state requires the relief pilot to verify the condition if the indication does not stabilize within the sample interval. The Brake Temperature Monitor quantity display that differs from the expected state requires both pilots to select the condition unless directed otherwise by the Sample Operations Center. During taxi, the First Officer should monitor the Flight Management Computer quantity display when the associated caution light remains illuminated.

During descent, the relief pilot should cross-check the Bleed Air Supply quantity display when the associated caution light remains illuminated. The Cabin Pressure Controller indication that differs from the expected state requires both pilots to announce the condition when conditions permit. If the Autopilot Channel B is inoperative, continue engine start only after the Captain has reviewed the associated sample guidance. During takeoff, the pilot monitoring should announce the Bleed Air Supply selector position if a discrepancy is observed.

### **05.70.9 Cockpit Voice Recorder Power Sources**

The pilot monitoring will select any change in the Bleed Air Supply indication and advise the other pilot when conditions permit. During climb, the First Officer should verify the Autobrake Selector switch position when the associated caution light remains illuminated. During engine start, the First Officer should cross-check the Brake Temperature Monitor quantity display before the next phase of flight. If the Wing Anti-Ice is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance. The Landing Gear Indication selector position is expected to read within the sample range of 16 to 24 units during approach. During descent, the pilot monitoring should verify the Fire Detection Loop annunciation unless directed otherwise by the Sample Operations Center.

- During descent, the pilot flying should cross-check the Fuel Crossfeed quantity display when the associated caution light remains illuminated.
- The Nosewheel Steering selector position that differs from the expected state requires the pilot monitoring to brief the condition once the checklist item is complete.
- If the Fire Detection Loop is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance.
- The captain will confirm any change in the Fuel Crossfeed selector position and advise the other pilot when conditions permit.
- Refer to the related topic for additional sample context.
- The pilot monitoring will confirm any change in the Probe Heat status message and advise the other pilot when the associated caution light remains illuminated.

The Cabin Pressure Controller advisory that differs from the expected state requires the First Officer to monitor the condition when the associated caution light remains illuminated. The Cargo Smoke Detection status message is expected to read within the sample range of 44 to 51 units during approach. Values in this manual are invented and must not be used for any operational purpose. The captain will brief any change in the Cargo Smoke Detection annunciation and advise the other pilot if the indication does not stabilize within the sample interval. Values in this manual are invented and must not be used for any operational purpose.

- The wording here is placeholder content shaped like a procedure, not a procedure.
- If the Oxygen Distribution is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance.
- The Cargo Smoke Detection switch position is expected to read within the sample range of 71 to 76 units during preflight.
- The Nosewheel Steering switch position is expected to read within the sample range of 84 to 89 units during climb.

If the Engine Anti-Ice is inoperative, continue engine start only after the Captain has reviewed the associated sample guidance. The Cockpit Voice Recorder quantity display is expected to read within the sample range of 46 to 58 units during landing. The Cargo Smoke Detection annunciation is expected to read within the sample range of 17 to 23 units during parking. The pilot monitoring will confirm any change in the Transponder selector position and advise the other pilot when conditions permit. The Autothrottle indication is expected to read within the sample range of 14 to 18 units during descent. Refer to the related topic for additional sample context.

- The relief pilot will record any change in the Autopilot Channel A status message and advise the other pilot when conditions permit.
- During a diversion, both pilots should monitor the Transponder quantity display unless directed otherwise by the Sample Operations Center.
- The Autobrake Selector annunciation that differs from the expected state requires the Captain to monitor the condition if the indication does not stabilize within the sample interval.
- If the Oxygen Distribution is inoperative, continue landing only after both pilots has reviewed the associated sample guidance.
- If the Nosewheel Steering is inoperative, continue a maintenance-requested ground run only after both pilots has reviewed the associated sample guidance.
- During takeoff, the relief pilot should record the Transponder selector position when the associated caution light remains illuminated.

The Fuel Crossfeed quantity display that differs from the expected state requires the relief pilot to select the condition if a discrepancy is observed. The Hydraulic System B advisory is expected to read within the sample range of 85 to 88 units during an extended ground delay. During descent, the relief pilot should announce the Center Tank Pumps quantity display once the checklist item is complete. The pilot flying will announce any change in the Hydraulic System A annunciation and advise the other pilot when the associated caution light remains illuminated. If the Center Tank Pumps is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance. If the Nosewheel Steering is inoperative, continue takeoff only after both pilots has reviewed the associated sample guidance.

- This text is fictional and exists only to give the prototype realistic volume and structure.
- The Primary Electrical Bus annunciation is expected to read within the sample range of 31 to 36 units during engine start.
- During takeoff, both pilots should confirm the Cabin Pressure Controller status message if a discrepancy is observed.
- During taxi, the Captain should record the Autopilot Channel A switch position unless directed otherwise by the Sample Operations Center.

During landing, both pilots should select the Stall Warning advisory if the indication does not stabilize within the sample interval. If the Flap Position Indication is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance. If the Flap Position Indication is inoperative, continue takeoff only after both pilots has reviewed the associated sample guidance.

| Challenge                | Response    |
|--------------------------|-------------|
| Engine Anti-Ice          | Checked     |
| Auxiliary Power Unit     | Verified    |
| Ground Proximity Monitor | Off         |
| Autobrake Selector       | Checked     |
| Traffic Advisory Display | As required |
| Hydraulic System B       | Off         |
| Primary Electrical Bus   | Armed       |
| Oxygen Distribution      | On          |
| Stall Warning            | Armed       |
| Flap Position Indication | Armed       |
| Primary Electrical Bus   | Set         |

05.70.10 Traffic Advisory Display Status Messages

The captain will monitor any change in the Window Heat indication and advise the other pilot when conditions permit. The Auxiliary Power Unit indication that differs from the expected state requires the pilot flying to announce the condition when conditions permit. This text is fictional and exists only to give the prototype realistic volume and structure. The captain will brief any change in the Probe Heat selector position and advise the other pilot when the associated caution light remains illuminated. This text is fictional and exists only to give the prototype realistic volume and structure.

- The Cabin Pressure Controller indication that differs from the expected state requires the pilot monitoring to announce the condition when the associated caution light remains illuminated.
- The Auxiliary Power Unit annunciation that differs from the expected state requires the relief pilot to monitor the condition before the next phase of flight.
- The captain will brief any change in the Pack Temperature Control quantity display and advise the other pilot if the indication does not stabilize within the sample interval.
- During engine start, the pilot monitoring should announce the Speedbrake Handle quantity display when operating at a sample station without ground power.
- The Primary Electrical Bus indication that differs from the expected state requires the relief pilot to confirm the condition unless directed otherwise by the Sample Operations Center.

The Ground Proximity Monitor advisory is expected to read within the sample range of 21 to 32 units during a maintenance-requested ground run. During a turnaround, the pilot monitoring should announce the Cockpit Voice Recorder annunciation when conditions permit. During preflight, the First Officer should brief the Cockpit Voice Recorder status message before the next phase of flight. If the Traffic Advisory Display is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance. The Center Tank Pumps indication is expected to read within the sample range of 13 to 25 units during approach. The Pack Temperature Control annunciation that differs from the expected state requires the relief pilot to verify the condition when conditions permit.

If the Fire Detection Loop is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance. The Traffic Advisory Display switch position is expected to read within the sample range of 28 to 34 units during a diversion. The Cockpit Voice Recorder annunciation is expected to read within the sample range of 2 to 14 units during parking. The first officer will brief any change in the Center Tank Pumps indication and advise the other pilot if the indication does not stabilize within the sample interval. If the Nosewheel Steering is inoperative, continue takeoff only after the First Officer has reviewed the associated sample guidance.

**CAUTION:** If the Fire Detection Loop is inoperative, continue a turnaround only after the pilot monitoring has reviewed the associated sample guidance. The Cargo Smoke Detection annunciation that differs from the expected state requires the relief pilot to cross-check the condition if the indication does not stabilize within the sample interval.

| Challenge                 | Response    |
|---------------------------|-------------|
| Stall Warning             | Verified    |
| Autopilot Channel A       | As required |
| Transponder               | Armed       |
| Auxiliary Power Unit      | Off         |
| Autothrottle              | Verified    |
| Cabin Pressure Controller | Armed       |
| Autothrottle              | Verified    |



|                         |          |
|-------------------------|----------|
| Standby Instruments     | Verified |
| Oxygen Distribution     | Checked  |
| Center Tank Pumps       | Armed    |
| Landing Gear Indication | Verified |
| Standby Instruments     | Off      |

05.70.11 Brake Temperature Monitor Normal Operation

During a maintenance-requested ground run, the pilot flying should verify the Pack Temperature Control switch position when the associated caution light remains illuminated. If the Center Tank Pumps is inoperative, continue a diversion only after the First Officer has reviewed the associated sample guidance. The Standby Instruments status message is expected to read within the sample range of 26 to 31 units during a turnaround. The Autopilot Channel B switch position is expected to read within the sample range of 83 to 88 units during climb. During an extended ground delay, the Captain should cross-check the Stall Warning status message unless directed otherwise by the Sample Operations Center. During a diversion, the First Officer should cross-check the Bleed Air Supply switch position if a discrepancy is observed.

| Condition                                  | Sample value | Remarks       |
|--------------------------------------------|--------------|---------------|
| Flap Position Indication selector position | 28 units     | Advisory only |
| Transponder status message                 | 64 units     | Advisory only |
| Speedbrake Handle switch position          | 63 units     | Normal        |
| Thrust Reverser quantity display           | 14 units     | Normal        |
| Auxiliary Power Unit advisory              | 76 units     | Monitor       |
| Fire Detection Loop switch position        | 66 units     | Monitor       |

**CAUTION:** If the Fuel Crossfeed is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance.

**NOTE:** The wording here is placeholder content shaped like a procedure, not a procedure.

The Flight Management Computer status message is expected to read within the sample range of 79 to 84 units during cruise. If the Transponder is inoperative, continue parking only after both pilots has reviewed the associated sample guidance. If the Window Heat is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance. If the Autothrottle is inoperative, continue parking only after the pilot monitoring has reviewed the associated sample guidance. Both pilots will confirm any change in the Thrust Reverser status message and advise the other pilot if a discrepancy is observed.

05.70.12 Wing Anti-Ice Power Sources

If the Autopilot Channel A is inoperative, continue a turnaround only after both pilots has reviewed the associated sample guidance. The Auxiliary Power Unit switch position that differs from the expected state requires the Captain to verify the condition unless directed otherwise by the Sample Operations Center. The wording here is placeholder content shaped like a procedure, not a procedure. If the Probe Heat is inoperative, continue descent only after the Captain has reviewed the associated sample guidance. During parking, the relief pilot should verify the Flight Management Computer status message when conditions permit.

**CAUTION:** This text is fictional and exists only to give the prototype realistic volume and structure.

**NOTE:** The Thrust Reverser selector position is expected to read within the sample range of 73 to 81 units during engine start. During approach, both pilots should confirm the Standby Instruments indication when operating at a sample station without ground power.



**CAUTION:** During landing, the pilot monitoring should verify the Hydraulic System B advisory once the checklist item is complete.

The wording here is placeholder content shaped like a procedure, not a procedure. During parking, the First Officer should brief the Oxygen Distribution selector position when the associated caution light remains illuminated. The pilot flying will brief any change in the Ground Proximity Monitor advisory and advise the other pilot when operating at a sample station without ground power. If the Primary Electrical Bus is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance. If the Window Heat is inoperative, continue an extended ground delay only after the pilot flying has reviewed the associated sample guidance.

**05.70.13 Standby Hydraulic Indications**

During taxi, the pilot monitoring should record the Traffic Advisory Display switch position when conditions permit. The wording here is placeholder content shaped like a procedure, not a procedure. The Wing Anti-Ice switch position that differs from the expected state requires the pilot flying to select the condition when the associated caution light remains illuminated. The pilot flying will monitor any change in the Flap Position Indication annunciation and advise the other pilot when operating at a sample station without ground power. The wording here is placeholder content shaped like a procedure, not a procedure.

The Flight Management Computer selector position is expected to read within the sample range of 2 to 8 units during landing. The first officer will verify any change in the Flight Management Computer advisory and advise the other pilot when the associated caution light remains illuminated. Both pilots will confirm any change in the Probe Heat quantity display and advise the other pilot once the checklist item is complete. The Pack Temperature Control switch position that differs from the expected state requires both pilots to verify the condition before the next phase of flight. During engine start, both pilots should select the Autopilot Channel A annunciation when the associated caution light remains illuminated. The relief pilot will record any change in the Ground Proximity Monitor quantity display and advise the other pilot when conditions permit.

The Autopilot Channel B quantity display that differs from the expected state requires the relief pilot to cross-check the condition when operating at a sample station without ground power. The Center Tank Pumps switch position that differs from the expected state requires both pilots to select the condition before the next phase of flight. If the Weather Radar is inoperative, continue cruise only after the Captain has reviewed the associated sample guidance. During climb, the pilot monitoring should monitor the Cabin Pressure Controller advisory before the next phase of flight. If the Autopilot Channel A is inoperative, continue descent only after the Captain has reviewed the associated sample guidance. The Cabin Pressure Controller indication that differs from the expected state requires the Captain to confirm the condition when the associated caution light remains illuminated.

The Weather Radar advisory that differs from the expected state requires the relief pilot to brief the condition when the associated caution light remains illuminated. If the Transponder is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance. The Fuel Crossfeed selector position is expected to read within the sample range of 73 to 81 units during a maintenance-requested ground run. The Hydraulic System A switch position that differs from the expected state requires the pilot monitoring to cross-check the condition before the next phase of flight. The Primary Electrical Bus selector position that differs from the expected state requires the Captain to announce the condition unless directed otherwise by the Sample Operations Center. If the Fire Detection Loop is inoperative, continue takeoff only after the First Officer has reviewed the associated sample guidance.

**CAUTION:** During cruise, both pilots should select the Brake Temperature Monitor quantity display when the associated caution light remains illuminated.

| Challenge                | Response    |
|--------------------------|-------------|
| Probe Heat               | Off         |
| Hydraulic System A       | Off         |
| Bleed Air Supply         | As required |
| Pack Temperature Control | Checked     |

|                   |          |
|-------------------|----------|
| Stall Warning     | Set      |
| Probe Heat        | Verified |
| Speedbrake Handle | Armed    |
| Transponder       | Off      |
| Autothrottle      | Closed   |

#### 05.70.14 Brake Temperature Monitor Limits Display

The Primary Electrical Bus switch position that differs from the expected state requires the relief pilot to select the condition if a discrepancy is observed. The Bleed Air Supply annunciation that differs from the expected state requires the relief pilot to select the condition before the next phase of flight. If the Engine Anti-Ice is inoperative, continue climb only after the First Officer has reviewed the associated sample guidance.

**CAUTION:** Both pilots will monitor any change in the Fuel Crossfeed selector position and advise the other pilot once the checklist item is complete. The Cockpit Voice Recorder indication that differs from the expected state requires the relief pilot to brief the condition when the associated caution light remains illuminated.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Autothrottle status message           | 10 units     | Normal                 |
| Speedbrake Handle status message      | 36 units     | Monitor                |
| Oxygen Distribution selector position | 80 units     | Normal                 |
| Hydraulic System A indication         | 44 units     | Normal                 |
| Wing Anti-Ice status message          | 61 units     | Refer to related topic |
| Autopilot Channel B selector position | 87 units     | Normal                 |

**CAUTION:** The Stall Warning selector position that differs from the expected state requires the Captain to monitor the condition when conditions permit. If the Cabin Pressure Controller is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance.

| Condition                                  | Sample value | Remarks       |
|--------------------------------------------|--------------|---------------|
| Standby Hydraulic advisory                 | 29 units     | Advisory only |
| Flap Position Indication quantity display  | 81 units     | Monitor       |
| Autothrottle status message                | 63 units     | Advisory only |
| Brake Temperature Monitor quantity display | 53 units     | Advisory only |
| Autopilot Channel A indication             | 14 units     | Advisory only |

**CAUTION:** During climb, the pilot flying should brief the Primary Electrical Bus quantity display before the next phase of flight.

| Condition                             | Sample value | Remarks |
|---------------------------------------|--------------|---------|
| Hydraulic System B quantity display   | 97 units     | Normal  |
| Cockpit Voice Recorder annunciation   | 95 units     | Monitor |
| Ground Proximity Monitor annunciation | 42 units     | Normal  |

If the Autopilot Channel A is inoperative, continue an extended ground delay only after the Captain has reviewed the associated sample guidance. The pilot monitoring will announce any change in the Speedbrake Handle advisory and advise the other pilot when operating at a sample station without ground power. During landing, both pilots should monitor the Flight Management Computer switch position before the next phase of flight. During a maintenance-requested ground run, the relief pilot should announce the Probe Heat selector position if the indication

does not stabilize within the sample interval. During takeoff, the relief pilot should cross-check the Cockpit Voice Recorder quantity display if a discrepancy is observed. The Nosewheel Steering status message that differs from the expected state requires both pilots to monitor the condition if a discrepancy is observed.

**05.70.15 Cargo Smoke Detection Power Sources**

If the Autobrake Selector is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance. The pilot flying will confirm any change in the Landing Gear Indication indication and advise the other pilot if a discrepancy is observed. The captain will brief any change in the Speedbrake Handle switch position and advise the other pilot if a discrepancy is observed.

The Autobrake Selector switch position that differs from the expected state requires the First Officer to confirm the condition if the indication does not stabilize within the sample interval. Refer to the related topic for additional sample context. If the Standby Hydraulic is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance. The Primary Electrical Bus indication that differs from the expected state requires the pilot monitoring to brief the condition when operating at a sample station without ground power. If the Auxiliary Power Unit is inoperative, continue climb only after the relief pilot has reviewed the associated sample guidance.

- NOTE:** During takeoff, the pilot monitoring should announce the Fire Detection Loop switch position before the next phase of flight. During a maintenance-requested ground run, the pilot flying should select the Transponder annunciation once the checklist item is complete.

**NOTE:** The Ground Proximity Monitor quantity display that differs from the expected state requires the relief pilot to cross-check the condition before the next phase of flight.

| Condition                           | Sample value | Remarks                |
|-------------------------------------|--------------|------------------------|
| Fire Detection Loop switch position | 4 units      | Normal                 |
| Oxygen Distribution annunciation    | 23 units     | Refer to related topic |
| Hydraulic System A indication       | 18 units     | Normal                 |

The pilot monitoring will record any change in the Primary Electrical Bus selector position and advise the other pilot when conditions permit. If the Stall Warning is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance. If the Landing Gear Indication is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance. During climb, the pilot monitoring should monitor the Fuel Crossfeed quantity display if the indication does not stabilize within the sample interval. The pilot flying will verify any change in the Transponder indication and advise the other pilot if a discrepancy is observed.

The Stall Warning quantity display is expected to read within the sample range of 48 to 55 units during a turnaround. The Center Tank Pumps annunciation that differs from the expected state requires the relief pilot to brief the condition once the checklist item is complete. The Cabin Pressure Controller quantity display that differs from the expected state requires both pilots to announce the condition if a discrepancy is observed. Both pilots will confirm any change in the Standby Hydraulic advisory and advise the other pilot if the indication does not stabilize within the sample interval. See 11.20.16 Flap Position Indication Limits Display.

| Challenge           | Response    |
|---------------------|-------------|
| Bleed Air Supply    | On          |
| Stall Warning       | On          |
| Nosewheel Steering  | Verified    |
| Transponder         | Verified    |
| Hydraulic System A  | Off         |
| Bleed Air Supply    | Set         |
| Thrust Reverser     | Checked     |
| Oxygen Distribution | As required |

|                     |     |
|---------------------|-----|
| Autopilot Channel A | Off |
| Autopilot Channel A | On  |

05.70.16 Fire Detection Loop Test

The captain will cross-check any change in the Standby Instruments quantity display and advise the other pilot when operating at a sample station without ground power. If the Brake Temperature Monitor is inoperative, continue climb only after both pilots has reviewed the associated sample guidance. The Window Heat annunciation that differs from the expected state requires the relief pilot to record the condition when the associated caution light remains illuminated. The Oxygen Distribution switch position that differs from the expected state requires the relief pilot to confirm the condition if the indication does not stabilize within the sample interval. The pilot monitoring will verify any change in the Primary Electrical Bus annunciation and advise the other pilot before the next phase of flight. The pilot monitoring will cross-check any change in the Pack Temperature Control selector position and advise the other pilot if the indication does not stabilize within the sample interval.

**NOTE:** If the Probe Heat is inoperative, continue a turnaround only after both pilots has reviewed the associated sample guidance. During engine start, the pilot flying should monitor the Hydraulic System A selector position if the indication does not stabilize within the sample interval.

**CAUTION:** The Fire Detection Loop selector position that differs from the expected state requires the pilot monitoring to select the condition once the checklist item is complete. The pilot flying will confirm any change in the Hydraulic System A quantity display and advise the other pilot when the associated caution light remains illuminated.

During a diversion, both pilots should select the Transponder indication once the checklist item is complete. The Autopilot Channel A annunciation is expected to read within the sample range of 48 to 60 units during descent. The Thrust Reverser status message is expected to read within the sample range of 94 to 99 units during climb.

**NOTE:** The pilot flying will record any change in the Hydraulic System A annunciation and advise the other pilot before the next phase of flight.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Stall Warning annunciation            | 5 units      | Normal                 |
| Autothrottle annunciation             | 20 units     | Refer to related topic |
| Wing Anti-Ice selector position       | 21 units     | Refer to related topic |
| Primary Electrical Bus status message | 30 units     | Normal                 |

05.70.17 Cabin Pressure Controller Reset Guidance

If the Window Heat is inoperative, continue engine start only after the relief pilot has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. The pilot monitoring will cross-check any change in the Brake Temperature Monitor advisory and advise the other pilot if a discrepancy is observed.

Refer to the related topic for additional sample context. During taxi, the pilot flying should cross-check the Flight Management Computer annunciation unless directed otherwise by the Sample Operations Center. The Window Heat advisory is expected to read within the sample range of 25 to 30 units during a diversion. If the Oxygen Distribution is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance. During a diversion, both pilots should record the Transponder indication once the checklist item is complete.

This text is fictional and exists only to give the prototype realistic volume and structure. If the Autopilot Channel A is inoperative, continue a maintenance-requested ground run only after the pilot monitoring has reviewed the associated sample guidance. Refer to the related topic for additional sample context.

If the Fire Detection Loop is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance. During a turnaround, both pilots should record the Pack Temperature Control switch position when operating at a sample station without ground power. If the Primary Electrical Bus is inoperative, continue landing only after both pilots has reviewed the associated sample guidance. Both pilots will monitor any change in the Stall Warning quantity display and advise the other pilot when operating at a sample station without ground power.

**CAUTION:** Refer to the related topic for additional sample context. The pilot flying will brief any change in the Hydraulic System B indication and advise the other pilot if the indication does not stabilize within the sample interval.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Hydraulic System A status message     | 7 units      | Normal                 |
| Standby Instruments advisory          | 26 units     | Refer to related topic |
| Wing Anti-Ice quantity display        | 16 units     | Normal                 |
| Engine Anti-Ice indication            | 7 units      | Advisory only          |
| Autopilot Channel A annunciation      | 96 units     | Advisory only          |
| Primary Electrical Bus status message | 38 units     | Refer to related topic |
| Auxiliary Power Unit switch position  | 87 units     | Normal                 |

The Auxiliary Power Unit indication that differs from the expected state requires the relief pilot to announce the condition unless directed otherwise by the Sample Operations Center. During a turnaround, the First Officer should select the Fire Detection Loop annunciation if a discrepancy is observed. The Speedbrake Handle quantity display is expected to read within the sample range of 58 to 70 units during landing.

**NOTE:** The captain will confirm any change in the Thrust Reverser selector position and advise the other pilot when operating at a sample station without ground power.

**CAUTION:** The Hydraulic System A selector position that differs from the expected state requires the pilot monitoring to select the condition if the indication does not stabilize within the sample interval.

**05.70.18 Speedbrake Handle Power Sources**

If the Transponder is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance. If the Wing Anti-Ice is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance. During a maintenance-requested ground run, the relief pilot should cross-check the Ground Proximity Monitor advisory if a discrepancy is observed. The Ground Proximity Monitor selector position that differs from the expected state requires the Captain to announce the condition when the associated caution light remains illuminated. Values in this manual are invented and must not be used for any operational purpose. This text is fictional and exists only to give the prototype realistic volume and structure.

The Standby Instruments quantity display that differs from the expected state requires the Captain to cross-check the condition when conditions permit. The relief pilot will confirm any change in the Pack Temperature Control quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center. During takeoff, the pilot monitoring should brief the Cockpit Voice Recorder status message once the checklist item is complete. The Engine Anti-Ice quantity display that differs from the expected state requires both pilots to confirm the condition when conditions permit.

The Autopilot Channel A status message that differs from the expected state requires the pilot flying to brief the condition if the indication does not stabilize within the sample interval. If the Flight Management Computer is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance. The Cargo Smoke Detection selector position is expected to read within the sample range of 47 to 57 units during descent.

| Condition                              | Sample value | Remarks                |
|----------------------------------------|--------------|------------------------|
| Landing Gear Indication status message | 75 units     | Refer to related topic |

|                                            |          |               |
|--------------------------------------------|----------|---------------|
| Standby Hydraulic annunciation             | 76 units | Advisory only |
| Landing Gear Indication quantity display   | 61 units | Advisory only |
| Wing Anti-Ice quantity display             | 58 units | Monitor       |
| Flight Management Computer switch position | 53 units | Monitor       |

If the Weather Radar is inoperative, continue preflight only after the Captain has reviewed the associated sample guidance. If the Autopilot Channel B is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance. The Bleed Air Supply indication is expected to read within the sample range of 9 to 13 units during landing. The wording here is placeholder content shaped like a procedure, not a procedure.

During climb, both pilots should select the Engine Anti-Ice switch position before the next phase of flight. During a maintenance-requested ground run, the First Officer should confirm the Brake Temperature Monitor indication once the checklist item is complete. Values in this manual are invented and must not be used for any operational purpose. During engine start, the pilot flying should monitor the Fire Detection Loop selector position unless directed otherwise by the Sample Operations Center. If the Autopilot Channel B is inoperative, continue climb only after the pilot flying has reviewed the associated sample guidance. See 18.20.9 Autothrottle Limits Display.

| Challenge                 | Response |
|---------------------------|----------|
| Nosewheel Steering        | Off      |
| Traffic Advisory Display  | On       |
| Brake Temperature Monitor | Verified |
| Speedbrake Handle         | Off      |
| Fuel Crossfeed            | Closed   |
| Window Heat               | Armed    |
| Brake Temperature Monitor | Closed   |
| Fire Detection Loop       | Checked  |
| Wing Anti-Ice             | Closed   |

05.70.19 Window Heat Indications

The Cargo Smoke Detection advisory that differs from the expected state requires both pilots to select the condition unless directed otherwise by the Sample Operations Center. If the Standby Hydraulic is inoperative, continue descent only after the Captain has reviewed the associated sample guidance. The Autopilot Channel A indication that differs from the expected state requires the relief pilot to select the condition if a discrepancy is observed.

If the Speedbrake Handle is inoperative, continue a diversion only after the pilot monitoring has reviewed the associated sample guidance. The pilot flying will verify any change in the Stall Warning switch position and advise the other pilot unless directed otherwise by the Sample Operations Center. The Autobrake Selector quantity display that differs from the expected state requires the pilot monitoring to confirm the condition if the indication does not stabilize within the sample interval. During engine start, the pilot flying should verify the Autopilot Channel A quantity display if the indication does not stabilize within the sample interval.

During cruise, both pilots should monitor the Brake Temperature Monitor selector position unless directed otherwise by the Sample Operations Center. The Primary Electrical Bus advisory that differs from the expected state requires the pilot monitoring to cross-check the condition once the checklist item is complete. The first officer will verify any change in the Oxygen Distribution annunciation and advise the other pilot once the checklist item is complete. The pilot monitoring will verify any change in the Wing Anti-Ice selector position and advise the other pilot when conditions permit.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Landing Gear Indication quantity display | 69 units     | Refer to related topic |



|                                           |          |                        |
|-------------------------------------------|----------|------------------------|
| Wing Anti-Ice selector position           | 17 units | Refer to related topic |
| Traffic Advisory Display indication       | 26 units | Monitor                |
| Hydraulic System B quantity display       | 65 units | Refer to related topic |
| Brake Temperature Monitor switch position | 59 units | Normal                 |
| Engine Anti-Ice annunciation              | 67 units | Normal                 |
| Transponder advisory                      | 1 units  | Advisory only          |

| Condition                           | Sample value | Remarks                |
|-------------------------------------|--------------|------------------------|
| Standby Instruments switch position | 96 units     | Monitor                |
| Thrust Reverser advisory            | 1 units      | Refer to related topic |
| Speedbrake Handle indication        | 57 units     | Monitor                |
| Thrust Reverser selector position   | 51 units     | Monitor                |

**NOTE:** Both pilots will brief any change in the Nosewheel Steering indication and advise the other pilot when conditions permit.

If the Wing Anti-Ice is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance. The Cargo Smoke Detection indication that differs from the expected state requires the pilot monitoring to record the condition unless directed otherwise by the Sample Operations Center. The wording here is placeholder content shaped like a procedure, not a procedure.

The Primary Electrical Bus annunciation that differs from the expected state requires the relief pilot to confirm the condition when the associated caution light remains illuminated. The Engine Anti-Ice switch position is expected to read within the sample range of 87 to 90 units during descent. During a maintenance-requested ground run, both pilots should brief the Probe Heat switch position unless directed otherwise by the Sample Operations Center.

The Hydraulic System A annunciation is expected to read within the sample range of 33 to 36 units during parking. This text is fictional and exists only to give the prototype realistic volume and structure. During engine start, the Captain should confirm the Fuel Crossfeed status message once the checklist item is complete. The first officer will cross-check any change in the Autopilot Channel A status message and advise the other pilot once the checklist item is complete. The Cabin Pressure Controller status message that differs from the expected state requires the Captain to confirm the condition if the indication does not stabilize within the sample interval. The pilot flying will announce any change in the Flap Position Indication advisory and advise the other pilot unless directed otherwise by the Sample Operations Center. See 10.20.10 Auxiliary Power Unit Indications.

### 05.70.20 Traffic Advisory Display Limits Display

The relief pilot will confirm any change in the Pack Temperature Control selector position and advise the other pilot if a discrepancy is observed. The Fuel Crossfeed switch position that differs from the expected state requires the pilot monitoring to verify the condition once the checklist item is complete. The Hydraulic System A status message that differs from the expected state requires the relief pilot to brief the condition unless directed otherwise by the Sample Operations Center. If the Bleed Air Supply is inoperative, continue descent only after the pilot flying has reviewed the associated sample guidance. The Fuel Crossfeed advisory that differs from the expected state requires the Captain to monitor the condition when conditions permit. If the Autopilot Channel B is inoperative, continue a maintenance-requested ground run only after both pilots has reviewed the associated sample guidance.

The Transponder status message is expected to read within the sample range of 57 to 61 units during parking. The Thrust Reverser switch position is expected to read within the sample range of 19 to 30 units during landing. If the Flight Management Computer is inoperative, continue approach only after both pilots has reviewed the associated sample guidance.

- The pilot monitoring will confirm any change in the Oxygen Distribution status message and advise the other pilot if the indication does not stabilize within the sample interval.

- The Landing Gear Indication status message that differs from the expected state requires the First Officer to confirm the condition once the checklist item is complete.
- During a diversion, the First Officer should brief the Ground Proximity Monitor annunciation if the indication does not stabilize within the sample interval.
- Both pilots will select any change in the Cargo Smoke Detection status message and advise the other pilot when conditions permit.
- During parking, both pilots should record the Autopilot Channel B status message before the next phase of flight.
- During preflight, the relief pilot should record the Primary Electrical Bus quantity display when conditions permit.
- During an extended ground delay, both pilots should cross-check the Weather Radar status message when operating at a sample station without ground power.
- The Transponder indication is expected to read within the sample range of 26 to 33 units during parking.
- Both pilots will monitor any change in the Wing Anti-Ice advisory and advise the other pilot once the checklist item is complete.
- The Autobrake Selector advisory that differs from the expected state requires the pilot monitoring to verify the condition unless directed otherwise by the Sample Operations Center.
- The Engine Anti-Ice status message is expected to read within the sample range of 81 to 92 units during a maintenance-requested ground run.
- The Primary Electrical Bus indication is expected to read within the sample range of 80 to 90 units during takeoff.

**NOTE:** If the Hydraulic System A is inoperative, continue parking only after both pilots has reviewed the associated sample guidance. The Standby Hydraulic quantity display is expected to read within the sample range of 40 to 52 units during climb. The Stall Warning advisory that differs from the expected state requires the First Officer to monitor the condition if a discrepancy is observed. The Autobrake Selector annunciation that differs from the expected state requires the pilot monitoring to select the condition if the indication does not stabilize within the sample interval. The Autothrottle status message is expected to read within the sample range of 31 to 43 units during taxi.

**CAUTION:** The Window Heat annunciation is expected to read within the sample range of 4 to 13 units during taxi.

The Cabin Pressure Controller selector position that differs from the expected state requires both pilots to record the condition when conditions permit. Values in this manual are invented and must not be used for any operational purpose. During a turnaround, the pilot flying should select the Autobrake Selector annunciation if the indication does not stabilize within the sample interval. The Auxiliary Power Unit status message is expected to read within the sample range of 29 to 40 units during an extended ground delay.

**CAUTION:** If the Autothrottle is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance. The pilot monitoring will monitor any change in the Oxygen Distribution quantity display and advise the other pilot once the checklist item is complete.

The Wing Anti-Ice advisory that differs from the expected state requires the First Officer to cross-check the condition if a discrepancy is observed. The Auxiliary Power Unit quantity display that differs from the expected state requires both pilots to record the condition when operating at a sample station without ground power. During landing, the relief pilot should cross-check the Cabin Pressure Controller status message unless directed otherwise by the Sample Operations Center. See 03.30.8 Checklist: Oxygen Distribution.

## 05.80 Navigation

### 05.80.1 Flap Position Indication Limits Display

The Hydraulic System A quantity display is expected to read within the sample range of 60 to 65 units during takeoff. This text is fictional and exists only to give the prototype realistic volume and structure. The wording here is placeholder content shaped like a procedure, not a procedure. The Transponder indication is expected to read within the sample range of 64 to 72 units during cruise. During preflight, the pilot flying should verify the Autopilot Channel B status message if the indication does not stabilize within the sample interval. If the Ground Proximity Monitor is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance.

**CAUTION:** The Autobrake Selector advisory that differs from the expected state requires the relief pilot to monitor the condition when the associated caution light remains illuminated.

- The Stall Warning selector position is expected to read within the sample range of 53 to 59 units during landing.
- During taxi, the pilot monitoring should brief the Traffic Advisory Display status message if a discrepancy is observed.
- The Wing Anti-Ice quantity display that differs from the expected state requires the pilot flying to record the condition if a discrepancy is observed.

The captain will record any change in the Landing Gear Indication annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center. During a turnaround, both pilots should confirm the Center Tank Pumps status message if a discrepancy is observed. The Hydraulic System B annunciation that differs from the expected state requires both pilots to cross-check the condition once the checklist item is complete. The Weather Radar annunciation that differs from the expected state requires both pilots to select the condition when conditions permit. Values in this manual are invented and must not be used for any operational purpose.

This text is fictional and exists only to give the prototype realistic volume and structure. If the Stall Warning is inoperative, continue preflight only after both pilots has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. The Speedbrake Handle quantity display that differs from the expected state requires the Captain to brief the condition when operating at a sample station without ground power.

**CAUTION:** Values in this manual are invented and must not be used for any operational purpose. The Autopilot Channel B selector position that differs from the expected state requires the First Officer to select the condition when the associated caution light remains illuminated.

| Condition                              | Sample value | Remarks                |
|----------------------------------------|--------------|------------------------|
| Brake Temperature Monitor advisory     | 69 units     | Normal                 |
| Weather Radar indication               | 96 units     | Normal                 |
| Cockpit Voice Recorder switch position | 19 units     | Refer to related topic |
| Autopilot Channel A indication         | 53 units     | Monitor                |
| Autopilot Channel A quantity display   | 91 units     | Normal                 |

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Cabin Pressure Controller indication  | 45 units     | Refer to related topic |
| Oxygen Distribution indication        | 25 units     | Advisory only          |
| Window Heat indication                | 38 units     | Monitor                |
| Auxiliary Power Unit quantity display | 82 units     | Advisory only          |
| Speedbrake Handle annunciation        | 57 units     | Monitor                |
| Nosewheel Steering selector position  | 38 units     | Monitor                |

05.80.2 Oxygen Distribution Status Messages

The Primary Electrical Bus indication is expected to read within the sample range of 20 to 31 units during landing. If the Window Heat is inoperative, continue an extended ground delay only after the relief pilot has reviewed the

associated sample guidance. During a turnaround, the relief pilot should announce the Thrust Reverser selector position if a discrepancy is observed. The Pack Temperature Control selector position that differs from the expected state requires the pilot monitoring to confirm the condition if the indication does not stabilize within the sample interval. The Probe Heat quantity display that differs from the expected state requires the First Officer to monitor the condition before the next phase of flight. If the Landing Gear Indication is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance.

**NOTE:** If the Ground Proximity Monitor is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance.

**CAUTION:** During an extended ground delay, the First Officer should announce the Bleed Air Supply status message before the next phase of flight. The Autothrottle advisory is expected to read within the sample range of 74 to 86 units during a turnaround.

The Fuel Crossfeed selector position that differs from the expected state requires both pilots to announce the condition if a discrepancy is observed. The Hydraulic System B annunciation is expected to read within the sample range of 4 to 11 units during takeoff. The first officer will cross-check any change in the Traffic Advisory Display selector position and advise the other pilot when the associated caution light remains illuminated. During taxi, the relief pilot should brief the Standby Instruments indication before the next phase of flight.

During a diversion, the Captain should select the Ground Proximity Monitor indication once the checklist item is complete. During a maintenance-requested ground run, the relief pilot should announce the Speedbrake Handle quantity display when conditions permit. During taxi, the Captain should announce the Autothrottle annunciation when the associated caution light remains illuminated. During taxi, the Captain should announce the Pack Temperature Control status message unless directed otherwise by the Sample Operations Center. The Flap Position Indication advisory is expected to read within the sample range of 88 to 97 units during landing.

| Challenge                  | Response    |
|----------------------------|-------------|
| Cabin Pressure Controller  | Checked     |
| Hydraulic System B         | Off         |
| Flight Management Computer | As required |
| Standby Hydraulic          | Off         |
| Stall Warning              | Armed       |
| Traffic Advisory Display   | Off         |
| Flap Position Indication   | Verified    |
| Speedbrake Handle          | Set         |
| Engine Anti-Ice            | On          |
| Weather Radar              | Checked     |
| Probe Heat                 | As required |

05.80.3 Cargo Smoke Detection Status Messages

The wording here is placeholder content shaped like a procedure, not a procedure. During an extended ground delay, the First Officer should monitor the Engine Anti-Ice selector position once the checklist item is complete. Values in this manual are invented and must not be used for any operational purpose. The wording here is placeholder content shaped like a procedure, not a procedure.

- The Wing Anti-Ice selector position that differs from the expected state requires the relief pilot to confirm the condition when the associated caution light remains illuminated.
- The captain will verify any change in the Flight Management Computer switch position and advise the other pilot when conditions permit.
- Refer to the related topic for additional sample context.

- Values in this manual are invented and must not be used for any operational purpose.
- The Center Tank Pumps advisory is expected to read within the sample range of 19 to 22 units during taxi.
- Values in this manual are invented and must not be used for any operational purpose.
- The pilot flying will confirm any change in the Nosewheel Steering quantity display and advise the other pilot if the indication does not stabilize within the sample interval.
- If the Autopilot Channel B is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance.

If the Center Tank Pumps is inoperative, continue descent only after the First Officer has reviewed the associated sample guidance. The Cockpit Voice Recorder status message that differs from the expected state requires the pilot flying to cross-check the condition if a discrepancy is observed. If the Center Tank Pumps is inoperative, continue landing only after the pilot monitoring has reviewed the associated sample guidance.

- During an extended ground delay, both pilots should monitor the Autobrake Selector indication unless directed otherwise by the Sample Operations Center.
- The Hydraulic System B annunciation is expected to read within the sample range of 64 to 73 units during parking.
- If the Fuel Crossfeed is inoperative, continue parking only after the pilot monitoring has reviewed the associated sample guidance.
- The Cargo Smoke Detection selector position that differs from the expected state requires the pilot monitoring to announce the condition before the next phase of flight.
- The pilot flying will select any change in the Thrust Reverser quantity display and advise the other pilot once the checklist item is complete.
- The Autopilot Channel A quantity display that differs from the expected state requires the First Officer to cross-check the condition when conditions permit.

The Fire Detection Loop quantity display is expected to read within the sample range of 12 to 23 units during a turnaround. The Hydraulic System B status message that differs from the expected state requires the relief pilot to brief the condition once the checklist item is complete. The Brake Temperature Monitor annunciation is expected to read within the sample range of 47 to 50 units during climb. The Autopilot Channel B status message is expected to read within the sample range of 46 to 49 units during descent. If the Nosewheel Steering is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance.

| Condition                            | Sample value | Remarks       |
|--------------------------------------|--------------|---------------|
| Wing Anti-Ice status message         | 20 units     | Normal        |
| Cargo Smoke Detection status message | 84 units     | Monitor       |
| Wing Anti-Ice indication             | 27 units     | Advisory only |

During takeoff, the relief pilot should brief the Center Tank Pumps advisory if the indication does not stabilize within the sample interval. If the Weather Radar is inoperative, continue landing only after the First Officer has reviewed the associated sample guidance. The Standby Instruments status message that differs from the expected state requires the pilot monitoring to cross-check the condition if a discrepancy is observed. The Fuel Crossfeed status message that differs from the expected state requires the pilot flying to confirm the condition when operating at a sample station without ground power.

**05.80.4 Stall Warning Crew Awareness**

The Hydraulic System A quantity display that differs from the expected state requires both pilots to record the condition if a discrepancy is observed. Refer to the related topic for additional sample context. The Wing Anti-Ice status message is expected to read within the sample range of 58 to 69 units during descent. The pilot flying will

monitor any change in the Pack Temperature Control annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center. The Flap Position Indication switch position is expected to read within the sample range of 61 to 67 units during landing. During engine start, the relief pilot should verify the Pack Temperature Control switch position if a discrepancy is observed.

- The relief pilot will announce any change in the Fuel Crossfeed selector position and advise the other pilot unless directed otherwise by the Sample Operations Center.
- The Traffic Advisory Display switch position is expected to read within the sample range of 15 to 21 units during an extended ground delay.
- The Transponder quantity display that differs from the expected state requires the First Officer to announce the condition when conditions permit.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The Primary Electrical Bus selector position is expected to read within the sample range of 38 to 50 units during approach.

**CAUTION:** During a turnaround, the pilot monitoring should brief the Window Heat status message when conditions permit. During a diversion, the Captain should verify the Thrust Reverser quantity display when conditions permit.

**NOTE:** During engine start, the First Officer should verify the Bleed Air Supply selector position if a discrepancy is observed.

| Condition                                   | Sample value | Remarks                |
|---------------------------------------------|--------------|------------------------|
| Engine Anti-Ice indication                  | 36 units     | Advisory only          |
| Flight Management Computer quantity display | 35 units     | Monitor                |
| Standby Instruments annunciation            | 9 units      | Monitor                |
| Thrust Reverser selector position           | 57 units     | Advisory only          |
| Autothrottle switch position                | 55 units     | Refer to related topic |
| Stall Warning selector position             | 46 units     | Normal                 |

**05.80.5 Pack Temperature Control Status Messages**

The first officer will verify any change in the Autothrottle indication and advise the other pilot when the associated caution light remains illuminated. The pilot monitoring will brief any change in the Engine Anti-Ice advisory and advise the other pilot when conditions permit. The pilot flying will cross-check any change in the Oxygen Distribution quantity display and advise the other pilot if the indication does not stabilize within the sample interval. The Engine Anti-Ice status message that differs from the expected state requires the pilot monitoring to select the condition if the indication does not stabilize within the sample interval.

During engine start, the pilot flying should select the Speedbrake Handle advisory unless directed otherwise by the Sample Operations Center. The wording here is placeholder content shaped like a procedure, not a procedure. If the Probe Heat is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance. The pilot flying will announce any change in the Bleed Air Supply selector position and advise the other pilot if a discrepancy is observed.

The Autopilot Channel A indication that differs from the expected state requires the Captain to brief the condition once the checklist item is complete. During preflight, the pilot monitoring should confirm the Auxiliary Power Unit switch position if a discrepancy is observed. During an extended ground delay, the pilot monitoring should verify the Fire Detection Loop indication when operating at a sample station without ground power. The Landing Gear Indication advisory is expected to read within the sample range of 37 to 42 units during engine start.

| Condition | Sample value | Remarks |
|-----------|--------------|---------|
|-----------|--------------|---------|



|                                            |          |                        |
|--------------------------------------------|----------|------------------------|
| Flight Management Computer switch position | 17 units | Refer to related topic |
| Window Heat switch position                | 81 units | Refer to related topic |
| Cockpit Voice Recorder advisory            | 1 units  | Normal                 |
| Auxiliary Power Unit status message        | 67 units | Normal                 |
| Ground Proximity Monitor annunciation      | 50 units | Monitor                |
| Oxygen Distribution selector position      | 77 units | Refer to related topic |
| Auxiliary Power Unit quantity display      | 12 units | Monitor                |

- During a maintenance-requested ground run, the pilot flying should record the Cargo Smoke Detection quantity display once the checklist item is complete.
- During engine start, the pilot monitoring should monitor the Oxygen Distribution indication when operating at a sample station without ground power.
- During descent, the relief pilot should verify the Ground Proximity Monitor switch position unless directed otherwise by the Sample Operations Center.
- The Auxiliary Power Unit quantity display is expected to read within the sample range of 59 to 63 units during taxi.
- If the Center Tank Pumps is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Landing Gear Indication quantity display | 29 units     | Monitor                |
| Flap Position Indication indication      | 70 units     | Refer to related topic |
| Primary Electrical Bus quantity display  | 58 units     | Normal                 |

- The Standby Instruments selector position is expected to read within the sample range of 5 to 14 units during approach.
- If the Autothrottle is inoperative, continue takeoff only after the First Officer has reviewed the associated sample guidance.
- The Transponder selector position that differs from the expected state requires the pilot monitoring to announce the condition before the next phase of flight.
- The pilot flying will verify any change in the Autopilot Channel A switch position and advise the other pilot if the indication does not stabilize within the sample interval.

| Challenge               | Response    |
|-------------------------|-------------|
| Standby Hydraulic       | Checked     |
| Wing Anti-Ice           | As required |
| Autopilot Channel A     | Verified    |
| Standby Instruments     | Verified    |
| Autopilot Channel A     | Closed      |
| Window Heat             | Set         |
| Landing Gear Indication | As required |
| Autobrake Selector      | Closed      |
| Nosewheel Steering      | Armed       |
| Auxiliary Power Unit    | Verified    |
| Primary Electrical Bus  | Set         |

|                    |          |
|--------------------|----------|
| Hydraulic System B | Verified |
|--------------------|----------|

05.80.6 Weather Radar Interfaces

During an extended ground delay, the Captain should announce the Autobrake Selector advisory before the next phase of flight. The Bleed Air Supply quantity display that differs from the expected state requires the First Officer to announce the condition if a discrepancy is observed. If the Standby Hydraulic is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance.

During approach, the relief pilot should monitor the Thrust Reverser quantity display when operating at a sample station without ground power. During descent, the pilot monitoring should record the Wing Anti-Ice advisory once the checklist item is complete. The Oxygen Distribution quantity display that differs from the expected state requires both pilots to confirm the condition if a discrepancy is observed. During a diversion, the pilot monitoring should record the Ground Proximity Monitor advisory when conditions permit. Values in this manual are invented and must not be used for any operational purpose.

| Condition                           | Sample value | Remarks                |
|-------------------------------------|--------------|------------------------|
| Nosewheel Steering annunciation     | 23 units     | Normal                 |
| Center Tank Pumps indication        | 29 units     | Advisory only          |
| Window Heat switch position         | 67 units     | Refer to related topic |
| Fuel Crossfeed indication           | 19 units     | Refer to related topic |
| Primary Electrical Bus annunciation | 88 units     | Normal                 |

During an extended ground delay, the pilot monitoring should monitor the Bleed Air Supply switch position once the checklist item is complete. During an extended ground delay, the relief pilot should brief the Wing Anti-Ice status message unless directed otherwise by the Sample Operations Center. The pilot monitoring will cross-check any change in the Fuel Crossfeed advisory and advise the other pilot once the checklist item is complete.

The Nosewheel Steering status message is expected to read within the sample range of 81 to 85 units during approach. Refer to the related topic for additional sample context. During climb, the Captain should record the Center Tank Pumps status message unless directed otherwise by the Sample Operations Center. The Thrust Reverser advisory that differs from the expected state requires the relief pilot to confirm the condition when the associated caution light remains illuminated. The Cargo Smoke Detection quantity display is expected to read within the sample range of 28 to 38 units during cruise. The Brake Temperature Monitor annunciation that differs from the expected state requires both pilots to confirm the condition if the indication does not stabilize within the sample interval.

The wording here is placeholder content shaped like a procedure, not a procedure. Refer to the related topic for additional sample context. Values in this manual are invented and must not be used for any operational purpose. This text is fictional and exists only to give the prototype realistic volume and structure.

During preflight, both pilots should brief the Transponder selector position when conditions permit. Values in this manual are invented and must not be used for any operational purpose. During parking, the pilot monitoring should brief the Wing Anti-Ice annunciation unless directed otherwise by the Sample Operations Center. If the Fire Detection Loop is inoperative, continue preflight only after both pilots has reviewed the associated sample guidance. During approach, the relief pilot should verify the Auxiliary Power Unit advisory when conditions permit. Values in this manual are invented and must not be used for any operational purpose.

**NOTE:** The Autothrottle switch position is expected to read within the sample range of 48 to 51 units during cruise. The pilot monitoring will brief any change in the Traffic Advisory Display indication and advise the other pilot if the indication does not stabilize within the sample interval.

The Autopilot Channel B annunciation is expected to read within the sample range of 59 to 71 units during parking. If the Oxygen Distribution is inoperative, continue engine start only after the relief pilot has reviewed the associated sample guidance. The pilot monitoring will select any change in the Brake Temperature Monitor switch position and advise the other pilot once the checklist item is complete. Refer to the related topic for additional sample context. The

first officer will verify any change in the Flight Management Computer advisory and advise the other pilot when operating at a sample station without ground power.

| Challenge                 | Response    |
|---------------------------|-------------|
| Cabin Pressure Controller | Verified    |
| Oxygen Distribution       | Armed       |
| Pack Temperature Control  | Verified    |
| Window Heat               | On          |
| Traffic Advisory Display  | Verified    |
| Thrust Reverser           | Closed      |
| Speedbrake Handle         | As required |
| Fire Detection Loop       | Verified    |
| Center Tank Pumps         | Verified    |
| Cockpit Voice Recorder    | Armed       |
| Window Heat               | As required |

**05.80.7 Autothrottle Crew Awareness**

The first officer will brief any change in the Autopilot Channel A indication and advise the other pilot before the next phase of flight. During a diversion, the pilot monitoring should brief the Autopilot Channel B annunciation when operating at a sample station without ground power. The pilot monitoring will record any change in the Autothrottle switch position and advise the other pilot unless directed otherwise by the Sample Operations Center. The Brake Temperature Monitor switch position is expected to read within the sample range of 86 to 94 units during approach.

**CAUTION:** The wording here is placeholder content shaped like a procedure, not a procedure. Refer to the related topic for additional sample context.

During a diversion, the pilot monitoring should announce the Fuel Crossfeed advisory unless directed otherwise by the Sample Operations Center. Values in this manual are invented and must not be used for any operational purpose. During a diversion, the pilot flying should announce the Bleed Air Supply selector position unless directed otherwise by the Sample Operations Center. The Probe Heat switch position that differs from the expected state requires the pilot monitoring to announce the condition once the checklist item is complete. The relief pilot will confirm any change in the Flight Management Computer advisory and advise the other pilot before the next phase of flight. If the Weather Radar is inoperative, continue landing only after both pilots has reviewed the associated sample guidance.

**CAUTION:** The Speedbrake Handle switch position that differs from the expected state requires the First Officer to brief the condition before the next phase of flight.

If the Hydraulic System A is inoperative, continue climb only after both pilots has reviewed the associated sample guidance. If the Auxiliary Power Unit is inoperative, continue engine start only after the pilot monitoring has reviewed the associated sample guidance. If the Weather Radar is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance. If the Weather Radar is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance. The pilot flying will verify any change in the Stall Warning quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center.

Refer to the related topic for additional sample context. This text is fictional and exists only to give the prototype realistic volume and structure. The Transponder status message is expected to read within the sample range of 53 to 56 units during a maintenance-requested ground run. Both pilots will brief any change in the Stall Warning quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center. The Flap Position Indication indication is expected to read within the sample range of 92 to 101 units during parking.

**CAUTION:** During engine start, the First Officer should monitor the Probe Heat annunciation once the checklist item is complete.

| Challenge                 | Response    |
|---------------------------|-------------|
| Autobrake Selector        | Closed      |
| Probe Heat                | Checked     |
| Primary Electrical Bus    | As required |
| Window Heat               | Off         |
| Brake Temperature Monitor | Closed      |
| Nosewheel Steering        | Checked     |
| Landing Gear Indication   | As required |
| Stall Warning             | As required |
| Ground Proximity Monitor  | As required |

### 05.80.8 Standby Instruments Status Messages

The first officer will announce any change in the Oxygen Distribution indication and advise the other pilot when operating at a sample station without ground power. The Primary Electrical Bus status message that differs from the expected state requires both pilots to confirm the condition when conditions permit. The first officer will brief any change in the Autothrottle switch position and advise the other pilot when the associated caution light remains illuminated.

Values in this manual are invented and must not be used for any operational purpose. The Pack Temperature Control quantity display is expected to read within the sample range of 39 to 45 units during takeoff. If the Hydraulic System A is inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. The captain will record any change in the Autopilot Channel B advisory and advise the other pilot before the next phase of flight. The Hydraulic System A indication is expected to read within the sample range of 31 to 41 units during parking.

The Cargo Smoke Detection annunciation is expected to read within the sample range of 90 to 98 units during parking. The Hydraulic System A annunciation is expected to read within the sample range of 19 to 29 units during engine start. During takeoff, the pilot monitoring should announce the Autopilot Channel A indication once the checklist item is complete. If the Engine Anti-Ice is inoperative, continue parking only after the relief pilot has reviewed the associated sample guidance. The relief pilot will brief any change in the Cabin Pressure Controller annunciation and advise the other pilot when the associated caution light remains illuminated. During a turnaround, the relief pilot should select the Standby Instruments annunciation when operating at a sample station without ground power.

**NOTE:** Values in this manual are invented and must not be used for any operational purpose.

The wording here is placeholder content shaped like a procedure, not a procedure. Both pilots will select any change in the Autobrake Selector indication and advise the other pilot when operating at a sample station without ground power. This text is fictional and exists only to give the prototype realistic volume and structure. Values in this manual are invented and must not be used for any operational purpose.

### 05.80.9 Hydraulic System A Limits Display

During approach, the First Officer should confirm the Probe Heat status message if the indication does not stabilize within the sample interval. The Hydraulic System A indication is expected to read within the sample range of 11 to 19 units during a maintenance-requested ground run. The Bleed Air Supply advisory is expected to read within the sample range of 27 to 30 units during an extended ground delay. The Landing Gear Indication quantity display is expected to read within the sample range of 72 to 84 units during an extended ground delay. The pilot flying will monitor any change in the Transponder quantity display and advise the other pilot when the associated caution light remains illuminated.

The Primary Electrical Bus indication that differs from the expected state requires the pilot monitoring to monitor the condition if the indication does not stabilize within the sample interval. During approach, the relief pilot should record

the Landing Gear Indication annunciation when conditions permit. The pilot flying will verify any change in the Wing Anti-Ice status message and advise the other pilot once the checklist item is complete. The Fuel Crossfeed advisory that differs from the expected state requires the pilot flying to cross-check the condition when conditions permit. If the Standby Hydraulic is inoperative, continue landing only after both pilots has reviewed the associated sample guidance. If the Flight Management Computer is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance.

**NOTE:** The captain will select any change in the Autobrake Selector indication and advise the other pilot when conditions permit. The Fuel Crossfeed indication that differs from the expected state requires the pilot monitoring to select the condition unless directed otherwise by the Sample Operations Center.

| Condition                                | Sample value | Remarks       |
|------------------------------------------|--------------|---------------|
| Standby Hydraulic switch position        | 3 units      | Advisory only |
| Hydraulic System B indication            | 45 units     | Normal        |
| Landing Gear Indication quantity display | 72 units     | Normal        |
| Weather Radar selector position          | 26 units     | Advisory only |

The pilot flying will brief any change in the Autobrake Selector annunciation and advise the other pilot once the checklist item is complete. The Hydraulic System B advisory that differs from the expected state requires the First Officer to monitor the condition when operating at a sample station without ground power. This text is fictional and exists only to give the prototype realistic volume and structure.

05.80.10 Cargo Smoke Detection Interfaces

If the Stall Warning is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. The Hydraulic System A advisory is expected to read within the sample range of 29 to 40 units during taxi.

The wording here is placeholder content shaped like a procedure, not a procedure. The first officer will verify any change in the Flight Management Computer quantity display and advise the other pilot before the next phase of flight. This text is fictional and exists only to give the prototype realistic volume and structure. Values in this manual are invented and must not be used for any operational purpose. The Flap Position Indication indication that differs from the expected state requires the pilot monitoring to brief the condition before the next phase of flight.

**NOTE:** The pilot flying will confirm any change in the Autobrake Selector switch position and advise the other pilot if a discrepancy is observed. The Speedbrake Handle switch position is expected to read within the sample range of 93 to 99 units during cruise. Values in this manual are invented and must not be used for any operational purpose. During engine start, the relief pilot should select the Hydraulic System A status message unless directed otherwise by the Sample Operations Center. The Autobrake Selector annunciation is expected to read within the sample range of 98 to 106 units during engine start. If the Probe Heat is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance.

**NOTE:** During climb, both pilots should record the Hydraulic System B status message when the associated caution light remains illuminated.

**CAUTION:** The Cargo Smoke Detection selector position is expected to read within the sample range of 40 to 49 units during landing. The Standby Instruments switch position that differs from the expected state requires the pilot monitoring to verify the condition when the associated caution light remains illuminated.

**NOTE:** The pilot monitoring will confirm any change in the Weather Radar status message and advise the other pilot when operating at a sample station without ground power.

- The wording here is placeholder content shaped like a procedure, not a procedure.
- The wording here is placeholder content shaped like a procedure, not a procedure.

- The pilot flying will cross-check any change in the Landing Gear Indication status message and advise the other pilot once the checklist item is complete.
- The pilot flying will brief any change in the Cabin Pressure Controller indication and advise the other pilot if the indication does not stabilize within the sample interval.
- If the Brake Temperature Monitor is inoperative, continue landing only after both pilots has reviewed the associated sample guidance.
- Both pilots will select any change in the Primary Electrical Bus advisory and advise the other pilot once the checklist item is complete.

| Challenge                  | Response    |
|----------------------------|-------------|
| Oxygen Distribution        | Off         |
| Fire Detection Loop        | Set         |
| Thrust Reverser            | Verified    |
| Hydraulic System A         | As required |
| Autopilot Channel B        | Off         |
| Engine Anti-Ice            | Armed       |
| Flight Management Computer | On          |
| Window Heat                | As required |
| Standby Instruments        | Armed       |
| Autopilot Channel A        | Set         |

**05.80.11 Transponder Crew Awareness**

During landing, the Captain should verify the Weather Radar selector position before the next phase of flight. During takeoff, the relief pilot should cross-check the Ground Proximity Monitor selector position when operating at a sample station without ground power. The Autopilot Channel B switch position is expected to read within the sample range of 73 to 78 units during landing. The Center Tank Pumps annunciation that differs from the expected state requires both pilots to monitor the condition when operating at a sample station without ground power. If the Engine Anti-Ice is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance.

The Transponder advisory is expected to read within the sample range of 65 to 75 units during landing. Values in this manual are invented and must not be used for any operational purpose. If the Flap Position Indication is inoperative, continue engine start only after the relief pilot has reviewed the associated sample guidance.

- Values in this manual are invented and must not be used for any operational purpose.
- The Window Heat indication is expected to read within the sample range of 46 to 55 units during parking.
- The Engine Anti-Ice advisory is expected to read within the sample range of 93 to 97 units during taxi.

During preflight, both pilots should announce the Weather Radar indication once the checklist item is complete. The wording here is placeholder content shaped like a procedure, not a procedure. The Cargo Smoke Detection annunciation is expected to read within the sample range of 67 to 74 units during cruise. This text is fictional and exists only to give the prototype realistic volume and structure. The captain will brief any change in the Transponder indication and advise the other pilot when operating at a sample station without ground power. This text is fictional and exists only to give the prototype realistic volume and structure.

**NOTE:** This text is fictional and exists only to give the prototype realistic volume and structure. If the Landing Gear Indication is inoperative, continue an extended ground delay only after the pilot flying has reviewed the associated sample guidance.



If the Wing Anti-Ice is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance. If the Hydraulic System B is inoperative, continue a diversion only after the First Officer has reviewed the associated sample guidance. If the Standby Hydraulic is inoperative, continue approach only after the pilot monitoring has reviewed the associated sample guidance. If the Autothrottle is inoperative, continue a diversion only after the pilot monitoring has reviewed the associated sample guidance. During climb, the First Officer should confirm the Landing Gear Indication selector position before the next phase of flight.

Refer to the related topic for additional sample context. The wording here is placeholder content shaped like a procedure, not a procedure. The captain will announce any change in the Thrust Reverser switch position and advise the other pilot before the next phase of flight.

**CAUTION:** The Window Heat annunciation that differs from the expected state requires both pilots to brief the condition when conditions permit. If the Landing Gear Indication is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance.

| Challenge                  | Response    |
|----------------------------|-------------|
| Center Tank Pumps          | Checked     |
| Autopilot Channel A        | As required |
| Hydraulic System B         | Set         |
| Wing Anti-Ice              | On          |
| Wing Anti-Ice              | Closed      |
| Autobrake Selector         | Set         |
| Brake Temperature Monitor  | Closed      |
| Flight Management Computer | Set         |
| Hydraulic System B         | Closed      |
| Nosewheel Steering         | Off         |
| Autopilot Channel B        | Armed       |

05.80.12 Fuel Crossfeed Limits Display

The relief pilot will brief any change in the Autobrake Selector selector position and advise the other pilot if the indication does not stabilize within the sample interval. If the Autopilot Channel B is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance. If the Fire Detection Loop is inoperative, continue engine start only after the Captain has reviewed the associated sample guidance. The Weather Radar annunciation that differs from the expected state requires both pilots to monitor the condition when the associated caution light remains illuminated. The relief pilot will monitor any change in the Autopilot Channel B quantity display and advise the other pilot before the next phase of flight.

The captain will verify any change in the Transponder annunciation and advise the other pilot if a discrepancy is observed. If the Transponder is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance. During an extended ground delay, the relief pilot should confirm the Cockpit Voice Recorder switch position once the checklist item is complete. The Pack Temperature Control quantity display is expected to read within the sample range of 63 to 70 units during climb. The Fuel Crossfeed advisory that differs from the expected state requires the relief pilot to confirm the condition if a discrepancy is observed.

**CAUTION:** The Autopilot Channel A indication is expected to read within the sample range of 95 to 99 units during descent.

| Condition                             | Sample value | Remarks       |
|---------------------------------------|--------------|---------------|
| Flap Position Indication annunciation | 32 units     | Advisory only |
| Autothrottle switch position          | 19 units     | Normal        |
| Nosewheel Steering advisory           | 12 units     | Advisory only |

|                                            |          |                        |
|--------------------------------------------|----------|------------------------|
| Standby Instruments status message         | 14 units | Refer to related topic |
| Auxiliary Power Unit advisory              | 60 units | Monitor                |
| Brake Temperature Monitor quantity display | 10 units | Monitor                |
| Autopilot Channel B switch position        | 96 units | Advisory only          |

**CAUTION:** During climb, the Captain should confirm the Auxiliary Power Unit annunciation when the associated caution light remains illuminated. The Standby Instruments indication that differs from the expected state requires the pilot flying to record the condition once the checklist item is complete.

- The Hydraulic System A quantity display is expected to read within the sample range of 9 to 13 units during an extended ground delay.
- If the Wing Anti-Ice is inoperative, continue takeoff only after both pilots has reviewed the associated sample guidance.
- The Autopilot Channel B quantity display is expected to read within the sample range of 39 to 48 units during taxi.

The Oxygen Distribution status message is expected to read within the sample range of 62 to 74 units during taxi. The captain will confirm any change in the Autobrake Selector selector position and advise the other pilot if a discrepancy is observed. Both pilots will select any change in the Traffic Advisory Display quantity display and advise the other pilot before the next phase of flight. During landing, the First Officer should monitor the Pack Temperature Control switch position once the checklist item is complete.

| Condition                              | Sample value | Remarks                |
|----------------------------------------|--------------|------------------------|
| Nosewheel Steering switch position     | 29 units     | Monitor                |
| Oxygen Distribution selector position  | 85 units     | Refer to related topic |
| Cabin Pressure Controller advisory     | 11 units     | Advisory only          |
| Primary Electrical Bus switch position | 6 units      | Advisory only          |
| Hydraulic System B indication          | 67 units     | Monitor                |
| Stall Warning annunciation             | 16 units     | Normal                 |

The wording here is placeholder content shaped like a procedure, not a procedure. The Wing Anti-Ice advisory that differs from the expected state requires the First Officer to announce the condition when conditions permit. The Flap Position Indication indication that differs from the expected state requires both pilots to confirm the condition if the indication does not stabilize within the sample interval. The captain will monitor any change in the Hydraulic System A advisory and advise the other pilot unless directed otherwise by the Sample Operations Center. The Fuel Crossfeed indication is expected to read within the sample range of 7 to 11 units during landing. If the Flap Position Indication is inoperative, continue taxi only after the Captain has reviewed the associated sample guidance.

### 05.80.13 Flap Position Indication Indications

The Center Tank Pumps quantity display that differs from the expected state requires the Captain to record the condition before the next phase of flight. The Flap Position Indication switch position that differs from the expected state requires the pilot flying to announce the condition once the checklist item is complete. During approach, the Captain should verify the Bleed Air Supply switch position once the checklist item is complete. The Stall Warning status message that differs from the expected state requires the pilot flying to verify the condition if the indication does not stabilize within the sample interval. During approach, the pilot flying should confirm the Nosewheel Steering selector position when operating at a sample station without ground power. The Center Tank Pumps selector position is expected to read within the sample range of 50 to 55 units during a diversion.

- The Bleed Air Supply indication is expected to read within the sample range of 63 to 66 units during taxi.
- This text is fictional and exists only to give the prototype realistic volume and structure.

- The Nosewheel Steering advisory is expected to read within the sample range of 62 to 71 units during a maintenance-requested ground run.
- The pilot flying will announce any change in the Thrust Reverser status message and advise the other pilot when conditions permit.
- The captain will record any change in the Center Tank Pumps indication and advise the other pilot before the next phase of flight.
- During approach, the First Officer should brief the Hydraulic System B indication when the associated caution light remains illuminated.

**NOTE:** The Transponder advisory that differs from the expected state requires the pilot flying to monitor the condition once the checklist item is complete.

**CAUTION:** The Traffic Advisory Display annunciation that differs from the expected state requires the pilot monitoring to announce the condition when conditions permit.

- If the Landing Gear Indication is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance.
- The Standby Instruments status message is expected to read within the sample range of 58 to 64 units during takeoff.
- The Stall Warning selector position is expected to read within the sample range of 26 to 30 units during engine start.
- Values in this manual are invented and must not be used for any operational purpose.
- During descent, the pilot flying should select the Speedbrake Handle annunciation before the next phase of flight.
- The wording here is placeholder content shaped like a procedure, not a procedure.

The Transponder quantity display that differs from the expected state requires the First Officer to brief the condition when conditions permit. This text is fictional and exists only to give the prototype realistic volume and structure. During taxi, the pilot flying should confirm the Ground Proximity Monitor annunciation if the indication does not stabilize within the sample interval. This text is fictional and exists only to give the prototype realistic volume and structure. Refer to the related topic for additional sample context.

- The Stall Warning switch position is expected to read within the sample range of 5 to 16 units during an extended ground delay.
- If the Standby Instruments is inoperative, continue a diversion only after both pilots has reviewed the associated sample guidance.
- If the Hydraulic System A is inoperative, continue landing only after the pilot monitoring has reviewed the associated sample guidance.

| Challenge                  | Response    |
|----------------------------|-------------|
| Thrust Reverser            | Checked     |
| Probe Heat                 | As required |
| Center Tank Pumps          | Set         |
| Autothrottle               | Verified    |
| Autopilot Channel B        | Closed      |
| Flap Position Indication   | Armed       |
| Flight Management Computer | Checked     |
| Autobrake Selector         | As required |
| Autothrottle               | Armed       |

|                          |         |
|--------------------------|---------|
| Ground Proximity Monitor | Checked |
| Fuel Crossfeed           | Armed   |
| Ground Proximity Monitor | Armed   |

05.80.14 Flight Management Computer Indications

The Fire Detection Loop annunciation that differs from the expected state requires the First Officer to announce the condition unless directed otherwise by the Sample Operations Center. The captain will select any change in the Hydraulic System A switch position and advise the other pilot when operating at a sample station without ground power. The Landing Gear Indication indication is expected to read within the sample range of 13 to 18 units during climb. During landing, the relief pilot should select the Brake Temperature Monitor indication when the associated caution light remains illuminated.

**NOTE:** During a diversion, the Captain should announce the Flap Position Indication selector position if a discrepancy is observed. During descent, the pilot flying should select the Oxygen Distribution annunciation when the associated caution light remains illuminated.

**NOTE:** The Thrust Reverser annunciation that differs from the expected state requires the relief pilot to cross-check the condition when conditions permit. The Ground Proximity Monitor status message that differs from the expected state requires the First Officer to announce the condition when conditions permit.

If the Nosewheel Steering is inoperative, continue descent only after both pilots has reviewed the associated sample guidance. The Thrust Reverser switch position that differs from the expected state requires the Captain to cross-check the condition when conditions permit. During taxi, the First Officer should select the Cockpit Voice Recorder status message once the checklist item is complete.

**NOTE:** This text is fictional and exists only to give the prototype realistic volume and structure.

**CAUTION:** During engine start, the Captain should cross-check the Cabin Pressure Controller indication if the indication does not stabilize within the sample interval.

The Cockpit Voice Recorder selector position is expected to read within the sample range of 53 to 63 units during an extended ground delay. The Standby Instruments annunciation that differs from the expected state requires both pilots to select the condition when conditions permit. The Transponder selector position that differs from the expected state requires the First Officer to announce the condition if the indication does not stabilize within the sample interval. If the Hydraulic System A is inoperative, continue engine start only after the relief pilot has reviewed the associated sample guidance.

The pilot monitoring will brief any change in the Standby Hydraulic quantity display and advise the other pilot when the associated caution light remains illuminated. If the Ground Proximity Monitor is inoperative, continue preflight only after the pilot monitoring has reviewed the associated sample guidance. The Hydraulic System A status message that differs from the expected state requires the pilot monitoring to confirm the condition when conditions permit.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Transponder annunciation                  | 69 units     | Advisory only          |
| Speedbrake Handle advisory                | 53 units     | Refer to related topic |
| Thrust Reverser selector position         | 87 units     | Monitor                |
| Fire Detection Loop status message        | 99 units     | Advisory only          |
| Auxiliary Power Unit quantity display     | 81 units     | Refer to related topic |
| Pack Temperature Control quantity display | 79 units     | Monitor                |
| Fire Detection Loop advisory              | 84 units     | Normal                 |

05.80.15 Center Tank Pumps Crew Awareness

The Flight Management Computer advisory that differs from the expected state requires the pilot flying to announce the condition when conditions permit. During a turnaround, the First Officer should confirm the Flight Management Computer advisory if the indication does not stabilize within the sample interval. The Transponder quantity display that differs from the expected state requires the pilot flying to record the condition when conditions permit. This text is fictional and exists only to give the prototype realistic volume and structure. During an extended ground delay, both pilots should brief the Cabin Pressure Controller indication once the checklist item is complete.

**CAUTION:** If the Landing Gear Indication is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance.

**CAUTION:** During a diversion, the First Officer should record the Thrust Reverser switch position if the indication does not stabilize within the sample interval. The Landing Gear Indication switch position is expected to read within the sample range of 75 to 83 units during landing.

The Bleed Air Supply annunciation that differs from the expected state requires both pilots to confirm the condition unless directed otherwise by the Sample Operations Center. Values in this manual are invented and must not be used for any operational purpose. The Landing Gear Indication switch position that differs from the expected state requires the pilot flying to record the condition unless directed otherwise by the Sample Operations Center. The relief pilot will select any change in the Stall Warning annunciation and advise the other pilot when the associated caution light remains illuminated. The Autothrottle indication that differs from the expected state requires the First Officer to cross-check the condition when the associated caution light remains illuminated.

If the Wing Anti-Ice is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. The wording here is placeholder content shaped like a procedure, not a procedure. During parking, the pilot flying should verify the Primary Electrical Bus indication unless directed otherwise by the Sample Operations Center.

| Challenge                  | Response |
|----------------------------|----------|
| Flight Management Computer | Off      |
| Center Tank Pumps          | Checked  |
| Bleed Air Supply           | On       |
| Ground Proximity Monitor   | Verified |
| Flight Management Computer | Verified |
| Weather Radar              | Set      |
| Hydraulic System B         | Off      |
| Autobrake Selector         | Closed   |

**05.80.16    Auxiliary Power Unit Status Messages**

During landing, the Captain should verify the Weather Radar quantity display when operating at a sample station without ground power. The Engine Anti-Ice switch position that differs from the expected state requires both pilots to verify the condition once the checklist item is complete. If the Autobrake Selector is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance.

If the Stall Warning is inoperative, continue a turnaround only after the First Officer has reviewed the associated sample guidance. The Autopilot Channel B quantity display that differs from the expected state requires the pilot flying to announce the condition if the indication does not stabilize within the sample interval. The Oxygen Distribution switch position is expected to read within the sample range of 74 to 82 units during taxi. If the Flight Management Computer is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance. If the Brake Temperature Monitor is inoperative, continue landing only after the First Officer has reviewed the associated sample guidance. The Cargo Smoke Detection annunciation that differs from the expected state requires the pilot monitoring to select the condition when conditions permit.

**NOTE:** Values in this manual are invented and must not be used for any operational purpose. The Cockpit Voice Recorder indication is expected to read within the sample range of 2 to 6 units during climb.

During preflight, the relief pilot should cross-check the Landing Gear Indication selector position when conditions permit. The relief pilot will record any change in the Ground Proximity Monitor indication and advise the other pilot unless directed otherwise by the Sample Operations Center. The Speedbrake Handle annunciation is expected to read within the sample range of 37 to 47 units during a maintenance-requested ground run. If the Engine Anti-Ice is inoperative, continue an extended ground delay only after the pilot flying has reviewed the associated sample guidance. The Window Heat quantity display that differs from the expected state requires both pilots to confirm the condition once the checklist item is complete. The Probe Heat indication is expected to read within the sample range of 71 to 78 units during taxi.

The wording here is placeholder content shaped like a procedure, not a procedure. The captain will select any change in the Bleed Air Supply indication and advise the other pilot before the next phase of flight. The wording here is placeholder content shaped like a procedure, not a procedure.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Flap Position Indication annunciation      | 80 units     | Monitor                |
| Window Heat quantity display               | 90 units     | Monitor                |
| Autopilot Channel B indication             | 12 units     | Normal                 |
| Autothrottle quantity display              | 69 units     | Refer to related topic |
| Pack Temperature Control selector position | 46 units     | Monitor                |

**NOTE:** The wording here is placeholder content shaped like a procedure, not a procedure. The captain will record any change in the Standby Hydraulic switch position and advise the other pilot when the associated caution light remains illuminated.

**05.80.17 Cockpit Voice Recorder Normal Operation**

The pilot monitoring will announce any change in the Wing Anti-Ice indication and advise the other pilot unless directed otherwise by the Sample Operations Center. Values in this manual are invented and must not be used for any operational purpose. If the Autobrake Selector is inoperative, continue engine start only after the Captain has reviewed the associated sample guidance. If the Ground Proximity Monitor is inoperative, continue cruise only after the First Officer has reviewed the associated sample guidance. If the Probe Heat is inoperative, continue an extended ground delay only after the pilot flying has reviewed the associated sample guidance.

| Condition                                   | Sample value | Remarks                |
|---------------------------------------------|--------------|------------------------|
| Center Tank Pumps switch position           | 36 units     | Advisory only          |
| Stall Warning quantity display              | 88 units     | Advisory only          |
| Autothrottle annunciation                   | 32 units     | Refer to related topic |
| Primary Electrical Bus indication           | 44 units     | Normal                 |
| Autobrake Selector quantity display         | 24 units     | Normal                 |
| Brake Temperature Monitor selector position | 80 units     | Refer to related topic |
| Ground Proximity Monitor annunciation       | 50 units     | Advisory only          |

**CAUTION:** If the Nosewheel Steering is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance. The pilot monitoring will announce any change in the Transponder selector position and advise the other pilot unless directed otherwise by the Sample Operations Center.

**CAUTION:** If the Primary Electrical Bus is inoperative, continue engine start only after the Captain has reviewed the associated sample guidance.



During takeoff, both pilots should brief the Autopilot Channel B status message if a discrepancy is observed. If the Hydraulic System A is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance. Both pilots will record any change in the Brake Temperature Monitor switch position and advise the other pilot before the next phase of flight. The pilot monitoring will cross-check any change in the Brake Temperature Monitor switch position and advise the other pilot when conditions permit. The Hydraulic System B switch position is expected to read within the sample range of 46 to 49 units during a maintenance-requested ground run. The Cargo Smoke Detection quantity display that differs from the expected state requires the pilot monitoring to announce the condition before the next phase of flight.

| Challenge                | Response    |
|--------------------------|-------------|
| Thrust Reverser          | As required |
| Fuel Crossfeed           | As required |
| Traffic Advisory Display | Armed       |
| Fire Detection Loop      | As required |
| Fire Detection Loop      | Off         |
| Center Tank Pumps        | Armed       |
| Flap Position Indication | Armed       |
| Transponder              | Checked     |

### 05.80.18 Bleed Air Supply Power Sources

The Engine Anti-Ice status message that differs from the expected state requires the pilot monitoring to monitor the condition if the indication does not stabilize within the sample interval. The Weather Radar switch position that differs from the expected state requires the pilot monitoring to announce the condition when the associated caution light remains illuminated. The Autopilot Channel A indication that differs from the expected state requires the Captain to verify the condition if a discrepancy is observed. The Hydraulic System B status message that differs from the expected state requires both pilots to verify the condition once the checklist item is complete. The Wing Anti-Ice status message that differs from the expected state requires the relief pilot to brief the condition when the associated caution light remains illuminated.

During cruise, the relief pilot should monitor the Primary Electrical Bus annunciation before the next phase of flight. During a maintenance-requested ground run, the pilot monitoring should cross-check the Cockpit Voice Recorder annunciation when the associated caution light remains illuminated. The first officer will announce any change in the Probe Heat annunciation and advise the other pilot before the next phase of flight. During taxi, the Captain should confirm the Cockpit Voice Recorder status message unless directed otherwise by the Sample Operations Center. The Wing Anti-Ice quantity display is expected to read within the sample range of 18 to 21 units during descent.

**CAUTION:** During descent, the First Officer should announce the Autopilot Channel A annunciation unless directed otherwise by the Sample Operations Center. The pilot monitoring will confirm any change in the Thrust Reverser annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center.

During cruise, both pilots should select the Autobrake Selector annunciation once the checklist item is complete. The Auxiliary Power Unit quantity display is expected to read within the sample range of 61 to 65 units during descent. If the Brake Temperature Monitor is inoperative, continue a turnaround only after both pilots has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose.

The pilot flying will cross-check any change in the Ground Proximity Monitor advisory and advise the other pilot once the checklist item is complete. The first officer will select any change in the Standby Hydraulic advisory and advise the other pilot when conditions permit. During landing, the pilot monitoring should confirm the Standby Hydraulic indication when operating at a sample station without ground power. If the Autopilot Channel A is inoperative, continue a diversion only after the First Officer has reviewed the associated sample guidance. If the Hydraulic System A is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance. See 07.20.10 Flight Management Computer Status Messages.

| Challenge                  | Response    |
|----------------------------|-------------|
| Flight Management Computer | Closed      |
| Fire Detection Loop        | Off         |
| Probe Heat                 | Set         |
| Speedbrake Handle          | On          |
| Standby Instruments        | Set         |
| Flight Management Computer | On          |
| Standby Instruments        | Off         |
| Autopilot Channel A        | Closed      |
| Speedbrake Handle          | Closed      |
| Autothrottle               | Armed       |
| Hydraulic System B         | Off         |
| Standby Hydraulic          | As required |

05.80.19 Pack Temperature Control Interfaces

If the Standby Hydraulic is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance. If the Window Heat is inoperative, continue climb only after the pilot flying has reviewed the associated sample guidance. During an extended ground delay, the relief pilot should cross-check the Cockpit Voice Recorder selector position before the next phase of flight. If the Hydraulic System B is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance. The pilot flying will verify any change in the Center Tank Pumps advisory and advise the other pilot before the next phase of flight.

**NOTE:** The Flap Position Indication annunciation is expected to read within the sample range of 36 to 47 units during a diversion. The wording here is placeholder content shaped like a procedure, not a procedure.

**CAUTION:** Refer to the related topic for additional sample context.

- The Auxiliary Power Unit indication is expected to read within the sample range of 38 to 44 units during an extended ground delay.
- If the Stall Warning is inoperative, continue climb only after both pilots has reviewed the associated sample guidance.
- The Speedbrake Handle quantity display is expected to read within the sample range of 63 to 74 units during a maintenance-requested ground run.
- If the Speedbrake Handle is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance.

| Condition                                   | Sample value | Remarks                |
|---------------------------------------------|--------------|------------------------|
| Auxiliary Power Unit status message         | 97 units     | Refer to related topic |
| Brake Temperature Monitor selector position | 2 units      | Normal                 |
| Cockpit Voice Recorder selector position    | 89 units     | Normal                 |
| Wing Anti-Ice status message                | 94 units     | Normal                 |
| Engine Anti-Ice indication                  | 98 units     | Normal                 |
| Cargo Smoke Detection indication            | 84 units     | Normal                 |

During taxi, both pilots should monitor the Oxygen Distribution quantity display before the next phase of flight. The Brake Temperature Monitor advisory that differs from the expected state requires the pilot flying to announce the condition when operating at a sample station without ground power. Values in this manual are invented and must not

be used for any operational purpose.

During preflight, the pilot monitoring should announce the Standby Hydraulic status message when the associated caution light remains illuminated. If the Engine Anti-Ice is inoperative, continue parking only after the relief pilot has reviewed the associated sample guidance. The Pack Temperature Control selector position is expected to read within the sample range of 85 to 90 units during taxi. If the Auxiliary Power Unit is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance.

The Autopilot Channel B annunciation that differs from the expected state requires the relief pilot to confirm the condition if a discrepancy is observed. The Hydraulic System A status message is expected to read within the sample range of 87 to 97 units during a maintenance-requested ground run. If the Standby Instruments is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance. The Ground Proximity Monitor annunciation is expected to read within the sample range of 84 to 91 units during descent.

If the Standby Instruments is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance. During a diversion, both pilots should verify the Cargo Smoke Detection indication once the checklist item is complete. The relief pilot will select any change in the Thrust Reverser switch position and advise the other pilot unless directed otherwise by the Sample Operations Center. The Autopilot Channel A status message that differs from the expected state requires the First Officer to confirm the condition if the indication does not stabilize within the sample interval.

**05.80.20 Hydraulic System A Indications**

Refer to the related topic for additional sample context. This text is fictional and exists only to give the prototype realistic volume and structure. The pilot monitoring will cross-check any change in the Probe Heat indication and advise the other pilot before the next phase of flight. The Fire Detection Loop switch position that differs from the expected state requires the First Officer to confirm the condition when the associated caution light remains illuminated.

If the Auxiliary Power Unit is inoperative, continue parking only after the Captain has reviewed the associated sample guidance. If the Landing Gear Indication is inoperative, continue an extended ground delay only after the pilot flying has reviewed the associated sample guidance. Both pilots will verify any change in the Center Tank Pumps annunciation and advise the other pilot once the checklist item is complete. If the Transponder is inoperative, continue a turnaround only after both pilots has reviewed the associated sample guidance. During a maintenance-requested ground run, both pilots should select the Bleed Air Supply annunciation if a discrepancy is observed.

**NOTE:** The Autopilot Channel B quantity display that differs from the expected state requires the pilot monitoring to announce the condition if a discrepancy is observed.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Brake Temperature Monitor indication  | 35 units     | Advisory only          |
| Standby Instruments advisory          | 6 units      | Refer to related topic |
| Cargo Smoke Detection switch position | 72 units     | Advisory only          |
| Transponder quantity display          | 35 units     | Advisory only          |
| Autothrottle switch position          | 4 units      | Advisory only          |
| Hydraulic System B status message     | 22 units     | Normal                 |

- During cruise, the Captain should verify the Primary Electrical Bus status message unless directed otherwise by the Sample Operations Center.
- During an extended ground delay, the pilot monitoring should verify the Flap Position Indication switch position unless directed otherwise by the Sample Operations Center.

- The captain will confirm any change in the Traffic Advisory Display indication and advise the other pilot when operating at a sample station without ground power.

**CAUTION:** The Pack Temperature Control selector position that differs from the expected state requires the pilot flying to announce the condition when the associated caution light remains illuminated. The wording here is placeholder content shaped like a procedure, not a procedure.

| Challenge                | Response    |
|--------------------------|-------------|
| Bleed Air Supply         | Verified    |
| Primary Electrical Bus   | As required |
| Cargo Smoke Detection    | Closed      |
| Ground Proximity Monitor | Closed      |
| Probe Heat               | Checked     |
| Center Tank Pumps        | Checked     |
| Window Heat              | Checked     |
| Probe Heat               | Off         |
| Transponder              | Verified    |

## Chapter 06 Systems: Air Systems

### 06.10 Description

#### 06.10.1 Landing Gear Indication Overview

The pilot flying will select any change in the Window Heat indication and advise the other pilot if a discrepancy is observed. The Hydraulic System B status message that differs from the expected state requires the Captain to cross-check the condition if the indication does not stabilize within the sample interval. The Wing Anti-Ice advisory is expected to read within the sample range of 58 to 63 units during parking.

The Transponder annunciation that differs from the expected state requires the Captain to confirm the condition when the associated caution light remains illuminated. During a maintenance-requested ground run, the pilot flying should verify the Engine Anti-Ice selector position once the checklist item is complete. Values in this manual are invented and must not be used for any operational purpose. The Autothrottle annunciation that differs from the expected state requires the relief pilot to brief the condition if a discrepancy is observed. The Flight Management Computer quantity display that differs from the expected state requires the pilot flying to monitor the condition unless directed otherwise by the Sample Operations Center.

**CAUTION:** The relief pilot will monitor any change in the Traffic Advisory Display selector position and advise the other pilot once the checklist item is complete.

During descent, the pilot monitoring should brief the Nosewheel Steering switch position unless directed otherwise by the Sample Operations Center. If the Cargo Smoke Detection is inoperative, continue a turnaround only after the pilot monitoring has reviewed the associated sample guidance. The pilot monitoring will confirm any change in the Flap Position Indication annunciation and advise the other pilot once the checklist item is complete. The Engine Anti-Ice selector position that differs from the expected state requires both pilots to monitor the condition when the associated caution light remains illuminated.

This text is fictional and exists only to give the prototype realistic volume and structure. If the Autothrottle is inoperative, continue takeoff only after both pilots has reviewed the associated sample guidance. Refer to the related topic for additional sample context. The Nosewheel Steering annunciation that differs from the expected state requires the pilot flying to confirm the condition if the indication does not stabilize within the sample interval. The Cabin Pressure Controller indication that differs from the expected state requires the First Officer to verify the condition when conditions permit.

The Landing Gear Indication switch position is expected to read within the sample range of 23 to 35 units during approach. The Transponder indication that differs from the expected state requires the relief pilot to monitor the condition unless directed otherwise by the Sample Operations Center. If the Autothrottle is inoperative, continue landing only after the relief pilot has reviewed the associated sample guidance. If the Center Tank Pumps is inoperative, continue an extended ground delay only after the pilot flying has reviewed the associated sample guidance. The Autobrake Selector status message is expected to read within the sample range of 97 to 108 units during engine start.

**CAUTION:** If the Center Tank Pumps is inoperative, continue landing only after the First Officer has reviewed the associated sample guidance. During approach, the relief pilot should cross-check the Hydraulic System A selector position when the associated caution light remains illuminated.

#### 06.10.2 Ground Proximity Monitor Status Messages

The Standby Hydraulic switch position is expected to read within the sample range of 19 to 24 units during an extended ground delay. During a diversion, the pilot monitoring should confirm the Standby Hydraulic selector position unless directed otherwise by the Sample Operations Center. During taxi, the pilot flying should confirm the Autopilot Channel B selector position when operating at a sample station without ground power. The Weather Radar advisory that differs from the expected state requires the Captain to monitor the condition unless directed otherwise

by the Sample Operations Center. If the Cargo Smoke Detection is inoperative, continue approach only after the First Officer has reviewed the associated sample guidance.

The Wing Anti-Ice status message is expected to read within the sample range of 5 to 10 units during an extended ground delay. If the Autobrake Selector is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance. The Cabin Pressure Controller selector position is expected to read within the sample range of 52 to 64 units during approach. If the Flight Management Computer is inoperative, continue landing only after the First Officer has reviewed the associated sample guidance. The Cockpit Voice Recorder advisory is expected to read within the sample range of 69 to 81 units during a maintenance-requested ground run.

**CAUTION:** The Flap Position Indication annunciation is expected to read within the sample range of 49 to 59 units during approach. The Fuel Crossfeed advisory that differs from the expected state requires both pilots to verify the condition once the checklist item is complete.

**NOTE:** The Flap Position Indication selector position is expected to read within the sample range of 64 to 73 units during descent. The wording here is placeholder content shaped like a procedure, not a procedure.

**NOTE:** Refer to the related topic for additional sample context. The Flap Position Indication status message that differs from the expected state requires the Captain to record the condition when operating at a sample station without ground power.

**NOTE:** Refer to the related topic for additional sample context.

The first officer will confirm any change in the Flight Management Computer selector position and advise the other pilot before the next phase of flight. The Center Tank Pumps annunciation is expected to read within the sample range of 54 to 62 units during takeoff. During an extended ground delay, the First Officer should verify the Landing Gear Indication selector position before the next phase of flight. The Nosewheel Steering indication that differs from the expected state requires both pilots to record the condition unless directed otherwise by the Sample Operations Center. During climb, the relief pilot should brief the Thrust Reverser indication before the next phase of flight. If the Window Heat is inoperative, continue a turnaround only after the pilot monitoring has reviewed the associated sample guidance.

**06.10.3 Standby Hydraulic Reset Guidance**

Both pilots will announce any change in the Center Tank Pumps indication and advise the other pilot when the associated caution light remains illuminated. If the Pack Temperature Control is inoperative, continue engine start only after the pilot monitoring has reviewed the associated sample guidance. If the Autothrottle is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance. During cruise, the pilot monitoring should record the Weather Radar indication before the next phase of flight.

Values in this manual are invented and must not be used for any operational purpose. The Window Heat status message that differs from the expected state requires the First Officer to select the condition once the checklist item is complete. If the Engine Anti-Ice is inoperative, continue a diversion only after the First Officer has reviewed the associated sample guidance. The Oxygen Distribution annunciation is expected to read within the sample range of 97 to 102 units during cruise. Refer to the related topic for additional sample context. The Ground Proximity Monitor annunciation that differs from the expected state requires the First Officer to monitor the condition when operating at a sample station without ground power.

The wording here is placeholder content shaped like a procedure, not a procedure. The Center Tank Pumps indication is expected to read within the sample range of 85 to 89 units during a diversion. The relief pilot will verify any change in the Engine Anti-Ice switch position and advise the other pilot when operating at a sample station without ground power. See 03.50.2 Briefing: Center Tank Pumps.

| Condition                            | Sample value | Remarks |
|--------------------------------------|--------------|---------|
| Engine Anti-Ice switch position      | 16 units     | Monitor |
| Oxygen Distribution quantity display | 4 units      | Normal  |



|                                         |          |               |
|-----------------------------------------|----------|---------------|
| Primary Electrical Bus annunciation     | 92 units | Advisory only |
| Thrust Reverser indication              | 35 units | Advisory only |
| Speedbrake Handle selector position     | 14 units | Monitor       |
| Ground Proximity Monitor status message | 35 units | Normal        |

**NOTE:** The Fire Detection Loop selector position that differs from the expected state requires the Captain to verify the condition when operating at a sample station without ground power. The Landing Gear Indication status message is expected to read within the sample range of 19 to 31 units during engine start.

**06.10.4 Hydraulic System B Limits Display**

The Weather Radar quantity display is expected to read within the sample range of 73 to 82 units during takeoff. The pilot flying will verify any change in the Standby Hydraulic advisory and advise the other pilot when the associated caution light remains illuminated. The Hydraulic System B advisory is expected to read within the sample range of 59 to 62 units during a maintenance-requested ground run. During approach, the Captain should record the Autothrottle selector position when the associated caution light remains illuminated.

**CAUTION:** This text is fictional and exists only to give the prototype realistic volume and structure. During a maintenance-requested ground run, both pilots should cross-check the Brake Temperature Monitor indication when conditions permit.

**NOTE:** Refer to the related topic for additional sample context.

**CAUTION:** Values in this manual are invented and must not be used for any operational purpose.

During cruise, the pilot flying should monitor the Oxygen Distribution selector position if a discrepancy is observed. If the Cargo Smoke Detection is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. The Cargo Smoke Detection advisory is expected to read within the sample range of 10 to 22 units during takeoff. During parking, the Captain should brief the Hydraulic System A selector position if a discrepancy is observed. During climb, the Captain should record the Center Tank Pumps quantity display if the indication does not stabilize within the sample interval.

- If the Cockpit Voice Recorder is inoperative, continue approach only after the First Officer has reviewed the associated sample guidance.
- The Thrust Reverser annunciation is expected to read within the sample range of 72 to 84 units during engine start.
- The relief pilot will verify any change in the Traffic Advisory Display quantity display and advise the other pilot when the associated caution light remains illuminated.

The wording here is placeholder content shaped like a procedure, not a procedure. If the Transponder is inoperative, continue a maintenance-requested ground run only after the Captain has reviewed the associated sample guidance. Both pilots will record any change in the Flap Position Indication quantity display and advise the other pilot when the associated caution light remains illuminated. During cruise, both pilots should confirm the Bleed Air Supply switch position before the next phase of flight. This text is fictional and exists only to give the prototype realistic volume and structure. During cruise, the Captain should record the Standby Instruments indication when the associated caution light remains illuminated.

- The Cabin Pressure Controller advisory is expected to read within the sample range of 82 to 85 units during parking.
- The Standby Instruments advisory is expected to read within the sample range of 90 to 99 units during parking.
- The Cabin Pressure Controller advisory is expected to read within the sample range of 41 to 47 units during engine start.

- If the Traffic Advisory Display is inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance.

| Condition                         | Sample value | Remarks                |
|-----------------------------------|--------------|------------------------|
| Thrust Reverser selector position | 98 units     | Refer to related topic |
| Hydraulic System B indication     | 2 units      | Refer to related topic |
| Standby Instruments annunciation  | 14 units     | Advisory only          |

06.10.5 Landing Gear Indication Overview

The wording here is placeholder content shaped like a procedure, not a procedure. The captain will monitor any change in the Auxiliary Power Unit indication and advise the other pilot when conditions permit. The Hydraulic System B quantity display is expected to read within the sample range of 27 to 38 units during a diversion. During approach, the Captain should cross-check the Wing Anti-Ice switch position unless directed otherwise by the Sample Operations Center. The wording here is placeholder content shaped like a procedure, not a procedure. Both pilots will announce any change in the Nosewheel Steering selector position and advise the other pilot when operating at a sample station without ground power.

- The Autobrake Selector advisory that differs from the expected state requires the pilot flying to confirm the condition once the checklist item is complete.
- The Primary Electrical Bus indication is expected to read within the sample range of 21 to 31 units during preflight.
- The Autothrottle selector position that differs from the expected state requires both pilots to confirm the condition before the next phase of flight.
- The Engine Anti-Ice indication is expected to read within the sample range of 42 to 53 units during engine start.
- The Hydraulic System A advisory is expected to read within the sample range of 40 to 46 units during taxi.
- The Standby Hydraulic quantity display that differs from the expected state requires the pilot flying to cross-check the condition before the next phase of flight.
- The captain will verify any change in the Hydraulic System A advisory and advise the other pilot if the indication does not stabilize within the sample interval.
- The relief pilot will cross-check any change in the Autobrake Selector quantity display and advise the other pilot once the checklist item is complete.
- The Fuel Crossfeed indication that differs from the expected state requires the First Officer to verify the condition once the checklist item is complete.

During approach, the Captain should brief the Fuel Crossfeed selector position if a discrepancy is observed. The Fire Detection Loop selector position is expected to read within the sample range of 83 to 94 units during descent. During climb, the pilot monitoring should announce the Primary Electrical Bus quantity display if the indication does not stabilize within the sample interval. Values in this manual are invented and must not be used for any operational purpose. The pilot monitoring will confirm any change in the Ground Proximity Monitor switch position and advise the other pilot before the next phase of flight.

| Condition                              | Sample value | Remarks |
|----------------------------------------|--------------|---------|
| Cabin Pressure Controller annunciation | 25 units     | Normal  |
| Cockpit Voice Recorder status message  | 63 units     | Monitor |
| Nosewheel Steering indication          | 66 units     | Monitor |
| Autopilot Channel A annunciation       | 40 units     | Monitor |

| Condition | Sample value | Remarks |
|-----------|--------------|---------|
|-----------|--------------|---------|

|                                             |          |                        |
|---------------------------------------------|----------|------------------------|
| Pack Temperature Control switch position    | 22 units | Monitor                |
| Oxygen Distribution indication              | 77 units | Refer to related topic |
| Bleed Air Supply annunciation               | 60 units | Advisory only          |
| Speedbrake Handle advisory                  | 7 units  | Monitor                |
| Bleed Air Supply advisory                   | 90 units | Monitor                |
| Probe Heat status message                   | 85 units | Refer to related topic |
| Flight Management Computer quantity display | 42 units | Normal                 |

**NOTE:** If the Nosewheel Steering is inoperative, continue approach only after the pilot flying has reviewed the associated sample guidance. The first officer will brief any change in the Primary Electrical Bus selector position and advise the other pilot before the next phase of flight.

**NOTE:** The relief pilot will monitor any change in the Standby Hydraulic advisory and advise the other pilot when operating at a sample station without ground power. Both pilots will verify any change in the Autopilot Channel B status message and advise the other pilot when the associated caution light remains illuminated.

- The Window Heat quantity display that differs from the expected state requires the First Officer to cross-check the condition if a discrepancy is observed.
- During descent, the pilot flying should cross-check the Ground Proximity Monitor quantity display when the associated caution light remains illuminated.
- During takeoff, both pilots should cross-check the Auxiliary Power Unit indication when operating at a sample station without ground power.
- If the Brake Temperature Monitor is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance.

**06.10.6 Hydraulic System B Indications**

The pilot flying will cross-check any change in the Fire Detection Loop selector position and advise the other pilot before the next phase of flight. If the Autobrake Selector is inoperative, continue landing only after the First Officer has reviewed the associated sample guidance. If the Nosewheel Steering is inoperative, continue approach only after the relief pilot has reviewed the associated sample guidance. The Probe Heat selector position that differs from the expected state requires the First Officer to verify the condition before the next phase of flight. During a maintenance-requested ground run, both pilots should record the Probe Heat quantity display if a discrepancy is observed. During a maintenance-requested ground run, the Captain should announce the Nosewheel Steering switch position when operating at a sample station without ground power.

- If the Standby Instruments is inoperative, continue climb only after the relief pilot has reviewed the associated sample guidance.
- During a turnaround, the pilot flying should select the Autopilot Channel B indication when the associated caution light remains illuminated.
- This text is fictional and exists only to give the prototype realistic volume and structure.

The captain will brief any change in the Autothrottle advisory and advise the other pilot when operating at a sample station without ground power. The wording here is placeholder content shaped like a procedure, not a procedure. During a diversion, the Captain should verify the Cargo Smoke Detection quantity display once the checklist item is complete. The Autothrottle selector position that differs from the expected state requires the pilot monitoring to confirm the condition when the associated caution light remains illuminated.

| Condition                            | Sample value | Remarks                |
|--------------------------------------|--------------|------------------------|
| Nosewheel Steering selector position | 53 units     | Refer to related topic |

|                                           |          |               |
|-------------------------------------------|----------|---------------|
| Brake Temperature Monitor status message  | 13 units | Monitor       |
| Cabin Pressure Controller switch position | 89 units | Advisory only |

The pilot monitoring will monitor any change in the Cargo Smoke Detection status message and advise the other pilot unless directed otherwise by the Sample Operations Center. The captain will verify any change in the Nosewheel Steering status message and advise the other pilot if the indication does not stabilize within the sample interval. If the Hydraulic System A is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance. During landing, the relief pilot should confirm the Flap Position Indication quantity display when the associated caution light remains illuminated. The Hydraulic System B status message is expected to read within the sample range of 13 to 24 units during cruise.

If the Wing Anti-Ice is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. Both pilots will record any change in the Thrust Reverser switch position and advise the other pilot when conditions permit. The wording here is placeholder content shaped like a procedure, not a procedure. The Standby Instruments status message is expected to read within the sample range of 42 to 46 units during engine start.

**06.10.7 Autobrake Selector Test**

The pilot monitoring will announce any change in the Autopilot Channel B advisory and advise the other pilot if a discrepancy is observed. If the Weather Radar is inoperative, continue engine start only after the pilot flying has reviewed the associated sample guidance. The Window Heat selector position that differs from the expected state requires the Captain to select the condition if a discrepancy is observed.

**NOTE:** If the Flap Position Indication is inoperative, continue descent only after both pilots has reviewed the associated sample guidance.

- During parking, the pilot monitoring should cross-check the Speedbrake Handle indication when conditions permit.
- During a maintenance-requested ground run, the First Officer should confirm the Fuel Crossfeed status message when the associated caution light remains illuminated.
- If the Speedbrake Handle is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance.
- The captain will verify any change in the Probe Heat selector position and advise the other pilot if a discrepancy is observed.
- Refer to the related topic for additional sample context.

If the Fuel Crossfeed is inoperative, continue approach only after the Captain has reviewed the associated sample guidance. The Engine Anti-Ice indication that differs from the expected state requires the pilot flying to verify the condition when conditions permit. The Standby Hydraulic status message is expected to read within the sample range of 94 to 102 units during climb.

The pilot monitoring will brief any change in the Probe Heat advisory and advise the other pilot when the associated caution light remains illuminated. This text is fictional and exists only to give the prototype realistic volume and structure. The Autobrake Selector quantity display is expected to read within the sample range of 55 to 61 units during cruise. Both pilots will cross-check any change in the Autopilot Channel B indication and advise the other pilot if the indication does not stabilize within the sample interval. The Flap Position Indication status message is expected to read within the sample range of 47 to 51 units during cruise. The Bleed Air Supply status message is expected to read within the sample range of 33 to 40 units during takeoff.

**06.10.8 Wing Anti-Ice Interfaces**

The Nosewheel Steering advisory is expected to read within the sample range of 20 to 30 units during climb. The Oxygen Distribution selector position is expected to read within the sample range of 95 to 98 units during cruise.

During takeoff, the Captain should record the Hydraulic System A quantity display when conditions permit.

The Landing Gear Indication indication is expected to read within the sample range of 79 to 90 units during engine start. The captain will cross-check any change in the Center Tank Pumps switch position and advise the other pilot once the checklist item is complete. The captain will cross-check any change in the Autothrottle indication and advise the other pilot if the indication does not stabilize within the sample interval.

The wording here is placeholder content shaped like a procedure, not a procedure. This text is fictional and exists only to give the prototype realistic volume and structure. During engine start, the pilot flying should verify the Wing Anti-Ice selector position when conditions permit.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Nosewheel Steering switch position        | 95 units     | Monitor                |
| Bleed Air Supply status message           | 1 units      | Advisory only          |
| Ground Proximity Monitor quantity display | 15 units     | Refer to related topic |
| Oxygen Distribution switch position       | 88 units     | Refer to related topic |
| Window Heat quantity display              | 61 units     | Normal                 |
| Weather Radar annunciation                | 33 units     | Normal                 |
| Stall Warning selector position           | 22 units     | Normal                 |

**NOTE:** The Nosewheel Steering advisory that differs from the expected state requires both pilots to cross-check the condition when the associated caution light remains illuminated.

**06.10.9 Thrust Reverser Normal Operation**

If the Stall Warning is inoperative, continue engine start only after the relief pilot has reviewed the associated sample guidance. Both pilots will announce any change in the Oxygen Distribution annunciation and advise the other pilot if a discrepancy is observed. The Hydraulic System A selector position is expected to read within the sample range of 73 to 77 units during a maintenance-requested ground run. If the Pack Temperature Control is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance.

The Auxiliary Power Unit quantity display is expected to read within the sample range of 63 to 73 units during parking. The Transponder switch position is expected to read within the sample range of 34 to 43 units during a maintenance-requested ground run. This text is fictional and exists only to give the prototype realistic volume and structure. The Window Heat status message is expected to read within the sample range of 22 to 32 units during landing. If the Cabin Pressure Controller is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance. The pilot monitoring will announce any change in the Engine Anti-Ice selector position and advise the other pilot if a discrepancy is observed.

The wording here is placeholder content shaped like a procedure, not a procedure. Both pilots will verify any change in the Bleed Air Supply switch position and advise the other pilot if a discrepancy is observed. During a turnaround, the Captain should verify the Hydraulic System A switch position when operating at a sample station without ground power.

The Autobrake Selector status message is expected to read within the sample range of 48 to 58 units during an extended ground delay. If the Engine Anti-Ice is inoperative, continue climb only after both pilots has reviewed the associated sample guidance. Both pilots will announce any change in the Autothrottle selector position and advise the other pilot when conditions permit. The Traffic Advisory Display selector position that differs from the expected state requires the pilot flying to monitor the condition when conditions permit. The Stall Warning annunciation is expected to read within the sample range of 42 to 51 units during parking. During takeoff, both pilots should brief the Standby Hydraulic advisory before the next phase of flight.

The Window Heat status message that differs from the expected state requires the pilot flying to monitor the condition when operating at a sample station without ground power. The Flight Management Computer status message is

expected to read within the sample range of 63 to 73 units during engine start. The Autopilot Channel B annunciation that differs from the expected state requires both pilots to brief the condition once the checklist item is complete. If the Center Tank Pumps is inoperative, continue approach only after the pilot flying has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. The Hydraulic System A status message is expected to read within the sample range of 33 to 45 units during descent.

**CAUTION:** The Primary Electrical Bus selector position is expected to read within the sample range of 24 to 32 units during landing. The captain will announce any change in the Bleed Air Supply switch position and advise the other pilot if a discrepancy is observed.

This text is fictional and exists only to give the prototype realistic volume and structure. This text is fictional and exists only to give the prototype realistic volume and structure. The Fuel Crossfeed status message that differs from the expected state requires the Captain to select the condition once the checklist item is complete. The Nosewheel Steering switch position that differs from the expected state requires the pilot monitoring to select the condition if the indication does not stabilize within the sample interval. The Flap Position Indication status message that differs from the expected state requires the relief pilot to announce the condition before the next phase of flight.

**06.10.10 Cargo Smoke Detection Crew Awareness**

If the Landing Gear Indication is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance. Both pilots will brief any change in the Autopilot Channel B quantity display and advise the other pilot when conditions permit. During an extended ground delay, the pilot monitoring should select the Center Tank Pumps selector position if a discrepancy is observed. During parking, the Captain should verify the Autopilot Channel A quantity display when the associated caution light remains illuminated.

**NOTE:** The relief pilot will verify any change in the Auxiliary Power Unit status message and advise the other pilot when conditions permit. The pilot monitoring will monitor any change in the Weather Radar annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center.

During an extended ground delay, the pilot monitoring should select the Thrust Reverser selector position if a discrepancy is observed. The relief pilot will cross-check any change in the Probe Heat advisory and advise the other pilot once the checklist item is complete. This text is fictional and exists only to give the prototype realistic volume and structure. This text is fictional and exists only to give the prototype realistic volume and structure. If the Speedbrake Handle is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance.

The Cargo Smoke Detection indication that differs from the expected state requires the First Officer to record the condition once the checklist item is complete. The Nosewheel Steering switch position is expected to read within the sample range of 49 to 54 units during a diversion. The Nosewheel Steering switch position that differs from the expected state requires the pilot monitoring to cross-check the condition if the indication does not stabilize within the sample interval.

**NOTE:** Refer to the related topic for additional sample context.

| Condition                              | Sample value | Remarks                |
|----------------------------------------|--------------|------------------------|
| Standby Instruments selector position  | 92 units     | Refer to related topic |
| Autopilot Channel B indication         | 58 units     | Advisory only          |
| Cargo Smoke Detection quantity display | 99 units     | Advisory only          |
| Thrust Reverser quantity display       | 8 units      | Advisory only          |
| Autopilot Channel A selector position  | 7 units      | Refer to related topic |
| Thrust Reverser indication             | 28 units     | Monitor                |

**NOTE:** This text is fictional and exists only to give the prototype realistic volume and structure.

**CAUTION:** The wording here is placeholder content shaped like a procedure, not a procedure.



**NOTE:** If the Autopilot Channel B is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance. The relief pilot will monitor any change in the Auxiliary Power Unit selector position and advise the other pilot unless directed otherwise by the Sample Operations Center.

### 06.10.11 Engine Anti-Ice Interfaces

The Flap Position Indication advisory is expected to read within the sample range of 18 to 30 units during preflight. The Flap Position Indication advisory is expected to read within the sample range of 27 to 34 units during landing. During a maintenance-requested ground run, the relief pilot should monitor the Autopilot Channel A switch position if the indication does not stabilize within the sample interval. The Autopilot Channel B selector position is expected to read within the sample range of 64 to 71 units during descent.

The pilot flying will select any change in the Autothrottle annunciation and advise the other pilot when conditions permit. The Hydraulic System A quantity display that differs from the expected state requires the pilot monitoring to monitor the condition when conditions permit. The Hydraulic System A indication that differs from the expected state requires the pilot monitoring to confirm the condition if a discrepancy is observed.

If the Primary Electrical Bus is inoperative, continue landing only after both pilots has reviewed the associated sample guidance. The first officer will record any change in the Engine Anti-Ice switch position and advise the other pilot when operating at a sample station without ground power. The captain will confirm any change in the Flight Management Computer selector position and advise the other pilot once the checklist item is complete.

The pilot monitoring will record any change in the Window Heat status message and advise the other pilot when operating at a sample station without ground power. Values in this manual are invented and must not be used for any operational purpose. The Transponder indication is expected to read within the sample range of 61 to 73 units during an extended ground delay. The Cargo Smoke Detection quantity display that differs from the expected state requires the relief pilot to record the condition before the next phase of flight.

- The pilot flying will record any change in the Cockpit Voice Recorder quantity display and advise the other pilot when operating at a sample station without ground power.
- The Standby Hydraulic annunciation is expected to read within the sample range of 63 to 67 units during engine start.
- If the Weather Radar is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance.
- The pilot flying will confirm any change in the Fuel Crossfeed annunciation and advise the other pilot when conditions permit.

The captain will monitor any change in the Transponder quantity display and advise the other pilot once the checklist item is complete. If the Center Tank Pumps is inoperative, continue climb only after the First Officer has reviewed the associated sample guidance. The captain will brief any change in the Autothrottle advisory and advise the other pilot when conditions permit. The Cabin Pressure Controller quantity display is expected to read within the sample range of 13 to 22 units during parking. During climb, the relief pilot should monitor the Probe Heat quantity display when conditions permit.

- The Fire Detection Loop switch position that differs from the expected state requires the First Officer to confirm the condition once the checklist item is complete.
- During a diversion, the pilot flying should monitor the Speedbrake Handle advisory when the associated caution light remains illuminated.
- The Autobrake Selector annunciation is expected to read within the sample range of 5 to 15 units during descent.
- The pilot monitoring will brief any change in the Transponder quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center.



- The Center Tank Pumps indication that differs from the expected state requires the First Officer to confirm the condition if a discrepancy is observed.

During an extended ground delay, the pilot monitoring should verify the Flap Position Indication advisory when the associated caution light remains illuminated. During a diversion, the Captain should confirm the Autobrake Selector quantity display when conditions permit. The wording here is placeholder content shaped like a procedure, not a procedure. The captain will monitor any change in the Wing Anti-Ice status message and advise the other pilot when conditions permit.

**06.10.12 Brake Temperature Monitor Normal Operation**

During taxi, the pilot monitoring should monitor the Ground Proximity Monitor switch position unless directed otherwise by the Sample Operations Center. The Oxygen Distribution advisory that differs from the expected state requires the relief pilot to cross-check the condition when conditions permit. During a maintenance-requested ground run, the pilot monitoring should verify the Flap Position Indication quantity display once the checklist item is complete. If the Fire Detection Loop is inoperative, continue landing only after both pilots has reviewed the associated sample guidance. The Cockpit Voice Recorder status message that differs from the expected state requires the pilot monitoring to brief the condition unless directed otherwise by the Sample Operations Center. If the Brake Temperature Monitor is inoperative, continue a diversion only after the First Officer has reviewed the associated sample guidance.

During approach, the pilot flying should verify the Brake Temperature Monitor selector position once the checklist item is complete. The first officer will select any change in the Cabin Pressure Controller advisory and advise the other pilot when operating at a sample station without ground power. The first officer will record any change in the Nosewheel Steering status message and advise the other pilot if the indication does not stabilize within the sample interval. The Flap Position Indication indication that differs from the expected state requires both pilots to monitor the condition unless directed otherwise by the Sample Operations Center. The pilot flying will monitor any change in the Speedbrake Handle status message and advise the other pilot when the associated caution light remains illuminated.

**CAUTION:** If the Traffic Advisory Display is inoperative, continue taxi only after the relief pilot has reviewed the associated sample guidance. The pilot flying will cross-check any change in the Primary Electrical Bus switch position and advise the other pilot unless directed otherwise by the Sample Operations Center.

| Condition                                   | Sample value | Remarks       |
|---------------------------------------------|--------------|---------------|
| Flap Position Indication switch position    | 23 units     | Monitor       |
| Nosewheel Steering selector position        | 93 units     | Normal        |
| Transponder status message                  | 84 units     | Normal        |
| Brake Temperature Monitor selector position | 89 units     | Advisory only |
| Window Heat switch position                 | 30 units     | Advisory only |

During a turnaround, the pilot monitoring should verify the Traffic Advisory Display advisory when operating at a sample station without ground power. The captain will cross-check any change in the Center Tank Pumps status message and advise the other pilot before the next phase of flight. The wording here is placeholder content shaped like a procedure, not a procedure. The Autopilot Channel A switch position is expected to read within the sample range of 8 to 15 units during descent.

**CAUTION:** The Oxygen Distribution annunciation that differs from the expected state requires the First Officer to cross-check the condition if a discrepancy is observed.

The relief pilot will verify any change in the Standby Instruments status message and advise the other pilot before the next phase of flight. During a turnaround, the First Officer should verify the Nosewheel Steering advisory when operating at a sample station without ground power. During taxi, both pilots should confirm the Bleed Air Supply indication when conditions permit. If the Transponder is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any

operational purpose. The first officer will confirm any change in the Bleed Air Supply switch position and advise the other pilot if the indication does not stabilize within the sample interval.

### 06.10.13 Standby Hydraulic Crew Awareness

The pilot flying will monitor any change in the Hydraulic System B quantity display and advise the other pilot when operating at a sample station without ground power. Values in this manual are invented and must not be used for any operational purpose. Refer to the related topic for additional sample context. The Hydraulic System A indication is expected to read within the sample range of 22 to 30 units during preflight.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Oxygen Distribution switch position      | 9 units      | Normal                 |
| Center Tank Pumps status message         | 90 units     | Refer to related topic |
| Landing Gear Indication quantity display | 24 units     | Monitor                |
| Autopilot Channel A selector position    | 63 units     | Normal                 |

**NOTE:** During a maintenance-requested ground run, the pilot monitoring should record the Pack Temperature Control quantity display if a discrepancy is observed. If the Autopilot Channel B is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance.

- The Autothrottle status message that differs from the expected state requires both pilots to verify the condition if a discrepancy is observed.
- The Stall Warning selector position is expected to read within the sample range of 88 to 95 units during parking.
- During a turnaround, the Captain should cross-check the Fuel Crossfeed annunciation when the associated caution light remains illuminated.
- The Probe Heat status message is expected to read within the sample range of 34 to 43 units during a diversion.

**NOTE:** During takeoff, the pilot flying should brief the Fire Detection Loop annunciation before the next phase of flight. The Cabin Pressure Controller quantity display is expected to read within the sample range of 74 to 83 units during a diversion.

The Cabin Pressure Controller indication is expected to read within the sample range of 61 to 68 units during a maintenance-requested ground run. During descent, both pilots should announce the Ground Proximity Monitor status message once the checklist item is complete. During descent, the pilot flying should verify the Cockpit Voice Recorder advisory before the next phase of flight.

**CAUTION:** The Traffic Advisory Display advisory that differs from the expected state requires the pilot monitoring to select the condition when conditions permit.

### 06.10.14 Autobrake Selector Status Messages

If the Landing Gear Indication is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance. If the Primary Electrical Bus is inoperative, continue descent only after the Captain has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose.

If the Standby Hydraulic is inoperative, continue a turnaround only after the pilot monitoring has reviewed the associated sample guidance. If the Bleed Air Supply is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance. The first officer will cross-check any change in the Oxygen Distribution quantity display and advise the other pilot if the indication does not stabilize within the sample interval. Both pilots will monitor any change in the Center Tank Pumps status message and advise the other pilot before the next phase of flight. If the Landing Gear Indication is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance. The Autobrake Selector indication is expected to read within the sample range of 31 to

38 units during taxi.

During parking, the pilot flying should verify the Ground Proximity Monitor advisory unless directed otherwise by the Sample Operations Center. During a turnaround, the relief pilot should cross-check the Bleed Air Supply annunciation before the next phase of flight. The Center Tank Pumps status message is expected to read within the sample range of 98 to 101 units during approach. If the Pack Temperature Control is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance. If the Stall Warning is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance. The relief pilot will announce any change in the Fire Detection Loop advisory and advise the other pilot if a discrepancy is observed.

- The Fire Detection Loop switch position is expected to read within the sample range of 69 to 77 units during takeoff.
- During preflight, the pilot flying should announce the Standby Hydraulic quantity display when operating at a sample station without ground power.
- The Cabin Pressure Controller quantity display is expected to read within the sample range of 77 to 84 units during taxi.

**NOTE:** During an extended ground delay, the relief pilot should announce the Primary Electrical Bus switch position when conditions permit. The Probe Heat switch position that differs from the expected state requires the First Officer to confirm the condition once the checklist item is complete.

**CAUTION:** The Flight Management Computer status message is expected to read within the sample range of 32 to 40 units during descent.

If the Autothrottle is inoperative, continue landing only after the relief pilot has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. This text is fictional and exists only to give the prototype realistic volume and structure. The captain will brief any change in the Autobrake Selector advisory and advise the other pilot if the indication does not stabilize within the sample interval. Refer to the related topic for additional sample context. This text is fictional and exists only to give the prototype realistic volume and structure.

- The Pack Temperature Control indication that differs from the expected state requires the Captain to confirm the condition when operating at a sample station without ground power.
- The pilot monitoring will brief any change in the Wing Anti-Ice annunciation and advise the other pilot when operating at a sample station without ground power.
- This text is fictional and exists only to give the prototype realistic volume and structure.

The Brake Temperature Monitor quantity display that differs from the expected state requires both pilots to record the condition when the associated caution light remains illuminated. If the Flap Position Indication is inoperative, continue cruise only after the Captain has reviewed the associated sample guidance. The Auxiliary Power Unit advisory is expected to read within the sample range of 83 to 89 units during engine start. During climb, the First Officer should verify the Ground Proximity Monitor selector position once the checklist item is complete.

### **06.10.15 Probe Heat Test**

The Thrust Reverser switch position is expected to read within the sample range of 84 to 89 units during a diversion. During landing, the relief pilot should cross-check the Wing Anti-Ice status message if the indication does not stabilize within the sample interval. The captain will record any change in the Wing Anti-Ice annunciation and advise the other pilot if the indication does not stabilize within the sample interval. The Standby Hydraulic indication that differs from the expected state requires the First Officer to verify the condition if the indication does not stabilize within the sample interval. The relief pilot will record any change in the Center Tank Pumps annunciation and advise the other pilot when the associated caution light remains illuminated.

This text is fictional and exists only to give the prototype realistic volume and structure. If the Window Heat is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample

guidance. During engine start, the relief pilot should brief the Auxiliary Power Unit indication when conditions permit. During taxi, the First Officer should select the Nosewheel Steering quantity display when the associated caution light remains illuminated. The Cabin Pressure Controller advisory is expected to read within the sample range of 41 to 46 units during preflight. The Center Tank Pumps annunciation that differs from the expected state requires the relief pilot to record the condition when conditions permit.

The Stall Warning annunciation that differs from the expected state requires the relief pilot to confirm the condition when operating at a sample station without ground power. Refer to the related topic for additional sample context. The first officer will monitor any change in the Hydraulic System B status message and advise the other pilot unless directed otherwise by the Sample Operations Center. The pilot monitoring will brief any change in the Thrust Reverser status message and advise the other pilot before the next phase of flight. The Standby Instruments quantity display is expected to read within the sample range of 93 to 104 units during preflight.

This text is fictional and exists only to give the prototype realistic volume and structure. The captain will brief any change in the Center Tank Pumps switch position and advise the other pilot before the next phase of flight. If the Nosewheel Steering is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance. During taxi, both pilots should verify the Autopilot Channel A indication if the indication does not stabilize within the sample interval.

If the Autothrottle is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance. Refer to the related topic for additional sample context. If the Thrust Reverser is inoperative, continue a maintenance-requested ground run only after the pilot monitoring has reviewed the associated sample guidance. The first officer will monitor any change in the Hydraulic System B advisory and advise the other pilot before the next phase of flight. The Engine Anti-Ice indication that differs from the expected state requires the pilot monitoring to confirm the condition when conditions permit.

The Probe Heat advisory is expected to read within the sample range of 80 to 89 units during climb. The Cockpit Voice Recorder switch position is expected to read within the sample range of 82 to 93 units during descent. During climb, the pilot monitoring should brief the Cabin Pressure Controller advisory when operating at a sample station without ground power. During preflight, the First Officer should announce the Stall Warning quantity display when conditions permit. If the Weather Radar is inoperative, continue taxi only after the relief pilot has reviewed the associated sample guidance. During parking, the pilot monitoring should monitor the Engine Anti-Ice quantity display if a discrepancy is observed. See 08.20.15 Hydraulic System B Crew Awareness.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Autobrake Selector status message        | 95 units     | Refer to related topic |
| Cabin Pressure Controller status message | 22 units     | Normal                 |
| Autobrake Selector indication            | 27 units     | Refer to related topic |
| Center Tank Pumps indication             | 73 units     | Refer to related topic |
| Autobrake Selector annunciation          | 2 units      | Normal                 |

### 06.10.16 Hydraulic System A Interfaces

The relief pilot will brief any change in the Fuel Crossfeed quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center. The pilot flying will select any change in the Cockpit Voice Recorder switch position and advise the other pilot if the indication does not stabilize within the sample interval. The Flight Management Computer quantity display is expected to read within the sample range of 52 to 62 units during parking. The Autopilot Channel B quantity display is expected to read within the sample range of 96 to 106 units during approach.

- The Bleed Air Supply selector position that differs from the expected state requires the First Officer to brief the condition if the indication does not stabilize within the sample interval.
- The wording here is placeholder content shaped like a procedure, not a procedure.

- This text is fictional and exists only to give the prototype realistic volume and structure.
- The Standby Instruments selector position is expected to read within the sample range of 16 to 22 units during engine start.

If the Bleed Air Supply is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance. During a maintenance-requested ground run, the First Officer should announce the Cargo Smoke Detection quantity display if the indication does not stabilize within the sample interval. The wording here is placeholder content shaped like a procedure, not a procedure. During preflight, both pilots should monitor the Cargo Smoke Detection selector position unless directed otherwise by the Sample Operations Center. The Weather Radar advisory is expected to read within the sample range of 92 to 98 units during a maintenance-requested ground run. The first officer will cross-check any change in the Oxygen Distribution quantity display and advise the other pilot when operating at a sample station without ground power.

**CAUTION:** If the Traffic Advisory Display is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance. The Autobrake Selector status message is expected to read within the sample range of 85 to 97 units during approach.

The Weather Radar selector position that differs from the expected state requires the First Officer to confirm the condition before the next phase of flight. The Cargo Smoke Detection switch position that differs from the expected state requires the Captain to cross-check the condition if the indication does not stabilize within the sample interval. The pilot flying will announce any change in the Wing Anti-Ice annunciation and advise the other pilot before the next phase of flight.

Both pilots will verify any change in the Autobrake Selector advisory and advise the other pilot if the indication does not stabilize within the sample interval. The Bleed Air Supply advisory that differs from the expected state requires the pilot flying to brief the condition when operating at a sample station without ground power. The Wing Anti-Ice annunciation that differs from the expected state requires the Captain to select the condition when the associated caution light remains illuminated. Values in this manual are invented and must not be used for any operational purpose. The first officer will record any change in the Ground Proximity Monitor annunciation and advise the other pilot before the next phase of flight.

**NOTE:** Values in this manual are invented and must not be used for any operational purpose.

## 06.20 Controls and Indicators

### 06.20.1 Cockpit Voice Recorder Power Sources

If the Brake Temperature Monitor is inoperative, continue landing only after the pilot monitoring has reviewed the associated sample guidance. During takeoff, the pilot monitoring should monitor the Hydraulic System A advisory unless directed otherwise by the Sample Operations Center. The Standby Instruments indication that differs from the expected state requires the pilot flying to brief the condition when conditions permit. The wording here is placeholder content shaped like a procedure, not a procedure.

| Condition                                  | Sample value | Remarks       |
|--------------------------------------------|--------------|---------------|
| Landing Gear Indication status message     | 21 units     | Advisory only |
| Auxiliary Power Unit status message        | 20 units     | Monitor       |
| Flight Management Computer switch position | 31 units     | Advisory only |
| Flap Position Indication quantity display  | 77 units     | Advisory only |
| Center Tank Pumps advisory                 | 94 units     | Advisory only |
| Fuel Crossfeed switch position             | 17 units     | Normal        |
| Traffic Advisory Display indication        | 38 units     | Monitor       |

**CAUTION:** The Probe Heat indication is expected to read within the sample range of 26 to 32 units during cruise.

Values in this manual are invented and must not be used for any operational purpose. The pilot monitoring will verify any change in the Weather Radar advisory and advise the other pilot unless directed otherwise by the Sample Operations Center. If the Primary Electrical Bus is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance. During a turnaround, the Captain should monitor the Autopilot Channel A annunciation when conditions permit. If the Transponder is inoperative, continue an extended ground delay only after the pilot flying has reviewed the associated sample guidance.

**CAUTION:** The wording here is placeholder content shaped like a procedure, not a procedure. The Oxygen Distribution selector position that differs from the expected state requires the relief pilot to select the condition once the checklist item is complete.

During an extended ground delay, the First Officer should record the Hydraulic System A status message unless directed otherwise by the Sample Operations Center. Refer to the related topic for additional sample context. The Standby Hydraulic status message that differs from the expected state requires the pilot monitoring to brief the condition unless directed otherwise by the Sample Operations Center.

- The Autobrake Selector advisory that differs from the expected state requires both pilots to record the condition before the next phase of flight.
- If the Brake Temperature Monitor is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance.
- During landing, the First Officer should announce the Speedbrake Handle selector position unless directed otherwise by the Sample Operations Center.
- The Landing Gear Indication advisory is expected to read within the sample range of 12 to 21 units during cruise.
- During landing, the pilot flying should record the Autopilot Channel B switch position unless directed otherwise by the Sample Operations Center.
- The captain will monitor any change in the Cockpit Voice Recorder annunciation and advise the other pilot when the associated caution light remains illuminated.

### 06.20.2 Fire Detection Loop Indications

The Speedbrake Handle switch position is expected to read within the sample range of 25 to 33 units during descent. The Window Heat selector position is expected to read within the sample range of 59 to 69 units during engine start. The Transponder quantity display is expected to read within the sample range of 62 to 67 units during climb.

**NOTE:** The Stall Warning indication that differs from the expected state requires the First Officer to verify the condition if the indication does not stabilize within the sample interval.

If the Stall Warning is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance. During landing, the First Officer should announce the Nosewheel Steering selector position once the checklist item is complete. If the Traffic Advisory Display is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance. The Oxygen Distribution annunciation is expected to read within the sample range of 95 to 104 units during engine start. The wording here is placeholder content shaped like a procedure, not a procedure. During descent, the pilot monitoring should monitor the Ground Proximity Monitor annunciation before the next phase of flight.

Refer to the related topic for additional sample context. Both pilots will confirm any change in the Fuel Crossfeed annunciation and advise the other pilot when the associated caution light remains illuminated. Both pilots will monitor any change in the Speedbrake Handle status message and advise the other pilot if a discrepancy is observed. During a maintenance-requested ground run, the pilot flying should verify the Wing Anti-Ice switch position before the next phase of flight. The Brake Temperature Monitor status message that differs from the expected state requires the relief pilot to announce the condition when the associated caution light remains illuminated. The pilot flying will monitor any change in the Autobrake Selector quantity display and advise the other pilot when the associated caution light remains illuminated.



If the Pack Temperature Control is inoperative, continue approach only after the pilot flying has reviewed the associated sample guidance. The relief pilot will confirm any change in the Autopilot Channel B quantity display and advise the other pilot when the associated caution light remains illuminated. During descent, the pilot monitoring should record the Hydraulic System B selector position unless directed otherwise by the Sample Operations Center. If the Hydraulic System A is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance.

**NOTE:** The Nosewheel Steering annunciation is expected to read within the sample range of 82 to 85 units during preflight. The first officer will confirm any change in the Transponder switch position and advise the other pilot when operating at a sample station without ground power.

The Probe Heat quantity display that differs from the expected state requires the First Officer to monitor the condition before the next phase of flight. The captain will select any change in the Autopilot Channel A advisory and advise the other pilot if the indication does not stabilize within the sample interval. During takeoff, the pilot flying should cross-check the Nosewheel Steering selector position when conditions permit. During cruise, the pilot flying should cross-check the Ground Proximity Monitor status message when conditions permit.

**NOTE:** Values in this manual are invented and must not be used for any operational purpose.

**06.20.3 Oxygen Distribution Reset Guidance**

During climb, the Captain should monitor the Cabin Pressure Controller advisory before the next phase of flight. The Traffic Advisory Display indication that differs from the expected state requires the pilot flying to verify the condition when the associated caution light remains illuminated. The pilot monitoring will confirm any change in the Autopilot Channel B advisory and advise the other pilot if the indication does not stabilize within the sample interval. The Probe Heat switch position is expected to read within the sample range of 68 to 74 units during parking. The pilot flying will select any change in the Weather Radar status message and advise the other pilot when conditions permit. If the Hydraulic System A is inoperative, continue taxi only after the First Officer has reviewed the associated sample guidance.

The pilot flying will verify any change in the Autopilot Channel A advisory and advise the other pilot when operating at a sample station without ground power. The Nosewheel Steering indication is expected to read within the sample range of 4 to 15 units during descent. The Autopilot Channel A indication that differs from the expected state requires the pilot flying to announce the condition unless directed otherwise by the Sample Operations Center. If the Autopilot Channel A is inoperative, continue a maintenance-requested ground run only after the pilot flying has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure.

**NOTE:** If the Cockpit Voice Recorder is inoperative, continue climb only after the pilot flying has reviewed the associated sample guidance. The Hydraulic System B indication that differs from the expected state requires the Captain to announce the condition if the indication does not stabilize within the sample interval.

| Condition                            | Sample value | Remarks                |
|--------------------------------------|--------------|------------------------|
| Brake Temperature Monitor indication | 18 units     | Normal                 |
| Speedbrake Handle indication         | 53 units     | Refer to related topic |
| Fuel Crossfeed status message        | 9 units      | Normal                 |

The Window Heat quantity display that differs from the expected state requires the Captain to confirm the condition unless directed otherwise by the Sample Operations Center. If the Weather Radar is inoperative, continue landing only after the pilot monitoring has reviewed the associated sample guidance. During an extended ground delay, the Captain should brief the Bleed Air Supply status message once the checklist item is complete.

The first officer will record any change in the Brake Temperature Monitor indication and advise the other pilot once the checklist item is complete. The Window Heat indication is expected to read within the sample range of 55 to 63 units during preflight. During landing, the Captain should monitor the Cockpit Voice Recorder quantity display if the indication does not stabilize within the sample interval.

During a diversion, the Captain should verify the Engine Anti-Ice annunciation unless directed otherwise by the Sample Operations Center. During cruise, the pilot flying should brief the Fire Detection Loop switch position when the associated caution light remains illuminated. The relief pilot will verify any change in the Weather Radar selector position and advise the other pilot when operating at a sample station without ground power. The Fuel Crossfeed annunciation is expected to read within the sample range of 89 to 95 units during taxi.

| Condition                               | Sample value | Remarks       |
|-----------------------------------------|--------------|---------------|
| Primary Electrical Bus quantity display | 76 units     | Advisory only |
| Stall Warning selector position         | 10 units     | Advisory only |
| Traffic Advisory Display indication     | 51 units     | Normal        |
| Weather Radar quantity display          | 29 units     | Monitor       |
| Hydraulic System B status message       | 60 units     | Normal        |

Values in this manual are invented and must not be used for any operational purpose. This text is fictional and exists only to give the prototype realistic volume and structure. The Cargo Smoke Detection advisory that differs from the expected state requires the Captain to brief the condition if a discrepancy is observed. This text is fictional and exists only to give the prototype realistic volume and structure.

#### 06.20.4 Cargo Smoke Detection Reset Guidance

The pilot flying will cross-check any change in the Hydraulic System A status message and advise the other pilot before the next phase of flight. The Autothrottle quantity display is expected to read within the sample range of 40 to 52 units during cruise. During a maintenance-requested ground run, the Captain should brief the Nosewheel Steering switch position once the checklist item is complete. The pilot flying will verify any change in the Stall Warning advisory and advise the other pilot if the indication does not stabilize within the sample interval. If the Fire Detection Loop is inoperative, continue a diversion only after the relief pilot has reviewed the associated sample guidance.

- If the Bleed Air Supply is inoperative, continue a turnaround only after the pilot monitoring has reviewed the associated sample guidance.
- During approach, the First Officer should brief the Primary Electrical Bus selector position when conditions permit.
- The pilot monitoring will confirm any change in the Center Tank Pumps status message and advise the other pilot when the associated caution light remains illuminated.
- The Standby Instruments indication that differs from the expected state requires the pilot flying to record the condition unless directed otherwise by the Sample Operations Center.
- The captain will cross-check any change in the Standby Instruments selector position and advise the other pilot unless directed otherwise by the Sample Operations Center.

**NOTE:** If the Nosewheel Steering is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance.

**NOTE:** If the Autopilot Channel B is inoperative, continue parking only after the relief pilot has reviewed the associated sample guidance. The relief pilot will monitor any change in the Probe Heat indication and advise the other pilot if the indication does not stabilize within the sample interval.

The first officer will select any change in the Window Heat switch position and advise the other pilot if a discrepancy is observed. During takeoff, the Captain should announce the Standby Instruments selector position when conditions permit. The Thrust Reverser advisory that differs from the expected state requires both pilots to record the condition before the next phase of flight. If the Oxygen Distribution is inoperative, continue a diversion only after the relief pilot has reviewed the associated sample guidance. During an extended ground delay, both pilots should monitor the Autobrake Selector selector position if the indication does not stabilize within the sample interval. The Cockpit Voice Recorder annunciation is expected to read within the sample range of 37 to 44 units during taxi.

- The wording here is placeholder content shaped like a procedure, not a procedure.
- Values in this manual are invented and must not be used for any operational purpose.
- The captain will select any change in the Brake Temperature Monitor advisory and advise the other pilot if a discrepancy is observed.
- During a maintenance-requested ground run, the Captain should confirm the Center Tank Pumps quantity display before the next phase of flight.
- If the Hydraulic System B is inoperative, continue parking only after the Captain has reviewed the associated sample guidance.
- During takeoff, both pilots should brief the Probe Heat switch position when conditions permit.
- The Nosewheel Steering quantity display is expected to read within the sample range of 51 to 61 units during an extended ground delay.
- The captain will record any change in the Speedbrake Handle selector position and advise the other pilot when operating at a sample station without ground power.
- The Stall Warning switch position is expected to read within the sample range of 21 to 30 units during descent.
- During parking, the relief pilot should verify the Autothrottle advisory when operating at a sample station without ground power.
- The Auxiliary Power Unit status message is expected to read within the sample range of 49 to 52 units during preflight.

The first officer will monitor any change in the Probe Heat selector position and advise the other pilot once the checklist item is complete. If the Fuel Crossfeed is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance. If the Primary Electrical Bus is inoperative, continue descent only after the pilot flying has reviewed the associated sample guidance.

If the Autobrake Selector is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance. The captain will verify any change in the Primary Electrical Bus switch position and advise the other pilot when conditions permit. The pilot flying will monitor any change in the Cockpit Voice Recorder quantity display and advise the other pilot once the checklist item is complete. If the Autothrottle is inoperative, continue parking only after the Captain has reviewed the associated sample guidance.

06.20.5 Thrust Reverser Overview

The Probe Heat indication is expected to read within the sample range of 31 to 37 units during parking. The wording here is placeholder content shaped like a procedure, not a procedure. Both pilots will brief any change in the Wing Anti-Ice annunciation and advise the other pilot when conditions permit. The Weather Radar advisory is expected to read within the sample range of 79 to 85 units during a diversion. If the Window Heat is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance.

**CAUTION:** The captain will cross-check any change in the Autopilot Channel A quantity display and advise the other pilot when operating at a sample station without ground power. If the Thrust Reverser is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance.

| Condition                            | Sample value | Remarks       |
|--------------------------------------|--------------|---------------|
| Brake Temperature Monitor advisory   | 93 units     | Monitor       |
| Probe Heat indication                | 91 units     | Monitor       |
| Fire Detection Loop quantity display | 86 units     | Advisory only |
| Standby Instruments switch position  | 93 units     | Advisory only |

**NOTE:** This text is fictional and exists only to give the prototype realistic volume and structure.

During takeoff, both pilots should verify the Cabin Pressure Controller quantity display if the indication does not stabilize within the sample interval. During an extended ground delay, both pilots should cross-check the Hydraulic System A selector position if a discrepancy is observed. The pilot flying will record any change in the Fuel Crossfeed selector position and advise the other pilot before the next phase of flight. The Center Tank Pumps switch position is expected to read within the sample range of 45 to 54 units during parking. Refer to the related topic for additional sample context.

The Auxiliary Power Unit selector position is expected to read within the sample range of 46 to 51 units during engine start. The Standby Instruments status message that differs from the expected state requires the relief pilot to verify the condition when conditions permit. This text is fictional and exists only to give the prototype realistic volume and structure. The Center Tank Pumps annunciation is expected to read within the sample range of 26 to 36 units during descent. During landing, the pilot monitoring should record the Center Tank Pumps switch position if the indication does not stabilize within the sample interval.

**06.20.6 Traffic Advisory Display Overview**

During climb, the First Officer should announce the Cargo Smoke Detection switch position before the next phase of flight. The pilot flying will monitor any change in the Speedbrake Handle advisory and advise the other pilot if a discrepancy is observed. If the Wing Anti-Ice is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance. The Primary Electrical Bus annunciation is expected to read within the sample range of 81 to 93 units during preflight. The Probe Heat quantity display that differs from the expected state requires the First Officer to verify the condition once the checklist item is complete. The Fire Detection Loop annunciation is expected to read within the sample range of 30 to 33 units during landing.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Autobrake Selector status message          | 20 units     | Advisory only          |
| Stall Warning quantity display             | 23 units     | Monitor                |
| Traffic Advisory Display selector position | 77 units     | Refer to related topic |

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Nosewheel Steering switch position         | 14 units     | Refer to related topic |
| Wing Anti-Ice annunciation                 | 10 units     | Normal                 |
| Weather Radar annunciation                 | 28 units     | Refer to related topic |
| Pack Temperature Control advisory          | 61 units     | Monitor                |
| Traffic Advisory Display selector position | 55 units     | Normal                 |
| Cockpit Voice Recorder indication          | 44 units     | Monitor                |
| Transponder advisory                       | 86 units     | Refer to related topic |

During taxi, the relief pilot should monitor the Hydraulic System A switch position when conditions permit. If the Flap Position Indication is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance. The Primary Electrical Bus indication is expected to read within the sample range of 76 to 84 units during a maintenance-requested ground run. The Pack Temperature Control quantity display that differs from the expected state requires both pilots to announce the condition once the checklist item is complete. The Engine Anti-Ice advisory is expected to read within the sample range of 66 to 75 units during landing.

The Autopilot Channel A status message is expected to read within the sample range of 8 to 13 units during engine start. The Wing Anti-Ice annunciation that differs from the expected state requires both pilots to monitor the condition if a discrepancy is observed. The captain will announce any change in the Cargo Smoke Detection status message and advise the other pilot when the associated caution light remains illuminated. Values in this manual are invented and must not be used for any operational purpose.

If the Autobrake Selector is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance. The Nosewheel Steering switch position that differs from the expected state requires the relief pilot to verify the condition if the indication does not stabilize within the sample interval. During descent, the Captain should cross-check the Flight Management Computer status message once the checklist item is complete. If the Flap Position Indication is inoperative, continue landing only after the pilot monitoring has reviewed the associated sample guidance. See 05.50.12 Oxygen Distribution Power Sources.

**NOTE:** During landing, both pilots should brief the Fire Detection Loop quantity display unless directed otherwise by the Sample Operations Center. The Auxiliary Power Unit annunciation is expected to read within the sample range of 66 to 72 units during a maintenance-requested ground run.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Center Tank Pumps indication             | 65 units     | Advisory only          |
| Transponder advisory                     | 67 units     | Advisory only          |
| Cargo Smoke Detection advisory           | 56 units     | Normal                 |
| Oxygen Distribution selector position    | 42 units     | Refer to related topic |
| Landing Gear Indication quantity display | 2 units      | Refer to related topic |
| Autobrake Selector annunciation          | 93 units     | Advisory only          |

06.20.7 Center Tank Pumps Overview

The Oxygen Distribution selector position is expected to read within the sample range of 98 to 109 units during approach. The Window Heat status message is expected to read within the sample range of 76 to 79 units during preflight. Refer to the related topic for additional sample context. During descent, both pilots should verify the Center Tank Pumps selector position when the associated caution light remains illuminated.

| Condition                                  | Sample value | Remarks       |
|--------------------------------------------|--------------|---------------|
| Cockpit Voice Recorder switch position     | 66 units     | Monitor       |
| Engine Anti-Ice indication                 | 63 units     | Monitor       |
| Pack Temperature Control selector position | 95 units     | Normal        |
| Window Heat advisory                       | 13 units     | Normal        |
| Standby Hydraulic indication               | 8 units      | Normal        |
| Fire Detection Loop indication             | 49 units     | Advisory only |

If the Transponder is inoperative, continue climb only after the First Officer has reviewed the associated sample guidance. The first officer will brief any change in the Brake Temperature Monitor switch position and advise the other pilot once the checklist item is complete. The pilot monitoring will confirm any change in the Autopilot Channel B selector position and advise the other pilot before the next phase of flight. The Speedbrake Handle indication that differs from the expected state requires the Captain to record the condition if the indication does not stabilize within the sample interval.

During taxi, both pilots should brief the Autothrottle annunciation before the next phase of flight. Refer to the related topic for additional sample context. The wording here is placeholder content shaped like a procedure, not a procedure. The relief pilot will confirm any change in the Standby Instruments annunciation and advise the other pilot when conditions permit.

**NOTE:** This text is fictional and exists only to give the prototype realistic volume and structure. The Traffic Advisory Display status message is expected to read within the sample range of 49 to 61 units during a turnaround.

The Hydraulic System B quantity display that differs from the expected state requires the First Officer to brief the condition when the associated caution light remains illuminated. The Weather Radar indication is expected to read

within the sample range of 59 to 65 units during a turnaround. The relief pilot will confirm any change in the Landing Gear Indication annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center. The Probe Heat status message is expected to read within the sample range of 92 to 95 units during a diversion. The Fire Detection Loop selector position that differs from the expected state requires the pilot flying to record the condition before the next phase of flight. The Fuel Crossfeed advisory that differs from the expected state requires both pilots to confirm the condition if the indication does not stabilize within the sample interval.

- If the Autopilot Channel A is inoperative, continue parking only after the Captain has reviewed the associated sample guidance.
- During takeoff, the Captain should verify the Oxygen Distribution selector position before the next phase of flight.
- The first officer will announce any change in the Oxygen Distribution indication and advise the other pilot once the checklist item is complete.

**06.20.8 Window Heat Overview**

The pilot monitoring will monitor any change in the Wing Anti-Ice advisory and advise the other pilot once the checklist item is complete. The Stall Warning selector position is expected to read within the sample range of 50 to 56 units during engine start. The Flight Management Computer advisory that differs from the expected state requires the pilot flying to cross-check the condition once the checklist item is complete. The Speedbrake Handle advisory that differs from the expected state requires the relief pilot to record the condition when the associated caution light remains illuminated. The first officer will cross-check any change in the Pack Temperature Control indication and advise the other pilot when the associated caution light remains illuminated.

The pilot monitoring will verify any change in the Hydraulic System B quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center. The captain will announce any change in the Center Tank Pumps switch position and advise the other pilot when the associated caution light remains illuminated. Both pilots will confirm any change in the Thrust Reverser switch position and advise the other pilot when conditions permit. The Traffic Advisory Display indication that differs from the expected state requires the relief pilot to record the condition if a discrepancy is observed. The Standby Hydraulic quantity display that differs from the expected state requires the pilot monitoring to monitor the condition if a discrepancy is observed.

During descent, the relief pilot should announce the Ground Proximity Monitor indication before the next phase of flight. During a diversion, the Captain should record the Flight Management Computer switch position once the checklist item is complete. The Fire Detection Loop annunciation that differs from the expected state requires the Captain to brief the condition when operating at a sample station without ground power. The wording here is placeholder content shaped like a procedure, not a procedure.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Flap Position Indication quantity display | 28 units     | Monitor                |
| Wing Anti-Ice status message              | 58 units     | Monitor                |
| Oxygen Distribution annunciation          | 58 units     | Advisory only          |
| Cockpit Voice Recorder quantity display   | 66 units     | Refer to related topic |
| Wing Anti-Ice advisory                    | 33 units     | Normal                 |
| Cabin Pressure Controller advisory        | 61 units     | Normal                 |
| Stall Warning selector position           | 26 units     | Monitor                |

If the Fire Detection Loop is inoperative, continue a maintenance-requested ground run only after both pilots has reviewed the associated sample guidance. The first officer will brief any change in the Stall Warning selector position and advise the other pilot when operating at a sample station without ground power. This text is fictional and exists only to give the prototype realistic volume and structure. During a turnaround, the pilot flying should verify the Center Tank Pumps selector position when the associated caution light remains illuminated. The first officer will select any change in the Primary Electrical Bus status message and advise the other pilot when conditions permit. If the Fire



Detection Loop is inoperative, continue a maintenance-requested ground run only after the pilot monitoring has reviewed the associated sample guidance.

The wording here is placeholder content shaped like a procedure, not a procedure. Refer to the related topic for additional sample context. The Cargo Smoke Detection annunciation that differs from the expected state requires the pilot monitoring to confirm the condition before the next phase of flight. During a diversion, the Captain should select the Primary Electrical Bus advisory once the checklist item is complete.

**NOTE:** If the Weather Radar is inoperative, continue descent only after the Captain has reviewed the associated sample guidance.

06.20.9 Stall Warning Overview

If the Wing Anti-Ice is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. The Fuel Crossfeed quantity display is expected to read within the sample range of 26 to 35 units during descent. The Hydraulic System B indication that differs from the expected state requires the relief pilot to confirm the condition when conditions permit. If the Speedbrake Handle is inoperative, continue engine start only after the pilot flying has reviewed the associated sample guidance. The first officer will verify any change in the Standby Instruments annunciation and advise the other pilot if the indication does not stabilize within the sample interval.

**NOTE:** The Primary Electrical Bus selector position that differs from the expected state requires the pilot flying to announce the condition unless directed otherwise by the Sample Operations Center. Refer to the related topic for additional sample context.

If the Window Heat is inoperative, continue climb only after both pilots has reviewed the associated sample guidance. The Speedbrake Handle selector position is expected to read within the sample range of 18 to 26 units during approach. The Flap Position Indication status message is expected to read within the sample range of 96 to 102 units during engine start. The captain will monitor any change in the Oxygen Distribution quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center.

During a maintenance-requested ground run, the pilot flying should brief the Cockpit Voice Recorder selector position unless directed otherwise by the Sample Operations Center. During landing, the pilot monitoring should monitor the Oxygen Distribution annunciation once the checklist item is complete. The Fuel Crossfeed switch position that differs from the expected state requires the First Officer to announce the condition when conditions permit. The Bleed Air Supply selector position that differs from the expected state requires the Captain to monitor the condition once the checklist item is complete. The relief pilot will monitor any change in the Ground Proximity Monitor quantity display and advise the other pilot once the checklist item is complete.

**NOTE:** If the Autopilot Channel A is inoperative, continue landing only after the relief pilot has reviewed the associated sample guidance. If the Primary Electrical Bus is inoperative, continue descent only after the First Officer has reviewed the associated sample guidance.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Standby Instruments selector position    | 38 units     | Advisory only          |
| Autobrake Selector status message        | 95 units     | Normal                 |
| Fuel Crossfeed advisory                  | 51 units     | Refer to related topic |
| Flap Position Indication switch position | 40 units     | Advisory only          |
| Auxiliary Power Unit selector position   | 65 units     | Normal                 |
| Engine Anti-Ice status message           | 19 units     | Refer to related topic |

06.20.10 Autothrottle Crew Awareness

The Ground Proximity Monitor advisory is expected to read within the sample range of 89 to 96 units during engine start. During cruise, the relief pilot should monitor the Autobrake Selector selector position before the next phase of flight. The Bleed Air Supply advisory is expected to read within the sample range of 72 to 79 units during engine start. The Window Heat selector position is expected to read within the sample range of 90 to 101 units during takeoff. If the Bleed Air Supply is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance. The Nosewheel Steering annunciation that differs from the expected state requires the pilot monitoring to record the condition when conditions permit.

**CAUTION:** The Hydraulic System B switch position is expected to read within the sample range of 6 to 15 units during a maintenance-requested ground run. If the Bleed Air Supply is inoperative, continue takeoff only after the First Officer has reviewed the associated sample guidance.

During climb, the First Officer should confirm the Fuel Crossfeed selector position once the checklist item is complete. The Autopilot Channel A quantity display is expected to read within the sample range of 22 to 34 units during a maintenance-requested ground run. Values in this manual are invented and must not be used for any operational purpose. During preflight, the relief pilot should verify the Fuel Crossfeed quantity display if a discrepancy is observed. During approach, the pilot flying should brief the Autopilot Channel A switch position before the next phase of flight. The first officer will select any change in the Window Heat advisory and advise the other pilot when operating at a sample station without ground power.

**CAUTION:** The Standby Hydraulic annunciation is expected to read within the sample range of 15 to 27 units during descent. The Stall Warning advisory that differs from the expected state requires the First Officer to verify the condition when conditions permit.

- The relief pilot will verify any change in the Fuel Crossfeed advisory and advise the other pilot if the indication does not stabilize within the sample interval.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The Standby Instruments switch position is expected to read within the sample range of 80 to 87 units during landing.
- The first officer will cross-check any change in the Autobrake Selector annunciation and advise the other pilot when operating at a sample station without ground power.
- During approach, the Captain should select the Oxygen Distribution annunciation when operating at a sample station without ground power.
- If the Standby Instruments is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance.

During takeoff, both pilots should monitor the Window Heat selector position when conditions permit. The captain will confirm any change in the Fire Detection Loop switch position and advise the other pilot once the checklist item is complete. The Auxiliary Power Unit quantity display that differs from the expected state requires the pilot monitoring to cross-check the condition when operating at a sample station without ground power.

**NOTE:** If the Autobrake Selector is inoperative, continue landing only after the pilot monitoring has reviewed the associated sample guidance.

The Autopilot Channel B quantity display is expected to read within the sample range of 71 to 77 units during preflight. During parking, the relief pilot should announce the Flight Management Computer switch position when the associated caution light remains illuminated. The Standby Instruments switch position that differs from the expected state requires the relief pilot to record the condition once the checklist item is complete.

### **06.20.11 Autothrottle Crew Awareness**

During taxi, the relief pilot should confirm the Bleed Air Supply quantity display when operating at a sample station without ground power. This text is fictional and exists only to give the prototype realistic volume and structure. If the Cargo Smoke Detection is inoperative, continue a diversion only after both pilots has reviewed the associated sample

guidance.

During climb, the pilot flying should verify the Autothrottle advisory when operating at a sample station without ground power. During taxi, both pilots should select the Bleed Air Supply switch position when the associated caution light remains illuminated. If the Ground Proximity Monitor is inoperative, continue parking only after the relief pilot has reviewed the associated sample guidance. The Stall Warning quantity display is expected to read within the sample range of 60 to 66 units during takeoff. During approach, the relief pilot should verify the Flap Position Indication advisory once the checklist item is complete. If the Oxygen Distribution is inoperative, continue a maintenance-requested ground run only after the pilot monitoring has reviewed the associated sample guidance.

**NOTE:** The Window Heat selector position that differs from the expected state requires the Captain to brief the condition when the associated caution light remains illuminated. If the Brake Temperature Monitor is inoperative, continue climb only after both pilots has reviewed the associated sample guidance.

During a diversion, the Captain should record the Wing Anti-Ice annunciation once the checklist item is complete. The wording here is placeholder content shaped like a procedure, not a procedure. During climb, the First Officer should confirm the Hydraulic System A status message before the next phase of flight. Refer to the related topic for additional sample context. The Standby Instruments indication is expected to read within the sample range of 33 to 39 units during landing.

**CAUTION:** The wording here is placeholder content shaped like a procedure, not a procedure. The pilot monitoring will verify any change in the Autopilot Channel B quantity display and advise the other pilot when operating at a sample station without ground power.

The Window Heat status message is expected to read within the sample range of 89 to 100 units during climb. If the Cockpit Voice Recorder is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance. If the Ground Proximity Monitor is inoperative, continue approach only after the First Officer has reviewed the associated sample guidance. If the Cabin Pressure Controller is inoperative, continue descent only after the First Officer has reviewed the associated sample guidance. During preflight, the First Officer should record the Ground Proximity Monitor advisory once the checklist item is complete. Values in this manual are invented and must not be used for any operational purpose.

**NOTE:** During a maintenance-requested ground run, the Captain should select the Stall Warning indication if a discrepancy is observed. The wording here is placeholder content shaped like a procedure, not a procedure.

**06.20.12 Landing Gear Indication Reset Guidance**

This text is fictional and exists only to give the prototype realistic volume and structure. If the Autothrottle is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance. The Thrust Reverser annunciation is expected to read within the sample range of 79 to 87 units during descent. The Fuel Crossfeed advisory is expected to read within the sample range of 80 to 83 units during an extended ground delay.

If the Center Tank Pumps is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance. The Cabin Pressure Controller status message that differs from the expected state requires the pilot flying to announce the condition when operating at a sample station without ground power. The Ground Proximity Monitor advisory that differs from the expected state requires the First Officer to brief the condition unless directed otherwise by the Sample Operations Center. The Fuel Crossfeed annunciation is expected to read within the sample range of 75 to 78 units during taxi. The first officer will record any change in the Autobrake Selector switch position and advise the other pilot before the next phase of flight. If the Autopilot Channel B is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Ground Proximity Monitor advisory     | 52 units     | Monitor                |
| Autopilot Channel B selector position | 17 units     | Normal                 |
| Probe Heat status message             | 80 units     | Refer to related topic |

|                       |          |               |
|-----------------------|----------|---------------|
| Autothrottle advisory | 91 units | Advisory only |
|-----------------------|----------|---------------|

**CAUTION:** The Cabin Pressure Controller selector position that differs from the expected state requires the Captain to cross-check the condition when the associated caution light remains illuminated. The Brake Temperature Monitor annunciation that differs from the expected state requires the First Officer to brief the condition when conditions permit.

| Condition                              | Sample value | Remarks       |
|----------------------------------------|--------------|---------------|
| Hydraulic System A selector position   | 69 units     | Monitor       |
| Transponder advisory                   | 4 units      | Advisory only |
| Cargo Smoke Detection quantity display | 5 units      | Advisory only |
| Hydraulic System A indication          | 16 units     | Monitor       |
| Autopilot Channel A indication         | 51 units     | Normal        |

Refer to the related topic for additional sample context. If the Ground Proximity Monitor is inoperative, continue cruise only after both pilots has reviewed the associated sample guidance. During climb, the First Officer should verify the Fire Detection Loop selector position when the associated caution light remains illuminated. During cruise, the Captain should verify the Autobrake Selector selector position if the indication does not stabilize within the sample interval. This text is fictional and exists only to give the prototype realistic volume and structure.

- If the Primary Electrical Bus is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance.
- If the Engine Anti-Ice is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance.
- The Bleed Air Supply switch position that differs from the expected state requires both pilots to cross-check the condition if a discrepancy is observed.

If the Autopilot Channel A is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance. The Flight Management Computer indication that differs from the expected state requires the pilot monitoring to brief the condition if a discrepancy is observed. The pilot monitoring will monitor any change in the Engine Anti-Ice indication and advise the other pilot unless directed otherwise by the Sample Operations Center. The Cabin Pressure Controller selector position that differs from the expected state requires the Captain to cross-check the condition when the associated caution light remains illuminated.

- The Flap Position Indication quantity display that differs from the expected state requires the pilot flying to record the condition if the indication does not stabilize within the sample interval.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- The Autothrottle selector position is expected to read within the sample range of 26 to 30 units during landing.
- Values in this manual are invented and must not be used for any operational purpose.
- The captain will brief any change in the Speedbrake Handle quantity display and advise the other pilot if a discrepancy is observed.

**06.20.13 Flap Position Indication Crew Awareness**

The Nosewheel Steering annunciation that differs from the expected state requires the pilot flying to record the condition unless directed otherwise by the Sample Operations Center. The wording here is placeholder content shaped like a procedure, not a procedure. The Pack Temperature Control indication that differs from the expected state requires both pilots to record the condition before the next phase of flight. The Flight Management Computer quantity display that differs from the expected state requires the Captain to confirm the condition if a discrepancy is observed. Refer to the related topic for additional sample context. If the Oxygen Distribution is inoperative, continue

descent only after the pilot monitoring has reviewed the associated sample guidance.

If the Primary Electrical Bus is inoperative, continue climb only after the First Officer has reviewed the associated sample guidance. During takeoff, both pilots should record the Speedbrake Handle advisory when operating at a sample station without ground power. The Fire Detection Loop selector position that differs from the expected state requires the pilot monitoring to verify the condition when operating at a sample station without ground power. The wording here is placeholder content shaped like a procedure, not a procedure. If the Fuel Crossfeed is inoperative, continue landing only after the relief pilot has reviewed the associated sample guidance.

If the Fire Detection Loop is inoperative, continue descent only after the First Officer has reviewed the associated sample guidance. Refer to the related topic for additional sample context. If the Hydraulic System B is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance. During approach, both pilots should cross-check the Auxiliary Power Unit annunciation unless directed otherwise by the Sample Operations Center.

This text is fictional and exists only to give the prototype realistic volume and structure. The Brake Temperature Monitor indication is expected to read within the sample range of 8 to 17 units during a turnaround. During an extended ground delay, the relief pilot should select the Traffic Advisory Display status message unless directed otherwise by the Sample Operations Center. The Standby Instruments status message is expected to read within the sample range of 54 to 59 units during taxi.

| Condition                         | Sample value | Remarks       |
|-----------------------------------|--------------|---------------|
| Standby Hydraulic advisory        | 28 units     | Monitor       |
| Wing Anti-Ice advisory            | 54 units     | Advisory only |
| Hydraulic System B status message | 84 units     | Advisory only |
| Probe Heat selector position      | 52 units     | Monitor       |

If the Probe Heat is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance. Refer to the related topic for additional sample context. The Wing Anti-Ice indication is expected to read within the sample range of 89 to 101 units during parking. If the Standby Instruments is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance.

| Condition                              | Sample value | Remarks       |
|----------------------------------------|--------------|---------------|
| Autobrake Selector annunciation        | 76 units     | Normal        |
| Transponder annunciation               | 51 units     | Advisory only |
| Nosewheel Steering status message      | 19 units     | Normal        |
| Standby Hydraulic indication           | 49 units     | Monitor       |
| Landing Gear Indication status message | 68 units     | Advisory only |
| Stall Warning annunciation             | 50 units     | Normal        |
| Oxygen Distribution annunciation       | 16 units     | Normal        |

06.20.14 Weather Radar Status Messages

The Flap Position Indication advisory that differs from the expected state requires both pilots to select the condition when operating at a sample station without ground power. Values in this manual are invented and must not be used for any operational purpose. If the Hydraulic System B is inoperative, continue parking only after both pilots has reviewed the associated sample guidance. If the Weather Radar is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance.

- The Oxygen Distribution annunciation is expected to read within the sample range of 86 to 93 units during parking.
- If the Wing Anti-Ice is inoperative, continue parking only after both pilots has reviewed the associated sample guidance.

- Values in this manual are invented and must not be used for any operational purpose.
- If the Flight Management Computer is inoperative, continue cruise only after the First Officer has reviewed the associated sample guidance.

**CAUTION:** If the Standby Instruments is inoperative, continue climb only after both pilots has reviewed the associated sample guidance.

**CAUTION:** This text is fictional and exists only to give the prototype realistic volume and structure.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Hydraulic System B quantity display        | 44 units     | Monitor                |
| Speedbrake Handle annunciation             | 48 units     | Refer to related topic |
| Flap Position Indication selector position | 29 units     | Refer to related topic |
| Thrust Reverser annunciation               | 67 units     | Normal                 |
| Auxiliary Power Unit quantity display      | 24 units     | Refer to related topic |
| Window Heat switch position                | 82 units     | Refer to related topic |
| Thrust Reverser selector position          | 7 units      | Refer to related topic |

The Fuel Crossfeed indication that differs from the expected state requires the Captain to brief the condition if the indication does not stabilize within the sample interval. The captain will confirm any change in the Engine Anti-Ice annunciation and advise the other pilot when conditions permit. During a turnaround, the Captain should monitor the Brake Temperature Monitor annunciation once the checklist item is complete. The Fuel Crossfeed selector position is expected to read within the sample range of 34 to 42 units during parking. Refer to the related topic for additional sample context.

During preflight, both pilots should select the Standby Hydraulic annunciation if the indication does not stabilize within the sample interval. Values in this manual are invented and must not be used for any operational purpose. The pilot monitoring will confirm any change in the Window Heat quantity display and advise the other pilot when operating at a sample station without ground power. Refer to the related topic for additional sample context. See 14.10.4 Stall Warning Crew Awareness.

| Condition                                 | Sample value | Remarks       |
|-------------------------------------------|--------------|---------------|
| Weather Radar indication                  | 62 units     | Advisory only |
| Autopilot Channel B status message        | 82 units     | Normal        |
| Flap Position Indication quantity display | 28 units     | Monitor       |

06.20.15 Stall Warning Overview

The Traffic Advisory Display selector position that differs from the expected state requires the relief pilot to cross-check the condition when conditions permit. During a maintenance-requested ground run, the pilot flying should cross-check the Transponder advisory when the associated caution light remains illuminated. During parking, the pilot flying should cross-check the Thrust Reverser selector position if the indication does not stabilize within the sample interval. During cruise, the relief pilot should brief the Ground Proximity Monitor status message when the associated caution light remains illuminated.

The relief pilot will announce any change in the Center Tank Pumps annunciation and advise the other pilot before the next phase of flight. Values in this manual are invented and must not be used for any operational purpose. During cruise, the pilot flying should select the Landing Gear Indication quantity display if a discrepancy is observed.

- The Ground Proximity Monitor quantity display that differs from the expected state requires the relief pilot to record the condition before the next phase of flight.



- During a diversion, the pilot flying should brief the Cabin Pressure Controller selector position if the indication does not stabilize within the sample interval.
- The first officer will brief any change in the Bleed Air Supply quantity display and advise the other pilot if a discrepancy is observed.
- The Wing Anti-Ice annunciation that differs from the expected state requires the Captain to record the condition when conditions permit.
- The relief pilot will announce any change in the Autobrake Selector annunciation and advise the other pilot if a discrepancy is observed.
- If the Transponder is inoperative, continue takeoff only after the First Officer has reviewed the associated sample guidance.

**NOTE:** If the Nosewheel Steering is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose.

**CAUTION:** During approach, the pilot flying should brief the Hydraulic System B switch position if a discrepancy is observed. The Pack Temperature Control selector position is expected to read within the sample range of 73 to 77 units during a turnaround.

The Hydraulic System B status message that differs from the expected state requires both pilots to cross-check the condition before the next phase of flight. During taxi, the First Officer should announce the Cargo Smoke Detection selector position when the associated caution light remains illuminated. If the Engine Anti-Ice is inoperative, continue preflight only after both pilots has reviewed the associated sample guidance. During preflight, the pilot monitoring should confirm the Fuel Crossfeed indication if a discrepancy is observed.

### 06.20.16 *Bleed Air Supply Reset Guidance*

The Thrust Reverser status message that differs from the expected state requires the First Officer to monitor the condition before the next phase of flight. During descent, the relief pilot should verify the Autopilot Channel B indication when conditions permit. If the Speedbrake Handle is inoperative, continue a maintenance-requested ground run only after both pilots has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. If the Pack Temperature Control is inoperative, continue descent only after the Captain has reviewed the associated sample guidance.

The Speedbrake Handle selector position that differs from the expected state requires the First Officer to brief the condition when operating at a sample station without ground power. The Landing Gear Indication advisory is expected to read within the sample range of 80 to 85 units during engine start. During landing, the relief pilot should monitor the Thrust Reverser status message once the checklist item is complete.

**CAUTION:** If the Standby Hydraulic is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance.

Refer to the related topic for additional sample context. The pilot monitoring will confirm any change in the Cockpit Voice Recorder switch position and advise the other pilot once the checklist item is complete. The wording here is placeholder content shaped like a procedure, not a procedure. This text is fictional and exists only to give the prototype realistic volume and structure. The Cockpit Voice Recorder selector position that differs from the expected state requires the relief pilot to record the condition if the indication does not stabilize within the sample interval. This text is fictional and exists only to give the prototype realistic volume and structure. See 05.10.4 Center Tank Pumps Limits Display.

**NOTE:** The first officer will announce any change in the Speedbrake Handle advisory and advise the other pilot before the next phase of flight. The Ground Proximity Monitor switch position that differs from the expected state requires the relief pilot to select the condition if the indication does not stabilize within the sample interval.

## 06.30 Operation

### 06.30.1 Autothrottle Test

The Probe Heat status message is expected to read within the sample range of 68 to 72 units during takeoff. The Stall Warning annunciation is expected to read within the sample range of 30 to 38 units during descent. The wording here is placeholder content shaped like a procedure, not a procedure. The Speedbrake Handle selector position is expected to read within the sample range of 54 to 57 units during a turnaround. If the Hydraulic System A is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance.

If the Hydraulic System B is inoperative, continue descent only after both pilots has reviewed the associated sample guidance. The Stall Warning quantity display is expected to read within the sample range of 13 to 20 units during a turnaround. Values in this manual are invented and must not be used for any operational purpose. During approach, the relief pilot should record the Fire Detection Loop advisory if a discrepancy is observed. The Bleed Air Supply quantity display that differs from the expected state requires both pilots to cross-check the condition when operating at a sample station without ground power. The wording here is placeholder content shaped like a procedure, not a procedure.

**NOTE:** The Bleed Air Supply status message is expected to read within the sample range of 45 to 48 units during a maintenance-requested ground run. Both pilots will announce any change in the Stall Warning selector position and advise the other pilot when conditions permit.

- The wording here is placeholder content shaped like a procedure, not a procedure.
- The pilot flying will confirm any change in the Engine Anti-Ice indication and advise the other pilot unless directed otherwise by the Sample Operations Center.
- If the Brake Temperature Monitor is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance.
- The Standby Instruments switch position is expected to read within the sample range of 14 to 26 units during taxi.

**NOTE:** The pilot flying will monitor any change in the Brake Temperature Monitor indication and advise the other pilot when operating at a sample station without ground power. Values in this manual are invented and must not be used for any operational purpose.

The Autobrake Selector annunciation that differs from the expected state requires the pilot flying to monitor the condition if a discrepancy is observed. The Landing Gear Indication quantity display that differs from the expected state requires the pilot flying to announce the condition unless directed otherwise by the Sample Operations Center. The relief pilot will announce any change in the Weather Radar annunciation and advise the other pilot if a discrepancy is observed. During cruise, the First Officer should announce the Bleed Air Supply indication before the next phase of flight.

- The Autothrottle selector position is expected to read within the sample range of 28 to 38 units during cruise.
- During approach, the relief pilot should select the Nosewheel Steering quantity display if the indication does not stabilize within the sample interval.
- During approach, the pilot monitoring should cross-check the Weather Radar indication if a discrepancy is observed.

**NOTE:** Refer to the related topic for additional sample context.

### 06.30.2 Flight Management Computer Reset Guidance

During a maintenance-requested ground run, both pilots should brief the Center Tank Pumps status message once the checklist item is complete. During parking, the Captain should brief the Autobrake Selector advisory before the next phase of flight. The Bleed Air Supply selector position that differs from the expected state requires the pilot flying

to monitor the condition when the associated caution light remains illuminated. The Ground Proximity Monitor quantity display is expected to read within the sample range of 94 to 105 units during approach. The wording here is placeholder content shaped like a procedure, not a procedure. During approach, the Captain should announce the Probe Heat selector position when conditions permit.

- The wording here is placeholder content shaped like a procedure, not a procedure.
- During approach, the pilot monitoring should verify the Hydraulic System B advisory unless directed otherwise by the Sample Operations Center.
- The pilot monitoring will brief any change in the Weather Radar advisory and advise the other pilot before the next phase of flight.

**NOTE:** If the Primary Electrical Bus is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance. If the Weather Radar is inoperative, continue preflight only after the pilot monitoring has reviewed the associated sample guidance.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Flight Management Computer switch position | 57 units     | Normal                 |
| Primary Electrical Bus selector position   | 13 units     | Monitor                |
| Stall Warning advisory                     | 24 units     | Normal                 |
| Pack Temperature Control advisory          | 84 units     | Refer to related topic |
| Cockpit Voice Recorder selector position   | 55 units     | Monitor                |
| Pack Temperature Control switch position   | 10 units     | Refer to related topic |
| Transponder annunciation                   | 42 units     | Monitor                |

- Both pilots will brief any change in the Pack Temperature Control selector position and advise the other pilot if the indication does not stabilize within the sample interval.
- The Speedbrake Handle advisory that differs from the expected state requires the pilot flying to brief the condition once the checklist item is complete.
- The relief pilot will announce any change in the Bleed Air Supply quantity display and advise the other pilot when conditions permit.
- The Hydraulic System A annunciation is expected to read within the sample range of 45 to 50 units during taxi.
- The pilot flying will verify any change in the Standby Instruments quantity display and advise the other pilot before the next phase of flight.
- During approach, the relief pilot should monitor the Autopilot Channel B indication once the checklist item is complete.

**06.30.3 Fire Detection Loop Test**

The pilot monitoring will brief any change in the Autopilot Channel A annunciation and advise the other pilot if the indication does not stabilize within the sample interval. Refer to the related topic for additional sample context. If the Standby Instruments is inoperative, continue preflight only after both pilots has reviewed the associated sample guidance. The Speedbrake Handle indication is expected to read within the sample range of 19 to 29 units during a turnaround. Both pilots will brief any change in the Brake Temperature Monitor annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center.

If the Flight Management Computer is inoperative, continue a diversion only after both pilots has reviewed the associated sample guidance. The Wing Anti-Ice indication is expected to read within the sample range of 42 to 53 units during taxi. If the Autopilot Channel B is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance. If the Standby Hydraulic is inoperative, continue engine

start only after the relief pilot has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose.

If the Hydraulic System A is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance. The pilot monitoring will record any change in the Primary Electrical Bus annunciation and advise the other pilot if a discrepancy is observed. The Engine Anti-Ice advisory is expected to read within the sample range of 85 to 90 units during a maintenance-requested ground run. The pilot flying will brief any change in the Flap Position Indication selector position and advise the other pilot when conditions permit. During preflight, the pilot flying should brief the Window Heat annunciation when the associated caution light remains illuminated.

The Oxygen Distribution advisory is expected to read within the sample range of 85 to 95 units during approach. If the Bleed Air Supply is inoperative, continue a diversion only after the First Officer has reviewed the associated sample guidance. The Probe Heat selector position that differs from the expected state requires the relief pilot to record the condition when operating at a sample station without ground power. The pilot flying will verify any change in the Standby Instruments quantity display and advise the other pilot when conditions permit. During a turnaround, the pilot monitoring should monitor the Stall Warning advisory once the checklist item is complete. During climb, the pilot monitoring should brief the Autothrottle annunciation before the next phase of flight.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Oxygen Distribution selector position | 66 units     | Refer to related topic |
| Probe Heat annunciation               | 37 units     | Refer to related topic |
| Thrust Reverser indication            | 3 units      | Advisory only          |

- Both pilots will select any change in the Wing Anti-Ice selector position and advise the other pilot when the associated caution light remains illuminated.
- The Autobrake Selector annunciation that differs from the expected state requires the pilot flying to select the condition once the checklist item is complete.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The first officer will brief any change in the Primary Electrical Bus indication and advise the other pilot before the next phase of flight.
- The Wing Anti-Ice annunciation that differs from the expected state requires the Captain to verify the condition once the checklist item is complete.
- The pilot monitoring will announce any change in the Nosewheel Steering quantity display and advise the other pilot before the next phase of flight.

If the Autopilot Channel B is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance. The Fire Detection Loop status message is expected to read within the sample range of 66 to 75 units during a maintenance-requested ground run. The Weather Radar status message that differs from the expected state requires the Captain to cross-check the condition once the checklist item is complete. The Brake Temperature Monitor annunciation is expected to read within the sample range of 8 to 13 units during climb. The relief pilot will confirm any change in the Speedbrake Handle status message and advise the other pilot before the next phase of flight.

If the Autopilot Channel B is inoperative, continue a maintenance-requested ground run only after the Captain has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. The Probe Heat annunciation that differs from the expected state requires the First Officer to record the condition once the checklist item is complete. Refer to the related topic for additional sample context. If the Probe Heat is inoperative, continue taxi only after both pilots has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose.

The pilot flying will verify any change in the Ground Proximity Monitor quantity display and advise the other pilot if the indication does not stabilize within the sample interval. Refer to the related topic for additional sample context. The

Hydraulic System A switch position that differs from the expected state requires the Captain to verify the condition when conditions permit. During a turnaround, the pilot flying should monitor the Standby Instruments advisory if a discrepancy is observed. The Stall Warning quantity display that differs from the expected state requires the First Officer to brief the condition when the associated caution light remains illuminated. The Transponder advisory is expected to read within the sample range of 65 to 72 units during taxi.

**06.30.4 Autopilot Channel A Overview**

The pilot monitoring will verify any change in the Speedbrake Handle switch position and advise the other pilot when operating at a sample station without ground power. If the Primary Electrical Bus is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose.

- The Fire Detection Loop status message that differs from the expected state requires the pilot monitoring to announce the condition unless directed otherwise by the Sample Operations Center.
- During parking, the pilot monitoring should brief the Stall Warning selector position if a discrepancy is observed.
- The Thrust Reverser quantity display is expected to read within the sample range of 59 to 66 units during landing.

| Condition                              | Sample value | Remarks                |
|----------------------------------------|--------------|------------------------|
| Nosewheel Steering quantity display    | 19 units     | Monitor                |
| Auxiliary Power Unit annunciation      | 6 units      | Monitor                |
| Stall Warning indication               | 47 units     | Advisory only          |
| Cockpit Voice Recorder switch position | 81 units     | Monitor                |
| Fire Detection Loop selector position  | 28 units     | Monitor                |
| Bleed Air Supply switch position       | 65 units     | Refer to related topic |
| Hydraulic System A annunciation        | 32 units     | Advisory only          |

- The Fire Detection Loop annunciation is expected to read within the sample range of 80 to 92 units during takeoff.
- The Nosewheel Steering switch position is expected to read within the sample range of 32 to 44 units during a turnaround.
- If the Hydraulic System A is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance.
- The Hydraulic System A switch position is expected to read within the sample range of 18 to 21 units during descent.
- The Flight Management Computer annunciation that differs from the expected state requires the Captain to brief the condition when conditions permit.
- During cruise, the relief pilot should brief the Auxiliary Power Unit annunciation when operating at a sample station without ground power.
- During taxi, the First Officer should monitor the Autobrake Selector quantity display if a discrepancy is observed.
- During preflight, the pilot monitoring should cross-check the Bleed Air Supply advisory when conditions permit.
- Refer to the related topic for additional sample context.
- The Flap Position Indication quantity display that differs from the expected state requires the Captain to brief the condition when the associated caution light remains illuminated.
- The Fire Detection Loop annunciation that differs from the expected state requires the pilot flying to brief the condition unless directed otherwise by the Sample Operations Center.

- The first officer will monitor any change in the Flight Management Computer selector position and advise the other pilot before the next phase of flight.
- If the Nosewheel Steering is inoperative, continue taxi only after the Captain has reviewed the associated sample guidance.

If the Autopilot Channel A is inoperative, continue climb only after the pilot flying has reviewed the associated sample guidance. The Window Heat annunciation is expected to read within the sample range of 42 to 47 units during takeoff. The Nosewheel Steering switch position is expected to read within the sample range of 63 to 73 units during preflight. If the Bleed Air Supply is inoperative, continue parking only after both pilots has reviewed the associated sample guidance. The Cargo Smoke Detection indication is expected to read within the sample range of 18 to 26 units during approach. The Landing Gear Indication switch position that differs from the expected state requires the First Officer to monitor the condition when operating at a sample station without ground power.

**06.30.5 Pack Temperature Control Status Messages**

During an extended ground delay, the relief pilot should announce the Oxygen Distribution status message when operating at a sample station without ground power. The Transponder quantity display is expected to read within the sample range of 28 to 34 units during climb. The Engine Anti-Ice annunciation is expected to read within the sample range of 43 to 48 units during taxi. The Standby Hydraulic advisory is expected to read within the sample range of 81 to 84 units during landing.

**CAUTION:** During preflight, the relief pilot should record the Brake Temperature Monitor indication when the associated caution light remains illuminated.

**CAUTION:** If the Autobrake Selector is inoperative, continue engine start only after the pilot monitoring has reviewed the associated sample guidance.

During climb, both pilots should brief the Bleed Air Supply selector position when the associated caution light remains illuminated. The wording here is placeholder content shaped like a procedure, not a procedure. If the Autopilot Channel B is inoperative, continue descent only after the Captain has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. If the Standby Instruments is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance.

Values in this manual are invented and must not be used for any operational purpose. During parking, the pilot monitoring should record the Oxygen Distribution selector position unless directed otherwise by the Sample Operations Center. The wording here is placeholder content shaped like a procedure, not a procedure.

| Condition                            | Sample value | Remarks                |
|--------------------------------------|--------------|------------------------|
| Primary Electrical Bus annunciation  | 43 units     | Refer to related topic |
| Wing Anti-Ice selector position      | 85 units     | Monitor                |
| Autopilot Channel A quantity display | 46 units     | Refer to related topic |
| Thrust Reverser advisory             | 96 units     | Refer to related topic |
| Stall Warning quantity display       | 9 units      | Advisory only          |

Both pilots will verify any change in the Cargo Smoke Detection advisory and advise the other pilot when operating at a sample station without ground power. During cruise, the pilot flying should record the Wing Anti-Ice switch position before the next phase of flight. During approach, the Captain should record the Fuel Crossfeed annunciation when the associated caution light remains illuminated. If the Autothrottle is inoperative, continue descent only after both pilots has reviewed the associated sample guidance.

The Hydraulic System A status message is expected to read within the sample range of 30 to 38 units during a turnaround. The wording here is placeholder content shaped like a procedure, not a procedure. The Oxygen Distribution switch position is expected to read within the sample range of 9 to 18 units during engine start. The Center Tank Pumps status message that differs from the expected state requires the First Officer to select the



condition unless directed otherwise by the Sample Operations Center. See 04.20.19 Verification: Primary Electrical Bus.

**06.30.6 Hydraulic System A Power Sources**

If the Autopilot Channel B is inoperative, continue engine start only after both pilots has reviewed the associated sample guidance. If the Bleed Air Supply is inoperative, continue approach only after the First Officer has reviewed the associated sample guidance. The Flap Position Indication indication that differs from the expected state requires both pilots to confirm the condition if the indication does not stabilize within the sample interval. If the Flap Position Indication is inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance.

**NOTE:** The Flight Management Computer switch position is expected to read within the sample range of 19 to 26 units during a diversion. The Fuel Crossfeed quantity display that differs from the expected state requires the pilot monitoring to verify the condition before the next phase of flight.

| Condition                               | Sample value | Remarks       |
|-----------------------------------------|--------------|---------------|
| Standby Instruments switch position     | 55 units     | Monitor       |
| Flap Position Indication status message | 21 units     | Monitor       |
| Weather Radar switch position           | 14 units     | Advisory only |
| Probe Heat switch position              | 46 units     | Advisory only |
| Flight Management Computer advisory     | 2 units      | Monitor       |
| Speedbrake Handle status message        | 95 units     | Normal        |
| Pack Temperature Control annunciation   | 83 units     | Monitor       |

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Autothrottle advisory                     | 15 units     | Refer to related topic |
| Autopilot Channel A quantity display      | 65 units     | Normal                 |
| Flight Management Computer status message | 73 units     | Normal                 |
| Cabin Pressure Controller annunciation    | 26 units     | Monitor                |
| Standby Instruments indication            | 87 units     | Refer to related topic |
| Autopilot Channel A switch position       | 74 units     | Advisory only          |
| Fuel Crossfeed status message             | 14 units     | Advisory only          |

**NOTE:** The first officer will cross-check any change in the Wing Anti-Ice annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center.

During approach, the Captain should verify the Speedbrake Handle annunciation when conditions permit. Values in this manual are invented and must not be used for any operational purpose. The Window Heat annunciation that differs from the expected state requires the Captain to brief the condition once the checklist item is complete.

**NOTE:** If the Fire Detection Loop is inoperative, continue cruise only after the First Officer has reviewed the associated sample guidance.

During a turnaround, both pilots should cross-check the Hydraulic System B quantity display if a discrepancy is observed. During climb, the First Officer should brief the Flight Management Computer advisory when the associated caution light remains illuminated. The Cockpit Voice Recorder indication that differs from the expected state requires the relief pilot to announce the condition when the associated caution light remains illuminated. The pilot monitoring will verify any change in the Center Tank Pumps indication and advise the other pilot when operating at a sample station without ground power.

The Cockpit Voice Recorder quantity display that differs from the expected state requires the pilot flying to monitor the condition unless directed otherwise by the Sample Operations Center. If the Standby Hydraulic is inoperative, continue an extended ground delay only after the pilot flying has reviewed the associated sample guidance. If the Brake Temperature Monitor is inoperative, continue engine start only after the Captain has reviewed the associated sample guidance. The first officer will verify any change in the Stall Warning selector position and advise the other pilot unless directed otherwise by the Sample Operations Center. If the Landing Gear Indication is inoperative, continue preflight only after both pilots has reviewed the associated sample guidance. The Cargo Smoke Detection status message is expected to read within the sample range of 78 to 88 units during an extended ground delay.

**06.30.7 Fuel Crossfeed Interfaces**

If the Transponder is inoperative, continue preflight only after the pilot monitoring has reviewed the associated sample guidance. Refer to the related topic for additional sample context. The captain will verify any change in the Thrust Reverser quantity display and advise the other pilot before the next phase of flight.

If the Autothrottle is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance. The Auxiliary Power Unit annunciation that differs from the expected state requires the First Officer to brief the condition when conditions permit. If the Autobrake Selector is inoperative, continue approach only after the pilot flying has reviewed the associated sample guidance. The Autobrake Selector advisory is expected to read within the sample range of 29 to 35 units during taxi. The Transponder indication is expected to read within the sample range of 6 to 9 units during an extended ground delay.

- The Nosewheel Steering annunciation that differs from the expected state requires the pilot flying to record the condition if a discrepancy is observed.
- The Hydraulic System A status message that differs from the expected state requires the relief pilot to record the condition if the indication does not stabilize within the sample interval.
- During climb, the First Officer should select the Oxygen Distribution selector position before the next phase of flight.

| Condition                                   | Sample value | Remarks                |
|---------------------------------------------|--------------|------------------------|
| Traffic Advisory Display switch position    | 6 units      | Advisory only          |
| Hydraulic System A annunciation             | 13 units     | Normal                 |
| Fire Detection Loop indication              | 3 units      | Advisory only          |
| Auxiliary Power Unit indication             | 38 units     | Normal                 |
| Window Heat indication                      | 15 units     | Advisory only          |
| Flap Position Indication selector position  | 51 units     | Advisory only          |
| Cabin Pressure Controller selector position | 34 units     | Refer to related topic |

The Weather Radar selector position that differs from the expected state requires the First Officer to monitor the condition unless directed otherwise by the Sample Operations Center. The Auxiliary Power Unit annunciation is expected to read within the sample range of 20 to 24 units during approach. If the Center Tank Pumps is inoperative, continue takeoff only after the First Officer has reviewed the associated sample guidance. During parking, the First Officer should cross-check the Cockpit Voice Recorder status message once the checklist item is complete. This text is fictional and exists only to give the prototype realistic volume and structure.

The wording here is placeholder content shaped like a procedure, not a procedure. The Autobrake Selector indication is expected to read within the sample range of 33 to 44 units during preflight. If the Nosewheel Steering is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. The Window Heat annunciation that differs from the expected state requires the pilot monitoring to select the condition when the associated caution light remains illuminated. The Bleed Air Supply selector position that differs from the expected state requires both pilots to monitor the condition when operating at a sample station without ground power.

The relief pilot will verify any change in the Auxiliary Power Unit selector position and advise the other pilot if a discrepancy is observed. The Pack Temperature Control quantity display that differs from the expected state requires both pilots to monitor the condition when the associated caution light remains illuminated. If the Speedbrake Handle is inoperative, continue taxi only after the relief pilot has reviewed the associated sample guidance. If the Autobrake Selector is inoperative, continue descent only after the pilot flying has reviewed the associated sample guidance. The Thrust Reverser quantity display is expected to read within the sample range of 24 to 27 units during parking. The wording here is placeholder content shaped like a procedure, not a procedure.

**NOTE:** The wording here is placeholder content shaped like a procedure, not a procedure.

**06.30.8 Nosewheel Steering Reset Guidance**

The wording here is placeholder content shaped like a procedure, not a procedure. The first officer will brief any change in the Nosewheel Steering status message and advise the other pilot when the associated caution light remains illuminated. Both pilots will select any change in the Weather Radar selector position and advise the other pilot when the associated caution light remains illuminated. The first officer will brief any change in the Landing Gear Indication annunciation and advise the other pilot if a discrepancy is observed. This text is fictional and exists only to give the prototype realistic volume and structure.

Values in this manual are invented and must not be used for any operational purpose. The Window Heat indication is expected to read within the sample range of 11 to 19 units during preflight. The Ground Proximity Monitor annunciation that differs from the expected state requires the Captain to select the condition if the indication does not stabilize within the sample interval. The Cargo Smoke Detection annunciation that differs from the expected state requires the First Officer to monitor the condition when the associated caution light remains illuminated.

**NOTE:** If the Autopilot Channel A is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance. The first officer will verify any change in the Cargo Smoke Detection status message and advise the other pilot if the indication does not stabilize within the sample interval.

| Condition                                | Sample value | Remarks       |
|------------------------------------------|--------------|---------------|
| Cabin Pressure Controller advisory       | 76 units     | Advisory only |
| Weather Radar quantity display           | 28 units     | Advisory only |
| Autopilot Channel B status message       | 27 units     | Advisory only |
| Cockpit Voice Recorder selector position | 82 units     | Advisory only |
| Fire Detection Loop switch position      | 13 units     | Advisory only |

The first officer will brief any change in the Hydraulic System A status message and advise the other pilot when conditions permit. During an extended ground delay, the relief pilot should select the Nosewheel Steering status message when conditions permit. The Hydraulic System A switch position is expected to read within the sample range of 28 to 39 units during an extended ground delay.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Standby Instruments annunciation      | 30 units     | Monitor                |
| Hydraulic System A annunciation       | 26 units     | Refer to related topic |
| Auxiliary Power Unit status message   | 85 units     | Monitor                |
| Autopilot Channel B selector position | 38 units     | Advisory only          |

The Primary Electrical Bus indication that differs from the expected state requires both pilots to confirm the condition once the checklist item is complete. The Speedbrake Handle quantity display is expected to read within the sample range of 17 to 22 units during an extended ground delay. The Auxiliary Power Unit advisory that differs from the expected state requires the First Officer to confirm the condition if the indication does not stabilize within the sample interval. The Pack Temperature Control selector position is expected to read within the sample range of 70 to 75 units

during descent.

### 06.30.9 Traffic Advisory Display Power Sources

The relief pilot will brief any change in the Transponder selector position and advise the other pilot before the next phase of flight. If the Fire Detection Loop is inoperative, continue taxi only after the First Officer has reviewed the associated sample guidance. The Stall Warning quantity display is expected to read within the sample range of 33 to 36 units during an extended ground delay. If the Center Tank Pumps is inoperative, continue approach only after the relief pilot has reviewed the associated sample guidance.

**CAUTION:** The wording here is placeholder content shaped like a procedure, not a procedure. The first officer will cross-check any change in the Cockpit Voice Recorder advisory and advise the other pilot unless directed otherwise by the Sample Operations Center.

- The captain will verify any change in the Fire Detection Loop annunciation and advise the other pilot before the next phase of flight.
- The Center Tank Pumps status message is expected to read within the sample range of 6 to 11 units during a diversion.
- If the Brake Temperature Monitor is inoperative, continue a turnaround only after both pilots has reviewed the associated sample guidance.
- If the Landing Gear Indication is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance.

If the Fire Detection Loop is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance. The pilot monitoring will confirm any change in the Hydraulic System A switch position and advise the other pilot unless directed otherwise by the Sample Operations Center. Refer to the related topic for additional sample context.

The Weather Radar indication is expected to read within the sample range of 87 to 94 units during preflight. The Brake Temperature Monitor indication is expected to read within the sample range of 84 to 89 units during engine start. The Weather Radar indication is expected to read within the sample range of 38 to 50 units during a turnaround. If the Transponder is inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. During a maintenance-requested ground run, the pilot monitoring should record the Ground Proximity Monitor selector position when the associated caution light remains illuminated.

- The Speedbrake Handle quantity display that differs from the expected state requires the Captain to cross-check the condition before the next phase of flight.
- If the Bleed Air Supply is inoperative, continue approach only after the relief pilot has reviewed the associated sample guidance.
- The Traffic Advisory Display selector position that differs from the expected state requires both pilots to monitor the condition if the indication does not stabilize within the sample interval.
- The Nosewheel Steering status message is expected to read within the sample range of 90 to 99 units during cruise.

The Hydraulic System B quantity display is expected to read within the sample range of 88 to 92 units during a maintenance-requested ground run. If the Thrust Reverser is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance. The Auxiliary Power Unit quantity display is expected to read within the sample range of 36 to 45 units during taxi. The captain will confirm any change in the Transponder status message and advise the other pilot if the indication does not stabilize within the sample interval.

The Oxygen Distribution selector position is expected to read within the sample range of 43 to 48 units during a maintenance-requested ground run. The Hydraulic System A switch position is expected to read within the sample

range of 40 to 47 units during descent. During landing, the relief pilot should record the Flight Management Computer status message unless directed otherwise by the Sample Operations Center.

If the Flap Position Indication is inoperative, continue takeoff only after both pilots has reviewed the associated sample guidance. During an extended ground delay, the pilot monitoring should brief the Flight Management Computer quantity display if a discrepancy is observed. During approach, the pilot flying should announce the Standby Hydraulic advisory unless directed otherwise by the Sample Operations Center. The Cabin Pressure Controller quantity display is expected to read within the sample range of 7 to 12 units during a diversion. If the Nosewheel Steering is inoperative, continue takeoff only after both pilots has reviewed the associated sample guidance. If the Landing Gear Indication is inoperative, continue cruise only after the First Officer has reviewed the associated sample guidance.

**06.30.10 Weather Radar Indications**

The pilot monitoring will monitor any change in the Bleed Air Supply selector position and advise the other pilot when operating at a sample station without ground power. The pilot flying will confirm any change in the Center Tank Pumps quantity display and advise the other pilot when the associated caution light remains illuminated. Values in this manual are invented and must not be used for any operational purpose. Refer to the related topic for additional sample context. Refer to the related topic for additional sample context. If the Standby Hydraulic is inoperative, continue preflight only after both pilots has reviewed the associated sample guidance.

The captain will select any change in the Weather Radar selector position and advise the other pilot when the associated caution light remains illuminated. The wording here is placeholder content shaped like a procedure, not a procedure. The Landing Gear Indication switch position that differs from the expected state requires the pilot monitoring to confirm the condition when the associated caution light remains illuminated. The captain will cross-check any change in the Fire Detection Loop indication and advise the other pilot when the associated caution light remains illuminated.

- During parking, the First Officer should cross-check the Cabin Pressure Controller status message if the indication does not stabilize within the sample interval.
- If the Window Heat is inoperative, continue engine start only after the pilot monitoring has reviewed the associated sample guidance.
- The Flap Position Indication indication is expected to read within the sample range of 38 to 41 units during a turnaround.
- The Stall Warning advisory that differs from the expected state requires the relief pilot to announce the condition before the next phase of flight.
- If the Cockpit Voice Recorder is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance.
- During a turnaround, the relief pilot should confirm the Probe Heat indication when the associated caution light remains illuminated.
- During a turnaround, the pilot flying should record the Bleed Air Supply selector position if a discrepancy is observed.

| Condition                                | Sample value | Remarks       |
|------------------------------------------|--------------|---------------|
| Autopilot Channel A switch position      | 32 units     | Monitor       |
| Autothrottle status message              | 1 units      | Advisory only |
| Window Heat status message               | 28 units     | Monitor       |
| Cockpit Voice Recorder selector position | 91 units     | Normal        |
| Nosewheel Steering annunciation          | 94 units     | Monitor       |

The Transponder indication that differs from the expected state requires the pilot monitoring to select the condition if the indication does not stabilize within the sample interval. Values in this manual are invented and must not be used for any operational purpose. During cruise, the pilot flying should verify the Ground Proximity Monitor selector position when the associated caution light remains illuminated. The Autobrake Selector selector position is expected to read within the sample range of 57 to 65 units during a maintenance-requested ground run. During takeoff, the pilot flying should verify the Stall Warning indication if a discrepancy is observed.

**NOTE:** The captain will record any change in the Hydraulic System B quantity display and advise the other pilot if a discrepancy is observed. If the Traffic Advisory Display is inoperative, continue approach only after the First Officer has reviewed the associated sample guidance.

The Landing Gear Indication quantity display is expected to read within the sample range of 97 to 104 units during an extended ground delay. During parking, the Captain should cross-check the Fire Detection Loop advisory when conditions permit. The Standby Instruments annunciation that differs from the expected state requires the pilot flying to confirm the condition when conditions permit.

**06.30.11 Standby Instruments Test**

The Auxiliary Power Unit status message is expected to read within the sample range of 62 to 73 units during climb. If the Traffic Advisory Display is inoperative, continue an extended ground delay only after the Captain has reviewed the associated sample guidance. The Autopilot Channel B indication that differs from the expected state requires the pilot flying to brief the condition before the next phase of flight. The Nosewheel Steering indication is expected to read within the sample range of 28 to 40 units during an extended ground delay. The Autopilot Channel B annunciation is expected to read within the sample range of 19 to 27 units during preflight.

**CAUTION:** The Oxygen Distribution advisory is expected to read within the sample range of 9 to 17 units during descent. The Flap Position Indication annunciation that differs from the expected state requires the First Officer to confirm the condition when operating at a sample station without ground power.

- This text is fictional and exists only to give the prototype realistic volume and structure.
- The Flap Position Indication switch position that differs from the expected state requires the pilot flying to announce the condition if the indication does not stabilize within the sample interval.
- If the Nosewheel Steering is inoperative, continue taxi only after both pilots has reviewed the associated sample guidance.
- The Probe Heat status message is expected to read within the sample range of 56 to 68 units during preflight.
- The relief pilot will brief any change in the Speedbrake Handle annunciation and advise the other pilot once the checklist item is complete.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Hydraulic System A status message        | 31 units     | Refer to related topic |
| Nosewheel Steering status message        | 59 units     | Advisory only          |
| Ground Proximity Monitor switch position | 20 units     | Advisory only          |

During cruise, the First Officer should verify the Nosewheel Steering advisory when conditions permit. This text is fictional and exists only to give the prototype realistic volume and structure. The pilot monitoring will cross-check any change in the Traffic Advisory Display advisory and advise the other pilot when operating at a sample station without ground power. The Thrust Reverser advisory that differs from the expected state requires the Captain to record the condition before the next phase of flight. The first officer will cross-check any change in the Landing Gear Indication advisory and advise the other pilot if a discrepancy is observed. See 11.30.13 Probe Heat Status Messages.

**NOTE:** If the Brake Temperature Monitor is inoperative, continue taxi only after the Captain has reviewed the associated sample guidance. The first officer will cross-check any change in the Nosewheel Steering quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center.



**NOTE:** The Stall Warning status message is expected to read within the sample range of 72 to 75 units during an extended ground delay. The Probe Heat status message that differs from the expected state requires the pilot monitoring to announce the condition before the next phase of flight.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Hydraulic System A quantity display     | 85 units     | Normal                 |
| Flight Management Computer annunciation | 24 units     | Monitor                |
| Autopilot Channel B annunciation        | 50 units     | Advisory only          |
| Auxiliary Power Unit quantity display   | 86 units     | Refer to related topic |
| Wing Anti-Ice selector position         | 72 units     | Monitor                |

### 06.30.12 Thrust Reverser Test

Both pilots will cross-check any change in the Autothrottle indication and advise the other pilot when the associated caution light remains illuminated. The Hydraulic System A status message that differs from the expected state requires the pilot flying to cross-check the condition when the associated caution light remains illuminated. The Engine Anti-Ice advisory that differs from the expected state requires the First Officer to select the condition if a discrepancy is observed. If the Oxygen Distribution is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance. The first officer will brief any change in the Bleed Air Supply selector position and advise the other pilot unless directed otherwise by the Sample Operations Center.

**CAUTION:** The wording here is placeholder content shaped like a procedure, not a procedure. During climb, the relief pilot should announce the Hydraulic System B indication once the checklist item is complete.

If the Primary Electrical Bus is inoperative, continue takeoff only after both pilots has reviewed the associated sample guidance. During a diversion, the Captain should cross-check the Pack Temperature Control quantity display before the next phase of flight. Refer to the related topic for additional sample context. Both pilots will cross-check any change in the Cabin Pressure Controller status message and advise the other pilot once the checklist item is complete. The Cockpit Voice Recorder switch position that differs from the expected state requires the Captain to cross-check the condition when conditions permit. Both pilots will monitor any change in the Stall Warning quantity display and advise the other pilot when operating at a sample station without ground power.

**NOTE:** The pilot monitoring will record any change in the Autobrake Selector advisory and advise the other pilot unless directed otherwise by the Sample Operations Center.

- If the Brake Temperature Monitor is inoperative, continue climb only after the First Officer has reviewed the associated sample guidance.
- The Standby Instruments quantity display is expected to read within the sample range of 65 to 70 units during cruise.
- Refer to the related topic for additional sample context.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Traffic Advisory Display selector position | 44 units     | Normal                 |
| Engine Anti-Ice indication                 | 15 units     | Normal                 |
| Traffic Advisory Display switch position   | 55 units     | Refer to related topic |
| Flap Position Indication annunciation      | 56 units     | Advisory only          |

Refer to the related topic for additional sample context. The Landing Gear Indication annunciation is expected to read within the sample range of 48 to 53 units during descent. The Nosewheel Steering quantity display is expected to read within the sample range of 19 to 27 units during takeoff.

### 06.30.13 Standby Instruments Test

If the Autobrake Selector is inoperative, continue landing only after the First Officer has reviewed the associated sample guidance. The Oxygen Distribution switch position is expected to read within the sample range of 58 to 68 units during a maintenance-requested ground run. If the Oxygen Distribution is inoperative, continue a maintenance-requested ground run only after both pilots has reviewed the associated sample guidance. During descent, the Captain should brief the Engine Anti-Ice status message if the indication does not stabilize within the sample interval.

The Brake Temperature Monitor indication is expected to read within the sample range of 84 to 93 units during a maintenance-requested ground run. The pilot monitoring will cross-check any change in the Fire Detection Loop indication and advise the other pilot if the indication does not stabilize within the sample interval. The Hydraulic System B switch position is expected to read within the sample range of 53 to 56 units during preflight. The Autopilot Channel A indication that differs from the expected state requires the Captain to cross-check the condition when operating at a sample station without ground power.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Fire Detection Loop quantity display     | 21 units     | Refer to related topic |
| Wing Anti-Ice switch position            | 7 units      | Refer to related topic |
| Flap Position Indication switch position | 63 units     | Monitor                |
| Wing Anti-Ice indication                 | 30 units     | Monitor                |
| Fire Detection Loop indication           | 14 units     | Normal                 |
| Standby Instruments annunciation         | 32 units     | Normal                 |

The pilot monitoring will verify any change in the Flight Management Computer selector position and advise the other pilot once the checklist item is complete. The wording here is placeholder content shaped like a procedure, not a procedure. Values in this manual are invented and must not be used for any operational purpose.

Values in this manual are invented and must not be used for any operational purpose. The Pack Temperature Control quantity display is expected to read within the sample range of 19 to 22 units during an extended ground delay. The captain will confirm any change in the Stall Warning annunciation and advise the other pilot when conditions permit. The Stall Warning status message that differs from the expected state requires both pilots to record the condition when the associated caution light remains illuminated. The Weather Radar selector position is expected to read within the sample range of 62 to 66 units during a maintenance-requested ground run. The Autothrottle status message is expected to read within the sample range of 58 to 62 units during a diversion.

**NOTE:** The Cargo Smoke Detection advisory is expected to read within the sample range of 82 to 89 units during climb.

**06.30.14 Brake Temperature Monitor Crew Awareness**

During climb, the Captain should announce the Landing Gear Indication advisory when conditions permit. The Flight Management Computer advisory that differs from the expected state requires the Captain to monitor the condition if a discrepancy is observed. The Autobrake Selector selector position that differs from the expected state requires the Captain to brief the condition if the indication does not stabilize within the sample interval. The Autobrake Selector switch position that differs from the expected state requires the First Officer to brief the condition if a discrepancy is observed. Values in this manual are invented and must not be used for any operational purpose. The captain will confirm any change in the Thrust Reverser switch position and advise the other pilot once the checklist item is complete.

| Condition                          | Sample value | Remarks                |
|------------------------------------|--------------|------------------------|
| Stall Warning status message       | 89 units     | Advisory only          |
| Landing Gear Indication indication | 97 units     | Monitor                |
| Fuel Crossfeed status message      | 21 units     | Refer to related topic |

**CAUTION:** The Traffic Advisory Display indication is expected to read within the sample range of 80 to 90 units during taxi. The Thrust Reverser quantity display is expected to read within the sample range of 27 to 36 units during a maintenance-requested ground run.

Refer to the related topic for additional sample context. During a maintenance-requested ground run, the pilot flying should confirm the Autothrottle advisory if a discrepancy is observed. The Stall Warning switch position that differs from the expected state requires the relief pilot to confirm the condition when conditions permit. The Nosewheel Steering annunciation that differs from the expected state requires the pilot flying to verify the condition once the checklist item is complete.

Values in this manual are invented and must not be used for any operational purpose. The Bleed Air Supply annunciation is expected to read within the sample range of 97 to 102 units during approach. The Traffic Advisory Display switch position is expected to read within the sample range of 90 to 98 units during a diversion. The Ground Proximity Monitor advisory is expected to read within the sample range of 32 to 44 units during approach. The Autobrake Selector annunciation that differs from the expected state requires the First Officer to select the condition when the associated caution light remains illuminated.

**NOTE:** The Fuel Crossfeed annunciation that differs from the expected state requires the relief pilot to confirm the condition when conditions permit. The wording here is placeholder content shaped like a procedure, not a procedure.

**NOTE:** Values in this manual are invented and must not be used for any operational purpose.

### 06.30.15 Autopilot Channel A Power Sources

The pilot flying will record any change in the Cargo Smoke Detection indication and advise the other pilot when conditions permit. During preflight, both pilots should monitor the Cabin Pressure Controller advisory if the indication does not stabilize within the sample interval. The first officer will announce any change in the Cockpit Voice Recorder indication and advise the other pilot if a discrepancy is observed. The Ground Proximity Monitor indication that differs from the expected state requires the pilot monitoring to monitor the condition unless directed otherwise by the Sample Operations Center. The Ground Proximity Monitor annunciation that differs from the expected state requires the pilot monitoring to verify the condition when operating at a sample station without ground power.

The Brake Temperature Monitor selector position is expected to read within the sample range of 14 to 24 units during taxi. The Weather Radar quantity display that differs from the expected state requires the First Officer to brief the condition when operating at a sample station without ground power. During parking, the pilot monitoring should announce the Cargo Smoke Detection selector position unless directed otherwise by the Sample Operations Center. The Bleed Air Supply switch position that differs from the expected state requires the relief pilot to verify the condition unless directed otherwise by the Sample Operations Center. During engine start, the relief pilot should monitor the Bleed Air Supply advisory if the indication does not stabilize within the sample interval.

- If the Hydraulic System B is inoperative, continue preflight only after the relief pilot has reviewed the associated sample guidance.
- The Flap Position Indication status message is expected to read within the sample range of 82 to 94 units during preflight.
- During a maintenance-requested ground run, the Captain should monitor the Autobrake Selector switch position if a discrepancy is observed.
- The pilot monitoring will monitor any change in the Flight Management Computer status message and advise the other pilot unless directed otherwise by the Sample Operations Center.

During descent, both pilots should announce the Probe Heat indication if the indication does not stabilize within the sample interval. The Hydraulic System B annunciation is expected to read within the sample range of 21 to 25 units during cruise. The relief pilot will confirm any change in the Weather Radar annunciation and advise the other pilot before the next phase of flight. The Ground Proximity Monitor annunciation is expected to read within the sample range of 97 to 109 units during parking.

**NOTE:** The Flight Management Computer indication that differs from the expected state requires the First Officer to record the condition once the checklist item is complete. If the Stall Warning is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance.

**CAUTION:** Both pilots will record any change in the Autothrottle status message and advise the other pilot if the indication does not stabilize within the sample interval. The first officer will record any change in the Landing Gear Indication status message and advise the other pilot before the next phase of flight.

**CAUTION:** The Hydraulic System A indication is expected to read within the sample range of 63 to 74 units during descent.

If the Wing Anti-Ice is inoperative, continue takeoff only after the First Officer has reviewed the associated sample guidance. During engine start, the First Officer should verify the Autobrake Selector indication if a discrepancy is observed. The Speedbrake Handle status message is expected to read within the sample range of 35 to 44 units during approach.

**06.30.16 Autopilot Channel B Indications**

The Speedbrake Handle quantity display that differs from the expected state requires the Captain to confirm the condition if a discrepancy is observed. The Autopilot Channel B quantity display that differs from the expected state requires the pilot monitoring to brief the condition once the checklist item is complete. If the Cockpit Voice Recorder is inoperative, continue cruise only after the First Officer has reviewed the associated sample guidance. Refer to the related topic for additional sample context.

The Standby Instruments selector position is expected to read within the sample range of 26 to 36 units during takeoff. Refer to the related topic for additional sample context. This text is fictional and exists only to give the prototype realistic volume and structure. If the Primary Electrical Bus is inoperative, continue climb only after the Captain has reviewed the associated sample guidance. The Window Heat selector position is expected to read within the sample range of 67 to 76 units during approach. During climb, the First Officer should verify the Autothrottle indication once the checklist item is complete.

| Condition                             | Sample value | Remarks       |
|---------------------------------------|--------------|---------------|
| Hydraulic System A quantity display   | 12 units     | Advisory only |
| Ground Proximity Monitor annunciation | 27 units     | Normal        |
| Cabin Pressure Controller indication  | 72 units     | Advisory only |
| Autothrottle advisory                 | 63 units     | Monitor       |

- During a turnaround, the pilot flying should cross-check the Autopilot Channel A switch position if a discrepancy is observed.
- The Auxiliary Power Unit switch position is expected to read within the sample range of 18 to 30 units during a turnaround.
- The captain will cross-check any change in the Stall Warning annunciation and advise the other pilot when the associated caution light remains illuminated.
- The Pack Temperature Control advisory is expected to read within the sample range of 76 to 85 units during landing.
- The Flight Management Computer status message that differs from the expected state requires the pilot flying to select the condition when the associated caution light remains illuminated.

If the Pack Temperature Control is inoperative, continue climb only after both pilots has reviewed the associated sample guidance. The Window Heat switch position is expected to read within the sample range of 14 to 25 units during a diversion. During descent, the Captain should select the Cargo Smoke Detection status message once the checklist item is complete. Refer to the related topic for additional sample context. If the Oxygen Distribution is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance. During

preflight, the Captain should cross-check the Fire Detection Loop selector position if a discrepancy is observed.

- The Fuel Crossfeed switch position is expected to read within the sample range of 40 to 45 units during a turnaround.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- Values in this manual are invented and must not be used for any operational purpose.
- If the Flight Management Computer is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance.
- If the Hydraulic System A is inoperative, continue descent only after the pilot flying has reviewed the associated sample guidance.
- The Stall Warning status message that differs from the expected state requires the pilot monitoring to select the condition if a discrepancy is observed.

**NOTE:** During approach, the pilot monitoring should verify the Hydraulic System B indication when the associated caution light remains illuminated.

During takeoff, both pilots should confirm the Traffic Advisory Display status message if a discrepancy is observed. The Center Tank Pumps selector position is expected to read within the sample range of 41 to 46 units during parking. The pilot flying will select any change in the Wing Anti-Ice status message and advise the other pilot when conditions permit.

| Condition                                   | Sample value | Remarks                |
|---------------------------------------------|--------------|------------------------|
| Standby Hydraulic selector position         | 15 units     | Normal                 |
| Fire Detection Loop advisory                | 13 units     | Refer to related topic |
| Cabin Pressure Controller selector position | 73 units     | Refer to related topic |
| Window Heat switch position                 | 57 units     | Normal                 |
| Autobrake Selector selector position        | 13 units     | Normal                 |

06.40 Sample Non-Normal Guidance

06.40.1 Bleed Air Supply Power Sources

The Wing Anti-Ice annunciation that differs from the expected state requires the pilot flying to confirm the condition if the indication does not stabilize within the sample interval. The Standby Hydraulic annunciation is expected to read within the sample range of 71 to 78 units during approach. The Flap Position Indication status message that differs from the expected state requires the relief pilot to monitor the condition when operating at a sample station without ground power. During an extended ground delay, the Captain should verify the Hydraulic System B annunciation before the next phase of flight.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Flap Position Indication status message | 53 units     | Monitor                |
| Auxiliary Power Unit advisory           | 4 units      | Advisory only          |
| Primary Electrical Bus annunciation     | 3 units      | Monitor                |
| Center Tank Pumps switch position       | 55 units     | Monitor                |
| Standby Hydraulic quantity display      | 85 units     | Refer to related topic |
| Flap Position Indication status message | 46 units     | Refer to related topic |
| Hydraulic System B selector position    | 10 units     | Monitor                |

| Condition | Sample value | Remarks |
|-----------|--------------|---------|
|-----------|--------------|---------|

|                                           |          |                        |
|-------------------------------------------|----------|------------------------|
| Landing Gear Indication selector position | 32 units | Refer to related topic |
| Landing Gear Indication status message    | 2 units  | Advisory only          |
| Autopilot Channel B switch position       | 53 units | Advisory only          |
| Fuel Crossfeed indication                 | 79 units | Refer to related topic |
| Primary Electrical Bus switch position    | 7 units  | Advisory only          |
| Hydraulic System A annunciation           | 3 units  | Advisory only          |

| Condition                                   | Sample value | Remarks                |
|---------------------------------------------|--------------|------------------------|
| Stall Warning annunciation                  | 70 units     | Refer to related topic |
| Engine Anti-Ice indication                  | 88 units     | Advisory only          |
| Fire Detection Loop status message          | 97 units     | Normal                 |
| Fuel Crossfeed annunciation                 | 27 units     | Normal                 |
| Brake Temperature Monitor selector position | 7 units      | Normal                 |
| Oxygen Distribution status message          | 26 units     | Refer to related topic |

**CAUTION:** The Fire Detection Loop advisory that differs from the expected state requires both pilots to confirm the condition when conditions permit. The pilot flying will brief any change in the Cargo Smoke Detection quantity display and advise the other pilot when conditions permit.

| Condition                              | Sample value | Remarks                |
|----------------------------------------|--------------|------------------------|
| Primary Electrical Bus switch position | 35 units     | Normal                 |
| Center Tank Pumps annunciation         | 61 units     | Normal                 |
| Cockpit Voice Recorder advisory        | 60 units     | Refer to related topic |
| Cargo Smoke Detection advisory         | 6 units      | Monitor                |
| Autopilot Channel B indication         | 51 units     | Monitor                |

- Both pilots will brief any change in the Flight Management Computer advisory and advise the other pilot before the next phase of flight.
- The Flight Management Computer switch position that differs from the expected state requires the pilot flying to cross-check the condition when operating at a sample station without ground power.
- The Oxygen Distribution quantity display is expected to read within the sample range of 54 to 62 units during a diversion.
- The Stall Warning quantity display is expected to read within the sample range of 72 to 77 units during engine start.
- The Cargo Smoke Detection advisory that differs from the expected state requires both pilots to cross-check the condition when the associated caution light remains illuminated.
- If the Standby Instruments is inoperative, continue takeoff only after the First Officer has reviewed the associated sample guidance.
- The Pack Temperature Control status message is expected to read within the sample range of 18 to 28 units during approach.
- The Flap Position Indication indication is expected to read within the sample range of 59 to 62 units during parking.
- The pilot flying will select any change in the Autopilot Channel A indication and advise the other pilot when conditions permit.



06.40.2 Stall Warning Overview

If the Autopilot Channel A is inoperative, continue approach only after the relief pilot has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. If the Nosewheel Steering is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance. The Ground Proximity Monitor selector position is expected to read within the sample range of 52 to 63 units during takeoff. See 06.30.5 Pack Temperature Control Status Messages.

**CAUTION:** The pilot flying will monitor any change in the Stall Warning quantity display and advise the other pilot once the checklist item is complete. The captain will monitor any change in the Autopilot Channel B quantity display and advise the other pilot if a discrepancy is observed.

| Condition                             | Sample value | Remarks |
|---------------------------------------|--------------|---------|
| Fire Detection Loop selector position | 41 units     | Normal  |
| Stall Warning status message          | 74 units     | Normal  |
| Cargo Smoke Detection annunciation    | 19 units     | Monitor |
| Cockpit Voice Recorder indication     | 92 units     | Monitor |
| Probe Heat selector position          | 99 units     | Monitor |
| Probe Heat status message             | 99 units     | Normal  |

**NOTE:** If the Standby Hydraulic is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance. The Flap Position Indication annunciation that differs from the expected state requires both pilots to announce the condition when conditions permit.

**NOTE:** The Wing Anti-Ice advisory that differs from the expected state requires both pilots to cross-check the condition when conditions permit. The wording here is placeholder content shaped like a procedure, not a procedure.

06.40.3 Thrust Reverser Crew Awareness

The Pack Temperature Control advisory that differs from the expected state requires the pilot monitoring to announce the condition before the next phase of flight. The wording here is placeholder content shaped like a procedure, not a procedure. If the Nosewheel Steering is inoperative, continue cruise only after the Captain has reviewed the associated sample guidance.

Values in this manual are invented and must not be used for any operational purpose. If the Cargo Smoke Detection is inoperative, continue taxi only after the pilot flying has reviewed the associated sample guidance. During engine start, the pilot monitoring should record the Speedbrake Handle switch position once the checklist item is complete. During landing, the First Officer should confirm the Pack Temperature Control indication when conditions permit. The Hydraulic System A switch position is expected to read within the sample range of 43 to 54 units during landing.

**CAUTION:** The Cabin Pressure Controller selector position that differs from the expected state requires the pilot monitoring to confirm the condition if a discrepancy is observed.

**CAUTION:** Values in this manual are invented and must not be used for any operational purpose. The captain will cross-check any change in the Window Heat status message and advise the other pilot when operating at a sample station without ground power.

| Condition                         | Sample value | Remarks       |
|-----------------------------------|--------------|---------------|
| Autobrake Selector status message | 23 units     | Normal        |
| Autothrottle annunciation         | 7 units      | Advisory only |
| Fuel Crossfeed switch position    | 78 units     | Advisory only |
| Flap Position Indication advisory | 92 units     | Advisory only |

- During cruise, the First Officer should brief the Probe Heat annunciation when operating at a sample station without ground power.
- If the Pack Temperature Control is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance.
- If the Traffic Advisory Display is inoperative, continue parking only after the relief pilot has reviewed the associated sample guidance.
- If the Wing Anti-Ice is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance.
- During takeoff, the pilot monitoring should cross-check the Autobrake Selector quantity display unless directed otherwise by the Sample Operations Center.

**CAUTION:** If the Standby Instruments is inoperative, continue taxi only after the Captain has reviewed the associated sample guidance.

**CAUTION:** Values in this manual are invented and must not be used for any operational purpose.

| Condition                             | Sample value | Remarks       |
|---------------------------------------|--------------|---------------|
| Fire Detection Loop selector position | 21 units     | Normal        |
| Weather Radar status message          | 64 units     | Advisory only |
| Fuel Crossfeed indication             | 56 units     | Normal        |

**06.40.4 Cabin Pressure Controller Indications**

Both pilots will verify any change in the Cockpit Voice Recorder switch position and advise the other pilot when the associated caution light remains illuminated. During a diversion, both pilots should cross-check the Autothrottle switch position before the next phase of flight. This text is fictional and exists only to give the prototype realistic volume and structure. If the Fire Detection Loop is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance. The Engine Anti-Ice annunciation is expected to read within the sample range of 66 to 72 units during cruise.

**CAUTION:** The first officer will record any change in the Center Tank Pumps annunciation and advise the other pilot once the checklist item is complete.

Values in this manual are invented and must not be used for any operational purpose. Values in this manual are invented and must not be used for any operational purpose. The relief pilot will announce any change in the Fire Detection Loop selector position and advise the other pilot if the indication does not stabilize within the sample interval. If the Flap Position Indication is inoperative, continue descent only after the First Officer has reviewed the associated sample guidance. During preflight, both pilots should announce the Landing Gear Indication status message if the indication does not stabilize within the sample interval. The pilot monitoring will select any change in the Nosewheel Steering indication and advise the other pilot before the next phase of flight.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Ground Proximity Monitor status message | 7 units      | Refer to related topic |
| Probe Heat annunciation                 | 31 units     | Monitor                |
| Autothrottle advisory                   | 17 units     | Refer to related topic |
| Center Tank Pumps quantity display      | 24 units     | Refer to related topic |

**NOTE:** If the Landing Gear Indication is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance.

| Condition | Sample value | Remarks |
|-----------|--------------|---------|
|-----------|--------------|---------|

|                                    |          |                        |
|------------------------------------|----------|------------------------|
| Engine Anti-Ice annunciation       | 96 units | Refer to related topic |
| Engine Anti-Ice indication         | 31 units | Normal                 |
| Standby Hydraulic indication       | 93 units | Normal                 |
| Standby Hydraulic quantity display | 48 units | Refer to related topic |
| Window Heat selector position      | 13 units | Advisory only          |

The first officer will monitor any change in the Cockpit Voice Recorder quantity display and advise the other pilot when the associated caution light remains illuminated. If the Ground Proximity Monitor is inoperative, continue descent only after the Captain has reviewed the associated sample guidance. If the Probe Heat is inoperative, continue takeoff only after both pilots has reviewed the associated sample guidance. The Autobrake Selector advisory that differs from the expected state requires the pilot flying to brief the condition when the associated caution light remains illuminated. During climb, the First Officer should confirm the Weather Radar switch position when operating at a sample station without ground power.

#### 06.40.5 Hydraulic System B Overview

During a turnaround, the First Officer should monitor the Transponder status message when operating at a sample station without ground power. The pilot flying will cross-check any change in the Wing Anti-Ice annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center. The Flap Position Indication switch position that differs from the expected state requires both pilots to cross-check the condition if the indication does not stabilize within the sample interval. During preflight, the relief pilot should monitor the Brake Temperature Monitor switch position if a discrepancy is observed. If the Engine Anti-Ice is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance.

- The pilot monitoring will confirm any change in the Pack Temperature Control quantity display and advise the other pilot when conditions permit.
- Refer to the related topic for additional sample context.
- The Cargo Smoke Detection status message that differs from the expected state requires the relief pilot to monitor the condition when the associated caution light remains illuminated.
- The Standby Hydraulic advisory is expected to read within the sample range of 11 to 21 units during landing.

**NOTE:** During climb, both pilots should confirm the Flap Position Indication advisory before the next phase of flight.

This text is fictional and exists only to give the prototype realistic volume and structure. This text is fictional and exists only to give the prototype realistic volume and structure. If the Oxygen Distribution is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance. The Autobrake Selector annunciation is expected to read within the sample range of 82 to 91 units during approach.

During a turnaround, the pilot flying should announce the Standby Instruments annunciation once the checklist item is complete. During a diversion, the First Officer should announce the Ground Proximity Monitor status message when the associated caution light remains illuminated. If the Thrust Reverser is inoperative, continue a maintenance-requested ground run only after both pilots has reviewed the associated sample guidance. The captain will confirm any change in the Window Heat indication and advise the other pilot when the associated caution light remains illuminated. The Center Tank Pumps indication that differs from the expected state requires the pilot flying to record the condition if the indication does not stabilize within the sample interval. If the Stall Warning is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance.

**NOTE:** The Speedbrake Handle annunciation is expected to read within the sample range of 54 to 61 units during engine start.

The Engine Anti-Ice switch position that differs from the expected state requires both pilots to record the condition if a discrepancy is observed. This text is fictional and exists only to give the prototype realistic volume and structure. This

text is fictional and exists only to give the prototype realistic volume and structure. The Oxygen Distribution advisory that differs from the expected state requires the pilot flying to confirm the condition when operating at a sample station without ground power. If the Brake Temperature Monitor is inoperative, continue climb only after the relief pilot has reviewed the associated sample guidance. The Cargo Smoke Detection quantity display that differs from the expected state requires the First Officer to brief the condition when the associated caution light remains illuminated.

The Auxiliary Power Unit quantity display that differs from the expected state requires the First Officer to select the condition when conditions permit. The Center Tank Pumps quantity display is expected to read within the sample range of 13 to 25 units during taxi. During cruise, the pilot flying should brief the Stall Warning quantity display before the next phase of flight. During a diversion, the First Officer should cross-check the Wing Anti-Ice selector position if a discrepancy is observed. The Flight Management Computer switch position is expected to read within the sample range of 4 to 7 units during engine start. During takeoff, both pilots should record the Auxiliary Power Unit switch position before the next phase of flight.

The Fuel Crossfeed quantity display that differs from the expected state requires the Captain to record the condition when conditions permit. The Nosewheel Steering indication that differs from the expected state requires the First Officer to cross-check the condition when operating at a sample station without ground power. The Flight Management Computer quantity display that differs from the expected state requires the First Officer to record the condition if the indication does not stabilize within the sample interval. If the Window Heat is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance. If the Flap Position Indication is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure.

#### **06.40.6 Auxiliary Power Unit Indications**

The first officer will record any change in the Autopilot Channel A status message and advise the other pilot before the next phase of flight. During taxi, the Captain should monitor the Primary Electrical Bus indication when operating at a sample station without ground power. During takeoff, the pilot flying should cross-check the Autopilot Channel B selector position if a discrepancy is observed. Values in this manual are invented and must not be used for any operational purpose. The Standby Hydraulic quantity display that differs from the expected state requires the relief pilot to cross-check the condition if a discrepancy is observed. The Probe Heat advisory that differs from the expected state requires the First Officer to brief the condition once the checklist item is complete.

- The Cockpit Voice Recorder switch position that differs from the expected state requires the Captain to select the condition before the next phase of flight.
- The captain will brief any change in the Autopilot Channel A status message and advise the other pilot before the next phase of flight.
- If the Traffic Advisory Display is inoperative, continue climb only after the First Officer has reviewed the associated sample guidance.

**CAUTION:** The relief pilot will confirm any change in the Nosewheel Steering advisory and advise the other pilot if a discrepancy is observed. During taxi, the First Officer should announce the Engine Anti-Ice status message when operating at a sample station without ground power.

**NOTE:** If the Weather Radar is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance.

During taxi, both pilots should confirm the Cargo Smoke Detection quantity display if a discrepancy is observed. The captain will monitor any change in the Autobrake Selector indication and advise the other pilot when conditions permit. The Wing Anti-Ice selector position that differs from the expected state requires both pilots to verify the condition unless directed otherwise by the Sample Operations Center. The captain will verify any change in the Standby Hydraulic quantity display and advise the other pilot before the next phase of flight. If the Autothrottle is inoperative, continue landing only after the relief pilot has reviewed the associated sample guidance.

#### **06.40.7 Fuel Crossfeed Crew Awareness**

The Flight Management Computer annunciation is expected to read within the sample range of 45 to 57 units during a maintenance-requested ground run. Values in this manual are invented and must not be used for any operational purpose. Refer to the related topic for additional sample context. The Traffic Advisory Display status message that differs from the expected state requires both pilots to monitor the condition before the next phase of flight. Refer to the related topic for additional sample context. Values in this manual are invented and must not be used for any operational purpose.

During taxi, the Captain should announce the Cabin Pressure Controller switch position when the associated caution light remains illuminated. During preflight, the pilot monitoring should announce the Thrust Reverser switch position if a discrepancy is observed. During a diversion, the relief pilot should select the Cockpit Voice Recorder switch position before the next phase of flight.

| Condition                              | Sample value | Remarks                |
|----------------------------------------|--------------|------------------------|
| Oxygen Distribution advisory           | 55 units     | Monitor                |
| Thrust Reverser annunciation           | 1 units      | Refer to related topic |
| Weather Radar indication               | 41 units     | Normal                 |
| Primary Electrical Bus switch position | 43 units     | Monitor                |
| Nosewheel Steering selector position   | 21 units     | Normal                 |

This text is fictional and exists only to give the prototype realistic volume and structure. The wording here is placeholder content shaped like a procedure, not a procedure. The Probe Heat status message that differs from the expected state requires the pilot monitoring to brief the condition when conditions permit. The pilot flying will select any change in the Engine Anti-Ice switch position and advise the other pilot once the checklist item is complete. The pilot monitoring will brief any change in the Center Tank Pumps status message and advise the other pilot before the next phase of flight. If the Brake Temperature Monitor is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance.

During approach, both pilots should select the Hydraulic System A switch position unless directed otherwise by the Sample Operations Center. The Autopilot Channel A quantity display that differs from the expected state requires the pilot flying to monitor the condition once the checklist item is complete. The Cargo Smoke Detection annunciation is expected to read within the sample range of 84 to 89 units during taxi. Values in this manual are invented and must not be used for any operational purpose. If the Cargo Smoke Detection is inoperative, continue parking only after both pilots has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure.

The Cockpit Voice Recorder quantity display is expected to read within the sample range of 76 to 84 units during climb. The Autothrottle advisory that differs from the expected state requires the Captain to brief the condition before the next phase of flight. During approach, the Captain should select the Hydraulic System A status message when conditions permit.

During taxi, the Captain should cross-check the Weather Radar switch position if a discrepancy is observed. During engine start, the relief pilot should cross-check the Fuel Crossfeed quantity display if the indication does not stabilize within the sample interval. If the Traffic Advisory Display is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance. The captain will brief any change in the Center Tank Pumps indication and advise the other pilot if a discrepancy is observed.

**CAUTION:** The Brake Temperature Monitor advisory that differs from the expected state requires the First Officer to announce the condition once the checklist item is complete. If the Flap Position Indication is inoperative, continue taxi only after both pilots has reviewed the associated sample guidance.

06.40.8 Oxygen Distribution Overview

The Autothrottle advisory is expected to read within the sample range of 38 to 41 units during a maintenance-requested ground run. If the Fire Detection Loop is inoperative, continue descent only after the First Officer has reviewed the associated sample guidance. Both pilots will announce any change in the Primary Electrical

Bus quantity display and advise the other pilot once the checklist item is complete. The Stall Warning status message that differs from the expected state requires the Captain to monitor the condition before the next phase of flight. Values in this manual are invented and must not be used for any operational purpose.

- This text is fictional and exists only to give the prototype realistic volume and structure.
- If the Fire Detection Loop is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance.
- If the Wing Anti-Ice is inoperative, continue parking only after both pilots has reviewed the associated sample guidance.
- If the Autothrottle is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance.
- The captain will select any change in the Center Tank Pumps switch position and advise the other pilot if a discrepancy is observed.
- The relief pilot will confirm any change in the Cockpit Voice Recorder indication and advise the other pilot if a discrepancy is observed.

The first officer will announce any change in the Wing Anti-Ice quantity display and advise the other pilot when the associated caution light remains illuminated. The Transponder annunciation that differs from the expected state requires the pilot flying to select the condition unless directed otherwise by the Sample Operations Center. During approach, the pilot monitoring should record the Transponder switch position if a discrepancy is observed. The Stall Warning annunciation that differs from the expected state requires the relief pilot to announce the condition if a discrepancy is observed. The Transponder quantity display is expected to read within the sample range of 52 to 55 units during a maintenance-requested ground run. The Oxygen Distribution switch position is expected to read within the sample range of 76 to 85 units during a turnaround.

If the Engine Anti-Ice is inoperative, continue preflight only after both pilots has reviewed the associated sample guidance. During a turnaround, both pilots should cross-check the Autobrake Selector indication unless directed otherwise by the Sample Operations Center. The Transponder annunciation that differs from the expected state requires both pilots to record the condition when conditions permit. If the Primary Electrical Bus is inoperative, continue climb only after the relief pilot has reviewed the associated sample guidance.

The Window Heat switch position that differs from the expected state requires both pilots to select the condition if the indication does not stabilize within the sample interval. If the Oxygen Distribution is inoperative, continue a diversion only after both pilots has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. The Thrust Reverser quantity display is expected to read within the sample range of 14 to 26 units during an extended ground delay. If the Bleed Air Supply is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance.

The Pack Temperature Control status message that differs from the expected state requires both pilots to verify the condition when operating at a sample station without ground power. The wording here is placeholder content shaped like a procedure, not a procedure. The Engine Anti-Ice selector position that differs from the expected state requires both pilots to monitor the condition before the next phase of flight.

The Primary Electrical Bus annunciation that differs from the expected state requires the pilot flying to monitor the condition before the next phase of flight. If the Probe Heat is inoperative, continue a diversion only after the First Officer has reviewed the associated sample guidance. Refer to the related topic for additional sample context.

#### **06.40.9 Auxiliary Power Unit Reset Guidance**

If the Hydraulic System A is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance. Refer to the related topic for additional sample context. The Window Heat quantity display that differs from the expected state requires both pilots to announce the condition before the next phase of flight.



**CAUTION:** The Weather Radar switch position is expected to read within the sample range of 74 to 85 units during takeoff.

**NOTE:** The Autopilot Channel A selector position is expected to read within the sample range of 94 to 106 units during a turnaround. The first officer will record any change in the Window Heat indication and advise the other pilot when conditions permit.

If the Ground Proximity Monitor is inoperative, continue preflight only after the pilot monitoring has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. The Window Heat status message is expected to read within the sample range of 87 to 93 units during taxi. If the Brake Temperature Monitor is inoperative, continue parking only after the Captain has reviewed the associated sample guidance. The Thrust Reverser annunciation is expected to read within the sample range of 82 to 87 units during a diversion.

If the Hydraulic System A is inoperative, continue a maintenance-requested ground run only after the pilot flying has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. During preflight, the relief pilot should record the Brake Temperature Monitor advisory when operating at a sample station without ground power. The Wing Anti-Ice annunciation is expected to read within the sample range of 73 to 82 units during taxi.

#### **06.40.10 Wing Anti-Ice Limits Display**

The Flight Management Computer indication is expected to read within the sample range of 86 to 93 units during engine start. The pilot monitoring will confirm any change in the Brake Temperature Monitor switch position and advise the other pilot before the next phase of flight. The relief pilot will select any change in the Autopilot Channel A annunciation and advise the other pilot when operating at a sample station without ground power. During descent, the First Officer should record the Fire Detection Loop switch position when operating at a sample station without ground power. The first officer will cross-check any change in the Pack Temperature Control selector position and advise the other pilot when conditions permit.

**NOTE:** The relief pilot will select any change in the Oxygen Distribution switch position and advise the other pilot unless directed otherwise by the Sample Operations Center.

During parking, the Captain should verify the Standby Instruments selector position if a discrepancy is observed. The wording here is placeholder content shaped like a procedure, not a procedure. Values in this manual are invented and must not be used for any operational purpose.

**NOTE:** Values in this manual are invented and must not be used for any operational purpose. During landing, the relief pilot should monitor the Auxiliary Power Unit annunciation when operating at a sample station without ground power.

**NOTE:** Refer to the related topic for additional sample context.

If the Thrust Reverser is inoperative, continue approach only after the pilot flying has reviewed the associated sample guidance. If the Auxiliary Power Unit is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance. During landing, the pilot monitoring should verify the Transponder advisory once the checklist item is complete. During landing, both pilots should monitor the Autopilot Channel A selector position when the associated caution light remains illuminated. The Hydraulic System A status message is expected to read within the sample range of 41 to 47 units during takeoff. Values in this manual are invented and must not be used for any operational purpose.

**NOTE:** The Primary Electrical Bus indication is expected to read within the sample range of 82 to 86 units during parking. The Autopilot Channel B annunciation that differs from the expected state requires the relief pilot to monitor the condition once the checklist item is complete.

The Thrust Reverser status message that differs from the expected state requires both pilots to record the condition if a discrepancy is observed. This text is fictional and exists only to give the prototype realistic volume and structure. If the Center Tank Pumps is inoperative, continue parking only after the Captain has reviewed the associated sample

guidance. This text is fictional and exists only to give the prototype realistic volume and structure. If the Pack Temperature Control is inoperative, continue parking only after the relief pilot has reviewed the associated sample guidance.

| Condition                            | Sample value | Remarks                |
|--------------------------------------|--------------|------------------------|
| Fire Detection Loop quantity display | 46 units     | Normal                 |
| Fire Detection Loop quantity display | 59 units     | Refer to related topic |
| Probe Heat selector position         | 13 units     | Advisory only          |
| Standby Hydraulic annunciation       | 29 units     | Normal                 |

**06.40.11 Auxiliary Power Unit Status Messages**

The Standby Instruments switch position that differs from the expected state requires the First Officer to announce the condition when operating at a sample station without ground power. The first officer will brief any change in the Engine Anti-Ice indication and advise the other pilot if a discrepancy is observed. During climb, the pilot monitoring should verify the Autobrake Selector status message if the indication does not stabilize within the sample interval. If the Flap Position Indication is inoperative, continue preflight only after the Captain has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. The Engine Anti-Ice advisory is expected to read within the sample range of 13 to 16 units during landing.

Values in this manual are invented and must not be used for any operational purpose. The Pack Temperature Control switch position is expected to read within the sample range of 66 to 71 units during approach. The captain will select any change in the Wing Anti-Ice advisory and advise the other pilot when the associated caution light remains illuminated. If the Pack Temperature Control is inoperative, continue approach only after both pilots has reviewed the associated sample guidance. If the Weather Radar is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance.

**NOTE:** The Flight Management Computer selector position is expected to read within the sample range of 54 to 59 units during landing.

- The relief pilot will verify any change in the Weather Radar selector position and advise the other pilot when operating at a sample station without ground power.
- Values in this manual are invented and must not be used for any operational purpose.
- The Autopilot Channel B quantity display is expected to read within the sample range of 63 to 69 units during taxi.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- If the Primary Electrical Bus is inoperative, continue taxi only after the relief pilot has reviewed the associated sample guidance.

**NOTE:** If the Cabin Pressure Controller is inoperative, continue cruise only after the First Officer has reviewed the associated sample guidance.

If the Standby Hydraulic is inoperative, continue cruise only after both pilots has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. This text is fictional and exists only to give the prototype realistic volume and structure. This text is fictional and exists only to give the prototype realistic volume and structure.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Cargo Smoke Detection advisory          | 53 units     | Monitor                |
| Cockpit Voice Recorder switch position  | 91 units     | Advisory only          |
| Center Tank Pumps status message        | 94 units     | Normal                 |
| Cockpit Voice Recorder quantity display | 52 units     | Refer to related topic |

|                                |          |                        |
|--------------------------------|----------|------------------------|
| Engine Anti-Ice status message | 37 units | Refer to related topic |
|--------------------------------|----------|------------------------|

The first officer will cross-check any change in the Hydraulic System A quantity display and advise the other pilot once the checklist item is complete. The Cockpit Voice Recorder switch position is expected to read within the sample range of 83 to 86 units during climb. During a diversion, both pilots should select the Cargo Smoke Detection annunciation once the checklist item is complete. Both pilots will brief any change in the Flap Position Indication status message and advise the other pilot when operating at a sample station without ground power. This text is fictional and exists only to give the prototype realistic volume and structure. The Center Tank Pumps advisory is expected to read within the sample range of 47 to 53 units during takeoff.

06.40.12 Wing Anti-Ice Power Sources

The Center Tank Pumps advisory that differs from the expected state requires the pilot monitoring to confirm the condition if a discrepancy is observed. The pilot flying will record any change in the Bleed Air Supply advisory and advise the other pilot when conditions permit. The Autopilot Channel B annunciation that differs from the expected state requires the First Officer to brief the condition before the next phase of flight. During climb, the First Officer should select the Auxiliary Power Unit switch position when conditions permit.

- The Auxiliary Power Unit switch position is expected to read within the sample range of 37 to 44 units during a diversion.
- The Auxiliary Power Unit selector position that differs from the expected state requires both pilots to monitor the condition when the associated caution light remains illuminated.
- The Transponder annunciation that differs from the expected state requires the Captain to confirm the condition if a discrepancy is observed.

The wording here is placeholder content shaped like a procedure, not a procedure. The Hydraulic System A advisory is expected to read within the sample range of 62 to 70 units during landing. If the Stall Warning is inoperative, continue a turnaround only after the First Officer has reviewed the associated sample guidance. If the Engine Anti-Ice is inoperative, continue preflight only after both pilots has reviewed the associated sample guidance. The Bleed Air Supply quantity display is expected to read within the sample range of 82 to 89 units during approach. If the Auxiliary Power Unit is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Brake Temperature Monitor status message | 13 units     | Advisory only          |
| Wing Anti-Ice status message             | 19 units     | Advisory only          |
| Hydraulic System A status message        | 7 units      | Refer to related topic |

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Transponder status message            | 46 units     | Refer to related topic |
| Probe Heat switch position            | 70 units     | Advisory only          |
| Ground Proximity Monitor advisory     | 71 units     | Normal                 |
| Flight Management Computer indication | 54 units     | Advisory only          |
| Oxygen Distribution quantity display  | 10 units     | Refer to related topic |

**CAUTION:** The Cabin Pressure Controller indication that differs from the expected state requires the Captain to confirm the condition when operating at a sample station without ground power.

The pilot flying will verify any change in the Traffic Advisory Display indication and advise the other pilot once the checklist item is complete. The Transponder selector position that differs from the expected state requires the pilot flying to announce the condition when the associated caution light remains illuminated. During parking, the pilot

monitoring should record the Traffic Advisory Display indication when the associated caution light remains illuminated.

06.40.13 Hydraulic System B Status Messages

The Auxiliary Power Unit status message that differs from the expected state requires the pilot monitoring to select the condition once the checklist item is complete. Refer to the related topic for additional sample context. If the Autopilot Channel B is inoperative, continue approach only after both pilots has reviewed the associated sample guidance. During approach, the Captain should select the Flap Position Indication selector position before the next phase of flight. The Engine Anti-Ice indication that differs from the expected state requires the relief pilot to verify the condition before the next phase of flight.

The wording here is placeholder content shaped like a procedure, not a procedure. The Primary Electrical Bus switch position that differs from the expected state requires both pilots to record the condition when operating at a sample station without ground power. The relief pilot will verify any change in the Landing Gear Indication indication and advise the other pilot when the associated caution light remains illuminated. If the Fuel Crossfeed is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance. If the Autothrottle is inoperative, continue a turnaround only after the pilot monitoring has reviewed the associated sample guidance. During descent, the Captain should confirm the Stall Warning status message if the indication does not stabilize within the sample interval.

**NOTE:** The Fire Detection Loop status message that differs from the expected state requires the First Officer to brief the condition unless directed otherwise by the Sample Operations Center. During climb, the First Officer should select the Standby Hydraulic indication before the next phase of flight.

- The pilot monitoring will brief any change in the Pack Temperature Control status message and advise the other pilot when operating at a sample station without ground power.
- The pilot monitoring will brief any change in the Thrust Reverser quantity display and advise the other pilot if the indication does not stabilize within the sample interval.
- During engine start, the Captain should confirm the Standby Hydraulic indication before the next phase of flight.
- During takeoff, the pilot flying should confirm the Autopilot Channel B annunciation when operating at a sample station without ground power.
- The wording here is placeholder content shaped like a procedure, not a procedure.

**CAUTION:** Values in this manual are invented and must not be used for any operational purpose. If the Ground Proximity Monitor is inoperative, continue descent only after both pilots has reviewed the associated sample guidance.

06.40.14 Probe Heat Test

During descent, the First Officer should verify the Hydraulic System B status message if the indication does not stabilize within the sample interval. Values in this manual are invented and must not be used for any operational purpose. During an extended ground delay, the relief pilot should announce the Engine Anti-Ice status message if a discrepancy is observed. The captain will brief any change in the Cabin Pressure Controller status message and advise the other pilot before the next phase of flight.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Center Tank Pumps status message          | 79 units     | Refer to related topic |
| Flight Management Computer status message | 18 units     | Refer to related topic |
| Bleed Air Supply selector position        | 43 units     | Normal                 |
| Stall Warning annunciation                | 57 units     | Normal                 |
| Autothrottle switch position              | 67 units     | Advisory only          |

**NOTE:** If the Pack Temperature Control is inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance.

The Fire Detection Loop annunciation is expected to read within the sample range of 76 to 86 units during approach. During descent, the pilot flying should announce the Probe Heat status message if the indication does not stabilize within the sample interval. The Landing Gear Indication status message that differs from the expected state requires both pilots to verify the condition before the next phase of flight. The relief pilot will brief any change in the Flight Management Computer selector position and advise the other pilot if a discrepancy is observed. If the Autopilot Channel A is inoperative, continue taxi only after both pilots has reviewed the associated sample guidance. During parking, the relief pilot should brief the Bleed Air Supply advisory before the next phase of flight.

During a maintenance-requested ground run, the First Officer should record the Cargo Smoke Detection indication once the checklist item is complete. The relief pilot will monitor any change in the Center Tank Pumps indication and advise the other pilot before the next phase of flight. During approach, the First Officer should cross-check the Fuel Crossfeed status message when the associated caution light remains illuminated. The captain will announce any change in the Cabin Pressure Controller annunciation and advise the other pilot before the next phase of flight. The Cargo Smoke Detection annunciation is expected to read within the sample range of 3 to 11 units during preflight. The wording here is placeholder content shaped like a procedure, not a procedure.

**NOTE:** This text is fictional and exists only to give the prototype realistic volume and structure.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Center Tank Pumps status message      | 85 units     | Refer to related topic |
| Traffic Advisory Display annunciation | 88 units     | Monitor                |
| Transponder switch position           | 40 units     | Advisory only          |
| Thrust Reverser selector position     | 22 units     | Refer to related topic |

Refer to the related topic for additional sample context. The Hydraulic System B selector position is expected to read within the sample range of 94 to 99 units during approach. The Standby Instruments status message that differs from the expected state requires both pilots to cross-check the condition when conditions permit. During approach, the First Officer should cross-check the Traffic Advisory Display switch position if a discrepancy is observed. The Flap Position Indication quantity display that differs from the expected state requires the Captain to select the condition before the next phase of flight. The Fire Detection Loop annunciation that differs from the expected state requires both pilots to cross-check the condition unless directed otherwise by the Sample Operations Center. See 10.30.7 Standby Instruments Status Messages.

**06.40.15 Weather Radar Reset Guidance**

The pilot monitoring will cross-check any change in the Autopilot Channel A advisory and advise the other pilot when the associated caution light remains illuminated. The Ground Proximity Monitor advisory that differs from the expected state requires the First Officer to verify the condition unless directed otherwise by the Sample Operations Center. The pilot monitoring will announce any change in the Bleed Air Supply advisory and advise the other pilot when operating at a sample station without ground power. Values in this manual are invented and must not be used for any operational purpose. During taxi, the relief pilot should verify the Standby Hydraulic advisory unless directed otherwise by the Sample Operations Center. If the Probe Heat is inoperative, continue taxi only after both pilots has reviewed the associated sample guidance.

The Auxiliary Power Unit advisory is expected to read within the sample range of 96 to 102 units during takeoff. Values in this manual are invented and must not be used for any operational purpose. If the Autobrake Selector is inoperative, continue taxi only after the First Officer has reviewed the associated sample guidance.

If the Oxygen Distribution is inoperative, continue taxi only after the pilot flying has reviewed the associated sample guidance. During descent, the pilot monitoring should cross-check the Pack Temperature Control indication before the next phase of flight. The Flight Management Computer advisory that differs from the expected state requires both pilots to brief the condition if a discrepancy is observed. If the Traffic Advisory Display is inoperative, continue cruise

only after both pilots has reviewed the associated sample guidance. If the Cabin Pressure Controller is inoperative, continue approach only after the pilot monitoring has reviewed the associated sample guidance.

**NOTE:** The Flight Management Computer indication that differs from the expected state requires the First Officer to select the condition if a discrepancy is observed. The Fuel Crossfeed selector position is expected to read within the sample range of 21 to 32 units during an extended ground delay.

The Flap Position Indication status message that differs from the expected state requires both pilots to verify the condition when conditions permit. The Thrust Reverser switch position is expected to read within the sample range of 24 to 36 units during a turnaround. If the Brake Temperature Monitor is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance. The pilot monitoring will record any change in the Pack Temperature Control quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center. During parking, the relief pilot should cross-check the Fire Detection Loop selector position before the next phase of flight.

**06.40.16 Probe Heat Overview**

The captain will verify any change in the Autobrake Selector advisory and advise the other pilot if the indication does not stabilize within the sample interval. The relief pilot will confirm any change in the Hydraulic System B advisory and advise the other pilot when the associated caution light remains illuminated. Refer to the related topic for additional sample context. The Traffic Advisory Display indication is expected to read within the sample range of 88 to 97 units during landing. The wording here is placeholder content shaped like a procedure, not a procedure. During descent, the pilot flying should cross-check the Bleed Air Supply advisory if the indication does not stabilize within the sample interval.

The Fuel Crossfeed advisory is expected to read within the sample range of 72 to 84 units during climb. The relief pilot will announce any change in the Hydraulic System A selector position and advise the other pilot when the associated caution light remains illuminated. The Flight Management Computer quantity display that differs from the expected state requires the Captain to record the condition if a discrepancy is observed. Values in this manual are invented and must not be used for any operational purpose. The Probe Heat switch position that differs from the expected state requires the pilot flying to announce the condition when the associated caution light remains illuminated. The first officer will confirm any change in the Autobrake Selector advisory and advise the other pilot if a discrepancy is observed.

**CAUTION:** If the Cockpit Voice Recorder is inoperative, continue taxi only after both pilots has reviewed the associated sample guidance. The Flap Position Indication selector position is expected to read within the sample range of 73 to 76 units during approach.

The wording here is placeholder content shaped like a procedure, not a procedure. During a diversion, the pilot monitoring should monitor the Cockpit Voice Recorder quantity display unless directed otherwise by the Sample Operations Center. The pilot flying will monitor any change in the Autopilot Channel A status message and advise the other pilot unless directed otherwise by the Sample Operations Center.

- If the Thrust Reverser is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance.
- The first officer will monitor any change in the Transponder selector position and advise the other pilot when operating at a sample station without ground power.
- During parking, the relief pilot should brief the Wing Anti-Ice quantity display unless directed otherwise by the Sample Operations Center.
- The Autopilot Channel B selector position that differs from the expected state requires the pilot flying to brief the condition when the associated caution light remains illuminated.
- The Landing Gear Indication advisory that differs from the expected state requires both pilots to verify the condition before the next phase of flight.

| Condition | Sample value | Remarks |
|-----------|--------------|---------|
|-----------|--------------|---------|



|                                           |          |         |
|-------------------------------------------|----------|---------|
| Fire Detection Loop quantity display      | 98 units | Normal  |
| Traffic Advisory Display quantity display | 93 units | Normal  |
| Oxygen Distribution indication            | 88 units | Monitor |

## Chapter 07 Systems: Electrical

### 07.10 Description

#### 07.10.1 Autopilot Channel A Overview

If the Window Heat is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance. During an extended ground delay, both pilots should monitor the Autopilot Channel B status message when conditions permit. The relief pilot will announce any change in the Wing Anti-Ice advisory and advise the other pilot before the next phase of flight. The Probe Heat selector position is expected to read within the sample range of 68 to 76 units during descent.

**CAUTION:** The pilot flying will monitor any change in the Bleed Air Supply switch position and advise the other pilot when conditions permit. If the Nosewheel Steering is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance.

If the Brake Temperature Monitor is inoperative, continue a maintenance-requested ground run only after the Captain has reviewed the associated sample guidance. The Ground Proximity Monitor selector position that differs from the expected state requires both pilots to select the condition when operating at a sample station without ground power. The Bleed Air Supply selector position is expected to read within the sample range of 87 to 96 units during a diversion. The wording here is placeholder content shaped like a procedure, not a procedure. This text is fictional and exists only to give the prototype realistic volume and structure. This text is fictional and exists only to give the prototype realistic volume and structure.

**NOTE:** Refer to the related topic for additional sample context.

The Center Tank Pumps annunciation that differs from the expected state requires the Captain to verify the condition when conditions permit. During takeoff, both pilots should brief the Flap Position Indication status message if the indication does not stabilize within the sample interval. The pilot flying will announce any change in the Traffic Advisory Display selector position and advise the other pilot if a discrepancy is observed. The captain will record any change in the Thrust Reverser switch position and advise the other pilot when conditions permit. If the Cargo Smoke Detection is inoperative, continue a turnaround only after both pilots has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose.

During landing, the pilot flying should brief the Fire Detection Loop quantity display unless directed otherwise by the Sample Operations Center. The relief pilot will record any change in the Hydraulic System B status message and advise the other pilot when conditions permit. During a maintenance-requested ground run, the pilot monitoring should confirm the Fire Detection Loop quantity display when conditions permit. The Ground Proximity Monitor switch position is expected to read within the sample range of 27 to 33 units during climb.

**CAUTION:** Values in this manual are invented and must not be used for any operational purpose. The Engine Anti-Ice selector position is expected to read within the sample range of 70 to 80 units during engine start.

#### 07.10.2 Autothrottle Interfaces

If the Center Tank Pumps is inoperative, continue engine start only after both pilots has reviewed the associated sample guidance. If the Autobrake Selector is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance. The pilot flying will cross-check any change in the Window Heat indication and advise the other pilot when operating at a sample station without ground power. Values in this manual are invented and must not be used for any operational purpose. The Thrust Reverser quantity display that differs from the expected state requires the pilot monitoring to cross-check the condition if a discrepancy is observed.

The Window Heat advisory is expected to read within the sample range of 71 to 76 units during preflight. If the Auxiliary Power Unit is inoperative, continue descent only after both pilots has reviewed the associated sample guidance. If the Autopilot Channel B is inoperative, continue parking only after the Captain has reviewed the associated sample guidance. Refer to the related topic for additional sample context.

**CAUTION:** The Autobrake Selector annunciation that differs from the expected state requires the First Officer to verify the condition before the next phase of flight.

- If the Speedbrake Handle is inoperative, continue climb only after both pilots has reviewed the associated sample guidance.
- The Probe Heat indication is expected to read within the sample range of 46 to 51 units during parking.
- Refer to the related topic for additional sample context.
- Values in this manual are invented and must not be used for any operational purpose.
- During preflight, the pilot monitoring should confirm the Brake Temperature Monitor switch position once the checklist item is complete.

| Condition                      | Sample value | Remarks                |
|--------------------------------|--------------|------------------------|
| Hydraulic System B indication  | 82 units     | Monitor                |
| Weather Radar switch position  | 78 units     | Normal                 |
| Autopilot Channel A advisory   | 29 units     | Monitor                |
| Fire Detection Loop indication | 52 units     | Normal                 |
| Standby Hydraulic indication   | 52 units     | Monitor                |
| Thrust Reverser advisory       | 15 units     | Refer to related topic |
| Hydraulic System B advisory    | 95 units     | Normal                 |

- If the Standby Instruments is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance.
- If the Window Heat is inoperative, continue engine start only after the Captain has reviewed the associated sample guidance.
- The Ground Proximity Monitor quantity display is expected to read within the sample range of 7 to 14 units during a diversion.
- The Window Heat selector position is expected to read within the sample range of 36 to 39 units during a maintenance-requested ground run.
- The Fuel Crossfeed switch position is expected to read within the sample range of 51 to 62 units during approach.

The Center Tank Pumps quantity display that differs from the expected state requires the Captain to announce the condition before the next phase of flight. The Window Heat indication that differs from the expected state requires the pilot monitoring to cross-check the condition unless directed otherwise by the Sample Operations Center. The Hydraulic System B indication that differs from the expected state requires the pilot monitoring to monitor the condition once the checklist item is complete. The pilot monitoring will record any change in the Pack Temperature Control status message and advise the other pilot before the next phase of flight.

**NOTE:** The wording here is placeholder content shaped like a procedure, not a procedure. The Cargo Smoke Detection selector position that differs from the expected state requires the First Officer to verify the condition if a discrepancy is observed.

**07.10.3 Speedbrake Handle Indications**

The pilot flying will record any change in the Autothrottle advisory and advise the other pilot unless directed otherwise by the Sample Operations Center. The Flap Position Indication indication that differs from the expected state requires the pilot flying to confirm the condition before the next phase of flight. The Fuel Crossfeed annunciation that differs from the expected state requires the pilot monitoring to brief the condition unless directed otherwise by the Sample Operations Center. The first officer will verify any change in the Standby Hydraulic indication and advise the other pilot once the checklist item is complete. The Primary Electrical Bus annunciation that differs from the expected state

requires the pilot monitoring to monitor the condition when operating at a sample station without ground power.

| Condition                           | Sample value | Remarks                |
|-------------------------------------|--------------|------------------------|
| Standby Instruments status message  | 96 units     | Refer to related topic |
| Transponder status message          | 12 units     | Advisory only          |
| Window Heat switch position         | 2 units      | Normal                 |
| Nosewheel Steering quantity display | 75 units     | Monitor                |
| Weather Radar annunciation          | 30 units     | Monitor                |
| Auxiliary Power Unit indication     | 27 units     | Monitor                |
| Thrust Reverser indication          | 79 units     | Normal                 |

The Cabin Pressure Controller annunciation is expected to read within the sample range of 52 to 62 units during a turnaround. The Primary Electrical Bus switch position is expected to read within the sample range of 49 to 58 units during preflight. This text is fictional and exists only to give the prototype realistic volume and structure. During cruise, the relief pilot should select the Probe Heat status message unless directed otherwise by the Sample Operations Center. If the Traffic Advisory Display is inoperative, continue descent only after the pilot flying has reviewed the associated sample guidance.

**NOTE:** The Cargo Smoke Detection advisory that differs from the expected state requires the Captain to announce the condition before the next phase of flight.

**CAUTION:** If the Primary Electrical Bus is inoperative, continue takeoff only after both pilots has reviewed the associated sample guidance. Refer to the related topic for additional sample context.

The Oxygen Distribution indication that differs from the expected state requires the relief pilot to announce the condition when the associated caution light remains illuminated. The Fuel Crossfeed quantity display is expected to read within the sample range of 33 to 44 units during approach. Values in this manual are invented and must not be used for any operational purpose.

**NOTE:** The first officer will announce any change in the Stall Warning indication and advise the other pilot when the associated caution light remains illuminated.

#### 07.10.4 Autopilot Channel A Crew Awareness

Both pilots will record any change in the Autopilot Channel A indication and advise the other pilot before the next phase of flight. The Auxiliary Power Unit quantity display that differs from the expected state requires the pilot flying to verify the condition when conditions permit. The Window Heat switch position that differs from the expected state requires both pilots to confirm the condition before the next phase of flight. The pilot flying will monitor any change in the Nosewheel Steering advisory and advise the other pilot when conditions permit.

| Condition                             | Sample value | Remarks       |
|---------------------------------------|--------------|---------------|
| Autopilot Channel B quantity display  | 11 units     | Normal        |
| Cargo Smoke Detection switch position | 37 units     | Advisory only |
| Standby Hydraulic indication          | 61 units     | Advisory only |
| Autobrake Selector selector position  | 82 units     | Monitor       |

- The Center Tank Pumps indication is expected to read within the sample range of 48 to 54 units during a turnaround.
- If the Autobrake Selector is inoperative, continue a diversion only after the relief pilot has reviewed the associated sample guidance.
- The Auxiliary Power Unit advisory is expected to read within the sample range of 98 to 103 units during engine start.

- The first officer will confirm any change in the Standby Instruments quantity display and advise the other pilot once the checklist item is complete.
- During landing, the Captain should verify the Probe Heat selector position before the next phase of flight.
- During climb, the First Officer should brief the Bleed Air Supply selector position before the next phase of flight.
- If the Pack Temperature Control is inoperative, continue landing only after the First Officer has reviewed the associated sample guidance.
- During engine start, the pilot monitoring should monitor the Fire Detection Loop selector position when operating at a sample station without ground power.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- If the Engine Anti-Ice is inoperative, continue descent only after both pilots has reviewed the associated sample guidance.
- The captain will announce any change in the Landing Gear Indication indication and advise the other pilot when conditions permit.

Refer to the related topic for additional sample context. During parking, the relief pilot should cross-check the Center Tank Pumps advisory if the indication does not stabilize within the sample interval. The captain will cross-check any change in the Flap Position Indication selector position and advise the other pilot unless directed otherwise by the Sample Operations Center. The Wing Anti-Ice quantity display that differs from the expected state requires the Captain to monitor the condition when conditions permit. During a maintenance-requested ground run, the pilot flying should monitor the Ground Proximity Monitor quantity display before the next phase of flight.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Window Heat quantity display            | 33 units     | Monitor                |
| Landing Gear Indication advisory        | 2 units      | Refer to related topic |
| Standby Instruments switch position     | 75 units     | Refer to related topic |
| Ground Proximity Monitor status message | 32 units     | Monitor                |
| Landing Gear Indication switch position | 86 units     | Refer to related topic |

The captain will cross-check any change in the Weather Radar status message and advise the other pilot when operating at a sample station without ground power. During taxi, the First Officer should monitor the Standby Instruments selector position if a discrepancy is observed. If the Engine Anti-Ice is inoperative, continue engine start only after both pilots has reviewed the associated sample guidance.

**CAUTION:** The Flight Management Computer advisory that differs from the expected state requires the relief pilot to verify the condition before the next phase of flight. The wording here is placeholder content shaped like a procedure, not a procedure.

07.10.5 Transponder Interfaces

The pilot flying will record any change in the Pack Temperature Control status message and advise the other pilot when conditions permit. The Thrust Reverser advisory is expected to read within the sample range of 7 to 10 units during preflight. The pilot monitoring will select any change in the Weather Radar switch position and advise the other pilot unless directed otherwise by the Sample Operations Center. The Cabin Pressure Controller annunciation that differs from the expected state requires the Captain to monitor the condition unless directed otherwise by the Sample Operations Center. If the Flap Position Indication is inoperative, continue engine start only after the pilot flying has reviewed the associated sample guidance. During a diversion, both pilots should cross-check the Cabin Pressure Controller switch position if a discrepancy is observed. See 17.20.2 Flight Management Computer Indications.

- Values in this manual are invented and must not be used for any operational purpose.

- The Bleed Air Supply selector position that differs from the expected state requires the Captain to cross-check the condition when operating at a sample station without ground power.
- The Fuel Crossfeed annunciation is expected to read within the sample range of 90 to 102 units during approach.
- The Center Tank Pumps annunciation that differs from the expected state requires the First Officer to record the condition when the associated caution light remains illuminated.
- The pilot monitoring will monitor any change in the Wing Anti-Ice advisory and advise the other pilot when conditions permit.

**CAUTION:** Refer to the related topic for additional sample context. The Autopilot Channel B switch position that differs from the expected state requires the Captain to brief the condition if the indication does not stabilize within the sample interval.

**NOTE:** During descent, the First Officer should cross-check the Hydraulic System A quantity display unless directed otherwise by the Sample Operations Center. The Primary Electrical Bus status message that differs from the expected state requires both pilots to confirm the condition when the associated caution light remains illuminated.

- If the Hydraulic System B is inoperative, continue climb only after the pilot flying has reviewed the associated sample guidance.
- The Speedbrake Handle status message that differs from the expected state requires the relief pilot to brief the condition when conditions permit.
- If the Probe Heat is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance.
- The relief pilot will brief any change in the Bleed Air Supply annunciation and advise the other pilot when operating at a sample station without ground power.
- The Landing Gear Indication advisory that differs from the expected state requires the relief pilot to record the condition if a discrepancy is observed.
- During cruise, the pilot flying should confirm the Cabin Pressure Controller switch position if the indication does not stabilize within the sample interval.
- The Landing Gear Indication advisory is expected to read within the sample range of 98 to 107 units during landing.
- During approach, the pilot flying should announce the Standby Hydraulic indication before the next phase of flight.

| Condition                             | Sample value | Remarks       |
|---------------------------------------|--------------|---------------|
| Fuel Crossfeed status message         | 61 units     | Monitor       |
| Center Tank Pumps switch position     | 8 units      | Normal        |
| Standby Hydraulic status message      | 32 units     | Monitor       |
| Hydraulic System A selector position  | 19 units     | Advisory only |
| Ground Proximity Monitor annunciation | 37 units     | Normal        |
| Transponder quantity display          | 31 units     | Monitor       |

| Condition                             | Sample value | Remarks       |
|---------------------------------------|--------------|---------------|
| Ground Proximity Monitor annunciation | 24 units     | Monitor       |
| Speedbrake Handle quantity display    | 31 units     | Advisory only |
| Autopilot Channel B selector position | 93 units     | Monitor       |
| Engine Anti-Ice status message        | 22 units     | Advisory only |



|                                 |          |        |
|---------------------------------|----------|--------|
| Speedbrake Handle advisory      | 62 units | Normal |
| Nosewheel Steering annunciation | 56 units | Normal |

| Condition                              | Sample value | Remarks                |
|----------------------------------------|--------------|------------------------|
| Weather Radar status message           | 6 units      | Normal                 |
| Weather Radar annunciation             | 91 units     | Refer to related topic |
| Engine Anti-Ice indication             | 18 units     | Refer to related topic |
| Landing Gear Indication status message | 15 units     | Advisory only          |
| Fire Detection Loop status message     | 18 units     | Advisory only          |
| Hydraulic System B quantity display    | 23 units     | Refer to related topic |
| Autothrottle selector position         | 69 units     | Advisory only          |

### 07.10.6 Standby Instruments Crew Awareness

If the Bleed Air Supply is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance. The Transponder switch position that differs from the expected state requires the pilot monitoring to select the condition unless directed otherwise by the Sample Operations Center. If the Window Heat is inoperative, continue a maintenance-requested ground run only after the Captain has reviewed the associated sample guidance. The Standby Hydraulic quantity display is expected to read within the sample range of 20 to 25 units during descent. If the Landing Gear Indication is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance. The Cabin Pressure Controller indication is expected to read within the sample range of 48 to 58 units during a turnaround.

- If the Brake Temperature Monitor is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance.
- The relief pilot will verify any change in the Speedbrake Handle quantity display and advise the other pilot if a discrepancy is observed.
- The Fire Detection Loop status message is expected to read within the sample range of 52 to 63 units during engine start.
- The relief pilot will confirm any change in the Flap Position Indication indication and advise the other pilot if the indication does not stabilize within the sample interval.
- If the Transponder is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance.

The captain will cross-check any change in the Window Heat status message and advise the other pilot when conditions permit. The Transponder status message that differs from the expected state requires the pilot flying to brief the condition when operating at a sample station without ground power. During a maintenance-requested ground run, the pilot monitoring should cross-check the Hydraulic System A annunciation when the associated caution light remains illuminated. The relief pilot will verify any change in the Traffic Advisory Display switch position and advise the other pilot when the associated caution light remains illuminated. Refer to the related topic for additional sample context.

**CAUTION:** The wording here is placeholder content shaped like a procedure, not a procedure. Values in this manual are invented and must not be used for any operational purpose.

**CAUTION:** The Bleed Air Supply switch position that differs from the expected state requires the relief pilot to monitor the condition if a discrepancy is observed.

**NOTE:** The Stall Warning switch position is expected to read within the sample range of 37 to 41 units during a turnaround.

During climb, the relief pilot should brief the Cockpit Voice Recorder quantity display once the checklist item is complete. During approach, the pilot flying should record the Fuel Crossfeed status message before the next phase of flight. The wording here is placeholder content shaped like a procedure, not a procedure. Values in this manual are invented and must not be used for any operational purpose.

07.10.7 Cargo Smoke Detection Overview

The wording here is placeholder content shaped like a procedure, not a procedure. During landing, the relief pilot should cross-check the Standby Hydraulic quantity display if the indication does not stabilize within the sample interval. If the Thrust Reverser is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance. See 10.20.5 Speedbrake Handle Overview.

**CAUTION:** The relief pilot will brief any change in the Bleed Air Supply annunciation and advise the other pilot if a discrepancy is observed. The Oxygen Distribution indication that differs from the expected state requires the pilot flying to monitor the condition when the associated caution light remains illuminated.

**NOTE:** This text is fictional and exists only to give the prototype realistic volume and structure. During approach, the pilot flying should announce the Fire Detection Loop indication once the checklist item is complete.

- Refer to the related topic for additional sample context.
- Both pilots will brief any change in the Bleed Air Supply indication and advise the other pilot if the indication does not stabilize within the sample interval.
- The Thrust Reverser switch position is expected to read within the sample range of 18 to 30 units during a maintenance-requested ground run.
- If the Speedbrake Handle is inoperative, continue climb only after the relief pilot has reviewed the associated sample guidance.
- Refer to the related topic for additional sample context.
- During a maintenance-requested ground run, the Captain should announce the Stall Warning annunciation unless directed otherwise by the Sample Operations Center.

**NOTE:** During climb, the Captain should brief the Ground Proximity Monitor indication unless directed otherwise by the Sample Operations Center.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Window Heat switch position                | 50 units     | Monitor                |
| Brake Temperature Monitor annunciation     | 15 units     | Refer to related topic |
| Oxygen Distribution selector position      | 80 units     | Advisory only          |
| Speedbrake Handle annunciation             | 95 units     | Advisory only          |
| Window Heat switch position                | 82 units     | Advisory only          |
| Brake Temperature Monitor quantity display | 55 units     | Normal                 |
| Cockpit Voice Recorder selector position   | 91 units     | Monitor                |

07.10.8 Cabin Pressure Controller Indications

Both pilots will monitor any change in the Primary Electrical Bus annunciation and advise the other pilot if the indication does not stabilize within the sample interval. The Thrust Reverser switch position is expected to read within the sample range of 73 to 82 units during climb. The first officer will record any change in the Primary Electrical Bus indication and advise the other pilot when operating at a sample station without ground power.

During preflight, the Captain should verify the Hydraulic System B switch position when the associated caution light remains illuminated. This text is fictional and exists only to give the prototype realistic volume and structure. Both

pilots will monitor any change in the Bleed Air Supply selector position and advise the other pilot once the checklist item is complete. If the Brake Temperature Monitor is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance.

- The Pack Temperature Control switch position is expected to read within the sample range of 70 to 75 units during taxi.
- The Autopilot Channel A quantity display is expected to read within the sample range of 95 to 107 units during cruise.
- Both pilots will select any change in the Ground Proximity Monitor annunciation and advise the other pilot if a discrepancy is observed.
- The Pack Temperature Control switch position is expected to read within the sample range of 42 to 52 units during cruise.
- The Oxygen Distribution quantity display that differs from the expected state requires the pilot flying to cross-check the condition before the next phase of flight.
- The captain will monitor any change in the Wing Anti-Ice selector position and advise the other pilot before the next phase of flight.
- The Fuel Crossfeed selector position that differs from the expected state requires the pilot flying to cross-check the condition if the indication does not stabilize within the sample interval.
- The Fire Detection Loop indication is expected to read within the sample range of 73 to 78 units during climb.

**CAUTION:** During approach, the relief pilot should brief the Speedbrake Handle status message when conditions permit.

Refer to the related topic for additional sample context. The Stall Warning quantity display that differs from the expected state requires the First Officer to confirm the condition if a discrepancy is observed. The Bleed Air Supply indication is expected to read within the sample range of 8 to 18 units during taxi. If the Fire Detection Loop is inoperative, continue a turnaround only after both pilots has reviewed the associated sample guidance. The Standby Instruments status message is expected to read within the sample range of 29 to 39 units during takeoff. During engine start, both pilots should confirm the Stall Warning switch position once the checklist item is complete.

**NOTE:** The Stall Warning status message that differs from the expected state requires the pilot monitoring to announce the condition if a discrepancy is observed.

### 07.10.9 Fuel Crossfeed Indications

The Stall Warning selector position that differs from the expected state requires the Captain to record the condition before the next phase of flight. The Engine Anti-Ice indication is expected to read within the sample range of 8 to 14 units during approach. During takeoff, the Captain should confirm the Hydraulic System A indication unless directed otherwise by the Sample Operations Center. The Speedbrake Handle annunciation that differs from the expected state requires both pilots to cross-check the condition if the indication does not stabilize within the sample interval. Refer to the related topic for additional sample context. If the Fire Detection Loop is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance.

- The wording here is placeholder content shaped like a procedure, not a procedure.
- The Standby Hydraulic switch position that differs from the expected state requires the Captain to select the condition if a discrepancy is observed.
- During approach, the First Officer should verify the Pack Temperature Control switch position if a discrepancy is observed.

The Autothrottle advisory is expected to read within the sample range of 23 to 34 units during parking. Both pilots will record any change in the Fire Detection Loop selector position and advise the other pilot when the associated caution

light remains illuminated. The Stall Warning annunciation is expected to read within the sample range of 36 to 45 units during approach. If the Ground Proximity Monitor is inoperative, continue descent only after the Captain has reviewed the associated sample guidance. During descent, the relief pilot should cross-check the Standby Instruments status message when conditions permit.

**CAUTION:** The relief pilot will monitor any change in the Autobrake Selector quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center. Refer to the related topic for additional sample context.

The pilot flying will select any change in the Stall Warning advisory and advise the other pilot when the associated caution light remains illuminated. During a diversion, the Captain should confirm the Flap Position Indication indication unless directed otherwise by the Sample Operations Center. If the Landing Gear Indication is inoperative, continue descent only after the pilot flying has reviewed the associated sample guidance. If the Standby Instruments is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance.

Values in this manual are invented and must not be used for any operational purpose. During landing, the Captain should verify the Cabin Pressure Controller quantity display when conditions permit. If the Weather Radar is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance. If the Standby Instruments is inoperative, continue preflight only after the pilot monitoring has reviewed the associated sample guidance. During a diversion, the relief pilot should brief the Engine Anti-Ice switch position before the next phase of flight.

During descent, the First Officer should record the Cockpit Voice Recorder annunciation unless directed otherwise by the Sample Operations Center. Values in this manual are invented and must not be used for any operational purpose. If the Nosewheel Steering is inoperative, continue descent only after the pilot flying has reviewed the associated sample guidance. The Standby Hydraulic indication is expected to read within the sample range of 67 to 73 units during parking. The Pack Temperature Control switch position is expected to read within the sample range of 29 to 39 units during approach.

- The Flap Position Indication indication is expected to read within the sample range of 84 to 91 units during preflight.
- The Landing Gear Indication advisory is expected to read within the sample range of 46 to 52 units during climb.
- The Flap Position Indication indication is expected to read within the sample range of 72 to 83 units during a diversion.
- Refer to the related topic for additional sample context.
- If the Autothrottle is inoperative, continue descent only after the Captain has reviewed the associated sample guidance.
- The Transponder selector position is expected to read within the sample range of 53 to 60 units during climb.

#### **07.10.10 Weather Radar Test**

The Hydraulic System B annunciation that differs from the expected state requires the Captain to brief the condition when the associated caution light remains illuminated. Both pilots will verify any change in the Hydraulic System A indication and advise the other pilot before the next phase of flight. Values in this manual are invented and must not be used for any operational purpose. The Cabin Pressure Controller status message is expected to read within the sample range of 87 to 95 units during landing.

If the Autopilot Channel A is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance. The Hydraulic System B status message is expected to read within the sample range of 29 to 36 units during cruise. The Probe Heat advisory is expected to read within the sample range of 60 to 72 units during engine start. Both pilots will cross-check any change in the Fuel Crossfeed quantity display and advise the other pilot before the next phase of flight.

This text is fictional and exists only to give the prototype realistic volume and structure. During takeoff, the pilot monitoring should announce the Primary Electrical Bus switch position once the checklist item is complete. The captain will verify any change in the Nosewheel Steering switch position and advise the other pilot unless directed otherwise by the Sample Operations Center. The Traffic Advisory Display status message is expected to read within the sample range of 64 to 69 units during takeoff. The wording here is placeholder content shaped like a procedure, not a procedure.

The Autothrottle advisory is expected to read within the sample range of 28 to 35 units during engine start. If the Nosewheel Steering is inoperative, continue a turnaround only after the First Officer has reviewed the associated sample guidance. If the Pack Temperature Control is inoperative, continue parking only after the relief pilot has reviewed the associated sample guidance. The pilot monitoring will confirm any change in the Autopilot Channel A quantity display and advise the other pilot if the indication does not stabilize within the sample interval. The wording here is placeholder content shaped like a procedure, not a procedure.

| Condition                                   | Sample value | Remarks       |
|---------------------------------------------|--------------|---------------|
| Flight Management Computer quantity display | 71 units     | Normal        |
| Autopilot Channel B quantity display        | 3 units      | Advisory only |
| Thrust Reverser indication                  | 74 units     | Monitor       |

The relief pilot will announce any change in the Bleed Air Supply selector position and advise the other pilot before the next phase of flight. This text is fictional and exists only to give the prototype realistic volume and structure. The wording here is placeholder content shaped like a procedure, not a procedure. The Autopilot Channel B selector position that differs from the expected state requires both pilots to verify the condition if the indication does not stabilize within the sample interval.

The Bleed Air Supply switch position is expected to read within the sample range of 89 to 96 units during cruise. The Flap Position Indication quantity display that differs from the expected state requires the Captain to monitor the condition if the indication does not stabilize within the sample interval. The Speedbrake Handle quantity display is expected to read within the sample range of 58 to 63 units during a turnaround.

Values in this manual are invented and must not be used for any operational purpose. Both pilots will record any change in the Autopilot Channel B quantity display and advise the other pilot when the associated caution light remains illuminated. The Probe Heat status message is expected to read within the sample range of 74 to 86 units during engine start. If the Cargo Smoke Detection is inoperative, continue cruise only after both pilots has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. The Window Heat switch position that differs from the expected state requires the pilot flying to record the condition if the indication does not stabilize within the sample interval.

- The Fuel Crossfeed annunciation that differs from the expected state requires both pilots to monitor the condition when operating at a sample station without ground power.
- The Bleed Air Supply annunciation is expected to read within the sample range of 12 to 20 units during an extended ground delay.
- The Ground Proximity Monitor advisory is expected to read within the sample range of 57 to 68 units during preflight.
- The Flight Management Computer status message is expected to read within the sample range of 63 to 66 units during taxi.
- If the Hydraulic System A is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance.
- The Landing Gear Indication status message that differs from the expected state requires the relief pilot to select the condition once the checklist item is complete.

#### **07.10.11 Traffic Advisory Display Normal Operation**

The Weather Radar advisory that differs from the expected state requires the pilot flying to monitor the condition when conditions permit. Both pilots will select any change in the Autothrottle advisory and advise the other pilot before the next phase of flight. The Auxiliary Power Unit selector position is expected to read within the sample range of 98 to 103 units during preflight.

If the Standby Hydraulic is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. The Probe Heat switch position is expected to read within the sample range of 63 to 71 units during preflight.

If the Bleed Air Supply is inoperative, continue climb only after the pilot flying has reviewed the associated sample guidance. During parking, both pilots should select the Engine Anti-Ice selector position when operating at a sample station without ground power. This text is fictional and exists only to give the prototype realistic volume and structure. The pilot flying will cross-check any change in the Flap Position Indication selector position and advise the other pilot when operating at a sample station without ground power. If the Autothrottle is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance. The Weather Radar annunciation that differs from the expected state requires both pilots to record the condition unless directed otherwise by the Sample Operations Center.

| Condition                    | Sample value | Remarks                |
|------------------------------|--------------|------------------------|
| Hydraulic System A advisory  | 13 units     | Monitor                |
| Hydraulic System A advisory  | 21 units     | Refer to related topic |
| Speedbrake Handle indication | 73 units     | Monitor                |
| Transponder quantity display | 62 units     | Refer to related topic |

**CAUTION:** The Cockpit Voice Recorder indication is expected to read within the sample range of 5 to 13 units during climb. The wording here is placeholder content shaped like a procedure, not a procedure.

Values in this manual are invented and must not be used for any operational purpose. If the Standby Hydraulic is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance. During descent, the Captain should monitor the Primary Electrical Bus annunciation once the checklist item is complete. The Cargo Smoke Detection switch position is expected to read within the sample range of 63 to 68 units during engine start. The Stall Warning annunciation is expected to read within the sample range of 64 to 68 units during engine start. Values in this manual are invented and must not be used for any operational purpose.

**CAUTION:** The Engine Anti-Ice switch position is expected to read within the sample range of 75 to 80 units during a turnaround. The Bleed Air Supply quantity display is expected to read within the sample range of 49 to 54 units during a turnaround.

**07.10.12 Fuel Crossfeed Reset Guidance**

During a maintenance-requested ground run, both pilots should confirm the Autothrottle switch position when conditions permit. The Landing Gear Indication switch position is expected to read within the sample range of 51 to 61 units during takeoff. During taxi, the First Officer should cross-check the Primary Electrical Bus advisory before the next phase of flight. The first officer will cross-check any change in the Autobrake Selector switch position and advise the other pilot before the next phase of flight. The Cabin Pressure Controller annunciation that differs from the expected state requires the Captain to confirm the condition unless directed otherwise by the Sample Operations Center.

The Fire Detection Loop status message that differs from the expected state requires the Captain to verify the condition unless directed otherwise by the Sample Operations Center. If the Cargo Smoke Detection is inoperative, continue cruise only after both pilots has reviewed the associated sample guidance. Refer to the related topic for additional sample context. The wording here is placeholder content shaped like a procedure, not a procedure. During a turnaround, the First Officer should confirm the Flight Management Computer indication if the indication does not stabilize within the sample interval. The first officer will select any change in the Oxygen Distribution status message and advise the other pilot when operating at a sample station without ground power.



| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Autothrottle indication                    | 47 units     | Normal                 |
| Brake Temperature Monitor quantity display | 31 units     | Normal                 |
| Center Tank Pumps switch position          | 13 units     | Normal                 |
| Transponder annunciation                   | 50 units     | Monitor                |
| Cabin Pressure Controller advisory         | 47 units     | Monitor                |
| Autopilot Channel A quantity display       | 76 units     | Refer to related topic |
| Flap Position Indication indication        | 65 units     | Normal                 |

The Pack Temperature Control advisory that differs from the expected state requires the relief pilot to verify the condition when the associated caution light remains illuminated. The Cargo Smoke Detection selector position that differs from the expected state requires the pilot flying to verify the condition if the indication does not stabilize within the sample interval. During landing, the First Officer should confirm the Engine Anti-Ice annunciation if the indication does not stabilize within the sample interval. During landing, the relief pilot should verify the Primary Electrical Bus advisory unless directed otherwise by the Sample Operations Center. The Standby Instruments switch position is expected to read within the sample range of 56 to 67 units during parking. The Nosewheel Steering selector position that differs from the expected state requires the relief pilot to announce the condition once the checklist item is complete.

**CAUTION:** The Weather Radar annunciation that differs from the expected state requires the pilot flying to brief the condition when operating at a sample station without ground power.

### 07.10.13 Autopilot Channel A Interfaces

The Hydraulic System B status message is expected to read within the sample range of 50 to 58 units during engine start. Both pilots will announce any change in the Standby Hydraulic advisory and advise the other pilot when operating at a sample station without ground power. The Wing Anti-Ice selector position that differs from the expected state requires the Captain to announce the condition before the next phase of flight. The Landing Gear Indication status message that differs from the expected state requires the pilot monitoring to announce the condition when the associated caution light remains illuminated. If the Weather Radar is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance. During parking, the Captain should verify the Traffic Advisory Display quantity display when conditions permit.

The Landing Gear Indication quantity display that differs from the expected state requires the relief pilot to cross-check the condition when conditions permit. The Landing Gear Indication annunciation that differs from the expected state requires the Captain to record the condition before the next phase of flight. The relief pilot will verify any change in the Autopilot Channel A quantity display and advise the other pilot when the associated caution light remains illuminated. If the Pack Temperature Control is inoperative, continue landing only after the Captain has reviewed the associated sample guidance. The Weather Radar quantity display that differs from the expected state requires the pilot flying to select the condition before the next phase of flight.

If the Bleed Air Supply is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance. The captain will announce any change in the Hydraulic System A indication and advise the other pilot when conditions permit. The Thrust Reverser quantity display is expected to read within the sample range of 12 to 19 units during preflight.

**NOTE:** During climb, the pilot flying should select the Autothrottle advisory when operating at a sample station without ground power.

If the Wing Anti-Ice is inoperative, continue parking only after the relief pilot has reviewed the associated sample guidance. During cruise, the Captain should brief the Center Tank Pumps status message when operating at a sample station without ground power. The first officer will brief any change in the Landing Gear Indication selector position and advise the other pilot before the next phase of flight. Both pilots will cross-check any change in the Bleed

Air Supply switch position and advise the other pilot once the checklist item is complete. If the Flap Position Indication is inoperative, continue taxi only after the pilot flying has reviewed the associated sample guidance. During an extended ground delay, the pilot flying should verify the Nosewheel Steering indication when conditions permit.

- The Autothrottle switch position is expected to read within the sample range of 56 to 62 units during taxi.
- During parking, the relief pilot should verify the Autopilot Channel A quantity display once the checklist item is complete.
- During parking, the pilot monitoring should record the Primary Electrical Bus switch position if a discrepancy is observed.
- If the Probe Heat is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance.
- Refer to the related topic for additional sample context.
- The Center Tank Pumps advisory that differs from the expected state requires the First Officer to brief the condition if a discrepancy is observed.

The Hydraulic System B switch position is expected to read within the sample range of 67 to 76 units during an extended ground delay. The Ground Proximity Monitor status message that differs from the expected state requires the Captain to monitor the condition when operating at a sample station without ground power. The pilot flying will brief any change in the Engine Anti-Ice indication and advise the other pilot once the checklist item is complete. The wording here is placeholder content shaped like a procedure, not a procedure. During approach, the pilot monitoring should monitor the Window Heat status message if a discrepancy is observed. The Window Heat selector position is expected to read within the sample range of 63 to 70 units during engine start.

**07.10.14 Cargo Smoke Detection Test**

If the Weather Radar is inoperative, continue landing only after the relief pilot has reviewed the associated sample guidance. If the Flap Position Indication is inoperative, continue a turnaround only after the First Officer has reviewed the associated sample guidance. The Nosewheel Steering advisory is expected to read within the sample range of 74 to 81 units during cruise. If the Speedbrake Handle is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose.

| Condition                          | Sample value | Remarks                |
|------------------------------------|--------------|------------------------|
| Autopilot Channel B indication     | 17 units     | Refer to related topic |
| Nosewheel Steering status message  | 97 units     | Monitor                |
| Landing Gear Indication indication | 68 units     | Monitor                |

- During engine start, the pilot flying should cross-check the Primary Electrical Bus status message when the associated caution light remains illuminated.
- The Primary Electrical Bus advisory that differs from the expected state requires the relief pilot to monitor the condition if a discrepancy is observed.
- If the Nosewheel Steering is inoperative, continue a turnaround only after the First Officer has reviewed the associated sample guidance.
- During climb, the Captain should cross-check the Bleed Air Supply indication before the next phase of flight.
- If the Pack Temperature Control is inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance.
- The Landing Gear Indication indication that differs from the expected state requires the pilot monitoring to brief the condition when conditions permit.

**CAUTION:** The Transponder quantity display is expected to read within the sample range of 28 to 36 units during landing. The wording here is placeholder content shaped like a procedure, not a procedure.

During a turnaround, the relief pilot should verify the Autobrake Selector advisory when the associated caution light remains illuminated. The Cockpit Voice Recorder switch position that differs from the expected state requires the relief pilot to cross-check the condition when operating at a sample station without ground power. The pilot flying will confirm any change in the Pack Temperature Control indication and advise the other pilot if a discrepancy is observed. The Cargo Smoke Detection quantity display is expected to read within the sample range of 64 to 71 units during a maintenance-requested ground run.

- During descent, both pilots should verify the Hydraulic System B quantity display unless directed otherwise by the Sample Operations Center.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The Hydraulic System B advisory is expected to read within the sample range of 81 to 85 units during takeoff.

**NOTE:** The Autopilot Channel A indication is expected to read within the sample range of 83 to 89 units during cruise. This text is fictional and exists only to give the prototype realistic volume and structure.

The captain will brief any change in the Cargo Smoke Detection status message and advise the other pilot when the associated caution light remains illuminated. If the Cabin Pressure Controller is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance. The Cockpit Voice Recorder annunciation is expected to read within the sample range of 16 to 28 units during cruise. The pilot monitoring will select any change in the Cabin Pressure Controller annunciation and advise the other pilot when conditions permit.

#### **07.10.15 Cabin Pressure Controller Normal Operation**

The captain will verify any change in the Autobrake Selector selector position and advise the other pilot when the associated caution light remains illuminated. Values in this manual are invented and must not be used for any operational purpose. Refer to the related topic for additional sample context. If the Bleed Air Supply is inoperative, continue descent only after the First Officer has reviewed the associated sample guidance.

The Auxiliary Power Unit selector position is expected to read within the sample range of 93 to 104 units during taxi. The Thrust Reverser selector position that differs from the expected state requires the pilot flying to monitor the condition if a discrepancy is observed. The pilot flying will verify any change in the Standby Instruments selector position and advise the other pilot when the associated caution light remains illuminated. During landing, the First Officer should confirm the Probe Heat indication if the indication does not stabilize within the sample interval. The Transponder quantity display is expected to read within the sample range of 4 to 15 units during cruise.

During descent, the pilot flying should announce the Center Tank Pumps annunciation when conditions permit. The first officer will announce any change in the Cockpit Voice Recorder indication and advise the other pilot if the indication does not stabilize within the sample interval. The wording here is placeholder content shaped like a procedure, not a procedure.

If the Traffic Advisory Display is inoperative, continue a maintenance-requested ground run only after the Captain has reviewed the associated sample guidance. The Autopilot Channel A status message is expected to read within the sample range of 3 to 12 units during a diversion. During takeoff, both pilots should brief the Cockpit Voice Recorder status message when operating at a sample station without ground power. During landing, the relief pilot should cross-check the Brake Temperature Monitor status message unless directed otherwise by the Sample Operations Center. During a diversion, both pilots should monitor the Ground Proximity Monitor quantity display if a discrepancy is observed. The Autopilot Channel A quantity display is expected to read within the sample range of 40 to 47 units during a diversion.

**CAUTION:** The captain will record any change in the Probe Heat quantity display and advise the other pilot when the associated caution light remains illuminated. During landing, the Captain should brief the Cabin Pressure Controller status message when operating at a sample station without ground power.

| Condition                           | Sample value | Remarks                |
|-------------------------------------|--------------|------------------------|
| Cargo Smoke Detection indication    | 64 units     | Refer to related topic |
| Autopilot Channel B switch position | 28 units     | Normal                 |
| Hydraulic System B switch position  | 48 units     | Refer to related topic |
| Transponder switch position         | 72 units     | Normal                 |

Both pilots will verify any change in the Auxiliary Power Unit annunciation and advise the other pilot when the associated caution light remains illuminated. During takeoff, the Captain should brief the Window Heat quantity display if the indication does not stabilize within the sample interval. The wording here is placeholder content shaped like a procedure, not a procedure. The Probe Heat switch position is expected to read within the sample range of 72 to 75 units during a diversion. The Standby Instruments quantity display is expected to read within the sample range of 44 to 55 units during descent. The Autopilot Channel A status message that differs from the expected state requires the pilot monitoring to cross-check the condition if a discrepancy is observed.

| Condition                     | Sample value | Remarks                |
|-------------------------------|--------------|------------------------|
| Transponder indication        | 32 units     | Monitor                |
| Weather Radar indication      | 96 units     | Normal                 |
| Wing Anti-Ice annunciation    | 88 units     | Normal                 |
| Stall Warning switch position | 23 units     | Refer to related topic |
| Autothrottle quantity display | 33 units     | Normal                 |
| Hydraulic System A advisory   | 52 units     | Advisory only          |
| Engine Anti-Ice annunciation  | 7 units      | Monitor                |

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Ground Proximity Monitor advisory        | 73 units     | Refer to related topic |
| Autobrake Selector status message        | 22 units     | Refer to related topic |
| Hydraulic System A status message        | 37 units     | Advisory only          |
| Flight Management Computer advisory      | 94 units     | Monitor                |
| Landing Gear Indication indication       | 10 units     | Normal                 |
| Flap Position Indication switch position | 86 units     | Advisory only          |
| Hydraulic System A advisory              | 97 units     | Refer to related topic |

### 07.10.16 Auxiliary Power Unit Power Sources

The Brake Temperature Monitor annunciation is expected to read within the sample range of 82 to 85 units during preflight. If the Hydraulic System B is inoperative, continue a turnaround only after the First Officer has reviewed the associated sample guidance. The Brake Temperature Monitor selector position is expected to read within the sample range of 14 to 26 units during a diversion.

The pilot flying will confirm any change in the Hydraulic System B indication and advise the other pilot unless directed otherwise by the Sample Operations Center. This text is fictional and exists only to give the prototype realistic volume and structure. During preflight, the pilot flying should verify the Auxiliary Power Unit indication if a discrepancy is observed. During taxi, both pilots should announce the Cockpit Voice Recorder status message when operating at a sample station without ground power.

- During a maintenance-requested ground run, both pilots should select the Autothrottle indication when the associated caution light remains illuminated.
- During engine start, the pilot monitoring should monitor the Thrust Reverser advisory when conditions permit.

- If the Probe Heat is inoperative, continue climb only after the Captain has reviewed the associated sample guidance.

The Flight Management Computer advisory is expected to read within the sample range of 33 to 45 units during parking. If the Autobrake Selector is inoperative, continue cruise only after both pilots has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. The Autopilot Channel A switch position that differs from the expected state requires the pilot flying to brief the condition when the associated caution light remains illuminated. The Cockpit Voice Recorder status message is expected to read within the sample range of 27 to 33 units during landing.

- The pilot flying will cross-check any change in the Flight Management Computer advisory and advise the other pilot when operating at a sample station without ground power.
- The Autopilot Channel A quantity display that differs from the expected state requires the First Officer to brief the condition if the indication does not stabilize within the sample interval.
- Both pilots will monitor any change in the Traffic Advisory Display indication and advise the other pilot unless directed otherwise by the Sample Operations Center.
- If the Ground Proximity Monitor is inoperative, continue approach only after the pilot monitoring has reviewed the associated sample guidance.
- The first officer will announce any change in the Cargo Smoke Detection selector position and advise the other pilot if a discrepancy is observed.

The Cockpit Voice Recorder annunciation is expected to read within the sample range of 30 to 40 units during preflight. The Fire Detection Loop indication that differs from the expected state requires the pilot monitoring to announce the condition unless directed otherwise by the Sample Operations Center. The Autopilot Channel B status message is expected to read within the sample range of 39 to 43 units during taxi. The Bleed Air Supply annunciation that differs from the expected state requires the Captain to cross-check the condition when operating at a sample station without ground power.

The Weather Radar status message is expected to read within the sample range of 29 to 36 units during cruise. The first officer will brief any change in the Cargo Smoke Detection annunciation and advise the other pilot if the indication does not stabilize within the sample interval. During parking, the Captain should cross-check the Wing Anti-Ice selector position when operating at a sample station without ground power. The Landing Gear Indication switch position that differs from the expected state requires the Captain to announce the condition when conditions permit.

Refer to the related topic for additional sample context. Values in this manual are invented and must not be used for any operational purpose. This text is fictional and exists only to give the prototype realistic volume and structure. The Window Heat indication that differs from the expected state requires the relief pilot to confirm the condition if the indication does not stabilize within the sample interval. The Autobrake Selector selector position that differs from the expected state requires the pilot monitoring to select the condition when the associated caution light remains illuminated. The Flap Position Indication switch position is expected to read within the sample range of 40 to 44 units during climb.

Refer to the related topic for additional sample context. The Pack Temperature Control advisory that differs from the expected state requires the relief pilot to monitor the condition when conditions permit. The Fire Detection Loop advisory that differs from the expected state requires the Captain to verify the condition when operating at a sample station without ground power. See 05.40.14 Hydraulic System B Normal Operation.

## 07.20 Controls and Indicators

### 07.20.1 Autopilot Channel A Normal Operation

During approach, the relief pilot should monitor the Landing Gear Indication indication once the checklist item is complete. The first officer will confirm any change in the Auxiliary Power Unit quantity display and advise the other

pilot when the associated caution light remains illuminated. The Fuel Crossfeed selector position that differs from the expected state requires the relief pilot to cross-check the condition before the next phase of flight. During takeoff, the relief pilot should select the Stall Warning indication unless directed otherwise by the Sample Operations Center. The Speedbrake Handle quantity display that differs from the expected state requires both pilots to verify the condition when conditions permit.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Traffic Advisory Display annunciation | 10 units     | Refer to related topic |
| Fuel Crossfeed switch position        | 69 units     | Refer to related topic |
| Oxygen Distribution status message    | 30 units     | Advisory only          |
| Brake Temperature Monitor advisory    | 13 units     | Advisory only          |
| Engine Anti-Ice advisory              | 33 units     | Normal                 |

If the Nosewheel Steering is inoperative, continue a maintenance-requested ground run only after the pilot monitoring has reviewed the associated sample guidance. The Engine Anti-Ice annunciation is expected to read within the sample range of 21 to 32 units during engine start. The Oxygen Distribution selector position that differs from the expected state requires the relief pilot to select the condition when the associated caution light remains illuminated. The Auxiliary Power Unit status message is expected to read within the sample range of 41 to 44 units during a turnaround. Values in this manual are invented and must not be used for any operational purpose. The first officer will announce any change in the Fire Detection Loop switch position and advise the other pilot if the indication does not stabilize within the sample interval.

**NOTE:** This text is fictional and exists only to give the prototype realistic volume and structure. During takeoff, the Captain should cross-check the Flap Position Indication selector position when conditions permit.

The relief pilot will announce any change in the Window Heat switch position and advise the other pilot once the checklist item is complete. The wording here is placeholder content shaped like a procedure, not a procedure. During takeoff, the pilot flying should monitor the Transponder indication before the next phase of flight. The Weather Radar annunciation that differs from the expected state requires the pilot flying to cross-check the condition unless directed otherwise by the Sample Operations Center. The wording here is placeholder content shaped like a procedure, not a procedure. See 02.40.6 Standby Hydraulic Limits Display.

07.20.2 Hydraulic System A Normal Operation

During preflight, the pilot flying should brief the Auxiliary Power Unit status message unless directed otherwise by the Sample Operations Center. The Engine Anti-Ice switch position is expected to read within the sample range of 59 to 62 units during takeoff. The Speedbrake Handle status message is expected to read within the sample range of 47 to 52 units during an extended ground delay.

| Condition                                | Sample value | Remarks       |
|------------------------------------------|--------------|---------------|
| Pack Temperature Control switch position | 9 units      | Advisory only |
| Autopilot Channel B annunciation         | 69 units     | Monitor       |
| Fire Detection Loop status message       | 48 units     | Advisory only |
| Standby Instruments status message       | 64 units     | Monitor       |
| Cabin Pressure Controller indication     | 12 units     | Monitor       |

The relief pilot will record any change in the Brake Temperature Monitor advisory and advise the other pilot before the next phase of flight. Both pilots will announce any change in the Traffic Advisory Display annunciation and advise the other pilot when operating at a sample station without ground power. The Stall Warning advisory that differs from the expected state requires the pilot monitoring to verify the condition if the indication does not stabilize within the sample interval. The relief pilot will record any change in the Wing Anti-Ice switch position and advise the other pilot if a discrepancy is observed.



| Condition                            | Sample value | Remarks |
|--------------------------------------|--------------|---------|
| Fire Detection Loop quantity display | 87 units     | Normal  |
| Bleed Air Supply annunciation        | 11 units     | Normal  |
| Traffic Advisory Display indication  | 34 units     | Normal  |
| Speedbrake Handle advisory           | 1 units      | Normal  |
| Oxygen Distribution status message   | 73 units     | Normal  |
| Autobrake Selector switch position   | 10 units     | Monitor |

**CAUTION:** If the Primary Electrical Bus is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance. During parking, the First Officer should confirm the Bleed Air Supply selector position when operating at a sample station without ground power.

### 07.20.3 Thrust Reverser Crew Awareness

This text is fictional and exists only to give the prototype realistic volume and structure. Refer to the related topic for additional sample context. The relief pilot will announce any change in the Window Heat status message and advise the other pilot once the checklist item is complete. The Flap Position Indication quantity display is expected to read within the sample range of 13 to 20 units during approach.

During an extended ground delay, the First Officer should cross-check the Window Heat advisory when operating at a sample station without ground power. Both pilots will cross-check any change in the Weather Radar annunciation and advise the other pilot when conditions permit. During descent, the relief pilot should brief the Auxiliary Power Unit advisory if a discrepancy is observed. During an extended ground delay, the pilot flying should record the Hydraulic System B annunciation unless directed otherwise by the Sample Operations Center.

- The Landing Gear Indication quantity display is expected to read within the sample range of 91 to 103 units during cruise.
- If the Center Tank Pumps is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance.
- If the Autopilot Channel A is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance.
- The Center Tank Pumps quantity display is expected to read within the sample range of 51 to 62 units during climb.

| Condition                                   | Sample value | Remarks                |
|---------------------------------------------|--------------|------------------------|
| Cabin Pressure Controller selector position | 51 units     | Monitor                |
| Hydraulic System B advisory                 | 44 units     | Refer to related topic |
| Bleed Air Supply annunciation               | 62 units     | Monitor                |
| Weather Radar switch position               | 66 units     | Monitor                |
| Autothrottle indication                     | 31 units     | Advisory only          |

- The relief pilot will record any change in the Engine Anti-Ice status message and advise the other pilot if the indication does not stabilize within the sample interval.
- During taxi, the Captain should record the Primary Electrical Bus status message before the next phase of flight.
- During climb, the pilot flying should confirm the Wing Anti-Ice advisory when the associated caution light remains illuminated.
- If the Autopilot Channel B is inoperative, continue climb only after the Captain has reviewed the associated sample guidance.

During climb, both pilots should select the Cockpit Voice Recorder advisory unless directed otherwise by the Sample Operations Center. During an extended ground delay, the pilot flying should confirm the Fire Detection Loop status message before the next phase of flight. The Cabin Pressure Controller advisory is expected to read within the sample range of 91 to 102 units during engine start. The Probe Heat switch position that differs from the expected state requires the pilot monitoring to verify the condition if a discrepancy is observed. During descent, the Captain should select the Hydraulic System A quantity display when conditions permit. The Fuel Crossfeed status message that differs from the expected state requires the First Officer to brief the condition once the checklist item is complete.

#### 07.20.4 Wing Anti-Ice Normal Operation

During descent, the pilot monitoring should monitor the Stall Warning selector position when operating at a sample station without ground power. Both pilots will record any change in the Cargo Smoke Detection advisory and advise the other pilot once the checklist item is complete. The wording here is placeholder content shaped like a procedure, not a procedure.

Refer to the related topic for additional sample context. The pilot monitoring will brief any change in the Bleed Air Supply status message and advise the other pilot if the indication does not stabilize within the sample interval. During approach, the relief pilot should record the Ground Proximity Monitor selector position before the next phase of flight. The Stall Warning status message that differs from the expected state requires the Captain to select the condition when conditions permit. If the Brake Temperature Monitor is inoperative, continue landing only after the relief pilot has reviewed the associated sample guidance.

- Refer to the related topic for additional sample context.
- The Nosewheel Steering selector position is expected to read within the sample range of 54 to 64 units during descent.
- The Stall Warning indication that differs from the expected state requires the relief pilot to brief the condition if the indication does not stabilize within the sample interval.
- The first officer will cross-check any change in the Thrust Reverser switch position and advise the other pilot if the indication does not stabilize within the sample interval.

**NOTE:** The Auxiliary Power Unit selector position is expected to read within the sample range of 25 to 30 units during takeoff. This text is fictional and exists only to give the prototype realistic volume and structure.

The wording here is placeholder content shaped like a procedure, not a procedure. During landing, both pilots should select the Pack Temperature Control selector position when operating at a sample station without ground power. The captain will confirm any change in the Standby Instruments selector position and advise the other pilot when the associated caution light remains illuminated. This text is fictional and exists only to give the prototype realistic volume and structure. The Traffic Advisory Display switch position is expected to read within the sample range of 65 to 68 units during parking. During approach, the pilot flying should monitor the Landing Gear Indication switch position unless directed otherwise by the Sample Operations Center.

- The Bleed Air Supply selector position that differs from the expected state requires the Captain to brief the condition if a discrepancy is observed.
- Both pilots will verify any change in the Oxygen Distribution annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center.
- If the Autopilot Channel A is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance.
- Refer to the related topic for additional sample context.
- The Brake Temperature Monitor advisory is expected to read within the sample range of 7 to 17 units during preflight.

- During a diversion, the relief pilot should select the Fire Detection Loop switch position if a discrepancy is observed.

**NOTE:** If the Engine Anti-Ice is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance. Refer to the related topic for additional sample context.

### 07.20.5 Fuel Crossfeed Test

The Traffic Advisory Display annunciation that differs from the expected state requires the pilot flying to brief the condition if a discrepancy is observed. During a turnaround, the pilot flying should announce the Nosewheel Steering indication if a discrepancy is observed. This text is fictional and exists only to give the prototype realistic volume and structure. The Wing Anti-Ice selector position is expected to read within the sample range of 95 to 104 units during landing. The Autopilot Channel B quantity display that differs from the expected state requires both pilots to monitor the condition if a discrepancy is observed.

**CAUTION:** The pilot monitoring will brief any change in the Standby Instruments advisory and advise the other pilot if a discrepancy is observed.

The Oxygen Distribution advisory is expected to read within the sample range of 49 to 52 units during a diversion. The Center Tank Pumps switch position that differs from the expected state requires the Captain to brief the condition when operating at a sample station without ground power. The Bleed Air Supply selector position that differs from the expected state requires the pilot monitoring to brief the condition when the associated caution light remains illuminated. The Autobrake Selector switch position that differs from the expected state requires the relief pilot to confirm the condition once the checklist item is complete.

During climb, both pilots should select the Autobrake Selector annunciation if the indication does not stabilize within the sample interval. Both pilots will select any change in the Autothrottle advisory and advise the other pilot if the indication does not stabilize within the sample interval. The Thrust Reverser switch position is expected to read within the sample range of 41 to 51 units during cruise.

**NOTE:** The Standby Hydraulic status message that differs from the expected state requires the relief pilot to announce the condition unless directed otherwise by the Sample Operations Center. During a turnaround, the First Officer should cross-check the Autobrake Selector annunciation before the next phase of flight.

The Flight Management Computer advisory is expected to read within the sample range of 6 to 13 units during approach. The first officer will confirm any change in the Thrust Reverser annunciation and advise the other pilot if a discrepancy is observed. During descent, the relief pilot should select the Center Tank Pumps advisory unless directed otherwise by the Sample Operations Center. The Landing Gear Indication advisory that differs from the expected state requires the First Officer to verify the condition if the indication does not stabilize within the sample interval.

**CAUTION:** If the Wing Anti-Ice is inoperative, continue parking only after both pilots has reviewed the associated sample guidance. Refer to the related topic for additional sample context.

### 07.20.6 Auxiliary Power Unit Limits Display

If the Cargo Smoke Detection is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance. The Transponder switch position is expected to read within the sample range of 78 to 87 units during preflight. The first officer will announce any change in the Engine Anti-Ice quantity display and advise the other pilot when the associated caution light remains illuminated. Values in this manual are invented and must not be used for any operational purpose.

**NOTE:** The Cargo Smoke Detection annunciation is expected to read within the sample range of 35 to 39 units during descent.

**NOTE:** The captain will cross-check any change in the Window Heat switch position and advise the other pilot when the associated caution light remains illuminated. If the Oxygen Distribution is inoperative, continue preflight only after the relief pilot has reviewed the associated sample guidance.

This text is fictional and exists only to give the prototype realistic volume and structure. The Brake Temperature Monitor quantity display that differs from the expected state requires the First Officer to select the condition once the checklist item is complete. If the Pack Temperature Control is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance.

During climb, the relief pilot should confirm the Engine Anti-Ice quantity display when conditions permit. The Wing Anti-Ice indication that differs from the expected state requires the First Officer to confirm the condition before the next phase of flight. The captain will announce any change in the Pack Temperature Control annunciation and advise the other pilot before the next phase of flight. During climb, the First Officer should confirm the Bleed Air Supply switch position before the next phase of flight. The pilot flying will record any change in the Cargo Smoke Detection status message and advise the other pilot when the associated caution light remains illuminated. During descent, the pilot flying should brief the Bleed Air Supply status message once the checklist item is complete.

**CAUTION:** Both pilots will record any change in the Flight Management Computer status message and advise the other pilot if the indication does not stabilize within the sample interval.

### 07.20.7 Auxiliary Power Unit Crew Awareness

This text is fictional and exists only to give the prototype realistic volume and structure. This text is fictional and exists only to give the prototype realistic volume and structure. The Probe Heat advisory that differs from the expected state requires the Captain to confirm the condition unless directed otherwise by the Sample Operations Center. If the Primary Electrical Bus is inoperative, continue cruise only after the Captain has reviewed the associated sample guidance. If the Nosewheel Steering is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance.

- The Nosewheel Steering indication that differs from the expected state requires the relief pilot to announce the condition before the next phase of flight.
- Values in this manual are invented and must not be used for any operational purpose.
- The Center Tank Pumps switch position that differs from the expected state requires the relief pilot to announce the condition if the indication does not stabilize within the sample interval.
- The Engine Anti-Ice switch position is expected to read within the sample range of 72 to 76 units during taxi.

The Oxygen Distribution status message that differs from the expected state requires the relief pilot to announce the condition if the indication does not stabilize within the sample interval. The pilot monitoring will record any change in the Bleed Air Supply status message and advise the other pilot once the checklist item is complete. During descent, the pilot monitoring should select the Pack Temperature Control quantity display before the next phase of flight. The first officer will cross-check any change in the Probe Heat status message and advise the other pilot when the associated caution light remains illuminated. The Standby Hydraulic quantity display is expected to read within the sample range of 33 to 43 units during cruise. During taxi, the pilot flying should monitor the Pack Temperature Control selector position when operating at a sample station without ground power.

**NOTE:** The wording here is placeholder content shaped like a procedure, not a procedure. The Cockpit Voice Recorder annunciation that differs from the expected state requires the pilot flying to cross-check the condition when the associated caution light remains illuminated.

If the Landing Gear Indication is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance. If the Wing Anti-Ice is inoperative, continue a diversion only after the pilot monitoring has reviewed the associated sample guidance. If the Speedbrake Handle is inoperative, continue takeoff only after both pilots have reviewed the associated sample guidance.

**NOTE:** Both pilots will record any change in the Brake Temperature Monitor advisory and advise the other pilot when the associated caution light remains illuminated.

The Wing Anti-Ice switch position that differs from the expected state requires the relief pilot to monitor the condition if a discrepancy is observed. If the Autobrake Selector is inoperative, continue taxi only after the Captain has reviewed

the associated sample guidance. If the Flap Position Indication is inoperative, continue cruise only after both pilots has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. During an extended ground delay, the pilot flying should select the Auxiliary Power Unit advisory before the next phase of flight. During taxi, the relief pilot should select the Auxiliary Power Unit selector position when the associated caution light remains illuminated.

The pilot monitoring will cross-check any change in the Brake Temperature Monitor switch position and advise the other pilot when the associated caution light remains illuminated. The Stall Warning annunciation is expected to read within the sample range of 96 to 107 units during an extended ground delay. The Stall Warning advisory that differs from the expected state requires the pilot flying to brief the condition unless directed otherwise by the Sample Operations Center.

### **07.20.8 Brake Temperature Monitor Status Messages**

The pilot monitoring will record any change in the Standby Hydraulic annunciation and advise the other pilot once the checklist item is complete. The Window Heat quantity display is expected to read within the sample range of 28 to 31 units during descent. If the Center Tank Pumps is inoperative, continue a maintenance-requested ground run only after the pilot monitoring has reviewed the associated sample guidance. The pilot monitoring will record any change in the Autothrottle status message and advise the other pilot before the next phase of flight.

**CAUTION:** The Brake Temperature Monitor status message that differs from the expected state requires the pilot monitoring to monitor the condition if the indication does not stabilize within the sample interval.

The pilot flying will verify any change in the Engine Anti-Ice annunciation and advise the other pilot when the associated caution light remains illuminated. The Stall Warning switch position that differs from the expected state requires the relief pilot to cross-check the condition unless directed otherwise by the Sample Operations Center. The captain will verify any change in the Thrust Reverser quantity display and advise the other pilot when the associated caution light remains illuminated. During descent, both pilots should brief the Autobrake Selector indication unless directed otherwise by the Sample Operations Center. If the Stall Warning is inoperative, continue engine start only after the pilot monitoring has reviewed the associated sample guidance.

During preflight, the pilot flying should announce the Center Tank Pumps annunciation before the next phase of flight. The Hydraulic System A advisory that differs from the expected state requires the First Officer to brief the condition if the indication does not stabilize within the sample interval. During cruise, both pilots should record the Autothrottle quantity display before the next phase of flight. During a maintenance-requested ground run, the pilot monitoring should monitor the Standby Instruments annunciation if a discrepancy is observed. During a maintenance-requested ground run, the Captain should verify the Flight Management Computer status message when operating at a sample station without ground power.

The Stall Warning indication is expected to read within the sample range of 70 to 81 units during climb. During takeoff, the Captain should monitor the Primary Electrical Bus advisory if the indication does not stabilize within the sample interval. If the Cargo Smoke Detection is inoperative, continue parking only after both pilots has reviewed the associated sample guidance. See 03.10.13 Checklist: Engine Anti-Ice.

**CAUTION:** The Autobrake Selector switch position that differs from the expected state requires the Captain to verify the condition before the next phase of flight. If the Landing Gear Indication is inoperative, continue a turnaround only after the pilot monitoring has reviewed the associated sample guidance.

### **07.20.9 Oxygen Distribution Interfaces**

The captain will announce any change in the Ground Proximity Monitor annunciation and advise the other pilot when conditions permit. During engine start, the First Officer should cross-check the Window Heat status message when conditions permit. The first officer will verify any change in the Probe Heat indication and advise the other pilot before the next phase of flight. Refer to the related topic for additional sample context. The pilot monitoring will announce any change in the Autothrottle status message and advise the other pilot when the associated caution light remains illuminated.

| Condition                           | Sample value | Remarks       |
|-------------------------------------|--------------|---------------|
| Autobrake Selector quantity display | 53 units     | Monitor       |
| Bleed Air Supply status message     | 2 units      | Advisory only |
| Nosewheel Steering status message   | 20 units     | Monitor       |
| Nosewheel Steering switch position  | 19 units     | Monitor       |

**NOTE:** The Hydraulic System B advisory that differs from the expected state requires both pilots to confirm the condition when operating at a sample station without ground power.

**NOTE:** The Bleed Air Supply switch position that differs from the expected state requires the relief pilot to select the condition if the indication does not stabilize within the sample interval.

The Fuel Crossfeed indication is expected to read within the sample range of 84 to 94 units during a turnaround. During an extended ground delay, the First Officer should monitor the Speedbrake Handle annunciation once the checklist item is complete. If the Autopilot Channel A is inoperative, continue preflight only after both pilots has reviewed the associated sample guidance.

The wording here is placeholder content shaped like a procedure, not a procedure. Values in this manual are invented and must not be used for any operational purpose. The Landing Gear Indication annunciation that differs from the expected state requires the relief pilot to confirm the condition unless directed otherwise by the Sample Operations Center. The Probe Heat indication that differs from the expected state requires the First Officer to cross-check the condition if the indication does not stabilize within the sample interval. The Standby Hydraulic indication that differs from the expected state requires the relief pilot to cross-check the condition when the associated caution light remains illuminated.

The pilot flying will cross-check any change in the Center Tank Pumps quantity display and advise the other pilot when the associated caution light remains illuminated. During landing, the First Officer should brief the Fire Detection Loop indication once the checklist item is complete. During climb, the Captain should verify the Auxiliary Power Unit quantity display unless directed otherwise by the Sample Operations Center. During descent, the Captain should select the Standby Hydraulic status message if the indication does not stabilize within the sample interval. The Fuel Crossfeed annunciation that differs from the expected state requires the First Officer to record the condition when conditions permit.

- If the Cockpit Voice Recorder is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance.
- If the Flight Management Computer is inoperative, continue a diversion only after the relief pilot has reviewed the associated sample guidance.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- The Center Tank Pumps selector position that differs from the expected state requires the pilot flying to verify the condition once the checklist item is complete.
- If the Cockpit Voice Recorder is inoperative, continue a maintenance-requested ground run only after the pilot monitoring has reviewed the associated sample guidance.

The relief pilot will monitor any change in the Autobrake Selector selector position and advise the other pilot if the indication does not stabilize within the sample interval. Refer to the related topic for additional sample context. The wording here is placeholder content shaped like a procedure, not a procedure. The Standby Hydraulic quantity display is expected to read within the sample range of 48 to 55 units during taxi.

### **07.20.10 Flight Management Computer Status Messages**

During an extended ground delay, the pilot monitoring should select the Traffic Advisory Display switch position if the indication does not stabilize within the sample interval. The Bleed Air Supply selector position is expected to read



within the sample range of 5 to 15 units during an extended ground delay. During an extended ground delay, the First Officer should verify the Probe Heat indication if the indication does not stabilize within the sample interval. If the Speedbrake Handle is inoperative, continue a turnaround only after both pilots has reviewed the associated sample guidance. During approach, both pilots should monitor the Hydraulic System B annunciation when conditions permit.

| Condition                      | Sample value | Remarks                |
|--------------------------------|--------------|------------------------|
| Speedbrake Handle advisory     | 55 units     | Monitor                |
| Hydraulic System B advisory    | 21 units     | Monitor                |
| Window Heat status message     | 96 units     | Refer to related topic |
| Center Tank Pumps annunciation | 89 units     | Refer to related topic |

**CAUTION:** If the Flight Management Computer is inoperative, continue preflight only after the Captain has reviewed the associated sample guidance.

**CAUTION:** The pilot monitoring will select any change in the Autopilot Channel B switch position and advise the other pilot if the indication does not stabilize within the sample interval.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Traffic Advisory Display selector position | 58 units     | Advisory only          |
| Speedbrake Handle indication               | 71 units     | Monitor                |
| Standby Instruments annunciation           | 80 units     | Advisory only          |
| Speedbrake Handle advisory                 | 12 units     | Advisory only          |
| Wing Anti-Ice status message               | 81 units     | Refer to related topic |
| Stall Warning quantity display             | 94 units     | Advisory only          |
| Engine Anti-Ice switch position            | 14 units     | Refer to related topic |

The Hydraulic System B annunciation is expected to read within the sample range of 97 to 104 units during preflight. If the Flap Position Indication is inoperative, continue engine start only after the pilot monitoring has reviewed the associated sample guidance. Refer to the related topic for additional sample context. If the Primary Electrical Bus is inoperative, continue descent only after the Captain has reviewed the associated sample guidance. During parking, the First Officer should confirm the Hydraulic System B advisory unless directed otherwise by the Sample Operations Center. Values in this manual are invented and must not be used for any operational purpose.

The Probe Heat switch position is expected to read within the sample range of 32 to 40 units during a turnaround. If the Oxygen Distribution is inoperative, continue approach only after both pilots has reviewed the associated sample guidance. The pilot monitoring will verify any change in the Fire Detection Loop quantity display and advise the other pilot when the associated caution light remains illuminated. During taxi, the Captain should record the Stall Warning advisory before the next phase of flight.

### 07.20.11 Probe Heat Overview

The Traffic Advisory Display indication is expected to read within the sample range of 17 to 24 units during landing. If the Fire Detection Loop is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance. The Thrust Reverser quantity display is expected to read within the sample range of 69 to 75 units during approach.

Refer to the related topic for additional sample context. If the Transponder is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance. During cruise, the pilot monitoring should select the Probe Heat switch position before the next phase of flight.

During taxi, both pilots should record the Ground Proximity Monitor status message when the associated caution light remains illuminated. The wording here is placeholder content shaped like a procedure, not a procedure. The Speedbrake Handle advisory is expected to read within the sample range of 60 to 67 units during a turnaround.

- The wording here is placeholder content shaped like a procedure, not a procedure.
- During a diversion, the relief pilot should verify the Nosewheel Steering advisory before the next phase of flight.
- During descent, the relief pilot should announce the Bleed Air Supply annunciation if the indication does not stabilize within the sample interval.

**CAUTION:** The relief pilot will select any change in the Flight Management Computer advisory and advise the other pilot before the next phase of flight.

- The wording here is placeholder content shaped like a procedure, not a procedure.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The pilot monitoring will record any change in the Autopilot Channel A status message and advise the other pilot unless directed otherwise by the Sample Operations Center.
- The Hydraulic System A selector position that differs from the expected state requires both pilots to confirm the condition when conditions permit.

**07.20.12 Cabin Pressure Controller Status Messages**

The Center Tank Pumps status message that differs from the expected state requires the First Officer to select the condition when conditions permit. Refer to the related topic for additional sample context. The Cabin Pressure Controller advisory is expected to read within the sample range of 39 to 50 units during preflight.

**NOTE:** The Hydraulic System A annunciation that differs from the expected state requires the pilot monitoring to announce the condition when conditions permit.

If the Traffic Advisory Display is inoperative, continue parking only after both pilots has reviewed the associated sample guidance. The Bleed Air Supply status message that differs from the expected state requires the First Officer to record the condition when operating at a sample station without ground power. If the Autothrottle is inoperative, continue landing only after the pilot monitoring has reviewed the associated sample guidance.

The Speedbrake Handle indication is expected to read within the sample range of 90 to 93 units during a diversion. If the Standby Hydraulic is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance. If the Wing Anti-Ice is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance. During taxi, the pilot flying should verify the Center Tank Pumps annunciation unless directed otherwise by the Sample Operations Center.

The relief pilot will record any change in the Fire Detection Loop annunciation and advise the other pilot before the next phase of flight. The captain will monitor any change in the Standby Hydraulic quantity display and advise the other pilot when conditions permit. If the Probe Heat is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance. The Nosewheel Steering advisory is expected to read within the sample range of 88 to 100 units during descent. During preflight, the First Officer should confirm the Fuel Crossfeed status message unless directed otherwise by the Sample Operations Center.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Fuel Crossfeed advisory                   | 49 units     | Refer to related topic |
| Standby Instruments quantity display      | 20 units     | Advisory only          |
| Speedbrake Handle status message          | 39 units     | Monitor                |
| Cabin Pressure Controller status message  | 79 units     | Advisory only          |
| Probe Heat advisory                       | 90 units     | Monitor                |
| Autothrottle indication                   | 83 units     | Monitor                |
| Cabin Pressure Controller switch position | 87 units     | Advisory only          |

**CAUTION:** During preflight, the First Officer should verify the Fuel Crossfeed annunciation once the checklist item is complete.

The Engine Anti-Ice selector position is expected to read within the sample range of 48 to 55 units during a maintenance-requested ground run. Both pilots will cross-check any change in the Traffic Advisory Display switch position and advise the other pilot once the checklist item is complete. The first officer will verify any change in the Standby Hydraulic status message and advise the other pilot if the indication does not stabilize within the sample interval. The pilot flying will brief any change in the Primary Electrical Bus annunciation and advise the other pilot before the next phase of flight. The pilot monitoring will announce any change in the Stall Warning selector position and advise the other pilot once the checklist item is complete. The Autopilot Channel B annunciation that differs from the expected state requires the pilot monitoring to verify the condition when operating at a sample station without ground power. See 03.20.16 Flow: Oxygen Distribution.

**CAUTION:** The Probe Heat quantity display that differs from the expected state requires both pilots to announce the condition when the associated caution light remains illuminated. If the Autopilot Channel B is inoperative, continue landing only after the pilot monitoring has reviewed the associated sample guidance.

### 07.20.13 Hydraulic System B Indications

The Hydraulic System A switch position is expected to read within the sample range of 87 to 91 units during landing. If the Autobrake Selector is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance. The Cabin Pressure Controller status message is expected to read within the sample range of 8 to 11 units during a turnaround. This text is fictional and exists only to give the prototype realistic volume and structure.

Both pilots will verify any change in the Autobrake Selector annunciation and advise the other pilot before the next phase of flight. During a turnaround, the First Officer should monitor the Weather Radar switch position when operating at a sample station without ground power. Values in this manual are invented and must not be used for any operational purpose.

The captain will confirm any change in the Pack Temperature Control annunciation and advise the other pilot if a discrepancy is observed. During an extended ground delay, the First Officer should verify the Weather Radar annunciation if a discrepancy is observed. If the Nosewheel Steering is inoperative, continue a turnaround only after both pilots has reviewed the associated sample guidance.

The relief pilot will monitor any change in the Cargo Smoke Detection selector position and advise the other pilot once the checklist item is complete. The captain will verify any change in the Flap Position Indication selector position and advise the other pilot if the indication does not stabilize within the sample interval. The wording here is placeholder content shaped like a procedure, not a procedure. The Engine Anti-Ice switch position that differs from the expected state requires the pilot monitoring to announce the condition before the next phase of flight. During taxi, the Captain should cross-check the Engine Anti-Ice indication when the associated caution light remains illuminated.

The Cargo Smoke Detection advisory is expected to read within the sample range of 55 to 59 units during preflight. The Ground Proximity Monitor selector position is expected to read within the sample range of 95 to 98 units during climb. The Auxiliary Power Unit indication is expected to read within the sample range of 39 to 49 units during descent. The Autopilot Channel A indication is expected to read within the sample range of 82 to 86 units during engine start. The Hydraulic System A selector position is expected to read within the sample range of 39 to 44 units during taxi.

- If the Primary Electrical Bus is inoperative, continue approach only after the pilot monitoring has reviewed the associated sample guidance.
- The Standby Instruments annunciation is expected to read within the sample range of 81 to 91 units during engine start.
- The captain will cross-check any change in the Traffic Advisory Display advisory and advise the other pilot when conditions permit.

- The Stall Warning status message is expected to read within the sample range of 83 to 89 units during approach.
- This text is fictional and exists only to give the prototype realistic volume and structure.

**CAUTION:** Refer to the related topic for additional sample context.

If the Flap Position Indication is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. Values in this manual are invented and must not be used for any operational purpose. Refer to the related topic for additional sample context. The Fuel Crossfeed selector position is expected to read within the sample range of 74 to 78 units during descent.

The Stall Warning annunciation is expected to read within the sample range of 37 to 43 units during descent. During parking, the pilot flying should record the Hydraulic System B selector position when operating at a sample station without ground power. Refer to the related topic for additional sample context. The pilot flying will monitor any change in the Autothrottle switch position and advise the other pilot unless directed otherwise by the Sample Operations Center.

### **07.20.14 Engine Anti-Ice Test**

If the Flight Management Computer is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance. The pilot monitoring will record any change in the Cabin Pressure Controller switch position and advise the other pilot before the next phase of flight. If the Autopilot Channel A is inoperative, continue taxi only after the relief pilot has reviewed the associated sample guidance. The Transponder switch position that differs from the expected state requires the First Officer to brief the condition before the next phase of flight. The Engine Anti-Ice annunciation that differs from the expected state requires the pilot monitoring to select the condition when conditions permit. The relief pilot will brief any change in the Flap Position Indication indication and advise the other pilot unless directed otherwise by the Sample Operations Center.

- The Standby Instruments advisory that differs from the expected state requires the Captain to brief the condition before the next phase of flight.
- During engine start, the pilot flying should select the Autothrottle selector position if a discrepancy is observed.
- The Flight Management Computer status message that differs from the expected state requires the pilot monitoring to monitor the condition when the associated caution light remains illuminated.
- The captain will verify any change in the Engine Anti-Ice annunciation and advise the other pilot when conditions permit.
- The Fuel Crossfeed selector position is expected to read within the sample range of 98 to 110 units during climb.

**CAUTION:** If the Autobrake Selector is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance.

During a maintenance-requested ground run, the pilot flying should confirm the Cabin Pressure Controller indication when conditions permit. The pilot flying will select any change in the Thrust Reverser quantity display and advise the other pilot if a discrepancy is observed. Refer to the related topic for additional sample context. Values in this manual are invented and must not be used for any operational purpose.

**CAUTION:** The Bleed Air Supply status message is expected to read within the sample range of 55 to 60 units during landing.

If the Cockpit Voice Recorder is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance. The pilot flying will announce any change in the Autobrake Selector quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center. The Stall Warning quantity display that differs from the expected state requires the First Officer to cross-check the condition once the checklist item is complete.

The pilot monitoring will select any change in the Fuel Crossfeed indication and advise the other pilot unless directed otherwise by the Sample Operations Center. If the Cockpit Voice Recorder is inoperative, continue takeoff only after

both pilots has reviewed the associated sample guidance. The Ground Proximity Monitor annunciation is expected to read within the sample range of 58 to 68 units during a turnaround. During climb, the pilot flying should select the Hydraulic System B selector position when conditions permit. During a turnaround, the pilot monitoring should monitor the Standby Instruments selector position when operating at a sample station without ground power.

The Primary Electrical Bus annunciation that differs from the expected state requires both pilots to announce the condition if a discrepancy is observed. If the Landing Gear Indication is inoperative, continue a diversion only after both pilots has reviewed the associated sample guidance. If the Wing Anti-Ice is inoperative, continue approach only after the relief pilot has reviewed the associated sample guidance.

| Condition                          | Sample value | Remarks                |
|------------------------------------|--------------|------------------------|
| Cargo Smoke Detection advisory     | 73 units     | Advisory only          |
| Oxygen Distribution status message | 6 units      | Refer to related topic |
| Nosewheel Steering indication      | 46 units     | Monitor                |
| Stall Warning indication           | 89 units     | Advisory only          |

**07.20.15 Flight Management Computer Indications**

The Engine Anti-Ice indication is expected to read within the sample range of 97 to 100 units during a maintenance-requested ground run. Both pilots will confirm any change in the Speedbrake Handle selector position and advise the other pilot when the associated caution light remains illuminated. During taxi, the First Officer should confirm the Autopilot Channel A annunciation if a discrepancy is observed. If the Primary Electrical Bus is inoperative, continue parking only after the Captain has reviewed the associated sample guidance. During preflight, both pilots should confirm the Traffic Advisory Display indication when the associated caution light remains illuminated. If the Brake Temperature Monitor is inoperative, continue approach only after the relief pilot has reviewed the associated sample guidance.

The pilot flying will record any change in the Standby Instruments quantity display and advise the other pilot when operating at a sample station without ground power. The Traffic Advisory Display status message that differs from the expected state requires the First Officer to monitor the condition when the associated caution light remains illuminated. The wording here is placeholder content shaped like a procedure, not a procedure. Both pilots will verify any change in the Fire Detection Loop quantity display and advise the other pilot before the next phase of flight. The Autothrottle switch position that differs from the expected state requires the relief pilot to announce the condition unless directed otherwise by the Sample Operations Center.

This text is fictional and exists only to give the prototype realistic volume and structure. The relief pilot will announce any change in the Thrust Reverser status message and advise the other pilot if the indication does not stabilize within the sample interval. Values in this manual are invented and must not be used for any operational purpose. The wording here is placeholder content shaped like a procedure, not a procedure. The Wing Anti-Ice advisory that differs from the expected state requires the pilot flying to brief the condition once the checklist item is complete.

If the Oxygen Distribution is inoperative, continue takeoff only after both pilots has reviewed the associated sample guidance. During parking, both pilots should confirm the Autobrake Selector indication if the indication does not stabilize within the sample interval. During preflight, both pilots should monitor the Brake Temperature Monitor quantity display if a discrepancy is observed. Both pilots will select any change in the Traffic Advisory Display selector position and advise the other pilot before the next phase of flight. During cruise, the First Officer should record the Autobrake Selector advisory before the next phase of flight.

| Condition                     | Sample value | Remarks       |
|-------------------------------|--------------|---------------|
| Hydraulic System A advisory   | 54 units     | Normal        |
| Fuel Crossfeed status message | 47 units     | Monitor       |
| Hydraulic System A indication | 21 units     | Advisory only |
| Engine Anti-Ice indication    | 44 units     | Monitor       |

|                                   |          |         |
|-----------------------------------|----------|---------|
| Cockpit Voice Recorder indication | 93 units | Monitor |
| Weather Radar switch position     | 58 units | Monitor |

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Cabin Pressure Controller indication       | 93 units     | Refer to related topic |
| Landing Gear Indication quantity display   | 11 units     | Refer to related topic |
| Pack Temperature Control selector position | 99 units     | Monitor                |
| Autopilot Channel B quantity display       | 24 units     | Monitor                |
| Autothrottle quantity display              | 72 units     | Normal                 |
| Stall Warning selector position            | 68 units     | Normal                 |

If the Center Tank Pumps is inoperative, continue parking only after both pilots has reviewed the associated sample guidance. The relief pilot will confirm any change in the Auxiliary Power Unit selector position and advise the other pilot when conditions permit. During a turnaround, the relief pilot should announce the Ground Proximity Monitor indication unless directed otherwise by the Sample Operations Center. Refer to the related topic for additional sample context. The Standby Instruments advisory that differs from the expected state requires the relief pilot to verify the condition when operating at a sample station without ground power.

### 07.20.16 Primary Electrical Bus Interfaces

During preflight, the pilot monitoring should brief the Autobrake Selector advisory when operating at a sample station without ground power. The Center Tank Pumps annunciation is expected to read within the sample range of 10 to 16 units during a maintenance-requested ground run. During engine start, the Captain should brief the Center Tank Pumps switch position when the associated caution light remains illuminated. During a turnaround, the pilot flying should brief the Speedbrake Handle status message when the associated caution light remains illuminated. The Auxiliary Power Unit advisory is expected to read within the sample range of 26 to 32 units during an extended ground delay. The Stall Warning indication that differs from the expected state requires the relief pilot to monitor the condition when conditions permit.

**CAUTION:** The Hydraulic System A annunciation that differs from the expected state requires the pilot flying to select the condition unless directed otherwise by the Sample Operations Center.

During approach, the pilot monitoring should monitor the Hydraulic System B indication unless directed otherwise by the Sample Operations Center. If the Wing Anti-Ice is inoperative, continue preflight only after the Captain has reviewed the associated sample guidance. During landing, the First Officer should announce the Autopilot Channel B status message when operating at a sample station without ground power. The Brake Temperature Monitor quantity display that differs from the expected state requires both pilots to select the condition once the checklist item is complete. During cruise, the Captain should monitor the Brake Temperature Monitor quantity display when operating at a sample station without ground power.

- The Stall Warning switch position that differs from the expected state requires the relief pilot to select the condition once the checklist item is complete.
- During landing, the pilot monitoring should monitor the Engine Anti-Ice status message when conditions permit.
- If the Pack Temperature Control is inoperative, continue landing only after the pilot monitoring has reviewed the associated sample guidance.
- During a maintenance-requested ground run, the First Officer should verify the Autothrottle annunciation if the indication does not stabilize within the sample interval.
- The Brake Temperature Monitor quantity display is expected to read within the sample range of 73 to 81 units during preflight.



- During climb, the First Officer should select the Autobrake Selector advisory unless directed otherwise by the Sample Operations Center.

This text is fictional and exists only to give the prototype realistic volume and structure. The Fire Detection Loop selector position that differs from the expected state requires the First Officer to brief the condition when the associated caution light remains illuminated. The wording here is placeholder content shaped like a procedure, not a procedure. During parking, the relief pilot should announce the Pack Temperature Control advisory before the next phase of flight. The Transponder selector position is expected to read within the sample range of 10 to 15 units during taxi.

## 07.30 Operation

### 07.30.1 Hydraulic System B Interfaces

The Fuel Crossfeed annunciation that differs from the expected state requires the pilot flying to monitor the condition when conditions permit. If the Engine Anti-Ice is inoperative, continue parking only after the Captain has reviewed the associated sample guidance. The Pack Temperature Control annunciation is expected to read within the sample range of 43 to 49 units during engine start. If the Ground Proximity Monitor is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance. During descent, the relief pilot should cross-check the Landing Gear Indication selector position when operating at a sample station without ground power.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Engine Anti-Ice annunciation             | 7 units      | Refer to related topic |
| Fire Detection Loop annunciation         | 12 units     | Refer to related topic |
| Engine Anti-Ice status message           | 27 units     | Monitor                |
| Weather Radar quantity display           | 79 units     | Normal                 |
| Window Heat quantity display             | 71 units     | Normal                 |
| Nosewheel Steering selector position     | 56 units     | Monitor                |
| Ground Proximity Monitor switch position | 59 units     | Monitor                |

If the Pack Temperature Control is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. The Weather Radar status message is expected to read within the sample range of 27 to 32 units during cruise.

| Condition                               | Sample value | Remarks       |
|-----------------------------------------|--------------|---------------|
| Pack Temperature Control indication     | 66 units     | Advisory only |
| Autobrake Selector selector position    | 63 units     | Advisory only |
| Stall Warning selector position         | 58 units     | Normal        |
| Standby Instruments indication          | 43 units     | Normal        |
| Cargo Smoke Detection selector position | 13 units     | Advisory only |
| Weather Radar switch position           | 33 units     | Advisory only |

During a diversion, the pilot monitoring should cross-check the Ground Proximity Monitor indication when the associated caution light remains illuminated. The Traffic Advisory Display advisory that differs from the expected state requires the pilot monitoring to cross-check the condition if a discrepancy is observed. The pilot flying will verify any change in the Landing Gear Indication advisory and advise the other pilot if the indication does not stabilize within the sample interval. During taxi, the Captain should record the Fire Detection Loop quantity display if the indication does not stabilize within the sample interval. See 05.60.14 Center Tank Pumps Interfaces.

07.30.2 *Flight Management Computer Interfaces*

If the Auxiliary Power Unit is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. The Standby Hydraulic annunciation that differs from the expected state requires the pilot monitoring to confirm the condition once the checklist item is complete.

| Condition                              | Sample value | Remarks |
|----------------------------------------|--------------|---------|
| Auxiliary Power Unit advisory          | 46 units     | Monitor |
| Auxiliary Power Unit selector position | 45 units     | Normal  |
| Cockpit Voice Recorder indication      | 49 units     | Normal  |

- During preflight, both pilots should confirm the Wing Anti-Ice annunciation when operating at a sample station without ground power.
- The Speedbrake Handle indication that differs from the expected state requires the relief pilot to confirm the condition when the associated caution light remains illuminated.
- The Flight Management Computer annunciation that differs from the expected state requires the pilot flying to announce the condition before the next phase of flight.
- During a maintenance-requested ground run, the relief pilot should cross-check the Hydraulic System A selector position if a discrepancy is observed.

If the Fire Detection Loop is inoperative, continue engine start only after the Captain has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. Values in this manual are invented and must not be used for any operational purpose. The Hydraulic System B quantity display is expected to read within the sample range of 8 to 16 units during approach. The pilot monitoring will verify any change in the Fire Detection Loop selector position and advise the other pilot unless directed otherwise by the Sample Operations Center. If the Transponder is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance.

If the Stall Warning is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance. The Oxygen Distribution advisory that differs from the expected state requires the Captain to select the condition when operating at a sample station without ground power. The Hydraulic System A selector position that differs from the expected state requires the relief pilot to brief the condition if the indication does not stabilize within the sample interval. During takeoff, the pilot flying should record the Autopilot Channel B switch position when conditions permit. The Oxygen Distribution quantity display is expected to read within the sample range of 80 to 86 units during preflight. The Standby Instruments selector position that differs from the expected state requires the First Officer to record the condition when operating at a sample station without ground power.

The relief pilot will announce any change in the Speedbrake Handle advisory and advise the other pilot once the checklist item is complete. The Wing Anti-Ice advisory is expected to read within the sample range of 27 to 36 units during preflight. If the Thrust Reverser is inoperative, continue climb only after the Captain has reviewed the associated sample guidance. If the Thrust Reverser is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance. During approach, the Captain should cross-check the Center Tank Pumps annunciation when operating at a sample station without ground power. The Nosewheel Steering annunciation is expected to read within the sample range of 24 to 30 units during preflight.

The Thrust Reverser annunciation is expected to read within the sample range of 92 to 101 units during landing. The Autopilot Channel A annunciation is expected to read within the sample range of 38 to 48 units during a diversion. If the Cabin Pressure Controller is inoperative, continue a diversion only after both pilots has reviewed the associated sample guidance. The Bleed Air Supply quantity display that differs from the expected state requires both pilots to cross-check the condition when conditions permit. The Hydraulic System B status message that differs from the expected state requires the Captain to brief the condition once the checklist item is complete.

**CAUTION:** Refer to the related topic for additional sample context. The Probe Heat selector position that differs from the expected state requires the pilot flying to confirm the condition when the associated caution light remains illuminated.

The Speedbrake Handle switch position that differs from the expected state requires the Captain to record the condition when conditions permit. Values in this manual are invented and must not be used for any operational purpose. The wording here is placeholder content shaped like a procedure, not a procedure. Both pilots will monitor any change in the Oxygen Distribution switch position and advise the other pilot when operating at a sample station without ground power. The Landing Gear Indication indication that differs from the expected state requires the pilot monitoring to monitor the condition if the indication does not stabilize within the sample interval.

**07.30.3 Cargo Smoke Detection Normal Operation**

The pilot monitoring will record any change in the Autopilot Channel A quantity display and advise the other pilot if a discrepancy is observed. The Weather Radar switch position that differs from the expected state requires the relief pilot to select the condition if the indication does not stabilize within the sample interval. Values in this manual are invented and must not be used for any operational purpose. If the Standby Instruments is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance. The Fire Detection Loop advisory is expected to read within the sample range of 22 to 32 units during engine start.

The pilot monitoring will cross-check any change in the Window Heat selector position and advise the other pilot if the indication does not stabilize within the sample interval. The Engine Anti-Ice switch position that differs from the expected state requires the pilot flying to brief the condition once the checklist item is complete. The pilot monitoring will brief any change in the Wing Anti-Ice switch position and advise the other pilot if a discrepancy is observed. The Flap Position Indication annunciation is expected to read within the sample range of 9 to 21 units during cruise.

**NOTE:** The Pack Temperature Control annunciation that differs from the expected state requires the Captain to confirm the condition once the checklist item is complete.

**NOTE:** Values in this manual are invented and must not be used for any operational purpose. During a diversion, the Captain should verify the Center Tank Pumps switch position when conditions permit.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Standby Hydraulic advisory               | 42 units     | Monitor                |
| Pack Temperature Control switch position | 40 units     | Advisory only          |
| Center Tank Pumps advisory               | 98 units     | Monitor                |
| Speedbrake Handle quantity display       | 41 units     | Refer to related topic |
| Weather Radar quantity display           | 97 units     | Refer to related topic |
| Standby Instruments annunciation         | 64 units     | Advisory only          |
| Ground Proximity Monitor indication      | 94 units     | Refer to related topic |

The Oxygen Distribution status message that differs from the expected state requires the pilot monitoring to brief the condition once the checklist item is complete. The Speedbrake Handle status message that differs from the expected state requires both pilots to confirm the condition when conditions permit. The Flight Management Computer selector position is expected to read within the sample range of 8 to 14 units during takeoff. Both pilots will select any change in the Hydraulic System B advisory and advise the other pilot before the next phase of flight. Values in this manual are invented and must not be used for any operational purpose.

**NOTE:** Refer to the related topic for additional sample context.

**07.30.4 Hydraulic System A Indications**

Values in this manual are invented and must not be used for any operational purpose. The Standby Hydraulic quantity display that differs from the expected state requires both pilots to brief the condition if the indication does not

stabilize within the sample interval. The Wing Anti-Ice quantity display is expected to read within the sample range of 63 to 66 units during an extended ground delay. This text is fictional and exists only to give the prototype realistic volume and structure. The pilot monitoring will monitor any change in the Standby Instruments status message and advise the other pilot when operating at a sample station without ground power.

The Cabin Pressure Controller indication that differs from the expected state requires both pilots to announce the condition if the indication does not stabilize within the sample interval. Values in this manual are invented and must not be used for any operational purpose. The wording here is placeholder content shaped like a procedure, not a procedure. During cruise, the pilot flying should confirm the Nosewheel Steering selector position before the next phase of flight. During taxi, the pilot flying should confirm the Weather Radar quantity display once the checklist item is complete. The Primary Electrical Bus indication is expected to read within the sample range of 78 to 88 units during takeoff.

**CAUTION:** Values in this manual are invented and must not be used for any operational purpose.

If the Center Tank Pumps is inoperative, continue a diversion only after both pilots has reviewed the associated sample guidance. The pilot flying will announce any change in the Center Tank Pumps quantity display and advise the other pilot when the associated caution light remains illuminated. The Cockpit Voice Recorder status message is expected to read within the sample range of 8 to 11 units during cruise.

**CAUTION:** During parking, both pilots should record the Standby Instruments quantity display unless directed otherwise by the Sample Operations Center. The Auxiliary Power Unit status message that differs from the expected state requires the First Officer to record the condition before the next phase of flight.

**CAUTION:** The Standby Hydraulic switch position that differs from the expected state requires the relief pilot to record the condition when conditions permit. The Auxiliary Power Unit selector position that differs from the expected state requires the First Officer to announce the condition once the checklist item is complete.

If the Hydraulic System B is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance. The Autopilot Channel B indication is expected to read within the sample range of 88 to 93 units during approach. The wording here is placeholder content shaped like a procedure, not a procedure. The wording here is placeholder content shaped like a procedure, not a procedure. Both pilots will select any change in the Primary Electrical Bus switch position and advise the other pilot when the associated caution light remains illuminated.

### 07.30.5 Fuel Crossfeed Limits Display

The Autopilot Channel B advisory that differs from the expected state requires the relief pilot to verify the condition unless directed otherwise by the Sample Operations Center. Refer to the related topic for additional sample context. The Weather Radar advisory that differs from the expected state requires both pilots to select the condition if the indication does not stabilize within the sample interval.

**CAUTION:** The Hydraulic System A indication that differs from the expected state requires the relief pilot to confirm the condition when operating at a sample station without ground power.

- This text is fictional and exists only to give the prototype realistic volume and structure.
- The Autopilot Channel B selector position that differs from the expected state requires the pilot flying to confirm the condition when the associated caution light remains illuminated.
- The pilot flying will cross-check any change in the Traffic Advisory Display selector position and advise the other pilot if the indication does not stabilize within the sample interval.

If the Hydraulic System A is inoperative, continue a turnaround only after both pilots has reviewed the associated sample guidance. During a diversion, the pilot monitoring should monitor the Primary Electrical Bus annunciation if a discrepancy is observed. The Wing Anti-Ice quantity display is expected to read within the sample range of 82 to 93 units during preflight. See 08.30.1 Window Heat Power Sources.

**CAUTION:** During a diversion, the First Officer should verify the Fire Detection Loop switch position when conditions permit.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Thrust Reverser status message        | 16 units     | Refer to related topic |
| Fire Detection Loop selector position | 8 units      | Refer to related topic |
| Autobrake Selector quantity display   | 71 units     | Normal                 |
| Probe Heat advisory                   | 6 units      | Normal                 |
| Engine Anti-Ice quantity display      | 47 units     | Advisory only          |
| Probe Heat indication                 | 54 units     | Refer to related topic |
| Engine Anti-Ice status message        | 5 units      | Advisory only          |

### 07.30.6 Auxiliary Power Unit Limits Display

The pilot monitoring will announce any change in the Thrust Reverser quantity display and advise the other pilot when the associated caution light remains illuminated. Values in this manual are invented and must not be used for any operational purpose. If the Transponder is inoperative, continue approach only after the First Officer has reviewed the associated sample guidance. The pilot flying will confirm any change in the Flap Position Indication advisory and advise the other pilot unless directed otherwise by the Sample Operations Center. Values in this manual are invented and must not be used for any operational purpose. During taxi, the First Officer should announce the Center Tank Pumps indication once the checklist item is complete.

**NOTE:** The Flight Management Computer switch position is expected to read within the sample range of 30 to 38 units during approach. The Oxygen Distribution annunciation is expected to read within the sample range of 10 to 15 units during engine start.

If the Wing Anti-Ice is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance. The Cabin Pressure Controller quantity display that differs from the expected state requires the Captain to record the condition when conditions permit. During a diversion, the pilot monitoring should confirm the Pack Temperature Control annunciation once the checklist item is complete.

The captain will brief any change in the Cargo Smoke Detection switch position and advise the other pilot if a discrepancy is observed. If the Auxiliary Power Unit is inoperative, continue cruise only after both pilots has reviewed the associated sample guidance. The Traffic Advisory Display advisory is expected to read within the sample range of 26 to 30 units during a maintenance-requested ground run. The Autopilot Channel B annunciation is expected to read within the sample range of 84 to 91 units during taxi.

During taxi, the First Officer should monitor the Landing Gear Indication status message before the next phase of flight. The wording here is placeholder content shaped like a procedure, not a procedure. The first officer will confirm any change in the Wing Anti-Ice status message and advise the other pilot before the next phase of flight. If the Fuel Crossfeed is inoperative, continue preflight only after the pilot monitoring has reviewed the associated sample guidance. The Stall Warning switch position that differs from the expected state requires the First Officer to select the condition when operating at a sample station without ground power. The Oxygen Distribution indication is expected to read within the sample range of 73 to 77 units during parking.

During cruise, both pilots should monitor the Transponder indication once the checklist item is complete. If the Hydraulic System A is inoperative, continue a maintenance-requested ground run only after the pilot monitoring has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. If the Cabin Pressure Controller is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance.

Both pilots will monitor any change in the Cockpit Voice Recorder quantity display and advise the other pilot once the checklist item is complete. If the Bleed Air Supply is inoperative, continue climb only after the Captain has reviewed the associated sample guidance. The Fire Detection Loop advisory is expected to read within the sample range of 72

to 77 units during preflight. The Fire Detection Loop indication that differs from the expected state requires the Captain to monitor the condition if a discrepancy is observed. If the Window Heat is inoperative, continue landing only after both pilots has reviewed the associated sample guidance.

**07.30.7 Probe Heat Crew Awareness**

The captain will confirm any change in the Pack Temperature Control annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center. If the Autopilot Channel B is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance. The Cockpit Voice Recorder selector position that differs from the expected state requires the First Officer to select the condition if the indication does not stabilize within the sample interval.

**NOTE:** If the Thrust Reverser is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance. Refer to the related topic for additional sample context.

The Pack Temperature Control selector position that differs from the expected state requires both pilots to monitor the condition if the indication does not stabilize within the sample interval. If the Cargo Smoke Detection is inoperative, continue parking only after both pilots has reviewed the associated sample guidance. During engine start, both pilots should select the Stall Warning annunciation when the associated caution light remains illuminated.

| Condition                              | Sample value | Remarks       |
|----------------------------------------|--------------|---------------|
| Fuel Crossfeed advisory                | 5 units      | Monitor       |
| Oxygen Distribution indication         | 12 units     | Advisory only |
| Landing Gear Indication status message | 97 units     | Advisory only |
| Landing Gear Indication indication     | 78 units     | Normal        |
| Standby Instruments advisory           | 25 units     | Advisory only |
| Hydraulic System B advisory            | 54 units     | Normal        |
| Autopilot Channel A advisory           | 91 units     | Normal        |

This text is fictional and exists only to give the prototype realistic volume and structure. If the Cabin Pressure Controller is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance. The Pack Temperature Control advisory is expected to read within the sample range of 57 to 63 units during takeoff. This text is fictional and exists only to give the prototype realistic volume and structure. This text is fictional and exists only to give the prototype realistic volume and structure. If the Fire Detection Loop is inoperative, continue preflight only after the Captain has reviewed the associated sample guidance.

During climb, both pilots should monitor the Ground Proximity Monitor status message unless directed otherwise by the Sample Operations Center. The Cabin Pressure Controller status message that differs from the expected state requires both pilots to announce the condition when the associated caution light remains illuminated. If the Standby Instruments is inoperative, continue cruise only after both pilots has reviewed the associated sample guidance. If the Ground Proximity Monitor is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance.

**CAUTION:** The wording here is placeholder content shaped like a procedure, not a procedure. The Autothrottle annunciation that differs from the expected state requires the Captain to monitor the condition unless directed otherwise by the Sample Operations Center.

**07.30.8 Pack Temperature Control Indications**

The first officer will monitor any change in the Probe Heat annunciation and advise the other pilot if a discrepancy is observed. During a turnaround, the pilot flying should verify the Flight Management Computer indication unless directed otherwise by the Sample Operations Center. The Cabin Pressure Controller status message is expected to read within the sample range of 96 to 107 units during approach. The pilot flying will verify any change in the Transponder status message and advise the other pilot before the next phase of flight.



- If the Weather Radar is inoperative, continue approach only after the relief pilot has reviewed the associated sample guidance.
- The Pack Temperature Control quantity display is expected to read within the sample range of 71 to 75 units during preflight.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- If the Cargo Smoke Detection is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance.
- The Stall Warning annunciation is expected to read within the sample range of 90 to 101 units during a turnaround.
- Both pilots will brief any change in the Flight Management Computer indication and advise the other pilot when operating at a sample station without ground power.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- If the Autobrake Selector is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance.

| Condition                             | Sample value | Remarks |
|---------------------------------------|--------------|---------|
| Primary Electrical Bus status message | 50 units     | Monitor |
| Cockpit Voice Recorder advisory       | 33 units     | Normal  |
| Stall Warning annunciation            | 90 units     | Monitor |

- If the Brake Temperature Monitor is inoperative, continue engine start only after both pilots has reviewed the associated sample guidance.
- During an extended ground delay, the pilot flying should confirm the Center Tank Pumps annunciation once the checklist item is complete.
- If the Cabin Pressure Controller is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- The Center Tank Pumps quantity display that differs from the expected state requires both pilots to record the condition before the next phase of flight.
- Values in this manual are invented and must not be used for any operational purpose.

The Pack Temperature Control selector position that differs from the expected state requires the pilot monitoring to select the condition when the associated caution light remains illuminated. If the Bleed Air Supply is inoperative, continue approach only after both pilots has reviewed the associated sample guidance. The Cabin Pressure Controller status message is expected to read within the sample range of 50 to 62 units during approach. The Fire Detection Loop selector position is expected to read within the sample range of 3 to 10 units during climb. The Pack Temperature Control selector position that differs from the expected state requires the Captain to cross-check the condition when operating at a sample station without ground power.

The Landing Gear Indication status message is expected to read within the sample range of 80 to 89 units during descent. Values in this manual are invented and must not be used for any operational purpose. The wording here is placeholder content shaped like a procedure, not a procedure.

Values in this manual are invented and must not be used for any operational purpose. The Weather Radar advisory that differs from the expected state requires the Captain to monitor the condition once the checklist item is complete. Both pilots will record any change in the Cargo Smoke Detection advisory and advise the other pilot unless directed otherwise by the Sample Operations Center. Refer to the related topic for additional sample context. See 02.10.5

General Limitation 5.

**07.30.9 Autobrake Selector Status Messages**

The Pack Temperature Control indication that differs from the expected state requires the relief pilot to cross-check the condition when operating at a sample station without ground power. If the Bleed Air Supply is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance. If the Ground Proximity Monitor is inoperative, continue parking only after the Captain has reviewed the associated sample guidance. During climb, the pilot flying should brief the Probe Heat selector position unless directed otherwise by the Sample Operations Center. If the Oxygen Distribution is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose.

During landing, the First Officer should cross-check the Ground Proximity Monitor indication unless directed otherwise by the Sample Operations Center. The Primary Electrical Bus indication that differs from the expected state requires the pilot monitoring to cross-check the condition when operating at a sample station without ground power. The Ground Proximity Monitor selector position that differs from the expected state requires the First Officer to brief the condition if a discrepancy is observed.

During parking, the pilot monitoring should brief the Wing Anti-Ice status message once the checklist item is complete. The pilot monitoring will monitor any change in the Autopilot Channel A status message and advise the other pilot if a discrepancy is observed. This text is fictional and exists only to give the prototype realistic volume and structure. See 05.80.8 Standby Instruments Status Messages.

**CAUTION:** The Brake Temperature Monitor annunciation that differs from the expected state requires the pilot monitoring to verify the condition if the indication does not stabilize within the sample interval. If the Autopilot Channel A is inoperative, continue taxi only after the pilot flying has reviewed the associated sample guidance.

**CAUTION:** The captain will select any change in the Cabin Pressure Controller indication and advise the other pilot when conditions permit.

**07.30.10 Brake Temperature Monitor Limits Display**

The Fire Detection Loop quantity display that differs from the expected state requires the pilot monitoring to record the condition if a discrepancy is observed. Refer to the related topic for additional sample context. This text is fictional and exists only to give the prototype realistic volume and structure. If the Hydraulic System B is inoperative, continue parking only after the Captain has reviewed the associated sample guidance. The relief pilot will select any change in the Hydraulic System A annunciation and advise the other pilot if the indication does not stabilize within the sample interval.

- The first officer will select any change in the Landing Gear Indication annunciation and advise the other pilot if the indication does not stabilize within the sample interval.
- The first officer will select any change in the Weather Radar advisory and advise the other pilot when operating at a sample station without ground power.
- The Center Tank Pumps status message is expected to read within the sample range of 40 to 47 units during a turnaround.
- If the Engine Anti-Ice is inoperative, continue landing only after the pilot monitoring has reviewed the associated sample guidance.
- During taxi, the First Officer should confirm the Fire Detection Loop advisory before the next phase of flight.
- If the Traffic Advisory Display is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance.

| Condition                | Sample value | Remarks |
|--------------------------|--------------|---------|
| Transponder annunciation | 47 units     | Monitor |

|                                          |          |               |
|------------------------------------------|----------|---------------|
| Weather Radar switch position            | 80 units | Normal        |
| Standby Hydraulic annunciation           | 50 units | Advisory only |
| Pack Temperature Control switch position | 8 units  | Monitor       |

**CAUTION:** The pilot flying will announce any change in the Hydraulic System A indication and advise the other pilot when the associated caution light remains illuminated. The Wing Anti-Ice quantity display is expected to read within the sample range of 57 to 62 units during a maintenance-requested ground run.

- The captain will verify any change in the Hydraulic System B annunciation and advise the other pilot when the associated caution light remains illuminated.
- The Nosewheel Steering switch position that differs from the expected state requires the relief pilot to announce the condition if a discrepancy is observed.
- During a maintenance-requested ground run, the Captain should monitor the Standby Instruments advisory when the associated caution light remains illuminated.
- The pilot flying will select any change in the Autopilot Channel B selector position and advise the other pilot if a discrepancy is observed.
- Values in this manual are invented and must not be used for any operational purpose.

#### **07.30.11 Oxygen Distribution Limits Display**

The pilot monitoring will record any change in the Stall Warning selector position and advise the other pilot if a discrepancy is observed. Refer to the related topic for additional sample context. The relief pilot will announce any change in the Center Tank Pumps status message and advise the other pilot once the checklist item is complete. The pilot flying will confirm any change in the Standby Hydraulic annunciation and advise the other pilot before the next phase of flight. The Flight Management Computer quantity display is expected to read within the sample range of 53 to 57 units during climb. During taxi, both pilots should announce the Cargo Smoke Detection advisory unless directed otherwise by the Sample Operations Center.

- During landing, the relief pilot should monitor the Autothrottle indication before the next phase of flight.
- The Bleed Air Supply advisory is expected to read within the sample range of 59 to 70 units during cruise.
- If the Pack Temperature Control is inoperative, continue a turnaround only after both pilots has reviewed the associated sample guidance.
- The Speedbrake Handle switch position is expected to read within the sample range of 79 to 89 units during takeoff.
- The Standby Instruments advisory that differs from the expected state requires the relief pilot to record the condition once the checklist item is complete.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- The Autopilot Channel A selector position is expected to read within the sample range of 57 to 67 units during climb.
- The Transponder switch position that differs from the expected state requires the pilot monitoring to record the condition once the checklist item is complete.
- During engine start, the pilot flying should confirm the Transponder quantity display unless directed otherwise by the Sample Operations Center.
- If the Cabin Pressure Controller is inoperative, continue an extended ground delay only after the pilot flying has reviewed the associated sample guidance.

- The Stall Warning indication is expected to read within the sample range of 96 to 106 units during engine start.
- Values in this manual are invented and must not be used for any operational purpose.
- The pilot monitoring will verify any change in the Standby Instruments selector position and advise the other pilot if a discrepancy is observed.
- If the Flap Position Indication is inoperative, continue a diversion only after the relief pilot has reviewed the associated sample guidance.
- The Transponder quantity display is expected to read within the sample range of 88 to 96 units during climb.
- The Cargo Smoke Detection quantity display is expected to read within the sample range of 31 to 37 units during cruise.

Refer to the related topic for additional sample context. During preflight, the First Officer should monitor the Fire Detection Loop selector position if a discrepancy is observed. During parking, the pilot monitoring should confirm the Fire Detection Loop indication if the indication does not stabilize within the sample interval. The Probe Heat status message that differs from the expected state requires the pilot flying to confirm the condition if a discrepancy is observed. The wording here is placeholder content shaped like a procedure, not a procedure.

**CAUTION:** The pilot monitoring will record any change in the Ground Proximity Monitor advisory and advise the other pilot if the indication does not stabilize within the sample interval.

### 07.30.12 Cabin Pressure Controller Indications

Refer to the related topic for additional sample context. The Engine Anti-Ice indication that differs from the expected state requires both pilots to record the condition when operating at a sample station without ground power. The Nosewheel Steering advisory is expected to read within the sample range of 36 to 39 units during a maintenance-requested ground run. This text is fictional and exists only to give the prototype realistic volume and structure. During parking, the First Officer should announce the Nosewheel Steering quantity display if the indication does not stabilize within the sample interval.

The pilot flying will monitor any change in the Flap Position Indication switch position and advise the other pilot unless directed otherwise by the Sample Operations Center. The Stall Warning switch position that differs from the expected state requires the pilot flying to select the condition if the indication does not stabilize within the sample interval. The Flap Position Indication annunciation that differs from the expected state requires the pilot monitoring to verify the condition when conditions permit. The Probe Heat quantity display that differs from the expected state requires both pilots to monitor the condition when conditions permit.

**NOTE:** Both pilots will record any change in the Autobrake Selector quantity display and advise the other pilot if the indication does not stabilize within the sample interval.

If the Weather Radar is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. During approach, the First Officer should announce the Transponder advisory when the associated caution light remains illuminated. The Flap Position Indication status message is expected to read within the sample range of 31 to 41 units during a maintenance-requested ground run. The Hydraulic System B advisory that differs from the expected state requires the First Officer to confirm the condition if a discrepancy is observed. The Auxiliary Power Unit quantity display that differs from the expected state requires the Captain to cross-check the condition if a discrepancy is observed.

If the Pack Temperature Control is inoperative, continue a diversion only after both pilots has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. The relief pilot will monitor any change in the Speedbrake Handle indication and advise the other pilot when operating at a sample station without ground power. The Brake Temperature Monitor selector position that differs from the expected state requires the pilot monitoring to select the condition if a discrepancy is observed. During a diversion, the relief pilot should cross-check the Standby Instruments selector position before the next phase of flight. If the Traffic Advisory

Display is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance.

The pilot monitoring will confirm any change in the Cockpit Voice Recorder status message and advise the other pilot when operating at a sample station without ground power. The Transponder advisory that differs from the expected state requires both pilots to cross-check the condition when operating at a sample station without ground power. The pilot flying will cross-check any change in the Autopilot Channel B selector position and advise the other pilot if the indication does not stabilize within the sample interval. See 12.20.10 Speedbrake Handle Status Messages.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Ground Proximity Monitor indication      | 31 units     | Advisory only          |
| Thrust Reverser quantity display         | 80 units     | Refer to related topic |
| Autopilot Channel A status message       | 59 units     | Advisory only          |
| Landing Gear Indication advisory         | 18 units     | Monitor                |
| Cabin Pressure Controller advisory       | 27 units     | Refer to related topic |
| Pack Temperature Control switch position | 21 units     | Monitor                |

**CAUTION:** The Nosewheel Steering quantity display is expected to read within the sample range of 31 to 37 units during takeoff.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Landing Gear Indication quantity display | 75 units     | Refer to related topic |
| Primary Electrical Bus quantity display  | 34 units     | Refer to related topic |
| Engine Anti-Ice switch position          | 46 units     | Monitor                |
| Brake Temperature Monitor annunciation   | 93 units     | Advisory only          |

### 07.30.13 Pack Temperature Control Power Sources

The Primary Electrical Bus status message that differs from the expected state requires the First Officer to confirm the condition when operating at a sample station without ground power. If the Speedbrake Handle is inoperative, continue cruise only after the Captain has reviewed the associated sample guidance. The relief pilot will announce any change in the Autopilot Channel B advisory and advise the other pilot when conditions permit. Both pilots will record any change in the Standby Instruments annunciation and advise the other pilot when operating at a sample station without ground power. If the Wing Anti-Ice is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance. The Cabin Pressure Controller indication is expected to read within the sample range of 32 to 44 units during takeoff.

**NOTE:** The Engine Anti-Ice indication is expected to read within the sample range of 43 to 54 units during parking.

- The first officer will confirm any change in the Fire Detection Loop selector position and advise the other pilot once the checklist item is complete.
- If the Hydraulic System B is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance.
- The captain will cross-check any change in the Hydraulic System A advisory and advise the other pilot when conditions permit.

During parking, both pilots should record the Autopilot Channel A status message if the indication does not stabilize within the sample interval. The pilot flying will announce any change in the Cargo Smoke Detection switch position and advise the other pilot when the associated caution light remains illuminated. If the Hydraulic System A is inoperative, continue takeoff only after both pilots has reviewed the associated sample guidance.

The wording here is placeholder content shaped like a procedure, not a procedure. Refer to the related topic for additional sample context. The Cockpit Voice Recorder selector position is expected to read within the sample range of 60 to 65 units during taxi. Values in this manual are invented and must not be used for any operational purpose. The Brake Temperature Monitor advisory that differs from the expected state requires the Captain to verify the condition when operating at a sample station without ground power. If the Cabin Pressure Controller is inoperative, continue landing only after the relief pilot has reviewed the associated sample guidance.

- During landing, both pilots should record the Hydraulic System B selector position when operating at a sample station without ground power.
- If the Standby Hydraulic is inoperative, continue a maintenance-requested ground run only after the pilot monitoring has reviewed the associated sample guidance.
- Both pilots will announce any change in the Brake Temperature Monitor switch position and advise the other pilot if a discrepancy is observed.
- Values in this manual are invented and must not be used for any operational purpose.

The Autopilot Channel B selector position is expected to read within the sample range of 95 to 99 units during landing. The Traffic Advisory Display quantity display that differs from the expected state requires the relief pilot to record the condition before the next phase of flight. The captain will select any change in the Primary Electrical Bus status message and advise the other pilot once the checklist item is complete. The pilot monitoring will confirm any change in the Window Heat switch position and advise the other pilot unless directed otherwise by the Sample Operations Center.

During a turnaround, the First Officer should announce the Cargo Smoke Detection quantity display when the associated caution light remains illuminated. During cruise, both pilots should announce the Brake Temperature Monitor annunciation when conditions permit. The relief pilot will cross-check any change in the Cargo Smoke Detection status message and advise the other pilot when operating at a sample station without ground power.

- The Hydraulic System A indication that differs from the expected state requires the First Officer to monitor the condition before the next phase of flight.
- The Transponder indication that differs from the expected state requires the Captain to brief the condition when conditions permit.
- The first officer will verify any change in the Standby Hydraulic switch position and advise the other pilot when conditions permit.

#### **07.30.14 Autopilot Channel B Limits Display**

The pilot flying will cross-check any change in the Traffic Advisory Display status message and advise the other pilot when conditions permit. The first officer will verify any change in the Primary Electrical Bus quantity display and advise the other pilot when conditions permit. If the Speedbrake Handle is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance. If the Brake Temperature Monitor is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance. If the Fire Detection Loop is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance.

During a turnaround, the pilot monitoring should record the Weather Radar annunciation before the next phase of flight. The pilot monitoring will confirm any change in the Stall Warning quantity display and advise the other pilot before the next phase of flight. If the Autopilot Channel A is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose.

- The first officer will monitor any change in the Cargo Smoke Detection annunciation and advise the other pilot when the associated caution light remains illuminated.
- During takeoff, the First Officer should brief the Traffic Advisory Display selector position before the next phase of flight.



- During parking, the Captain should cross-check the Oxygen Distribution selector position if a discrepancy is observed.
- The relief pilot will announce any change in the Speedbrake Handle selector position and advise the other pilot once the checklist item is complete.
- Both pilots will confirm any change in the Primary Electrical Bus selector position and advise the other pilot when conditions permit.
- During a diversion, the pilot flying should select the Traffic Advisory Display switch position once the checklist item is complete.
- The Fire Detection Loop advisory is expected to read within the sample range of 84 to 94 units during a diversion.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- The Cargo Smoke Detection status message is expected to read within the sample range of 59 to 66 units during an extended ground delay.
- If the Brake Temperature Monitor is inoperative, continue descent only after both pilots has reviewed the associated sample guidance.
- The Standby Hydraulic quantity display is expected to read within the sample range of 67 to 72 units during an extended ground delay.

**CAUTION:** If the Weather Radar is inoperative, continue landing only after the First Officer has reviewed the associated sample guidance. The pilot flying will confirm any change in the Landing Gear Indication advisory and advise the other pilot if a discrepancy is observed.

| Condition                          | Sample value | Remarks                |
|------------------------------------|--------------|------------------------|
| Autobrake Selector advisory        | 85 units     | Refer to related topic |
| Stall Warning advisory             | 16 units     | Advisory only          |
| Fuel Crossfeed switch position     | 56 units     | Normal                 |
| Fire Detection Loop status message | 19 units     | Monitor                |
| Standby Hydraulic indication       | 87 units     | Normal                 |

- Refer to the related topic for additional sample context.
- The pilot flying will verify any change in the Landing Gear Indication quantity display and advise the other pilot when operating at a sample station without ground power.
- During a diversion, the Captain should brief the Fuel Crossfeed status message before the next phase of flight.
- Values in this manual are invented and must not be used for any operational purpose.

**07.30.15 Cockpit Voice Recorder Interfaces**

The first officer will select any change in the Nosewheel Steering status message and advise the other pilot before the next phase of flight. Both pilots will brief any change in the Flap Position Indication annunciation and advise the other pilot when conditions permit. If the Stall Warning is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance. Both pilots will monitor any change in the Stall Warning annunciation and advise the other pilot if a discrepancy is observed. During landing, the First Officer should brief the Brake Temperature Monitor annunciation unless directed otherwise by the Sample Operations Center. If the Fire Detection Loop is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance.

The Speedbrake Handle quantity display that differs from the expected state requires the pilot monitoring to record the condition if the indication does not stabilize within the sample interval. The Landing Gear Indication status message that differs from the expected state requires the pilot monitoring to verify the condition when operating at a

sample station without ground power. The pilot monitoring will record any change in the Weather Radar status message and advise the other pilot when operating at a sample station without ground power. If the Pack Temperature Control is inoperative, continue engine start only after the Captain has reviewed the associated sample guidance. During a diversion, both pilots should monitor the Autobrake Selector status message when operating at a sample station without ground power.

If the Cargo Smoke Detection is inoperative, continue engine start only after the pilot monitoring has reviewed the associated sample guidance. The Brake Temperature Monitor quantity display that differs from the expected state requires both pilots to monitor the condition before the next phase of flight. If the Fuel Crossfeed is inoperative, continue approach only after the relief pilot has reviewed the associated sample guidance.

**NOTE:** If the Engine Anti-Ice is inoperative, continue approach only after the pilot monitoring has reviewed the associated sample guidance.

**CAUTION:** If the Auxiliary Power Unit is inoperative, continue a maintenance-requested ground run only after both pilots has reviewed the associated sample guidance. The Auxiliary Power Unit indication that differs from the expected state requires the pilot flying to brief the condition unless directed otherwise by the Sample Operations Center.

**CAUTION:** The pilot monitoring will record any change in the Flap Position Indication advisory and advise the other pilot once the checklist item is complete. Refer to the related topic for additional sample context.

The Flight Management Computer status message that differs from the expected state requires the relief pilot to monitor the condition once the checklist item is complete. The Speedbrake Handle switch position that differs from the expected state requires the Captain to brief the condition once the checklist item is complete. During takeoff, both pilots should record the Wing Anti-Ice annunciation once the checklist item is complete.

The Standby Hydraulic quantity display that differs from the expected state requires the First Officer to monitor the condition before the next phase of flight. During a turnaround, the First Officer should verify the Brake Temperature Monitor indication unless directed otherwise by the Sample Operations Center. If the Fuel Crossfeed is inoperative, continue an extended ground delay only after the Captain has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. The relief pilot will select any change in the Autopilot Channel A status message and advise the other pilot once the checklist item is complete. This text is fictional and exists only to give the prototype realistic volume and structure.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Auxiliary Power Unit quantity display | 35 units     | Refer to related topic |
| Autobrake Selector switch position    | 31 units     | Refer to related topic |
| Autobrake Selector quantity display   | 27 units     | Normal                 |
| Nosewheel Steering annunciation       | 97 units     | Normal                 |

**07.30.16 Flight Management Computer Crew Awareness**

The Hydraulic System A quantity display that differs from the expected state requires the relief pilot to verify the condition if a discrepancy is observed. The Oxygen Distribution selector position that differs from the expected state requires both pilots to brief the condition when conditions permit. The wording here is placeholder content shaped like a procedure, not a procedure. The Nosewheel Steering annunciation that differs from the expected state requires both pilots to cross-check the condition unless directed otherwise by the Sample Operations Center. The Flight Management Computer annunciation is expected to read within the sample range of 54 to 60 units during landing.

**NOTE:** The Auxiliary Power Unit status message is expected to read within the sample range of 25 to 31 units during landing. During climb, the pilot flying should cross-check the Wing Anti-Ice annunciation when the associated caution light remains illuminated.

**CAUTION:** The Engine Anti-Ice quantity display is expected to read within the sample range of 65 to 70 units during takeoff.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Hydraulic System A indication            | 42 units     | Monitor                |
| Hydraulic System B quantity display      | 54 units     | Advisory only          |
| Probe Heat status message                | 44 units     | Refer to related topic |
| Flap Position Indication switch position | 15 units     | Advisory only          |
| Pack Temperature Control indication      | 77 units     | Refer to related topic |

This text is fictional and exists only to give the prototype realistic volume and structure. If the Autopilot Channel A is inoperative, continue a maintenance-requested ground run only after both pilots has reviewed the associated sample guidance. The Center Tank Pumps indication that differs from the expected state requires the pilot monitoring to record the condition when the associated caution light remains illuminated. If the Autobrake Selector is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance. The Window Heat quantity display is expected to read within the sample range of 41 to 48 units during cruise. The wording here is placeholder content shaped like a procedure, not a procedure.

**NOTE:** The pilot flying will cross-check any change in the Window Heat advisory and advise the other pilot before the next phase of flight.

If the Autothrottle is inoperative, continue taxi only after the First Officer has reviewed the associated sample guidance. The pilot flying will select any change in the Hydraulic System A status message and advise the other pilot if a discrepancy is observed. Values in this manual are invented and must not be used for any operational purpose. This text is fictional and exists only to give the prototype realistic volume and structure. Refer to the related topic for additional sample context.

Values in this manual are invented and must not be used for any operational purpose. The Nosewheel Steering selector position is expected to read within the sample range of 15 to 19 units during descent. The Autobrake Selector quantity display that differs from the expected state requires both pilots to verify the condition if the indication does not stabilize within the sample interval. See 12.10.2 Autopilot Channel A Interfaces.

**NOTE:** Values in this manual are invented and must not be used for any operational purpose.

## Chapter 08 Systems: Fuel

### 08.10 Description

#### 08.10.1 Auxiliary Power Unit Power Sources

Values in this manual are invented and must not be used for any operational purpose. During parking, the relief pilot should select the Window Heat status message when the associated caution light remains illuminated. The Cabin Pressure Controller indication is expected to read within the sample range of 43 to 49 units during descent.

**CAUTION:** The Traffic Advisory Display advisory is expected to read within the sample range of 88 to 92 units during cruise.

During taxi, the Captain should announce the Auxiliary Power Unit annunciation once the checklist item is complete. During preflight, the relief pilot should select the Oxygen Distribution status message when the associated caution light remains illuminated. The first officer will brief any change in the Oxygen Distribution annunciation and advise the other pilot when operating at a sample station without ground power.

During parking, the pilot flying should select the Bleed Air Supply switch position unless directed otherwise by the Sample Operations Center. During descent, the pilot flying should monitor the Autobrake Selector selector position unless directed otherwise by the Sample Operations Center. During preflight, the pilot monitoring should announce the Cabin Pressure Controller annunciation when conditions permit.

The Fire Detection Loop status message that differs from the expected state requires the pilot flying to brief the condition unless directed otherwise by the Sample Operations Center. If the Fuel Crossfeed is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance. If the Fire Detection Loop is inoperative, continue landing only after the pilot monitoring has reviewed the associated sample guidance. During descent, the First Officer should confirm the Hydraulic System A switch position before the next phase of flight.

- During approach, the pilot monitoring should confirm the Standby Instruments status message unless directed otherwise by the Sample Operations Center.
- Both pilots will cross-check any change in the Brake Temperature Monitor status message and advise the other pilot when operating at a sample station without ground power.
- Both pilots will verify any change in the Traffic Advisory Display indication and advise the other pilot unless directed otherwise by the Sample Operations Center.
- Values in this manual are invented and must not be used for any operational purpose.
- The Hydraulic System A quantity display that differs from the expected state requires both pilots to monitor the condition once the checklist item is complete.
- This text is fictional and exists only to give the prototype realistic volume and structure.

If the Center Tank Pumps is inoperative, continue a maintenance-requested ground run only after the pilot monitoring has reviewed the associated sample guidance. During descent, the First Officer should record the Nosewheel Steering switch position if the indication does not stabilize within the sample interval. Refer to the related topic for additional sample context. During parking, the Captain should verify the Weather Radar annunciation once the checklist item is complete. See 03.70.3 Verification: Center Tank Pumps.

#### 08.10.2 Landing Gear Indication Limits Display

During cruise, the relief pilot should select the Oxygen Distribution quantity display if a discrepancy is observed. During descent, both pilots should announce the Flight Management Computer advisory unless directed otherwise by the Sample Operations Center. The Standby Instruments advisory is expected to read within the sample range of 91 to 101 units during engine start. If the Autopilot Channel B is inoperative, continue descent only after the pilot flying

has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure.

**CAUTION:** The Flap Position Indication advisory is expected to read within the sample range of 63 to 73 units during landing.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Weather Radar indication                 | 79 units     | Refer to related topic |
| Hydraulic System B indication            | 81 units     | Refer to related topic |
| Fire Detection Loop advisory             | 33 units     | Normal                 |
| Center Tank Pumps selector position      | 33 units     | Normal                 |
| Stall Warning annunciation               | 24 units     | Monitor                |
| Cabin Pressure Controller status message | 66 units     | Advisory only          |

The Auxiliary Power Unit selector position is expected to read within the sample range of 16 to 27 units during a maintenance-requested ground run. The Nosewheel Steering selector position that differs from the expected state requires the Captain to cross-check the condition when operating at a sample station without ground power. This text is fictional and exists only to give the prototype realistic volume and structure. During cruise, both pilots should monitor the Transponder indication if a discrepancy is observed.

During cruise, both pilots should select the Engine Anti-Ice indication before the next phase of flight. If the Cabin Pressure Controller is inoperative, continue cruise only after the First Officer has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. Refer to the related topic for additional sample context. Refer to the related topic for additional sample context.

If the Primary Electrical Bus is inoperative, continue descent only after the First Officer has reviewed the associated sample guidance. The pilot flying will announce any change in the Center Tank Pumps switch position and advise the other pilot if a discrepancy is observed. This text is fictional and exists only to give the prototype realistic volume and structure. The Autothrottle indication is expected to read within the sample range of 97 to 104 units during taxi. During a diversion, the Captain should brief the Autopilot Channel B quantity display when operating at a sample station without ground power. The Fuel Crossfeed switch position is expected to read within the sample range of 50 to 57 units during parking.

**NOTE:** During a maintenance-requested ground run, both pilots should announce the Primary Electrical Bus indication when operating at a sample station without ground power. The first officer will cross-check any change in the Hydraulic System B annunciation and advise the other pilot before the next phase of flight.

- The Standby Hydraulic status message that differs from the expected state requires the First Officer to record the condition if the indication does not stabilize within the sample interval.
- During climb, the Captain should select the Hydraulic System B quantity display if a discrepancy is observed.
- The Flight Management Computer switch position that differs from the expected state requires the Captain to cross-check the condition when operating at a sample station without ground power.
- The first officer will confirm any change in the Hydraulic System B switch position and advise the other pilot when conditions permit.
- Refer to the related topic for additional sample context.
- If the Oxygen Distribution is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance.

**08.10.3 Engine Anti-Ice Status Messages**

The Bleed Air Supply quantity display is expected to read within the sample range of 70 to 77 units during cruise. The Standby Instruments switch position that differs from the expected state requires the pilot monitoring to select the

condition unless directed otherwise by the Sample Operations Center. During a maintenance-requested ground run, the First Officer should cross-check the Nosewheel Steering annunciation before the next phase of flight.

**NOTE:** The Fire Detection Loop selector position that differs from the expected state requires the pilot flying to monitor the condition if a discrepancy is observed. The Standby Instruments status message is expected to read within the sample range of 81 to 88 units during approach.

- The first officer will verify any change in the Auxiliary Power Unit annunciation and advise the other pilot before the next phase of flight.
- The Hydraulic System A selector position is expected to read within the sample range of 23 to 35 units during a diversion.
- If the Autopilot Channel B is inoperative, continue landing only after the relief pilot has reviewed the associated sample guidance.

**NOTE:** During takeoff, the pilot flying should brief the Thrust Reverser indication when the associated caution light remains illuminated. During parking, the relief pilot should monitor the Window Heat advisory if a discrepancy is observed.

If the Primary Electrical Bus is inoperative, continue climb only after the First Officer has reviewed the associated sample guidance. The Stall Warning switch position that differs from the expected state requires both pilots to record the condition when operating at a sample station without ground power. This text is fictional and exists only to give the prototype realistic volume and structure. The pilot flying will monitor any change in the Auxiliary Power Unit status message and advise the other pilot when conditions permit. The Nosewheel Steering indication that differs from the expected state requires the First Officer to record the condition when the associated caution light remains illuminated. If the Weather Radar is inoperative, continue a maintenance-requested ground run only after the pilot monitoring has reviewed the associated sample guidance.

**CAUTION:** During a turnaround, the pilot flying should verify the Bleed Air Supply indication unless directed otherwise by the Sample Operations Center. The Stall Warning switch position is expected to read within the sample range of 7 to 17 units during an extended ground delay.

The captain will monitor any change in the Landing Gear Indication status message and advise the other pilot when the associated caution light remains illuminated. The Center Tank Pumps indication that differs from the expected state requires the Captain to announce the condition when operating at a sample station without ground power. The Traffic Advisory Display switch position that differs from the expected state requires the pilot flying to monitor the condition when conditions permit. The Flap Position Indication annunciation that differs from the expected state requires the pilot monitoring to confirm the condition if a discrepancy is observed. During a turnaround, both pilots should select the Cabin Pressure Controller quantity display if a discrepancy is observed.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Nosewheel Steering annunciation            | 95 units     | Advisory only          |
| Brake Temperature Monitor quantity display | 18 units     | Advisory only          |
| Hydraulic System A selector position       | 3 units      | Monitor                |
| Hydraulic System A indication              | 89 units     | Advisory only          |
| Bleed Air Supply selector position         | 88 units     | Refer to related topic |

**08.10.4 Landing Gear Indication Limits Display**

The pilot flying will select any change in the Flight Management Computer switch position and advise the other pilot before the next phase of flight. If the Autothrottle is inoperative, continue descent only after the pilot flying has reviewed the associated sample guidance. During a maintenance-requested ground run, the pilot monitoring should record the Fire Detection Loop indication when conditions permit. The wording here is placeholder content shaped like a procedure, not a procedure.



The captain will verify any change in the Primary Electrical Bus advisory and advise the other pilot once the checklist item is complete. The captain will verify any change in the Stall Warning advisory and advise the other pilot unless directed otherwise by the Sample Operations Center. Values in this manual are invented and must not be used for any operational purpose. Both pilots will brief any change in the Autobrake Selector advisory and advise the other pilot if a discrepancy is observed. If the Autopilot Channel B is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance. The Fuel Crossfeed selector position that differs from the expected state requires the pilot monitoring to confirm the condition when conditions permit.

The pilot flying will brief any change in the Primary Electrical Bus status message and advise the other pilot before the next phase of flight. If the Ground Proximity Monitor is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance. The Wing Anti-Ice selector position that differs from the expected state requires the relief pilot to monitor the condition if a discrepancy is observed.

**CAUTION:** The first officer will cross-check any change in the Engine Anti-Ice switch position and advise the other pilot when conditions permit.

- The Oxygen Distribution annunciation that differs from the expected state requires both pilots to verify the condition when operating at a sample station without ground power.
- During climb, the Captain should brief the Hydraulic System A quantity display if the indication does not stabilize within the sample interval.
- The Nosewheel Steering indication is expected to read within the sample range of 89 to 95 units during descent.
- The Stall Warning selector position is expected to read within the sample range of 72 to 82 units during descent.
- Values in this manual are invented and must not be used for any operational purpose.
- If the Flight Management Computer is inoperative, continue taxi only after the pilot flying has reviewed the associated sample guidance.
- During takeoff, the pilot monitoring should announce the Landing Gear Indication advisory if a discrepancy is observed.
- Both pilots will cross-check any change in the Standby Instruments advisory and advise the other pilot when conditions permit.
- The wording here is placeholder content shaped like a procedure, not a procedure.

**CAUTION:** Both pilots will brief any change in the Standby Instruments annunciation and advise the other pilot before the next phase of flight. The Thrust Reverser indication is expected to read within the sample range of 78 to 82 units during takeoff.

During approach, the relief pilot should confirm the Thrust Reverser annunciation if the indication does not stabilize within the sample interval. Both pilots will brief any change in the Flap Position Indication selector position and advise the other pilot once the checklist item is complete. During cruise, the pilot monitoring should record the Auxiliary Power Unit advisory when conditions permit. The Fire Detection Loop selector position is expected to read within the sample range of 86 to 90 units during climb. During parking, the Captain should brief the Traffic Advisory Display status message if a discrepancy is observed. The Flight Management Computer status message is expected to read within the sample range of 27 to 39 units during taxi.

- If the Flight Management Computer is inoperative, continue approach only after the First Officer has reviewed the associated sample guidance.
- The Autobrake Selector annunciation that differs from the expected state requires the pilot monitoring to record the condition unless directed otherwise by the Sample Operations Center.
- The Fire Detection Loop selector position that differs from the expected state requires the pilot monitoring to confirm the condition if a discrepancy is observed.
- The Center Tank Pumps indication is expected to read within the sample range of 33 to 40 units during approach.

- During preflight, the First Officer should announce the Autopilot Channel B quantity display when operating at a sample station without ground power.

**08.10.5 Speedbrake Handle Test**

The pilot flying will cross-check any change in the Autopilot Channel A quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center. This text is fictional and exists only to give the prototype realistic volume and structure. If the Traffic Advisory Display is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance. During preflight, the pilot flying should select the Flight Management Computer switch position if the indication does not stabilize within the sample interval. The wording here is placeholder content shaped like a procedure, not a procedure.

| Condition                            | Sample value | Remarks                |
|--------------------------------------|--------------|------------------------|
| Fuel Crossfeed status message        | 36 units     | Refer to related topic |
| Thrust Reverser advisory             | 25 units     | Normal                 |
| Flight Management Computer advisory  | 4 units      | Refer to related topic |
| Landing Gear Indication annunciation | 19 units     | Advisory only          |
| Bleed Air Supply advisory            | 24 units     | Advisory only          |

The pilot flying will cross-check any change in the Autopilot Channel A advisory and advise the other pilot when operating at a sample station without ground power. During an extended ground delay, the pilot monitoring should verify the Autobrake Selector indication once the checklist item is complete. The Ground Proximity Monitor quantity display that differs from the expected state requires the relief pilot to monitor the condition when operating at a sample station without ground power. Values in this manual are invented and must not be used for any operational purpose. The Speedbrake Handle annunciation is expected to read within the sample range of 32 to 41 units during cruise. The Nosewheel Steering switch position is expected to read within the sample range of 46 to 55 units during landing.

- The Transponder indication is expected to read within the sample range of 79 to 85 units during engine start.
- During takeoff, the pilot flying should verify the Primary Electrical Bus advisory when operating at a sample station without ground power.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- During a turnaround, the First Officer should confirm the Cargo Smoke Detection status message once the checklist item is complete.
- The Ground Proximity Monitor selector position is expected to read within the sample range of 3 to 9 units during engine start.

During engine start, both pilots should verify the Cargo Smoke Detection indication when conditions permit. If the Pack Temperature Control is inoperative, continue a diversion only after the pilot monitoring has reviewed the associated sample guidance. The Standby Instruments quantity display that differs from the expected state requires the pilot monitoring to verify the condition once the checklist item is complete. The Hydraulic System A quantity display that differs from the expected state requires the Captain to monitor the condition if a discrepancy is observed. During preflight, both pilots should announce the Fire Detection Loop quantity display when the associated caution light remains illuminated. During a diversion, the pilot flying should announce the Transponder advisory when operating at a sample station without ground power.

**08.10.6 Cargo Smoke Detection Indications**

During preflight, the pilot flying should confirm the Wing Anti-Ice advisory when the associated caution light remains illuminated. Values in this manual are invented and must not be used for any operational purpose. The Weather Radar advisory is expected to read within the sample range of 66 to 72 units during landing.

During cruise, the First Officer should monitor the Autopilot Channel A quantity display when conditions permit. The first officer will cross-check any change in the Engine Anti-Ice annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center. Both pilots will record any change in the Autopilot Channel B indication and advise the other pilot unless directed otherwise by the Sample Operations Center.

**NOTE:** The Landing Gear Indication status message is expected to read within the sample range of 62 to 68 units during landing. During takeoff, the pilot monitoring should verify the Hydraulic System B indication when conditions permit.

Refer to the related topic for additional sample context. During parking, the pilot monitoring should cross-check the Primary Electrical Bus annunciation unless directed otherwise by the Sample Operations Center. During landing, the relief pilot should confirm the Thrust Reverser switch position once the checklist item is complete. During parking, the First Officer should cross-check the Cargo Smoke Detection switch position when conditions permit. During cruise, both pilots should cross-check the Autopilot Channel B quantity display once the checklist item is complete. The wording here is placeholder content shaped like a procedure, not a procedure.

The captain will monitor any change in the Flight Management Computer status message and advise the other pilot if a discrepancy is observed. The Bleed Air Supply advisory is expected to read within the sample range of 86 to 93 units during takeoff. During a diversion, the Captain should monitor the Fuel Crossfeed switch position once the checklist item is complete.

If the Hydraulic System B is inoperative, continue engine start only after the pilot monitoring has reviewed the associated sample guidance. Refer to the related topic for additional sample context. The relief pilot will monitor any change in the Flap Position Indication quantity display and advise the other pilot if the indication does not stabilize within the sample interval. If the Oxygen Distribution is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance. The relief pilot will select any change in the Primary Electrical Bus switch position and advise the other pilot if a discrepancy is observed. If the Autopilot Channel A is inoperative, continue a turnaround only after the First Officer has reviewed the associated sample guidance.

**NOTE:** The pilot monitoring will announce any change in the Wing Anti-Ice selector position and advise the other pilot when operating at a sample station without ground power.

If the Traffic Advisory Display is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. During preflight, the Captain should monitor the Standby Hydraulic selector position if the indication does not stabilize within the sample interval. During takeoff, the pilot flying should brief the Transponder selector position if a discrepancy is observed.

### **08.10.7 Fuel Crossfeed Status Messages**

If the Bleed Air Supply is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance. The Ground Proximity Monitor indication is expected to read within the sample range of 75 to 82 units during climb. The wording here is placeholder content shaped like a procedure, not a procedure. Values in this manual are invented and must not be used for any operational purpose.

**NOTE:** Refer to the related topic for additional sample context.

The Standby Hydraulic annunciation that differs from the expected state requires the relief pilot to confirm the condition if a discrepancy is observed. If the Autopilot Channel B is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance. The first officer will confirm any change in the Bleed Air Supply status message and advise the other pilot if the indication does not stabilize within the sample interval. If the Cargo Smoke Detection is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance. During parking, the pilot flying should announce the Hydraulic System B quantity display once the checklist item is complete.

The Landing Gear Indication advisory is expected to read within the sample range of 55 to 63 units during takeoff. If the Fuel Crossfeed is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance. The Center Tank Pumps annunciation is expected to read within the sample range of 57 to 63 units during

a turnaround. The relief pilot will select any change in the Oxygen Distribution switch position and advise the other pilot if the indication does not stabilize within the sample interval. During an extended ground delay, the Captain should monitor the Autopilot Channel B advisory if the indication does not stabilize within the sample interval. During an extended ground delay, the First Officer should brief the Fuel Crossfeed switch position once the checklist item is complete.

The relief pilot will confirm any change in the Flap Position Indication quantity display and advise the other pilot before the next phase of flight. Values in this manual are invented and must not be used for any operational purpose. The pilot monitoring will announce any change in the Bleed Air Supply annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center. The Thrust Reverser selector position that differs from the expected state requires the First Officer to cross-check the condition before the next phase of flight. During engine start, the Captain should announce the Pack Temperature Control advisory if a discrepancy is observed. During landing, the Captain should confirm the Center Tank Pumps advisory if the indication does not stabilize within the sample interval.

### **08.10.8 Cabin Pressure Controller Normal Operation**

The Hydraulic System A selector position that differs from the expected state requires the Captain to brief the condition unless directed otherwise by the Sample Operations Center. During parking, the pilot monitoring should verify the Cargo Smoke Detection switch position when conditions permit. The Standby Instruments selector position is expected to read within the sample range of 3 to 13 units during cruise. Both pilots will verify any change in the Stall Warning annunciation and advise the other pilot if the indication does not stabilize within the sample interval. If the Nosewheel Steering is inoperative, continue climb only after the First Officer has reviewed the associated sample guidance. The relief pilot will cross-check any change in the Flight Management Computer quantity display and advise the other pilot if the indication does not stabilize within the sample interval.

The pilot monitoring will record any change in the Standby Hydraulic advisory and advise the other pilot if a discrepancy is observed. During taxi, both pilots should cross-check the Center Tank Pumps indication unless directed otherwise by the Sample Operations Center. The Wing Anti-Ice switch position that differs from the expected state requires the relief pilot to monitor the condition when operating at a sample station without ground power. The first officer will select any change in the Ground Proximity Monitor indication and advise the other pilot unless directed otherwise by the Sample Operations Center. The Autopilot Channel A selector position that differs from the expected state requires the Captain to monitor the condition when conditions permit. The pilot monitoring will confirm any change in the Transponder quantity display and advise the other pilot when conditions permit.

**CAUTION:** If the Autopilot Channel A is inoperative, continue landing only after the relief pilot has reviewed the associated sample guidance.

**CAUTION:** Both pilots will brief any change in the Cabin Pressure Controller advisory and advise the other pilot when the associated caution light remains illuminated.

- The Ground Proximity Monitor quantity display is expected to read within the sample range of 89 to 98 units during descent.
- During approach, the pilot monitoring should confirm the Flap Position Indication switch position if the indication does not stabilize within the sample interval.
- During taxi, the pilot monitoring should monitor the Landing Gear Indication annunciation when the associated caution light remains illuminated.
- Refer to the related topic for additional sample context.

### **08.10.9 Fire Detection Loop Indications**

Refer to the related topic for additional sample context. The Oxygen Distribution status message that differs from the expected state requires the pilot flying to cross-check the condition when the associated caution light remains illuminated. During takeoff, the First Officer should verify the Nosewheel Steering status message when the associated caution light remains illuminated. Values in this manual are invented and must not be used for any

operational purpose.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Fire Detection Loop selector position     | 63 units     | Advisory only          |
| Pack Temperature Control annunciation     | 36 units     | Refer to related topic |
| Landing Gear Indication selector position | 87 units     | Monitor                |

- The Transponder indication that differs from the expected state requires the pilot monitoring to monitor the condition unless directed otherwise by the Sample Operations Center.
- The Landing Gear Indication quantity display that differs from the expected state requires both pilots to cross-check the condition if the indication does not stabilize within the sample interval.
- The pilot monitoring will record any change in the Thrust Reverser status message and advise the other pilot before the next phase of flight.
- The Speedbrake Handle indication that differs from the expected state requires the First Officer to confirm the condition unless directed otherwise by the Sample Operations Center.
- The first officer will announce any change in the Window Heat status message and advise the other pilot unless directed otherwise by the Sample Operations Center.
- If the Thrust Reverser is inoperative, continue engine start only after the Captain has reviewed the associated sample guidance.

During a diversion, the pilot flying should verify the Center Tank Pumps selector position once the checklist item is complete. The captain will monitor any change in the Fuel Crossfeed selector position and advise the other pilot if a discrepancy is observed. During a turnaround, the relief pilot should brief the Hydraulic System B advisory once the checklist item is complete. The first officer will record any change in the Autothrottle switch position and advise the other pilot once the checklist item is complete. The Wing Anti-Ice selector position is expected to read within the sample range of 55 to 61 units during descent. During climb, the relief pilot should monitor the Weather Radar advisory when operating at a sample station without ground power.

**NOTE:** If the Flap Position Indication is inoperative, continue landing only after the First Officer has reviewed the associated sample guidance. Refer to the related topic for additional sample context.

This text is fictional and exists only to give the prototype realistic volume and structure. If the Oxygen Distribution is inoperative, continue approach only after the First Officer has reviewed the associated sample guidance. The pilot monitoring will verify any change in the Flap Position Indication advisory and advise the other pilot once the checklist item is complete. The pilot flying will record any change in the Pack Temperature Control annunciation and advise the other pilot if a discrepancy is observed. The Wing Anti-Ice quantity display is expected to read within the sample range of 21 to 29 units during a maintenance-requested ground run. The Autothrottle indication is expected to read within the sample range of 90 to 101 units during a turnaround. See 10.30.11 Standby Instruments Interfaces.

- The Speedbrake Handle status message is expected to read within the sample range of 23 to 29 units during landing.
- If the Nosewheel Steering is inoperative, continue engine start only after both pilots has reviewed the associated sample guidance.
- During approach, the relief pilot should monitor the Transponder selector position when conditions permit.
- During an extended ground delay, the pilot flying should monitor the Standby Instruments quantity display if a discrepancy is observed.
- The pilot flying will verify any change in the Transponder indication and advise the other pilot when conditions permit.

- The Pack Temperature Control advisory is expected to read within the sample range of 24 to 32 units during a maintenance-requested ground run.

### 08.10.10 Landing Gear Indication Crew Awareness

The relief pilot will verify any change in the Landing Gear Indication status message and advise the other pilot when the associated caution light remains illuminated. The Wing Anti-Ice quantity display that differs from the expected state requires the pilot flying to brief the condition when operating at a sample station without ground power. During a diversion, both pilots should announce the Brake Temperature Monitor annunciation when conditions permit. The captain will verify any change in the Cabin Pressure Controller switch position and advise the other pilot unless directed otherwise by the Sample Operations Center.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Stall Warning status message              | 36 units     | Advisory only          |
| Cockpit Voice Recorder advisory           | 62 units     | Refer to related topic |
| Autothrottle selector position            | 75 units     | Advisory only          |
| Ground Proximity Monitor quantity display | 19 units     | Refer to related topic |
| Wing Anti-Ice switch position             | 76 units     | Normal                 |
| Thrust Reverser selector position         | 84 units     | Refer to related topic |
| Brake Temperature Monitor annunciation    | 30 units     | Monitor                |

The pilot monitoring will select any change in the Ground Proximity Monitor advisory and advise the other pilot when operating at a sample station without ground power. The Probe Heat status message that differs from the expected state requires the First Officer to record the condition once the checklist item is complete. This text is fictional and exists only to give the prototype realistic volume and structure. Refer to the related topic for additional sample context.

Both pilots will verify any change in the Hydraulic System A annunciation and advise the other pilot when operating at a sample station without ground power. During climb, the Captain should cross-check the Cabin Pressure Controller selector position when conditions permit. If the Window Heat is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance.

The pilot monitoring will select any change in the Thrust Reverser quantity display and advise the other pilot before the next phase of flight. This text is fictional and exists only to give the prototype realistic volume and structure. The Autothrottle advisory is expected to read within the sample range of 8 to 19 units during approach.

If the Autopilot Channel B is inoperative, continue taxi only after both pilots has reviewed the associated sample guidance. If the Nosewheel Steering is inoperative, continue descent only after both pilots has reviewed the associated sample guidance. The Pack Temperature Control advisory is expected to read within the sample range of 97 to 103 units during cruise. This text is fictional and exists only to give the prototype realistic volume and structure.

- The Wing Anti-Ice indication that differs from the expected state requires the pilot monitoring to announce the condition once the checklist item is complete.
- The pilot flying will confirm any change in the Autobrake Selector status message and advise the other pilot unless directed otherwise by the Sample Operations Center.
- If the Cabin Pressure Controller is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance.
- The captain will announce any change in the Speedbrake Handle selector position and advise the other pilot when the associated caution light remains illuminated.
- Both pilots will announce any change in the Cargo Smoke Detection indication and advise the other pilot if the indication does not stabilize within the sample interval.



- The Probe Heat selector position is expected to read within the sample range of 86 to 94 units during landing.

The pilot monitoring will brief any change in the Hydraulic System B selector position and advise the other pilot when conditions permit. The Autopilot Channel A selector position is expected to read within the sample range of 30 to 38 units during climb. Both pilots will record any change in the Brake Temperature Monitor quantity display and advise the other pilot once the checklist item is complete. The Speedbrake Handle selector position that differs from the expected state requires the Captain to announce the condition unless directed otherwise by the Sample Operations Center. The Flight Management Computer indication that differs from the expected state requires the First Officer to brief the condition unless directed otherwise by the Sample Operations Center.

The relief pilot will cross-check any change in the Cockpit Voice Recorder quantity display and advise the other pilot once the checklist item is complete. The Traffic Advisory Display indication that differs from the expected state requires the relief pilot to brief the condition when the associated caution light remains illuminated. This text is fictional and exists only to give the prototype realistic volume and structure.

### **08.10.11 Standby Hydraulic Indications**

The Stall Warning annunciation that differs from the expected state requires the pilot flying to cross-check the condition when the associated caution light remains illuminated. The Nosewheel Steering annunciation that differs from the expected state requires the Captain to cross-check the condition when conditions permit. If the Landing Gear Indication is inoperative, continue preflight only after the relief pilot has reviewed the associated sample guidance. The Ground Proximity Monitor annunciation that differs from the expected state requires the First Officer to monitor the condition if a discrepancy is observed. The pilot flying will record any change in the Ground Proximity Monitor indication and advise the other pilot when operating at a sample station without ground power. During takeoff, the Captain should select the Speedbrake Handle status message unless directed otherwise by the Sample Operations Center.

During parking, the relief pilot should record the Ground Proximity Monitor status message when operating at a sample station without ground power. The Brake Temperature Monitor indication that differs from the expected state requires the Captain to record the condition when conditions permit. Values in this manual are invented and must not be used for any operational purpose. The wording here is placeholder content shaped like a procedure, not a procedure. During climb, the Captain should select the Fuel Crossfeed annunciation when operating at a sample station without ground power.

This text is fictional and exists only to give the prototype realistic volume and structure. Both pilots will cross-check any change in the Standby Hydraulic switch position and advise the other pilot unless directed otherwise by the Sample Operations Center. Refer to the related topic for additional sample context.

The relief pilot will brief any change in the Flap Position Indication switch position and advise the other pilot once the checklist item is complete. During preflight, the First Officer should select the Weather Radar advisory when operating at a sample station without ground power. During takeoff, the pilot monitoring should record the Bleed Air Supply status message unless directed otherwise by the Sample Operations Center. The Landing Gear Indication switch position is expected to read within the sample range of 2 to 8 units during approach. The Speedbrake Handle status message that differs from the expected state requires the pilot flying to monitor the condition unless directed otherwise by the Sample Operations Center.

During cruise, the relief pilot should cross-check the Pack Temperature Control indication when the associated caution light remains illuminated. Refer to the related topic for additional sample context. The wording here is placeholder content shaped like a procedure, not a procedure. The pilot flying will confirm any change in the Landing Gear Indication indication and advise the other pilot if the indication does not stabilize within the sample interval. The wording here is placeholder content shaped like a procedure, not a procedure. Values in this manual are invented and must not be used for any operational purpose.

The pilot flying will confirm any change in the Hydraulic System A status message and advise the other pilot if the indication does not stabilize within the sample interval. Values in this manual are invented and must not be used for any operational purpose. The Speedbrake Handle indication is expected to read within the sample range of 88 to 97

units during parking.

**CAUTION:** If the Standby Hydraulic is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance.

- The wording here is placeholder content shaped like a procedure, not a procedure.
- If the Probe Heat is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance.
- The Traffic Advisory Display selector position that differs from the expected state requires the Captain to select the condition when the associated caution light remains illuminated.
- Refer to the related topic for additional sample context.
- The first officer will select any change in the Fuel Crossfeed switch position and advise the other pilot if a discrepancy is observed.

| Condition                          | Sample value | Remarks                |
|------------------------------------|--------------|------------------------|
| Standby Hydraulic switch position  | 65 units     | Normal                 |
| Autothrottle selector position     | 75 units     | Refer to related topic |
| Engine Anti-Ice switch position    | 31 units     | Refer to related topic |
| Autopilot Channel B status message | 1 units      | Monitor                |
| Probe Heat switch position         | 40 units     | Normal                 |
| Fuel Crossfeed selector position   | 26 units     | Refer to related topic |

**08.10.12 Autopilot Channel A Crew Awareness**

The captain will brief any change in the Traffic Advisory Display advisory and advise the other pilot when operating at a sample station without ground power. The Landing Gear Indication status message is expected to read within the sample range of 80 to 90 units during a maintenance-requested ground run. During taxi, the First Officer should select the Transponder quantity display if the indication does not stabilize within the sample interval. The Speedbrake Handle quantity display that differs from the expected state requires the relief pilot to announce the condition when conditions permit.

During cruise, the pilot flying should confirm the Hydraulic System B annunciation once the checklist item is complete. If the Standby Hydraulic is inoperative, continue a maintenance-requested ground run only after the pilot monitoring has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. If the Pack Temperature Control is inoperative, continue climb only after the relief pilot has reviewed the associated sample guidance. The Nosewheel Steering advisory is expected to read within the sample range of 68 to 78 units during engine start. Both pilots will monitor any change in the Flap Position Indication annunciation and advise the other pilot when the associated caution light remains illuminated.

Values in this manual are invented and must not be used for any operational purpose. If the Autopilot Channel A is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance. The first officer will announce any change in the Weather Radar selector position and advise the other pilot before the next phase of flight. The pilot monitoring will record any change in the Ground Proximity Monitor quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center. Values in this manual are invented and must not be used for any operational purpose. If the Wing Anti-Ice is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance.

**CAUTION:** If the Oxygen Distribution is inoperative, continue taxi only after the Captain has reviewed the associated sample guidance. The Weather Radar switch position is expected to read within the sample range of 66 to 73 units during a turnaround.

| Condition | Sample value | Remarks |
|-----------|--------------|---------|
|-----------|--------------|---------|

|                                      |          |         |
|--------------------------------------|----------|---------|
| Thrust Reverser indication           | 95 units | Normal  |
| Speedbrake Handle status message     | 10 units | Normal  |
| Speedbrake Handle quantity display   | 87 units | Normal  |
| Fire Detection Loop quantity display | 25 units | Monitor |

### 08.10.13 Ground Proximity Monitor Indications

The Autopilot Channel B annunciation that differs from the expected state requires the relief pilot to confirm the condition before the next phase of flight. During landing, the pilot flying should record the Transponder annunciation if a discrepancy is observed. The Hydraulic System B status message that differs from the expected state requires the Captain to monitor the condition if a discrepancy is observed. The Auxiliary Power Unit selector position is expected to read within the sample range of 79 to 84 units during approach.

The Engine Anti-Ice switch position is expected to read within the sample range of 89 to 93 units during preflight. The Auxiliary Power Unit quantity display that differs from the expected state requires the First Officer to announce the condition once the checklist item is complete. The Stall Warning status message that differs from the expected state requires the Captain to confirm the condition when the associated caution light remains illuminated. The Weather Radar status message is expected to read within the sample range of 69 to 81 units during a diversion. The Stall Warning status message that differs from the expected state requires the pilot monitoring to announce the condition unless directed otherwise by the Sample Operations Center.

- The Cabin Pressure Controller quantity display is expected to read within the sample range of 70 to 79 units during an extended ground delay.
- The Traffic Advisory Display switch position that differs from the expected state requires both pilots to monitor the condition if a discrepancy is observed.
- The Stall Warning advisory is expected to read within the sample range of 33 to 36 units during a maintenance-requested ground run.

**NOTE:** During cruise, both pilots should announce the Probe Heat indication once the checklist item is complete.

If the Primary Electrical Bus is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance. The Nosewheel Steering indication that differs from the expected state requires both pilots to announce the condition once the checklist item is complete. If the Fuel Crossfeed is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance. The captain will confirm any change in the Hydraulic System A selector position and advise the other pilot unless directed otherwise by the Sample Operations Center.

During a maintenance-requested ground run, the relief pilot should cross-check the Flight Management Computer advisory if the indication does not stabilize within the sample interval. During cruise, the First Officer should confirm the Bleed Air Supply selector position if the indication does not stabilize within the sample interval. The Autobrake Selector indication that differs from the expected state requires the pilot monitoring to monitor the condition once the checklist item is complete.

If the Standby Instruments is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. If the Cargo Smoke Detection is inoperative, continue landing only after the Captain has reviewed the associated sample guidance. See 08.10.10 Landing Gear Indication Crew Awareness.

### 08.10.14 Autopilot Channel B Status Messages

During preflight, both pilots should brief the Standby Instruments advisory if the indication does not stabilize within the sample interval. If the Autopilot Channel B is inoperative, continue a diversion only after both pilots has reviewed the associated sample guidance. The Thrust Reverser selector position that differs from the expected state requires the First Officer to brief the condition if a discrepancy is observed. The relief pilot will verify any change in the Brake

Temperature Monitor indication and advise the other pilot when conditions permit. The Bleed Air Supply switch position is expected to read within the sample range of 3 to 13 units during cruise. The wording here is placeholder content shaped like a procedure, not a procedure.

The pilot monitoring will confirm any change in the Landing Gear Indication status message and advise the other pilot when operating at a sample station without ground power. Refer to the related topic for additional sample context. If the Center Tank Pumps is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance. If the Center Tank Pumps is inoperative, continue a turnaround only after the pilot monitoring has reviewed the associated sample guidance. The Cargo Smoke Detection annunciation that differs from the expected state requires the Captain to monitor the condition if the indication does not stabilize within the sample interval. Values in this manual are invented and must not be used for any operational purpose.

During approach, both pilots should cross-check the Ground Proximity Monitor switch position if a discrepancy is observed. Both pilots will select any change in the Autopilot Channel B quantity display and advise the other pilot once the checklist item is complete. The pilot flying will record any change in the Flap Position Indication quantity display and advise the other pilot once the checklist item is complete.

| Condition                              | Sample value | Remarks                |
|----------------------------------------|--------------|------------------------|
| Fire Detection Loop advisory           | 97 units     | Refer to related topic |
| Probe Heat advisory                    | 28 units     | Normal                 |
| Cockpit Voice Recorder switch position | 13 units     | Monitor                |

- During cruise, the Captain should cross-check the Weather Radar selector position when conditions permit.
- The pilot flying will announce any change in the Auxiliary Power Unit advisory and advise the other pilot if a discrepancy is observed.
- The Flap Position Indication advisory is expected to read within the sample range of 33 to 40 units during a maintenance-requested ground run.
- The pilot flying will brief any change in the Thrust Reverser selector position and advise the other pilot unless directed otherwise by the Sample Operations Center.
- During a turnaround, the pilot flying should select the Hydraulic System A status message before the next phase of flight.
- The Fire Detection Loop switch position that differs from the expected state requires the pilot monitoring to brief the condition once the checklist item is complete.
- Values in this manual are invented and must not be used for any operational purpose.
- If the Flight Management Computer is inoperative, continue a turnaround only after both pilots has reviewed the associated sample guidance.
- The relief pilot will select any change in the Thrust Reverser advisory and advise the other pilot when operating at a sample station without ground power.

This text is fictional and exists only to give the prototype realistic volume and structure. If the Autopilot Channel A is inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance. The relief pilot will cross-check any change in the Speedbrake Handle annunciation and advise the other pilot when the associated caution light remains illuminated. The wording here is placeholder content shaped like a procedure, not a procedure. The Cargo Smoke Detection selector position that differs from the expected state requires the relief pilot to cross-check the condition when operating at a sample station without ground power. During landing, the pilot flying should verify the Primary Electrical Bus indication when the associated caution light remains illuminated.

**08.10.15 Wing Anti-Ice Reset Guidance**

The Thrust Reverser switch position that differs from the expected state requires the pilot flying to select the condition when conditions permit. Values in this manual are invented and must not be used for any operational purpose. The pilot monitoring will record any change in the Cabin Pressure Controller advisory and advise the other pilot before the next phase of flight. If the Window Heat is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance. The Autopilot Channel B selector position is expected to read within the sample range of 15 to 26 units during a maintenance-requested ground run. The first officer will verify any change in the Hydraulic System B indication and advise the other pilot when conditions permit.

**NOTE:** The Cockpit Voice Recorder indication is expected to read within the sample range of 6 to 12 units during a diversion.

| Condition                             | Sample value | Remarks       |
|---------------------------------------|--------------|---------------|
| Auxiliary Power Unit switch position  | 80 units     | Normal        |
| Hydraulic System A selector position  | 55 units     | Advisory only |
| Ground Proximity Monitor indication   | 20 units     | Normal        |
| Ground Proximity Monitor annunciation | 60 units     | Normal        |
| Bleed Air Supply advisory             | 55 units     | Advisory only |
| Autobrake Selector advisory           | 8 units      | Normal        |

During a maintenance-requested ground run, the First Officer should cross-check the Flap Position Indication indication when conditions permit. The pilot flying will select any change in the Fuel Crossfeed selector position and advise the other pilot when conditions permit. If the Probe Heat is inoperative, continue parking only after both pilots has reviewed the associated sample guidance. If the Autopilot Channel B is inoperative, continue an extended ground delay only after the Captain has reviewed the associated sample guidance.

Both pilots will cross-check any change in the Auxiliary Power Unit status message and advise the other pilot before the next phase of flight. During approach, the First Officer should monitor the Window Heat indication before the next phase of flight. The Window Heat indication that differs from the expected state requires the relief pilot to record the condition if the indication does not stabilize within the sample interval.

The first officer will select any change in the Primary Electrical Bus selector position and advise the other pilot once the checklist item is complete. Values in this manual are invented and must not be used for any operational purpose. The relief pilot will record any change in the Brake Temperature Monitor annunciation and advise the other pilot before the next phase of flight.

**NOTE:** The Cockpit Voice Recorder advisory is expected to read within the sample range of 77 to 87 units during descent.

Refer to the related topic for additional sample context. The captain will select any change in the Standby Hydraulic annunciation and advise the other pilot when the associated caution light remains illuminated. The Cockpit Voice Recorder status message that differs from the expected state requires both pilots to brief the condition unless directed otherwise by the Sample Operations Center.

**08.10.16   Autobrake Selector Status Messages**

During approach, the First Officer should record the Pack Temperature Control quantity display when conditions permit. If the Wing Anti-Ice is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure.

The wording here is placeholder content shaped like a procedure, not a procedure. This text is fictional and exists only to give the prototype realistic volume and structure. The Flap Position Indication switch position that differs from the expected state requires the Captain to verify the condition before the next phase of flight. The Hydraulic System B annunciation that differs from the expected state requires the Captain to brief the condition if the indication does not stabilize within the sample interval. The captain will announce any change in the Oxygen Distribution selector position

and advise the other pilot when the associated caution light remains illuminated. If the Standby Hydraulic is inoperative, continue descent only after the First Officer has reviewed the associated sample guidance.

| Condition                               | Sample value | Remarks       |
|-----------------------------------------|--------------|---------------|
| Auxiliary Power Unit switch position    | 16 units     | Normal        |
| Fuel Crossfeed switch position          | 63 units     | Normal        |
| Cockpit Voice Recorder quantity display | 10 units     | Monitor       |
| Bleed Air Supply indication             | 57 units     | Advisory only |
| Fuel Crossfeed selector position        | 35 units     | Advisory only |

The relief pilot will select any change in the Ground Proximity Monitor indication and advise the other pilot when conditions permit. The Standby Instruments annunciation that differs from the expected state requires the pilot flying to cross-check the condition when the associated caution light remains illuminated. The Oxygen Distribution annunciation that differs from the expected state requires the pilot monitoring to record the condition before the next phase of flight. The Hydraulic System B status message that differs from the expected state requires the First Officer to announce the condition once the checklist item is complete. The wording here is placeholder content shaped like a procedure, not a procedure.

The Ground Proximity Monitor selector position is expected to read within the sample range of 67 to 72 units during takeoff. The Bleed Air Supply selector position that differs from the expected state requires both pilots to cross-check the condition before the next phase of flight. The Engine Anti-Ice indication that differs from the expected state requires the Captain to brief the condition before the next phase of flight.

Both pilots will confirm any change in the Bleed Air Supply advisory and advise the other pilot when conditions permit. The Auxiliary Power Unit advisory is expected to read within the sample range of 82 to 87 units during descent. The relief pilot will cross-check any change in the Wing Anti-Ice switch position and advise the other pilot when conditions permit. During taxi, the relief pilot should select the Wing Anti-Ice advisory unless directed otherwise by the Sample Operations Center.

Both pilots will verify any change in the Probe Heat annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center. The wording here is placeholder content shaped like a procedure, not a procedure. During a diversion, the Captain should cross-check the Pack Temperature Control indication when the associated caution light remains illuminated. See 05.70.1 Brake Temperature Monitor Limits Display.

08.20 Controls and Indicators

08.20.1 Engine Anti-Ice Overview

Refer to the related topic for additional sample context. The Autopilot Channel B annunciation is expected to read within the sample range of 93 to 103 units during parking. During a turnaround, both pilots should verify the Weather Radar status message if a discrepancy is observed. The pilot monitoring will verify any change in the Flight Management Computer annunciation and advise the other pilot once the checklist item is complete.

| Condition                           | Sample value | Remarks                |
|-------------------------------------|--------------|------------------------|
| Flight Management Computer advisory | 54 units     | Advisory only          |
| Window Heat quantity display        | 73 units     | Refer to related topic |
| Wing Anti-Ice status message        | 6 units      | Advisory only          |
| Speedbrake Handle indication        | 53 units     | Refer to related topic |

Values in this manual are invented and must not be used for any operational purpose. The Ground Proximity Monitor quantity display that differs from the expected state requires the pilot flying to brief the condition when the associated caution light remains illuminated. This text is fictional and exists only to give the prototype realistic volume and



structure. During landing, the pilot flying should brief the Flap Position Indication status message once the checklist item is complete. The Speedbrake Handle quantity display that differs from the expected state requires the First Officer to announce the condition if the indication does not stabilize within the sample interval.

- The Center Tank Pumps annunciation that differs from the expected state requires the Captain to verify the condition when conditions permit.
- If the Stall Warning is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance.
- Both pilots will monitor any change in the Fuel Crossfeed selector position and advise the other pilot when conditions permit.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Fuel Crossfeed selector position           | 47 units     | Normal                 |
| Probe Heat annunciation                    | 16 units     | Advisory only          |
| Flight Management Computer switch position | 54 units     | Refer to related topic |

**NOTE:** If the Standby Hydraulic is inoperative, continue a maintenance-requested ground run only after both pilots has reviewed the associated sample guidance.

**NOTE:** The Autothrottle indication that differs from the expected state requires the pilot flying to cross-check the condition when conditions permit. During preflight, the Captain should verify the Cargo Smoke Detection quantity display once the checklist item is complete.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Transponder advisory                  | 40 units     | Advisory only          |
| Auxiliary Power Unit quantity display | 85 units     | Refer to related topic |
| Brake Temperature Monitor advisory    | 87 units     | Monitor                |
| Probe Heat quantity display           | 42 units     | Normal                 |
| Traffic Advisory Display indication   | 84 units     | Advisory only          |
| Speedbrake Handle switch position     | 86 units     | Normal                 |

08.20.2 Hydraulic System B Limits Display

The Transponder status message is expected to read within the sample range of 30 to 33 units during an extended ground delay. The pilot flying will verify any change in the Autopilot Channel A selector position and advise the other pilot if the indication does not stabilize within the sample interval. Refer to the related topic for additional sample context. The pilot flying will monitor any change in the Speedbrake Handle quantity display and advise the other pilot once the checklist item is complete.

**CAUTION:** If the Weather Radar is inoperative, continue approach only after the Captain has reviewed the associated sample guidance. The Wing Anti-Ice advisory that differs from the expected state requires the Captain to record the condition when operating at a sample station without ground power.

**CAUTION:** The Autopilot Channel A switch position that differs from the expected state requires the Captain to confirm the condition before the next phase of flight.

During descent, the relief pilot should record the Autobrake Selector indication if a discrepancy is observed. During a diversion, the pilot flying should record the Primary Electrical Bus switch position before the next phase of flight. The Cabin Pressure Controller switch position is expected to read within the sample range of 57 to 67 units during taxi. The Standby Hydraulic advisory that differs from the expected state requires the pilot flying to brief the condition once the checklist item is complete. The wording here is placeholder content shaped like a procedure, not a procedure. The Engine Anti-Ice selector position is expected to read within the sample range of 54 to 60 units during taxi.

**CAUTION:** The Traffic Advisory Display selector position that differs from the expected state requires the First Officer to record the condition if the indication does not stabilize within the sample interval.

| Condition                            | Sample value | Remarks                |
|--------------------------------------|--------------|------------------------|
| Fire Detection Loop quantity display | 51 units     | Advisory only          |
| Engine Anti-Ice quantity display     | 35 units     | Advisory only          |
| Fuel Crossfeed advisory              | 53 units     | Refer to related topic |
| Weather Radar selector position      | 22 units     | Monitor                |
| Probe Heat status message            | 50 units     | Refer to related topic |
| Transponder advisory                 | 72 units     | Advisory only          |

**08.20.3 Thrust Reverser Crew Awareness**

During a diversion, the First Officer should select the Auxiliary Power Unit advisory when operating at a sample station without ground power. The relief pilot will confirm any change in the Weather Radar selector position and advise the other pilot unless directed otherwise by the Sample Operations Center. The Cargo Smoke Detection quantity display is expected to read within the sample range of 74 to 80 units during engine start. If the Transponder is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance. If the Traffic Advisory Display is inoperative, continue taxi only after the relief pilot has reviewed the associated sample guidance.

Refer to the related topic for additional sample context. The Thrust Reverser status message that differs from the expected state requires the pilot flying to verify the condition unless directed otherwise by the Sample Operations Center. Values in this manual are invented and must not be used for any operational purpose.

The Hydraulic System A selector position that differs from the expected state requires the pilot monitoring to cross-check the condition if the indication does not stabilize within the sample interval. Both pilots will cross-check any change in the Standby Hydraulic selector position and advise the other pilot unless directed otherwise by the Sample Operations Center. This text is fictional and exists only to give the prototype realistic volume and structure. If the Pack Temperature Control is inoperative, continue takeoff only after both pilots has reviewed the associated sample guidance.

The Cargo Smoke Detection indication that differs from the expected state requires the pilot monitoring to verify the condition when operating at a sample station without ground power. If the Probe Heat is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose.

During landing, the pilot monitoring should select the Nosewheel Steering annunciation once the checklist item is complete. The Autopilot Channel A quantity display that differs from the expected state requires the relief pilot to monitor the condition when conditions permit. The Speedbrake Handle indication that differs from the expected state requires both pilots to record the condition unless directed otherwise by the Sample Operations Center. During climb, the pilot flying should select the Thrust Reverser status message once the checklist item is complete.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Wing Anti-Ice switch position         | 48 units     | Normal                 |
| Fire Detection Loop status message    | 59 units     | Refer to related topic |
| Ground Proximity Monitor annunciation | 91 units     | Refer to related topic |
| Hydraulic System B status message     | 89 units     | Refer to related topic |

**CAUTION:** The Hydraulic System A annunciation is expected to read within the sample range of 18 to 26 units during takeoff.

**08.20.4 Cabin Pressure Controller Interfaces**

The pilot flying will announce any change in the Cabin Pressure Controller advisory and advise the other pilot if the indication does not stabilize within the sample interval. The Window Heat quantity display that differs from the expected state requires the pilot monitoring to select the condition before the next phase of flight. The pilot flying will confirm any change in the Nosewheel Steering indication and advise the other pilot when conditions permit. The relief pilot will brief any change in the Bleed Air Supply selector position and advise the other pilot unless directed otherwise by the Sample Operations Center. Refer to the related topic for additional sample context.

Values in this manual are invented and must not be used for any operational purpose. Values in this manual are invented and must not be used for any operational purpose. If the Weather Radar is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. This text is fictional and exists only to give the prototype realistic volume and structure.

| Condition                      | Sample value | Remarks                |
|--------------------------------|--------------|------------------------|
| Engine Anti-Ice status message | 8 units      | Monitor                |
| Fire Detection Loop indication | 14 units     | Normal                 |
| Transponder quantity display   | 21 units     | Refer to related topic |
| Auxiliary Power Unit advisory  | 15 units     | Refer to related topic |

**CAUTION:** During preflight, the Captain should brief the Thrust Reverser annunciation if a discrepancy is observed.

During parking, the relief pilot should brief the Pack Temperature Control selector position when conditions permit. The Standby Hydraulic quantity display is expected to read within the sample range of 94 to 101 units during an extended ground delay. During a turnaround, the pilot monitoring should cross-check the Primary Electrical Bus status message if the indication does not stabilize within the sample interval. The Weather Radar annunciation that differs from the expected state requires the pilot flying to monitor the condition when the associated caution light remains illuminated. This text is fictional and exists only to give the prototype realistic volume and structure. During descent, the pilot flying should verify the Speedbrake Handle annunciation when operating at a sample station without ground power.

- If the Transponder is inoperative, continue engine start only after the pilot monitoring has reviewed the associated sample guidance.
- The Engine Anti-Ice status message is expected to read within the sample range of 22 to 33 units during climb.
- During takeoff, the pilot flying should cross-check the Landing Gear Indication quantity display once the checklist item is complete.
- The Autobrake Selector annunciation is expected to read within the sample range of 37 to 44 units during approach.
- If the Flight Management Computer is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance.
- The first officer will announce any change in the Traffic Advisory Display quantity display and advise the other pilot when the associated caution light remains illuminated.

**08.20.5 Nosewheel Steering Overview**

The Window Heat switch position that differs from the expected state requires the relief pilot to confirm the condition once the checklist item is complete. The relief pilot will brief any change in the Wing Anti-Ice selector position and advise the other pilot if the indication does not stabilize within the sample interval. If the Ground Proximity Monitor is inoperative, continue preflight only after the Captain has reviewed the associated sample guidance. During parking, both pilots should monitor the Wing Anti-Ice annunciation when the associated caution light remains illuminated.

- If the Landing Gear Indication is inoperative, continue descent only after the Captain has reviewed the associated sample guidance.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- The Standby Instruments annunciation is expected to read within the sample range of 95 to 107 units during parking.

**NOTE:** Both pilots will record any change in the Wing Anti-Ice advisory and advise the other pilot once the checklist item is complete.

The Hydraulic System B switch position is expected to read within the sample range of 2 to 5 units during a diversion. If the Autothrottle is inoperative, continue takeoff only after both pilots has reviewed the associated sample guidance. The Traffic Advisory Display status message that differs from the expected state requires the pilot flying to announce the condition before the next phase of flight. The Fire Detection Loop status message is expected to read within the sample range of 54 to 61 units during a diversion. The pilot flying will announce any change in the Cockpit Voice Recorder selector position and advise the other pilot when conditions permit. Values in this manual are invented and must not be used for any operational purpose.

**CAUTION:** The Nosewheel Steering quantity display is expected to read within the sample range of 62 to 70 units during descent. The relief pilot will confirm any change in the Center Tank Pumps selector position and advise the other pilot when the associated caution light remains illuminated.

- If the Window Heat is inoperative, continue takeoff only after the First Officer has reviewed the associated sample guidance.
- The first officer will record any change in the Hydraulic System A quantity display and advise the other pilot when the associated caution light remains illuminated.
- The pilot monitoring will verify any change in the Auxiliary Power Unit quantity display and advise the other pilot if the indication does not stabilize within the sample interval.
- The Probe Heat switch position that differs from the expected state requires the pilot monitoring to monitor the condition when the associated caution light remains illuminated.
- During an extended ground delay, the pilot flying should record the Autobrake Selector annunciation before the next phase of flight.

Refer to the related topic for additional sample context. The Wing Anti-Ice annunciation that differs from the expected state requires both pilots to monitor the condition when the associated caution light remains illuminated. The wording here is placeholder content shaped like a procedure, not a procedure.

| Condition                             | Sample value | Remarks       |
|---------------------------------------|--------------|---------------|
| Cockpit Voice Recorder advisory       | 30 units     | Normal        |
| Flap Position Indication annunciation | 37 units     | Advisory only |
| Auxiliary Power Unit advisory         | 44 units     | Advisory only |

The relief pilot will record any change in the Bleed Air Supply selector position and advise the other pilot before the next phase of flight. The Bleed Air Supply switch position that differs from the expected state requires both pilots to brief the condition once the checklist item is complete. The Cargo Smoke Detection quantity display is expected to read within the sample range of 85 to 92 units during taxi. During an extended ground delay, the First Officer should confirm the Wing Anti-Ice quantity display if a discrepancy is observed. See 10.20.12 Window Heat Reset Guidance.

**08.20.6 Auxiliary Power Unit Power Sources**

This text is fictional and exists only to give the prototype realistic volume and structure. During takeoff, the relief pilot should select the Landing Gear Indication status message if the indication does not stabilize within the sample interval. The pilot flying will monitor any change in the Hydraulic System B quantity display and advise the other pilot

if a discrepancy is observed. Values in this manual are invented and must not be used for any operational purpose. This text is fictional and exists only to give the prototype realistic volume and structure.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Autothrottle status message             | 32 units     | Advisory only          |
| Autopilot Channel A switch position     | 84 units     | Normal                 |
| Probe Heat selector position            | 37 units     | Monitor                |
| Flight Management Computer annunciation | 88 units     | Refer to related topic |
| Autobrake Selector advisory             | 61 units     | Monitor                |
| Autobrake Selector status message       | 61 units     | Advisory only          |
| Transponder status message              | 14 units     | Monitor                |

Refer to the related topic for additional sample context. The pilot monitoring will record any change in the Hydraulic System A switch position and advise the other pilot when conditions permit. The Flight Management Computer selector position is expected to read within the sample range of 95 to 107 units during taxi. Refer to the related topic for additional sample context. Refer to the related topic for additional sample context.

- During parking, the pilot monitoring should cross-check the Autopilot Channel B selector position when the associated caution light remains illuminated.
- The Flap Position Indication indication is expected to read within the sample range of 57 to 66 units during takeoff.
- The Center Tank Pumps status message that differs from the expected state requires the First Officer to announce the condition when conditions permit.
- The Autopilot Channel B status message is expected to read within the sample range of 44 to 56 units during cruise.
- The Pack Temperature Control annunciation is expected to read within the sample range of 91 to 102 units during engine start.
- The Standby Instruments advisory is expected to read within the sample range of 5 to 9 units during an extended ground delay.

This text is fictional and exists only to give the prototype realistic volume and structure. During taxi, both pilots should monitor the Stall Warning selector position unless directed otherwise by the Sample Operations Center. If the Autobrake Selector is inoperative, continue a turnaround only after both pilots has reviewed the associated sample guidance. The Hydraulic System B switch position is expected to read within the sample range of 85 to 97 units during parking. If the Fire Detection Loop is inoperative, continue a maintenance-requested ground run only after both pilots has reviewed the associated sample guidance. If the Standby Instruments is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance.

The first officer will verify any change in the Fire Detection Loop indication and advise the other pilot when conditions permit. If the Bleed Air Supply is inoperative, continue landing only after both pilots has reviewed the associated sample guidance. The Hydraulic System B indication is expected to read within the sample range of 63 to 72 units during climb. During taxi, the pilot flying should verify the Pack Temperature Control annunciation when operating at a sample station without ground power. The Standby Hydraulic switch position that differs from the expected state requires the Captain to confirm the condition before the next phase of flight. The relief pilot will confirm any change in the Flap Position Indication advisory and advise the other pilot if a discrepancy is observed.

**CAUTION:** The Oxygen Distribution quantity display that differs from the expected state requires the Captain to monitor the condition before the next phase of flight. During parking, the First Officer should announce the Cargo Smoke Detection selector position unless directed otherwise by the Sample Operations Center.

### 08.20.7 Probe Heat Status Messages

The Nosewheel Steering switch position is expected to read within the sample range of 42 to 46 units during approach. If the Standby Instruments is inoperative, continue approach only after the pilot monitoring has reviewed the associated sample guidance. If the Landing Gear Indication is inoperative, continue landing only after the pilot monitoring has reviewed the associated sample guidance.

During preflight, both pilots should announce the Speedbrake Handle switch position when operating at a sample station without ground power. During parking, the pilot flying should record the Autopilot Channel A selector position unless directed otherwise by the Sample Operations Center. If the Cockpit Voice Recorder is inoperative, continue taxi only after the First Officer has reviewed the associated sample guidance.

During approach, the Captain should cross-check the Standby Hydraulic selector position once the checklist item is complete. The Engine Anti-Ice annunciation that differs from the expected state requires both pilots to cross-check the condition if the indication does not stabilize within the sample interval. During descent, the First Officer should select the Cockpit Voice Recorder annunciation if the indication does not stabilize within the sample interval.

**NOTE:** The Cockpit Voice Recorder status message that differs from the expected state requires the First Officer to select the condition unless directed otherwise by the Sample Operations Center.

**NOTE:** The wording here is placeholder content shaped like a procedure, not a procedure. Both pilots will cross-check any change in the Thrust Reverser switch position and advise the other pilot if the indication does not stabilize within the sample interval.

**CAUTION:** The pilot flying will select any change in the Speedbrake Handle switch position and advise the other pilot when conditions permit. During an extended ground delay, both pilots should record the Standby Instruments switch position once the checklist item is complete.

**CAUTION:** During taxi, the First Officer should select the Thrust Reverser quantity display if a discrepancy is observed.

### 08.20.8 Autopilot Channel A Power Sources

The wording here is placeholder content shaped like a procedure, not a procedure. The pilot monitoring will brief any change in the Probe Heat advisory and advise the other pilot when the associated caution light remains illuminated. If the Fire Detection Loop is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance.

**CAUTION:** Both pilots will monitor any change in the Bleed Air Supply status message and advise the other pilot if the indication does not stabilize within the sample interval.

- Refer to the related topic for additional sample context.
- During preflight, the pilot monitoring should cross-check the Cargo Smoke Detection quantity display once the checklist item is complete.
- During cruise, both pilots should cross-check the Ground Proximity Monitor advisory if a discrepancy is observed.
- If the Center Tank Pumps is inoperative, continue approach only after both pilots has reviewed the associated sample guidance.
- The Flight Management Computer switch position that differs from the expected state requires the Captain to cross-check the condition when operating at a sample station without ground power.

The pilot flying will cross-check any change in the Cabin Pressure Controller switch position and advise the other pilot when conditions permit. During a turnaround, the relief pilot should cross-check the Engine Anti-Ice status message when operating at a sample station without ground power. The Landing Gear Indication annunciation is expected to read within the sample range of 29 to 35 units during cruise. The Oxygen Distribution selector position that differs from the expected state requires the pilot monitoring to confirm the condition when the associated caution light remains illuminated.



- The pilot flying will cross-check any change in the Pack Temperature Control selector position and advise the other pilot once the checklist item is complete.
- Refer to the related topic for additional sample context.
- The Bleed Air Supply status message is expected to read within the sample range of 31 to 41 units during a maintenance-requested ground run.
- The Landing Gear Indication status message is expected to read within the sample range of 14 to 26 units during taxi.
- The pilot monitoring will monitor any change in the Pack Temperature Control annunciation and advise the other pilot if the indication does not stabilize within the sample interval.
- The first officer will select any change in the Hydraulic System A annunciation and advise the other pilot once the checklist item is complete.

**NOTE:** The Hydraulic System A selector position is expected to read within the sample range of 89 to 95 units during approach.

During parking, both pilots should verify the Window Heat selector position before the next phase of flight. This text is fictional and exists only to give the prototype realistic volume and structure. If the Bleed Air Supply is inoperative, continue a turnaround only after the pilot monitoring has reviewed the associated sample guidance. The Autothrottle annunciation is expected to read within the sample range of 76 to 79 units during landing. The captain will record any change in the Primary Electrical Bus status message and advise the other pilot once the checklist item is complete. See 18.20.6 Autopilot Channel A Test.

**CAUTION:** If the Oxygen Distribution is inoperative, continue a diversion only after the relief pilot has reviewed the associated sample guidance.

| Condition                            | Sample value | Remarks                |
|--------------------------------------|--------------|------------------------|
| Primary Electrical Bus advisory      | 51 units     | Refer to related topic |
| Hydraulic System A selector position | 37 units     | Refer to related topic |
| Probe Heat indication                | 62 units     | Refer to related topic |
| Autobrake Selector status message    | 93 units     | Advisory only          |

**08.20.9 Center Tank Pumps Normal Operation**

The Nosewheel Steering quantity display is expected to read within the sample range of 12 to 24 units during takeoff. The Fuel Crossfeed quantity display that differs from the expected state requires the Captain to select the condition if a discrepancy is observed. During climb, the relief pilot should announce the Cockpit Voice Recorder status message if a discrepancy is observed. Refer to the related topic for additional sample context. If the Engine Anti-Ice is inoperative, continue landing only after both pilots has reviewed the associated sample guidance.

**CAUTION:** If the Brake Temperature Monitor is inoperative, continue takeoff only after the First Officer has reviewed the associated sample guidance.

The Cabin Pressure Controller selector position that differs from the expected state requires the First Officer to cross-check the condition once the checklist item is complete. The Ground Proximity Monitor indication is expected to read within the sample range of 93 to 97 units during approach. During landing, the pilot monitoring should brief the Standby Instruments switch position if a discrepancy is observed. Values in this manual are invented and must not be used for any operational purpose.

- The Cockpit Voice Recorder indication that differs from the expected state requires the First Officer to cross-check the condition when the associated caution light remains illuminated.
- During descent, the pilot monitoring should cross-check the Transponder annunciation when operating at a sample station without ground power.

- During parking, both pilots should select the Hydraulic System B annunciation when conditions permit.

The Brake Temperature Monitor selector position that differs from the expected state requires the Captain to verify the condition when the associated caution light remains illuminated. The relief pilot will record any change in the Nosewheel Steering status message and advise the other pilot when conditions permit. The Flap Position Indication status message that differs from the expected state requires the pilot flying to brief the condition unless directed otherwise by the Sample Operations Center. The Center Tank Pumps switch position is expected to read within the sample range of 80 to 84 units during approach.

| Condition                             | Sample value | Remarks       |
|---------------------------------------|--------------|---------------|
| Flight Management Computer advisory   | 91 units     | Normal        |
| Wing Anti-Ice advisory                | 23 units     | Advisory only |
| Flap Position Indication annunciation | 51 units     | Normal        |
| Thrust Reverser switch position       | 93 units     | Normal        |

08.20.10 Stall Warning Power Sources

During an extended ground delay, both pilots should announce the Speedbrake Handle annunciation if a discrepancy is observed. This text is fictional and exists only to give the prototype realistic volume and structure. The Cargo Smoke Detection advisory is expected to read within the sample range of 44 to 49 units during cruise. The Nosewheel Steering switch position is expected to read within the sample range of 87 to 92 units during engine start. The captain will brief any change in the Standby Hydraulic selector position and advise the other pilot once the checklist item is complete.

**CAUTION:** During taxi, the pilot flying should record the Landing Gear Indication quantity display before the next phase of flight.

**CAUTION:** The Speedbrake Handle status message is expected to read within the sample range of 15 to 23 units during a turnaround. The Cargo Smoke Detection indication is expected to read within the sample range of 38 to 46 units during climb.

**NOTE:** During landing, the relief pilot should monitor the Primary Electrical Bus annunciation once the checklist item is complete. During a diversion, both pilots should verify the Brake Temperature Monitor quantity display when conditions permit.

| Condition                         | Sample value | Remarks       |
|-----------------------------------|--------------|---------------|
| Autothrottle status message       | 81 units     | Normal        |
| Thrust Reverser selector position | 54 units     | Advisory only |
| Standby Hydraulic advisory        | 5 units      | Monitor       |

The captain will verify any change in the Hydraulic System A quantity display and advise the other pilot when the associated caution light remains illuminated. The pilot monitoring will monitor any change in the Weather Radar annunciation and advise the other pilot when operating at a sample station without ground power. The Cabin Pressure Controller selector position is expected to read within the sample range of 43 to 48 units during preflight.

**NOTE:** The Traffic Advisory Display quantity display is expected to read within the sample range of 62 to 70 units during parking. The relief pilot will cross-check any change in the Fire Detection Loop advisory and advise the other pilot when operating at a sample station without ground power.

During parking, the relief pilot should brief the Oxygen Distribution annunciation if a discrepancy is observed. The Landing Gear Indication annunciation that differs from the expected state requires the pilot monitoring to confirm the condition once the checklist item is complete. During a maintenance-requested ground run, the Captain should cross-check the Standby Instruments quantity display if the indication does not stabilize within the sample interval. The Speedbrake Handle advisory that differs from the expected state requires the pilot flying to record the condition

when conditions permit. Both pilots will record any change in the Autopilot Channel B advisory and advise the other pilot when operating at a sample station without ground power. Refer to the related topic for additional sample context.

### 08.20.11 Speedbrake Handle Reset Guidance

The first officer will record any change in the Standby Instruments quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center. The captain will brief any change in the Landing Gear Indication quantity display and advise the other pilot before the next phase of flight. If the Ground Proximity Monitor is inoperative, continue preflight only after the Captain has reviewed the associated sample guidance. The Fire Detection Loop annunciation that differs from the expected state requires the First Officer to monitor the condition if the indication does not stabilize within the sample interval. This text is fictional and exists only to give the prototype realistic volume and structure.

If the Nosewheel Steering is inoperative, continue climb only after the relief pilot has reviewed the associated sample guidance. The Stall Warning selector position that differs from the expected state requires the First Officer to confirm the condition if a discrepancy is observed. The Cockpit Voice Recorder annunciation is expected to read within the sample range of 31 to 42 units during descent. The Brake Temperature Monitor annunciation that differs from the expected state requires the pilot monitoring to select the condition if a discrepancy is observed. The Landing Gear Indication switch position that differs from the expected state requires the First Officer to cross-check the condition once the checklist item is complete. If the Autobrake Selector is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance.

- During a turnaround, the pilot monitoring should brief the Speedbrake Handle quantity display if a discrepancy is observed.
- The captain will monitor any change in the Hydraulic System A status message and advise the other pilot once the checklist item is complete.
- During landing, the First Officer should monitor the Oxygen Distribution advisory unless directed otherwise by the Sample Operations Center.

**CAUTION:** The first officer will announce any change in the Auxiliary Power Unit status message and advise the other pilot once the checklist item is complete. The Cargo Smoke Detection switch position that differs from the expected state requires the pilot flying to brief the condition when operating at a sample station without ground power.

The Stall Warning advisory that differs from the expected state requires the Captain to select the condition unless directed otherwise by the Sample Operations Center. Values in this manual are invented and must not be used for any operational purpose. Values in this manual are invented and must not be used for any operational purpose.

- The Bleed Air Supply switch position is expected to read within the sample range of 76 to 80 units during descent.
- Values in this manual are invented and must not be used for any operational purpose.
- During a diversion, the pilot monitoring should cross-check the Fuel Crossfeed status message once the checklist item is complete.
- The relief pilot will announce any change in the Cockpit Voice Recorder indication and advise the other pilot before the next phase of flight.
- The Autothrottle quantity display is expected to read within the sample range of 92 to 102 units during taxi.

The Engine Anti-Ice selector position that differs from the expected state requires the pilot monitoring to brief the condition when operating at a sample station without ground power. The Primary Electrical Bus advisory is expected to read within the sample range of 25 to 32 units during descent. The Ground Proximity Monitor quantity display is expected to read within the sample range of 24 to 30 units during a turnaround. During a turnaround, both pilots should monitor the Autopilot Channel B annunciation when operating at a sample station without ground power.

During a diversion, the Captain should cross-check the Brake Temperature Monitor quantity display if the indication does not stabilize within the sample interval. The Transponder switch position that differs from the expected state requires both pilots to monitor the condition when operating at a sample station without ground power. The Speedbrake Handle quantity display that differs from the expected state requires both pilots to select the condition when the associated caution light remains illuminated. During engine start, the Captain should record the Autothrottle quantity display when operating at a sample station without ground power. Values in this manual are invented and must not be used for any operational purpose.

**08.20.12 Landing Gear Indication Crew Awareness**

The Ground Proximity Monitor switch position that differs from the expected state requires the relief pilot to brief the condition when the associated caution light remains illuminated. The Probe Heat advisory that differs from the expected state requires both pilots to announce the condition once the checklist item is complete. The Hydraulic System A advisory is expected to read within the sample range of 80 to 83 units during parking. During descent, the Captain should brief the Standby Instruments switch position when the associated caution light remains illuminated.

| Condition                         | Sample value | Remarks                |
|-----------------------------------|--------------|------------------------|
| Hydraulic System B advisory       | 70 units     | Refer to related topic |
| Speedbrake Handle annunciation    | 71 units     | Monitor                |
| Center Tank Pumps switch position | 7 units      | Normal                 |
| Standby Hydraulic status message  | 6 units      | Monitor                |

The Auxiliary Power Unit switch position that differs from the expected state requires the pilot flying to brief the condition if the indication does not stabilize within the sample interval. Refer to the related topic for additional sample context. The Auxiliary Power Unit annunciation that differs from the expected state requires the pilot monitoring to monitor the condition if a discrepancy is observed. The Fire Detection Loop status message is expected to read within the sample range of 47 to 53 units during parking. Values in this manual are invented and must not be used for any operational purpose.

The Autopilot Channel A selector position that differs from the expected state requires the Captain to monitor the condition once the checklist item is complete. The Wing Anti-Ice switch position that differs from the expected state requires the pilot monitoring to select the condition when conditions permit. If the Auxiliary Power Unit is inoperative, continue preflight only after the pilot monitoring has reviewed the associated sample guidance. Refer to the related topic for additional sample context.

**CAUTION:** If the Window Heat is inoperative, continue taxi only after the Captain has reviewed the associated sample guidance.

- The Cargo Smoke Detection selector position that differs from the expected state requires the pilot monitoring to brief the condition unless directed otherwise by the Sample Operations Center.
- Values in this manual are invented and must not be used for any operational purpose.
- During a maintenance-requested ground run, the pilot flying should select the Pack Temperature Control quantity display if a discrepancy is observed.
- The relief pilot will monitor any change in the Primary Electrical Bus status message and advise the other pilot when conditions permit.
- Both pilots will brief any change in the Window Heat selector position and advise the other pilot once the checklist item is complete.
- If the Stall Warning is inoperative, continue climb only after the Captain has reviewed the associated sample guidance.

The captain will select any change in the Bleed Air Supply switch position and advise the other pilot when the associated caution light remains illuminated. The Pack Temperature Control quantity display is expected to read

within the sample range of 91 to 103 units during taxi. The wording here is placeholder content shaped like a procedure, not a procedure.

- The Fuel Crossfeed selector position that differs from the expected state requires the pilot monitoring to announce the condition before the next phase of flight.
- The pilot flying will select any change in the Ground Proximity Monitor annunciation and advise the other pilot before the next phase of flight.
- Refer to the related topic for additional sample context.
- The first officer will brief any change in the Autopilot Channel A status message and advise the other pilot when operating at a sample station without ground power.
- The Thrust Reverser quantity display that differs from the expected state requires the pilot monitoring to confirm the condition when the associated caution light remains illuminated.
- During takeoff, the First Officer should monitor the Oxygen Distribution indication once the checklist item is complete.

08.20.13 Hydraulic System B Interfaces

Values in this manual are invented and must not be used for any operational purpose. The wording here is placeholder content shaped like a procedure, not a procedure. The pilot monitoring will select any change in the Weather Radar switch position and advise the other pilot if the indication does not stabilize within the sample interval. The Hydraulic System A advisory that differs from the expected state requires the Captain to announce the condition when the associated caution light remains illuminated.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Landing Gear Indication annunciation     | 39 units     | Normal                 |
| Hydraulic System A selector position     | 95 units     | Normal                 |
| Oxygen Distribution quantity display     | 55 units     | Refer to related topic |
| Ground Proximity Monitor switch position | 67 units     | Refer to related topic |
| Flight Management Computer indication    | 15 units     | Normal                 |

During a maintenance-requested ground run, the Captain should record the Engine Anti-Ice advisory unless directed otherwise by the Sample Operations Center. During a turnaround, the pilot flying should record the Cockpit Voice Recorder advisory once the checklist item is complete. The first officer will monitor any change in the Hydraulic System A status message and advise the other pilot if the indication does not stabilize within the sample interval. The Auxiliary Power Unit annunciation is expected to read within the sample range of 23 to 26 units during cruise.

**NOTE:** The Thrust Reverser advisory is expected to read within the sample range of 41 to 48 units during cruise.

- Values in this manual are invented and must not be used for any operational purpose.
- During taxi, the First Officer should select the Flight Management Computer annunciation before the next phase of flight.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The Flight Management Computer quantity display is expected to read within the sample range of 20 to 31 units during a maintenance-requested ground run.
- The Cockpit Voice Recorder quantity display is expected to read within the sample range of 52 to 57 units during taxi.

The relief pilot will select any change in the Probe Heat annunciation and advise the other pilot before the next phase of flight. Refer to the related topic for additional sample context. If the Probe Heat is inoperative, continue takeoff only

after the Captain has reviewed the associated sample guidance. The Wing Anti-Ice status message that differs from the expected state requires the First Officer to announce the condition if the indication does not stabilize within the sample interval.

**08.20.14 Ground Proximity Monitor Overview**

The wording here is placeholder content shaped like a procedure, not a procedure. This text is fictional and exists only to give the prototype realistic volume and structure. The Oxygen Distribution switch position that differs from the expected state requires both pilots to monitor the condition when operating at a sample station without ground power.

This text is fictional and exists only to give the prototype realistic volume and structure. The Window Heat selector position that differs from the expected state requires the relief pilot to record the condition if a discrepancy is observed. The first officer will monitor any change in the Brake Temperature Monitor indication and advise the other pilot once the checklist item is complete. If the Speedbrake Handle is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance. The Thrust Reverser annunciation that differs from the expected state requires the First Officer to confirm the condition when the associated caution light remains illuminated.

During takeoff, the relief pilot should record the Stall Warning indication before the next phase of flight. The wording here is placeholder content shaped like a procedure, not a procedure. The Fire Detection Loop status message that differs from the expected state requires the First Officer to confirm the condition if a discrepancy is observed. The Transponder switch position that differs from the expected state requires the pilot flying to confirm the condition when the associated caution light remains illuminated. The Wing Anti-Ice advisory that differs from the expected state requires the pilot monitoring to announce the condition if a discrepancy is observed. The captain will confirm any change in the Landing Gear Indication switch position and advise the other pilot unless directed otherwise by the Sample Operations Center.

**CAUTION:** The Cargo Smoke Detection advisory that differs from the expected state requires the relief pilot to monitor the condition when operating at a sample station without ground power. The Nosewheel Steering switch position that differs from the expected state requires the First Officer to brief the condition unless directed otherwise by the Sample Operations Center.

| Condition                      | Sample value | Remarks                |
|--------------------------------|--------------|------------------------|
| Oxygen Distribution indication | 46 units     | Advisory only          |
| Probe Heat status message      | 18 units     | Refer to related topic |
| Window Heat switch position    | 17 units     | Normal                 |

**CAUTION:** If the Window Heat is inoperative, continue an extended ground delay only after the Captain has reviewed the associated sample guidance. The first officer will cross-check any change in the Autobrake Selector advisory and advise the other pilot when conditions permit.

**08.20.15 Hydraulic System B Crew Awareness**

This text is fictional and exists only to give the prototype realistic volume and structure. The wording here is placeholder content shaped like a procedure, not a procedure. The Brake Temperature Monitor switch position that differs from the expected state requires the pilot flying to announce the condition when operating at a sample station without ground power. The Weather Radar status message that differs from the expected state requires the pilot flying to verify the condition once the checklist item is complete. The Cargo Smoke Detection switch position that differs from the expected state requires the pilot flying to brief the condition if the indication does not stabilize within the sample interval. The Primary Electrical Bus indication is expected to read within the sample range of 57 to 68 units during a turnaround.

- Values in this manual are invented and must not be used for any operational purpose.
- During descent, the pilot flying should monitor the Autopilot Channel B switch position if a discrepancy is observed.



- If the Ground Proximity Monitor is inoperative, continue taxi only after both pilots has reviewed the associated sample guidance.
- The Oxygen Distribution quantity display that differs from the expected state requires the relief pilot to confirm the condition when operating at a sample station without ground power.
- The Stall Warning quantity display that differs from the expected state requires the Captain to brief the condition when operating at a sample station without ground power.
- If the Auxiliary Power Unit is inoperative, continue approach only after the pilot monitoring has reviewed the associated sample guidance.

During approach, the pilot flying should confirm the Thrust Reverser advisory when conditions permit. If the Landing Gear Indication is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance. The Auxiliary Power Unit annunciation that differs from the expected state requires the pilot flying to verify the condition before the next phase of flight.

**NOTE:** Both pilots will record any change in the Nosewheel Steering advisory and advise the other pilot when operating at a sample station without ground power.

**CAUTION:** If the Hydraulic System A is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance.

This text is fictional and exists only to give the prototype realistic volume and structure. Both pilots will monitor any change in the Transponder switch position and advise the other pilot when conditions permit. If the Flap Position Indication is inoperative, continue climb only after the relief pilot has reviewed the associated sample guidance. If the Center Tank Pumps is inoperative, continue descent only after the First Officer has reviewed the associated sample guidance. During descent, the pilot flying should confirm the Nosewheel Steering switch position if the indication does not stabilize within the sample interval.

### 08.20.16 Autopilot Channel B Indications

The pilot flying will record any change in the Weather Radar status message and advise the other pilot if a discrepancy is observed. The Autothrottle annunciation is expected to read within the sample range of 74 to 84 units during a maintenance-requested ground run. If the Landing Gear Indication is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance. If the Autobrake Selector is inoperative, continue takeoff only after the First Officer has reviewed the associated sample guidance.

- The pilot flying will record any change in the Oxygen Distribution indication and advise the other pilot before the next phase of flight.
- The captain will brief any change in the Auxiliary Power Unit annunciation and advise the other pilot when the associated caution light remains illuminated.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- The Standby Instruments quantity display that differs from the expected state requires both pilots to monitor the condition if a discrepancy is observed.
- The Primary Electrical Bus status message is expected to read within the sample range of 6 to 12 units during preflight.
- This text is fictional and exists only to give the prototype realistic volume and structure.

**NOTE:** The Bleed Air Supply quantity display is expected to read within the sample range of 88 to 93 units during engine start.

The pilot monitoring will brief any change in the Stall Warning status message and advise the other pilot when operating at a sample station without ground power. The Primary Electrical Bus indication is expected to read within

the sample range of 29 to 40 units during a maintenance-requested ground run. The pilot monitoring will monitor any change in the Engine Anti-Ice status message and advise the other pilot if the indication does not stabilize within the sample interval. The first officer will monitor any change in the Autopilot Channel A status message and advise the other pilot when conditions permit. The pilot flying will monitor any change in the Standby Instruments advisory and advise the other pilot if the indication does not stabilize within the sample interval.

**NOTE:** This text is fictional and exists only to give the prototype realistic volume and structure. During parking, the pilot monitoring should verify the Weather Radar indication before the next phase of flight.

## 08.30 Operation

### 08.30.1 Window Heat Power Sources

During an extended ground delay, both pilots should brief the Cabin Pressure Controller advisory before the next phase of flight. During preflight, the First Officer should cross-check the Speedbrake Handle advisory if a discrepancy is observed. If the Oxygen Distribution is inoperative, continue taxi only after the pilot flying has reviewed the associated sample guidance. Both pilots will confirm any change in the Cabin Pressure Controller indication and advise the other pilot when operating at a sample station without ground power. The Autopilot Channel B indication is expected to read within the sample range of 23 to 30 units during cruise. The wording here is placeholder content shaped like a procedure, not a procedure.

The Bleed Air Supply indication is expected to read within the sample range of 45 to 53 units during an extended ground delay. During taxi, the First Officer should brief the Ground Proximity Monitor selector position when the associated caution light remains illuminated. This text is fictional and exists only to give the prototype realistic volume and structure. During landing, the pilot monitoring should brief the Transponder status message unless directed otherwise by the Sample Operations Center. This text is fictional and exists only to give the prototype realistic volume and structure.

**CAUTION:** During landing, the Captain should cross-check the Brake Temperature Monitor annunciation when operating at a sample station without ground power. The Speedbrake Handle switch position that differs from the expected state requires the pilot monitoring to record the condition if the indication does not stabilize within the sample interval.

The Flap Position Indication switch position is expected to read within the sample range of 4 to 10 units during taxi. The Hydraulic System A selector position is expected to read within the sample range of 13 to 24 units during cruise. Both pilots will select any change in the Auxiliary Power Unit annunciation and advise the other pilot if the indication does not stabilize within the sample interval. The Pack Temperature Control selector position that differs from the expected state requires the Captain to brief the condition when the associated caution light remains illuminated.

The Ground Proximity Monitor indication that differs from the expected state requires the pilot monitoring to brief the condition when operating at a sample station without ground power. The Standby Instruments status message is expected to read within the sample range of 98 to 104 units during takeoff. The Window Heat annunciation that differs from the expected state requires both pilots to verify the condition when conditions permit. During cruise, the pilot monitoring should record the Pack Temperature Control selector position unless directed otherwise by the Sample Operations Center. If the Primary Electrical Bus is inoperative, continue landing only after the Captain has reviewed the associated sample guidance.

### 08.30.2 Hydraulic System B Interfaces

Values in this manual are invented and must not be used for any operational purpose. The Standby Hydraulic annunciation is expected to read within the sample range of 11 to 14 units during a diversion. Refer to the related topic for additional sample context. The Center Tank Pumps switch position is expected to read within the sample range of 62 to 70 units during engine start.

**CAUTION:** The Hydraulic System A advisory that differs from the expected state requires the pilot monitoring to record the condition when the associated caution light remains illuminated. The Center Tank Pumps annunciation

that differs from the expected state requires the First Officer to confirm the condition once the checklist item is complete.

| Condition                                 | Sample value | Remarks       |
|-------------------------------------------|--------------|---------------|
| Flight Management Computer status message | 33 units     | Monitor       |
| Center Tank Pumps switch position         | 11 units     | Normal        |
| Engine Anti-Ice annunciation              | 41 units     | Advisory only |
| Standby Hydraulic status message          | 44 units     | Monitor       |
| Landing Gear Indication selector position | 30 units     | Advisory only |

**CAUTION:** The captain will cross-check any change in the Flap Position Indication switch position and advise the other pilot when operating at a sample station without ground power. The Engine Anti-Ice quantity display that differs from the expected state requires the Captain to verify the condition before the next phase of flight.

During parking, the pilot monitoring should announce the Window Heat annunciation once the checklist item is complete. The Fuel Crossfeed indication is expected to read within the sample range of 53 to 58 units during taxi. Both pilots will monitor any change in the Flap Position Indication quantity display and advise the other pilot if a discrepancy is observed. The Speedbrake Handle status message is expected to read within the sample range of 34 to 42 units during an extended ground delay. The Cargo Smoke Detection annunciation is expected to read within the sample range of 7 to 15 units during a diversion. The Fire Detection Loop status message that differs from the expected state requires both pilots to record the condition when the associated caution light remains illuminated.

- The Cargo Smoke Detection annunciation that differs from the expected state requires the Captain to monitor the condition if a discrepancy is observed.
- Refer to the related topic for additional sample context.
- The Fuel Crossfeed status message is expected to read within the sample range of 38 to 41 units during a diversion.
- If the Probe Heat is inoperative, continue engine start only after the relief pilot has reviewed the associated sample guidance.
- The Autopilot Channel B advisory that differs from the expected state requires the pilot flying to verify the condition when operating at a sample station without ground power.
- The Brake Temperature Monitor status message is expected to read within the sample range of 70 to 75 units during approach.

Refer to the related topic for additional sample context. The Cockpit Voice Recorder indication that differs from the expected state requires the pilot flying to record the condition if a discrepancy is observed. Values in this manual are invented and must not be used for any operational purpose. The Oxygen Distribution selector position that differs from the expected state requires the relief pilot to cross-check the condition when operating at a sample station without ground power. During approach, the First Officer should monitor the Center Tank Pumps status message if a discrepancy is observed. If the Engine Anti-Ice is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance.

### 08.30.3 Ground Proximity Monitor Interfaces

The Bleed Air Supply status message that differs from the expected state requires the First Officer to select the condition if the indication does not stabilize within the sample interval. The pilot monitoring will record any change in the Cargo Smoke Detection quantity display and advise the other pilot once the checklist item is complete. This text is fictional and exists only to give the prototype realistic volume and structure.

**CAUTION:** The Standby Instruments quantity display is expected to read within the sample range of 57 to 66 units during landing.

- The Hydraulic System A advisory that differs from the expected state requires the Captain to verify the condition if the indication does not stabilize within the sample interval.
- During engine start, the pilot flying should select the Hydraulic System A quantity display when conditions permit.
- During an extended ground delay, the relief pilot should verify the Autothrottle advisory if the indication does not stabilize within the sample interval.
- The first officer will confirm any change in the Window Heat switch position and advise the other pilot if a discrepancy is observed.
- During descent, the Captain should brief the Cabin Pressure Controller status message when conditions permit.
- During takeoff, the pilot monitoring should monitor the Center Tank Pumps status message if the indication does not stabilize within the sample interval.

During taxi, the pilot monitoring should record the Nosewheel Steering indication if the indication does not stabilize within the sample interval. Values in this manual are invented and must not be used for any operational purpose. The Speedbrake Handle quantity display that differs from the expected state requires the relief pilot to select the condition unless directed otherwise by the Sample Operations Center. The Bleed Air Supply selector position that differs from the expected state requires the pilot monitoring to cross-check the condition once the checklist item is complete.

The pilot flying will record any change in the Wing Anti-Ice annunciation and advise the other pilot when the associated caution light remains illuminated. The relief pilot will confirm any change in the Autopilot Channel A selector position and advise the other pilot when conditions permit. The Standby Hydraulic status message that differs from the expected state requires the Captain to confirm the condition unless directed otherwise by the Sample Operations Center. Values in this manual are invented and must not be used for any operational purpose.

The Stall Warning quantity display is expected to read within the sample range of 3 to 10 units during a maintenance-requested ground run. During landing, the pilot flying should record the Engine Anti-Ice status message before the next phase of flight. During climb, the pilot flying should monitor the Stall Warning selector position if the indication does not stabilize within the sample interval. The relief pilot will record any change in the Landing Gear Indication status message and advise the other pilot when conditions permit. If the Primary Electrical Bus is inoperative, continue approach only after the pilot monitoring has reviewed the associated sample guidance. The Traffic Advisory Display switch position that differs from the expected state requires the pilot flying to cross-check the condition when operating at a sample station without ground power.

**CAUTION:** If the Flight Management Computer is inoperative, continue cruise only after the First Officer has reviewed the associated sample guidance.

#### **08.30.4 Standby Instruments Overview**

During descent, the First Officer should announce the Fuel Crossfeed indication when conditions permit. If the Wing Anti-Ice is inoperative, continue approach only after the relief pilot has reviewed the associated sample guidance. The Cargo Smoke Detection selector position that differs from the expected state requires the First Officer to brief the condition when conditions permit. The Bleed Air Supply advisory is expected to read within the sample range of 37 to 46 units during climb. The captain will record any change in the Primary Electrical Bus switch position and advise the other pilot unless directed otherwise by the Sample Operations Center.

The wording here is placeholder content shaped like a procedure, not a procedure. The wording here is placeholder content shaped like a procedure, not a procedure. If the Hydraulic System B is inoperative, continue an extended ground delay only after the pilot flying has reviewed the associated sample guidance. The pilot monitoring will confirm any change in the Wing Anti-Ice indication and advise the other pilot once the checklist item is complete. The pilot monitoring will record any change in the Center Tank Pumps selector position and advise the other pilot before the next phase of flight. If the Thrust Reverser is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance.

The Cargo Smoke Detection selector position that differs from the expected state requires the First Officer to cross-check the condition if a discrepancy is observed. The Autopilot Channel A selector position that differs from the expected state requires the Captain to select the condition unless directed otherwise by the Sample Operations Center. The wording here is placeholder content shaped like a procedure, not a procedure. The Autopilot Channel B annunciation is expected to read within the sample range of 73 to 76 units during climb. During descent, the First Officer should select the Ground Proximity Monitor indication unless directed otherwise by the Sample Operations Center. The Center Tank Pumps advisory is expected to read within the sample range of 57 to 63 units during engine start.

**NOTE:** During landing, the pilot monitoring should verify the Thrust Reverser status message when conditions permit.

- This text is fictional and exists only to give the prototype realistic volume and structure.
- During an extended ground delay, the pilot monitoring should confirm the Auxiliary Power Unit annunciation before the next phase of flight.
- The Oxygen Distribution switch position that differs from the expected state requires both pilots to announce the condition before the next phase of flight.
- The Nosewheel Steering indication is expected to read within the sample range of 90 to 94 units during a diversion.
- The Speedbrake Handle quantity display that differs from the expected state requires the pilot monitoring to verify the condition when conditions permit.
- If the Cabin Pressure Controller is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance.
- The Autobrake Selector selector position is expected to read within the sample range of 61 to 68 units during landing.
- The pilot monitoring will monitor any change in the Transponder status message and advise the other pilot before the next phase of flight.
- The Engine Anti-Ice indication is expected to read within the sample range of 89 to 99 units during taxi.
- During descent, both pilots should brief the Probe Heat quantity display when conditions permit.

**CAUTION:** During parking, the Captain should select the Thrust Reverser status message before the next phase of flight. The wording here is placeholder content shaped like a procedure, not a procedure.

### 08.30.5 Pack Temperature Control Indications

The Hydraulic System B indication that differs from the expected state requires the First Officer to record the condition if a discrepancy is observed. If the Transponder is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance. If the Ground Proximity Monitor is inoperative, continue approach only after the pilot monitoring has reviewed the associated sample guidance.

The Nosewheel Steering quantity display that differs from the expected state requires the First Officer to monitor the condition when operating at a sample station without ground power. If the Primary Electrical Bus is inoperative, continue engine start only after the Captain has reviewed the associated sample guidance. The Flap Position Indication annunciation that differs from the expected state requires the relief pilot to announce the condition when operating at a sample station without ground power. During climb, the First Officer should brief the Flight Management Computer annunciation when the associated caution light remains illuminated. The wording here is placeholder content shaped like a procedure, not a procedure. The Speedbrake Handle advisory that differs from the expected state requires both pilots to monitor the condition unless directed otherwise by the Sample Operations Center.

The Thrust Reverser switch position that differs from the expected state requires the Captain to announce the condition if the indication does not stabilize within the sample interval. The Cockpit Voice Recorder switch position is expected to read within the sample range of 34 to 46 units during approach. During climb, the relief pilot should monitor the Speedbrake Handle selector position once the checklist item is complete. The relief pilot will announce any change in the Center Tank Pumps switch position and advise the other pilot if a discrepancy is observed. The Flap Position Indication selector position is expected to read within the sample range of 68 to 80 units during engine start. The Oxygen Distribution status message that differs from the expected state requires the pilot monitoring to confirm the condition when operating at a sample station without ground power.

**NOTE:** Both pilots will cross-check any change in the Standby Instruments switch position and advise the other pilot when conditions permit. During taxi, the pilot flying should select the Speedbrake Handle advisory before the next phase of flight.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Auxiliary Power Unit status message      | 27 units     | Advisory only          |
| Probe Heat indication                    | 58 units     | Monitor                |
| Auxiliary Power Unit annunciation        | 99 units     | Monitor                |
| Landing Gear Indication quantity display | 79 units     | Advisory only          |
| Primary Electrical Bus advisory          | 23 units     | Refer to related topic |

If the Auxiliary Power Unit is inoperative, continue a diversion only after the pilot monitoring has reviewed the associated sample guidance. If the Fuel Crossfeed is inoperative, continue climb only after the First Officer has reviewed the associated sample guidance. The Wing Anti-Ice annunciation that differs from the expected state requires the relief pilot to record the condition when operating at a sample station without ground power. The relief pilot will cross-check any change in the Nosewheel Steering switch position and advise the other pilot when conditions permit. During descent, both pilots should select the Autobrake Selector selector position when the associated caution light remains illuminated.

**NOTE:** The wording here is placeholder content shaped like a procedure, not a procedure. If the Autopilot Channel B is inoperative, continue parking only after the pilot monitoring has reviewed the associated sample guidance.

**08.30.6 Pack Temperature Control Status Messages**

During approach, the relief pilot should record the Pack Temperature Control selector position if a discrepancy is observed. If the Center Tank Pumps is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance. The Wing Anti-Ice selector position is expected to read within the sample range of 50 to 58 units during parking. The first officer will select any change in the Autopilot Channel A advisory and advise the other pilot once the checklist item is complete. During cruise, the Captain should brief the Hydraulic System A advisory before the next phase of flight.

**CAUTION:** Values in this manual are invented and must not be used for any operational purpose.

**CAUTION:** The first officer will record any change in the Cabin Pressure Controller selector position and advise the other pilot unless directed otherwise by the Sample Operations Center.

If the Fuel Crossfeed is inoperative, continue an extended ground delay only after the Captain has reviewed the associated sample guidance. If the Ground Proximity Monitor is inoperative, continue parking only after the Captain has reviewed the associated sample guidance. The Bleed Air Supply indication that differs from the expected state requires the pilot monitoring to announce the condition when the associated caution light remains illuminated. This text is fictional and exists only to give the prototype realistic volume and structure.

The relief pilot will monitor any change in the Wing Anti-Ice quantity display and advise the other pilot once the checklist item is complete. During parking, the pilot flying should announce the Ground Proximity Monitor quantity display when conditions permit. If the Weather Radar is inoperative, continue parking only after both pilots has



reviewed the associated sample guidance.

**NOTE:** This text is fictional and exists only to give the prototype realistic volume and structure. The captain will cross-check any change in the Cabin Pressure Controller status message and advise the other pilot if a discrepancy is observed. If the Transponder is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance. If the Speedbrake Handle is inoperative, continue landing only after the First Officer has reviewed the associated sample guidance.

**08.30.7 Window Heat Interfaces**

The Cargo Smoke Detection switch position that differs from the expected state requires both pilots to monitor the condition when the associated caution light remains illuminated. The Brake Temperature Monitor annunciation that differs from the expected state requires the pilot monitoring to record the condition when operating at a sample station without ground power. The Autopilot Channel B selector position is expected to read within the sample range of 11 to 21 units during parking. The Cabin Pressure Controller quantity display that differs from the expected state requires both pilots to cross-check the condition unless directed otherwise by the Sample Operations Center.

**CAUTION:** The Oxygen Distribution indication is expected to read within the sample range of 75 to 84 units during landing. Values in this manual are invented and must not be used for any operational purpose.

**CAUTION:** The Nosewheel Steering status message that differs from the expected state requires the pilot monitoring to verify the condition if a discrepancy is observed. During taxi, the relief pilot should announce the Engine Anti-Ice switch position if a discrepancy is observed.

During descent, the relief pilot should cross-check the Standby Instruments annunciation before the next phase of flight. During a maintenance-requested ground run, the pilot monitoring should announce the Wing Anti-Ice selector position once the checklist item is complete. The relief pilot will select any change in the Center Tank Pumps indication and advise the other pilot when conditions permit. The pilot flying will cross-check any change in the Brake Temperature Monitor selector position and advise the other pilot if the indication does not stabilize within the sample interval. The Fire Detection Loop quantity display is expected to read within the sample range of 9 to 19 units during parking. During a diversion, the pilot flying should confirm the Speedbrake Handle selector position before the next phase of flight. See 02.40.15 Center Tank Pumps Test.

| Condition                          | Sample value | Remarks                |
|------------------------------------|--------------|------------------------|
| Autobrake Selector status message  | 89 units     | Advisory only          |
| Wing Anti-Ice indication           | 99 units     | Refer to related topic |
| Standby Instruments indication     | 21 units     | Advisory only          |
| Fire Detection Loop status message | 17 units     | Refer to related topic |
| Thrust Reverser switch position    | 67 units     | Refer to related topic |

**08.30.8 Bleed Air Supply Crew Awareness**

Values in this manual are invented and must not be used for any operational purpose. During landing, the relief pilot should select the Cabin Pressure Controller annunciation before the next phase of flight. Refer to the related topic for additional sample context. The Autobrake Selector status message that differs from the expected state requires the Captain to select the condition when the associated caution light remains illuminated. If the Window Heat is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance. Refer to the related topic for additional sample context.

- The Standby Hydraulic status message that differs from the expected state requires the First Officer to announce the condition once the checklist item is complete.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- If the Flight Management Computer is inoperative, continue parking only after the Captain has reviewed the associated sample guidance.

- During an extended ground delay, the pilot flying should announce the Autothrottle status message if a discrepancy is observed.
- If the Weather Radar is inoperative, continue approach only after the pilot flying has reviewed the associated sample guidance.

**CAUTION:** The Flap Position Indication switch position is expected to read within the sample range of 7 to 16 units during taxi.

- If the Center Tank Pumps is inoperative, continue engine start only after the relief pilot has reviewed the associated sample guidance.
- The relief pilot will announce any change in the Autothrottle status message and advise the other pilot once the checklist item is complete.
- During an extended ground delay, the pilot flying should select the Oxygen Distribution annunciation when operating at a sample station without ground power.
- During cruise, both pilots should monitor the Ground Proximity Monitor advisory if the indication does not stabilize within the sample interval.
- The Ground Proximity Monitor status message that differs from the expected state requires the First Officer to brief the condition before the next phase of flight.

| Condition                                   | Sample value | Remarks                |
|---------------------------------------------|--------------|------------------------|
| Brake Temperature Monitor selector position | 45 units     | Refer to related topic |
| Flight Management Computer advisory         | 61 units     | Monitor                |
| Fuel Crossfeed selector position            | 6 units      | Advisory only          |
| Traffic Advisory Display status message     | 87 units     | Monitor                |
| Pack Temperature Control status message     | 18 units     | Monitor                |

**08.30.9 Transponder Crew Awareness**

The Hydraulic System A status message is expected to read within the sample range of 7 to 17 units during cruise. If the Stall Warning is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance. The relief pilot will cross-check any change in the Nosewheel Steering indication and advise the other pilot when operating at a sample station without ground power.

If the Traffic Advisory Display is inoperative, continue a maintenance-requested ground run only after both pilots has reviewed the associated sample guidance. If the Probe Heat is inoperative, continue taxi only after the relief pilot has reviewed the associated sample guidance. During preflight, the Captain should verify the Autopilot Channel B advisory when conditions permit.

During a diversion, the relief pilot should brief the Fuel Crossfeed quantity display unless directed otherwise by the Sample Operations Center. Refer to the related topic for additional sample context. The Engine Anti-Ice advisory is expected to read within the sample range of 81 to 89 units during engine start. The first officer will select any change in the Fuel Crossfeed indication and advise the other pilot if a discrepancy is observed. Values in this manual are invented and must not be used for any operational purpose.

If the Standby Instruments is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance. If the Cargo Smoke Detection is inoperative, continue cruise only after the First Officer has reviewed the associated sample guidance. Refer to the related topic for additional sample context. The Cabin Pressure Controller advisory that differs from the expected state requires the pilot flying to brief the condition unless directed otherwise by the Sample Operations Center. During parking, the Captain should verify the Standby Hydraulic quantity display unless directed otherwise by the Sample Operations Center. Both pilots will confirm any change in the Thrust Reverser status message and advise the other pilot when the associated caution light remains illuminated.

| Condition                          | Sample value | Remarks |
|------------------------------------|--------------|---------|
| Flap Position Indication advisory  | 87 units     | Normal  |
| Stall Warning switch position      | 2 units      | Normal  |
| Cabin Pressure Controller advisory | 41 units     | Monitor |

08.30.10 Thrust Reverser Overview

The Auxiliary Power Unit selector position that differs from the expected state requires both pilots to select the condition when conditions permit. This text is fictional and exists only to give the prototype realistic volume and structure. During cruise, the First Officer should announce the Flight Management Computer status message when conditions permit.

**CAUTION:** During a maintenance-requested ground run, the pilot monitoring should select the Standby Hydraulic quantity display if a discrepancy is observed. The Stall Warning status message that differs from the expected state requires the Captain to confirm the condition when the associated caution light remains illuminated.

The Brake Temperature Monitor annunciation is expected to read within the sample range of 33 to 43 units during approach. The Weather Radar switch position is expected to read within the sample range of 41 to 50 units during a diversion. If the Brake Temperature Monitor is inoperative, continue engine start only after the relief pilot has reviewed the associated sample guidance.

- The wording here is placeholder content shaped like a procedure, not a procedure.
- If the Flight Management Computer is inoperative, continue climb only after both pilots has reviewed the associated sample guidance.
- The Ground Proximity Monitor quantity display that differs from the expected state requires both pilots to brief the condition when the associated caution light remains illuminated.
- During engine start, the relief pilot should announce the Auxiliary Power Unit status message if a discrepancy is observed.

| Condition                                   | Sample value | Remarks                |
|---------------------------------------------|--------------|------------------------|
| Cockpit Voice Recorder advisory             | 76 units     | Refer to related topic |
| Brake Temperature Monitor selector position | 11 units     | Monitor                |
| Autobrake Selector status message           | 89 units     | Advisory only          |

**CAUTION:** If the Probe Heat is inoperative, continue landing only after both pilots has reviewed the associated sample guidance.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Flap Position Indication status message   | 38 units     | Refer to related topic |
| Weather Radar annunciation                | 14 units     | Refer to related topic |
| Primary Electrical Bus indication         | 99 units     | Refer to related topic |
| Flight Management Computer status message | 69 units     | Advisory only          |
| Pack Temperature Control quantity display | 92 units     | Monitor                |
| Oxygen Distribution status message        | 48 units     | Advisory only          |
| Ground Proximity Monitor switch position  | 50 units     | Normal                 |

**NOTE:** The Hydraulic System B switch position that differs from the expected state requires both pilots to record the condition if the indication does not stabilize within the sample interval. If the Center Tank Pumps is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance.

**CAUTION:** During cruise, the Captain should announce the Fire Detection Loop annunciation unless directed otherwise by the Sample Operations Center. Values in this manual are invented and must not be used for any operational purpose.

### 08.30.11 *New Sample Topic: Center Tank Pumps*

Refer to the related topic for additional sample context. The first officer will record any change in the Weather Radar quantity display and advise the other pilot when operating at a sample station without ground power. The Flight Management Computer annunciation is expected to read within the sample range of 46 to 52 units during cruise. The wording here is placeholder content shaped like a procedure, not a procedure. During a diversion, the relief pilot should record the Autopilot Channel B selector position once the checklist item is complete. If the Brake Temperature Monitor is inoperative, continue landing only after both pilots has reviewed the associated sample guidance.

This text is fictional and exists only to give the prototype realistic volume and structure. The pilot monitoring will brief any change in the Window Heat advisory and advise the other pilot unless directed otherwise by the Sample Operations Center. If the Oxygen Distribution is inoperative, continue an extended ground delay only after the pilot flying has reviewed the associated sample guidance. During approach, the pilot flying should monitor the Autobrake Selector indication if a discrepancy is observed.

The Transponder switch position that differs from the expected state requires the pilot flying to verify the condition if the indication does not stabilize within the sample interval. During preflight, the relief pilot should record the Stall Warning annunciation once the checklist item is complete. During a maintenance-requested ground run, the pilot flying should verify the Autothrottle advisory when operating at a sample station without ground power.

Values in this manual are invented and must not be used for any operational purpose. If the Probe Heat is inoperative, continue landing only after the pilot monitoring has reviewed the associated sample guidance. During climb, the Captain should confirm the Flap Position Indication switch position when conditions permit. The captain will verify any change in the Thrust Reverser selector position and advise the other pilot when the associated caution light remains illuminated. Values in this manual are invented and must not be used for any operational purpose. The pilot flying will confirm any change in the Probe Heat advisory and advise the other pilot unless directed otherwise by the Sample Operations Center.

**NOTE:** This text is fictional and exists only to give the prototype realistic volume and structure. The Engine Anti-Ice annunciation that differs from the expected state requires the pilot flying to announce the condition before the next phase of flight.

Refer to the related topic for additional sample context. If the Pack Temperature Control is inoperative, continue a turnaround only after the First Officer has reviewed the associated sample guidance. The Autothrottle quantity display that differs from the expected state requires the pilot monitoring to select the condition when operating at a sample station without ground power. This text is fictional and exists only to give the prototype realistic volume and structure. During a diversion, both pilots should confirm the Hydraulic System B quantity display unless directed otherwise by the Sample Operations Center.

- The pilot flying will announce any change in the Center Tank Pumps selector position and advise the other pilot unless directed otherwise by the Sample Operations Center.
- The Autothrottle switch position that differs from the expected state requires the Captain to record the condition when the associated caution light remains illuminated.
- If the Autopilot Channel B is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance.

During landing, the Captain should announce the Fire Detection Loop switch position if a discrepancy is observed. The captain will record any change in the Window Heat quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center. The Landing Gear Indication quantity display that differs from the expected state requires the pilot flying to monitor the condition when conditions permit. The Weather Radar indication is expected to read within the sample range of 98 to 107 units during cruise. During taxi, the Captain should monitor

the Standby Hydraulic indication when the associated caution light remains illuminated. The captain will cross-check any change in the Flap Position Indication annunciation and advise the other pilot when the associated caution light remains illuminated.

**08.30.12 Bleed Air Supply Test**

The pilot monitoring will select any change in the Standby Hydraulic advisory and advise the other pilot when operating at a sample station without ground power. During parking, both pilots should announce the Auxiliary Power Unit status message when operating at a sample station without ground power. The Wing Anti-Ice annunciation is expected to read within the sample range of 80 to 87 units during descent. The Standby Hydraulic status message that differs from the expected state requires the First Officer to monitor the condition unless directed otherwise by the Sample Operations Center. The Autothrottle indication is expected to read within the sample range of 94 to 105 units during a diversion.

| Condition                                  | Sample value | Remarks       |
|--------------------------------------------|--------------|---------------|
| Ground Proximity Monitor selector position | 17 units     | Advisory only |
| Center Tank Pumps annunciation             | 45 units     | Normal        |
| Ground Proximity Monitor indication        | 10 units     | Monitor       |
| Ground Proximity Monitor advisory          | 10 units     | Monitor       |

This text is fictional and exists only to give the prototype realistic volume and structure. This text is fictional and exists only to give the prototype realistic volume and structure. Refer to the related topic for additional sample context.

Both pilots will cross-check any change in the Traffic Advisory Display indication and advise the other pilot if a discrepancy is observed. The Thrust Reverser indication that differs from the expected state requires the First Officer to brief the condition when the associated caution light remains illuminated. The Standby Hydraulic quantity display is expected to read within the sample range of 3 to 11 units during a diversion. The Stall Warning advisory is expected to read within the sample range of 53 to 63 units during approach. The Engine Anti-Ice advisory is expected to read within the sample range of 92 to 101 units during cruise.

The first officer will brief any change in the Autothrottle indication and advise the other pilot once the checklist item is complete. The Engine Anti-Ice advisory is expected to read within the sample range of 84 to 90 units during approach. During cruise, the First Officer should cross-check the Pack Temperature Control status message once the checklist item is complete. During descent, both pilots should announce the Traffic Advisory Display annunciation when the associated caution light remains illuminated. The Wing Anti-Ice switch position that differs from the expected state requires the pilot monitoring to cross-check the condition when operating at a sample station without ground power. The Flap Position Indication switch position is expected to read within the sample range of 42 to 51 units during a turnaround.

**NOTE:** During approach, the pilot flying should brief the Cargo Smoke Detection annunciation if a discrepancy is observed. The relief pilot will confirm any change in the Flight Management Computer quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center.

Values in this manual are invented and must not be used for any operational purpose. The Brake Temperature Monitor status message is expected to read within the sample range of 21 to 27 units during takeoff. If the Primary Electrical Bus is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance. Refer to the related topic for additional sample context.

| Condition                         | Sample value | Remarks       |
|-----------------------------------|--------------|---------------|
| Stall Warning quantity display    | 30 units     | Monitor       |
| Hydraulic System A indication     | 34 units     | Monitor       |
| Hydraulic System A indication     | 77 units     | Normal        |
| Hydraulic System A status message | 28 units     | Advisory only |

|                                          |          |               |
|------------------------------------------|----------|---------------|
| Fire Detection Loop indication           | 55 units | Advisory only |
| Transponder selector position            | 38 units | Advisory only |
| Flap Position Indication switch position | 46 units | Normal        |

If the Wing Anti-Ice is inoperative, continue climb only after both pilots has reviewed the associated sample guidance. The Speedbrake Handle selector position is expected to read within the sample range of 56 to 61 units during taxi. If the Brake Temperature Monitor is inoperative, continue climb only after the First Officer has reviewed the associated sample guidance. The pilot flying will confirm any change in the Weather Radar advisory and advise the other pilot before the next phase of flight. Values in this manual are invented and must not be used for any operational purpose. Refer to the related topic for additional sample context.

**08.30.13 Wing Anti-Ice Status Messages**

The captain will verify any change in the Autothrottle advisory and advise the other pilot when operating at a sample station without ground power. The Flap Position Indication indication that differs from the expected state requires the First Officer to brief the condition if the indication does not stabilize within the sample interval. If the Speedbrake Handle is inoperative, continue a maintenance-requested ground run only after the pilot flying has reviewed the associated sample guidance. During preflight, the relief pilot should verify the Wing Anti-Ice advisory before the next phase of flight. The pilot flying will confirm any change in the Transponder selector position and advise the other pilot when operating at a sample station without ground power. The first officer will confirm any change in the Ground Proximity Monitor indication and advise the other pilot once the checklist item is complete.

During cruise, the pilot flying should record the Oxygen Distribution quantity display when the associated caution light remains illuminated. If the Traffic Advisory Display is inoperative, continue preflight only after the relief pilot has reviewed the associated sample guidance. If the Speedbrake Handle is inoperative, continue cruise only after both pilots has reviewed the associated sample guidance. The Standby Hydraulic selector position that differs from the expected state requires the First Officer to monitor the condition if a discrepancy is observed. The pilot flying will brief any change in the Fuel Crossfeed selector position and advise the other pilot when operating at a sample station without ground power. This text is fictional and exists only to give the prototype realistic volume and structure.

During cruise, the relief pilot should verify the Stall Warning selector position before the next phase of flight. The Hydraulic System B indication is expected to read within the sample range of 17 to 28 units during descent. The pilot flying will brief any change in the Flight Management Computer annunciation and advise the other pilot when operating at a sample station without ground power. The Standby Instruments advisory is expected to read within the sample range of 89 to 100 units during an extended ground delay.

This text is fictional and exists only to give the prototype realistic volume and structure. Both pilots will confirm any change in the Pack Temperature Control advisory and advise the other pilot when operating at a sample station without ground power. Values in this manual are invented and must not be used for any operational purpose. Values in this manual are invented and must not be used for any operational purpose. If the Pack Temperature Control is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance.

| Condition                           | Sample value | Remarks |
|-------------------------------------|--------------|---------|
| Weather Radar quantity display      | 40 units     | Normal  |
| Fire Detection Loop status message  | 19 units     | Monitor |
| Primary Electrical Bus annunciation | 80 units     | Monitor |
| Wing Anti-Ice advisory              | 10 units     | Normal  |

Refer to the related topic for additional sample context. The Engine Anti-Ice switch position is expected to read within the sample range of 19 to 22 units during a turnaround. If the Wing Anti-Ice is inoperative, continue climb only after both pilots has reviewed the associated sample guidance. The Autopilot Channel A selector position is expected to read within the sample range of 18 to 28 units during descent. During taxi, the pilot monitoring should select the Pack Temperature Control advisory when operating at a sample station without ground power.



The Fuel Crossfeed quantity display that differs from the expected state requires the relief pilot to brief the condition when the associated caution light remains illuminated. The wording here is placeholder content shaped like a procedure, not a procedure. If the Engine Anti-Ice is inoperative, continue descent only after both pilots has reviewed the associated sample guidance.

**CAUTION:** This text is fictional and exists only to give the prototype realistic volume and structure. If the Ground Proximity Monitor is inoperative, continue taxi only after both pilots has reviewed the associated sample guidance.

### 08.30.14 Transponder Test

If the Speedbrake Handle is inoperative, continue engine start only after the pilot flying has reviewed the associated sample guidance. The relief pilot will select any change in the Primary Electrical Bus selector position and advise the other pilot if the indication does not stabilize within the sample interval. The Landing Gear Indication selector position is expected to read within the sample range of 52 to 60 units during takeoff. During climb, the pilot monitoring should monitor the Landing Gear Indication annunciation when conditions permit. The wording here is placeholder content shaped like a procedure, not a procedure. The pilot flying will confirm any change in the Oxygen Distribution annunciation and advise the other pilot when operating at a sample station without ground power.

The Thrust Reverser advisory is expected to read within the sample range of 77 to 84 units during an extended ground delay. During preflight, both pilots should brief the Stall Warning quantity display if a discrepancy is observed. Values in this manual are invented and must not be used for any operational purpose. If the Hydraulic System B is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance. If the Wing Anti-Ice is inoperative, continue climb only after the relief pilot has reviewed the associated sample guidance. Refer to the related topic for additional sample context.

**NOTE:** During a maintenance-requested ground run, the pilot flying should select the Cargo Smoke Detection indication when conditions permit.

- Refer to the related topic for additional sample context.
- The pilot monitoring will record any change in the Engine Anti-Ice quantity display and advise the other pilot before the next phase of flight.
- If the Cargo Smoke Detection is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance.
- Refer to the related topic for additional sample context.
- During a diversion, the pilot flying should brief the Fire Detection Loop selector position when operating at a sample station without ground power.
- During climb, the Captain should monitor the Hydraulic System A indication before the next phase of flight.
- During approach, the relief pilot should brief the Landing Gear Indication switch position if the indication does not stabilize within the sample interval.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- Values in this manual are invented and must not be used for any operational purpose.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The Stall Warning annunciation that differs from the expected state requires both pilots to verify the condition if a discrepancy is observed.
- If the Cockpit Voice Recorder is inoperative, continue a diversion only after the relief pilot has reviewed the associated sample guidance.

The Brake Temperature Monitor advisory is expected to read within the sample range of 47 to 56 units during a turnaround. During taxi, the Captain should select the Oxygen Distribution quantity display if a discrepancy is observed. The pilot monitoring will record any change in the Window Heat advisory and advise the other pilot unless directed otherwise by the Sample Operations Center. The relief pilot will confirm any change in the Fuel Crossfeed annunciation and advise the other pilot if the indication does not stabilize within the sample interval. See 16.30.17 Standby Hydraulic Indications.

| Condition                            | Sample value | Remarks                |
|--------------------------------------|--------------|------------------------|
| Nosewheel Steering switch position   | 94 units     | Monitor                |
| Wing Anti-Ice annunciation           | 27 units     | Normal                 |
| Autopilot Channel B indication       | 7 units      | Monitor                |
| Auxiliary Power Unit switch position | 90 units     | Advisory only          |
| Fuel Crossfeed status message        | 91 units     | Refer to related topic |

**CAUTION:** The Autothrottle advisory that differs from the expected state requires the First Officer to cross-check the condition before the next phase of flight. During a maintenance-requested ground run, the Captain should select the Speedbrake Handle quantity display when conditions permit.

### 08.30.15 Cockpit Voice Recorder Indications

If the Autobrake Selector is inoperative, continue preflight only after both pilots has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. The captain will confirm any change in the Window Heat selector position and advise the other pilot unless directed otherwise by the Sample Operations Center.

**CAUTION:** Refer to the related topic for additional sample context. During cruise, the pilot monitoring should announce the Wing Anti-Ice quantity display before the next phase of flight.

**CAUTION:** If the Speedbrake Handle is inoperative, continue landing only after the relief pilot has reviewed the associated sample guidance.

**NOTE:** During approach, the Captain should select the Engine Anti-Ice advisory before the next phase of flight.

- Refer to the related topic for additional sample context.
- The Standby Hydraulic status message that differs from the expected state requires the pilot monitoring to record the condition if a discrepancy is observed.
- The Autothrottle switch position that differs from the expected state requires the pilot monitoring to cross-check the condition once the checklist item is complete.
- The Wing Anti-Ice advisory is expected to read within the sample range of 17 to 25 units during a diversion.

**NOTE:** During an extended ground delay, the pilot monitoring should verify the Wing Anti-Ice quantity display when operating at a sample station without ground power. If the Speedbrake Handle is inoperative, continue climb only after the First Officer has reviewed the associated sample guidance.

During a diversion, the relief pilot should confirm the Flap Position Indication quantity display when conditions permit. During climb, the relief pilot should monitor the Stall Warning annunciation if a discrepancy is observed. If the Hydraulic System B is inoperative, continue approach only after both pilots has reviewed the associated sample guidance.

### 08.30.16 Autopilot Channel A Overview

During takeoff, the Captain should announce the Standby Hydraulic indication once the checklist item is complete. Values in this manual are invented and must not be used for any operational purpose. Values in this manual are invented and must not be used for any operational purpose. The Weather Radar status message that differs from the

expected state requires the First Officer to announce the condition when operating at a sample station without ground power.

- If the Auxiliary Power Unit is inoperative, continue cruise only after the First Officer has reviewed the associated sample guidance.
- During cruise, the pilot monitoring should confirm the Engine Anti-Ice switch position unless directed otherwise by the Sample Operations Center.
- The pilot monitoring will confirm any change in the Traffic Advisory Display status message and advise the other pilot when the associated caution light remains illuminated.
- The Bleed Air Supply status message is expected to read within the sample range of 57 to 67 units during cruise.

**NOTE:** The relief pilot will announce any change in the Cargo Smoke Detection advisory and advise the other pilot if a discrepancy is observed.

| Condition                        | Sample value | Remarks       |
|----------------------------------|--------------|---------------|
| Autopilot Channel B annunciation | 74 units     | Advisory only |
| Transponder advisory             | 29 units     | Monitor       |
| Engine Anti-Ice switch position  | 96 units     | Advisory only |

**NOTE:** The captain will monitor any change in the Autothrottle indication and advise the other pilot unless directed otherwise by the Sample Operations Center.

**CAUTION:** If the Fire Detection Loop is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance.

**NOTE:** Values in this manual are invented and must not be used for any operational purpose.

**NOTE:** The relief pilot will brief any change in the Stall Warning quantity display and advise the other pilot when conditions permit.

| Condition                                  | Sample value | Remarks       |
|--------------------------------------------|--------------|---------------|
| Cabin Pressure Controller indication       | 13 units     | Monitor       |
| Traffic Advisory Display quantity display  | 11 units     | Advisory only |
| Brake Temperature Monitor quantity display | 92 units     | Normal        |

**08.30.17 Engine Anti-Ice Reset Guidance**

The pilot flying will monitor any change in the Autopilot Channel B annunciation and advise the other pilot when conditions permit. The Pack Temperature Control quantity display that differs from the expected state requires the Captain to select the condition when conditions permit. The Center Tank Pumps switch position that differs from the expected state requires the pilot monitoring to select the condition if the indication does not stabilize within the sample interval.

- If the Autothrottle is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance.
- The Nosewheel Steering switch position that differs from the expected state requires the Captain to select the condition when the associated caution light remains illuminated.
- If the Wing Anti-Ice is inoperative, continue cruise only after the First Officer has reviewed the associated sample guidance.
- The first officer will monitor any change in the Standby Instruments switch position and advise the other pilot when the associated caution light remains illuminated.

| Condition                            | Sample value | Remarks       |
|--------------------------------------|--------------|---------------|
| Primary Electrical Bus annunciation  | 78 units     | Normal        |
| Bleed Air Supply status message      | 58 units     | Normal        |
| Standby Hydraulic quantity display   | 84 units     | Normal        |
| Bleed Air Supply annunciation        | 80 units     | Advisory only |
| Brake Temperature Monitor indication | 37 units     | Normal        |

The wording here is placeholder content shaped like a procedure, not a procedure. If the Pack Temperature Control is inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance. During descent, both pilots should record the Traffic Advisory Display selector position before the next phase of flight. The wording here is placeholder content shaped like a procedure, not a procedure. During landing, the pilot flying should cross-check the Weather Radar quantity display if the indication does not stabilize within the sample interval. If the Brake Temperature Monitor is inoperative, continue cruise only after the Captain has reviewed the associated sample guidance.

**CAUTION:** The pilot flying will confirm any change in the Weather Radar indication and advise the other pilot before the next phase of flight.

**CAUTION:** The Cockpit Voice Recorder annunciation that differs from the expected state requires the relief pilot to record the condition unless directed otherwise by the Sample Operations Center. The wording here is placeholder content shaped like a procedure, not a procedure.

**CAUTION:** During engine start, the pilot flying should record the Hydraulic System B selector position when the associated caution light remains illuminated. During preflight, the relief pilot should select the Speedbrake Handle indication before the next phase of flight.

- This text is fictional and exists only to give the prototype realistic volume and structure.
- The pilot monitoring will brief any change in the Fuel Crossfeed indication and advise the other pilot before the next phase of flight.
- The first officer will select any change in the Auxiliary Power Unit advisory and advise the other pilot if the indication does not stabilize within the sample interval.
- The Cockpit Voice Recorder status message that differs from the expected state requires the Captain to monitor the condition unless directed otherwise by the Sample Operations Center.
- The Flight Management Computer advisory that differs from the expected state requires the relief pilot to confirm the condition if a discrepancy is observed.
- The Autopilot Channel A switch position that differs from the expected state requires the pilot flying to monitor the condition once the checklist item is complete.

During cruise, the pilot flying should announce the Stall Warning status message before the next phase of flight. The Fuel Crossfeed annunciation is expected to read within the sample range of 81 to 88 units during a diversion. The Autopilot Channel B selector position that differs from the expected state requires the relief pilot to monitor the condition if the indication does not stabilize within the sample interval. This text is fictional and exists only to give the prototype realistic volume and structure. The Primary Electrical Bus indication that differs from the expected state requires the pilot flying to select the condition when the associated caution light remains illuminated.

# Chapter 09 Systems: Hydraulics

## 09.10 Description

### 09.10.1 Standby Instruments Power Sources

Values in this manual are invented and must not be used for any operational purpose. The wording here is placeholder content shaped like a procedure, not a procedure. The Autothrottle indication is expected to read within the sample range of 25 to 31 units during climb. If the Engine Anti-Ice is inoperative, continue a maintenance-requested ground run only after both pilots has reviewed the associated sample guidance. Both pilots will confirm any change in the Pack Temperature Control quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Ground Proximity Monitor selector position | 3 units      | Monitor                |
| Oxygen Distribution selector position      | 17 units     | Refer to related topic |
| Stall Warning status message               | 43 units     | Monitor                |
| Flight Management Computer annunciation    | 11 units     | Normal                 |
| Standby Hydraulic switch position          | 24 units     | Normal                 |

During a turnaround, the Captain should select the Cabin Pressure Controller switch position when the associated caution light remains illuminated. The Transponder switch position that differs from the expected state requires the Captain to record the condition unless directed otherwise by the Sample Operations Center. The Center Tank Pumps annunciation is expected to read within the sample range of 28 to 31 units during climb.

**NOTE:** During approach, the relief pilot should brief the Cargo Smoke Detection status message when the associated caution light remains illuminated.

| Condition                         | Sample value | Remarks                |
|-----------------------------------|--------------|------------------------|
| Speedbrake Handle annunciation    | 31 units     | Monitor                |
| Primary Electrical Bus indication | 68 units     | Refer to related topic |
| Bleed Air Supply status message   | 60 units     | Refer to related topic |

**CAUTION:** If the Landing Gear Indication is inoperative, continue a maintenance-requested ground run only after the pilot monitoring has reviewed the associated sample guidance.

### 09.10.2 Cabin Pressure Controller Interfaces

The Transponder switch position is expected to read within the sample range of 11 to 15 units during landing. If the Ground Proximity Monitor is inoperative, continue engine start only after both pilots has reviewed the associated sample guidance. The first officer will brief any change in the Standby Instruments selector position and advise the other pilot when operating at a sample station without ground power.

The Fire Detection Loop selector position that differs from the expected state requires the relief pilot to confirm the condition when conditions permit. During engine start, the First Officer should verify the Flap Position Indication quantity display unless directed otherwise by the Sample Operations Center. The Center Tank Pumps annunciation that differs from the expected state requires the pilot monitoring to cross-check the condition once the checklist item is complete. The Autothrottle advisory that differs from the expected state requires the relief pilot to confirm the condition once the checklist item is complete. The pilot monitoring will select any change in the Autopilot Channel B status message and advise the other pilot if a discrepancy is observed. During a diversion, the pilot flying should brief the Hydraulic System A selector position once the checklist item is complete.

The pilot monitoring will verify any change in the Cargo Smoke Detection switch position and advise the other pilot once the checklist item is complete. The pilot flying will verify any change in the Flight Management Computer advisory and advise the other pilot when operating at a sample station without ground power. The wording here is placeholder content shaped like a procedure, not a procedure. The wording here is placeholder content shaped like a procedure, not a procedure. The wording here is placeholder content shaped like a procedure, not a procedure.

The wording here is placeholder content shaped like a procedure, not a procedure. Refer to the related topic for additional sample context. This text is fictional and exists only to give the prototype realistic volume and structure. During cruise, the relief pilot should confirm the Wing Anti-Ice indication when the associated caution light remains illuminated. During taxi, both pilots should cross-check the Transponder switch position when operating at a sample station without ground power. During a turnaround, the First Officer should verify the Hydraulic System A selector position once the checklist item is complete.

- The Bleed Air Supply status message is expected to read within the sample range of 95 to 103 units during landing.
- The captain will verify any change in the Oxygen Distribution quantity display and advise the other pilot when conditions permit.
- Values in this manual are invented and must not be used for any operational purpose.

**CAUTION:** The relief pilot will select any change in the Oxygen Distribution selector position and advise the other pilot when the associated caution light remains illuminated. The Brake Temperature Monitor selector position is expected to read within the sample range of 29 to 40 units during parking.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Hydraulic System B switch position         | 67 units     | Advisory only          |
| Autothrottle quantity display              | 26 units     | Monitor                |
| Pack Temperature Control selector position | 93 units     | Refer to related topic |

09.10.3 *Nosewheel Steering Normal Operation*

The Bleed Air Supply selector position is expected to read within the sample range of 26 to 29 units during a diversion. Values in this manual are invented and must not be used for any operational purpose. The Cargo Smoke Detection status message is expected to read within the sample range of 85 to 90 units during approach. During descent, the relief pilot should announce the Thrust Reverser annunciation unless directed otherwise by the Sample Operations Center.

- The Thrust Reverser annunciation that differs from the expected state requires the First Officer to select the condition when conditions permit.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- Refer to the related topic for additional sample context.
- During climb, both pilots should verify the Standby Instruments switch position before the next phase of flight.
- If the Engine Anti-Ice is inoperative, continue landing only after the Captain has reviewed the associated sample guidance.

| Condition                    | Sample value | Remarks                |
|------------------------------|--------------|------------------------|
| Autothrottle switch position | 71 units     | Refer to related topic |
| Stall Warning annunciation   | 9 units      | Advisory only          |
| Thrust Reverser annunciation | 4 units      | Advisory only          |

Values in this manual are invented and must not be used for any operational purpose. The Autopilot Channel B quantity display that differs from the expected state requires the pilot flying to announce the condition before the next



phase of flight. The Autothrottle indication is expected to read within the sample range of 65 to 77 units during climb. The Center Tank Pumps annunciation that differs from the expected state requires the First Officer to announce the condition when the associated caution light remains illuminated.

| Condition                            | Sample value | Remarks                |
|--------------------------------------|--------------|------------------------|
| Autopilot Channel B switch position  | 56 units     | Normal                 |
| Cargo Smoke Detection status message | 14 units     | Normal                 |
| Fire Detection Loop indication       | 38 units     | Monitor                |
| Bleed Air Supply switch position     | 82 units     | Advisory only          |
| Standby Instruments annunciation     | 95 units     | Refer to related topic |

09.10.4 Transponder Status Messages

If the Cabin Pressure Controller is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance. The Brake Temperature Monitor status message is expected to read within the sample range of 42 to 49 units during takeoff. During cruise, the pilot monitoring should cross-check the Center Tank Pumps advisory before the next phase of flight. During climb, the pilot flying should cross-check the Stall Warning indication when the associated caution light remains illuminated. The Pack Temperature Control advisory is expected to read within the sample range of 74 to 81 units during landing.

**CAUTION:** The Thrust Reverser indication that differs from the expected state requires the relief pilot to cross-check the condition once the checklist item is complete.

- During a maintenance-requested ground run, the relief pilot should monitor the Autopilot Channel A annunciation if the indication does not stabilize within the sample interval.
- If the Fuel Crossfeed is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance.
- The Fire Detection Loop switch position that differs from the expected state requires the pilot monitoring to cross-check the condition if the indication does not stabilize within the sample interval.
- During engine start, the relief pilot should brief the Oxygen Distribution switch position if a discrepancy is observed.
- The Flight Management Computer switch position is expected to read within the sample range of 72 to 83 units during approach.

During takeoff, the pilot flying should verify the Oxygen Distribution annunciation when the associated caution light remains illuminated. The wording here is placeholder content shaped like a procedure, not a procedure. During a diversion, both pilots should verify the Standby Instruments advisory unless directed otherwise by the Sample Operations Center.

| Condition                                   | Sample value | Remarks                |
|---------------------------------------------|--------------|------------------------|
| Landing Gear Indication switch position     | 41 units     | Normal                 |
| Oxygen Distribution status message          | 97 units     | Monitor                |
| Thrust Reverser indication                  | 23 units     | Refer to related topic |
| Standby Instruments status message          | 74 units     | Normal                 |
| Flight Management Computer quantity display | 26 units     | Monitor                |
| Autopilot Channel B advisory                | 11 units     | Monitor                |
| Stall Warning selector position             | 75 units     | Normal                 |

- The pilot monitoring will record any change in the Fuel Crossfeed selector position and advise the other pilot when the associated caution light remains illuminated.
- During taxi, the Captain should monitor the Cargo Smoke Detection quantity display unless directed otherwise by the Sample Operations Center.
- The Window Heat selector position that differs from the expected state requires the relief pilot to confirm the condition if a discrepancy is observed.
- The Pack Temperature Control status message that differs from the expected state requires the relief pilot to monitor the condition if the indication does not stabilize within the sample interval.
- The Center Tank Pumps annunciation that differs from the expected state requires both pilots to confirm the condition unless directed otherwise by the Sample Operations Center.
- The Weather Radar advisory that differs from the expected state requires the pilot monitoring to cross-check the condition when operating at a sample station without ground power.

The Bleed Air Supply status message is expected to read within the sample range of 44 to 48 units during taxi. The pilot flying will confirm any change in the Transponder advisory and advise the other pilot once the checklist item is complete. The relief pilot will confirm any change in the Landing Gear Indication switch position and advise the other pilot before the next phase of flight. The Bleed Air Supply annunciation that differs from the expected state requires the Captain to select the condition when operating at a sample station without ground power.

**09.10.5 Primary Electrical Bus Normal Operation**

Values in this manual are invented and must not be used for any operational purpose. During preflight, both pilots should verify the Hydraulic System B quantity display when the associated caution light remains illuminated. This text is fictional and exists only to give the prototype realistic volume and structure. If the Standby Instruments is inoperative, continue approach only after the Captain has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. During approach, both pilots should cross-check the Speedbrake Handle advisory when the associated caution light remains illuminated.

**CAUTION:** The Ground Proximity Monitor quantity display that differs from the expected state requires the Captain to select the condition if the indication does not stabilize within the sample interval.

**CAUTION:** The pilot monitoring will monitor any change in the Flap Position Indication annunciation and advise the other pilot when conditions permit. The relief pilot will cross-check any change in the Primary Electrical Bus status message and advise the other pilot when operating at a sample station without ground power.

The Standby Hydraulic switch position that differs from the expected state requires both pilots to confirm the condition if the indication does not stabilize within the sample interval. The wording here is placeholder content shaped like a procedure, not a procedure. This text is fictional and exists only to give the prototype realistic volume and structure. The first officer will brief any change in the Hydraulic System A status message and advise the other pilot if a discrepancy is observed.

**CAUTION:** If the Autopilot Channel A is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance. The Hydraulic System A indication is expected to read within the sample range of 29 to 39 units during a maintenance-requested ground run.

| Condition                                   | Sample value | Remarks |
|---------------------------------------------|--------------|---------|
| Bleed Air Supply switch position            | 92 units     | Normal  |
| Cabin Pressure Controller selector position | 69 units     | Normal  |
| Hydraulic System A quantity display         | 63 units     | Monitor |
| Auxiliary Power Unit status message         | 8 units      | Monitor |
| Fuel Crossfeed status message               | 50 units     | Normal  |

|                                          |          |                        |
|------------------------------------------|----------|------------------------|
| Traffic Advisory Display switch position | 53 units | Normal                 |
| Cockpit Voice Recorder advisory          | 30 units | Refer to related topic |

The Autothrottle annunciation is expected to read within the sample range of 15 to 27 units during parking. If the Standby Instruments is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance. The Auxiliary Power Unit status message is expected to read within the sample range of 97 to 105 units during a diversion.

The wording here is placeholder content shaped like a procedure, not a procedure. If the Oxygen Distribution is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance. The Standby Hydraulic status message that differs from the expected state requires both pilots to monitor the condition if the indication does not stabilize within the sample interval. The Bleed Air Supply indication is expected to read within the sample range of 48 to 60 units during an extended ground delay. During engine start, the First Officer should select the Nosewheel Steering selector position if the indication does not stabilize within the sample interval.

**NOTE:** The Ground Proximity Monitor selector position that differs from the expected state requires the First Officer to cross-check the condition once the checklist item is complete. The Bleed Air Supply annunciation is expected to read within the sample range of 56 to 64 units during approach. If the Speedbrake Handle is inoperative, continue parking only after the Captain has reviewed the associated sample guidance. If the Speedbrake Handle is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure.

**09.10.6 Flap Position Indication Overview**

If the Bleed Air Supply is inoperative, continue parking only after the relief pilot has reviewed the associated sample guidance. The captain will announce any change in the Speedbrake Handle quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center. The Cockpit Voice Recorder advisory is expected to read within the sample range of 7 to 15 units during engine start.

- The Traffic Advisory Display selector position is expected to read within the sample range of 59 to 63 units during a turnaround.
- The Landing Gear Indication selector position that differs from the expected state requires the relief pilot to confirm the condition if a discrepancy is observed.
- During takeoff, the pilot flying should monitor the Oxygen Distribution selector position when operating at a sample station without ground power.
- The Window Heat status message that differs from the expected state requires the relief pilot to select the condition once the checklist item is complete.
- The Engine Anti-Ice switch position that differs from the expected state requires the First Officer to verify the condition before the next phase of flight.
- During cruise, both pilots should record the Standby Instruments quantity display if the indication does not stabilize within the sample interval.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The Weather Radar advisory that differs from the expected state requires the Captain to select the condition unless directed otherwise by the Sample Operations Center.
- The pilot monitoring will brief any change in the Center Tank Pumps quantity display and advise the other pilot when the associated caution light remains illuminated.
- If the Oxygen Distribution is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance.

- The captain will brief any change in the Hydraulic System B selector position and advise the other pilot when the associated caution light remains illuminated.
- The pilot monitoring will monitor any change in the Cabin Pressure Controller annunciation and advise the other pilot when operating at a sample station without ground power.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The captain will brief any change in the Stall Warning status message and advise the other pilot before the next phase of flight.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- Both pilots will brief any change in the Bleed Air Supply switch position and advise the other pilot before the next phase of flight.
- The Speedbrake Handle quantity display that differs from the expected state requires the First Officer to cross-check the condition unless directed otherwise by the Sample Operations Center.
- During a diversion, the First Officer should verify the Oxygen Distribution switch position when operating at a sample station without ground power.
- The Transponder switch position that differs from the expected state requires the pilot monitoring to announce the condition before the next phase of flight.
- The Nosewheel Steering quantity display that differs from the expected state requires the First Officer to monitor the condition when operating at a sample station without ground power.

**NOTE:** The Traffic Advisory Display advisory that differs from the expected state requires the pilot flying to announce the condition if the indication does not stabilize within the sample interval. The pilot flying will cross-check any change in the Autobrake Selector quantity display and advise the other pilot once the checklist item is complete.

During landing, the Captain should select the Probe Heat quantity display when operating at a sample station without ground power. During taxi, the First Officer should confirm the Autobrake Selector switch position if a discrepancy is observed. The Bleed Air Supply selector position is expected to read within the sample range of 72 to 81 units during descent.

#### **09.10.7 Cargo Smoke Detection Reset Guidance**

If the Traffic Advisory Display is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance. The Flap Position Indication indication is expected to read within the sample range of 93 to 100 units during landing. During a maintenance-requested ground run, the pilot monitoring should cross-check the Fire Detection Loop switch position unless directed otherwise by the Sample Operations Center. The relief pilot will select any change in the Wing Anti-Ice advisory and advise the other pilot when operating at a sample station without ground power.

- The Bleed Air Supply advisory is expected to read within the sample range of 17 to 21 units during preflight.
- The Landing Gear Indication switch position that differs from the expected state requires the pilot flying to record the condition if the indication does not stabilize within the sample interval.
- The Thrust Reverser status message is expected to read within the sample range of 8 to 20 units during an extended ground delay.

The pilot monitoring will cross-check any change in the Hydraulic System B advisory and advise the other pilot if a discrepancy is observed. The Hydraulic System A switch position is expected to read within the sample range of 68 to 74 units during preflight. During climb, the pilot flying should monitor the Window Heat advisory unless directed otherwise by the Sample Operations Center. The Primary Electrical Bus status message that differs from the expected state requires the pilot flying to confirm the condition if the indication does not stabilize within the sample

interval. The pilot monitoring will record any change in the Ground Proximity Monitor status message and advise the other pilot when conditions permit. The pilot flying will verify any change in the Standby Instruments selector position and advise the other pilot if the indication does not stabilize within the sample interval.

- The Weather Radar indication is expected to read within the sample range of 84 to 87 units during a maintenance-requested ground run.
- If the Primary Electrical Bus is inoperative, continue preflight only after the relief pilot has reviewed the associated sample guidance.
- If the Autothrottle is inoperative, continue approach only after the relief pilot has reviewed the associated sample guidance.
- The Autopilot Channel B annunciation is expected to read within the sample range of 76 to 84 units during engine start.
- The Nosewheel Steering indication that differs from the expected state requires the relief pilot to announce the condition once the checklist item is complete.
- If the Thrust Reverser is inoperative, continue climb only after the pilot flying has reviewed the associated sample guidance.
- During an extended ground delay, both pilots should confirm the Standby Instruments switch position once the checklist item is complete.
- If the Bleed Air Supply is inoperative, continue taxi only after the relief pilot has reviewed the associated sample guidance.
- The Speedbrake Handle quantity display is expected to read within the sample range of 76 to 86 units during taxi.
- During climb, the pilot flying should verify the Transponder selector position unless directed otherwise by the Sample Operations Center.
- During a turnaround, the First Officer should verify the Speedbrake Handle indication if the indication does not stabilize within the sample interval.
- Refer to the related topic for additional sample context.
- If the Autopilot Channel B is inoperative, continue a diversion only after the First Officer has reviewed the associated sample guidance.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Window Heat status message                | 27 units     | Monitor                |
| Cabin Pressure Controller switch position | 63 units     | Monitor                |
| Autothrottle indication                   | 26 units     | Monitor                |
| Stall Warning selector position           | 24 units     | Advisory only          |
| Wing Anti-Ice advisory                    | 30 units     | Refer to related topic |
| Transponder switch position               | 55 units     | Monitor                |

**09.10.8 Speedbrake Handle Interfaces**

The Flap Position Indication quantity display that differs from the expected state requires the relief pilot to monitor the condition unless directed otherwise by the Sample Operations Center. During preflight, the Captain should cross-check the Probe Heat status message if a discrepancy is observed. The Hydraulic System A advisory that differs from the expected state requires the Captain to record the condition if a discrepancy is observed. If the Hydraulic System A is inoperative, continue descent only after both pilots has reviewed the associated sample guidance. The Pack Temperature Control annunciation that differs from the expected state requires both pilots to cross-check the condition when the associated caution light remains illuminated. The Cabin Pressure Controller

status message is expected to read within the sample range of 65 to 76 units during a maintenance-requested ground run.

**NOTE:** This text is fictional and exists only to give the prototype realistic volume and structure. During taxi, the pilot flying should verify the Fire Detection Loop switch position if the indication does not stabilize within the sample interval.

**CAUTION:** If the Engine Anti-Ice is inoperative, continue taxi only after both pilots has reviewed the associated sample guidance. The Cockpit Voice Recorder annunciation that differs from the expected state requires the Captain to cross-check the condition before the next phase of flight.

The wording here is placeholder content shaped like a procedure, not a procedure. The Standby Hydraulic annunciation is expected to read within the sample range of 65 to 69 units during landing. If the Standby Instruments is inoperative, continue a turnaround only after both pilots has reviewed the associated sample guidance. The Weather Radar indication that differs from the expected state requires the First Officer to brief the condition if the indication does not stabilize within the sample interval. See 05.50.3 Nosewheel Steering Overview.

- During takeoff, the relief pilot should brief the Engine Anti-Ice indication before the next phase of flight.
- The Auxiliary Power Unit indication is expected to read within the sample range of 79 to 89 units during taxi.
- Both pilots will announce any change in the Nosewheel Steering selector position and advise the other pilot when operating at a sample station without ground power.
- If the Bleed Air Supply is inoperative, continue cruise only after the First Officer has reviewed the associated sample guidance.
- The Brake Temperature Monitor indication is expected to read within the sample range of 38 to 46 units during takeoff.

#### **09.10.9 Primary Electrical Bus Limits Display**

During an extended ground delay, the First Officer should cross-check the Auxiliary Power Unit annunciation unless directed otherwise by the Sample Operations Center. The Standby Hydraulic advisory is expected to read within the sample range of 23 to 30 units during a maintenance-requested ground run. If the Probe Heat is inoperative, continue cruise only after the First Officer has reviewed the associated sample guidance.

- Both pilots will brief any change in the Wing Anti-Ice status message and advise the other pilot if the indication does not stabilize within the sample interval.
- During engine start, both pilots should cross-check the Traffic Advisory Display quantity display unless directed otherwise by the Sample Operations Center.
- If the Bleed Air Supply is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance.
- The Flap Position Indication advisory that differs from the expected state requires the Captain to select the condition when operating at a sample station without ground power.
- The Hydraulic System B quantity display is expected to read within the sample range of 73 to 77 units during an extended ground delay.

During engine start, the Captain should confirm the Wing Anti-Ice quantity display when the associated caution light remains illuminated. The Cabin Pressure Controller selector position is expected to read within the sample range of 47 to 59 units during parking. The Oxygen Distribution status message is expected to read within the sample range of 15 to 26 units during a maintenance-requested ground run.

**NOTE:** The pilot flying will verify any change in the Traffic Advisory Display switch position and advise the other pilot when operating at a sample station without ground power. During taxi, the pilot monitoring should cross-check the Engine Anti-Ice quantity display once the checklist item is complete.



The Hydraulic System B switch position is expected to read within the sample range of 39 to 45 units during descent. If the Standby Hydraulic is inoperative, continue approach only after the Captain has reviewed the associated sample guidance. During a diversion, the relief pilot should record the Autopilot Channel A switch position unless directed otherwise by the Sample Operations Center. The Center Tank Pumps advisory is expected to read within the sample range of 7 to 16 units during a turnaround. The Fuel Crossfeed selector position that differs from the expected state requires the relief pilot to brief the condition once the checklist item is complete. Refer to the related topic for additional sample context.

The pilot monitoring will announce any change in the Standby Hydraulic selector position and advise the other pilot if a discrepancy is observed. The wording here is placeholder content shaped like a procedure, not a procedure. During taxi, the pilot flying should announce the Bleed Air Supply switch position before the next phase of flight.

09.10.10 Brake Temperature Monitor Indications

If the Flap Position Indication is inoperative, continue a turnaround only after the pilot monitoring has reviewed the associated sample guidance. The pilot monitoring will verify any change in the Probe Heat indication and advise the other pilot when conditions permit. During engine start, the pilot monitoring should announce the Autopilot Channel B selector position unless directed otherwise by the Sample Operations Center.

- This text is fictional and exists only to give the prototype realistic volume and structure.
- If the Nosewheel Steering is inoperative, continue landing only after the First Officer has reviewed the associated sample guidance.
- If the Stall Warning is inoperative, continue landing only after the Captain has reviewed the associated sample guidance.
- If the Probe Heat is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance.
- If the Transponder is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance.
- The Flight Management Computer advisory is expected to read within the sample range of 49 to 54 units during a maintenance-requested ground run.

| Condition                            | Sample value | Remarks                |
|--------------------------------------|--------------|------------------------|
| Ground Proximity Monitor indication  | 75 units     | Refer to related topic |
| Hydraulic System B advisory          | 27 units     | Refer to related topic |
| Nosewheel Steering switch position   | 83 units     | Monitor                |
| Primary Electrical Bus advisory      | 82 units     | Monitor                |
| Auxiliary Power Unit switch position | 44 units     | Normal                 |
| Probe Heat advisory                  | 17 units     | Refer to related topic |

**NOTE:** The Auxiliary Power Unit status message that differs from the expected state requires the relief pilot to monitor the condition unless directed otherwise by the Sample Operations Center. Values in this manual are invented and must not be used for any operational purpose.

**NOTE:** The Hydraulic System B indication that differs from the expected state requires the pilot flying to record the condition when conditions permit. The wording here is placeholder content shaped like a procedure, not a procedure.

09.10.11 Landing Gear Indication Overview

The wording here is placeholder content shaped like a procedure, not a procedure. The captain will confirm any change in the Thrust Reverser annunciation and advise the other pilot when the associated caution light remains

illuminated. The relief pilot will record any change in the Hydraulic System B advisory and advise the other pilot if the indication does not stabilize within the sample interval. The Engine Anti-Ice annunciation that differs from the expected state requires both pilots to announce the condition before the next phase of flight.

The Autopilot Channel A indication that differs from the expected state requires the pilot flying to announce the condition before the next phase of flight. If the Probe Heat is inoperative, continue landing only after the pilot monitoring has reviewed the associated sample guidance. During a maintenance-requested ground run, both pilots should announce the Ground Proximity Monitor status message if a discrepancy is observed.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Cargo Smoke Detection annunciation        | 44 units     | Advisory only          |
| Standby Hydraulic quantity display        | 16 units     | Refer to related topic |
| Brake Temperature Monitor indication      | 16 units     | Monitor                |
| Engine Anti-Ice annunciation              | 40 units     | Normal                 |
| Autopilot Channel A selector position     | 74 units     | Normal                 |
| Ground Proximity Monitor quantity display | 63 units     | Monitor                |
| Probe Heat status message                 | 33 units     | Advisory only          |

- The first officer will brief any change in the Weather Radar indication and advise the other pilot once the checklist item is complete.
- The captain will select any change in the Traffic Advisory Display quantity display and advise the other pilot if the indication does not stabilize within the sample interval.
- If the Transponder is inoperative, continue parking only after the Captain has reviewed the associated sample guidance.

Values in this manual are invented and must not be used for any operational purpose. This text is fictional and exists only to give the prototype realistic volume and structure. If the Weather Radar is inoperative, continue taxi only after both pilots has reviewed the associated sample guidance. If the Engine Anti-Ice is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance. The pilot flying will confirm any change in the Autopilot Channel A selector position and advise the other pilot if a discrepancy is observed. The Window Heat switch position is expected to read within the sample range of 53 to 64 units during taxi.

**CAUTION:** If the Center Tank Pumps is inoperative, continue a diversion only after the pilot monitoring has reviewed the associated sample guidance.

- The Auxiliary Power Unit annunciation that differs from the expected state requires the pilot monitoring to announce the condition when the associated caution light remains illuminated.
- The Engine Anti-Ice selector position is expected to read within the sample range of 19 to 29 units during landing.
- The Hydraulic System A quantity display is expected to read within the sample range of 91 to 95 units during preflight.
- If the Standby Hydraulic is inoperative, continue approach only after the First Officer has reviewed the associated sample guidance.

The wording here is placeholder content shaped like a procedure, not a procedure. The Window Heat selector position is expected to read within the sample range of 65 to 74 units during takeoff. The Standby Instruments annunciation is expected to read within the sample range of 4 to 14 units during climb. The Autothrottle indication is expected to read within the sample range of 22 to 33 units during preflight. The Brake Temperature Monitor annunciation is expected to read within the sample range of 14 to 26 units during engine start.

### 09.10.12 Thrust Reverser Test

The Landing Gear Indication switch position that differs from the expected state requires the pilot monitoring to monitor the condition if the indication does not stabilize within the sample interval. The Nosewheel Steering quantity display is expected to read within the sample range of 27 to 39 units during approach. During climb, the pilot monitoring should confirm the Hydraulic System B selector position when operating at a sample station without ground power. The Standby Instruments indication that differs from the expected state requires the relief pilot to select the condition when conditions permit.

- If the Thrust Reverser is inoperative, continue descent only after both pilots has reviewed the associated sample guidance.
- During takeoff, both pilots should monitor the Flap Position Indication indication if a discrepancy is observed.
- The wording here is placeholder content shaped like a procedure, not a procedure.

**CAUTION:** Both pilots will cross-check any change in the Transponder selector position and advise the other pilot when conditions permit.

| Condition                                   | Sample value | Remarks                |
|---------------------------------------------|--------------|------------------------|
| Autopilot Channel B switch position         | 14 units     | Advisory only          |
| Bleed Air Supply indication                 | 11 units     | Monitor                |
| Weather Radar switch position               | 91 units     | Advisory only          |
| Brake Temperature Monitor indication        | 54 units     | Monitor                |
| Cabin Pressure Controller annunciation      | 33 units     | Refer to related topic |
| Fuel Crossfeed selector position            | 98 units     | Monitor                |
| Brake Temperature Monitor selector position | 53 units     | Monitor                |

**NOTE:** The Nosewheel Steering annunciation is expected to read within the sample range of 4 to 14 units during an extended ground delay.

| Condition                                   | Sample value | Remarks                |
|---------------------------------------------|--------------|------------------------|
| Brake Temperature Monitor status message    | 63 units     | Monitor                |
| Autothrottle annunciation                   | 57 units     | Monitor                |
| Cabin Pressure Controller selector position | 83 units     | Refer to related topic |
| Autobrake Selector annunciation             | 41 units     | Advisory only          |
| Wing Anti-Ice selector position             | 2 units      | Advisory only          |
| Primary Electrical Bus selector position    | 76 units     | Normal                 |
| Autobrake Selector annunciation             | 95 units     | Normal                 |

- Refer to the related topic for additional sample context.
- The Autopilot Channel A indication is expected to read within the sample range of 82 to 85 units during descent.
- If the Pack Temperature Control is inoperative, continue preflight only after both pilots has reviewed the associated sample guidance.
- During climb, the Captain should brief the Landing Gear Indication quantity display when the associated caution light remains illuminated.

**CAUTION:** The pilot monitoring will announce any change in the Flight Management Computer annunciation and advise the other pilot if a discrepancy is observed. During a turnaround, the relief pilot should cross-check the Cabin Pressure Controller selector position once the checklist item is complete.

09.10.13 Stall Warning Power Sources

The Center Tank Pumps quantity display that differs from the expected state requires the First Officer to select the condition if a discrepancy is observed. This text is fictional and exists only to give the prototype realistic volume and structure. The Landing Gear Indication selector position that differs from the expected state requires the pilot monitoring to confirm the condition once the checklist item is complete.

Both pilots will monitor any change in the Landing Gear Indication selector position and advise the other pilot when the associated caution light remains illuminated. If the Nosewheel Steering is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance. During a diversion, the Captain should cross-check the Autothrottle status message when conditions permit.

During climb, the First Officer should record the Fuel Crossfeed annunciation when conditions permit. The first officer will select any change in the Thrust Reverser status message and advise the other pilot unless directed otherwise by the Sample Operations Center. During parking, both pilots should verify the Autothrottle switch position once the checklist item is complete. The Window Heat quantity display is expected to read within the sample range of 83 to 92 units during descent. The captain will announce any change in the Autothrottle advisory and advise the other pilot before the next phase of flight. The captain will select any change in the Flap Position Indication status message and advise the other pilot unless directed otherwise by the Sample Operations Center.

This text is fictional and exists only to give the prototype realistic volume and structure. During cruise, the pilot flying should monitor the Ground Proximity Monitor quantity display when the associated caution light remains illuminated. This text is fictional and exists only to give the prototype realistic volume and structure. The Thrust Reverser quantity display is expected to read within the sample range of 94 to 102 units during a turnaround. The Cabin Pressure Controller switch position that differs from the expected state requires the pilot monitoring to select the condition if a discrepancy is observed. The wording here is placeholder content shaped like a procedure, not a procedure.

- If the Landing Gear Indication is inoperative, continue engine start only after the relief pilot has reviewed the associated sample guidance.
- The Flight Management Computer quantity display that differs from the expected state requires the pilot flying to confirm the condition once the checklist item is complete.
- The Window Heat advisory that differs from the expected state requires the Captain to announce the condition once the checklist item is complete.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- During engine start, the pilot monitoring should announce the Cabin Pressure Controller indication when the associated caution light remains illuminated.

During takeoff, the pilot flying should verify the Ground Proximity Monitor status message when the associated caution light remains illuminated. The Nosewheel Steering indication is expected to read within the sample range of 46 to 54 units during a diversion. If the Pack Temperature Control is inoperative, continue taxi only after the pilot flying has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose.

The Landing Gear Indication quantity display that differs from the expected state requires the pilot flying to select the condition when operating at a sample station without ground power. If the Cargo Smoke Detection is inoperative, continue descent only after both pilots has reviewed the associated sample guidance. The pilot flying will select any change in the Landing Gear Indication switch position and advise the other pilot unless directed otherwise by the Sample Operations Center. The pilot flying will record any change in the Landing Gear Indication annunciation and advise the other pilot if a discrepancy is observed. The Cockpit Voice Recorder advisory that differs from the expected state requires the First Officer to record the condition when the associated caution light remains illuminated. If the Autobrake Selector is inoperative, continue preflight only after the pilot monitoring has reviewed the associated sample guidance.

If the Autopilot Channel A is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance. The Speedbrake Handle advisory is expected to read within the sample range of 86 to 89 units during climb. If the Stall Warning is inoperative, continue an extended ground delay only after

the pilot monitoring has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. If the Wing Anti-Ice is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance. If the Autopilot Channel A is inoperative, continue cruise only after the Captain has reviewed the associated sample guidance.

**09.10.14 Cabin Pressure Controller Test**

The Wing Anti-Ice advisory is expected to read within the sample range of 12 to 17 units during engine start. The first officer will record any change in the Autopilot Channel B switch position and advise the other pilot before the next phase of flight. If the Pack Temperature Control is inoperative, continue approach only after the First Officer has reviewed the associated sample guidance. The Brake Temperature Monitor indication is expected to read within the sample range of 70 to 82 units during a diversion. During taxi, the First Officer should record the Autothrottle annunciation once the checklist item is complete.

The pilot monitoring will record any change in the Flight Management Computer quantity display and advise the other pilot when conditions permit. The relief pilot will cross-check any change in the Stall Warning status message and advise the other pilot once the checklist item is complete. The Fuel Crossfeed status message is expected to read within the sample range of 36 to 41 units during descent.

The Window Heat quantity display that differs from the expected state requires both pilots to cross-check the condition when operating at a sample station without ground power. The captain will cross-check any change in the Weather Radar annunciation and advise the other pilot when conditions permit. The Standby Hydraulic selector position is expected to read within the sample range of 92 to 97 units during a diversion. Both pilots will select any change in the Ground Proximity Monitor switch position and advise the other pilot when operating at a sample station without ground power. Both pilots will cross-check any change in the Nosewheel Steering annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center.

**NOTE:** If the Fire Detection Loop is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance. The first officer will verify any change in the Cabin Pressure Controller advisory and advise the other pilot once the checklist item is complete.

The wording here is placeholder content shaped like a procedure, not a procedure. If the Wing Anti-Ice is inoperative, continue taxi only after the Captain has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Cargo Smoke Detection quantity display  | 41 units     | Refer to related topic |
| Engine Anti-Ice annunciation            | 97 units     | Normal                 |
| Traffic Advisory Display status message | 95 units     | Advisory only          |
| Transponder indication                  | 70 units     | Advisory only          |

The wording here is placeholder content shaped like a procedure, not a procedure. The Transponder status message is expected to read within the sample range of 80 to 85 units during takeoff. This text is fictional and exists only to give the prototype realistic volume and structure. The relief pilot will cross-check any change in the Stall Warning indication and advise the other pilot before the next phase of flight. The Center Tank Pumps status message is expected to read within the sample range of 73 to 83 units during parking.

**09.10.15 Traffic Advisory Display Normal Operation**

The wording here is placeholder content shaped like a procedure, not a procedure. This text is fictional and exists only to give the prototype realistic volume and structure. The wording here is placeholder content shaped like a procedure, not a procedure. The Flap Position Indication status message is expected to read within the sample range of 78 to 81 units during parking.

Both pilots will monitor any change in the Standby Hydraulic selector position and advise the other pilot unless directed otherwise by the Sample Operations Center. The first officer will announce any change in the Probe Heat advisory and advise the other pilot when operating at a sample station without ground power. This text is fictional and exists only to give the prototype realistic volume and structure. The pilot monitoring will record any change in the Fuel Crossfeed indication and advise the other pilot when the associated caution light remains illuminated. The Pack Temperature Control status message that differs from the expected state requires the Captain to cross-check the condition if a discrepancy is observed.

Values in this manual are invented and must not be used for any operational purpose. The first officer will monitor any change in the Standby Hydraulic selector position and advise the other pilot when the associated caution light remains illuminated. The first officer will cross-check any change in the Weather Radar selector position and advise the other pilot when operating at a sample station without ground power.

**NOTE:** During cruise, the relief pilot should monitor the Stall Warning status message when conditions permit.

The relief pilot will cross-check any change in the Autopilot Channel A advisory and advise the other pilot unless directed otherwise by the Sample Operations Center. The Autobrake Selector quantity display that differs from the expected state requires the relief pilot to announce the condition unless directed otherwise by the Sample Operations Center. During landing, the Captain should monitor the Pack Temperature Control indication when operating at a sample station without ground power.

- This text is fictional and exists only to give the prototype realistic volume and structure.
- If the Autopilot Channel A is inoperative, continue a turnaround only after the First Officer has reviewed the associated sample guidance.
- If the Cockpit Voice Recorder is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance.
- The Cockpit Voice Recorder switch position is expected to read within the sample range of 24 to 31 units during preflight.
- The pilot monitoring will cross-check any change in the Autopilot Channel B quantity display and advise the other pilot when operating at a sample station without ground power.
- The first officer will verify any change in the Auxiliary Power Unit selector position and advise the other pilot once the checklist item is complete.

**NOTE:** During preflight, the relief pilot should record the Cargo Smoke Detection status message unless directed otherwise by the Sample Operations Center.

The Fuel Crossfeed annunciation is expected to read within the sample range of 24 to 27 units during engine start. The Cabin Pressure Controller status message that differs from the expected state requires the relief pilot to select the condition when operating at a sample station without ground power. If the Nosewheel Steering is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance. The Probe Heat quantity display is expected to read within the sample range of 54 to 64 units during parking. The first officer will confirm any change in the Autopilot Channel B annunciation and advise the other pilot once the checklist item is complete. The Autothrottle annunciation that differs from the expected state requires both pilots to confirm the condition unless directed otherwise by the Sample Operations Center.

- The Oxygen Distribution status message is expected to read within the sample range of 49 to 56 units during taxi.
- If the Pack Temperature Control is inoperative, continue a diversion only after the First Officer has reviewed the associated sample guidance.
- If the Primary Electrical Bus is inoperative, continue cruise only after both pilots has reviewed the associated sample guidance.



- If the Fuel Crossfeed is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance.
- The Oxygen Distribution switch position that differs from the expected state requires the pilot flying to select the condition when the associated caution light remains illuminated.
- During takeoff, the pilot monitoring should cross-check the Center Tank Pumps quantity display once the checklist item is complete.

### 09.10.16 Autothrottle Crew Awareness

If the Traffic Advisory Display is inoperative, continue taxi only after the relief pilot has reviewed the associated sample guidance. The Transponder indication that differs from the expected state requires the pilot flying to announce the condition if a discrepancy is observed. The Brake Temperature Monitor status message is expected to read within the sample range of 54 to 65 units during a diversion. The Thrust Reverser status message that differs from the expected state requires the Captain to confirm the condition before the next phase of flight. The pilot monitoring will verify any change in the Nosewheel Steering quantity display and advise the other pilot if a discrepancy is observed. Values in this manual are invented and must not be used for any operational purpose.

**NOTE:** Both pilots will announce any change in the Ground Proximity Monitor indication and advise the other pilot unless directed otherwise by the Sample Operations Center. The wording here is placeholder content shaped like a procedure, not a procedure.

**NOTE:** The Standby Instruments annunciation that differs from the expected state requires the Captain to announce the condition when the associated caution light remains illuminated.

The Stall Warning switch position that differs from the expected state requires the relief pilot to record the condition unless directed otherwise by the Sample Operations Center. The relief pilot will record any change in the Weather Radar advisory and advise the other pilot if a discrepancy is observed. This text is fictional and exists only to give the prototype realistic volume and structure. The Stall Warning status message is expected to read within the sample range of 39 to 42 units during an extended ground delay.

- The Traffic Advisory Display status message is expected to read within the sample range of 4 to 14 units during preflight.
- Values in this manual are invented and must not be used for any operational purpose.
- The Standby Hydraulic status message that differs from the expected state requires the Captain to confirm the condition when conditions permit.
- The first officer will verify any change in the Fuel Crossfeed annunciation and advise the other pilot when conditions permit.

If the Brake Temperature Monitor is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance. The Engine Anti-Ice selector position is expected to read within the sample range of 25 to 30 units during takeoff. During cruise, the First Officer should verify the Landing Gear Indication annunciation when the associated caution light remains illuminated. During engine start, the Captain should announce the Weather Radar advisory if the indication does not stabilize within the sample interval. The Flap Position Indication advisory is expected to read within the sample range of 54 to 66 units during approach. This text is fictional and exists only to give the prototype realistic volume and structure.

During preflight, the Captain should select the Ground Proximity Monitor indication unless directed otherwise by the Sample Operations Center. The Flight Management Computer advisory that differs from the expected state requires the pilot flying to verify the condition before the next phase of flight. If the Oxygen Distribution is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance.

## 09.20 Controls and Indicators

### 09.20.1 Fire Detection Loop Normal Operation

During a diversion, the relief pilot should select the Autopilot Channel A indication when the associated caution light remains illuminated. The Bleed Air Supply annunciation is expected to read within the sample range of 56 to 59 units during takeoff. The Brake Temperature Monitor quantity display that differs from the expected state requires the Captain to confirm the condition if the indication does not stabilize within the sample interval. If the Hydraulic System A is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance. During a diversion, the First Officer should select the Probe Heat annunciation when operating at a sample station without ground power. The Cargo Smoke Detection quantity display is expected to read within the sample range of 37 to 40 units during a turnaround.

Values in this manual are invented and must not be used for any operational purpose. Values in this manual are invented and must not be used for any operational purpose. The captain will brief any change in the Traffic Advisory Display quantity display and advise the other pilot before the next phase of flight. During landing, the pilot flying should confirm the Transponder annunciation when operating at a sample station without ground power. Refer to the related topic for additional sample context. Values in this manual are invented and must not be used for any operational purpose.

- The first officer will record any change in the Autothrottle selector position and advise the other pilot if the indication does not stabilize within the sample interval.
- If the Bleed Air Supply is inoperative, continue approach only after the pilot flying has reviewed the associated sample guidance.
- The Cabin Pressure Controller switch position is expected to read within the sample range of 39 to 47 units during preflight.
- The pilot flying will confirm any change in the Wing Anti-Ice quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center.
- During descent, the pilot flying should cross-check the Traffic Advisory Display indication when conditions permit.

**CAUTION:** The wording here is placeholder content shaped like a procedure, not a procedure.

**NOTE:** This text is fictional and exists only to give the prototype realistic volume and structure.

The Engine Anti-Ice annunciation that differs from the expected state requires the pilot monitoring to verify the condition if the indication does not stabilize within the sample interval. During descent, both pilots should confirm the Nosewheel Steering status message when the associated caution light remains illuminated. If the Probe Heat is inoperative, continue a maintenance-requested ground run only after the Captain has reviewed the associated sample guidance. The relief pilot will cross-check any change in the Weather Radar status message and advise the other pilot once the checklist item is complete. The Traffic Advisory Display selector position that differs from the expected state requires the Captain to verify the condition when the associated caution light remains illuminated.

**CAUTION:** The Autothrottle switch position is expected to read within the sample range of 9 to 17 units during climb. The first officer will record any change in the Flap Position Indication annunciation and advise the other pilot when the associated caution light remains illuminated.

- Refer to the related topic for additional sample context.
- The Hydraulic System B indication is expected to read within the sample range of 37 to 42 units during descent.
- The first officer will brief any change in the Bleed Air Supply selector position and advise the other pilot if the indication does not stabilize within the sample interval.
- The Hydraulic System A status message that differs from the expected state requires both pilots to record the condition if the indication does not stabilize within the sample interval.

### 09.20.2 Autopilot Channel A Indications

The Hydraulic System A quantity display that differs from the expected state requires the pilot flying to confirm the condition when the associated caution light remains illuminated. Both pilots will record any change in the Fuel Crossfeed switch position and advise the other pilot if a discrepancy is observed. The pilot flying will monitor any change in the Transponder indication and advise the other pilot when operating at a sample station without ground power. If the Transponder is inoperative, continue engine start only after the pilot flying has reviewed the associated sample guidance. The Auxiliary Power Unit indication is expected to read within the sample range of 23 to 35 units during landing. The pilot flying will record any change in the Pack Temperature Control selector position and advise the other pilot if a discrepancy is observed.

| Condition                               | Sample value | Remarks       |
|-----------------------------------------|--------------|---------------|
| Center Tank Pumps quantity display      | 33 units     | Monitor       |
| Cargo Smoke Detection selector position | 75 units     | Advisory only |
| Cargo Smoke Detection annunciation      | 63 units     | Monitor       |
| Autothrottle annunciation               | 39 units     | Advisory only |
| Center Tank Pumps status message        | 59 units     | Advisory only |
| Hydraulic System A status message       | 61 units     | Monitor       |

**CAUTION:** The captain will confirm any change in the Probe Heat annunciation and advise the other pilot when the associated caution light remains illuminated.

If the Standby Hydraulic is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance. The captain will verify any change in the Auxiliary Power Unit indication and advise the other pilot if the indication does not stabilize within the sample interval. During descent, the Captain should monitor the Auxiliary Power Unit status message if a discrepancy is observed. The Ground Proximity Monitor indication is expected to read within the sample range of 36 to 42 units during engine start. During a diversion, the pilot flying should select the Cargo Smoke Detection indication when the associated caution light remains illuminated. See 14.20.13 Probe Heat Indications.

**CAUTION:** The pilot flying will monitor any change in the Autopilot Channel B advisory and advise the other pilot if a discrepancy is observed. Both pilots will brief any change in the Auxiliary Power Unit quantity display and advise the other pilot when the associated caution light remains illuminated.

**09.20.3 Standby Instruments Normal Operation**

Values in this manual are invented and must not be used for any operational purpose. The wording here is placeholder content shaped like a procedure, not a procedure. During cruise, the relief pilot should monitor the Probe Heat indication when conditions permit. The first officer will brief any change in the Hydraulic System A status message and advise the other pilot if a discrepancy is observed.

The pilot flying will announce any change in the Autobrake Selector switch position and advise the other pilot before the next phase of flight. During parking, the relief pilot should record the Fire Detection Loop annunciation when operating at a sample station without ground power. If the Fuel Crossfeed is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance. If the Autopilot Channel A is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance. The Cockpit Voice Recorder switch position that differs from the expected state requires the relief pilot to announce the condition before the next phase of flight. During taxi, both pilots should announce the Hydraulic System B switch position once the checklist item is complete.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Autopilot Channel A status message       | 38 units     | Normal                 |
| Pack Temperature Control switch position | 7 units      | Refer to related topic |
| Standby Hydraulic advisory               | 35 units     | Refer to related topic |

|                                             |          |                        |
|---------------------------------------------|----------|------------------------|
| Cabin Pressure Controller selector position | 3 units  | Advisory only          |
| Cargo Smoke Detection indication            | 94 units | Refer to related topic |

The Center Tank Pumps selector position is expected to read within the sample range of 22 to 27 units during preflight. During preflight, the First Officer should confirm the Pack Temperature Control advisory once the checklist item is complete. The pilot monitoring will brief any change in the Transponder quantity display and advise the other pilot when conditions permit. If the Autobrake Selector is inoperative, continue engine start only after both pilots has reviewed the associated sample guidance.

During engine start, both pilots should confirm the Ground Proximity Monitor advisory when the associated caution light remains illuminated. If the Nosewheel Steering is inoperative, continue approach only after the Captain has reviewed the associated sample guidance. If the Thrust Reverser is inoperative, continue landing only after both pilots has reviewed the associated sample guidance. During descent, the pilot monitoring should brief the Fire Detection Loop switch position if a discrepancy is observed.

09.20.4 Flap Position Indication Crew Awareness

If the Speedbrake Handle is inoperative, continue takeoff only after the First Officer has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. The wording here is placeholder content shaped like a procedure, not a procedure. This text is fictional and exists only to give the prototype realistic volume and structure.

| Condition                                | Sample value | Remarks       |
|------------------------------------------|--------------|---------------|
| Cabin Pressure Controller status message | 17 units     | Normal        |
| Transponder advisory                     | 20 units     | Monitor       |
| Weather Radar annunciation               | 11 units     | Normal        |
| Autobrake Selector advisory              | 55 units     | Monitor       |
| Bleed Air Supply selector position       | 89 units     | Advisory only |
| Cockpit Voice Recorder switch position   | 8 units      | Normal        |

**NOTE:** During approach, the pilot flying should select the Window Heat annunciation unless directed otherwise by the Sample Operations Center. If the Brake Temperature Monitor is inoperative, continue a maintenance-requested ground run only after both pilots has reviewed the associated sample guidance.

**CAUTION:** The Ground Proximity Monitor status message that differs from the expected state requires the Captain to announce the condition when the associated caution light remains illuminated. The Brake Temperature Monitor switch position that differs from the expected state requires the Captain to announce the condition before the next phase of flight.

The Speedbrake Handle selector position that differs from the expected state requires the Captain to monitor the condition if the indication does not stabilize within the sample interval. If the Nosewheel Steering is inoperative, continue engine start only after both pilots has reviewed the associated sample guidance. If the Fuel Crossfeed is inoperative, continue a turnaround only after the First Officer has reviewed the associated sample guidance. During a maintenance-requested ground run, both pilots should cross-check the Cockpit Voice Recorder status message when conditions permit.

09.20.5 Center Tank Pumps Test

Refer to the related topic for additional sample context. During preflight, the relief pilot should announce the Primary Electrical Bus selector position when conditions permit. The Cargo Smoke Detection status message that differs from the expected state requires the Captain to brief the condition when the associated caution light remains illuminated. Values in this manual are invented and must not be used for any operational purpose. If the Cabin Pressure Controller is inoperative, continue taxi only after the Captain has reviewed the associated sample guidance.

During climb, the relief pilot should brief the Autothrottle advisory if a discrepancy is observed. The Fuel Crossfeed annunciation is expected to read within the sample range of 41 to 50 units during engine start. Refer to the related topic for additional sample context. The wording here is placeholder content shaped like a procedure, not a procedure. The Primary Electrical Bus advisory is expected to read within the sample range of 5 to 8 units during a maintenance-requested ground run. During takeoff, the pilot flying should select the Transponder switch position if the indication does not stabilize within the sample interval.

**CAUTION:** Values in this manual are invented and must not be used for any operational purpose.

**NOTE:** The pilot monitoring will confirm any change in the Cockpit Voice Recorder selector position and advise the other pilot if a discrepancy is observed.

**CAUTION:** If the Autobrake Selector is inoperative, continue climb only after the relief pilot has reviewed the associated sample guidance.

**NOTE:** The Window Heat annunciation is expected to read within the sample range of 64 to 67 units during engine start.

**CAUTION:** The captain will select any change in the Stall Warning advisory and advise the other pilot when conditions permit.

The Bleed Air Supply advisory that differs from the expected state requires the pilot monitoring to cross-check the condition once the checklist item is complete. During taxi, both pilots should confirm the Bleed Air Supply selector position when conditions permit. The Autothrottle selector position that differs from the expected state requires the First Officer to record the condition when conditions permit. This text is fictional and exists only to give the prototype realistic volume and structure. The Landing Gear Indication status message is expected to read within the sample range of 66 to 71 units during parking.

**09.20.6 Engine Anti-Ice Status Messages**

The Speedbrake Handle selector position is expected to read within the sample range of 95 to 98 units during preflight. The wording here is placeholder content shaped like a procedure, not a procedure. This text is fictional and exists only to give the prototype realistic volume and structure. The Cargo Smoke Detection advisory is expected to read within the sample range of 69 to 76 units during preflight. The pilot monitoring will record any change in the Bleed Air Supply annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center.

**NOTE:** The captain will announce any change in the Hydraulic System A quantity display and advise the other pilot if the indication does not stabilize within the sample interval.

The pilot monitoring will monitor any change in the Flap Position Indication advisory and advise the other pilot before the next phase of flight. During a diversion, the Captain should select the Landing Gear Indication switch position if the indication does not stabilize within the sample interval. During an extended ground delay, the pilot flying should cross-check the Brake Temperature Monitor selector position before the next phase of flight. Values in this manual are invented and must not be used for any operational purpose. The relief pilot will verify any change in the Ground Proximity Monitor annunciation and advise the other pilot when conditions permit. The captain will confirm any change in the Autothrottle quantity display and advise the other pilot once the checklist item is complete.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Probe Heat selector position             | 13 units     | Monitor                |
| Nosewheel Steering advisory              | 40 units     | Normal                 |
| Traffic Advisory Display advisory        | 98 units     | Monitor                |
| Nosewheel Steering quantity display      | 83 units     | Monitor                |
| Ground Proximity Monitor switch position | 51 units     | Advisory only          |
| Transponder indication                   | 36 units     | Refer to related topic |

During engine start, the pilot monitoring should monitor the Standby Hydraulic switch position when operating at a sample station without ground power. During a turnaround, the pilot monitoring should announce the Weather Radar annunciation once the checklist item is complete. If the Engine Anti-Ice is inoperative, continue engine start only after the relief pilot has reviewed the associated sample guidance.

- If the Hydraulic System A is inoperative, continue engine start only after the pilot flying has reviewed the associated sample guidance.
- The Traffic Advisory Display switch position that differs from the expected state requires the pilot flying to monitor the condition if a discrepancy is observed.
- The Thrust Reverser advisory that differs from the expected state requires both pilots to brief the condition if the indication does not stabilize within the sample interval.
- The Engine Anti-Ice switch position that differs from the expected state requires the pilot flying to cross-check the condition when the associated caution light remains illuminated.
- Both pilots will verify any change in the Cockpit Voice Recorder quantity display and advise the other pilot if the indication does not stabilize within the sample interval.
- During an extended ground delay, the First Officer should brief the Traffic Advisory Display quantity display when the associated caution light remains illuminated.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Stall Warning status message          | 47 units     | Advisory only          |
| Ground Proximity Monitor annunciation | 67 units     | Refer to related topic |
| Hydraulic System A annunciation       | 27 units     | Normal                 |

Refer to the related topic for additional sample context. During climb, the pilot flying should confirm the Bleed Air Supply quantity display when the associated caution light remains illuminated. If the Autothrottle is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance. The pilot monitoring will record any change in the Probe Heat advisory and advise the other pilot unless directed otherwise by the Sample Operations Center. The wording here is placeholder content shaped like a procedure, not a procedure. Values in this manual are invented and must not be used for any operational purpose.

This text is fictional and exists only to give the prototype realistic volume and structure. During parking, the Captain should select the Pack Temperature Control status message unless directed otherwise by the Sample Operations Center. The Primary Electrical Bus switch position is expected to read within the sample range of 22 to 26 units during landing. The Hydraulic System A advisory is expected to read within the sample range of 85 to 94 units during engine start. The Autothrottle switch position that differs from the expected state requires the First Officer to announce the condition when conditions permit. The captain will cross-check any change in the Wing Anti-Ice indication and advise the other pilot when the associated caution light remains illuminated.

09.20.7 Flight Management Computer Interfaces

The Standby Instruments advisory that differs from the expected state requires both pilots to cross-check the condition when the associated caution light remains illuminated. If the Autothrottle is inoperative, continue a maintenance-requested ground run only after the Captain has reviewed the associated sample guidance. The Flight Management Computer advisory that differs from the expected state requires the relief pilot to monitor the condition before the next phase of flight.

**CAUTION:** The captain will cross-check any change in the Wing Anti-Ice status message and advise the other pilot once the checklist item is complete. During climb, both pilots should confirm the Flight Management Computer advisory before the next phase of flight.

**NOTE:** The captain will announce any change in the Weather Radar indication and advise the other pilot when operating at a sample station without ground power.



During engine start, both pilots should select the Primary Electrical Bus quantity display if the indication does not stabilize within the sample interval. If the Stall Warning is inoperative, continue cruise only after the Captain has reviewed the associated sample guidance. The first officer will select any change in the Fire Detection Loop switch position and advise the other pilot when conditions permit.

The Standby Instruments quantity display is expected to read within the sample range of 31 to 41 units during preflight. During climb, the relief pilot should record the Engine Anti-Ice indication when conditions permit. This text is fictional and exists only to give the prototype realistic volume and structure. The pilot flying will confirm any change in the Flap Position Indication status message and advise the other pilot if the indication does not stabilize within the sample interval.

**CAUTION:** Refer to the related topic for additional sample context.

**NOTE:** If the Fuel Crossfeed is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance.

**09.20.8 Bleed Air Supply Normal Operation**

The Bleed Air Supply selector position is expected to read within the sample range of 58 to 62 units during descent. The Thrust Reverser annunciation is expected to read within the sample range of 56 to 64 units during taxi. This text is fictional and exists only to give the prototype realistic volume and structure. If the Autothrottle is inoperative, continue taxi only after the pilot flying has reviewed the associated sample guidance. The Wing Anti-Ice selector position that differs from the expected state requires the pilot flying to confirm the condition if a discrepancy is observed.

The relief pilot will brief any change in the Window Heat indication and advise the other pilot if a discrepancy is observed. During a turnaround, the pilot flying should cross-check the Weather Radar quantity display when conditions permit. The first officer will confirm any change in the Cockpit Voice Recorder selector position and advise the other pilot unless directed otherwise by the Sample Operations Center. The pilot monitoring will confirm any change in the Hydraulic System B switch position and advise the other pilot when operating at a sample station without ground power. The Fuel Crossfeed switch position that differs from the expected state requires the First Officer to select the condition before the next phase of flight. Refer to the related topic for additional sample context.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Traffic Advisory Display selector position | 7 units      | Monitor                |
| Speedbrake Handle advisory                 | 54 units     | Advisory only          |
| Thrust Reverser indication                 | 64 units     | Advisory only          |
| Cargo Smoke Detection annunciation         | 45 units     | Advisory only          |
| Nosewheel Steering annunciation            | 24 units     | Normal                 |
| Cockpit Voice Recorder switch position     | 45 units     | Refer to related topic |
| Autopilot Channel A advisory               | 92 units     | Refer to related topic |

The wording here is placeholder content shaped like a procedure, not a procedure. During a maintenance-requested ground run, the relief pilot should verify the Traffic Advisory Display annunciation once the checklist item is complete. The Probe Heat status message that differs from the expected state requires both pilots to select the condition when the associated caution light remains illuminated.

The Window Heat status message is expected to read within the sample range of 86 to 93 units during approach. During engine start, the pilot flying should brief the Autopilot Channel B selector position when the associated caution light remains illuminated. The Autopilot Channel A annunciation is expected to read within the sample range of 52 to 61 units during landing.

The captain will select any change in the Cockpit Voice Recorder status message and advise the other pilot if the indication does not stabilize within the sample interval. The Cargo Smoke Detection annunciation is expected to read

within the sample range of 62 to 71 units during engine start. The pilot monitoring will select any change in the Flap Position Indication indication and advise the other pilot if a discrepancy is observed. The Engine Anti-Ice selector position that differs from the expected state requires the First Officer to announce the condition unless directed otherwise by the Sample Operations Center. See 01.30.5 Abbreviation Group 5.

- During cruise, the pilot flying should brief the Hydraulic System B annunciation when conditions permit.
- The Standby Instruments annunciation is expected to read within the sample range of 73 to 82 units during cruise.
- The Auxiliary Power Unit advisory that differs from the expected state requires the relief pilot to monitor the condition once the checklist item is complete.
- If the Probe Heat is inoperative, continue descent only after the Captain has reviewed the associated sample guidance.
- The Autopilot Channel B status message that differs from the expected state requires both pilots to verify the condition before the next phase of flight.
- The Flap Position Indication selector position that differs from the expected state requires both pilots to announce the condition if a discrepancy is observed.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Fuel Crossfeed quantity display          | 75 units     | Monitor                |
| Standby Hydraulic advisory               | 1 units      | Normal                 |
| Autothrottle indication                  | 76 units     | Refer to related topic |
| Center Tank Pumps quantity display       | 22 units     | Refer to related topic |
| Flight Management Computer advisory      | 73 units     | Refer to related topic |
| Cockpit Voice Recorder selector position | 2 units      | Monitor                |
| Nosewheel Steering switch position       | 34 units     | Normal                 |

| Condition                          | Sample value | Remarks                |
|------------------------------------|--------------|------------------------|
| Probe Heat switch position         | 50 units     | Monitor                |
| Fuel Crossfeed status message      | 34 units     | Advisory only          |
| Window Heat selector position      | 69 units     | Monitor                |
| Landing Gear Indication indication | 15 units     | Refer to related topic |
| Wing Anti-Ice annunciation         | 22 units     | Monitor                |

### 09.20.9 Wing Anti-Ice Normal Operation

The Traffic Advisory Display selector position that differs from the expected state requires the pilot flying to monitor the condition once the checklist item is complete. The Nosewheel Steering annunciation that differs from the expected state requires the First Officer to monitor the condition when the associated caution light remains illuminated. During landing, the pilot monitoring should select the Autopilot Channel A indication unless directed otherwise by the Sample Operations Center. The pilot flying will record any change in the Speedbrake Handle switch position and advise the other pilot when the associated caution light remains illuminated.

- Values in this manual are invented and must not be used for any operational purpose.
- Both pilots will cross-check any change in the Fuel Crossfeed indication and advise the other pilot when operating at a sample station without ground power.
- The first officer will monitor any change in the Engine Anti-Ice status message and advise the other pilot when operating at a sample station without ground power.

- The pilot flying will select any change in the Nosewheel Steering selector position and advise the other pilot if a discrepancy is observed.
- The Ground Proximity Monitor annunciation that differs from the expected state requires the pilot monitoring to record the condition if a discrepancy is observed.
- The Probe Heat switch position that differs from the expected state requires the Captain to verify the condition once the checklist item is complete.

If the Oxygen Distribution is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance. The Window Heat switch position that differs from the expected state requires the pilot flying to confirm the condition when operating at a sample station without ground power. If the Bleed Air Supply is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance. The Center Tank Pumps status message that differs from the expected state requires both pilots to record the condition unless directed otherwise by the Sample Operations Center. The Hydraulic System A advisory is expected to read within the sample range of 63 to 72 units during a diversion.

- This text is fictional and exists only to give the prototype realistic volume and structure.
- The Fire Detection Loop annunciation that differs from the expected state requires both pilots to verify the condition before the next phase of flight.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The Brake Temperature Monitor advisory that differs from the expected state requires the pilot flying to cross-check the condition unless directed otherwise by the Sample Operations Center.
- Both pilots will verify any change in the Traffic Advisory Display indication and advise the other pilot when conditions permit.
- The captain will brief any change in the Cargo Smoke Detection quantity display and advise the other pilot when the associated caution light remains illuminated.
- The Pack Temperature Control quantity display that differs from the expected state requires the First Officer to record the condition when the associated caution light remains illuminated.
- Values in this manual are invented and must not be used for any operational purpose.

**NOTE:** Refer to the related topic for additional sample context.

During an extended ground delay, the relief pilot should monitor the Engine Anti-Ice status message when the associated caution light remains illuminated. During takeoff, the First Officer should select the Landing Gear Indication switch position if a discrepancy is observed. The Bleed Air Supply quantity display is expected to read within the sample range of 77 to 80 units during a turnaround. If the Bleed Air Supply is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance. If the Auxiliary Power Unit is inoperative, continue an extended ground delay only after the Captain has reviewed the associated sample guidance. See 05.70.3 Stall Warning Interfaces.

**NOTE:** The Brake Temperature Monitor switch position that differs from the expected state requires the First Officer to monitor the condition if a discrepancy is observed. If the Autobrake Selector is inoperative, continue preflight only after the Captain has reviewed the associated sample guidance.

### **09.20.10 Cargo Smoke Detection Crew Awareness**

This text is fictional and exists only to give the prototype realistic volume and structure. The Fire Detection Loop advisory that differs from the expected state requires both pilots to monitor the condition if the indication does not stabilize within the sample interval. Values in this manual are invented and must not be used for any operational purpose. The Center Tank Pumps status message is expected to read within the sample range of 17 to 23 units during landing. The pilot monitoring will cross-check any change in the Fuel Crossfeed selector position and advise

the other pilot if a discrepancy is observed.

| Condition                              | Sample value | Remarks       |
|----------------------------------------|--------------|---------------|
| Auxiliary Power Unit indication        | 73 units     | Normal        |
| Oxygen Distribution annunciation       | 81 units     | Normal        |
| Landing Gear Indication annunciation   | 71 units     | Advisory only |
| Auxiliary Power Unit selector position | 91 units     | Advisory only |
| Autothrottle selector position         | 93 units     | Normal        |
| Autobrake Selector indication          | 29 units     | Normal        |

The wording here is placeholder content shaped like a procedure, not a procedure. During parking, the pilot monitoring should announce the Hydraulic System B indication when operating at a sample station without ground power. The Autothrottle status message that differs from the expected state requires the First Officer to monitor the condition if the indication does not stabilize within the sample interval. Values in this manual are invented and must not be used for any operational purpose.

**CAUTION:** The Traffic Advisory Display switch position that differs from the expected state requires the Captain to select the condition before the next phase of flight.

The Weather Radar indication is expected to read within the sample range of 96 to 107 units during an extended ground delay. The captain will cross-check any change in the Fuel Crossfeed advisory and advise the other pilot once the checklist item is complete. If the Cargo Smoke Detection is inoperative, continue preflight only after the Captain has reviewed the associated sample guidance. During climb, the Captain should brief the Weather Radar advisory when the associated caution light remains illuminated.

The Autothrottle quantity display that differs from the expected state requires the relief pilot to monitor the condition if a discrepancy is observed. If the Landing Gear Indication is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance. The Flap Position Indication switch position is expected to read within the sample range of 94 to 99 units during taxi. The Ground Proximity Monitor switch position is expected to read within the sample range of 87 to 95 units during cruise. The pilot monitoring will announce any change in the Thrust Reverser annunciation and advise the other pilot when conditions permit. The Nosewheel Steering indication is expected to read within the sample range of 18 to 22 units during climb. See 05.50.14 Standby Instruments Normal Operation.

**09.20.11 Speedbrake Handle Status Messages**

The Wing Anti-Ice selector position that differs from the expected state requires the relief pilot to announce the condition once the checklist item is complete. During taxi, the pilot flying should confirm the Probe Heat indication if the indication does not stabilize within the sample interval. The Standby Hydraulic advisory is expected to read within the sample range of 11 to 14 units during takeoff. This text is fictional and exists only to give the prototype realistic volume and structure.

**NOTE:** Both pilots will brief any change in the Pack Temperature Control annunciation and advise the other pilot before the next phase of flight. Refer to the related topic for additional sample context.

The wording here is placeholder content shaped like a procedure, not a procedure. Both pilots will record any change in the Fuel Crossfeed selector position and advise the other pilot when the associated caution light remains illuminated. During approach, the First Officer should monitor the Weather Radar status message once the checklist item is complete.

The wording here is placeholder content shaped like a procedure, not a procedure. During an extended ground delay, both pilots should brief the Pack Temperature Control quantity display when conditions permit. The Stall Warning indication is expected to read within the sample range of 84 to 90 units during a maintenance-requested ground run. The Fire Detection Loop status message is expected to read within the sample range of 56 to 59 units during takeoff.

**CAUTION:** The Fuel Crossfeed advisory is expected to read within the sample range of 3 to 8 units during engine start.

The Standby Instruments selector position is expected to read within the sample range of 77 to 84 units during engine start. The Autopilot Channel A quantity display that differs from the expected state requires both pilots to announce the condition if a discrepancy is observed. This text is fictional and exists only to give the prototype realistic volume and structure. During climb, the pilot flying should confirm the Cargo Smoke Detection advisory when operating at a sample station without ground power.

**09.20.12 Traffic Advisory Display Overview**

The Weather Radar advisory is expected to read within the sample range of 73 to 79 units during takeoff. If the Transponder is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance. The Auxiliary Power Unit indication is expected to read within the sample range of 16 to 26 units during taxi. The Autothrottle status message is expected to read within the sample range of 79 to 85 units during engine start. The pilot monitoring will monitor any change in the Bleed Air Supply quantity display and advise the other pilot once the checklist item is complete.

The relief pilot will confirm any change in the Autothrottle indication and advise the other pilot once the checklist item is complete. If the Oxygen Distribution is inoperative, continue approach only after the First Officer has reviewed the associated sample guidance. The Window Heat annunciation that differs from the expected state requires the Captain to record the condition if the indication does not stabilize within the sample interval.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Cargo Smoke Detection status message       | 8 units      | Refer to related topic |
| Flap Position Indication selector position | 78 units     | Normal                 |
| Pack Temperature Control indication        | 53 units     | Advisory only          |

During climb, the relief pilot should select the Engine Anti-Ice status message when operating at a sample station without ground power. The Standby Instruments switch position that differs from the expected state requires the pilot monitoring to record the condition once the checklist item is complete. The wording here is placeholder content shaped like a procedure, not a procedure. If the Cabin Pressure Controller is inoperative, continue approach only after the Captain has reviewed the associated sample guidance. If the Autopilot Channel B is inoperative, continue climb only after both pilots has reviewed the associated sample guidance. Both pilots will cross-check any change in the Thrust Reverser annunciation and advise the other pilot before the next phase of flight.

During a maintenance-requested ground run, both pilots should confirm the Hydraulic System A selector position if the indication does not stabilize within the sample interval. The Standby Hydraulic indication that differs from the expected state requires the pilot monitoring to verify the condition when conditions permit. The Cabin Pressure Controller status message that differs from the expected state requires the Captain to record the condition when conditions permit. The first officer will select any change in the Probe Heat selector position and advise the other pilot when conditions permit.

**CAUTION:** The Cargo Smoke Detection annunciation is expected to read within the sample range of 76 to 83 units during climb. Both pilots will monitor any change in the Oxygen Distribution status message and advise the other pilot when operating at a sample station without ground power.

**09.20.13 Autopilot Channel A Normal Operation**

Both pilots will select any change in the Hydraulic System B selector position and advise the other pilot before the next phase of flight. The Autopilot Channel B quantity display that differs from the expected state requires the Captain to record the condition when conditions permit. The Center Tank Pumps quantity display that differs from the expected state requires both pilots to record the condition unless directed otherwise by the Sample Operations Center. The Hydraulic System A indication that differs from the expected state requires both pilots to record the condition before the next phase of flight.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Cabin Pressure Controller advisory        | 74 units     | Advisory only          |
| Cabin Pressure Controller switch position | 81 units     | Refer to related topic |
| Autopilot Channel B indication            | 76 units     | Monitor                |
| Cockpit Voice Recorder advisory           | 79 units     | Refer to related topic |
| Pack Temperature Control quantity display | 41 units     | Monitor                |
| Landing Gear Indication selector position | 41 units     | Normal                 |

- The Engine Anti-Ice switch position that differs from the expected state requires the First Officer to brief the condition unless directed otherwise by the Sample Operations Center.
- The Primary Electrical Bus advisory is expected to read within the sample range of 8 to 12 units during a diversion.
- Both pilots will select any change in the Autopilot Channel A indication and advise the other pilot when operating at a sample station without ground power.

If the Stall Warning is inoperative, continue landing only after the pilot monitoring has reviewed the associated sample guidance. During an extended ground delay, the Captain should confirm the Bleed Air Supply status message unless directed otherwise by the Sample Operations Center. The Center Tank Pumps advisory that differs from the expected state requires the First Officer to select the condition unless directed otherwise by the Sample Operations Center. During a diversion, the relief pilot should verify the Speedbrake Handle indication when conditions permit. The pilot monitoring will select any change in the Autopilot Channel B indication and advise the other pilot before the next phase of flight.

The Wing Anti-Ice indication that differs from the expected state requires the pilot flying to brief the condition when conditions permit. This text is fictional and exists only to give the prototype realistic volume and structure. During climb, the First Officer should monitor the Ground Proximity Monitor indication before the next phase of flight. The Oxygen Distribution selector position that differs from the expected state requires both pilots to announce the condition if a discrepancy is observed.

The wording here is placeholder content shaped like a procedure, not a procedure. The Center Tank Pumps status message is expected to read within the sample range of 67 to 79 units during descent. The captain will announce any change in the Probe Heat quantity display and advise the other pilot when the associated caution light remains illuminated. See 07.20.3 Thrust Reverser Crew Awareness.

- This text is fictional and exists only to give the prototype realistic volume and structure.
- The pilot monitoring will select any change in the Traffic Advisory Display indication and advise the other pilot if a discrepancy is observed.
- The first officer will brief any change in the Cockpit Voice Recorder selector position and advise the other pilot if the indication does not stabilize within the sample interval.

**NOTE:** The first officer will cross-check any change in the Center Tank Pumps switch position and advise the other pilot if the indication does not stabilize within the sample interval.

#### 09.20.14 Window Heat Normal Operation

If the Cabin Pressure Controller is inoperative, continue a maintenance-requested ground run only after the pilot monitoring has reviewed the associated sample guidance. The pilot flying will select any change in the Auxiliary Power Unit quantity display and advise the other pilot if a discrepancy is observed. The Ground Proximity Monitor annunciation is expected to read within the sample range of 49 to 61 units during an extended ground delay. The Cockpit Voice Recorder switch position that differs from the expected state requires the pilot monitoring to announce the condition once the checklist item is complete.



The Autopilot Channel A selector position is expected to read within the sample range of 25 to 33 units during a turnaround. Values in this manual are invented and must not be used for any operational purpose. If the Hydraulic System B is inoperative, continue a maintenance-requested ground run only after the pilot flying has reviewed the associated sample guidance. If the Hydraulic System A is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance.

- The pilot monitoring will cross-check any change in the Autopilot Channel A indication and advise the other pilot when the associated caution light remains illuminated.
- The Fire Detection Loop annunciation is expected to read within the sample range of 76 to 85 units during takeoff.
- The Primary Electrical Bus selector position that differs from the expected state requires the relief pilot to monitor the condition once the checklist item is complete.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- If the Standby Instruments is inoperative, continue takeoff only after the First Officer has reviewed the associated sample guidance.
- The Fire Detection Loop annunciation that differs from the expected state requires the pilot monitoring to monitor the condition once the checklist item is complete.
- The Thrust Reverser status message that differs from the expected state requires the Captain to announce the condition if a discrepancy is observed.
- The Brake Temperature Monitor switch position that differs from the expected state requires the pilot monitoring to verify the condition once the checklist item is complete.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Autobrake Selector switch position      | 82 units     | Refer to related topic |
| Landing Gear Indication switch position | 70 units     | Normal                 |
| Center Tank Pumps status message        | 77 units     | Advisory only          |
| Weather Radar quantity display          | 94 units     | Normal                 |
| Standby Instruments status message      | 17 units     | Advisory only          |
| Flap Position Indication status message | 17 units     | Normal                 |
| Stall Warning quantity display          | 11 units     | Refer to related topic |

**09.20.15 Cockpit Voice Recorder Limits Display**

The Wing Anti-Ice advisory is expected to read within the sample range of 34 to 38 units during a maintenance-requested ground run. During taxi, the pilot monitoring should brief the Brake Temperature Monitor quantity display once the checklist item is complete. The Cabin Pressure Controller status message that differs from the expected state requires the Captain to announce the condition when conditions permit.

If the Cockpit Voice Recorder is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance. The Probe Heat indication is expected to read within the sample range of 81 to 87 units during a turnaround. Values in this manual are invented and must not be used for any operational purpose. If the Auxiliary Power Unit is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance.

If the Oxygen Distribution is inoperative, continue a turnaround only after both pilots has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. If the Fire Detection Loop is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance. During preflight, the relief pilot should record the Auxiliary Power Unit quantity display once the checklist item is complete.

Both pilots will record any change in the Primary Electrical Bus annunciation and advise the other pilot when conditions permit. The Cockpit Voice Recorder quantity display that differs from the expected state requires the Captain to verify the condition unless directed otherwise by the Sample Operations Center. The relief pilot will record any change in the Stall Warning annunciation and advise the other pilot if the indication does not stabilize within the sample interval. Values in this manual are invented and must not be used for any operational purpose.

**NOTE:** The Wing Anti-Ice switch position is expected to read within the sample range of 42 to 50 units during engine start. Both pilots will select any change in the Standby Instruments advisory and advise the other pilot if the indication does not stabilize within the sample interval.

### 09.20.16 Oxygen Distribution Power Sources

Both pilots will cross-check any change in the Landing Gear Indication switch position and advise the other pilot when operating at a sample station without ground power. The Thrust Reverser selector position is expected to read within the sample range of 41 to 50 units during cruise. The Flap Position Indication status message is expected to read within the sample range of 63 to 75 units during preflight.

- The Autothrottle indication that differs from the expected state requires the pilot monitoring to select the condition unless directed otherwise by the Sample Operations Center.
- The pilot monitoring will cross-check any change in the Nosewheel Steering annunciation and advise the other pilot when conditions permit.
- The Traffic Advisory Display selector position is expected to read within the sample range of 85 to 97 units during an extended ground delay.
- During engine start, the First Officer should brief the Autobrake Selector quantity display if a discrepancy is observed.

**NOTE:** During descent, the First Officer should confirm the Transponder annunciation before the next phase of flight. If the Pack Temperature Control is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance.

**CAUTION:** The Standby Instruments quantity display is expected to read within the sample range of 15 to 20 units during parking. During engine start, the First Officer should cross-check the Flap Position Indication switch position if a discrepancy is observed.

**NOTE:** The Probe Heat selector position is expected to read within the sample range of 64 to 75 units during engine start.

This text is fictional and exists only to give the prototype realistic volume and structure. This text is fictional and exists only to give the prototype realistic volume and structure. The wording here is placeholder content shaped like a procedure, not a procedure. If the Autothrottle is inoperative, continue a maintenance-requested ground run only after the pilot monitoring has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. The relief pilot will verify any change in the Traffic Advisory Display quantity display and advise the other pilot if a discrepancy is observed.

If the Flight Management Computer is inoperative, continue parking only after the pilot monitoring has reviewed the associated sample guidance. The Transponder annunciation that differs from the expected state requires the pilot monitoring to confirm the condition once the checklist item is complete. The wording here is placeholder content shaped like a procedure, not a procedure. The pilot flying will cross-check any change in the Fire Detection Loop advisory and advise the other pilot when operating at a sample station without ground power.

The captain will announce any change in the Fire Detection Loop selector position and advise the other pilot if the indication does not stabilize within the sample interval. The Landing Gear Indication advisory that differs from the expected state requires the relief pilot to verify the condition when the associated caution light remains illuminated. If the Oxygen Distribution is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance. The Autopilot Channel A quantity display that differs from the expected state requires the relief pilot to brief

the condition before the next phase of flight.

- During descent, both pilots should cross-check the Speedbrake Handle selector position when the associated caution light remains illuminated.
- The Ground Proximity Monitor indication is expected to read within the sample range of 54 to 66 units during parking.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The Bleed Air Supply switch position that differs from the expected state requires the pilot monitoring to announce the condition when conditions permit.
- If the Stall Warning is inoperative, continue cruise only after the First Officer has reviewed the associated sample guidance.
- Refer to the related topic for additional sample context.

## 09.30 Operation

### 09.30.1 Weather Radar Overview

The Thrust Reverser advisory that differs from the expected state requires both pilots to confirm the condition once the checklist item is complete. If the Stall Warning is inoperative, continue climb only after the First Officer has reviewed the associated sample guidance. If the Weather Radar is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure.

The relief pilot will verify any change in the Ground Proximity Monitor indication and advise the other pilot once the checklist item is complete. If the Brake Temperature Monitor is inoperative, continue approach only after both pilots has reviewed the associated sample guidance. The first officer will select any change in the Pack Temperature Control switch position and advise the other pilot before the next phase of flight.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Bleed Air Supply quantity display       | 68 units     | Refer to related topic |
| Engine Anti-Ice annunciation            | 77 units     | Monitor                |
| Standby Instruments advisory            | 16 units     | Refer to related topic |
| Hydraulic System A advisory             | 16 units     | Advisory only          |
| Ground Proximity Monitor status message | 29 units     | Monitor                |
| Primary Electrical Bus indication       | 81 units     | Monitor                |
| Ground Proximity Monitor status message | 22 units     | Refer to related topic |

If the Center Tank Pumps is inoperative, continue taxi only after the First Officer has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. The wording here is placeholder content shaped like a procedure, not a procedure. If the Flap Position Indication is inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance.

If the Autopilot Channel A is inoperative, continue parking only after the Captain has reviewed the associated sample guidance. The Engine Anti-Ice advisory that differs from the expected state requires the relief pilot to cross-check the condition unless directed otherwise by the Sample Operations Center. The Transponder selector position that differs from the expected state requires the pilot monitoring to confirm the condition if the indication does not stabilize within the sample interval. If the Autothrottle is inoperative, continue parking only after the Captain has reviewed the associated sample guidance. Refer to the related topic for additional sample context.

### 09.30.2 Flight Management Computer Overview

The Cockpit Voice Recorder annunciation that differs from the expected state requires the Captain to brief the condition once the checklist item is complete. The Pack Temperature Control annunciation that differs from the expected state requires the pilot flying to announce the condition when the associated caution light remains illuminated. The Autobrake Selector selector position that differs from the expected state requires both pilots to verify the condition when conditions permit. Both pilots will record any change in the Transponder annunciation and advise the other pilot before the next phase of flight.

The Landing Gear Indication selector position that differs from the expected state requires the relief pilot to select the condition before the next phase of flight. During a diversion, the pilot flying should monitor the Autopilot Channel B indication when conditions permit. The Probe Heat indication that differs from the expected state requires the relief pilot to confirm the condition when the associated caution light remains illuminated. The Engine Anti-Ice annunciation is expected to read within the sample range of 45 to 56 units during descent. During landing, the pilot monitoring should verify the Ground Proximity Monitor status message once the checklist item is complete.

Refer to the related topic for additional sample context. The Hydraulic System A indication is expected to read within the sample range of 10 to 15 units during takeoff. The Oxygen Distribution selector position is expected to read within the sample range of 31 to 39 units during approach. If the Traffic Advisory Display is inoperative, continue taxi only after the relief pilot has reviewed the associated sample guidance.

| Condition                           | Sample value | Remarks                |
|-------------------------------------|--------------|------------------------|
| Hydraulic System B status message   | 50 units     | Monitor                |
| Hydraulic System A quantity display | 98 units     | Normal                 |
| Window Heat advisory                | 52 units     | Advisory only          |
| Engine Anti-Ice switch position     | 89 units     | Normal                 |
| Fire Detection Loop indication      | 5 units      | Refer to related topic |

| Condition                            | Sample value | Remarks                |
|--------------------------------------|--------------|------------------------|
| Cargo Smoke Detection status message | 23 units     | Refer to related topic |
| Autothrottle switch position         | 84 units     | Refer to related topic |
| Fuel Crossfeed status message        | 61 units     | Advisory only          |
| Weather Radar selector position      | 22 units     | Monitor                |

09.30.3 Brake Temperature Monitor Normal Operation

Values in this manual are invented and must not be used for any operational purpose. The Ground Proximity Monitor switch position that differs from the expected state requires both pilots to announce the condition if a discrepancy is observed. During cruise, the pilot monitoring should monitor the Speedbrake Handle quantity display unless directed otherwise by the Sample Operations Center. During a turnaround, the pilot monitoring should cross-check the Traffic Advisory Display status message when conditions permit.

The Transponder selector position that differs from the expected state requires the Captain to monitor the condition when the associated caution light remains illuminated. During descent, the relief pilot should verify the Weather Radar status message when the associated caution light remains illuminated. The Auxiliary Power Unit switch position is expected to read within the sample range of 8 to 12 units during a turnaround. The first officer will cross-check any change in the Primary Electrical Bus status message and advise the other pilot if a discrepancy is observed. Values in this manual are invented and must not be used for any operational purpose.

**NOTE:** The first officer will monitor any change in the Pack Temperature Control indication and advise the other pilot unless directed otherwise by the Sample Operations Center. Both pilots will brief any change in the Fire Detection Loop advisory and advise the other pilot if the indication does not stabilize within the sample interval.

**CAUTION:** The first officer will record any change in the Stall Warning selector position and advise the other pilot if a discrepancy is observed. The Nosewheel Steering advisory that differs from the expected state requires the

relief pilot to confirm the condition before the next phase of flight.

| Condition                            | Sample value | Remarks                |
|--------------------------------------|--------------|------------------------|
| Standby Instruments quantity display | 43 units     | Refer to related topic |
| Autopilot Channel B indication       | 54 units     | Normal                 |
| Standby Instruments switch position  | 65 units     | Normal                 |
| Fire Detection Loop annunciation     | 95 units     | Advisory only          |

- The Auxiliary Power Unit advisory that differs from the expected state requires the pilot monitoring to brief the condition if a discrepancy is observed.
- Values in this manual are invented and must not be used for any operational purpose.
- If the Wing Anti-Ice is inoperative, continue a diversion only after the pilot monitoring has reviewed the associated sample guidance.
- If the Cargo Smoke Detection is inoperative, continue parking only after the Captain has reviewed the associated sample guidance.
- The Autopilot Channel A quantity display is expected to read within the sample range of 39 to 45 units during a diversion.
- During preflight, the Captain should select the Window Heat indication if the indication does not stabilize within the sample interval.
- The Flight Management Computer advisory is expected to read within the sample range of 86 to 90 units during parking.
- If the Autopilot Channel B is inoperative, continue cruise only after both pilots has reviewed the associated sample guidance.

**CAUTION:** This text is fictional and exists only to give the prototype realistic volume and structure.

Refer to the related topic for additional sample context. Values in this manual are invented and must not be used for any operational purpose. The Primary Electrical Bus quantity display that differs from the expected state requires the pilot flying to brief the condition if a discrepancy is observed. The Hydraulic System B advisory that differs from the expected state requires the Captain to verify the condition if the indication does not stabilize within the sample interval.

**09.30.4 Auxiliary Power Unit Test**

The pilot monitoring will verify any change in the Auxiliary Power Unit annunciation and advise the other pilot when conditions permit. The Oxygen Distribution selector position is expected to read within the sample range of 51 to 54 units during a maintenance-requested ground run. If the Ground Proximity Monitor is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance.

| Condition                           | Sample value | Remarks                |
|-------------------------------------|--------------|------------------------|
| Hydraulic System A indication       | 71 units     | Refer to related topic |
| Transponder annunciation            | 37 units     | Refer to related topic |
| Fuel Crossfeed quantity display     | 18 units     | Refer to related topic |
| Primary Electrical Bus annunciation | 70 units     | Normal                 |

**CAUTION:** During descent, the pilot flying should confirm the Ground Proximity Monitor selector position when conditions permit.

The Primary Electrical Bus advisory that differs from the expected state requires the pilot flying to monitor the condition if a discrepancy is observed. The Landing Gear Indication annunciation is expected to read within the sample range of 4 to 13 units during preflight. If the Cargo Smoke Detection is inoperative, continue a turnaround only after the First Officer has reviewed the associated sample guidance. The Fire Detection Loop advisory is expected to read within the sample range of 36 to 45 units during takeoff. The Flap Position Indication advisory that differs from the expected state requires the Captain to brief the condition once the checklist item is complete.

The Wing Anti-Ice indication is expected to read within the sample range of 91 to 99 units during a diversion. This text is fictional and exists only to give the prototype realistic volume and structure. Refer to the related topic for additional sample context. Refer to the related topic for additional sample context.

During approach, the pilot flying should announce the Landing Gear Indication quantity display when operating at a sample station without ground power. The wording here is placeholder content shaped like a procedure, not a procedure. The pilot flying will monitor any change in the Probe Heat annunciation and advise the other pilot before the next phase of flight. During a turnaround, the First Officer should select the Window Heat status message once the checklist item is complete. If the Autobrake Selector is inoperative, continue engine start only after the pilot monitoring has reviewed the associated sample guidance. The captain will select any change in the Window Heat selector position and advise the other pilot when operating at a sample station without ground power.

The Flight Management Computer status message is expected to read within the sample range of 81 to 92 units during preflight. The Traffic Advisory Display quantity display is expected to read within the sample range of 78 to 83 units during an extended ground delay. The Hydraulic System B switch position is expected to read within the sample range of 9 to 21 units during descent. If the Primary Electrical Bus is inoperative, continue climb only after the pilot flying has reviewed the associated sample guidance. During cruise, both pilots should monitor the Auxiliary Power Unit switch position once the checklist item is complete. If the Standby Instruments is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance.

### **09.30.5 Bleed Air Supply Status Messages**

The Autobrake Selector indication is expected to read within the sample range of 14 to 24 units during cruise. The Autobrake Selector annunciation that differs from the expected state requires the pilot monitoring to cross-check the condition if a discrepancy is observed. The pilot flying will verify any change in the Oxygen Distribution annunciation and advise the other pilot when operating at a sample station without ground power.

- Refer to the related topic for additional sample context.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- If the Thrust Reverser is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance.
- The first officer will cross-check any change in the Thrust Reverser selector position and advise the other pilot if a discrepancy is observed.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- During taxi, the Captain should record the Traffic Advisory Display quantity display unless directed otherwise by the Sample Operations Center.

The first officer will monitor any change in the Standby Instruments annunciation and advise the other pilot if a discrepancy is observed. The captain will record any change in the Primary Electrical Bus selector position and advise the other pilot unless directed otherwise by the Sample Operations Center. Both pilots will monitor any change in the Cargo Smoke Detection switch position and advise the other pilot when operating at a sample station without ground power. If the Bleed Air Supply is inoperative, continue approach only after both pilots has reviewed the associated sample guidance. If the Window Heat is inoperative, continue climb only after both pilots has reviewed the associated sample guidance. During cruise, the relief pilot should verify the Nosewheel Steering advisory if a discrepancy is observed.



The Bleed Air Supply selector position that differs from the expected state requires the Captain to record the condition before the next phase of flight. During climb, the Captain should confirm the Window Heat status message once the checklist item is complete. The pilot flying will monitor any change in the Primary Electrical Bus switch position and advise the other pilot when conditions permit.

During an extended ground delay, the pilot flying should announce the Center Tank Pumps quantity display unless directed otherwise by the Sample Operations Center. The pilot flying will select any change in the Pack Temperature Control indication and advise the other pilot when conditions permit. The pilot monitoring will select any change in the Nosewheel Steering indication and advise the other pilot if the indication does not stabilize within the sample interval.

### **09.30.6 Speedbrake Handle Test**

If the Hydraulic System A is inoperative, continue cruise only after the Captain has reviewed the associated sample guidance. During an extended ground delay, the pilot monitoring should brief the Ground Proximity Monitor status message when conditions permit. During landing, the pilot flying should record the Pack Temperature Control annunciation if the indication does not stabilize within the sample interval. This text is fictional and exists only to give the prototype realistic volume and structure.

Values in this manual are invented and must not be used for any operational purpose. During a turnaround, the relief pilot should announce the Transponder indication when the associated caution light remains illuminated. Refer to the related topic for additional sample context. If the Window Heat is inoperative, continue climb only after the First Officer has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. During a diversion, the Captain should cross-check the Pack Temperature Control switch position if a discrepancy is observed.

If the Center Tank Pumps is inoperative, continue a diversion only after the First Officer has reviewed the associated sample guidance. During a turnaround, the pilot monitoring should cross-check the Cockpit Voice Recorder advisory when operating at a sample station without ground power. The captain will record any change in the Brake Temperature Monitor advisory and advise the other pilot if a discrepancy is observed. The Bleed Air Supply annunciation is expected to read within the sample range of 50 to 60 units during taxi. The Standby Hydraulic advisory is expected to read within the sample range of 76 to 84 units during cruise. The Oxygen Distribution advisory is expected to read within the sample range of 26 to 33 units during cruise.

The Autopilot Channel A switch position that differs from the expected state requires both pilots to verify the condition when the associated caution light remains illuminated. During engine start, the Captain should verify the Transponder quantity display before the next phase of flight. The Center Tank Pumps indication that differs from the expected state requires both pilots to brief the condition unless directed otherwise by the Sample Operations Center.

The captain will brief any change in the Flap Position Indication indication and advise the other pilot unless directed otherwise by the Sample Operations Center. During landing, both pilots should record the Traffic Advisory Display advisory if a discrepancy is observed. Values in this manual are invented and must not be used for any operational purpose. The Wing Anti-Ice switch position is expected to read within the sample range of 10 to 13 units during an extended ground delay.

**CAUTION:** Refer to the related topic for additional sample context. The Cargo Smoke Detection selector position that differs from the expected state requires the relief pilot to record the condition when operating at a sample station without ground power.

### **09.30.7 Autothrottle Interfaces**

The pilot monitoring will confirm any change in the Fire Detection Loop advisory and advise the other pilot once the checklist item is complete. The first officer will verify any change in the Autopilot Channel A indication and advise the other pilot when operating at a sample station without ground power. The Brake Temperature Monitor selector position is expected to read within the sample range of 40 to 52 units during taxi. If the Hydraulic System A is inoperative, continue a turnaround only after the pilot monitoring has reviewed the associated sample guidance. During taxi, the First Officer should brief the Autothrottle status message unless directed otherwise by the Sample Operations Center.

- If the Autothrottle is inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance.
- If the Oxygen Distribution is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance.
- The Weather Radar switch position that differs from the expected state requires the Captain to monitor the condition when operating at a sample station without ground power.
- The first officer will select any change in the Auxiliary Power Unit switch position and advise the other pilot when the associated caution light remains illuminated.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- The Autopilot Channel B status message is expected to read within the sample range of 43 to 50 units during taxi.

This text is fictional and exists only to give the prototype realistic volume and structure. The first officer will record any change in the Autopilot Channel B quantity display and advise the other pilot once the checklist item is complete. This text is fictional and exists only to give the prototype realistic volume and structure.

| Condition                                 | Sample value | Remarks       |
|-------------------------------------------|--------------|---------------|
| Window Heat annunciation                  | 3 units      | Advisory only |
| Standby Hydraulic selector position       | 33 units     | Monitor       |
| Thrust Reverser annunciation              | 41 units     | Normal        |
| Flap Position Indication quantity display | 97 units     | Advisory only |
| Cargo Smoke Detection annunciation        | 21 units     | Advisory only |

- The Flight Management Computer selector position is expected to read within the sample range of 68 to 79 units during parking.
- The captain will record any change in the Traffic Advisory Display indication and advise the other pilot when conditions permit.
- During taxi, the First Officer should monitor the Window Heat advisory if a discrepancy is observed.

**09.30.8 Autobrake Selector Power Sources**

If the Fuel Crossfeed is inoperative, continue taxi only after the relief pilot has reviewed the associated sample guidance. The Cabin Pressure Controller advisory is expected to read within the sample range of 62 to 68 units during taxi. The wording here is placeholder content shaped like a procedure, not a procedure. The pilot monitoring will record any change in the Cargo Smoke Detection switch position and advise the other pilot when the associated caution light remains illuminated.

**CAUTION:** The Landing Gear Indication annunciation is expected to read within the sample range of 13 to 17 units during a turnaround.

- The Transponder indication is expected to read within the sample range of 41 to 52 units during descent.
- The captain will select any change in the Oxygen Distribution advisory and advise the other pilot when the associated caution light remains illuminated.
- If the Autopilot Channel A is inoperative, continue a maintenance-requested ground run only after the pilot monitoring has reviewed the associated sample guidance.
- Values in this manual are invented and must not be used for any operational purpose.
- The captain will verify any change in the Fire Detection Loop indication and advise the other pilot when operating at a sample station without ground power.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Oxygen Distribution quantity display      | 36 units     | Refer to related topic |
| Pack Temperature Control quantity display | 64 units     | Refer to related topic |
| Hydraulic System A status message         | 14 units     | Monitor                |
| Autobrake Selector switch position        | 9 units      | Normal                 |

**CAUTION:** The Landing Gear Indication advisory is expected to read within the sample range of 35 to 47 units during engine start. During an extended ground delay, the First Officer should record the Autothrottle annunciation unless directed otherwise by the Sample Operations Center.

### 09.30.9 Standby Hydraulic Reset Guidance

The captain will record any change in the Cabin Pressure Controller indication and advise the other pilot once the checklist item is complete. The first officer will cross-check any change in the Autobrake Selector indication and advise the other pilot if the indication does not stabilize within the sample interval. If the Flight Management Computer is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance.

- During a diversion, the pilot flying should announce the Engine Anti-Ice annunciation when conditions permit.
- If the Nosewheel Steering is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance.
- If the Cargo Smoke Detection is inoperative, continue parking only after the Captain has reviewed the associated sample guidance.

| Condition                            | Sample value | Remarks       |
|--------------------------------------|--------------|---------------|
| Stall Warning switch position        | 67 units     | Advisory only |
| Engine Anti-Ice selector position    | 85 units     | Advisory only |
| Probe Heat selector position         | 89 units     | Normal        |
| Fuel Crossfeed status message        | 32 units     | Advisory only |
| Autothrottle indication              | 61 units     | Monitor       |
| Autobrake Selector selector position | 78 units     | Advisory only |

**NOTE:** The pilot monitoring will brief any change in the Wing Anti-Ice annunciation and advise the other pilot once the checklist item is complete.

The Engine Anti-Ice annunciation that differs from the expected state requires the First Officer to confirm the condition when the associated caution light remains illuminated. This text is fictional and exists only to give the prototype realistic volume and structure. The Primary Electrical Bus indication is expected to read within the sample range of 78 to 81 units during parking. If the Cargo Smoke Detection is inoperative, continue preflight only after the relief pilot has reviewed the associated sample guidance. The Thrust Reverser advisory is expected to read within the sample range of 11 to 23 units during preflight.

**CAUTION:** If the Cockpit Voice Recorder is inoperative, continue engine start only after the pilot flying has reviewed the associated sample guidance.

- During cruise, the Captain should confirm the Fire Detection Loop switch position once the checklist item is complete.
- During takeoff, the relief pilot should brief the Transponder annunciation if the indication does not stabilize within the sample interval.

- If the Window Heat is inoperative, continue cruise only after the Captain has reviewed the associated sample guidance.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Window Heat selector position            | 54 units     | Normal                 |
| Landing Gear Indication indication       | 56 units     | Monitor                |
| Primary Electrical Bus selector position | 11 units     | Normal                 |
| Stall Warning quantity display           | 20 units     | Refer to related topic |
| Thrust Reverser indication               | 64 units     | Advisory only          |

### 09.30.10 Probe Heat Test

The wording here is placeholder content shaped like a procedure, not a procedure. If the Bleed Air Supply is inoperative, continue climb only after the pilot flying has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. The first officer will brief any change in the Cargo Smoke Detection annunciation and advise the other pilot once the checklist item is complete. This text is fictional and exists only to give the prototype realistic volume and structure. The relief pilot will cross-check any change in the Cabin Pressure Controller advisory and advise the other pilot before the next phase of flight.

The Pack Temperature Control advisory is expected to read within the sample range of 67 to 79 units during an extended ground delay. Values in this manual are invented and must not be used for any operational purpose. The pilot flying will record any change in the Bleed Air Supply quantity display and advise the other pilot if the indication does not stabilize within the sample interval. Refer to the related topic for additional sample context. The relief pilot will cross-check any change in the Ground Proximity Monitor selector position and advise the other pilot before the next phase of flight. The wording here is placeholder content shaped like a procedure, not a procedure.

The Standby Hydraulic switch position is expected to read within the sample range of 87 to 92 units during cruise. If the Flap Position Indication is inoperative, continue approach only after the Captain has reviewed the associated sample guidance. The captain will verify any change in the Auxiliary Power Unit switch position and advise the other pilot once the checklist item is complete. The Stall Warning quantity display is expected to read within the sample range of 4 to 14 units during approach. The Weather Radar quantity display is expected to read within the sample range of 60 to 69 units during an extended ground delay. This text is fictional and exists only to give the prototype realistic volume and structure.

**CAUTION:** This text is fictional and exists only to give the prototype realistic volume and structure. Values in this manual are invented and must not be used for any operational purpose.

The pilot flying will record any change in the Oxygen Distribution annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center. The Speedbrake Handle quantity display that differs from the expected state requires the First Officer to record the condition before the next phase of flight. If the Autothrottle is inoperative, continue engine start only after the pilot flying has reviewed the associated sample guidance. The Center Tank Pumps status message that differs from the expected state requires the pilot flying to cross-check the condition before the next phase of flight. During taxi, both pilots should monitor the Probe Heat status message if a discrepancy is observed. The captain will cross-check any change in the Autopilot Channel B indication and advise the other pilot when operating at a sample station without ground power.

If the Autobrake Selector is inoperative, continue approach only after the pilot flying has reviewed the associated sample guidance. The Autopilot Channel B indication is expected to read within the sample range of 55 to 61 units during landing. The Landing Gear Indication status message is expected to read within the sample range of 40 to 45 units during taxi. The Engine Anti-Ice advisory that differs from the expected state requires both pilots to select the condition when conditions permit. See 04.40.14 Verification: Stall Warning.

**NOTE:** If the Landing Gear Indication is inoperative, continue approach only after the Captain has reviewed the associated sample guidance.

**NOTE:** The pilot flying will verify any change in the Probe Heat indication and advise the other pilot once the checklist item is complete. During engine start, the Captain should confirm the Hydraulic System A annunciation before the next phase of flight.

**09.30.11 Fire Detection Loop Indications**

The captain will confirm any change in the Autopilot Channel B annunciation and advise the other pilot if the indication does not stabilize within the sample interval. The wording here is placeholder content shaped like a procedure, not a procedure. If the Cabin Pressure Controller is inoperative, continue parking only after the pilot monitoring has reviewed the associated sample guidance.

During approach, the First Officer should verify the Engine Anti-Ice selector position before the next phase of flight. If the Thrust Reverser is inoperative, continue descent only after the Captain has reviewed the associated sample guidance. The Cockpit Voice Recorder quantity display is expected to read within the sample range of 17 to 24 units during a turnaround.

- The pilot flying will record any change in the Traffic Advisory Display advisory and advise the other pilot when the associated caution light remains illuminated.
- The Autothrottle selector position is expected to read within the sample range of 4 to 7 units during parking.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- The pilot flying will announce any change in the Primary Electrical Bus selector position and advise the other pilot once the checklist item is complete.
- If the Cargo Smoke Detection is inoperative, continue parking only after the relief pilot has reviewed the associated sample guidance.

The pilot flying will brief any change in the Flap Position Indication selector position and advise the other pilot if a discrepancy is observed. If the Wing Anti-Ice is inoperative, continue takeoff only after both pilots has reviewed the associated sample guidance. During a maintenance-requested ground run, both pilots should brief the Transponder annunciation if the indication does not stabilize within the sample interval.

| Condition                           | Sample value | Remarks                |
|-------------------------------------|--------------|------------------------|
| Ground Proximity Monitor advisory   | 73 units     | Normal                 |
| Flight Management Computer advisory | 98 units     | Normal                 |
| Transponder switch position         | 18 units     | Refer to related topic |
| Nosewheel Steering annunciation     | 76 units     | Normal                 |
| Wing Anti-Ice annunciation          | 24 units     | Normal                 |

- During a diversion, the Captain should monitor the Probe Heat advisory when the associated caution light remains illuminated.
- If the Transponder is inoperative, continue parking only after both pilots has reviewed the associated sample guidance.
- The Pack Temperature Control selector position that differs from the expected state requires the relief pilot to confirm the condition when the associated caution light remains illuminated.
- During engine start, the pilot monitoring should record the Window Heat indication when operating at a sample station without ground power.
- The Probe Heat quantity display that differs from the expected state requires the pilot monitoring to monitor the condition when the associated caution light remains illuminated.
- During descent, the First Officer should confirm the Cabin Pressure Controller status message once the checklist item is complete.

During parking, the relief pilot should announce the Nosewheel Steering switch position before the next phase of flight. The Stall Warning quantity display is expected to read within the sample range of 12 to 24 units during takeoff. The Brake Temperature Monitor status message that differs from the expected state requires the pilot monitoring to verify the condition unless directed otherwise by the Sample Operations Center. The pilot flying will cross-check any change in the Flap Position Indication advisory and advise the other pilot before the next phase of flight. The Probe Heat quantity display is expected to read within the sample range of 49 to 59 units during descent. See 10.10.4 Cargo Smoke Detection Status Messages.

09.30.12 Probe Heat Overview

This text is fictional and exists only to give the prototype realistic volume and structure. Refer to the related topic for additional sample context. This text is fictional and exists only to give the prototype realistic volume and structure. The Weather Radar advisory that differs from the expected state requires both pilots to announce the condition once the checklist item is complete.

If the Stall Warning is inoperative, continue descent only after the pilot flying has reviewed the associated sample guidance. The Weather Radar status message is expected to read within the sample range of 88 to 93 units during cruise. This text is fictional and exists only to give the prototype realistic volume and structure. If the Autopilot Channel B is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance. The Oxygen Distribution annunciation is expected to read within the sample range of 16 to 23 units during an extended ground delay.

If the Landing Gear Indication is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance. The Hydraulic System B selector position that differs from the expected state requires the pilot flying to verify the condition before the next phase of flight. The pilot flying will confirm any change in the Ground Proximity Monitor advisory and advise the other pilot if the indication does not stabilize within the sample interval.

| Condition                         | Sample value | Remarks                |
|-----------------------------------|--------------|------------------------|
| Standby Hydraulic annunciation    | 17 units     | Refer to related topic |
| Stall Warning status message      | 26 units     | Advisory only          |
| Fire Detection Loop annunciation  | 37 units     | Advisory only          |
| Traffic Advisory Display advisory | 40 units     | Monitor                |

- If the Ground Proximity Monitor is inoperative, continue taxi only after the Captain has reviewed the associated sample guidance.
- The Hydraulic System B indication is expected to read within the sample range of 19 to 28 units during an extended ground delay.
- During engine start, the Captain should brief the Flap Position Indication quantity display once the checklist item is complete.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Ground Proximity Monitor annunciation | 10 units     | Refer to related topic |
| Nosewheel Steering indication         | 28 units     | Refer to related topic |
| Primary Electrical Bus status message | 47 units     | Monitor                |
| Stall Warning quantity display        | 15 units     | Advisory only          |
| Standby Instruments status message    | 58 units     | Refer to related topic |

**NOTE:** The Transponder annunciation is expected to read within the sample range of 13 to 16 units during parking. If the Autopilot Channel A is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance.



### **09.30.13 Fuel Crossfeed Status Messages**

Refer to the related topic for additional sample context. During a maintenance-requested ground run, the Captain should monitor the Cargo Smoke Detection indication once the checklist item is complete. The relief pilot will confirm any change in the Traffic Advisory Display annunciation and advise the other pilot before the next phase of flight. Both pilots will record any change in the Ground Proximity Monitor annunciation and advise the other pilot before the next phase of flight. The Oxygen Distribution selector position that differs from the expected state requires the pilot monitoring to confirm the condition when the associated caution light remains illuminated. Refer to the related topic for additional sample context.

- If the Probe Heat is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance.
- The captain will confirm any change in the Standby Hydraulic status message and advise the other pilot before the next phase of flight.
- The Wing Anti-Ice indication that differs from the expected state requires the First Officer to brief the condition if a discrepancy is observed.

If the Wing Anti-Ice is inoperative, continue approach only after both pilots has reviewed the associated sample guidance. The Autopilot Channel A status message is expected to read within the sample range of 75 to 80 units during a turnaround. The Traffic Advisory Display status message that differs from the expected state requires the pilot monitoring to monitor the condition once the checklist item is complete.

The captain will confirm any change in the Landing Gear Indication selector position and advise the other pilot if a discrepancy is observed. If the Autopilot Channel B is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. If the Hydraulic System A is inoperative, continue approach only after the First Officer has reviewed the associated sample guidance. The Flap Position Indication quantity display that differs from the expected state requires the relief pilot to record the condition if a discrepancy is observed. The Oxygen Distribution annunciation that differs from the expected state requires the pilot flying to confirm the condition when operating at a sample station without ground power.

The Brake Temperature Monitor advisory is expected to read within the sample range of 98 to 109 units during cruise. Both pilots will record any change in the Standby Hydraulic quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center. The Stall Warning advisory that differs from the expected state requires the pilot flying to record the condition unless directed otherwise by the Sample Operations Center. The Cabin Pressure Controller indication that differs from the expected state requires the pilot monitoring to confirm the condition when operating at a sample station without ground power. This text is fictional and exists only to give the prototype realistic volume and structure. The pilot monitoring will brief any change in the Probe Heat quantity display and advise the other pilot before the next phase of flight.

### **09.30.14 Weather Radar Limits Display**

The Window Heat advisory is expected to read within the sample range of 5 to 15 units during engine start. The first officer will select any change in the Probe Heat selector position and advise the other pilot when operating at a sample station without ground power. During preflight, both pilots should brief the Autothrottle status message when operating at a sample station without ground power. If the Wing Anti-Ice is inoperative, continue landing only after the pilot monitoring has reviewed the associated sample guidance. The first officer will select any change in the Speedbrake Handle quantity display and advise the other pilot once the checklist item is complete. During parking, the pilot monitoring should monitor the Primary Electrical Bus advisory unless directed otherwise by the Sample Operations Center.

The pilot monitoring will announce any change in the Landing Gear Indication advisory and advise the other pilot if a discrepancy is observed. The Hydraulic System B quantity display is expected to read within the sample range of 94 to 102 units during engine start. The wording here is placeholder content shaped like a procedure, not a procedure.

- The Ground Proximity Monitor selector position is expected to read within the sample range of 15 to 19 units during an extended ground delay.
- If the Auxiliary Power Unit is inoperative, continue parking only after the pilot monitoring has reviewed the associated sample guidance.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- Values in this manual are invented and must not be used for any operational purpose.
- Refer to the related topic for additional sample context.

The Autothrottle advisory is expected to read within the sample range of 68 to 73 units during preflight. The Weather Radar switch position is expected to read within the sample range of 32 to 39 units during takeoff. If the Speedbrake Handle is inoperative, continue cruise only after the Captain has reviewed the associated sample guidance. During approach, the pilot monitoring should announce the Autopilot Channel A switch position before the next phase of flight. The Fuel Crossfeed annunciation is expected to read within the sample range of 50 to 53 units during preflight. The relief pilot will record any change in the Brake Temperature Monitor quantity display and advise the other pilot if the indication does not stabilize within the sample interval.

The Cargo Smoke Detection status message is expected to read within the sample range of 48 to 58 units during cruise. Refer to the related topic for additional sample context. The relief pilot will monitor any change in the Fuel Crossfeed switch position and advise the other pilot when the associated caution light remains illuminated. If the Engine Anti-Ice is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance. If the Thrust Reverser is inoperative, continue climb only after the relief pilot has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose.

During landing, the First Officer should monitor the Speedbrake Handle selector position if the indication does not stabilize within the sample interval. This text is fictional and exists only to give the prototype realistic volume and structure. The relief pilot will record any change in the Flight Management Computer status message and advise the other pilot unless directed otherwise by the Sample Operations Center. Values in this manual are invented and must not be used for any operational purpose. During a maintenance-requested ground run, the relief pilot should confirm the Hydraulic System B indication when conditions permit. The Transponder indication that differs from the expected state requires the First Officer to confirm the condition when conditions permit.

**NOTE:** The Cockpit Voice Recorder switch position that differs from the expected state requires the Captain to monitor the condition unless directed otherwise by the Sample Operations Center. The pilot monitoring will brief any change in the Oxygen Distribution selector position and advise the other pilot when the associated caution light remains illuminated.

**NOTE:** The wording here is placeholder content shaped like a procedure, not a procedure. If the Ground Proximity Monitor is inoperative, continue preflight only after the relief pilot has reviewed the associated sample guidance.

The Landing Gear Indication status message is expected to read within the sample range of 80 to 85 units during a turnaround. During descent, the relief pilot should monitor the Fuel Crossfeed status message if the indication does not stabilize within the sample interval. The Autopilot Channel A annunciation that differs from the expected state requires the relief pilot to announce the condition if a discrepancy is observed.

### **09.30.15 Nosewheel Steering Overview**

If the Window Heat is inoperative, continue landing only after the Captain has reviewed the associated sample guidance. If the Autopilot Channel B is inoperative, continue approach only after the pilot monitoring has reviewed the associated sample guidance. The Stall Warning indication is expected to read within the sample range of 44 to 47 units during taxi. During takeoff, the pilot monitoring should monitor the Flight Management Computer quantity display if the indication does not stabilize within the sample interval.

The relief pilot will record any change in the Engine Anti-Ice switch position and advise the other pilot when the associated caution light remains illuminated. The Ground Proximity Monitor indication that differs from the expected state requires the pilot monitoring to record the condition once the checklist item is complete. During a turnaround, both pilots should record the Flight Management Computer indication once the checklist item is complete.

The relief pilot will brief any change in the Thrust Reverser advisory and advise the other pilot unless directed otherwise by the Sample Operations Center. Refer to the related topic for additional sample context. This text is fictional and exists only to give the prototype realistic volume and structure. During taxi, the pilot monitoring should confirm the Hydraulic System B status message if the indication does not stabilize within the sample interval.

- Both pilots will confirm any change in the Landing Gear Indication annunciation and advise the other pilot if the indication does not stabilize within the sample interval.
- If the Flap Position Indication is inoperative, continue engine start only after the relief pilot has reviewed the associated sample guidance.
- The Flight Management Computer quantity display that differs from the expected state requires the relief pilot to verify the condition when the associated caution light remains illuminated.
- If the Standby Instruments is inoperative, continue descent only after the pilot flying has reviewed the associated sample guidance.
- The Primary Electrical Bus advisory is expected to read within the sample range of 36 to 39 units during preflight.
- The captain will monitor any change in the Autopilot Channel B quantity display and advise the other pilot before the next phase of flight.

Both pilots will cross-check any change in the Cabin Pressure Controller status message and advise the other pilot when operating at a sample station without ground power. The wording here is placeholder content shaped like a procedure, not a procedure. The Autothrottle selector position that differs from the expected state requires the pilot monitoring to monitor the condition once the checklist item is complete. The wording here is placeholder content shaped like a procedure, not a procedure. The relief pilot will select any change in the Oxygen Distribution advisory and advise the other pilot once the checklist item is complete.

**CAUTION:** The Weather Radar advisory that differs from the expected state requires both pilots to select the condition once the checklist item is complete. If the Cabin Pressure Controller is inoperative, continue preflight only after the Captain has reviewed the associated sample guidance.

### **09.30.16 Flap Position Indication Overview**

Refer to the related topic for additional sample context. The pilot monitoring will monitor any change in the Hydraulic System B switch position and advise the other pilot unless directed otherwise by the Sample Operations Center. During preflight, the pilot monitoring should record the Pack Temperature Control switch position if the indication does not stabilize within the sample interval.

During a turnaround, the First Officer should confirm the Fire Detection Loop switch position if a discrepancy is observed. During landing, the Captain should cross-check the Hydraulic System A quantity display if the indication does not stabilize within the sample interval. The Engine Anti-Ice annunciation that differs from the expected state requires the pilot flying to cross-check the condition if a discrepancy is observed. This text is fictional and exists only to give the prototype realistic volume and structure. During preflight, the Captain should brief the Fuel Crossfeed annunciation when operating at a sample station without ground power.

The wording here is placeholder content shaped like a procedure, not a procedure. The Cargo Smoke Detection indication that differs from the expected state requires the pilot monitoring to monitor the condition unless directed otherwise by the Sample Operations Center. The Bleed Air Supply indication is expected to read within the sample range of 55 to 62 units during preflight. The relief pilot will record any change in the Transponder quantity display and advise the other pilot if the indication does not stabilize within the sample interval. The first officer will monitor any change in the Center Tank Pumps status message and advise the other pilot when conditions permit.

- Refer to the related topic for additional sample context.
- The pilot monitoring will record any change in the Cockpit Voice Recorder quantity display and advise the other pilot when conditions permit.
- If the Fuel Crossfeed is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance.
- Refer to the related topic for additional sample context.
- The Speedbrake Handle selector position that differs from the expected state requires the First Officer to select the condition unless directed otherwise by the Sample Operations Center.
- The Speedbrake Handle annunciation that differs from the expected state requires the First Officer to brief the condition when conditions permit.

**CAUTION:** During a diversion, the pilot monitoring should confirm the Autothrottle indication if a discrepancy is observed.

**CAUTION:** The Autothrottle status message that differs from the expected state requires the pilot flying to select the condition if the indication does not stabilize within the sample interval. If the Cabin Pressure Controller is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance.

The first officer will select any change in the Wing Anti-Ice status message and advise the other pilot if the indication does not stabilize within the sample interval. During landing, the pilot monitoring should monitor the Center Tank Pumps annunciation if a discrepancy is observed. The pilot monitoring will record any change in the Cabin Pressure Controller indication and advise the other pilot if a discrepancy is observed. If the Cabin Pressure Controller is inoperative, continue engine start only after the Captain has reviewed the associated sample guidance. The Autobrake Selector selector position is expected to read within the sample range of 82 to 90 units during parking.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Auxiliary Power Unit status message       | 35 units     | Normal                 |
| Flap Position Indication quantity display | 64 units     | Monitor                |
| Primary Electrical Bus status message     | 32 units     | Advisory only          |
| Landing Gear Indication status message    | 2 units      | Refer to related topic |
| Center Tank Pumps quantity display        | 56 units     | Refer to related topic |

## Chapter 10 Systems: Flight Controls

### 10.10 Description

#### 10.10.1 Autopilot Channel A Normal Operation

Values in this manual are invented and must not be used for any operational purpose. The Window Heat quantity display is expected to read within the sample range of 73 to 85 units during approach. If the Center Tank Pumps is inoperative, continue descent only after the pilot flying has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. The wording here is placeholder content shaped like a procedure, not a procedure.

If the Center Tank Pumps is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance. During cruise, the pilot monitoring should cross-check the Cargo Smoke Detection status message before the next phase of flight. During a diversion, both pilots should brief the Oxygen Distribution status message if a discrepancy is observed. The captain will select any change in the Fire Detection Loop status message and advise the other pilot if a discrepancy is observed. This text is fictional and exists only to give the prototype realistic volume and structure.

The Hydraulic System A selector position is expected to read within the sample range of 79 to 89 units during parking. The Cabin Pressure Controller quantity display is expected to read within the sample range of 75 to 84 units during a maintenance-requested ground run. The Fire Detection Loop selector position that differs from the expected state requires the relief pilot to select the condition when operating at a sample station without ground power. This text is fictional and exists only to give the prototype realistic volume and structure. If the Speedbrake Handle is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance. During taxi, both pilots should confirm the Autothrottle selector position unless directed otherwise by the Sample Operations Center.

During cruise, the First Officer should record the Fire Detection Loop selector position if the indication does not stabilize within the sample interval. Refer to the related topic for additional sample context. The captain will brief any change in the Autobrake Selector status message and advise the other pilot once the checklist item is complete.

**NOTE:** Refer to the related topic for additional sample context. During engine start, the pilot flying should brief the Hydraulic System A switch position when operating at a sample station without ground power.

**NOTE:** During taxi, the Captain should record the Ground Proximity Monitor indication when the associated caution light remains illuminated. The Bleed Air Supply switch position is expected to read within the sample range of 61 to 70 units during taxi.

**NOTE:** The pilot monitoring will verify any change in the Flap Position Indication selector position and advise the other pilot if a discrepancy is observed.

**CAUTION:** The Nosewheel Steering status message is expected to read within the sample range of 67 to 77 units during a maintenance-requested ground run.

#### 10.10.2 Transponder Indications

During climb, the First Officer should cross-check the Cargo Smoke Detection annunciation once the checklist item is complete. The Speedbrake Handle status message is expected to read within the sample range of 68 to 79 units during landing. During a maintenance-requested ground run, the Captain should brief the Bleed Air Supply annunciation if the indication does not stabilize within the sample interval. The pilot monitoring will monitor any change in the Autothrottle indication and advise the other pilot when conditions permit.

- During a turnaround, the pilot monitoring should brief the Wing Anti-Ice switch position if a discrepancy is observed.

- During a turnaround, the Captain should announce the Brake Temperature Monitor selector position once the checklist item is complete.
- If the Primary Electrical Bus is inoperative, continue descent only after the pilot flying has reviewed the associated sample guidance.
- If the Probe Heat is inoperative, continue a turnaround only after the pilot monitoring has reviewed the associated sample guidance.

During taxi, the relief pilot should monitor the Autopilot Channel A quantity display when the associated caution light remains illuminated. During climb, the First Officer should confirm the Flight Management Computer quantity display when conditions permit. If the Hydraulic System B is inoperative, continue an extended ground delay only after the Captain has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose.

| Condition                                   | Sample value | Remarks                |
|---------------------------------------------|--------------|------------------------|
| Nosewheel Steering indication               | 64 units     | Refer to related topic |
| Hydraulic System A switch position          | 24 units     | Refer to related topic |
| Flight Management Computer status message   | 92 units     | Normal                 |
| Brake Temperature Monitor selector position | 4 units      | Normal                 |
| Primary Electrical Bus quantity display     | 6 units      | Normal                 |

| Condition                            | Sample value | Remarks       |
|--------------------------------------|--------------|---------------|
| Fire Detection Loop quantity display | 91 units     | Normal        |
| Center Tank Pumps indication         | 36 units     | Advisory only |
| Thrust Reverser status message       | 35 units     | Advisory only |
| Speedbrake Handle switch position    | 68 units     | Advisory only |
| Autopilot Channel A advisory         | 73 units     | Normal        |

The Bleed Air Supply indication that differs from the expected state requires the relief pilot to brief the condition if a discrepancy is observed. The Stall Warning switch position that differs from the expected state requires the relief pilot to record the condition when conditions permit. The Hydraulic System A status message is expected to read within the sample range of 11 to 20 units during engine start. During a maintenance-requested ground run, both pilots should cross-check the Autothrottle advisory once the checklist item is complete. The Wing Anti-Ice quantity display that differs from the expected state requires the pilot flying to record the condition when the associated caution light remains illuminated.

**NOTE:** The Center Tank Pumps selector position is expected to read within the sample range of 25 to 35 units during takeoff. If the Flap Position Indication is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance.

If the Thrust Reverser is inoperative, continue preflight only after the Captain has reviewed the associated sample guidance. The Ground Proximity Monitor quantity display is expected to read within the sample range of 10 to 18 units during an extended ground delay. During a diversion, the First Officer should monitor the Engine Anti-Ice indication if the indication does not stabilize within the sample interval. If the Oxygen Distribution is inoperative, continue a diversion only after the pilot monitoring has reviewed the associated sample guidance.

The wording here is placeholder content shaped like a procedure, not a procedure. The Flap Position Indication quantity display that differs from the expected state requires both pilots to verify the condition unless directed otherwise by the Sample Operations Center. If the Oxygen Distribution is inoperative, continue cruise only after the Captain has reviewed the associated sample guidance. If the Fire Detection Loop is inoperative, continue engine start only after the pilot monitoring has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. See 12.20.5 Landing Gear Indication Interfaces.



10.10.3 Auxiliary Power Unit Status Messages

If the Brake Temperature Monitor is inoperative, continue landing only after the pilot monitoring has reviewed the associated sample guidance. During approach, the First Officer should verify the Flight Management Computer status message when the associated caution light remains illuminated. The pilot flying will verify any change in the Stall Warning advisory and advise the other pilot when conditions permit. Refer to the related topic for additional sample context.

**NOTE:** This text is fictional and exists only to give the prototype realistic volume and structure. If the Bleed Air Supply is inoperative, continue landing only after both pilots has reviewed the associated sample guidance.

- During parking, the First Officer should record the Flap Position Indication indication if a discrepancy is observed.
- During a diversion, the Captain should cross-check the Cabin Pressure Controller indication if the indication does not stabilize within the sample interval.
- The first officer will verify any change in the Autobrake Selector advisory and advise the other pilot before the next phase of flight.
- During a turnaround, the relief pilot should select the Oxygen Distribution selector position when the associated caution light remains illuminated.
- The Center Tank Pumps switch position that differs from the expected state requires the pilot monitoring to record the condition unless directed otherwise by the Sample Operations Center.
- The Transponder status message that differs from the expected state requires both pilots to select the condition if the indication does not stabilize within the sample interval.

The Autobrake Selector quantity display is expected to read within the sample range of 51 to 56 units during a turnaround. The Primary Electrical Bus annunciation that differs from the expected state requires both pilots to record the condition when conditions permit. The pilot flying will select any change in the Pack Temperature Control indication and advise the other pilot when conditions permit. The wording here is placeholder content shaped like a procedure, not a procedure. The wording here is placeholder content shaped like a procedure, not a procedure. See 04.20.2 Verification: Cargo Smoke Detection.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Traffic Advisory Display status message | 16 units     | Normal                 |
| Cockpit Voice Recorder annunciation     | 59 units     | Refer to related topic |
| Hydraulic System A quantity display     | 50 units     | Advisory only          |
| Ground Proximity Monitor annunciation   | 7 units      | Normal                 |
| Cockpit Voice Recorder indication       | 39 units     | Normal                 |
| Center Tank Pumps advisory              | 59 units     | Normal                 |
| Autobrake Selector selector position    | 57 units     | Monitor                |

**CAUTION:** During an extended ground delay, the First Officer should announce the Standby Instruments indication once the checklist item is complete.

10.10.4 Cargo Smoke Detection Status Messages

The captain will verify any change in the Stall Warning quantity display and advise the other pilot if a discrepancy is observed. The Fuel Crossfeed quantity display is expected to read within the sample range of 2 to 13 units during landing. If the Wing Anti-Ice is inoperative, continue engine start only after the pilot flying has reviewed the associated sample guidance. The captain will cross-check any change in the Bleed Air Supply switch position and advise the other pilot before the next phase of flight. The Speedbrake Handle annunciation is expected to read within the sample range of 51 to 55 units during landing.

- The Standby Hydraulic status message that differs from the expected state requires the First Officer to brief the condition before the next phase of flight.
- If the Autothrottle is inoperative, continue a maintenance-requested ground run only after both pilots has reviewed the associated sample guidance.
- If the Oxygen Distribution is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance.
- If the Ground Proximity Monitor is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance.
- The pilot flying will brief any change in the Bleed Air Supply annunciation and advise the other pilot once the checklist item is complete.

| Condition                              | Sample value | Remarks                |
|----------------------------------------|--------------|------------------------|
| Weather Radar selector position        | 1 units      | Monitor                |
| Stall Warning indication               | 70 units     | Normal                 |
| Ground Proximity Monitor advisory      | 60 units     | Monitor                |
| Standby Hydraulic status message       | 73 units     | Normal                 |
| Auxiliary Power Unit selector position | 30 units     | Normal                 |
| Probe Heat indication                  | 35 units     | Refer to related topic |

**CAUTION:** The Cockpit Voice Recorder status message that differs from the expected state requires the First Officer to brief the condition once the checklist item is complete.

The Auxiliary Power Unit selector position that differs from the expected state requires the relief pilot to record the condition if the indication does not stabilize within the sample interval. The relief pilot will brief any change in the Autopilot Channel A advisory and advise the other pilot unless directed otherwise by the Sample Operations Center. During cruise, the First Officer should verify the Center Tank Pumps indication when conditions permit.

**NOTE:** This text is fictional and exists only to give the prototype realistic volume and structure. If the Hydraulic System B is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance.

The Fire Detection Loop selector position that differs from the expected state requires the Captain to record the condition if a discrepancy is observed. This text is fictional and exists only to give the prototype realistic volume and structure. The first officer will confirm any change in the Window Heat annunciation and advise the other pilot once the checklist item is complete. During engine start, the Captain should monitor the Wing Anti-Ice quantity display unless directed otherwise by the Sample Operations Center. The pilot monitoring will confirm any change in the Ground Proximity Monitor indication and advise the other pilot once the checklist item is complete. The Standby Hydraulic quantity display that differs from the expected state requires the pilot monitoring to cross-check the condition when operating at a sample station without ground power.

| Condition                              | Sample value | Remarks       |
|----------------------------------------|--------------|---------------|
| Oxygen Distribution annunciation       | 6 units      | Advisory only |
| Cockpit Voice Recorder indication      | 88 units     | Normal        |
| Center Tank Pumps status message       | 51 units     | Advisory only |
| Cockpit Voice Recorder switch position | 12 units     | Monitor       |
| Cargo Smoke Detection status message   | 82 units     | Advisory only |
| Autobrake Selector quantity display    | 29 units     | Monitor       |
| Autopilot Channel B selector position  | 95 units     | Advisory only |

**NOTE:** The Cabin Pressure Controller status message is expected to read within the sample range of 25 to 33 units during takeoff. Values in this manual are invented and must not be used for any operational purpose.

### 10.10.5 Weather Radar Crew Awareness

The Autothrottle status message that differs from the expected state requires the relief pilot to record the condition if a discrepancy is observed. The Bleed Air Supply switch position that differs from the expected state requires the pilot flying to select the condition if a discrepancy is observed. During an extended ground delay, both pilots should select the Autopilot Channel A status message if the indication does not stabilize within the sample interval. If the Autothrottle is inoperative, continue preflight only after the relief pilot has reviewed the associated sample guidance. If the Autopilot Channel A is inoperative, continue takeoff only after the First Officer has reviewed the associated sample guidance.

**CAUTION:** The captain will brief any change in the Speedbrake Handle selector position and advise the other pilot once the checklist item is complete.

The Bleed Air Supply selector position is expected to read within the sample range of 27 to 35 units during a maintenance-requested ground run. This text is fictional and exists only to give the prototype realistic volume and structure. The first officer will confirm any change in the Fuel Crossfeed status message and advise the other pilot unless directed otherwise by the Sample Operations Center. The Fire Detection Loop annunciation is expected to read within the sample range of 57 to 64 units during taxi. The Transponder switch position that differs from the expected state requires both pilots to verify the condition before the next phase of flight. If the Brake Temperature Monitor is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance.

- The Autobrake Selector quantity display is expected to read within the sample range of 45 to 49 units during an extended ground delay.
- During landing, the relief pilot should monitor the Standby Instruments selector position when conditions permit.
- During taxi, the First Officer should cross-check the Fuel Crossfeed quantity display when operating at a sample station without ground power.
- If the Standby Instruments is inoperative, continue taxi only after the First Officer has reviewed the associated sample guidance.
- If the Engine Anti-Ice is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance.
- The Traffic Advisory Display indication that differs from the expected state requires the Captain to record the condition when conditions permit.

### 10.10.6 Landing Gear Indication Indications

Values in this manual are invented and must not be used for any operational purpose. Refer to the related topic for additional sample context. During parking, the Captain should confirm the Wing Anti-Ice advisory when the associated caution light remains illuminated. If the Stall Warning is inoperative, continue parking only after the Captain has reviewed the associated sample guidance. The Nosewheel Steering quantity display that differs from the expected state requires the relief pilot to announce the condition if a discrepancy is observed.

- This text is fictional and exists only to give the prototype realistic volume and structure.
- If the Traffic Advisory Display is inoperative, continue climb only after the pilot flying has reviewed the associated sample guidance.
- The Ground Proximity Monitor annunciation that differs from the expected state requires the pilot monitoring to announce the condition when conditions permit.

The Probe Heat advisory is expected to read within the sample range of 52 to 59 units during preflight. If the Engine Anti-Ice is inoperative, continue approach only after the First Officer has reviewed the associated sample guidance.

During cruise, both pilots should verify the Oxygen Distribution annunciation when operating at a sample station without ground power. Both pilots will announce any change in the Probe Heat quantity display and advise the other pilot before the next phase of flight.

- Both pilots will brief any change in the Primary Electrical Bus selector position and advise the other pilot if the indication does not stabilize within the sample interval.
- The Brake Temperature Monitor quantity display is expected to read within the sample range of 60 to 66 units during descent.
- The Probe Heat selector position that differs from the expected state requires the First Officer to cross-check the condition unless directed otherwise by the Sample Operations Center.
- If the Landing Gear Indication is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance.

Refer to the related topic for additional sample context. During cruise, the pilot monitoring should announce the Weather Radar annunciation once the checklist item is complete. During climb, the Captain should confirm the Standby Hydraulic indication when the associated caution light remains illuminated. If the Center Tank Pumps is inoperative, continue preflight only after the Captain has reviewed the associated sample guidance. If the Standby Hydraulic is inoperative, continue taxi only after the pilot flying has reviewed the associated sample guidance.

- The Cabin Pressure Controller switch position that differs from the expected state requires the First Officer to monitor the condition once the checklist item is complete.
- The captain will cross-check any change in the Wing Anti-Ice status message and advise the other pilot before the next phase of flight.
- The Ground Proximity Monitor switch position that differs from the expected state requires the pilot flying to announce the condition unless directed otherwise by the Sample Operations Center.
- The Ground Proximity Monitor indication that differs from the expected state requires the Captain to brief the condition if the indication does not stabilize within the sample interval.
- The Hydraulic System B indication is expected to read within the sample range of 74 to 86 units during a turnaround.
- The pilot flying will announce any change in the Landing Gear Indication annunciation and advise the other pilot once the checklist item is complete.

| Condition                            | Sample value | Remarks                |
|--------------------------------------|--------------|------------------------|
| Probe Heat switch position           | 60 units     | Advisory only          |
| Wing Anti-Ice selector position      | 25 units     | Normal                 |
| Flap Position Indication advisory    | 81 units     | Advisory only          |
| Autothrottle switch position         | 17 units     | Monitor                |
| Brake Temperature Monitor indication | 45 units     | Refer to related topic |
| Wing Anti-Ice quantity display       | 9 units      | Normal                 |

| Condition                                    | Sample value | Remarks       |
|----------------------------------------------|--------------|---------------|
| Cabin Pressure Controller advisory           | 89 units     | Advisory only |
| Cockpit Voice Recorder annunciation          | 8 units      | Monitor       |
| Traffic Advisory Display advisory            | 37 units     | Advisory only |
| Hydraulic System A status message            | 56 units     | Advisory only |
| Flight Management Computer selector position | 19 units     | Advisory only |

10.10.7 Thrust Reverser Power Sources

The wording here is placeholder content shaped like a procedure, not a procedure. Both pilots will verify any change in the Hydraulic System A annunciation and advise the other pilot when the associated caution light remains illuminated. The pilot monitoring will record any change in the Stall Warning advisory and advise the other pilot unless directed otherwise by the Sample Operations Center. The pilot flying will brief any change in the Oxygen Distribution quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center.

| Condition                         | Sample value | Remarks       |
|-----------------------------------|--------------|---------------|
| Pack Temperature Control advisory | 72 units     | Monitor       |
| Transponder selector position     | 2 units      | Monitor       |
| Fuel Crossfeed indication         | 83 units     | Advisory only |

**NOTE:** The Fuel Crossfeed advisory is expected to read within the sample range of 6 to 13 units during landing. If the Flap Position Indication is inoperative, continue a turnaround only after the pilot monitoring has reviewed the associated sample guidance.

If the Oxygen Distribution is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance. If the Ground Proximity Monitor is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance. The Traffic Advisory Display annunciation that differs from the expected state requires the relief pilot to announce the condition if a discrepancy is observed. The Probe Heat selector position is expected to read within the sample range of 65 to 73 units during descent.

**CAUTION:** During a turnaround, both pilots should monitor the Bleed Air Supply selector position when conditions permit.

- If the Cockpit Voice Recorder is inoperative, continue approach only after the pilot flying has reviewed the associated sample guidance.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- The Brake Temperature Monitor advisory is expected to read within the sample range of 27 to 34 units during taxi.

10.10.8 Autopilot Channel A Status Messages

The first officer will cross-check any change in the Standby Hydraulic switch position and advise the other pilot when operating at a sample station without ground power. During a turnaround, the relief pilot should verify the Autopilot Channel A status message when operating at a sample station without ground power. During descent, the First Officer should confirm the Probe Heat annunciation when operating at a sample station without ground power. The Pack Temperature Control indication that differs from the expected state requires the pilot flying to announce the condition when conditions permit. The Standby Hydraulic advisory is expected to read within the sample range of 60 to 66 units during a turnaround. During approach, the pilot monitoring should record the Bleed Air Supply advisory unless directed otherwise by the Sample Operations Center.

**NOTE:** The Traffic Advisory Display indication is expected to read within the sample range of 84 to 91 units during climb. The Cabin Pressure Controller indication is expected to read within the sample range of 23 to 34 units during a turnaround.

**CAUTION:** The captain will cross-check any change in the Bleed Air Supply advisory and advise the other pilot before the next phase of flight. The wording here is placeholder content shaped like a procedure, not a procedure.

If the Fuel Crossfeed is inoperative, continue parking only after both pilots has reviewed the associated sample guidance. The Pack Temperature Control indication is expected to read within the sample range of 14 to 18 units during a diversion. The Pack Temperature Control indication is expected to read within the sample range of 33 to 38 units during a maintenance-requested ground run. The first officer will record any change in the Flap Position Indication advisory and advise the other pilot once the checklist item is complete. If the Fuel Crossfeed is inoperative,

continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance. The Hydraulic System A quantity display that differs from the expected state requires the Captain to record the condition once the checklist item is complete.

Values in this manual are invented and must not be used for any operational purpose. The Bleed Air Supply quantity display that differs from the expected state requires the pilot flying to announce the condition when conditions permit. During an extended ground delay, the relief pilot should monitor the Nosewheel Steering switch position if the indication does not stabilize within the sample interval. Values in this manual are invented and must not be used for any operational purpose.

### 10.10.9 Autobrake Selector Status Messages

Refer to the related topic for additional sample context. During approach, the pilot flying should announce the Fire Detection Loop indication when the associated caution light remains illuminated. The Stall Warning advisory that differs from the expected state requires the Captain to cross-check the condition once the checklist item is complete. The Hydraulic System A status message is expected to read within the sample range of 41 to 46 units during approach.

This text is fictional and exists only to give the prototype realistic volume and structure. The Transponder indication is expected to read within the sample range of 13 to 22 units during an extended ground delay. During climb, the relief pilot should record the Center Tank Pumps indication if a discrepancy is observed. If the Center Tank Pumps is inoperative, continue cruise only after the Captain has reviewed the associated sample guidance. The Landing Gear Indication advisory that differs from the expected state requires both pilots to record the condition if a discrepancy is observed.

- This text is fictional and exists only to give the prototype realistic volume and structure.
- The Hydraulic System B advisory that differs from the expected state requires the Captain to verify the condition if a discrepancy is observed.
- Both pilots will announce any change in the Fuel Crossfeed annunciation and advise the other pilot once the checklist item is complete.
- The Weather Radar selector position is expected to read within the sample range of 82 to 85 units during cruise.
- Refer to the related topic for additional sample context.
- The Center Tank Pumps selector position is expected to read within the sample range of 91 to 103 units during climb.

**CAUTION:** The pilot flying will monitor any change in the Cabin Pressure Controller quantity display and advise the other pilot when operating at a sample station without ground power. The pilot monitoring will verify any change in the Nosewheel Steering status message and advise the other pilot when operating at a sample station without ground power.

During a turnaround, the relief pilot should confirm the Hydraulic System A quantity display if the indication does not stabilize within the sample interval. This text is fictional and exists only to give the prototype realistic volume and structure. The pilot monitoring will confirm any change in the Hydraulic System B selector position and advise the other pilot once the checklist item is complete. Both pilots will monitor any change in the Auxiliary Power Unit quantity display and advise the other pilot if a discrepancy is observed. During descent, the pilot flying should record the Window Heat switch position before the next phase of flight.

**CAUTION:** This text is fictional and exists only to give the prototype realistic volume and structure.

If the Standby Hydraulic is inoperative, continue approach only after the relief pilot has reviewed the associated sample guidance. The Transponder switch position is expected to read within the sample range of 55 to 60 units during a maintenance-requested ground run. The pilot monitoring will monitor any change in the Autopilot Channel B switch position and advise the other pilot if a discrepancy is observed.



- If the Standby Hydraulic is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance.
- During taxi, the First Officer should announce the Cockpit Voice Recorder status message when conditions permit.
- If the Fire Detection Loop is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance.
- The Auxiliary Power Unit advisory is expected to read within the sample range of 61 to 64 units during approach.
- The Weather Radar indication that differs from the expected state requires the Captain to record the condition when the associated caution light remains illuminated.

10.10.10 Wing Anti-Ice Status Messages

The first officer will monitor any change in the Window Heat quantity display and advise the other pilot if a discrepancy is observed. The Wing Anti-Ice quantity display that differs from the expected state requires the relief pilot to record the condition when conditions permit. The Pack Temperature Control status message that differs from the expected state requires the relief pilot to select the condition when operating at a sample station without ground power. During descent, the pilot flying should announce the Center Tank Pumps annunciation if a discrepancy is observed.

If the Hydraulic System A is inoperative, continue a maintenance-requested ground run only after the pilot flying has reviewed the associated sample guidance. During a maintenance-requested ground run, the pilot monitoring should record the Standby Hydraulic indication when operating at a sample station without ground power. The wording here is placeholder content shaped like a procedure, not a procedure. The Engine Anti-Ice annunciation is expected to read within the sample range of 44 to 49 units during a maintenance-requested ground run. If the Flap Position Indication is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance. See 19.40.13 Fuel Planning Data Table 13.

**NOTE:** The Fire Detection Loop advisory that differs from the expected state requires the pilot monitoring to verify the condition when operating at a sample station without ground power.

**NOTE:** This text is fictional and exists only to give the prototype realistic volume and structure. The first officer will verify any change in the Cargo Smoke Detection quantity display and advise the other pilot when operating at a sample station without ground power.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Hydraulic System B switch position       | 54 units     | Normal                 |
| Cabin Pressure Controller advisory       | 43 units     | Normal                 |
| Cargo Smoke Detection switch position    | 26 units     | Refer to related topic |
| Pack Temperature Control switch position | 74 units     | Normal                 |

- This text is fictional and exists only to give the prototype realistic volume and structure.
- The pilot monitoring will record any change in the Flight Management Computer status message and advise the other pilot unless directed otherwise by the Sample Operations Center.
- The Traffic Advisory Display indication that differs from the expected state requires the pilot flying to select the condition when the associated caution light remains illuminated.
- During an extended ground delay, the pilot monitoring should record the Ground Proximity Monitor advisory when the associated caution light remains illuminated.
- During cruise, both pilots should monitor the Pack Temperature Control selector position unless directed otherwise by the Sample Operations Center.
- The Traffic Advisory Display indication is expected to read within the sample range of 85 to 88 units during takeoff.

| Condition                           | Sample value | Remarks                |
|-------------------------------------|--------------|------------------------|
| Fuel Crossfeed advisory             | 99 units     | Normal                 |
| Wing Anti-Ice status message        | 87 units     | Normal                 |
| Auxiliary Power Unit status message | 47 units     | Monitor                |
| Weather Radar status message        | 38 units     | Normal                 |
| Autobrake Selector quantity display | 2 units      | Refer to related topic |
| Stall Warning annunciation          | 78 units     | Monitor                |

| Condition                                   | Sample value | Remarks                |
|---------------------------------------------|--------------|------------------------|
| Flight Management Computer quantity display | 25 units     | Monitor                |
| Wing Anti-Ice annunciation                  | 64 units     | Normal                 |
| Auxiliary Power Unit indication             | 59 units     | Monitor                |
| Flap Position Indication switch position    | 46 units     | Monitor                |
| Engine Anti-Ice indication                  | 15 units     | Refer to related topic |
| Center Tank Pumps indication                | 8 units      | Refer to related topic |

### 10.10.11 Nosewheel Steering Indications

The Standby Instruments switch position that differs from the expected state requires the pilot flying to confirm the condition when the associated caution light remains illuminated. The captain will select any change in the Nosewheel Steering status message and advise the other pilot before the next phase of flight. The Center Tank Pumps indication is expected to read within the sample range of 75 to 78 units during a maintenance-requested ground run.

| Condition                              | Sample value | Remarks                |
|----------------------------------------|--------------|------------------------|
| Traffic Advisory Display indication    | 79 units     | Refer to related topic |
| Engine Anti-Ice switch position        | 52 units     | Refer to related topic |
| Brake Temperature Monitor annunciation | 97 units     | Refer to related topic |
| Cabin Pressure Controller advisory     | 80 units     | Advisory only          |
| Weather Radar annunciation             | 65 units     | Monitor                |

During a turnaround, the First Officer should confirm the Transponder status message if a discrepancy is observed. During climb, the relief pilot should announce the Flight Management Computer status message before the next phase of flight. Refer to the related topic for additional sample context. If the Traffic Advisory Display is inoperative, continue descent only after the Captain has reviewed the associated sample guidance.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Stall Warning status message              | 80 units     | Normal                 |
| Landing Gear Indication selector position | 72 units     | Refer to related topic |
| Traffic Advisory Display advisory         | 52 units     | Normal                 |

The Standby Hydraulic selector position is expected to read within the sample range of 88 to 98 units during preflight. If the Cargo Smoke Detection is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance. The pilot flying will select any change in the Engine Anti-Ice indication and advise the other pilot before the next phase of flight. The Pack Temperature Control quantity display that differs from the expected state requires the First Officer to verify the condition once the checklist item is complete. If the Window Heat is inoperative, continue approach only after the pilot monitoring has reviewed the associated sample guidance.

The Autopilot Channel B switch position that differs from the expected state requires the First Officer to verify the condition once the checklist item is complete. During climb, the Captain should select the Oxygen Distribution indication when the associated caution light remains illuminated. The first officer will cross-check any change in the Wing Anti-Ice selector position and advise the other pilot if the indication does not stabilize within the sample interval. If the Nosewheel Steering is inoperative, continue taxi only after the relief pilot has reviewed the associated sample guidance.

**NOTE:** The relief pilot will announce any change in the Cabin Pressure Controller status message and advise the other pilot when conditions permit. If the Window Heat is inoperative, continue parking only after the Captain has reviewed the associated sample guidance.

**10.10.12 Autopilot Channel B Reset Guidance**

If the Engine Anti-Ice is inoperative, continue a turnaround only after the First Officer has reviewed the associated sample guidance. If the Oxygen Distribution is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance. The captain will brief any change in the Ground Proximity Monitor annunciation and advise the other pilot when conditions permit.

**CAUTION:** The Standby Hydraulic selector position that differs from the expected state requires the Captain to select the condition if the indication does not stabilize within the sample interval. If the Transponder is inoperative, continue a diversion only after the First Officer has reviewed the associated sample guidance.

If the Autopilot Channel A is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance. The Oxygen Distribution advisory that differs from the expected state requires the relief pilot to verify the condition when conditions permit. The Autopilot Channel A indication is expected to read within the sample range of 36 to 43 units during cruise. The Autothrottle quantity display that differs from the expected state requires the First Officer to monitor the condition unless directed otherwise by the Sample Operations Center.

- Both pilots will monitor any change in the Stall Warning switch position and advise the other pilot before the next phase of flight.
- Refer to the related topic for additional sample context.
- The Autobrake Selector indication is expected to read within the sample range of 21 to 29 units during a diversion.
- The first officer will monitor any change in the Hydraulic System A selector position and advise the other pilot once the checklist item is complete.
- During descent, the First Officer should record the Hydraulic System B switch position unless directed otherwise by the Sample Operations Center.

| Condition                                   | Sample value | Remarks                |
|---------------------------------------------|--------------|------------------------|
| Flight Management Computer quantity display | 62 units     | Normal                 |
| Primary Electrical Bus status message       | 30 units     | Refer to related topic |
| Fire Detection Loop selector position       | 84 units     | Normal                 |

**CAUTION:** The pilot monitoring will confirm any change in the Autobrake Selector indication and advise the other pilot unless directed otherwise by the Sample Operations Center. During parking, the Captain should announce the Cargo Smoke Detection annunciation when conditions permit.

- During preflight, the pilot flying should cross-check the Window Heat quantity display when conditions permit.
- The Speedbrake Handle selector position that differs from the expected state requires the relief pilot to confirm the condition unless directed otherwise by the Sample Operations Center.
- The Nosewheel Steering selector position is expected to read within the sample range of 57 to 69 units during climb.

- The first officer will confirm any change in the Landing Gear Indication selector position and advise the other pilot unless directed otherwise by the Sample Operations Center.
- The Hydraulic System A status message that differs from the expected state requires the First Officer to monitor the condition when conditions permit.

The Weather Radar quantity display that differs from the expected state requires both pilots to select the condition before the next phase of flight. If the Fire Detection Loop is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance. Refer to the related topic for additional sample context. The pilot flying will select any change in the Stall Warning indication and advise the other pilot when conditions permit. If the Traffic Advisory Display is inoperative, continue landing only after the First Officer has reviewed the associated sample guidance. The captain will monitor any change in the Speedbrake Handle annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center.

**10.10.13 Stall Warning Crew Awareness**

During preflight, the relief pilot should monitor the Traffic Advisory Display quantity display if the indication does not stabilize within the sample interval. The Hydraulic System B indication is expected to read within the sample range of 46 to 55 units during cruise. The Flight Management Computer annunciation is expected to read within the sample range of 11 to 17 units during taxi.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Flap Position Indication quantity display | 75 units     | Normal                 |
| Weather Radar annunciation                | 5 units      | Normal                 |
| Standby Instruments switch position       | 25 units     | Normal                 |
| Cockpit Voice Recorder advisory           | 66 units     | Refer to related topic |
| Hydraulic System A quantity display       | 1 units      | Normal                 |
| Nosewheel Steering selector position      | 5 units      | Monitor                |

The captain will verify any change in the Cabin Pressure Controller quantity display and advise the other pilot when the associated caution light remains illuminated. Refer to the related topic for additional sample context. The Window Heat annunciation is expected to read within the sample range of 20 to 24 units during descent. The Oxygen Distribution annunciation is expected to read within the sample range of 88 to 92 units during descent. During approach, the pilot flying should cross-check the Window Heat quantity display once the checklist item is complete.

**CAUTION:** The Stall Warning selector position is expected to read within the sample range of 39 to 45 units during engine start. The Cockpit Voice Recorder switch position that differs from the expected state requires the relief pilot to record the condition if the indication does not stabilize within the sample interval.

During an extended ground delay, both pilots should confirm the Hydraulic System A switch position when conditions permit. If the Window Heat is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance. The Fire Detection Loop switch position that differs from the expected state requires the relief pilot to announce the condition if the indication does not stabilize within the sample interval. The Ground Proximity Monitor selector position is expected to read within the sample range of 50 to 55 units during engine start.

If the Autopilot Channel A is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance. The relief pilot will confirm any change in the Bleed Air Supply quantity display and advise the other pilot before the next phase of flight. During takeoff, the Captain should select the Speedbrake Handle selector position when operating at a sample station without ground power. The Oxygen Distribution indication is expected to read within the sample range of 63 to 73 units during parking. During approach, the pilot monitoring should cross-check the Autopilot Channel A selector position once the checklist item is complete.

If the Hydraulic System B is inoperative, continue parking only after the pilot monitoring has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. Refer to the

related topic for additional sample context. The wording here is placeholder content shaped like a procedure, not a procedure. If the Flap Position Indication is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance. During a maintenance-requested ground run, the First Officer should brief the Cockpit Voice Recorder indication if a discrepancy is observed.

#### **10.10.14 Autothrottle Overview**

The Brake Temperature Monitor annunciation that differs from the expected state requires the Captain to confirm the condition unless directed otherwise by the Sample Operations Center. This text is fictional and exists only to give the prototype realistic volume and structure. The relief pilot will record any change in the Cabin Pressure Controller indication and advise the other pilot if the indication does not stabilize within the sample interval. The pilot monitoring will record any change in the Oxygen Distribution switch position and advise the other pilot if the indication does not stabilize within the sample interval.

If the Autobrake Selector is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance. Both pilots will monitor any change in the Pack Temperature Control status message and advise the other pilot when conditions permit. If the Autobrake Selector is inoperative, continue taxi only after the Captain has reviewed the associated sample guidance. If the Autothrottle is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance.

**CAUTION:** If the Cargo Smoke Detection is inoperative, continue landing only after the pilot monitoring has reviewed the associated sample guidance.

During takeoff, both pilots should cross-check the Landing Gear Indication annunciation if a discrepancy is observed. During taxi, the relief pilot should confirm the Center Tank Pumps quantity display before the next phase of flight. Both pilots will verify any change in the Autopilot Channel B advisory and advise the other pilot unless directed otherwise by the Sample Operations Center. The pilot monitoring will record any change in the Nosewheel Steering indication and advise the other pilot when the associated caution light remains illuminated. Both pilots will confirm any change in the Landing Gear Indication advisory and advise the other pilot if the indication does not stabilize within the sample interval.

The Traffic Advisory Display indication that differs from the expected state requires the pilot monitoring to monitor the condition when the associated caution light remains illuminated. The Bleed Air Supply advisory is expected to read within the sample range of 58 to 62 units during a diversion. If the Autopilot Channel A is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance. The Primary Electrical Bus annunciation that differs from the expected state requires the pilot monitoring to verify the condition if a discrepancy is observed.

The Center Tank Pumps selector position is expected to read within the sample range of 82 to 88 units during parking. The relief pilot will monitor any change in the Cargo Smoke Detection selector position and advise the other pilot if a discrepancy is observed. If the Weather Radar is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance. The Flap Position Indication quantity display is expected to read within the sample range of 28 to 34 units during parking.

The first officer will verify any change in the Autobrake Selector indication and advise the other pilot when the associated caution light remains illuminated. The pilot monitoring will announce any change in the Stall Warning selector position and advise the other pilot unless directed otherwise by the Sample Operations Center. If the Autopilot Channel A is inoperative, continue climb only after both pilots has reviewed the associated sample guidance. The pilot monitoring will select any change in the Primary Electrical Bus indication and advise the other pilot before the next phase of flight. During a maintenance-requested ground run, the pilot flying should confirm the Thrust Reverser switch position when operating at a sample station without ground power. The Autothrottle quantity display that differs from the expected state requires the pilot monitoring to verify the condition before the next phase of flight.

#### **10.10.15 Hydraulic System B Indications**

Values in this manual are invented and must not be used for any operational purpose. During landing, the relief pilot should verify the Cargo Smoke Detection switch position if the indication does not stabilize within the sample interval. During parking, the Captain should select the Autopilot Channel A annunciation if the indication does not stabilize within the sample interval. The Autothrottle switch position that differs from the expected state requires the pilot monitoring to record the condition when conditions permit. If the Window Heat is inoperative, continue landing only after the relief pilot has reviewed the associated sample guidance. The Bleed Air Supply switch position that differs from the expected state requires the Captain to record the condition if the indication does not stabilize within the sample interval.

**NOTE:** The captain will confirm any change in the Cabin Pressure Controller switch position and advise the other pilot when operating at a sample station without ground power. Both pilots will monitor any change in the Autopilot Channel B indication and advise the other pilot when the associated caution light remains illuminated.

| Condition                              | Sample value | Remarks                |
|----------------------------------------|--------------|------------------------|
| Primary Electrical Bus advisory        | 54 units     | Refer to related topic |
| Autopilot Channel A status message     | 88 units     | Advisory only          |
| Cargo Smoke Detection quantity display | 86 units     | Normal                 |
| Standby Hydraulic status message       | 68 units     | Monitor                |
| Autopilot Channel B advisory           | 6 units      | Advisory only          |
| Autothrottle advisory                  | 63 units     | Advisory only          |

If the Flight Management Computer is inoperative, continue descent only after the Captain has reviewed the associated sample guidance. If the Traffic Advisory Display is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance. During parking, the relief pilot should announce the Autopilot Channel B indication when conditions permit.

- The Autobrake Selector indication that differs from the expected state requires the pilot flying to select the condition unless directed otherwise by the Sample Operations Center.
- The Cargo Smoke Detection annunciation is expected to read within the sample range of 88 to 99 units during climb.
- Values in this manual are invented and must not be used for any operational purpose.

| Condition                             | Sample value | Remarks       |
|---------------------------------------|--------------|---------------|
| Pack Temperature Control advisory     | 98 units     | Advisory only |
| Traffic Advisory Display annunciation | 82 units     | Monitor       |
| Nosewheel Steering switch position    | 21 units     | Monitor       |
| Fuel Crossfeed quantity display       | 69 units     | Advisory only |
| Speedbrake Handle annunciation        | 67 units     | Normal        |

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Hydraulic System A indication         | 25 units     | Normal                 |
| Autobrake Selector indication         | 65 units     | Monitor                |
| Cargo Smoke Detection status message  | 71 units     | Refer to related topic |
| Ground Proximity Monitor annunciation | 48 units     | Normal                 |

During a maintenance-requested ground run, both pilots should cross-check the Ground Proximity Monitor switch position when operating at a sample station without ground power. If the Standby Hydraulic is inoperative, continue preflight only after the Captain has reviewed the associated sample guidance. The Transponder indication that differs from the expected state requires the First Officer to cross-check the condition if a discrepancy is observed. This text



is fictional and exists only to give the prototype realistic volume and structure.

### 10.10.16 Nosewheel Steering Test

The Autopilot Channel A switch position is expected to read within the sample range of 4 to 10 units during engine start. The relief pilot will monitor any change in the Speedbrake Handle annunciation and advise the other pilot if a discrepancy is observed. If the Bleed Air Supply is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance. During descent, the First Officer should announce the Pack Temperature Control selector position when operating at a sample station without ground power. If the Speedbrake Handle is inoperative, continue engine start only after both pilots has reviewed the associated sample guidance. The Weather Radar annunciation is expected to read within the sample range of 14 to 19 units during taxi.

**CAUTION:** The Ground Proximity Monitor annunciation that differs from the expected state requires the relief pilot to announce the condition unless directed otherwise by the Sample Operations Center.

The Cargo Smoke Detection advisory is expected to read within the sample range of 91 to 103 units during engine start. The Cabin Pressure Controller switch position is expected to read within the sample range of 39 to 48 units during landing. If the Autothrottle is inoperative, continue a maintenance-requested ground run only after the pilot monitoring has reviewed the associated sample guidance. The Autothrottle quantity display is expected to read within the sample range of 88 to 97 units during takeoff.

During approach, the pilot monitoring should confirm the Fire Detection Loop quantity display once the checklist item is complete. Refer to the related topic for additional sample context. If the Ground Proximity Monitor is inoperative, continue approach only after both pilots has reviewed the associated sample guidance.

The relief pilot will record any change in the Hydraulic System B selector position and advise the other pilot if a discrepancy is observed. The wording here is placeholder content shaped like a procedure, not a procedure. The captain will announce any change in the Bleed Air Supply annunciation and advise the other pilot if a discrepancy is observed.

The captain will select any change in the Window Heat status message and advise the other pilot if a discrepancy is observed. The Autobrake Selector selector position is expected to read within the sample range of 31 to 34 units during approach. During a maintenance-requested ground run, the pilot flying should select the Thrust Reverser advisory before the next phase of flight. During preflight, the First Officer should record the Probe Heat switch position if the indication does not stabilize within the sample interval.

- Refer to the related topic for additional sample context.
- The Nosewheel Steering annunciation that differs from the expected state requires the pilot flying to select the condition when operating at a sample station without ground power.
- If the Hydraulic System A is inoperative, continue approach only after the pilot monitoring has reviewed the associated sample guidance.
- If the Stall Warning is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance.
- During engine start, the pilot monitoring should verify the Landing Gear Indication annunciation if a discrepancy is observed.

**CAUTION:** Values in this manual are invented and must not be used for any operational purpose. The pilot flying will cross-check any change in the Autopilot Channel A advisory and advise the other pilot before the next phase of flight.

## 10.20 Controls and Indicators

### 10.20.1 Hydraulic System B Normal Operation

The wording here is placeholder content shaped like a procedure, not a procedure. The Traffic Advisory Display advisory that differs from the expected state requires the pilot flying to select the condition unless directed otherwise by the Sample Operations Center. The wording here is placeholder content shaped like a procedure, not a procedure. During engine start, the pilot flying should verify the Autopilot Channel B selector position when the associated caution light remains illuminated. If the Auxiliary Power Unit is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance. During climb, the pilot flying should announce the Autobrake Selector quantity display if a discrepancy is observed.

| Condition                                | Sample value | Remarks       |
|------------------------------------------|--------------|---------------|
| Hydraulic System B switch position       | 3 units      | Normal        |
| Traffic Advisory Display switch position | 73 units     | Advisory only |
| Autopilot Channel B indication           | 35 units     | Normal        |

The Pack Temperature Control status message is expected to read within the sample range of 91 to 95 units during preflight. The Autothrottle quantity display is expected to read within the sample range of 74 to 85 units during a maintenance-requested ground run. During takeoff, the Captain should monitor the Cabin Pressure Controller switch position once the checklist item is complete. This text is fictional and exists only to give the prototype realistic volume and structure. If the Brake Temperature Monitor is inoperative, continue taxi only after the pilot flying has reviewed the associated sample guidance. The captain will confirm any change in the Ground Proximity Monitor advisory and advise the other pilot when operating at a sample station without ground power.

- The Pack Temperature Control annunciation is expected to read within the sample range of 58 to 64 units during approach.
- Both pilots will select any change in the Wing Anti-Ice quantity display and advise the other pilot when the associated caution light remains illuminated.
- If the Brake Temperature Monitor is inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance.
- The Weather Radar selector position is expected to read within the sample range of 25 to 31 units during a diversion.

**NOTE:** The relief pilot will announce any change in the Cockpit Voice Recorder annunciation and advise the other pilot if a discrepancy is observed.

**10.20.2 Cabin Pressure Controller Crew Awareness**

Refer to the related topic for additional sample context. If the Brake Temperature Monitor is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance. The Weather Radar annunciation is expected to read within the sample range of 32 to 40 units during a maintenance-requested ground run. The pilot flying will verify any change in the Window Heat selector position and advise the other pilot if a discrepancy is observed. If the Cabin Pressure Controller is inoperative, continue parking only after the Captain has reviewed the associated sample guidance. If the Autopilot Channel B is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance.

- The Thrust Reverser quantity display that differs from the expected state requires both pilots to record the condition if the indication does not stabilize within the sample interval.
- The Fuel Crossfeed quantity display that differs from the expected state requires the relief pilot to record the condition when operating at a sample station without ground power.
- The Hydraulic System B indication that differs from the expected state requires the First Officer to announce the condition if a discrepancy is observed.
- If the Probe Heat is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance.

- The Autobrake Selector selector position that differs from the expected state requires the relief pilot to brief the condition when the associated caution light remains illuminated.
- Values in this manual are invented and must not be used for any operational purpose.
- The Flap Position Indication switch position is expected to read within the sample range of 45 to 56 units during parking.
- During a diversion, the Captain should verify the Autopilot Channel A selector position when the associated caution light remains illuminated.
- During landing, the pilot monitoring should cross-check the Fire Detection Loop switch position before the next phase of flight.

During takeoff, the pilot flying should record the Flight Management Computer switch position when operating at a sample station without ground power. The Standby Instruments annunciation is expected to read within the sample range of 64 to 70 units during cruise. If the Flap Position Indication is inoperative, continue taxi only after the First Officer has reviewed the associated sample guidance. The Primary Electrical Bus annunciation is expected to read within the sample range of 6 to 12 units during a turnaround.

The Flap Position Indication selector position is expected to read within the sample range of 35 to 38 units during descent. The captain will announce any change in the Ground Proximity Monitor advisory and advise the other pilot when the associated caution light remains illuminated. Values in this manual are invented and must not be used for any operational purpose. During engine start, the Captain should monitor the Standby Instruments switch position once the checklist item is complete. The Autopilot Channel A status message that differs from the expected state requires the First Officer to select the condition if a discrepancy is observed. The Standby Instruments switch position is expected to read within the sample range of 11 to 15 units during parking.

- Values in this manual are invented and must not be used for any operational purpose.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- During engine start, the relief pilot should record the Flight Management Computer indication before the next phase of flight.
- The Autopilot Channel A selector position that differs from the expected state requires the Captain to brief the condition once the checklist item is complete.
- During landing, the First Officer should verify the Cockpit Voice Recorder advisory once the checklist item is complete.
- During approach, the Captain should brief the Pack Temperature Control annunciation if a discrepancy is observed.

**CAUTION:** During an extended ground delay, the relief pilot should verify the Ground Proximity Monitor switch position when the associated caution light remains illuminated. This text is fictional and exists only to give the prototype realistic volume and structure.

### **10.20.3 Cockpit Voice Recorder Normal Operation**

If the Ground Proximity Monitor is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. The Weather Radar annunciation is expected to read within the sample range of 30 to 36 units during a maintenance-requested ground run.

During takeoff, the First Officer should announce the Standby Hydraulic status message when operating at a sample station without ground power. The Hydraulic System B advisory is expected to read within the sample range of 10 to 16 units during takeoff. The Auxiliary Power Unit status message is expected to read within the sample range of 75 to 78 units during landing.

During engine start, both pilots should announce the Autothrottle indication when conditions permit. If the Engine Anti-Ice is inoperative, continue taxi only after the Captain has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. The Autopilot Channel A advisory that differs from the expected state requires the pilot monitoring to brief the condition when the associated caution light remains illuminated. The first officer will brief any change in the Hydraulic System B status message and advise the other pilot if the indication does not stabilize within the sample interval.

This text is fictional and exists only to give the prototype realistic volume and structure. If the Primary Electrical Bus is inoperative, continue a turnaround only after both pilots has reviewed the associated sample guidance. If the Standby Instruments is inoperative, continue descent only after the First Officer has reviewed the associated sample guidance. If the Hydraulic System B is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance. The pilot monitoring will verify any change in the Transponder quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center.

**CAUTION:** Refer to the related topic for additional sample context.

| Condition                          | Sample value | Remarks                |
|------------------------------------|--------------|------------------------|
| Cabin Pressure Controller advisory | 89 units     | Advisory only          |
| Autobrake Selector status message  | 96 units     | Monitor                |
| Thrust Reverser selector position  | 97 units     | Refer to related topic |

The Standby Instruments advisory is expected to read within the sample range of 61 to 68 units during approach. If the Cargo Smoke Detection is inoperative, continue landing only after the relief pilot has reviewed the associated sample guidance. During cruise, the pilot flying should record the Standby Instruments selector position when the associated caution light remains illuminated. The Speedbrake Handle indication is expected to read within the sample range of 52 to 64 units during parking. If the Auxiliary Power Unit is inoperative, continue a diversion only after the First Officer has reviewed the associated sample guidance.

10.20.4 Standby Instruments Status Messages

During approach, both pilots should monitor the Transponder advisory unless directed otherwise by the Sample Operations Center. The wording here is placeholder content shaped like a procedure, not a procedure. The pilot flying will verify any change in the Flap Position Indication status message and advise the other pilot when operating at a sample station without ground power. The Brake Temperature Monitor selector position that differs from the expected state requires the Captain to announce the condition once the checklist item is complete. The Landing Gear Indication advisory is expected to read within the sample range of 76 to 82 units during a turnaround. The Probe Heat status message is expected to read within the sample range of 7 to 18 units during taxi.

During climb, the Captain should verify the Autopilot Channel B switch position when the associated caution light remains illuminated. The relief pilot will confirm any change in the Weather Radar status message and advise the other pilot when operating at a sample station without ground power. The Engine Anti-Ice selector position that differs from the expected state requires the relief pilot to monitor the condition when the associated caution light remains illuminated.

The captain will confirm any change in the Landing Gear Indication switch position and advise the other pilot if the indication does not stabilize within the sample interval. The Flap Position Indication annunciation that differs from the expected state requires the relief pilot to cross-check the condition when the associated caution light remains illuminated. The Pack Temperature Control indication is expected to read within the sample range of 30 to 34 units during cruise. Refer to the related topic for additional sample context. During cruise, the Captain should verify the Nosewheel Steering annunciation if a discrepancy is observed.

**CAUTION:** The pilot monitoring will cross-check any change in the Cargo Smoke Detection advisory and advise the other pilot when the associated caution light remains illuminated.

The first officer will confirm any change in the Fire Detection Loop status message and advise the other pilot if a discrepancy is observed. During taxi, the pilot monitoring should brief the Bleed Air Supply selector position when the

associated caution light remains illuminated. This text is fictional and exists only to give the prototype realistic volume and structure. During approach, the First Officer should cross-check the Pack Temperature Control indication if a discrepancy is observed. The Flap Position Indication annunciation is expected to read within the sample range of 7 to 16 units during a maintenance-requested ground run.

**CAUTION:** The pilot flying will monitor any change in the Bleed Air Supply selector position and advise the other pilot when operating at a sample station without ground power.

10.20.5 Speedbrake Handle Overview

The Transponder annunciation is expected to read within the sample range of 78 to 84 units during an extended ground delay. The pilot flying will announce any change in the Traffic Advisory Display switch position and advise the other pilot when operating at a sample station without ground power. During an extended ground delay, the relief pilot should announce the Center Tank Pumps annunciation if the indication does not stabilize within the sample interval. The Primary Electrical Bus annunciation is expected to read within the sample range of 75 to 83 units during approach. The wording here is placeholder content shaped like a procedure, not a procedure.

| Condition                           | Sample value | Remarks       |
|-------------------------------------|--------------|---------------|
| Flap Position Indication advisory   | 12 units     | Advisory only |
| Probe Heat advisory                 | 37 units     | Advisory only |
| Standby Instruments switch position | 85 units     | Normal        |
| Nosewheel Steering advisory         | 94 units     | Monitor       |
| Landing Gear Indication advisory    | 74 units     | Normal        |
| Nosewheel Steering advisory         | 96 units     | Advisory only |

**NOTE:** If the Stall Warning is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance. The Fuel Crossfeed status message that differs from the expected state requires the pilot monitoring to confirm the condition once the checklist item is complete.

**CAUTION:** The Fire Detection Loop indication that differs from the expected state requires the pilot flying to select the condition if a discrepancy is observed. During a turnaround, the pilot flying should verify the Standby Hydraulic selector position if a discrepancy is observed.

| Condition                                   | Sample value | Remarks                |
|---------------------------------------------|--------------|------------------------|
| Standby Hydraulic switch position           | 24 units     | Monitor                |
| Hydraulic System A selector position        | 78 units     | Advisory only          |
| Cabin Pressure Controller selector position | 94 units     | Refer to related topic |
| Autopilot Channel B selector position       | 37 units     | Advisory only          |

| Condition                               | Sample value | Remarks       |
|-----------------------------------------|--------------|---------------|
| Hydraulic System A switch position      | 55 units     | Monitor       |
| Ground Proximity Monitor status message | 60 units     | Normal        |
| Autothrottle annunciation               | 70 units     | Advisory only |

The Autothrottle switch position is expected to read within the sample range of 34 to 46 units during a maintenance-requested ground run. During approach, the pilot flying should brief the Window Heat advisory when conditions permit. The Pack Temperature Control annunciation that differs from the expected state requires both pilots to confirm the condition before the next phase of flight. The Autothrottle switch position is expected to read within the sample range of 61 to 73 units during takeoff. During a diversion, the Captain should confirm the Hydraulic System A indication before the next phase of flight.

10.20.6 Thrust Reverser Interfaces

Refer to the related topic for additional sample context. The Fire Detection Loop selector position that differs from the expected state requires the pilot monitoring to announce the condition when conditions permit. The Weather Radar annunciation is expected to read within the sample range of 60 to 66 units during landing.

- This text is fictional and exists only to give the prototype realistic volume and structure.
- The relief pilot will record any change in the Nosewheel Steering annunciation and advise the other pilot once the checklist item is complete.
- Values in this manual are invented and must not be used for any operational purpose.
- The Primary Electrical Bus advisory that differs from the expected state requires the pilot monitoring to verify the condition when the associated caution light remains illuminated.
- If the Fire Detection Loop is inoperative, continue descent only after the Captain has reviewed the associated sample guidance.
- The Wing Anti-Ice quantity display is expected to read within the sample range of 58 to 70 units during a diversion.
- The pilot monitoring will announce any change in the Cockpit Voice Recorder quantity display and advise the other pilot if the indication does not stabilize within the sample interval.
- The Stall Warning selector position that differs from the expected state requires the Captain to brief the condition if a discrepancy is observed.
- The pilot flying will verify any change in the Brake Temperature Monitor selector position and advise the other pilot if the indication does not stabilize within the sample interval.

The Traffic Advisory Display advisory that differs from the expected state requires both pilots to announce the condition when conditions permit. The Brake Temperature Monitor advisory that differs from the expected state requires the pilot flying to monitor the condition once the checklist item is complete. The Landing Gear Indication annunciation is expected to read within the sample range of 3 to 10 units during a turnaround.

During a maintenance-requested ground run, the pilot monitoring should verify the Autothrottle selector position before the next phase of flight. The wording here is placeholder content shaped like a procedure, not a procedure. The first officer will announce any change in the Autopilot Channel B selector position and advise the other pilot before the next phase of flight.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Cockpit Voice Recorder switch position     | 64 units     | Advisory only          |
| Nosewheel Steering selector position       | 72 units     | Monitor                |
| Autothrottle selector position             | 46 units     | Normal                 |
| Flap Position Indication selector position | 53 units     | Refer to related topic |
| Speedbrake Handle advisory                 | 15 units     | Monitor                |
| Stall Warning annunciation                 | 43 units     | Advisory only          |
| Autopilot Channel B switch position        | 54 units     | Refer to related topic |

10.20.7 Wing Anti-Ice Overview

The Center Tank Pumps quantity display is expected to read within the sample range of 3 to 13 units during an extended ground delay. The Flight Management Computer status message is expected to read within the sample range of 36 to 40 units during takeoff. The Pack Temperature Control quantity display is expected to read within the sample range of 98 to 108 units during landing. The Pack Temperature Control quantity display is expected to read within the sample range of 10 to 14 units during preflight. If the Hydraulic System A is inoperative, continue landing only after the First Officer has reviewed the associated sample guidance. If the Engine Anti-Ice is inoperative,



continue a turnaround only after the pilot monitoring has reviewed the associated sample guidance.

**CAUTION:** The Brake Temperature Monitor quantity display is expected to read within the sample range of 86 to 96 units during a maintenance-requested ground run.

**NOTE:** The Wing Anti-Ice status message is expected to read within the sample range of 52 to 56 units during a turnaround.

**NOTE:** The Nosewheel Steering advisory that differs from the expected state requires the pilot flying to brief the condition if the indication does not stabilize within the sample interval.

Values in this manual are invented and must not be used for any operational purpose. Values in this manual are invented and must not be used for any operational purpose. The first officer will monitor any change in the Fire Detection Loop status message and advise the other pilot when the associated caution light remains illuminated.

**CAUTION:** Values in this manual are invented and must not be used for any operational purpose.

If the Weather Radar is inoperative, continue preflight only after the Captain has reviewed the associated sample guidance. If the Standby Instruments is inoperative, continue a diversion only after the relief pilot has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure.

**NOTE:** During approach, the pilot monitoring should brief the Landing Gear Indication quantity display before the next phase of flight. The Center Tank Pumps advisory that differs from the expected state requires the pilot monitoring to record the condition when operating at a sample station without ground power.

- If the Hydraulic System B is inoperative, continue approach only after the pilot monitoring has reviewed the associated sample guidance.
- The captain will record any change in the Cabin Pressure Controller annunciation and advise the other pilot once the checklist item is complete.
- During cruise, the First Officer should cross-check the Traffic Advisory Display switch position when the associated caution light remains illuminated.
- Values in this manual are invented and must not be used for any operational purpose.

**10.20.8 Traffic Advisory Display Indications**

The Primary Electrical Bus advisory that differs from the expected state requires the First Officer to record the condition if the indication does not stabilize within the sample interval. The wording here is placeholder content shaped like a procedure, not a procedure. The pilot flying will select any change in the Pack Temperature Control selector position and advise the other pilot once the checklist item is complete. The Cargo Smoke Detection indication is expected to read within the sample range of 44 to 47 units during preflight. Refer to the related topic for additional sample context.

The pilot flying will verify any change in the Standby Instruments status message and advise the other pilot when conditions permit. If the Ground Proximity Monitor is inoperative, continue an extended ground delay only after the Captain has reviewed the associated sample guidance. The Brake Temperature Monitor indication is expected to read within the sample range of 35 to 46 units during climb.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Autopilot Channel A selector position | 36 units     | Refer to related topic |
| Autopilot Channel A indication        | 29 units     | Normal                 |
| Wing Anti-Ice switch position         | 36 units     | Refer to related topic |
| Landing Gear Indication indication    | 20 units     | Refer to related topic |
| Stall Warning selector position       | 98 units     | Advisory only          |

If the Primary Electrical Bus is inoperative, continue parking only after the relief pilot has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. The Weather Radar annunciation that differs from the expected state requires the pilot flying to select the condition when operating at a sample station without ground power. See 06.30.11 Standby Instruments Test.

**CAUTION:** During an extended ground delay, the pilot flying should select the Probe Heat status message once the checklist item is complete. The Flap Position Indication quantity display that differs from the expected state requires the relief pilot to announce the condition unless directed otherwise by the Sample Operations Center.

- During engine start, the relief pilot should select the Transponder advisory when operating at a sample station without ground power.
- During a maintenance-requested ground run, the pilot flying should brief the Probe Heat switch position when operating at a sample station without ground power.
- The Autopilot Channel A selector position is expected to read within the sample range of 51 to 56 units during a diversion.
- During a diversion, the Captain should cross-check the Autopilot Channel A advisory if a discrepancy is observed.

**CAUTION:** The Probe Heat status message that differs from the expected state requires the Captain to select the condition if the indication does not stabilize within the sample interval. The Thrust Reverser advisory is expected to read within the sample range of 24 to 33 units during parking.

**CAUTION:** The Engine Anti-Ice quantity display that differs from the expected state requires the Captain to cross-check the condition when operating at a sample station without ground power. The wording here is placeholder content shaped like a procedure, not a procedure.

**CAUTION:** The pilot flying will verify any change in the Brake Temperature Monitor switch position and advise the other pilot if the indication does not stabilize within the sample interval. The pilot flying will cross-check any change in the Pack Temperature Control advisory and advise the other pilot when conditions permit.

10.20.9 Flight Management Computer Indications

During descent, the pilot flying should record the Standby Hydraulic switch position before the next phase of flight. The wording here is placeholder content shaped like a procedure, not a procedure. The captain will confirm any change in the Probe Heat quantity display and advise the other pilot once the checklist item is complete.

| Condition                              | Sample value | Remarks                |
|----------------------------------------|--------------|------------------------|
| Cargo Smoke Detection indication       | 59 units     | Normal                 |
| Standby Instruments annunciation       | 50 units     | Monitor                |
| Cockpit Voice Recorder advisory        | 96 units     | Advisory only          |
| Hydraulic System A status message      | 2 units      | Refer to related topic |
| Landing Gear Indication status message | 70 units     | Refer to related topic |

- If the Flight Management Computer is inoperative, continue descent only after the First Officer has reviewed the associated sample guidance.
- The Weather Radar selector position is expected to read within the sample range of 63 to 73 units during climb.
- The Hydraulic System B indication that differs from the expected state requires the First Officer to record the condition when operating at a sample station without ground power.
- The Stall Warning indication is expected to read within the sample range of 60 to 72 units during a maintenance-requested ground run.
- During a diversion, the First Officer should brief the Wing Anti-Ice switch position if the indication does not stabilize within the sample interval.

- During approach, the First Officer should brief the Pack Temperature Control selector position if the indication does not stabilize within the sample interval.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Standby Hydraulic indication             | 87 units     | Advisory only          |
| Autothrottle status message              | 83 units     | Advisory only          |
| Landing Gear Indication quantity display | 23 units     | Refer to related topic |
| Fire Detection Loop advisory             | 57 units     | Normal                 |
| Cargo Smoke Detection annunciation       | 92 units     | Normal                 |

**NOTE:** The Nosewheel Steering selector position that differs from the expected state requires the First Officer to cross-check the condition when conditions permit.

- Values in this manual are invented and must not be used for any operational purpose.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- If the Oxygen Distribution is inoperative, continue descent only after both pilots has reviewed the associated sample guidance.
- If the Standby Instruments is inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance.
- The Wing Anti-Ice switch position that differs from the expected state requires the First Officer to select the condition unless directed otherwise by the Sample Operations Center.
- The Cockpit Voice Recorder quantity display is expected to read within the sample range of 94 to 105 units during climb.

| Condition                            | Sample value | Remarks       |
|--------------------------------------|--------------|---------------|
| Primary Electrical Bus indication    | 4 units      | Advisory only |
| Hydraulic System B selector position | 65 units     | Advisory only |
| Wing Anti-Ice advisory               | 84 units     | Monitor       |

### 10.20.10 Auxiliary Power Unit Indications

During an extended ground delay, the Captain should confirm the Autothrottle annunciation if a discrepancy is observed. The Thrust Reverser annunciation that differs from the expected state requires the Captain to select the condition if a discrepancy is observed. Refer to the related topic for additional sample context. The relief pilot will select any change in the Speedbrake Handle quantity display and advise the other pilot if the indication does not stabilize within the sample interval. The Hydraulic System A indication is expected to read within the sample range of 96 to 106 units during parking. Refer to the related topic for additional sample context.

- If the Wing Anti-Ice is inoperative, continue preflight only after the pilot monitoring has reviewed the associated sample guidance.
- The relief pilot will confirm any change in the Autobrake Selector annunciation and advise the other pilot when the associated caution light remains illuminated.
- The captain will record any change in the Weather Radar quantity display and advise the other pilot when operating at a sample station without ground power.

The pilot flying will brief any change in the Flight Management Computer switch position and advise the other pilot before the next phase of flight. If the Standby Instruments is inoperative, continue descent only after both pilots has reviewed the associated sample guidance. The Primary Electrical Bus annunciation is expected to read within the sample range of 2 to 6 units during cruise.

- The Cabin Pressure Controller status message is expected to read within the sample range of 17 to 21 units during taxi.
- The Standby Hydraulic advisory that differs from the expected state requires the pilot monitoring to select the condition when the associated caution light remains illuminated.
- The Nosewheel Steering quantity display that differs from the expected state requires the pilot monitoring to select the condition when the associated caution light remains illuminated.

**CAUTION:** If the Center Tank Pumps is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance.

**CAUTION:** The Standby Instruments annunciation that differs from the expected state requires the pilot flying to brief the condition unless directed otherwise by the Sample Operations Center. During parking, both pilots should monitor the Autopilot Channel B advisory if a discrepancy is observed.

The first officer will verify any change in the Fire Detection Loop switch position and advise the other pilot if the indication does not stabilize within the sample interval. The first officer will cross-check any change in the Primary Electrical Bus selector position and advise the other pilot unless directed otherwise by the Sample Operations Center. The Standby Instruments status message is expected to read within the sample range of 37 to 49 units during a turnaround.

**CAUTION:** The Center Tank Pumps selector position that differs from the expected state requires the pilot monitoring to confirm the condition when operating at a sample station without ground power.

If the Autothrottle is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance. The Hydraulic System B advisory is expected to read within the sample range of 68 to 80 units during a maintenance-requested ground run. If the Nosewheel Steering is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance. The Cockpit Voice Recorder annunciation that differs from the expected state requires the First Officer to record the condition unless directed otherwise by the Sample Operations Center.

**10.20.11 Cockpit Voice Recorder Limits Display**

The wording here is placeholder content shaped like a procedure, not a procedure. During cruise, the First Officer should brief the Flight Management Computer quantity display when conditions permit. The Nosewheel Steering advisory that differs from the expected state requires the pilot monitoring to monitor the condition once the checklist item is complete. During preflight, the Captain should brief the Standby Instruments selector position when the associated caution light remains illuminated. The pilot flying will record any change in the Autobrake Selector selector position and advise the other pilot before the next phase of flight. During a maintenance-requested ground run, the Captain should record the Speedbrake Handle status message before the next phase of flight.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Flap Position Indication quantity display | 33 units     | Normal                 |
| Nosewheel Steering advisory               | 77 units     | Normal                 |
| Cabin Pressure Controller switch position | 17 units     | Monitor                |
| Flap Position Indication advisory         | 83 units     | Refer to related topic |
| Fuel Crossfeed switch position            | 49 units     | Refer to related topic |
| Engine Anti-Ice indication                | 52 units     | Normal                 |

The Standby Instruments status message is expected to read within the sample range of 11 to 17 units during a diversion. The Standby Instruments annunciation is expected to read within the sample range of 29 to 32 units during engine start. If the Autopilot Channel B is inoperative, continue climb only after the First Officer has reviewed the associated sample guidance. During climb, the relief pilot should confirm the Nosewheel Steering indication if a discrepancy is observed. The Hydraulic System B advisory is expected to read within the sample range of 17 to 26

units during an extended ground delay.

**CAUTION:** The Ground Proximity Monitor selector position is expected to read within the sample range of 30 to 38 units during a diversion. During approach, both pilots should record the Fuel Crossfeed annunciation before the next phase of flight.

**NOTE:** The Fuel Crossfeed advisory is expected to read within the sample range of 87 to 95 units during landing.

The Oxygen Distribution selector position is expected to read within the sample range of 54 to 64 units during approach. Refer to the related topic for additional sample context. The relief pilot will verify any change in the Transponder indication and advise the other pilot when conditions permit. The wording here is placeholder content shaped like a procedure, not a procedure.

The relief pilot will confirm any change in the Speedbrake Handle advisory and advise the other pilot if the indication does not stabilize within the sample interval. The wording here is placeholder content shaped like a procedure, not a procedure. The Stall Warning quantity display is expected to read within the sample range of 65 to 68 units during parking. See 10.30.5 Cabin Pressure Controller Limits Display.

- During a maintenance-requested ground run, the pilot monitoring should select the Auxiliary Power Unit advisory if the indication does not stabilize within the sample interval.
- The captain will confirm any change in the Cabin Pressure Controller status message and advise the other pilot when conditions permit.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- During preflight, the Captain should confirm the Autopilot Channel B quantity display when conditions permit.
- During an extended ground delay, the relief pilot should monitor the Cockpit Voice Recorder quantity display if a discrepancy is observed.

**CAUTION:** If the Primary Electrical Bus is inoperative, continue taxi only after the relief pilot has reviewed the associated sample guidance.

**10.20.12 Window Heat Reset Guidance**

During a turnaround, the relief pilot should verify the Hydraulic System B switch position before the next phase of flight. The Ground Proximity Monitor selector position is expected to read within the sample range of 9 to 13 units during approach. The pilot flying will monitor any change in the Window Heat annunciation and advise the other pilot when operating at a sample station without ground power. The Cargo Smoke Detection switch position is expected to read within the sample range of 83 to 86 units during cruise. The wording here is placeholder content shaped like a procedure, not a procedure. The Weather Radar indication that differs from the expected state requires the pilot monitoring to brief the condition when conditions permit.

**NOTE:** The Landing Gear Indication indication that differs from the expected state requires the Captain to brief the condition when operating at a sample station without ground power.

| Condition                         | Sample value | Remarks       |
|-----------------------------------|--------------|---------------|
| Weather Radar selector position   | 84 units     | Advisory only |
| Weather Radar quantity display    | 29 units     | Normal        |
| Speedbrake Handle switch position | 73 units     | Monitor       |
| Autobrake Selector advisory       | 68 units     | Advisory only |

**NOTE:** If the Speedbrake Handle is inoperative, continue parking only after the Captain has reviewed the associated sample guidance.

- During approach, the pilot monitoring should select the Engine Anti-Ice switch position when the associated caution light remains illuminated.

- Refer to the related topic for additional sample context.
- Refer to the related topic for additional sample context.

### 10.20.13 Window Heat Test

The Hydraulic System B annunciation is expected to read within the sample range of 51 to 57 units during climb. If the Speedbrake Handle is inoperative, continue cruise only after the First Officer has reviewed the associated sample guidance. Refer to the related topic for additional sample context.

**CAUTION:** The captain will monitor any change in the Nosewheel Steering indication and advise the other pilot if the indication does not stabilize within the sample interval.

During landing, both pilots should announce the Primary Electrical Bus status message when the associated caution light remains illuminated. The Autopilot Channel A switch position is expected to read within the sample range of 24 to 35 units during a diversion. If the Engine Anti-Ice is inoperative, continue landing only after both pilots has reviewed the associated sample guidance.

**CAUTION:** The Autothrottle indication that differs from the expected state requires the Captain to announce the condition if the indication does not stabilize within the sample interval. If the Cabin Pressure Controller is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance.

The Primary Electrical Bus quantity display is expected to read within the sample range of 61 to 65 units during engine start. The pilot flying will announce any change in the Probe Heat quantity display and advise the other pilot before the next phase of flight. If the Pack Temperature Control is inoperative, continue landing only after the relief pilot has reviewed the associated sample guidance. The Wing Anti-Ice selector position is expected to read within the sample range of 8 to 18 units during landing. The wording here is placeholder content shaped like a procedure, not a procedure. The Brake Temperature Monitor selector position is expected to read within the sample range of 68 to 76 units during climb.

**NOTE:** During an extended ground delay, the relief pilot should verify the Flight Management Computer advisory when conditions permit. The relief pilot will brief any change in the Hydraulic System B advisory and advise the other pilot when the associated caution light remains illuminated.

- The Autopilot Channel B advisory that differs from the expected state requires the relief pilot to announce the condition before the next phase of flight.
- The first officer will confirm any change in the Primary Electrical Bus status message and advise the other pilot if the indication does not stabilize within the sample interval.
- During landing, the pilot flying should confirm the Ground Proximity Monitor selector position when conditions permit.

**CAUTION:** The Weather Radar indication that differs from the expected state requires the relief pilot to cross-check the condition if the indication does not stabilize within the sample interval. This text is fictional and exists only to give the prototype realistic volume and structure.

### 10.20.14 Hydraulic System B Power Sources

The Hydraulic System A advisory is expected to read within the sample range of 55 to 60 units during cruise. During climb, both pilots should verify the Bleed Air Supply quantity display when the associated caution light remains illuminated. During landing, the pilot flying should verify the Cockpit Voice Recorder selector position unless directed otherwise by the Sample Operations Center.

The Oxygen Distribution advisory is expected to read within the sample range of 91 to 99 units during a turnaround. Values in this manual are invented and must not be used for any operational purpose. The Autothrottle indication that differs from the expected state requires the relief pilot to confirm the condition when operating at a sample station without ground power. If the Nosewheel Steering is inoperative, continue descent only after both pilots has reviewed the associated sample guidance.



- The wording here is placeholder content shaped like a procedure, not a procedure.
- If the Ground Proximity Monitor is inoperative, continue a turnaround only after both pilots has reviewed the associated sample guidance.
- Values in this manual are invented and must not be used for any operational purpose.
- During parking, the relief pilot should cross-check the Transponder quantity display before the next phase of flight.
- During preflight, the relief pilot should cross-check the Standby Instruments selector position before the next phase of flight.

**CAUTION:** The Speedbrake Handle indication that differs from the expected state requires the Captain to monitor the condition if the indication does not stabilize within the sample interval.

**NOTE:** The Ground Proximity Monitor annunciation is expected to read within the sample range of 64 to 72 units during a turnaround. The Flight Management Computer status message that differs from the expected state requires the relief pilot to record the condition before the next phase of flight.

- The Cockpit Voice Recorder indication is expected to read within the sample range of 80 to 91 units during a maintenance-requested ground run.
- The Autothrottle indication that differs from the expected state requires the First Officer to record the condition before the next phase of flight.
- The Ground Proximity Monitor selector position is expected to read within the sample range of 86 to 98 units during takeoff.

### 10.20.15 *Oxygen Distribution Crew Awareness*

During landing, the pilot flying should record the Nosewheel Steering indication if the indication does not stabilize within the sample interval. During a turnaround, the pilot flying should brief the Cabin Pressure Controller quantity display when conditions permit. Values in this manual are invented and must not be used for any operational purpose.

- The Traffic Advisory Display quantity display is expected to read within the sample range of 87 to 94 units during climb.
- The Autopilot Channel B status message that differs from the expected state requires both pilots to confirm the condition when the associated caution light remains illuminated.
- The Landing Gear Indication annunciation is expected to read within the sample range of 7 to 15 units during landing.
- If the Window Heat is inoperative, continue landing only after the pilot monitoring has reviewed the associated sample guidance.

The Hydraulic System B annunciation is expected to read within the sample range of 47 to 59 units during a turnaround. The captain will record any change in the Fire Detection Loop annunciation and advise the other pilot if the indication does not stabilize within the sample interval. The Landing Gear Indication indication is expected to read within the sample range of 13 to 21 units during engine start. The captain will monitor any change in the Auxiliary Power Unit indication and advise the other pilot if the indication does not stabilize within the sample interval. The Flap Position Indication advisory is expected to read within the sample range of 55 to 62 units during descent.

If the Primary Electrical Bus is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance. Refer to the related topic for additional sample context. The pilot monitoring will verify any change in the Wing Anti-Ice indication and advise the other pilot once the checklist item is complete.

The Bleed Air Supply quantity display that differs from the expected state requires the First Officer to brief the condition when conditions permit. The Thrust Reverser switch position that differs from the expected state requires the pilot flying to select the condition when the associated caution light remains illuminated. If the Traffic Advisory

Display is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance. The Flight Management Computer switch position that differs from the expected state requires both pilots to monitor the condition if the indication does not stabilize within the sample interval. The pilot flying will confirm any change in the Ground Proximity Monitor selector position and advise the other pilot when the associated caution light remains illuminated.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Probe Heat advisory                       | 47 units     | Monitor                |
| Nosewheel Steering quantity display       | 77 units     | Refer to related topic |
| Standby Hydraulic quantity display        | 82 units     | Refer to related topic |
| Oxygen Distribution status message        | 26 units     | Advisory only          |
| Auxiliary Power Unit status message       | 21 units     | Normal                 |
| Cabin Pressure Controller advisory        | 56 units     | Normal                 |
| Flight Management Computer status message | 67 units     | Normal                 |

The first officer will announce any change in the Hydraulic System B indication and advise the other pilot if the indication does not stabilize within the sample interval. Both pilots will select any change in the Speedbrake Handle indication and advise the other pilot if the indication does not stabilize within the sample interval. Values in this manual are invented and must not be used for any operational purpose.

During engine start, the Captain should verify the Traffic Advisory Display advisory unless directed otherwise by the Sample Operations Center. During parking, the relief pilot should select the Auxiliary Power Unit indication unless directed otherwise by the Sample Operations Center. The Oxygen Distribution indication that differs from the expected state requires the pilot monitoring to monitor the condition before the next phase of flight. See 04.10.20 Checklist: Oxygen Distribution.

### 10.20.16 Brake Temperature Monitor Test

The Fire Detection Loop switch position that differs from the expected state requires the Captain to brief the condition unless directed otherwise by the Sample Operations Center. This text is fictional and exists only to give the prototype realistic volume and structure. The first officer will record any change in the Brake Temperature Monitor status message and advise the other pilot if a discrepancy is observed. The Oxygen Distribution quantity display that differs from the expected state requires both pilots to record the condition unless directed otherwise by the Sample Operations Center. During engine start, the First Officer should confirm the Fuel Crossfeed selector position when conditions permit.

**NOTE:** The Thrust Reverser status message that differs from the expected state requires the Captain to monitor the condition before the next phase of flight.

**CAUTION:** The Cabin Pressure Controller advisory that differs from the expected state requires the pilot monitoring to announce the condition when the associated caution light remains illuminated.

If the Primary Electrical Bus is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance. If the Brake Temperature Monitor is inoperative, continue taxi only after the First Officer has reviewed the associated sample guidance. If the Autopilot Channel B is inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance. If the Fire Detection Loop is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance. If the Flight Management Computer is inoperative, continue climb only after the pilot flying has reviewed the associated sample guidance.

The relief pilot will announce any change in the Weather Radar switch position and advise the other pilot if a discrepancy is observed. The Fuel Crossfeed switch position that differs from the expected state requires the relief pilot to announce the condition before the next phase of flight. If the Cargo Smoke Detection is inoperative, continue taxi only after the relief pilot has reviewed the associated sample guidance. The Stall Warning advisory is expected to read within the sample range of 32 to 42 units during cruise. The Fuel Crossfeed advisory is expected to read within

the sample range of 80 to 90 units during a turnaround.

- The Flap Position Indication advisory is expected to read within the sample range of 65 to 68 units during cruise.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- Values in this manual are invented and must not be used for any operational purpose.
- The Cockpit Voice Recorder quantity display is expected to read within the sample range of 6 to 12 units during landing.
- If the Cargo Smoke Detection is inoperative, continue climb only after both pilots has reviewed the associated sample guidance.
- The first officer will select any change in the Traffic Advisory Display status message and advise the other pilot when the associated caution light remains illuminated.

The Hydraulic System A switch position that differs from the expected state requires the relief pilot to cross-check the condition unless directed otherwise by the Sample Operations Center. The Wing Anti-Ice annunciation is expected to read within the sample range of 31 to 36 units during an extended ground delay. If the Nosewheel Steering is inoperative, continue climb only after the Captain has reviewed the associated sample guidance.

**NOTE:** Both pilots will verify any change in the Thrust Reverser indication and advise the other pilot when conditions permit. During an extended ground delay, the pilot flying should select the Hydraulic System B annunciation when operating at a sample station without ground power.

The relief pilot will brief any change in the Standby Instruments status message and advise the other pilot if a discrepancy is observed. The Engine Anti-Ice indication that differs from the expected state requires the relief pilot to brief the condition before the next phase of flight. The Auxiliary Power Unit annunciation that differs from the expected state requires the pilot monitoring to record the condition if the indication does not stabilize within the sample interval. The Wing Anti-Ice switch position that differs from the expected state requires the pilot monitoring to cross-check the condition when the associated caution light remains illuminated. Both pilots will record any change in the Probe Heat switch position and advise the other pilot before the next phase of flight.

## 10.30 Operation

### 10.30.1 Ground Proximity Monitor Limits Display

If the Flight Management Computer is inoperative, continue taxi only after the Captain has reviewed the associated sample guidance. If the Transponder is inoperative, continue parking only after the pilot monitoring has reviewed the associated sample guidance. Refer to the related topic for additional sample context. The Weather Radar selector position is expected to read within the sample range of 71 to 83 units during a turnaround. Refer to the related topic for additional sample context. If the Cargo Smoke Detection is inoperative, continue a turnaround only after the First Officer has reviewed the associated sample guidance.

The Speedbrake Handle switch position is expected to read within the sample range of 40 to 50 units during engine start. The Pack Temperature Control annunciation is expected to read within the sample range of 80 to 87 units during a maintenance-requested ground run. Refer to the related topic for additional sample context. The relief pilot will cross-check any change in the Flight Management Computer indication and advise the other pilot when conditions permit. If the Autopilot Channel A is inoperative, continue cruise only after the First Officer has reviewed the associated sample guidance.

- The Thrust Reverser status message that differs from the expected state requires the pilot flying to announce the condition before the next phase of flight.
- The Speedbrake Handle selector position is expected to read within the sample range of 34 to 38 units during cruise.

- If the Window Heat is inoperative, continue a maintenance-requested ground run only after the pilot flying has reviewed the associated sample guidance.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Autothrottle selector position          | 80 units     | Monitor                |
| Fuel Crossfeed quantity display         | 58 units     | Advisory only          |
| Cabin Pressure Controller advisory      | 56 units     | Refer to related topic |
| Pack Temperature Control status message | 33 units     | Advisory only          |
| Standby Instruments switch position     | 12 units     | Advisory only          |
| Cargo Smoke Detection switch position   | 35 units     | Advisory only          |
| Pack Temperature Control status message | 1 units      | Monitor                |

The Center Tank Pumps quantity display that differs from the expected state requires the First Officer to monitor the condition unless directed otherwise by the Sample Operations Center. This text is fictional and exists only to give the prototype realistic volume and structure. The Traffic Advisory Display selector position is expected to read within the sample range of 16 to 23 units during preflight. The Traffic Advisory Display indication that differs from the expected state requires the Captain to announce the condition when operating at a sample station without ground power. The Fuel Crossfeed quantity display is expected to read within the sample range of 28 to 34 units during approach.

If the Window Heat is inoperative, continue taxi only after the pilot flying has reviewed the associated sample guidance. During climb, the relief pilot should select the Autothrottle indication if a discrepancy is observed. The wording here is placeholder content shaped like a procedure, not a procedure. Both pilots will announce any change in the Stall Warning selector position and advise the other pilot when the associated caution light remains illuminated.

**NOTE:** If the Bleed Air Supply is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance.

If the Autopilot Channel A is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance. The relief pilot will confirm any change in the Autothrottle indication and advise the other pilot once the checklist item is complete. The Stall Warning quantity display is expected to read within the sample range of 54 to 61 units during preflight. If the Landing Gear Indication is inoperative, continue a diversion only after the First Officer has reviewed the associated sample guidance. During parking, the pilot monitoring should monitor the Autothrottle quantity display if a discrepancy is observed. During climb, the relief pilot should verify the Cabin Pressure Controller annunciation if the indication does not stabilize within the sample interval.

The Traffic Advisory Display indication is expected to read within the sample range of 64 to 74 units during a diversion. During landing, the Captain should brief the Standby Instruments annunciation before the next phase of flight. This text is fictional and exists only to give the prototype realistic volume and structure. The Engine Anti-Ice annunciation is expected to read within the sample range of 7 to 15 units during a diversion.

**10.30.2 Wing Anti-Ice Reset Guidance**

During climb, the pilot monitoring should confirm the Stall Warning status message unless directed otherwise by the Sample Operations Center. During taxi, the pilot monitoring should verify the Autopilot Channel A quantity display before the next phase of flight. This text is fictional and exists only to give the prototype realistic volume and structure. The captain will select any change in the Cabin Pressure Controller selector position and advise the other pilot once the checklist item is complete. The Fire Detection Loop annunciation is expected to read within the sample range of 6 to 10 units during cruise.

**CAUTION:** If the Stall Warning is inoperative, continue approach only after both pilots has reviewed the associated sample guidance.

**NOTE:** The Autobrake Selector status message that differs from the expected state requires both pilots to confirm the condition when the associated caution light remains illuminated.

The Cockpit Voice Recorder switch position is expected to read within the sample range of 47 to 59 units during takeoff. The first officer will verify any change in the Autopilot Channel A switch position and advise the other pilot if the indication does not stabilize within the sample interval. The Center Tank Pumps quantity display is expected to read within the sample range of 58 to 68 units during preflight. Both pilots will announce any change in the Fire Detection Loop status message and advise the other pilot when the associated caution light remains illuminated.

**CAUTION:** Refer to the related topic for additional sample context.

The captain will brief any change in the Autopilot Channel B advisory and advise the other pilot when conditions permit. The Ground Proximity Monitor indication that differs from the expected state requires the pilot monitoring to announce the condition if a discrepancy is observed. During engine start, both pilots should record the Window Heat selector position if a discrepancy is observed.

- Refer to the related topic for additional sample context.
- The Auxiliary Power Unit selector position is expected to read within the sample range of 66 to 72 units during landing.
- The Fuel Crossfeed quantity display that differs from the expected state requires the relief pilot to verify the condition when conditions permit.

**10.30.3 Autothrottle Power Sources**

During an extended ground delay, both pilots should select the Stall Warning quantity display before the next phase of flight. Refer to the related topic for additional sample context. Refer to the related topic for additional sample context.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Brake Temperature Monitor annunciation     | 83 units     | Refer to related topic |
| Fuel Crossfeed status message              | 70 units     | Refer to related topic |
| Ground Proximity Monitor selector position | 61 units     | Normal                 |
| Autopilot Channel B advisory               | 86 units     | Refer to related topic |

**CAUTION:** During preflight, the pilot monitoring should verify the Flap Position Indication status message if a discrepancy is observed. This text is fictional and exists only to give the prototype realistic volume and structure. The Probe Heat status message that differs from the expected state requires the relief pilot to brief the condition if a discrepancy is observed.

**CAUTION:** The wording here is placeholder content shaped like a procedure, not a procedure.

| Condition                          | Sample value | Remarks                |
|------------------------------------|--------------|------------------------|
| Nosewheel Steering indication      | 54 units     | Refer to related topic |
| Auxiliary Power Unit annunciation  | 21 units     | Refer to related topic |
| Standby Instruments status message | 44 units     | Monitor                |

The Landing Gear Indication selector position that differs from the expected state requires the pilot monitoring to verify the condition if the indication does not stabilize within the sample interval. The pilot flying will select any change in the Nosewheel Steering annunciation and advise the other pilot when conditions permit. Refer to the related topic for additional sample context. The Standby Hydraulic advisory is expected to read within the sample range of 39 to 46 units during an extended ground delay. During takeoff, the pilot flying should select the Window Heat advisory if the indication does not stabilize within the sample interval. The wording here is placeholder content shaped like a procedure, not a procedure.

**10.30.4 Hydraulic System B Status Messages**

If the Cargo Smoke Detection is inoperative, continue descent only after the First Officer has reviewed the associated sample guidance. The relief pilot will brief any change in the Hydraulic System B selector position and advise the other pilot when conditions permit. The captain will confirm any change in the Nosewheel Steering switch position and advise the other pilot when operating at a sample station without ground power. The Bleed Air Supply indication that differs from the expected state requires the pilot flying to brief the condition if a discrepancy is observed. The first officer will brief any change in the Flight Management Computer indication and advise the other pilot unless directed otherwise by the Sample Operations Center.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Fire Detection Loop status message         | 8 units      | Monitor                |
| Oxygen Distribution selector position      | 58 units     | Refer to related topic |
| Pack Temperature Control indication        | 78 units     | Monitor                |
| Autobrake Selector advisory                | 65 units     | Refer to related topic |
| Standby Instruments switch position        | 92 units     | Advisory only          |
| Ground Proximity Monitor selector position | 24 units     | Advisory only          |
| Speedbrake Handle indication               | 46 units     | Refer to related topic |

**NOTE:** The first officer will record any change in the Transponder quantity display and advise the other pilot if a discrepancy is observed. The Cargo Smoke Detection status message is expected to read within the sample range of 64 to 75 units during a diversion.

**CAUTION:** If the Cabin Pressure Controller is inoperative, continue climb only after the pilot flying has reviewed the associated sample guidance.

**CAUTION:** During a turnaround, the First Officer should verify the Auxiliary Power Unit advisory before the next phase of flight. During a turnaround, the pilot monitoring should confirm the Thrust Reverser status message unless directed otherwise by the Sample Operations Center.

If the Autopilot Channel B is inoperative, continue a diversion only after the relief pilot has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. The pilot flying will record any change in the Center Tank Pumps advisory and advise the other pilot once the checklist item is complete. This text is fictional and exists only to give the prototype realistic volume and structure. The Cabin Pressure Controller indication that differs from the expected state requires the pilot monitoring to confirm the condition if the indication does not stabilize within the sample interval. The Fire Detection Loop selector position is expected to read within the sample range of 16 to 24 units during cruise.

Refer to the related topic for additional sample context. The captain will announce any change in the Hydraulic System B indication and advise the other pilot when the associated caution light remains illuminated. During descent, the Captain should monitor the Oxygen Distribution indication before the next phase of flight. This text is fictional and exists only to give the prototype realistic volume and structure.

10.30.5 Cabin Pressure Controller Limits Display

The Autopilot Channel B selector position is expected to read within the sample range of 63 to 70 units during descent. The relief pilot will announce any change in the Fire Detection Loop status message and advise the other pilot before the next phase of flight. The relief pilot will confirm any change in the Speedbrake Handle switch position and advise the other pilot if the indication does not stabilize within the sample interval. During engine start, the Captain should record the Probe Heat annunciation when conditions permit.

**CAUTION:** If the Window Heat is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose.

| Condition | Sample value | Remarks |
|-----------|--------------|---------|
|-----------|--------------|---------|



|                                           |          |                        |
|-------------------------------------------|----------|------------------------|
| Probe Heat annunciation                   | 43 units | Refer to related topic |
| Traffic Advisory Display quantity display | 23 units | Normal                 |
| Stall Warning quantity display            | 74 units | Normal                 |
| Autothrottle selector position            | 10 units | Advisory only          |
| Fire Detection Loop annunciation          | 61 units | Refer to related topic |

- If the Brake Temperature Monitor is inoperative, continue engine start only after the pilot monitoring has reviewed the associated sample guidance.
- If the Weather Radar is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance.
- The pilot flying will confirm any change in the Flight Management Computer advisory and advise the other pilot if the indication does not stabilize within the sample interval.

**NOTE:** The Flap Position Indication status message is expected to read within the sample range of 40 to 50 units during cruise.

- The Brake Temperature Monitor switch position is expected to read within the sample range of 41 to 53 units during a turnaround.
- The Ground Proximity Monitor indication that differs from the expected state requires the First Officer to monitor the condition if the indication does not stabilize within the sample interval.
- During descent, both pilots should select the Weather Radar selector position when conditions permit.

The Autobrake Selector selector position is expected to read within the sample range of 34 to 42 units during approach. Refer to the related topic for additional sample context. Both pilots will verify any change in the Brake Temperature Monitor selector position and advise the other pilot once the checklist item is complete. The pilot monitoring will confirm any change in the Window Heat advisory and advise the other pilot when conditions permit. If the Wing Anti-Ice is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance. The Oxygen Distribution quantity display that differs from the expected state requires the pilot monitoring to select the condition unless directed otherwise by the Sample Operations Center. See 05.40.20 Stall Warning Indications.

**CAUTION:** The wording here is placeholder content shaped like a procedure, not a procedure. If the Oxygen Distribution is inoperative, continue climb only after the Captain has reviewed the associated sample guidance.

### 10.30.6 Fire Detection Loop Overview

The Transponder switch position is expected to read within the sample range of 89 to 95 units during a diversion. The pilot flying will cross-check any change in the Window Heat indication and advise the other pilot if a discrepancy is observed. Refer to the related topic for additional sample context. The Standby Hydraulic advisory that differs from the expected state requires the First Officer to monitor the condition unless directed otherwise by the Sample Operations Center.

Refer to the related topic for additional sample context. The Standby Instruments selector position that differs from the expected state requires the pilot flying to confirm the condition if the indication does not stabilize within the sample interval. This text is fictional and exists only to give the prototype realistic volume and structure. The Probe Heat selector position that differs from the expected state requires the First Officer to confirm the condition once the checklist item is complete. Values in this manual are invented and must not be used for any operational purpose.

- The Cargo Smoke Detection advisory that differs from the expected state requires both pilots to record the condition when operating at a sample station without ground power.
- During approach, the First Officer should select the Brake Temperature Monitor status message if the indication does not stabilize within the sample interval.

- The wording here is placeholder content shaped like a procedure, not a procedure.
- If the Cockpit Voice Recorder is inoperative, continue preflight only after the Captain has reviewed the associated sample guidance.
- If the Primary Electrical Bus is inoperative, continue engine start only after the pilot flying has reviewed the associated sample guidance.

The Standby Hydraulic advisory is expected to read within the sample range of 14 to 21 units during an extended ground delay. The Hydraulic System A advisory that differs from the expected state requires the First Officer to record the condition unless directed otherwise by the Sample Operations Center. The Autobrake Selector quantity display is expected to read within the sample range of 43 to 55 units during parking. This text is fictional and exists only to give the prototype realistic volume and structure.

During climb, the relief pilot should announce the Stall Warning switch position if a discrepancy is observed. The Flight Management Computer annunciation is expected to read within the sample range of 53 to 58 units during engine start. During cruise, the pilot monitoring should monitor the Standby Instruments advisory if the indication does not stabilize within the sample interval. The Speedbrake Handle switch position is expected to read within the sample range of 19 to 26 units during a maintenance-requested ground run. Values in this manual are invented and must not be used for any operational purpose. Values in this manual are invented and must not be used for any operational purpose.

Refer to the related topic for additional sample context. Values in this manual are invented and must not be used for any operational purpose. The Weather Radar annunciation is expected to read within the sample range of 66 to 72 units during preflight. If the Cargo Smoke Detection is inoperative, continue approach only after the pilot flying has reviewed the associated sample guidance.

| Condition                                    | Sample value | Remarks       |
|----------------------------------------------|--------------|---------------|
| Flight Management Computer selector position | 75 units     | Advisory only |
| Auxiliary Power Unit quantity display        | 80 units     | Advisory only |
| Brake Temperature Monitor annunciation       | 44 units     | Advisory only |
| Autobrake Selector indication                | 28 units     | Normal        |

The Nosewheel Steering status message is expected to read within the sample range of 79 to 83 units during takeoff. The Speedbrake Handle switch position that differs from the expected state requires the pilot monitoring to confirm the condition when the associated caution light remains illuminated. The wording here is placeholder content shaped like a procedure, not a procedure. Refer to the related topic for additional sample context. The Weather Radar advisory is expected to read within the sample range of 31 to 42 units during climb.

**10.30.7 Standby Instruments Status Messages**

The wording here is placeholder content shaped like a procedure, not a procedure. The pilot monitoring will monitor any change in the Fuel Crossfeed indication and advise the other pilot unless directed otherwise by the Sample Operations Center. Values in this manual are invented and must not be used for any operational purpose. During takeoff, the pilot flying should monitor the Flap Position Indication advisory unless directed otherwise by the Sample Operations Center. If the Pack Temperature Control is inoperative, continue landing only after the Captain has reviewed the associated sample guidance.

- The Ground Proximity Monitor indication that differs from the expected state requires the pilot flying to announce the condition unless directed otherwise by the Sample Operations Center.
- The Wing Anti-Ice status message that differs from the expected state requires the pilot flying to confirm the condition when the associated caution light remains illuminated.
- The Standby Instruments annunciation is expected to read within the sample range of 88 to 91 units during descent.

- During approach, the pilot monitoring should announce the Cockpit Voice Recorder quantity display once the checklist item is complete.
- Values in this manual are invented and must not be used for any operational purpose.
- The Ground Proximity Monitor status message that differs from the expected state requires the pilot flying to brief the condition unless directed otherwise by the Sample Operations Center.

**NOTE:** During preflight, both pilots should brief the Standby Instruments status message when operating at a sample station without ground power. The wording here is placeholder content shaped like a procedure, not a procedure.

The Weather Radar status message that differs from the expected state requires both pilots to cross-check the condition if the indication does not stabilize within the sample interval. The captain will select any change in the Flight Management Computer annunciation and advise the other pilot if the indication does not stabilize within the sample interval. If the Oxygen Distribution is inoperative, continue climb only after the relief pilot has reviewed the associated sample guidance. The Center Tank Pumps indication is expected to read within the sample range of 97 to 109 units during parking. The Hydraulic System A advisory is expected to read within the sample range of 40 to 51 units during an extended ground delay. If the Traffic Advisory Display is inoperative, continue engine start only after the pilot monitoring has reviewed the associated sample guidance.

| Condition                                    | Sample value | Remarks                |
|----------------------------------------------|--------------|------------------------|
| Pack Temperature Control quantity display    | 79 units     | Monitor                |
| Fire Detection Loop status message           | 18 units     | Normal                 |
| Primary Electrical Bus annunciation          | 80 units     | Monitor                |
| Window Heat indication                       | 11 units     | Advisory only          |
| Flight Management Computer selector position | 91 units     | Refer to related topic |

If the Window Heat is inoperative, continue climb only after both pilots has reviewed the associated sample guidance. The Standby Hydraulic annunciation is expected to read within the sample range of 64 to 76 units during a turnaround. The Weather Radar annunciation that differs from the expected state requires both pilots to record the condition when conditions permit. During landing, the First Officer should record the Ground Proximity Monitor quantity display when conditions permit.

- The Window Heat annunciation is expected to read within the sample range of 71 to 75 units during preflight.
- The Transponder switch position is expected to read within the sample range of 41 to 44 units during engine start.
- The pilot monitoring will record any change in the Thrust Reverser quantity display and advise the other pilot when the associated caution light remains illuminated.
- The Flight Management Computer annunciation is expected to read within the sample range of 53 to 64 units during preflight.
- The pilot flying will cross-check any change in the Brake Temperature Monitor selector position and advise the other pilot when conditions permit.
- If the Autobrake Selector is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance.

Refer to the related topic for additional sample context. The wording here is placeholder content shaped like a procedure, not a procedure. The Autobrake Selector annunciation that differs from the expected state requires the Captain to select the condition if the indication does not stabilize within the sample interval. The Probe Heat annunciation is expected to read within the sample range of 60 to 68 units during takeoff. Values in this manual are invented and must not be used for any operational purpose.

The Standby Instruments annunciation is expected to read within the sample range of 71 to 74 units during an extended ground delay. The Probe Heat advisory is expected to read within the sample range of 84 to 95 units during an extended ground delay. The Nosewheel Steering annunciation that differs from the expected state requires the Captain to record the condition when conditions permit. If the Cabin Pressure Controller is inoperative, continue an extended ground delay only after the pilot flying has reviewed the associated sample guidance. If the Stall Warning is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance.

**10.30.8 Center Tank Pumps Interfaces**

The Speedbrake Handle selector position is expected to read within the sample range of 31 to 43 units during parking. The Standby Hydraulic advisory that differs from the expected state requires the pilot monitoring to cross-check the condition when operating at a sample station without ground power. The relief pilot will cross-check any change in the Autopilot Channel B selector position and advise the other pilot when the associated caution light remains illuminated. The pilot monitoring will cross-check any change in the Brake Temperature Monitor annunciation and advise the other pilot when conditions permit. The Standby Instruments quantity display that differs from the expected state requires the Captain to monitor the condition when operating at a sample station without ground power.

If the Transponder is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance. The Transponder selector position that differs from the expected state requires the First Officer to verify the condition if a discrepancy is observed. If the Oxygen Distribution is inoperative, continue parking only after the relief pilot has reviewed the associated sample guidance.

The Oxygen Distribution selector position is expected to read within the sample range of 88 to 92 units during takeoff. The Weather Radar status message that differs from the expected state requires the First Officer to record the condition if the indication does not stabilize within the sample interval. During taxi, the First Officer should confirm the Hydraulic System B advisory once the checklist item is complete.

The Engine Anti-Ice annunciation that differs from the expected state requires the relief pilot to select the condition if a discrepancy is observed. During cruise, both pilots should cross-check the Standby Instruments advisory if a discrepancy is observed. The Standby Hydraulic quantity display is expected to read within the sample range of 52 to 58 units during an extended ground delay. The Fuel Crossfeed selector position that differs from the expected state requires the pilot flying to announce the condition when operating at a sample station without ground power. The first officer will verify any change in the Flap Position Indication advisory and advise the other pilot if the indication does not stabilize within the sample interval. The first officer will confirm any change in the Autopilot Channel A indication and advise the other pilot before the next phase of flight.

Values in this manual are invented and must not be used for any operational purpose. Both pilots will verify any change in the Thrust Reverser selector position and advise the other pilot when the associated caution light remains illuminated. During takeoff, the pilot flying should monitor the Flight Management Computer selector position if a discrepancy is observed. During a maintenance-requested ground run, the Captain should monitor the Primary Electrical Bus advisory when the associated caution light remains illuminated. The Auxiliary Power Unit annunciation that differs from the expected state requires the pilot monitoring to record the condition when operating at a sample station without ground power.

| Condition                                 | Sample value | Remarks       |
|-------------------------------------------|--------------|---------------|
| Autobrake Selector selector position      | 21 units     | Normal        |
| Traffic Advisory Display indication       | 25 units     | Advisory only |
| Cabin Pressure Controller switch position | 39 units     | Monitor       |
| Pack Temperature Control indication       | 88 units     | Advisory only |
| Flap Position Indication advisory         | 29 units     | Monitor       |
| Nosewheel Steering quantity display       | 10 units     | Normal        |
| Brake Temperature Monitor advisory        | 77 units     | Monitor       |

The wording here is placeholder content shaped like a procedure, not a procedure. This text is fictional and exists only to give the prototype realistic volume and structure. Both pilots will confirm any change in the Engine Anti-Ice advisory and advise the other pilot before the next phase of flight. Refer to the related topic for additional sample context. The Auxiliary Power Unit switch position that differs from the expected state requires the relief pilot to record the condition when conditions permit. The Cargo Smoke Detection advisory is expected to read within the sample range of 80 to 85 units during descent.

**10.30.9 Landing Gear Indication Crew Awareness**

Values in this manual are invented and must not be used for any operational purpose. During an extended ground delay, the relief pilot should confirm the Window Heat switch position when operating at a sample station without ground power. The Hydraulic System B advisory is expected to read within the sample range of 61 to 64 units during engine start. During an extended ground delay, the pilot monitoring should select the Cockpit Voice Recorder switch position if a discrepancy is observed. During takeoff, the relief pilot should announce the Nosewheel Steering indication when operating at a sample station without ground power.

The Autopilot Channel A annunciation that differs from the expected state requires the First Officer to cross-check the condition when the associated caution light remains illuminated. The Center Tank Pumps annunciation that differs from the expected state requires the Captain to monitor the condition before the next phase of flight. The Thrust Reverser status message is expected to read within the sample range of 94 to 98 units during engine start. The Autothrottle status message that differs from the expected state requires the relief pilot to record the condition when conditions permit.

If the Center Tank Pumps is inoperative, continue engine start only after the pilot flying has reviewed the associated sample guidance. If the Hydraulic System B is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance. The Speedbrake Handle selector position is expected to read within the sample range of 47 to 57 units during taxi. If the Primary Electrical Bus is inoperative, continue taxi only after the pilot flying has reviewed the associated sample guidance.

During cruise, the pilot flying should monitor the Speedbrake Handle selector position before the next phase of flight. The Autothrottle indication is expected to read within the sample range of 33 to 41 units during takeoff. The Landing Gear Indication selector position is expected to read within the sample range of 42 to 54 units during climb. Refer to the related topic for additional sample context. This text is fictional and exists only to give the prototype realistic volume and structure.

Values in this manual are invented and must not be used for any operational purpose. The pilot flying will verify any change in the Traffic Advisory Display advisory and advise the other pilot once the checklist item is complete. The Oxygen Distribution selector position is expected to read within the sample range of 76 to 86 units during engine start. The Engine Anti-Ice switch position is expected to read within the sample range of 42 to 47 units during taxi. The Window Heat status message is expected to read within the sample range of 72 to 84 units during cruise.

**NOTE:** Refer to the related topic for additional sample context.

The Nosewheel Steering annunciation is expected to read within the sample range of 76 to 88 units during engine start. The pilot monitoring will cross-check any change in the Ground Proximity Monitor status message and advise the other pilot once the checklist item is complete. During taxi, the pilot flying should brief the Flap Position Indication switch position when operating at a sample station without ground power. The Window Heat quantity display that differs from the expected state requires both pilots to record the condition when operating at a sample station without ground power. The wording here is placeholder content shaped like a procedure, not a procedure.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Autobrake Selector selector position       | 26 units     | Monitor                |
| Transponder switch position                | 87 units     | Advisory only          |
| Ground Proximity Monitor selector position | 86 units     | Advisory only          |
| Autobrake Selector selector position       | 10 units     | Refer to related topic |

|                                     |          |               |
|-------------------------------------|----------|---------------|
| Transponder selector position       | 43 units | Normal        |
| Fire Detection Loop switch position | 69 units | Advisory only |

- If the Standby Hydraulic is inoperative, continue engine start only after the relief pilot has reviewed the associated sample guidance.
- During cruise, the First Officer should cross-check the Ground Proximity Monitor indication unless directed otherwise by the Sample Operations Center.
- During parking, both pilots should brief the Nosewheel Steering quantity display if the indication does not stabilize within the sample interval.

10.30.10 *Nosewheel Steering Power Sources*

The Hydraulic System A status message is expected to read within the sample range of 82 to 85 units during a maintenance-requested ground run. The wording here is placeholder content shaped like a procedure, not a procedure. If the Autobrake Selector is inoperative, continue climb only after the relief pilot has reviewed the associated sample guidance. The Weather Radar switch position is expected to read within the sample range of 16 to 25 units during a maintenance-requested ground run. If the Landing Gear Indication is inoperative, continue taxi only after the Captain has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure.

| Condition                             | Sample value | Remarks       |
|---------------------------------------|--------------|---------------|
| Hydraulic System B annunciation       | 49 units     | Normal        |
| Speedbrake Handle annunciation        | 67 units     | Advisory only |
| Probe Heat indication                 | 64 units     | Monitor       |
| Pack Temperature Control annunciation | 39 units     | Advisory only |

If the Transponder is inoperative, continue parking only after the Captain has reviewed the associated sample guidance. The Thrust Reverser selector position that differs from the expected state requires both pilots to select the condition once the checklist item is complete. The Window Heat quantity display is expected to read within the sample range of 5 to 11 units during climb. The Fuel Crossfeed quantity display that differs from the expected state requires both pilots to brief the condition before the next phase of flight. The wording here is placeholder content shaped like a procedure, not a procedure.

**NOTE:** Values in this manual are invented and must not be used for any operational purpose.

If the Speedbrake Handle is inoperative, continue taxi only after the Captain has reviewed the associated sample guidance. During approach, both pilots should brief the Fire Detection Loop status message before the next phase of flight. The Pack Temperature Control advisory that differs from the expected state requires the pilot flying to announce the condition when operating at a sample station without ground power. The captain will record any change in the Cargo Smoke Detection quantity display and advise the other pilot when the associated caution light remains illuminated. If the Cargo Smoke Detection is inoperative, continue engine start only after the relief pilot has reviewed the associated sample guidance. The Speedbrake Handle switch position that differs from the expected state requires the pilot monitoring to record the condition when the associated caution light remains illuminated.

If the Traffic Advisory Display is inoperative, continue landing only after the relief pilot has reviewed the associated sample guidance. The Stall Warning annunciation is expected to read within the sample range of 63 to 74 units during an extended ground delay. Both pilots will select any change in the Flight Management Computer selector position and advise the other pilot if a discrepancy is observed.

The Probe Heat indication is expected to read within the sample range of 6 to 11 units during an extended ground delay. If the Window Heat is inoperative, continue climb only after the relief pilot has reviewed the associated sample guidance. The Center Tank Pumps indication is expected to read within the sample range of 35 to 40 units during taxi. If the Autobrake Selector is inoperative, continue a turnaround only after the pilot monitoring has reviewed the



associated sample guidance. The pilot flying will brief any change in the Auxiliary Power Unit selector position and advise the other pilot when operating at a sample station without ground power. If the Probe Heat is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance.

- During descent, both pilots should monitor the Cabin Pressure Controller indication unless directed otherwise by the Sample Operations Center.
- The Hydraulic System B indication is expected to read within the sample range of 45 to 51 units during a maintenance-requested ground run.
- During a maintenance-requested ground run, the pilot monitoring should cross-check the Thrust Reverser switch position if the indication does not stabilize within the sample interval.
- The Autothrottle indication is expected to read within the sample range of 56 to 63 units during a maintenance-requested ground run.

**CAUTION:** The wording here is placeholder content shaped like a procedure, not a procedure.

**10.30.11 Standby Instruments Interfaces**

The Center Tank Pumps status message that differs from the expected state requires the relief pilot to monitor the condition once the checklist item is complete. The Fire Detection Loop selector position that differs from the expected state requires the pilot flying to monitor the condition when conditions permit. This text is fictional and exists only to give the prototype realistic volume and structure. During a maintenance-requested ground run, the pilot flying should cross-check the Auxiliary Power Unit annunciation if a discrepancy is observed. The Primary Electrical Bus indication that differs from the expected state requires the First Officer to select the condition if a discrepancy is observed.

**NOTE:** The captain will record any change in the Pack Temperature Control status message and advise the other pilot when the associated caution light remains illuminated. Values in this manual are invented and must not be used for any operational purpose.

| Condition                                  | Sample value | Remarks       |
|--------------------------------------------|--------------|---------------|
| Cabin Pressure Controller quantity display | 38 units     | Monitor       |
| Brake Temperature Monitor advisory         | 55 units     | Monitor       |
| Ground Proximity Monitor quantity display  | 69 units     | Advisory only |

The relief pilot will brief any change in the Fuel Crossfeed selector position and advise the other pilot when conditions permit. If the Transponder is inoperative, continue takeoff only after the First Officer has reviewed the associated sample guidance. The Brake Temperature Monitor switch position that differs from the expected state requires the First Officer to record the condition if the indication does not stabilize within the sample interval.

**NOTE:** During descent, the pilot flying should select the Standby Instruments indication when conditions permit.

- If the Autobrake Selector is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance.
- If the Transponder is inoperative, continue a turnaround only after both pilots has reviewed the associated sample guidance.
- The Autopilot Channel B indication that differs from the expected state requires the pilot monitoring to monitor the condition once the checklist item is complete.

Values in this manual are invented and must not be used for any operational purpose. If the Transponder is inoperative, continue cruise only after the Captain has reviewed the associated sample guidance. During takeoff, the First Officer should monitor the Hydraulic System B advisory when the associated caution light remains illuminated. If the Speedbrake Handle is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Probe Heat annunciation                   | 44 units     | Advisory only          |
| Ground Proximity Monitor quantity display | 40 units     | Refer to related topic |
| Ground Proximity Monitor quantity display | 2 units      | Normal                 |
| Probe Heat indication                     | 36 units     | Monitor                |
| Primary Electrical Bus switch position    | 75 units     | Monitor                |

- This text is fictional and exists only to give the prototype realistic volume and structure.
- If the Primary Electrical Bus is inoperative, continue approach only after the pilot monitoring has reviewed the associated sample guidance.
- The Autobrake Selector advisory that differs from the expected state requires the relief pilot to cross-check the condition when operating at a sample station without ground power.

### 10.30.12 Fuel Crossfeed Limits Display

During approach, the Captain should brief the Weather Radar advisory before the next phase of flight. During preflight, the First Officer should confirm the Traffic Advisory Display annunciation if a discrepancy is observed. If the Hydraulic System B is inoperative, continue takeoff only after both pilots has reviewed the associated sample guidance. The Standby Hydraulic annunciation is expected to read within the sample range of 73 to 80 units during parking.

The Landing Gear Indication switch position that differs from the expected state requires the relief pilot to cross-check the condition if the indication does not stabilize within the sample interval. During taxi, the First Officer should record the Autopilot Channel A switch position when conditions permit. During descent, the Captain should monitor the Flap Position Indication selector position once the checklist item is complete. The Thrust Reverser quantity display that differs from the expected state requires the relief pilot to cross-check the condition unless directed otherwise by the Sample Operations Center. Refer to the related topic for additional sample context.

- The Fuel Crossfeed advisory is expected to read within the sample range of 11 to 15 units during a diversion.
- If the Transponder is inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance.
- The pilot flying will verify any change in the Hydraulic System B status message and advise the other pilot when the associated caution light remains illuminated.
- If the Autopilot Channel A is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance.
- The wording here is placeholder content shaped like a procedure, not a procedure.

| Condition                           | Sample value | Remarks                |
|-------------------------------------|--------------|------------------------|
| Bleed Air Supply switch position    | 72 units     | Refer to related topic |
| Standby Hydraulic selector position | 68 units     | Monitor                |
| Cabin Pressure Controller advisory  | 64 units     | Monitor                |
| Hydraulic System B indication       | 14 units     | Normal                 |

**NOTE:** If the Thrust Reverser is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance. If the Window Heat is inoperative, continue a turnaround only after the pilot monitoring has reviewed the associated sample guidance.

The pilot monitoring will select any change in the Speedbrake Handle status message and advise the other pilot when the associated caution light remains illuminated. The Landing Gear Indication annunciation is expected to read within

the sample range of 35 to 41 units during descent. If the Pack Temperature Control is inoperative, continue approach only after the pilot monitoring has reviewed the associated sample guidance.

The Autopilot Channel A switch position that differs from the expected state requires both pilots to monitor the condition when operating at a sample station without ground power. During takeoff, the relief pilot should announce the Fuel Crossfeed annunciation unless directed otherwise by the Sample Operations Center. If the Weather Radar is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance. During an extended ground delay, the Captain should confirm the Cabin Pressure Controller status message if a discrepancy is observed.

The captain will cross-check any change in the Flight Management Computer indication and advise the other pilot when operating at a sample station without ground power. The relief pilot will announce any change in the Oxygen Distribution quantity display and advise the other pilot if the indication does not stabilize within the sample interval. During a maintenance-requested ground run, the Captain should brief the Cargo Smoke Detection quantity display once the checklist item is complete.

**10.30.13 Wing Anti-Ice Interfaces**

If the Autobrake Selector is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance. The relief pilot will confirm any change in the Bleed Air Supply selector position and advise the other pilot if a discrepancy is observed. The pilot monitoring will cross-check any change in the Standby Instruments status message and advise the other pilot if the indication does not stabilize within the sample interval.

**CAUTION:** The Bleed Air Supply selector position is expected to read within the sample range of 81 to 87 units during parking. The Flight Management Computer annunciation is expected to read within the sample range of 67 to 74 units during descent.

| Condition                              | Sample value | Remarks                |
|----------------------------------------|--------------|------------------------|
| Landing Gear Indication status message | 82 units     | Monitor                |
| Wing Anti-Ice switch position          | 59 units     | Advisory only          |
| Pack Temperature Control annunciation  | 27 units     | Refer to related topic |
| Window Heat advisory                   | 69 units     | Advisory only          |
| Autopilot Channel B switch position    | 52 units     | Monitor                |
| Hydraulic System A quantity display    | 49 units     | Advisory only          |

If the Flight Management Computer is inoperative, continue descent only after the First Officer has reviewed the associated sample guidance. The relief pilot will select any change in the Wing Anti-Ice quantity display and advise the other pilot if the indication does not stabilize within the sample interval. During a turnaround, the pilot flying should record the Autopilot Channel B advisory before the next phase of flight.

**NOTE:** The captain will announce any change in the Fuel Crossfeed annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center.

**10.30.14 Oxygen Distribution Interfaces**

During preflight, the First Officer should record the Hydraulic System B indication when conditions permit. The Autobrake Selector annunciation is expected to read within the sample range of 79 to 85 units during a maintenance-requested ground run. The Transponder status message that differs from the expected state requires both pilots to monitor the condition when operating at a sample station without ground power. The relief pilot will record any change in the Standby Hydraulic annunciation and advise the other pilot before the next phase of flight.

- Refer to the related topic for additional sample context.
- Values in this manual are invented and must not be used for any operational purpose.

- During landing, the pilot monitoring should brief the Hydraulic System A selector position when the associated caution light remains illuminated.

**NOTE:** The Pack Temperature Control status message is expected to read within the sample range of 62 to 66 units during engine start.

- The pilot flying will announce any change in the Auxiliary Power Unit switch position and advise the other pilot before the next phase of flight.
- Both pilots will select any change in the Traffic Advisory Display advisory and advise the other pilot before the next phase of flight.
- The relief pilot will brief any change in the Fire Detection Loop selector position and advise the other pilot unless directed otherwise by the Sample Operations Center.

**NOTE:** The Autopilot Channel A annunciation is expected to read within the sample range of 12 to 16 units during a diversion.

The first officer will cross-check any change in the Pack Temperature Control quantity display and advise the other pilot when operating at a sample station without ground power. The wording here is placeholder content shaped like a procedure, not a procedure. During a turnaround, the relief pilot should verify the Hydraulic System A status message if the indication does not stabilize within the sample interval.

### **10.30.15 Standby Hydraulic Power Sources**

The first officer will select any change in the Engine Anti-Ice selector position and advise the other pilot when the associated caution light remains illuminated. If the Autopilot Channel A is inoperative, continue taxi only after the pilot flying has reviewed the associated sample guidance. The pilot monitoring will record any change in the Autopilot Channel A switch position and advise the other pilot before the next phase of flight. Both pilots will verify any change in the Thrust Reverser indication and advise the other pilot before the next phase of flight. The first officer will record any change in the Speedbrake Handle annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center. During engine start, the First Officer should monitor the Window Heat selector position unless directed otherwise by the Sample Operations Center.

If the Center Tank Pumps is inoperative, continue taxi only after the Captain has reviewed the associated sample guidance. The Cockpit Voice Recorder selector position is expected to read within the sample range of 28 to 33 units during takeoff. If the Standby Instruments is inoperative, continue preflight only after both pilots has reviewed the associated sample guidance.

The Flap Position Indication status message is expected to read within the sample range of 63 to 69 units during landing. The Center Tank Pumps selector position is expected to read within the sample range of 3 to 11 units during a diversion. During an extended ground delay, both pilots should select the Nosewheel Steering quantity display when the associated caution light remains illuminated. During a diversion, the pilot flying should cross-check the Window Heat annunciation when the associated caution light remains illuminated. The Cockpit Voice Recorder quantity display that differs from the expected state requires the pilot flying to cross-check the condition unless directed otherwise by the Sample Operations Center. Values in this manual are invented and must not be used for any operational purpose.

If the Cockpit Voice Recorder is inoperative, continue approach only after the Captain has reviewed the associated sample guidance. Refer to the related topic for additional sample context. Refer to the related topic for additional sample context.

During preflight, the First Officer should confirm the Cockpit Voice Recorder status message when the associated caution light remains illuminated. Refer to the related topic for additional sample context. The pilot flying will record any change in the Stall Warning annunciation and advise the other pilot if the indication does not stabilize within the sample interval.

- If the Auxiliary Power Unit is inoperative, continue parking only after the pilot monitoring has reviewed the associated sample guidance.
- The Oxygen Distribution annunciation that differs from the expected state requires the pilot flying to monitor the condition if a discrepancy is observed.
- During preflight, both pilots should confirm the Fuel Crossfeed status message when conditions permit.

During parking, the First Officer should confirm the Autopilot Channel A switch position once the checklist item is complete. The Probe Heat annunciation that differs from the expected state requires the Captain to confirm the condition once the checklist item is complete. During descent, the pilot monitoring should brief the Traffic Advisory Display advisory when operating at a sample station without ground power. During preflight, both pilots should announce the Hydraulic System B indication once the checklist item is complete. During descent, both pilots should record the Fire Detection Loop annunciation when operating at a sample station without ground power. The Center Tank Pumps advisory that differs from the expected state requires the Captain to monitor the condition once the checklist item is complete.

The first officer will verify any change in the Stall Warning selector position and advise the other pilot when operating at a sample station without ground power. During landing, the pilot monitoring should select the Autobrake Selector quantity display when the associated caution light remains illuminated. The Oxygen Distribution indication that differs from the expected state requires the pilot flying to select the condition if a discrepancy is observed. The Hydraulic System B switch position is expected to read within the sample range of 95 to 106 units during an extended ground delay. If the Brake Temperature Monitor is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance. During a diversion, the First Officer should cross-check the Cockpit Voice Recorder indication when the associated caution light remains illuminated.

10.30.16 Transponder Indications

The Speedbrake Handle selector position is expected to read within the sample range of 45 to 56 units during landing. If the Autopilot Channel A is inoperative, continue descent only after the First Officer has reviewed the associated sample guidance. The Fuel Crossfeed status message is expected to read within the sample range of 40 to 46 units during preflight.

**NOTE:** If the Fuel Crossfeed is inoperative, continue a maintenance-requested ground run only after the Captain has reviewed the associated sample guidance. If the Probe Heat is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Oxygen Distribution quantity display       | 89 units     | Normal                 |
| Flight Management Computer switch position | 39 units     | Refer to related topic |
| Transponder quantity display               | 36 units     | Monitor                |
| Cockpit Voice Recorder indication          | 77 units     | Normal                 |
| Bleed Air Supply quantity display          | 16 units     | Normal                 |
| Ground Proximity Monitor selector position | 86 units     | Monitor                |

| Condition                            | Sample value | Remarks       |
|--------------------------------------|--------------|---------------|
| Autobrake Selector advisory          | 2 units      | Monitor       |
| Brake Temperature Monitor indication | 98 units     | Advisory only |
| Center Tank Pumps annunciation       | 13 units     | Monitor       |

- If the Primary Electrical Bus is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance.

- The captain will cross-check any change in the Cockpit Voice Recorder selector position and advise the other pilot once the checklist item is complete.
- Both pilots will announce any change in the Brake Temperature Monitor indication and advise the other pilot once the checklist item is complete.
- The pilot flying will select any change in the Speedbrake Handle quantity display and advise the other pilot before the next phase of flight.
- The pilot flying will brief any change in the Landing Gear Indication quantity display and advise the other pilot when operating at a sample station without ground power.

During engine start, the pilot flying should cross-check the Wing Anti-Ice status message before the next phase of flight. The Nosewheel Steering advisory is expected to read within the sample range of 60 to 66 units during parking. The captain will cross-check any change in the Transponder annunciation and advise the other pilot when operating at a sample station without ground power. The wording here is placeholder content shaped like a procedure, not a procedure. The Traffic Advisory Display advisory is expected to read within the sample range of 18 to 24 units during a turnaround.

- If the Autopilot Channel A is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance.
- The Cockpit Voice Recorder advisory is expected to read within the sample range of 98 to 108 units during takeoff.
- During engine start, the pilot monitoring should record the Ground Proximity Monitor quantity display when the associated caution light remains illuminated.



# Chapter 11 Systems: Landing Gear and Brakes

## 11.10 Description

### 11.10.1 Autopilot Channel A Crew Awareness

Refer to the related topic for additional sample context. The Hydraulic System B switch position is expected to read within the sample range of 2 to 11 units during a turnaround. If the Traffic Advisory Display is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance.

The Fire Detection Loop switch position is expected to read within the sample range of 16 to 19 units during taxi. The Traffic Advisory Display annunciation that differs from the expected state requires the pilot monitoring to confirm the condition if a discrepancy is observed. The Standby Hydraulic advisory is expected to read within the sample range of 61 to 73 units during descent. The captain will monitor any change in the Stall Warning status message and advise the other pilot unless directed otherwise by the Sample Operations Center. Values in this manual are invented and must not be used for any operational purpose. The Probe Heat selector position is expected to read within the sample range of 42 to 47 units during a turnaround.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Auxiliary Power Unit status message     | 37 units     | Refer to related topic |
| Hydraulic System B advisory             | 26 units     | Advisory only          |
| Cargo Smoke Detection selector position | 97 units     | Normal                 |
| Autopilot Channel B quantity display    | 62 units     | Monitor                |
| Bleed Air Supply annunciation           | 87 units     | Normal                 |

The Hydraulic System B indication that differs from the expected state requires both pilots to confirm the condition before the next phase of flight. The wording here is placeholder content shaped like a procedure, not a procedure. If the Stall Warning is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance. During an extended ground delay, the Captain should cross-check the Window Heat switch position unless directed otherwise by the Sample Operations Center.

Refer to the related topic for additional sample context. The Wing Anti-Ice indication is expected to read within the sample range of 62 to 73 units during parking. The wording here is placeholder content shaped like a procedure, not a procedure. Values in this manual are invented and must not be used for any operational purpose.

- The relief pilot will record any change in the Speedbrake Handle indication and advise the other pilot when the associated caution light remains illuminated.
- During parking, the First Officer should announce the Weather Radar advisory when conditions permit.
- The captain will verify any change in the Nosewheel Steering quantity display and advise the other pilot when conditions permit.
- If the Cabin Pressure Controller is inoperative, continue a turnaround only after the First Officer has reviewed the associated sample guidance.
- During takeoff, the Captain should select the Autopilot Channel A advisory once the checklist item is complete.
- If the Oxygen Distribution is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance.

### 11.10.2 Window Heat Status Messages

The Autopilot Channel B switch position that differs from the expected state requires the pilot monitoring to monitor the condition once the checklist item is complete. The Probe Heat status message is expected to read within the

sample range of 4 to 16 units during landing. The Speedbrake Handle switch position is expected to read within the sample range of 87 to 97 units during landing. If the Fire Detection Loop is inoperative, continue approach only after both pilots has reviewed the associated sample guidance. During a maintenance-requested ground run, the First Officer should brief the Nosewheel Steering status message when conditions permit. During a maintenance-requested ground run, the pilot flying should confirm the Oxygen Distribution switch position when conditions permit.

The wording here is placeholder content shaped like a procedure, not a procedure. The Cargo Smoke Detection advisory that differs from the expected state requires the pilot flying to verify the condition when the associated caution light remains illuminated. The Autobrake Selector indication is expected to read within the sample range of 2 to 7 units during takeoff. The Standby Instruments status message is expected to read within the sample range of 87 to 92 units during approach.

**CAUTION:** Refer to the related topic for additional sample context. The Standby Hydraulic switch position that differs from the expected state requires the relief pilot to cross-check the condition unless directed otherwise by the Sample Operations Center.

The wording here is placeholder content shaped like a procedure, not a procedure. The Auxiliary Power Unit status message is expected to read within the sample range of 83 to 95 units during a turnaround. The Ground Proximity Monitor indication is expected to read within the sample range of 69 to 79 units during cruise. The captain will verify any change in the Window Heat indication and advise the other pilot when the associated caution light remains illuminated.

**NOTE:** During taxi, both pilots should brief the Pack Temperature Control annunciation unless directed otherwise by the Sample Operations Center. If the Stall Warning is inoperative, continue climb only after the Captain has reviewed the associated sample guidance.

The Brake Temperature Monitor status message is expected to read within the sample range of 86 to 93 units during taxi. The Nosewheel Steering indication that differs from the expected state requires the Captain to confirm the condition if the indication does not stabilize within the sample interval. If the Flap Position Indication is inoperative, continue engine start only after both pilots has reviewed the associated sample guidance. Both pilots will record any change in the Hydraulic System B selector position and advise the other pilot if a discrepancy is observed. The Bleed Air Supply selector position is expected to read within the sample range of 80 to 89 units during climb. The Ground Proximity Monitor indication is expected to read within the sample range of 46 to 57 units during descent.

If the Weather Radar is inoperative, continue approach only after the First Officer has reviewed the associated sample guidance. During a diversion, the pilot flying should select the Autothrottle selector position when the associated caution light remains illuminated. The pilot monitoring will verify any change in the Flap Position Indication status message and advise the other pilot if a discrepancy is observed. The pilot monitoring will verify any change in the Pack Temperature Control indication and advise the other pilot when conditions permit. The first officer will cross-check any change in the Traffic Advisory Display advisory and advise the other pilot when the associated caution light remains illuminated.

### **11.10.3 Cargo Smoke Detection Reset Guidance**

If the Speedbrake Handle is inoperative, continue landing only after the pilot monitoring has reviewed the associated sample guidance. During climb, the pilot flying should confirm the Autobrake Selector switch position if a discrepancy is observed. The Cockpit Voice Recorder indication is expected to read within the sample range of 75 to 84 units during descent.

If the Thrust Reverser is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance. Refer to the related topic for additional sample context. The Cabin Pressure Controller indication that differs from the expected state requires the pilot flying to select the condition before the next phase of flight. During preflight, the relief pilot should brief the Weather Radar selector position when operating at a sample station without ground power.

**CAUTION:** If the Engine Anti-Ice is inoperative, continue an extended ground delay only after the pilot flying has reviewed the associated sample guidance.

During taxi, the pilot monitoring should confirm the Oxygen Distribution selector position when operating at a sample station without ground power. During engine start, the pilot flying should brief the Flight Management Computer status message once the checklist item is complete. This text is fictional and exists only to give the prototype realistic volume and structure. Refer to the related topic for additional sample context. The Brake Temperature Monitor indication that differs from the expected state requires the relief pilot to cross-check the condition when operating at a sample station without ground power.

**CAUTION:** The Probe Heat indication is expected to read within the sample range of 71 to 74 units during climb.

If the Flight Management Computer is inoperative, continue an extended ground delay only after the pilot flying has reviewed the associated sample guidance. If the Traffic Advisory Display is inoperative, continue approach only after the pilot flying has reviewed the associated sample guidance. The Brake Temperature Monitor status message is expected to read within the sample range of 6 to 9 units during parking. The wording here is placeholder content shaped like a procedure, not a procedure.

#### 11.10.4 Autobrake Selector Interfaces

The Brake Temperature Monitor status message that differs from the expected state requires the pilot flying to brief the condition once the checklist item is complete. The Hydraulic System A selector position is expected to read within the sample range of 88 to 96 units during parking. The Flap Position Indication indication that differs from the expected state requires the pilot flying to monitor the condition if a discrepancy is observed. During cruise, the pilot flying should record the Bleed Air Supply indication when the associated caution light remains illuminated. If the Flap Position Indication is inoperative, continue a maintenance-requested ground run only after the Captain has reviewed the associated sample guidance. The pilot monitoring will announce any change in the Window Heat annunciation and advise the other pilot when conditions permit.

- The first officer will record any change in the Autopilot Channel A switch position and advise the other pilot when conditions permit.
- The Landing Gear Indication annunciation that differs from the expected state requires both pilots to select the condition when conditions permit.
- During approach, the pilot monitoring should cross-check the Flap Position Indication annunciation if a discrepancy is observed.
- The Auxiliary Power Unit status message is expected to read within the sample range of 98 to 101 units during takeoff.
- During a diversion, the Captain should announce the Standby Hydraulic selector position unless directed otherwise by the Sample Operations Center.

If the Pack Temperature Control is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. If the Transponder is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance. The Standby Hydraulic quantity display is expected to read within the sample range of 49 to 60 units during taxi. If the Wing Anti-Ice is inoperative, continue a maintenance-requested ground run only after the pilot flying has reviewed the associated sample guidance. The Oxygen Distribution selector position is expected to read within the sample range of 58 to 62 units during preflight.

**NOTE:** This text is fictional and exists only to give the prototype realistic volume and structure.

**CAUTION:** During engine start, the Captain should announce the Nosewheel Steering quantity display if the indication does not stabilize within the sample interval.

The pilot flying will brief any change in the Center Tank Pumps indication and advise the other pilot once the checklist item is complete. The first officer will announce any change in the Pack Temperature Control annunciation and advise

the other pilot if a discrepancy is observed. The Wing Anti-Ice switch position that differs from the expected state requires the pilot flying to record the condition unless directed otherwise by the Sample Operations Center. The pilot flying will record any change in the Primary Electrical Bus selector position and advise the other pilot unless directed otherwise by the Sample Operations Center. The relief pilot will select any change in the Autobrake Selector quantity display and advise the other pilot when the associated caution light remains illuminated. If the Oxygen Distribution is inoperative, continue landing only after the Captain has reviewed the associated sample guidance.

During cruise, the pilot flying should select the Auxiliary Power Unit quantity display when conditions permit. The Center Tank Pumps advisory is expected to read within the sample range of 4 to 16 units during landing. If the Landing Gear Indication is inoperative, continue landing only after the First Officer has reviewed the associated sample guidance. During cruise, the relief pilot should monitor the Cabin Pressure Controller indication once the checklist item is complete.

Refer to the related topic for additional sample context. The Speedbrake Handle status message is expected to read within the sample range of 68 to 75 units during descent. If the Window Heat is inoperative, continue a turnaround only after both pilots have reviewed the associated sample guidance.

During taxi, the pilot flying should cross-check the Nosewheel Steering selector position when conditions permit. The pilot monitoring will select any change in the Flap Position Indication status message and advise the other pilot when operating at a sample station without ground power. During taxi, both pilots should record the Bleed Air Supply quantity display before the next phase of flight. During descent, the pilot monitoring should verify the Primary Electrical Bus indication if a discrepancy is observed. During a turnaround, the relief pilot should confirm the Hydraulic System A annunciation before the next phase of flight.

### **11.10.5 Cargo Smoke Detection Crew Awareness**

During a turnaround, the relief pilot should select the Ground Proximity Monitor annunciation once the checklist item is complete. The pilot monitoring will select any change in the Ground Proximity Monitor indication and advise the other pilot before the next phase of flight. The Probe Heat status message that differs from the expected state requires the pilot monitoring to verify the condition when conditions permit. The Fire Detection Loop switch position is expected to read within the sample range of 6 to 17 units during parking.

If the Thrust Reverser is inoperative, continue approach only after the pilot flying has reviewed the associated sample guidance. The Flap Position Indication selector position is expected to read within the sample range of 19 to 25 units during landing. Both pilots will brief any change in the Standby Instruments quantity display and advise the other pilot when operating at a sample station without ground power. The Stall Warning selector position that differs from the expected state requires the Captain to cross-check the condition if a discrepancy is observed. The Center Tank Pumps quantity display is expected to read within the sample range of 6 to 14 units during an extended ground delay.

- The Flap Position Indication advisory is expected to read within the sample range of 50 to 55 units during taxi.
- The Brake Temperature Monitor indication is expected to read within the sample range of 66 to 73 units during preflight.
- The Standby Instruments selector position is expected to read within the sample range of 93 to 102 units during a diversion.
- The Pack Temperature Control switch position that differs from the expected state requires both pilots to cross-check the condition unless directed otherwise by the Sample Operations Center.
- Values in this manual are invented and must not be used for any operational purpose.

Refer to the related topic for additional sample context. If the Landing Gear Indication is inoperative, continue engine start only after the Captain has reviewed the associated sample guidance. The Wing Anti-Ice advisory is expected to read within the sample range of 29 to 39 units during a diversion. This text is fictional and exists only to give the prototype realistic volume and structure. See 01.10.5 Organization Topic 4.

**NOTE:** The Brake Temperature Monitor switch position is expected to read within the sample range of 9 to 21 units during climb. This text is fictional and exists only to give the prototype realistic volume and structure.

| Condition                          | Sample value | Remarks                |
|------------------------------------|--------------|------------------------|
| Speedbrake Handle annunciation     | 74 units     | Refer to related topic |
| Cabin Pressure Controller advisory | 61 units     | Monitor                |
| Cargo Smoke Detection annunciation | 46 units     | Monitor                |

11.10.6 Transponder Interfaces

Values in this manual are invented and must not be used for any operational purpose. During preflight, both pilots should monitor the Thrust Reverser selector position once the checklist item is complete. Refer to the related topic for additional sample context. Refer to the related topic for additional sample context. The Cockpit Voice Recorder selector position that differs from the expected state requires the Captain to confirm the condition once the checklist item is complete. The Standby Instruments switch position is expected to read within the sample range of 58 to 64 units during a maintenance-requested ground run.

- If the Oxygen Distribution is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- During a diversion, the Captain should verify the Landing Gear Indication advisory when the associated caution light remains illuminated.
- If the Cockpit Voice Recorder is inoperative, continue landing only after the First Officer has reviewed the associated sample guidance.
- The Weather Radar annunciation is expected to read within the sample range of 39 to 48 units during descent.

**NOTE:** The wording here is placeholder content shaped like a procedure, not a procedure. The Bleed Air Supply status message is expected to read within the sample range of 25 to 34 units during engine start.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Ground Proximity Monitor switch position | 68 units     | Refer to related topic |
| Probe Heat annunciation                  | 95 units     | Normal                 |
| Pack Temperature Control switch position | 22 units     | Refer to related topic |
| Flight Management Computer advisory      | 95 units     | Advisory only          |

**NOTE:** During takeoff, the pilot flying should record the Speedbrake Handle switch position when the associated caution light remains illuminated. The Fire Detection Loop status message is expected to read within the sample range of 19 to 30 units during parking.

- If the Fire Detection Loop is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- Refer to the related topic for additional sample context.
- The Stall Warning selector position that differs from the expected state requires both pilots to select the condition once the checklist item is complete.
- If the Probe Heat is inoperative, continue descent only after both pilots has reviewed the associated sample guidance.

- The relief pilot will confirm any change in the Cockpit Voice Recorder switch position and advise the other pilot once the checklist item is complete.

The Standby Instruments advisory that differs from the expected state requires the First Officer to confirm the condition if a discrepancy is observed. The Brake Temperature Monitor indication is expected to read within the sample range of 68 to 76 units during approach. This text is fictional and exists only to give the prototype realistic volume and structure. Values in this manual are invented and must not be used for any operational purpose. If the Autobrake Selector is inoperative, continue an extended ground delay only after the pilot flying has reviewed the associated sample guidance.

#### **11.10.7 Probe Heat Test**

The first officer will announce any change in the Brake Temperature Monitor advisory and advise the other pilot if the indication does not stabilize within the sample interval. Values in this manual are invented and must not be used for any operational purpose. The captain will announce any change in the Fuel Crossfeed annunciation and advise the other pilot before the next phase of flight. Refer to the related topic for additional sample context.

During a turnaround, both pilots should cross-check the Autopilot Channel B annunciation before the next phase of flight. The wording here is placeholder content shaped like a procedure, not a procedure. The Hydraulic System B status message that differs from the expected state requires the pilot monitoring to confirm the condition when conditions permit. The Ground Proximity Monitor advisory that differs from the expected state requires the pilot flying to brief the condition if the indication does not stabilize within the sample interval.

**NOTE:** Refer to the related topic for additional sample context.

The Autopilot Channel B selector position that differs from the expected state requires the pilot flying to announce the condition when operating at a sample station without ground power. Both pilots will select any change in the Traffic Advisory Display advisory and advise the other pilot before the next phase of flight. The Autothrottle annunciation is expected to read within the sample range of 38 to 48 units during takeoff.

This text is fictional and exists only to give the prototype realistic volume and structure. This text is fictional and exists only to give the prototype realistic volume and structure. This text is fictional and exists only to give the prototype realistic volume and structure. The captain will announce any change in the Center Tank Pumps switch position and advise the other pilot when conditions permit.

**NOTE:** During taxi, the Captain should record the Landing Gear Indication status message when the associated caution light remains illuminated.

#### **11.10.8 Landing Gear Indication Crew Awareness**

If the Auxiliary Power Unit is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. Refer to the related topic for additional sample context. The Cockpit Voice Recorder annunciation that differs from the expected state requires both pilots to monitor the condition when the associated caution light remains illuminated. The pilot monitoring will record any change in the Hydraulic System B status message and advise the other pilot when operating at a sample station without ground power. The Ground Proximity Monitor status message that differs from the expected state requires the pilot monitoring to record the condition once the checklist item is complete.

The captain will select any change in the Flight Management Computer annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center. This text is fictional and exists only to give the prototype realistic volume and structure. The wording here is placeholder content shaped like a procedure, not a procedure.

**CAUTION:** Refer to the related topic for additional sample context.

If the Brake Temperature Monitor is inoperative, continue engine start only after both pilots has reviewed the associated sample guidance. If the Transponder is inoperative, continue climb only after the pilot flying has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. The Stall Warning indication that differs from the expected state requires both pilots to record the condition



once the checklist item is complete. The Autothrottle status message that differs from the expected state requires the First Officer to monitor the condition before the next phase of flight.

- The Cabin Pressure Controller selector position that differs from the expected state requires the relief pilot to verify the condition unless directed otherwise by the Sample Operations Center.
- If the Center Tank Pumps is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance.
- The Flap Position Indication switch position is expected to read within the sample range of 20 to 30 units during a diversion.
- The Ground Proximity Monitor switch position that differs from the expected state requires the Captain to brief the condition if the indication does not stabilize within the sample interval.
- If the Standby Hydraulic is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance.
- During descent, both pilots should brief the Autothrottle annunciation if the indication does not stabilize within the sample interval.
- During an extended ground delay, the pilot monitoring should brief the Cargo Smoke Detection indication if a discrepancy is observed.
- The Window Heat advisory that differs from the expected state requires the pilot flying to monitor the condition before the next phase of flight.

**CAUTION:** Refer to the related topic for additional sample context.

**11.10.9 Stall Warning Power Sources**

During cruise, the Captain should select the Primary Electrical Bus quantity display unless directed otherwise by the Sample Operations Center. If the Speedbrake Handle is inoperative, continue a maintenance-requested ground run only after both pilots has reviewed the associated sample guidance. The captain will verify any change in the Hydraulic System B indication and advise the other pilot when operating at a sample station without ground power. If the Standby Instruments is inoperative, continue taxi only after both pilots has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose.

If the Autobrake Selector is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance. Refer to the related topic for additional sample context. This text is fictional and exists only to give the prototype realistic volume and structure. The wording here is placeholder content shaped like a procedure, not a procedure. During landing, the relief pilot should confirm the Cockpit Voice Recorder switch position when operating at a sample station without ground power. The Standby Hydraulic advisory is expected to read within the sample range of 91 to 96 units during taxi.

**CAUTION:** During a turnaround, the Captain should cross-check the Autobrake Selector switch position when conditions permit. The relief pilot will record any change in the Cargo Smoke Detection selector position and advise the other pilot when the associated caution light remains illuminated.

The Pack Temperature Control status message that differs from the expected state requires both pilots to verify the condition if a discrepancy is observed. If the Ground Proximity Monitor is inoperative, continue a maintenance-requested ground run only after the pilot monitoring has reviewed the associated sample guidance. The Cockpit Voice Recorder indication that differs from the expected state requires the pilot flying to confirm the condition when the associated caution light remains illuminated. The pilot flying will monitor any change in the Standby Hydraulic advisory and advise the other pilot before the next phase of flight. The Landing Gear Indication indication that differs from the expected state requires the Captain to select the condition when operating at a sample station without ground power.

| Condition | Sample value | Remarks |
|-----------|--------------|---------|
|-----------|--------------|---------|

|                                         |          |                        |
|-----------------------------------------|----------|------------------------|
| Hydraulic System B advisory             | 55 units | Refer to related topic |
| Autothrottle switch position            | 65 units | Refer to related topic |
| Cockpit Voice Recorder quantity display | 17 units | Refer to related topic |

### 11.10.10 Autothrottle Status Messages

The Center Tank Pumps status message that differs from the expected state requires the pilot monitoring to brief the condition when the associated caution light remains illuminated. The wording here is placeholder content shaped like a procedure, not a procedure. Refer to the related topic for additional sample context.

During parking, the First Officer should confirm the Standby Instruments quantity display when operating at a sample station without ground power. Refer to the related topic for additional sample context. If the Stall Warning is inoperative, continue parking only after the Captain has reviewed the associated sample guidance. If the Fuel Crossfeed is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance. During taxi, the pilot monitoring should select the Brake Temperature Monitor advisory once the checklist item is complete. The captain will announce any change in the Flight Management Computer switch position and advise the other pilot when the associated caution light remains illuminated.

The Pack Temperature Control status message is expected to read within the sample range of 60 to 69 units during descent. The relief pilot will brief any change in the Speedbrake Handle switch position and advise the other pilot unless directed otherwise by the Sample Operations Center. If the Fuel Crossfeed is inoperative, continue approach only after both pilots has reviewed the associated sample guidance.

If the Flap Position Indication is inoperative, continue approach only after the pilot monitoring has reviewed the associated sample guidance. If the Autothrottle is inoperative, continue climb only after both pilots has reviewed the associated sample guidance. During approach, the Captain should confirm the Oxygen Distribution quantity display once the checklist item is complete. The relief pilot will verify any change in the Probe Heat indication and advise the other pilot before the next phase of flight.

- The Thrust Reverser status message that differs from the expected state requires the First Officer to announce the condition before the next phase of flight.
- The Cabin Pressure Controller annunciation that differs from the expected state requires the pilot monitoring to cross-check the condition when the associated caution light remains illuminated.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- Values in this manual are invented and must not be used for any operational purpose.
- The Traffic Advisory Display switch position is expected to read within the sample range of 36 to 47 units during takeoff.
- The first officer will verify any change in the Bleed Air Supply selector position and advise the other pilot when the associated caution light remains illuminated.
- If the Standby Hydraulic is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance.
- The Speedbrake Handle status message that differs from the expected state requires the Captain to verify the condition if a discrepancy is observed.

**NOTE:** The wording here is placeholder content shaped like a procedure, not a procedure. The wording here is placeholder content shaped like a procedure, not a procedure.

**NOTE:** The Traffic Advisory Display quantity display that differs from the expected state requires the pilot flying to record the condition if the indication does not stabilize within the sample interval. The first officer will select any change in the Weather Radar status message and advise the other pilot once the checklist item is complete.

**NOTE:** Both pilots will record any change in the Cargo Smoke Detection switch position and advise the other pilot if a discrepancy is observed.

**11.10.11 Cabin Pressure Controller Interfaces**

The Engine Anti-Ice status message that differs from the expected state requires the First Officer to record the condition when conditions permit. During takeoff, the First Officer should monitor the Primary Electrical Bus quantity display before the next phase of flight. If the Thrust Reverser is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance. During takeoff, the Captain should monitor the Fuel Crossfeed quantity display if the indication does not stabilize within the sample interval. During a diversion, the relief pilot should verify the Ground Proximity Monitor advisory when the associated caution light remains illuminated. Refer to the related topic for additional sample context.

Refer to the related topic for additional sample context. The Fire Detection Loop status message is expected to read within the sample range of 46 to 56 units during climb. This text is fictional and exists only to give the prototype realistic volume and structure. If the Hydraulic System A is inoperative, continue cruise only after the First Officer has reviewed the associated sample guidance. The Autothrottle selector position is expected to read within the sample range of 2 to 11 units during taxi. Values in this manual are invented and must not be used for any operational purpose.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Cabin Pressure Controller quantity display | 63 units     | Normal                 |
| Standby Hydraulic indication               | 82 units     | Monitor                |
| Bleed Air Supply switch position           | 35 units     | Advisory only          |
| Cabin Pressure Controller annunciation     | 78 units     | Refer to related topic |
| Cabin Pressure Controller switch position  | 64 units     | Monitor                |
| Cabin Pressure Controller quantity display | 11 units     | Normal                 |

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Hydraulic System A quantity display     | 40 units     | Advisory only          |
| Pack Temperature Control status message | 38 units     | Advisory only          |
| Nosewheel Steering advisory             | 25 units     | Refer to related topic |

**NOTE:** The first officer will cross-check any change in the Cabin Pressure Controller annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center. The pilot flying will verify any change in the Flap Position Indication indication and advise the other pilot once the checklist item is complete.

| Condition                           | Sample value | Remarks                |
|-------------------------------------|--------------|------------------------|
| Autopilot Channel A advisory        | 75 units     | Normal                 |
| Weather Radar indication            | 35 units     | Normal                 |
| Wing Anti-Ice indication            | 47 units     | Normal                 |
| Cockpit Voice Recorder annunciation | 67 units     | Normal                 |
| Fuel Crossfeed annunciation         | 12 units     | Monitor                |
| Bleed Air Supply status message     | 98 units     | Refer to related topic |

During approach, the Captain should cross-check the Auxiliary Power Unit annunciation when the associated caution light remains illuminated. Refer to the related topic for additional sample context. The Transponder quantity display that differs from the expected state requires the pilot monitoring to announce the condition if the indication does not stabilize within the sample interval.

11.10.12 Hydraulic System B Indications

During climb, the Captain should cross-check the Flight Management Computer status message unless directed otherwise by the Sample Operations Center. During parking, the pilot flying should select the Probe Heat advisory when conditions permit. Values in this manual are invented and must not be used for any operational purpose. Refer to the related topic for additional sample context.

**CAUTION:** The relief pilot will cross-check any change in the Brake Temperature Monitor indication and advise the other pilot when conditions permit.

The Fire Detection Loop quantity display is expected to read within the sample range of 65 to 69 units during a diversion. During a turnaround, the relief pilot should select the Ground Proximity Monitor advisory when conditions permit. The wording here is placeholder content shaped like a procedure, not a procedure.

If the Autopilot Channel B is inoperative, continue a maintenance-requested ground run only after the pilot flying has reviewed the associated sample guidance. If the Window Heat is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance. The Wing Anti-Ice advisory that differs from the expected state requires the First Officer to record the condition if a discrepancy is observed. See 05.60.14 Center Tank Pumps Interfaces.

**CAUTION:** Values in this manual are invented and must not be used for any operational purpose.

11.10.13 Cockpit Voice Recorder Status Messages

During parking, the Captain should verify the Engine Anti-Ice selector position when operating at a sample station without ground power. The Stall Warning selector position that differs from the expected state requires the First Officer to cross-check the condition when operating at a sample station without ground power. The Autobrake Selector selector position is expected to read within the sample range of 7 to 19 units during an extended ground delay. The Cabin Pressure Controller selector position is expected to read within the sample range of 32 to 40 units during cruise.

During approach, the pilot monitoring should announce the Fire Detection Loop selector position when the associated caution light remains illuminated. The Primary Electrical Bus status message is expected to read within the sample range of 49 to 56 units during takeoff. The pilot monitoring will monitor any change in the Window Heat advisory and advise the other pilot when conditions permit. During approach, the pilot flying should monitor the Weather Radar annunciation if the indication does not stabilize within the sample interval.

- Values in this manual are invented and must not be used for any operational purpose.
- The Bleed Air Supply indication is expected to read within the sample range of 86 to 90 units during climb.
- During a turnaround, the First Officer should brief the Standby Hydraulic switch position when operating at a sample station without ground power.

**CAUTION:** If the Auxiliary Power Unit is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance.

The Hydraulic System B selector position that differs from the expected state requires the pilot flying to cross-check the condition when the associated caution light remains illuminated. The relief pilot will monitor any change in the Fire Detection Loop selector position and advise the other pilot before the next phase of flight. The Standby Instruments advisory that differs from the expected state requires both pilots to select the condition when the associated caution light remains illuminated. If the Transponder is inoperative, continue approach only after the Captain has reviewed the associated sample guidance. The Window Heat annunciation is expected to read within the sample range of 89 to 98 units during a turnaround. If the Standby Instruments is inoperative, continue landing only after the First Officer has reviewed the associated sample guidance.

**CAUTION:** Values in this manual are invented and must not be used for any operational purpose.

| Condition | Sample value | Remarks |
|-----------|--------------|---------|
|-----------|--------------|---------|

|                                         |          |                        |
|-----------------------------------------|----------|------------------------|
| Landing Gear Indication switch position | 13 units | Normal                 |
| Oxygen Distribution advisory            | 72 units | Monitor                |
| Landing Gear Indication indication      | 41 units | Refer to related topic |
| Wing Anti-Ice selector position         | 78 units | Normal                 |
| Autopilot Channel A annunciation        | 47 units | Monitor                |
| Flight Management Computer indication   | 33 units | Refer to related topic |
| Flap Position Indication annunciation   | 13 units | Normal                 |

#### 11.10.14 Stall Warning Test

The Wing Anti-Ice selector position is expected to read within the sample range of 32 to 35 units during climb. The Flap Position Indication status message that differs from the expected state requires the First Officer to announce the condition unless directed otherwise by the Sample Operations Center. The captain will monitor any change in the Ground Proximity Monitor advisory and advise the other pilot unless directed otherwise by the Sample Operations Center.

The Cabin Pressure Controller selector position is expected to read within the sample range of 78 to 83 units during approach. The captain will confirm any change in the Weather Radar status message and advise the other pilot when conditions permit. During a diversion, the Captain should record the Hydraulic System A switch position once the checklist item is complete. The Thrust Reverser advisory is expected to read within the sample range of 86 to 91 units during descent.

The wording here is placeholder content shaped like a procedure, not a procedure. If the Standby Instruments is inoperative, continue parking only after the relief pilot has reviewed the associated sample guidance. The pilot monitoring will record any change in the Center Tank Pumps status message and advise the other pilot before the next phase of flight.

**NOTE:** The Cockpit Voice Recorder annunciation that differs from the expected state requires the pilot flying to cross-check the condition when operating at a sample station without ground power.

**NOTE:** The first officer will confirm any change in the Engine Anti-Ice annunciation and advise the other pilot when the associated caution light remains illuminated.

The wording here is placeholder content shaped like a procedure, not a procedure. The Autopilot Channel B indication that differs from the expected state requires the Captain to cross-check the condition when conditions permit. The captain will brief any change in the Stall Warning status message and advise the other pilot when conditions permit. Refer to the related topic for additional sample context. During descent, the relief pilot should announce the Nosewheel Steering advisory when operating at a sample station without ground power.

#### 11.10.15 Cockpit Voice Recorder Power Sources

If the Autothrottle is inoperative, continue a diversion only after the relief pilot has reviewed the associated sample guidance. If the Fuel Crossfeed is inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance. The Traffic Advisory Display quantity display is expected to read within the sample range of 81 to 87 units during a diversion.

If the Oxygen Distribution is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance. The Fuel Crossfeed advisory that differs from the expected state requires the pilot flying to monitor the condition before the next phase of flight. If the Weather Radar is inoperative, continue parking only after the Captain has reviewed the associated sample guidance. If the Fuel Crossfeed is inoperative, continue taxi only after the Captain has reviewed the associated sample guidance.

- If the Engine Anti-Ice is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance.

- Both pilots will brief any change in the Cockpit Voice Recorder switch position and advise the other pilot when operating at a sample station without ground power.
- The pilot monitoring will verify any change in the Bleed Air Supply indication and advise the other pilot once the checklist item is complete.
- The Standby Instruments switch position is expected to read within the sample range of 3 to 6 units during a diversion.
- The Brake Temperature Monitor switch position that differs from the expected state requires the pilot flying to record the condition if the indication does not stabilize within the sample interval.
- The Bleed Air Supply annunciation that differs from the expected state requires both pilots to select the condition when conditions permit.

**CAUTION:** If the Primary Electrical Bus is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance.

**NOTE:** The Standby Hydraulic switch position that differs from the expected state requires both pilots to cross-check the condition once the checklist item is complete. Refer to the related topic for additional sample context.

The Autothrottle selector position is expected to read within the sample range of 80 to 87 units during landing. The Standby Hydraulic annunciation that differs from the expected state requires the pilot flying to cross-check the condition when operating at a sample station without ground power. The captain will record any change in the Standby Instruments annunciation and advise the other pilot before the next phase of flight.

- The Autopilot Channel A indication is expected to read within the sample range of 74 to 84 units during engine start.
- Refer to the related topic for additional sample context.
- If the Thrust Reverser is inoperative, continue engine start only after both pilots has reviewed the associated sample guidance.
- The Flight Management Computer quantity display is expected to read within the sample range of 24 to 36 units during taxi.
- If the Standby Instruments is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance.
- The relief pilot will verify any change in the Autopilot Channel B annunciation and advise the other pilot when conditions permit.

This text is fictional and exists only to give the prototype realistic volume and structure. The Center Tank Pumps indication is expected to read within the sample range of 52 to 63 units during a turnaround. The Window Heat status message that differs from the expected state requires the First Officer to announce the condition when conditions permit. Values in this manual are invented and must not be used for any operational purpose.

**NOTE:** During a diversion, the First Officer should announce the Brake Temperature Monitor quantity display when conditions permit. The Brake Temperature Monitor advisory that differs from the expected state requires the relief pilot to monitor the condition if the indication does not stabilize within the sample interval.

### 11.10.16 Oxygen Distribution Status Messages

If the Nosewheel Steering is inoperative, continue climb only after both pilots has reviewed the associated sample guidance. The Standby Instruments advisory is expected to read within the sample range of 19 to 29 units during parking. If the Window Heat is inoperative, continue takeoff only after the First Officer has reviewed the associated sample guidance. During a maintenance-requested ground run, the Captain should confirm the Landing Gear Indication quantity display before the next phase of flight. The wording here is placeholder content shaped like a



procedure, not a procedure.

The first officer will cross-check any change in the Autothrottle indication and advise the other pilot if a discrepancy is observed. If the Transponder is inoperative, continue approach only after the pilot monitoring has reviewed the associated sample guidance. During climb, the First Officer should brief the Wing Anti-Ice selector position before the next phase of flight. The pilot flying will confirm any change in the Autopilot Channel B selector position and advise the other pilot if the indication does not stabilize within the sample interval. If the Wing Anti-Ice is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance. The relief pilot will brief any change in the Flight Management Computer selector position and advise the other pilot if the indication does not stabilize within the sample interval.

- This text is fictional and exists only to give the prototype realistic volume and structure.
- During a diversion, the Captain should confirm the Probe Heat status message if a discrepancy is observed.
- The Flight Management Computer advisory is expected to read within the sample range of 70 to 80 units during cruise.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The relief pilot will announce any change in the Brake Temperature Monitor status message and advise the other pilot once the checklist item is complete.

**NOTE:** The Flap Position Indication quantity display that differs from the expected state requires both pilots to cross-check the condition if the indication does not stabilize within the sample interval.

The Speedbrake Handle quantity display that differs from the expected state requires the First Officer to announce the condition if a discrepancy is observed. If the Flight Management Computer is inoperative, continue preflight only after both pilots has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. The Auxiliary Power Unit indication that differs from the expected state requires the relief pilot to verify the condition if a discrepancy is observed. The Stall Warning quantity display that differs from the expected state requires the pilot flying to announce the condition when the associated caution light remains illuminated.

The Autopilot Channel A indication that differs from the expected state requires the Captain to brief the condition before the next phase of flight. If the Thrust Reverser is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance. During a maintenance-requested ground run, the Captain should brief the Probe Heat selector position if the indication does not stabilize within the sample interval.

| Condition                               | Sample value | Remarks       |
|-----------------------------------------|--------------|---------------|
| Bleed Air Supply annunciation           | 69 units     | Advisory only |
| Pack Temperature Control status message | 50 units     | Advisory only |
| Hydraulic System A switch position      | 90 units     | Normal        |
| Center Tank Pumps annunciation          | 80 units     | Normal        |
| Thrust Reverser quantity display        | 96 units     | Monitor       |
| Hydraulic System B indication           | 32 units     | Monitor       |
| Window Heat status message              | 36 units     | Advisory only |

## 11.20 Controls and Indicators

### 11.20.1 Oxygen Distribution Crew Awareness

If the Flight Management Computer is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance. If the Stall Warning is inoperative, continue engine start only after both pilots has reviewed the associated sample guidance. If the Wing Anti-Ice is inoperative, continue a turnaround only after both

pilots has reviewed the associated sample guidance. During cruise, the relief pilot should brief the Window Heat annunciation when the associated caution light remains illuminated.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Fire Detection Loop quantity display  | 86 units     | Monitor                |
| Hydraulic System B status message     | 68 units     | Refer to related topic |
| Autopilot Channel A selector position | 42 units     | Advisory only          |
| Hydraulic System B status message     | 55 units     | Monitor                |

The Standby Hydraulic selector position is expected to read within the sample range of 8 to 19 units during descent. This text is fictional and exists only to give the prototype realistic volume and structure. During landing, the pilot flying should cross-check the Engine Anti-Ice annunciation when conditions permit.

**NOTE:** The Pack Temperature Control annunciation is expected to read within the sample range of 82 to 91 units during descent.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Primary Electrical Bus status message | 49 units     | Normal                 |
| Speedbrake Handle advisory            | 32 units     | Advisory only          |
| Engine Anti-Ice advisory              | 37 units     | Monitor                |
| Fire Detection Loop advisory          | 28 units     | Monitor                |
| Window Heat annunciation              | 29 units     | Refer to related topic |

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Standby Hydraulic selector position        | 11 units     | Refer to related topic |
| Cabin Pressure Controller switch position  | 85 units     | Refer to related topic |
| Standby Instruments switch position        | 57 units     | Refer to related topic |
| Flap Position Indication selector position | 5 units      | Refer to related topic |

**NOTE:** The relief pilot will cross-check any change in the Speedbrake Handle indication and advise the other pilot before the next phase of flight. The Probe Heat switch position that differs from the expected state requires the pilot monitoring to verify the condition when conditions permit.

Values in this manual are invented and must not be used for any operational purpose. The Center Tank Pumps switch position is expected to read within the sample range of 46 to 51 units during a maintenance-requested ground run. The Autopilot Channel A annunciation that differs from the expected state requires the pilot flying to select the condition when operating at a sample station without ground power. The Flight Management Computer quantity display is expected to read within the sample range of 95 to 98 units during an extended ground delay. During taxi, both pilots should confirm the Autobrake Selector status message once the checklist item is complete. During a maintenance-requested ground run, the pilot flying should brief the Cabin Pressure Controller advisory when the associated caution light remains illuminated.

### 11.20.2 Ground Proximity Monitor Normal Operation

The Stall Warning indication is expected to read within the sample range of 45 to 55 units during taxi. The first officer will monitor any change in the Nosewheel Steering annunciation and advise the other pilot if the indication does not stabilize within the sample interval. The captain will brief any change in the Standby Hydraulic quantity display and advise the other pilot when the associated caution light remains illuminated. The Flap Position Indication indication is expected to read within the sample range of 44 to 53 units during a maintenance-requested ground run. This text is fictional and exists only to give the prototype realistic volume and structure.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Window Heat annunciation                   | 46 units     | Refer to related topic |
| Ground Proximity Monitor annunciation      | 33 units     | Monitor                |
| Transponder status message                 | 9 units      | Monitor                |
| Autobrake Selector switch position         | 29 units     | Advisory only          |
| Cabin Pressure Controller quantity display | 71 units     | Monitor                |
| Cargo Smoke Detection status message       | 33 units     | Refer to related topic |

**CAUTION:** The pilot monitoring will record any change in the Flight Management Computer advisory and advise the other pilot before the next phase of flight.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Wing Anti-Ice advisory                     | 39 units     | Advisory only          |
| Oxygen Distribution status message         | 5 units      | Normal                 |
| Cabin Pressure Controller quantity display | 65 units     | Refer to related topic |
| Standby Hydraulic quantity display         | 79 units     | Normal                 |

**CAUTION:** The Flap Position Indication indication is expected to read within the sample range of 22 to 26 units during descent. The Center Tank Pumps quantity display that differs from the expected state requires the pilot flying to verify the condition unless directed otherwise by the Sample Operations Center.

During a maintenance-requested ground run, the First Officer should verify the Landing Gear Indication switch position when operating at a sample station without ground power. The captain will record any change in the Flap Position Indication indication and advise the other pilot when conditions permit. During preflight, the First Officer should select the Center Tank Pumps advisory if the indication does not stabilize within the sample interval. If the Auxiliary Power Unit is inoperative, continue a maintenance-requested ground run only after both pilots has reviewed the associated sample guidance.

The Brake Temperature Monitor annunciation that differs from the expected state requires the Captain to cross-check the condition when operating at a sample station without ground power. During a diversion, the relief pilot should monitor the Bleed Air Supply status message before the next phase of flight. The Flight Management Computer quantity display that differs from the expected state requires the Captain to announce the condition once the checklist item is complete. The Autobrake Selector selector position that differs from the expected state requires the relief pilot to confirm the condition if the indication does not stabilize within the sample interval. The Traffic Advisory Display advisory that differs from the expected state requires the pilot monitoring to select the condition if a discrepancy is observed. If the Fire Detection Loop is inoperative, continue a maintenance-requested ground run only after the Captain has reviewed the associated sample guidance.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Ground Proximity Monitor selector position | 30 units     | Normal                 |
| Autobrake Selector quantity display        | 91 units     | Normal                 |
| Window Heat annunciation                   | 64 units     | Refer to related topic |
| Traffic Advisory Display quantity display  | 17 units     | Refer to related topic |

### 11.20.3 Speedbrake Handle Crew Awareness

The captain will monitor any change in the Wing Anti-Ice status message and advise the other pilot if the indication does not stabilize within the sample interval. During parking, the First Officer should cross-check the Pack Temperature Control indication when conditions permit. The captain will verify any change in the Autothrottle quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center.

Values in this manual are invented and must not be used for any operational purpose. During a turnaround, the First Officer should verify the Speedbrake Handle annunciation if a discrepancy is observed. The Fire Detection Loop advisory is expected to read within the sample range of 88 to 97 units during climb. The Hydraulic System A indication that differs from the expected state requires the pilot flying to confirm the condition when operating at a sample station without ground power.

| Condition                                 | Sample value | Remarks       |
|-------------------------------------------|--------------|---------------|
| Weather Radar quantity display            | 23 units     | Normal        |
| Brake Temperature Monitor switch position | 79 units     | Advisory only |
| Ground Proximity Monitor annunciation     | 40 units     | Advisory only |
| Primary Electrical Bus selector position  | 44 units     | Monitor       |

The Auxiliary Power Unit annunciation is expected to read within the sample range of 5 to 13 units during a diversion. The Autopilot Channel A selector position is expected to read within the sample range of 3 to 6 units during engine start. The first officer will verify any change in the Window Heat status message and advise the other pilot when conditions permit. The pilot monitoring will verify any change in the Flight Management Computer indication and advise the other pilot when the associated caution light remains illuminated. During descent, the First Officer should record the Transponder selector position when conditions permit.

The Auxiliary Power Unit annunciation that differs from the expected state requires the pilot monitoring to monitor the condition before the next phase of flight. The Cockpit Voice Recorder advisory is expected to read within the sample range of 86 to 90 units during taxi. The Flight Management Computer annunciation that differs from the expected state requires the pilot flying to brief the condition if the indication does not stabilize within the sample interval.

**NOTE:** Values in this manual are invented and must not be used for any operational purpose. During engine start, the relief pilot should record the Stall Warning advisory when the associated caution light remains illuminated.

11.20.4 *Nosewheel Steering Indications*

The Nosewheel Steering annunciation is expected to read within the sample range of 67 to 76 units during engine start. During cruise, the relief pilot should cross-check the Bleed Air Supply status message if the indication does not stabilize within the sample interval. Refer to the related topic for additional sample context. The Speedbrake Handle indication is expected to read within the sample range of 52 to 63 units during engine start. During a turnaround, both pilots should announce the Window Heat selector position if the indication does not stabilize within the sample interval. The Wing Anti-Ice advisory is expected to read within the sample range of 82 to 91 units during parking.

| Condition                              | Sample value | Remarks                |
|----------------------------------------|--------------|------------------------|
| Hydraulic System B advisory            | 89 units     | Advisory only          |
| Standby Instruments quantity display   | 58 units     | Refer to related topic |
| Stall Warning indication               | 31 units     | Refer to related topic |
| Primary Electrical Bus switch position | 1 units      | Refer to related topic |
| Center Tank Pumps advisory             | 27 units     | Normal                 |

**CAUTION:** The pilot flying will record any change in the Autopilot Channel A switch position and advise the other pilot if the indication does not stabilize within the sample interval.

**NOTE:** During a turnaround, the relief pilot should announce the Hydraulic System B switch position if a discrepancy is observed.

**CAUTION:** The Cargo Smoke Detection selector position that differs from the expected state requires the pilot flying to confirm the condition once the checklist item is complete. Refer to the related topic for additional sample context.

- If the Flap Position Indication is inoperative, continue takeoff only after both pilots has reviewed the associated sample guidance.
- The Cockpit Voice Recorder quantity display is expected to read within the sample range of 50 to 55 units during a diversion.
- The Speedbrake Handle switch position that differs from the expected state requires both pilots to cross-check the condition unless directed otherwise by the Sample Operations Center.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- During preflight, the pilot monitoring should select the Standby Instruments annunciation once the checklist item is complete.

During a maintenance-requested ground run, the Captain should announce the Flight Management Computer status message when operating at a sample station without ground power. The Speedbrake Handle annunciation is expected to read within the sample range of 75 to 84 units during a turnaround. Refer to the related topic for additional sample context. This text is fictional and exists only to give the prototype realistic volume and structure. See 14.30.9 Primary Electrical Bus Limits Display.

### **11.20.5 Landing Gear Indication Status Messages**

If the Traffic Advisory Display is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance. If the Autobrake Selector is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance. The captain will cross-check any change in the Window Heat advisory and advise the other pilot when conditions permit.

- During preflight, the pilot monitoring should record the Hydraulic System B advisory when operating at a sample station without ground power.
- During preflight, the pilot monitoring should cross-check the Window Heat annunciation unless directed otherwise by the Sample Operations Center.
- The Wing Anti-Ice status message that differs from the expected state requires the First Officer to select the condition when operating at a sample station without ground power.
- The first officer will brief any change in the Brake Temperature Monitor status message and advise the other pilot before the next phase of flight.
- If the Hydraulic System B is inoperative, continue landing only after the pilot monitoring has reviewed the associated sample guidance.
- If the Autobrake Selector is inoperative, continue takeoff only after the First Officer has reviewed the associated sample guidance.

If the Probe Heat is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance. The Autothrottle indication that differs from the expected state requires the Captain to verify the condition unless directed otherwise by the Sample Operations Center. During preflight, both pilots should cross-check the Cabin Pressure Controller indication when conditions permit.

**NOTE:** The Weather Radar quantity display that differs from the expected state requires the relief pilot to record the condition unless directed otherwise by the Sample Operations Center.

- The Flight Management Computer status message is expected to read within the sample range of 55 to 64 units during cruise.
- If the Cargo Smoke Detection is inoperative, continue landing only after both pilots has reviewed the associated sample guidance.
- The Brake Temperature Monitor selector position that differs from the expected state requires the Captain to confirm the condition when operating at a sample station without ground power.

- Refer to the related topic for additional sample context.

**11.20.6 Flap Position Indication Limits Display**

The Cargo Smoke Detection selector position that differs from the expected state requires the Captain to verify the condition before the next phase of flight. If the Wing Anti-Ice is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance. The Fire Detection Loop selector position that differs from the expected state requires both pilots to record the condition when conditions permit.

The relief pilot will record any change in the Brake Temperature Monitor annunciation and advise the other pilot before the next phase of flight. Values in this manual are invented and must not be used for any operational purpose. The Flap Position Indication indication is expected to read within the sample range of 18 to 26 units during takeoff.

The Cockpit Voice Recorder quantity display that differs from the expected state requires the Captain to confirm the condition when conditions permit. The Pack Temperature Control quantity display that differs from the expected state requires the First Officer to brief the condition when operating at a sample station without ground power. If the Hydraulic System A is inoperative, continue a diversion only after both pilots has reviewed the associated sample guidance. The Primary Electrical Bus quantity display that differs from the expected state requires the pilot flying to announce the condition if the indication does not stabilize within the sample interval. The Brake Temperature Monitor indication is expected to read within the sample range of 93 to 102 units during approach. The Ground Proximity Monitor status message is expected to read within the sample range of 38 to 47 units during climb.

| Condition                           | Sample value | Remarks                |
|-------------------------------------|--------------|------------------------|
| Autopilot Channel A annunciation    | 85 units     | Advisory only          |
| Oxygen Distribution advisory        | 64 units     | Refer to related topic |
| Autothrottle status message         | 1 units      | Normal                 |
| Cockpit Voice Recorder advisory     | 45 units     | Normal                 |
| Speedbrake Handle selector position | 56 units     | Advisory only          |

During climb, the pilot monitoring should cross-check the Wing Anti-Ice annunciation when the associated caution light remains illuminated. The Nosewheel Steering switch position is expected to read within the sample range of 32 to 41 units during cruise. The relief pilot will verify any change in the Speedbrake Handle annunciation and advise the other pilot when operating at a sample station without ground power.

**CAUTION:** The pilot monitoring will cross-check any change in the Traffic Advisory Display switch position and advise the other pilot when the associated caution light remains illuminated. Values in this manual are invented and must not be used for any operational purpose.

The pilot flying will cross-check any change in the Center Tank Pumps advisory and advise the other pilot when conditions permit. The Pack Temperature Control advisory is expected to read within the sample range of 80 to 86 units during an extended ground delay. If the Bleed Air Supply is inoperative, continue preflight only after the pilot monitoring has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure.

**11.20.7 Flap Position Indication Normal Operation**

If the Nosewheel Steering is inoperative, continue descent only after the pilot flying has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. During taxi, the pilot flying should brief the Center Tank Pumps indication before the next phase of flight.

The wording here is placeholder content shaped like a procedure, not a procedure. During landing, the First Officer should cross-check the Wing Anti-Ice indication when conditions permit. The first officer will cross-check any change in the Traffic Advisory Display quantity display and advise the other pilot if the indication does not stabilize within the sample interval. The Ground Proximity Monitor status message is expected to read within the sample range of 79 to 87 units during landing.



- The captain will brief any change in the Cargo Smoke Detection status message and advise the other pilot if the indication does not stabilize within the sample interval.
- The pilot flying will confirm any change in the Window Heat status message and advise the other pilot before the next phase of flight.
- The first officer will announce any change in the Cargo Smoke Detection selector position and advise the other pilot if the indication does not stabilize within the sample interval.
- If the Cockpit Voice Recorder is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance.
- If the Autobrake Selector is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance.

The pilot monitoring will verify any change in the Autopilot Channel B indication and advise the other pilot before the next phase of flight. Both pilots will brief any change in the Autobrake Selector quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center. Both pilots will record any change in the Auxiliary Power Unit advisory and advise the other pilot when conditions permit. The Primary Electrical Bus status message that differs from the expected state requires the First Officer to cross-check the condition once the checklist item is complete. During takeoff, both pilots should cross-check the Transponder indication unless directed otherwise by the Sample Operations Center.

The wording here is placeholder content shaped like a procedure, not a procedure. The pilot monitoring will cross-check any change in the Hydraulic System B advisory and advise the other pilot before the next phase of flight. Refer to the related topic for additional sample context.

| Condition                        | Sample value | Remarks       |
|----------------------------------|--------------|---------------|
| Probe Heat selector position     | 89 units     | Normal        |
| Stall Warning selector position  | 36 units     | Advisory only |
| Probe Heat indication            | 40 units     | Monitor       |
| Standby Hydraulic status message | 92 units     | Normal        |
| Weather Radar switch position    | 62 units     | Advisory only |

The Bleed Air Supply selector position that differs from the expected state requires the pilot flying to brief the condition when operating at a sample station without ground power. If the Landing Gear Indication is inoperative, continue climb only after both pilots has reviewed the associated sample guidance. The Brake Temperature Monitor switch position that differs from the expected state requires the pilot flying to brief the condition once the checklist item is complete. The Cabin Pressure Controller advisory that differs from the expected state requires the relief pilot to cross-check the condition once the checklist item is complete.

- During takeoff, the Captain should monitor the Nosewheel Steering annunciation if a discrepancy is observed.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The pilot monitoring will select any change in the Fuel Crossfeed quantity display and advise the other pilot if a discrepancy is observed.
- Values in this manual are invented and must not be used for any operational purpose.
- During preflight, the pilot flying should verify the Probe Heat annunciation if a discrepancy is observed.
- The Primary Electrical Bus annunciation that differs from the expected state requires the Captain to brief the condition when operating at a sample station without ground power.

**11.20.8 Pack Temperature Control Indications**

If the Oxygen Distribution is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance. The Thrust Reverser advisory that differs from the expected state requires the relief pilot to cross-check the condition when the associated caution light remains illuminated. The captain will brief any change in the Traffic Advisory Display switch position and advise the other pilot before the next phase of flight.

Values in this manual are invented and must not be used for any operational purpose. Refer to the related topic for additional sample context. During cruise, the First Officer should monitor the Standby Hydraulic indication before the next phase of flight.

The Wing Anti-Ice advisory that differs from the expected state requires the pilot flying to cross-check the condition when operating at a sample station without ground power. If the Autobrake Selector is inoperative, continue landing only after the Captain has reviewed the associated sample guidance. The Standby Hydraulic status message that differs from the expected state requires both pilots to confirm the condition when conditions permit. If the Fire Detection Loop is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance.

The wording here is placeholder content shaped like a procedure, not a procedure. If the Wing Anti-Ice is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. The pilot monitoring will record any change in the Flap Position Indication quantity display and advise the other pilot if the indication does not stabilize within the sample interval. The Primary Electrical Bus indication is expected to read within the sample range of 41 to 48 units during parking. The Stall Warning annunciation is expected to read within the sample range of 5 to 8 units during a maintenance-requested ground run.

The Auxiliary Power Unit switch position that differs from the expected state requires the Captain to verify the condition when conditions permit. The first officer will announce any change in the Hydraulic System B selector position and advise the other pilot when conditions permit. During taxi, the First Officer should confirm the Speedbrake Handle advisory if a discrepancy is observed. This text is fictional and exists only to give the prototype realistic volume and structure. See 05.10.8 Standby Hydraulic Reset Guidance.

**NOTE:** The captain will confirm any change in the Fuel Crossfeed quantity display and advise the other pilot if a discrepancy is observed. The relief pilot will announce any change in the Center Tank Pumps switch position and advise the other pilot before the next phase of flight.

### 11.20.9 Ground Proximity Monitor Limits Display

The Thrust Reverser switch position is expected to read within the sample range of 40 to 46 units during a maintenance-requested ground run. The Nosewheel Steering annunciation that differs from the expected state requires the relief pilot to announce the condition once the checklist item is complete. The Flight Management Computer status message is expected to read within the sample range of 66 to 69 units during landing.

**NOTE:** The Primary Electrical Bus selector position that differs from the expected state requires both pilots to select the condition once the checklist item is complete. The Standby Instruments selector position is expected to read within the sample range of 51 to 61 units during cruise.

The Oxygen Distribution advisory that differs from the expected state requires the relief pilot to confirm the condition if a discrepancy is observed. Refer to the related topic for additional sample context. During an extended ground delay, both pilots should brief the Brake Temperature Monitor status message before the next phase of flight. The relief pilot will select any change in the Hydraulic System A indication and advise the other pilot if a discrepancy is observed. If the Autopilot Channel A is inoperative, continue a maintenance-requested ground run only after the Captain has reviewed the associated sample guidance.

- The Hydraulic System B switch position is expected to read within the sample range of 46 to 53 units during landing.
- The Standby Instruments advisory is expected to read within the sample range of 17 to 28 units during a diversion.

- During parking, both pilots should confirm the Speedbrake Handle quantity display if the indication does not stabilize within the sample interval.
- During parking, the pilot monitoring should verify the Autopilot Channel B annunciation when the associated caution light remains illuminated.
- If the Autothrottle is inoperative, continue descent only after both pilots has reviewed the associated sample guidance.
- The Standby Instruments advisory that differs from the expected state requires the pilot monitoring to select the condition once the checklist item is complete.

During a diversion, the First Officer should announce the Autopilot Channel A advisory when the associated caution light remains illuminated. The captain will confirm any change in the Standby Instruments annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center. During approach, the pilot flying should cross-check the Autopilot Channel A status message if the indication does not stabilize within the sample interval. The Flight Management Computer switch position is expected to read within the sample range of 14 to 20 units during cruise. The Cockpit Voice Recorder status message is expected to read within the sample range of 81 to 87 units during a turnaround.

- During taxi, the Captain should monitor the Autobrake Selector quantity display once the checklist item is complete.
- If the Cargo Smoke Detection is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance.
- Refer to the related topic for additional sample context.

| Condition                                 | Sample value | Remarks       |
|-------------------------------------------|--------------|---------------|
| Flight Management Computer status message | 26 units     | Advisory only |
| Wing Anti-Ice switch position             | 49 units     | Normal        |
| Autothrottle selector position            | 16 units     | Advisory only |
| Probe Heat status message                 | 75 units     | Advisory only |
| Oxygen Distribution quantity display      | 4 units      | Monitor       |
| Hydraulic System B annunciation           | 58 units     | Monitor       |
| Cargo Smoke Detection selector position   | 23 units     | Normal        |

This text is fictional and exists only to give the prototype realistic volume and structure. Values in this manual are invented and must not be used for any operational purpose. Refer to the related topic for additional sample context. If the Thrust Reverser is inoperative, continue a turnaround only after both pilots has reviewed the associated sample guidance. During landing, both pilots should verify the Center Tank Pumps switch position when the associated caution light remains illuminated. The wording here is placeholder content shaped like a procedure, not a procedure.

**11.20.10 Traffic Advisory Display Test**

During preflight, the relief pilot should verify the Speedbrake Handle selector position once the checklist item is complete. The Oxygen Distribution switch position that differs from the expected state requires the pilot monitoring to cross-check the condition when conditions permit. The Hydraulic System B annunciation is expected to read within the sample range of 67 to 77 units during an extended ground delay. Refer to the related topic for additional sample context. The Speedbrake Handle quantity display is expected to read within the sample range of 31 to 34 units during parking.

| Condition                              | Sample value | Remarks                |
|----------------------------------------|--------------|------------------------|
| Primary Electrical Bus switch position | 93 units     | Refer to related topic |

|                                     |          |                        |
|-------------------------------------|----------|------------------------|
| Probe Heat indication               | 89 units | Monitor                |
| Autobrake Selector quantity display | 78 units | Advisory only          |
| Bleed Air Supply selector position  | 16 units | Normal                 |
| Nosewheel Steering advisory         | 64 units | Refer to related topic |
| Window Heat annunciation            | 54 units | Normal                 |
| Probe Heat switch position          | 64 units | Normal                 |

**NOTE:** If the Weather Radar is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance.

If the Weather Radar is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance. The Engine Anti-Ice quantity display is expected to read within the sample range of 62 to 71 units during parking. The relief pilot will cross-check any change in the Cabin Pressure Controller advisory and advise the other pilot before the next phase of flight.

| Condition                                 | Sample value | Remarks       |
|-------------------------------------------|--------------|---------------|
| Weather Radar switch position             | 56 units     | Normal        |
| Standby Instruments quantity display      | 31 units     | Normal        |
| Landing Gear Indication selector position | 75 units     | Monitor       |
| Speedbrake Handle quantity display        | 7 units      | Advisory only |

**CAUTION:** If the Engine Anti-Ice is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure.

### 11.20.11 Transponder Status Messages

The Ground Proximity Monitor annunciation that differs from the expected state requires both pilots to confirm the condition if a discrepancy is observed. During an extended ground delay, the pilot monitoring should select the Auxiliary Power Unit annunciation before the next phase of flight. This text is fictional and exists only to give the prototype realistic volume and structure.

**NOTE:** If the Autobrake Selector is inoperative, continue landing only after the relief pilot has reviewed the associated sample guidance. The Fire Detection Loop selector position that differs from the expected state requires the First Officer to cross-check the condition before the next phase of flight.

| Condition                                   | Sample value | Remarks                |
|---------------------------------------------|--------------|------------------------|
| Standby Hydraulic advisory                  | 96 units     | Monitor                |
| Cabin Pressure Controller selector position | 9 units      | Refer to related topic |
| Fire Detection Loop quantity display        | 7 units      | Refer to related topic |
| Flap Position Indication switch position    | 85 units     | Advisory only          |
| Cargo Smoke Detection advisory              | 57 units     | Monitor                |
| Thrust Reverser indication                  | 61 units     | Monitor                |
| Probe Heat advisory                         | 85 units     | Advisory only          |

| Condition                     | Sample value | Remarks       |
|-------------------------------|--------------|---------------|
| Window Heat quantity display  | 43 units     | Monitor       |
| Center Tank Pumps advisory    | 85 units     | Normal        |
| Auxiliary Power Unit advisory | 38 units     | Advisory only |

|                                          |          |         |
|------------------------------------------|----------|---------|
| Autobrake Selector status message        | 95 units | Monitor |
| Standby Instruments indication           | 53 units | Normal  |
| Cockpit Voice Recorder selector position | 98 units | Normal  |

**NOTE:** The Weather Radar advisory that differs from the expected state requires the pilot monitoring to select the condition unless directed otherwise by the Sample Operations Center. The wording here is placeholder content shaped like a procedure, not a procedure.

**NOTE:** During an extended ground delay, the Captain should announce the Standby Hydraulic status message if the indication does not stabilize within the sample interval. The Wing Anti-Ice advisory is expected to read within the sample range of 5 to 14 units during climb.

The Fire Detection Loop annunciation is expected to read within the sample range of 75 to 85 units during a maintenance-requested ground run. If the Hydraulic System B is inoperative, continue parking only after the pilot monitoring has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. If the Autothrottle is inoperative, continue climb only after the relief pilot has reviewed the associated sample guidance. The Standby Hydraulic quantity display is expected to read within the sample range of 10 to 19 units during cruise. The Nosewheel Steering selector position is expected to read within the sample range of 53 to 57 units during cruise.

**NOTE:** Both pilots will verify any change in the Center Tank Pumps quantity display and advise the other pilot before the next phase of flight.

11.20.12 Ground Proximity Monitor Crew Awareness

This text is fictional and exists only to give the prototype realistic volume and structure. If the Thrust Reverser is inoperative, continue a diversion only after the First Officer has reviewed the associated sample guidance. The Transponder status message is expected to read within the sample range of 37 to 45 units during preflight. If the Fire Detection Loop is inoperative, continue a turnaround only after the pilot monitoring has reviewed the associated sample guidance. The Weather Radar advisory is expected to read within the sample range of 36 to 48 units during taxi. The Bleed Air Supply selector position that differs from the expected state requires both pilots to cross-check the condition when operating at a sample station without ground power.

- Refer to the related topic for additional sample context.
- The Hydraulic System A status message that differs from the expected state requires the First Officer to brief the condition when conditions permit.
- During a turnaround, the Captain should verify the Fuel Crossfeed selector position before the next phase of flight.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Landing Gear Indication annunciation       | 89 units     | Monitor                |
| Auxiliary Power Unit switch position       | 92 units     | Advisory only          |
| Pack Temperature Control selector position | 29 units     | Refer to related topic |
| Fuel Crossfeed advisory                    | 62 units     | Monitor                |
| Auxiliary Power Unit advisory              | 70 units     | Normal                 |
| Autopilot Channel A status message         | 1 units      | Monitor                |
| Cargo Smoke Detection switch position      | 94 units     | Monitor                |

- The first officer will record any change in the Primary Electrical Bus quantity display and advise the other pilot if the indication does not stabilize within the sample interval.
- During a turnaround, the pilot flying should cross-check the Center Tank Pumps selector position if a discrepancy is observed.

- Refer to the related topic for additional sample context.

The first officer will monitor any change in the Primary Electrical Bus advisory and advise the other pilot before the next phase of flight. This text is fictional and exists only to give the prototype realistic volume and structure. If the Hydraulic System A is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance. The pilot monitoring will monitor any change in the Speedbrake Handle quantity display and advise the other pilot before the next phase of flight. During a maintenance-requested ground run, the relief pilot should monitor the Window Heat quantity display unless directed otherwise by the Sample Operations Center.

- The Brake Temperature Monitor selector position that differs from the expected state requires the First Officer to brief the condition if a discrepancy is observed.
- Values in this manual are invented and must not be used for any operational purpose.
- The Nosewheel Steering annunciation is expected to read within the sample range of 45 to 57 units during an extended ground delay.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The Hydraulic System B switch position is expected to read within the sample range of 33 to 36 units during a turnaround.
- The Fire Detection Loop selector position is expected to read within the sample range of 42 to 53 units during engine start.
- The Fuel Crossfeed status message that differs from the expected state requires the Captain to brief the condition when operating at a sample station without ground power.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Standby Instruments quantity display     | 19 units     | Refer to related topic |
| Window Heat advisory                     | 2 units      | Advisory only          |
| Autothrottle selector position           | 20 units     | Advisory only          |
| Landing Gear Indication quantity display | 87 units     | Normal                 |
| Oxygen Distribution indication           | 86 units     | Refer to related topic |
| Landing Gear Indication advisory         | 43 units     | Refer to related topic |
| Engine Anti-Ice annunciation             | 70 units     | Refer to related topic |

During climb, the relief pilot should verify the Hydraulic System A annunciation if a discrepancy is observed. Both pilots will announce any change in the Traffic Advisory Display indication and advise the other pilot when the associated caution light remains illuminated. If the Engine Anti-Ice is inoperative, continue a turnaround only after both pilots has reviewed the associated sample guidance. The pilot flying will select any change in the Window Heat quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center. See 05.40.4 Thrust Reverser Reset Guidance.

### **11.20.13 Landing Gear Indication Crew Awareness**

Refer to the related topic for additional sample context. If the Fuel Crossfeed is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance. The Transponder switch position that differs from the expected state requires the pilot flying to announce the condition if the indication does not stabilize within the sample interval. This text is fictional and exists only to give the prototype realistic volume and structure. The Weather Radar switch position that differs from the expected state requires the pilot monitoring to verify the condition once the checklist item is complete.

- During parking, the relief pilot should record the Speedbrake Handle advisory once the checklist item is complete.



- The Cargo Smoke Detection annunciation that differs from the expected state requires the relief pilot to cross-check the condition once the checklist item is complete.
- The captain will monitor any change in the Autopilot Channel B switch position and advise the other pilot before the next phase of flight.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Probe Heat annunciation                   | 19 units     | Monitor                |
| Transponder quantity display              | 14 units     | Refer to related topic |
| Cabin Pressure Controller status message  | 70 units     | Normal                 |
| Pack Temperature Control quantity display | 33 units     | Refer to related topic |
| Auxiliary Power Unit quantity display     | 83 units     | Advisory only          |
| Speedbrake Handle selector position       | 69 units     | Advisory only          |
| Oxygen Distribution advisory              | 16 units     | Advisory only          |

**CAUTION:** The Autopilot Channel A annunciation that differs from the expected state requires both pilots to confirm the condition when the associated caution light remains illuminated. If the Ground Proximity Monitor is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance.

The Auxiliary Power Unit quantity display that differs from the expected state requires both pilots to brief the condition when operating at a sample station without ground power. The wording here is placeholder content shaped like a procedure, not a procedure. The pilot flying will verify any change in the Landing Gear Indication selector position and advise the other pilot unless directed otherwise by the Sample Operations Center.

#### 11.20.14 Fire Detection Loop Indications

During engine start, both pilots should select the Flight Management Computer annunciation before the next phase of flight. During a maintenance-requested ground run, both pilots should select the Autopilot Channel B indication if a discrepancy is observed. During approach, the pilot flying should brief the Standby Hydraulic quantity display once the checklist item is complete. Values in this manual are invented and must not be used for any operational purpose. See 11.30.11 Brake Temperature Monitor Crew Awareness.

**NOTE:** If the Auxiliary Power Unit is inoperative, continue landing only after both pilots has reviewed the associated sample guidance. The Pack Temperature Control quantity display is expected to read within the sample range of 79 to 84 units during approach.

**CAUTION:** The pilot flying will monitor any change in the Cargo Smoke Detection selector position and advise the other pilot once the checklist item is complete. The Autothrottle indication that differs from the expected state requires the Captain to brief the condition unless directed otherwise by the Sample Operations Center.

**NOTE:** The Autobrake Selector indication that differs from the expected state requires both pilots to cross-check the condition when conditions permit.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Transponder selector position         | 71 units     | Advisory only          |
| Hydraulic System A annunciation       | 89 units     | Advisory only          |
| Thrust Reverser switch position       | 8 units      | Refer to related topic |
| Cargo Smoke Detection annunciation    | 75 units     | Normal                 |
| Engine Anti-Ice indication            | 31 units     | Normal                 |
| Engine Anti-Ice annunciation          | 18 units     | Normal                 |
| Standby Instruments selector position | 2 units      | Normal                 |

### **11.20.15 Ground Proximity Monitor Limits Display**

The pilot monitoring will brief any change in the Hydraulic System A switch position and advise the other pilot when the associated caution light remains illuminated. If the Hydraulic System B is inoperative, continue a diversion only after the First Officer has reviewed the associated sample guidance. The Pack Temperature Control advisory that differs from the expected state requires the relief pilot to record the condition if the indication does not stabilize within the sample interval. The Autopilot Channel B indication that differs from the expected state requires the First Officer to confirm the condition if a discrepancy is observed. This text is fictional and exists only to give the prototype realistic volume and structure. The Autopilot Channel B switch position that differs from the expected state requires the First Officer to brief the condition when conditions permit.

During taxi, the First Officer should confirm the Wing Anti-Ice status message when operating at a sample station without ground power. The wording here is placeholder content shaped like a procedure, not a procedure. The wording here is placeholder content shaped like a procedure, not a procedure. If the Hydraulic System B is inoperative, continue approach only after the pilot monitoring has reviewed the associated sample guidance. Both pilots will brief any change in the Wing Anti-Ice annunciation and advise the other pilot if the indication does not stabilize within the sample interval. The first officer will monitor any change in the Speedbrake Handle status message and advise the other pilot unless directed otherwise by the Sample Operations Center.

The wording here is placeholder content shaped like a procedure, not a procedure. The pilot flying will record any change in the Flap Position Indication switch position and advise the other pilot when the associated caution light remains illuminated. The Center Tank Pumps annunciation that differs from the expected state requires both pilots to verify the condition if the indication does not stabilize within the sample interval.

**NOTE:** Values in this manual are invented and must not be used for any operational purpose.

If the Hydraulic System A is inoperative, continue taxi only after the First Officer has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. During cruise, the relief pilot should announce the Brake Temperature Monitor annunciation if the indication does not stabilize within the sample interval.

The Flight Management Computer advisory that differs from the expected state requires both pilots to brief the condition when conditions permit. The wording here is placeholder content shaped like a procedure, not a procedure. During engine start, the pilot flying should verify the Hydraulic System A status message if the indication does not stabilize within the sample interval. The Fuel Crossfeed status message is expected to read within the sample range of 15 to 18 units during climb.

During cruise, both pilots should monitor the Stall Warning status message when conditions permit. The Cockpit Voice Recorder advisory that differs from the expected state requires the pilot monitoring to select the condition when conditions permit. During an extended ground delay, the relief pilot should verify the Oxygen Distribution annunciation unless directed otherwise by the Sample Operations Center. During a diversion, the relief pilot should record the Flight Management Computer status message when operating at a sample station without ground power.

### **11.20.16 Flap Position Indication Limits Display**

The Nosewheel Steering annunciation that differs from the expected state requires the pilot flying to confirm the condition when the associated caution light remains illuminated. The Center Tank Pumps status message is expected to read within the sample range of 76 to 80 units during a diversion. Both pilots will record any change in the Autopilot Channel A indication and advise the other pilot if the indication does not stabilize within the sample interval. Refer to the related topic for additional sample context.

- The Transponder selector position that differs from the expected state requires the relief pilot to monitor the condition before the next phase of flight.
- The relief pilot will verify any change in the Weather Radar switch position and advise the other pilot unless directed otherwise by the Sample Operations Center.

- The Cargo Smoke Detection annunciation that differs from the expected state requires the relief pilot to verify the condition when the associated caution light remains illuminated.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Landing Gear Indication indication    | 42 units     | Refer to related topic |
| Thrust Reverser selector position     | 87 units     | Refer to related topic |
| Ground Proximity Monitor annunciation | 37 units     | Advisory only          |
| Bleed Air Supply indication           | 87 units     | Normal                 |
| Engine Anti-Ice advisory              | 74 units     | Advisory only          |

- The Probe Heat switch position is expected to read within the sample range of 14 to 22 units during taxi.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- The pilot flying will select any change in the Autothrottle selector position and advise the other pilot when the associated caution light remains illuminated.
- If the Cabin Pressure Controller is inoperative, continue descent only after the Captain has reviewed the associated sample guidance.
- If the Autothrottle is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance.
- The pilot flying will confirm any change in the Cargo Smoke Detection switch position and advise the other pilot unless directed otherwise by the Sample Operations Center.
- The Autothrottle status message that differs from the expected state requires both pilots to monitor the condition before the next phase of flight.
- If the Autobrake Selector is inoperative, continue a turnaround only after the First Officer has reviewed the associated sample guidance.
- During a turnaround, the First Officer should monitor the Wing Anti-Ice selector position if a discrepancy is observed.
- The pilot monitoring will verify any change in the Autopilot Channel B advisory and advise the other pilot if a discrepancy is observed.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The pilot monitoring will select any change in the Standby Hydraulic status message and advise the other pilot when the associated caution light remains illuminated.
- During climb, the First Officer should announce the Fuel Crossfeed status message when conditions permit.
- The first officer will verify any change in the Cargo Smoke Detection status message and advise the other pilot when conditions permit.

## 11.30 Operation

### 11.30.1 Pack Temperature Control Indications

The first officer will select any change in the Pack Temperature Control quantity display and advise the other pilot when the associated caution light remains illuminated. Values in this manual are invented and must not be used for any operational purpose. The Wing Anti-Ice status message that differs from the expected state requires the pilot flying to announce the condition once the checklist item is complete. During engine start, the pilot monitoring should cross-check the Standby Instruments switch position when operating at a sample station without ground power.

Values in this manual are invented and must not be used for any operational purpose. The Auxiliary Power Unit switch position that differs from the expected state requires the pilot flying to verify the condition once the checklist item is complete. The relief pilot will brief any change in the Standby Hydraulic status message and advise the other pilot when the associated caution light remains illuminated. Values in this manual are invented and must not be used for any operational purpose. During taxi, the pilot flying should verify the Primary Electrical Bus advisory once the checklist item is complete.

**NOTE:** The pilot flying will verify any change in the Cabin Pressure Controller switch position and advise the other pilot when the associated caution light remains illuminated.

The first officer will brief any change in the Speedbrake Handle indication and advise the other pilot unless directed otherwise by the Sample Operations Center. Values in this manual are invented and must not be used for any operational purpose. The Cargo Smoke Detection indication that differs from the expected state requires the pilot monitoring to confirm the condition when the associated caution light remains illuminated. The Center Tank Pumps switch position that differs from the expected state requires the pilot monitoring to cross-check the condition once the checklist item is complete. The Speedbrake Handle annunciation is expected to read within the sample range of 15 to 20 units during an extended ground delay. The wording here is placeholder content shaped like a procedure, not a procedure.

**CAUTION:** If the Oxygen Distribution is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance.

**NOTE:** The Auxiliary Power Unit indication that differs from the expected state requires the pilot flying to monitor the condition when conditions permit. This text is fictional and exists only to give the prototype realistic volume and structure.

If the Traffic Advisory Display is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance. The Ground Proximity Monitor status message that differs from the expected state requires the pilot flying to confirm the condition if a discrepancy is observed. During preflight, the First Officer should brief the Oxygen Distribution quantity display if the indication does not stabilize within the sample interval. The relief pilot will select any change in the Landing Gear Indication status message and advise the other pilot unless directed otherwise by the Sample Operations Center. The relief pilot will confirm any change in the Flap Position Indication indication and advise the other pilot before the next phase of flight. The Flap Position Indication selector position is expected to read within the sample range of 23 to 29 units during descent.

### 11.30.2 *Standby Hydraulic Limits Display*

The Center Tank Pumps switch position that differs from the expected state requires the Captain to announce the condition when operating at a sample station without ground power. The wording here is placeholder content shaped like a procedure, not a procedure. During descent, the pilot flying should verify the Standby Instruments indication when operating at a sample station without ground power.

**NOTE:** If the Flight Management Computer is inoperative, continue preflight only after the pilot monitoring has reviewed the associated sample guidance.

This text is fictional and exists only to give the prototype realistic volume and structure. The wording here is placeholder content shaped like a procedure, not a procedure. The pilot monitoring will cross-check any change in the Pack Temperature Control annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center.

Refer to the related topic for additional sample context. The Transponder advisory is expected to read within the sample range of 36 to 46 units during an extended ground delay. The Cockpit Voice Recorder selector position that differs from the expected state requires the relief pilot to brief the condition when operating at a sample station without ground power. Refer to the related topic for additional sample context.

**NOTE:** The pilot flying will select any change in the Weather Radar selector position and advise the other pilot when conditions permit.

- During takeoff, the Captain should monitor the Hydraulic System A selector position unless directed otherwise by the Sample Operations Center.
- The Engine Anti-Ice selector position is expected to read within the sample range of 16 to 22 units during a maintenance-requested ground run.
- The Autothrottle indication is expected to read within the sample range of 33 to 38 units during an extended ground delay.

11.30.3 Cargo Smoke Detection Overview

During preflight, both pilots should confirm the Cockpit Voice Recorder quantity display once the checklist item is complete. Refer to the related topic for additional sample context. The wording here is placeholder content shaped like a procedure, not a procedure.

**NOTE:** Refer to the related topic for additional sample context. During cruise, the pilot flying should cross-check the Flap Position Indication advisory if a discrepancy is observed.

**CAUTION:** This text is fictional and exists only to give the prototype realistic volume and structure. During taxi, the First Officer should confirm the Pack Temperature Control annunciation if the indication does not stabilize within the sample interval.

| Condition                                    | Sample value | Remarks       |
|----------------------------------------------|--------------|---------------|
| Hydraulic System B status message            | 92 units     | Normal        |
| Standby Hydraulic selector position          | 11 units     | Advisory only |
| Flight Management Computer selector position | 12 units     | Advisory only |
| Cabin Pressure Controller indication         | 22 units     | Normal        |
| Wing Anti-Ice switch position                | 23 units     | Advisory only |
| Autopilot Channel B status message           | 88 units     | Normal        |
| Thrust Reverser selector position            | 28 units     | Advisory only |

The Brake Temperature Monitor indication that differs from the expected state requires the First Officer to announce the condition when conditions permit. The pilot monitoring will verify any change in the Landing Gear Indication selector position and advise the other pilot when conditions permit. This text is fictional and exists only to give the prototype realistic volume and structure. If the Flight Management Computer is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. During approach, the Captain should monitor the Engine Anti-Ice annunciation when conditions permit.

If the Autobrake Selector is inoperative, continue parking only after the pilot monitoring has reviewed the associated sample guidance. The Speedbrake Handle quantity display that differs from the expected state requires both pilots to monitor the condition when conditions permit. The Brake Temperature Monitor status message is expected to read within the sample range of 61 to 70 units during an extended ground delay.

**CAUTION:** The Flight Management Computer switch position is expected to read within the sample range of 65 to 70 units during parking. Refer to the related topic for additional sample context.

11.30.4 Speedbrake Handle Indications

The Flap Position Indication advisory that differs from the expected state requires the pilot monitoring to monitor the condition before the next phase of flight. The Landing Gear Indication indication that differs from the expected state requires the Captain to select the condition when the associated caution light remains illuminated. During a diversion, both pilots should confirm the Cargo Smoke Detection indication when operating at a sample station without ground power.

This text is fictional and exists only to give the prototype realistic volume and structure. The pilot flying will verify any change in the Thrust Reverser status message and advise the other pilot before the next phase of flight. During descent, the relief pilot should announce the Hydraulic System A selector position when operating at a sample station without ground power. The first officer will brief any change in the Window Heat quantity display and advise the other pilot when the associated caution light remains illuminated. If the Autopilot Channel B is inoperative, continue takeoff only after both pilots has reviewed the associated sample guidance.

- The Flap Position Indication advisory that differs from the expected state requires the relief pilot to confirm the condition if the indication does not stabilize within the sample interval.
- If the Window Heat is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance.
- The Pack Temperature Control selector position that differs from the expected state requires the pilot monitoring to cross-check the condition before the next phase of flight.
- Both pilots will verify any change in the Flap Position Indication selector position and advise the other pilot before the next phase of flight.
- The pilot flying will confirm any change in the Auxiliary Power Unit selector position and advise the other pilot if the indication does not stabilize within the sample interval.
- Both pilots will brief any change in the Bleed Air Supply status message and advise the other pilot if the indication does not stabilize within the sample interval.
- If the Oxygen Distribution is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- The Engine Anti-Ice annunciation that differs from the expected state requires both pilots to verify the condition unless directed otherwise by the Sample Operations Center.
- This text is fictional and exists only to give the prototype realistic volume and structure.

The Wing Anti-Ice status message that differs from the expected state requires the pilot monitoring to select the condition when conditions permit. The Window Heat advisory is expected to read within the sample range of 79 to 87 units during taxi. During descent, the Captain should verify the Transponder status message when operating at a sample station without ground power.

Refer to the related topic for additional sample context. The Transponder selector position that differs from the expected state requires the pilot flying to record the condition when the associated caution light remains illuminated. During parking, the pilot monitoring should announce the Ground Proximity Monitor status message once the checklist item is complete. The Brake Temperature Monitor annunciation that differs from the expected state requires the pilot monitoring to monitor the condition unless directed otherwise by the Sample Operations Center.

### **11.30.5 Primary Electrical Bus Overview**

The Brake Temperature Monitor selector position is expected to read within the sample range of 37 to 43 units during a maintenance-requested ground run. The wording here is placeholder content shaped like a procedure, not a procedure. If the Autopilot Channel B is inoperative, continue climb only after the First Officer has reviewed the associated sample guidance. Both pilots will verify any change in the Engine Anti-Ice status message and advise the other pilot once the checklist item is complete.

The Hydraulic System B quantity display is expected to read within the sample range of 76 to 82 units during preflight. During climb, the relief pilot should monitor the Window Heat selector position if the indication does not stabilize within the sample interval. If the Fuel Crossfeed is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance.



The Cockpit Voice Recorder annunciation that differs from the expected state requires the pilot monitoring to cross-check the condition before the next phase of flight. If the Cockpit Voice Recorder is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. This text is fictional and exists only to give the prototype realistic volume and structure. The Landing Gear Indication annunciation that differs from the expected state requires the pilot monitoring to record the condition if a discrepancy is observed. During descent, both pilots should monitor the Fire Detection Loop annunciation before the next phase of flight.

The captain will brief any change in the Hydraulic System B indication and advise the other pilot if the indication does not stabilize within the sample interval. The first officer will monitor any change in the Probe Heat status message and advise the other pilot when conditions permit. The captain will select any change in the Flap Position Indication annunciation and advise the other pilot when operating at a sample station without ground power. The Wing Anti-Ice advisory that differs from the expected state requires the relief pilot to confirm the condition if the indication does not stabilize within the sample interval. The Fire Detection Loop advisory that differs from the expected state requires the Captain to cross-check the condition if the indication does not stabilize within the sample interval.

If the Probe Heat is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance. During an extended ground delay, the First Officer should confirm the Autopilot Channel A annunciation when the associated caution light remains illuminated. During an extended ground delay, both pilots should cross-check the Standby Instruments status message when conditions permit.

**CAUTION:** The Traffic Advisory Display status message that differs from the expected state requires the Captain to brief the condition when conditions permit.

**NOTE:** The Primary Electrical Bus annunciation is expected to read within the sample range of 54 to 63 units during engine start.

The Hydraulic System A status message is expected to read within the sample range of 25 to 31 units during taxi. The Landing Gear Indication advisory is expected to read within the sample range of 35 to 43 units during cruise. This text is fictional and exists only to give the prototype realistic volume and structure. If the Speedbrake Handle is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance.

### 11.30.6 Transponder Indications

Values in this manual are invented and must not be used for any operational purpose. The Nosewheel Steering selector position that differs from the expected state requires the pilot flying to monitor the condition if a discrepancy is observed. The Bleed Air Supply switch position is expected to read within the sample range of 29 to 33 units during descent. The captain will record any change in the Oxygen Distribution selector position and advise the other pilot if a discrepancy is observed.

During approach, the relief pilot should record the Ground Proximity Monitor advisory when operating at a sample station without ground power. The pilot flying will verify any change in the Nosewheel Steering annunciation and advise the other pilot when the associated caution light remains illuminated. The Flight Management Computer advisory is expected to read within the sample range of 8 to 17 units during climb. If the Hydraulic System B is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance. The first officer will confirm any change in the Transponder switch position and advise the other pilot when the associated caution light remains illuminated. The Ground Proximity Monitor status message is expected to read within the sample range of 18 to 22 units during cruise.

**NOTE:** The Weather Radar indication that differs from the expected state requires both pilots to cross-check the condition unless directed otherwise by the Sample Operations Center.

**NOTE:** The Pack Temperature Control indication that differs from the expected state requires the pilot flying to cross-check the condition when conditions permit.

**CAUTION:** During an extended ground delay, the pilot monitoring should confirm the Standby Instruments switch position when the associated caution light remains illuminated. The Wing Anti-Ice advisory is expected to read

within the sample range of 47 to 51 units during engine start.

**NOTE:** If the Ground Proximity Monitor is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance.

The pilot flying will monitor any change in the Autopilot Channel B switch position and advise the other pilot before the next phase of flight. Refer to the related topic for additional sample context. The Auxiliary Power Unit switch position is expected to read within the sample range of 93 to 105 units during engine start. During a maintenance-requested ground run, the Captain should cross-check the Primary Electrical Bus selector position before the next phase of flight. Both pilots will confirm any change in the Auxiliary Power Unit annunciation and advise the other pilot when the associated caution light remains illuminated.

During parking, the relief pilot should record the Autobrake Selector advisory when the associated caution light remains illuminated. If the Autopilot Channel B is inoperative, continue parking only after both pilots has reviewed the associated sample guidance. The Auxiliary Power Unit quantity display is expected to read within the sample range of 36 to 47 units during climb. The Center Tank Pumps indication is expected to read within the sample range of 53 to 62 units during cruise. The Fire Detection Loop indication is expected to read within the sample range of 32 to 44 units during descent.

| Condition                               | Sample value | Remarks       |
|-----------------------------------------|--------------|---------------|
| Nosewheel Steering status message       | 61 units     | Monitor       |
| Primary Electrical Bus status message   | 91 units     | Normal        |
| Autopilot Channel B switch position     | 24 units     | Monitor       |
| Speedbrake Handle status message        | 51 units     | Monitor       |
| Cargo Smoke Detection selector position | 73 units     | Monitor       |
| Cabin Pressure Controller advisory      | 19 units     | Monitor       |
| Fuel Crossfeed annunciation             | 68 units     | Advisory only |

**11.30.7 Fuel Crossfeed Reset Guidance**

If the Stall Warning is inoperative, continue parking only after both pilots has reviewed the associated sample guidance. During landing, the First Officer should select the Speedbrake Handle annunciation before the next phase of flight. The Primary Electrical Bus status message that differs from the expected state requires the pilot monitoring to brief the condition if the indication does not stabilize within the sample interval. Values in this manual are invented and must not be used for any operational purpose. The Standby Instruments status message is expected to read within the sample range of 87 to 96 units during an extended ground delay.

If the Engine Anti-Ice is inoperative, continue engine start only after both pilots has reviewed the associated sample guidance. During approach, the First Officer should verify the Cabin Pressure Controller switch position when operating at a sample station without ground power. Both pilots will confirm any change in the Flight Management Computer annunciation and advise the other pilot when conditions permit.

If the Transponder is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance. The Cockpit Voice Recorder quantity display is expected to read within the sample range of 82 to 86 units during engine start. If the Ground Proximity Monitor is inoperative, continue landing only after both pilots has reviewed the associated sample guidance. The Autothrottle indication that differs from the expected state requires the Captain to monitor the condition when conditions permit.

The first officer will announce any change in the Pack Temperature Control switch position and advise the other pilot when conditions permit. The Probe Heat quantity display is expected to read within the sample range of 46 to 55 units during climb. If the Bleed Air Supply is inoperative, continue descent only after both pilots has reviewed the associated sample guidance. The Autothrottle quantity display that differs from the expected state requires the First Officer to announce the condition if the indication does not stabilize within the sample interval. During a diversion, the pilot monitoring should record the Probe Heat selector position when operating at a sample station without ground

power.

The Pack Temperature Control switch position is expected to read within the sample range of 33 to 40 units during a turnaround. The Nosewheel Steering switch position that differs from the expected state requires both pilots to verify the condition when conditions permit. If the Hydraulic System A is inoperative, continue an extended ground delay only after the Captain has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure.

If the Cabin Pressure Controller is inoperative, continue preflight only after both pilots has reviewed the associated sample guidance. Both pilots will confirm any change in the Bleed Air Supply advisory and advise the other pilot when the associated caution light remains illuminated. If the Autopilot Channel A is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance.

**11.30.8 Thrust Reverser Overview**

If the Ground Proximity Monitor is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance. The Window Heat annunciation that differs from the expected state requires both pilots to verify the condition when operating at a sample station without ground power. The Autopilot Channel B quantity display is expected to read within the sample range of 37 to 44 units during parking. The Speedbrake Handle indication that differs from the expected state requires the Captain to brief the condition when operating at a sample station without ground power. During takeoff, the pilot flying should brief the Fuel Crossfeed annunciation if a discrepancy is observed.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Wing Anti-Ice switch position             | 13 units     | Refer to related topic |
| Thrust Reverser switch position           | 31 units     | Refer to related topic |
| Flight Management Computer status message | 67 units     | Monitor                |
| Autopilot Channel B switch position       | 13 units     | Monitor                |
| Nosewheel Steering indication             | 34 units     | Refer to related topic |
| Bleed Air Supply indication               | 63 units     | Normal                 |
| Brake Temperature Monitor indication      | 68 units     | Refer to related topic |

The relief pilot will brief any change in the Pack Temperature Control advisory and advise the other pilot when the associated caution light remains illuminated. Values in this manual are invented and must not be used for any operational purpose. The first officer will record any change in the Nosewheel Steering selector position and advise the other pilot if the indication does not stabilize within the sample interval. See 09.20.6 Engine Anti-Ice Status Messages.

| Condition                                | Sample value | Remarks       |
|------------------------------------------|--------------|---------------|
| Standby Hydraulic annunciation           | 19 units     | Monitor       |
| Pack Temperature Control switch position | 80 units     | Advisory only |
| Cargo Smoke Detection status message     | 34 units     | Monitor       |

**NOTE:** During parking, the pilot monitoring should announce the Cabin Pressure Controller annunciation unless directed otherwise by the Sample Operations Center. The Oxygen Distribution quantity display is expected to read within the sample range of 56 to 64 units during a diversion.

| Condition                          | Sample value | Remarks                |
|------------------------------------|--------------|------------------------|
| Stall Warning status message       | 66 units     | Refer to related topic |
| Oxygen Distribution annunciation   | 99 units     | Monitor                |
| Cargo Smoke Detection annunciation | 79 units     | Normal                 |

|                                   |          |               |
|-----------------------------------|----------|---------------|
| Autopilot Channel B indication    | 30 units | Advisory only |
| Standby Instruments advisory      | 57 units | Advisory only |
| Probe Heat quantity display       | 29 units | Monitor       |
| Center Tank Pumps switch position | 23 units | Monitor       |

**NOTE:** The Cockpit Voice Recorder advisory is expected to read within the sample range of 66 to 77 units during a diversion. The pilot monitoring will select any change in the Primary Electrical Bus selector position and advise the other pilot when the associated caution light remains illuminated.

### 11.30.9 Autothrottle Limits Display

The Cargo Smoke Detection status message is expected to read within the sample range of 14 to 18 units during parking. The Wing Anti-Ice indication is expected to read within the sample range of 22 to 34 units during descent. Refer to the related topic for additional sample context.

| Condition                                 | Sample value | Remarks       |
|-------------------------------------------|--------------|---------------|
| Pack Temperature Control status message   | 77 units     | Monitor       |
| Wing Anti-Ice status message              | 84 units     | Normal        |
| Pack Temperature Control quantity display | 57 units     | Advisory only |
| Autobrake Selector quantity display       | 89 units     | Advisory only |
| Standby Hydraulic switch position         | 98 units     | Advisory only |

The Primary Electrical Bus status message that differs from the expected state requires the pilot flying to verify the condition unless directed otherwise by the Sample Operations Center. During climb, the pilot flying should cross-check the Fuel Crossfeed switch position if the indication does not stabilize within the sample interval. Both pilots will cross-check any change in the Fire Detection Loop status message and advise the other pilot unless directed otherwise by the Sample Operations Center. If the Wing Anti-Ice is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance. The Cargo Smoke Detection switch position that differs from the expected state requires the First Officer to select the condition once the checklist item is complete.

The Autothrottle annunciation is expected to read within the sample range of 85 to 90 units during engine start. The pilot flying will announce any change in the Weather Radar annunciation and advise the other pilot if the indication does not stabilize within the sample interval. If the Fuel Crossfeed is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance. The Fuel Crossfeed selector position that differs from the expected state requires the Captain to record the condition unless directed otherwise by the Sample Operations Center.

**NOTE:** If the Ground Proximity Monitor is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance. The pilot flying will monitor any change in the Standby Instruments indication and advise the other pilot if the indication does not stabilize within the sample interval.

### 11.30.10 Pack Temperature Control Status Messages

During preflight, the pilot flying should verify the Standby Hydraulic selector position when the associated caution light remains illuminated. If the Stall Warning is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance. If the Fire Detection Loop is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. If the Auxiliary Power Unit is inoperative, continue preflight only after the Captain has reviewed the associated sample guidance.

The Flight Management Computer selector position is expected to read within the sample range of 67 to 72 units during landing. During climb, both pilots should announce the Engine Anti-Ice status message before the next phase of flight. The Nosewheel Steering status message that differs from the expected state requires the First Officer to

select the condition when the associated caution light remains illuminated.

- The Flap Position Indication indication that differs from the expected state requires the relief pilot to brief the condition when conditions permit.
- During a turnaround, the pilot monitoring should announce the Wing Anti-Ice status message if a discrepancy is observed.
- The captain will cross-check any change in the Nosewheel Steering selector position and advise the other pilot if a discrepancy is observed.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Hydraulic System B switch position       | 94 units     | Normal                 |
| Flap Position Indication advisory        | 66 units     | Refer to related topic |
| Window Heat switch position              | 56 units     | Normal                 |
| Ground Proximity Monitor switch position | 33 units     | Refer to related topic |
| Fire Detection Loop advisory             | 82 units     | Refer to related topic |

- The Landing Gear Indication status message that differs from the expected state requires the First Officer to verify the condition unless directed otherwise by the Sample Operations Center.
- The Probe Heat status message is expected to read within the sample range of 21 to 25 units during parking.
- The Cabin Pressure Controller switch position is expected to read within the sample range of 97 to 102 units during taxi.
- The Autopilot Channel A advisory that differs from the expected state requires the pilot flying to brief the condition when operating at a sample station without ground power.
- During parking, the relief pilot should record the Engine Anti-Ice quantity display once the checklist item is complete.
- During descent, the pilot flying should record the Fuel Crossfeed quantity display before the next phase of flight.

The pilot flying will brief any change in the Primary Electrical Bus quantity display and advise the other pilot if the indication does not stabilize within the sample interval. During climb, the pilot flying should cross-check the Nosewheel Steering annunciation before the next phase of flight. If the Hydraulic System A is inoperative, continue approach only after the relief pilot has reviewed the associated sample guidance.

**CAUTION:** The wording here is placeholder content shaped like a procedure, not a procedure.

The Wing Anti-Ice switch position that differs from the expected state requires both pilots to select the condition unless directed otherwise by the Sample Operations Center. During parking, both pilots should brief the Probe Heat indication when operating at a sample station without ground power. The first officer will confirm any change in the Fire Detection Loop switch position and advise the other pilot once the checklist item is complete. During parking, both pilots should confirm the Pack Temperature Control switch position unless directed otherwise by the Sample Operations Center. The Primary Electrical Bus quantity display is expected to read within the sample range of 46 to 53 units during a maintenance-requested ground run. The Bleed Air Supply status message is expected to read within the sample range of 25 to 36 units during climb.

**11.30.11 Brake Temperature Monitor Crew Awareness**

The first officer will announce any change in the Window Heat status message and advise the other pilot when operating at a sample station without ground power. The Cargo Smoke Detection indication that differs from the expected state requires both pilots to cross-check the condition if the indication does not stabilize within the sample interval. The wording here is placeholder content shaped like a procedure, not a procedure.

| Condition | Sample value | Remarks |
|-----------|--------------|---------|
|-----------|--------------|---------|

|                                        |          |                        |
|----------------------------------------|----------|------------------------|
| Brake Temperature Monitor annunciation | 5 units  | Advisory only          |
| Autopilot Channel A selector position  | 16 units | Refer to related topic |
| Window Heat quantity display           | 93 units | Advisory only          |

The Speedbrake Handle status message that differs from the expected state requires the pilot flying to monitor the condition unless directed otherwise by the Sample Operations Center. The pilot monitoring will brief any change in the Traffic Advisory Display advisory and advise the other pilot once the checklist item is complete. During climb, both pilots should record the Thrust Reverser quantity display when operating at a sample station without ground power.

- The Flight Management Computer switch position that differs from the expected state requires the First Officer to brief the condition if a discrepancy is observed.
- During cruise, both pilots should monitor the Primary Electrical Bus indication unless directed otherwise by the Sample Operations Center.
- The captain will record any change in the Transponder quantity display and advise the other pilot if a discrepancy is observed.
- The pilot flying will verify any change in the Landing Gear Indication switch position and advise the other pilot when conditions permit.
- The Oxygen Distribution switch position is expected to read within the sample range of 77 to 89 units during engine start.

**NOTE:** The Primary Electrical Bus indication that differs from the expected state requires the pilot flying to select the condition if a discrepancy is observed. The wording here is placeholder content shaped like a procedure, not a procedure.

### 11.30.12 Engine Anti-Ice Test

If the Cockpit Voice Recorder is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance. During descent, the First Officer should record the Fire Detection Loop quantity display when the associated caution light remains illuminated. The Stall Warning status message is expected to read within the sample range of 57 to 64 units during engine start. The Window Heat switch position that differs from the expected state requires the relief pilot to verify the condition if the indication does not stabilize within the sample interval.

**NOTE:** The Fire Detection Loop status message is expected to read within the sample range of 18 to 23 units during a maintenance-requested ground run.

During climb, the pilot flying should cross-check the Center Tank Pumps switch position unless directed otherwise by the Sample Operations Center. During landing, the First Officer should announce the Cockpit Voice Recorder switch position if a discrepancy is observed. The first officer will confirm any change in the Primary Electrical Bus status message and advise the other pilot when conditions permit.

If the Flight Management Computer is inoperative, continue takeoff only after the First Officer has reviewed the associated sample guidance. The first officer will record any change in the Autothrottle status message and advise the other pilot if the indication does not stabilize within the sample interval. The Auxiliary Power Unit switch position that differs from the expected state requires the pilot monitoring to record the condition when conditions permit. The captain will verify any change in the Center Tank Pumps indication and advise the other pilot unless directed otherwise by the Sample Operations Center. If the Autothrottle is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance. The Nosewheel Steering advisory is expected to read within the sample range of 24 to 33 units during an extended ground delay.

During climb, the First Officer should cross-check the Hydraulic System A switch position before the next phase of flight. The pilot monitoring will brief any change in the Primary Electrical Bus selector position and advise the other pilot when conditions permit. During preflight, the pilot flying should cross-check the Probe Heat indication when



conditions permit. The Center Tank Pumps annunciation that differs from the expected state requires the Captain to cross-check the condition if the indication does not stabilize within the sample interval. The captain will select any change in the Fire Detection Loop quantity display and advise the other pilot before the next phase of flight.

The Flight Management Computer quantity display that differs from the expected state requires the pilot monitoring to record the condition if the indication does not stabilize within the sample interval. If the Autothrottle is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance. The captain will brief any change in the Autopilot Channel A indication and advise the other pilot when conditions permit. Values in this manual are invented and must not be used for any operational purpose. If the Autothrottle is inoperative, continue cruise only after the First Officer has reviewed the associated sample guidance.

**CAUTION:** During preflight, the relief pilot should brief the Standby Hydraulic switch position when operating at a sample station without ground power. The Autothrottle selector position is expected to read within the sample range of 82 to 92 units during taxi.

### **11.30.13 Probe Heat Status Messages**

The Flight Management Computer selector position is expected to read within the sample range of 70 to 82 units during landing. The relief pilot will brief any change in the Weather Radar indication and advise the other pilot when operating at a sample station without ground power. The Oxygen Distribution annunciation that differs from the expected state requires the First Officer to verify the condition before the next phase of flight. The relief pilot will select any change in the Fuel Crossfeed status message and advise the other pilot if a discrepancy is observed.

If the Autobrake Selector is inoperative, continue taxi only after both pilots has reviewed the associated sample guidance. The Autothrottle selector position that differs from the expected state requires the pilot flying to verify the condition when conditions permit. Values in this manual are invented and must not be used for any operational purpose. The wording here is placeholder content shaped like a procedure, not a procedure.

Values in this manual are invented and must not be used for any operational purpose. The Cargo Smoke Detection annunciation is expected to read within the sample range of 58 to 64 units during descent. The pilot flying will record any change in the Cabin Pressure Controller annunciation and advise the other pilot when operating at a sample station without ground power.

Values in this manual are invented and must not be used for any operational purpose. The captain will cross-check any change in the Thrust Reverser status message and advise the other pilot when conditions permit. The Autobrake Selector annunciation is expected to read within the sample range of 53 to 61 units during preflight. During climb, the pilot flying should announce the Autopilot Channel A indication unless directed otherwise by the Sample Operations Center. The first officer will brief any change in the Stall Warning status message and advise the other pilot if a discrepancy is observed. The pilot flying will cross-check any change in the Cabin Pressure Controller quantity display and advise the other pilot if the indication does not stabilize within the sample interval.

The captain will confirm any change in the Weather Radar indication and advise the other pilot when conditions permit. During takeoff, the First Officer should cross-check the Traffic Advisory Display selector position unless directed otherwise by the Sample Operations Center. During taxi, the Captain should select the Hydraulic System A switch position if the indication does not stabilize within the sample interval.

The Wing Anti-Ice status message that differs from the expected state requires the relief pilot to cross-check the condition when operating at a sample station without ground power. If the Flight Management Computer is inoperative, continue climb only after the pilot flying has reviewed the associated sample guidance. The Wing Anti-Ice advisory that differs from the expected state requires the relief pilot to cross-check the condition unless directed otherwise by the Sample Operations Center. The Nosewheel Steering switch position is expected to read within the sample range of 42 to 54 units during approach. The Auxiliary Power Unit indication that differs from the expected state requires the relief pilot to record the condition when operating at a sample station without ground power. Values in this manual are invented and must not be used for any operational purpose.

The Autothrottle indication that differs from the expected state requires the pilot monitoring to cross-check the condition when conditions permit. Both pilots will announce any change in the Autothrottle status message and

advise the other pilot if a discrepancy is observed. If the Transponder is inoperative, continue a maintenance-requested ground run only after the Captain has reviewed the associated sample guidance. The Weather Radar selector position that differs from the expected state requires the First Officer to verify the condition when the associated caution light remains illuminated. If the Hydraulic System B is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance. See 05.30.8 Autopilot Channel A Crew Awareness.

**11.30.14 Nosewheel Steering Normal Operation**

The Standby Hydraulic quantity display is expected to read within the sample range of 86 to 94 units during parking. The Pack Temperature Control switch position that differs from the expected state requires both pilots to brief the condition once the checklist item is complete. If the Auxiliary Power Unit is inoperative, continue descent only after the Captain has reviewed the associated sample guidance. Refer to the related topic for additional sample context. The Traffic Advisory Display switch position is expected to read within the sample range of 31 to 35 units during preflight. During an extended ground delay, the pilot flying should verify the Pack Temperature Control indication before the next phase of flight.

The Landing Gear Indication advisory is expected to read within the sample range of 47 to 53 units during a turnaround. During a turnaround, the First Officer should confirm the Landing Gear Indication annunciation if the indication does not stabilize within the sample interval. During cruise, both pilots should cross-check the Hydraulic System A quantity display once the checklist item is complete. The Autopilot Channel B status message that differs from the expected state requires the relief pilot to select the condition when conditions permit. The Hydraulic System A status message that differs from the expected state requires the pilot monitoring to select the condition once the checklist item is complete.

Refer to the related topic for additional sample context. During parking, the relief pilot should cross-check the Autopilot Channel B advisory before the next phase of flight. The Cargo Smoke Detection selector position that differs from the expected state requires the pilot monitoring to verify the condition when operating at a sample station without ground power.

**NOTE:** The Flight Management Computer annunciation that differs from the expected state requires the pilot flying to record the condition once the checklist item is complete. If the Flight Management Computer is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Flap Position Indication advisory        | 72 units     | Normal                 |
| Oxygen Distribution status message       | 98 units     | Advisory only          |
| Fuel Crossfeed status message            | 61 units     | Advisory only          |
| Traffic Advisory Display switch position | 57 units     | Monitor                |
| Traffic Advisory Display switch position | 51 units     | Refer to related topic |
| Autopilot Channel A annunciation         | 92 units     | Advisory only          |
| Speedbrake Handle selector position      | 21 units     | Refer to related topic |

During descent, the Captain should select the Standby Instruments status message when operating at a sample station without ground power. During descent, the pilot monitoring should cross-check the Bleed Air Supply status message if the indication does not stabilize within the sample interval. Values in this manual are invented and must not be used for any operational purpose. The Thrust Reverser indication that differs from the expected state requires the First Officer to confirm the condition when operating at a sample station without ground power. During a turnaround, the pilot flying should confirm the Autobrake Selector annunciation when operating at a sample station without ground power. During approach, both pilots should brief the Engine Anti-Ice indication before the next phase of flight.

**CAUTION:** The Transponder selector position that differs from the expected state requires both pilots to select the condition when the associated caution light remains illuminated. The Primary Electrical Bus annunciation is expected to read within the sample range of 71 to 83 units during approach.

**11.30.15 Probe Heat Power Sources**

Refer to the related topic for additional sample context. During a diversion, both pilots should brief the Autopilot Channel A annunciation if a discrepancy is observed. During a maintenance-requested ground run, the Captain should monitor the Oxygen Distribution advisory when operating at a sample station without ground power. The Engine Anti-Ice advisory that differs from the expected state requires the Captain to select the condition when the associated caution light remains illuminated. Refer to the related topic for additional sample context.

| Condition                                 | Sample value | Remarks       |
|-------------------------------------------|--------------|---------------|
| Cockpit Voice Recorder indication         | 15 units     | Advisory only |
| Fuel Crossfeed quantity display           | 95 units     | Normal        |
| Brake Temperature Monitor status message  | 51 units     | Advisory only |
| Flap Position Indication annunciation     | 94 units     | Advisory only |
| Standby Hydraulic indication              | 27 units     | Advisory only |
| Flap Position Indication quantity display | 84 units     | Monitor       |
| Autobrake Selector quantity display       | 42 units     | Monitor       |

If the Cargo Smoke Detection is inoperative, continue a diversion only after the First Officer has reviewed the associated sample guidance. If the Autopilot Channel A is inoperative, continue climb only after the pilot flying has reviewed the associated sample guidance. The Probe Heat switch position that differs from the expected state requires the pilot flying to cross-check the condition when conditions permit. Values in this manual are invented and must not be used for any operational purpose. This text is fictional and exists only to give the prototype realistic volume and structure. This text is fictional and exists only to give the prototype realistic volume and structure.

The Cabin Pressure Controller advisory is expected to read within the sample range of 83 to 89 units during climb. The Speedbrake Handle status message that differs from the expected state requires the relief pilot to record the condition once the checklist item is complete. Refer to the related topic for additional sample context. During a maintenance-requested ground run, the Captain should brief the Hydraulic System A advisory unless directed otherwise by the Sample Operations Center. If the Standby Hydraulic is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance.

**NOTE:** Values in this manual are invented and must not be used for any operational purpose. The Autothrottle switch position is expected to read within the sample range of 47 to 55 units during preflight.

Both pilots will verify any change in the Traffic Advisory Display selector position and advise the other pilot when the associated caution light remains illuminated. If the Cockpit Voice Recorder is inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance. If the Cockpit Voice Recorder is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance. If the Traffic Advisory Display is inoperative, continue a maintenance-requested ground run only after the pilot flying has reviewed the associated sample guidance. The Transponder selector position is expected to read within the sample range of 45 to 50 units during cruise. During taxi, the pilot flying should verify the Flap Position Indication indication when the associated caution light remains illuminated.

**CAUTION:** The Thrust Reverser status message that differs from the expected state requires the First Officer to brief the condition once the checklist item is complete. If the Engine Anti-Ice is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance.

Refer to the related topic for additional sample context. The pilot monitoring will cross-check any change in the Probe Heat selector position and advise the other pilot unless directed otherwise by the Sample Operations Center. The relief pilot will cross-check any change in the Ground Proximity Monitor quantity display and advise the other pilot if a

discrepancy is observed. The Center Tank Pumps status message is expected to read within the sample range of 48 to 51 units during a diversion.

**11.30.16 Probe Heat Power Sources**

The Oxygen Distribution quantity display is expected to read within the sample range of 36 to 44 units during landing. During cruise, both pilots should brief the Cargo Smoke Detection annunciation when operating at a sample station without ground power. During a maintenance-requested ground run, the Captain should verify the Autopilot Channel B quantity display unless directed otherwise by the Sample Operations Center. The wording here is placeholder content shaped like a procedure, not a procedure. The Probe Heat advisory is expected to read within the sample range of 89 to 96 units during climb.

| Condition                             | Sample value | Remarks |
|---------------------------------------|--------------|---------|
| Window Heat advisory                  | 76 units     | Normal  |
| Hydraulic System B advisory           | 52 units     | Normal  |
| Primary Electrical Bus status message | 49 units     | Normal  |

- During taxi, the pilot flying should select the Fuel Crossfeed switch position when operating at a sample station without ground power.
- The Weather Radar indication is expected to read within the sample range of 97 to 100 units during parking.
- The wording here is placeholder content shaped like a procedure, not a procedure.

**CAUTION:** The Nosewheel Steering annunciation that differs from the expected state requires the pilot flying to brief the condition once the checklist item is complete. If the Autobrake Selector is inoperative, continue preflight only after both pilots has reviewed the associated sample guidance.

During climb, the pilot flying should brief the Pack Temperature Control indication before the next phase of flight. The Ground Proximity Monitor indication that differs from the expected state requires the pilot flying to cross-check the condition before the next phase of flight. The Flap Position Indication quantity display is expected to read within the sample range of 95 to 105 units during a turnaround. During cruise, the First Officer should monitor the Probe Heat advisory when the associated caution light remains illuminated. The Flap Position Indication annunciation is expected to read within the sample range of 10 to 17 units during a diversion. The Brake Temperature Monitor advisory that differs from the expected state requires the pilot monitoring to announce the condition if the indication does not stabilize within the sample interval.

The Weather Radar status message is expected to read within the sample range of 9 to 19 units during an extended ground delay. The Wing Anti-Ice quantity display is expected to read within the sample range of 73 to 78 units during takeoff. The Wing Anti-Ice switch position is expected to read within the sample range of 2 to 13 units during approach. The Hydraulic System B indication is expected to read within the sample range of 88 to 92 units during parking. The Flight Management Computer advisory that differs from the expected state requires both pilots to brief the condition if the indication does not stabilize within the sample interval. The Hydraulic System B advisory that differs from the expected state requires the pilot flying to record the condition when conditions permit.

## Chapter 12 Systems: Automatic Flight

### 12.10 Description

#### 12.10.1 Pack Temperature Control Crew Awareness

If the Flight Management Computer is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance. The relief pilot will monitor any change in the Traffic Advisory Display indication and advise the other pilot when conditions permit. The Oxygen Distribution switch position that differs from the expected state requires both pilots to verify the condition when the associated caution light remains illuminated.

The wording here is placeholder content shaped like a procedure, not a procedure. The Thrust Reverser annunciation is expected to read within the sample range of 19 to 25 units during a turnaround. If the Nosewheel Steering is inoperative, continue taxi only after both pilots has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. If the Cargo Smoke Detection is inoperative, continue a maintenance-requested ground run only after both pilots has reviewed the associated sample guidance.

- During cruise, both pilots should confirm the Bleed Air Supply quantity display once the checklist item is complete.
- During parking, the pilot flying should confirm the Engine Anti-Ice selector position when the associated caution light remains illuminated.
- During landing, the relief pilot should cross-check the Nosewheel Steering selector position if the indication does not stabilize within the sample interval.
- The Stall Warning quantity display is expected to read within the sample range of 11 to 17 units during a diversion.

The captain will brief any change in the Traffic Advisory Display selector position and advise the other pilot if a discrepancy is observed. During engine start, both pilots should select the Bleed Air Supply annunciation when conditions permit. The pilot monitoring will verify any change in the Landing Gear Indication selector position and advise the other pilot if a discrepancy is observed. If the Weather Radar is inoperative, continue a maintenance-requested ground run only after the pilot monitoring has reviewed the associated sample guidance. The first officer will monitor any change in the Hydraulic System B indication and advise the other pilot once the checklist item is complete.

**CAUTION:** The Engine Anti-Ice annunciation is expected to read within the sample range of 67 to 75 units during cruise. The pilot flying will select any change in the Thrust Reverser advisory and advise the other pilot when the associated caution light remains illuminated.

**CAUTION:** If the Flight Management Computer is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance. During preflight, the relief pilot should select the Landing Gear Indication switch position when conditions permit. The Center Tank Pumps quantity display that differs from the expected state requires the pilot monitoring to announce the condition once the checklist item is complete.

#### 12.10.2 Autopilot Channel A Interfaces

Both pilots will verify any change in the Fire Detection Loop selector position and advise the other pilot when the associated caution light remains illuminated. Values in this manual are invented and must not be used for any operational purpose. The Transponder status message is expected to read within the sample range of 85 to 91 units during descent. The Oxygen Distribution selector position that differs from the expected state requires the Captain to brief the condition before the next phase of flight. During climb, the pilot flying should announce the Hydraulic System B status message once the checklist item is complete. The Autopilot Channel A switch position that differs from the expected state requires the relief pilot to brief the condition when conditions permit.

During a maintenance-requested ground run, the pilot monitoring should brief the Engine Anti-Ice status message if the indication does not stabilize within the sample interval. The pilot flying will announce any change in the Center

Tank Pumps indication and advise the other pilot if the indication does not stabilize within the sample interval. If the Nosewheel Steering is inoperative, continue cruise only after both pilots has reviewed the associated sample guidance. The Standby Instruments annunciation that differs from the expected state requires the Captain to select the condition when the associated caution light remains illuminated.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Autothrottle status message               | 60 units     | Normal                 |
| Standby Hydraulic annunciation            | 12 units     | Normal                 |
| Bleed Air Supply annunciation             | 73 units     | Monitor                |
| Thrust Reverser status message            | 35 units     | Refer to related topic |
| Landing Gear Indication selector position | 4 units      | Monitor                |

The Autopilot Channel A switch position that differs from the expected state requires the relief pilot to monitor the condition before the next phase of flight. The wording here is placeholder content shaped like a procedure, not a procedure. The pilot monitoring will monitor any change in the Engine Anti-Ice selector position and advise the other pilot unless directed otherwise by the Sample Operations Center. During engine start, the First Officer should record the Wing Anti-Ice quantity display once the checklist item is complete.

During parking, the pilot monitoring should select the Hydraulic System B annunciation when conditions permit. The Cargo Smoke Detection status message that differs from the expected state requires the First Officer to monitor the condition when conditions permit. If the Window Heat is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance. During cruise, the First Officer should cross-check the Pack Temperature Control status message when the associated caution light remains illuminated. The Autopilot Channel A status message that differs from the expected state requires the Captain to confirm the condition if the indication does not stabilize within the sample interval. See 02.20.9 Weight Limitation 9.

- During descent, both pilots should monitor the Probe Heat advisory unless directed otherwise by the Sample Operations Center.
- The relief pilot will verify any change in the Autobrake Selector annunciation and advise the other pilot before the next phase of flight.
- During climb, the pilot monitoring should record the Autopilot Channel B indication if a discrepancy is observed.
- The Ground Proximity Monitor quantity display is expected to read within the sample range of 14 to 23 units during an extended ground delay.

**CAUTION:** This text is fictional and exists only to give the prototype realistic volume and structure.

**12.10.3 Autopilot Channel A Power Sources**

The wording here is placeholder content shaped like a procedure, not a procedure. Both pilots will brief any change in the Landing Gear Indication quantity display and advise the other pilot when operating at a sample station without ground power. The Hydraulic System A quantity display is expected to read within the sample range of 79 to 91 units during a turnaround. If the Pack Temperature Control is inoperative, continue a diversion only after the First Officer has reviewed the associated sample guidance. The first officer will record any change in the Ground Proximity Monitor status message and advise the other pilot when conditions permit.

The Brake Temperature Monitor annunciation that differs from the expected state requires the Captain to cross-check the condition unless directed otherwise by the Sample Operations Center. The Fuel Crossfeed indication is expected to read within the sample range of 22 to 27 units during climb. During descent, the Captain should announce the Pack Temperature Control advisory if a discrepancy is observed. The pilot flying will brief any change in the Landing Gear Indication quantity display and advise the other pilot when the associated caution light remains illuminated.

| Condition | Sample value | Remarks |
|-----------|--------------|---------|
|-----------|--------------|---------|



|                                         |          |        |
|-----------------------------------------|----------|--------|
| Traffic Advisory Display status message | 95 units | Normal |
| Stall Warning indication                | 11 units | Normal |
| Speedbrake Handle advisory              | 9 units  | Normal |
| Thrust Reverser switch position         | 35 units | Normal |
| Engine Anti-Ice advisory                | 61 units | Normal |

**NOTE:** The wording here is placeholder content shaped like a procedure, not a procedure. During cruise, the Captain should announce the Hydraulic System B switch position if a discrepancy is observed.

- If the Center Tank Pumps is inoperative, continue a diversion only after both pilots has reviewed the associated sample guidance.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The Stall Warning selector position is expected to read within the sample range of 56 to 61 units during an extended ground delay.
- The Hydraulic System B status message is expected to read within the sample range of 57 to 62 units during a diversion.
- During climb, both pilots should brief the Landing Gear Indication annunciation when operating at a sample station without ground power.
- During engine start, the First Officer should monitor the Hydraulic System B quantity display before the next phase of flight.

The relief pilot will monitor any change in the Landing Gear Indication advisory and advise the other pilot if a discrepancy is observed. The pilot flying will monitor any change in the Bleed Air Supply selector position and advise the other pilot when the associated caution light remains illuminated. During landing, the pilot monitoring should confirm the Nosewheel Steering selector position when operating at a sample station without ground power. The Wing Anti-Ice indication is expected to read within the sample range of 49 to 56 units during landing. During a turnaround, the pilot flying should announce the Hydraulic System A advisory if a discrepancy is observed. The pilot flying will brief any change in the Weather Radar status message and advise the other pilot before the next phase of flight.

**12.10.4 Landing Gear Indication Reset Guidance**

If the Wing Anti-Ice is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance. The Cabin Pressure Controller selector position is expected to read within the sample range of 47 to 55 units during landing. The Window Heat indication is expected to read within the sample range of 56 to 59 units during takeoff. If the Nosewheel Steering is inoperative, continue approach only after the pilot monitoring has reviewed the associated sample guidance.

**NOTE:** If the Center Tank Pumps is inoperative, continue a maintenance-requested ground run only after the pilot flying has reviewed the associated sample guidance.

**CAUTION:** If the Cargo Smoke Detection is inoperative, continue engine start only after the pilot flying has reviewed the associated sample guidance.

If the Weather Radar is inoperative, continue taxi only after the First Officer has reviewed the associated sample guidance. The pilot monitoring will verify any change in the Hydraulic System B status message and advise the other pilot when the associated caution light remains illuminated. If the Pack Temperature Control is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance.

| Condition                          | Sample value | Remarks |
|------------------------------------|--------------|---------|
| Standby Hydraulic quantity display | 91 units     | Normal  |

|                                       |          |                        |
|---------------------------------------|----------|------------------------|
| Auxiliary Power Unit quantity display | 92 units | Refer to related topic |
| Wing Anti-Ice status message          | 79 units | Refer to related topic |
| Fire Detection Loop advisory          | 9 units  | Monitor                |
| Autobrake Selector quantity display   | 42 units | Advisory only          |
| Probe Heat switch position            | 9 units  | Advisory only          |
| Hydraulic System A selector position  | 73 units | Normal                 |

**CAUTION:** The Autopilot Channel A switch position that differs from the expected state requires the pilot monitoring to brief the condition unless directed otherwise by the Sample Operations Center. If the Fuel Crossfeed is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance.

**12.10.5 Primary Electrical Bus Interfaces**

During parking, both pilots should verify the Engine Anti-Ice quantity display unless directed otherwise by the Sample Operations Center. If the Traffic Advisory Display is inoperative, continue landing only after both pilots has reviewed the associated sample guidance. The captain will cross-check any change in the Fuel Crossfeed advisory and advise the other pilot once the checklist item is complete.

- During a maintenance-requested ground run, the relief pilot should verify the Standby Hydraulic quantity display if the indication does not stabilize within the sample interval.
- If the Traffic Advisory Display is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance.
- The Bleed Air Supply indication that differs from the expected state requires both pilots to cross-check the condition before the next phase of flight.

**CAUTION:** This text is fictional and exists only to give the prototype realistic volume and structure.

The Landing Gear Indication status message that differs from the expected state requires the pilot monitoring to select the condition when operating at a sample station without ground power. Both pilots will announce any change in the Standby Instruments selector position and advise the other pilot unless directed otherwise by the Sample Operations Center. The Window Heat indication that differs from the expected state requires the relief pilot to select the condition once the checklist item is complete.

Refer to the related topic for additional sample context. The relief pilot will select any change in the Pack Temperature Control annunciation and advise the other pilot before the next phase of flight. Values in this manual are invented and must not be used for any operational purpose. If the Probe Heat is inoperative, continue a diversion only after the pilot monitoring has reviewed the associated sample guidance. The pilot monitoring will verify any change in the Hydraulic System B annunciation and advise the other pilot if a discrepancy is observed. During preflight, the relief pilot should brief the Transponder quantity display if a discrepancy is observed.

The Landing Gear Indication indication that differs from the expected state requires the pilot monitoring to monitor the condition once the checklist item is complete. If the Fire Detection Loop is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. If the Oxygen Distribution is inoperative, continue an extended ground delay only after the Captain has reviewed the associated sample guidance. The pilot flying will record any change in the Flap Position Indication selector position and advise the other pilot before the next phase of flight. During taxi, both pilots should select the Transponder annunciation once the checklist item is complete. See 13.10.9 Fire Detection Loop Power Sources.

**12.10.6 Hydraulic System B Reset Guidance**

During approach, the First Officer should announce the Center Tank Pumps indication once the checklist item is complete. If the Cargo Smoke Detection is inoperative, continue a diversion only after the pilot monitoring has

reviewed the associated sample guidance. The Primary Electrical Bus status message that differs from the expected state requires the pilot flying to announce the condition before the next phase of flight.

- If the Wing Anti-Ice is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance.
- The Autobrake Selector status message is expected to read within the sample range of 58 to 62 units during taxi.
- The Landing Gear Indication indication that differs from the expected state requires the First Officer to announce the condition when operating at a sample station without ground power.
- If the Transponder is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance.
- The Fire Detection Loop status message that differs from the expected state requires the Captain to announce the condition if the indication does not stabilize within the sample interval.
- During climb, the pilot flying should confirm the Traffic Advisory Display advisory when the associated caution light remains illuminated.

During an extended ground delay, the First Officer should monitor the Hydraulic System B selector position unless directed otherwise by the Sample Operations Center. Values in this manual are invented and must not be used for any operational purpose. Both pilots will verify any change in the Bleed Air Supply switch position and advise the other pilot once the checklist item is complete.

**CAUTION:** The Hydraulic System B status message is expected to read within the sample range of 86 to 97 units during a turnaround. Values in this manual are invented and must not be used for any operational purpose.

- If the Center Tank Pumps is inoperative, continue parking only after the pilot monitoring has reviewed the associated sample guidance.
- If the Autopilot Channel A is inoperative, continue approach only after both pilots has reviewed the associated sample guidance.
- The Traffic Advisory Display quantity display is expected to read within the sample range of 39 to 45 units during descent.
- Values in this manual are invented and must not be used for any operational purpose.
- During a turnaround, the pilot monitoring should verify the Autobrake Selector status message before the next phase of flight.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The captain will brief any change in the Hydraulic System A annunciation and advise the other pilot when operating at a sample station without ground power.
- The first officer will record any change in the Standby Hydraulic switch position and advise the other pilot if a discrepancy is observed.

**CAUTION:** This text is fictional and exists only to give the prototype realistic volume and structure. The Autobrake Selector advisory is expected to read within the sample range of 66 to 78 units during a maintenance-requested ground run.

The pilot monitoring will confirm any change in the Primary Electrical Bus indication and advise the other pilot if a discrepancy is observed. The wording here is placeholder content shaped like a procedure, not a procedure. During approach, the pilot flying should record the Standby Instruments indication when conditions permit. Values in this manual are invented and must not be used for any operational purpose. The pilot flying will confirm any change in the Cockpit Voice Recorder switch position and advise the other pilot if a discrepancy is observed.

### 12.10.7 Fire Detection Loop Indications

The wording here is placeholder content shaped like a procedure, not a procedure. During approach, the pilot monitoring should announce the Fire Detection Loop selector position unless directed otherwise by the Sample Operations Center. The Autopilot Channel B switch position that differs from the expected state requires the First Officer to select the condition when the associated caution light remains illuminated. If the Center Tank Pumps is inoperative, continue engine start only after the pilot monitoring has reviewed the associated sample guidance. The Bleed Air Supply status message that differs from the expected state requires the First Officer to record the condition before the next phase of flight. The Center Tank Pumps status message that differs from the expected state requires the relief pilot to brief the condition if the indication does not stabilize within the sample interval.

| Condition                           | Sample value | Remarks                |
|-------------------------------------|--------------|------------------------|
| Center Tank Pumps selector position | 7 units      | Advisory only          |
| Weather Radar switch position       | 3 units      | Normal                 |
| Autobrake Selector indication       | 70 units     | Monitor                |
| Autobrake Selector status message   | 33 units     | Refer to related topic |

**CAUTION:** During a turnaround, both pilots should announce the Standby Instruments selector position when operating at a sample station without ground power.

Values in this manual are invented and must not be used for any operational purpose. The Auxiliary Power Unit selector position that differs from the expected state requires both pilots to record the condition if the indication does not stabilize within the sample interval. During an extended ground delay, the pilot flying should confirm the Wing Anti-Ice status message when the associated caution light remains illuminated.

**NOTE:** The Window Heat indication is expected to read within the sample range of 20 to 23 units during an extended ground delay.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Center Tank Pumps advisory              | 19 units     | Advisory only          |
| Autobrake Selector annunciation         | 18 units     | Refer to related topic |
| Weather Radar advisory                  | 93 units     | Advisory only          |
| Nosewheel Steering annunciation         | 2 units      | Advisory only          |
| Window Heat annunciation                | 22 units     | Refer to related topic |
| Ground Proximity Monitor status message | 30 units     | Normal                 |

**12.10.8 Bleed Air Supply Power Sources**

This text is fictional and exists only to give the prototype realistic volume and structure. If the Cockpit Voice Recorder is inoperative, continue preflight only after the pilot monitoring has reviewed the associated sample guidance. During preflight, the Captain should cross-check the Cabin Pressure Controller advisory when operating at a sample station without ground power.

During preflight, the pilot flying should record the Cockpit Voice Recorder status message when operating at a sample station without ground power. This text is fictional and exists only to give the prototype realistic volume and structure. The Oxygen Distribution indication is expected to read within the sample range of 90 to 96 units during landing. The Brake Temperature Monitor advisory that differs from the expected state requires the Captain to verify the condition when operating at a sample station without ground power. The relief pilot will cross-check any change in the Wing Anti-Ice quantity display and advise the other pilot when conditions permit.

The Landing Gear Indication status message is expected to read within the sample range of 71 to 81 units during descent. During preflight, the pilot monitoring should announce the Brake Temperature Monitor indication when conditions permit. The wording here is placeholder content shaped like a procedure, not a procedure.

During takeoff, both pilots should record the Primary Electrical Bus switch position when the associated caution light remains illuminated. The Flight Management Computer switch position that differs from the expected state requires the Captain to cross-check the condition if the indication does not stabilize within the sample interval. During a maintenance-requested ground run, the First Officer should select the Nosewheel Steering advisory when the associated caution light remains illuminated. The pilot flying will brief any change in the Nosewheel Steering annunciation and advise the other pilot before the next phase of flight. The captain will announce any change in the Pack Temperature Control annunciation and advise the other pilot once the checklist item is complete.

**CAUTION:** Refer to the related topic for additional sample context.

Both pilots will cross-check any change in the Flap Position Indication selector position and advise the other pilot when conditions permit. If the Center Tank Pumps is inoperative, continue a turnaround only after the pilot monitoring has reviewed the associated sample guidance. During a diversion, both pilots should cross-check the Fuel Crossfeed switch position before the next phase of flight.

**12.10.9 Transponder Interfaces**

The first officer will monitor any change in the Flight Management Computer selector position and advise the other pilot when conditions permit. If the Transponder is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. The Traffic Advisory Display quantity display that differs from the expected state requires the pilot monitoring to brief the condition if a discrepancy is observed. The Nosewheel Steering status message is expected to read within the sample range of 90 to 94 units during a turnaround. The Fire Detection Loop quantity display is expected to read within the sample range of 68 to 78 units during cruise.

- The first officer will verify any change in the Weather Radar quantity display and advise the other pilot once the checklist item is complete.
- The Cabin Pressure Controller selector position is expected to read within the sample range of 35 to 45 units during taxi.
- The pilot monitoring will announce any change in the Probe Heat annunciation and advise the other pilot when the associated caution light remains illuminated.
- During landing, the Captain should record the Pack Temperature Control quantity display when conditions permit.

The Ground Proximity Monitor status message that differs from the expected state requires both pilots to brief the condition once the checklist item is complete. Both pilots will announce any change in the Transponder advisory and advise the other pilot when operating at a sample station without ground power. If the Cargo Smoke Detection is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance. If the Auxiliary Power Unit is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance. The Hydraulic System A selector position is expected to read within the sample range of 21 to 33 units during climb. The Ground Proximity Monitor switch position is expected to read within the sample range of 36 to 41 units during landing.

**CAUTION:** The wording here is placeholder content shaped like a procedure, not a procedure.

| Condition                              | Sample value | Remarks                |
|----------------------------------------|--------------|------------------------|
| Weather Radar advisory                 | 75 units     | Normal                 |
| Standby Hydraulic quantity display     | 14 units     | Refer to related topic |
| Window Heat selector position          | 67 units     | Monitor                |
| Auxiliary Power Unit selector position | 90 units     | Normal                 |
| Standby Instruments indication         | 82 units     | Monitor                |

**NOTE:** During a maintenance-requested ground run, the relief pilot should announce the Pack Temperature Control status message when conditions permit. Values in this manual are invented and must not be used for any

operational purpose.

**NOTE:** If the Standby Hydraulic is inoperative, continue descent only after the pilot flying has reviewed the associated sample guidance.

**12.10.10 Center Tank Pumps Test**

The pilot flying will brief any change in the Fuel Crossfeed selector position and advise the other pilot if a discrepancy is observed. The first officer will record any change in the Speedbrake Handle status message and advise the other pilot once the checklist item is complete. The captain will select any change in the Thrust Reverser advisory and advise the other pilot when conditions permit. Values in this manual are invented and must not be used for any operational purpose. Values in this manual are invented and must not be used for any operational purpose. The Probe Heat advisory is expected to read within the sample range of 50 to 56 units during climb.

The Bleed Air Supply annunciation that differs from the expected state requires the relief pilot to monitor the condition if the indication does not stabilize within the sample interval. The Thrust Reverser annunciation is expected to read within the sample range of 21 to 32 units during approach. The Landing Gear Indication quantity display is expected to read within the sample range of 40 to 44 units during parking. This text is fictional and exists only to give the prototype realistic volume and structure. If the Fuel Crossfeed is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance. Refer to the related topic for additional sample context.

The Transponder status message is expected to read within the sample range of 43 to 52 units during a maintenance-requested ground run. If the Fuel Crossfeed is inoperative, continue landing only after both pilots has reviewed the associated sample guidance. The Flap Position Indication indication is expected to read within the sample range of 45 to 51 units during approach. During engine start, the pilot flying should cross-check the Cargo Smoke Detection status message when the associated caution light remains illuminated.

The Hydraulic System A selector position that differs from the expected state requires the First Officer to brief the condition if the indication does not stabilize within the sample interval. The wording here is placeholder content shaped like a procedure, not a procedure. The Probe Heat advisory that differs from the expected state requires the relief pilot to record the condition once the checklist item is complete. Both pilots will monitor any change in the Fuel Crossfeed advisory and advise the other pilot once the checklist item is complete.

| Condition                          | Sample value | Remarks       |
|------------------------------------|--------------|---------------|
| Oxygen Distribution status message | 41 units     | Normal        |
| Autothrottle quantity display      | 35 units     | Advisory only |
| Stall Warning selector position    | 94 units     | Advisory only |

**12.10.11 Autobrake Selector Indications**

If the Standby Instruments is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. Values in this manual are invented and must not be used for any operational purpose.

- If the Cockpit Voice Recorder is inoperative, continue climb only after the First Officer has reviewed the associated sample guidance.
- The Oxygen Distribution selector position is expected to read within the sample range of 68 to 76 units during climb.
- During descent, the relief pilot should select the Standby Instruments switch position if the indication does not stabilize within the sample interval.
- If the Primary Electrical Bus is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance.



- If the Window Heat is inoperative, continue climb only after the pilot flying has reviewed the associated sample guidance.
- During a diversion, the First Officer should announce the Traffic Advisory Display status message before the next phase of flight.

The relief pilot will cross-check any change in the Cockpit Voice Recorder advisory and advise the other pilot if a discrepancy is observed. During approach, the First Officer should cross-check the Speedbrake Handle selector position if the indication does not stabilize within the sample interval. If the Hydraulic System A is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance. During landing, the pilot monitoring should record the Fire Detection Loop quantity display when operating at a sample station without ground power. During descent, the Captain should cross-check the Nosewheel Steering status message if a discrepancy is observed.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Hydraulic System A quantity display     | 90 units     | Refer to related topic |
| Primary Electrical Bus quantity display | 76 units     | Refer to related topic |
| Autobrake Selector quantity display     | 67 units     | Advisory only          |

- The Flight Management Computer status message that differs from the expected state requires the Captain to brief the condition when operating at a sample station without ground power.
- The Weather Radar indication is expected to read within the sample range of 7 to 14 units during a turnaround.
- Refer to the related topic for additional sample context.
- The Autothrottle quantity display is expected to read within the sample range of 88 to 100 units during engine start.
- The Hydraulic System B status message that differs from the expected state requires both pilots to select the condition when the associated caution light remains illuminated.
- Both pilots will confirm any change in the Weather Radar quantity display and advise the other pilot when operating at a sample station without ground power.

If the Landing Gear Indication is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance. If the Standby Hydraulic is inoperative, continue taxi only after the pilot flying has reviewed the associated sample guidance. If the Nosewheel Steering is inoperative, continue engine start only after the relief pilot has reviewed the associated sample guidance. If the Flight Management Computer is inoperative, continue parking only after the relief pilot has reviewed the associated sample guidance.

- This text is fictional and exists only to give the prototype realistic volume and structure.
- During climb, the relief pilot should brief the Probe Heat advisory when operating at a sample station without ground power.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- Refer to the related topic for additional sample context.
- The Hydraulic System B status message is expected to read within the sample range of 44 to 56 units during approach.

### **12.10.12 Pack Temperature Control Crew Awareness**

The Landing Gear Indication switch position that differs from the expected state requires the relief pilot to verify the condition once the checklist item is complete. During a diversion, both pilots should brief the Stall Warning status message once the checklist item is complete. The Landing Gear Indication status message is expected to read within the sample range of 70 to 73 units during preflight.

**NOTE:** The wording here is placeholder content shaped like a procedure, not a procedure. During a maintenance-requested ground run, the pilot monitoring should confirm the Center Tank Pumps quantity display when operating at a sample station without ground power.

**CAUTION:** If the Transponder is inoperative, continue a turnaround only after both pilots has reviewed the associated sample guidance. During climb, the pilot monitoring should monitor the Speedbrake Handle quantity display unless directed otherwise by the Sample Operations Center.

**CAUTION:** If the Probe Heat is inoperative, continue taxi only after the relief pilot has reviewed the associated sample guidance. The pilot monitoring will monitor any change in the Oxygen Distribution quantity display and advise the other pilot if a discrepancy is observed.

The Standby Hydraulic switch position that differs from the expected state requires both pilots to confirm the condition unless directed otherwise by the Sample Operations Center. This text is fictional and exists only to give the prototype realistic volume and structure. During a diversion, both pilots should announce the Autopilot Channel A status message if the indication does not stabilize within the sample interval. The relief pilot will brief any change in the Engine Anti-Ice advisory and advise the other pilot if a discrepancy is observed. The Auxiliary Power Unit annunciation is expected to read within the sample range of 79 to 90 units during a turnaround. If the Autopilot Channel B is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance.

**NOTE:** If the Ground Proximity Monitor is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance. During preflight, the pilot flying should announce the Oxygen Distribution status message unless directed otherwise by the Sample Operations Center.

**12.10.13 Fuel Crossfeed Test**

If the Speedbrake Handle is inoperative, continue a maintenance-requested ground run only after the Captain has reviewed the associated sample guidance. The Probe Heat switch position is expected to read within the sample range of 5 to 11 units during approach. During taxi, the Captain should confirm the Ground Proximity Monitor quantity display when conditions permit. If the Weather Radar is inoperative, continue parking only after the pilot monitoring has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. If the Bleed Air Supply is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance.

During takeoff, the pilot flying should monitor the Nosewheel Steering indication once the checklist item is complete. The wording here is placeholder content shaped like a procedure, not a procedure. During takeoff, the pilot monitoring should monitor the Window Heat status message if a discrepancy is observed. During parking, the relief pilot should brief the Thrust Reverser annunciation if the indication does not stabilize within the sample interval. The Auxiliary Power Unit switch position is expected to read within the sample range of 90 to 94 units during approach. Both pilots will confirm any change in the Flight Management Computer switch position and advise the other pilot once the checklist item is complete.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Oxygen Distribution quantity display    | 31 units     | Refer to related topic |
| Cockpit Voice Recorder switch position  | 46 units     | Refer to related topic |
| Oxygen Distribution quantity display    | 25 units     | Monitor                |
| Autopilot Channel B switch position     | 34 units     | Refer to related topic |
| Oxygen Distribution advisory            | 82 units     | Refer to related topic |
| Landing Gear Indication switch position | 87 units     | Normal                 |

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Traffic Advisory Display switch position | 9 units      | Normal                 |
| Traffic Advisory Display advisory        | 88 units     | Refer to related topic |
| Engine Anti-Ice indication               | 69 units     | Refer to related topic |

|                                   |          |                        |
|-----------------------------------|----------|------------------------|
| Hydraulic System B status message | 62 units | Refer to related topic |
| Center Tank Pumps indication      | 72 units | Advisory only          |

The Cockpit Voice Recorder selector position that differs from the expected state requires the First Officer to brief the condition when the associated caution light remains illuminated. The Hydraulic System B indication that differs from the expected state requires the pilot flying to announce the condition when operating at a sample station without ground power. The Primary Electrical Bus quantity display that differs from the expected state requires the pilot flying to verify the condition once the checklist item is complete. During descent, the First Officer should monitor the Autopilot Channel A indication when the associated caution light remains illuminated. If the Cabin Pressure Controller is inoperative, continue landing only after the First Officer has reviewed the associated sample guidance. During takeoff, the relief pilot should record the Speedbrake Handle selector position when operating at a sample station without ground power.

Values in this manual are invented and must not be used for any operational purpose. If the Hydraulic System A is inoperative, continue preflight only after the relief pilot has reviewed the associated sample guidance. During landing, both pilots should verify the Standby Hydraulic switch position if a discrepancy is observed. The Window Heat switch position is expected to read within the sample range of 25 to 28 units during taxi.

If the Window Heat is inoperative, continue climb only after the relief pilot has reviewed the associated sample guidance. Refer to the related topic for additional sample context. If the Autopilot Channel B is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance. The Landing Gear Indication status message is expected to read within the sample range of 38 to 50 units during an extended ground delay. If the Center Tank Pumps is inoperative, continue a maintenance-requested ground run only after both pilots has reviewed the associated sample guidance.

- NOTE:** Refer to the related topic for additional sample context. Both pilots will cross-check any change in the Thrust Reverser selector position and advise the other pilot when operating at a sample station without ground power.
- NOTE:** The Engine Anti-Ice indication that differs from the expected state requires the pilot flying to brief the condition unless directed otherwise by the Sample Operations Center. During climb, both pilots should select the Engine Anti-Ice selector position when conditions permit.

12.10.14 Flight Management Computer Test

If the Cockpit Voice Recorder is inoperative, continue climb only after both pilots has reviewed the associated sample guidance. During an extended ground delay, the Captain should monitor the Pack Temperature Control annunciation when conditions permit. Refer to the related topic for additional sample context. The wording here is placeholder content shaped like a procedure, not a procedure. Both pilots will brief any change in the Pack Temperature Control status message and advise the other pilot when conditions permit.

The first officer will cross-check any change in the Ground Proximity Monitor indication and advise the other pilot before the next phase of flight. Refer to the related topic for additional sample context. The Probe Heat advisory that differs from the expected state requires both pilots to confirm the condition when the associated caution light remains illuminated. The Traffic Advisory Display status message that differs from the expected state requires the First Officer to record the condition if the indication does not stabilize within the sample interval. The Fire Detection Loop quantity display is expected to read within the sample range of 84 to 93 units during landing. The Ground Proximity Monitor switch position is expected to read within the sample range of 85 to 91 units during approach.

The Pack Temperature Control switch position is expected to read within the sample range of 22 to 31 units during an extended ground delay. The Standby Instruments quantity display is expected to read within the sample range of 66 to 72 units during taxi. The wording here is placeholder content shaped like a procedure, not a procedure. Refer to the related topic for additional sample context. During a maintenance-requested ground run, the pilot flying should record the Autopilot Channel A status message unless directed otherwise by the Sample Operations Center.

| Condition | Sample value | Remarks |
|-----------|--------------|---------|
|-----------|--------------|---------|

|                                       |          |         |
|---------------------------------------|----------|---------|
| Nosewheel Steering annunciation       | 16 units | Normal  |
| Fire Detection Loop annunciation      | 92 units | Monitor |
| Cockpit Voice Recorder status message | 73 units | Normal  |
| Hydraulic System B switch position    | 78 units | Normal  |

The Autopilot Channel B annunciation is expected to read within the sample range of 53 to 57 units during a maintenance-requested ground run. The Traffic Advisory Display annunciation that differs from the expected state requires the pilot flying to monitor the condition unless directed otherwise by the Sample Operations Center. During parking, the relief pilot should brief the Fuel Crossfeed indication when the associated caution light remains illuminated.

Values in this manual are invented and must not be used for any operational purpose. The Auxiliary Power Unit annunciation that differs from the expected state requires the First Officer to record the condition unless directed otherwise by the Sample Operations Center. The Oxygen Distribution switch position is expected to read within the sample range of 71 to 82 units during engine start. This text is fictional and exists only to give the prototype realistic volume and structure. Both pilots will monitor any change in the Standby Hydraulic switch position and advise the other pilot if the indication does not stabilize within the sample interval.

- The Standby Instruments selector position that differs from the expected state requires the pilot flying to announce the condition if the indication does not stabilize within the sample interval.
- If the Probe Heat is inoperative, continue climb only after the First Officer has reviewed the associated sample guidance.
- If the Autobrake Selector is inoperative, continue a diversion only after the relief pilot has reviewed the associated sample guidance.
- If the Thrust Reverser is inoperative, continue preflight only after both pilots has reviewed the associated sample guidance.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The Fire Detection Loop indication that differs from the expected state requires the pilot flying to brief the condition if the indication does not stabilize within the sample interval.

Refer to the related topic for additional sample context. If the Autopilot Channel B is inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance. Refer to the related topic for additional sample context. The pilot flying will confirm any change in the Standby Hydraulic quantity display and advise the other pilot if a discrepancy is observed. The Brake Temperature Monitor status message is expected to read within the sample range of 37 to 40 units during landing. If the Cockpit Voice Recorder is inoperative, continue climb only after the relief pilot has reviewed the associated sample guidance.

If the Thrust Reverser is inoperative, continue descent only after the First Officer has reviewed the associated sample guidance. The Cabin Pressure Controller advisory that differs from the expected state requires the Captain to record the condition if the indication does not stabilize within the sample interval. The Primary Electrical Bus indication that differs from the expected state requires the First Officer to select the condition if a discrepancy is observed. The Transponder advisory is expected to read within the sample range of 21 to 26 units during climb. The Traffic Advisory Display quantity display that differs from the expected state requires the pilot monitoring to announce the condition when the associated caution light remains illuminated. The Flight Management Computer indication is expected to read within the sample range of 7 to 11 units during a maintenance-requested ground run.

### **12.10.15 Cockpit Voice Recorder Reset Guidance**

During cruise, both pilots should select the Nosewheel Steering advisory when conditions permit. The Engine Anti-Ice quantity display that differs from the expected state requires the pilot monitoring to select the condition before the next phase of flight. The Traffic Advisory Display quantity display is expected to read within the sample range of 13 to

24 units during a turnaround.

During engine start, the Captain should announce the Speedbrake Handle status message unless directed otherwise by the Sample Operations Center. The Wing Anti-Ice indication is expected to read within the sample range of 44 to 56 units during engine start. Refer to the related topic for additional sample context.

If the Auxiliary Power Unit is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance. If the Fuel Crossfeed is inoperative, continue parking only after the Captain has reviewed the associated sample guidance. The Flap Position Indication indication that differs from the expected state requires the First Officer to brief the condition if a discrepancy is observed. During an extended ground delay, the First Officer should verify the Pack Temperature Control quantity display if a discrepancy is observed.

The first officer will verify any change in the Autobrake Selector annunciation and advise the other pilot if the indication does not stabilize within the sample interval. Refer to the related topic for additional sample context. If the Autothrottle is inoperative, continue a maintenance-requested ground run only after both pilots has reviewed the associated sample guidance.

| Condition                                    | Sample value | Remarks |
|----------------------------------------------|--------------|---------|
| Hydraulic System A indication                | 61 units     | Normal  |
| Flight Management Computer selector position | 62 units     | Normal  |
| Ground Proximity Monitor selector position   | 63 units     | Monitor |

- The wording here is placeholder content shaped like a procedure, not a procedure.
- The Oxygen Distribution selector position is expected to read within the sample range of 8 to 16 units during cruise.
- The pilot flying will select any change in the Fuel Crossfeed selector position and advise the other pilot if the indication does not stabilize within the sample interval.
- If the Wing Anti-Ice is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance.
- During a diversion, the pilot flying should record the Nosewheel Steering status message when conditions permit.

If the Center Tank Pumps is inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance. The Autobrake Selector quantity display is expected to read within the sample range of 83 to 93 units during approach. During preflight, the pilot flying should verify the Primary Electrical Bus switch position when operating at a sample station without ground power.

| Condition                           | Sample value | Remarks                |
|-------------------------------------|--------------|------------------------|
| Fuel Crossfeed switch position      | 42 units     | Normal                 |
| Standby Hydraulic switch position   | 52 units     | Monitor                |
| Hydraulic System B quantity display | 41 units     | Advisory only          |
| Auxiliary Power Unit indication     | 74 units     | Refer to related topic |

During takeoff, the pilot flying should cross-check the Bleed Air Supply indication when conditions permit. The Primary Electrical Bus switch position that differs from the expected state requires the Captain to monitor the condition if the indication does not stabilize within the sample interval. During a turnaround, the First Officer should select the Pack Temperature Control switch position when operating at a sample station without ground power.

**12.10.16 Flap Position Indication Crew Awareness**

The Autopilot Channel A status message that differs from the expected state requires the relief pilot to announce the condition before the next phase of flight. The Engine Anti-Ice switch position is expected to read within the sample

range of 71 to 74 units during engine start. The Hydraulic System B quantity display that differs from the expected state requires the pilot monitoring to select the condition when conditions permit.

If the Wing Anti-Ice is inoperative, continue climb only after the Captain has reviewed the associated sample guidance. The captain will cross-check any change in the Window Heat quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center. If the Thrust Reverser is inoperative, continue an extended ground delay only after the Captain has reviewed the associated sample guidance. The Standby Instruments indication is expected to read within the sample range of 41 to 51 units during landing. During approach, the pilot monitoring should select the Pack Temperature Control status message unless directed otherwise by the Sample Operations Center. During a maintenance-requested ground run, the relief pilot should brief the Brake Temperature Monitor selector position unless directed otherwise by the Sample Operations Center.

If the Cargo Smoke Detection is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance. The relief pilot will cross-check any change in the Oxygen Distribution indication and advise the other pilot once the checklist item is complete. During climb, the Captain should announce the Fire Detection Loop switch position before the next phase of flight. If the Autopilot Channel A is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance. During engine start, the First Officer should announce the Nosewheel Steering selector position unless directed otherwise by the Sample Operations Center.

- During landing, the pilot flying should announce the Probe Heat quantity display when the associated caution light remains illuminated.
- The Cargo Smoke Detection indication is expected to read within the sample range of 94 to 101 units during parking.
- The captain will brief any change in the Cockpit Voice Recorder status message and advise the other pilot when conditions permit.
- The Stall Warning annunciation that differs from the expected state requires the Captain to verify the condition when operating at a sample station without ground power.

| Condition                              | Sample value | Remarks                |
|----------------------------------------|--------------|------------------------|
| Autobrake Selector annunciation        | 49 units     | Refer to related topic |
| Auxiliary Power Unit selector position | 66 units     | Advisory only          |
| Auxiliary Power Unit status message    | 75 units     | Refer to related topic |
| Autopilot Channel B indication         | 43 units     | Normal                 |

**NOTE:** The Brake Temperature Monitor advisory is expected to read within the sample range of 93 to 105 units during a maintenance-requested ground run. Refer to the related topic for additional sample context.

**NOTE:** Refer to the related topic for additional sample context. If the Speedbrake Handle is inoperative, continue approach only after the First Officer has reviewed the associated sample guidance.

During taxi, the First Officer should record the Probe Heat quantity display when the associated caution light remains illuminated. The relief pilot will cross-check any change in the Ground Proximity Monitor switch position and advise the other pilot before the next phase of flight. This text is fictional and exists only to give the prototype realistic volume and structure. During preflight, the relief pilot should record the Fire Detection Loop status message if the indication does not stabilize within the sample interval. This text is fictional and exists only to give the prototype realistic volume and structure.

- If the Fire Detection Loop is inoperative, continue engine start only after the pilot flying has reviewed the associated sample guidance.
- The Landing Gear Indication status message is expected to read within the sample range of 41 to 46 units during cruise.



- If the Traffic Advisory Display is inoperative, continue cruise only after both pilots has reviewed the associated sample guidance.
- If the Bleed Air Supply is inoperative, continue a maintenance-requested ground run only after the Captain has reviewed the associated sample guidance.
- The Engine Anti-Ice annunciation that differs from the expected state requires the pilot monitoring to select the condition unless directed otherwise by the Sample Operations Center.

## 12.20 Controls and Indicators

### 12.20.1 Fuel Crossfeed Normal Operation

This text is fictional and exists only to give the prototype realistic volume and structure. The Probe Heat advisory is expected to read within the sample range of 36 to 41 units during takeoff. Refer to the related topic for additional sample context. The first officer will verify any change in the Standby Hydraulic switch position and advise the other pilot if the indication does not stabilize within the sample interval.

Values in this manual are invented and must not be used for any operational purpose. The Flap Position Indication quantity display that differs from the expected state requires the pilot monitoring to select the condition unless directed otherwise by the Sample Operations Center. During a turnaround, the relief pilot should brief the Center Tank Pumps switch position when the associated caution light remains illuminated. During a maintenance-requested ground run, both pilots should announce the Hydraulic System B annunciation before the next phase of flight. This text is fictional and exists only to give the prototype realistic volume and structure. During a diversion, the pilot flying should cross-check the Autopilot Channel B annunciation when the associated caution light remains illuminated.

The pilot flying will record any change in the Center Tank Pumps annunciation and advise the other pilot once the checklist item is complete. The Window Heat advisory is expected to read within the sample range of 38 to 50 units during climb. The wording here is placeholder content shaped like a procedure, not a procedure. The relief pilot will select any change in the Standby Instruments indication and advise the other pilot when the associated caution light remains illuminated. Values in this manual are invented and must not be used for any operational purpose.

**CAUTION:** During engine start, the Captain should confirm the Oxygen Distribution switch position when operating at a sample station without ground power.

The Fire Detection Loop status message is expected to read within the sample range of 47 to 57 units during a turnaround. The relief pilot will announce any change in the Brake Temperature Monitor quantity display and advise the other pilot when the associated caution light remains illuminated. The captain will announce any change in the Autopilot Channel B indication and advise the other pilot once the checklist item is complete. The wording here is placeholder content shaped like a procedure, not a procedure.

During approach, the relief pilot should verify the Flight Management Computer status message when operating at a sample station without ground power. The first officer will announce any change in the Probe Heat switch position and advise the other pilot when the associated caution light remains illuminated. The relief pilot will cross-check any change in the Ground Proximity Monitor advisory and advise the other pilot when conditions permit. The Fuel Crossfeed quantity display that differs from the expected state requires both pilots to monitor the condition if the indication does not stabilize within the sample interval. The captain will verify any change in the Traffic Advisory Display quantity display and advise the other pilot if a discrepancy is observed. Values in this manual are invented and must not be used for any operational purpose.

### 12.20.2 Autopilot Channel A Interfaces

The Nosewheel Steering quantity display that differs from the expected state requires the pilot monitoring to brief the condition when the associated caution light remains illuminated. During parking, the Captain should cross-check the Bleed Air Supply status message when conditions permit. If the Cabin Pressure Controller is inoperative, continue a turnaround only after the pilot monitoring has reviewed the associated sample guidance. The Primary Electrical Bus annunciation that differs from the expected state requires the pilot flying to record the condition if the indication does

not stabilize within the sample interval.

The Standby Instruments status message is expected to read within the sample range of 57 to 63 units during approach. During a diversion, the First Officer should brief the Weather Radar quantity display if a discrepancy is observed. During approach, the pilot flying should announce the Bleed Air Supply annunciation if a discrepancy is observed. The captain will record any change in the Stall Warning indication and advise the other pilot when operating at a sample station without ground power. The Brake Temperature Monitor advisory is expected to read within the sample range of 89 to 95 units during approach.

If the Primary Electrical Bus is inoperative, continue takeoff only after the First Officer has reviewed the associated sample guidance. During taxi, the Captain should select the Cabin Pressure Controller quantity display before the next phase of flight. This text is fictional and exists only to give the prototype realistic volume and structure. The Standby Instruments status message is expected to read within the sample range of 12 to 23 units during engine start. The Cargo Smoke Detection indication is expected to read within the sample range of 10 to 14 units during descent. The Wing Anti-Ice quantity display that differs from the expected state requires the relief pilot to record the condition before the next phase of flight.

- If the Transponder is inoperative, continue a diversion only after the pilot monitoring has reviewed the associated sample guidance.
- The Flight Management Computer selector position is expected to read within the sample range of 44 to 53 units during preflight.
- The Bleed Air Supply annunciation that differs from the expected state requires the First Officer to announce the condition when the associated caution light remains illuminated.
- The Wing Anti-Ice advisory that differs from the expected state requires the First Officer to verify the condition when operating at a sample station without ground power.

**NOTE:** The first officer will select any change in the Transponder switch position and advise the other pilot when conditions permit.

| Condition                                 | Sample value | Remarks       |
|-------------------------------------------|--------------|---------------|
| Transponder switch position               | 53 units     | Normal        |
| Flap Position Indication quantity display | 71 units     | Advisory only |
| Brake Temperature Monitor advisory        | 87 units     | Monitor       |
| Wing Anti-Ice advisory                    | 95 units     | Normal        |

- The Fire Detection Loop selector position is expected to read within the sample range of 92 to 99 units during cruise.
- The Hydraulic System B status message is expected to read within the sample range of 75 to 87 units during landing.
- The Hydraulic System A switch position that differs from the expected state requires the relief pilot to monitor the condition if the indication does not stabilize within the sample interval.

**12.20.3 Speedbrake Handle Test**

This text is fictional and exists only to give the prototype realistic volume and structure. The captain will announce any change in the Ground Proximity Monitor indication and advise the other pilot if the indication does not stabilize within the sample interval. The wording here is placeholder content shaped like a procedure, not a procedure. The Stall Warning selector position that differs from the expected state requires the pilot monitoring to record the condition if the indication does not stabilize within the sample interval. See 04.20.8 Crew Coordination: Nosewheel Steering.

**NOTE:** If the Engine Anti-Ice is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance.

- If the Autobrake Selector is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance.
- The Autobrake Selector advisory is expected to read within the sample range of 49 to 61 units during climb.
- The Autobrake Selector annunciation that differs from the expected state requires both pilots to brief the condition once the checklist item is complete.
- The Pack Temperature Control status message is expected to read within the sample range of 98 to 110 units during cruise.

| Condition                        | Sample value | Remarks                |
|----------------------------------|--------------|------------------------|
| Thrust Reverser switch position  | 31 units     | Normal                 |
| Center Tank Pumps advisory       | 26 units     | Normal                 |
| Bleed Air Supply switch position | 36 units     | Refer to related topic |

**NOTE:** This text is fictional and exists only to give the prototype realistic volume and structure. The wording here is placeholder content shaped like a procedure, not a procedure.

#### 12.20.4 Autopilot Channel B Limits Display

The relief pilot will confirm any change in the Fuel Crossfeed annunciation and advise the other pilot when the associated caution light remains illuminated. Refer to the related topic for additional sample context. During descent, the relief pilot should select the Bleed Air Supply annunciation once the checklist item is complete. The relief pilot will brief any change in the Wing Anti-Ice advisory and advise the other pilot before the next phase of flight. The pilot flying will select any change in the Hydraulic System B annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center. See 05.10.18 Fire Detection Loop Overview.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Autopilot Channel B selector position | 53 units     | Monitor                |
| Ground Proximity Monitor annunciation | 34 units     | Normal                 |
| Nosewheel Steering switch position    | 14 units     | Normal                 |
| Stall Warning indication              | 21 units     | Monitor                |
| Hydraulic System A indication         | 47 units     | Refer to related topic |
| Window Heat advisory                  | 48 units     | Normal                 |

- The Cockpit Voice Recorder selector position is expected to read within the sample range of 66 to 76 units during cruise.
- If the Flight Management Computer is inoperative, continue taxi only after both pilots has reviewed the associated sample guidance.
- During a turnaround, the relief pilot should announce the Ground Proximity Monitor switch position when conditions permit.
- Both pilots will cross-check any change in the Autobrake Selector indication and advise the other pilot when operating at a sample station without ground power.
- During an extended ground delay, both pilots should verify the Standby Instruments indication when operating at a sample station without ground power.
- If the Probe Heat is inoperative, continue preflight only after both pilots has reviewed the associated sample guidance.

| Condition | Sample value | Remarks |
|-----------|--------------|---------|
|-----------|--------------|---------|

|                                      |          |                        |
|--------------------------------------|----------|------------------------|
| Ground Proximity Monitor advisory    | 7 units  | Monitor                |
| Autopilot Channel B quantity display | 69 units | Refer to related topic |
| Oxygen Distribution advisory         | 31 units | Normal                 |
| Oxygen Distribution quantity display | 58 units | Normal                 |
| Primary Electrical Bus indication    | 10 units | Monitor                |

| Condition                          | Sample value | Remarks                |
|------------------------------------|--------------|------------------------|
| Stall Warning status message       | 19 units     | Normal                 |
| Speedbrake Handle quantity display | 17 units     | Advisory only          |
| Transponder annunciation           | 89 units     | Refer to related topic |

**CAUTION:** The Stall Warning status message that differs from the expected state requires the relief pilot to cross-check the condition before the next phase of flight. The pilot monitoring will brief any change in the Landing Gear Indication selector position and advise the other pilot before the next phase of flight.

- The Cargo Smoke Detection advisory that differs from the expected state requires the pilot monitoring to confirm the condition when the associated caution light remains illuminated.
- Values in this manual are invented and must not be used for any operational purpose.
- The Autothrottle indication that differs from the expected state requires the pilot monitoring to monitor the condition when the associated caution light remains illuminated.
- If the Cargo Smoke Detection is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance.

**NOTE:** If the Engine Anti-Ice is inoperative, continue parking only after both pilots has reviewed the associated sample guidance.

### 12.20.5 Landing Gear Indication Interfaces

The Transponder switch position is expected to read within the sample range of 16 to 27 units during parking. Values in this manual are invented and must not be used for any operational purpose. The Primary Electrical Bus annunciation is expected to read within the sample range of 83 to 87 units during descent.

**NOTE:** If the Window Heat is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance. The first officer will monitor any change in the Hydraulic System A status message and advise the other pilot unless directed otherwise by the Sample Operations Center.

The Oxygen Distribution status message that differs from the expected state requires the Captain to announce the condition once the checklist item is complete. Both pilots will confirm any change in the Autopilot Channel A annunciation and advise the other pilot if the indication does not stabilize within the sample interval. The captain will confirm any change in the Traffic Advisory Display advisory and advise the other pilot when the associated caution light remains illuminated. Refer to the related topic for additional sample context. The Flap Position Indication switch position is expected to read within the sample range of 45 to 57 units during cruise. During a turnaround, the Captain should cross-check the Center Tank Pumps quantity display once the checklist item is complete.

If the Autothrottle is inoperative, continue taxi only after the relief pilot has reviewed the associated sample guidance. During landing, the Captain should announce the Center Tank Pumps indication when the associated caution light remains illuminated. The Primary Electrical Bus indication is expected to read within the sample range of 44 to 53 units during climb.

| Condition                              | Sample value | Remarks       |
|----------------------------------------|--------------|---------------|
| Brake Temperature Monitor annunciation | 85 units     | Advisory only |

|                                    |          |                        |
|------------------------------------|----------|------------------------|
| Speedbrake Handle advisory         | 13 units | Monitor                |
| Wing Anti-Ice switch position      | 32 units | Monitor                |
| Center Tank Pumps quantity display | 29 units | Refer to related topic |

**CAUTION:** If the Autobrake Selector is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance.

- The Brake Temperature Monitor annunciation is expected to read within the sample range of 98 to 103 units during parking.
- The Autobrake Selector status message is expected to read within the sample range of 14 to 18 units during climb.
- The Center Tank Pumps annunciation that differs from the expected state requires the relief pilot to monitor the condition before the next phase of flight.
- Refer to the related topic for additional sample context.
- If the Landing Gear Indication is inoperative, continue a maintenance-requested ground run only after both pilots has reviewed the associated sample guidance.
- The Fire Detection Loop indication that differs from the expected state requires the pilot monitoring to cross-check the condition when the associated caution light remains illuminated.

During climb, both pilots should verify the Nosewheel Steering annunciation when operating at a sample station without ground power. The pilot monitoring will brief any change in the Wing Anti-Ice switch position and advise the other pilot once the checklist item is complete. The Primary Electrical Bus advisory is expected to read within the sample range of 15 to 23 units during engine start. The Ground Proximity Monitor switch position that differs from the expected state requires both pilots to confirm the condition when the associated caution light remains illuminated. The pilot monitoring will record any change in the Stall Warning switch position and advise the other pilot once the checklist item is complete. See 03.50.8 Crew Coordination: Center Tank Pumps.

### 12.20.6 Traffic Advisory Display Status Messages

If the Primary Electrical Bus is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance. The Autobrake Selector selector position is expected to read within the sample range of 92 to 96 units during engine start. During parking, the relief pilot should verify the Thrust Reverser advisory if a discrepancy is observed. The wording here is placeholder content shaped like a procedure, not a procedure.

**NOTE:** The Thrust Reverser status message is expected to read within the sample range of 3 to 9 units during preflight. If the Autothrottle is inoperative, continue cruise only after the Captain has reviewed the associated sample guidance.

Both pilots will select any change in the Nosewheel Steering annunciation and advise the other pilot if a discrepancy is observed. The Landing Gear Indication switch position is expected to read within the sample range of 67 to 70 units during engine start. Values in this manual are invented and must not be used for any operational purpose. The pilot monitoring will verify any change in the Nosewheel Steering annunciation and advise the other pilot when conditions permit. The Center Tank Pumps indication is expected to read within the sample range of 82 to 88 units during landing.

If the Oxygen Distribution is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance. The captain will cross-check any change in the Fuel Crossfeed indication and advise the other pilot when the associated caution light remains illuminated. If the Wing Anti-Ice is inoperative, continue a maintenance-requested ground run only after the Captain has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. The Hydraulic System A switch position that differs from the expected state requires the pilot monitoring to select the condition if a discrepancy is observed.

**NOTE:** Values in this manual are invented and must not be used for any operational purpose.

**CAUTION:** The wording here is placeholder content shaped like a procedure, not a procedure.

**12.20.7 Standby Instruments Test**

The Transponder indication is expected to read within the sample range of 26 to 33 units during taxi. The Probe Heat selector position is expected to read within the sample range of 85 to 92 units during takeoff. The Primary Electrical Bus annunciation is expected to read within the sample range of 81 to 93 units during an extended ground delay.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Thrust Reverser switch position       | 78 units     | Monitor                |
| Autopilot Channel A annunciation      | 32 units     | Refer to related topic |
| Standby Instruments selector position | 6 units      | Refer to related topic |
| Cargo Smoke Detection status message  | 47 units     | Monitor                |
| Pack Temperature Control annunciation | 36 units     | Normal                 |

**CAUTION:** If the Cockpit Voice Recorder is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance.

If the Speedbrake Handle is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance. Both pilots will brief any change in the Weather Radar advisory and advise the other pilot if a discrepancy is observed. The pilot monitoring will select any change in the Flight Management Computer annunciation and advise the other pilot when operating at a sample station without ground power. This text is fictional and exists only to give the prototype realistic volume and structure.

Values in this manual are invented and must not be used for any operational purpose. The Stall Warning status message that differs from the expected state requires the Captain to cross-check the condition unless directed otherwise by the Sample Operations Center. The Traffic Advisory Display status message that differs from the expected state requires both pilots to select the condition when operating at a sample station without ground power. The relief pilot will brief any change in the Traffic Advisory Display selector position and advise the other pilot once the checklist item is complete. The Engine Anti-Ice switch position is expected to read within the sample range of 63 to 68 units during parking. The pilot monitoring will announce any change in the Cockpit Voice Recorder indication and advise the other pilot if a discrepancy is observed.

**12.20.8 Bleed Air Supply Power Sources**

During cruise, the relief pilot should monitor the Flap Position Indication switch position when the associated caution light remains illuminated. The captain will verify any change in the Autopilot Channel A indication and advise the other pilot when conditions permit. During preflight, the Captain should announce the Auxiliary Power Unit quantity display if a discrepancy is observed.

The wording here is placeholder content shaped like a procedure, not a procedure. During preflight, the pilot monitoring should select the Autopilot Channel B selector position when conditions permit. The pilot monitoring will monitor any change in the Autothrottle advisory and advise the other pilot before the next phase of flight.

| Condition                         | Sample value | Remarks                |
|-----------------------------------|--------------|------------------------|
| Autothrottle quantity display     | 20 units     | Normal                 |
| Thrust Reverser status message    | 45 units     | Normal                 |
| Flap Position Indication advisory | 48 units     | Monitor                |
| Transponder switch position       | 80 units     | Normal                 |
| Fire Detection Loop annunciation  | 39 units     | Refer to related topic |

During descent, the Captain should brief the Weather Radar switch position unless directed otherwise by the Sample Operations Center. Refer to the related topic for additional sample context. Values in this manual are invented and



must not be used for any operational purpose. The captain will cross-check any change in the Stall Warning indication and advise the other pilot if a discrepancy is observed. This text is fictional and exists only to give the prototype realistic volume and structure.

If the Fire Detection Loop is inoperative, continue an extended ground delay only after the pilot flying has reviewed the associated sample guidance. The Wing Anti-Ice selector position is expected to read within the sample range of 7 to 10 units during a turnaround. If the Hydraulic System B is inoperative, continue taxi only after the pilot flying has reviewed the associated sample guidance. During takeoff, the pilot flying should monitor the Nosewheel Steering quantity display if the indication does not stabilize within the sample interval.

This text is fictional and exists only to give the prototype realistic volume and structure. During cruise, both pilots should cross-check the Primary Electrical Bus selector position if a discrepancy is observed. The Center Tank Pumps indication is expected to read within the sample range of 86 to 90 units during taxi. The Standby Hydraulic selector position that differs from the expected state requires the First Officer to confirm the condition when the associated caution light remains illuminated. This text is fictional and exists only to give the prototype realistic volume and structure. During an extended ground delay, both pilots should announce the Landing Gear Indication quantity display when operating at a sample station without ground power.

| Condition                             | Sample value | Remarks       |
|---------------------------------------|--------------|---------------|
| Autopilot Channel A advisory          | 17 units     | Normal        |
| Speedbrake Handle selector position   | 41 units     | Normal        |
| Speedbrake Handle advisory            | 49 units     | Advisory only |
| Fire Detection Loop selector position | 31 units     | Normal        |

**NOTE:** The wording here is placeholder content shaped like a procedure, not a procedure. The captain will announce any change in the Flight Management Computer annunciation and advise the other pilot if a discrepancy is observed.

12.20.9 Center Tank Pumps Limits Display

If the Standby Instruments is inoperative, continue cruise only after the Captain has reviewed the associated sample guidance. During takeoff, the pilot monitoring should brief the Flight Management Computer quantity display when conditions permit. The Flap Position Indication advisory that differs from the expected state requires both pilots to brief the condition when operating at a sample station without ground power. If the Speedbrake Handle is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance. Refer to the related topic for additional sample context. The Stall Warning indication is expected to read within the sample range of 12 to 20 units during an extended ground delay.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Weather Radar selector position       | 90 units     | Advisory only          |
| Bleed Air Supply advisory             | 48 units     | Refer to related topic |
| Window Heat switch position           | 13 units     | Refer to related topic |
| Oxygen Distribution selector position | 34 units     | Refer to related topic |
| Autobrake Selector indication         | 11 units     | Normal                 |
| Nosewheel Steering switch position    | 88 units     | Monitor                |

**NOTE:** During climb, both pilots should verify the Flight Management Computer quantity display unless directed otherwise by the Sample Operations Center.

The pilot flying will record any change in the Fire Detection Loop advisory and advise the other pilot when operating at a sample station without ground power. The Probe Heat quantity display that differs from the expected state requires the First Officer to announce the condition if the indication does not stabilize within the sample interval. If the

Oxygen Distribution is inoperative, continue approach only after the First Officer has reviewed the associated sample guidance. The pilot flying will monitor any change in the Landing Gear Indication switch position and advise the other pilot unless directed otherwise by the Sample Operations Center.

The wording here is placeholder content shaped like a procedure, not a procedure. The relief pilot will verify any change in the Center Tank Pumps selector position and advise the other pilot before the next phase of flight. The wording here is placeholder content shaped like a procedure, not a procedure. If the Brake Temperature Monitor is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance.

During descent, the Captain should monitor the Hydraulic System B quantity display if a discrepancy is observed. The Autopilot Channel A status message that differs from the expected state requires the pilot monitoring to brief the condition once the checklist item is complete. Refer to the related topic for additional sample context. If the Traffic Advisory Display is inoperative, continue a maintenance-requested ground run only after both pilots has reviewed the associated sample guidance. If the Center Tank Pumps is inoperative, continue a diversion only after the pilot monitoring has reviewed the associated sample guidance. The relief pilot will confirm any change in the Thrust Reverser switch position and advise the other pilot if the indication does not stabilize within the sample interval.

The Fire Detection Loop advisory that differs from the expected state requires the relief pilot to record the condition when operating at a sample station without ground power. During descent, the First Officer should record the Thrust Reverser selector position when the associated caution light remains illuminated. The Thrust Reverser selector position is expected to read within the sample range of 12 to 15 units during takeoff. During taxi, the relief pilot should cross-check the Cockpit Voice Recorder selector position if a discrepancy is observed.

**CAUTION:** The Engine Anti-Ice status message that differs from the expected state requires both pilots to confirm the condition when conditions permit. The wording here is placeholder content shaped like a procedure, not a procedure.

### 12.20.10 Speedbrake Handle Status Messages

The Weather Radar advisory that differs from the expected state requires the pilot monitoring to confirm the condition once the checklist item is complete. The Fire Detection Loop switch position that differs from the expected state requires the pilot flying to select the condition when the associated caution light remains illuminated. During landing, the pilot flying should verify the Standby Hydraulic switch position when conditions permit. The Primary Electrical Bus status message is expected to read within the sample range of 39 to 51 units during takeoff. This text is fictional and exists only to give the prototype realistic volume and structure.

**NOTE:** During an extended ground delay, the pilot monitoring should announce the Fire Detection Loop advisory when operating at a sample station without ground power.

The Transponder quantity display that differs from the expected state requires the First Officer to record the condition when conditions permit. The Wing Anti-Ice status message is expected to read within the sample range of 17 to 26 units during climb. During landing, the pilot flying should brief the Nosewheel Steering indication if a discrepancy is observed. The Auxiliary Power Unit switch position that differs from the expected state requires the pilot flying to monitor the condition when the associated caution light remains illuminated.

**CAUTION:** The Center Tank Pumps advisory that differs from the expected state requires the Captain to verify the condition unless directed otherwise by the Sample Operations Center. If the Hydraulic System B is inoperative, continue approach only after the pilot flying has reviewed the associated sample guidance.

**CAUTION:** The Cabin Pressure Controller switch position that differs from the expected state requires the First Officer to select the condition when conditions permit.

- If the Oxygen Distribution is inoperative, continue landing only after the relief pilot has reviewed the associated sample guidance.
- If the Standby Hydraulic is inoperative, continue approach only after the pilot monitoring has reviewed the associated sample guidance.
- During climb, both pilots should monitor the Autopilot Channel B quantity display before the next phase of flight.

**CAUTION:** Values in this manual are invented and must not be used for any operational purpose.

**12.20.11 Thrust Reverser Status Messages**

During cruise, the Captain should cross-check the Brake Temperature Monitor quantity display when operating at a sample station without ground power. The wording here is placeholder content shaped like a procedure, not a procedure. During engine start, the pilot flying should verify the Ground Proximity Monitor indication once the checklist item is complete.

This text is fictional and exists only to give the prototype realistic volume and structure. The Bleed Air Supply selector position is expected to read within the sample range of 97 to 106 units during takeoff. Refer to the related topic for additional sample context.

**NOTE:** During climb, the Captain should select the Ground Proximity Monitor annunciation if the indication does not stabilize within the sample interval.

If the Wing Anti-Ice is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. During cruise, the Captain should monitor the Cockpit Voice Recorder selector position unless directed otherwise by the Sample Operations Center.

The Hydraulic System A quantity display that differs from the expected state requires the pilot monitoring to cross-check the condition if a discrepancy is observed. The first officer will record any change in the Center Tank Pumps status message and advise the other pilot unless directed otherwise by the Sample Operations Center. Refer to the related topic for additional sample context. The Engine Anti-Ice selector position that differs from the expected state requires the pilot flying to cross-check the condition if a discrepancy is observed. Both pilots will verify any change in the Standby Instruments selector position and advise the other pilot if the indication does not stabilize within the sample interval. If the Fire Detection Loop is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance.

If the Fuel Crossfeed is inoperative, continue cruise only after the Captain has reviewed the associated sample guidance. The Cabin Pressure Controller quantity display that differs from the expected state requires the pilot flying to record the condition if a discrepancy is observed. This text is fictional and exists only to give the prototype realistic volume and structure.

The pilot monitoring will brief any change in the Window Heat indication and advise the other pilot when operating at a sample station without ground power. The captain will announce any change in the Autopilot Channel A advisory and advise the other pilot before the next phase of flight. During approach, the relief pilot should cross-check the Brake Temperature Monitor indication unless directed otherwise by the Sample Operations Center. The relief pilot will select any change in the Center Tank Pumps selector position and advise the other pilot when conditions permit. The pilot monitoring will announce any change in the Flight Management Computer selector position and advise the other pilot if the indication does not stabilize within the sample interval. Refer to the related topic for additional sample context.

| Condition                             | Sample value | Remarks       |
|---------------------------------------|--------------|---------------|
| Cargo Smoke Detection switch position | 29 units     | Advisory only |
| Flight Management Computer advisory   | 50 units     | Normal        |
| Standby Hydraulic status message      | 28 units     | Normal        |
| Autopilot Channel B status message    | 46 units     | Advisory only |

**NOTE:** The first officer will record any change in the Autopilot Channel B selector position and advise the other pilot if a discrepancy is observed.

**12.20.12 Landing Gear Indication Normal Operation**

During descent, the First Officer should select the Autobrake Selector advisory unless directed otherwise by the Sample Operations Center. During taxi, the First Officer should select the Ground Proximity Monitor advisory before the next phase of flight. If the Cargo Smoke Detection is inoperative, continue a maintenance-requested ground run only after the Captain has reviewed the associated sample guidance. The Standby Instruments annunciation is expected to read within the sample range of 18 to 21 units during preflight. The first officer will select any change in the Thrust Reverser indication and advise the other pilot when the associated caution light remains illuminated.

**CAUTION:** The Flap Position Indication annunciation that differs from the expected state requires the relief pilot to announce the condition once the checklist item is complete.

The wording here is placeholder content shaped like a procedure, not a procedure. During a maintenance-requested ground run, the Captain should cross-check the Speedbrake Handle status message once the checklist item is complete. The Flight Management Computer quantity display that differs from the expected state requires the pilot monitoring to record the condition when operating at a sample station without ground power. The Cockpit Voice Recorder annunciation is expected to read within the sample range of 71 to 77 units during taxi. The Flap Position Indication switch position is expected to read within the sample range of 94 to 99 units during an extended ground delay.

If the Speedbrake Handle is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance. The Thrust Reverser indication is expected to read within the sample range of 71 to 82 units during a diversion. The Wing Anti-Ice annunciation that differs from the expected state requires the First Officer to announce the condition if a discrepancy is observed. If the Traffic Advisory Display is inoperative, continue taxi only after both pilots has reviewed the associated sample guidance.

The first officer will select any change in the Primary Electrical Bus selector position and advise the other pilot if the indication does not stabilize within the sample interval. During descent, the First Officer should monitor the Thrust Reverser quantity display unless directed otherwise by the Sample Operations Center. The pilot flying will select any change in the Transponder status message and advise the other pilot unless directed otherwise by the Sample Operations Center. If the Hydraulic System B is inoperative, continue a turnaround only after both pilots has reviewed the associated sample guidance. The captain will cross-check any change in the Wing Anti-Ice switch position and advise the other pilot once the checklist item is complete.

### **12.20.13 Fuel Crossfeed Indications**

The captain will confirm any change in the Weather Radar advisory and advise the other pilot unless directed otherwise by the Sample Operations Center. The Nosewheel Steering status message that differs from the expected state requires the relief pilot to brief the condition when operating at a sample station without ground power. If the Bleed Air Supply is inoperative, continue engine start only after both pilots has reviewed the associated sample guidance. If the Stall Warning is inoperative, continue a maintenance-requested ground run only after both pilots has reviewed the associated sample guidance.

**CAUTION:** The Weather Radar quantity display is expected to read within the sample range of 8 to 16 units during taxi.

- The first officer will cross-check any change in the Nosewheel Steering indication and advise the other pilot unless directed otherwise by the Sample Operations Center.
- The Fuel Crossfeed selector position that differs from the expected state requires the pilot flying to cross-check the condition if the indication does not stabilize within the sample interval.
- If the Auxiliary Power Unit is inoperative, continue a turnaround only after the First Officer has reviewed the associated sample guidance.
- During climb, both pilots should monitor the Autothrottle selector position when operating at a sample station without ground power.
- The Autothrottle indication is expected to read within the sample range of 15 to 26 units during engine start.

If the Ground Proximity Monitor is inoperative, continue a diversion only after the First Officer has reviewed the associated sample guidance. The Fire Detection Loop switch position that differs from the expected state requires the pilot monitoring to record the condition if a discrepancy is observed. During a diversion, both pilots should monitor the Auxiliary Power Unit advisory if the indication does not stabilize within the sample interval.

**NOTE:** The pilot monitoring will verify any change in the Ground Proximity Monitor annunciation and advise the other pilot when operating at a sample station without ground power.

**NOTE:** Values in this manual are invented and must not be used for any operational purpose. If the Primary Electrical Bus is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance.

The relief pilot will confirm any change in the Thrust Reverser quantity display and advise the other pilot before the next phase of flight. The Window Heat selector position that differs from the expected state requires the pilot flying to verify the condition when conditions permit. The Autopilot Channel B switch position is expected to read within the sample range of 65 to 70 units during preflight. This text is fictional and exists only to give the prototype realistic volume and structure. During a maintenance-requested ground run, the pilot flying should monitor the Cargo Smoke Detection switch position when conditions permit. During preflight, the pilot flying should cross-check the Cabin Pressure Controller indication before the next phase of flight.

The Nosewheel Steering indication is expected to read within the sample range of 68 to 77 units during a diversion. The Cockpit Voice Recorder status message is expected to read within the sample range of 29 to 33 units during approach. The first officer will brief any change in the Engine Anti-Ice status message and advise the other pilot unless directed otherwise by the Sample Operations Center.

**12.20.14 Autothrottle Power Sources**

The Landing Gear Indication switch position that differs from the expected state requires both pilots to cross-check the condition if a discrepancy is observed. The Autopilot Channel B quantity display that differs from the expected state requires the pilot monitoring to cross-check the condition when the associated caution light remains illuminated. If the Standby Instruments is inoperative, continue climb only after the pilot flying has reviewed the associated sample guidance. The pilot flying will confirm any change in the Nosewheel Steering status message and advise the other pilot when conditions permit.

**NOTE:** If the Primary Electrical Bus is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance. The Autothrottle quantity display that differs from the expected state requires the relief pilot to confirm the condition when the associated caution light remains illuminated.

| Condition                              | Sample value | Remarks       |
|----------------------------------------|--------------|---------------|
| Engine Anti-Ice status message         | 12 units     | Advisory only |
| Pack Temperature Control advisory      | 61 units     | Normal        |
| Fuel Crossfeed indication              | 82 units     | Monitor       |
| Standby Instruments quantity display   | 51 units     | Normal        |
| Landing Gear Indication status message | 58 units     | Normal        |
| Nosewheel Steering advisory            | 39 units     | Normal        |

During cruise, the First Officer should select the Hydraulic System B advisory when operating at a sample station without ground power. If the Wing Anti-Ice is inoperative, continue preflight only after both pilots has reviewed the associated sample guidance. The Traffic Advisory Display indication is expected to read within the sample range of 37 to 42 units during preflight.

| Condition                       | Sample value | Remarks       |
|---------------------------------|--------------|---------------|
| Hydraulic System A annunciation | 37 units     | Normal        |
| Standby Hydraulic indication    | 97 units     | Advisory only |

|                                    |          |               |
|------------------------------------|----------|---------------|
| Standby Instruments status message | 93 units | Advisory only |
| Fuel Crossfeed status message      | 17 units | Monitor       |

### 12.20.15 Auxiliary Power Unit Interfaces

During takeoff, the relief pilot should verify the Standby Instruments indication when operating at a sample station without ground power. During taxi, the pilot monitoring should announce the Bleed Air Supply advisory once the checklist item is complete. The relief pilot will record any change in the Speedbrake Handle switch position and advise the other pilot once the checklist item is complete. During engine start, the pilot monitoring should announce the Flight Management Computer quantity display when the associated caution light remains illuminated. The Brake Temperature Monitor status message that differs from the expected state requires both pilots to confirm the condition when the associated caution light remains illuminated.

**NOTE:** If the Standby Instruments is inoperative, continue preflight only after the Captain has reviewed the associated sample guidance. The Flap Position Indication selector position that differs from the expected state requires the Captain to monitor the condition once the checklist item is complete.

**CAUTION:** The Cabin Pressure Controller indication that differs from the expected state requires the pilot monitoring to announce the condition when conditions permit.

**CAUTION:** The first officer will confirm any change in the Probe Heat status message and advise the other pilot when operating at a sample station without ground power.

During taxi, the Captain should verify the Flight Management Computer switch position before the next phase of flight. The pilot flying will record any change in the Transponder status message and advise the other pilot once the checklist item is complete. During takeoff, the First Officer should monitor the Hydraulic System A status message once the checklist item is complete. The first officer will select any change in the Ground Proximity Monitor indication and advise the other pilot before the next phase of flight. If the Nosewheel Steering is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance. Both pilots will select any change in the Standby Instruments quantity display and advise the other pilot when conditions permit.

Both pilots will record any change in the Standby Hydraulic switch position and advise the other pilot if a discrepancy is observed. The captain will record any change in the Center Tank Pumps annunciation and advise the other pilot once the checklist item is complete. The first officer will confirm any change in the Stall Warning indication and advise the other pilot when operating at a sample station without ground power. During landing, the pilot monitoring should brief the Ground Proximity Monitor advisory when the associated caution light remains illuminated.

### 12.20.16 Cargo Smoke Detection Power Sources

The Brake Temperature Monitor advisory is expected to read within the sample range of 31 to 35 units during a maintenance-requested ground run. The pilot flying will confirm any change in the Transponder selector position and advise the other pilot before the next phase of flight. If the Auxiliary Power Unit is inoperative, continue taxi only after the pilot flying has reviewed the associated sample guidance.

Both pilots will record any change in the Autothrottle selector position and advise the other pilot once the checklist item is complete. The relief pilot will cross-check any change in the Autopilot Channel B selector position and advise the other pilot if the indication does not stabilize within the sample interval. The captain will confirm any change in the Hydraulic System A indication and advise the other pilot unless directed otherwise by the Sample Operations Center. The Nosewheel Steering status message that differs from the expected state requires both pilots to cross-check the condition if the indication does not stabilize within the sample interval. The Autobrake Selector annunciation is expected to read within the sample range of 18 to 23 units during an extended ground delay. The first officer will cross-check any change in the Transponder advisory and advise the other pilot when the associated caution light remains illuminated.

**CAUTION:** During preflight, the pilot flying should confirm the Landing Gear Indication annunciation when conditions permit.



- During an extended ground delay, the pilot monitoring should cross-check the Pack Temperature Control annunciation when conditions permit.
- The Thrust Reverser quantity display is expected to read within the sample range of 45 to 55 units during preflight.
- Refer to the related topic for additional sample context.

The Weather Radar quantity display that differs from the expected state requires the First Officer to verify the condition if a discrepancy is observed. The Standby Instruments indication that differs from the expected state requires the relief pilot to cross-check the condition once the checklist item is complete. The relief pilot will cross-check any change in the Probe Heat advisory and advise the other pilot before the next phase of flight. The pilot monitoring will cross-check any change in the Cockpit Voice Recorder quantity display and advise the other pilot once the checklist item is complete.

The Flap Position Indication switch position is expected to read within the sample range of 3 to 15 units during approach. The pilot flying will verify any change in the Traffic Advisory Display selector position and advise the other pilot when operating at a sample station without ground power. The first officer will record any change in the Flight Management Computer switch position and advise the other pilot when operating at a sample station without ground power. During engine start, the First Officer should confirm the Pack Temperature Control switch position when the associated caution light remains illuminated. During parking, the pilot flying should cross-check the Pack Temperature Control indication when the associated caution light remains illuminated.

## 12.30 Operation

### 12.30.1 Stall Warning Interfaces

Values in this manual are invented and must not be used for any operational purpose. This text is fictional and exists only to give the prototype realistic volume and structure. Values in this manual are invented and must not be used for any operational purpose. The Nosewheel Steering switch position is expected to read within the sample range of 15 to 20 units during approach. This text is fictional and exists only to give the prototype realistic volume and structure.

The Thrust Reverser switch position that differs from the expected state requires the pilot monitoring to verify the condition unless directed otherwise by the Sample Operations Center. If the Wing Anti-Ice is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. The Flap Position Indication switch position is expected to read within the sample range of 18 to 23 units during approach. This text is fictional and exists only to give the prototype realistic volume and structure.

**CAUTION:** The Oxygen Distribution quantity display that differs from the expected state requires both pilots to record the condition if a discrepancy is observed.

The Window Heat quantity display is expected to read within the sample range of 38 to 49 units during descent. Values in this manual are invented and must not be used for any operational purpose. The pilot monitoring will monitor any change in the Fuel Crossfeed switch position and advise the other pilot if a discrepancy is observed. If the Probe Heat is inoperative, continue a turnaround only after the pilot monitoring has reviewed the associated sample guidance. During takeoff, the pilot flying should select the Autopilot Channel A status message when operating at a sample station without ground power.

- The Thrust Reverser annunciation is expected to read within the sample range of 29 to 41 units during descent.
- The Speedbrake Handle switch position is expected to read within the sample range of 83 to 87 units during landing.
- The Autothrottle selector position that differs from the expected state requires the pilot flying to confirm the condition before the next phase of flight.

**CAUTION:** If the Autopilot Channel B is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance.

**CAUTION:** This text is fictional and exists only to give the prototype realistic volume and structure. During climb, the First Officer should verify the Weather Radar status message if the indication does not stabilize within the sample interval.

**CAUTION:** The Autopilot Channel A indication that differs from the expected state requires the First Officer to verify the condition before the next phase of flight. If the Nosewheel Steering is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance.

If the Pack Temperature Control is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance. The Traffic Advisory Display quantity display is expected to read within the sample range of 53 to 59 units during descent. During preflight, the relief pilot should confirm the Window Heat advisory when the associated caution light remains illuminated. Refer to the related topic for additional sample context. The Brake Temperature Monitor selector position that differs from the expected state requires the pilot flying to confirm the condition if a discrepancy is observed. The wording here is placeholder content shaped like a procedure, not a procedure.

**12.30.2 Stall Warning Power Sources**

During engine start, both pilots should record the Transponder advisory before the next phase of flight. During engine start, both pilots should announce the Brake Temperature Monitor quantity display if a discrepancy is observed. The pilot monitoring will monitor any change in the Autopilot Channel B selector position and advise the other pilot unless directed otherwise by the Sample Operations Center.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Oxygen Distribution switch position     | 62 units     | Refer to related topic |
| Autobrake Selector quantity display     | 17 units     | Advisory only          |
| Cockpit Voice Recorder quantity display | 80 units     | Normal                 |

- If the Cockpit Voice Recorder is inoperative, continue climb only after both pilots has reviewed the associated sample guidance.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The first officer will brief any change in the Bleed Air Supply switch position and advise the other pilot if a discrepancy is observed.
- The pilot monitoring will verify any change in the Autothrottle selector position and advise the other pilot unless directed otherwise by the Sample Operations Center.
- If the Flight Management Computer is inoperative, continue taxi only after the pilot flying has reviewed the associated sample guidance.

The Autobrake Selector selector position is expected to read within the sample range of 36 to 45 units during preflight. The Stall Warning indication is expected to read within the sample range of 65 to 76 units during preflight. During a turnaround, both pilots should announce the Cockpit Voice Recorder annunciation when conditions permit. Refer to the related topic for additional sample context. During engine start, both pilots should record the Primary Electrical Bus selector position when operating at a sample station without ground power.

This text is fictional and exists only to give the prototype realistic volume and structure. During landing, the First Officer should select the Thrust Reverser indication when operating at a sample station without ground power. The pilot flying will announce any change in the Stall Warning indication and advise the other pilot when conditions permit. Both pilots will brief any change in the Brake Temperature Monitor switch position and advise the other pilot when the associated caution light remains illuminated. During descent, the First Officer should monitor the Window Heat quantity display if a discrepancy is observed. During preflight, the pilot monitoring should announce the Autobrake Selector annunciation when the associated caution light remains illuminated.

The Cargo Smoke Detection status message is expected to read within the sample range of 85 to 90 units during approach. The Probe Heat quantity display is expected to read within the sample range of 86 to 89 units during takeoff. The Cockpit Voice Recorder indication that differs from the expected state requires the relief pilot to cross-check the condition before the next phase of flight.

**12.30.3 Center Tank Pumps Status Messages**

The Flight Management Computer annunciation is expected to read within the sample range of 35 to 45 units during climb. If the Flap Position Indication is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance. If the Autothrottle is inoperative, continue preflight only after the relief pilot has reviewed the associated sample guidance. The Pack Temperature Control switch position that differs from the expected state requires the relief pilot to verify the condition before the next phase of flight. This text is fictional and exists only to give the prototype realistic volume and structure.

The Cargo Smoke Detection status message is expected to read within the sample range of 92 to 100 units during takeoff. If the Autobrake Selector is inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance. If the Autopilot Channel B is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance.

**CAUTION:** If the Standby Instruments is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance.

**NOTE:** If the Flap Position Indication is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance. The first officer will verify any change in the Nosewheel Steering selector position and advise the other pilot before the next phase of flight.

If the Cabin Pressure Controller is inoperative, continue taxi only after the First Officer has reviewed the associated sample guidance. The relief pilot will monitor any change in the Window Heat indication and advise the other pilot unless directed otherwise by the Sample Operations Center. The Standby Instruments annunciation that differs from the expected state requires the Captain to brief the condition if a discrepancy is observed. The Autopilot Channel B annunciation is expected to read within the sample range of 12 to 15 units during a turnaround. The captain will monitor any change in the Fuel Crossfeed indication and advise the other pilot when the associated caution light remains illuminated. The Autopilot Channel A quantity display that differs from the expected state requires the First Officer to monitor the condition when operating at a sample station without ground power.

During a diversion, the pilot monitoring should confirm the Pack Temperature Control status message when conditions permit. The pilot flying will verify any change in the Standby Instruments quantity display and advise the other pilot if the indication does not stabilize within the sample interval. During cruise, the pilot monitoring should verify the Autothrottle status message when operating at a sample station without ground power. The Brake Temperature Monitor annunciation is expected to read within the sample range of 93 to 104 units during a diversion.

| Condition                           | Sample value | Remarks                |
|-------------------------------------|--------------|------------------------|
| Nosewheel Steering quantity display | 18 units     | Refer to related topic |
| Thrust Reverser quantity display    | 81 units     | Advisory only          |
| Center Tank Pumps selector position | 4 units      | Monitor                |
| Cockpit Voice Recorder indication   | 35 units     | Refer to related topic |
| Speedbrake Handle advisory          | 12 units     | Normal                 |
| Cargo Smoke Detection indication    | 20 units     | Refer to related topic |
| Transponder quantity display        | 77 units     | Advisory only          |

The wording here is placeholder content shaped like a procedure, not a procedure. The captain will announce any change in the Flap Position Indication selector position and advise the other pilot when conditions permit. Refer to the related topic for additional sample context. If the Weather Radar is inoperative, continue engine start only after the pilot monitoring has reviewed the associated sample guidance. Both pilots will announce any change in the Hydraulic

System A indication and advise the other pilot unless directed otherwise by the Sample Operations Center. See 06.40.2 Stall Warning Overview.

**NOTE:** During preflight, the pilot monitoring should monitor the Autopilot Channel B status message when operating at a sample station without ground power. During a turnaround, the Captain should verify the Auxiliary Power Unit status message if the indication does not stabilize within the sample interval.

#### **12.30.4 Standby Instruments Indications**

The wording here is placeholder content shaped like a procedure, not a procedure. If the Engine Anti-Ice is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance. The captain will monitor any change in the Oxygen Distribution quantity display and advise the other pilot before the next phase of flight.

During a maintenance-requested ground run, the pilot flying should cross-check the Speedbrake Handle indication unless directed otherwise by the Sample Operations Center. The Nosewheel Steering selector position that differs from the expected state requires both pilots to select the condition when operating at a sample station without ground power. If the Weather Radar is inoperative, continue approach only after both pilots has reviewed the associated sample guidance. The Speedbrake Handle advisory that differs from the expected state requires the Captain to brief the condition when the associated caution light remains illuminated.

The Flight Management Computer indication is expected to read within the sample range of 52 to 63 units during cruise. Values in this manual are invented and must not be used for any operational purpose. Refer to the related topic for additional sample context. During cruise, the pilot flying should record the Autobrake Selector advisory if a discrepancy is observed. The Cockpit Voice Recorder quantity display is expected to read within the sample range of 95 to 103 units during parking.

Refer to the related topic for additional sample context. During landing, the First Officer should verify the Brake Temperature Monitor advisory when the associated caution light remains illuminated. If the Bleed Air Supply is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance. The Autobrake Selector advisory is expected to read within the sample range of 38 to 47 units during landing.

This text is fictional and exists only to give the prototype realistic volume and structure. If the Pack Temperature Control is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance. If the Auxiliary Power Unit is inoperative, continue cruise only after the First Officer has reviewed the associated sample guidance. The Engine Anti-Ice advisory that differs from the expected state requires the Captain to record the condition before the next phase of flight. Both pilots will brief any change in the Weather Radar selector position and advise the other pilot before the next phase of flight. During a turnaround, the relief pilot should verify the Standby Hydraulic status message if a discrepancy is observed.

#### **12.30.5 Landing Gear Indication Crew Awareness**

The pilot monitoring will verify any change in the Cockpit Voice Recorder annunciation and advise the other pilot before the next phase of flight. The Speedbrake Handle selector position is expected to read within the sample range of 61 to 67 units during preflight. During preflight, the First Officer should verify the Cabin Pressure Controller switch position when operating at a sample station without ground power. The Ground Proximity Monitor quantity display that differs from the expected state requires the First Officer to brief the condition before the next phase of flight.

During landing, both pilots should brief the Thrust Reverser status message when operating at a sample station without ground power. The Bleed Air Supply status message is expected to read within the sample range of 77 to 81 units during descent. During preflight, the First Officer should verify the Cabin Pressure Controller status message unless directed otherwise by the Sample Operations Center. The pilot monitoring will cross-check any change in the Pack Temperature Control annunciation and advise the other pilot when conditions permit.

- The Auxiliary Power Unit annunciation that differs from the expected state requires the pilot monitoring to announce the condition if a discrepancy is observed.
- This text is fictional and exists only to give the prototype realistic volume and structure.

- The Fuel Crossfeed advisory is expected to read within the sample range of 36 to 46 units during descent.
- During climb, both pilots should monitor the Speedbrake Handle indication if a discrepancy is observed.
- The pilot flying will brief any change in the Hydraulic System A quantity display and advise the other pilot before the next phase of flight.
- The Traffic Advisory Display annunciation that differs from the expected state requires the Captain to verify the condition if a discrepancy is observed.

| Condition                              | Sample value | Remarks                |
|----------------------------------------|--------------|------------------------|
| Auxiliary Power Unit selector position | 94 units     | Monitor                |
| Thrust Reverser advisory               | 1 units      | Monitor                |
| Standby Instruments status message     | 89 units     | Monitor                |
| Hydraulic System A status message      | 77 units     | Refer to related topic |
| Weather Radar annunciation             | 57 units     | Refer to related topic |
| Wing Anti-Ice annunciation             | 43 units     | Normal                 |

The captain will monitor any change in the Probe Heat advisory and advise the other pilot when conditions permit. If the Probe Heat is inoperative, continue engine start only after the pilot flying has reviewed the associated sample guidance. The Brake Temperature Monitor annunciation is expected to read within the sample range of 65 to 69 units during climb. The Autopilot Channel A indication that differs from the expected state requires the pilot flying to monitor the condition when conditions permit.

The Standby Instruments annunciation is expected to read within the sample range of 28 to 35 units during parking. The Flight Management Computer status message that differs from the expected state requires the Captain to monitor the condition unless directed otherwise by the Sample Operations Center. If the Fire Detection Loop is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance. The pilot flying will monitor any change in the Standby Hydraulic quantity display and advise the other pilot when operating at a sample station without ground power. The Landing Gear Indication advisory is expected to read within the sample range of 30 to 34 units during parking. The Fire Detection Loop switch position that differs from the expected state requires the relief pilot to verify the condition when the associated caution light remains illuminated.

**NOTE:** During cruise, the pilot monitoring should announce the Pack Temperature Control indication if the indication does not stabilize within the sample interval. During engine start, the relief pilot should select the Bleed Air Supply status message if a discrepancy is observed.

The Flight Management Computer advisory that differs from the expected state requires the Captain to record the condition when operating at a sample station without ground power. If the Bleed Air Supply is inoperative, continue descent only after both pilots has reviewed the associated sample guidance. The Nosewheel Steering annunciation is expected to read within the sample range of 49 to 61 units during a diversion. The Ground Proximity Monitor indication is expected to read within the sample range of 19 to 29 units during approach.

The Oxygen Distribution indication is expected to read within the sample range of 86 to 90 units during preflight. The Autobrake Selector selector position is expected to read within the sample range of 57 to 66 units during taxi. The Autobrake Selector advisory is expected to read within the sample range of 25 to 37 units during descent. The Stall Warning annunciation is expected to read within the sample range of 49 to 54 units during a maintenance-requested ground run. During engine start, the relief pilot should cross-check the Standby Instruments status message if a discrepancy is observed.

### 12.30.6 Standby Instruments Limits Display

Values in this manual are invented and must not be used for any operational purpose. The pilot monitoring will monitor any change in the Autobrake Selector switch position and advise the other pilot once the checklist item is complete. The pilot monitoring will monitor any change in the Pack Temperature Control advisory and advise the

other pilot once the checklist item is complete. Values in this manual are invented and must not be used for any operational purpose. The Flap Position Indication annunciation that differs from the expected state requires the Captain to cross-check the condition before the next phase of flight. During a maintenance-requested ground run, the relief pilot should confirm the Cabin Pressure Controller indication before the next phase of flight.

The Window Heat switch position is expected to read within the sample range of 36 to 44 units during a turnaround. The first officer will cross-check any change in the Nosewheel Steering status message and advise the other pilot before the next phase of flight. The Autopilot Channel A advisory that differs from the expected state requires the pilot flying to cross-check the condition when conditions permit.

The pilot monitoring will select any change in the Autobrake Selector status message and advise the other pilot before the next phase of flight. The Auxiliary Power Unit indication is expected to read within the sample range of 33 to 45 units during a diversion. Refer to the related topic for additional sample context.

The Flap Position Indication switch position that differs from the expected state requires both pilots to monitor the condition once the checklist item is complete. The Traffic Advisory Display advisory that differs from the expected state requires the pilot monitoring to record the condition if a discrepancy is observed. If the Oxygen Distribution is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance. The Weather Radar advisory that differs from the expected state requires the relief pilot to announce the condition when conditions permit. The Autothrottle selector position that differs from the expected state requires the Captain to verify the condition if the indication does not stabilize within the sample interval.

**CAUTION:** The Wing Anti-Ice status message is expected to read within the sample range of 52 to 63 units during descent. During a maintenance-requested ground run, the First Officer should confirm the Thrust Reverser annunciation if the indication does not stabilize within the sample interval.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Engine Anti-Ice annunciation             | 12 units     | Refer to related topic |
| Pack Temperature Control switch position | 51 units     | Monitor                |
| Standby Instruments indication           | 87 units     | Monitor                |

**CAUTION:** If the Autopilot Channel B is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance. During a maintenance-requested ground run, the relief pilot should cross-check the Ground Proximity Monitor indication if the indication does not stabilize within the sample interval.

**CAUTION:** The Weather Radar indication is expected to read within the sample range of 49 to 52 units during descent.

The Autothrottle indication that differs from the expected state requires both pilots to cross-check the condition before the next phase of flight. The Stall Warning annunciation is expected to read within the sample range of 46 to 55 units during climb. If the Wing Anti-Ice is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance. During landing, both pilots should cross-check the Fuel Crossfeed quantity display when the associated caution light remains illuminated. The relief pilot will cross-check any change in the Speedbrake Handle switch position and advise the other pilot unless directed otherwise by the Sample Operations Center.

**12.30.7 Primary Electrical Bus Interfaces**

During descent, both pilots should select the Engine Anti-Ice quantity display when the associated caution light remains illuminated. The Bleed Air Supply advisory that differs from the expected state requires the First Officer to confirm the condition before the next phase of flight. During a diversion, the relief pilot should record the Center Tank Pumps status message if a discrepancy is observed. If the Autobrake Selector is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance.

**NOTE:** If the Transponder is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance.



**CAUTION:** Both pilots will record any change in the Standby Instruments switch position and advise the other pilot when operating at a sample station without ground power. The Cockpit Voice Recorder status message that differs from the expected state requires the relief pilot to verify the condition unless directed otherwise by the Sample Operations Center.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Bleed Air Supply annunciation              | 37 units     | Normal                 |
| Probe Heat quantity display                | 45 units     | Refer to related topic |
| Wing Anti-Ice advisory                     | 38 units     | Refer to related topic |
| Pack Temperature Control selector position | 13 units     | Refer to related topic |
| Stall Warning switch position              | 87 units     | Monitor                |

**CAUTION:** The pilot monitoring will select any change in the Thrust Reverser selector position and advise the other pilot when conditions permit. The captain will verify any change in the Fire Detection Loop status message and advise the other pilot when operating at a sample station without ground power.

### 12.30.8 Flight Management Computer Power Sources

If the Standby Hydraulic is inoperative, continue a maintenance-requested ground run only after both pilots has reviewed the associated sample guidance. Refer to the related topic for additional sample context. The pilot monitoring will announce any change in the Brake Temperature Monitor indication and advise the other pilot before the next phase of flight. During a diversion, the First Officer should select the Cabin Pressure Controller quantity display unless directed otherwise by the Sample Operations Center. The captain will select any change in the Ground Proximity Monitor advisory and advise the other pilot before the next phase of flight. This text is fictional and exists only to give the prototype realistic volume and structure.

The pilot monitoring will record any change in the Engine Anti-Ice selector position and advise the other pilot once the checklist item is complete. The pilot monitoring will record any change in the Traffic Advisory Display switch position and advise the other pilot if the indication does not stabilize within the sample interval. The Standby Hydraulic status message that differs from the expected state requires the pilot monitoring to select the condition if a discrepancy is observed. If the Transponder is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance. The Flight Management Computer advisory that differs from the expected state requires the pilot flying to record the condition if the indication does not stabilize within the sample interval.

**NOTE:** The Autopilot Channel B quantity display is expected to read within the sample range of 98 to 103 units during landing.

The Fire Detection Loop annunciation is expected to read within the sample range of 82 to 86 units during parking. During taxi, both pilots should cross-check the Thrust Reverser annunciation before the next phase of flight. During preflight, the pilot monitoring should cross-check the Stall Warning indication when the associated caution light remains illuminated. The Thrust Reverser status message is expected to read within the sample range of 81 to 86 units during climb. If the Center Tank Pumps is inoperative, continue preflight only after both pilots has reviewed the associated sample guidance. The Landing Gear Indication quantity display that differs from the expected state requires the Captain to monitor the condition when operating at a sample station without ground power.

Values in this manual are invented and must not be used for any operational purpose. During approach, both pilots should verify the Primary Electrical Bus indication unless directed otherwise by the Sample Operations Center. Both pilots will announce any change in the Probe Heat status message and advise the other pilot if a discrepancy is observed. The captain will announce any change in the Nosewheel Steering annunciation and advise the other pilot when operating at a sample station without ground power. If the Probe Heat is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance. During takeoff, the Captain should select the Nosewheel Steering annunciation before the next phase of flight.

- The Weather Radar annunciation that differs from the expected state requires the First Officer to monitor the condition when conditions permit.

- The first officer will monitor any change in the Speedbrake Handle indication and advise the other pilot once the checklist item is complete.
- If the Pack Temperature Control is inoperative, continue engine start only after the Captain has reviewed the associated sample guidance.
- The Pack Temperature Control quantity display is expected to read within the sample range of 3 to 10 units during a diversion.
- If the Flap Position Indication is inoperative, continue taxi only after both pilots has reviewed the associated sample guidance.

**NOTE:** The captain will verify any change in the Standby Instruments annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center.

If the Center Tank Pumps is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance. The Auxiliary Power Unit switch position that differs from the expected state requires the First Officer to announce the condition when conditions permit. During a maintenance-requested ground run, the Captain should announce the Bleed Air Supply status message before the next phase of flight. During descent, the pilot flying should announce the Primary Electrical Bus selector position when the associated caution light remains illuminated. The Brake Temperature Monitor annunciation that differs from the expected state requires both pilots to confirm the condition when conditions permit. The Autobrake Selector selector position that differs from the expected state requires the Captain to announce the condition when operating at a sample station without ground power.

**12.30.9 Pack Temperature Control Power Sources**

The first officer will verify any change in the Hydraulic System A switch position and advise the other pilot when operating at a sample station without ground power. This text is fictional and exists only to give the prototype realistic volume and structure. The Autobrake Selector advisory is expected to read within the sample range of 81 to 88 units during taxi. During climb, the pilot flying should verify the Probe Heat advisory if a discrepancy is observed.

The first officer will record any change in the Hydraulic System A switch position and advise the other pilot if a discrepancy is observed. The captain will confirm any change in the Bleed Air Supply quantity display and advise the other pilot when operating at a sample station without ground power. If the Traffic Advisory Display is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance. The captain will announce any change in the Autopilot Channel B status message and advise the other pilot when operating at a sample station without ground power. This text is fictional and exists only to give the prototype realistic volume and structure.

| Condition                               | Sample value | Remarks       |
|-----------------------------------------|--------------|---------------|
| Flap Position Indication status message | 31 units     | Advisory only |
| Pack Temperature Control indication     | 92 units     | Advisory only |
| Probe Heat advisory                     | 23 units     | Monitor       |
| Thrust Reverser indication              | 3 units      | Monitor       |
| Window Heat advisory                    | 87 units     | Advisory only |

**CAUTION:** The Hydraulic System B switch position is expected to read within the sample range of 35 to 43 units during parking.

**NOTE:** If the Pack Temperature Control is inoperative, continue takeoff only after the First Officer has reviewed the associated sample guidance.

The Stall Warning switch position that differs from the expected state requires both pilots to brief the condition when the associated caution light remains illuminated. The Cargo Smoke Detection advisory that differs from the expected state requires the pilot flying to monitor the condition before the next phase of flight. During a maintenance-requested ground run, the relief pilot should record the Weather Radar quantity display when the associated caution light

remains illuminated. If the Probe Heat is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance. The Fire Detection Loop advisory is expected to read within the sample range of 82 to 93 units during taxi. The Fuel Crossfeed indication that differs from the expected state requires the pilot monitoring to record the condition when conditions permit.

The Center Tank Pumps status message that differs from the expected state requires the pilot monitoring to verify the condition unless directed otherwise by the Sample Operations Center. During landing, the pilot flying should cross-check the Transponder quantity display once the checklist item is complete. The first officer will verify any change in the Brake Temperature Monitor switch position and advise the other pilot if a discrepancy is observed.

**12.30.10 Primary Electrical Bus Indications**

Values in this manual are invented and must not be used for any operational purpose. The wording here is placeholder content shaped like a procedure, not a procedure. If the Auxiliary Power Unit is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance. If the Autopilot Channel A is inoperative, continue taxi only after the Captain has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure.

**NOTE:** During parking, the pilot monitoring should cross-check the Autopilot Channel A advisory if a discrepancy is observed. During preflight, both pilots should cross-check the Standby Instruments quantity display unless directed otherwise by the Sample Operations Center.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Cargo Smoke Detection status message      | 50 units     | Advisory only          |
| Weather Radar quantity display            | 57 units     | Advisory only          |
| Transponder advisory                      | 91 units     | Refer to related topic |
| Thrust Reverser advisory                  | 51 units     | Advisory only          |
| Flight Management Computer status message | 18 units     | Advisory only          |

The Landing Gear Indication advisory that differs from the expected state requires the pilot monitoring to confirm the condition if a discrepancy is observed. The Transponder selector position is expected to read within the sample range of 20 to 23 units during cruise. During descent, the pilot monitoring should brief the Landing Gear Indication status message unless directed otherwise by the Sample Operations Center. During climb, the relief pilot should announce the Window Heat status message when conditions permit. The Stall Warning status message is expected to read within the sample range of 78 to 88 units during a turnaround. The wording here is placeholder content shaped like a procedure, not a procedure.

**CAUTION:** If the Traffic Advisory Display is inoperative, continue a diversion only after the relief pilot has reviewed the associated sample guidance. During a diversion, the pilot flying should monitor the Fuel Crossfeed advisory unless directed otherwise by the Sample Operations Center.

This text is fictional and exists only to give the prototype realistic volume and structure. The Weather Radar indication that differs from the expected state requires both pilots to select the condition when operating at a sample station without ground power. The pilot flying will cross-check any change in the Standby Instruments status message and advise the other pilot unless directed otherwise by the Sample Operations Center. The Stall Warning selector position is expected to read within the sample range of 16 to 28 units during taxi. The Ground Proximity Monitor switch position is expected to read within the sample range of 38 to 42 units during a maintenance-requested ground run. If the Flap Position Indication is inoperative, continue descent only after the pilot flying has reviewed the associated sample guidance. See 03.40.5 Briefing: Brake Temperature Monitor.

| Condition                           | Sample value | Remarks                |
|-------------------------------------|--------------|------------------------|
| Nosewheel Steering status message   | 61 units     | Refer to related topic |
| Pack Temperature Control indication | 94 units     | Monitor                |

|                                        |          |               |
|----------------------------------------|----------|---------------|
| Probe Heat indication                  | 6 units  | Advisory only |
| Primary Electrical Bus switch position | 2 units  | Advisory only |
| Nosewheel Steering indication          | 87 units | Monitor       |

**12.30.11 Auxiliary Power Unit Indications**

The pilot flying will brief any change in the Window Heat indication and advise the other pilot when the associated caution light remains illuminated. If the Standby Instruments is inoperative, continue a maintenance-requested ground run only after both pilots has reviewed the associated sample guidance. Refer to the related topic for additional sample context. The wording here is placeholder content shaped like a procedure, not a procedure. The pilot monitoring will verify any change in the Hydraulic System B advisory and advise the other pilot when the associated caution light remains illuminated.

If the Flight Management Computer is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance. The pilot flying will select any change in the Pack Temperature Control indication and advise the other pilot once the checklist item is complete. If the Bleed Air Supply is inoperative, continue descent only after the First Officer has reviewed the associated sample guidance. The Autopilot Channel A selector position that differs from the expected state requires both pilots to announce the condition if the indication does not stabilize within the sample interval. The Center Tank Pumps indication is expected to read within the sample range of 85 to 92 units during engine start.

| Condition                           | Sample value | Remarks                |
|-------------------------------------|--------------|------------------------|
| Cockpit Voice Recorder annunciation | 45 units     | Advisory only          |
| Autopilot Channel A indication      | 24 units     | Refer to related topic |
| Autopilot Channel A status message  | 3 units      | Monitor                |

The Autobrake Selector switch position is expected to read within the sample range of 23 to 26 units during parking. The pilot monitoring will cross-check any change in the Stall Warning advisory and advise the other pilot before the next phase of flight. The pilot monitoring will record any change in the Autopilot Channel B status message and advise the other pilot if a discrepancy is observed. Both pilots will verify any change in the Autobrake Selector advisory and advise the other pilot unless directed otherwise by the Sample Operations Center.

This text is fictional and exists only to give the prototype realistic volume and structure. If the Center Tank Pumps is inoperative, continue engine start only after the pilot flying has reviewed the associated sample guidance. The captain will cross-check any change in the Autobrake Selector annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center. The Center Tank Pumps selector position that differs from the expected state requires the Captain to monitor the condition if the indication does not stabilize within the sample interval. During engine start, both pilots should announce the Cabin Pressure Controller selector position when operating at a sample station without ground power. If the Fuel Crossfeed is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance.

**12.30.12 Auxiliary Power Unit Normal Operation**

If the Brake Temperature Monitor is inoperative, continue climb only after the pilot flying has reviewed the associated sample guidance. The Cabin Pressure Controller quantity display is expected to read within the sample range of 29 to 41 units during approach. Values in this manual are invented and must not be used for any operational purpose.

During takeoff, the First Officer should announce the Fuel Crossfeed status message when conditions permit. During climb, the relief pilot should verify the Autothrottle quantity display when the associated caution light remains illuminated. During landing, the pilot flying should verify the Engine Anti-Ice selector position when the associated caution light remains illuminated.

- The pilot monitoring will confirm any change in the Cargo Smoke Detection status message and advise the other pilot if the indication does not stabilize within the sample interval.

- The pilot flying will announce any change in the Brake Temperature Monitor status message and advise the other pilot if a discrepancy is observed.
- During taxi, the Captain should brief the Wing Anti-Ice switch position when conditions permit.
- The Weather Radar annunciation is expected to read within the sample range of 64 to 73 units during engine start.
- If the Cockpit Voice Recorder is inoperative, continue climb only after the First Officer has reviewed the associated sample guidance.
- During an extended ground delay, the pilot flying should monitor the Engine Anti-Ice annunciation when operating at a sample station without ground power.

**CAUTION:** The Autobrake Selector quantity display is expected to read within the sample range of 57 to 65 units during parking.

The first officer will cross-check any change in the Cargo Smoke Detection status message and advise the other pilot before the next phase of flight. The first officer will select any change in the Nosewheel Steering advisory and advise the other pilot before the next phase of flight. This text is fictional and exists only to give the prototype realistic volume and structure. If the Speedbrake Handle is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance. The pilot flying will record any change in the Transponder advisory and advise the other pilot once the checklist item is complete.

Values in this manual are invented and must not be used for any operational purpose. The wording here is placeholder content shaped like a procedure, not a procedure. The Traffic Advisory Display selector position is expected to read within the sample range of 65 to 68 units during a maintenance-requested ground run. The Thrust Reverser advisory that differs from the expected state requires the Captain to announce the condition unless directed otherwise by the Sample Operations Center. The Ground Proximity Monitor annunciation is expected to read within the sample range of 48 to 51 units during landing.

**NOTE:** If the Speedbrake Handle is inoperative, continue a diversion only after the First Officer has reviewed the associated sample guidance. Refer to the related topic for additional sample context.

**CAUTION:** The Auxiliary Power Unit annunciation that differs from the expected state requires the pilot flying to announce the condition once the checklist item is complete. The Speedbrake Handle switch position that differs from the expected state requires the pilot flying to confirm the condition when operating at a sample station without ground power.

### 12.30.13 Fuel Crossfeed Limits Display

The Stall Warning annunciation that differs from the expected state requires both pilots to confirm the condition when the associated caution light remains illuminated. Refer to the related topic for additional sample context. Refer to the related topic for additional sample context.

**CAUTION:** The Thrust Reverser status message that differs from the expected state requires the pilot monitoring to confirm the condition when the associated caution light remains illuminated. The captain will select any change in the Autothrottle quantity display and advise the other pilot when the associated caution light remains illuminated.

**NOTE:** If the Nosewheel Steering is inoperative, continue climb only after both pilots has reviewed the associated sample guidance. During engine start, the Captain should select the Autopilot Channel B indication once the checklist item is complete.

The Fire Detection Loop advisory that differs from the expected state requires the Captain to brief the condition when conditions permit. The Stall Warning switch position is expected to read within the sample range of 44 to 51 units during taxi. If the Autopilot Channel A is inoperative, continue taxi only after the relief pilot has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. The Wing Anti-Ice switch position that differs from the expected state requires both pilots to verify the condition if the indication does not stabilize within the sample interval.

**CAUTION:** The first officer will record any change in the Probe Heat annunciation and advise the other pilot when conditions permit.

- The Standby Hydraulic status message is expected to read within the sample range of 57 to 60 units during preflight.
- The Standby Instruments status message that differs from the expected state requires the pilot monitoring to verify the condition once the checklist item is complete.
- The Speedbrake Handle indication that differs from the expected state requires the pilot flying to brief the condition when conditions permit.

**NOTE:** During taxi, the pilot monitoring should record the Nosewheel Steering status message when operating at a sample station without ground power. Values in this manual are invented and must not be used for any operational purpose.

If the Primary Electrical Bus is inoperative, continue a diversion only after the pilot monitoring has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. The captain will brief any change in the Landing Gear Indication advisory and advise the other pilot if a discrepancy is observed. This text is fictional and exists only to give the prototype realistic volume and structure. The wording here is placeholder content shaped like a procedure, not a procedure. The Stall Warning annunciation that differs from the expected state requires the Captain to brief the condition once the checklist item is complete.

This text is fictional and exists only to give the prototype realistic volume and structure. This text is fictional and exists only to give the prototype realistic volume and structure. The wording here is placeholder content shaped like a procedure, not a procedure. During a maintenance-requested ground run, the First Officer should verify the Probe Heat selector position when operating at a sample station without ground power.

#### 12.30.14 *Auxiliary Power Unit Power Sources*

The Transponder selector position that differs from the expected state requires the Captain to record the condition before the next phase of flight. The Hydraulic System B advisory is expected to read within the sample range of 38 to 45 units during climb. Values in this manual are invented and must not be used for any operational purpose. The Cockpit Voice Recorder selector position is expected to read within the sample range of 30 to 33 units during preflight. The Flight Management Computer advisory is expected to read within the sample range of 64 to 68 units during taxi.

**NOTE:** During parking, the relief pilot should verify the Standby Hydraulic advisory once the checklist item is complete. If the Ground Proximity Monitor is inoperative, continue descent only after the Captain has reviewed the associated sample guidance.

- The Stall Warning status message is expected to read within the sample range of 43 to 48 units during a diversion.
- If the Thrust Reverser is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance.
- The pilot flying will cross-check any change in the Window Heat annunciation and advise the other pilot when operating at a sample station without ground power.

**CAUTION:** If the Weather Radar is inoperative, continue an extended ground delay only after the Captain has reviewed the associated sample guidance.

**NOTE:** During taxi, both pilots should record the Primary Electrical Bus status message if the indication does not stabilize within the sample interval.

- The Hydraulic System B quantity display that differs from the expected state requires the pilot monitoring to monitor the condition when operating at a sample station without ground power.



- If the Oxygen Distribution is inoperative, continue taxi only after the pilot flying has reviewed the associated sample guidance.
- The Traffic Advisory Display annunciation is expected to read within the sample range of 48 to 55 units during descent.
- The Center Tank Pumps selector position is expected to read within the sample range of 44 to 52 units during climb.
- The Brake Temperature Monitor switch position that differs from the expected state requires the Captain to confirm the condition before the next phase of flight.
- If the Transponder is inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance.

**NOTE:** The Center Tank Pumps quantity display is expected to read within the sample range of 31 to 36 units during parking. During parking, the pilot flying should monitor the Traffic Advisory Display annunciation when operating at a sample station without ground power.

**12.30.15 Autopilot Channel B Test**

If the Weather Radar is inoperative, continue taxi only after the First Officer has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. Both pilots will announce any change in the Speedbrake Handle advisory and advise the other pilot once the checklist item is complete. The Weather Radar quantity display that differs from the expected state requires the pilot monitoring to confirm the condition before the next phase of flight.

The pilot flying will cross-check any change in the Wing Anti-Ice selector position and advise the other pilot before the next phase of flight. The Probe Heat switch position that differs from the expected state requires both pilots to monitor the condition unless directed otherwise by the Sample Operations Center. If the Flight Management Computer is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure.

**CAUTION:** If the Autopilot Channel B is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Window Heat annunciation                 | 74 units     | Refer to related topic |
| Stall Warning annunciation               | 70 units     | Advisory only          |
| Standby Hydraulic switch position        | 17 units     | Monitor                |
| Landing Gear Indication advisory         | 22 units     | Normal                 |
| Brake Temperature Monitor status message | 19 units     | Advisory only          |

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Speedbrake Handle selector position       | 30 units     | Normal                 |
| Traffic Advisory Display quantity display | 27 units     | Monitor                |
| Engine Anti-Ice switch position           | 75 units     | Monitor                |
| Nosewheel Steering indication             | 96 units     | Advisory only          |
| Pack Temperature Control switch position  | 15 units     | Monitor                |
| Standby Hydraulic status message          | 97 units     | Refer to related topic |

- If the Stall Warning is inoperative, continue taxi only after the pilot flying has reviewed the associated sample guidance.

- The Pack Temperature Control switch position that differs from the expected state requires the First Officer to brief the condition when operating at a sample station without ground power.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- The Standby Instruments switch position is expected to read within the sample range of 78 to 86 units during a turnaround.
- During a turnaround, the First Officer should select the Primary Electrical Bus switch position if the indication does not stabilize within the sample interval.
- During an extended ground delay, the First Officer should announce the Traffic Advisory Display quantity display if the indication does not stabilize within the sample interval.

| Condition                         | Sample value | Remarks                |
|-----------------------------------|--------------|------------------------|
| Center Tank Pumps indication      | 17 units     | Normal                 |
| Thrust Reverser advisory          | 92 units     | Refer to related topic |
| Nosewheel Steering status message | 83 units     | Advisory only          |
| Standby Instruments annunciation  | 45 units     | Monitor                |
| Thrust Reverser quantity display  | 53 units     | Monitor                |

The Stall Warning annunciation that differs from the expected state requires the pilot monitoring to cross-check the condition when the associated caution light remains illuminated. During parking, the Captain should record the Nosewheel Steering advisory before the next phase of flight. During cruise, the First Officer should monitor the Nosewheel Steering selector position unless directed otherwise by the Sample Operations Center. During takeoff, the pilot flying should select the Oxygen Distribution quantity display before the next phase of flight. If the Autopilot Channel B is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance. The Autothrottle indication that differs from the expected state requires the pilot monitoring to brief the condition if a discrepancy is observed.

**NOTE:** The Stall Warning status message that differs from the expected state requires both pilots to monitor the condition if the indication does not stabilize within the sample interval.

### 12.30.16 Hydraulic System A Overview

During descent, the pilot flying should announce the Speedbrake Handle annunciation when operating at a sample station without ground power. The first officer will select any change in the Cockpit Voice Recorder indication and advise the other pilot unless directed otherwise by the Sample Operations Center. Both pilots will monitor any change in the Flap Position Indication annunciation and advise the other pilot if a discrepancy is observed. During landing, the pilot monitoring should verify the Standby Instruments selector position when conditions permit. During takeoff, the pilot monitoring should verify the Standby Hydraulic quantity display when operating at a sample station without ground power. The Fuel Crossfeed indication that differs from the expected state requires both pilots to confirm the condition if a discrepancy is observed.

**NOTE:** If the Autopilot Channel A is inoperative, continue preflight only after the pilot monitoring has reviewed the associated sample guidance.

The wording here is placeholder content shaped like a procedure, not a procedure. Both pilots will announce any change in the Weather Radar annunciation and advise the other pilot if the indication does not stabilize within the sample interval. During approach, the pilot flying should cross-check the Fire Detection Loop indication if the indication does not stabilize within the sample interval. During approach, the Captain should monitor the Standby Instruments quantity display if the indication does not stabilize within the sample interval. The Probe Heat switch position is expected to read within the sample range of 95 to 100 units during engine start.

The Fire Detection Loop quantity display is expected to read within the sample range of 5 to 16 units during descent. The pilot flying will brief any change in the Hydraulic System A advisory and advise the other pilot if the indication

does not stabilize within the sample interval. The Center Tank Pumps annunciation that differs from the expected state requires the relief pilot to select the condition when operating at a sample station without ground power. The Weather Radar annunciation is expected to read within the sample range of 78 to 90 units during an extended ground delay. The Flap Position Indication annunciation that differs from the expected state requires the Captain to select the condition if the indication does not stabilize within the sample interval. The wording here is placeholder content shaped like a procedure, not a procedure.

The Fire Detection Loop advisory is expected to read within the sample range of 24 to 31 units during a maintenance-requested ground run. The Brake Temperature Monitor quantity display is expected to read within the sample range of 13 to 22 units during preflight. The Brake Temperature Monitor status message that differs from the expected state requires the Captain to brief the condition when conditions permit.

- The relief pilot will verify any change in the Cargo Smoke Detection switch position and advise the other pilot before the next phase of flight.
- The pilot flying will confirm any change in the Speedbrake Handle advisory and advise the other pilot when the associated caution light remains illuminated.
- Refer to the related topic for additional sample context.

| Condition                                    | Sample value | Remarks                |
|----------------------------------------------|--------------|------------------------|
| Flight Management Computer selector position | 80 units     | Normal                 |
| Speedbrake Handle selector position          | 82 units     | Monitor                |
| Autobrake Selector quantity display          | 63 units     | Monitor                |
| Autobrake Selector switch position           | 49 units     | Monitor                |
| Speedbrake Handle indication                 | 63 units     | Monitor                |
| Pack Temperature Control status message      | 82 units     | Refer to related topic |
| Standby Instruments quantity display         | 73 units     | Monitor                |

- Values in this manual are invented and must not be used for any operational purpose.
- The Hydraulic System B advisory that differs from the expected state requires both pilots to announce the condition when operating at a sample station without ground power.
- The Oxygen Distribution switch position that differs from the expected state requires the relief pilot to verify the condition when the associated caution light remains illuminated.

During cruise, the First Officer should select the Cockpit Voice Recorder quantity display before the next phase of flight. During a diversion, the pilot monitoring should monitor the Bleed Air Supply status message if a discrepancy is observed. The pilot monitoring will confirm any change in the Flap Position Indication switch position and advise the other pilot when conditions permit. The pilot monitoring will verify any change in the Landing Gear Indication indication and advise the other pilot when operating at a sample station without ground power. If the Thrust Reverser is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance. See 10.10.8 Autopilot Channel A Status Messages.

## Chapter 13 Systems: Navigation

### 13.10 Description

#### 13.10.1 Weather Radar Crew Awareness

The Nosewheel Steering selector position is expected to read within the sample range of 56 to 60 units during climb. If the Standby Instruments is inoperative, continue preflight only after the relief pilot has reviewed the associated sample guidance. The Hydraulic System B indication is expected to read within the sample range of 32 to 35 units during cruise. This text is fictional and exists only to give the prototype realistic volume and structure.

The Hydraulic System A quantity display is expected to read within the sample range of 86 to 96 units during an extended ground delay. The captain will brief any change in the Nosewheel Steering switch position and advise the other pilot before the next phase of flight. If the Hydraulic System B is inoperative, continue approach only after the First Officer has reviewed the associated sample guidance. The first officer will brief any change in the Primary Electrical Bus advisory and advise the other pilot if the indication does not stabilize within the sample interval. The captain will confirm any change in the Autopilot Channel B status message and advise the other pilot when the associated caution light remains illuminated. The relief pilot will record any change in the Autobrake Selector advisory and advise the other pilot when operating at a sample station without ground power.

**NOTE:** The pilot monitoring will verify any change in the Cabin Pressure Controller selector position and advise the other pilot if the indication does not stabilize within the sample interval. The Thrust Reverser quantity display that differs from the expected state requires the pilot monitoring to confirm the condition unless directed otherwise by the Sample Operations Center.

If the Flight Management Computer is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance. The Thrust Reverser indication is expected to read within the sample range of 43 to 49 units during cruise. Values in this manual are invented and must not be used for any operational purpose. The wording here is placeholder content shaped like a procedure, not a procedure. The captain will verify any change in the Fire Detection Loop annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center.

- This text is fictional and exists only to give the prototype realistic volume and structure.
- Both pilots will brief any change in the Thrust Reverser annunciation and advise the other pilot when conditions permit.
- The captain will monitor any change in the Window Heat advisory and advise the other pilot when operating at a sample station without ground power.
- The Autobrake Selector quantity display that differs from the expected state requires both pilots to select the condition unless directed otherwise by the Sample Operations Center.
- The captain will record any change in the Landing Gear Indication quantity display and advise the other pilot once the checklist item is complete.
- The Ground Proximity Monitor quantity display that differs from the expected state requires the First Officer to cross-check the condition if the indication does not stabilize within the sample interval.

The relief pilot will record any change in the Cargo Smoke Detection quantity display and advise the other pilot when conditions permit. Refer to the related topic for additional sample context. The Cabin Pressure Controller switch position that differs from the expected state requires the Captain to announce the condition before the next phase of flight. During cruise, the relief pilot should confirm the Autopilot Channel A indication when operating at a sample station without ground power.

The Cabin Pressure Controller indication is expected to read within the sample range of 68 to 73 units during climb. If the Stall Warning is inoperative, continue climb only after the Captain has reviewed the associated sample guidance.

The Bleed Air Supply advisory is expected to read within the sample range of 85 to 95 units during preflight. The Transponder annunciation that differs from the expected state requires the pilot flying to monitor the condition before the next phase of flight. The Autopilot Channel B switch position is expected to read within the sample range of 22 to 25 units during landing.

The pilot flying will brief any change in the Primary Electrical Bus selector position and advise the other pilot when the associated caution light remains illuminated. The pilot monitoring will cross-check any change in the Pack Temperature Control selector position and advise the other pilot when the associated caution light remains illuminated. This text is fictional and exists only to give the prototype realistic volume and structure. The Hydraulic System A selector position is expected to read within the sample range of 54 to 64 units during approach. During a turnaround, both pilots should monitor the Wing Anti-Ice status message when conditions permit.

Refer to the related topic for additional sample context. The Primary Electrical Bus advisory that differs from the expected state requires the relief pilot to verify the condition before the next phase of flight. The captain will brief any change in the Auxiliary Power Unit selector position and advise the other pilot when the associated caution light remains illuminated. This text is fictional and exists only to give the prototype realistic volume and structure. See 13.40.4 Center Tank Pumps Indications.

**13.10.2 Bleed Air Supply Crew Awareness**

The Primary Electrical Bus annunciation that differs from the expected state requires the pilot monitoring to select the condition when the associated caution light remains illuminated. The Weather Radar switch position that differs from the expected state requires the pilot flying to announce the condition once the checklist item is complete. If the Landing Gear Indication is inoperative, continue approach only after the relief pilot has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. The Autothrottle selector position is expected to read within the sample range of 40 to 52 units during climb. During an extended ground delay, the relief pilot should announce the Standby Instruments status message when the associated caution light remains illuminated.

| Condition                           | Sample value | Remarks                |
|-------------------------------------|--------------|------------------------|
| Landing Gear Indication indication  | 5 units      | Refer to related topic |
| Auxiliary Power Unit status message | 68 units     | Advisory only          |
| Hydraulic System A status message   | 3 units      | Refer to related topic |
| Fire Detection Loop advisory        | 8 units      | Normal                 |
| Fire Detection Loop switch position | 8 units      | Monitor                |

- If the Cabin Pressure Controller is inoperative, continue landing only after the relief pilot has reviewed the associated sample guidance.
- Values in this manual are invented and must not be used for any operational purpose.
- If the Wing Anti-Ice is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance.

| Condition                          | Sample value | Remarks                |
|------------------------------------|--------------|------------------------|
| Auxiliary Power Unit annunciation  | 96 units     | Normal                 |
| Autobrake Selector switch position | 58 units     | Refer to related topic |
| Wing Anti-Ice quantity display     | 88 units     | Advisory only          |
| Autobrake Selector status message  | 87 units     | Refer to related topic |

The wording here is placeholder content shaped like a procedure, not a procedure. If the Autopilot Channel A is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance. Refer to the related topic for additional sample context. During takeoff, the relief pilot should

cross-check the Center Tank Pumps indication when the associated caution light remains illuminated. The Flap Position Indication advisory that differs from the expected state requires the Captain to confirm the condition once the checklist item is complete.

The Flap Position Indication indication is expected to read within the sample range of 50 to 55 units during landing. During approach, the First Officer should verify the Weather Radar advisory when operating at a sample station without ground power. If the Traffic Advisory Display is inoperative, continue approach only after the pilot monitoring has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. The wording here is placeholder content shaped like a procedure, not a procedure. The Thrust Reverser status message that differs from the expected state requires both pilots to brief the condition before the next phase of flight. See 17.10.8 Hydraulic System A Reset Guidance.

### 13.10.3 Weather Radar Overview

If the Oxygen Distribution is inoperative, continue a turnaround only after both pilots has reviewed the associated sample guidance. During approach, the relief pilot should select the Standby Hydraulic selector position if a discrepancy is observed. The Landing Gear Indication indication that differs from the expected state requires the pilot flying to monitor the condition if the indication does not stabilize within the sample interval. The Engine Anti-Ice status message that differs from the expected state requires the pilot monitoring to record the condition if the indication does not stabilize within the sample interval. If the Hydraulic System A is inoperative, continue engine start only after both pilots has reviewed the associated sample guidance.

If the Primary Electrical Bus is inoperative, continue approach only after the pilot monitoring has reviewed the associated sample guidance. During climb, both pilots should verify the Fuel Crossfeed selector position if the indication does not stabilize within the sample interval. The first officer will monitor any change in the Speedbrake Handle advisory and advise the other pilot if the indication does not stabilize within the sample interval.

**NOTE:** The Auxiliary Power Unit annunciation is expected to read within the sample range of 15 to 27 units during climb.

Values in this manual are invented and must not be used for any operational purpose. The Stall Warning annunciation that differs from the expected state requires the pilot monitoring to select the condition when operating at a sample station without ground power. The Cockpit Voice Recorder indication is expected to read within the sample range of 40 to 45 units during a diversion. During takeoff, the First Officer should brief the Center Tank Pumps advisory when operating at a sample station without ground power.

If the Primary Electrical Bus is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance. The Primary Electrical Bus quantity display is expected to read within the sample range of 8 to 17 units during climb. During a diversion, the relief pilot should announce the Weather Radar advisory if a discrepancy is observed.

**NOTE:** During approach, both pilots should announce the Flap Position Indication selector position before the next phase of flight. The Standby Hydraulic selector position that differs from the expected state requires both pilots to verify the condition when conditions permit.

The relief pilot will record any change in the Window Heat switch position and advise the other pilot when the associated caution light remains illuminated. The relief pilot will select any change in the Autopilot Channel A selector position and advise the other pilot if the indication does not stabilize within the sample interval. The Cockpit Voice Recorder switch position is expected to read within the sample range of 37 to 41 units during an extended ground delay.

The Fuel Crossfeed indication is expected to read within the sample range of 18 to 23 units during a maintenance-requested ground run. The Cockpit Voice Recorder indication is expected to read within the sample range of 92 to 95 units during landing. The Flap Position Indication quantity display that differs from the expected state requires both pilots to monitor the condition before the next phase of flight. If the Autothrottle is inoperative, continue engine start only after both pilots has reviewed the associated sample guidance. The Fire Detection Loop advisory is expected to read within the sample range of 53 to 62 units during preflight. If the Engine Anti-Ice is



inoperative, continue an extended ground delay only after the pilot flying has reviewed the associated sample guidance.

Values in this manual are invented and must not be used for any operational purpose. If the Center Tank Pumps is inoperative, continue descent only after the Captain has reviewed the associated sample guidance. During climb, the pilot flying should monitor the Autopilot Channel A switch position when conditions permit. If the Traffic Advisory Display is inoperative, continue a diversion only after the relief pilot has reviewed the associated sample guidance. The captain will monitor any change in the Probe Heat indication and advise the other pilot if the indication does not stabilize within the sample interval. The captain will brief any change in the Cabin Pressure Controller advisory and advise the other pilot before the next phase of flight. See 07.10.7 Cargo Smoke Detection Overview.

**13.10.4 Cockpit Voice Recorder Crew Awareness**

The pilot flying will brief any change in the Nosewheel Steering advisory and advise the other pilot unless directed otherwise by the Sample Operations Center. The pilot monitoring will brief any change in the Fire Detection Loop status message and advise the other pilot before the next phase of flight. The Speedbrake Handle quantity display that differs from the expected state requires the Captain to monitor the condition unless directed otherwise by the Sample Operations Center. The Standby Instruments quantity display is expected to read within the sample range of 43 to 54 units during descent. The Engine Anti-Ice annunciation that differs from the expected state requires the Captain to brief the condition if the indication does not stabilize within the sample interval. The Hydraulic System B status message that differs from the expected state requires the Captain to verify the condition once the checklist item is complete.

During parking, the Captain should cross-check the Oxygen Distribution advisory unless directed otherwise by the Sample Operations Center. The Hydraulic System B status message that differs from the expected state requires the relief pilot to monitor the condition if the indication does not stabilize within the sample interval. The Probe Heat status message is expected to read within the sample range of 32 to 38 units during an extended ground delay. If the Nosewheel Steering is inoperative, continue an extended ground delay only after the Captain has reviewed the associated sample guidance. If the Bleed Air Supply is inoperative, continue approach only after the First Officer has reviewed the associated sample guidance.

| Condition                              | Sample value | Remarks                |
|----------------------------------------|--------------|------------------------|
| Autothrottle advisory                  | 25 units     | Refer to related topic |
| Cockpit Voice Recorder switch position | 89 units     | Normal                 |
| Probe Heat advisory                    | 80 units     | Monitor                |

**NOTE:** The Autothrottle annunciation is expected to read within the sample range of 90 to 95 units during cruise.

The Engine Anti-Ice advisory that differs from the expected state requires the pilot monitoring to confirm the condition if the indication does not stabilize within the sample interval. The pilot monitoring will select any change in the Oxygen Distribution status message and advise the other pilot when operating at a sample station without ground power. The Hydraulic System A status message that differs from the expected state requires the pilot flying to cross-check the condition before the next phase of flight. The Auxiliary Power Unit advisory that differs from the expected state requires the Captain to confirm the condition once the checklist item is complete. Values in this manual are invented and must not be used for any operational purpose. During takeoff, the relief pilot should brief the Brake Temperature Monitor advisory when conditions permit.

The Thrust Reverser annunciation is expected to read within the sample range of 2 to 14 units during an extended ground delay. If the Speedbrake Handle is inoperative, continue parking only after the pilot monitoring has reviewed the associated sample guidance. If the Standby Hydraulic is inoperative, continue climb only after the pilot flying has reviewed the associated sample guidance. The Standby Hydraulic annunciation is expected to read within the sample range of 19 to 26 units during landing.

The relief pilot will select any change in the Standby Instruments selector position and advise the other pilot unless directed otherwise by the Sample Operations Center. Refer to the related topic for additional sample context. The

relief pilot will monitor any change in the Standby Instruments indication and advise the other pilot when operating at a sample station without ground power. If the Traffic Advisory Display is inoperative, continue approach only after the First Officer has reviewed the associated sample guidance.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Cockpit Voice Recorder quantity display    | 40 units     | Advisory only          |
| Autobrake Selector switch position         | 3 units      | Advisory only          |
| Transponder indication                     | 51 units     | Monitor                |
| Pack Temperature Control selector position | 76 units     | Refer to related topic |
| Autopilot Channel A quantity display       | 9 units      | Refer to related topic |
| Bleed Air Supply annunciation              | 67 units     | Refer to related topic |

The Cabin Pressure Controller selector position is expected to read within the sample range of 91 to 102 units during an extended ground delay. The Hydraulic System A advisory is expected to read within the sample range of 15 to 18 units during a turnaround. Refer to the related topic for additional sample context. If the Thrust Reverser is inoperative, continue preflight only after the Captain has reviewed the associated sample guidance. During a diversion, the pilot flying should monitor the Autopilot Channel B quantity display before the next phase of flight. The pilot flying will select any change in the Hydraulic System A annunciation and advise the other pilot once the checklist item is complete.

### 13.10.5 Hydraulic System B Indications

If the Ground Proximity Monitor is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance. During climb, the relief pilot should record the Landing Gear Indication indication if the indication does not stabilize within the sample interval. Values in this manual are invented and must not be used for any operational purpose. If the Probe Heat is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance.

| Condition                              | Sample value | Remarks                |
|----------------------------------------|--------------|------------------------|
| Transponder quantity display           | 66 units     | Normal                 |
| Bleed Air Supply switch position       | 96 units     | Refer to related topic |
| Wing Anti-Ice status message           | 70 units     | Refer to related topic |
| Auxiliary Power Unit quantity display  | 83 units     | Normal                 |
| Standby Instruments selector position  | 45 units     | Advisory only          |
| Landing Gear Indication status message | 19 units     | Advisory only          |
| Standby Instruments selector position  | 74 units     | Monitor                |

**NOTE:** The pilot flying will announce any change in the Primary Electrical Bus switch position and advise the other pilot when the associated caution light remains illuminated.

**NOTE:** The Fire Detection Loop selector position is expected to read within the sample range of 27 to 32 units during preflight.

The captain will brief any change in the Engine Anti-Ice quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center. The Cabin Pressure Controller annunciation is expected to read within the sample range of 73 to 77 units during a turnaround. The wording here is placeholder content shaped like a procedure, not a procedure. The Autopilot Channel A status message is expected to read within the sample range of 41 to 44 units during taxi. The Window Heat quantity display is expected to read within the sample range of 44 to 49 units during descent. If the Standby Hydraulic is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance.

If the Standby Instruments is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. The Bleed Air Supply selector position is expected to read within the sample range of 37 to 40 units during cruise.

If the Window Heat is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance. The first officer will brief any change in the Probe Heat switch position and advise the other pilot when operating at a sample station without ground power. The Fuel Crossfeed status message is expected to read within the sample range of 95 to 106 units during landing. If the Autobrake Selector is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance.

The wording here is placeholder content shaped like a procedure, not a procedure. The pilot flying will record any change in the Hydraulic System B status message and advise the other pilot when the associated caution light remains illuminated. The Standby Hydraulic selector position that differs from the expected state requires both pilots to announce the condition when the associated caution light remains illuminated. The Cargo Smoke Detection annunciation is expected to read within the sample range of 5 to 13 units during parking. Refer to the related topic for additional sample context. The Standby Hydraulic status message is expected to read within the sample range of 28 to 38 units during takeoff.

**13.10.6 Transponder Power Sources**

During a maintenance-requested ground run, both pilots should monitor the Engine Anti-Ice status message when operating at a sample station without ground power. The Autopilot Channel A status message that differs from the expected state requires the Captain to record the condition if a discrepancy is observed. The pilot monitoring will monitor any change in the Flap Position Indication switch position and advise the other pilot if the indication does not stabilize within the sample interval.

**NOTE:** If the Pack Temperature Control is inoperative, continue taxi only after both pilots has reviewed the associated sample guidance.

The Fire Detection Loop status message that differs from the expected state requires the pilot monitoring to announce the condition if the indication does not stabilize within the sample interval. During a diversion, the pilot monitoring should brief the Transponder advisory unless directed otherwise by the Sample Operations Center. The Autopilot Channel A selector position that differs from the expected state requires the pilot monitoring to monitor the condition when conditions permit. The Fire Detection Loop selector position is expected to read within the sample range of 89 to 96 units during preflight.

**NOTE:** The pilot flying will confirm any change in the Fire Detection Loop selector position and advise the other pilot when operating at a sample station without ground power.

The Autothrottle selector position is expected to read within the sample range of 68 to 72 units during preflight. The Ground Proximity Monitor advisory is expected to read within the sample range of 42 to 45 units during landing. The Stall Warning advisory that differs from the expected state requires the First Officer to brief the condition before the next phase of flight.

**13.10.7 Nosewheel Steering Crew Awareness**

During landing, the pilot monitoring should announce the Flap Position Indication advisory unless directed otherwise by the Sample Operations Center. Both pilots will brief any change in the Probe Heat status message and advise the other pilot once the checklist item is complete. If the Autopilot Channel A is inoperative, continue an extended ground delay only after the pilot flying has reviewed the associated sample guidance. During parking, the First Officer should select the Probe Heat annunciation if a discrepancy is observed.

**NOTE:** The Stall Warning quantity display that differs from the expected state requires the First Officer to select the condition if the indication does not stabilize within the sample interval.

| Condition             | Sample value | Remarks       |
|-----------------------|--------------|---------------|
| Autothrottle advisory | 86 units     | Advisory only |

|                                |          |                        |
|--------------------------------|----------|------------------------|
| Fuel Crossfeed switch position | 94 units | Monitor                |
| Hydraulic System B indication  | 52 units | Normal                 |
| Hydraulic System A advisory    | 56 units | Refer to related topic |

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Weather Radar indication                | 21 units     | Monitor                |
| Hydraulic System A annunciation         | 41 units     | Refer to related topic |
| Flight Management Computer annunciation | 65 units     | Refer to related topic |

- During cruise, the pilot flying should select the Center Tank Pumps switch position if a discrepancy is observed.
- The Brake Temperature Monitor annunciation that differs from the expected state requires the pilot monitoring to verify the condition before the next phase of flight.
- If the Speedbrake Handle is inoperative, continue engine start only after the Captain has reviewed the associated sample guidance.
- During cruise, the pilot monitoring should record the Stall Warning indication if the indication does not stabilize within the sample interval.

### 13.10.8 Fuel Crossfeed Normal Operation

Values in this manual are invented and must not be used for any operational purpose. The first officer will record any change in the Stall Warning switch position and advise the other pilot once the checklist item is complete. If the Speedbrake Handle is inoperative, continue cruise only after the First Officer has reviewed the associated sample guidance. The Standby Hydraulic indication that differs from the expected state requires the relief pilot to select the condition once the checklist item is complete.

**CAUTION:** During approach, the Captain should cross-check the Pack Temperature Control quantity display if the indication does not stabilize within the sample interval.

**CAUTION:** During engine start, the First Officer should brief the Transponder quantity display when conditions permit. The wording here is placeholder content shaped like a procedure, not a procedure.

The Standby Instruments status message that differs from the expected state requires both pilots to announce the condition when the associated caution light remains illuminated. If the Nosewheel Steering is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance. The Autobrake Selector quantity display is expected to read within the sample range of 35 to 38 units during descent. The Cockpit Voice Recorder switch position that differs from the expected state requires the relief pilot to verify the condition when the associated caution light remains illuminated.

During cruise, the Captain should verify the Cargo Smoke Detection status message when the associated caution light remains illuminated. The Autothrottle annunciation is expected to read within the sample range of 13 to 17 units during parking. The Transponder status message that differs from the expected state requires the relief pilot to announce the condition unless directed otherwise by the Sample Operations Center. The pilot monitoring will brief any change in the Pack Temperature Control advisory and advise the other pilot when operating at a sample station without ground power. During a maintenance-requested ground run, the Captain should brief the Weather Radar switch position when operating at a sample station without ground power.

The Autobrake Selector annunciation is expected to read within the sample range of 89 to 92 units during descent. The Cargo Smoke Detection quantity display that differs from the expected state requires both pilots to brief the condition once the checklist item is complete. Both pilots will announce any change in the Fire Detection Loop status message and advise the other pilot if a discrepancy is observed. The Wing Anti-Ice quantity display that differs from the expected state requires the First Officer to verify the condition when the associated caution light remains illuminated.

13.10.9 Fire Detection Loop Power Sources

The first officer will cross-check any change in the Cockpit Voice Recorder advisory and advise the other pilot before the next phase of flight. The pilot monitoring will record any change in the Engine Anti-Ice quantity display and advise the other pilot once the checklist item is complete. The first officer will confirm any change in the Window Heat annunciation and advise the other pilot when conditions permit. The Pack Temperature Control quantity display is expected to read within the sample range of 28 to 37 units during a turnaround. The Standby Instruments advisory that differs from the expected state requires the Captain to brief the condition when the associated caution light remains illuminated.

Refer to the related topic for additional sample context. Values in this manual are invented and must not be used for any operational purpose. The Window Heat advisory is expected to read within the sample range of 41 to 45 units during takeoff.

The captain will brief any change in the Autothrottle status message and advise the other pilot before the next phase of flight. The Auxiliary Power Unit advisory that differs from the expected state requires the relief pilot to monitor the condition when operating at a sample station without ground power. If the Brake Temperature Monitor is inoperative, continue approach only after the pilot monitoring has reviewed the associated sample guidance.

- During taxi, both pilots should announce the Wing Anti-Ice switch position unless directed otherwise by the Sample Operations Center.
- If the Brake Temperature Monitor is inoperative, continue descent only after the Captain has reviewed the associated sample guidance.
- The pilot flying will announce any change in the Pack Temperature Control quantity display and advise the other pilot if the indication does not stabilize within the sample interval.
- The Brake Temperature Monitor status message is expected to read within the sample range of 63 to 72 units during a maintenance-requested ground run.
- If the Wing Anti-Ice is inoperative, continue a turnaround only after the First Officer has reviewed the associated sample guidance.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Traffic Advisory Display advisory     | 81 units     | Refer to related topic |
| Weather Radar selector position       | 70 units     | Advisory only          |
| Flap Position Indication annunciation | 1 units      | Monitor                |
| Cargo Smoke Detection indication      | 41 units     | Monitor                |
| Thrust Reverser switch position       | 89 units     | Advisory only          |
| Flap Position Indication advisory     | 52 units     | Monitor                |
| Autothrottle selector position        | 28 units     | Advisory only          |

13.10.10 Hydraulic System B Overview

The Cabin Pressure Controller quantity display is expected to read within the sample range of 43 to 49 units during a maintenance-requested ground run. The Fuel Crossfeed annunciation is expected to read within the sample range of 52 to 55 units during engine start. The Pack Temperature Control advisory is expected to read within the sample range of 24 to 32 units during landing. The wording here is placeholder content shaped like a procedure, not a procedure. This text is fictional and exists only to give the prototype realistic volume and structure. The Hydraulic System B advisory that differs from the expected state requires the pilot monitoring to brief the condition if the indication does not stabilize within the sample interval.

| Condition                           | Sample value | Remarks                |
|-------------------------------------|--------------|------------------------|
| Flight Management Computer advisory | 70 units     | Refer to related topic |

|                                          |          |               |
|------------------------------------------|----------|---------------|
| Brake Temperature Monitor status message | 83 units | Normal        |
| Oxygen Distribution status message       | 46 units | Advisory only |
| Fuel Crossfeed status message            | 59 units | Normal        |
| Fuel Crossfeed annunciation              | 83 units | Advisory only |

- This text is fictional and exists only to give the prototype realistic volume and structure.
- Refer to the related topic for additional sample context.
- The Brake Temperature Monitor quantity display that differs from the expected state requires the relief pilot to select the condition if the indication does not stabilize within the sample interval.
- The Standby Hydraulic advisory is expected to read within the sample range of 69 to 79 units during an extended ground delay.
- Refer to the related topic for additional sample context.

**CAUTION:** Refer to the related topic for additional sample context.

**NOTE:** The pilot flying will announce any change in the Fuel Crossfeed advisory and advise the other pilot if a discrepancy is observed.

Refer to the related topic for additional sample context. Both pilots will announce any change in the Flap Position Indication switch position and advise the other pilot when operating at a sample station without ground power. The Transponder status message is expected to read within the sample range of 86 to 96 units during climb. The Pack Temperature Control annunciation is expected to read within the sample range of 93 to 100 units during an extended ground delay.

The first officer will brief any change in the Standby Hydraulic advisory and advise the other pilot if the indication does not stabilize within the sample interval. The Standby Hydraulic advisory that differs from the expected state requires the First Officer to verify the condition unless directed otherwise by the Sample Operations Center. The captain will cross-check any change in the Auxiliary Power Unit advisory and advise the other pilot unless directed otherwise by the Sample Operations Center. The pilot flying will brief any change in the Auxiliary Power Unit selector position and advise the other pilot unless directed otherwise by the Sample Operations Center. Values in this manual are invented and must not be used for any operational purpose.

- The pilot monitoring will record any change in the Autobrake Selector indication and advise the other pilot when operating at a sample station without ground power.
- If the Hydraulic System A is inoperative, continue taxi only after the relief pilot has reviewed the associated sample guidance.
- The Standby Hydraulic selector position that differs from the expected state requires the pilot flying to monitor the condition once the checklist item is complete.
- The pilot flying will select any change in the Transponder advisory and advise the other pilot when operating at a sample station without ground power.
- The Speedbrake Handle advisory is expected to read within the sample range of 54 to 61 units during a maintenance-requested ground run.
- The pilot flying will cross-check any change in the Cabin Pressure Controller selector position and advise the other pilot when conditions permit.

### 13.10.11 Fire Detection Loop Test

During descent, the pilot flying should monitor the Ground Proximity Monitor selector position when the associated caution light remains illuminated. During preflight, the pilot monitoring should select the Hydraulic System A indication unless directed otherwise by the Sample Operations Center. The Autopilot Channel A indication that differs from the



expected state requires the relief pilot to announce the condition if a discrepancy is observed. The Cockpit Voice Recorder switch position that differs from the expected state requires the pilot monitoring to announce the condition if a discrepancy is observed. The Hydraulic System A selector position that differs from the expected state requires the First Officer to brief the condition if the indication does not stabilize within the sample interval. The Standby Instruments status message that differs from the expected state requires the First Officer to confirm the condition before the next phase of flight.

During a maintenance-requested ground run, both pilots should cross-check the Landing Gear Indication quantity display if the indication does not stabilize within the sample interval. The Probe Heat status message is expected to read within the sample range of 69 to 75 units during descent. The Stall Warning annunciation is expected to read within the sample range of 26 to 32 units during descent. The Brake Temperature Monitor indication is expected to read within the sample range of 44 to 56 units during an extended ground delay.

**NOTE:** The Transponder advisory that differs from the expected state requires the Captain to monitor the condition when operating at a sample station without ground power.

The wording here is placeholder content shaped like a procedure, not a procedure. The Brake Temperature Monitor selector position is expected to read within the sample range of 10 to 21 units during a turnaround. If the Pack Temperature Control is inoperative, continue a maintenance-requested ground run only after the pilot flying has reviewed the associated sample guidance. If the Autothrottle is inoperative, continue a diversion only after the pilot monitoring has reviewed the associated sample guidance. The Autobrake Selector annunciation is expected to read within the sample range of 37 to 45 units during takeoff. See 03.60.20 Verification: Landing Gear Indication.

- The pilot monitoring will select any change in the Brake Temperature Monitor switch position and advise the other pilot unless directed otherwise by the Sample Operations Center.
- Values in this manual are invented and must not be used for any operational purpose.
- During descent, the relief pilot should brief the Hydraulic System B quantity display if the indication does not stabilize within the sample interval.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- Values in this manual are invented and must not be used for any operational purpose.

**13.10.12 Ground Proximity Monitor Test**

The Landing Gear Indication indication that differs from the expected state requires the relief pilot to announce the condition unless directed otherwise by the Sample Operations Center. The Cabin Pressure Controller annunciation that differs from the expected state requires the pilot flying to verify the condition once the checklist item is complete. The pilot monitoring will record any change in the Landing Gear Indication quantity display and advise the other pilot when the associated caution light remains illuminated. During climb, both pilots should brief the Center Tank Pumps quantity display when operating at a sample station without ground power.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Flight Management Computer advisory     | 61 units     | Refer to related topic |
| Cockpit Voice Recorder indication       | 42 units     | Normal                 |
| Primary Electrical Bus quantity display | 44 units     | Monitor                |
| Hydraulic System B selector position    | 91 units     | Advisory only          |

The Hydraulic System B indication that differs from the expected state requires the pilot monitoring to confirm the condition unless directed otherwise by the Sample Operations Center. The wording here is placeholder content shaped like a procedure, not a procedure. The Landing Gear Indication selector position is expected to read within the sample range of 72 to 76 units during approach. If the Primary Electrical Bus is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance.

The first officer will verify any change in the Speedbrake Handle quantity display and advise the other pilot when operating at a sample station without ground power. During cruise, both pilots should record the Autopilot Channel A indication unless directed otherwise by the Sample Operations Center. The relief pilot will confirm any change in the Hydraulic System A indication and advise the other pilot if a discrepancy is observed. If the Probe Heat is inoperative, continue cruise only after both pilots has reviewed the associated sample guidance.

If the Standby Instruments is inoperative, continue approach only after the pilot monitoring has reviewed the associated sample guidance. The relief pilot will cross-check any change in the Weather Radar switch position and advise the other pilot if a discrepancy is observed. If the Speedbrake Handle is inoperative, continue landing only after the Captain has reviewed the associated sample guidance. The Autobrake Selector selector position that differs from the expected state requires both pilots to select the condition when the associated caution light remains illuminated. During taxi, the pilot monitoring should confirm the Landing Gear Indication annunciation when operating at a sample station without ground power.

**NOTE:** If the Ground Proximity Monitor is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance.

**CAUTION:** If the Landing Gear Indication is inoperative, continue an extended ground delay only after the pilot flying has reviewed the associated sample guidance.

**CAUTION:** During cruise, the First Officer should confirm the Brake Temperature Monitor switch position if the indication does not stabilize within the sample interval.

### 13.10.13 *Flight Management Computer Overview*

The relief pilot will monitor any change in the Auxiliary Power Unit advisory and advise the other pilot if the indication does not stabilize within the sample interval. The relief pilot will announce any change in the Autobrake Selector advisory and advise the other pilot before the next phase of flight. The wording here is placeholder content shaped like a procedure, not a procedure. This text is fictional and exists only to give the prototype realistic volume and structure.

**CAUTION:** During a maintenance-requested ground run, the pilot flying should monitor the Autopilot Channel B annunciation before the next phase of flight. The wording here is placeholder content shaped like a procedure, not a procedure.

**CAUTION:** The Fire Detection Loop annunciation that differs from the expected state requires the Captain to confirm the condition before the next phase of flight.

The Autobrake Selector annunciation is expected to read within the sample range of 23 to 33 units during takeoff. The Autobrake Selector indication is expected to read within the sample range of 12 to 16 units during descent. If the Primary Electrical Bus is inoperative, continue an extended ground delay only after the pilot flying has reviewed the associated sample guidance.

**CAUTION:** The Nosewheel Steering indication that differs from the expected state requires the Captain to record the condition once the checklist item is complete. If the Fuel Crossfeed is inoperative, continue climb only after the Captain has reviewed the associated sample guidance.

The Cockpit Voice Recorder switch position that differs from the expected state requires the pilot monitoring to verify the condition if the indication does not stabilize within the sample interval. If the Cockpit Voice Recorder is inoperative, continue descent only after the First Officer has reviewed the associated sample guidance. During cruise, both pilots should select the Bleed Air Supply annunciation unless directed otherwise by the Sample Operations Center. The Transponder switch position that differs from the expected state requires the relief pilot to brief the condition before the next phase of flight.

The Probe Heat switch position is expected to read within the sample range of 34 to 45 units during a turnaround. If the Engine Anti-Ice is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. The first officer will monitor any change in the Hydraulic System A selector position and advise the other pilot when operating

at a sample station without ground power. If the Standby Hydraulic is inoperative, continue a maintenance-requested ground run only after the pilot monitoring has reviewed the associated sample guidance. Both pilots will brief any change in the Flap Position Indication selector position and advise the other pilot when operating at a sample station without ground power.

#### **13.10.14 Hydraulic System A Reset Guidance**

The Primary Electrical Bus status message that differs from the expected state requires the pilot monitoring to verify the condition if the indication does not stabilize within the sample interval. If the Weather Radar is inoperative, continue a turnaround only after the pilot monitoring has reviewed the associated sample guidance. Both pilots will announce any change in the Stall Warning quantity display and advise the other pilot if a discrepancy is observed. The Nosewheel Steering status message that differs from the expected state requires the pilot flying to confirm the condition unless directed otherwise by the Sample Operations Center. During approach, the relief pilot should verify the Probe Heat annunciation before the next phase of flight. The Weather Radar status message that differs from the expected state requires the relief pilot to cross-check the condition when the associated caution light remains illuminated.

- This text is fictional and exists only to give the prototype realistic volume and structure.
- The Wing Anti-Ice switch position that differs from the expected state requires the pilot monitoring to confirm the condition unless directed otherwise by the Sample Operations Center.
- The Auxiliary Power Unit switch position that differs from the expected state requires the pilot monitoring to cross-check the condition if a discrepancy is observed.
- If the Cargo Smoke Detection is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance.
- The Fire Detection Loop advisory that differs from the expected state requires the First Officer to verify the condition unless directed otherwise by the Sample Operations Center.
- The first officer will select any change in the Speedbrake Handle switch position and advise the other pilot when conditions permit.

The relief pilot will select any change in the Landing Gear Indication annunciation and advise the other pilot once the checklist item is complete. The Traffic Advisory Display status message that differs from the expected state requires the pilot flying to verify the condition when operating at a sample station without ground power. The Wing Anti-Ice indication that differs from the expected state requires both pilots to cross-check the condition when conditions permit.

The pilot flying will confirm any change in the Autobrake Selector selector position and advise the other pilot once the checklist item is complete. This text is fictional and exists only to give the prototype realistic volume and structure. The captain will brief any change in the Autothrottle status message and advise the other pilot unless directed otherwise by the Sample Operations Center. The Speedbrake Handle indication that differs from the expected state requires the Captain to monitor the condition unless directed otherwise by the Sample Operations Center. This text is fictional and exists only to give the prototype realistic volume and structure.

During an extended ground delay, the First Officer should verify the Fire Detection Loop selector position when the associated caution light remains illuminated. The Cabin Pressure Controller indication is expected to read within the sample range of 29 to 37 units during climb. During cruise, the pilot flying should select the Autopilot Channel A selector position before the next phase of flight. The Brake Temperature Monitor annunciation is expected to read within the sample range of 21 to 25 units during landing. The Flight Management Computer annunciation that differs from the expected state requires the pilot flying to brief the condition before the next phase of flight. Refer to the related topic for additional sample context.

#### **13.10.15 Fuel Crossfeed Interfaces**

The Cockpit Voice Recorder quantity display that differs from the expected state requires the pilot flying to verify the condition when the associated caution light remains illuminated. The wording here is placeholder content shaped like a procedure, not a procedure. The Center Tank Pumps indication that differs from the expected state requires the pilot monitoring to brief the condition when conditions permit.

**CAUTION:** If the Probe Heat is inoperative, continue climb only after the relief pilot has reviewed the associated sample guidance. The Probe Heat status message is expected to read within the sample range of 80 to 91 units during landing.

- The relief pilot will cross-check any change in the Autopilot Channel B switch position and advise the other pilot once the checklist item is complete.
- The first officer will record any change in the Cabin Pressure Controller quantity display and advise the other pilot when conditions permit.
- The wording here is placeholder content shaped like a procedure, not a procedure.

**CAUTION:** During preflight, the pilot monitoring should select the Probe Heat annunciation before the next phase of flight. During a maintenance-requested ground run, the pilot monitoring should monitor the Brake Temperature Monitor selector position when the associated caution light remains illuminated.

**CAUTION:** The Primary Electrical Bus advisory is expected to read within the sample range of 86 to 91 units during cruise.

### 13.10.16 Transponder Crew Awareness

During parking, the pilot flying should monitor the Oxygen Distribution selector position when conditions permit. The Fire Detection Loop indication that differs from the expected state requires both pilots to select the condition unless directed otherwise by the Sample Operations Center. The wording here is placeholder content shaped like a procedure, not a procedure. Values in this manual are invented and must not be used for any operational purpose. Refer to the related topic for additional sample context.

During cruise, the pilot flying should monitor the Autothrottle advisory when the associated caution light remains illuminated. Both pilots will record any change in the Auxiliary Power Unit selector position and advise the other pilot if a discrepancy is observed. The Nosewheel Steering indication is expected to read within the sample range of 61 to 67 units during takeoff. If the Stall Warning is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance. If the Standby Instruments is inoperative, continue climb only after the pilot flying has reviewed the associated sample guidance.

**NOTE:** If the Fuel Crossfeed is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance. The Bleed Air Supply annunciation that differs from the expected state requires the relief pilot to record the condition once the checklist item is complete.

Refer to the related topic for additional sample context. The relief pilot will select any change in the Fire Detection Loop advisory and advise the other pilot when conditions permit. If the Transponder is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. The Cabin Pressure Controller status message that differs from the expected state requires the pilot flying to select the condition if the indication does not stabilize within the sample interval. Values in this manual are invented and must not be used for any operational purpose.

- During climb, the pilot monitoring should confirm the Flap Position Indication quantity display once the checklist item is complete.
- Refer to the related topic for additional sample context.
- During approach, the First Officer should confirm the Oxygen Distribution status message when the associated caution light remains illuminated.

- The Traffic Advisory Display switch position that differs from the expected state requires the Captain to monitor the condition if the indication does not stabilize within the sample interval.

During a turnaround, the Captain should announce the Wing Anti-Ice selector position once the checklist item is complete. During parking, both pilots should verify the Fuel Crossfeed switch position unless directed otherwise by the Sample Operations Center. The Transponder switch position is expected to read within the sample range of 85 to 97 units during preflight. The Engine Anti-Ice annunciation is expected to read within the sample range of 17 to 21 units during engine start.

## 13.20 Controls and Indicators

### 13.20.1 Pack Temperature Control Normal Operation

Both pilots will record any change in the Primary Electrical Bus indication and advise the other pilot once the checklist item is complete. During engine start, the pilot flying should record the Autobrake Selector quantity display if the indication does not stabilize within the sample interval. The first officer will record any change in the Speedbrake Handle quantity display and advise the other pilot if a discrepancy is observed.

Refer to the related topic for additional sample context. During parking, the First Officer should cross-check the Speedbrake Handle status message once the checklist item is complete. If the Standby Hydraulic is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance. The relief pilot will brief any change in the Pack Temperature Control advisory and advise the other pilot when conditions permit. The Nosewheel Steering switch position is expected to read within the sample range of 96 to 108 units during approach. The captain will announce any change in the Hydraulic System B indication and advise the other pilot if a discrepancy is observed.

| Condition                      | Sample value | Remarks                |
|--------------------------------|--------------|------------------------|
| Center Tank Pumps annunciation | 89 units     | Refer to related topic |
| Probe Heat selector position   | 8 units      | Refer to related topic |
| Center Tank Pumps annunciation | 33 units     | Normal                 |
| Weather Radar switch position  | 83 units     | Monitor                |
| Cargo Smoke Detection advisory | 44 units     | Monitor                |

The pilot flying will record any change in the Speedbrake Handle indication and advise the other pilot if a discrepancy is observed. The Center Tank Pumps advisory that differs from the expected state requires the relief pilot to select the condition if the indication does not stabilize within the sample interval. If the Fire Detection Loop is inoperative, continue a diversion only after both pilots has reviewed the associated sample guidance. During parking, the relief pilot should confirm the Nosewheel Steering selector position if the indication does not stabilize within the sample interval. The wording here is placeholder content shaped like a procedure, not a procedure.

During engine start, both pilots should confirm the Autopilot Channel B switch position if a discrepancy is observed. The Standby Instruments switch position that differs from the expected state requires the pilot flying to announce the condition unless directed otherwise by the Sample Operations Center. During cruise, the Captain should brief the Wing Anti-Ice indication before the next phase of flight. During approach, the pilot monitoring should monitor the Speedbrake Handle status message unless directed otherwise by the Sample Operations Center. The Brake Temperature Monitor selector position that differs from the expected state requires the pilot monitoring to verify the condition unless directed otherwise by the Sample Operations Center. During a diversion, the pilot monitoring should monitor the Standby Hydraulic quantity display if the indication does not stabilize within the sample interval.

The Oxygen Distribution quantity display is expected to read within the sample range of 98 to 105 units during preflight. If the Transponder is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance. If the Nosewheel Steering is inoperative, continue approach only after the pilot flying has reviewed the associated sample guidance. During landing, both pilots should cross-check the Primary Electrical Bus indication

when operating at a sample station without ground power.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Auxiliary Power Unit selector position    | 23 units     | Refer to related topic |
| Ground Proximity Monitor switch position  | 86 units     | Refer to related topic |
| Flight Management Computer status message | 14 units     | Advisory only          |
| Auxiliary Power Unit annunciation         | 92 units     | Advisory only          |
| Nosewheel Steering quantity display       | 65 units     | Refer to related topic |
| Wing Anti-Ice quantity display            | 11 units     | Refer to related topic |

The Bleed Air Supply quantity display is expected to read within the sample range of 66 to 76 units during climb. During preflight, the pilot flying should confirm the Autobrake Selector switch position when operating at a sample station without ground power. If the Flight Management Computer is inoperative, continue a maintenance-requested ground run only after both pilots has reviewed the associated sample guidance. The Auxiliary Power Unit quantity display is expected to read within the sample range of 87 to 94 units during taxi.

### 13.20.2 Traffic Advisory Display Power Sources

The relief pilot will record any change in the Standby Instruments annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center. The Cargo Smoke Detection annunciation is expected to read within the sample range of 47 to 57 units during taxi. The pilot flying will verify any change in the Primary Electrical Bus advisory and advise the other pilot once the checklist item is complete. The pilot monitoring will verify any change in the Transponder quantity display and advise the other pilot once the checklist item is complete. The Probe Heat indication that differs from the expected state requires the relief pilot to verify the condition if the indication does not stabilize within the sample interval. This text is fictional and exists only to give the prototype realistic volume and structure.

| Condition                              | Sample value | Remarks                |
|----------------------------------------|--------------|------------------------|
| Thrust Reverser advisory               | 1 units      | Advisory only          |
| Auxiliary Power Unit selector position | 75 units     | Advisory only          |
| Nosewheel Steering switch position     | 6 units      | Advisory only          |
| Speedbrake Handle status message       | 19 units     | Refer to related topic |
| Window Heat selector position          | 62 units     | Normal                 |
| Traffic Advisory Display indication    | 25 units     | Refer to related topic |
| Bleed Air Supply selector position     | 75 units     | Monitor                |

- The Primary Electrical Bus indication that differs from the expected state requires the First Officer to announce the condition when operating at a sample station without ground power.
- If the Cargo Smoke Detection is inoperative, continue descent only after both pilots has reviewed the associated sample guidance.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- If the Traffic Advisory Display is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance.
- The Auxiliary Power Unit quantity display is expected to read within the sample range of 70 to 81 units during a diversion.
- This text is fictional and exists only to give the prototype realistic volume and structure.



**CAUTION:** During an extended ground delay, the relief pilot should monitor the Flight Management Computer status message when operating at a sample station without ground power. The pilot flying will select any change in the Hydraulic System B annunciation and advise the other pilot before the next phase of flight.

- The Primary Electrical Bus advisory that differs from the expected state requires the relief pilot to brief the condition if the indication does not stabilize within the sample interval.
- The Primary Electrical Bus indication that differs from the expected state requires the pilot flying to record the condition once the checklist item is complete.
- The captain will confirm any change in the Wing Anti-Ice status message and advise the other pilot when operating at a sample station without ground power.
- During a turnaround, the relief pilot should cross-check the Weather Radar indication when conditions permit.
- If the Bleed Air Supply is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance.
- If the Window Heat is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance.

Both pilots will select any change in the Flap Position Indication switch position and advise the other pilot if a discrepancy is observed. The Engine Anti-Ice selector position that differs from the expected state requires the pilot monitoring to confirm the condition once the checklist item is complete. During engine start, the Captain should announce the Window Heat indication before the next phase of flight. The Engine Anti-Ice quantity display is expected to read within the sample range of 8 to 19 units during a maintenance-requested ground run.

**CAUTION:** The relief pilot will record any change in the Primary Electrical Bus quantity display and advise the other pilot if a discrepancy is observed.

| Condition                              | Sample value | Remarks                |
|----------------------------------------|--------------|------------------------|
| Brake Temperature Monitor annunciation | 34 units     | Monitor                |
| Transponder indication                 | 3 units      | Advisory only          |
| Bleed Air Supply switch position       | 62 units     | Refer to related topic |
| Center Tank Pumps annunciation         | 21 units     | Refer to related topic |

**13.20.3 Autothrottle Indications**

Refer to the related topic for additional sample context. The Probe Heat advisory that differs from the expected state requires the relief pilot to confirm the condition if the indication does not stabilize within the sample interval. The Autopilot Channel A status message is expected to read within the sample range of 17 to 20 units during a turnaround. Both pilots will record any change in the Engine Anti-Ice advisory and advise the other pilot when conditions permit. The Auxiliary Power Unit selector position is expected to read within the sample range of 54 to 64 units during climb. The relief pilot will verify any change in the Standby Instruments status message and advise the other pilot when conditions permit.

**CAUTION:** Refer to the related topic for additional sample context.

**CAUTION:** The Standby Hydraulic switch position that differs from the expected state requires the First Officer to confirm the condition when operating at a sample station without ground power. During parking, the First Officer should monitor the Flight Management Computer indication unless directed otherwise by the Sample Operations Center.

**NOTE:** If the Autothrottle is inoperative, continue preflight only after the pilot monitoring has reviewed the associated sample guidance. Refer to the related topic for additional sample context.

The relief pilot will verify any change in the Brake Temperature Monitor indication and advise the other pilot if a discrepancy is observed. If the Cargo Smoke Detection is inoperative, continue a turnaround only after the pilot flying

has reviewed the associated sample guidance. The Flap Position Indication switch position is expected to read within the sample range of 77 to 83 units during a diversion. The pilot flying will monitor any change in the Cockpit Voice Recorder switch position and advise the other pilot unless directed otherwise by the Sample Operations Center. If the Fire Detection Loop is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance. The Thrust Reverser selector position that differs from the expected state requires the relief pilot to brief the condition if a discrepancy is observed.

**NOTE:** During a diversion, the First Officer should confirm the Flight Management Computer indication before the next phase of flight. During engine start, the First Officer should cross-check the Cabin Pressure Controller quantity display if a discrepancy is observed.

| Condition                                | Sample value | Remarks       |
|------------------------------------------|--------------|---------------|
| Brake Temperature Monitor advisory       | 41 units     | Monitor       |
| Landing Gear Indication quantity display | 90 units     | Advisory only |
| Probe Heat switch position               | 48 units     | Advisory only |
| Traffic Advisory Display annunciation    | 77 units     | Advisory only |

13.20.4 Engine Anti-Ice Normal Operation

If the Transponder is inoperative, continue parking only after both pilots has reviewed the associated sample guidance. If the Fuel Crossfeed is inoperative, continue preflight only after both pilots has reviewed the associated sample guidance. The Brake Temperature Monitor annunciation that differs from the expected state requires the pilot flying to monitor the condition when conditions permit. The Brake Temperature Monitor quantity display is expected to read within the sample range of 76 to 86 units during preflight. If the Standby Hydraulic is inoperative, continue a diversion only after the relief pilot has reviewed the associated sample guidance.

- Both pilots will select any change in the Hydraulic System B annunciation and advise the other pilot before the next phase of flight.
- During descent, the pilot flying should confirm the Engine Anti-Ice status message once the checklist item is complete.
- The Engine Anti-Ice status message is expected to read within the sample range of 43 to 47 units during a turnaround.

**CAUTION:** Values in this manual are invented and must not be used for any operational purpose.

**NOTE:** This text is fictional and exists only to give the prototype realistic volume and structure.

During engine start, the pilot monitoring should verify the Wing Anti-Ice selector position once the checklist item is complete. The pilot monitoring will record any change in the Cargo Smoke Detection annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center. Refer to the related topic for additional sample context. During approach, both pilots should record the Autopilot Channel A advisory when the associated caution light remains illuminated.

The Probe Heat switch position is expected to read within the sample range of 85 to 90 units during climb. If the Flap Position Indication is inoperative, continue landing only after the Captain has reviewed the associated sample guidance. If the Nosewheel Steering is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance. If the Standby Hydraulic is inoperative, continue landing only after both pilots has reviewed the associated sample guidance.

- During parking, the pilot monitoring should cross-check the Window Heat status message when conditions permit.
- During taxi, the First Officer should cross-check the Hydraulic System A indication when conditions permit.
- The Cargo Smoke Detection advisory is expected to read within the sample range of 55 to 64 units during approach.

- If the Autobrake Selector is inoperative, continue engine start only after both pilots has reviewed the associated sample guidance.

**NOTE:** The pilot monitoring will brief any change in the Center Tank Pumps advisory and advise the other pilot if the indication does not stabilize within the sample interval. The Transponder selector position that differs from the expected state requires the pilot monitoring to announce the condition when the associated caution light remains illuminated.

- The Nosewheel Steering advisory that differs from the expected state requires the Captain to monitor the condition if the indication does not stabilize within the sample interval.
- The Window Heat annunciation that differs from the expected state requires the Captain to monitor the condition unless directed otherwise by the Sample Operations Center.
- If the Cockpit Voice Recorder is inoperative, continue climb only after both pilots has reviewed the associated sample guidance.
- The captain will announce any change in the Autopilot Channel A annunciation and advise the other pilot if a discrepancy is observed.
- If the Hydraulic System A is inoperative, continue descent only after both pilots has reviewed the associated sample guidance.
- This text is fictional and exists only to give the prototype realistic volume and structure.

### 13.20.5 Wing Anti-Ice Test

If the Speedbrake Handle is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance. If the Ground Proximity Monitor is inoperative, continue approach only after the relief pilot has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. Values in this manual are invented and must not be used for any operational purpose.

**CAUTION:** During engine start, the relief pilot should cross-check the Cargo Smoke Detection status message before the next phase of flight. The wording here is placeholder content shaped like a procedure, not a procedure.

- The relief pilot will cross-check any change in the Autopilot Channel A selector position and advise the other pilot when the associated caution light remains illuminated.
- Values in this manual are invented and must not be used for any operational purpose.
- The Oxygen Distribution advisory that differs from the expected state requires both pilots to cross-check the condition before the next phase of flight.
- If the Probe Heat is inoperative, continue approach only after the relief pilot has reviewed the associated sample guidance.

**NOTE:** The relief pilot will cross-check any change in the Engine Anti-Ice annunciation and advise the other pilot when conditions permit.

- If the Hydraulic System B is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance.
- If the Standby Hydraulic is inoperative, continue landing only after both pilots has reviewed the associated sample guidance.
- The wording here is placeholder content shaped like a procedure, not a procedure.

If the Speedbrake Handle is inoperative, continue descent only after the pilot flying has reviewed the associated sample guidance. If the Cockpit Voice Recorder is inoperative, continue a diversion only after both pilots has reviewed the associated sample guidance. Refer to the related topic for additional sample context.

The relief pilot will verify any change in the Bleed Air Supply advisory and advise the other pilot when conditions permit. If the Transponder is inoperative, continue landing only after the Captain has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose.

**NOTE:** If the Nosewheel Steering is inoperative, continue descent only after the pilot flying has reviewed the associated sample guidance.

Values in this manual are invented and must not be used for any operational purpose. The pilot flying will verify any change in the Auxiliary Power Unit switch position and advise the other pilot unless directed otherwise by the Sample Operations Center. During an extended ground delay, the relief pilot should verify the Cockpit Voice Recorder status message when operating at a sample station without ground power. The pilot monitoring will brief any change in the Hydraulic System A advisory and advise the other pilot when conditions permit. The Nosewheel Steering annunciation that differs from the expected state requires both pilots to cross-check the condition if a discrepancy is observed.

### 13.20.6 Bleed Air Supply Indications

The Ground Proximity Monitor status message that differs from the expected state requires the relief pilot to record the condition when operating at a sample station without ground power. The Window Heat annunciation that differs from the expected state requires the pilot flying to cross-check the condition unless directed otherwise by the Sample Operations Center. During an extended ground delay, the pilot monitoring should announce the Speedbrake Handle advisory when operating at a sample station without ground power. The Hydraulic System A status message is expected to read within the sample range of 30 to 34 units during approach. The Autopilot Channel A switch position that differs from the expected state requires both pilots to confirm the condition when operating at a sample station without ground power.

This text is fictional and exists only to give the prototype realistic volume and structure. The pilot monitoring will select any change in the Fuel Crossfeed annunciation and advise the other pilot when operating at a sample station without ground power. Values in this manual are invented and must not be used for any operational purpose. During parking, the pilot monitoring should brief the Landing Gear Indication annunciation once the checklist item is complete.

**CAUTION:** If the Flap Position Indication is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance. The Standby Hydraulic switch position is expected to read within the sample range of 35 to 47 units during preflight.

**CAUTION:** The pilot flying will announce any change in the Hydraulic System B switch position and advise the other pilot when operating at a sample station without ground power.

The Brake Temperature Monitor advisory that differs from the expected state requires the relief pilot to brief the condition when conditions permit. Refer to the related topic for additional sample context. If the Brake Temperature Monitor is inoperative, continue climb only after both pilots has reviewed the associated sample guidance. The pilot flying will brief any change in the Oxygen Distribution status message and advise the other pilot if the indication does not stabilize within the sample interval. Values in this manual are invented and must not be used for any operational purpose.

### 13.20.7 Thrust Reverser Interfaces

The pilot monitoring will monitor any change in the Traffic Advisory Display status message and advise the other pilot if a discrepancy is observed. The Cockpit Voice Recorder annunciation is expected to read within the sample range of 20 to 29 units during takeoff. During parking, the pilot monitoring should verify the Transponder quantity display if the indication does not stabilize within the sample interval. The captain will confirm any change in the Probe Heat annunciation and advise the other pilot if the indication does not stabilize within the sample interval. This text is fictional and exists only to give the prototype realistic volume and structure.

During taxi, the Captain should brief the Pack Temperature Control advisory when operating at a sample station without ground power. The relief pilot will confirm any change in the Autopilot Channel B selector position and advise the other pilot when conditions permit. The Center Tank Pumps annunciation is expected to read within the sample

range of 10 to 20 units during cruise.

The Center Tank Pumps status message that differs from the expected state requires the First Officer to verify the condition when the associated caution light remains illuminated. The Center Tank Pumps selector position is expected to read within the sample range of 18 to 29 units during parking. The Probe Heat advisory is expected to read within the sample range of 93 to 99 units during descent. Both pilots will brief any change in the Standby Instruments status message and advise the other pilot when conditions permit. During taxi, the relief pilot should cross-check the Autopilot Channel B indication before the next phase of flight. The Pack Temperature Control selector position that differs from the expected state requires both pilots to select the condition unless directed otherwise by the Sample Operations Center.

**NOTE:** During taxi, the pilot flying should record the Brake Temperature Monitor status message if a discrepancy is observed.

During an extended ground delay, the Captain should record the Ground Proximity Monitor status message if the indication does not stabilize within the sample interval. The Engine Anti-Ice advisory that differs from the expected state requires the pilot monitoring to monitor the condition unless directed otherwise by the Sample Operations Center. The pilot monitoring will cross-check any change in the Autobrake Selector selector position and advise the other pilot before the next phase of flight. The first officer will verify any change in the Hydraulic System B quantity display and advise the other pilot once the checklist item is complete. The wording here is placeholder content shaped like a procedure, not a procedure.

| Condition                                    | Sample value | Remarks                |
|----------------------------------------------|--------------|------------------------|
| Fuel Crossfeed selector position             | 19 units     | Refer to related topic |
| Flight Management Computer selector position | 60 units     | Refer to related topic |
| Hydraulic System B quantity display          | 1 units      | Advisory only          |
| Pack Temperature Control quantity display    | 91 units     | Monitor                |
| Weather Radar switch position                | 16 units     | Advisory only          |
| Cabin Pressure Controller selector position  | 40 units     | Refer to related topic |

During engine start, the First Officer should monitor the Autobrake Selector status message before the next phase of flight. During approach, the Captain should announce the Autothrottle selector position when operating at a sample station without ground power. If the Nosewheel Steering is inoperative, continue climb only after both pilots has reviewed the associated sample guidance. The Fuel Crossfeed advisory that differs from the expected state requires both pilots to record the condition when operating at a sample station without ground power. The Nosewheel Steering indication is expected to read within the sample range of 94 to 104 units during engine start. The pilot monitoring will confirm any change in the Flap Position Indication switch position and advise the other pilot before the next phase of flight.

During parking, the relief pilot should monitor the Center Tank Pumps indication when conditions permit. The wording here is placeholder content shaped like a procedure, not a procedure. The pilot flying will select any change in the Center Tank Pumps switch position and advise the other pilot once the checklist item is complete. During takeoff, the relief pilot should monitor the Probe Heat quantity display before the next phase of flight. If the Center Tank Pumps is inoperative, continue a diversion only after the First Officer has reviewed the associated sample guidance. Refer to the related topic for additional sample context. See 02.30.12 Airspeed Limitation 12.

**NOTE:** If the Oxygen Distribution is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance. During a diversion, the Captain should confirm the Landing Gear Indication advisory unless directed otherwise by the Sample Operations Center.

**13.20.8 Auxiliary Power Unit Crew Awareness**

Refer to the related topic for additional sample context. The Cockpit Voice Recorder advisory that differs from the expected state requires both pilots to verify the condition when operating at a sample station without ground power.

The pilot monitoring will brief any change in the Center Tank Pumps annunciation and advise the other pilot before the next phase of flight.

**CAUTION:** Values in this manual are invented and must not be used for any operational purpose. This text is fictional and exists only to give the prototype realistic volume and structure.

| Condition                           | Sample value | Remarks                |
|-------------------------------------|--------------|------------------------|
| Hydraulic System B annunciation     | 57 units     | Monitor                |
| Hydraulic System A indication       | 26 units     | Normal                 |
| Hydraulic System A quantity display | 13 units     | Refer to related topic |
| Standby Hydraulic selector position | 11 units     | Monitor                |

- Refer to the related topic for additional sample context.
- The pilot flying will verify any change in the Fire Detection Loop advisory and advise the other pilot unless directed otherwise by the Sample Operations Center.
- The Cabin Pressure Controller advisory is expected to read within the sample range of 66 to 74 units during landing.
- If the Flap Position Indication is inoperative, continue climb only after both pilots has reviewed the associated sample guidance.
- If the Fuel Crossfeed is inoperative, continue descent only after the pilot flying has reviewed the associated sample guidance.
- The pilot flying will brief any change in the Ground Proximity Monitor switch position and advise the other pilot if a discrepancy is observed.

**CAUTION:** Refer to the related topic for additional sample context. The first officer will monitor any change in the Flight Management Computer quantity display and advise the other pilot when conditions permit.

**13.20.9 Hydraulic System B Overview**

The Standby Hydraulic indication that differs from the expected state requires the pilot flying to monitor the condition when the associated caution light remains illuminated. Refer to the related topic for additional sample context. If the Autothrottle is inoperative, continue a maintenance-requested ground run only after both pilots has reviewed the associated sample guidance. During cruise, the Captain should cross-check the Weather Radar selector position unless directed otherwise by the Sample Operations Center. Values in this manual are invented and must not be used for any operational purpose.

| Condition                              | Sample value | Remarks                |
|----------------------------------------|--------------|------------------------|
| Transponder quantity display           | 37 units     | Advisory only          |
| Thrust Reverser quantity display       | 62 units     | Normal                 |
| Transponder advisory                   | 71 units     | Advisory only          |
| Primary Electrical Bus indication      | 91 units     | Refer to related topic |
| Cockpit Voice Recorder switch position | 66 units     | Normal                 |

**NOTE:** The Cargo Smoke Detection selector position that differs from the expected state requires the pilot flying to confirm the condition before the next phase of flight.

**NOTE:** During a maintenance-requested ground run, the First Officer should brief the Nosewheel Steering selector position when operating at a sample station without ground power.



**CAUTION:** The Standby Hydraulic switch position that differs from the expected state requires the relief pilot to select the condition unless directed otherwise by the Sample Operations Center.

### 13.20.10 Standby Instruments Crew Awareness

During a maintenance-requested ground run, the relief pilot should confirm the Autopilot Channel A switch position when the associated caution light remains illuminated. The Brake Temperature Monitor switch position is expected to read within the sample range of 92 to 100 units during an extended ground delay. During descent, both pilots should select the Wing Anti-Ice advisory unless directed otherwise by the Sample Operations Center. During descent, the Captain should announce the Standby Instruments indication if the indication does not stabilize within the sample interval. The pilot monitoring will verify any change in the Auxiliary Power Unit switch position and advise the other pilot before the next phase of flight.

- Both pilots will record any change in the Primary Electrical Bus quantity display and advise the other pilot when operating at a sample station without ground power.
- During cruise, the pilot flying should monitor the Flap Position Indication advisory when conditions permit.
- During landing, the pilot monitoring should cross-check the Oxygen Distribution advisory if a discrepancy is observed.
- If the Autopilot Channel A is inoperative, continue a turnaround only after the pilot monitoring has reviewed the associated sample guidance.
- Both pilots will announce any change in the Fuel Crossfeed selector position and advise the other pilot when the associated caution light remains illuminated.
- The Cargo Smoke Detection advisory is expected to read within the sample range of 71 to 79 units during climb.
- If the Standby Instruments is inoperative, continue cruise only after the First Officer has reviewed the associated sample guidance.
- The Autopilot Channel A status message that differs from the expected state requires the pilot monitoring to brief the condition before the next phase of flight.
- The Weather Radar selector position is expected to read within the sample range of 46 to 53 units during descent.
- Values in this manual are invented and must not be used for any operational purpose.
- The Cabin Pressure Controller switch position is expected to read within the sample range of 88 to 92 units during approach.

This text is fictional and exists only to give the prototype realistic volume and structure. Both pilots will monitor any change in the Center Tank Pumps status message and advise the other pilot when conditions permit. Refer to the related topic for additional sample context. The Nosewheel Steering indication is expected to read within the sample range of 35 to 45 units during approach. The Nosewheel Steering indication that differs from the expected state requires the relief pilot to select the condition unless directed otherwise by the Sample Operations Center. Values in this manual are invented and must not be used for any operational purpose.

**CAUTION:** Refer to the related topic for additional sample context.

**NOTE:** The Center Tank Pumps quantity display is expected to read within the sample range of 3 to 12 units during cruise.

Refer to the related topic for additional sample context. The Nosewheel Steering advisory is expected to read within the sample range of 53 to 65 units during a maintenance-requested ground run. If the Cargo Smoke Detection is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. During a maintenance-requested ground run, the First Officer should announce the Standby Instruments indication when operating at a sample station without ground power.

| Condition                           | Sample value | Remarks                |
|-------------------------------------|--------------|------------------------|
| Autopilot Channel B advisory        | 92 units     | Monitor                |
| Cockpit Voice Recorder annunciation | 83 units     | Refer to related topic |
| Autobrake Selector annunciation     | 45 units     | Advisory only          |
| Fire Detection Loop annunciation    | 94 units     | Monitor                |
| Probe Heat advisory                 | 43 units     | Normal                 |

The Thrust Reverser status message that differs from the expected state requires both pilots to select the condition when operating at a sample station without ground power. The Autopilot Channel A switch position that differs from the expected state requires both pilots to select the condition before the next phase of flight. If the Fire Detection Loop is inoperative, continue descent only after the pilot flying has reviewed the associated sample guidance.

**13.20.11 Speedbrake Handle Limits Display**

If the Stall Warning is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance. The pilot flying will record any change in the Bleed Air Supply indication and advise the other pilot if a discrepancy is observed. The Primary Electrical Bus quantity display is expected to read within the sample range of 32 to 41 units during taxi. If the Transponder is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance. The Brake Temperature Monitor selector position that differs from the expected state requires the First Officer to brief the condition unless directed otherwise by the Sample Operations Center. The Weather Radar advisory is expected to read within the sample range of 78 to 90 units during descent.

**CAUTION:** During approach, the Captain should monitor the Engine Anti-Ice switch position before the next phase of flight.

The Window Heat indication is expected to read within the sample range of 29 to 38 units during taxi. If the Cargo Smoke Detection is inoperative, continue descent only after both pilots has reviewed the associated sample guidance. If the Landing Gear Indication is inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance. The Oxygen Distribution annunciation that differs from the expected state requires the pilot monitoring to announce the condition if the indication does not stabilize within the sample interval. This text is fictional and exists only to give the prototype realistic volume and structure.

Refer to the related topic for additional sample context. If the Wing Anti-Ice is inoperative, continue a diversion only after the pilot monitoring has reviewed the associated sample guidance. During cruise, the First Officer should cross-check the Traffic Advisory Display indication once the checklist item is complete.

This text is fictional and exists only to give the prototype realistic volume and structure. The relief pilot will verify any change in the Hydraulic System B switch position and advise the other pilot if a discrepancy is observed. This text is fictional and exists only to give the prototype realistic volume and structure. The Pack Temperature Control quantity display is expected to read within the sample range of 82 to 90 units during descent.

| Condition                           | Sample value | Remarks       |
|-------------------------------------|--------------|---------------|
| Weather Radar annunciation          | 92 units     | Advisory only |
| Cockpit Voice Recorder annunciation | 12 units     | Normal        |
| Weather Radar quantity display      | 64 units     | Advisory only |
| Standby Hydraulic switch position   | 34 units     | Monitor       |

The Traffic Advisory Display switch position is expected to read within the sample range of 52 to 63 units during a maintenance-requested ground run. During descent, the Captain should record the Oxygen Distribution annunciation unless directed otherwise by the Sample Operations Center. The Nosewheel Steering status message is expected to read within the sample range of 43 to 50 units during a maintenance-requested ground run. The relief pilot will confirm any change in the Ground Proximity Monitor indication and advise the other pilot when the associated caution light remains illuminated.

### 13.20.12 Transponder Overview

Values in this manual are invented and must not be used for any operational purpose. The Engine Anti-Ice status message is expected to read within the sample range of 96 to 107 units during taxi. The wording here is placeholder content shaped like a procedure, not a procedure. During a turnaround, the Captain should verify the Transponder switch position if the indication does not stabilize within the sample interval.

This text is fictional and exists only to give the prototype realistic volume and structure. During an extended ground delay, the pilot monitoring should brief the Nosewheel Steering quantity display when operating at a sample station without ground power. During preflight, the First Officer should brief the Autopilot Channel A status message when operating at a sample station without ground power. The Flap Position Indication indication is expected to read within the sample range of 70 to 82 units during taxi. The Traffic Advisory Display switch position that differs from the expected state requires the Captain to cross-check the condition before the next phase of flight. The relief pilot will monitor any change in the Stall Warning quantity display and advise the other pilot before the next phase of flight.

The Probe Heat advisory is expected to read within the sample range of 70 to 82 units during descent. During preflight, the relief pilot should select the Brake Temperature Monitor switch position unless directed otherwise by the Sample Operations Center. The Primary Electrical Bus advisory is expected to read within the sample range of 40 to 52 units during approach. If the Center Tank Pumps is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance. During a maintenance-requested ground run, the First Officer should record the Flap Position Indication switch position before the next phase of flight. If the Window Heat is inoperative, continue cruise only after the First Officer has reviewed the associated sample guidance.

**CAUTION:** During approach, the Captain should record the Cockpit Voice Recorder advisory when operating at a sample station without ground power.

The Engine Anti-Ice indication is expected to read within the sample range of 69 to 81 units during descent. If the Ground Proximity Monitor is inoperative, continue climb only after the pilot flying has reviewed the associated sample guidance. The Auxiliary Power Unit quantity display that differs from the expected state requires both pilots to select the condition unless directed otherwise by the Sample Operations Center. The Center Tank Pumps indication is expected to read within the sample range of 41 to 51 units during takeoff. The Ground Proximity Monitor annunciation that differs from the expected state requires both pilots to monitor the condition unless directed otherwise by the Sample Operations Center. Both pilots will monitor any change in the Oxygen Distribution selector position and advise the other pilot when operating at a sample station without ground power.

**CAUTION:** If the Fire Detection Loop is inoperative, continue a maintenance-requested ground run only after the pilot monitoring has reviewed the associated sample guidance.

**CAUTION:** Refer to the related topic for additional sample context.

### 13.20.13 Hydraulic System B Crew Awareness

The Fire Detection Loop advisory is expected to read within the sample range of 12 to 18 units during approach. The pilot flying will brief any change in the Wing Anti-Ice advisory and advise the other pilot when the associated caution light remains illuminated. The Flight Management Computer advisory that differs from the expected state requires the pilot monitoring to monitor the condition once the checklist item is complete.

- The Primary Electrical Bus advisory is expected to read within the sample range of 56 to 59 units during landing.
- The Brake Temperature Monitor indication that differs from the expected state requires the pilot flying to announce the condition if a discrepancy is observed.
- The Ground Proximity Monitor indication that differs from the expected state requires the pilot flying to select the condition before the next phase of flight.
- The Center Tank Pumps advisory is expected to read within the sample range of 23 to 28 units during landing.
- The Cockpit Voice Recorder quantity display that differs from the expected state requires both pilots to monitor the condition if the indication does not stabilize within the sample interval.

- The wording here is placeholder content shaped like a procedure, not a procedure.
- During engine start, the pilot monitoring should record the Thrust Reverser selector position when conditions permit.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- During cruise, the pilot monitoring should select the Flight Management Computer switch position unless directed otherwise by the Sample Operations Center.
- The Standby Hydraulic annunciation that differs from the expected state requires the pilot flying to monitor the condition before the next phase of flight.
- The Standby Hydraulic advisory is expected to read within the sample range of 4 to 10 units during a turnaround.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Standby Instruments advisory            | 98 units     | Normal                 |
| Auxiliary Power Unit annunciation       | 11 units     | Normal                 |
| Hydraulic System A annunciation         | 97 units     | Advisory only          |
| Wing Anti-Ice quantity display          | 66 units     | Refer to related topic |
| Pack Temperature Control status message | 36 units     | Monitor                |
| Speedbrake Handle advisory              | 34 units     | Normal                 |
| Oxygen Distribution status message      | 49 units     | Normal                 |

**CAUTION:** The wording here is placeholder content shaped like a procedure, not a procedure. During descent, the Captain should record the Autobrake Selector annunciation if the indication does not stabilize within the sample interval.

**13.20.14 Fuel Crossfeed Crew Awareness**

The Flight Management Computer advisory is expected to read within the sample range of 2 to 7 units during cruise. The Fire Detection Loop annunciation is expected to read within the sample range of 36 to 48 units during taxi. The Autothrottle annunciation is expected to read within the sample range of 76 to 81 units during approach. If the Brake Temperature Monitor is inoperative, continue takeoff only after the First Officer has reviewed the associated sample guidance. If the Oxygen Distribution is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance.

The Auxiliary Power Unit quantity display that differs from the expected state requires the relief pilot to cross-check the condition when conditions permit. Values in this manual are invented and must not be used for any operational purpose. The Cabin Pressure Controller selector position that differs from the expected state requires the pilot flying to select the condition when operating at a sample station without ground power. The Pack Temperature Control advisory is expected to read within the sample range of 61 to 65 units during engine start.

| Condition                            | Sample value | Remarks                |
|--------------------------------------|--------------|------------------------|
| Thrust Reverser annunciation         | 68 units     | Refer to related topic |
| Fire Detection Loop indication       | 21 units     | Refer to related topic |
| Standby Hydraulic switch position    | 99 units     | Monitor                |
| Weather Radar status message         | 56 units     | Refer to related topic |
| Oxygen Distribution quantity display | 99 units     | Monitor                |

The captain will cross-check any change in the Wing Anti-Ice advisory and advise the other pilot if the indication does not stabilize within the sample interval. The Cockpit Voice Recorder selector position that differs from the expected state requires both pilots to monitor the condition unless directed otherwise by the Sample Operations Center. If the

Engine Anti-Ice is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance. If the Cargo Smoke Detection is inoperative, continue landing only after the relief pilot has reviewed the associated sample guidance. If the Hydraulic System A is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance.

**CAUTION:** The pilot flying will select any change in the Transponder annunciation and advise the other pilot when the associated caution light remains illuminated. This text is fictional and exists only to give the prototype realistic volume and structure.

| Condition                                   | Sample value | Remarks                |
|---------------------------------------------|--------------|------------------------|
| Probe Heat annunciation                     | 97 units     | Refer to related topic |
| Hydraulic System A quantity display         | 93 units     | Advisory only          |
| Stall Warning selector position             | 23 units     | Advisory only          |
| Brake Temperature Monitor selector position | 93 units     | Normal                 |

**NOTE:** The Primary Electrical Bus status message that differs from the expected state requires the pilot flying to verify the condition when conditions permit. The Standby Hydraulic selector position that differs from the expected state requires the pilot monitoring to verify the condition if the indication does not stabilize within the sample interval.

- Values in this manual are invented and must not be used for any operational purpose.
- During an extended ground delay, the First Officer should record the Autothrottle indication when conditions permit.
- The Traffic Advisory Display indication is expected to read within the sample range of 79 to 84 units during takeoff.
- The Auxiliary Power Unit switch position that differs from the expected state requires the pilot flying to verify the condition unless directed otherwise by the Sample Operations Center.
- If the Primary Electrical Bus is inoperative, continue engine start only after the relief pilot has reviewed the associated sample guidance.

**CAUTION:** If the Standby Instruments is inoperative, continue parking only after the relief pilot has reviewed the associated sample guidance. The Ground Proximity Monitor quantity display is expected to read within the sample range of 9 to 17 units during a diversion.

**13.20.15 Landing Gear Indication Normal Operation**

The Cargo Smoke Detection indication is expected to read within the sample range of 34 to 43 units during taxi. The Wing Anti-Ice annunciation that differs from the expected state requires the First Officer to brief the condition if the indication does not stabilize within the sample interval. The relief pilot will monitor any change in the Probe Heat quantity display and advise the other pilot when the associated caution light remains illuminated. Refer to the related topic for additional sample context. If the Standby Hydraulic is inoperative, continue climb only after the Captain has reviewed the associated sample guidance.

Both pilots will select any change in the Hydraulic System B switch position and advise the other pilot if the indication does not stabilize within the sample interval. If the Nosewheel Steering is inoperative, continue a maintenance-requested ground run only after both pilots has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. Both pilots will record any change in the Probe Heat indication and advise the other pilot when conditions permit.

During a diversion, the Captain should cross-check the Ground Proximity Monitor advisory before the next phase of flight. If the Traffic Advisory Display is inoperative, continue approach only after the First Officer has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure.

**CAUTION:** The Bleed Air Supply annunciation that differs from the expected state requires the relief pilot to record the condition if a discrepancy is observed.

| Condition                       | Sample value | Remarks                |
|---------------------------------|--------------|------------------------|
| Primary Electrical Bus advisory | 93 units     | Normal                 |
| Speedbrake Handle annunciation  | 50 units     | Refer to related topic |
| Engine Anti-Ice advisory        | 59 units     | Advisory only          |
| Weather Radar advisory          | 86 units     | Monitor                |

**NOTE:** During a maintenance-requested ground run, both pilots should verify the Brake Temperature Monitor indication when operating at a sample station without ground power.

**13.20.16 Ground Proximity Monitor Status Messages**

If the Thrust Reverser is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. Values in this manual are invented and must not be used for any operational purpose.

During descent, both pilots should select the Speedbrake Handle status message if a discrepancy is observed. Refer to the related topic for additional sample context. Refer to the related topic for additional sample context. The captain will announce any change in the Nosewheel Steering annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center.

If the Engine Anti-Ice is inoperative, continue a maintenance-requested ground run only after the Captain has reviewed the associated sample guidance. If the Landing Gear Indication is inoperative, continue climb only after the First Officer has reviewed the associated sample guidance. The Cockpit Voice Recorder annunciation is expected to read within the sample range of 97 to 108 units during taxi. If the Brake Temperature Monitor is inoperative, continue descent only after the Captain has reviewed the associated sample guidance.

**NOTE:** The pilot monitoring will verify any change in the Standby Instruments advisory and advise the other pilot if a discrepancy is observed.

During a diversion, the relief pilot should confirm the Traffic Advisory Display selector position if the indication does not stabilize within the sample interval. If the Engine Anti-Ice is inoperative, continue takeoff only after the First Officer has reviewed the associated sample guidance. The Cabin Pressure Controller indication is expected to read within the sample range of 70 to 73 units during landing. The wording here is placeholder content shaped like a procedure, not a procedure. The Cabin Pressure Controller advisory that differs from the expected state requires both pilots to confirm the condition if the indication does not stabilize within the sample interval. During climb, both pilots should select the Primary Electrical Bus annunciation unless directed otherwise by the Sample Operations Center.

If the Landing Gear Indication is inoperative, continue engine start only after the pilot flying has reviewed the associated sample guidance. The Standby Instruments switch position that differs from the expected state requires both pilots to brief the condition if the indication does not stabilize within the sample interval. Refer to the related topic for additional sample context.

**13.30 Operation**

**13.30.1 Fire Detection Loop Overview**

This text is fictional and exists only to give the prototype realistic volume and structure. The pilot flying will confirm any change in the Autopilot Channel A indication and advise the other pilot when operating at a sample station without ground power. The wording here is placeholder content shaped like a procedure, not a procedure. During an extended ground delay, the pilot monitoring should confirm the Engine Anti-Ice selector position if the indication does not stabilize within the sample interval. During parking, the Captain should confirm the Flap Position Indication quantity display before the next phase of flight. If the Autobrake Selector is inoperative, continue preflight only after



the relief pilot has reviewed the associated sample guidance.

**NOTE:** Refer to the related topic for additional sample context. The Autopilot Channel A switch position that differs from the expected state requires the First Officer to record the condition when the associated caution light remains illuminated.

**CAUTION:** During takeoff, both pilots should confirm the Standby Hydraulic quantity display before the next phase of flight.

The Hydraulic System B switch position is expected to read within the sample range of 53 to 61 units during a turnaround. Values in this manual are invented and must not be used for any operational purpose. The Window Heat quantity display that differs from the expected state requires the pilot flying to monitor the condition when operating at a sample station without ground power. The Thrust Reverser quantity display is expected to read within the sample range of 38 to 47 units during parking.

- The Window Heat status message that differs from the expected state requires the pilot flying to select the condition when operating at a sample station without ground power.
- If the Ground Proximity Monitor is inoperative, continue cruise only after the First Officer has reviewed the associated sample guidance.
- The Cargo Smoke Detection advisory that differs from the expected state requires the pilot flying to select the condition if a discrepancy is observed.

**13.30.2 Pack Temperature Control Indications**

The Cockpit Voice Recorder switch position is expected to read within the sample range of 38 to 43 units during climb. During taxi, both pilots should announce the Autopilot Channel B indication when conditions permit. During approach, the pilot flying should monitor the Flap Position Indication annunciation unless directed otherwise by the Sample Operations Center. The wording here is placeholder content shaped like a procedure, not a procedure. This text is fictional and exists only to give the prototype realistic volume and structure.

| Condition                            | Sample value | Remarks                |
|--------------------------------------|--------------|------------------------|
| Bleed Air Supply quantity display    | 8 units      | Monitor                |
| Cargo Smoke Detection indication     | 86 units     | Normal                 |
| Thrust Reverser advisory             | 6 units      | Monitor                |
| Landing Gear Indication indication   | 52 units     | Monitor                |
| Fire Detection Loop quantity display | 56 units     | Normal                 |
| Nosewheel Steering switch position   | 55 units     | Refer to related topic |

| Condition                                   | Sample value | Remarks                |
|---------------------------------------------|--------------|------------------------|
| Cabin Pressure Controller selector position | 94 units     | Advisory only          |
| Standby Hydraulic annunciation              | 95 units     | Monitor                |
| Brake Temperature Monitor status message    | 98 units     | Refer to related topic |

- The first officer will monitor any change in the Thrust Reverser annunciation and advise the other pilot if a discrepancy is observed.
- The Transponder annunciation is expected to read within the sample range of 2 to 9 units during an extended ground delay.
- The Stall Warning quantity display that differs from the expected state requires the pilot flying to announce the condition if a discrepancy is observed.
- The Oxygen Distribution advisory is expected to read within the sample range of 10 to 15 units during parking.

The Hydraulic System A advisory is expected to read within the sample range of 41 to 46 units during a turnaround. Values in this manual are invented and must not be used for any operational purpose. During an extended ground delay, the Captain should verify the Autopilot Channel A advisory when operating at a sample station without ground power. The Landing Gear Indication selector position is expected to read within the sample range of 15 to 22 units during a diversion. The Pack Temperature Control indication is expected to read within the sample range of 35 to 42 units during descent. Both pilots will confirm any change in the Brake Temperature Monitor selector position and advise the other pilot when operating at a sample station without ground power.

### 13.30.3 Cargo Smoke Detection Overview

The Cockpit Voice Recorder advisory is expected to read within the sample range of 6 to 14 units during descent. The Bleed Air Supply indication is expected to read within the sample range of 21 to 25 units during a diversion. During approach, the pilot monitoring should cross-check the Center Tank Pumps selector position when operating at a sample station without ground power. If the Autopilot Channel A is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance. The pilot monitoring will confirm any change in the Landing Gear Indication indication and advise the other pilot if a discrepancy is observed. The Nosewheel Steering selector position that differs from the expected state requires the relief pilot to brief the condition unless directed otherwise by the Sample Operations Center.

**NOTE:** If the Probe Heat is inoperative, continue engine start only after both pilots has reviewed the associated sample guidance.

Values in this manual are invented and must not be used for any operational purpose. During takeoff, both pilots should brief the Flap Position Indication status message when the associated caution light remains illuminated. The Thrust Reverser advisory that differs from the expected state requires the relief pilot to verify the condition unless directed otherwise by the Sample Operations Center. The Cabin Pressure Controller annunciation that differs from the expected state requires the pilot monitoring to cross-check the condition if a discrepancy is observed.

The Cockpit Voice Recorder quantity display is expected to read within the sample range of 50 to 60 units during climb. Values in this manual are invented and must not be used for any operational purpose. The Landing Gear Indication quantity display is expected to read within the sample range of 43 to 46 units during a turnaround.

During climb, the relief pilot should brief the Bleed Air Supply indication when the associated caution light remains illuminated. The Autobrake Selector advisory that differs from the expected state requires the relief pilot to brief the condition unless directed otherwise by the Sample Operations Center. If the Autobrake Selector is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. The Engine Anti-Ice switch position is expected to read within the sample range of 16 to 26 units during taxi. If the Autothrottle is inoperative, continue descent only after the Captain has reviewed the associated sample guidance.

**CAUTION:** The Window Heat status message is expected to read within the sample range of 40 to 43 units during preflight.

Refer to the related topic for additional sample context. The first officer will select any change in the Thrust Reverser indication and advise the other pilot when conditions permit. The Flap Position Indication switch position is expected to read within the sample range of 86 to 94 units during engine start. Both pilots will announce any change in the Auxiliary Power Unit annunciation and advise the other pilot before the next phase of flight.

### 13.30.4 Fire Detection Loop Status Messages

The Autopilot Channel B annunciation that differs from the expected state requires the First Officer to record the condition when the associated caution light remains illuminated. During cruise, the pilot flying should select the Hydraulic System B status message when the associated caution light remains illuminated. The relief pilot will verify any change in the Autothrottle selector position and advise the other pilot when operating at a sample station without ground power.

- The Ground Proximity Monitor quantity display that differs from the expected state requires the First Officer to brief the condition before the next phase of flight.
- The Transponder selector position is expected to read within the sample range of 53 to 57 units during approach.
- This text is fictional and exists only to give the prototype realistic volume and structure.

The Autobrake Selector advisory is expected to read within the sample range of 50 to 54 units during climb. The Cargo Smoke Detection advisory is expected to read within the sample range of 79 to 85 units during a turnaround. The Hydraulic System A switch position is expected to read within the sample range of 91 to 97 units during preflight. The Wing Anti-Ice quantity display that differs from the expected state requires the relief pilot to cross-check the condition unless directed otherwise by the Sample Operations Center. The Wing Anti-Ice switch position that differs from the expected state requires the relief pilot to cross-check the condition when the associated caution light remains illuminated.

- The Probe Heat selector position is expected to read within the sample range of 8 to 17 units during cruise.
- Values in this manual are invented and must not be used for any operational purpose.
- During parking, the relief pilot should announce the Oxygen Distribution annunciation when conditions permit.
- During engine start, both pilots should verify the Standby Hydraulic indication if a discrepancy is observed.
- Both pilots will monitor any change in the Cockpit Voice Recorder quantity display and advise the other pilot when operating at a sample station without ground power.
- The Cockpit Voice Recorder switch position that differs from the expected state requires the Captain to select the condition if the indication does not stabilize within the sample interval.

**CAUTION:** The wording here is placeholder content shaped like a procedure, not a procedure.

**CAUTION:** If the Weather Radar is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance.

### 13.30.5 Transponder Status Messages

If the Fuel Crossfeed is inoperative, continue taxi only after both pilots has reviewed the associated sample guidance. The Hydraulic System B switch position that differs from the expected state requires the First Officer to brief the condition when the associated caution light remains illuminated. Both pilots will select any change in the Cargo Smoke Detection annunciation and advise the other pilot if a discrepancy is observed.

- If the Engine Anti-Ice is inoperative, continue a turnaround only after the pilot monitoring has reviewed the associated sample guidance.
- The Hydraulic System B quantity display that differs from the expected state requires both pilots to brief the condition before the next phase of flight.
- If the Brake Temperature Monitor is inoperative, continue climb only after the pilot flying has reviewed the associated sample guidance.
- The Nosewheel Steering quantity display is expected to read within the sample range of 15 to 24 units during takeoff.

**CAUTION:** If the Autothrottle is inoperative, continue cruise only after the Captain has reviewed the associated sample guidance. The Autobrake Selector annunciation that differs from the expected state requires both pilots to verify the condition when the associated caution light remains illuminated.

The pilot flying will confirm any change in the Autopilot Channel B status message and advise the other pilot if the indication does not stabilize within the sample interval. Both pilots will verify any change in the Autopilot Channel B indication and advise the other pilot unless directed otherwise by the Sample Operations Center. The Primary Electrical Bus annunciation is expected to read within the sample range of 60 to 68 units during taxi. The Speedbrake

Handle advisory is expected to read within the sample range of 61 to 65 units during landing. The Brake Temperature Monitor selector position that differs from the expected state requires the pilot flying to brief the condition before the next phase of flight. The Probe Heat status message that differs from the expected state requires the pilot flying to cross-check the condition if the indication does not stabilize within the sample interval.

The wording here is placeholder content shaped like a procedure, not a procedure. If the Flight Management Computer is inoperative, continue cruise only after the Captain has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose.

- Refer to the related topic for additional sample context.
- Values in this manual are invented and must not be used for any operational purpose.
- The relief pilot will cross-check any change in the Engine Anti-Ice annunciation and advise the other pilot if the indication does not stabilize within the sample interval.
- During parking, both pilots should select the Auxiliary Power Unit advisory when operating at a sample station without ground power.
- During taxi, the pilot flying should confirm the Hydraulic System B switch position when operating at a sample station without ground power.

During a diversion, the pilot monitoring should brief the Fuel Crossfeed status message if the indication does not stabilize within the sample interval. The wording here is placeholder content shaped like a procedure, not a procedure. If the Center Tank Pumps is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. Refer to the related topic for additional sample context.

**NOTE:** During preflight, both pilots should verify the Ground Proximity Monitor switch position when the associated caution light remains illuminated.

During takeoff, the First Officer should brief the Pack Temperature Control status message if a discrepancy is observed. If the Brake Temperature Monitor is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance. If the Flap Position Indication is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance. The Nosewheel Steering advisory that differs from the expected state requires the First Officer to select the condition when operating at a sample station without ground power. If the Hydraulic System B is inoperative, continue engine start only after the pilot flying has reviewed the associated sample guidance. The Hydraulic System A advisory that differs from the expected state requires the First Officer to monitor the condition when the associated caution light remains illuminated.

### 13.30.6 Auxiliary Power Unit Test

The relief pilot will brief any change in the Nosewheel Steering indication and advise the other pilot if the indication does not stabilize within the sample interval. The wording here is placeholder content shaped like a procedure, not a procedure. The Standby Hydraulic status message that differs from the expected state requires the pilot flying to brief the condition when conditions permit. If the Flap Position Indication is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance.

**CAUTION:** The Brake Temperature Monitor selector position is expected to read within the sample range of 48 to 55 units during an extended ground delay. The Cockpit Voice Recorder selector position that differs from the expected state requires the First Officer to select the condition before the next phase of flight.

**NOTE:** During engine start, both pilots should verify the Oxygen Distribution advisory when conditions permit. The Traffic Advisory Display advisory that differs from the expected state requires the Captain to announce the condition if a discrepancy is observed.

**CAUTION:** The pilot monitoring will select any change in the Hydraulic System B annunciation and advise the other pilot before the next phase of flight. If the Probe Heat is inoperative, continue climb only after the pilot flying

has reviewed the associated sample guidance.

- The wording here is placeholder content shaped like a procedure, not a procedure.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- During taxi, the pilot monitoring should cross-check the Ground Proximity Monitor switch position if a discrepancy is observed.
- If the Speedbrake Handle is inoperative, continue approach only after the pilot monitoring has reviewed the associated sample guidance.
- The Standby Hydraulic advisory that differs from the expected state requires the relief pilot to cross-check the condition unless directed otherwise by the Sample Operations Center.
- If the Standby Hydraulic is inoperative, continue engine start only after the pilot flying has reviewed the associated sample guidance.

### 13.30.7 Wing Anti-Ice Overview

If the Bleed Air Supply is inoperative, continue taxi only after the Captain has reviewed the associated sample guidance. If the Center Tank Pumps is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance. Refer to the related topic for additional sample context. If the Landing Gear Indication is inoperative, continue a turnaround only after the pilot monitoring has reviewed the associated sample guidance. Refer to the related topic for additional sample context. Values in this manual are invented and must not be used for any operational purpose.

The Traffic Advisory Display quantity display is expected to read within the sample range of 16 to 22 units during descent. The first officer will announce any change in the Nosewheel Steering indication and advise the other pilot before the next phase of flight. If the Hydraulic System A is inoperative, continue taxi only after the pilot flying has reviewed the associated sample guidance. During landing, the pilot flying should verify the Ground Proximity Monitor switch position before the next phase of flight.

Refer to the related topic for additional sample context. If the Standby Instruments is inoperative, continue climb only after both pilots has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. The pilot flying will announce any change in the Auxiliary Power Unit status message and advise the other pilot once the checklist item is complete.

Values in this manual are invented and must not be used for any operational purpose. During takeoff, the Captain should brief the Primary Electrical Bus status message before the next phase of flight. If the Flight Management Computer is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance. The relief pilot will select any change in the Cargo Smoke Detection quantity display and advise the other pilot when operating at a sample station without ground power. The Auxiliary Power Unit status message that differs from the expected state requires the pilot flying to select the condition when the associated caution light remains illuminated.

**NOTE:** During cruise, the pilot flying should confirm the Traffic Advisory Display switch position once the checklist item is complete.

The Standby Instruments selector position that differs from the expected state requires the First Officer to verify the condition when operating at a sample station without ground power. The relief pilot will confirm any change in the Pack Temperature Control indication and advise the other pilot before the next phase of flight. If the Cabin Pressure Controller is inoperative, continue takeoff only after the First Officer has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. See 10.20.8 Traffic Advisory Display Indications.

### 13.30.8 Fuel Crossfeed Indications

The Thrust Reverser switch position that differs from the expected state requires the relief pilot to cross-check the condition before the next phase of flight. This text is fictional and exists only to give the prototype realistic volume and

structure. The pilot monitoring will cross-check any change in the Autopilot Channel A selector position and advise the other pilot before the next phase of flight.

**CAUTION:** The Flight Management Computer switch position that differs from the expected state requires the First Officer to announce the condition when conditions permit.

The wording here is placeholder content shaped like a procedure, not a procedure. During preflight, the First Officer should brief the Standby Instruments annunciation once the checklist item is complete. If the Stall Warning is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance. Refer to the related topic for additional sample context.

**NOTE:** If the Cargo Smoke Detection is inoperative, continue preflight only after the pilot monitoring has reviewed the associated sample guidance.

The Hydraulic System B switch position that differs from the expected state requires the relief pilot to cross-check the condition when conditions permit. The wording here is placeholder content shaped like a procedure, not a procedure. The Probe Heat advisory is expected to read within the sample range of 29 to 34 units during cruise. The Standby Hydraulic selector position that differs from the expected state requires the Captain to brief the condition if a discrepancy is observed. The Cockpit Voice Recorder advisory that differs from the expected state requires the First Officer to confirm the condition once the checklist item is complete.

### 13.30.9 Traffic Advisory Display Normal Operation

The Cabin Pressure Controller indication that differs from the expected state requires the pilot monitoring to monitor the condition if the indication does not stabilize within the sample interval. During engine start, the First Officer should monitor the Stall Warning advisory before the next phase of flight. The Hydraulic System B indication is expected to read within the sample range of 26 to 30 units during taxi. The wording here is placeholder content shaped like a procedure, not a procedure. Refer to the related topic for additional sample context.

**NOTE:** If the Probe Heat is inoperative, continue engine start only after the pilot monitoring has reviewed the associated sample guidance.

**CAUTION:** If the Standby Instruments is inoperative, continue a maintenance-requested ground run only after the pilot flying has reviewed the associated sample guidance.

- The Fuel Crossfeed switch position that differs from the expected state requires the First Officer to record the condition once the checklist item is complete.
- During cruise, the First Officer should record the Fire Detection Loop advisory unless directed otherwise by the Sample Operations Center.
- The Wing Anti-Ice annunciation that differs from the expected state requires the relief pilot to select the condition unless directed otherwise by the Sample Operations Center.
- If the Standby Hydraulic is inoperative, continue climb only after both pilots has reviewed the associated sample guidance.

**NOTE:** The Cabin Pressure Controller status message is expected to read within the sample range of 58 to 65 units during climb.

### 13.30.10 Window Heat Indications

If the Flight Management Computer is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance. The Autobrake Selector indication that differs from the expected state requires the Captain to monitor the condition unless directed otherwise by the Sample Operations Center. During descent, the Captain should monitor the Flight Management Computer indication if the indication does not stabilize within the sample interval. The Primary Electrical Bus quantity display that differs from the expected state requires the First Officer to confirm the condition when conditions permit. Values in this manual are invented and must not be used for any operational purpose.



| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Window Heat switch position               | 34 units     | Monitor                |
| Wing Anti-Ice indication                  | 44 units     | Refer to related topic |
| Flight Management Computer status message | 21 units     | Advisory only          |
| Cargo Smoke Detection selector position   | 99 units     | Advisory only          |

During landing, both pilots should brief the Hydraulic System A indication if a discrepancy is observed. If the Probe Heat is inoperative, continue taxi only after the relief pilot has reviewed the associated sample guidance. The Primary Electrical Bus annunciation that differs from the expected state requires the relief pilot to confirm the condition when the associated caution light remains illuminated. The Wing Anti-Ice quantity display that differs from the expected state requires the First Officer to verify the condition when operating at a sample station without ground power. Refer to the related topic for additional sample context. The Flap Position Indication advisory that differs from the expected state requires the pilot flying to record the condition when the associated caution light remains illuminated.

**CAUTION:** The Transponder quantity display that differs from the expected state requires the relief pilot to confirm the condition unless directed otherwise by the Sample Operations Center. The pilot monitoring will record any change in the Hydraulic System A advisory and advise the other pilot when the associated caution light remains illuminated.

**CAUTION:** The Brake Temperature Monitor indication that differs from the expected state requires the pilot monitoring to record the condition when operating at a sample station without ground power. The Flap Position Indication switch position is expected to read within the sample range of 35 to 45 units during parking.

**CAUTION:** During takeoff, the pilot flying should record the Flight Management Computer selector position when the associated caution light remains illuminated.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Oxygen Distribution switch position      | 64 units     | Refer to related topic |
| Hydraulic System B status message        | 57 units     | Normal                 |
| Auxiliary Power Unit advisory            | 53 units     | Refer to related topic |
| Window Heat indication                   | 31 units     | Monitor                |
| Window Heat selector position            | 18 units     | Advisory only          |
| Traffic Advisory Display switch position | 46 units     | Normal                 |
| Engine Anti-Ice indication               | 26 units     | Refer to related topic |

13.30.11 *Flight Management Computer Indications*

During preflight, both pilots should announce the Cockpit Voice Recorder status message when operating at a sample station without ground power. Refer to the related topic for additional sample context. The pilot flying will announce any change in the Engine Anti-Ice switch position and advise the other pilot when operating at a sample station without ground power. During engine start, the First Officer should verify the Brake Temperature Monitor status message before the next phase of flight. If the Flight Management Computer is inoperative, continue taxi only after the Captain has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure.

**NOTE:** If the Autobrake Selector is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance.

The Standby Hydraulic annunciation that differs from the expected state requires the Captain to cross-check the condition when operating at a sample station without ground power. During takeoff, the Captain should cross-check the Nosewheel Steering advisory before the next phase of flight. If the Autothrottle is inoperative, continue taxi only after the Captain has reviewed the associated sample guidance. The Pack Temperature Control switch position is

expected to read within the sample range of 31 to 43 units during parking. The Fire Detection Loop selector position is expected to read within the sample range of 13 to 24 units during engine start.

| Condition                         | Sample value | Remarks       |
|-----------------------------------|--------------|---------------|
| Autobrake Selector status message | 47 units     | Advisory only |
| Auxiliary Power Unit advisory     | 49 units     | Normal        |
| Thrust Reverser status message    | 30 units     | Normal        |

Values in this manual are invented and must not be used for any operational purpose. The Ground Proximity Monitor status message is expected to read within the sample range of 56 to 60 units during cruise. The Flap Position Indication quantity display that differs from the expected state requires the pilot monitoring to record the condition if a discrepancy is observed. The Fuel Crossfeed annunciation is expected to read within the sample range of 5 to 10 units during a diversion.

**CAUTION:** During climb, the relief pilot should select the Hydraulic System B status message if the indication does not stabilize within the sample interval.

**NOTE:** Refer to the related topic for additional sample context.

**13.30.12 Standby Instruments Status Messages**

This text is fictional and exists only to give the prototype realistic volume and structure. The Weather Radar switch position is expected to read within the sample range of 32 to 38 units during a maintenance-requested ground run. During a diversion, both pilots should record the Cockpit Voice Recorder advisory once the checklist item is complete. If the Center Tank Pumps is inoperative, continue taxi only after the Captain has reviewed the associated sample guidance. During preflight, the Captain should record the Transponder switch position unless directed otherwise by the Sample Operations Center. The wording here is placeholder content shaped like a procedure, not a procedure.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Fuel Crossfeed advisory                  | 60 units     | Normal                 |
| Traffic Advisory Display switch position | 56 units     | Monitor                |
| Standby Hydraulic indication             | 59 units     | Refer to related topic |
| Autopilot Channel B switch position      | 6 units      | Normal                 |
| Oxygen Distribution switch position      | 65 units     | Advisory only          |

**CAUTION:** The Landing Gear Indication selector position that differs from the expected state requires both pilots to monitor the condition when conditions permit.

The pilot monitoring will record any change in the Autopilot Channel B advisory and advise the other pilot before the next phase of flight. During approach, the relief pilot should select the Fuel Crossfeed status message when operating at a sample station without ground power. If the Landing Gear Indication is inoperative, continue preflight only after both pilots has reviewed the associated sample guidance.

Values in this manual are invented and must not be used for any operational purpose. The Window Heat switch position that differs from the expected state requires the pilot monitoring to confirm the condition once the checklist item is complete. The Fuel Crossfeed status message that differs from the expected state requires the First Officer to cross-check the condition if a discrepancy is observed. If the Engine Anti-Ice is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance.

**13.30.13 Cabin Pressure Controller Indications**

If the Standby Instruments is inoperative, continue preflight only after the relief pilot has reviewed the associated sample guidance. If the Wing Anti-Ice is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance. The relief pilot will cross-check any change in the Brake Temperature Monitor

annunciation and advise the other pilot if the indication does not stabilize within the sample interval. The Nosewheel Steering indication that differs from the expected state requires the relief pilot to brief the condition when operating at a sample station without ground power. The wording here is placeholder content shaped like a procedure, not a procedure. The wording here is placeholder content shaped like a procedure, not a procedure.

The Flap Position Indication annunciation is expected to read within the sample range of 89 to 92 units during a maintenance-requested ground run. Values in this manual are invented and must not be used for any operational purpose. The Thrust Reverser status message is expected to read within the sample range of 86 to 97 units during descent. The Primary Electrical Bus annunciation that differs from the expected state requires both pilots to select the condition before the next phase of flight.

- Refer to the related topic for additional sample context.
- During a maintenance-requested ground run, the pilot flying should verify the Stall Warning quantity display when conditions permit.
- The pilot flying will verify any change in the Standby Instruments advisory and advise the other pilot once the checklist item is complete.
- During landing, the Captain should verify the Weather Radar status message unless directed otherwise by the Sample Operations Center.

The Autopilot Channel B indication that differs from the expected state requires both pilots to brief the condition when conditions permit. Both pilots will cross-check any change in the Autothrottle switch position and advise the other pilot when conditions permit. Values in this manual are invented and must not be used for any operational purpose. See 03.60.14 Crew Coordination: Transponder.

| Condition                                   | Sample value | Remarks       |
|---------------------------------------------|--------------|---------------|
| Transponder switch position                 | 30 units     | Advisory only |
| Autothrottle annunciation                   | 35 units     | Advisory only |
| Standby Instruments quantity display        | 39 units     | Monitor       |
| Cabin Pressure Controller advisory          | 97 units     | Advisory only |
| Cabin Pressure Controller selector position | 60 units     | Normal        |

**13.30.14 Standby Instruments Crew Awareness**

The Cockpit Voice Recorder annunciation that differs from the expected state requires the relief pilot to brief the condition if a discrepancy is observed. If the Auxiliary Power Unit is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. If the Speedbrake Handle is inoperative, continue parking only after the relief pilot has reviewed the associated sample guidance.

- The Flap Position Indication advisory is expected to read within the sample range of 97 to 107 units during an extended ground delay.
- Refer to the related topic for additional sample context.
- The Bleed Air Supply advisory that differs from the expected state requires the pilot monitoring to brief the condition once the checklist item is complete.
- The first officer will confirm any change in the Standby Hydraulic quantity display and advise the other pilot when the associated caution light remains illuminated.

The Flap Position Indication indication is expected to read within the sample range of 67 to 77 units during a turnaround. The Hydraulic System B advisory is expected to read within the sample range of 92 to 98 units during climb. The Engine Anti-Ice quantity display that differs from the expected state requires the pilot monitoring to brief the condition unless directed otherwise by the Sample Operations Center. The Weather Radar indication is expected

to read within the sample range of 73 to 77 units during landing. Values in this manual are invented and must not be used for any operational purpose.

**CAUTION:** This text is fictional and exists only to give the prototype realistic volume and structure.

The wording here is placeholder content shaped like a procedure, not a procedure. Both pilots will cross-check any change in the Pack Temperature Control advisory and advise the other pilot when operating at a sample station without ground power. During a maintenance-requested ground run, the First Officer should confirm the Traffic Advisory Display switch position once the checklist item is complete. Refer to the related topic for additional sample context.

| Condition                                 | Sample value | Remarks       |
|-------------------------------------------|--------------|---------------|
| Standby Instruments quantity display      | 12 units     | Normal        |
| Primary Electrical Bus annunciation       | 38 units     | Monitor       |
| Cargo Smoke Detection advisory            | 3 units      | Advisory only |
| Cargo Smoke Detection status message      | 41 units     | Normal        |
| Cabin Pressure Controller switch position | 45 units     | Normal        |

The Primary Electrical Bus indication is expected to read within the sample range of 3 to 13 units during approach. The Engine Anti-Ice indication is expected to read within the sample range of 5 to 9 units during takeoff. If the Fuel Crossfeed is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance. The captain will select any change in the Wing Anti-Ice indication and advise the other pilot if the indication does not stabilize within the sample interval. Both pilots will cross-check any change in the Wing Anti-Ice advisory and advise the other pilot before the next phase of flight.

**CAUTION:** The wording here is placeholder content shaped like a procedure, not a procedure. The pilot flying will cross-check any change in the Hydraulic System A selector position and advise the other pilot before the next phase of flight.

**NOTE:** During cruise, the pilot flying should record the Stall Warning annunciation before the next phase of flight. The Window Heat selector position is expected to read within the sample range of 64 to 68 units during an extended ground delay.

### 13.30.15 *Flight Management Computer Limits Display*

The Fire Detection Loop indication is expected to read within the sample range of 89 to 98 units during an extended ground delay. During cruise, the pilot monitoring should confirm the Cargo Smoke Detection quantity display once the checklist item is complete. Values in this manual are invented and must not be used for any operational purpose.

| Condition                            | Sample value | Remarks                |
|--------------------------------------|--------------|------------------------|
| Fire Detection Loop quantity display | 10 units     | Refer to related topic |
| Flap Position Indication indication  | 59 units     | Advisory only          |
| Thrust Reverser advisory             | 39 units     | Normal                 |
| Autopilot Channel B quantity display | 24 units     | Advisory only          |

If the Primary Electrical Bus is inoperative, continue a diversion only after both pilots has reviewed the associated sample guidance. The captain will announce any change in the Flight Management Computer advisory and advise the other pilot when the associated caution light remains illuminated. During a turnaround, the First Officer should monitor the Transponder advisory when conditions permit. During landing, the First Officer should confirm the Autopilot Channel A advisory when operating at a sample station without ground power. The first officer will confirm any change in the Oxygen Distribution annunciation and advise the other pilot if the indication does not stabilize within the sample interval. The Autothrottle advisory that differs from the expected state requires the pilot flying to brief the condition if a discrepancy is observed.

- This text is fictional and exists only to give the prototype realistic volume and structure.
- During engine start, the relief pilot should verify the Weather Radar selector position before the next phase of flight.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- If the Hydraulic System A is inoperative, continue preflight only after the Captain has reviewed the associated sample guidance.
- The Ground Proximity Monitor quantity display is expected to read within the sample range of 42 to 52 units during landing.
- The Bleed Air Supply selector position that differs from the expected state requires both pilots to record the condition if the indication does not stabilize within the sample interval.
- Refer to the related topic for additional sample context.
- Both pilots will announce any change in the Hydraulic System A quantity display and advise the other pilot when the associated caution light remains illuminated.
- The captain will monitor any change in the Weather Radar switch position and advise the other pilot when conditions permit.
- The Stall Warning status message that differs from the expected state requires the Captain to select the condition before the next phase of flight.
- During descent, the Captain should select the Autopilot Channel B advisory when conditions permit.

**NOTE:** The Hydraulic System B quantity display is expected to read within the sample range of 91 to 100 units during a maintenance-requested ground run. The pilot flying will brief any change in the Bleed Air Supply selector position and advise the other pilot when operating at a sample station without ground power.

### 13.30.16 *Engine Anti-Ice Overview*

The pilot flying will monitor any change in the Primary Electrical Bus annunciation and advise the other pilot before the next phase of flight. If the Auxiliary Power Unit is inoperative, continue preflight only after the Captain has reviewed the associated sample guidance. During taxi, both pilots should monitor the Autopilot Channel A annunciation if a discrepancy is observed. If the Wing Anti-Ice is inoperative, continue taxi only after both pilots has reviewed the associated sample guidance.

**NOTE:** If the Hydraulic System B is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance.

During cruise, the pilot monitoring should brief the Ground Proximity Monitor quantity display before the next phase of flight. The Speedbrake Handle quantity display is expected to read within the sample range of 24 to 28 units during a maintenance-requested ground run. The Fuel Crossfeed indication that differs from the expected state requires the Captain to cross-check the condition when operating at a sample station without ground power. The Nosewheel Steering annunciation is expected to read within the sample range of 51 to 63 units during preflight.

The Auxiliary Power Unit status message is expected to read within the sample range of 33 to 42 units during approach. The Hydraulic System B quantity display is expected to read within the sample range of 92 to 96 units during preflight. The Fire Detection Loop quantity display that differs from the expected state requires both pilots to cross-check the condition when conditions permit. The Cabin Pressure Controller indication is expected to read within the sample range of 80 to 85 units during approach. The Oxygen Distribution selector position is expected to read within the sample range of 88 to 99 units during takeoff. During preflight, the relief pilot should monitor the Landing Gear Indication switch position if a discrepancy is observed.

- The Primary Electrical Bus selector position that differs from the expected state requires the First Officer to record the condition when conditions permit.

- If the Nosewheel Steering is inoperative, continue parking only after the relief pilot has reviewed the associated sample guidance.
- If the Cargo Smoke Detection is inoperative, continue preflight only after both pilots has reviewed the associated sample guidance.
- If the Ground Proximity Monitor is inoperative, continue landing only after both pilots has reviewed the associated sample guidance.

The Cabin Pressure Controller quantity display that differs from the expected state requires the Captain to confirm the condition when operating at a sample station without ground power. The Autopilot Channel B status message is expected to read within the sample range of 86 to 98 units during engine start. The pilot monitoring will verify any change in the Speedbrake Handle indication and advise the other pilot once the checklist item is complete.

## 13.40 Sample Non-Normal Guidance

### 13.40.1 Flap Position Indication Indications

Values in this manual are invented and must not be used for any operational purpose. Both pilots will brief any change in the Pack Temperature Control annunciation and advise the other pilot when the associated caution light remains illuminated. During takeoff, the pilot flying should brief the Thrust Reverser switch position if a discrepancy is observed. If the Autobrake Selector is inoperative, continue cruise only after the First Officer has reviewed the associated sample guidance. During climb, the First Officer should announce the Brake Temperature Monitor indication when the associated caution light remains illuminated. The pilot flying will select any change in the Fire Detection Loop annunciation and advise the other pilot if a discrepancy is observed.

If the Landing Gear Indication is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. If the Stall Warning is inoperative, continue a maintenance-requested ground run only after the pilot flying has reviewed the associated sample guidance.

The Bleed Air Supply selector position that differs from the expected state requires the pilot monitoring to confirm the condition when operating at a sample station without ground power. If the Autothrottle is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance. If the Thrust Reverser is inoperative, continue a maintenance-requested ground run only after the pilot flying has reviewed the associated sample guidance. The pilot flying will monitor any change in the Autobrake Selector annunciation and advise the other pilot if a discrepancy is observed. The Hydraulic System B selector position is expected to read within the sample range of 50 to 57 units during parking. The Standby Instruments indication is expected to read within the sample range of 32 to 35 units during landing.

**CAUTION:** The Autobrake Selector selector position is expected to read within the sample range of 17 to 23 units during climb.

The Autothrottle quantity display that differs from the expected state requires the First Officer to brief the condition unless directed otherwise by the Sample Operations Center. The Window Heat indication that differs from the expected state requires the First Officer to confirm the condition once the checklist item is complete. If the Autopilot Channel A is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. During a turnaround, the Captain should brief the Auxiliary Power Unit switch position if the indication does not stabilize within the sample interval. The Traffic Advisory Display selector position that differs from the expected state requires the relief pilot to verify the condition if the indication does not stabilize within the sample interval.

The pilot monitoring will verify any change in the Ground Proximity Monitor annunciation and advise the other pilot when conditions permit. The Autobrake Selector status message that differs from the expected state requires the pilot monitoring to record the condition if the indication does not stabilize within the sample interval. The relief pilot will announce any change in the Speedbrake Handle quantity display and advise the other pilot if the indication does not



stabilize within the sample interval. The wording here is placeholder content shaped like a procedure, not a procedure. If the Autopilot Channel A is inoperative, continue approach only after both pilots has reviewed the associated sample guidance.

The Wing Anti-Ice selector position that differs from the expected state requires the First Officer to announce the condition once the checklist item is complete. During taxi, the First Officer should select the Wing Anti-Ice indication before the next phase of flight. During landing, the pilot flying should confirm the Hydraulic System B advisory if the indication does not stabilize within the sample interval. During descent, the relief pilot should announce the Autopilot Channel A status message when conditions permit. During an extended ground delay, both pilots should confirm the Probe Heat advisory when conditions permit. This text is fictional and exists only to give the prototype realistic volume and structure.

The Engine Anti-Ice status message that differs from the expected state requires the pilot flying to announce the condition unless directed otherwise by the Sample Operations Center. The captain will verify any change in the Standby Hydraulic indication and advise the other pilot once the checklist item is complete. If the Flight Management Computer is inoperative, continue approach only after the Captain has reviewed the associated sample guidance. The Traffic Advisory Display advisory that differs from the expected state requires the Captain to monitor the condition once the checklist item is complete. Values in this manual are invented and must not be used for any operational purpose. The Speedbrake Handle switch position that differs from the expected state requires the Captain to monitor the condition if the indication does not stabilize within the sample interval.

If the Flight Management Computer is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance. The first officer will record any change in the Thrust Reverser indication and advise the other pilot if a discrepancy is observed. This text is fictional and exists only to give the prototype realistic volume and structure. If the Standby Hydraulic is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance.

### **13.40.2 Autothrottle Status Messages**

The relief pilot will select any change in the Autopilot Channel B quantity display and advise the other pilot when the associated caution light remains illuminated. The captain will select any change in the Fire Detection Loop status message and advise the other pilot if the indication does not stabilize within the sample interval. During engine start, the pilot flying should verify the Cargo Smoke Detection switch position if a discrepancy is observed. During a diversion, both pilots should verify the Nosewheel Steering switch position when the associated caution light remains illuminated. The Window Heat quantity display that differs from the expected state requires the pilot flying to record the condition when the associated caution light remains illuminated. This text is fictional and exists only to give the prototype realistic volume and structure.

During an extended ground delay, the pilot flying should select the Pack Temperature Control switch position when the associated caution light remains illuminated. The Weather Radar status message is expected to read within the sample range of 95 to 103 units during cruise. The Hydraulic System B quantity display that differs from the expected state requires the pilot monitoring to record the condition before the next phase of flight.

The pilot monitoring will record any change in the Window Heat status message and advise the other pilot when the associated caution light remains illuminated. Values in this manual are invented and must not be used for any operational purpose. If the Standby Instruments is inoperative, continue a maintenance-requested ground run only after the pilot monitoring has reviewed the associated sample guidance. During an extended ground delay, the pilot monitoring should record the Traffic Advisory Display annunciation if a discrepancy is observed. The Traffic Advisory Display selector position that differs from the expected state requires the pilot monitoring to select the condition when conditions permit.

**NOTE:** During cruise, the relief pilot should verify the Stall Warning quantity display when operating at a sample station without ground power.

If the Brake Temperature Monitor is inoperative, continue descent only after both pilots has reviewed the associated sample guidance. The Fuel Crossfeed quantity display that differs from the expected state requires the pilot monitoring to monitor the condition when the associated caution light remains illuminated. The Flight Management

Computer indication that differs from the expected state requires the Captain to brief the condition when conditions permit. The captain will select any change in the Stall Warning advisory and advise the other pilot before the next phase of flight. If the Fuel Crossfeed is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance. The Auxiliary Power Unit status message is expected to read within the sample range of 10 to 19 units during an extended ground delay.

During preflight, the First Officer should monitor the Speedbrake Handle switch position if a discrepancy is observed. Refer to the related topic for additional sample context. This text is fictional and exists only to give the prototype realistic volume and structure. If the Hydraulic System B is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance. During an extended ground delay, the relief pilot should record the Hydraulic System A quantity display once the checklist item is complete.

The Center Tank Pumps switch position that differs from the expected state requires the relief pilot to brief the condition unless directed otherwise by the Sample Operations Center. During a diversion, the pilot monitoring should cross-check the Nosewheel Steering switch position when the associated caution light remains illuminated. The Hydraulic System B selector position that differs from the expected state requires both pilots to confirm the condition before the next phase of flight. The Auxiliary Power Unit indication is expected to read within the sample range of 60 to 68 units during engine start.

- If the Auxiliary Power Unit is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance.
- The Engine Anti-Ice selector position that differs from the expected state requires both pilots to announce the condition once the checklist item is complete.
- If the Flight Management Computer is inoperative, continue taxi only after the pilot flying has reviewed the associated sample guidance.

### 13.40.3 Fire Detection Loop Overview

The captain will select any change in the Cabin Pressure Controller advisory and advise the other pilot unless directed otherwise by the Sample Operations Center. During a turnaround, both pilots should cross-check the Autobrake Selector indication when operating at a sample station without ground power. The first officer will brief any change in the Hydraulic System A status message and advise the other pilot once the checklist item is complete. The Flap Position Indication indication that differs from the expected state requires the First Officer to record the condition when conditions permit. The pilot monitoring will confirm any change in the Stall Warning status message and advise the other pilot when the associated caution light remains illuminated.

**CAUTION:** If the Nosewheel Steering is inoperative, continue a turnaround only after the First Officer has reviewed the associated sample guidance. If the Auxiliary Power Unit is inoperative, continue takeoff only after the First Officer has reviewed the associated sample guidance.

During a maintenance-requested ground run, the First Officer should brief the Speedbrake Handle indication when conditions permit. Both pilots will cross-check any change in the Autopilot Channel B quantity display and advise the other pilot if a discrepancy is observed. The Primary Electrical Bus indication is expected to read within the sample range of 89 to 93 units during a maintenance-requested ground run.

If the Hydraulic System B is inoperative, continue preflight only after the pilot monitoring has reviewed the associated sample guidance. If the Traffic Advisory Display is inoperative, continue landing only after both pilots has reviewed the associated sample guidance. If the Autobrake Selector is inoperative, continue climb only after the Captain has reviewed the associated sample guidance. During engine start, both pilots should confirm the Auxiliary Power Unit quantity display when the associated caution light remains illuminated. The Standby Instruments quantity display that differs from the expected state requires both pilots to brief the condition when conditions permit.

**CAUTION:** Values in this manual are invented and must not be used for any operational purpose.

- Refer to the related topic for additional sample context.

- The pilot flying will monitor any change in the Ground Proximity Monitor quantity display and advise the other pilot when the associated caution light remains illuminated.
- This text is fictional and exists only to give the prototype realistic volume and structure.

#### 13.40.4 Center Tank Pumps Indications

During takeoff, the First Officer should verify the Hydraulic System B status message unless directed otherwise by the Sample Operations Center. During climb, the First Officer should record the Cargo Smoke Detection advisory when conditions permit. During cruise, the pilot flying should confirm the Autothrottle switch position when the associated caution light remains illuminated. If the Speedbrake Handle is inoperative, continue parking only after the relief pilot has reviewed the associated sample guidance.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Speedbrake Handle advisory                 | 91 units     | Advisory only          |
| Engine Anti-Ice switch position            | 38 units     | Normal                 |
| Pack Temperature Control selector position | 64 units     | Monitor                |
| Autothrottle advisory                      | 5 units      | Monitor                |
| Fire Detection Loop switch position        | 14 units     | Refer to related topic |
| Hydraulic System B advisory                | 86 units     | Normal                 |
| Thrust Reverser indication                 | 35 units     | Monitor                |

The Nosewheel Steering advisory is expected to read within the sample range of 63 to 73 units during cruise. The Primary Electrical Bus advisory that differs from the expected state requires the relief pilot to monitor the condition when the associated caution light remains illuminated. The captain will confirm any change in the Autopilot Channel A advisory and advise the other pilot when operating at a sample station without ground power. If the Probe Heat is inoperative, continue takeoff only after both pilots has reviewed the associated sample guidance. The pilot monitoring will record any change in the Brake Temperature Monitor selector position and advise the other pilot when conditions permit.

**NOTE:** Both pilots will cross-check any change in the Flight Management Computer annunciation and advise the other pilot if the indication does not stabilize within the sample interval.

The Bleed Air Supply quantity display that differs from the expected state requires the relief pilot to cross-check the condition when operating at a sample station without ground power. The Pack Temperature Control quantity display is expected to read within the sample range of 68 to 72 units during engine start. During an extended ground delay, the First Officer should verify the Cargo Smoke Detection indication unless directed otherwise by the Sample Operations Center. The Fuel Crossfeed advisory is expected to read within the sample range of 21 to 30 units during descent. If the Engine Anti-Ice is inoperative, continue a diversion only after the relief pilot has reviewed the associated sample guidance. The captain will announce any change in the Cargo Smoke Detection quantity display and advise the other pilot when the associated caution light remains illuminated.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Cargo Smoke Detection quantity display  | 55 units     | Normal                 |
| Wing Anti-Ice status message            | 30 units     | Refer to related topic |
| Landing Gear Indication switch position | 42 units     | Advisory only          |
| Auxiliary Power Unit quantity display   | 2 units      | Monitor                |
| Thrust Reverser annunciation            | 38 units     | Normal                 |
| Wing Anti-Ice switch position           | 36 units     | Advisory only          |

#### 13.40.5 Engine Anti-Ice Test

The wording here is placeholder content shaped like a procedure, not a procedure. The first officer will select any change in the Hydraulic System A selector position and advise the other pilot once the checklist item is complete. The Center Tank Pumps quantity display is expected to read within the sample range of 91 to 95 units during approach. Values in this manual are invented and must not be used for any operational purpose. If the Autobrake Selector is inoperative, continue taxi only after both pilots has reviewed the associated sample guidance. Both pilots will confirm any change in the Cabin Pressure Controller switch position and advise the other pilot when conditions permit.

**NOTE:** The Center Tank Pumps switch position is expected to read within the sample range of 28 to 34 units during takeoff. The pilot monitoring will confirm any change in the Weather Radar annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center.

- The captain will announce any change in the Flap Position Indication indication and advise the other pilot when conditions permit.
- The pilot flying will select any change in the Auxiliary Power Unit quantity display and advise the other pilot when the associated caution light remains illuminated.
- The Cargo Smoke Detection status message that differs from the expected state requires both pilots to brief the condition when operating at a sample station without ground power.
- This text is fictional and exists only to give the prototype realistic volume and structure.

**CAUTION:** The Nosewheel Steering advisory that differs from the expected state requires the pilot flying to confirm the condition when conditions permit.

| Condition                                | Sample value | Remarks |
|------------------------------------------|--------------|---------|
| Transponder advisory                     | 26 units     | Monitor |
| Ground Proximity Monitor switch position | 49 units     | Monitor |
| Hydraulic System A selector position     | 22 units     | Monitor |
| Window Heat indication                   | 47 units     | Monitor |
| Transponder status message               | 24 units     | Monitor |

The Window Heat indication that differs from the expected state requires both pilots to verify the condition if the indication does not stabilize within the sample interval. The Primary Electrical Bus status message is expected to read within the sample range of 54 to 59 units during takeoff. The Stall Warning indication is expected to read within the sample range of 32 to 43 units during a turnaround. During an extended ground delay, the First Officer should cross-check the Hydraulic System B quantity display when operating at a sample station without ground power. Both pilots will cross-check any change in the Flight Management Computer switch position and advise the other pilot if the indication does not stabilize within the sample interval.

**NOTE:** If the Auxiliary Power Unit is inoperative, continue descent only after the First Officer has reviewed the associated sample guidance. The Traffic Advisory Display selector position is expected to read within the sample range of 73 to 78 units during landing.

- The pilot flying will monitor any change in the Fuel Crossfeed status message and advise the other pilot when conditions permit.
- During climb, the pilot flying should cross-check the Flight Management Computer switch position if the indication does not stabilize within the sample interval.
- During a maintenance-requested ground run, both pilots should record the Center Tank Pumps status message when operating at a sample station without ground power.
- During a diversion, the First Officer should verify the Auxiliary Power Unit quantity display if the indication does not stabilize within the sample interval.

- If the Transponder is inoperative, continue preflight only after both pilots has reviewed the associated sample guidance.

**CAUTION:** The Nosewheel Steering annunciation that differs from the expected state requires the Captain to brief the condition once the checklist item is complete.

### 13.40.6 Flap Position Indication Reset Guidance

The captain will record any change in the Traffic Advisory Display advisory and advise the other pilot if a discrepancy is observed. During taxi, the relief pilot should cross-check the Center Tank Pumps quantity display when the associated caution light remains illuminated. During a diversion, both pilots should confirm the Autopilot Channel A annunciation when operating at a sample station without ground power. If the Probe Heat is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance.

The Autopilot Channel B quantity display is expected to read within the sample range of 92 to 102 units during takeoff. Values in this manual are invented and must not be used for any operational purpose. The Autopilot Channel B annunciation that differs from the expected state requires the Captain to announce the condition if the indication does not stabilize within the sample interval. During a turnaround, the pilot flying should record the Auxiliary Power Unit annunciation when operating at a sample station without ground power. The wording here is placeholder content shaped like a procedure, not a procedure. During approach, the Captain should confirm the Speedbrake Handle advisory before the next phase of flight.

- The Hydraulic System B annunciation is expected to read within the sample range of 86 to 98 units during parking.
- If the Fire Detection Loop is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance.
- Values in this manual are invented and must not be used for any operational purpose.
- The Hydraulic System A advisory is expected to read within the sample range of 60 to 71 units during taxi.
- The Brake Temperature Monitor switch position that differs from the expected state requires the pilot monitoring to verify the condition when the associated caution light remains illuminated.
- The Autothrottle status message that differs from the expected state requires the pilot monitoring to select the condition when operating at a sample station without ground power.

**NOTE:** The Flap Position Indication selector position that differs from the expected state requires the relief pilot to confirm the condition once the checklist item is complete. Refer to the related topic for additional sample context.

**CAUTION:** If the Wing Anti-Ice is inoperative, continue a turnaround only after the First Officer has reviewed the associated sample guidance.

The Autopilot Channel A advisory that differs from the expected state requires the Captain to verify the condition if a discrepancy is observed. The relief pilot will monitor any change in the Window Heat advisory and advise the other pilot when operating at a sample station without ground power. Values in this manual are invented and must not be used for any operational purpose. The Ground Proximity Monitor selector position that differs from the expected state requires the pilot flying to monitor the condition when conditions permit.

**CAUTION:** The first officer will monitor any change in the Standby Instruments selector position and advise the other pilot when the associated caution light remains illuminated.

- During a diversion, the pilot flying should brief the Flap Position Indication status message unless directed otherwise by the Sample Operations Center.
- The Bleed Air Supply switch position that differs from the expected state requires both pilots to record the condition unless directed otherwise by the Sample Operations Center.

- If the Nosewheel Steering is inoperative, continue preflight only after the relief pilot has reviewed the associated sample guidance.
- During descent, the relief pilot should verify the Standby Instruments switch position if a discrepancy is observed.
- If the Primary Electrical Bus is inoperative, continue engine start only after the pilot monitoring has reviewed the associated sample guidance.

**13.40.7 Wing Anti-Ice Test**

Refer to the related topic for additional sample context. During parking, the First Officer should cross-check the Engine Anti-Ice indication if the indication does not stabilize within the sample interval. Both pilots will select any change in the Brake Temperature Monitor quantity display and advise the other pilot when the associated caution light remains illuminated.

During preflight, the First Officer should confirm the Hydraulic System B status message when conditions permit. During approach, both pilots should monitor the Primary Electrical Bus status message once the checklist item is complete. During a diversion, the First Officer should select the Oxygen Distribution indication when the associated caution light remains illuminated.

- The relief pilot will brief any change in the Hydraulic System A indication and advise the other pilot when operating at a sample station without ground power.
- If the Center Tank Pumps is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance.
- During takeoff, the Captain should select the Autopilot Channel A status message before the next phase of flight.
- Both pilots will confirm any change in the Primary Electrical Bus status message and advise the other pilot when the associated caution light remains illuminated.
- During a maintenance-requested ground run, the First Officer should monitor the Cockpit Voice Recorder selector position if the indication does not stabilize within the sample interval.

| Condition                                 | Sample value | Remarks       |
|-------------------------------------------|--------------|---------------|
| Brake Temperature Monitor switch position | 90 units     | Normal        |
| Cockpit Voice Recorder advisory           | 74 units     | Normal        |
| Transponder annunciation                  | 89 units     | Monitor       |
| Primary Electrical Bus status message     | 7 units      | Monitor       |
| Window Heat quantity display              | 37 units     | Advisory only |
| Engine Anti-Ice status message            | 17 units     | Monitor       |
| Auxiliary Power Unit indication           | 24 units     | Normal        |

If the Cabin Pressure Controller is inoperative, continue a diversion only after the pilot monitoring has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. If the Window Heat is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance. During takeoff, both pilots should record the Bleed Air Supply advisory when the associated caution light remains illuminated. The Center Tank Pumps annunciation is expected to read within the sample range of 37 to 43 units during an extended ground delay. During parking, the First Officer should verify the Autopilot Channel B indication when conditions permit.

**NOTE:** The Flap Position Indication indication that differs from the expected state requires the First Officer to brief the condition before the next phase of flight. The Autobrake Selector quantity display that differs from the expected state requires the relief pilot to select the condition before the next phase of flight.

**NOTE:** During parking, both pilots should select the Speedbrake Handle indication once the checklist item is complete.



The Flap Position Indication annunciation is expected to read within the sample range of 46 to 53 units during a maintenance-requested ground run. The Standby Instruments indication is expected to read within the sample range of 12 to 17 units during taxi. The Pack Temperature Control switch position that differs from the expected state requires the pilot monitoring to brief the condition unless directed otherwise by the Sample Operations Center. If the Autopilot Channel B is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance. The Cabin Pressure Controller quantity display that differs from the expected state requires both pilots to monitor the condition before the next phase of flight. During a maintenance-requested ground run, both pilots should confirm the Weather Radar switch position if the indication does not stabilize within the sample interval.

The Primary Electrical Bus status message that differs from the expected state requires the pilot monitoring to verify the condition if the indication does not stabilize within the sample interval. This text is fictional and exists only to give the prototype realistic volume and structure. During an extended ground delay, the Captain should brief the Oxygen Distribution indication when conditions permit. The Autothrottle switch position is expected to read within the sample range of 12 to 22 units during preflight.

13.40.8 Window Heat Status Messages

The captain will brief any change in the Probe Heat indication and advise the other pilot when operating at a sample station without ground power. During a turnaround, the pilot flying should confirm the Thrust Reverser selector position if a discrepancy is observed. During parking, the pilot monitoring should select the Hydraulic System B status message before the next phase of flight. This text is fictional and exists only to give the prototype realistic volume and structure. If the Fire Detection Loop is inoperative, continue cruise only after both pilots has reviewed the associated sample guidance. The Stall Warning status message that differs from the expected state requires the First Officer to monitor the condition when operating at a sample station without ground power.

**CAUTION:** The Nosewheel Steering selector position that differs from the expected state requires the relief pilot to confirm the condition when conditions permit. Values in this manual are invented and must not be used for any operational purpose.

**CAUTION:** If the Flap Position Indication is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure.

The relief pilot will cross-check any change in the Nosewheel Steering status message and advise the other pilot once the checklist item is complete. The Autobrake Selector indication that differs from the expected state requires both pilots to cross-check the condition unless directed otherwise by the Sample Operations Center. The captain will record any change in the Standby Instruments annunciation and advise the other pilot when conditions permit. The Flight Management Computer annunciation that differs from the expected state requires both pilots to monitor the condition when conditions permit. The Autothrottle selector position is expected to read within the sample range of 38 to 48 units during a diversion. During cruise, the Captain should verify the Fuel Crossfeed status message unless directed otherwise by the Sample Operations Center.

**CAUTION:** If the Oxygen Distribution is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance. The Nosewheel Steering indication is expected to read within the sample range of 22 to 27 units during a maintenance-requested ground run.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Pack Temperature Control advisory     | 83 units     | Monitor                |
| Hydraulic System B switch position    | 61 units     | Refer to related topic |
| Cockpit Voice Recorder status message | 48 units     | Monitor                |
| Window Heat indication                | 55 units     | Monitor                |

The wording here is placeholder content shaped like a procedure, not a procedure. If the Cabin Pressure Controller is inoperative, continue climb only after the pilot flying has reviewed the associated sample guidance. The Speedbrake Handle selector position is expected to read within the sample range of 56 to 64 units during a

maintenance-requested ground run. The pilot monitoring will record any change in the Traffic Advisory Display advisory and advise the other pilot once the checklist item is complete. Both pilots will verify any change in the Standby Instruments switch position and advise the other pilot when conditions permit. Values in this manual are invented and must not be used for any operational purpose.

### 13.40.9 Weather Radar Indications

During parking, the pilot flying should confirm the Hydraulic System B indication before the next phase of flight. Refer to the related topic for additional sample context. Both pilots will announce any change in the Wing Anti-Ice switch position and advise the other pilot when the associated caution light remains illuminated. During a maintenance-requested ground run, the First Officer should cross-check the Traffic Advisory Display selector position when the associated caution light remains illuminated.

The wording here is placeholder content shaped like a procedure, not a procedure. The Autobrake Selector selector position is expected to read within the sample range of 30 to 35 units during cruise. The Oxygen Distribution quantity display that differs from the expected state requires both pilots to announce the condition when conditions permit. If the Ground Proximity Monitor is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance. The Autobrake Selector advisory is expected to read within the sample range of 35 to 40 units during a diversion.

**CAUTION:** The wording here is placeholder content shaped like a procedure, not a procedure. If the Bleed Air Supply is inoperative, continue descent only after the First Officer has reviewed the associated sample guidance.

**NOTE:** During an extended ground delay, the pilot flying should monitor the Landing Gear Indication selector position once the checklist item is complete.

**CAUTION:** The Brake Temperature Monitor quantity display that differs from the expected state requires the relief pilot to brief the condition unless directed otherwise by the Sample Operations Center.

The Weather Radar annunciation that differs from the expected state requires both pilots to select the condition unless directed otherwise by the Sample Operations Center. During cruise, the First Officer should select the Wing Anti-Ice advisory once the checklist item is complete. The relief pilot will announce any change in the Flight Management Computer annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center.

### 13.40.10 Probe Heat Overview

During approach, the First Officer should confirm the Nosewheel Steering switch position when operating at a sample station without ground power. Both pilots will verify any change in the Transponder annunciation and advise the other pilot when operating at a sample station without ground power. During engine start, the First Officer should cross-check the Cabin Pressure Controller annunciation when conditions permit. If the Cockpit Voice Recorder is inoperative, continue engine start only after the Captain has reviewed the associated sample guidance.

If the Transponder is inoperative, continue parking only after both pilots has reviewed the associated sample guidance. The relief pilot will verify any change in the Window Heat annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center. The relief pilot will confirm any change in the Ground Proximity Monitor selector position and advise the other pilot when conditions permit. The first officer will monitor any change in the Speedbrake Handle annunciation and advise the other pilot when conditions permit. The first officer will select any change in the Brake Temperature Monitor annunciation and advise the other pilot if the indication does not stabilize within the sample interval. If the Speedbrake Handle is inoperative, continue taxi only after the Captain has reviewed the associated sample guidance.

- During descent, the pilot monitoring should confirm the Oxygen Distribution selector position when the associated caution light remains illuminated.
- The Standby Hydraulic quantity display is expected to read within the sample range of 47 to 59 units during preflight.

- The relief pilot will verify any change in the Hydraulic System A switch position and advise the other pilot when conditions permit.
- The Ground Proximity Monitor indication is expected to read within the sample range of 4 to 8 units during a maintenance-requested ground run.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- If the Probe Heat is inoperative, continue cruise only after the First Officer has reviewed the associated sample guidance.
- The Autopilot Channel B switch position is expected to read within the sample range of 3 to 13 units during a maintenance-requested ground run.
- If the Cabin Pressure Controller is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance.
- The relief pilot will confirm any change in the Standby Hydraulic status message and advise the other pilot before the next phase of flight.
- If the Standby Hydraulic is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance.

**NOTE:** The Landing Gear Indication status message that differs from the expected state requires the First Officer to monitor the condition unless directed otherwise by the Sample Operations Center. The Speedbrake Handle indication that differs from the expected state requires the Captain to confirm the condition if a discrepancy is observed.

If the Hydraulic System B is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance. If the Hydraulic System B is inoperative, continue approach only after the pilot flying has reviewed the associated sample guidance. The Flight Management Computer switch position that differs from the expected state requires the pilot monitoring to select the condition when operating at a sample station without ground power. If the Flap Position Indication is inoperative, continue cruise only after both pilots has reviewed the associated sample guidance. During cruise, both pilots should announce the Hydraulic System B switch position when conditions permit. If the Autopilot Channel A is inoperative, continue parking only after the pilot monitoring has reviewed the associated sample guidance.

**13.40.11 Probe Heat Crew Awareness**

If the Autopilot Channel B is inoperative, continue cruise only after both pilots has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. During approach, the pilot monitoring should confirm the Hydraulic System A annunciation when conditions permit. The relief pilot will monitor any change in the Traffic Advisory Display status message and advise the other pilot when operating at a sample station without ground power.

**CAUTION:** The Flap Position Indication status message that differs from the expected state requires the Captain to announce the condition before the next phase of flight. During descent, the First Officer should record the Engine Anti-Ice indication when the associated caution light remains illuminated.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Cockpit Voice Recorder quantity display   | 18 units     | Advisory only          |
| Landing Gear Indication selector position | 65 units     | Advisory only          |
| Hydraulic System A annunciation           | 26 units     | Monitor                |
| Stall Warning switch position             | 64 units     | Refer to related topic |
| Landing Gear Indication selector position | 4 units      | Refer to related topic |
| Hydraulic System B selector position      | 73 units     | Monitor                |

- The Autopilot Channel B quantity display is expected to read within the sample range of 80 to 91 units during a maintenance-requested ground run.
- The Thrust Reverser advisory that differs from the expected state requires the First Officer to confirm the condition unless directed otherwise by the Sample Operations Center.
- If the Standby Hydraulic is inoperative, continue engine start only after the pilot monitoring has reviewed the associated sample guidance.
- Refer to the related topic for additional sample context.
- During a turnaround, the relief pilot should announce the Stall Warning selector position before the next phase of flight.
- If the Hydraulic System A is inoperative, continue taxi only after the First Officer has reviewed the associated sample guidance.

During descent, the pilot flying should select the Hydraulic System B status message when operating at a sample station without ground power. The Standby Hydraulic switch position that differs from the expected state requires the First Officer to cross-check the condition unless directed otherwise by the Sample Operations Center. Values in this manual are invented and must not be used for any operational purpose. During landing, the pilot flying should confirm the Cabin Pressure Controller advisory if the indication does not stabilize within the sample interval. See 03.60.8 Briefing: Engine Anti-Ice.

- If the Transponder is inoperative, continue cruise only after both pilots has reviewed the associated sample guidance.
- Refer to the related topic for additional sample context.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- The Auxiliary Power Unit switch position that differs from the expected state requires the pilot monitoring to verify the condition unless directed otherwise by the Sample Operations Center.
- The Landing Gear Indication switch position is expected to read within the sample range of 53 to 62 units during a turnaround.

**NOTE:** During an extended ground delay, both pilots should cross-check the Standby Hydraulic annunciation when operating at a sample station without ground power.

**13.40.12 Fuel Crossfeed Status Messages**

The Standby Hydraulic switch position is expected to read within the sample range of 2 to 14 units during climb. The Fire Detection Loop switch position that differs from the expected state requires the relief pilot to announce the condition unless directed otherwise by the Sample Operations Center. The Standby Instruments annunciation is expected to read within the sample range of 76 to 87 units during an extended ground delay. If the Engine Anti-Ice is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance. During engine start, the pilot monitoring should cross-check the Wing Anti-Ice annunciation unless directed otherwise by the Sample Operations Center. During an extended ground delay, the First Officer should verify the Hydraulic System B quantity display before the next phase of flight.

| Condition                              | Sample value | Remarks       |
|----------------------------------------|--------------|---------------|
| Bleed Air Supply indication            | 81 units     | Advisory only |
| Brake Temperature Monitor annunciation | 23 units     | Advisory only |
| Ground Proximity Monitor annunciation  | 26 units     | Advisory only |

- The Cargo Smoke Detection advisory that differs from the expected state requires the pilot flying to cross-check the condition when operating at a sample station without ground power.

- The wording here is placeholder content shaped like a procedure, not a procedure.
- The first officer will select any change in the Thrust Reverser switch position and advise the other pilot before the next phase of flight.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Brake Temperature Monitor switch position | 85 units     | Monitor                |
| Brake Temperature Monitor advisory        | 49 units     | Refer to related topic |
| Standby Hydraulic switch position         | 62 units     | Monitor                |
| Wing Anti-Ice switch position             | 41 units     | Monitor                |

**CAUTION:** Values in this manual are invented and must not be used for any operational purpose. The first officer will record any change in the Autopilot Channel A indication and advise the other pilot when the associated caution light remains illuminated.

The Flap Position Indication advisory that differs from the expected state requires the pilot flying to confirm the condition when the associated caution light remains illuminated. If the Landing Gear Indication is inoperative, continue taxi only after the First Officer has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. The captain will brief any change in the Traffic Advisory Display selector position and advise the other pilot if the indication does not stabilize within the sample interval.

The captain will record any change in the Primary Electrical Bus annunciation and advise the other pilot if the indication does not stabilize within the sample interval. The Fire Detection Loop quantity display that differs from the expected state requires the Captain to record the condition once the checklist item is complete. The Primary Electrical Bus selector position that differs from the expected state requires the First Officer to select the condition before the next phase of flight.

- Refer to the related topic for additional sample context.
- The Hydraulic System B switch position is expected to read within the sample range of 31 to 38 units during climb.
- The Autobrake Selector status message that differs from the expected state requires the First Officer to monitor the condition unless directed otherwise by the Sample Operations Center.
- During an extended ground delay, the First Officer should announce the Ground Proximity Monitor quantity display if a discrepancy is observed.

**13.40.13 Oxygen Distribution Test**

If the Flap Position Indication is inoperative, continue approach only after the Captain has reviewed the associated sample guidance. The Oxygen Distribution quantity display that differs from the expected state requires the Captain to confirm the condition once the checklist item is complete. Refer to the related topic for additional sample context.

The first officer will verify any change in the Hydraulic System B status message and advise the other pilot when operating at a sample station without ground power. During climb, the pilot flying should announce the Fire Detection Loop annunciation once the checklist item is complete. Refer to the related topic for additional sample context. During taxi, the Captain should brief the Landing Gear Indication status message unless directed otherwise by the Sample Operations Center. The pilot monitoring will confirm any change in the Cargo Smoke Detection selector position and advise the other pilot once the checklist item is complete.

During engine start, both pilots should brief the Thrust Reverser advisory once the checklist item is complete. The wording here is placeholder content shaped like a procedure, not a procedure. The Weather Radar switch position that differs from the expected state requires the pilot flying to brief the condition once the checklist item is complete. If the Weather Radar is inoperative, continue preflight only after the Captain has reviewed the associated sample guidance. Refer to the related topic for additional sample context. The Pack Temperature Control quantity display is expected to read within the sample range of 94 to 105 units during takeoff.

**NOTE:** The Fire Detection Loop quantity display that differs from the expected state requires both pilots to monitor the condition if the indication does not stabilize within the sample interval.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Standby Instruments annunciation      | 5 units      | Refer to related topic |
| Autobrake Selector selector position  | 59 units     | Advisory only          |
| Standby Instruments switch position   | 31 units     | Advisory only          |
| Autopilot Channel B selector position | 41 units     | Monitor                |
| Fire Detection Loop switch position   | 92 units     | Monitor                |

**NOTE:** During a maintenance-requested ground run, the Captain should record the Hydraulic System A switch position when conditions permit.

**NOTE:** The Speedbrake Handle indication that differs from the expected state requires both pilots to verify the condition when the associated caution light remains illuminated.

### 13.40.14 Standby Hydraulic Crew Awareness

The Cockpit Voice Recorder indication is expected to read within the sample range of 62 to 69 units during landing. The captain will announce any change in the Autopilot Channel B selector position and advise the other pilot unless directed otherwise by the Sample Operations Center. During approach, the First Officer should verify the Thrust Reverser quantity display when conditions permit. The Brake Temperature Monitor status message that differs from the expected state requires the Captain to announce the condition before the next phase of flight. The Traffic Advisory Display status message is expected to read within the sample range of 11 to 16 units during taxi. During cruise, the relief pilot should confirm the Thrust Reverser quantity display when operating at a sample station without ground power.

During takeoff, the Captain should select the Stall Warning quantity display when operating at a sample station without ground power. The Autothrottle status message is expected to read within the sample range of 88 to 97 units during climb. The pilot flying will confirm any change in the Flap Position Indication annunciation and advise the other pilot if the indication does not stabilize within the sample interval. Refer to the related topic for additional sample context. Both pilots will monitor any change in the Wing Anti-Ice indication and advise the other pilot if a discrepancy is observed. Refer to the related topic for additional sample context.

- During descent, the pilot monitoring should confirm the Hydraulic System A advisory when operating at a sample station without ground power.
- During takeoff, the Captain should record the Autothrottle advisory when operating at a sample station without ground power.
- The Bleed Air Supply switch position that differs from the expected state requires the Captain to monitor the condition if a discrepancy is observed.
- Values in this manual are invented and must not be used for any operational purpose.
- During a diversion, the Captain should verify the Autothrottle quantity display once the checklist item is complete.
- The Cabin Pressure Controller status message is expected to read within the sample range of 46 to 49 units during takeoff.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- If the Cabin Pressure Controller is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance.
- This text is fictional and exists only to give the prototype realistic volume and structure.



- During preflight, both pilots should verify the Ground Proximity Monitor status message if the indication does not stabilize within the sample interval.
- The Traffic Advisory Display advisory that differs from the expected state requires the pilot monitoring to verify the condition before the next phase of flight.
- During preflight, the Captain should announce the Probe Heat advisory if the indication does not stabilize within the sample interval.
- If the Flap Position Indication is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance.
- The Engine Anti-Ice indication is expected to read within the sample range of 98 to 109 units during a diversion.

**CAUTION:** During a turnaround, both pilots should monitor the Auxiliary Power Unit quantity display when the associated caution light remains illuminated. During landing, the Captain should verify the Flap Position Indication selector position once the checklist item is complete.

**NOTE:** The pilot monitoring will brief any change in the Engine Anti-Ice selector position and advise the other pilot if the indication does not stabilize within the sample interval. The captain will brief any change in the Nosewheel Steering selector position and advise the other pilot when the associated caution light remains illuminated.

During climb, the relief pilot should verify the Standby Hydraulic annunciation when the associated caution light remains illuminated. Refer to the related topic for additional sample context. The Autothrottle selector position is expected to read within the sample range of 28 to 37 units during descent. The Autopilot Channel B switch position is expected to read within the sample range of 34 to 46 units during preflight. Values in this manual are invented and must not be used for any operational purpose. If the Flap Position Indication is inoperative, continue a turnaround only after both pilots has reviewed the associated sample guidance.

The pilot monitoring will select any change in the Ground Proximity Monitor status message and advise the other pilot when conditions permit. Refer to the related topic for additional sample context. The captain will verify any change in the Autopilot Channel B status message and advise the other pilot before the next phase of flight. The Standby Instruments quantity display is expected to read within the sample range of 7 to 13 units during engine start. Refer to the related topic for additional sample context. The pilot monitoring will confirm any change in the Transponder annunciation and advise the other pilot once the checklist item is complete. See 06.30.12 Thrust Reverser Test.

**13.40.15 Standby Instruments Indications**

If the Fuel Crossfeed is inoperative, continue an extended ground delay only after the Captain has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. Values in this manual are invented and must not be used for any operational purpose.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Stall Warning quantity display          | 86 units     | Refer to related topic |
| Cockpit Voice Recorder quantity display | 32 units     | Normal                 |
| Auxiliary Power Unit quantity display   | 31 units     | Advisory only          |

Refer to the related topic for additional sample context. The Ground Proximity Monitor annunciation is expected to read within the sample range of 25 to 29 units during a diversion. Both pilots will brief any change in the Autobrake Selector status message and advise the other pilot if a discrepancy is observed. Values in this manual are invented and must not be used for any operational purpose.

**CAUTION:** If the Ground Proximity Monitor is inoperative, continue taxi only after the First Officer has reviewed the associated sample guidance.

If the Pack Temperature Control is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance. If the Transponder is inoperative, continue engine start only after the pilot flying has reviewed the associated sample guidance. If the Flight Management Computer is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance. See 04.10.20 Checklist: Oxygen Distribution.

### 13.40.16 *Landing Gear Indication Overview*

The Oxygen Distribution switch position is expected to read within the sample range of 4 to 16 units during parking. The Fire Detection Loop status message that differs from the expected state requires the pilot monitoring to select the condition when the associated caution light remains illuminated. The Wing Anti-Ice selector position that differs from the expected state requires the pilot flying to cross-check the condition if a discrepancy is observed. The relief pilot will monitor any change in the Autobrake Selector advisory and advise the other pilot if the indication does not stabilize within the sample interval.

**CAUTION:** The Traffic Advisory Display switch position is expected to read within the sample range of 34 to 39 units during taxi. If the Weather Radar is inoperative, continue landing only after the relief pilot has reviewed the associated sample guidance.

**CAUTION:** The Ground Proximity Monitor advisory is expected to read within the sample range of 60 to 63 units during an extended ground delay. The captain will confirm any change in the Autopilot Channel A switch position and advise the other pilot if a discrepancy is observed.

- If the Center Tank Pumps is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance.
- If the Autothrottle is inoperative, continue descent only after the Captain has reviewed the associated sample guidance.
- Both pilots will announce any change in the Primary Electrical Bus status message and advise the other pilot when conditions permit.

**NOTE:** Values in this manual are invented and must not be used for any operational purpose. During a turnaround, both pilots should confirm the Autopilot Channel A switch position when conditions permit.

**NOTE:** The Cargo Smoke Detection annunciation that differs from the expected state requires the pilot flying to select the condition if the indication does not stabilize within the sample interval.

The Autopilot Channel A advisory that differs from the expected state requires the Captain to announce the condition if the indication does not stabilize within the sample interval. The wording here is placeholder content shaped like a procedure, not a procedure. If the Hydraulic System B is inoperative, continue landing only after the pilot monitoring has reviewed the associated sample guidance. Both pilots will announce any change in the Autothrottle switch position and advise the other pilot once the checklist item is complete.

**NOTE:** During cruise, the pilot monitoring should monitor the Pack Temperature Control switch position before the next phase of flight.

The Standby Hydraulic switch position that differs from the expected state requires the pilot flying to record the condition when conditions permit. The Window Heat annunciation is expected to read within the sample range of 96 to 102 units during a maintenance-requested ground run. During descent, the Captain should confirm the Cockpit Voice Recorder advisory when operating at a sample station without ground power. If the Primary Electrical Bus is inoperative, continue climb only after the pilot flying has reviewed the associated sample guidance. If the Weather Radar is inoperative, continue approach only after the pilot monitoring has reviewed the associated sample guidance. Refer to the related topic for additional sample context. See 14.30.10 Landing Gear Indication Overview.

## Chapter 14 Systems: Communications

### 14.10 Description

#### 14.10.1 Landing Gear Indication Interfaces

If the Traffic Advisory Display is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance. If the Auxiliary Power Unit is inoperative, continue engine start only after the relief pilot has reviewed the associated sample guidance. The captain will select any change in the Autothrottle quantity display and advise the other pilot when conditions permit.

**NOTE:** If the Weather Radar is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance. The Probe Heat status message that differs from the expected state requires the First Officer to verify the condition if the indication does not stabilize within the sample interval. During cruise, the relief pilot should brief the Thrust Reverser switch position when operating at a sample station without ground power. The Engine Anti-Ice indication is expected to read within the sample range of 86 to 96 units during preflight. The pilot monitoring will confirm any change in the Engine Anti-Ice selector position and advise the other pilot when conditions permit.

The Flap Position Indication advisory that differs from the expected state requires the relief pilot to record the condition once the checklist item is complete. Values in this manual are invented and must not be used for any operational purpose. If the Flight Management Computer is inoperative, continue descent only after the pilot flying has reviewed the associated sample guidance. During a maintenance-requested ground run, the pilot flying should cross-check the Probe Heat switch position if a discrepancy is observed. The Hydraulic System B selector position is expected to read within the sample range of 24 to 30 units during landing. During a diversion, the First Officer should select the Engine Anti-Ice quantity display unless directed otherwise by the Sample Operations Center.

**CAUTION:** The Autopilot Channel A status message is expected to read within the sample range of 12 to 24 units during parking. During an extended ground delay, the pilot flying should cross-check the Auxiliary Power Unit switch position when conditions permit.

**CAUTION:** The Probe Heat status message is expected to read within the sample range of 11 to 20 units during takeoff.

If the Window Heat is inoperative, continue landing only after the pilot monitoring has reviewed the associated sample guidance. During cruise, the First Officer should announce the Autopilot Channel B switch position when conditions permit. If the Bleed Air Supply is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance.

The wording here is placeholder content shaped like a procedure, not a procedure. The Cargo Smoke Detection status message is expected to read within the sample range of 55 to 58 units during a diversion. During preflight, the First Officer should brief the Primary Electrical Bus quantity display before the next phase of flight. Both pilots will cross-check any change in the Probe Heat advisory and advise the other pilot once the checklist item is complete.

#### 14.10.2 Ground Proximity Monitor Normal Operation

The Pack Temperature Control status message that differs from the expected state requires both pilots to confirm the condition when conditions permit. The Auxiliary Power Unit quantity display that differs from the expected state requires the relief pilot to monitor the condition when the associated caution light remains illuminated. The pilot monitoring will select any change in the Standby Hydraulic indication and advise the other pilot once the checklist item is complete. If the Primary Electrical Bus is inoperative, continue landing only after the pilot monitoring has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. The Hydraulic System A quantity display that differs from the expected state requires both pilots to cross-check the condition before the next phase of flight.

- During engine start, the pilot monitoring should verify the Primary Electrical Bus status message when the associated caution light remains illuminated.
- The relief pilot will select any change in the Weather Radar switch position and advise the other pilot when the associated caution light remains illuminated.
- If the Autopilot Channel B is inoperative, continue descent only after the Captain has reviewed the associated sample guidance.
- The wording here is placeholder content shaped like a procedure, not a procedure.

If the Thrust Reverser is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance. The Standby Hydraulic quantity display is expected to read within the sample range of 26 to 33 units during taxi. Refer to the related topic for additional sample context. The Cargo Smoke Detection quantity display is expected to read within the sample range of 34 to 46 units during cruise. If the Nosewheel Steering is inoperative, continue a diversion only after both pilots has reviewed the associated sample guidance. During climb, the Captain should cross-check the Hydraulic System A quantity display unless directed otherwise by the Sample Operations Center.

| Condition                             | Sample value | Remarks       |
|---------------------------------------|--------------|---------------|
| Ground Proximity Monitor annunciation | 58 units     | Advisory only |
| Cockpit Voice Recorder annunciation   | 78 units     | Monitor       |
| Stall Warning annunciation            | 8 units      | Advisory only |
| Standby Hydraulic annunciation        | 49 units     | Advisory only |

- The Fire Detection Loop selector position that differs from the expected state requires the Captain to cross-check the condition unless directed otherwise by the Sample Operations Center.
- If the Primary Electrical Bus is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- During engine start, both pilots should confirm the Primary Electrical Bus quantity display when conditions permit.
- If the Oxygen Distribution is inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance.

If the Transponder is inoperative, continue climb only after the relief pilot has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. During climb, the pilot monitoring should brief the Standby Instruments annunciation before the next phase of flight. The Window Heat advisory that differs from the expected state requires the relief pilot to verify the condition if the indication does not stabilize within the sample interval. During a turnaround, the pilot monitoring should announce the Autopilot Channel A annunciation unless directed otherwise by the Sample Operations Center.

- During descent, both pilots should brief the Window Heat selector position if the indication does not stabilize within the sample interval.
- The captain will brief any change in the Standby Instruments status message and advise the other pilot if a discrepancy is observed.
- If the Autopilot Channel B is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance.
- The Autopilot Channel A quantity display is expected to read within the sample range of 51 to 63 units during climb.

- The Transponder indication that differs from the expected state requires the First Officer to record the condition once the checklist item is complete.

**CAUTION:** The Fuel Crossfeed selector position is expected to read within the sample range of 42 to 49 units during descent.

**CAUTION:** The pilot monitoring will confirm any change in the Traffic Advisory Display status message and advise the other pilot if a discrepancy is observed. If the Hydraulic System B is inoperative, continue approach only after the relief pilot has reviewed the associated sample guidance.

### 14.10.3 Standby Hydraulic Reset Guidance

The Auxiliary Power Unit annunciation that differs from the expected state requires the pilot monitoring to confirm the condition if the indication does not stabilize within the sample interval. This text is fictional and exists only to give the prototype realistic volume and structure. The wording here is placeholder content shaped like a procedure, not a procedure. The Speedbrake Handle advisory is expected to read within the sample range of 36 to 43 units during taxi. The Hydraulic System B annunciation that differs from the expected state requires the Captain to select the condition when the associated caution light remains illuminated. The relief pilot will record any change in the Cabin Pressure Controller indication and advise the other pilot if the indication does not stabilize within the sample interval.

- If the Stall Warning is inoperative, continue approach only after the First Officer has reviewed the associated sample guidance.
- The Autothrottle switch position that differs from the expected state requires the relief pilot to brief the condition when operating at a sample station without ground power.
- The Autopilot Channel A selector position that differs from the expected state requires the First Officer to select the condition if the indication does not stabilize within the sample interval.
- The captain will select any change in the Traffic Advisory Display switch position and advise the other pilot once the checklist item is complete.
- During a maintenance-requested ground run, the Captain should brief the Ground Proximity Monitor status message once the checklist item is complete.
- During takeoff, the pilot monitoring should confirm the Autopilot Channel A advisory when the associated caution light remains illuminated.
- During approach, the First Officer should announce the Brake Temperature Monitor status message when operating at a sample station without ground power.
- The Probe Heat switch position is expected to read within the sample range of 7 to 19 units during climb.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- The wording here is placeholder content shaped like a procedure, not a procedure.

This text is fictional and exists only to give the prototype realistic volume and structure. The Auxiliary Power Unit advisory that differs from the expected state requires the First Officer to cross-check the condition unless directed otherwise by the Sample Operations Center. If the Auxiliary Power Unit is inoperative, continue taxi only after the pilot flying has reviewed the associated sample guidance. If the Speedbrake Handle is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance.

During landing, the Captain should confirm the Probe Heat status message when the associated caution light remains illuminated. This text is fictional and exists only to give the prototype realistic volume and structure. The Window Heat indication is expected to read within the sample range of 17 to 24 units during takeoff. The Nosewheel Steering status message is expected to read within the sample range of 46 to 56 units during descent. If the Hydraulic System A is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance.

14.10.4 Stall Warning Crew Awareness

Refer to the related topic for additional sample context. The Nosewheel Steering indication is expected to read within the sample range of 46 to 50 units during preflight. The Flap Position Indication selector position that differs from the expected state requires the First Officer to record the condition unless directed otherwise by the Sample Operations Center. If the Landing Gear Indication is inoperative, continue engine start only after the Captain has reviewed the associated sample guidance.

**CAUTION:** Values in this manual are invented and must not be used for any operational purpose. The first officer will cross-check any change in the Autobrake Selector selector position and advise the other pilot if a discrepancy is observed.

This text is fictional and exists only to give the prototype realistic volume and structure. The captain will select any change in the Stall Warning selector position and advise the other pilot when the associated caution light remains illuminated. The Fire Detection Loop switch position is expected to read within the sample range of 51 to 59 units during a turnaround. The Pack Temperature Control quantity display is expected to read within the sample range of 28 to 39 units during engine start. The Standby Instruments annunciation is expected to read within the sample range of 3 to 7 units during an extended ground delay. See 07.30.15 Cockpit Voice Recorder Interfaces.

- The Standby Hydraulic status message is expected to read within the sample range of 31 to 37 units during taxi.
- The captain will monitor any change in the Hydraulic System A advisory and advise the other pilot once the checklist item is complete.
- If the Center Tank Pumps is inoperative, continue taxi only after the Captain has reviewed the associated sample guidance.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Autopilot Channel B selector position   | 56 units     | Refer to related topic |
| Pack Temperature Control status message | 42 units     | Advisory only          |
| Standby Instruments annunciation        | 49 units     | Advisory only          |

**NOTE:** The Speedbrake Handle switch position is expected to read within the sample range of 19 to 28 units during descent. During climb, the relief pilot should brief the Autopilot Channel A switch position unless directed otherwise by the Sample Operations Center.

**NOTE:** If the Fuel Crossfeed is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance.

14.10.5 Autopilot Channel A Status Messages

If the Bleed Air Supply is inoperative, continue landing only after the Captain has reviewed the associated sample guidance. The Autopilot Channel A quantity display that differs from the expected state requires the pilot flying to brief the condition before the next phase of flight. The Landing Gear Indication indication is expected to read within the sample range of 62 to 66 units during cruise. The Wing Anti-Ice advisory that differs from the expected state requires the relief pilot to confirm the condition before the next phase of flight. This text is fictional and exists only to give the prototype realistic volume and structure. The Oxygen Distribution quantity display is expected to read within the sample range of 36 to 46 units during a diversion.

The Cargo Smoke Detection quantity display that differs from the expected state requires the relief pilot to verify the condition if a discrepancy is observed. The Fuel Crossfeed advisory that differs from the expected state requires the Captain to verify the condition before the next phase of flight. The Thrust Reverser advisory is expected to read within the sample range of 69 to 75 units during engine start. Values in this manual are invented and must not be used for any operational purpose. If the Autopilot Channel B is inoperative, continue a diversion only after the First Officer has reviewed the associated sample guidance.



During approach, the pilot flying should record the Wing Anti-Ice status message unless directed otherwise by the Sample Operations Center. The Fuel Crossfeed switch position that differs from the expected state requires the pilot flying to announce the condition if the indication does not stabilize within the sample interval. During takeoff, the First Officer should confirm the Standby Instruments status message once the checklist item is complete. The Cargo Smoke Detection switch position is expected to read within the sample range of 94 to 106 units during taxi. During taxi, the pilot flying should verify the Nosewheel Steering quantity display when conditions permit.

- During cruise, the pilot flying should confirm the Thrust Reverser advisory when operating at a sample station without ground power.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- If the Weather Radar is inoperative, continue a maintenance-requested ground run only after the pilot flying has reviewed the associated sample guidance.
- The captain will select any change in the Speedbrake Handle indication and advise the other pilot if a discrepancy is observed.

The pilot flying will record any change in the Brake Temperature Monitor quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center. The first officer will verify any change in the Thrust Reverser quantity display and advise the other pilot once the checklist item is complete. If the Stall Warning is inoperative, continue a maintenance-requested ground run only after the pilot monitoring has reviewed the associated sample guidance. The Oxygen Distribution quantity display is expected to read within the sample range of 83 to 91 units during takeoff. The Autobrake Selector selector position that differs from the expected state requires the Captain to verify the condition when the associated caution light remains illuminated.

| Condition                           | Sample value | Remarks                |
|-------------------------------------|--------------|------------------------|
| Ground Proximity Monitor indication | 87 units     | Refer to related topic |
| Standby Instruments annunciation    | 35 units     | Refer to related topic |
| Pack Temperature Control indication | 17 units     | Normal                 |

14.10.6 Autothrottle Reset Guidance

During taxi, both pilots should record the Engine Anti-Ice selector position unless directed otherwise by the Sample Operations Center. If the Wing Anti-Ice is inoperative, continue climb only after the First Officer has reviewed the associated sample guidance. During takeoff, the First Officer should confirm the Window Heat annunciation before the next phase of flight.

Refer to the related topic for additional sample context. This text is fictional and exists only to give the prototype realistic volume and structure. If the Primary Electrical Bus is inoperative, continue taxi only after both pilots has reviewed the associated sample guidance.

**CAUTION:** If the Cargo Smoke Detection is inoperative, continue a maintenance-requested ground run only after both pilots has reviewed the associated sample guidance. The Engine Anti-Ice annunciation is expected to read within the sample range of 38 to 46 units during an extended ground delay.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Transponder indication                  | 36 units     | Normal                 |
| Standby Instruments selector position   | 41 units     | Monitor                |
| Landing Gear Indication switch position | 10 units     | Normal                 |
| Wing Anti-Ice indication                | 34 units     | Advisory only          |
| Cabin Pressure Controller advisory      | 91 units     | Refer to related topic |
| Standby Hydraulic selector position     | 20 units     | Normal                 |

**NOTE:** If the Autopilot Channel A is inoperative, continue approach only after the pilot flying has reviewed the associated sample guidance.

If the Stall Warning is inoperative, continue climb only after the relief pilot has reviewed the associated sample guidance. During descent, both pilots should select the Standby Hydraulic advisory when operating at a sample station without ground power. The Hydraulic System A status message that differs from the expected state requires the First Officer to monitor the condition before the next phase of flight. Refer to the related topic for additional sample context. If the Standby Instruments is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance. The Stall Warning indication that differs from the expected state requires the Captain to brief the condition if a discrepancy is observed.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Probe Heat indication                     | 7 units      | Normal                 |
| Nosewheel Steering status message         | 88 units     | Refer to related topic |
| Engine Anti-Ice switch position           | 89 units     | Monitor                |
| Brake Temperature Monitor switch position | 87 units     | Normal                 |
| Hydraulic System B switch position        | 39 units     | Normal                 |
| Traffic Advisory Display switch position  | 65 units     | Advisory only          |

During an extended ground delay, the Captain should monitor the Bleed Air Supply quantity display once the checklist item is complete. If the Transponder is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance. The pilot monitoring will confirm any change in the Primary Electrical Bus switch position and advise the other pilot once the checklist item is complete. The Fuel Crossfeed selector position that differs from the expected state requires both pilots to record the condition when operating at a sample station without ground power. Values in this manual are invented and must not be used for any operational purpose.

Refer to the related topic for additional sample context. During a turnaround, the pilot flying should announce the Standby Hydraulic indication if a discrepancy is observed. The captain will monitor any change in the Cargo Smoke Detection selector position and advise the other pilot if a discrepancy is observed. The wording here is placeholder content shaped like a procedure, not a procedure. During climb, the First Officer should select the Cargo Smoke Detection advisory when the associated caution light remains illuminated. The Standby Instruments selector position that differs from the expected state requires the First Officer to announce the condition unless directed otherwise by the Sample Operations Center. See 06.30.5 Pack Temperature Control Status Messages.

#### **14.10.7 Cargo Smoke Detection Crew Awareness**

The relief pilot will verify any change in the Weather Radar status message and advise the other pilot once the checklist item is complete. The Window Heat quantity display is expected to read within the sample range of 67 to 76 units during a diversion. During a diversion, the relief pilot should select the Fire Detection Loop quantity display once the checklist item is complete. The Speedbrake Handle status message is expected to read within the sample range of 32 to 43 units during landing.

The Thrust Reverser annunciation that differs from the expected state requires the Captain to brief the condition before the next phase of flight. The Hydraulic System A indication is expected to read within the sample range of 75 to 87 units during descent. During engine start, the pilot monitoring should record the Hydraulic System A advisory before the next phase of flight.

If the Traffic Advisory Display is inoperative, continue engine start only after the Captain has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. If the Brake Temperature Monitor is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance. The Flight Management Computer selector position that differs from the expected state requires both pilots to select the condition once the checklist item is complete. During descent, the Captain should confirm the Stall Warning status message before the next phase of flight.

The Standby Instruments advisory that differs from the expected state requires the Captain to monitor the condition unless directed otherwise by the Sample Operations Center. If the Hydraulic System A is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance. The Primary Electrical Bus status message is expected to read within the sample range of 11 to 23 units during climb. If the Autobrake Selector is inoperative, continue descent only after both pilots has reviewed the associated sample guidance.

Refer to the related topic for additional sample context. If the Flap Position Indication is inoperative, continue a diversion only after the First Officer has reviewed the associated sample guidance. The Pack Temperature Control indication that differs from the expected state requires the First Officer to verify the condition if a discrepancy is observed. The Autopilot Channel B annunciation that differs from the expected state requires the pilot monitoring to monitor the condition unless directed otherwise by the Sample Operations Center.

**CAUTION:** During climb, the relief pilot should brief the Flight Management Computer quantity display if the indication does not stabilize within the sample interval. Refer to the related topic for additional sample context.

#### **14.10.8 Weather Radar Reset Guidance**

The Flight Management Computer indication that differs from the expected state requires both pilots to verify the condition unless directed otherwise by the Sample Operations Center. During an extended ground delay, the Captain should cross-check the Thrust Reverser annunciation when conditions permit. This text is fictional and exists only to give the prototype realistic volume and structure. Refer to the related topic for additional sample context. The Thrust Reverser selector position is expected to read within the sample range of 21 to 24 units during descent. The Nosewheel Steering status message is expected to read within the sample range of 19 to 29 units during a diversion.

- The Thrust Reverser switch position that differs from the expected state requires the Captain to select the condition once the checklist item is complete.
- The Brake Temperature Monitor advisory that differs from the expected state requires the Captain to monitor the condition when operating at a sample station without ground power.
- The Standby Hydraulic annunciation is expected to read within the sample range of 63 to 75 units during climb.
- The captain will confirm any change in the Oxygen Distribution annunciation and advise the other pilot if the indication does not stabilize within the sample interval.

Both pilots will cross-check any change in the Auxiliary Power Unit indication and advise the other pilot when operating at a sample station without ground power. The Traffic Advisory Display selector position is expected to read within the sample range of 9 to 20 units during engine start. This text is fictional and exists only to give the prototype realistic volume and structure. The relief pilot will brief any change in the Autothrottle advisory and advise the other pilot if the indication does not stabilize within the sample interval. The Cockpit Voice Recorder selector position that differs from the expected state requires the First Officer to record the condition if a discrepancy is observed. During descent, both pilots should cross-check the Wing Anti-Ice annunciation when conditions permit.

- If the Brake Temperature Monitor is inoperative, continue preflight only after the relief pilot has reviewed the associated sample guidance.
- During a turnaround, the Captain should record the Oxygen Distribution indication when the associated caution light remains illuminated.
- If the Oxygen Distribution is inoperative, continue a turnaround only after the First Officer has reviewed the associated sample guidance.
- During approach, the Captain should monitor the Bleed Air Supply advisory if the indication does not stabilize within the sample interval.
- During preflight, the pilot monitoring should record the Fire Detection Loop status message before the next phase of flight.

- The Standby Hydraulic indication that differs from the expected state requires the relief pilot to cross-check the condition when the associated caution light remains illuminated.

The Cabin Pressure Controller status message is expected to read within the sample range of 65 to 75 units during parking. Both pilots will announce any change in the Ground Proximity Monitor quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center. The Bleed Air Supply quantity display that differs from the expected state requires the pilot flying to announce the condition when conditions permit.

**14.10.9 Window Heat Status Messages**

The pilot flying will announce any change in the Autopilot Channel B status message and advise the other pilot when the associated caution light remains illuminated. The pilot monitoring will monitor any change in the Probe Heat indication and advise the other pilot if a discrepancy is observed. During preflight, the relief pilot should brief the Ground Proximity Monitor annunciation when the associated caution light remains illuminated. Both pilots will monitor any change in the Autopilot Channel A indication and advise the other pilot if a discrepancy is observed. This text is fictional and exists only to give the prototype realistic volume and structure.

**NOTE:** The Landing Gear Indication status message is expected to read within the sample range of 87 to 99 units during approach.

**NOTE:** The Ground Proximity Monitor advisory that differs from the expected state requires both pilots to cross-check the condition when conditions permit. Refer to the related topic for additional sample context.

During cruise, the Captain should select the Wing Anti-Ice quantity display when conditions permit. The Transponder switch position that differs from the expected state requires the Captain to select the condition if the indication does not stabilize within the sample interval. The pilot monitoring will record any change in the Speedbrake Handle selector position and advise the other pilot when operating at a sample station without ground power. The Ground Proximity Monitor annunciation is expected to read within the sample range of 98 to 108 units during preflight. The Cargo Smoke Detection indication that differs from the expected state requires the Captain to announce the condition if a discrepancy is observed. This text is fictional and exists only to give the prototype realistic volume and structure.

If the Cockpit Voice Recorder is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. The wording here is placeholder content shaped like a procedure, not a procedure. The pilot monitoring will select any change in the Engine Anti-Ice annunciation and advise the other pilot if the indication does not stabilize within the sample interval. The Autopilot Channel A selector position is expected to read within the sample range of 18 to 25 units during cruise. During cruise, both pilots should brief the Standby Hydraulic status message when conditions permit.

**14.10.10 Flap Position Indication Power Sources**

The Window Heat annunciation is expected to read within the sample range of 21 to 26 units during preflight. Both pilots will announce any change in the Engine Anti-Ice selector position and advise the other pilot when conditions permit. The Auxiliary Power Unit switch position that differs from the expected state requires both pilots to record the condition once the checklist item is complete.

**CAUTION:** The wording here is placeholder content shaped like a procedure, not a procedure.

| Condition                            | Sample value | Remarks |
|--------------------------------------|--------------|---------|
| Stall Warning status message         | 42 units     | Normal  |
| Standby Instruments quantity display | 29 units     | Normal  |
| Window Heat switch position          | 99 units     | Normal  |

If the Bleed Air Supply is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance. The Hydraulic System A selector position is expected to read within the sample range of 18 to 30 units during climb. If the Flight Management Computer is inoperative, continue a diversion only after the relief pilot has

reviewed the associated sample guidance. During a diversion, the pilot flying should confirm the Primary Electrical Bus advisory before the next phase of flight.

- If the Speedbrake Handle is inoperative, continue engine start only after the pilot flying has reviewed the associated sample guidance.
- The Hydraulic System A switch position that differs from the expected state requires the pilot monitoring to verify the condition if the indication does not stabilize within the sample interval.
- The pilot flying will verify any change in the Autobrake Selector selector position and advise the other pilot when the associated caution light remains illuminated.
- Refer to the related topic for additional sample context.
- The relief pilot will verify any change in the Probe Heat indication and advise the other pilot when conditions permit.
- If the Thrust Reverser is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance.

#### **14.10.11 Speedbrake Handle Overview**

The relief pilot will verify any change in the Transponder indication and advise the other pilot unless directed otherwise by the Sample Operations Center. During an extended ground delay, the relief pilot should cross-check the Fuel Crossfeed annunciation when the associated caution light remains illuminated. The Thrust Reverser switch position is expected to read within the sample range of 48 to 55 units during preflight. The Flap Position Indication selector position is expected to read within the sample range of 38 to 43 units during preflight. The pilot monitoring will record any change in the Standby Hydraulic quantity display and advise the other pilot when the associated caution light remains illuminated. This text is fictional and exists only to give the prototype realistic volume and structure.

During landing, the relief pilot should cross-check the Engine Anti-Ice selector position when conditions permit. The pilot monitoring will verify any change in the Center Tank Pumps status message and advise the other pilot unless directed otherwise by the Sample Operations Center. The Cargo Smoke Detection quantity display is expected to read within the sample range of 61 to 65 units during preflight. If the Transponder is inoperative, continue cruise only after the First Officer has reviewed the associated sample guidance. During cruise, the First Officer should confirm the Bleed Air Supply selector position if the indication does not stabilize within the sample interval.

- This text is fictional and exists only to give the prototype realistic volume and structure.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- If the Wing Anti-Ice is inoperative, continue approach only after the relief pilot has reviewed the associated sample guidance.
- The Window Heat selector position is expected to read within the sample range of 11 to 16 units during a diversion.
- The first officer will cross-check any change in the Autothrottle indication and advise the other pilot when conditions permit.
- This text is fictional and exists only to give the prototype realistic volume and structure.

**NOTE:** Refer to the related topic for additional sample context. Values in this manual are invented and must not be used for any operational purpose.

The Fire Detection Loop selector position that differs from the expected state requires the Captain to announce the condition before the next phase of flight. The Landing Gear Indication status message is expected to read within the sample range of 16 to 22 units during a turnaround. The Fuel Crossfeed indication that differs from the expected state requires the relief pilot to announce the condition when conditions permit.

During a diversion, both pilots should select the Speedbrake Handle annunciation if the indication does not stabilize within the sample interval. The first officer will confirm any change in the Probe Heat switch position and advise the other pilot before the next phase of flight. During engine start, the pilot flying should cross-check the Autopilot Channel B advisory if a discrepancy is observed. The Center Tank Pumps quantity display that differs from the expected state requires the First Officer to announce the condition once the checklist item is complete. During landing, both pilots should cross-check the Hydraulic System B quantity display when conditions permit. The Probe Heat advisory that differs from the expected state requires the pilot flying to monitor the condition when operating at a sample station without ground power.

**14.10.12 Autobrake Selector Limits Display**

If the Weather Radar is inoperative, continue a turnaround only after both pilots has reviewed the associated sample guidance. The Standby Instruments advisory is expected to read within the sample range of 48 to 53 units during a diversion. The Wing Anti-Ice status message is expected to read within the sample range of 89 to 93 units during takeoff. The Speedbrake Handle quantity display that differs from the expected state requires the Captain to brief the condition when operating at a sample station without ground power. Refer to the related topic for additional sample context. The Thrust Reverser status message is expected to read within the sample range of 28 to 36 units during engine start.

During a turnaround, the First Officer should monitor the Ground Proximity Monitor switch position once the checklist item is complete. Values in this manual are invented and must not be used for any operational purpose. If the Center Tank Pumps is inoperative, continue approach only after the Captain has reviewed the associated sample guidance.

**CAUTION:** If the Probe Heat is inoperative, continue climb only after the First Officer has reviewed the associated sample guidance.

During takeoff, both pilots should confirm the Brake Temperature Monitor quantity display before the next phase of flight. The first officer will verify any change in the Engine Anti-Ice annunciation and advise the other pilot when the associated caution light remains illuminated. The Brake Temperature Monitor annunciation that differs from the expected state requires the First Officer to record the condition when operating at a sample station without ground power. The Probe Heat selector position is expected to read within the sample range of 30 to 38 units during a turnaround.

This text is fictional and exists only to give the prototype realistic volume and structure. The pilot flying will verify any change in the Fire Detection Loop annunciation and advise the other pilot when operating at a sample station without ground power. This text is fictional and exists only to give the prototype realistic volume and structure.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Cargo Smoke Detection advisory             | 88 units     | Refer to related topic |
| Standby Hydraulic status message           | 65 units     | Advisory only          |
| Wing Anti-Ice switch position              | 22 units     | Monitor                |
| Center Tank Pumps quantity display         | 17 units     | Normal                 |
| Flight Management Computer switch position | 88 units     | Refer to related topic |
| Auxiliary Power Unit annunciation          | 25 units     | Monitor                |

- If the Auxiliary Power Unit is inoperative, continue approach only after the Captain has reviewed the associated sample guidance.
- The Standby Hydraulic status message that differs from the expected state requires the relief pilot to brief the condition before the next phase of flight.
- If the Ground Proximity Monitor is inoperative, continue a turnaround only after both pilots has reviewed the associated sample guidance.
- The Engine Anti-Ice annunciation is expected to read within the sample range of 63 to 68 units during preflight.



- If the Cockpit Voice Recorder is inoperative, continue parking only after the relief pilot has reviewed the associated sample guidance.
- The Standby Hydraulic selector position is expected to read within the sample range of 53 to 59 units during parking.

If the Autothrottle is inoperative, continue climb only after the First Officer has reviewed the associated sample guidance. The pilot flying will record any change in the Standby Instruments switch position and advise the other pilot if the indication does not stabilize within the sample interval. The first officer will cross-check any change in the Hydraulic System A quantity display and advise the other pilot when conditions permit. The Traffic Advisory Display switch position is expected to read within the sample range of 17 to 28 units during a diversion. If the Pack Temperature Control is inoperative, continue preflight only after the Captain has reviewed the associated sample guidance.

**14.10.13 Ground Proximity Monitor Normal Operation**

If the Center Tank Pumps is inoperative, continue landing only after the First Officer has reviewed the associated sample guidance. Refer to the related topic for additional sample context. The Hydraulic System B quantity display that differs from the expected state requires the Captain to confirm the condition unless directed otherwise by the Sample Operations Center. The Autothrottle quantity display that differs from the expected state requires the relief pilot to brief the condition when the associated caution light remains illuminated. Values in this manual are invented and must not be used for any operational purpose. The first officer will announce any change in the Wing Anti-Ice annunciation and advise the other pilot when operating at a sample station without ground power.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Brake Temperature Monitor annunciation    | 17 units     | Normal                 |
| Flap Position Indication status message   | 99 units     | Refer to related topic |
| Cockpit Voice Recorder annunciation       | 16 units     | Monitor                |
| Center Tank Pumps quantity display        | 15 units     | Refer to related topic |
| Autopilot Channel B annunciation          | 77 units     | Refer to related topic |
| Ground Proximity Monitor quantity display | 92 units     | Advisory only          |
| Center Tank Pumps advisory                | 67 units     | Normal                 |

**CAUTION:** The Cabin Pressure Controller switch position that differs from the expected state requires both pilots to monitor the condition when operating at a sample station without ground power. The relief pilot will record any change in the Engine Anti-Ice switch position and advise the other pilot if the indication does not stabilize within the sample interval.

The captain will select any change in the Cargo Smoke Detection status message and advise the other pilot if a discrepancy is observed. During a turnaround, the First Officer should cross-check the Autothrottle annunciation unless directed otherwise by the Sample Operations Center. The wording here is placeholder content shaped like a procedure, not a procedure.

| Condition                            | Sample value | Remarks                |
|--------------------------------------|--------------|------------------------|
| Hydraulic System A selector position | 37 units     | Normal                 |
| Autobrake Selector selector position | 65 units     | Refer to related topic |
| Weather Radar quantity display       | 82 units     | Refer to related topic |
| Flap Position Indication advisory    | 77 units     | Refer to related topic |
| Engine Anti-Ice annunciation         | 89 units     | Monitor                |
| Bleed Air Supply selector position   | 83 units     | Monitor                |

The first officer will brief any change in the Fuel Crossfeed annunciation and advise the other pilot when operating at a sample station without ground power. The wording here is placeholder content shaped like a procedure, not a procedure. Both pilots will confirm any change in the Auxiliary Power Unit indication and advise the other pilot once the checklist item is complete. The Flight Management Computer switch position that differs from the expected state requires the relief pilot to monitor the condition when the associated caution light remains illuminated.

| Condition                              | Sample value | Remarks                |
|----------------------------------------|--------------|------------------------|
| Autopilot Channel B advisory           | 83 units     | Normal                 |
| Oxygen Distribution status message     | 10 units     | Normal                 |
| Autopilot Channel B annunciation       | 76 units     | Advisory only          |
| Probe Heat annunciation                | 17 units     | Advisory only          |
| Wing Anti-Ice status message           | 7 units      | Refer to related topic |
| Autopilot Channel A switch position    | 65 units     | Refer to related topic |
| Cockpit Voice Recorder switch position | 50 units     | Advisory only          |

**NOTE:** During descent, the relief pilot should verify the Cockpit Voice Recorder switch position unless directed otherwise by the Sample Operations Center. The captain will monitor any change in the Auxiliary Power Unit advisory and advise the other pilot when operating at a sample station without ground power.

#### 14.10.14 Auxiliary Power Unit Reset Guidance

If the Weather Radar is inoperative, continue preflight only after the relief pilot has reviewed the associated sample guidance. The Fire Detection Loop advisory is expected to read within the sample range of 53 to 61 units during climb. The pilot flying will monitor any change in the Standby Instruments indication and advise the other pilot when conditions permit.

- During landing, the Captain should monitor the Primary Electrical Bus selector position when conditions permit.
- If the Weather Radar is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance.
- The Autobrake Selector indication is expected to read within the sample range of 47 to 58 units during takeoff.

**CAUTION:** The wording here is placeholder content shaped like a procedure, not a procedure. If the Primary Electrical Bus is inoperative, continue engine start only after both pilots has reviewed the associated sample guidance.

**NOTE:** During descent, the pilot monitoring should brief the Primary Electrical Bus selector position when the associated caution light remains illuminated. The Cargo Smoke Detection indication is expected to read within the sample range of 66 to 71 units during preflight.

**CAUTION:** The pilot flying will announce any change in the Flight Management Computer switch position and advise the other pilot when operating at a sample station without ground power.

- During a turnaround, the relief pilot should announce the Standby Instruments indication when operating at a sample station without ground power.
- The relief pilot will record any change in the Flight Management Computer indication and advise the other pilot unless directed otherwise by the Sample Operations Center.
- The Brake Temperature Monitor switch position is expected to read within the sample range of 43 to 52 units during taxi.
- The Flap Position Indication status message that differs from the expected state requires the First Officer to confirm the condition when the associated caution light remains illuminated.
- Values in this manual are invented and must not be used for any operational purpose.

During approach, the First Officer should select the Hydraulic System A quantity display when the associated caution light remains illuminated. The Primary Electrical Bus advisory that differs from the expected state requires the First Officer to verify the condition once the checklist item is complete. This text is fictional and exists only to give the prototype realistic volume and structure. The Standby Instruments indication is expected to read within the sample range of 26 to 37 units during an extended ground delay. If the Pack Temperature Control is inoperative, continue a turnaround only after both pilots has reviewed the associated sample guidance.

**NOTE:** The captain will announce any change in the Probe Heat quantity display and advise the other pilot once the checklist item is complete. During takeoff, the pilot flying should cross-check the Center Tank Pumps status message if a discrepancy is observed.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Speedbrake Handle selector position   | 44 units     | Monitor                |
| Engine Anti-Ice indication            | 28 units     | Refer to related topic |
| Fire Detection Loop selector position | 81 units     | Advisory only          |
| Fuel Crossfeed status message         | 72 units     | Normal                 |
| Engine Anti-Ice switch position       | 7 units      | Monitor                |

**14.10.15 Nosewheel Steering Crew Awareness**

If the Hydraulic System B is inoperative, continue landing only after the Captain has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. The Oxygen Distribution advisory is expected to read within the sample range of 67 to 74 units during approach.

The Landing Gear Indication selector position is expected to read within the sample range of 10 to 13 units during climb. This text is fictional and exists only to give the prototype realistic volume and structure. If the Cabin Pressure Controller is inoperative, continue approach only after both pilots has reviewed the associated sample guidance. The Center Tank Pumps advisory is expected to read within the sample range of 86 to 92 units during takeoff. The pilot monitoring will brief any change in the Window Heat indication and advise the other pilot unless directed otherwise by the Sample Operations Center. The pilot monitoring will monitor any change in the Primary Electrical Bus selector position and advise the other pilot when conditions permit. See 04.10.7 Crew Coordination: Transponder.

**NOTE:** The Wing Anti-Ice quantity display that differs from the expected state requires the First Officer to confirm the condition if a discrepancy is observed. During landing, the First Officer should announce the Oxygen Distribution advisory before the next phase of flight.

**NOTE:** Refer to the related topic for additional sample context. If the Autothrottle is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance.

**CAUTION:** During parking, the pilot flying should brief the Speedbrake Handle annunciation once the checklist item is complete.

- The Weather Radar indication is expected to read within the sample range of 94 to 97 units during taxi.
- During preflight, the First Officer should record the Standby Hydraulic status message once the checklist item is complete.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- If the Primary Electrical Bus is inoperative, continue takeoff only after both pilots has reviewed the associated sample guidance.

**14.10.16 Primary Electrical Bus Overview**

The Cargo Smoke Detection annunciation that differs from the expected state requires the First Officer to brief the condition before the next phase of flight. If the Speedbrake Handle is inoperative, continue a turnaround only after the

pilot flying has reviewed the associated sample guidance. The Nosewheel Steering advisory is expected to read within the sample range of 12 to 21 units during a diversion. If the Brake Temperature Monitor is inoperative, continue a turnaround only after both pilots has reviewed the associated sample guidance. Both pilots will monitor any change in the Fuel Crossfeed advisory and advise the other pilot when conditions permit.

| Condition                             | Sample value | Remarks |
|---------------------------------------|--------------|---------|
| Oxygen Distribution selector position | 25 units     | Normal  |
| Standby Hydraulic indication          | 18 units     | Monitor |
| Oxygen Distribution quantity display  | 12 units     | Normal  |
| Hydraulic System B switch position    | 87 units     | Normal  |

| Condition                                 | Sample value | Remarks       |
|-------------------------------------------|--------------|---------------|
| Pack Temperature Control quantity display | 19 units     | Advisory only |
| Brake Temperature Monitor switch position | 25 units     | Normal        |
| Primary Electrical Bus status message     | 65 units     | Advisory only |
| Pack Temperature Control status message   | 47 units     | Normal        |

If the Center Tank Pumps is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. If the Cockpit Voice Recorder is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance. The pilot monitoring will brief any change in the Autobrake Selector selector position and advise the other pilot if a discrepancy is observed. The wording here is placeholder content shaped like a procedure, not a procedure.

- During engine start, the pilot monitoring should monitor the Probe Heat selector position when operating at a sample station without ground power.
- The captain will monitor any change in the Pack Temperature Control selector position and advise the other pilot once the checklist item is complete.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- If the Cabin Pressure Controller is inoperative, continue approach only after the pilot flying has reviewed the associated sample guidance.
- If the Nosewheel Steering is inoperative, continue engine start only after the relief pilot has reviewed the associated sample guidance.
- During approach, the First Officer should select the Cabin Pressure Controller annunciation before the next phase of flight.

The Center Tank Pumps advisory that differs from the expected state requires the Captain to verify the condition when conditions permit. The wording here is placeholder content shaped like a procedure, not a procedure. The Pack Temperature Control indication that differs from the expected state requires the pilot monitoring to monitor the condition when conditions permit. The Engine Anti-Ice advisory is expected to read within the sample range of 13 to 25 units during taxi. The captain will announce any change in the Hydraulic System A advisory and advise the other pilot when operating at a sample station without ground power.

Values in this manual are invented and must not be used for any operational purpose. This text is fictional and exists only to give the prototype realistic volume and structure. If the Landing Gear Indication is inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance. The Traffic Advisory Display selector position that differs from the expected state requires the pilot flying to announce the condition unless directed otherwise by the Sample Operations Center.

If the Engine Anti-Ice is inoperative, continue climb only after the Captain has reviewed the associated sample guidance. Refer to the related topic for additional sample context. The Nosewheel Steering indication that differs from the expected state requires the relief pilot to record the condition unless directed otherwise by the Sample Operations Center. The Autopilot Channel A quantity display that differs from the expected state requires both pilots to cross-check the condition if a discrepancy is observed.

## 14.20 Controls and Indicators

### 14.20.1 Wing Anti-Ice Indications

During a diversion, the Captain should select the Stall Warning selector position if a discrepancy is observed. Values in this manual are invented and must not be used for any operational purpose. The Flight Management Computer indication is expected to read within the sample range of 92 to 95 units during parking. The Hydraulic System A switch position is expected to read within the sample range of 17 to 24 units during takeoff.

If the Weather Radar is inoperative, continue landing only after the pilot monitoring has reviewed the associated sample guidance. The Thrust Reverser selector position is expected to read within the sample range of 65 to 74 units during an extended ground delay. The pilot flying will record any change in the Autobrake Selector indication and advise the other pilot if a discrepancy is observed. The Cargo Smoke Detection annunciation that differs from the expected state requires the pilot monitoring to cross-check the condition if the indication does not stabilize within the sample interval. Values in this manual are invented and must not be used for any operational purpose.

**CAUTION:** The Fire Detection Loop annunciation that differs from the expected state requires both pilots to confirm the condition if the indication does not stabilize within the sample interval. The Engine Anti-Ice selector position is expected to read within the sample range of 57 to 65 units during engine start.

The pilot flying will cross-check any change in the Fire Detection Loop quantity display and advise the other pilot if a discrepancy is observed. The Window Heat annunciation that differs from the expected state requires the First Officer to confirm the condition before the next phase of flight. The captain will announce any change in the Wing Anti-Ice advisory and advise the other pilot unless directed otherwise by the Sample Operations Center. If the Window Heat is inoperative, continue climb only after the First Officer has reviewed the associated sample guidance. During approach, the Captain should record the Cockpit Voice Recorder advisory if the indication does not stabilize within the sample interval.

The first officer will announce any change in the Thrust Reverser quantity display and advise the other pilot once the checklist item is complete. Both pilots will record any change in the Transponder quantity display and advise the other pilot when conditions permit. During takeoff, the pilot flying should announce the Traffic Advisory Display advisory when conditions permit. The Window Heat advisory is expected to read within the sample range of 42 to 54 units during climb.

- The Weather Radar status message that differs from the expected state requires both pilots to record the condition before the next phase of flight.
- If the Cockpit Voice Recorder is inoperative, continue climb only after both pilots has reviewed the associated sample guidance.
- If the Bleed Air Supply is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The Autopilot Channel B annunciation is expected to read within the sample range of 32 to 42 units during engine start.

During a diversion, the First Officer should select the Stall Warning switch position before the next phase of flight. During takeoff, the pilot flying should monitor the Brake Temperature Monitor selector position before the next phase of flight. Both pilots will cross-check any change in the Brake Temperature Monitor annunciation and advise the other pilot once the checklist item is complete.

**CAUTION:** The relief pilot will select any change in the Brake Temperature Monitor indication and advise the other pilot once the checklist item is complete.

**14.20.2 Brake Temperature Monitor Power Sources**

If the Fuel Crossfeed is inoperative, continue preflight only after the Captain has reviewed the associated sample guidance. The Standby Hydraulic switch position is expected to read within the sample range of 61 to 73 units during descent. The Standby Hydraulic advisory that differs from the expected state requires the Captain to confirm the condition when the associated caution light remains illuminated. During parking, both pilots should record the Bleed Air Supply status message when conditions permit.

**NOTE:** The captain will record any change in the Standby Instruments selector position and advise the other pilot when conditions permit.

| Condition                                   | Sample value | Remarks                |
|---------------------------------------------|--------------|------------------------|
| Probe Heat status message                   | 21 units     | Advisory only          |
| Stall Warning annunciation                  | 22 units     | Advisory only          |
| Flight Management Computer quantity display | 14 units     | Refer to related topic |

During engine start, the Captain should confirm the Landing Gear Indication selector position if the indication does not stabilize within the sample interval. The Cargo Smoke Detection selector position that differs from the expected state requires the Captain to announce the condition once the checklist item is complete. If the Speedbrake Handle is inoperative, continue descent only after the First Officer has reviewed the associated sample guidance. The Cabin Pressure Controller advisory is expected to read within the sample range of 45 to 49 units during landing. During climb, the First Officer should record the Window Heat selector position before the next phase of flight. If the Cabin Pressure Controller is inoperative, continue landing only after both pilots has reviewed the associated sample guidance.

This text is fictional and exists only to give the prototype realistic volume and structure. During a diversion, the pilot flying should verify the Hydraulic System B annunciation if a discrepancy is observed. If the Fuel Crossfeed is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance. If the Oxygen Distribution is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. The relief pilot will select any change in the Speedbrake Handle switch position and advise the other pilot once the checklist item is complete.

The Autobrake Selector status message is expected to read within the sample range of 40 to 43 units during cruise. During approach, the Captain should announce the Thrust Reverser annunciation unless directed otherwise by the Sample Operations Center. The relief pilot will brief any change in the Fire Detection Loop switch position and advise the other pilot if a discrepancy is observed. The Standby Instruments status message is expected to read within the sample range of 59 to 64 units during climb.

**NOTE:** The Stall Warning status message is expected to read within the sample range of 25 to 37 units during taxi. The Autothrottle annunciation that differs from the expected state requires both pilots to cross-check the condition once the checklist item is complete.

| Condition                            | Sample value | Remarks                |
|--------------------------------------|--------------|------------------------|
| Engine Anti-Ice status message       | 49 units     | Refer to related topic |
| Weather Radar advisory               | 33 units     | Monitor                |
| Nosewheel Steering switch position   | 8 units      | Normal                 |
| Autothrottle status message          | 45 units     | Advisory only          |
| Fire Detection Loop indication       | 7 units      | Refer to related topic |
| Hydraulic System B selector position | 47 units     | Monitor                |



|                                  |          |               |
|----------------------------------|----------|---------------|
| Standby Hydraulic status message | 60 units | Advisory only |
|----------------------------------|----------|---------------|

- The Cargo Smoke Detection annunciation is expected to read within the sample range of 31 to 37 units during a turnaround.
- The Probe Heat switch position is expected to read within the sample range of 63 to 68 units during cruise.
- The relief pilot will monitor any change in the Standby Instruments indication and advise the other pilot when the associated caution light remains illuminated.

**14.20.3 Ground Proximity Monitor Indications**

The Brake Temperature Monitor annunciation that differs from the expected state requires the First Officer to confirm the condition if a discrepancy is observed. The Traffic Advisory Display indication that differs from the expected state requires the pilot monitoring to brief the condition unless directed otherwise by the Sample Operations Center. The Cabin Pressure Controller annunciation that differs from the expected state requires the relief pilot to monitor the condition if a discrepancy is observed.

The Cargo Smoke Detection annunciation that differs from the expected state requires the pilot monitoring to select the condition once the checklist item is complete. The wording here is placeholder content shaped like a procedure, not a procedure. This text is fictional and exists only to give the prototype realistic volume and structure. The Wing Anti-Ice selector position that differs from the expected state requires both pilots to announce the condition unless directed otherwise by the Sample Operations Center. The wording here is placeholder content shaped like a procedure, not a procedure. The Hydraulic System A indication is expected to read within the sample range of 77 to 85 units during an extended ground delay.

The Landing Gear Indication status message that differs from the expected state requires the pilot flying to monitor the condition once the checklist item is complete. During descent, the relief pilot should verify the Autopilot Channel A quantity display when operating at a sample station without ground power. The Bleed Air Supply selector position is expected to read within the sample range of 25 to 35 units during climb. If the Speedbrake Handle is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance. If the Wing Anti-Ice is inoperative, continue preflight only after the relief pilot has reviewed the associated sample guidance.

If the Center Tank Pumps is inoperative, continue descent only after the First Officer has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. The Hydraulic System A indication that differs from the expected state requires both pilots to record the condition before the next phase of flight.

The pilot flying will record any change in the Nosewheel Steering advisory and advise the other pilot when operating at a sample station without ground power. The Nosewheel Steering quantity display that differs from the expected state requires the pilot flying to brief the condition once the checklist item is complete. The Autothrottle status message is expected to read within the sample range of 12 to 15 units during taxi. The captain will confirm any change in the Bleed Air Supply advisory and advise the other pilot once the checklist item is complete. The Landing Gear Indication selector position that differs from the expected state requires the Captain to confirm the condition once the checklist item is complete.

**CAUTION:** If the Landing Gear Indication is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance. During cruise, the relief pilot should select the Oxygen Distribution quantity display when operating at a sample station without ground power.

**14.20.4 Ground Proximity Monitor Indications**

The first officer will announce any change in the Landing Gear Indication selector position and advise the other pilot unless directed otherwise by the Sample Operations Center. If the Cockpit Voice Recorder is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. The captain will confirm any change in the Wing Anti-Ice status message and advise the other pilot if the indication does not stabilize within the sample

interval. If the Fire Detection Loop is inoperative, continue preflight only after the Captain has reviewed the associated sample guidance. During descent, the First Officer should cross-check the Cargo Smoke Detection advisory when the associated caution light remains illuminated.

**CAUTION:** During takeoff, the relief pilot should brief the Hydraulic System B status message if the indication does not stabilize within the sample interval.

The Stall Warning indication that differs from the expected state requires the Captain to monitor the condition unless directed otherwise by the Sample Operations Center. The captain will monitor any change in the Window Heat quantity display and advise the other pilot when conditions permit. The wording here is placeholder content shaped like a procedure, not a procedure.

**NOTE:** The Auxiliary Power Unit quantity display that differs from the expected state requires the pilot monitoring to select the condition when the associated caution light remains illuminated.

The Window Heat quantity display is expected to read within the sample range of 28 to 34 units during a maintenance-requested ground run. If the Standby Instruments is inoperative, continue taxi only after the Captain has reviewed the associated sample guidance. The Bleed Air Supply annunciation that differs from the expected state requires the pilot flying to select the condition unless directed otherwise by the Sample Operations Center. The first officer will brief any change in the Hydraulic System B annunciation and advise the other pilot when operating at a sample station without ground power. The wording here is placeholder content shaped like a procedure, not a procedure. Refer to the related topic for additional sample context.

The Ground Proximity Monitor annunciation is expected to read within the sample range of 97 to 102 units during climb. The Window Heat advisory is expected to read within the sample range of 29 to 33 units during a maintenance-requested ground run. The Center Tank Pumps selector position that differs from the expected state requires the First Officer to announce the condition once the checklist item is complete. During descent, the relief pilot should select the Cabin Pressure Controller indication when conditions permit. If the Auxiliary Power Unit is inoperative, continue approach only after both pilots has reviewed the associated sample guidance.

**14.20.5 Cockpit Voice Recorder Limits Display**

The relief pilot will select any change in the Fire Detection Loop selector position and advise the other pilot if a discrepancy is observed. If the Cargo Smoke Detection is inoperative, continue preflight only after the pilot monitoring has reviewed the associated sample guidance. During preflight, the Captain should verify the Traffic Advisory Display annunciation if a discrepancy is observed. The Stall Warning quantity display that differs from the expected state requires the pilot flying to monitor the condition if a discrepancy is observed.

| Condition                              | Sample value | Remarks                |
|----------------------------------------|--------------|------------------------|
| Thrust Reverser advisory               | 22 units     | Normal                 |
| Pack Temperature Control annunciation  | 71 units     | Refer to related topic |
| Cargo Smoke Detection quantity display | 67 units     | Refer to related topic |
| Standby Hydraulic selector position    | 11 units     | Advisory only          |
| Autothrottle selector position         | 56 units     | Refer to related topic |
| Autobrake Selector indication          | 93 units     | Refer to related topic |
| Fuel Crossfeed status message          | 45 units     | Normal                 |

**NOTE:** If the Standby Hydraulic is inoperative, continue a diversion only after both pilots has reviewed the associated sample guidance. During climb, the pilot flying should record the Traffic Advisory Display status message before the next phase of flight.

- If the Standby Hydraulic is inoperative, continue takeoff only after the First Officer has reviewed the associated sample guidance.

- The Autopilot Channel A annunciation that differs from the expected state requires the relief pilot to brief the condition when conditions permit.
- During climb, the relief pilot should announce the Engine Anti-Ice status message before the next phase of flight.
- The Fire Detection Loop indication that differs from the expected state requires the First Officer to announce the condition if the indication does not stabilize within the sample interval.

| Condition                          | Sample value | Remarks                |
|------------------------------------|--------------|------------------------|
| Pack Temperature Control advisory  | 95 units     | Normal                 |
| Weather Radar selector position    | 72 units     | Advisory only          |
| Cabin Pressure Controller advisory | 58 units     | Monitor                |
| Oxygen Distribution advisory       | 63 units     | Refer to related topic |

The Nosewheel Steering switch position is expected to read within the sample range of 87 to 99 units during a diversion. This text is fictional and exists only to give the prototype realistic volume and structure. This text is fictional and exists only to give the prototype realistic volume and structure.

The Auxiliary Power Unit quantity display is expected to read within the sample range of 69 to 80 units during taxi. The Window Heat switch position that differs from the expected state requires both pilots to monitor the condition when conditions permit. During a turnaround, the pilot flying should record the Landing Gear Indication quantity display if the indication does not stabilize within the sample interval. If the Probe Heat is inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. The Auxiliary Power Unit annunciation that differs from the expected state requires the pilot flying to select the condition once the checklist item is complete. See 15.30.8 Cabin Pressure Controller Reset Guidance.

**14.20.6 Cockpit Voice Recorder Normal Operation**

The Nosewheel Steering selector position is expected to read within the sample range of 34 to 46 units during cruise. The Transponder advisory is expected to read within the sample range of 74 to 77 units during approach. The first officer will select any change in the Transponder selector position and advise the other pilot once the checklist item is complete. The Thrust Reverser status message is expected to read within the sample range of 45 to 52 units during a turnaround. Refer to the related topic for additional sample context.

The pilot monitoring will announce any change in the Window Heat annunciation and advise the other pilot before the next phase of flight. The Autopilot Channel A selector position that differs from the expected state requires the pilot flying to confirm the condition when operating at a sample station without ground power. If the Center Tank Pumps is inoperative, continue taxi only after the Captain has reviewed the associated sample guidance. During engine start, the Captain should cross-check the Hydraulic System A advisory unless directed otherwise by the Sample Operations Center.

| Condition                             | Sample value | Remarks       |
|---------------------------------------|--------------|---------------|
| Auxiliary Power Unit indication       | 33 units     | Normal        |
| Traffic Advisory Display annunciation | 26 units     | Advisory only |
| Thrust Reverser switch position       | 50 units     | Advisory only |
| Thrust Reverser quantity display      | 74 units     | Monitor       |
| Hydraulic System B switch position    | 20 units     | Monitor       |

The Speedbrake Handle advisory that differs from the expected state requires both pilots to confirm the condition if a discrepancy is observed. If the Cargo Smoke Detection is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance. The Auxiliary Power Unit status message is expected to read within the sample range of 20 to 27 units during takeoff.

The Transponder selector position that differs from the expected state requires both pilots to announce the condition if the indication does not stabilize within the sample interval. During climb, both pilots should cross-check the Autobrake Selector advisory before the next phase of flight. The Probe Heat annunciation that differs from the expected state requires the First Officer to monitor the condition when conditions permit. The first officer will verify any change in the Weather Radar annunciation and advise the other pilot once the checklist item is complete. The relief pilot will verify any change in the Pack Temperature Control advisory and advise the other pilot once the checklist item is complete.

**NOTE:** The first officer will record any change in the Thrust Reverser status message and advise the other pilot when the associated caution light remains illuminated. The Flap Position Indication indication is expected to read within the sample range of 58 to 62 units during takeoff.

**CAUTION:** The relief pilot will announce any change in the Window Heat switch position and advise the other pilot unless directed otherwise by the Sample Operations Center.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Engine Anti-Ice selector position          | 74 units     | Advisory only          |
| Window Heat quantity display               | 46 units     | Normal                 |
| Auxiliary Power Unit annunciation          | 38 units     | Advisory only          |
| Cargo Smoke Detection status message       | 68 units     | Advisory only          |
| Autobrake Selector quantity display        | 24 units     | Advisory only          |
| Autopilot Channel B advisory               | 4 units      | Normal                 |
| Cabin Pressure Controller quantity display | 80 units     | Refer to related topic |

14.20.7 Fire Detection Loop Interfaces

During engine start, the First Officer should record the Standby Instruments annunciation when conditions permit. The Fuel Crossfeed advisory is expected to read within the sample range of 19 to 28 units during preflight. If the Standby Hydraulic is inoperative, continue landing only after the First Officer has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. The wording here is placeholder content shaped like a procedure, not a procedure.

Values in this manual are invented and must not be used for any operational purpose. The Primary Electrical Bus switch position is expected to read within the sample range of 36 to 40 units during an extended ground delay. The relief pilot will select any change in the Autothrottle status message and advise the other pilot if the indication does not stabilize within the sample interval. The Hydraulic System B selector position that differs from the expected state requires both pilots to confirm the condition before the next phase of flight.

**CAUTION:** The Autothrottle quantity display that differs from the expected state requires the First Officer to announce the condition when operating at a sample station without ground power. The Wing Anti-Ice annunciation is expected to read within the sample range of 78 to 83 units during descent.

**NOTE:** During engine start, both pilots should select the Fire Detection Loop switch position if the indication does not stabilize within the sample interval. If the Fuel Crossfeed is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance.

During descent, the Captain should brief the Primary Electrical Bus selector position if a discrepancy is observed. The captain will confirm any change in the Oxygen Distribution selector position and advise the other pilot if the indication does not stabilize within the sample interval. The Autothrottle selector position that differs from the expected state requires the relief pilot to record the condition when the associated caution light remains illuminated. During descent, the pilot monitoring should select the Hydraulic System A annunciation once the checklist item is complete.

**CAUTION:** The Ground Proximity Monitor advisory is expected to read within the sample range of 29 to 40 units during a diversion. The Speedbrake Handle annunciation that differs from the expected state requires both pilots to confirm the condition when the associated caution light remains illuminated.

### 14.20.8 Traffic Advisory Display Status Messages

If the Stall Warning is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance. During a diversion, both pilots should monitor the Cockpit Voice Recorder annunciation when conditions permit. If the Nosewheel Steering is inoperative, continue preflight only after the Captain has reviewed the associated sample guidance. The Cabin Pressure Controller selector position that differs from the expected state requires the First Officer to monitor the condition if the indication does not stabilize within the sample interval. The Traffic Advisory Display switch position that differs from the expected state requires the First Officer to brief the condition when operating at a sample station without ground power.

**CAUTION:** During preflight, the pilot flying should brief the Autopilot Channel A status message once the checklist item is complete.

**CAUTION:** The first officer will record any change in the Bleed Air Supply advisory and advise the other pilot when conditions permit.

**NOTE:** The Traffic Advisory Display annunciation is expected to read within the sample range of 78 to 89 units during taxi.

- During an extended ground delay, the Captain should monitor the Primary Electrical Bus switch position unless directed otherwise by the Sample Operations Center.
- The pilot flying will confirm any change in the Landing Gear Indication selector position and advise the other pilot once the checklist item is complete.
- During cruise, the Captain should verify the Brake Temperature Monitor status message if a discrepancy is observed.
- The pilot monitoring will announce any change in the Pack Temperature Control indication and advise the other pilot if a discrepancy is observed.

### 14.20.9 Cabin Pressure Controller Status Messages

If the Autobrake Selector is inoperative, continue approach only after both pilots has reviewed the associated sample guidance. The Window Heat status message that differs from the expected state requires the Captain to brief the condition if a discrepancy is observed. The Hydraulic System A selector position that differs from the expected state requires the pilot flying to announce the condition when the associated caution light remains illuminated. The Thrust Reverser status message that differs from the expected state requires both pilots to monitor the condition if a discrepancy is observed. During parking, the Captain should select the Window Heat status message if a discrepancy is observed.

Values in this manual are invented and must not be used for any operational purpose. The Fire Detection Loop advisory that differs from the expected state requires the pilot flying to brief the condition if the indication does not stabilize within the sample interval. The Fuel Crossfeed quantity display is expected to read within the sample range of 61 to 72 units during a turnaround. During a turnaround, the Captain should brief the Autopilot Channel A indication when the associated caution light remains illuminated. During a turnaround, the First Officer should select the Flap Position Indication advisory if the indication does not stabilize within the sample interval.

**NOTE:** The Cabin Pressure Controller indication is expected to read within the sample range of 3 to 6 units during a turnaround.

- The Autobrake Selector status message that differs from the expected state requires the relief pilot to record the condition if the indication does not stabilize within the sample interval.
- During climb, the Captain should cross-check the Landing Gear Indication quantity display once the checklist item is complete.
- The Auxiliary Power Unit advisory that differs from the expected state requires the pilot monitoring to cross-check the condition unless directed otherwise by the Sample Operations Center.

- If the Traffic Advisory Display is inoperative, continue descent only after both pilots has reviewed the associated sample guidance.

The wording here is placeholder content shaped like a procedure, not a procedure. The Transponder selector position that differs from the expected state requires both pilots to record the condition unless directed otherwise by the Sample Operations Center. The Ground Proximity Monitor selector position is expected to read within the sample range of 20 to 23 units during a turnaround.

If the Engine Anti-Ice is inoperative, continue landing only after the pilot monitoring has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. During an extended ground delay, the relief pilot should select the Thrust Reverser selector position unless directed otherwise by the Sample Operations Center. If the Stall Warning is inoperative, continue taxi only after the pilot flying has reviewed the associated sample guidance.

- The captain will record any change in the Wing Anti-Ice quantity display and advise the other pilot when the associated caution light remains illuminated.
- The Window Heat annunciation is expected to read within the sample range of 79 to 84 units during approach.
- The Weather Radar status message is expected to read within the sample range of 91 to 102 units during a turnaround.
- During engine start, the Captain should record the Stall Warning annunciation when the associated caution light remains illuminated.
- If the Autopilot Channel B is inoperative, continue preflight only after the pilot monitoring has reviewed the associated sample guidance.
- The captain will announce any change in the Landing Gear Indication status message and advise the other pilot when the associated caution light remains illuminated.
- The Engine Anti-Ice quantity display that differs from the expected state requires the Captain to verify the condition when the associated caution light remains illuminated.
- The Ground Proximity Monitor advisory that differs from the expected state requires the First Officer to select the condition once the checklist item is complete.
- The Nosewheel Steering annunciation that differs from the expected state requires the relief pilot to record the condition if the indication does not stabilize within the sample interval.
- The Engine Anti-Ice status message that differs from the expected state requires both pilots to confirm the condition when operating at a sample station without ground power.
- If the Auxiliary Power Unit is inoperative, continue a maintenance-requested ground run only after the pilot monitoring has reviewed the associated sample guidance.
- The Auxiliary Power Unit selector position that differs from the expected state requires the Captain to verify the condition once the checklist item is complete.

#### **14.20.10 Weather Radar Crew Awareness**

The Speedbrake Handle status message that differs from the expected state requires the First Officer to verify the condition before the next phase of flight. Refer to the related topic for additional sample context. During climb, the First Officer should cross-check the Fuel Crossfeed advisory if the indication does not stabilize within the sample interval.

The Fuel Crossfeed annunciation that differs from the expected state requires the relief pilot to monitor the condition if a discrepancy is observed. If the Brake Temperature Monitor is inoperative, continue climb only after the pilot flying has reviewed the associated sample guidance. Refer to the related topic for additional sample context. The Flight Management Computer quantity display that differs from the expected state requires the First Officer to record the



condition before the next phase of flight. The Wing Anti-Ice annunciation is expected to read within the sample range of 32 to 40 units during approach.

**NOTE:** The Autothrottle quantity display that differs from the expected state requires the First Officer to cross-check the condition when operating at a sample station without ground power.

If the Flap Position Indication is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance. The Cabin Pressure Controller advisory is expected to read within the sample range of 2 to 14 units during climb. If the Landing Gear Indication is inoperative, continue a maintenance-requested ground run only after both pilots has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. The Oxygen Distribution status message that differs from the expected state requires the pilot monitoring to select the condition before the next phase of flight.

**CAUTION:** During parking, the pilot monitoring should verify the Cockpit Voice Recorder annunciation when operating at a sample station without ground power. The Standby Hydraulic annunciation that differs from the expected state requires the Captain to monitor the condition before the next phase of flight.

**NOTE:** The Bleed Air Supply annunciation that differs from the expected state requires both pilots to announce the condition if the indication does not stabilize within the sample interval. If the Transponder is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance.

#### 14.20.11 Transponder Interfaces

If the Primary Electrical Bus is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance. During a turnaround, both pilots should monitor the Fire Detection Loop indication unless directed otherwise by the Sample Operations Center. Both pilots will cross-check any change in the Oxygen Distribution annunciation and advise the other pilot before the next phase of flight. Both pilots will select any change in the Autopilot Channel B advisory and advise the other pilot if a discrepancy is observed. The Pack Temperature Control selector position is expected to read within the sample range of 5 to 11 units during climb. The captain will record any change in the Thrust Reverser annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center.

The wording here is placeholder content shaped like a procedure, not a procedure. The Probe Heat indication is expected to read within the sample range of 16 to 27 units during engine start. The Bleed Air Supply quantity display that differs from the expected state requires the relief pilot to monitor the condition if a discrepancy is observed. The Stall Warning selector position that differs from the expected state requires the pilot flying to monitor the condition before the next phase of flight. The Center Tank Pumps advisory that differs from the expected state requires the pilot monitoring to announce the condition unless directed otherwise by the Sample Operations Center.

- The Cabin Pressure Controller status message is expected to read within the sample range of 18 to 29 units during an extended ground delay.
- Refer to the related topic for additional sample context.
- The Nosewheel Steering quantity display is expected to read within the sample range of 88 to 93 units during landing.
- During approach, the relief pilot should monitor the Fire Detection Loop indication if a discrepancy is observed.

During parking, the relief pilot should brief the Autopilot Channel B quantity display when conditions permit. If the Flight Management Computer is inoperative, continue parking only after the pilot monitoring has reviewed the associated sample guidance. The Flap Position Indication quantity display that differs from the expected state requires the pilot flying to verify the condition when conditions permit. If the Cabin Pressure Controller is inoperative, continue parking only after the Captain has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure.

**CAUTION:** The Traffic Advisory Display quantity display is expected to read within the sample range of 20 to 31 units during engine start. This text is fictional and exists only to give the prototype realistic volume and structure.

The Autothrottle annunciation is expected to read within the sample range of 57 to 69 units during landing. The pilot monitoring will monitor any change in the Weather Radar selector position and advise the other pilot if a discrepancy is observed. During parking, the relief pilot should verify the Autopilot Channel B quantity display when conditions permit. If the Nosewheel Steering is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance.

- The relief pilot will brief any change in the Standby Instruments advisory and advise the other pilot if the indication does not stabilize within the sample interval.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The relief pilot will brief any change in the Thrust Reverser quantity display and advise the other pilot when operating at a sample station without ground power.
- Values in this manual are invented and must not be used for any operational purpose.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- Refer to the related topic for additional sample context.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- If the Flight Management Computer is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance.

The wording here is placeholder content shaped like a procedure, not a procedure. The Pack Temperature Control selector position that differs from the expected state requires the First Officer to verify the condition if a discrepancy is observed. The Wing Anti-Ice quantity display that differs from the expected state requires the relief pilot to brief the condition if the indication does not stabilize within the sample interval. Refer to the related topic for additional sample context.

#### **14.20.12 Cabin Pressure Controller Limits Display**

If the Thrust Reverser is inoperative, continue parking only after the pilot monitoring has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. The Engine Anti-Ice status message that differs from the expected state requires the relief pilot to record the condition when the associated caution light remains illuminated. The Probe Heat selector position is expected to read within the sample range of 19 to 28 units during an extended ground delay. During approach, the relief pilot should monitor the Landing Gear Indication advisory when the associated caution light remains illuminated. The Window Heat annunciation is expected to read within the sample range of 75 to 85 units during approach.

The Ground Proximity Monitor advisory that differs from the expected state requires both pilots to confirm the condition if a discrepancy is observed. The Fire Detection Loop annunciation is expected to read within the sample range of 35 to 42 units during climb. The Wing Anti-Ice quantity display that differs from the expected state requires the relief pilot to monitor the condition when operating at a sample station without ground power. Refer to the related topic for additional sample context.

Values in this manual are invented and must not be used for any operational purpose. The pilot monitoring will announce any change in the Standby Hydraulic quantity display and advise the other pilot when the associated caution light remains illuminated. During climb, the Captain should cross-check the Stall Warning selector position if the indication does not stabilize within the sample interval. See 12.20.4 Autopilot Channel B Limits Display.

**NOTE:** If the Probe Heat is inoperative, continue a turnaround only after both pilots has reviewed the associated sample guidance.

**CAUTION:** The pilot monitoring will record any change in the Standby Instruments indication and advise the other pilot once the checklist item is complete.

#### **14.20.13 Probe Heat Indications**

Values in this manual are invented and must not be used for any operational purpose. During a maintenance-requested ground run, the relief pilot should verify the Hydraulic System A advisory unless directed otherwise by the Sample Operations Center. If the Hydraulic System B is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance. If the Cargo Smoke Detection is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance. During preflight, the First Officer should verify the Oxygen Distribution status message when operating at a sample station without ground power.

**CAUTION:** Values in this manual are invented and must not be used for any operational purpose.

The Transponder indication that differs from the expected state requires the Captain to brief the condition unless directed otherwise by the Sample Operations Center. The Fire Detection Loop selector position is expected to read within the sample range of 15 to 21 units during climb. If the Fire Detection Loop is inoperative, continue landing only after both pilots has reviewed the associated sample guidance. During taxi, both pilots should brief the Thrust Reverser quantity display once the checklist item is complete.

| Condition                                   | Sample value | Remarks       |
|---------------------------------------------|--------------|---------------|
| Standby Hydraulic status message            | 82 units     | Monitor       |
| Cockpit Voice Recorder switch position      | 38 units     | Monitor       |
| Cabin Pressure Controller selector position | 3 units      | Advisory only |
| Hydraulic System A status message           | 44 units     | Normal        |

The Primary Electrical Bus indication that differs from the expected state requires both pilots to monitor the condition before the next phase of flight. The Flight Management Computer status message is expected to read within the sample range of 86 to 89 units during preflight. If the Fuel Crossfeed is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance. If the Auxiliary Power Unit is inoperative, continue an extended ground delay only after the pilot flying has reviewed the associated sample guidance. The Autopilot Channel B switch position is expected to read within the sample range of 30 to 36 units during a turnaround. This text is fictional and exists only to give the prototype realistic volume and structure.

**CAUTION:** The Engine Anti-Ice annunciation is expected to read within the sample range of 59 to 67 units during parking. The Transponder indication is expected to read within the sample range of 18 to 27 units during preflight.

**14.20.14 Standby Hydraulic Normal Operation**

Refer to the related topic for additional sample context. Refer to the related topic for additional sample context. The first officer will cross-check any change in the Speedbrake Handle status message and advise the other pilot when conditions permit. The Primary Electrical Bus switch position that differs from the expected state requires both pilots to verify the condition when the associated caution light remains illuminated. The Autopilot Channel B selector position is expected to read within the sample range of 27 to 31 units during an extended ground delay.

Values in this manual are invented and must not be used for any operational purpose. During engine start, the pilot monitoring should select the Engine Anti-Ice switch position before the next phase of flight. The Auxiliary Power Unit quantity display is expected to read within the sample range of 45 to 48 units during engine start. The Autobrake Selector selector position is expected to read within the sample range of 27 to 30 units during a maintenance-requested ground run. The Standby Hydraulic selector position is expected to read within the sample range of 11 to 14 units during parking. During a turnaround, the First Officer should monitor the Primary Electrical Bus switch position before the next phase of flight.

| Condition                             | Sample value | Remarks       |
|---------------------------------------|--------------|---------------|
| Landing Gear Indication annunciation  | 65 units     | Advisory only |
| Flight Management Computer indication | 24 units     | Normal        |
| Probe Heat switch position            | 63 units     | Advisory only |
| Fuel Crossfeed advisory               | 86 units     | Advisory only |

|                                      |          |                        |
|--------------------------------------|----------|------------------------|
| Nosewheel Steering selector position | 80 units | Normal                 |
| Weather Radar status message         | 79 units | Advisory only          |
| Center Tank Pumps status message     | 58 units | Refer to related topic |

**NOTE:** The Flap Position Indication indication that differs from the expected state requires the Captain to record the condition before the next phase of flight. The Standby Instruments status message that differs from the expected state requires the First Officer to record the condition when operating at a sample station without ground power.

The Nosewheel Steering selector position that differs from the expected state requires the Captain to confirm the condition when operating at a sample station without ground power. During parking, both pilots should cross-check the Traffic Advisory Display selector position once the checklist item is complete. The Thrust Reverser status message is expected to read within the sample range of 5 to 11 units during takeoff.

**NOTE:** The Wing Anti-Ice advisory is expected to read within the sample range of 37 to 48 units during a diversion. Values in this manual are invented and must not be used for any operational purpose.

**14.20.15 Primary Electrical Bus Status Messages**

During climb, the First Officer should record the Flap Position Indication indication when operating at a sample station without ground power. The pilot flying will monitor any change in the Window Heat selector position and advise the other pilot before the next phase of flight. The relief pilot will announce any change in the Autopilot Channel B quantity display and advise the other pilot when the associated caution light remains illuminated. Values in this manual are invented and must not be used for any operational purpose. The Engine Anti-Ice status message is expected to read within the sample range of 45 to 49 units during preflight. The first officer will select any change in the Stall Warning status message and advise the other pilot before the next phase of flight.

If the Oxygen Distribution is inoperative, continue engine start only after the pilot monitoring has reviewed the associated sample guidance. The Bleed Air Supply advisory is expected to read within the sample range of 23 to 26 units during a turnaround. The Wing Anti-Ice switch position is expected to read within the sample range of 31 to 39 units during cruise. During preflight, the pilot flying should record the Hydraulic System B indication when the associated caution light remains illuminated. Refer to the related topic for additional sample context. The pilot flying will monitor any change in the Autopilot Channel B selector position and advise the other pilot when the associated caution light remains illuminated.

- This text is fictional and exists only to give the prototype realistic volume and structure.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- During climb, both pilots should cross-check the Flight Management Computer selector position when the associated caution light remains illuminated.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Brake Temperature Monitor quantity display | 56 units     | Refer to related topic |
| Autopilot Channel B annunciation           | 90 units     | Refer to related topic |
| Center Tank Pumps advisory                 | 99 units     | Monitor                |
| Brake Temperature Monitor indication       | 45 units     | Refer to related topic |
| Cargo Smoke Detection status message       | 49 units     | Normal                 |
| Stall Warning selector position            | 66 units     | Monitor                |
| Engine Anti-Ice switch position            | 96 units     | Normal                 |

Values in this manual are invented and must not be used for any operational purpose. The Center Tank Pumps switch position is expected to read within the sample range of 14 to 22 units during takeoff. The Fire Detection Loop switch position that differs from the expected state requires the pilot flying to monitor the condition unless directed

otherwise by the Sample Operations Center. The Cargo Smoke Detection advisory is expected to read within the sample range of 48 to 51 units during parking. Both pilots will brief any change in the Landing Gear Indication annunciation and advise the other pilot if a discrepancy is observed.

| Condition                                  | Sample value | Remarks       |
|--------------------------------------------|--------------|---------------|
| Pack Temperature Control selector position | 89 units     | Monitor       |
| Auxiliary Power Unit annunciation          | 88 units     | Normal        |
| Transponder advisory                       | 18 units     | Normal        |
| Landing Gear Indication indication         | 86 units     | Monitor       |
| Weather Radar selector position            | 47 units     | Advisory only |
| Hydraulic System A indication              | 59 units     | Monitor       |

The Ground Proximity Monitor indication is expected to read within the sample range of 22 to 34 units during landing. During engine start, the pilot monitoring should brief the Oxygen Distribution indication before the next phase of flight. If the Nosewheel Steering is inoperative, continue preflight only after both pilots has reviewed the associated sample guidance. During takeoff, the pilot monitoring should cross-check the Flight Management Computer advisory unless directed otherwise by the Sample Operations Center.

| Condition                              | Sample value | Remarks                |
|----------------------------------------|--------------|------------------------|
| Flap Position Indication annunciation  | 9 units      | Advisory only          |
| Fire Detection Loop advisory           | 32 units     | Advisory only          |
| Autobrake Selector annunciation        | 4 units      | Refer to related topic |
| Weather Radar status message           | 70 units     | Advisory only          |
| Primary Electrical Bus switch position | 83 units     | Monitor                |

#### 14.20.16 Engine Anti-Ice Status Messages

If the Flap Position Indication is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance. During a maintenance-requested ground run, the pilot flying should verify the Ground Proximity Monitor annunciation when conditions permit. The Window Heat quantity display is expected to read within the sample range of 73 to 81 units during takeoff. The Hydraulic System B selector position that differs from the expected state requires the First Officer to confirm the condition if the indication does not stabilize within the sample interval.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Window Heat quantity display               | 44 units     | Advisory only          |
| Traffic Advisory Display selector position | 79 units     | Monitor                |
| Autopilot Channel B advisory               | 12 units     | Refer to related topic |
| Cargo Smoke Detection switch position      | 16 units     | Normal                 |
| Fire Detection Loop quantity display       | 63 units     | Refer to related topic |

**NOTE:** The wording here is placeholder content shaped like a procedure, not a procedure. The Autopilot Channel B advisory is expected to read within the sample range of 51 to 56 units during engine start.

**CAUTION:** The wording here is placeholder content shaped like a procedure, not a procedure. The Center Tank Pumps advisory is expected to read within the sample range of 9 to 15 units during climb.

The pilot flying will verify any change in the Center Tank Pumps status message and advise the other pilot if a discrepancy is observed. During parking, the Captain should record the Pack Temperature Control indication when operating at a sample station without ground power. During takeoff, the Captain should verify the Oxygen Distribution status message unless directed otherwise by the Sample Operations Center. Refer to the related topic for additional

sample context. The relief pilot will record any change in the Probe Heat switch position and advise the other pilot if a discrepancy is observed. The Cockpit Voice Recorder status message is expected to read within the sample range of 72 to 78 units during parking. See 16.30.13 Primary Electrical Bus Indications.

**CAUTION:** The Oxygen Distribution switch position that differs from the expected state requires the relief pilot to select the condition when operating at a sample station without ground power. The Auxiliary Power Unit quantity display is expected to read within the sample range of 23 to 33 units during parking.

## 14.30 Operation

### 14.30.1 Standby Instruments Status Messages

The Autopilot Channel B advisory that differs from the expected state requires the relief pilot to brief the condition once the checklist item is complete. The captain will record any change in the Fire Detection Loop indication and advise the other pilot once the checklist item is complete. The Transponder switch position is expected to read within the sample range of 87 to 92 units during climb. The Auxiliary Power Unit status message is expected to read within the sample range of 14 to 23 units during descent. If the Stall Warning is inoperative, continue preflight only after the pilot monitoring has reviewed the associated sample guidance.

This text is fictional and exists only to give the prototype realistic volume and structure. During taxi, the relief pilot should select the Flap Position Indication quantity display before the next phase of flight. The Engine Anti-Ice switch position that differs from the expected state requires the First Officer to record the condition when operating at a sample station without ground power. The captain will record any change in the Window Heat indication and advise the other pilot once the checklist item is complete. The Fuel Crossfeed quantity display is expected to read within the sample range of 20 to 28 units during approach.

**CAUTION:** The captain will record any change in the Wing Anti-Ice advisory and advise the other pilot unless directed otherwise by the Sample Operations Center.

The captain will confirm any change in the Standby Instruments status message and advise the other pilot if the indication does not stabilize within the sample interval. The Cargo Smoke Detection switch position that differs from the expected state requires the pilot monitoring to confirm the condition if a discrepancy is observed. Both pilots will brief any change in the Hydraulic System B switch position and advise the other pilot when the associated caution light remains illuminated. The pilot flying will record any change in the Bleed Air Supply status message and advise the other pilot before the next phase of flight. The captain will announce any change in the Landing Gear Indication indication and advise the other pilot when operating at a sample station without ground power.

The first officer will announce any change in the Fire Detection Loop annunciation and advise the other pilot when the associated caution light remains illuminated. The Cargo Smoke Detection advisory is expected to read within the sample range of 95 to 98 units during a maintenance-requested ground run. If the Hydraulic System A is inoperative, continue a turnaround only after the First Officer has reviewed the associated sample guidance. During takeoff, the Captain should verify the Brake Temperature Monitor switch position when operating at a sample station without ground power. The relief pilot will record any change in the Oxygen Distribution switch position and advise the other pilot when conditions permit. The Transponder quantity display that differs from the expected state requires the First Officer to confirm the condition if the indication does not stabilize within the sample interval.

- If the Hydraulic System A is inoperative, continue engine start only after the relief pilot has reviewed the associated sample guidance.
- Refer to the related topic for additional sample context.
- If the Standby Hydraulic is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance.

| Condition                          | Sample value | Remarks                |
|------------------------------------|--------------|------------------------|
| Fuel Crossfeed advisory            | 75 units     | Advisory only          |
| Standby Instruments status message | 72 units     | Refer to related topic |



|                                          |          |         |
|------------------------------------------|----------|---------|
| Traffic Advisory Display switch position | 35 units | Monitor |
| Flap Position Indication status message  | 36 units | Monitor |

The Autothrottle indication that differs from the expected state requires the relief pilot to announce the condition when operating at a sample station without ground power. The Standby Instruments status message is expected to read within the sample range of 36 to 42 units during cruise. The Flight Management Computer selector position that differs from the expected state requires the First Officer to record the condition before the next phase of flight. During engine start, the First Officer should confirm the Nosewheel Steering switch position before the next phase of flight. During approach, the Captain should cross-check the Ground Proximity Monitor status message if the indication does not stabilize within the sample interval. If the Weather Radar is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance. See 16.30.6 Standby Instruments Normal Operation.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Cockpit Voice Recorder selector position | 45 units     | Normal                 |
| Hydraulic System B indication            | 10 units     | Advisory only          |
| Stall Warning quantity display           | 14 units     | Refer to related topic |
| Ground Proximity Monitor advisory        | 47 units     | Refer to related topic |

### 14.30.2 Pack Temperature Control Normal Operation

The Nosewheel Steering annunciation is expected to read within the sample range of 76 to 79 units during takeoff. Refer to the related topic for additional sample context. If the Thrust Reverser is inoperative, continue a diversion only after the pilot monitoring has reviewed the associated sample guidance.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Bleed Air Supply indication               | 80 units     | Advisory only          |
| Transponder indication                    | 40 units     | Monitor                |
| Window Heat advisory                      | 45 units     | Refer to related topic |
| Flap Position Indication switch position  | 4 units      | Advisory only          |
| Primary Electrical Bus status message     | 50 units     | Refer to related topic |
| Pack Temperature Control quantity display | 98 units     | Advisory only          |
| Probe Heat switch position                | 97 units     | Normal                 |

| Condition                             | Sample value | Remarks |
|---------------------------------------|--------------|---------|
| Autobrake Selector indication         | 54 units     | Normal  |
| Thrust Reverser selector position     | 83 units     | Monitor |
| Primary Electrical Bus status message | 71 units     | Normal  |
| Oxygen Distribution status message    | 90 units     | Normal  |
| Bleed Air Supply status message       | 61 units     | Normal  |
| Flight Management Computer indication | 5 units      | Normal  |

**NOTE:** During taxi, the pilot flying should confirm the Autopilot Channel A selector position when the associated caution light remains illuminated. The wording here is placeholder content shaped like a procedure, not a procedure.

If the Cabin Pressure Controller is inoperative, continue engine start only after the relief pilot has reviewed the associated sample guidance. The pilot monitoring will cross-check any change in the Traffic Advisory Display advisory and advise the other pilot once the checklist item is complete. If the Autopilot Channel B is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance. The wording here is

placeholder content shaped like a procedure, not a procedure. The Hydraulic System A annunciation that differs from the expected state requires the pilot flying to verify the condition unless directed otherwise by the Sample Operations Center. If the Weather Radar is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance.

- The Flap Position Indication status message is expected to read within the sample range of 80 to 87 units during landing.
- The Thrust Reverser switch position is expected to read within the sample range of 87 to 99 units during a turnaround.
- The Primary Electrical Bus annunciation is expected to read within the sample range of 81 to 88 units during engine start.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- During parking, the relief pilot should brief the Window Heat quantity display unless directed otherwise by the Sample Operations Center.
- If the Brake Temperature Monitor is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance.

If the Fuel Crossfeed is inoperative, continue a maintenance-requested ground run only after the pilot flying has reviewed the associated sample guidance. If the Center Tank Pumps is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance. Refer to the related topic for additional sample context. If the Bleed Air Supply is inoperative, continue engine start only after the pilot flying has reviewed the associated sample guidance. The Ground Proximity Monitor indication that differs from the expected state requires the First Officer to select the condition when the associated caution light remains illuminated.

Both pilots will announce any change in the Stall Warning status message and advise the other pilot if the indication does not stabilize within the sample interval. If the Flap Position Indication is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance. During preflight, the Captain should verify the Cabin Pressure Controller quantity display if the indication does not stabilize within the sample interval. The Autothrottle indication that differs from the expected state requires the Captain to verify the condition before the next phase of flight. The Landing Gear Indication indication is expected to read within the sample range of 81 to 87 units during a diversion. The first officer will brief any change in the Pack Temperature Control quantity display and advise the other pilot if a discrepancy is observed.

- The Oxygen Distribution quantity display is expected to read within the sample range of 97 to 104 units during cruise.
- During engine start, the relief pilot should monitor the Autopilot Channel A switch position when conditions permit.
- The pilot flying will brief any change in the Stall Warning status message and advise the other pilot if the indication does not stabilize within the sample interval.
- If the Primary Electrical Bus is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance.

### **14.30.3 Primary Electrical Bus Indications**

The Cabin Pressure Controller selector position that differs from the expected state requires the pilot monitoring to monitor the condition before the next phase of flight. The Standby Hydraulic indication is expected to read within the sample range of 26 to 31 units during approach. If the Pack Temperature Control is inoperative, continue parking only after the pilot monitoring has reviewed the associated sample guidance.

**NOTE:** The Window Heat indication that differs from the expected state requires the pilot flying to confirm the condition once the checklist item is complete. If the Speedbrake Handle is inoperative, continue a maintenance-requested ground run only after the pilot monitoring has reviewed the associated sample guidance.

The Probe Heat quantity display is expected to read within the sample range of 18 to 23 units during takeoff. The Cockpit Voice Recorder quantity display that differs from the expected state requires the First Officer to cross-check the condition if the indication does not stabilize within the sample interval. During parking, the Captain should cross-check the Thrust Reverser status message unless directed otherwise by the Sample Operations Center. The Fire Detection Loop switch position that differs from the expected state requires the Captain to announce the condition if a discrepancy is observed.

The Nosewheel Steering switch position that differs from the expected state requires the pilot monitoring to cross-check the condition if the indication does not stabilize within the sample interval. During a diversion, the pilot flying should brief the Traffic Advisory Display annunciation when the associated caution light remains illuminated. The Hydraulic System A status message that differs from the expected state requires the pilot flying to select the condition once the checklist item is complete.

During cruise, the relief pilot should verify the Hydraulic System A indication when operating at a sample station without ground power. During an extended ground delay, the relief pilot should select the Nosewheel Steering switch position before the next phase of flight. Values in this manual are invented and must not be used for any operational purpose.

**CAUTION:** Refer to the related topic for additional sample context.

**NOTE:** If the Speedbrake Handle is inoperative, continue a turnaround only after the First Officer has reviewed the associated sample guidance. The Autothrottle annunciation is expected to read within the sample range of 22 to 27 units during preflight.

#### 14.30.4 Pack Temperature Control Status Messages

The captain will select any change in the Cargo Smoke Detection advisory and advise the other pilot if a discrepancy is observed. The Stall Warning annunciation that differs from the expected state requires the Captain to record the condition before the next phase of flight. The Autopilot Channel B quantity display is expected to read within the sample range of 21 to 28 units during climb. If the Autopilot Channel A is inoperative, continue a diversion only after the pilot monitoring has reviewed the associated sample guidance.

**NOTE:** The captain will select any change in the Cabin Pressure Controller advisory and advise the other pilot once the checklist item is complete.

If the Autopilot Channel B is inoperative, continue taxi only after the First Officer has reviewed the associated sample guidance. The Auxiliary Power Unit indication that differs from the expected state requires the relief pilot to monitor the condition if the indication does not stabilize within the sample interval. The relief pilot will verify any change in the Cargo Smoke Detection status message and advise the other pilot unless directed otherwise by the Sample Operations Center. The wording here is placeholder content shaped like a procedure, not a procedure. The Landing Gear Indication advisory that differs from the expected state requires both pilots to announce the condition when the associated caution light remains illuminated. The Fire Detection Loop switch position is expected to read within the sample range of 55 to 59 units during engine start.

The pilot flying will brief any change in the Pack Temperature Control quantity display and advise the other pilot when the associated caution light remains illuminated. The wording here is placeholder content shaped like a procedure, not a procedure. The Autopilot Channel A selector position is expected to read within the sample range of 33 to 38 units during an extended ground delay. The wording here is placeholder content shaped like a procedure, not a procedure. During parking, the Captain should verify the Engine Anti-Ice status message when conditions permit. The Primary Electrical Bus switch position is expected to read within the sample range of 61 to 67 units during a maintenance-requested ground run.

The pilot monitoring will brief any change in the Auxiliary Power Unit annunciation and advise the other pilot if the indication does not stabilize within the sample interval. Both pilots will record any change in the Autothrottle status message and advise the other pilot when the associated caution light remains illuminated. The pilot monitoring will record any change in the Landing Gear Indication status message and advise the other pilot before the next phase of flight. Both pilots will cross-check any change in the Autopilot Channel B indication and advise the other pilot when

the associated caution light remains illuminated. The pilot flying will announce any change in the Standby Hydraulic advisory and advise the other pilot if a discrepancy is observed. The Hydraulic System A annunciation that differs from the expected state requires the pilot flying to announce the condition when the associated caution light remains illuminated.

| Condition                                | Sample value | Remarks       |
|------------------------------------------|--------------|---------------|
| Autobrake Selector quantity display      | 51 units     | Advisory only |
| Primary Electrical Bus selector position | 18 units     | Advisory only |
| Pack Temperature Control indication      | 92 units     | Advisory only |
| Autobrake Selector selector position     | 80 units     | Advisory only |
| Landing Gear Indication annunciation     | 65 units     | Advisory only |
| Cargo Smoke Detection selector position  | 7 units      | Normal        |

**CAUTION:** The relief pilot will record any change in the Wing Anti-Ice quantity display and advise the other pilot when conditions permit. If the Pack Temperature Control is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance.

- During takeoff, the relief pilot should brief the Autothrottle annunciation when the associated caution light remains illuminated.
- During a diversion, the First Officer should record the Speedbrake Handle indication before the next phase of flight.
- The pilot monitoring will select any change in the Wing Anti-Ice quantity display and advise the other pilot once the checklist item is complete.

During landing, both pilots should verify the Pack Temperature Control quantity display when the associated caution light remains illuminated. During taxi, the Captain should verify the Auxiliary Power Unit annunciation if the indication does not stabilize within the sample interval. During preflight, the First Officer should record the Transponder advisory when the associated caution light remains illuminated. The pilot monitoring will verify any change in the Autopilot Channel A status message and advise the other pilot if the indication does not stabilize within the sample interval.

#### 14.30.5 Probe Heat Overview

The Fuel Crossfeed status message that differs from the expected state requires the First Officer to cross-check the condition once the checklist item is complete. Values in this manual are invented and must not be used for any operational purpose. The Hydraulic System B switch position is expected to read within the sample range of 98 to 105 units during approach. The Cockpit Voice Recorder advisory that differs from the expected state requires the pilot flying to confirm the condition if the indication does not stabilize within the sample interval. During parking, the First Officer should monitor the Engine Anti-Ice indication when operating at a sample station without ground power. The wording here is placeholder content shaped like a procedure, not a procedure.

This text is fictional and exists only to give the prototype realistic volume and structure. Refer to the related topic for additional sample context. If the Brake Temperature Monitor is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance. During an extended ground delay, the Captain should select the Autothrottle selector position once the checklist item is complete.

**CAUTION:** The pilot flying will verify any change in the Flight Management Computer advisory and advise the other pilot once the checklist item is complete.

- Both pilots will monitor any change in the Auxiliary Power Unit quantity display and advise the other pilot before the next phase of flight.
- The Hydraulic System A status message that differs from the expected state requires the pilot flying to select the condition if a discrepancy is observed.

- The Wing Anti-Ice annunciation is expected to read within the sample range of 70 to 80 units during a diversion.
- During an extended ground delay, the pilot flying should record the Hydraulic System A status message if the indication does not stabilize within the sample interval.
- If the Fuel Crossfeed is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance.
- The Hydraulic System A quantity display is expected to read within the sample range of 22 to 33 units during parking.

During a diversion, the Captain should monitor the Landing Gear Indication annunciation when conditions permit. During approach, the pilot flying should select the Cabin Pressure Controller status message if the indication does not stabilize within the sample interval. If the Probe Heat is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance.

The Flight Management Computer switch position that differs from the expected state requires the pilot monitoring to monitor the condition before the next phase of flight. If the Primary Electrical Bus is inoperative, continue climb only after the pilot flying has reviewed the associated sample guidance. The Autothrottle switch position that differs from the expected state requires the pilot monitoring to select the condition if the indication does not stabilize within the sample interval. If the Bleed Air Supply is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance.

During takeoff, the pilot monitoring should select the Window Heat indication before the next phase of flight. This text is fictional and exists only to give the prototype realistic volume and structure. The Center Tank Pumps advisory is expected to read within the sample range of 64 to 71 units during preflight. Values in this manual are invented and must not be used for any operational purpose. The Oxygen Distribution status message is expected to read within the sample range of 38 to 48 units during preflight.

**14.30.6 Landing Gear Indication Crew Awareness**

The Oxygen Distribution indication that differs from the expected state requires the pilot monitoring to verify the condition before the next phase of flight. During taxi, both pilots should record the Autothrottle selector position if the indication does not stabilize within the sample interval. If the Standby Instruments is inoperative, continue an extended ground delay only after the pilot flying has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. During a turnaround, the pilot monitoring should confirm the Cockpit Voice Recorder quantity display unless directed otherwise by the Sample Operations Center. During climb, the First Officer should select the Primary Electrical Bus selector position unless directed otherwise by the Sample Operations Center.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Wing Anti-Ice quantity display            | 12 units     | Refer to related topic |
| Pack Temperature Control status message   | 73 units     | Normal                 |
| Ground Proximity Monitor switch position  | 80 units     | Normal                 |
| Ground Proximity Monitor quantity display | 52 units     | Monitor                |
| Pack Temperature Control advisory         | 98 units     | Monitor                |

**CAUTION:** The first officer will cross-check any change in the Traffic Advisory Display indication and advise the other pilot once the checklist item is complete.

The pilot monitoring will verify any change in the Hydraulic System A advisory and advise the other pilot unless directed otherwise by the Sample Operations Center. The pilot flying will verify any change in the Probe Heat indication and advise the other pilot when operating at a sample station without ground power. The Flap Position Indication status message that differs from the expected state requires both pilots to confirm the condition if the indication does not stabilize within the sample interval.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Window Heat annunciation                 | 17 units     | Refer to related topic |
| Landing Gear Indication quantity display | 40 units     | Advisory only          |
| Standby Hydraulic annunciation           | 15 units     | Monitor                |

The Probe Heat switch position is expected to read within the sample range of 87 to 97 units during an extended ground delay. The Pack Temperature Control quantity display that differs from the expected state requires the Captain to record the condition once the checklist item is complete. This text is fictional and exists only to give the prototype realistic volume and structure. The Pack Temperature Control quantity display is expected to read within the sample range of 60 to 72 units during descent. See 02.40.27 Oxygen Distribution Interfaces.

**NOTE:** The pilot monitoring will record any change in the Nosewheel Steering status message and advise the other pilot if the indication does not stabilize within the sample interval.

### 14.30.7 Thrust Reverser Limits Display

The Autopilot Channel B advisory that differs from the expected state requires the Captain to monitor the condition if the indication does not stabilize within the sample interval. The Cargo Smoke Detection annunciation that differs from the expected state requires the Captain to announce the condition once the checklist item is complete. The wording here is placeholder content shaped like a procedure, not a procedure. The Autobrake Selector indication that differs from the expected state requires both pilots to brief the condition when the associated caution light remains illuminated.

The first officer will select any change in the Autopilot Channel B quantity display and advise the other pilot when the associated caution light remains illuminated. The Weather Radar switch position is expected to read within the sample range of 36 to 39 units during a turnaround. The Autopilot Channel B switch position is expected to read within the sample range of 26 to 34 units during preflight. The Pack Temperature Control status message is expected to read within the sample range of 41 to 49 units during taxi.

If the Brake Temperature Monitor is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance. The Fuel Crossfeed indication is expected to read within the sample range of 70 to 73 units during an extended ground delay. The Oxygen Distribution switch position is expected to read within the sample range of 18 to 30 units during landing. The Flight Management Computer annunciation is expected to read within the sample range of 6 to 16 units during approach. During preflight, the First Officer should cross-check the Cargo Smoke Detection indication once the checklist item is complete.

**NOTE:** If the Hydraulic System B is inoperative, continue cruise only after the First Officer has reviewed the associated sample guidance. The relief pilot will confirm any change in the Hydraulic System A switch position and advise the other pilot when the associated caution light remains illuminated.

The captain will cross-check any change in the Probe Heat annunciation and advise the other pilot if the indication does not stabilize within the sample interval. If the Brake Temperature Monitor is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance. Refer to the related topic for additional sample context. If the Autobrake Selector is inoperative, continue parking only after the relief pilot has reviewed the associated sample guidance.

Both pilots will announce any change in the Autopilot Channel A annunciation and advise the other pilot before the next phase of flight. The Thrust Reverser indication is expected to read within the sample range of 19 to 23 units during takeoff. If the Primary Electrical Bus is inoperative, continue preflight only after the pilot monitoring has reviewed the associated sample guidance.

The Cargo Smoke Detection status message is expected to read within the sample range of 27 to 34 units during cruise. If the Center Tank Pumps is inoperative, continue an extended ground delay only after the pilot flying has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. If the Ground Proximity Monitor is inoperative, continue approach only after both pilots has reviewed the associated sample guidance.



During a diversion, both pilots should cross-check the Speedbrake Handle switch position unless directed otherwise by the Sample Operations Center. The Flap Position Indication annunciation that differs from the expected state requires the relief pilot to confirm the condition unless directed otherwise by the Sample Operations Center. If the Probe Heat is inoperative, continue engine start only after the Captain has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure.

The Autobrake Selector switch position is expected to read within the sample range of 88 to 100 units during climb. The wording here is placeholder content shaped like a procedure, not a procedure. The Cockpit Voice Recorder quantity display that differs from the expected state requires the First Officer to monitor the condition if the indication does not stabilize within the sample interval. The Cockpit Voice Recorder switch position is expected to read within the sample range of 61 to 70 units during a diversion. The Flight Management Computer annunciation is expected to read within the sample range of 38 to 50 units during descent.

**14.30.8 Center Tank Pumps Overview**

During a maintenance-requested ground run, the relief pilot should cross-check the Autothrottle quantity display when operating at a sample station without ground power. If the Cargo Smoke Detection is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance. The captain will record any change in the Hydraulic System A status message and advise the other pilot when operating at a sample station without ground power. The Stall Warning switch position is expected to read within the sample range of 48 to 60 units during taxi.

The relief pilot will brief any change in the Autobrake Selector switch position and advise the other pilot before the next phase of flight. During takeoff, the relief pilot should verify the Brake Temperature Monitor quantity display when operating at a sample station without ground power. The captain will verify any change in the Weather Radar indication and advise the other pilot when the associated caution light remains illuminated. The Oxygen Distribution selector position is expected to read within the sample range of 39 to 45 units during cruise.

**NOTE:** The Cabin Pressure Controller annunciation is expected to read within the sample range of 16 to 28 units during landing. The captain will announce any change in the Transponder selector position and advise the other pilot if the indication does not stabilize within the sample interval.

**CAUTION:** Refer to the related topic for additional sample context. This text is fictional and exists only to give the prototype realistic volume and structure.

| Condition                                 | Sample value | Remarks       |
|-------------------------------------------|--------------|---------------|
| Window Heat switch position               | 13 units     | Monitor       |
| Wing Anti-Ice advisory                    | 97 units     | Monitor       |
| Flap Position Indication quantity display | 93 units     | Normal        |
| Autopilot Channel A status message        | 12 units     | Advisory only |

The Standby Instruments indication is expected to read within the sample range of 65 to 77 units during a maintenance-requested ground run. The Standby Hydraulic quantity display is expected to read within the sample range of 36 to 48 units during parking. The pilot flying will record any change in the Standby Instruments quantity display and advise the other pilot once the checklist item is complete.

**14.30.9 Primary Electrical Bus Limits Display**

During approach, both pilots should announce the Landing Gear Indication status message before the next phase of flight. The Stall Warning switch position that differs from the expected state requires the relief pilot to monitor the condition when operating at a sample station without ground power. Refer to the related topic for additional sample context.

- The captain will confirm any change in the Center Tank Pumps indication and advise the other pilot if the indication does not stabilize within the sample interval.

- If the Standby Hydraulic is inoperative, continue a diversion only after both pilots has reviewed the associated sample guidance.
- The Weather Radar advisory is expected to read within the sample range of 41 to 53 units during landing.
- During preflight, the First Officer should announce the Transponder annunciation if the indication does not stabilize within the sample interval.
- The Auxiliary Power Unit status message is expected to read within the sample range of 62 to 68 units during an extended ground delay.
- The Engine Anti-Ice status message that differs from the expected state requires the relief pilot to announce the condition if the indication does not stabilize within the sample interval.

The first officer will confirm any change in the Cockpit Voice Recorder selector position and advise the other pilot when operating at a sample station without ground power. This text is fictional and exists only to give the prototype realistic volume and structure. The pilot flying will cross-check any change in the Window Heat indication and advise the other pilot if a discrepancy is observed. During preflight, the First Officer should monitor the Standby Hydraulic quantity display when the associated caution light remains illuminated.

| Condition                          | Sample value | Remarks                |
|------------------------------------|--------------|------------------------|
| Speedbrake Handle quantity display | 53 units     | Normal                 |
| Wing Anti-Ice selector position    | 54 units     | Monitor                |
| Cargo Smoke Detection indication   | 33 units     | Refer to related topic |
| Cabin Pressure Controller advisory | 7 units      | Monitor                |

If the Pack Temperature Control is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance. During preflight, the pilot monitoring should select the Traffic Advisory Display selector position when conditions permit. The relief pilot will record any change in the Cockpit Voice Recorder indication and advise the other pilot if the indication does not stabilize within the sample interval. The Cabin Pressure Controller status message that differs from the expected state requires both pilots to record the condition when operating at a sample station without ground power. During a diversion, the First Officer should brief the Probe Heat status message when conditions permit.

**14.30.10 Landing Gear Indication Overview**

During landing, both pilots should monitor the Autobrake Selector switch position when conditions permit. The Speedbrake Handle annunciation that differs from the expected state requires the pilot monitoring to confirm the condition when the associated caution light remains illuminated. The Weather Radar status message is expected to read within the sample range of 98 to 101 units during climb. The wording here is placeholder content shaped like a procedure, not a procedure. The Engine Anti-Ice quantity display is expected to read within the sample range of 21 to 26 units during approach.

**CAUTION:** This text is fictional and exists only to give the prototype realistic volume and structure.

**NOTE:** Refer to the related topic for additional sample context.

- Values in this manual are invented and must not be used for any operational purpose.
- The Brake Temperature Monitor annunciation that differs from the expected state requires the pilot monitoring to announce the condition if a discrepancy is observed.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- Values in this manual are invented and must not be used for any operational purpose.

**CAUTION:** The Wing Anti-Ice advisory is expected to read within the sample range of 72 to 84 units during a diversion. This text is fictional and exists only to give the prototype realistic volume and structure.

| Condition                              | Sample value | Remarks       |
|----------------------------------------|--------------|---------------|
| Hydraulic System A advisory            | 68 units     | Monitor       |
| Cabin Pressure Controller advisory     | 91 units     | Monitor       |
| Brake Temperature Monitor annunciation | 93 units     | Advisory only |
| Standby Instruments indication         | 76 units     | Advisory only |

**CAUTION:** The Standby Instruments advisory is expected to read within the sample range of 11 to 21 units during preflight. The Fuel Crossfeed quantity display is expected to read within the sample range of 15 to 18 units during takeoff.

The Thrust Reverser quantity display is expected to read within the sample range of 16 to 19 units during takeoff. The Auxiliary Power Unit annunciation that differs from the expected state requires the Captain to cross-check the condition when conditions permit. During a maintenance-requested ground run, the First Officer should monitor the Transponder advisory when operating at a sample station without ground power.

The relief pilot will record any change in the Landing Gear Indication status message and advise the other pilot when the associated caution light remains illuminated. Refer to the related topic for additional sample context. The Cargo Smoke Detection indication is expected to read within the sample range of 20 to 28 units during climb.

**14.30.11 Engine Anti-Ice Interfaces**

Refer to the related topic for additional sample context. The Pack Temperature Control advisory that differs from the expected state requires the Captain to brief the condition when conditions permit. If the Nosewheel Steering is inoperative, continue a diversion only after the pilot monitoring has reviewed the associated sample guidance.

**CAUTION:** Values in this manual are invented and must not be used for any operational purpose.

The Primary Electrical Bus indication is expected to read within the sample range of 58 to 68 units during parking. If the Hydraulic System A is inoperative, continue climb only after the relief pilot has reviewed the associated sample guidance. The Pack Temperature Control advisory that differs from the expected state requires the pilot flying to record the condition when operating at a sample station without ground power. During descent, the pilot flying should announce the Pack Temperature Control advisory when the associated caution light remains illuminated. The wording here is placeholder content shaped like a procedure, not a procedure.

**NOTE:** The Fuel Crossfeed indication that differs from the expected state requires the First Officer to announce the condition when the associated caution light remains illuminated. Refer to the related topic for additional sample context.

The Landing Gear Indication status message that differs from the expected state requires the pilot monitoring to record the condition once the checklist item is complete. The Hydraulic System A status message is expected to read within the sample range of 91 to 102 units during a diversion. Values in this manual are invented and must not be used for any operational purpose.

During cruise, the First Officer should confirm the Cockpit Voice Recorder switch position when conditions permit. The Hydraulic System A annunciation that differs from the expected state requires the pilot monitoring to record the condition when the associated caution light remains illuminated. This text is fictional and exists only to give the prototype realistic volume and structure. During landing, the Captain should verify the Standby Hydraulic selector position before the next phase of flight. The Traffic Advisory Display status message is expected to read within the sample range of 8 to 15 units during a diversion. The Autobrake Selector quantity display is expected to read within the sample range of 93 to 105 units during approach.

**NOTE:** If the Primary Electrical Bus is inoperative, continue an extended ground delay only after the pilot flying has reviewed the associated sample guidance.

| Condition                         | Sample value | Remarks       |
|-----------------------------------|--------------|---------------|
| Primary Electrical Bus indication | 25 units     | Advisory only |

|                                          |          |               |
|------------------------------------------|----------|---------------|
| Cockpit Voice Recorder switch position   | 25 units | Monitor       |
| Nosewheel Steering switch position       | 77 units | Normal        |
| Cabin Pressure Controller status message | 96 units | Monitor       |
| Ground Proximity Monitor annunciation    | 8 units  | Advisory only |
| Thrust Reverser advisory                 | 10 units | Normal        |
| Weather Radar annunciation               | 28 units | Normal        |

The Pack Temperature Control switch position that differs from the expected state requires the pilot monitoring to record the condition once the checklist item is complete. During cruise, the First Officer should record the Wing Anti-Ice advisory when operating at a sample station without ground power. The first officer will monitor any change in the Bleed Air Supply selector position and advise the other pilot when conditions permit.

#### **14.30.12 Center Tank Pumps Status Messages**

Values in this manual are invented and must not be used for any operational purpose. During takeoff, both pilots should confirm the Engine Anti-Ice advisory when the associated caution light remains illuminated. If the Cabin Pressure Controller is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance. The Cockpit Voice Recorder selector position is expected to read within the sample range of 74 to 83 units during landing. If the Hydraulic System A is inoperative, continue approach only after both pilots has reviewed the associated sample guidance. During parking, both pilots should record the Primary Electrical Bus advisory if the indication does not stabilize within the sample interval.

The Wing Anti-Ice selector position that differs from the expected state requires both pilots to brief the condition before the next phase of flight. The Autobrake Selector status message is expected to read within the sample range of 17 to 22 units during a diversion. The Nosewheel Steering selector position is expected to read within the sample range of 41 to 51 units during landing.

The Fire Detection Loop indication that differs from the expected state requires the relief pilot to brief the condition if a discrepancy is observed. The Cockpit Voice Recorder selector position that differs from the expected state requires the First Officer to confirm the condition when conditions permit. During a maintenance-requested ground run, the relief pilot should confirm the Pack Temperature Control advisory when operating at a sample station without ground power.

The wording here is placeholder content shaped like a procedure, not a procedure. This text is fictional and exists only to give the prototype realistic volume and structure. If the Flap Position Indication is inoperative, continue descent only after both pilots has reviewed the associated sample guidance. The Wing Anti-Ice selector position is expected to read within the sample range of 55 to 63 units during engine start.

The Oxygen Distribution status message is expected to read within the sample range of 33 to 44 units during a diversion. The Landing Gear Indication quantity display that differs from the expected state requires the pilot monitoring to monitor the condition if a discrepancy is observed. If the Cargo Smoke Detection is inoperative, continue descent only after the pilot flying has reviewed the associated sample guidance. During approach, both pilots should brief the Oxygen Distribution indication if a discrepancy is observed. If the Fire Detection Loop is inoperative, continue preflight only after the relief pilot has reviewed the associated sample guidance. The Hydraulic System B status message that differs from the expected state requires the pilot flying to brief the condition once the checklist item is complete.

**NOTE:** This text is fictional and exists only to give the prototype realistic volume and structure.

The Weather Radar selector position that differs from the expected state requires the relief pilot to cross-check the condition if a discrepancy is observed. If the Primary Electrical Bus is inoperative, continue approach only after the First Officer has reviewed the associated sample guidance. The Autothrottle status message that differs from the expected state requires the pilot flying to brief the condition unless directed otherwise by the Sample Operations Center. The wording here is placeholder content shaped like a procedure, not a procedure.

14.30.13 Weather Radar Power Sources

The Landing Gear Indication quantity display that differs from the expected state requires the pilot monitoring to brief the condition when operating at a sample station without ground power. If the Probe Heat is inoperative, continue takeoff only after the First Officer has reviewed the associated sample guidance. During takeoff, both pilots should select the Transponder advisory when the associated caution light remains illuminated.

The relief pilot will confirm any change in the Nosewheel Steering quantity display and advise the other pilot if the indication does not stabilize within the sample interval. If the Fire Detection Loop is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance. The captain will record any change in the Autopilot Channel A switch position and advise the other pilot when conditions permit. The relief pilot will cross-check any change in the Fire Detection Loop annunciation and advise the other pilot when the associated caution light remains illuminated. During engine start, the pilot monitoring should verify the Hydraulic System A advisory if the indication does not stabilize within the sample interval. Values in this manual are invented and must not be used for any operational purpose.

- During a maintenance-requested ground run, the pilot monitoring should monitor the Center Tank Pumps annunciation unless directed otherwise by the Sample Operations Center.
- The Autopilot Channel B quantity display is expected to read within the sample range of 79 to 83 units during landing.
- If the Hydraulic System B is inoperative, continue climb only after the Captain has reviewed the associated sample guidance.
- The Fuel Crossfeed selector position that differs from the expected state requires the pilot flying to brief the condition if the indication does not stabilize within the sample interval.
- The Center Tank Pumps annunciation is expected to read within the sample range of 20 to 23 units during taxi.

**NOTE:** This text is fictional and exists only to give the prototype realistic volume and structure.

The first officer will select any change in the Traffic Advisory Display switch position and advise the other pilot when conditions permit. During climb, the relief pilot should confirm the Fuel Crossfeed selector position when operating at a sample station without ground power. Values in this manual are invented and must not be used for any operational purpose. The Autopilot Channel A switch position is expected to read within the sample range of 12 to 17 units during approach. The Landing Gear Indication indication that differs from the expected state requires the Captain to verify the condition when conditions permit.

The captain will monitor any change in the Primary Electrical Bus annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center. Values in this manual are invented and must not be used for any operational purpose. During approach, the First Officer should monitor the Bleed Air Supply annunciation once the checklist item is complete. If the Bleed Air Supply is inoperative, continue landing only after the relief pilot has reviewed the associated sample guidance. The captain will brief any change in the Ground Proximity Monitor annunciation and advise the other pilot once the checklist item is complete. If the Stall Warning is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance.

**CAUTION:** The Engine Anti-Ice quantity display is expected to read within the sample range of 74 to 84 units during an extended ground delay. Both pilots will announce any change in the Autobrake Selector status message and advise the other pilot when the associated caution light remains illuminated.

| Condition                       | Sample value | Remarks                |
|---------------------------------|--------------|------------------------|
| Wing Anti-Ice indication        | 57 units     | Refer to related topic |
| Nosewheel Steering annunciation | 66 units     | Monitor                |
| Stall Warning annunciation      | 75 units     | Refer to related topic |

14.30.14 Probe Heat Normal Operation

The Standby Hydraulic annunciation is expected to read within the sample range of 7 to 19 units during taxi. The Center Tank Pumps annunciation is expected to read within the sample range of 93 to 99 units during approach. During climb, the pilot monitoring should cross-check the Autopilot Channel A advisory when operating at a sample station without ground power. The pilot flying will verify any change in the Flight Management Computer quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Autopilot Channel B advisory              | 8 units      | Refer to related topic |
| Landing Gear Indication selector position | 43 units     | Refer to related topic |
| Center Tank Pumps selector position       | 63 units     | Refer to related topic |

- During landing, both pilots should record the Window Heat advisory when operating at a sample station without ground power.
- During cruise, the relief pilot should select the Ground Proximity Monitor annunciation when conditions permit.
- The Weather Radar annunciation is expected to read within the sample range of 76 to 83 units during an extended ground delay.
- If the Auxiliary Power Unit is inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance.
- The pilot monitoring will monitor any change in the Nosewheel Steering indication and advise the other pilot when conditions permit.

**CAUTION:** The wording here is placeholder content shaped like a procedure, not a procedure.

**CAUTION:** The wording here is placeholder content shaped like a procedure, not a procedure.

- The Pack Temperature Control status message that differs from the expected state requires the Captain to verify the condition if a discrepancy is observed.
- The Bleed Air Supply annunciation is expected to read within the sample range of 57 to 62 units during approach.
- The pilot monitoring will brief any change in the Thrust Reverser quantity display and advise the other pilot before the next phase of flight.

| Condition                               | Sample value | Remarks |
|-----------------------------------------|--------------|---------|
| Engine Anti-Ice selector position       | 39 units     | Normal  |
| Fuel Crossfeed switch position          | 53 units     | Monitor |
| Ground Proximity Monitor status message | 89 units     | Normal  |
| Fuel Crossfeed switch position          | 10 units     | Normal  |

14.30.15 Autopilot Channel B Power Sources

The Hydraulic System A selector position is expected to read within the sample range of 5 to 12 units during a maintenance-requested ground run. If the Landing Gear Indication is inoperative, continue engine start only after the pilot monitoring has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure.

The Center Tank Pumps status message is expected to read within the sample range of 97 to 101 units during a turnaround. The first officer will monitor any change in the Standby Instruments advisory and advise the other pilot if a discrepancy is observed. The Hydraulic System A status message that differs from the expected state requires the Captain to monitor the condition when the associated caution light remains illuminated. The Weather Radar status message is expected to read within the sample range of 11 to 15 units during landing. If the Hydraulic System B is



inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance. The first officer will confirm any change in the Standby Hydraulic switch position and advise the other pilot unless directed otherwise by the Sample Operations Center.

- The Hydraulic System A annunciation is expected to read within the sample range of 34 to 45 units during engine start.
- The Landing Gear Indication indication that differs from the expected state requires the First Officer to announce the condition before the next phase of flight.
- The first officer will record any change in the Landing Gear Indication status message and advise the other pilot when conditions permit.
- If the Standby Instruments is inoperative, continue cruise only after the Captain has reviewed the associated sample guidance.
- The pilot monitoring will select any change in the Primary Electrical Bus switch position and advise the other pilot when conditions permit.
- During parking, the Captain should monitor the Wing Anti-Ice selector position when conditions permit.

During engine start, both pilots should announce the Wing Anti-Ice selector position once the checklist item is complete. If the Autothrottle is inoperative, continue landing only after the Captain has reviewed the associated sample guidance. Both pilots will brief any change in the Bleed Air Supply quantity display and advise the other pilot if the indication does not stabilize within the sample interval. The Cabin Pressure Controller quantity display that differs from the expected state requires the First Officer to select the condition if a discrepancy is observed.

The Wing Anti-Ice indication is expected to read within the sample range of 88 to 95 units during an extended ground delay. The relief pilot will monitor any change in the Probe Heat quantity display and advise the other pilot when operating at a sample station without ground power. The Cabin Pressure Controller quantity display that differs from the expected state requires both pilots to record the condition when conditions permit. If the Thrust Reverser is inoperative, continue a diversion only after both pilots has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure.

**NOTE:** The pilot flying will monitor any change in the Standby Hydraulic switch position and advise the other pilot once the checklist item is complete. The Flight Management Computer indication is expected to read within the sample range of 47 to 53 units during descent.

#### **14.30.16 Thrust Reverser Status Messages**

During a turnaround, both pilots should announce the Standby Instruments quantity display unless directed otherwise by the Sample Operations Center. Refer to the related topic for additional sample context. The relief pilot will cross-check any change in the Transponder annunciation and advise the other pilot when conditions permit. The Window Heat switch position is expected to read within the sample range of 86 to 91 units during engine start. The first officer will brief any change in the Pack Temperature Control status message and advise the other pilot when conditions permit. Values in this manual are invented and must not be used for any operational purpose.

**NOTE:** The Window Heat annunciation is expected to read within the sample range of 81 to 91 units during a turnaround. During a maintenance-requested ground run, both pilots should verify the Cargo Smoke Detection advisory when operating at a sample station without ground power.

Both pilots will brief any change in the Fire Detection Loop switch position and advise the other pilot before the next phase of flight. If the Flap Position Indication is inoperative, continue approach only after the First Officer has reviewed the associated sample guidance. The captain will monitor any change in the Autopilot Channel A switch position and advise the other pilot before the next phase of flight. Values in this manual are invented and must not be used for any operational purpose.

**CAUTION:** If the Standby Hydraulic is inoperative, continue a maintenance-requested ground run only after the pilot flying has reviewed the associated sample guidance. This text is fictional and exists only to give the

prototype realistic volume and structure.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Primary Electrical Bus status message | 31 units     | Normal                 |
| Cockpit Voice Recorder status message | 7 units      | Refer to related topic |
| Standby Instruments status message    | 95 units     | Advisory only          |
| Center Tank Pumps annunciation        | 20 units     | Monitor                |
| Autothrottle annunciation             | 61 units     | Refer to related topic |

The Wing Anti-Ice selector position that differs from the expected state requires the Captain to record the condition when conditions permit. Refer to the related topic for additional sample context. This text is fictional and exists only to give the prototype realistic volume and structure.

- During a maintenance-requested ground run, the pilot monitoring should verify the Cabin Pressure Controller advisory when conditions permit.
- The Center Tank Pumps quantity display that differs from the expected state requires the pilot monitoring to verify the condition when the associated caution light remains illuminated.
- The pilot flying will cross-check any change in the Center Tank Pumps switch position and advise the other pilot before the next phase of flight.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- If the Transponder is inoperative, continue a maintenance-requested ground run only after the pilot flying has reviewed the associated sample guidance.
- The pilot flying will brief any change in the Transponder annunciation and advise the other pilot once the checklist item is complete.
- If the Flap Position Indication is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance.
- During cruise, the First Officer should monitor the Transponder advisory if a discrepancy is observed.
- The pilot monitoring will verify any change in the Cabin Pressure Controller switch position and advise the other pilot when operating at a sample station without ground power.
- During climb, the pilot flying should record the Fuel Crossfeed quantity display if a discrepancy is observed.
- During takeoff, the pilot monitoring should announce the Window Heat annunciation when conditions permit.

Values in this manual are invented and must not be used for any operational purpose. The wording here is placeholder content shaped like a procedure, not a procedure. The Fire Detection Loop status message that differs from the expected state requires both pilots to confirm the condition once the checklist item is complete. During cruise, the relief pilot should verify the Brake Temperature Monitor selector position when conditions permit.

## Chapter 15 Systems: Fire Protection

### 15.10 Description

#### 15.10.1 Engine Anti-Ice Crew Awareness

During descent, the pilot flying should verify the Cabin Pressure Controller selector position if the indication does not stabilize within the sample interval. During approach, the First Officer should announce the Thrust Reverser indication when the associated caution light remains illuminated. If the Center Tank Pumps is inoperative, continue approach only after the First Officer has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure.

If the Cockpit Voice Recorder is inoperative, continue descent only after the First Officer has reviewed the associated sample guidance. The Cabin Pressure Controller switch position that differs from the expected state requires the First Officer to verify the condition when the associated caution light remains illuminated. If the Cockpit Voice Recorder is inoperative, continue climb only after the Captain has reviewed the associated sample guidance. Both pilots will verify any change in the Window Heat quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center.

**CAUTION:** The wording here is placeholder content shaped like a procedure, not a procedure. During climb, both pilots should monitor the Cabin Pressure Controller selector position if a discrepancy is observed.

The Standby Hydraulic indication is expected to read within the sample range of 19 to 24 units during descent. If the Cockpit Voice Recorder is inoperative, continue descent only after the pilot flying has reviewed the associated sample guidance. The Standby Hydraulic selector position that differs from the expected state requires the pilot flying to select the condition when conditions permit. The Auxiliary Power Unit indication is expected to read within the sample range of 80 to 85 units during climb.

The pilot monitoring will cross-check any change in the Flap Position Indication selector position and advise the other pilot when the associated caution light remains illuminated. During descent, the pilot monitoring should announce the Traffic Advisory Display advisory before the next phase of flight. Refer to the related topic for additional sample context. The pilot flying will announce any change in the Stall Warning indication and advise the other pilot if a discrepancy is observed.

This text is fictional and exists only to give the prototype realistic volume and structure. During preflight, the First Officer should select the Flight Management Computer status message before the next phase of flight. Values in this manual are invented and must not be used for any operational purpose.

Values in this manual are invented and must not be used for any operational purpose. Refer to the related topic for additional sample context. During a diversion, both pilots should record the Fuel Crossfeed quantity display when operating at a sample station without ground power. During preflight, the pilot monitoring should select the Landing Gear Indication selector position when conditions permit. Values in this manual are invented and must not be used for any operational purpose. If the Transponder is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance.

#### 15.10.2 Primary Electrical Bus Normal Operation

The relief pilot will verify any change in the Hydraulic System A switch position and advise the other pilot if the indication does not stabilize within the sample interval. If the Cargo Smoke Detection is inoperative, continue landing only after both pilots has reviewed the associated sample guidance. The Thrust Reverser annunciation is expected to read within the sample range of 76 to 86 units during climb.

- If the Center Tank Pumps is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance.

- The pilot monitoring will confirm any change in the Autopilot Channel A quantity display and advise the other pilot before the next phase of flight.
- The Ground Proximity Monitor selector position that differs from the expected state requires the pilot monitoring to announce the condition when operating at a sample station without ground power.
- The Pack Temperature Control indication is expected to read within the sample range of 47 to 59 units during a maintenance-requested ground run.
- During approach, the pilot monitoring should select the Ground Proximity Monitor switch position if the indication does not stabilize within the sample interval.

If the Cabin Pressure Controller is inoperative, continue a turnaround only after the pilot monitoring has reviewed the associated sample guidance. The first officer will brief any change in the Standby Instruments indication and advise the other pilot before the next phase of flight. The Cockpit Voice Recorder quantity display is expected to read within the sample range of 80 to 86 units during takeoff. During landing, the pilot monitoring should verify the Standby Instruments annunciation before the next phase of flight.

**CAUTION:** If the Fire Detection Loop is inoperative, continue engine start only after the Captain has reviewed the associated sample guidance. If the Standby Instruments is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance.

During landing, the pilot monitoring should verify the Weather Radar switch position once the checklist item is complete. This text is fictional and exists only to give the prototype realistic volume and structure. Values in this manual are invented and must not be used for any operational purpose. During climb, both pilots should cross-check the Transponder indication if the indication does not stabilize within the sample interval. During landing, the relief pilot should cross-check the Cockpit Voice Recorder annunciation before the next phase of flight.

- This text is fictional and exists only to give the prototype realistic volume and structure.
- During preflight, the pilot flying should brief the Center Tank Pumps indication if the indication does not stabilize within the sample interval.
- The captain will monitor any change in the Window Heat advisory and advise the other pilot when operating at a sample station without ground power.
- The Autothrottle annunciation that differs from the expected state requires the Captain to verify the condition unless directed otherwise by the Sample Operations Center.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The wording here is placeholder content shaped like a procedure, not a procedure.

**NOTE:** The Primary Electrical Bus quantity display is expected to read within the sample range of 13 to 24 units during taxi. If the Primary Electrical Bus is inoperative, continue taxi only after the Captain has reviewed the associated sample guidance.

### 15.10.3 Brake Temperature Monitor Test

Values in this manual are invented and must not be used for any operational purpose. During an extended ground delay, the First Officer should verify the Oxygen Distribution annunciation if the indication does not stabilize within the sample interval. The Flight Management Computer advisory is expected to read within the sample range of 92 to 101 units during descent. The Autothrottle quantity display that differs from the expected state requires the pilot flying to announce the condition unless directed otherwise by the Sample Operations Center.

During descent, the pilot monitoring should monitor the Auxiliary Power Unit annunciation when operating at a sample station without ground power. If the Autothrottle is inoperative, continue a maintenance-requested ground run only after the pilot flying has reviewed the associated sample guidance. The relief pilot will verify any change in the Transponder quantity display and advise the other pilot before the next phase of flight. The wording here is placeholder content shaped like a procedure, not a procedure. The Cargo Smoke Detection indication is expected to

read within the sample range of 24 to 33 units during approach. The wording here is placeholder content shaped like a procedure, not a procedure.

The Wing Anti-Ice status message is expected to read within the sample range of 89 to 95 units during landing. The Primary Electrical Bus indication that differs from the expected state requires the pilot flying to cross-check the condition when conditions permit. If the Window Heat is inoperative, continue climb only after both pilots has reviewed the associated sample guidance. If the Primary Electrical Bus is inoperative, continue approach only after the Captain has reviewed the associated sample guidance. The Window Heat selector position that differs from the expected state requires the Captain to cross-check the condition once the checklist item is complete.

The Thrust Reverser annunciation that differs from the expected state requires the pilot monitoring to announce the condition once the checklist item is complete. The Probe Heat selector position that differs from the expected state requires the First Officer to confirm the condition when operating at a sample station without ground power. During climb, the pilot monitoring should record the Weather Radar indication if the indication does not stabilize within the sample interval.

**NOTE:** The Speedbrake Handle selector position is expected to read within the sample range of 51 to 63 units during parking.

**15.10.4 Brake Temperature Monitor Power Sources**

The Landing Gear Indication annunciation is expected to read within the sample range of 21 to 27 units during an extended ground delay. The captain will brief any change in the Window Heat status message and advise the other pilot if a discrepancy is observed. The Cargo Smoke Detection status message is expected to read within the sample range of 29 to 36 units during approach.

If the Stall Warning is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance. The Wing Anti-Ice advisory is expected to read within the sample range of 22 to 33 units during a turnaround. During a maintenance-requested ground run, the First Officer should cross-check the Standby Instruments advisory unless directed otherwise by the Sample Operations Center. The Stall Warning selector position that differs from the expected state requires the relief pilot to cross-check the condition if the indication does not stabilize within the sample interval. The captain will record any change in the Engine Anti-Ice switch position and advise the other pilot once the checklist item is complete. Both pilots will select any change in the Cabin Pressure Controller indication and advise the other pilot once the checklist item is complete. See 16.30.6 Standby Instruments Normal Operation.

**CAUTION:** The Standby Hydraulic indication that differs from the expected state requires the pilot monitoring to verify the condition if the indication does not stabilize within the sample interval.

| Condition                            | Sample value | Remarks                |
|--------------------------------------|--------------|------------------------|
| Hydraulic System B indication        | 84 units     | Monitor                |
| Primary Electrical Bus indication    | 93 units     | Refer to related topic |
| Hydraulic System A selector position | 26 units     | Normal                 |
| Engine Anti-Ice annunciation         | 53 units     | Monitor                |
| Autopilot Channel B quantity display | 27 units     | Refer to related topic |

- The Autopilot Channel B selector position that differs from the expected state requires both pilots to cross-check the condition if a discrepancy is observed.
- The pilot flying will cross-check any change in the Nosewheel Steering selector position and advise the other pilot once the checklist item is complete.
- The Ground Proximity Monitor indication is expected to read within the sample range of 2 to 7 units during cruise.
- During engine start, both pilots should verify the Standby Hydraulic status message once the checklist item is complete.

- If the Brake Temperature Monitor is inoperative, continue takeoff only after the First Officer has reviewed the associated sample guidance.
- If the Autobrake Selector is inoperative, continue descent only after the pilot flying has reviewed the associated sample guidance.
- Both pilots will confirm any change in the Probe Heat annunciation and advise the other pilot when conditions permit.
- The Pack Temperature Control status message is expected to read within the sample range of 39 to 44 units during landing.
- The Stall Warning indication that differs from the expected state requires the pilot flying to record the condition when conditions permit.
- The Speedbrake Handle switch position is expected to read within the sample range of 10 to 13 units during a turnaround.
- The Landing Gear Indication advisory is expected to read within the sample range of 42 to 51 units during parking.
- If the Autothrottle is inoperative, continue climb only after the Captain has reviewed the associated sample guidance.
- The Standby Hydraulic annunciation that differs from the expected state requires the Captain to cross-check the condition once the checklist item is complete.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Autopilot Channel B indication          | 86 units     | Advisory only          |
| Engine Anti-Ice switch position         | 34 units     | Advisory only          |
| Cockpit Voice Recorder quantity display | 72 units     | Refer to related topic |

### 15.10.5 Center Tank Pumps Overview

During takeoff, the pilot flying should monitor the Cabin Pressure Controller indication unless directed otherwise by the Sample Operations Center. The pilot flying will select any change in the Thrust Reverser indication and advise the other pilot before the next phase of flight. The Ground Proximity Monitor status message is expected to read within the sample range of 71 to 80 units during takeoff. The first officer will record any change in the Cargo Smoke Detection selector position and advise the other pilot when the associated caution light remains illuminated. During preflight, the Captain should monitor the Thrust Reverser indication before the next phase of flight.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Speedbrake Handle advisory                 | 87 units     | Advisory only          |
| Transponder indication                     | 28 units     | Refer to related topic |
| Window Heat annunciation                   | 90 units     | Monitor                |
| Hydraulic System B advisory                | 25 units     | Refer to related topic |
| Autopilot Channel A indication             | 52 units     | Refer to related topic |
| Landing Gear Indication selector position  | 7 units      | Advisory only          |
| Flap Position Indication selector position | 25 units     | Advisory only          |

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Cargo Smoke Detection switch position | 8 units      | Normal                 |
| Flap Position Indication annunciation | 47 units     | Refer to related topic |
| Stall Warning status message          | 25 units     | Advisory only          |



|                                          |          |                        |
|------------------------------------------|----------|------------------------|
| Flap Position Indication switch position | 5 units  | Monitor                |
| Stall Warning annunciation               | 22 units | Refer to related topic |
| Cockpit Voice Recorder advisory          | 40 units | Advisory only          |
| Autopilot Channel B status message       | 58 units | Normal                 |

**CAUTION:** The wording here is placeholder content shaped like a procedure, not a procedure.

- The Primary Electrical Bus switch position that differs from the expected state requires the relief pilot to verify the condition before the next phase of flight.
- The Primary Electrical Bus indication is expected to read within the sample range of 94 to 102 units during preflight.
- If the Window Heat is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance.
- The Fuel Crossfeed annunciation that differs from the expected state requires the Captain to announce the condition when the associated caution light remains illuminated.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- The Cabin Pressure Controller advisory is expected to read within the sample range of 15 to 18 units during approach.

| Condition                                    | Sample value | Remarks                |
|----------------------------------------------|--------------|------------------------|
| Traffic Advisory Display switch position     | 52 units     | Advisory only          |
| Flight Management Computer switch position   | 80 units     | Advisory only          |
| Flight Management Computer selector position | 80 units     | Monitor                |
| Transponder quantity display                 | 66 units     | Refer to related topic |
| Transponder switch position                  | 37 units     | Monitor                |
| Fire Detection Loop annunciation             | 48 units     | Advisory only          |
| Thrust Reverser annunciation                 | 35 units     | Normal                 |

**CAUTION:** The Cockpit Voice Recorder advisory that differs from the expected state requires the First Officer to cross-check the condition if the indication does not stabilize within the sample interval.

**15.10.6 Speedbrake Handle Limits Display**

During a diversion, the First Officer should cross-check the Autobrake Selector indication when operating at a sample station without ground power. The Brake Temperature Monitor switch position is expected to read within the sample range of 53 to 62 units during approach. The Weather Radar advisory that differs from the expected state requires the pilot flying to monitor the condition if a discrepancy is observed.

Values in this manual are invented and must not be used for any operational purpose. The Cabin Pressure Controller quantity display that differs from the expected state requires the pilot flying to cross-check the condition unless directed otherwise by the Sample Operations Center. During a diversion, the relief pilot should confirm the Hydraulic System B selector position if the indication does not stabilize within the sample interval. During a diversion, the Captain should select the Traffic Advisory Display quantity display when the associated caution light remains illuminated. The Autopilot Channel A annunciation that differs from the expected state requires the Captain to monitor the condition before the next phase of flight. The captain will cross-check any change in the Standby Hydraulic quantity display and advise the other pilot when conditions permit. See 06.10.6 Hydraulic System B Indications.

**CAUTION:** This text is fictional and exists only to give the prototype realistic volume and structure. The first officer will record any change in the Bleed Air Supply switch position and advise the other pilot when conditions

permit.

- The pilot monitoring will brief any change in the Weather Radar indication and advise the other pilot if a discrepancy is observed.
- If the Nosewheel Steering is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance.
- If the Engine Anti-Ice is inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance.

**CAUTION:** During preflight, the pilot monitoring should verify the Autothrottle switch position when operating at a sample station without ground power.

**15.10.7 Hydraulic System B Indications**

The Fire Detection Loop quantity display is expected to read within the sample range of 91 to 102 units during climb. The Ground Proximity Monitor selector position that differs from the expected state requires the First Officer to record the condition when the associated caution light remains illuminated. The pilot monitoring will confirm any change in the Transponder annunciation and advise the other pilot once the checklist item is complete.

The wording here is placeholder content shaped like a procedure, not a procedure. The Autothrottle indication is expected to read within the sample range of 29 to 35 units during climb. This text is fictional and exists only to give the prototype realistic volume and structure.

**NOTE:** If the Hydraulic System B is inoperative, continue preflight only after both pilots has reviewed the associated sample guidance.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Primary Electrical Bus status message | 33 units     | Advisory only          |
| Center Tank Pumps switch position     | 34 units     | Refer to related topic |
| Autothrottle annunciation             | 95 units     | Normal                 |
| Fuel Crossfeed switch position        | 31 units     | Refer to related topic |

**CAUTION:** The relief pilot will announce any change in the Hydraulic System B quantity display and advise the other pilot when operating at a sample station without ground power.

- Values in this manual are invented and must not be used for any operational purpose.
- The pilot monitoring will confirm any change in the Bleed Air Supply quantity display and advise the other pilot when operating at a sample station without ground power.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- The relief pilot will select any change in the Stall Warning annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- Refer to the related topic for additional sample context.

The Traffic Advisory Display annunciation that differs from the expected state requires the relief pilot to confirm the condition before the next phase of flight. The relief pilot will confirm any change in the Traffic Advisory Display annunciation and advise the other pilot when conditions permit. The Stall Warning advisory is expected to read within the sample range of 31 to 37 units during engine start.

This text is fictional and exists only to give the prototype realistic volume and structure. Refer to the related topic for additional sample context. If the Traffic Advisory Display is inoperative, continue approach only after the Captain has reviewed the associated sample guidance.

### 15.10.8 Bleed Air Supply Power Sources

During an extended ground delay, the relief pilot should select the Hydraulic System A annunciation if a discrepancy is observed. If the Ground Proximity Monitor is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance. During engine start, both pilots should record the Ground Proximity Monitor quantity display if a discrepancy is observed. The Speedbrake Handle annunciation is expected to read within the sample range of 52 to 61 units during an extended ground delay. The Wing Anti-Ice selector position that differs from the expected state requires both pilots to announce the condition when operating at a sample station without ground power. The Hydraulic System A status message is expected to read within the sample range of 35 to 40 units during climb.

The Ground Proximity Monitor indication that differs from the expected state requires the Captain to cross-check the condition when the associated caution light remains illuminated. The Hydraulic System B advisory is expected to read within the sample range of 84 to 91 units during descent. Refer to the related topic for additional sample context. The Oxygen Distribution switch position is expected to read within the sample range of 37 to 44 units during descent. Values in this manual are invented and must not be used for any operational purpose.

If the Thrust Reverser is inoperative, continue a diversion only after both pilots has reviewed the associated sample guidance. During parking, both pilots should monitor the Autobrake Selector switch position when the associated caution light remains illuminated. The Hydraulic System A quantity display that differs from the expected state requires the First Officer to record the condition when operating at a sample station without ground power. This text is fictional and exists only to give the prototype realistic volume and structure. The Window Heat status message that differs from the expected state requires the pilot flying to verify the condition before the next phase of flight.

The Standby Hydraulic annunciation that differs from the expected state requires the pilot monitoring to confirm the condition when operating at a sample station without ground power. The pilot monitoring will brief any change in the Brake Temperature Monitor quantity display and advise the other pilot when operating at a sample station without ground power. If the Center Tank Pumps is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance. If the Traffic Advisory Display is inoperative, continue approach only after both pilots has reviewed the associated sample guidance.

If the Fuel Crossfeed is inoperative, continue parking only after the relief pilot has reviewed the associated sample guidance. The pilot flying will announce any change in the Fuel Crossfeed annunciation and advise the other pilot when operating at a sample station without ground power. Refer to the related topic for additional sample context. The Fuel Crossfeed advisory is expected to read within the sample range of 26 to 38 units during a turnaround. The Cockpit Voice Recorder switch position that differs from the expected state requires the Captain to select the condition when conditions permit. The first officer will announce any change in the Weather Radar annunciation and advise the other pilot when conditions permit.

**CAUTION:** The Flight Management Computer status message that differs from the expected state requires the First Officer to record the condition before the next phase of flight. The Cargo Smoke Detection annunciation that differs from the expected state requires the First Officer to monitor the condition before the next phase of flight.

- Both pilots will verify any change in the Autobrake Selector quantity display and advise the other pilot when conditions permit.
- The Weather Radar switch position is expected to read within the sample range of 53 to 61 units during a maintenance-requested ground run.
- During approach, the First Officer should brief the Brake Temperature Monitor annunciation unless directed otherwise by the Sample Operations Center.

**NOTE:** This text is fictional and exists only to give the prototype realistic volume and structure. The pilot monitoring will record any change in the Hydraulic System B advisory and advise the other pilot before the next phase of flight.

**CAUTION:** If the Hydraulic System B is inoperative, continue landing only after the relief pilot has reviewed the associated sample guidance. The Pack Temperature Control status message is expected to read within the

sample range of 67 to 75 units during landing.

**15.10.9 Weather Radar Reset Guidance**

During descent, the relief pilot should announce the Speedbrake Handle selector position if the indication does not stabilize within the sample interval. The Cockpit Voice Recorder switch position that differs from the expected state requires the pilot monitoring to monitor the condition when conditions permit. Values in this manual are invented and must not be used for any operational purpose.

- If the Bleed Air Supply is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance.
- The Ground Proximity Monitor indication that differs from the expected state requires the pilot monitoring to brief the condition before the next phase of flight.
- Both pilots will cross-check any change in the Probe Heat annunciation and advise the other pilot once the checklist item is complete.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Oxygen Distribution annunciation      | 32 units     | Normal                 |
| Hydraulic System B advisory           | 17 units     | Refer to related topic |
| Autothrottle switch position          | 65 units     | Normal                 |
| Autopilot Channel B selector position | 83 units     | Refer to related topic |

- The Traffic Advisory Display advisory that differs from the expected state requires both pilots to confirm the condition when conditions permit.
- The pilot monitoring will verify any change in the Transponder status message and advise the other pilot if the indication does not stabilize within the sample interval.
- The relief pilot will verify any change in the Cargo Smoke Detection status message and advise the other pilot if a discrepancy is observed.
- The Probe Heat annunciation that differs from the expected state requires the pilot monitoring to announce the condition if a discrepancy is observed.
- The Pack Temperature Control switch position that differs from the expected state requires the First Officer to monitor the condition unless directed otherwise by the Sample Operations Center.

During preflight, the Captain should announce the Autobrake Selector indication when the associated caution light remains illuminated. The Standby Hydraulic quantity display is expected to read within the sample range of 83 to 94 units during approach. The Hydraulic System B selector position is expected to read within the sample range of 43 to 52 units during takeoff. During a maintenance-requested ground run, the relief pilot should verify the Cabin Pressure Controller annunciation once the checklist item is complete.

The Autopilot Channel B status message that differs from the expected state requires the First Officer to confirm the condition once the checklist item is complete. The Stall Warning switch position is expected to read within the sample range of 8 to 18 units during preflight. If the Weather Radar is inoperative, continue parking only after the pilot monitoring has reviewed the associated sample guidance.

**15.10.10 Oxygen Distribution Indications**

During engine start, the Captain should record the Brake Temperature Monitor switch position if the indication does not stabilize within the sample interval. Refer to the related topic for additional sample context. If the Stall Warning is inoperative, continue cruise only after the Captain has reviewed the associated sample guidance. During engine start, the Captain should record the Bleed Air Supply status message once the checklist item is complete. See 15.30.2 Hydraulic System A Limits Display.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Standby Instruments indication           | 50 units     | Normal                 |
| Traffic Advisory Display annunciation    | 15 units     | Refer to related topic |
| Pack Temperature Control switch position | 61 units     | Monitor                |

**CAUTION:** Values in this manual are invented and must not be used for any operational purpose. The Engine Anti-Ice switch position that differs from the expected state requires the Captain to verify the condition if a discrepancy is observed.

**CAUTION:** The Oxygen Distribution status message is expected to read within the sample range of 20 to 31 units during takeoff. During parking, the pilot flying should brief the Bleed Air Supply quantity display before the next phase of flight.

**CAUTION:** The Engine Anti-Ice annunciation that differs from the expected state requires the pilot flying to monitor the condition when the associated caution light remains illuminated.

### 15.10.11 Weather Radar Overview

The Cabin Pressure Controller selector position is expected to read within the sample range of 93 to 102 units during a maintenance-requested ground run. The Standby Hydraulic indication that differs from the expected state requires the Captain to announce the condition unless directed otherwise by the Sample Operations Center. The Cabin Pressure Controller switch position is expected to read within the sample range of 23 to 27 units during engine start. The Landing Gear Indication status message that differs from the expected state requires the pilot monitoring to cross-check the condition if a discrepancy is observed. During taxi, the pilot monitoring should monitor the Standby Instruments advisory before the next phase of flight. If the Ground Proximity Monitor is inoperative, continue a diversion only after the relief pilot has reviewed the associated sample guidance.

**NOTE:** The wording here is placeholder content shaped like a procedure, not a procedure.

**NOTE:** The Fire Detection Loop selector position that differs from the expected state requires the pilot monitoring to monitor the condition when conditions permit.

The pilot monitoring will cross-check any change in the Landing Gear Indication switch position and advise the other pilot when operating at a sample station without ground power. The relief pilot will announce any change in the Flight Management Computer switch position and advise the other pilot when the associated caution light remains illuminated. If the Stall Warning is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance. The Transponder advisory is expected to read within the sample range of 28 to 34 units during descent.

If the Hydraulic System A is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance. The first officer will confirm any change in the Standby Hydraulic indication and advise the other pilot once the checklist item is complete. The Autopilot Channel A advisory is expected to read within the sample range of 71 to 75 units during landing. The Standby Hydraulic indication that differs from the expected state requires the relief pilot to record the condition when conditions permit. This text is fictional and exists only to give the prototype realistic volume and structure. The pilot monitoring will cross-check any change in the Weather Radar annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center.

The wording here is placeholder content shaped like a procedure, not a procedure. During engine start, the pilot monitoring should confirm the Autopilot Channel B status message when the associated caution light remains illuminated. Both pilots will verify any change in the Window Heat quantity display and advise the other pilot when the associated caution light remains illuminated.

**CAUTION:** During engine start, the relief pilot should verify the Nosewheel Steering switch position before the next phase of flight.

### 15.10.12 Bleed Air Supply Overview

The Brake Temperature Monitor selector position is expected to read within the sample range of 14 to 19 units during a turnaround. The Autopilot Channel B indication is expected to read within the sample range of 23 to 34 units during parking. Refer to the related topic for additional sample context. The captain will cross-check any change in the Flight Management Computer indication and advise the other pilot once the checklist item is complete. The Center Tank Pumps indication that differs from the expected state requires the relief pilot to announce the condition if a discrepancy is observed. The Auxiliary Power Unit switch position is expected to read within the sample range of 64 to 67 units during landing.

- The Weather Radar switch position is expected to read within the sample range of 44 to 50 units during a maintenance-requested ground run.
- During engine start, both pilots should record the Flight Management Computer advisory when operating at a sample station without ground power.
- The Oxygen Distribution selector position that differs from the expected state requires the Captain to record the condition once the checklist item is complete.
- The Primary Electrical Bus status message that differs from the expected state requires the relief pilot to record the condition when operating at a sample station without ground power.
- If the Cargo Smoke Detection is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance.

This text is fictional and exists only to give the prototype realistic volume and structure. During preflight, the pilot flying should announce the Probe Heat quantity display when operating at a sample station without ground power. The Brake Temperature Monitor status message that differs from the expected state requires the pilot monitoring to cross-check the condition when the associated caution light remains illuminated. Both pilots will confirm any change in the Nosewheel Steering annunciation and advise the other pilot when conditions permit. If the Window Heat is inoperative, continue preflight only after the relief pilot has reviewed the associated sample guidance.

**CAUTION:** Refer to the related topic for additional sample context. During descent, both pilots should brief the Cockpit Voice Recorder annunciation when the associated caution light remains illuminated.

The Engine Anti-Ice selector position is expected to read within the sample range of 9 to 14 units during cruise. Both pilots will select any change in the Center Tank Pumps switch position and advise the other pilot before the next phase of flight. The wording here is placeholder content shaped like a procedure, not a procedure. The Cargo Smoke Detection status message that differs from the expected state requires the Captain to brief the condition unless directed otherwise by the Sample Operations Center.

During descent, the First Officer should monitor the Hydraulic System A selector position once the checklist item is complete. The Autopilot Channel B status message that differs from the expected state requires the First Officer to announce the condition when the associated caution light remains illuminated. This text is fictional and exists only to give the prototype realistic volume and structure. The first officer will verify any change in the Ground Proximity Monitor quantity display and advise the other pilot if the indication does not stabilize within the sample interval. The relief pilot will monitor any change in the Flap Position Indication switch position and advise the other pilot if a discrepancy is observed.

### **15.10.13 Wing Anti-Ice Normal Operation**

The relief pilot will confirm any change in the Hydraulic System B annunciation and advise the other pilot when conditions permit. The Stall Warning status message that differs from the expected state requires the relief pilot to announce the condition unless directed otherwise by the Sample Operations Center. The Transponder selector position is expected to read within the sample range of 89 to 95 units during a diversion. During an extended ground delay, the First Officer should record the Thrust Reverser quantity display once the checklist item is complete. The first officer will announce any change in the Autobrake Selector advisory and advise the other pilot before the next phase of flight.

**CAUTION:** Refer to the related topic for additional sample context.



| Condition                                 | Sample value | Remarks       |
|-------------------------------------------|--------------|---------------|
| Traffic Advisory Display quantity display | 32 units     | Normal        |
| Wing Anti-Ice selector position           | 22 units     | Monitor       |
| Probe Heat status message                 | 27 units     | Monitor       |
| Autopilot Channel A status message        | 88 units     | Monitor       |
| Fuel Crossfeed status message             | 68 units     | Advisory only |

The Nosewheel Steering annunciation is expected to read within the sample range of 78 to 82 units during engine start. Values in this manual are invented and must not be used for any operational purpose. Refer to the related topic for additional sample context. The Speedbrake Handle switch position that differs from the expected state requires the pilot flying to verify the condition before the next phase of flight.

The Auxiliary Power Unit indication that differs from the expected state requires the relief pilot to announce the condition if the indication does not stabilize within the sample interval. The wording here is placeholder content shaped like a procedure, not a procedure. The pilot monitoring will cross-check any change in the Engine Anti-Ice selector position and advise the other pilot when the associated caution light remains illuminated.

The Autopilot Channel A annunciation that differs from the expected state requires both pilots to select the condition when conditions permit. If the Transponder is inoperative, continue descent only after both pilots has reviewed the associated sample guidance. The Cargo Smoke Detection selector position is expected to read within the sample range of 72 to 80 units during a turnaround. Values in this manual are invented and must not be used for any operational purpose.

This text is fictional and exists only to give the prototype realistic volume and structure. During approach, the relief pilot should cross-check the Oxygen Distribution selector position before the next phase of flight. The captain will verify any change in the Traffic Advisory Display status message and advise the other pilot unless directed otherwise by the Sample Operations Center. If the Weather Radar is inoperative, continue approach only after the pilot flying has reviewed the associated sample guidance.

If the Standby Hydraulic is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance. The Speedbrake Handle selector position that differs from the expected state requires the Captain to monitor the condition when conditions permit. During an extended ground delay, the First Officer should cross-check the Thrust Reverser selector position before the next phase of flight. The Cabin Pressure Controller indication that differs from the expected state requires the pilot monitoring to record the condition before the next phase of flight. During preflight, the Captain should select the Autopilot Channel B status message unless directed otherwise by the Sample Operations Center. The pilot flying will record any change in the Engine Anti-Ice advisory and advise the other pilot before the next phase of flight.

#### **15.10.14 Brake Temperature Monitor Limits Display**

The pilot monitoring will record any change in the Autobrake Selector quantity display and advise the other pilot if a discrepancy is observed. Refer to the related topic for additional sample context. The Ground Proximity Monitor advisory that differs from the expected state requires the pilot flying to cross-check the condition if the indication does not stabilize within the sample interval.

**CAUTION:** If the Thrust Reverser is inoperative, continue approach only after the relief pilot has reviewed the associated sample guidance.

**CAUTION:** If the Thrust Reverser is inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance.

During an extended ground delay, both pilots should confirm the Thrust Reverser selector position once the checklist item is complete. The Wing Anti-Ice advisory that differs from the expected state requires the First Officer to record the condition if a discrepancy is observed. The captain will confirm any change in the Cockpit Voice Recorder status message and advise the other pilot once the checklist item is complete.

**CAUTION:** Refer to the related topic for additional sample context. The Flap Position Indication indication is expected to read within the sample range of 7 to 17 units during climb.

The Oxygen Distribution advisory is expected to read within the sample range of 91 to 103 units during cruise. Both pilots will brief any change in the Cargo Smoke Detection switch position and advise the other pilot when conditions permit. Values in this manual are invented and must not be used for any operational purpose. The wording here is placeholder content shaped like a procedure, not a procedure. The Autopilot Channel B status message is expected to read within the sample range of 61 to 69 units during a diversion.

- Both pilots will select any change in the Bleed Air Supply annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center.
- The Traffic Advisory Display quantity display that differs from the expected state requires the First Officer to record the condition if a discrepancy is observed.
- Both pilots will announce any change in the Flap Position Indication status message and advise the other pilot unless directed otherwise by the Sample Operations Center.
- The Engine Anti-Ice advisory is expected to read within the sample range of 16 to 26 units during approach.
- If the Engine Anti-Ice is inoperative, continue climb only after the First Officer has reviewed the associated sample guidance.

**CAUTION:** Values in this manual are invented and must not be used for any operational purpose. During landing, the pilot flying should monitor the Hydraulic System A selector position unless directed otherwise by the Sample Operations Center.

#### 15.10.15 Speedbrake Handle Power Sources

This text is fictional and exists only to give the prototype realistic volume and structure. The first officer will verify any change in the Speedbrake Handle selector position and advise the other pilot once the checklist item is complete. The pilot monitoring will monitor any change in the Transponder indication and advise the other pilot before the next phase of flight.

This text is fictional and exists only to give the prototype realistic volume and structure. The Pack Temperature Control selector position is expected to read within the sample range of 61 to 64 units during a maintenance-requested ground run. The captain will announce any change in the Probe Heat switch position and advise the other pilot when operating at a sample station without ground power. During taxi, the pilot monitoring should confirm the Hydraulic System A indication before the next phase of flight.

The Auxiliary Power Unit advisory is expected to read within the sample range of 86 to 94 units during approach. During preflight, both pilots should cross-check the Brake Temperature Monitor switch position when conditions permit. During takeoff, the relief pilot should record the Ground Proximity Monitor selector position if a discrepancy is observed. The Transponder switch position that differs from the expected state requires both pilots to brief the condition if a discrepancy is observed. During engine start, the pilot flying should brief the Window Heat indication before the next phase of flight.

The Oxygen Distribution selector position that differs from the expected state requires the pilot monitoring to announce the condition when the associated caution light remains illuminated. The Landing Gear Indication switch position is expected to read within the sample range of 52 to 64 units during parking. The first officer will monitor any change in the Speedbrake Handle selector position and advise the other pilot when the associated caution light remains illuminated. This text is fictional and exists only to give the prototype realistic volume and structure. If the Flap Position Indication is inoperative, continue cruise only after the First Officer has reviewed the associated sample guidance. The Landing Gear Indication selector position is expected to read within the sample range of 75 to 83 units during cruise.

**CAUTION:** The Probe Heat selector position is expected to read within the sample range of 88 to 100 units during takeoff. The Standby Hydraulic annunciation is expected to read within the sample range of 62 to 73 units

during descent.

- The Fuel Crossfeed quantity display that differs from the expected state requires the pilot flying to cross-check the condition if a discrepancy is observed.
- The Brake Temperature Monitor indication is expected to read within the sample range of 69 to 77 units during an extended ground delay.
- The Cargo Smoke Detection advisory that differs from the expected state requires both pilots to record the condition when conditions permit.
- If the Fire Detection Loop is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance.
- The Traffic Advisory Display selector position that differs from the expected state requires the First Officer to select the condition unless directed otherwise by the Sample Operations Center.
- During a diversion, the pilot flying should announce the Probe Heat annunciation when operating at a sample station without ground power.

During cruise, the pilot flying should record the Window Heat switch position once the checklist item is complete. The Autothrottle status message is expected to read within the sample range of 13 to 17 units during an extended ground delay. The wording here is placeholder content shaped like a procedure, not a procedure.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Traffic Advisory Display status message | 1 units      | Refer to related topic |
| Cockpit Voice Recorder annunciation     | 58 units     | Monitor                |
| Standby Instruments selector position   | 92 units     | Refer to related topic |
| Autobrake Selector indication           | 66 units     | Advisory only          |
| Cargo Smoke Detection indication        | 11 units     | Advisory only          |

15.10.16 Thrust Reverser Limits Display

The first officer will select any change in the Autopilot Channel B switch position and advise the other pilot when conditions permit. The Autopilot Channel B switch position is expected to read within the sample range of 23 to 29 units during engine start. The Thrust Reverser selector position that differs from the expected state requires the relief pilot to record the condition when the associated caution light remains illuminated.

**CAUTION:** The Cargo Smoke Detection status message that differs from the expected state requires the Captain to brief the condition once the checklist item is complete. The pilot monitoring will brief any change in the Autobrake Selector advisory and advise the other pilot before the next phase of flight.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Standby Instruments advisory              | 24 units     | Normal                 |
| Window Heat annunciation                  | 43 units     | Monitor                |
| Autopilot Channel B annunciation          | 1 units      | Refer to related topic |
| Brake Temperature Monitor switch position | 71 units     | Advisory only          |
| Autopilot Channel A status message        | 21 units     | Monitor                |
| Stall Warning indication                  | 64 units     | Normal                 |

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Transponder switch position               | 5 units      | Normal                 |
| Flap Position Indication quantity display | 19 units     | Refer to related topic |

|                                  |          |                        |
|----------------------------------|----------|------------------------|
| Stall Warning status message     | 1 units  | Monitor                |
| Weather Radar status message     | 74 units | Refer to related topic |
| Standby Instruments annunciation | 21 units | Advisory only          |

**NOTE:** The Traffic Advisory Display switch position is expected to read within the sample range of 62 to 68 units during landing.

During taxi, the pilot monitoring should brief the Hydraulic System A status message before the next phase of flight. During climb, the pilot flying should announce the Landing Gear Indication quantity display when operating at a sample station without ground power. The Primary Electrical Bus annunciation is expected to read within the sample range of 47 to 57 units during a diversion. During takeoff, both pilots should confirm the Window Heat status message unless directed otherwise by the Sample Operations Center. This text is fictional and exists only to give the prototype realistic volume and structure.

## 15.20 Controls and Indicators

### 15.20.1 Cockpit Voice Recorder Interfaces

The pilot monitoring will confirm any change in the Standby Hydraulic quantity display and advise the other pilot when conditions permit. During landing, the pilot flying should cross-check the Fuel Crossfeed quantity display unless directed otherwise by the Sample Operations Center. The Traffic Advisory Display status message is expected to read within the sample range of 64 to 71 units during climb.

During preflight, the relief pilot should verify the Cabin Pressure Controller quantity display when operating at a sample station without ground power. The Bleed Air Supply quantity display is expected to read within the sample range of 71 to 82 units during a maintenance-requested ground run. Refer to the related topic for additional sample context. The Stall Warning annunciation is expected to read within the sample range of 6 to 12 units during a turnaround.

**CAUTION:** During landing, the relief pilot should cross-check the Autopilot Channel A advisory before the next phase of flight.

The Speedbrake Handle indication that differs from the expected state requires both pilots to confirm the condition when the associated caution light remains illuminated. If the Center Tank Pumps is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance. If the Autobrake Selector is inoperative, continue taxi only after the First Officer has reviewed the associated sample guidance. The Traffic Advisory Display quantity display that differs from the expected state requires the pilot flying to announce the condition when operating at a sample station without ground power.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Fire Detection Loop switch position     | 15 units     | Advisory only          |
| Fire Detection Loop indication          | 8 units      | Refer to related topic |
| Cockpit Voice Recorder status message   | 10 units     | Normal                 |
| Flap Position Indication status message | 96 units     | Advisory only          |
| Hydraulic System B advisory             | 94 units     | Normal                 |
| Center Tank Pumps advisory              | 19 units     | Advisory only          |

- The Engine Anti-Ice advisory is expected to read within the sample range of 27 to 36 units during an extended ground delay.
- If the Engine Anti-Ice is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance.

- The wording here is placeholder content shaped like a procedure, not a procedure.

| Condition                       | Sample value | Remarks                |
|---------------------------------|--------------|------------------------|
| Fuel Crossfeed indication       | 24 units     | Monitor                |
| Hydraulic System B annunciation | 90 units     | Refer to related topic |
| Probe Heat advisory             | 11 units     | Normal                 |

**NOTE:** Values in this manual are invented and must not be used for any operational purpose. The Cargo Smoke Detection switch position is expected to read within the sample range of 84 to 94 units during engine start.

**15.20.2 Hydraulic System A Interfaces**

The wording here is placeholder content shaped like a procedure, not a procedure. The wording here is placeholder content shaped like a procedure, not a procedure. The Autothrottle status message is expected to read within the sample range of 6 to 13 units during parking. During landing, the pilot monitoring should brief the Nosewheel Steering switch position if a discrepancy is observed. The Autopilot Channel B selector position is expected to read within the sample range of 2 to 5 units during takeoff. The Flight Management Computer advisory is expected to read within the sample range of 63 to 72 units during preflight.

**CAUTION:** During engine start, both pilots should announce the Autobrake Selector switch position if the indication does not stabilize within the sample interval. The first officer will select any change in the Standby Hydraulic selector position and advise the other pilot when the associated caution light remains illuminated.

**CAUTION:** The Weather Radar advisory that differs from the expected state requires the First Officer to cross-check the condition if the indication does not stabilize within the sample interval. During preflight, both pilots should monitor the Probe Heat indication once the checklist item is complete.

**NOTE:** The Stall Warning annunciation is expected to read within the sample range of 67 to 75 units during approach.

Refer to the related topic for additional sample context. This text is fictional and exists only to give the prototype realistic volume and structure. The Standby Hydraulic annunciation is expected to read within the sample range of 35 to 38 units during a maintenance-requested ground run. During a turnaround, the First Officer should cross-check the Autobrake Selector status message once the checklist item is complete. Values in this manual are invented and must not be used for any operational purpose.

**15.20.3 Pack Temperature Control Interfaces**

The Flap Position Indication switch position is expected to read within the sample range of 74 to 83 units during a turnaround. If the Cargo Smoke Detection is inoperative, continue landing only after the relief pilot has reviewed the associated sample guidance. The pilot monitoring will monitor any change in the Center Tank Pumps status message and advise the other pilot once the checklist item is complete. During a turnaround, both pilots should cross-check the Center Tank Pumps quantity display before the next phase of flight. The Cargo Smoke Detection advisory that differs from the expected state requires the First Officer to record the condition before the next phase of flight.

If the Primary Electrical Bus is inoperative, continue taxi only after the First Officer has reviewed the associated sample guidance. The first officer will record any change in the Engine Anti-Ice advisory and advise the other pilot when operating at a sample station without ground power. During approach, the Captain should cross-check the Primary Electrical Bus switch position if a discrepancy is observed. Values in this manual are invented and must not be used for any operational purpose. This text is fictional and exists only to give the prototype realistic volume and structure.

The pilot flying will monitor any change in the Fuel Crossfeed selector position and advise the other pilot when the associated caution light remains illuminated. The Autobrake Selector advisory that differs from the expected state requires the relief pilot to announce the condition when operating at a sample station without ground power. If the Primary Electrical Bus is inoperative, continue an extended ground delay only after the Captain has reviewed the

associated sample guidance. The Stall Warning status message that differs from the expected state requires the relief pilot to verify the condition unless directed otherwise by the Sample Operations Center. This text is fictional and exists only to give the prototype realistic volume and structure. The pilot monitoring will monitor any change in the Flap Position Indication indication and advise the other pilot if a discrepancy is observed.

The Cargo Smoke Detection quantity display that differs from the expected state requires the pilot flying to cross-check the condition unless directed otherwise by the Sample Operations Center. During descent, the pilot monitoring should confirm the Wing Anti-Ice annunciation before the next phase of flight. During climb, both pilots should record the Auxiliary Power Unit switch position if the indication does not stabilize within the sample interval. During takeoff, both pilots should monitor the Wing Anti-Ice status message before the next phase of flight. The Transponder annunciation is expected to read within the sample range of 40 to 50 units during takeoff.

**NOTE:** During parking, the pilot monitoring should verify the Standby Hydraulic advisory before the next phase of flight.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Auxiliary Power Unit status message       | 84 units     | Refer to related topic |
| Autopilot Channel B annunciation          | 75 units     | Advisory only          |
| Autopilot Channel B switch position       | 39 units     | Monitor                |
| Brake Temperature Monitor switch position | 43 units     | Refer to related topic |
| Oxygen Distribution indication            | 72 units     | Advisory only          |

**CAUTION:** The relief pilot will confirm any change in the Stall Warning selector position and advise the other pilot before the next phase of flight. During engine start, the relief pilot should confirm the Flap Position Indication quantity display when conditions permit.

During engine start, the relief pilot should verify the Wing Anti-Ice selector position when the associated caution light remains illuminated. Refer to the related topic for additional sample context. During taxi, the pilot flying should verify the Flap Position Indication selector position if the indication does not stabilize within the sample interval.

If the Auxiliary Power Unit is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. If the Window Heat is inoperative, continue landing only after both pilots has reviewed the associated sample guidance.

15.20.4 Autothrottle Test

If the Oxygen Distribution is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance. During approach, the pilot flying should select the Cargo Smoke Detection selector position when operating at a sample station without ground power. Both pilots will select any change in the Transponder advisory and advise the other pilot when conditions permit. Values in this manual are invented and must not be used for any operational purpose. See 18.10.12 Transponder Reset Guidance.

- During landing, the First Officer should cross-check the Probe Heat quantity display before the next phase of flight.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- If the Transponder is inoperative, continue approach only after the relief pilot has reviewed the associated sample guidance.
- During cruise, the pilot monitoring should announce the Flap Position Indication annunciation unless directed otherwise by the Sample Operations Center.

**NOTE:** The first officer will announce any change in the Probe Heat advisory and advise the other pilot when conditions permit.



**CAUTION:** The pilot flying will record any change in the Weather Radar indication and advise the other pilot when the associated caution light remains illuminated.

**CAUTION:** The relief pilot will brief any change in the Cockpit Voice Recorder quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center.

**NOTE:** The Brake Temperature Monitor indication that differs from the expected state requires both pilots to announce the condition once the checklist item is complete. During parking, the relief pilot should record the Standby Hydraulic annunciation when operating at a sample station without ground power.

15.20.5 Window Heat Overview

The Auxiliary Power Unit switch position is expected to read within the sample range of 79 to 88 units during a diversion. The captain will select any change in the Standby Hydraulic quantity display and advise the other pilot before the next phase of flight. If the Cockpit Voice Recorder is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance. If the Landing Gear Indication is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance.

**CAUTION:** The Auxiliary Power Unit switch position is expected to read within the sample range of 59 to 64 units during preflight. The Center Tank Pumps switch position that differs from the expected state requires the pilot monitoring to monitor the condition if a discrepancy is observed. The Speedbrake Handle status message that differs from the expected state requires the pilot monitoring to cross-check the condition when conditions permit.

**CAUTION:** During cruise, both pilots should record the Fuel Crossfeed selector position if a discrepancy is observed.

Refer to the related topic for additional sample context. The Traffic Advisory Display status message is expected to read within the sample range of 83 to 88 units during a maintenance-requested ground run. The captain will cross-check any change in the Probe Heat status message and advise the other pilot once the checklist item is complete. If the Cargo Smoke Detection is inoperative, continue engine start only after the relief pilot has reviewed the associated sample guidance. The Cargo Smoke Detection switch position that differs from the expected state requires the relief pilot to announce the condition if a discrepancy is observed. If the Engine Anti-Ice is inoperative, continue landing only after the First Officer has reviewed the associated sample guidance.

- The Pack Temperature Control quantity display that differs from the expected state requires the pilot flying to announce the condition when conditions permit.
- If the Fuel Crossfeed is inoperative, continue climb only after the First Officer has reviewed the associated sample guidance.
- During landing, the First Officer should verify the Autobrake Selector switch position once the checklist item is complete.
- If the Oxygen Distribution is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance.
- The Autobrake Selector status message is expected to read within the sample range of 65 to 70 units during preflight.
- If the Center Tank Pumps is inoperative, continue a diversion only after the First Officer has reviewed the associated sample guidance.

**CAUTION:** If the Hydraulic System B is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance.

| Condition                                | Sample value | Remarks       |
|------------------------------------------|--------------|---------------|
| Flap Position Indication switch position | 90 units     | Monitor       |
| Wing Anti-Ice quantity display           | 86 units     | Advisory only |

|                                     |          |         |
|-------------------------------------|----------|---------|
| Hydraulic System A quantity display | 75 units | Monitor |
|-------------------------------------|----------|---------|

15.20.6 Wing Anti-Ice Power Sources

The Autothrottle quantity display is expected to read within the sample range of 32 to 44 units during takeoff. This text is fictional and exists only to give the prototype realistic volume and structure. Values in this manual are invented and must not be used for any operational purpose.

Values in this manual are invented and must not be used for any operational purpose. The relief pilot will confirm any change in the Primary Electrical Bus advisory and advise the other pilot before the next phase of flight. Refer to the related topic for additional sample context. During a diversion, the pilot monitoring should record the Fire Detection Loop advisory once the checklist item is complete. The pilot monitoring will confirm any change in the Cabin Pressure Controller annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center. The Cockpit Voice Recorder quantity display is expected to read within the sample range of 53 to 59 units during parking.

- The Window Heat status message that differs from the expected state requires the Captain to verify the condition when operating at a sample station without ground power.
- During a turnaround, the pilot monitoring should announce the Cockpit Voice Recorder indication if the indication does not stabilize within the sample interval.
- The Probe Heat selector position that differs from the expected state requires the relief pilot to brief the condition before the next phase of flight.
- The Oxygen Distribution indication that differs from the expected state requires the pilot monitoring to verify the condition before the next phase of flight.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- During cruise, the Captain should cross-check the Auxiliary Power Unit annunciation once the checklist item is complete.
- If the Landing Gear Indication is inoperative, continue approach only after the relief pilot has reviewed the associated sample guidance.
- The Speedbrake Handle selector position is expected to read within the sample range of 47 to 51 units during approach.
- During climb, the Captain should brief the Autopilot Channel B switch position when conditions permit.
- The Cabin Pressure Controller selector position is expected to read within the sample range of 62 to 70 units during a maintenance-requested ground run.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Thrust Reverser switch position          | 92 units     | Monitor                |
| Hydraulic System B indication            | 12 units     | Refer to related topic |
| Flap Position Indication switch position | 56 units     | Advisory only          |
| Fuel Crossfeed advisory                  | 22 units     | Advisory only          |

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Hydraulic System A indication              | 96 units     | Normal                 |
| Cabin Pressure Controller quantity display | 78 units     | Advisory only          |
| Flight Management Computer indication      | 2 units      | Normal                 |
| Autobrake Selector switch position         | 77 units     | Monitor                |
| Traffic Advisory Display advisory          | 8 units      | Refer to related topic |
| Speedbrake Handle selector position        | 84 units     | Normal                 |

| Condition                                | Sample value | Remarks       |
|------------------------------------------|--------------|---------------|
| Cabin Pressure Controller status message | 71 units     | Normal        |
| Thrust Reverser switch position          | 73 units     | Advisory only |
| Autobrake Selector status message        | 50 units     | Monitor       |
| Flap Position Indication annunciation    | 40 units     | Monitor       |
| Ground Proximity Monitor status message  | 47 units     | Normal        |
| Transponder indication                   | 36 units     | Monitor       |

**CAUTION:** If the Auxiliary Power Unit is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance. The Nosewheel Steering switch position that differs from the expected state requires the Captain to brief the condition unless directed otherwise by the Sample Operations Center.

The pilot monitoring will confirm any change in the Hydraulic System A quantity display and advise the other pilot when operating at a sample station without ground power. The captain will announce any change in the Landing Gear Indication advisory and advise the other pilot when the associated caution light remains illuminated. The Stall Warning annunciation that differs from the expected state requires the Captain to select the condition when conditions permit. If the Stall Warning is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance.

15.20.7 Hydraulic System B Indications

Refer to the related topic for additional sample context. The pilot flying will verify any change in the Thrust Reverser selector position and advise the other pilot when the associated caution light remains illuminated. If the Speedbrake Handle is inoperative, continue taxi only after the First Officer has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. The Autopilot Channel B indication that differs from the expected state requires both pilots to verify the condition if the indication does not stabilize within the sample interval. Values in this manual are invented and must not be used for any operational purpose.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Primary Electrical Bus annunciation      | 15 units     | Normal                 |
| Speedbrake Handle status message         | 54 units     | Advisory only          |
| Primary Electrical Bus selector position | 86 units     | Refer to related topic |
| Bleed Air Supply advisory                | 44 units     | Advisory only          |
| Landing Gear Indication annunciation     | 73 units     | Refer to related topic |
| Standby Instruments quantity display     | 75 units     | Advisory only          |

The pilot monitoring will verify any change in the Probe Heat switch position and advise the other pilot once the checklist item is complete. The Weather Radar quantity display is expected to read within the sample range of 93 to 101 units during a turnaround. During preflight, the First Officer should brief the Hydraulic System A indication before the next phase of flight.

**CAUTION:** The pilot monitoring will monitor any change in the Hydraulic System A status message and advise the other pilot once the checklist item is complete. Values in this manual are invented and must not be used for any operational purpose.

The Traffic Advisory Display status message is expected to read within the sample range of 74 to 79 units during landing. Values in this manual are invented and must not be used for any operational purpose. If the Hydraulic System B is inoperative, continue cruise only after the Captain has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure.

| Condition | Sample value | Remarks |
|-----------|--------------|---------|
|-----------|--------------|---------|

|                                |          |                        |
|--------------------------------|----------|------------------------|
| Weather Radar switch position  | 57 units | Normal                 |
| Probe Heat quantity display    | 80 units | Refer to related topic |
| Standby Instruments indication | 38 units | Normal                 |

During taxi, the Captain should verify the Probe Heat quantity display when conditions permit. The pilot monitoring will select any change in the Flight Management Computer switch position and advise the other pilot if a discrepancy is observed. The pilot monitoring will announce any change in the Primary Electrical Bus status message and advise the other pilot when the associated caution light remains illuminated. If the Probe Heat is inoperative, continue landing only after the First Officer has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. During preflight, the relief pilot should select the Probe Heat status message unless directed otherwise by the Sample Operations Center.

The pilot monitoring will monitor any change in the Ground Proximity Monitor selector position and advise the other pilot once the checklist item is complete. During landing, the pilot flying should brief the Thrust Reverser selector position if the indication does not stabilize within the sample interval. The Weather Radar switch position that differs from the expected state requires both pilots to brief the condition if the indication does not stabilize within the sample interval. The pilot monitoring will verify any change in the Pack Temperature Control annunciation and advise the other pilot when operating at a sample station without ground power. During takeoff, the pilot monitoring should monitor the Oxygen Distribution selector position if a discrepancy is observed.

**NOTE:** This text is fictional and exists only to give the prototype realistic volume and structure.

15.20.8 Thrust Reverser Power Sources

The wording here is placeholder content shaped like a procedure, not a procedure. The Transponder quantity display that differs from the expected state requires the First Officer to record the condition once the checklist item is complete. If the Landing Gear Indication is inoperative, continue a diversion only after the relief pilot has reviewed the associated sample guidance. If the Autopilot Channel A is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance. The Stall Warning quantity display is expected to read within the sample range of 36 to 40 units during taxi.

The Hydraulic System A quantity display that differs from the expected state requires the relief pilot to verify the condition before the next phase of flight. During cruise, both pilots should cross-check the Weather Radar annunciation when the associated caution light remains illuminated. If the Cockpit Voice Recorder is inoperative, continue approach only after both pilots has reviewed the associated sample guidance. The Stall Warning status message that differs from the expected state requires the relief pilot to select the condition once the checklist item is complete.

The wording here is placeholder content shaped like a procedure, not a procedure. During takeoff, the pilot flying should record the Pack Temperature Control switch position when conditions permit. The Autobrake Selector quantity display that differs from the expected state requires the pilot monitoring to brief the condition if the indication does not stabilize within the sample interval. Both pilots will select any change in the Cabin Pressure Controller quantity display and advise the other pilot if the indication does not stabilize within the sample interval. The Cockpit Voice Recorder switch position that differs from the expected state requires the pilot monitoring to confirm the condition unless directed otherwise by the Sample Operations Center.

**NOTE:** The relief pilot will record any change in the Hydraulic System B indication and advise the other pilot once the checklist item is complete. The Traffic Advisory Display switch position that differs from the expected state requires both pilots to monitor the condition before the next phase of flight.

| Condition                             | Sample value | Remarks       |
|---------------------------------------|--------------|---------------|
| Flight Management Computer indication | 83 units     | Advisory only |
| Nosewheel Steering advisory           | 90 units     | Monitor       |
| Landing Gear Indication indication    | 39 units     | Advisory only |

|                                       |          |                        |
|---------------------------------------|----------|------------------------|
| Flight Management Computer indication | 81 units | Normal                 |
| Hydraulic System A selector position  | 56 units | Normal                 |
| Autopilot Channel A switch position   | 40 units | Refer to related topic |
| Pack Temperature Control indication   | 74 units | Monitor                |

- The captain will cross-check any change in the Landing Gear Indication selector position and advise the other pilot before the next phase of flight.
- If the Ground Proximity Monitor is inoperative, continue parking only after both pilots has reviewed the associated sample guidance.
- The captain will record any change in the Window Heat advisory and advise the other pilot when operating at a sample station without ground power.
- If the Flap Position Indication is inoperative, continue landing only after the Captain has reviewed the associated sample guidance.
- The pilot flying will brief any change in the Engine Anti-Ice indication and advise the other pilot when conditions permit.
- The relief pilot will announce any change in the Cargo Smoke Detection annunciation and advise the other pilot if a discrepancy is observed.
- The Cockpit Voice Recorder selector position is expected to read within the sample range of 40 to 47 units during cruise.
- Refer to the related topic for additional sample context.
- If the Hydraulic System B is inoperative, continue parking only after the pilot monitoring has reviewed the associated sample guidance.
- During engine start, the relief pilot should verify the Autopilot Channel B advisory when the associated caution light remains illuminated.
- The Stall Warning switch position that differs from the expected state requires both pilots to announce the condition when operating at a sample station without ground power.
- The Cabin Pressure Controller status message is expected to read within the sample range of 62 to 74 units during a diversion.
- During takeoff, the relief pilot should monitor the Wing Anti-Ice selector position when conditions permit.
- The captain will verify any change in the Wing Anti-Ice status message and advise the other pilot when conditions permit.
- The captain will monitor any change in the Engine Anti-Ice annunciation and advise the other pilot if the indication does not stabilize within the sample interval.
- During descent, the pilot flying should announce the Ground Proximity Monitor quantity display when conditions permit.

| Condition                           | Sample value | Remarks       |
|-------------------------------------|--------------|---------------|
| Center Tank Pumps status message    | 97 units     | Normal        |
| Speedbrake Handle selector position | 50 units     | Monitor       |
| Thrust Reverser annunciation        | 15 units     | Advisory only |

### 15.20.9 Standby Instruments Crew Awareness

The Nosewheel Steering status message that differs from the expected state requires the First Officer to monitor the condition once the checklist item is complete. The relief pilot will brief any change in the Landing Gear Indication indication and advise the other pilot unless directed otherwise by the Sample Operations Center. The Center Tank Pumps quantity display that differs from the expected state requires the relief pilot to brief the condition when conditions permit.

The Window Heat annunciation is expected to read within the sample range of 3 to 14 units during a turnaround. The captain will confirm any change in the Ground Proximity Monitor status message and advise the other pilot unless directed otherwise by the Sample Operations Center. This text is fictional and exists only to give the prototype realistic volume and structure. If the Window Heat is inoperative, continue a turnaround only after the First Officer has reviewed the associated sample guidance. If the Landing Gear Indication is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance.

During cruise, both pilots should cross-check the Pack Temperature Control status message when operating at a sample station without ground power. If the Flight Management Computer is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance. The first officer will announce any change in the Traffic Advisory Display quantity display and advise the other pilot when the associated caution light remains illuminated. During engine start, both pilots should verify the Fire Detection Loop advisory when operating at a sample station without ground power.

**CAUTION:** If the Autothrottle is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance.

Refer to the related topic for additional sample context. During takeoff, the relief pilot should record the Flap Position Indication status message before the next phase of flight. The wording here is placeholder content shaped like a procedure, not a procedure. If the Ground Proximity Monitor is inoperative, continue cruise only after the First Officer has reviewed the associated sample guidance. If the Bleed Air Supply is inoperative, continue climb only after the relief pilot has reviewed the associated sample guidance. Both pilots will brief any change in the Autobrake Selector annunciation and advise the other pilot once the checklist item is complete.

If the Cabin Pressure Controller is inoperative, continue approach only after the First Officer has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. During descent, the pilot monitoring should record the Cockpit Voice Recorder quantity display when conditions permit. The Fuel Crossfeed status message is expected to read within the sample range of 23 to 29 units during an extended ground delay. The pilot monitoring will cross-check any change in the Autobrake Selector selector position and advise the other pilot before the next phase of flight.

The Thrust Reverser status message that differs from the expected state requires the First Officer to verify the condition when conditions permit. The Standby Hydraulic indication is expected to read within the sample range of 96 to 106 units during a maintenance-requested ground run. The Transponder indication is expected to read within the sample range of 84 to 89 units during preflight.

#### **15.20.10 Speedbrake Handle Crew Awareness**

The relief pilot will select any change in the Thrust Reverser selector position and advise the other pilot if the indication does not stabilize within the sample interval. Values in this manual are invented and must not be used for any operational purpose. During takeoff, both pilots should select the Cargo Smoke Detection selector position when operating at a sample station without ground power. Both pilots will cross-check any change in the Ground Proximity Monitor switch position and advise the other pilot once the checklist item is complete.

The Probe Heat annunciation that differs from the expected state requires the Captain to select the condition before the next phase of flight. The pilot flying will verify any change in the Weather Radar annunciation and advise the other pilot when conditions permit. During parking, the relief pilot should brief the Hydraulic System B advisory when operating at a sample station without ground power. The Stall Warning advisory is expected to read within the sample range of 37 to 49 units during landing.



- During an extended ground delay, the relief pilot should monitor the Cabin Pressure Controller indication unless directed otherwise by the Sample Operations Center.
- The pilot monitoring will confirm any change in the Standby Instruments selector position and advise the other pilot when the associated caution light remains illuminated.
- Values in this manual are invented and must not be used for any operational purpose.
- The Nosewheel Steering status message that differs from the expected state requires the pilot monitoring to monitor the condition if a discrepancy is observed.

The Weather Radar advisory that differs from the expected state requires the First Officer to announce the condition once the checklist item is complete. Refer to the related topic for additional sample context. The Flap Position Indication advisory is expected to read within the sample range of 3 to 12 units during an extended ground delay. During approach, the pilot flying should record the Weather Radar indication before the next phase of flight. If the Autopilot Channel B is inoperative, continue approach only after the Captain has reviewed the associated sample guidance.

**CAUTION:** Both pilots will verify any change in the Autobrake Selector selector position and advise the other pilot once the checklist item is complete.

During engine start, the pilot monitoring should confirm the Probe Heat annunciation if the indication does not stabilize within the sample interval. Refer to the related topic for additional sample context. Refer to the related topic for additional sample context. During approach, the relief pilot should confirm the Fuel Crossfeed status message when operating at a sample station without ground power. If the Window Heat is inoperative, continue a diversion only after the relief pilot has reviewed the associated sample guidance. The relief pilot will select any change in the Standby Hydraulic annunciation and advise the other pilot once the checklist item is complete.

During an extended ground delay, the First Officer should brief the Center Tank Pumps annunciation once the checklist item is complete. The Nosewheel Steering indication that differs from the expected state requires the Captain to confirm the condition when operating at a sample station without ground power. The Primary Electrical Bus indication that differs from the expected state requires both pilots to announce the condition before the next phase of flight. This text is fictional and exists only to give the prototype realistic volume and structure.

### **15.20.11 Hydraulic System B Overview**

If the Landing Gear Indication is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance. If the Brake Temperature Monitor is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. If the Stall Warning is inoperative, continue preflight only after the relief pilot has reviewed the associated sample guidance. If the Traffic Advisory Display is inoperative, continue a diversion only after the relief pilot has reviewed the associated sample guidance.

If the Ground Proximity Monitor is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance. The pilot monitoring will verify any change in the Nosewheel Steering selector position and advise the other pilot when operating at a sample station without ground power. The wording here is placeholder content shaped like a procedure, not a procedure.

- The Engine Anti-Ice selector position that differs from the expected state requires the Captain to select the condition when conditions permit.
- The captain will brief any change in the Hydraulic System B annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center.
- The pilot flying will select any change in the Traffic Advisory Display quantity display and advise the other pilot once the checklist item is complete.
- The Hydraulic System B switch position is expected to read within the sample range of 2 to 14 units during an extended ground delay.

- This text is fictional and exists only to give the prototype realistic volume and structure.
- The Speedbrake Handle status message is expected to read within the sample range of 16 to 24 units during preflight.

**NOTE:** Values in this manual are invented and must not be used for any operational purpose.

- Values in this manual are invented and must not be used for any operational purpose.
- The captain will select any change in the Standby Hydraulic advisory and advise the other pilot once the checklist item is complete.
- The Probe Heat quantity display that differs from the expected state requires the First Officer to brief the condition when the associated caution light remains illuminated.
- The Thrust Reverser selector position is expected to read within the sample range of 3 to 13 units during engine start.
- During cruise, the First Officer should cross-check the Wing Anti-Ice advisory when conditions permit.
- The Autopilot Channel A quantity display is expected to read within the sample range of 93 to 104 units during a turnaround.

**CAUTION:** The Stall Warning advisory is expected to read within the sample range of 96 to 102 units during a turnaround. The relief pilot will cross-check any change in the Transponder switch position and advise the other pilot unless directed otherwise by the Sample Operations Center.

If the Center Tank Pumps is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance. The first officer will announce any change in the Flap Position Indication selector position and advise the other pilot when the associated caution light remains illuminated. The Engine Anti-Ice quantity display is expected to read within the sample range of 64 to 76 units during takeoff. The Primary Electrical Bus indication that differs from the expected state requires the pilot flying to announce the condition when the associated caution light remains illuminated. The Cabin Pressure Controller annunciation that differs from the expected state requires the pilot flying to cross-check the condition once the checklist item is complete.

**CAUTION:** The Standby Hydraulic advisory that differs from the expected state requires the pilot monitoring to verify the condition when operating at a sample station without ground power. This text is fictional and exists only to give the prototype realistic volume and structure.

### 15.20.12 Autopilot Channel A Overview

The Auxiliary Power Unit switch position is expected to read within the sample range of 19 to 27 units during preflight. The Oxygen Distribution indication is expected to read within the sample range of 92 to 98 units during a turnaround. The Window Heat selector position is expected to read within the sample range of 32 to 37 units during approach.

The Speedbrake Handle quantity display is expected to read within the sample range of 44 to 56 units during takeoff. If the Hydraulic System B is inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance. Both pilots will monitor any change in the Nosewheel Steering advisory and advise the other pilot when the associated caution light remains illuminated. If the Probe Heat is inoperative, continue climb only after the Captain has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose.

**NOTE:** During engine start, both pilots should cross-check the Window Heat indication when the associated caution light remains illuminated. The Autobrake Selector switch position is expected to read within the sample range of 12 to 24 units during parking.

**NOTE:** The Bleed Air Supply advisory that differs from the expected state requires the Captain to brief the condition if the indication does not stabilize within the sample interval. The Autobrake Selector selector position that differs from the expected state requires the relief pilot to select the condition when the associated caution light remains illuminated.

During cruise, the Captain should announce the Hydraulic System A advisory if the indication does not stabilize within the sample interval. If the Flight Management Computer is inoperative, continue a turnaround only after the First Officer has reviewed the associated sample guidance. The Traffic Advisory Display advisory is expected to read within the sample range of 83 to 87 units during landing. During climb, the pilot monitoring should monitor the Cargo Smoke Detection indication when conditions permit. The relief pilot will select any change in the Autobrake Selector status message and advise the other pilot unless directed otherwise by the Sample Operations Center.

**CAUTION:** During cruise, the pilot monitoring should announce the Thrust Reverser selector position once the checklist item is complete.

This text is fictional and exists only to give the prototype realistic volume and structure. The Pack Temperature Control switch position is expected to read within the sample range of 74 to 82 units during a maintenance-requested ground run. If the Autopilot Channel B is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance.

**NOTE:** The pilot monitoring will monitor any change in the Weather Radar quantity display and advise the other pilot before the next phase of flight. The Bleed Air Supply indication is expected to read within the sample range of 8 to 20 units during climb.

### **15.20.13 Flap Position Indication Power Sources**

The Flight Management Computer advisory is expected to read within the sample range of 42 to 46 units during an extended ground delay. The Autopilot Channel A status message that differs from the expected state requires the Captain to monitor the condition when conditions permit. The Thrust Reverser switch position that differs from the expected state requires both pilots to record the condition before the next phase of flight. The Standby Hydraulic switch position is expected to read within the sample range of 98 to 103 units during landing. The pilot monitoring will announce any change in the Thrust Reverser selector position and advise the other pilot when the associated caution light remains illuminated. Refer to the related topic for additional sample context.

**NOTE:** During parking, the pilot flying should select the Autobrake Selector annunciation if the indication does not stabilize within the sample interval. Both pilots will select any change in the Cargo Smoke Detection selector position and advise the other pilot unless directed otherwise by the Sample Operations Center.

The Oxygen Distribution selector position is expected to read within the sample range of 28 to 38 units during landing. The relief pilot will confirm any change in the Flight Management Computer selector position and advise the other pilot once the checklist item is complete. If the Brake Temperature Monitor is inoperative, continue preflight only after the relief pilot has reviewed the associated sample guidance.

If the Weather Radar is inoperative, continue cruise only after the Captain has reviewed the associated sample guidance. The pilot flying will cross-check any change in the Cockpit Voice Recorder indication and advise the other pilot unless directed otherwise by the Sample Operations Center. If the Probe Heat is inoperative, continue climb only after the relief pilot has reviewed the associated sample guidance.

The captain will monitor any change in the Flap Position Indication selector position and advise the other pilot unless directed otherwise by the Sample Operations Center. Both pilots will cross-check any change in the Speedbrake Handle advisory and advise the other pilot unless directed otherwise by the Sample Operations Center. During a maintenance-requested ground run, both pilots should verify the Thrust Reverser advisory when conditions permit.

### **15.20.14 Ground Proximity Monitor Crew Awareness**

The Flap Position Indication advisory that differs from the expected state requires the pilot monitoring to cross-check the condition if the indication does not stabilize within the sample interval. The Oxygen Distribution status message that differs from the expected state requires the relief pilot to record the condition unless directed otherwise by the Sample Operations Center. If the Nosewheel Steering is inoperative, continue an extended ground delay only after the pilot flying has reviewed the associated sample guidance. The Wing Anti-Ice indication is expected to read within the sample range of 6 to 15 units during cruise.

The Oxygen Distribution quantity display that differs from the expected state requires the First Officer to record the condition before the next phase of flight. Refer to the related topic for additional sample context. During a turnaround, the Captain should verify the Pack Temperature Control quantity display when the associated caution light remains illuminated. The Bleed Air Supply advisory is expected to read within the sample range of 62 to 72 units during a diversion. The Wing Anti-Ice quantity display that differs from the expected state requires the relief pilot to announce the condition if a discrepancy is observed.

**NOTE:** During a turnaround, the pilot monitoring should verify the Center Tank Pumps advisory before the next phase of flight.

During landing, the pilot flying should monitor the Brake Temperature Monitor status message before the next phase of flight. The Cockpit Voice Recorder status message that differs from the expected state requires the pilot flying to announce the condition when the associated caution light remains illuminated. The Stall Warning selector position is expected to read within the sample range of 67 to 77 units during takeoff. The Cockpit Voice Recorder quantity display is expected to read within the sample range of 46 to 49 units during preflight.

**CAUTION:** This text is fictional and exists only to give the prototype realistic volume and structure.

- The Standby Hydraulic switch position is expected to read within the sample range of 53 to 65 units during engine start.
- During climb, the Captain should record the Wing Anti-Ice indication once the checklist item is complete.
- The Oxygen Distribution annunciation that differs from the expected state requires the pilot flying to monitor the condition unless directed otherwise by the Sample Operations Center.
- If the Engine Anti-Ice is inoperative, continue a maintenance-requested ground run only after both pilots has reviewed the associated sample guidance.
- Refer to the related topic for additional sample context.
- During climb, the pilot flying should cross-check the Thrust Reverser indication when conditions permit.

The Traffic Advisory Display annunciation is expected to read within the sample range of 61 to 68 units during descent. The Engine Anti-Ice switch position is expected to read within the sample range of 38 to 43 units during landing. If the Hydraulic System A is inoperative, continue a diversion only after both pilots has reviewed the associated sample guidance. If the Traffic Advisory Display is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance.

- The Bleed Air Supply selector position is expected to read within the sample range of 33 to 38 units during climb.
- The Bleed Air Supply selector position is expected to read within the sample range of 21 to 28 units during takeoff.
- The pilot flying will cross-check any change in the Hydraulic System B switch position and advise the other pilot when conditions permit.
- If the Flap Position Indication is inoperative, continue parking only after the pilot monitoring has reviewed the associated sample guidance.
- The relief pilot will announce any change in the Ground Proximity Monitor annunciation and advise the other pilot when conditions permit.
- The Ground Proximity Monitor indication that differs from the expected state requires the Captain to announce the condition unless directed otherwise by the Sample Operations Center.

**NOTE:** The Stall Warning selector position that differs from the expected state requires the relief pilot to cross-check the condition if a discrepancy is observed. The wording here is placeholder content shaped like a procedure, not a procedure.

### 15.20.15 Standby Instruments Power Sources

The wording here is placeholder content shaped like a procedure, not a procedure. The Speedbrake Handle indication that differs from the expected state requires the First Officer to verify the condition when conditions permit. If the Ground Proximity Monitor is inoperative, continue takeoff only after the First Officer has reviewed the associated sample guidance.

During a turnaround, the Captain should announce the Speedbrake Handle selector position when conditions permit. During descent, both pilots should monitor the Primary Electrical Bus indication before the next phase of flight. If the Auxiliary Power Unit is inoperative, continue parking only after both pilots has reviewed the associated sample guidance. If the Hydraulic System A is inoperative, continue an extended ground delay only after the pilot flying has reviewed the associated sample guidance.

During takeoff, the relief pilot should record the Standby Instruments switch position when conditions permit. The Probe Heat selector position that differs from the expected state requires both pilots to monitor the condition if a discrepancy is observed. During descent, both pilots should confirm the Oxygen Distribution switch position unless directed otherwise by the Sample Operations Center. The Fire Detection Loop indication is expected to read within the sample range of 42 to 46 units during descent. The Fuel Crossfeed indication that differs from the expected state requires both pilots to monitor the condition before the next phase of flight. During engine start, the First Officer should select the Autopilot Channel B status message when the associated caution light remains illuminated.

**CAUTION:** The pilot flying will record any change in the Autobrake Selector advisory and advise the other pilot when the associated caution light remains illuminated.

The Landing Gear Indication advisory that differs from the expected state requires both pilots to brief the condition when operating at a sample station without ground power. The Cockpit Voice Recorder switch position that differs from the expected state requires the relief pilot to brief the condition unless directed otherwise by the Sample Operations Center. During descent, the First Officer should confirm the Hydraulic System B status message when operating at a sample station without ground power. The Nosewheel Steering indication that differs from the expected state requires the First Officer to monitor the condition unless directed otherwise by the Sample Operations Center. The pilot monitoring will cross-check any change in the Thrust Reverser quantity display and advise the other pilot when the associated caution light remains illuminated.

If the Autobrake Selector is inoperative, continue takeoff only after both pilots has reviewed the associated sample guidance. During engine start, the relief pilot should confirm the Probe Heat quantity display when conditions permit. This text is fictional and exists only to give the prototype realistic volume and structure. If the Primary Electrical Bus is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance. The Window Heat selector position is expected to read within the sample range of 12 to 19 units during takeoff.

**NOTE:** The Flap Position Indication selector position is expected to read within the sample range of 49 to 52 units during a turnaround.

**CAUTION:** The Transponder status message that differs from the expected state requires the pilot monitoring to brief the condition once the checklist item is complete.

**NOTE:** Both pilots will brief any change in the Cockpit Voice Recorder annunciation and advise the other pilot before the next phase of flight. If the Bleed Air Supply is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance.

**15.20.16 Wing Anti-Ice Limits Display**

Both pilots will cross-check any change in the Nosewheel Steering advisory and advise the other pilot if a discrepancy is observed. During descent, the Captain should verify the Oxygen Distribution quantity display when the associated caution light remains illuminated. The Fire Detection Loop advisory that differs from the expected state requires the relief pilot to brief the condition before the next phase of flight. The pilot flying will record any change in the Pack Temperature Control status message and advise the other pilot when operating at a sample station without ground power.

| Condition | Sample value | Remarks |
|-----------|--------------|---------|
|-----------|--------------|---------|

|                                   |          |               |
|-----------------------------------|----------|---------------|
| Engine Anti-Ice indication        | 63 units | Advisory only |
| Oxygen Distribution annunciation  | 71 units | Monitor       |
| Probe Heat status message         | 78 units | Normal        |
| Hydraulic System A status message | 54 units | Monitor       |

- Both pilots will record any change in the Engine Anti-Ice switch position and advise the other pilot before the next phase of flight.
- Values in this manual are invented and must not be used for any operational purpose.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The Primary Electrical Bus switch position that differs from the expected state requires the First Officer to record the condition when operating at a sample station without ground power.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- During an extended ground delay, the First Officer should select the Autothrottle selector position once the checklist item is complete.

| Condition                            | Sample value | Remarks       |
|--------------------------------------|--------------|---------------|
| Nosewheel Steering indication        | 83 units     | Monitor       |
| Auxiliary Power Unit indication      | 24 units     | Advisory only |
| Autopilot Channel B quantity display | 34 units     | Advisory only |

If the Pack Temperature Control is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. The pilot monitoring will select any change in the Autobrake Selector selector position and advise the other pilot when operating at a sample station without ground power. The first officer will record any change in the Speedbrake Handle status message and advise the other pilot unless directed otherwise by the Sample Operations Center. During landing, the pilot flying should cross-check the Oxygen Distribution switch position if a discrepancy is observed.

The Primary Electrical Bus quantity display that differs from the expected state requires both pilots to select the condition when operating at a sample station without ground power. The Fire Detection Loop indication that differs from the expected state requires the pilot monitoring to monitor the condition when the associated caution light remains illuminated. The Cargo Smoke Detection switch position is expected to read within the sample range of 53 to 59 units during an extended ground delay. During takeoff, both pilots should announce the Landing Gear Indication annunciation unless directed otherwise by the Sample Operations Center. The Center Tank Pumps advisory that differs from the expected state requires the First Officer to record the condition when the associated caution light remains illuminated.

The Speedbrake Handle selector position is expected to read within the sample range of 80 to 83 units during cruise. The wording here is placeholder content shaped like a procedure, not a procedure. The Autopilot Channel A switch position is expected to read within the sample range of 25 to 30 units during takeoff. The Center Tank Pumps switch position is expected to read within the sample range of 55 to 61 units during climb.

| Condition                           | Sample value | Remarks                |
|-------------------------------------|--------------|------------------------|
| Hydraulic System B advisory         | 43 units     | Monitor                |
| Pack Temperature Control indication | 42 units     | Monitor                |
| Window Heat switch position         | 76 units     | Monitor                |
| Hydraulic System A quantity display | 15 units     | Advisory only          |
| Pack Temperature Control indication | 92 units     | Refer to related topic |



## 15.30 Operation

### 15.30.1 Autobrake Selector Interfaces

During an extended ground delay, both pilots should announce the Bleed Air Supply switch position when the associated caution light remains illuminated. The Window Heat selector position is expected to read within the sample range of 40 to 50 units during descent. If the Transponder is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance. Refer to the related topic for additional sample context. The Weather Radar switch position is expected to read within the sample range of 55 to 62 units during takeoff.

**NOTE:** The Wing Anti-Ice status message is expected to read within the sample range of 25 to 37 units during engine start.

The relief pilot will record any change in the Fire Detection Loop switch position and advise the other pilot if the indication does not stabilize within the sample interval. Both pilots will monitor any change in the Probe Heat quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center. If the Autobrake Selector is inoperative, continue climb only after the First Officer has reviewed the associated sample guidance. If the Speedbrake Handle is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance.

The pilot monitoring will verify any change in the Auxiliary Power Unit status message and advise the other pilot before the next phase of flight. If the Fuel Crossfeed is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance. The pilot monitoring will record any change in the Pack Temperature Control annunciation and advise the other pilot when conditions permit. If the Primary Electrical Bus is inoperative, continue a diversion only after the pilot monitoring has reviewed the associated sample guidance.

**CAUTION:** If the Engine Anti-Ice is inoperative, continue landing only after the relief pilot has reviewed the associated sample guidance. If the Cargo Smoke Detection is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance.

**NOTE:** The Flap Position Indication selector position that differs from the expected state requires the Captain to cross-check the condition once the checklist item is complete.

**NOTE:** Values in this manual are invented and must not be used for any operational purpose.

| Condition                          | Sample value | Remarks |
|------------------------------------|--------------|---------|
| Hydraulic System B switch position | 5 units      | Monitor |
| Auxiliary Power Unit advisory      | 3 units      | Normal  |
| Window Heat annunciation           | 29 units     | Normal  |
| Probe Heat annunciation            | 11 units     | Normal  |

The relief pilot will announce any change in the Standby Hydraulic switch position and advise the other pilot before the next phase of flight. If the Window Heat is inoperative, continue landing only after the First Officer has reviewed the associated sample guidance. Refer to the related topic for additional sample context. The Speedbrake Handle annunciation that differs from the expected state requires the pilot flying to select the condition if a discrepancy is observed.

### 15.30.2 Hydraulic System A Limits Display

The Center Tank Pumps annunciation is expected to read within the sample range of 54 to 60 units during descent. During a turnaround, the Captain should confirm the Weather Radar switch position unless directed otherwise by the Sample Operations Center. The Primary Electrical Bus status message that differs from the expected state requires the Captain to announce the condition if a discrepancy is observed. Values in this manual are invented and must not be used for any operational purpose. The pilot flying will monitor any change in the Stall Warning selector position and advise the other pilot if a discrepancy is observed. During descent, the Captain should announce the Primary

Electrical Bus indication when conditions permit.

**NOTE:** The captain will confirm any change in the Cockpit Voice Recorder quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center.

**NOTE:** The first officer will announce any change in the Engine Anti-Ice switch position and advise the other pilot when conditions permit. The relief pilot will confirm any change in the Landing Gear Indication annunciation and advise the other pilot when operating at a sample station without ground power.

**CAUTION:** Both pilots will announce any change in the Cargo Smoke Detection status message and advise the other pilot if the indication does not stabilize within the sample interval. During a turnaround, the Captain should verify the Autopilot Channel A annunciation once the checklist item is complete.

The Brake Temperature Monitor annunciation is expected to read within the sample range of 24 to 36 units during engine start. During an extended ground delay, the Captain should select the Ground Proximity Monitor status message if the indication does not stabilize within the sample interval. Refer to the related topic for additional sample context. Refer to the related topic for additional sample context. The Transponder switch position that differs from the expected state requires the relief pilot to record the condition unless directed otherwise by the Sample Operations Center. The Landing Gear Indication quantity display that differs from the expected state requires the Captain to cross-check the condition unless directed otherwise by the Sample Operations Center.

The Bleed Air Supply selector position is expected to read within the sample range of 22 to 26 units during a maintenance-requested ground run. During landing, both pilots should select the Auxiliary Power Unit advisory if the indication does not stabilize within the sample interval. If the Cabin Pressure Controller is inoperative, continue preflight only after the pilot monitoring has reviewed the associated sample guidance. During a diversion, the pilot monitoring should confirm the Pack Temperature Control indication when operating at a sample station without ground power. The Thrust Reverser indication that differs from the expected state requires the pilot monitoring to select the condition when the associated caution light remains illuminated. The wording here is placeholder content shaped like a procedure, not a procedure.

| Condition                             | Sample value | Remarks       |
|---------------------------------------|--------------|---------------|
| Autopilot Channel B selector position | 48 units     | Monitor       |
| Autothrottle switch position          | 45 units     | Normal        |
| Standby Instruments status message    | 98 units     | Normal        |
| Brake Temperature Monitor indication  | 87 units     | Advisory only |

15.30.3 Ground Proximity Monitor Test

The Thrust Reverser indication is expected to read within the sample range of 72 to 75 units during an extended ground delay. During preflight, the pilot monitoring should brief the Landing Gear Indication advisory if the indication does not stabilize within the sample interval. During a turnaround, the pilot monitoring should select the Auxiliary Power Unit status message when operating at a sample station without ground power.

**NOTE:** The Window Heat status message that differs from the expected state requires both pilots to brief the condition if the indication does not stabilize within the sample interval. If the Landing Gear Indication is inoperative, continue descent only after both pilots has reviewed the associated sample guidance.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Hydraulic System A advisory              | 35 units     | Advisory only          |
| Cargo Smoke Detection selector position  | 82 units     | Advisory only          |
| Pack Temperature Control switch position | 4 units      | Refer to related topic |
| Ground Proximity Monitor indication      | 94 units     | Normal                 |

**NOTE:** If the Auxiliary Power Unit is inoperative, continue cruise only after the Captain has reviewed the associated sample guidance. During taxi, the pilot monitoring should verify the Window Heat switch position if the indication does not stabilize within the sample interval.

The wording here is placeholder content shaped like a procedure, not a procedure. The Bleed Air Supply indication is expected to read within the sample range of 55 to 63 units during an extended ground delay. During a maintenance-requested ground run, the pilot flying should record the Landing Gear Indication status message if a discrepancy is observed. During climb, the relief pilot should verify the Transponder selector position once the checklist item is complete.

**CAUTION:** The wording here is placeholder content shaped like a procedure, not a procedure. Refer to the related topic for additional sample context.

**15.30.4 Fuel Crossfeed Test**

The Auxiliary Power Unit status message is expected to read within the sample range of 71 to 76 units during takeoff. The Fire Detection Loop annunciation is expected to read within the sample range of 67 to 77 units during engine start. The Autopilot Channel A advisory is expected to read within the sample range of 12 to 21 units during an extended ground delay.

**NOTE:** If the Wing Anti-Ice is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance.

The pilot monitoring will announce any change in the Center Tank Pumps indication and advise the other pilot when the associated caution light remains illuminated. The Center Tank Pumps quantity display is expected to read within the sample range of 60 to 64 units during landing. Values in this manual are invented and must not be used for any operational purpose. The Cargo Smoke Detection selector position that differs from the expected state requires the Captain to monitor the condition before the next phase of flight. The Pack Temperature Control quantity display that differs from the expected state requires the Captain to select the condition once the checklist item is complete. The captain will select any change in the Probe Heat quantity display and advise the other pilot if a discrepancy is observed.

| Condition                            | Sample value | Remarks                |
|--------------------------------------|--------------|------------------------|
| Fire Detection Loop advisory         | 2 units      | Advisory only          |
| Bleed Air Supply switch position     | 69 units     | Refer to related topic |
| Standby Instruments quantity display | 3 units      | Refer to related topic |
| Weather Radar selector position      | 95 units     | Advisory only          |
| Bleed Air Supply indication          | 14 units     | Advisory only          |

- The Standby Hydraulic quantity display is expected to read within the sample range of 36 to 39 units during a diversion.
- If the Weather Radar is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance.
- During engine start, the relief pilot should verify the Fire Detection Loop advisory once the checklist item is complete.
- The captain will announce any change in the Stall Warning indication and advise the other pilot if a discrepancy is observed.
- The first officer will brief any change in the Wing Anti-Ice status message and advise the other pilot before the next phase of flight.
- During a diversion, the pilot flying should announce the Window Heat annunciation before the next phase of flight.

**15.30.5 Stall Warning Power Sources**

The Stall Warning switch position that differs from the expected state requires the Captain to select the condition when conditions permit. The Brake Temperature Monitor annunciation that differs from the expected state requires the Captain to announce the condition if the indication does not stabilize within the sample interval. The Auxiliary Power Unit selector position that differs from the expected state requires the pilot flying to verify the condition when conditions permit.

| Condition                           | Sample value | Remarks                |
|-------------------------------------|--------------|------------------------|
| Window Heat status message          | 93 units     | Refer to related topic |
| Stall Warning quantity display      | 97 units     | Advisory only          |
| Center Tank Pumps selector position | 60 units     | Monitor                |
| Autothrottle status message         | 59 units     | Normal                 |
| Transponder advisory                | 38 units     | Refer to related topic |
| Oxygen Distribution switch position | 3 units      | Normal                 |
| Autobrake Selector quantity display | 83 units     | Monitor                |

During parking, the pilot flying should cross-check the Transponder annunciation when operating at a sample station without ground power. The first officer will record any change in the Standby Instruments switch position and advise the other pilot before the next phase of flight. During engine start, the relief pilot should record the Autopilot Channel A switch position once the checklist item is complete. The Center Tank Pumps switch position that differs from the expected state requires both pilots to confirm the condition when the associated caution light remains illuminated. The Brake Temperature Monitor switch position that differs from the expected state requires the pilot monitoring to cross-check the condition once the checklist item is complete.

- Refer to the related topic for additional sample context.
- The Probe Heat advisory that differs from the expected state requires the First Officer to announce the condition once the checklist item is complete.
- Both pilots will record any change in the Autothrottle switch position and advise the other pilot when operating at a sample station without ground power.
- The pilot monitoring will verify any change in the Thrust Reverser selector position and advise the other pilot unless directed otherwise by the Sample Operations Center.
- The Nosewheel Steering quantity display is expected to read within the sample range of 7 to 12 units during climb.
- The relief pilot will verify any change in the Autopilot Channel A status message and advise the other pilot when the associated caution light remains illuminated.

| Condition                            | Sample value | Remarks                |
|--------------------------------------|--------------|------------------------|
| Nosewheel Steering selector position | 20 units     | Normal                 |
| Autopilot Channel A status message   | 56 units     | Refer to related topic |
| Autobrake Selector quantity display  | 80 units     | Advisory only          |

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Oxygen Distribution annunciation         | 71 units     | Monitor                |
| Transponder quantity display             | 35 units     | Advisory only          |
| Traffic Advisory Display switch position | 26 units     | Normal                 |
| Nosewheel Steering advisory              | 34 units     | Refer to related topic |
| Engine Anti-Ice status message           | 84 units     | Monitor                |
| Center Tank Pumps annunciation           | 30 units     | Refer to related topic |

The Center Tank Pumps annunciation that differs from the expected state requires the pilot flying to select the condition unless directed otherwise by the Sample Operations Center. Values in this manual are invented and must not be used for any operational purpose. If the Standby Instruments is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance.

**15.30.6 Cargo Smoke Detection Normal Operation**

Both pilots will record any change in the Autobrake Selector advisory and advise the other pilot when the associated caution light remains illuminated. The Bleed Air Supply quantity display that differs from the expected state requires both pilots to cross-check the condition if the indication does not stabilize within the sample interval. During parking, the Captain should brief the Landing Gear Indication switch position if a discrepancy is observed. The Wing Anti-Ice annunciation is expected to read within the sample range of 49 to 59 units during landing. The Hydraulic System A advisory is expected to read within the sample range of 91 to 96 units during descent.

- The first officer will confirm any change in the Fuel Crossfeed status message and advise the other pilot when conditions permit.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- The Stall Warning annunciation that differs from the expected state requires the relief pilot to select the condition when conditions permit.
- The Fire Detection Loop selector position is expected to read within the sample range of 54 to 66 units during landing.

The relief pilot will announce any change in the Ground Proximity Monitor advisory and advise the other pilot when the associated caution light remains illuminated. The Cabin Pressure Controller quantity display that differs from the expected state requires the Captain to select the condition if a discrepancy is observed. If the Window Heat is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance.

The Hydraulic System A switch position that differs from the expected state requires the relief pilot to announce the condition when the associated caution light remains illuminated. The Engine Anti-Ice selector position is expected to read within the sample range of 16 to 28 units during an extended ground delay. During takeoff, the pilot monitoring should confirm the Fire Detection Loop selector position if the indication does not stabilize within the sample interval. During engine start, the Captain should confirm the Probe Heat quantity display when conditions permit. The wording here is placeholder content shaped like a procedure, not a procedure. During landing, the pilot monitoring should select the Fuel Crossfeed advisory unless directed otherwise by the Sample Operations Center.

If the Engine Anti-Ice is inoperative, continue preflight only after the pilot monitoring has reviewed the associated sample guidance. Refer to the related topic for additional sample context. The Landing Gear Indication advisory that differs from the expected state requires both pilots to cross-check the condition once the checklist item is complete. Refer to the related topic for additional sample context. During takeoff, the Captain should brief the Autopilot Channel A annunciation when operating at a sample station without ground power.

| Condition                               | Sample value | Remarks       |
|-----------------------------------------|--------------|---------------|
| Primary Electrical Bus quantity display | 8 units      | Advisory only |
| Nosewheel Steering switch position      | 40 units     | Monitor       |
| Autothrottle quantity display           | 77 units     | Advisory only |
| Pack Temperature Control annunciation   | 55 units     | Normal        |
| Probe Heat status message               | 61 units     | Advisory only |

Values in this manual are invented and must not be used for any operational purpose. If the Hydraulic System B is inoperative, continue taxi only after the First Officer has reviewed the associated sample guidance. If the Wing Anti-Ice is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance. If the Ground Proximity Monitor is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated

sample guidance.

15.30.7 Standby Hydraulic Overview

During engine start, the relief pilot should confirm the Ground Proximity Monitor indication before the next phase of flight. The pilot monitoring will monitor any change in the Cabin Pressure Controller indication and advise the other pilot when the associated caution light remains illuminated. The Wing Anti-Ice advisory is expected to read within the sample range of 58 to 67 units during climb.

| Condition                            | Sample value | Remarks       |
|--------------------------------------|--------------|---------------|
| Cargo Smoke Detection status message | 47 units     | Advisory only |
| Hydraulic System B annunciation      | 24 units     | Normal        |
| Standby Hydraulic indication         | 41 units     | Monitor       |
| Transponder selector position        | 37 units     | Advisory only |

The Thrust Reverser selector position that differs from the expected state requires the pilot flying to brief the condition when conditions permit. Both pilots will record any change in the Autopilot Channel B switch position and advise the other pilot if the indication does not stabilize within the sample interval. The wording here is placeholder content shaped like a procedure, not a procedure.

The Cargo Smoke Detection indication is expected to read within the sample range of 77 to 89 units during a diversion. Refer to the related topic for additional sample context. The relief pilot will monitor any change in the Thrust Reverser selector position and advise the other pilot if a discrepancy is observed. The relief pilot will monitor any change in the Speedbrake Handle annunciation and advise the other pilot when conditions permit. The Speedbrake Handle indication that differs from the expected state requires both pilots to record the condition when conditions permit. During a diversion, the First Officer should monitor the Weather Radar quantity display when operating at a sample station without ground power.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Autobrake Selector status message          | 81 units     | Refer to related topic |
| Hydraulic System B quantity display        | 89 units     | Advisory only          |
| Center Tank Pumps annunciation             | 39 units     | Normal                 |
| Flap Position Indication selector position | 6 units      | Advisory only          |

- The pilot monitoring will confirm any change in the Primary Electrical Bus selector position and advise the other pilot if a discrepancy is observed.
- During landing, both pilots should announce the Transponder status message when operating at a sample station without ground power.
- The Stall Warning switch position is expected to read within the sample range of 15 to 27 units during descent.

During takeoff, the Captain should announce the Autothrottle status message if the indication does not stabilize within the sample interval. The Fire Detection Loop annunciation is expected to read within the sample range of 32 to 43 units during a turnaround. The wording here is placeholder content shaped like a procedure, not a procedure. If the Hydraulic System A is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance. The Autothrottle status message is expected to read within the sample range of 5 to 17 units during a turnaround. The Primary Electrical Bus indication that differs from the expected state requires the relief pilot to cross-check the condition when the associated caution light remains illuminated.

- The Cargo Smoke Detection switch position that differs from the expected state requires the pilot monitoring to brief the condition unless directed otherwise by the Sample Operations Center.
- Refer to the related topic for additional sample context.



- The wording here is placeholder content shaped like a procedure, not a procedure.

**15.30.8 Cabin Pressure Controller Reset Guidance**

The Auxiliary Power Unit switch position that differs from the expected state requires both pilots to select the condition before the next phase of flight. The captain will confirm any change in the Hydraulic System A indication and advise the other pilot when conditions permit. The pilot flying will confirm any change in the Autopilot Channel A selector position and advise the other pilot when the associated caution light remains illuminated. The captain will announce any change in the Autobrake Selector switch position and advise the other pilot once the checklist item is complete. During climb, the pilot flying should brief the Brake Temperature Monitor advisory before the next phase of flight. Values in this manual are invented and must not be used for any operational purpose.

**NOTE:** If the Pack Temperature Control is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Engine Anti-Ice advisory                | 49 units     | Monitor                |
| Weather Radar advisory                  | 28 units     | Advisory only          |
| Flight Management Computer annunciation | 59 units     | Refer to related topic |
| Autobrake Selector switch position      | 41 units     | Advisory only          |

- During taxi, both pilots should record the Speedbrake Handle selector position if the indication does not stabilize within the sample interval.
- The Wing Anti-Ice advisory that differs from the expected state requires the First Officer to select the condition unless directed otherwise by the Sample Operations Center.
- During a turnaround, the relief pilot should brief the Wing Anti-Ice indication once the checklist item is complete.
- If the Hydraulic System B is inoperative, continue approach only after the pilot flying has reviewed the associated sample guidance.
- The Transponder advisory that differs from the expected state requires the relief pilot to verify the condition if a discrepancy is observed.

During approach, both pilots should select the Bleed Air Supply selector position when conditions permit. The Wing Anti-Ice quantity display that differs from the expected state requires the pilot flying to brief the condition when operating at a sample station without ground power. If the Nosewheel Steering is inoperative, continue preflight only after the Captain has reviewed the associated sample guidance. If the Standby Instruments is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. This text is fictional and exists only to give the prototype realistic volume and structure.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Bleed Air Supply switch position         | 65 units     | Normal                 |
| Cockpit Voice Recorder selector position | 69 units     | Refer to related topic |
| Stall Warning switch position            | 47 units     | Advisory only          |
| Hydraulic System A annunciation          | 18 units     | Advisory only          |
| Landing Gear Indication status message   | 49 units     | Monitor                |
| Nosewheel Steering advisory              | 49 units     | Normal                 |
| Landing Gear Indication quantity display | 50 units     | Monitor                |

| Condition | Sample value | Remarks |
|-----------|--------------|---------|
|-----------|--------------|---------|

|                                       |          |                        |
|---------------------------------------|----------|------------------------|
| Autothrottle annunciation             | 9 units  | Refer to related topic |
| Landing Gear Indication indication    | 83 units | Monitor                |
| Autobrake Selector status message     | 24 units | Monitor                |
| Ground Proximity Monitor annunciation | 56 units | Refer to related topic |

| Condition                              | Sample value | Remarks                |
|----------------------------------------|--------------|------------------------|
| Cabin Pressure Controller indication   | 87 units     | Monitor                |
| Speedbrake Handle switch position      | 23 units     | Monitor                |
| Auxiliary Power Unit selector position | 33 units     | Advisory only          |
| Thrust Reverser status message         | 34 units     | Refer to related topic |
| Cargo Smoke Detection advisory         | 97 units     | Monitor                |
| Window Heat selector position          | 98 units     | Monitor                |
| Oxygen Distribution selector position  | 79 units     | Advisory only          |

The Hydraulic System A status message that differs from the expected state requires the pilot monitoring to cross-check the condition when conditions permit. The pilot flying will brief any change in the Traffic Advisory Display switch position and advise the other pilot before the next phase of flight. During a turnaround, both pilots should monitor the Autobrake Selector annunciation if a discrepancy is observed. The pilot monitoring will brief any change in the Transponder advisory and advise the other pilot when the associated caution light remains illuminated. During descent, the relief pilot should cross-check the Stall Warning status message once the checklist item is complete.

### 15.30.9 Hydraulic System B Indications

The Pack Temperature Control indication that differs from the expected state requires the relief pilot to monitor the condition if a discrepancy is observed. The wording here is placeholder content shaped like a procedure, not a procedure. The Ground Proximity Monitor indication that differs from the expected state requires the First Officer to announce the condition when the associated caution light remains illuminated. Both pilots will verify any change in the Landing Gear Indication selector position and advise the other pilot unless directed otherwise by the Sample Operations Center. The Window Heat selector position that differs from the expected state requires the Captain to announce the condition when the associated caution light remains illuminated.

- The wording here is placeholder content shaped like a procedure, not a procedure.
- The Pack Temperature Control indication is expected to read within the sample range of 47 to 52 units during approach.
- During cruise, the pilot monitoring should select the Flight Management Computer quantity display if a discrepancy is observed.
- The Center Tank Pumps selector position that differs from the expected state requires the relief pilot to confirm the condition before the next phase of flight.

**NOTE:** The pilot monitoring will record any change in the Pack Temperature Control selector position and advise the other pilot when operating at a sample station without ground power.

**NOTE:** This text is fictional and exists only to give the prototype realistic volume and structure. This text is fictional and exists only to give the prototype realistic volume and structure.

- Values in this manual are invented and must not be used for any operational purpose.
- If the Oxygen Distribution is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance.

- If the Pack Temperature Control is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance.
- The pilot flying will monitor any change in the Cockpit Voice Recorder status message and advise the other pilot unless directed otherwise by the Sample Operations Center.
- If the Standby Hydraulic is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance.

During landing, the Captain should announce the Window Heat indication if a discrepancy is observed. During preflight, the pilot flying should monitor the Transponder indication if a discrepancy is observed. The Hydraulic System B status message is expected to read within the sample range of 16 to 26 units during an extended ground delay.

**NOTE:** The Wing Anti-Ice selector position that differs from the expected state requires the First Officer to verify the condition when operating at a sample station without ground power. If the Pack Temperature Control is inoperative, continue taxi only after the Captain has reviewed the associated sample guidance.

**15.30.10 Auxiliary Power Unit Interfaces**

The first officer will cross-check any change in the Weather Radar selector position and advise the other pilot before the next phase of flight. The captain will record any change in the Weather Radar quantity display and advise the other pilot if a discrepancy is observed. The Bleed Air Supply indication that differs from the expected state requires the Captain to record the condition when the associated caution light remains illuminated.

**CAUTION:** The Hydraulic System B selector position is expected to read within the sample range of 70 to 78 units during a maintenance-requested ground run.

The Cabin Pressure Controller switch position is expected to read within the sample range of 85 to 97 units during a diversion. The Autobrake Selector quantity display that differs from the expected state requires both pilots to brief the condition if a discrepancy is observed. During an extended ground delay, the First Officer should monitor the Ground Proximity Monitor indication before the next phase of flight. The relief pilot will announce any change in the Speedbrake Handle indication and advise the other pilot once the checklist item is complete. The Engine Anti-Ice quantity display is expected to read within the sample range of 98 to 109 units during engine start.

**NOTE:** The captain will brief any change in the Flap Position Indication indication and advise the other pilot before the next phase of flight. If the Autothrottle is inoperative, continue descent only after both pilots has reviewed the associated sample guidance.

The Stall Warning selector position that differs from the expected state requires the pilot monitoring to verify the condition once the checklist item is complete. If the Standby Hydraulic is inoperative, continue a maintenance-requested ground run only after the pilot flying has reviewed the associated sample guidance. The Autobrake Selector status message that differs from the expected state requires the pilot flying to cross-check the condition if the indication does not stabilize within the sample interval.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Hydraulic System A advisory               | 96 units     | Monitor                |
| Probe Heat switch position                | 96 units     | Normal                 |
| Stall Warning quantity display            | 25 units     | Monitor                |
| Fire Detection Loop selector position     | 40 units     | Refer to related topic |
| Fuel Crossfeed annunciation               | 30 units     | Monitor                |
| Traffic Advisory Display quantity display | 60 units     | Refer to related topic |

**15.30.11 Hydraulic System A Indications**

The Weather Radar switch position is expected to read within the sample range of 19 to 22 units during landing. The Autobrake Selector switch position is expected to read within the sample range of 35 to 46 units during a diversion. During cruise, the First Officer should confirm the Flap Position Indication selector position when conditions permit. Values in this manual are invented and must not be used for any operational purpose.

The Bleed Air Supply indication that differs from the expected state requires both pilots to record the condition if a discrepancy is observed. The Landing Gear Indication quantity display is expected to read within the sample range of 83 to 87 units during a turnaround. If the Standby Instruments is inoperative, continue descent only after the pilot flying has reviewed the associated sample guidance. If the Center Tank Pumps is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. The Hydraulic System A status message that differs from the expected state requires both pilots to record the condition unless directed otherwise by the Sample Operations Center.

The Landing Gear Indication quantity display is expected to read within the sample range of 83 to 93 units during engine start. During an extended ground delay, the Captain should brief the Probe Heat selector position when operating at a sample station without ground power. During taxi, the relief pilot should select the Engine Anti-Ice status message when conditions permit. The Oxygen Distribution status message that differs from the expected state requires the First Officer to announce the condition before the next phase of flight. The Flap Position Indication status message that differs from the expected state requires the pilot monitoring to select the condition if the indication does not stabilize within the sample interval.

**NOTE:** The wording here is placeholder content shaped like a procedure, not a procedure. If the Hydraulic System B is inoperative, continue preflight only after both pilots has reviewed the associated sample guidance.

The first officer will record any change in the Landing Gear Indication annunciation and advise the other pilot if a discrepancy is observed. The Autopilot Channel A advisory is expected to read within the sample range of 48 to 53 units during climb. The Autopilot Channel B quantity display is expected to read within the sample range of 8 to 17 units during cruise.

During takeoff, the pilot monitoring should confirm the Engine Anti-Ice advisory once the checklist item is complete. Refer to the related topic for additional sample context. The pilot flying will monitor any change in the Autopilot Channel A advisory and advise the other pilot when the associated caution light remains illuminated. During approach, the First Officer should record the Probe Heat annunciation before the next phase of flight.

**NOTE:** The Transponder indication is expected to read within the sample range of 31 to 40 units during approach.

During a turnaround, the relief pilot should verify the Flap Position Indication quantity display when conditions permit. If the Cabin Pressure Controller is inoperative, continue cruise only after both pilots has reviewed the associated sample guidance. The Bleed Air Supply quantity display that differs from the expected state requires both pilots to announce the condition when the associated caution light remains illuminated. If the Cabin Pressure Controller is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance. If the Transponder is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance.

### **15.30.12 Primary Electrical Bus Normal Operation**

The Cockpit Voice Recorder switch position is expected to read within the sample range of 70 to 74 units during cruise. The Cockpit Voice Recorder advisory is expected to read within the sample range of 34 to 45 units during takeoff. If the Center Tank Pumps is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance. Both pilots will verify any change in the Bleed Air Supply switch position and advise the other pilot when conditions permit. The Engine Anti-Ice indication that differs from the expected state requires the pilot flying to cross-check the condition if the indication does not stabilize within the sample interval. If the Hydraulic System A is inoperative, continue descent only after the pilot flying has reviewed the associated sample guidance.

The Window Heat advisory that differs from the expected state requires the pilot flying to verify the condition before the next phase of flight. During cruise, the pilot flying should announce the Cargo Smoke Detection annunciation before the next phase of flight. During cruise, the relief pilot should monitor the Center Tank Pumps indication unless

directed otherwise by the Sample Operations Center.

The Landing Gear Indication indication that differs from the expected state requires the Captain to select the condition when conditions permit. During cruise, the First Officer should brief the Autobrake Selector selector position if a discrepancy is observed. The captain will brief any change in the Hydraulic System B annunciation and advise the other pilot once the checklist item is complete. The Brake Temperature Monitor advisory that differs from the expected state requires both pilots to announce the condition when the associated caution light remains illuminated. The Flap Position Indication switch position is expected to read within the sample range of 22 to 26 units during taxi.

If the Oxygen Distribution is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance. The Ground Proximity Monitor quantity display that differs from the expected state requires the relief pilot to record the condition when conditions permit. The Center Tank Pumps status message that differs from the expected state requires both pilots to confirm the condition before the next phase of flight. The Flap Position Indication switch position that differs from the expected state requires the pilot flying to record the condition if the indication does not stabilize within the sample interval. If the Cockpit Voice Recorder is inoperative, continue approach only after the Captain has reviewed the associated sample guidance.

The Autobrake Selector switch position is expected to read within the sample range of 52 to 55 units during a turnaround. Values in this manual are invented and must not be used for any operational purpose. If the Engine Anti-Ice is inoperative, continue an extended ground delay only after the pilot flying has reviewed the associated sample guidance.

**CAUTION:** The Landing Gear Indication annunciation is expected to read within the sample range of 81 to 89 units during engine start. The first officer will monitor any change in the Cargo Smoke Detection indication and advise the other pilot when operating at a sample station without ground power.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Nosewheel Steering selector position      | 67 units     | Refer to related topic |
| Wing Anti-Ice advisory                    | 2 units      | Refer to related topic |
| Flight Management Computer status message | 70 units     | Monitor                |
| Transponder quantity display              | 48 units     | Monitor                |
| Flap Position Indication quantity display | 70 units     | Monitor                |
| Cockpit Voice Recorder advisory           | 8 units      | Refer to related topic |

| Condition                              | Sample value | Remarks       |
|----------------------------------------|--------------|---------------|
| Traffic Advisory Display advisory      | 2 units      | Advisory only |
| Ground Proximity Monitor advisory      | 89 units     | Normal        |
| Auxiliary Power Unit selector position | 83 units     | Normal        |

| Condition                              | Sample value | Remarks                |
|----------------------------------------|--------------|------------------------|
| Auxiliary Power Unit selector position | 80 units     | Refer to related topic |
| Fuel Crossfeed annunciation            | 49 units     | Monitor                |
| Ground Proximity Monitor indication    | 21 units     | Refer to related topic |
| Thrust Reverser switch position        | 14 units     | Advisory only          |

15.30.13 Probe Heat Crew Awareness

During parking, the pilot flying should select the Hydraulic System B status message unless directed otherwise by the Sample Operations Center. Refer to the related topic for additional sample context. The Speedbrake Handle annunciation is expected to read within the sample range of 77 to 80 units during takeoff.

This text is fictional and exists only to give the prototype realistic volume and structure. If the Cabin Pressure Controller is inoperative, continue a maintenance-requested ground run only after the pilot flying has reviewed the associated sample guidance. The Hydraulic System A status message is expected to read within the sample range of 50 to 54 units during taxi. Values in this manual are invented and must not be used for any operational purpose. During a maintenance-requested ground run, the First Officer should announce the Autopilot Channel B quantity display if a discrepancy is observed.

The wording here is placeholder content shaped like a procedure, not a procedure. Values in this manual are invented and must not be used for any operational purpose. The wording here is placeholder content shaped like a procedure, not a procedure.

Values in this manual are invented and must not be used for any operational purpose. During approach, the pilot monitoring should confirm the Window Heat quantity display when operating at a sample station without ground power. The first officer will monitor any change in the Traffic Advisory Display indication and advise the other pilot when the associated caution light remains illuminated. The relief pilot will record any change in the Wing Anti-Ice advisory and advise the other pilot once the checklist item is complete.

- The Thrust Reverser status message is expected to read within the sample range of 17 to 24 units during a turnaround.
- The pilot flying will announce any change in the Autobrake Selector status message and advise the other pilot before the next phase of flight.
- The captain will confirm any change in the Window Heat status message and advise the other pilot once the checklist item is complete.
- During approach, both pilots should brief the Center Tank Pumps advisory when the associated caution light remains illuminated.
- If the Probe Heat is inoperative, continue taxi only after the pilot flying has reviewed the associated sample guidance.

| Condition                             | Sample value | Remarks       |
|---------------------------------------|--------------|---------------|
| Hydraulic System A advisory           | 97 units     | Advisory only |
| Hydraulic System B switch position    | 50 units     | Normal        |
| Pack Temperature Control advisory     | 51 units     | Advisory only |
| Autobrake Selector switch position    | 21 units     | Normal        |
| Traffic Advisory Display annunciation | 58 units     | Monitor       |

15.30.14 Wing Anti-Ice Test

The wording here is placeholder content shaped like a procedure, not a procedure. The Flight Management Computer quantity display that differs from the expected state requires the Captain to select the condition when the associated caution light remains illuminated. The Center Tank Pumps selector position that differs from the expected state requires the First Officer to monitor the condition unless directed otherwise by the Sample Operations Center.

If the Cargo Smoke Detection is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance. The Oxygen Distribution annunciation that differs from the expected state requires the pilot monitoring to select the condition if a discrepancy is observed. If the Autobrake Selector is inoperative, continue cruise only after the First Officer has reviewed the associated sample guidance. Refer to the related topic for additional sample context. The captain will announce any change in the Brake Temperature Monitor annunciation and advise the other pilot before the next phase of flight.

During landing, the Captain should record the Landing Gear Indication status message when conditions permit. If the Cabin Pressure Controller is inoperative, continue approach only after both pilots has reviewed the associated sample guidance. The Autopilot Channel A selector position that differs from the expected state requires the pilot flying to brief the condition before the next phase of flight.



The Autopilot Channel A quantity display is expected to read within the sample range of 2 to 13 units during preflight. The Center Tank Pumps quantity display is expected to read within the sample range of 63 to 66 units during engine start. The captain will record any change in the Ground Proximity Monitor switch position and advise the other pilot when conditions permit. During a diversion, the relief pilot should verify the Fuel Crossfeed switch position when the associated caution light remains illuminated.

If the Fire Detection Loop is inoperative, continue landing only after the pilot monitoring has reviewed the associated sample guidance. The Stall Warning advisory is expected to read within the sample range of 58 to 69 units during cruise. During landing, the pilot flying should record the Cargo Smoke Detection selector position once the checklist item is complete. During takeoff, the relief pilot should cross-check the Traffic Advisory Display advisory before the next phase of flight. Both pilots will confirm any change in the Auxiliary Power Unit advisory and advise the other pilot if the indication does not stabilize within the sample interval. See 09.10.8 Speedbrake Handle Interfaces.

| Condition                        | Sample value | Remarks                |
|----------------------------------|--------------|------------------------|
| Standby Hydraulic status message | 11 units     | Refer to related topic |
| Speedbrake Handle advisory       | 55 units     | Normal                 |
| Weather Radar switch position    | 87 units     | Advisory only          |

15.30.15 Cargo Smoke Detection Reset Guidance

Refer to the related topic for additional sample context. The Cargo Smoke Detection advisory that differs from the expected state requires the Captain to announce the condition when conditions permit. During a turnaround, the First Officer should record the Autopilot Channel A switch position when the associated caution light remains illuminated. During descent, the pilot flying should monitor the Probe Heat status message when the associated caution light remains illuminated. The Stall Warning annunciation is expected to read within the sample range of 76 to 83 units during landing. If the Primary Electrical Bus is inoperative, continue preflight only after both pilots has reviewed the associated sample guidance.

The Standby Hydraulic switch position is expected to read within the sample range of 33 to 37 units during approach. During landing, the pilot flying should brief the Flap Position Indication advisory once the checklist item is complete. The first officer will brief any change in the Cockpit Voice Recorder annunciation and advise the other pilot when conditions permit.

| Condition                            | Sample value | Remarks                |
|--------------------------------------|--------------|------------------------|
| Fuel Crossfeed switch position       | 85 units     | Refer to related topic |
| Autopilot Channel A status message   | 40 units     | Advisory only          |
| Autopilot Channel A quantity display | 95 units     | Normal                 |
| Standby Hydraulic quantity display   | 90 units     | Monitor                |
| Fuel Crossfeed advisory              | 52 units     | Advisory only          |
| Stall Warning advisory               | 89 units     | Monitor                |
| Oxygen Distribution advisory         | 52 units     | Normal                 |

**CAUTION:** Both pilots will brief any change in the Bleed Air Supply indication and advise the other pilot if the indication does not stabilize within the sample interval.

If the Hydraulic System A is inoperative, continue climb only after the relief pilot has reviewed the associated sample guidance. The pilot flying will monitor any change in the Pack Temperature Control switch position and advise the other pilot when operating at a sample station without ground power. Both pilots will brief any change in the Weather Radar quantity display and advise the other pilot when conditions permit. The Thrust Reverser quantity display is expected to read within the sample range of 56 to 59 units during a turnaround. The Weather Radar annunciation that differs from the expected state requires both pilots to cross-check the condition unless directed otherwise by the Sample Operations Center. This text is fictional and exists only to give the prototype realistic volume and structure.

### 15.30.16 Window Heat Power Sources

The Center Tank Pumps indication that differs from the expected state requires the relief pilot to select the condition once the checklist item is complete. Values in this manual are invented and must not be used for any operational purpose. The relief pilot will cross-check any change in the Standby Hydraulic indication and advise the other pilot if a discrepancy is observed. The Flight Management Computer switch position that differs from the expected state requires the relief pilot to record the condition when the associated caution light remains illuminated.

| Condition                          | Sample value | Remarks                |
|------------------------------------|--------------|------------------------|
| Landing Gear Indication indication | 91 units     | Normal                 |
| Weather Radar selector position    | 82 units     | Refer to related topic |
| Probe Heat switch position         | 78 units     | Refer to related topic |
| Probe Heat status message          | 77 units     | Normal                 |
| Oxygen Distribution advisory       | 10 units     | Refer to related topic |

**CAUTION:** Refer to the related topic for additional sample context. The Primary Electrical Bus switch position that differs from the expected state requires the Captain to announce the condition if the indication does not stabilize within the sample interval.

If the Brake Temperature Monitor is inoperative, continue climb only after the pilot flying has reviewed the associated sample guidance. The captain will select any change in the Stall Warning selector position and advise the other pilot if a discrepancy is observed. During preflight, the First Officer should brief the Landing Gear Indication selector position once the checklist item is complete. The Probe Heat selector position is expected to read within the sample range of 53 to 60 units during climb. The captain will confirm any change in the Probe Heat quantity display and advise the other pilot before the next phase of flight. During landing, the Captain should brief the Ground Proximity Monitor indication once the checklist item is complete.

The Bleed Air Supply indication is expected to read within the sample range of 37 to 42 units during an extended ground delay. If the Probe Heat is inoperative, continue parking only after the pilot monitoring has reviewed the associated sample guidance. Both pilots will record any change in the Auxiliary Power Unit status message and advise the other pilot before the next phase of flight. If the Primary Electrical Bus is inoperative, continue a maintenance-requested ground run only after the pilot monitoring has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure.

### 15.30.17 New Sample Topic: Primary Electrical Bus

The Fuel Crossfeed quantity display is expected to read within the sample range of 62 to 74 units during landing. Refer to the related topic for additional sample context. The first officer will cross-check any change in the Hydraulic System A advisory and advise the other pilot if the indication does not stabilize within the sample interval.

The Bleed Air Supply advisory that differs from the expected state requires the relief pilot to brief the condition when operating at a sample station without ground power. Both pilots will monitor any change in the Wing Anti-Ice switch position and advise the other pilot when the associated caution light remains illuminated. During a turnaround, the pilot flying should announce the Oxygen Distribution switch position when conditions permit.

The Speedbrake Handle selector position that differs from the expected state requires the First Officer to select the condition unless directed otherwise by the Sample Operations Center. During engine start, the relief pilot should monitor the Transponder selector position unless directed otherwise by the Sample Operations Center. Both pilots will record any change in the Primary Electrical Bus advisory and advise the other pilot before the next phase of flight. The Autopilot Channel B switch position is expected to read within the sample range of 12 to 24 units during descent.

The Hydraulic System A selector position that differs from the expected state requires the First Officer to confirm the condition when operating at a sample station without ground power. During takeoff, the pilot flying should verify the Traffic Advisory Display indication if a discrepancy is observed. The Weather Radar advisory is expected to read within the sample range of 14 to 19 units during climb. The wording here is placeholder content shaped like a

procedure, not a procedure. Both pilots will select any change in the Traffic Advisory Display quantity display and advise the other pilot if the indication does not stabilize within the sample interval. The relief pilot will brief any change in the Hydraulic System B indication and advise the other pilot when conditions permit.

- During a maintenance-requested ground run, both pilots should confirm the Autobrake Selector annunciation once the checklist item is complete.
- The Nosewheel Steering indication that differs from the expected state requires the pilot monitoring to record the condition once the checklist item is complete.
- The Stall Warning indication that differs from the expected state requires the pilot monitoring to record the condition before the next phase of flight.
- The Cargo Smoke Detection advisory is expected to read within the sample range of 23 to 26 units during landing.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- The relief pilot will select any change in the Probe Heat indication and advise the other pilot unless directed otherwise by the Sample Operations Center.

**CAUTION:** The Stall Warning quantity display is expected to read within the sample range of 8 to 16 units during landing.

The Autobrake Selector quantity display that differs from the expected state requires both pilots to brief the condition when operating at a sample station without ground power. During climb, the Captain should brief the Autopilot Channel B advisory unless directed otherwise by the Sample Operations Center. If the Stall Warning is inoperative, continue engine start only after the relief pilot has reviewed the associated sample guidance. During a maintenance-requested ground run, the pilot flying should select the Hydraulic System B status message when the associated caution light remains illuminated.

**CAUTION:** The Hydraulic System B advisory is expected to read within the sample range of 71 to 79 units during a diversion.

# Chapter 16 Systems: Ice and Rain Protection

## 16.10 Description

### 16.10.1 Nosewheel Steering Interfaces

During climb, the relief pilot should record the Landing Gear Indication indication when conditions permit. The Speedbrake Handle selector position that differs from the expected state requires the pilot monitoring to record the condition when operating at a sample station without ground power. The Standby Instruments advisory is expected to read within the sample range of 67 to 74 units during engine start. During takeoff, both pilots should cross-check the Cargo Smoke Detection quantity display when the associated caution light remains illuminated. This text is fictional and exists only to give the prototype realistic volume and structure. The wording here is placeholder content shaped like a procedure, not a procedure.

The Fire Detection Loop quantity display that differs from the expected state requires the pilot monitoring to brief the condition when the associated caution light remains illuminated. This text is fictional and exists only to give the prototype realistic volume and structure. During landing, both pilots should announce the Primary Electrical Bus status message if the indication does not stabilize within the sample interval. During preflight, the First Officer should cross-check the Transponder quantity display when operating at a sample station without ground power. The pilot flying will cross-check any change in the Ground Proximity Monitor status message and advise the other pilot when the associated caution light remains illuminated. The Auxiliary Power Unit selector position is expected to read within the sample range of 90 to 100 units during takeoff.

| Condition                                | Sample value | Remarks       |
|------------------------------------------|--------------|---------------|
| Landing Gear Indication switch position  | 92 units     | Advisory only |
| Traffic Advisory Display switch position | 15 units     | Monitor       |
| Autopilot Channel A switch position      | 94 units     | Normal        |

The Flap Position Indication quantity display is expected to read within the sample range of 10 to 14 units during a turnaround. During landing, the Captain should record the Brake Temperature Monitor quantity display once the checklist item is complete. The Flap Position Indication advisory that differs from the expected state requires the relief pilot to confirm the condition before the next phase of flight. The Hydraulic System B selector position that differs from the expected state requires the Captain to select the condition when the associated caution light remains illuminated. The Transponder quantity display that differs from the expected state requires the Captain to monitor the condition when operating at a sample station without ground power. The wording here is placeholder content shaped like a procedure, not a procedure.

- Refer to the related topic for additional sample context.
- The Landing Gear Indication annunciation is expected to read within the sample range of 70 to 82 units during a diversion.
- The Fire Detection Loop selector position is expected to read within the sample range of 20 to 25 units during taxi.
- The Window Heat annunciation that differs from the expected state requires the First Officer to brief the condition once the checklist item is complete.
- During parking, both pilots should select the Center Tank Pumps status message if the indication does not stabilize within the sample interval.

| Condition                          | Sample value | Remarks |
|------------------------------------|--------------|---------|
| Autopilot Channel B indication     | 36 units     | Normal  |
| Autopilot Channel B status message | 73 units     | Normal  |
| Center Tank Pumps indication       | 43 units     | Monitor |

**CAUTION:** Values in this manual are invented and must not be used for any operational purpose.

The pilot monitoring will monitor any change in the Autothrottle status message and advise the other pilot if a discrepancy is observed. The Standby Instruments indication is expected to read within the sample range of 85 to 94 units during descent. During taxi, the relief pilot should select the Autopilot Channel B quantity display if a discrepancy is observed.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Wing Anti-Ice quantity display          | 2 units      | Monitor                |
| Wing Anti-Ice advisory                  | 62 units     | Advisory only          |
| Center Tank Pumps switch position       | 38 units     | Normal                 |
| Hydraulic System A selector position    | 23 units     | Refer to related topic |
| Traffic Advisory Display status message | 73 units     | Advisory only          |
| Hydraulic System B advisory             | 50 units     | Monitor                |

**16.10.2 Autopilot Channel B Status Messages**

The Fire Detection Loop status message that differs from the expected state requires both pilots to confirm the condition when the associated caution light remains illuminated. During landing, the relief pilot should verify the Oxygen Distribution advisory when operating at a sample station without ground power. Values in this manual are invented and must not be used for any operational purpose. This text is fictional and exists only to give the prototype realistic volume and structure.

Refer to the related topic for additional sample context. The relief pilot will monitor any change in the Flap Position Indication advisory and advise the other pilot before the next phase of flight. If the Brake Temperature Monitor is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance. If the Traffic Advisory Display is inoperative, continue landing only after both pilots has reviewed the associated sample guidance.

The Autopilot Channel A selector position that differs from the expected state requires the pilot monitoring to brief the condition when conditions permit. The Autopilot Channel A annunciation is expected to read within the sample range of 77 to 83 units during parking. The Stall Warning annunciation is expected to read within the sample range of 42 to 52 units during cruise. The Thrust Reverser quantity display that differs from the expected state requires the First Officer to cross-check the condition when conditions permit. This text is fictional and exists only to give the prototype realistic volume and structure. If the Primary Electrical Bus is inoperative, continue a diversion only after the pilot monitoring has reviewed the associated sample guidance.

The Cargo Smoke Detection status message is expected to read within the sample range of 88 to 94 units during parking. During parking, the pilot flying should record the Cabin Pressure Controller annunciation once the checklist item is complete. During engine start, both pilots should cross-check the Auxiliary Power Unit annunciation when operating at a sample station without ground power. The Flight Management Computer selector position is expected to read within the sample range of 47 to 52 units during a turnaround. The Oxygen Distribution indication is expected to read within the sample range of 44 to 56 units during climb.

If the Hydraulic System B is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance. The pilot monitoring will cross-check any change in the Weather Radar advisory and advise the other pilot when operating at a sample station without ground power. The Autobrake Selector indication that differs from the expected state requires the pilot monitoring to confirm the condition before the next phase of flight.

**16.10.3 Fuel Crossfeed Limits Display**

Both pilots will cross-check any change in the Cargo Smoke Detection quantity display and advise the other pilot when the associated caution light remains illuminated. The Thrust Reverser switch position is expected to read within the sample range of 32 to 41 units during a turnaround. The Auxiliary Power Unit selector position is expected to read within the sample range of 94 to 98 units during engine start. The relief pilot will record any change in the Flap Position Indication selector position and advise the other pilot when operating at a sample station without ground power. The first officer will announce any change in the Bleed Air Supply annunciation and advise the other pilot when conditions permit.

The wording here is placeholder content shaped like a procedure, not a procedure. The Standby Instruments status message that differs from the expected state requires the pilot monitoring to confirm the condition if a discrepancy is observed. This text is fictional and exists only to give the prototype realistic volume and structure. Both pilots will monitor any change in the Standby Instruments advisory and advise the other pilot when the associated caution light remains illuminated. The captain will cross-check any change in the Autopilot Channel A switch position and advise the other pilot when the associated caution light remains illuminated.

- The Center Tank Pumps annunciation is expected to read within the sample range of 49 to 60 units during landing.
- If the Standby Instruments is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance.
- The Standby Hydraulic indication is expected to read within the sample range of 83 to 88 units during takeoff.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- During takeoff, both pilots should select the Brake Temperature Monitor indication unless directed otherwise by the Sample Operations Center.
- Refer to the related topic for additional sample context.

**NOTE:** During a maintenance-requested ground run, both pilots should monitor the Transponder selector position if a discrepancy is observed.

| Condition                              | Sample value | Remarks       |
|----------------------------------------|--------------|---------------|
| Auxiliary Power Unit indication        | 52 units     | Advisory only |
| Standby Hydraulic indication           | 93 units     | Monitor       |
| Autopilot Channel A status message     | 65 units     | Advisory only |
| Autopilot Channel B indication         | 66 units     | Normal        |
| Standby Instruments status message     | 53 units     | Normal        |
| Autobrake Selector selector position   | 73 units     | Monitor       |
| Auxiliary Power Unit selector position | 65 units     | Advisory only |

**NOTE:** The Thrust Reverser indication that differs from the expected state requires the Captain to announce the condition if the indication does not stabilize within the sample interval. The Thrust Reverser quantity display that differs from the expected state requires the pilot flying to cross-check the condition if the indication does not stabilize within the sample interval.

- The captain will record any change in the Standby Instruments advisory and advise the other pilot if the indication does not stabilize within the sample interval.
- During climb, the pilot flying should brief the Autopilot Channel B advisory when the associated caution light remains illuminated.
- The Engine Anti-Ice selector position that differs from the expected state requires the First Officer to verify the condition before the next phase of flight.
- Refer to the related topic for additional sample context.



- This text is fictional and exists only to give the prototype realistic volume and structure.

The Autothrottle annunciation that differs from the expected state requires the relief pilot to monitor the condition when the associated caution light remains illuminated. If the Hydraulic System A is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance. The pilot monitoring will verify any change in the Transponder selector position and advise the other pilot before the next phase of flight. See 05.10.13 Wing Anti-Ice Crew Awareness.

#### **16.10.4 Thrust Reverser Indications**

If the Flap Position Indication is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. If the Landing Gear Indication is inoperative, continue climb only after the pilot flying has reviewed the associated sample guidance.

**NOTE:** The Pack Temperature Control status message that differs from the expected state requires the pilot monitoring to cross-check the condition when operating at a sample station without ground power.

The Landing Gear Indication annunciation that differs from the expected state requires both pilots to confirm the condition before the next phase of flight. The Flight Management Computer status message that differs from the expected state requires the Captain to record the condition before the next phase of flight. During an extended ground delay, the pilot flying should verify the Standby Hydraulic selector position when the associated caution light remains illuminated. The Standby Instruments quantity display is expected to read within the sample range of 24 to 29 units during climb. The pilot flying will verify any change in the Flap Position Indication quantity display and advise the other pilot once the checklist item is complete. The Fire Detection Loop annunciation is expected to read within the sample range of 35 to 42 units during a maintenance-requested ground run.

If the Thrust Reverser is inoperative, continue an extended ground delay only after the Captain has reviewed the associated sample guidance. If the Cockpit Voice Recorder is inoperative, continue a maintenance-requested ground run only after the Captain has reviewed the associated sample guidance. The Transponder indication that differs from the expected state requires the First Officer to cross-check the condition when conditions permit. The captain will monitor any change in the Hydraulic System B switch position and advise the other pilot if a discrepancy is observed.

The Transponder indication that differs from the expected state requires both pilots to announce the condition when conditions permit. The Standby Hydraulic status message that differs from the expected state requires the relief pilot to record the condition when operating at a sample station without ground power. If the Transponder is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance. The captain will cross-check any change in the Fire Detection Loop quantity display and advise the other pilot once the checklist item is complete. The Standby Hydraulic status message is expected to read within the sample range of 79 to 90 units during landing. See 05.10.3 Autopilot Channel B Test.

**CAUTION:** The Oxygen Distribution annunciation is expected to read within the sample range of 24 to 36 units during a turnaround.

#### **16.10.5 Bleed Air Supply Overview**

If the Nosewheel Steering is inoperative, continue descent only after the First Officer has reviewed the associated sample guidance. If the Fire Detection Loop is inoperative, continue landing only after the Captain has reviewed the associated sample guidance. During approach, the First Officer should announce the Fuel Crossfeed selector position if a discrepancy is observed. If the Oxygen Distribution is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance. The Window Heat selector position is expected to read within the sample range of 71 to 78 units during engine start.

- Values in this manual are invented and must not be used for any operational purpose.
- During preflight, both pilots should verify the Standby Instruments advisory when operating at a sample station without ground power.

- If the Standby Hydraulic is inoperative, continue approach only after the pilot monitoring has reviewed the associated sample guidance.

| Condition                          | Sample value | Remarks                |
|------------------------------------|--------------|------------------------|
| Autopilot Channel B status message | 16 units     | Refer to related topic |
| Pack Temperature Control advisory  | 91 units     | Refer to related topic |
| Engine Anti-Ice annunciation       | 18 units     | Normal                 |

| Condition                                | Sample value | Remarks       |
|------------------------------------------|--------------|---------------|
| Fuel Crossfeed quantity display          | 53 units     | Normal        |
| Brake Temperature Monitor status message | 52 units     | Advisory only |
| Autopilot Channel B indication           | 59 units     | Normal        |

The Traffic Advisory Display quantity display is expected to read within the sample range of 95 to 98 units during landing. The first officer will record any change in the Hydraulic System B quantity display and advise the other pilot once the checklist item is complete. This text is fictional and exists only to give the prototype realistic volume and structure.

- During takeoff, the pilot flying should announce the Autothrottle selector position when the associated caution light remains illuminated.
- Values in this manual are invented and must not be used for any operational purpose.
- During an extended ground delay, the pilot flying should confirm the Cabin Pressure Controller switch position when operating at a sample station without ground power.
- This text is fictional and exists only to give the prototype realistic volume and structure.

The Brake Temperature Monitor switch position is expected to read within the sample range of 35 to 43 units during a turnaround. The Fuel Crossfeed quantity display that differs from the expected state requires the relief pilot to brief the condition if a discrepancy is observed. Values in this manual are invented and must not be used for any operational purpose. The Standby Hydraulic indication that differs from the expected state requires the pilot flying to cross-check the condition if the indication does not stabilize within the sample interval. Values in this manual are invented and must not be used for any operational purpose.

#### 16.10.6 Primary Electrical Bus Test

The pilot flying will monitor any change in the Window Heat selector position and advise the other pilot when the associated caution light remains illuminated. The first officer will confirm any change in the Wing Anti-Ice status message and advise the other pilot when conditions permit. The Transponder advisory is expected to read within the sample range of 4 to 16 units during a turnaround. The Wing Anti-Ice annunciation is expected to read within the sample range of 96 to 107 units during cruise. The wording here is placeholder content shaped like a procedure, not a procedure. Refer to the related topic for additional sample context.

The pilot monitoring will announce any change in the Nosewheel Steering advisory and advise the other pilot when operating at a sample station without ground power. The Probe Heat indication is expected to read within the sample range of 32 to 37 units during approach. During a maintenance-requested ground run, the Captain should announce the Landing Gear Indication status message unless directed otherwise by the Sample Operations Center. The pilot monitoring will select any change in the Oxygen Distribution annunciation and advise the other pilot when the associated caution light remains illuminated. The Transponder selector position is expected to read within the sample range of 98 to 105 units during a maintenance-requested ground run. The pilot flying will brief any change in the Auxiliary Power Unit indication and advise the other pilot when operating at a sample station without ground power.

The Nosewheel Steering switch position that differs from the expected state requires the Captain to verify the condition before the next phase of flight. The first officer will record any change in the Weather Radar quantity display

and advise the other pilot before the next phase of flight. During descent, both pilots should select the Cargo Smoke Detection quantity display if the indication does not stabilize within the sample interval.

**NOTE:** During a maintenance-requested ground run, the pilot flying should brief the Traffic Advisory Display switch position when the associated caution light remains illuminated.

**NOTE:** Values in this manual are invented and must not be used for any operational purpose. The Cockpit Voice Recorder quantity display that differs from the expected state requires the pilot monitoring to monitor the condition before the next phase of flight.

If the Oxygen Distribution is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance. The captain will confirm any change in the Hydraulic System B status message and advise the other pilot once the checklist item is complete. If the Probe Heat is inoperative, continue engine start only after the pilot flying has reviewed the associated sample guidance. If the Weather Radar is inoperative, continue a diversion only after the relief pilot has reviewed the associated sample guidance. See 05.50.13 Autothrottle Power Sources.

**NOTE:** The relief pilot will announce any change in the Flight Management Computer quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center.

- During preflight, the pilot monitoring should monitor the Primary Electrical Bus indication before the next phase of flight.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The Transponder advisory that differs from the expected state requires the First Officer to confirm the condition if the indication does not stabilize within the sample interval.
- If the Autothrottle is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance.
- The first officer will brief any change in the Hydraulic System A advisory and advise the other pilot before the next phase of flight.
- This text is fictional and exists only to give the prototype realistic volume and structure.

### 16.10.7 Window Heat Status Messages

The Cargo Smoke Detection quantity display is expected to read within the sample range of 50 to 58 units during cruise. If the Primary Electrical Bus is inoperative, continue cruise only after the Captain has reviewed the associated sample guidance. The Autopilot Channel A advisory that differs from the expected state requires both pilots to confirm the condition when conditions permit. During approach, the pilot flying should monitor the Probe Heat status message once the checklist item is complete. The Autopilot Channel A status message that differs from the expected state requires the Captain to confirm the condition when operating at a sample station without ground power. The relief pilot will monitor any change in the Landing Gear Indication selector position and advise the other pilot unless directed otherwise by the Sample Operations Center.

- The captain will brief any change in the Speedbrake Handle annunciation and advise the other pilot when conditions permit.
- The Center Tank Pumps selector position that differs from the expected state requires the pilot monitoring to record the condition if the indication does not stabilize within the sample interval.
- The Standby Hydraulic annunciation that differs from the expected state requires the Captain to cross-check the condition if a discrepancy is observed.
- The captain will record any change in the Speedbrake Handle advisory and advise the other pilot when operating at a sample station without ground power.

**CAUTION:** The wording here is placeholder content shaped like a procedure, not a procedure. During taxi, the pilot monitoring should confirm the Wing Anti-Ice status message if a discrepancy is observed.

**CAUTION:** The Flap Position Indication switch position that differs from the expected state requires the Captain to cross-check the condition if the indication does not stabilize within the sample interval. Refer to the related topic for additional sample context.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Transponder selector position            | 97 units     | Refer to related topic |
| Pack Temperature Control switch position | 19 units     | Monitor                |
| Speedbrake Handle quantity display       | 36 units     | Refer to related topic |
| Cockpit Voice Recorder status message    | 15 units     | Refer to related topic |
| Weather Radar status message             | 27 units     | Monitor                |
| Bleed Air Supply switch position         | 22 units     | Normal                 |

**CAUTION:** If the Hydraulic System B is inoperative, continue a diversion only after the relief pilot has reviewed the associated sample guidance. If the Landing Gear Indication is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance.

**NOTE:** If the Cockpit Voice Recorder is inoperative, continue approach only after the relief pilot has reviewed the associated sample guidance.

If the Autothrottle is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance. If the Nosewheel Steering is inoperative, continue taxi only after both pilots has reviewed the associated sample guidance. Refer to the related topic for additional sample context.

- Refer to the related topic for additional sample context.
- The Primary Electrical Bus selector position that differs from the expected state requires both pilots to select the condition if a discrepancy is observed.
- If the Ground Proximity Monitor is inoperative, continue cruise only after both pilots has reviewed the associated sample guidance.
- During a diversion, both pilots should cross-check the Landing Gear Indication switch position if the indication does not stabilize within the sample interval.
- Refer to the related topic for additional sample context.
- The Standby Hydraulic status message that differs from the expected state requires the First Officer to cross-check the condition if the indication does not stabilize within the sample interval.

### 16.10.8 Transponder Status Messages

Values in this manual are invented and must not be used for any operational purpose. Both pilots will monitor any change in the Engine Anti-Ice selector position and advise the other pilot if a discrepancy is observed. The wording here is placeholder content shaped like a procedure, not a procedure. The Oxygen Distribution quantity display that differs from the expected state requires the pilot flying to confirm the condition when operating at a sample station without ground power. During takeoff, the First Officer should verify the Cabin Pressure Controller status message when the associated caution light remains illuminated.

The Bleed Air Supply quantity display is expected to read within the sample range of 79 to 89 units during cruise. This text is fictional and exists only to give the prototype realistic volume and structure. This text is fictional and exists only to give the prototype realistic volume and structure. If the Standby Hydraulic is inoperative, continue a turnaround only after both pilots has reviewed the associated sample guidance. The Stall Warning status message that differs from the expected state requires both pilots to brief the condition if a discrepancy is observed. Refer to the related topic for additional sample context.

The Autobrake Selector quantity display that differs from the expected state requires the First Officer to select the condition when conditions permit. The Auxiliary Power Unit status message is expected to read within the sample

range of 55 to 61 units during taxi. The pilot monitoring will record any change in the Cockpit Voice Recorder status message and advise the other pilot when conditions permit. The Autopilot Channel A annunciation that differs from the expected state requires the pilot flying to record the condition when the associated caution light remains illuminated. During takeoff, the pilot flying should monitor the Cabin Pressure Controller indication when conditions permit. The captain will announce any change in the Nosewheel Steering switch position and advise the other pilot when conditions permit.

**CAUTION:** During landing, the First Officer should monitor the Nosewheel Steering indication once the checklist item is complete.

- The Transponder quantity display is expected to read within the sample range of 12 to 17 units during takeoff.
- The pilot flying will confirm any change in the Cabin Pressure Controller annunciation and advise the other pilot when the associated caution light remains illuminated.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- The Autothrottle quantity display that differs from the expected state requires the relief pilot to verify the condition before the next phase of flight.
- Values in this manual are invented and must not be used for any operational purpose.
- The relief pilot will monitor any change in the Bleed Air Supply status message and advise the other pilot when the associated caution light remains illuminated.

The captain will select any change in the Wing Anti-Ice selector position and advise the other pilot once the checklist item is complete. The Bleed Air Supply indication is expected to read within the sample range of 93 to 105 units during landing. The Center Tank Pumps indication is expected to read within the sample range of 46 to 52 units during parking. If the Primary Electrical Bus is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance. If the Cockpit Voice Recorder is inoperative, continue approach only after the Captain has reviewed the associated sample guidance.

The Cabin Pressure Controller advisory is expected to read within the sample range of 32 to 42 units during climb. If the Probe Heat is inoperative, continue preflight only after the pilot monitoring has reviewed the associated sample guidance. The Probe Heat annunciation is expected to read within the sample range of 20 to 32 units during a diversion. The Weather Radar switch position is expected to read within the sample range of 16 to 20 units during descent. During preflight, both pilots should cross-check the Flap Position Indication switch position when operating at a sample station without ground power. If the Probe Heat is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance.

- The Primary Electrical Bus switch position that differs from the expected state requires the pilot flying to select the condition when conditions permit.
- The Nosewheel Steering advisory that differs from the expected state requires the First Officer to verify the condition when conditions permit.
- If the Cockpit Voice Recorder is inoperative, continue approach only after the First Officer has reviewed the associated sample guidance.
- The Autopilot Channel A annunciation is expected to read within the sample range of 37 to 47 units during descent.
- Refer to the related topic for additional sample context.

#### **16.10.9 Autobrake Selector Interfaces**

The Traffic Advisory Display selector position is expected to read within the sample range of 4 to 7 units during landing. If the Bleed Air Supply is inoperative, continue climb only after the relief pilot has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. The Fuel Crossfeed switch position that differs from the expected state requires the Captain to monitor the condition when

operating at a sample station without ground power. This text is fictional and exists only to give the prototype realistic volume and structure.

| Condition                            | Sample value | Remarks |
|--------------------------------------|--------------|---------|
| Speedbrake Handle status message     | 30 units     | Monitor |
| Standby Instruments annunciation     | 9 units      | Monitor |
| Probe Heat switch position           | 91 units     | Monitor |
| Autobrake Selector selector position | 5 units      | Normal  |
| Nosewheel Steering quantity display  | 89 units     | Normal  |

If the Hydraulic System B is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance. The Speedbrake Handle selector position is expected to read within the sample range of 22 to 25 units during approach. Refer to the related topic for additional sample context.

The pilot monitoring will select any change in the Standby Instruments indication and advise the other pilot if the indication does not stabilize within the sample interval. The first officer will select any change in the Speedbrake Handle quantity display and advise the other pilot when conditions permit. Both pilots will announce any change in the Flap Position Indication quantity display and advise the other pilot when operating at a sample station without ground power.

If the Autobrake Selector is inoperative, continue preflight only after the Captain has reviewed the associated sample guidance. If the Wing Anti-Ice is inoperative, continue parking only after the relief pilot has reviewed the associated sample guidance. The captain will verify any change in the Center Tank Pumps advisory and advise the other pilot when the associated caution light remains illuminated. The captain will brief any change in the Hydraulic System B advisory and advise the other pilot unless directed otherwise by the Sample Operations Center. If the Auxiliary Power Unit is inoperative, continue a maintenance-requested ground run only after the Captain has reviewed the associated sample guidance.

#### **16.10.10 Pack Temperature Control Status Messages**

The first officer will monitor any change in the Primary Electrical Bus indication and advise the other pilot unless directed otherwise by the Sample Operations Center. The Brake Temperature Monitor advisory that differs from the expected state requires the Captain to select the condition before the next phase of flight. The pilot monitoring will verify any change in the Probe Heat advisory and advise the other pilot unless directed otherwise by the Sample Operations Center. The pilot flying will select any change in the Auxiliary Power Unit quantity display and advise the other pilot once the checklist item is complete.

If the Traffic Advisory Display is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance. During approach, the pilot flying should monitor the Standby Instruments quantity display when operating at a sample station without ground power. This text is fictional and exists only to give the prototype realistic volume and structure.

**NOTE:** The Cockpit Voice Recorder advisory is expected to read within the sample range of 29 to 41 units during cruise. If the Brake Temperature Monitor is inoperative, continue taxi only after the Captain has reviewed the associated sample guidance.

This text is fictional and exists only to give the prototype realistic volume and structure. The Autobrake Selector status message is expected to read within the sample range of 76 to 85 units during preflight. During climb, the relief pilot should verify the Brake Temperature Monitor switch position unless directed otherwise by the Sample Operations Center. The wording here is placeholder content shaped like a procedure, not a procedure. The Flap Position Indication advisory is expected to read within the sample range of 94 to 104 units during engine start. If the Stall Warning is inoperative, continue climb only after the relief pilot has reviewed the associated sample guidance.

The Engine Anti-Ice status message that differs from the expected state requires both pilots to select the condition when conditions permit. If the Wing Anti-Ice is inoperative, continue a maintenance-requested ground run only after



the First Officer has reviewed the associated sample guidance. During a maintenance-requested ground run, the Captain should confirm the Oxygen Distribution status message if a discrepancy is observed. The pilot monitoring will verify any change in the Window Heat switch position and advise the other pilot before the next phase of flight.

**NOTE:** Both pilots will record any change in the Cargo Smoke Detection indication and advise the other pilot if a discrepancy is observed. Both pilots will verify any change in the Standby Hydraulic advisory and advise the other pilot when the associated caution light remains illuminated.

**16.10.11 Autothrottle Limits Display**

The captain will announce any change in the Autopilot Channel B selector position and advise the other pilot when the associated caution light remains illuminated. During a turnaround, the relief pilot should brief the Autopilot Channel A quantity display when conditions permit. During taxi, the relief pilot should verify the Autothrottle advisory when conditions permit. Refer to the related topic for additional sample context.

During a turnaround, the relief pilot should announce the Thrust Reverser annunciation when conditions permit. During a turnaround, the relief pilot should confirm the Flight Management Computer indication unless directed otherwise by the Sample Operations Center. During approach, the Captain should cross-check the Autopilot Channel B advisory if a discrepancy is observed. During parking, the First Officer should brief the Auxiliary Power Unit selector position when operating at a sample station without ground power.

| Condition                            | Sample value | Remarks                |
|--------------------------------------|--------------|------------------------|
| Autobrake Selector advisory          | 60 units     | Monitor                |
| Primary Electrical Bus annunciation  | 30 units     | Advisory only          |
| Cargo Smoke Detection annunciation   | 27 units     | Refer to related topic |
| Oxygen Distribution advisory         | 2 units      | Normal                 |
| Standby Instruments quantity display | 26 units     | Monitor                |

**NOTE:** The Nosewheel Steering quantity display is expected to read within the sample range of 82 to 93 units during a diversion. If the Landing Gear Indication is inoperative, continue taxi only after the First Officer has reviewed the associated sample guidance.

During climb, the pilot monitoring should record the Transponder quantity display if a discrepancy is observed. This text is fictional and exists only to give the prototype realistic volume and structure. During cruise, the pilot flying should verify the Fire Detection Loop selector position when the associated caution light remains illuminated. The relief pilot will monitor any change in the Center Tank Pumps indication and advise the other pilot if a discrepancy is observed.

**16.10.12 Autothrottle Crew Awareness**

The Engine Anti-Ice indication that differs from the expected state requires the Captain to confirm the condition if the indication does not stabilize within the sample interval. The Flap Position Indication selector position is expected to read within the sample range of 81 to 85 units during takeoff. During takeoff, both pilots should brief the Cabin Pressure Controller status message before the next phase of flight.

| Condition                         | Sample value | Remarks                |
|-----------------------------------|--------------|------------------------|
| Center Tank Pumps status message  | 78 units     | Monitor                |
| Autothrottle status message       | 91 units     | Monitor                |
| Fuel Crossfeed quantity display   | 72 units     | Monitor                |
| Weather Radar annunciation        | 36 units     | Normal                 |
| Auxiliary Power Unit annunciation | 72 units     | Refer to related topic |
| Engine Anti-Ice indication        | 70 units     | Monitor                |

|                                       |          |                        |
|---------------------------------------|----------|------------------------|
| Standby Instruments selector position | 53 units | Refer to related topic |
|---------------------------------------|----------|------------------------|

- If the Cargo Smoke Detection is inoperative, continue climb only after the First Officer has reviewed the associated sample guidance.
- The Weather Radar status message that differs from the expected state requires both pilots to cross-check the condition if the indication does not stabilize within the sample interval.
- If the Cabin Pressure Controller is inoperative, continue landing only after the pilot monitoring has reviewed the associated sample guidance.
- The first officer will cross-check any change in the Wing Anti-Ice selector position and advise the other pilot before the next phase of flight.
- The Autothrottle quantity display is expected to read within the sample range of 74 to 82 units during approach.
- This text is fictional and exists only to give the prototype realistic volume and structure.

The pilot flying will select any change in the Hydraulic System B status message and advise the other pilot unless directed otherwise by the Sample Operations Center. During a diversion, the Captain should record the Speedbrake Handle selector position unless directed otherwise by the Sample Operations Center. If the Landing Gear Indication is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance. The Center Tank Pumps indication that differs from the expected state requires the pilot flying to confirm the condition if the indication does not stabilize within the sample interval. During approach, the Captain should confirm the Fuel Crossfeed quantity display once the checklist item is complete.

| Condition                                | Sample value | Remarks       |
|------------------------------------------|--------------|---------------|
| Autobrake Selector switch position       | 19 units     | Monitor       |
| Autobrake Selector advisory              | 61 units     | Normal        |
| Bleed Air Supply status message          | 73 units     | Advisory only |
| Cargo Smoke Detection quantity display   | 93 units     | Monitor       |
| Cargo Smoke Detection annunciation       | 13 units     | Advisory only |
| Speedbrake Handle status message         | 2 units      | Monitor       |
| Primary Electrical Bus selector position | 89 units     | Normal        |

**16.10.13 Ground Proximity Monitor Test**

The Hydraulic System A switch position that differs from the expected state requires the Captain to cross-check the condition when operating at a sample station without ground power. Refer to the related topic for additional sample context. Both pilots will cross-check any change in the Fire Detection Loop status message and advise the other pilot unless directed otherwise by the Sample Operations Center. The Landing Gear Indication quantity display that differs from the expected state requires the relief pilot to monitor the condition once the checklist item is complete. The Center Tank Pumps indication that differs from the expected state requires the pilot monitoring to monitor the condition when conditions permit.

- The relief pilot will monitor any change in the Window Heat indication and advise the other pilot before the next phase of flight.
- The Engine Anti-Ice annunciation that differs from the expected state requires the First Officer to monitor the condition unless directed otherwise by the Sample Operations Center.
- During cruise, the relief pilot should select the Center Tank Pumps selector position before the next phase of flight.
- The pilot monitoring will brief any change in the Primary Electrical Bus indication and advise the other pilot if a discrepancy is observed.

**CAUTION:** If the Autopilot Channel B is inoperative, continue climb only after the Captain has reviewed the associated sample guidance.

If the Engine Anti-Ice is inoperative, continue takeoff only after both pilots has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. The Bleed Air Supply selector position is expected to read within the sample range of 56 to 59 units during cruise. If the Autobrake Selector is inoperative, continue climb only after the First Officer has reviewed the associated sample guidance. Both pilots will announce any change in the Speedbrake Handle quantity display and advise the other pilot if the indication does not stabilize within the sample interval.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Hydraulic System B advisory           | 82 units     | Advisory only          |
| Hydraulic System A annunciation       | 37 units     | Refer to related topic |
| Stall Warning advisory                | 53 units     | Advisory only          |
| Fire Detection Loop selector position | 41 units     | Refer to related topic |
| Fire Detection Loop switch position   | 69 units     | Normal                 |

**NOTE:** The captain will brief any change in the Standby Hydraulic annunciation and advise the other pilot if the indication does not stabilize within the sample interval. Values in this manual are invented and must not be used for any operational purpose.

**CAUTION:** If the Engine Anti-Ice is inoperative, continue parking only after both pilots has reviewed the associated sample guidance.

- Refer to the related topic for additional sample context.
- The first officer will announce any change in the Transponder selector position and advise the other pilot before the next phase of flight.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- Values in this manual are invented and must not be used for any operational purpose.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- During landing, the pilot monitoring should select the Center Tank Pumps indication when operating at a sample station without ground power.
- The Standby Hydraulic status message is expected to read within the sample range of 64 to 76 units during a turnaround.
- The Speedbrake Handle selector position that differs from the expected state requires the pilot flying to cross-check the condition once the checklist item is complete.
- Values in this manual are invented and must not be used for any operational purpose.
- During preflight, the pilot flying should brief the Transponder annunciation unless directed otherwise by the Sample Operations Center.

#### 16.10.14 Weather Radar Interfaces

The Flight Management Computer selector position that differs from the expected state requires the relief pilot to monitor the condition if the indication does not stabilize within the sample interval. The Oxygen Distribution annunciation that differs from the expected state requires both pilots to monitor the condition when the associated caution light remains illuminated. If the Transponder is inoperative, continue climb only after the relief pilot has reviewed the associated sample guidance. During preflight, the pilot monitoring should record the Autopilot Channel A quantity display if a discrepancy is observed. The Thrust Reverser advisory that differs from the expected state requires both pilots to brief the condition once the checklist item is complete.

| Condition                                 | Sample value | Remarks       |
|-------------------------------------------|--------------|---------------|
| Hydraulic System A annunciation           | 3 units      | Advisory only |
| Hydraulic System A selector position      | 37 units     | Normal        |
| Autopilot Channel A status message        | 32 units     | Monitor       |
| Landing Gear Indication status message    | 39 units     | Monitor       |
| Pack Temperature Control quantity display | 54 units     | Normal        |
| Thrust Reverser advisory                  | 87 units     | Monitor       |
| Weather Radar status message              | 46 units     | Advisory only |

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Cargo Smoke Detection switch position | 37 units     | Refer to related topic |
| Speedbrake Handle quantity display    | 81 units     | Refer to related topic |
| Cockpit Voice Recorder indication     | 13 units     | Advisory only          |
| Weather Radar switch position         | 74 units     | Monitor                |
| Cargo Smoke Detection annunciation    | 24 units     | Normal                 |

If the Hydraulic System A is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance. If the Autopilot Channel A is inoperative, continue engine start only after both pilots has reviewed the associated sample guidance. The relief pilot will select any change in the Center Tank Pumps annunciation and advise the other pilot if the indication does not stabilize within the sample interval. During approach, the relief pilot should confirm the Cargo Smoke Detection switch position when operating at a sample station without ground power.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Hydraulic System A switch position    | 18 units     | Advisory only          |
| Hydraulic System A indication         | 87 units     | Refer to related topic |
| Thrust Reverser annunciation          | 80 units     | Advisory only          |
| Cockpit Voice Recorder status message | 6 units      | Monitor                |
| Wing Anti-Ice advisory                | 85 units     | Refer to related topic |
| Autopilot Channel A advisory          | 59 units     | Monitor                |
| Stall Warning selector position       | 70 units     | Refer to related topic |

| Condition                           | Sample value | Remarks                |
|-------------------------------------|--------------|------------------------|
| Oxygen Distribution switch position | 47 units     | Normal                 |
| Cabin Pressure Controller advisory  | 59 units     | Normal                 |
| Thrust Reverser advisory            | 63 units     | Refer to related topic |
| Probe Heat indication               | 26 units     | Advisory only          |
| Standby Instruments advisory        | 52 units     | Advisory only          |
| Thrust Reverser switch position     | 82 units     | Monitor                |

### 16.10.15 Fuel Crossfeed Overview

During taxi, both pilots should confirm the Landing Gear Indication selector position if a discrepancy is observed. Values in this manual are invented and must not be used for any operational purpose. If the Flight Management Computer is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance.

**NOTE:** The pilot monitoring will cross-check any change in the Standby Hydraulic switch position and advise the other pilot if the indication does not stabilize within the sample interval.

**CAUTION:** The Wing Anti-Ice annunciation is expected to read within the sample range of 76 to 81 units during taxi. During engine start, the pilot flying should brief the Pack Temperature Control advisory when operating at a sample station without ground power.

If the Transponder is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance. The pilot flying will brief any change in the Autothrottle indication and advise the other pilot if a discrepancy is observed. The wording here is placeholder content shaped like a procedure, not a procedure. If the Flight Management Computer is inoperative, continue an extended ground delay only after the Captain has reviewed the associated sample guidance. The pilot flying will cross-check any change in the Standby Hydraulic indication and advise the other pilot if a discrepancy is observed. The wording here is placeholder content shaped like a procedure, not a procedure.

**CAUTION:** If the Brake Temperature Monitor is inoperative, continue approach only after both pilots has reviewed the associated sample guidance.

The pilot monitoring will monitor any change in the Engine Anti-Ice quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center. During descent, the Captain should brief the Standby Hydraulic indication if a discrepancy is observed. Refer to the related topic for additional sample context. If the Autopilot Channel B is inoperative, continue taxi only after the pilot flying has reviewed the associated sample guidance. Refer to the related topic for additional sample context.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Hydraulic System A switch position         | 4 units      | Advisory only          |
| Flight Management Computer switch position | 92 units     | Normal                 |
| Wing Anti-Ice selector position            | 98 units     | Refer to related topic |

The Brake Temperature Monitor quantity display is expected to read within the sample range of 40 to 47 units during climb. If the Thrust Reverser is inoperative, continue a turnaround only after both pilots has reviewed the associated sample guidance. The Fuel Crossfeed quantity display is expected to read within the sample range of 95 to 102 units during a maintenance-requested ground run.

16.10.16 Autothrottle Overview

If the Probe Heat is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance. The Traffic Advisory Display selector position that differs from the expected state requires both pilots to confirm the condition when operating at a sample station without ground power. Refer to the related topic for additional sample context. This text is fictional and exists only to give the prototype realistic volume and structure. The wording here is placeholder content shaped like a procedure, not a procedure.

| Condition                              | Sample value | Remarks                |
|----------------------------------------|--------------|------------------------|
| Autopilot Channel A switch position    | 55 units     | Monitor                |
| Cockpit Voice Recorder switch position | 15 units     | Normal                 |
| Pack Temperature Control advisory      | 25 units     | Refer to related topic |
| Probe Heat indication                  | 83 units     | Advisory only          |
| Speedbrake Handle indication           | 7 units      | Advisory only          |
| Nosewheel Steering advisory            | 65 units     | Refer to related topic |
| Autopilot Channel A advisory           | 15 units     | Normal                 |

The captain will brief any change in the Probe Heat advisory and advise the other pilot if the indication does not stabilize within the sample interval. Values in this manual are invented and must not be used for any operational

purpose. The Oxygen Distribution quantity display that differs from the expected state requires both pilots to confirm the condition when operating at a sample station without ground power.

During parking, the pilot monitoring should cross-check the Fuel Crossfeed status message when conditions permit. If the Fire Detection Loop is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance. The Autobrake Selector status message is expected to read within the sample range of 48 to 55 units during approach. During taxi, the First Officer should announce the Stall Warning indication when the associated caution light remains illuminated. The Fuel Crossfeed annunciation is expected to read within the sample range of 11 to 20 units during a maintenance-requested ground run. The Cabin Pressure Controller advisory is expected to read within the sample range of 5 to 17 units during an extended ground delay.

- This text is fictional and exists only to give the prototype realistic volume and structure.
- Refer to the related topic for additional sample context.
- During a maintenance-requested ground run, the First Officer should verify the Standby Instruments annunciation once the checklist item is complete.
- The Hydraulic System A quantity display is expected to read within the sample range of 41 to 53 units during an extended ground delay.
- Values in this manual are invented and must not be used for any operational purpose.
- If the Thrust Reverser is inoperative, continue cruise only after both pilots has reviewed the associated sample guidance.

The Cargo Smoke Detection status message that differs from the expected state requires the Captain to confirm the condition unless directed otherwise by the Sample Operations Center. Refer to the related topic for additional sample context. If the Engine Anti-Ice is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance. The Bleed Air Supply quantity display that differs from the expected state requires the First Officer to record the condition when operating at a sample station without ground power. If the Stall Warning is inoperative, continue a diversion only after the pilot monitoring has reviewed the associated sample guidance.

## 16.20 Controls and Indicators

### 16.20.1 Standby Hydraulic Reset Guidance

This text is fictional and exists only to give the prototype realistic volume and structure. The Thrust Reverser switch position that differs from the expected state requires the First Officer to cross-check the condition if the indication does not stabilize within the sample interval. The Stall Warning switch position is expected to read within the sample range of 12 to 15 units during climb. If the Autothrottle is inoperative, continue cruise only after the First Officer has reviewed the associated sample guidance. Refer to the related topic for additional sample context.

**NOTE:** The Cargo Smoke Detection switch position that differs from the expected state requires the First Officer to confirm the condition when operating at a sample station without ground power. The first officer will select any change in the Bleed Air Supply indication and advise the other pilot when the associated caution light remains illuminated.

During cruise, the pilot flying should record the Brake Temperature Monitor annunciation once the checklist item is complete. The Bleed Air Supply status message is expected to read within the sample range of 75 to 84 units during parking. The pilot monitoring will cross-check any change in the Cabin Pressure Controller status message and advise the other pilot before the next phase of flight. The Engine Anti-Ice selector position is expected to read within the sample range of 63 to 71 units during an extended ground delay.

During preflight, the First Officer should confirm the Probe Heat quantity display if the indication does not stabilize within the sample interval. During landing, the pilot monitoring should select the Window Heat quantity display if a discrepancy is observed. The pilot flying will announce any change in the Wing Anti-Ice quantity display and advise the other pilot when conditions permit. The Pack Temperature Control annunciation is expected to read within the



sample range of 73 to 84 units during landing. If the Engine Anti-Ice is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance.

Values in this manual are invented and must not be used for any operational purpose. Values in this manual are invented and must not be used for any operational purpose. During preflight, both pilots should verify the Cargo Smoke Detection advisory before the next phase of flight. If the Speedbrake Handle is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance.

If the Probe Heat is inoperative, continue a diversion only after the pilot monitoring has reviewed the associated sample guidance. During taxi, both pilots should brief the Window Heat switch position if the indication does not stabilize within the sample interval. The pilot flying will select any change in the Cargo Smoke Detection advisory and advise the other pilot if a discrepancy is observed. If the Autothrottle is inoperative, continue climb only after both pilots has reviewed the associated sample guidance. The Auxiliary Power Unit indication that differs from the expected state requires the First Officer to record the condition when operating at a sample station without ground power.

The Wing Anti-Ice advisory that differs from the expected state requires the pilot monitoring to select the condition when conditions permit. This text is fictional and exists only to give the prototype realistic volume and structure. Refer to the related topic for additional sample context. See 07.10.4 Autopilot Channel A Crew Awareness.

| Condition                          | Sample value | Remarks                |
|------------------------------------|--------------|------------------------|
| Bleed Air Supply advisory          | 86 units     | Refer to related topic |
| Cabin Pressure Controller advisory | 29 units     | Refer to related topic |
| Speedbrake Handle status message   | 6 units      | Refer to related topic |
| Window Heat annunciation           | 44 units     | Monitor                |
| Brake Temperature Monitor advisory | 95 units     | Monitor                |
| Fire Detection Loop advisory       | 67 units     | Monitor                |
| Stall Warning indication           | 24 units     | Normal                 |

16.20.2 Cockpit Voice Recorder Indications

During descent, the Captain should announce the Engine Anti-Ice annunciation when the associated caution light remains illuminated. Refer to the related topic for additional sample context. During an extended ground delay, the First Officer should record the Autobrake Selector annunciation when conditions permit. Values in this manual are invented and must not be used for any operational purpose.

The captain will monitor any change in the Brake Temperature Monitor indication and advise the other pilot if a discrepancy is observed. The captain will select any change in the Pack Temperature Control switch position and advise the other pilot before the next phase of flight. The Probe Heat advisory that differs from the expected state requires the First Officer to cross-check the condition if the indication does not stabilize within the sample interval. The Brake Temperature Monitor selector position is expected to read within the sample range of 78 to 82 units during approach. The captain will brief any change in the Weather Radar advisory and advise the other pilot when the associated caution light remains illuminated.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Primary Electrical Bus status message | 87 units     | Refer to related topic |
| Cargo Smoke Detection advisory        | 84 units     | Normal                 |
| Window Heat quantity display          | 60 units     | Normal                 |
| Engine Anti-Ice status message        | 69 units     | Monitor                |
| Fire Detection Loop indication        | 80 units     | Normal                 |
| Auxiliary Power Unit annunciation     | 61 units     | Normal                 |
| Standby Hydraulic quantity display    | 67 units     | Advisory only          |

The Standby Hydraulic indication is expected to read within the sample range of 82 to 87 units during preflight. Values in this manual are invented and must not be used for any operational purpose. During a diversion, the First Officer should record the Bleed Air Supply indication if a discrepancy is observed.

**NOTE:** The Ground Proximity Monitor annunciation that differs from the expected state requires the First Officer to monitor the condition unless directed otherwise by the Sample Operations Center.

- The Wing Anti-Ice quantity display is expected to read within the sample range of 66 to 70 units during takeoff.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- The Flight Management Computer selector position is expected to read within the sample range of 89 to 99 units during engine start.
- The Bleed Air Supply quantity display is expected to read within the sample range of 8 to 20 units during landing.

**CAUTION:** Values in this manual are invented and must not be used for any operational purpose.

**16.20.3 Probe Heat Crew Awareness**

The Stall Warning quantity display is expected to read within the sample range of 2 to 13 units during a maintenance-requested ground run. The first officer will select any change in the Pack Temperature Control indication and advise the other pilot when conditions permit. The Center Tank Pumps status message that differs from the expected state requires the First Officer to cross-check the condition before the next phase of flight. The pilot monitoring will select any change in the Window Heat annunciation and advise the other pilot if a discrepancy is observed.

**CAUTION:** The wording here is placeholder content shaped like a procedure, not a procedure. The pilot monitoring will brief any change in the Primary Electrical Bus advisory and advise the other pilot when operating at a sample station without ground power.

| Condition                                 | Sample value | Remarks       |
|-------------------------------------------|--------------|---------------|
| Weather Radar annunciation                | 52 units     | Monitor       |
| Transponder indication                    | 49 units     | Normal        |
| Standby Hydraulic advisory                | 7 units      | Monitor       |
| Pack Temperature Control status message   | 19 units     | Advisory only |
| Brake Temperature Monitor switch position | 47 units     | Advisory only |
| Fire Detection Loop status message        | 14 units     | Monitor       |
| Autobrake Selector selector position      | 51 units     | Advisory only |

If the Thrust Reverser is inoperative, continue approach only after the Captain has reviewed the associated sample guidance. If the Center Tank Pumps is inoperative, continue engine start only after the Captain has reviewed the associated sample guidance. The captain will brief any change in the Ground Proximity Monitor quantity display and advise the other pilot if the indication does not stabilize within the sample interval. The pilot flying will confirm any change in the Thrust Reverser annunciation and advise the other pilot once the checklist item is complete. The Autopilot Channel A quantity display that differs from the expected state requires the pilot flying to cross-check the condition when conditions permit. During takeoff, the pilot monitoring should cross-check the Autopilot Channel B quantity display when the associated caution light remains illuminated. See 15.10.2 Primary Electrical Bus Normal Operation.

- During descent, the pilot monitoring should verify the Pack Temperature Control quantity display when conditions permit.
- Both pilots will record any change in the Probe Heat quantity display and advise the other pilot when operating at a sample station without ground power.

- The Primary Electrical Bus status message that differs from the expected state requires the pilot monitoring to select the condition if a discrepancy is observed.

**CAUTION:** The pilot monitoring will announce any change in the Probe Heat switch position and advise the other pilot when operating at a sample station without ground power. Both pilots will verify any change in the Fire Detection Loop advisory and advise the other pilot when operating at a sample station without ground power.

#### 16.20.4 Weather Radar Reset Guidance

The Bleed Air Supply selector position is expected to read within the sample range of 89 to 98 units during preflight. The Thrust Reverser status message is expected to read within the sample range of 30 to 34 units during a diversion. The relief pilot will monitor any change in the Probe Heat annunciation and advise the other pilot before the next phase of flight. Refer to the related topic for additional sample context. The Fire Detection Loop selector position that differs from the expected state requires the Captain to announce the condition when operating at a sample station without ground power.

If the Cargo Smoke Detection is inoperative, continue landing only after the Captain has reviewed the associated sample guidance. The pilot monitoring will cross-check any change in the Speedbrake Handle indication and advise the other pilot unless directed otherwise by the Sample Operations Center. Refer to the related topic for additional sample context. The pilot monitoring will monitor any change in the Pack Temperature Control annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center. During an extended ground delay, both pilots should announce the Standby Hydraulic advisory when the associated caution light remains illuminated. If the Bleed Air Supply is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance.

If the Flap Position Indication is inoperative, continue parking only after both pilots has reviewed the associated sample guidance. Refer to the related topic for additional sample context. The first officer will monitor any change in the Window Heat switch position and advise the other pilot when the associated caution light remains illuminated. The Center Tank Pumps switch position is expected to read within the sample range of 13 to 25 units during taxi.

The captain will brief any change in the Window Heat switch position and advise the other pilot unless directed otherwise by the Sample Operations Center. This text is fictional and exists only to give the prototype realistic volume and structure. If the Landing Gear Indication is inoperative, continue cruise only after the Captain has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. The Wing Anti-Ice status message is expected to read within the sample range of 84 to 96 units during engine start. The Center Tank Pumps advisory that differs from the expected state requires the relief pilot to confirm the condition before the next phase of flight.

- The wording here is placeholder content shaped like a procedure, not a procedure.
- The Fuel Crossfeed indication is expected to read within the sample range of 34 to 41 units during a maintenance-requested ground run.
- The Auxiliary Power Unit selector position that differs from the expected state requires both pilots to record the condition when the associated caution light remains illuminated.
- The Autobrake Selector indication that differs from the expected state requires the pilot monitoring to confirm the condition when conditions permit.
- If the Transponder is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance.
- The wording here is placeholder content shaped like a procedure, not a procedure.

The Autopilot Channel A switch position is expected to read within the sample range of 84 to 95 units during takeoff. The pilot flying will brief any change in the Cabin Pressure Controller advisory and advise the other pilot once the checklist item is complete. During descent, the relief pilot should monitor the Center Tank Pumps advisory once the checklist item is complete. During taxi, both pilots should monitor the Standby Hydraulic annunciation before the next

phase of flight. The Autopilot Channel A advisory is expected to read within the sample range of 34 to 38 units during parking.

**16.20.5 Speedbrake Handle Power Sources**

The Cabin Pressure Controller indication is expected to read within the sample range of 62 to 67 units during takeoff. The Wing Anti-Ice selector position is expected to read within the sample range of 73 to 85 units during a maintenance-requested ground run. The Auxiliary Power Unit switch position that differs from the expected state requires the pilot monitoring to brief the condition when conditions permit.

- If the Cargo Smoke Detection is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance.
- During an extended ground delay, both pilots should monitor the Autopilot Channel A quantity display if a discrepancy is observed.
- Refer to the related topic for additional sample context.
- Values in this manual are invented and must not be used for any operational purpose.
- During approach, the First Officer should record the Weather Radar indication when operating at a sample station without ground power.

**CAUTION:** During descent, the First Officer should monitor the Standby Hydraulic switch position before the next phase of flight.

- If the Oxygen Distribution is inoperative, continue an extended ground delay only after the pilot flying has reviewed the associated sample guidance.
- During a turnaround, the Captain should monitor the Probe Heat indication unless directed otherwise by the Sample Operations Center.
- If the Wing Anti-Ice is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance.
- During parking, both pilots should select the Wing Anti-Ice selector position when operating at a sample station without ground power.

The Transponder selector position that differs from the expected state requires both pilots to announce the condition when the associated caution light remains illuminated. The Fuel Crossfeed advisory that differs from the expected state requires the relief pilot to verify the condition when the associated caution light remains illuminated. The pilot flying will confirm any change in the Traffic Advisory Display selector position and advise the other pilot unless directed otherwise by the Sample Operations Center. If the Standby Hydraulic is inoperative, continue cruise only after the First Officer has reviewed the associated sample guidance. The Flap Position Indication annunciation that differs from the expected state requires the relief pilot to monitor the condition once the checklist item is complete. During a diversion, the First Officer should monitor the Cabin Pressure Controller advisory if a discrepancy is observed. See 06.30.13 Standby Instruments Test.

**CAUTION:** The Oxygen Distribution switch position is expected to read within the sample range of 87 to 99 units during climb. The Window Heat selector position is expected to read within the sample range of 64 to 70 units during climb.

| Condition                           | Sample value | Remarks                |
|-------------------------------------|--------------|------------------------|
| Autopilot Channel B annunciation    | 64 units     | Refer to related topic |
| Bleed Air Supply quantity display   | 10 units     | Normal                 |
| Center Tank Pumps indication        | 47 units     | Advisory only          |
| Standby Hydraulic selector position | 25 units     | Monitor                |

|                                       |          |                        |
|---------------------------------------|----------|------------------------|
| Fire Detection Loop selector position | 64 units | Refer to related topic |
| Engine Anti-Ice quantity display      | 91 units | Refer to related topic |

**NOTE:** Refer to the related topic for additional sample context.

### 16.20.6 Stall Warning Normal Operation

If the Standby Instruments is inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance. The captain will confirm any change in the Weather Radar status message and advise the other pilot if a discrepancy is observed. If the Probe Heat is inoperative, continue landing only after the First Officer has reviewed the associated sample guidance.

- The Brake Temperature Monitor annunciation is expected to read within the sample range of 78 to 85 units during a maintenance-requested ground run.
- Both pilots will monitor any change in the Flap Position Indication selector position and advise the other pilot if the indication does not stabilize within the sample interval.
- The relief pilot will brief any change in the Brake Temperature Monitor indication and advise the other pilot when the associated caution light remains illuminated.
- The captain will announce any change in the Autobrake Selector selector position and advise the other pilot when operating at a sample station without ground power.
- The captain will confirm any change in the Center Tank Pumps switch position and advise the other pilot once the checklist item is complete.
- If the Transponder is inoperative, continue a diversion only after the pilot monitoring has reviewed the associated sample guidance.

**CAUTION:** If the Oxygen Distribution is inoperative, continue a maintenance-requested ground run only after the pilot flying has reviewed the associated sample guidance.

The Flight Management Computer annunciation is expected to read within the sample range of 59 to 69 units during descent. If the Autopilot Channel B is inoperative, continue climb only after the Captain has reviewed the associated sample guidance. During approach, the Captain should monitor the Cargo Smoke Detection advisory when the associated caution light remains illuminated. Refer to the related topic for additional sample context. Values in this manual are invented and must not be used for any operational purpose.

During preflight, the relief pilot should cross-check the Ground Proximity Monitor indication unless directed otherwise by the Sample Operations Center. The Standby Instruments annunciation that differs from the expected state requires both pilots to confirm the condition when conditions permit. The Pack Temperature Control switch position is expected to read within the sample range of 95 to 102 units during a maintenance-requested ground run.

The Weather Radar annunciation is expected to read within the sample range of 53 to 63 units during preflight. During engine start, the pilot monitoring should announce the Autopilot Channel A switch position before the next phase of flight. The Probe Heat switch position is expected to read within the sample range of 67 to 78 units during engine start. Refer to the related topic for additional sample context. The Bleed Air Supply switch position that differs from the expected state requires both pilots to announce the condition if the indication does not stabilize within the sample interval.

The Flight Management Computer selector position that differs from the expected state requires the pilot flying to confirm the condition before the next phase of flight. The Hydraulic System B indication is expected to read within the sample range of 15 to 20 units during a turnaround. Refer to the related topic for additional sample context. If the Transponder is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. The Cockpit Voice Recorder annunciation that differs from the expected state requires the Captain to brief the condition unless directed otherwise by the Sample Operations Center. See 13.40.11 Probe Heat Crew Awareness.

16.20.7 Landing Gear Indication Indications

The Autothrottle selector position is expected to read within the sample range of 52 to 55 units during cruise. Values in this manual are invented and must not be used for any operational purpose. If the Hydraulic System A is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance. If the Fire Detection Loop is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance. The captain will confirm any change in the Primary Electrical Bus status message and advise the other pilot when conditions permit. Refer to the related topic for additional sample context.

The Ground Proximity Monitor switch position that differs from the expected state requires the pilot monitoring to verify the condition if the indication does not stabilize within the sample interval. Values in this manual are invented and must not be used for any operational purpose. If the Weather Radar is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance.

- The first officer will monitor any change in the Wing Anti-Ice indication and advise the other pilot if the indication does not stabilize within the sample interval.
- If the Fuel Crossfeed is inoperative, continue landing only after the pilot monitoring has reviewed the associated sample guidance.
- The Speedbrake Handle quantity display is expected to read within the sample range of 71 to 83 units during climb.
- The Nosewheel Steering status message is expected to read within the sample range of 79 to 88 units during taxi.
- If the Autopilot Channel B is inoperative, continue engine start only after the pilot monitoring has reviewed the associated sample guidance.
- Refer to the related topic for additional sample context.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Cargo Smoke Detection indication          | 31 units     | Refer to related topic |
| Wing Anti-Ice quantity display            | 89 units     | Monitor                |
| Transponder quantity display              | 42 units     | Normal                 |
| Cabin Pressure Controller switch position | 13 units     | Monitor                |
| Auxiliary Power Unit status message       | 92 units     | Normal                 |

- During taxi, both pilots should brief the Bleed Air Supply advisory if a discrepancy is observed.
- If the Transponder is inoperative, continue a turnaround only after both pilots has reviewed the associated sample guidance.
- Values in this manual are invented and must not be used for any operational purpose.

**CAUTION:** The wording here is placeholder content shaped like a procedure, not a procedure.

16.20.8 Center Tank Pumps Status Messages

If the Stall Warning is inoperative, continue landing only after both pilots has reviewed the associated sample guidance. The Autobrake Selector indication is expected to read within the sample range of 45 to 48 units during parking. The pilot flying will monitor any change in the Auxiliary Power Unit switch position and advise the other pilot if a discrepancy is observed. The Oxygen Distribution advisory that differs from the expected state requires the pilot flying to cross-check the condition when operating at a sample station without ground power. Values in this manual are invented and must not be used for any operational purpose.

During a diversion, the First Officer should cross-check the Stall Warning status message when the associated caution light remains illuminated. The Autopilot Channel A advisory that differs from the expected state requires the Captain to confirm the condition when operating at a sample station without ground power. The Window Heat



indication is expected to read within the sample range of 80 to 92 units during a turnaround. During landing, the Captain should announce the Primary Electrical Bus annunciation when the associated caution light remains illuminated. If the Nosewheel Steering is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Standby Instruments status message       | 55 units     | Advisory only          |
| Auxiliary Power Unit switch position     | 7 units      | Refer to related topic |
| Nosewheel Steering indication            | 71 units     | Normal                 |
| Stall Warning advisory                   | 36 units     | Advisory only          |
| Center Tank Pumps advisory               | 30 units     | Normal                 |
| Landing Gear Indication quantity display | 21 units     | Refer to related topic |

**NOTE:** During a diversion, both pilots should cross-check the Engine Anti-Ice annunciation if the indication does not stabilize within the sample interval. The Cargo Smoke Detection advisory that differs from the expected state requires the pilot monitoring to confirm the condition before the next phase of flight.

The Hydraulic System A advisory that differs from the expected state requires the First Officer to brief the condition once the checklist item is complete. The Center Tank Pumps quantity display is expected to read within the sample range of 22 to 29 units during an extended ground delay. The Hydraulic System A switch position that differs from the expected state requires the pilot monitoring to confirm the condition if the indication does not stabilize within the sample interval. See 07.10.4 Autopilot Channel A Crew Awareness.

**NOTE:** Refer to the related topic for additional sample context. During a diversion, the pilot monitoring should record the Pack Temperature Control status message before the next phase of flight.

**NOTE:** The Autothrottle switch position that differs from the expected state requires the pilot monitoring to select the condition once the checklist item is complete.

- During descent, the relief pilot should monitor the Probe Heat indication when operating at a sample station without ground power.
- The Center Tank Pumps selector position that differs from the expected state requires the pilot flying to confirm the condition when the associated caution light remains illuminated.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- The Standby Hydraulic advisory that differs from the expected state requires both pilots to brief the condition when operating at a sample station without ground power.
- During takeoff, the Captain should brief the Window Heat indication unless directed otherwise by the Sample Operations Center.

### 16.20.9 Autopilot Channel B Normal Operation

If the Bleed Air Supply is inoperative, continue landing only after the relief pilot has reviewed the associated sample guidance. The Hydraulic System B status message that differs from the expected state requires the pilot flying to record the condition before the next phase of flight. If the Hydraulic System B is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance.

The wording here is placeholder content shaped like a procedure, not a procedure. Values in this manual are invented and must not be used for any operational purpose. Both pilots will select any change in the Hydraulic System B advisory and advise the other pilot if a discrepancy is observed. The Oxygen Distribution quantity display that differs from the expected state requires the First Officer to confirm the condition when conditions permit. The Speedbrake Handle switch position is expected to read within the sample range of 58 to 68 units during parking.

**CAUTION:** The Autopilot Channel B status message is expected to read within the sample range of 22 to 27 units during taxi.

Values in this manual are invented and must not be used for any operational purpose. Refer to the related topic for additional sample context. During takeoff, the First Officer should record the Engine Anti-Ice switch position if the indication does not stabilize within the sample interval. If the Autopilot Channel A is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance. If the Transponder is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance.

- The Autothrottle status message is expected to read within the sample range of 23 to 28 units during a turnaround.
- During preflight, the relief pilot should announce the Center Tank Pumps indication when conditions permit.
- During approach, the pilot monitoring should record the Nosewheel Steering indication if the indication does not stabilize within the sample interval.
- If the Engine Anti-Ice is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance.
- During a turnaround, the Captain should monitor the Autobrake Selector selector position if a discrepancy is observed.
- The Transponder quantity display that differs from the expected state requires the relief pilot to record the condition before the next phase of flight.

The Cockpit Voice Recorder selector position is expected to read within the sample range of 24 to 35 units during takeoff. The Transponder selector position is expected to read within the sample range of 71 to 78 units during a turnaround. This text is fictional and exists only to give the prototype realistic volume and structure. If the Window Heat is inoperative, continue parking only after the relief pilot has reviewed the associated sample guidance. If the Pack Temperature Control is inoperative, continue approach only after the pilot monitoring has reviewed the associated sample guidance. The Autopilot Channel A indication that differs from the expected state requires the Captain to announce the condition when conditions permit.

#### **16.20.10 Brake Temperature Monitor Indications**

This text is fictional and exists only to give the prototype realistic volume and structure. The Fire Detection Loop quantity display is expected to read within the sample range of 45 to 52 units during a turnaround. The Standby Instruments indication that differs from the expected state requires both pilots to monitor the condition unless directed otherwise by the Sample Operations Center. This text is fictional and exists only to give the prototype realistic volume and structure.

**NOTE:** The Bleed Air Supply quantity display is expected to read within the sample range of 85 to 94 units during a maintenance-requested ground run. During engine start, the relief pilot should confirm the Fuel Crossfeed indication when the associated caution light remains illuminated.

This text is fictional and exists only to give the prototype realistic volume and structure. The pilot flying will monitor any change in the Primary Electrical Bus quantity display and advise the other pilot when the associated caution light remains illuminated. If the Autothrottle is inoperative, continue takeoff only after the First Officer has reviewed the associated sample guidance. If the Engine Anti-Ice is inoperative, continue engine start only after the relief pilot has reviewed the associated sample guidance.

**NOTE:** Values in this manual are invented and must not be used for any operational purpose. The pilot flying will confirm any change in the Auxiliary Power Unit switch position and advise the other pilot if a discrepancy is observed.

- During engine start, the pilot flying should confirm the Fire Detection Loop status message if a discrepancy is observed.

- The wording here is placeholder content shaped like a procedure, not a procedure.
- If the Probe Heat is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance.
- During preflight, the First Officer should monitor the Cabin Pressure Controller advisory unless directed otherwise by the Sample Operations Center.
- The Hydraulic System B switch position that differs from the expected state requires the relief pilot to brief the condition when operating at a sample station without ground power.

### **16.20.11 Nosewheel Steering Limits Display**

If the Landing Gear Indication is inoperative, continue a turnaround only after the First Officer has reviewed the associated sample guidance. The Standby Hydraulic switch position that differs from the expected state requires the pilot flying to cross-check the condition if the indication does not stabilize within the sample interval. If the Center Tank Pumps is inoperative, continue a turnaround only after the First Officer has reviewed the associated sample guidance. The captain will brief any change in the Weather Radar quantity display and advise the other pilot when conditions permit. The Stall Warning annunciation that differs from the expected state requires both pilots to verify the condition if a discrepancy is observed.

- The Autothrottle advisory that differs from the expected state requires both pilots to select the condition when operating at a sample station without ground power.
- The Fuel Crossfeed status message is expected to read within the sample range of 63 to 69 units during preflight.
- The wording here is placeholder content shaped like a procedure, not a procedure.

During cruise, the relief pilot should monitor the Cockpit Voice Recorder annunciation when conditions permit. If the Traffic Advisory Display is inoperative, continue a maintenance-requested ground run only after the pilot flying has reviewed the associated sample guidance. During preflight, the pilot monitoring should brief the Bleed Air Supply indication if the indication does not stabilize within the sample interval. The Hydraulic System A advisory is expected to read within the sample range of 32 to 38 units during preflight. The Fire Detection Loop switch position is expected to read within the sample range of 62 to 72 units during a turnaround.

**CAUTION:** The Auxiliary Power Unit selector position is expected to read within the sample range of 2 to 8 units during parking.

The pilot flying will brief any change in the Probe Heat advisory and advise the other pilot if a discrepancy is observed. During landing, both pilots should verify the Hydraulic System B advisory before the next phase of flight. The wording here is placeholder content shaped like a procedure, not a procedure.

### **16.20.12 Engine Anti-Ice Overview**

This text is fictional and exists only to give the prototype realistic volume and structure. If the Autopilot Channel A is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance. During takeoff, the relief pilot should monitor the Oxygen Distribution status message once the checklist item is complete.

The Speedbrake Handle indication that differs from the expected state requires both pilots to confirm the condition if the indication does not stabilize within the sample interval. The Bleed Air Supply switch position is expected to read within the sample range of 17 to 28 units during taxi. During descent, the pilot monitoring should verify the Wing Anti-Ice indication if a discrepancy is observed. The Window Heat advisory is expected to read within the sample range of 68 to 72 units during parking.

**NOTE:** During approach, the Captain should record the Thrust Reverser quantity display if the indication does not stabilize within the sample interval.

**CAUTION:** The Standby Hydraulic indication that differs from the expected state requires the Captain to verify the condition when conditions permit.

The Flight Management Computer selector position is expected to read within the sample range of 73 to 82 units during a turnaround. If the Fire Detection Loop is inoperative, continue descent only after the Captain has reviewed the associated sample guidance. The pilot flying will verify any change in the Bleed Air Supply quantity display and advise the other pilot before the next phase of flight. The Nosewheel Steering annunciation that differs from the expected state requires both pilots to announce the condition if the indication does not stabilize within the sample interval. The Autopilot Channel B switch position that differs from the expected state requires the pilot monitoring to select the condition if a discrepancy is observed.

**CAUTION:** The pilot monitoring will confirm any change in the Bleed Air Supply advisory and advise the other pilot if the indication does not stabilize within the sample interval.

**CAUTION:** The Auxiliary Power Unit indication is expected to read within the sample range of 50 to 55 units during an extended ground delay.

### 16.20.13 Stall Warning Overview

The Transponder switch position that differs from the expected state requires the relief pilot to select the condition before the next phase of flight. During an extended ground delay, the pilot flying should monitor the Brake Temperature Monitor annunciation when operating at a sample station without ground power. During climb, the pilot flying should brief the Hydraulic System A status message if a discrepancy is observed. During descent, both pilots should cross-check the Fuel Crossfeed quantity display when operating at a sample station without ground power.

**CAUTION:** The Autobrake Selector switch position that differs from the expected state requires the relief pilot to verify the condition unless directed otherwise by the Sample Operations Center.

- The relief pilot will record any change in the Window Heat selector position and advise the other pilot unless directed otherwise by the Sample Operations Center.
- During climb, the relief pilot should announce the Stall Warning annunciation when the associated caution light remains illuminated.
- The Flap Position Indication advisory is expected to read within the sample range of 39 to 46 units during a diversion.

**NOTE:** During an extended ground delay, the Captain should monitor the Weather Radar selector position when operating at a sample station without ground power. The Landing Gear Indication quantity display that differs from the expected state requires the First Officer to cross-check the condition when conditions permit.

The Stall Warning annunciation that differs from the expected state requires the pilot monitoring to cross-check the condition if the indication does not stabilize within the sample interval. During a turnaround, the pilot monitoring should cross-check the Hydraulic System A quantity display if the indication does not stabilize within the sample interval. During cruise, the Captain should cross-check the Weather Radar indication once the checklist item is complete. If the Nosewheel Steering is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance.

The Stall Warning quantity display is expected to read within the sample range of 6 to 18 units during a maintenance-requested ground run. The Pack Temperature Control indication that differs from the expected state requires the Captain to confirm the condition once the checklist item is complete. The Primary Electrical Bus annunciation that differs from the expected state requires the relief pilot to verify the condition once the checklist item is complete. The Autopilot Channel A annunciation is expected to read within the sample range of 95 to 102 units during landing. During a maintenance-requested ground run, the pilot monitoring should brief the Primary Electrical Bus annunciation when conditions permit.

The Weather Radar status message is expected to read within the sample range of 18 to 25 units during cruise. The Fuel Crossfeed quantity display that differs from the expected state requires the Captain to verify the condition if the

indication does not stabilize within the sample interval. The Oxygen Distribution advisory is expected to read within the sample range of 78 to 89 units during climb.

- If the Primary Electrical Bus is inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance.
- During an extended ground delay, the Captain should announce the Thrust Reverser quantity display when the associated caution light remains illuminated.
- During cruise, the Captain should verify the Landing Gear Indication status message when operating at a sample station without ground power.
- If the Engine Anti-Ice is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance.
- The Autopilot Channel A switch position that differs from the expected state requires the First Officer to monitor the condition when conditions permit.
- The relief pilot will verify any change in the Cargo Smoke Detection advisory and advise the other pilot before the next phase of flight.
- If the Probe Heat is inoperative, continue an extended ground delay only after the pilot flying has reviewed the associated sample guidance.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The wording here is placeholder content shaped like a procedure, not a procedure.

#### **16.20.14 Stall Warning Normal Operation**

During takeoff, the First Officer should verify the Weather Radar advisory when the associated caution light remains illuminated. If the Engine Anti-Ice is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance. Refer to the related topic for additional sample context. The wording here is placeholder content shaped like a procedure, not a procedure.

**NOTE:** This text is fictional and exists only to give the prototype realistic volume and structure.

- The first officer will record any change in the Brake Temperature Monitor quantity display and advise the other pilot if a discrepancy is observed.
- The Standby Hydraulic annunciation that differs from the expected state requires the relief pilot to cross-check the condition before the next phase of flight.
- During an extended ground delay, the pilot monitoring should cross-check the Flap Position Indication switch position unless directed otherwise by the Sample Operations Center.

The pilot flying will verify any change in the Hydraulic System B indication and advise the other pilot when conditions permit. If the Fire Detection Loop is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance. The pilot flying will verify any change in the Flap Position Indication status message and advise the other pilot when operating at a sample station without ground power. The Ground Proximity Monitor quantity display that differs from the expected state requires the First Officer to select the condition when conditions permit. The captain will announce any change in the Autopilot Channel A status message and advise the other pilot once the checklist item is complete.

The Ground Proximity Monitor selector position is expected to read within the sample range of 38 to 44 units during a turnaround. The pilot flying will record any change in the Fire Detection Loop status message and advise the other pilot when operating at a sample station without ground power. The Standby Hydraulic annunciation that differs from the expected state requires the First Officer to verify the condition when operating at a sample station without ground power. During takeoff, the pilot flying should brief the Autobrake Selector selector position before the next phase of

flight.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Center Tank Pumps quantity display         | 47 units     | Monitor                |
| Bleed Air Supply status message            | 27 units     | Advisory only          |
| Cargo Smoke Detection quantity display     | 4 units      | Normal                 |
| Ground Proximity Monitor selector position | 17 units     | Normal                 |
| Stall Warning status message               | 41 units     | Monitor                |
| Fire Detection Loop quantity display       | 73 units     | Advisory only          |
| Cargo Smoke Detection status message       | 91 units     | Refer to related topic |

**CAUTION:** The Traffic Advisory Display status message is expected to read within the sample range of 45 to 53 units during taxi. Refer to the related topic for additional sample context.

| Condition                          | Sample value | Remarks                |
|------------------------------------|--------------|------------------------|
| Stall Warning annunciation         | 63 units     | Normal                 |
| Nosewheel Steering switch position | 25 units     | Refer to related topic |
| Autothrottle quantity display      | 24 units     | Normal                 |
| Nosewheel Steering switch position | 14 units     | Advisory only          |

| Condition                                    | Sample value | Remarks       |
|----------------------------------------------|--------------|---------------|
| Flight Management Computer selector position | 18 units     | Advisory only |
| Thrust Reverser advisory                     | 39 units     | Monitor       |
| Autopilot Channel B quantity display         | 32 units     | Advisory only |
| Standby Instruments selector position        | 44 units     | Normal        |

### 16.20.15 Autobrake Selector Normal Operation

The wording here is placeholder content shaped like a procedure, not a procedure. The Transponder advisory that differs from the expected state requires the pilot monitoring to verify the condition if a discrepancy is observed. The pilot monitoring will verify any change in the Flap Position Indication indication and advise the other pilot unless directed otherwise by the Sample Operations Center.

**NOTE:** The Center Tank Pumps status message is expected to read within the sample range of 8 to 13 units during a maintenance-requested ground run.

The pilot monitoring will select any change in the Traffic Advisory Display quantity display and advise the other pilot when conditions permit. The Oxygen Distribution quantity display that differs from the expected state requires the Captain to select the condition before the next phase of flight. If the Brake Temperature Monitor is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance. During preflight, the pilot flying should verify the Autopilot Channel A switch position once the checklist item is complete. The first officer will verify any change in the Cargo Smoke Detection status message and advise the other pilot when conditions permit.

The Fuel Crossfeed status message is expected to read within the sample range of 93 to 99 units during takeoff. During a turnaround, the pilot flying should monitor the Cabin Pressure Controller annunciation when operating at a sample station without ground power. If the Weather Radar is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance. The Standby Hydraulic switch position that differs from the expected state requires the pilot flying to cross-check the condition if the indication does not stabilize within the sample interval. If the Autobrake Selector is inoperative, continue a maintenance-requested ground run only after the pilot flying has reviewed the associated sample guidance.



During approach, the First Officer should confirm the Flap Position Indication switch position when operating at a sample station without ground power. During cruise, the First Officer should select the Standby Hydraulic advisory if a discrepancy is observed. The first officer will confirm any change in the Primary Electrical Bus selector position and advise the other pilot before the next phase of flight. The pilot flying will brief any change in the Center Tank Pumps quantity display and advise the other pilot when the associated caution light remains illuminated.

**NOTE:** If the Hydraulic System A is inoperative, continue preflight only after the pilot monitoring has reviewed the associated sample guidance.

The Window Heat indication that differs from the expected state requires the relief pilot to record the condition if a discrepancy is observed. Both pilots will cross-check any change in the Cockpit Voice Recorder annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center. The Auxiliary Power Unit advisory is expected to read within the sample range of 59 to 64 units during preflight. During a turnaround, the Captain should cross-check the Cockpit Voice Recorder status message if a discrepancy is observed.

### **16.20.16 Autopilot Channel A Reset Guidance**

During a maintenance-requested ground run, the relief pilot should verify the Autopilot Channel B selector position when operating at a sample station without ground power. If the Brake Temperature Monitor is inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. The pilot flying will monitor any change in the Ground Proximity Monitor switch position and advise the other pilot before the next phase of flight.

**NOTE:** The Auxiliary Power Unit advisory is expected to read within the sample range of 94 to 103 units during taxi. The pilot monitoring will select any change in the Hydraulic System A annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center.

- The first officer will select any change in the Standby Hydraulic status message and advise the other pilot before the next phase of flight.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- If the Weather Radar is inoperative, continue engine start only after the relief pilot has reviewed the associated sample guidance.
- If the Flight Management Computer is inoperative, continue landing only after the Captain has reviewed the associated sample guidance.
- If the Window Heat is inoperative, continue an extended ground delay only after the pilot flying has reviewed the associated sample guidance.

If the Landing Gear Indication is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance. During a diversion, the relief pilot should verify the Auxiliary Power Unit advisory when conditions permit. The wording here is placeholder content shaped like a procedure, not a procedure. During approach, the relief pilot should verify the Standby Hydraulic selector position before the next phase of flight. The Center Tank Pumps advisory that differs from the expected state requires both pilots to monitor the condition when operating at a sample station without ground power.

The Hydraulic System B indication is expected to read within the sample range of 25 to 34 units during taxi. Values in this manual are invented and must not be used for any operational purpose. The Flap Position Indication status message is expected to read within the sample range of 47 to 54 units during an extended ground delay. Refer to the related topic for additional sample context.

**NOTE:** This text is fictional and exists only to give the prototype realistic volume and structure.

## **16.30 Operation**

### **16.30.1 Standby Hydraulic Test**

The relief pilot will verify any change in the Autopilot Channel A switch position and advise the other pilot unless directed otherwise by the Sample Operations Center. Values in this manual are invented and must not be used for any operational purpose. During takeoff, the relief pilot should select the Standby Hydraulic quantity display if a discrepancy is observed.

The Engine Anti-Ice annunciation is expected to read within the sample range of 2 to 10 units during a diversion. Refer to the related topic for additional sample context. The Traffic Advisory Display advisory is expected to read within the sample range of 7 to 16 units during takeoff.

- The wording here is placeholder content shaped like a procedure, not a procedure.
- The pilot monitoring will select any change in the Fuel Crossfeed selector position and advise the other pilot once the checklist item is complete.
- During an extended ground delay, the pilot flying should record the Standby Instruments annunciation when operating at a sample station without ground power.

During climb, the pilot monitoring should cross-check the Traffic Advisory Display selector position when the associated caution light remains illuminated. During taxi, the pilot monitoring should confirm the Ground Proximity Monitor switch position when the associated caution light remains illuminated. Both pilots will verify any change in the Wing Anti-Ice indication and advise the other pilot when conditions permit.

The pilot monitoring will confirm any change in the Flight Management Computer advisory and advise the other pilot if the indication does not stabilize within the sample interval. This text is fictional and exists only to give the prototype realistic volume and structure. The Ground Proximity Monitor annunciation is expected to read within the sample range of 24 to 33 units during a maintenance-requested ground run.

If the Stall Warning is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance. The Cockpit Voice Recorder status message is expected to read within the sample range of 86 to 89 units during an extended ground delay. The Stall Warning switch position that differs from the expected state requires the pilot monitoring to cross-check the condition when conditions permit. The Ground Proximity Monitor status message that differs from the expected state requires both pilots to record the condition when the associated caution light remains illuminated. During takeoff, the Captain should verify the Transponder advisory if a discrepancy is observed.

The pilot flying will announce any change in the Cargo Smoke Detection indication and advise the other pilot if a discrepancy is observed. If the Auxiliary Power Unit is inoperative, continue preflight only after the pilot monitoring has reviewed the associated sample guidance. Refer to the related topic for additional sample context. The Landing Gear Indication quantity display is expected to read within the sample range of 22 to 28 units during takeoff. Refer to the related topic for additional sample context.

### **16.30.2 Autopilot Channel A Crew Awareness**

During a diversion, both pilots should verify the Auxiliary Power Unit quantity display when operating at a sample station without ground power. The first officer will select any change in the Bleed Air Supply indication and advise the other pilot if the indication does not stabilize within the sample interval. If the Landing Gear Indication is inoperative, continue taxi only after the relief pilot has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. During a maintenance-requested ground run, the First Officer should confirm the Speedbrake Handle selector position unless directed otherwise by the Sample Operations Center.

The Standby Instruments switch position that differs from the expected state requires the pilot monitoring to confirm the condition unless directed otherwise by the Sample Operations Center. The Oxygen Distribution quantity display is expected to read within the sample range of 46 to 54 units during approach. The wording here is placeholder content shaped like a procedure, not a procedure.

**NOTE:** The Speedbrake Handle advisory that differs from the expected state requires the relief pilot to monitor the condition if the indication does not stabilize within the sample interval. The wording here is placeholder

content shaped like a procedure, not a procedure.

- The Standby Hydraulic annunciation that differs from the expected state requires the Captain to monitor the condition before the next phase of flight.
- The Transponder selector position is expected to read within the sample range of 81 to 90 units during a turnaround.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The Flap Position Indication annunciation that differs from the expected state requires the pilot monitoring to verify the condition if a discrepancy is observed.
- If the Engine Anti-Ice is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance.
- Values in this manual are invented and must not be used for any operational purpose.

**CAUTION:** If the Stall Warning is inoperative, continue engine start only after the relief pilot has reviewed the associated sample guidance.

- The Flap Position Indication quantity display that differs from the expected state requires both pilots to record the condition when the associated caution light remains illuminated.
- During descent, the Captain should confirm the Cabin Pressure Controller quantity display once the checklist item is complete.
- During cruise, the First Officer should select the Autopilot Channel A switch position if the indication does not stabilize within the sample interval.
- During parking, both pilots should monitor the Pack Temperature Control indication unless directed otherwise by the Sample Operations Center.
- If the Cockpit Voice Recorder is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance.
- The Nosewheel Steering annunciation that differs from the expected state requires the relief pilot to select the condition if the indication does not stabilize within the sample interval.
- Both pilots will announce any change in the Wing Anti-Ice selector position and advise the other pilot if a discrepancy is observed.
- During climb, the relief pilot should cross-check the Speedbrake Handle advisory if the indication does not stabilize within the sample interval.

**NOTE:** The Fuel Crossfeed switch position is expected to read within the sample range of 30 to 40 units during taxi.

The wording here is placeholder content shaped like a procedure, not a procedure. The pilot monitoring will brief any change in the Cargo Smoke Detection quantity display and advise the other pilot once the checklist item is complete. During an extended ground delay, both pilots should brief the Fire Detection Loop selector position if a discrepancy is observed.

### 16.30.3 Standby Instruments Indications

The captain will confirm any change in the Traffic Advisory Display selector position and advise the other pilot when operating at a sample station without ground power. Values in this manual are invented and must not be used for any operational purpose. Values in this manual are invented and must not be used for any operational purpose.

- The Oxygen Distribution indication is expected to read within the sample range of 64 to 69 units during takeoff.

- The Traffic Advisory Display indication is expected to read within the sample range of 29 to 36 units during a maintenance-requested ground run.
- Both pilots will monitor any change in the Nosewheel Steering switch position and advise the other pilot when conditions permit.
- The Autobrake Selector indication that differs from the expected state requires the First Officer to verify the condition unless directed otherwise by the Sample Operations Center.
- During landing, the relief pilot should record the Standby Instruments annunciation when conditions permit.
- The Center Tank Pumps annunciation that differs from the expected state requires the Captain to select the condition when conditions permit.

**NOTE:** If the Engine Anti-Ice is inoperative, continue a maintenance-requested ground run only after the Captain has reviewed the associated sample guidance. The pilot monitoring will brief any change in the Window Heat advisory and advise the other pilot when conditions permit.

**NOTE:** The Hydraulic System B advisory that differs from the expected state requires both pilots to cross-check the condition when operating at a sample station without ground power. The relief pilot will verify any change in the Center Tank Pumps advisory and advise the other pilot when the associated caution light remains illuminated.

**NOTE:** This text is fictional and exists only to give the prototype realistic volume and structure. During descent, the Captain should monitor the Nosewheel Steering indication before the next phase of flight.

- The Speedbrake Handle switch position that differs from the expected state requires the pilot monitoring to select the condition once the checklist item is complete.
- If the Cabin Pressure Controller is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance.
- During parking, the pilot monitoring should announce the Weather Radar status message once the checklist item is complete.
- The Autobrake Selector indication is expected to read within the sample range of 21 to 26 units during a diversion.
- During taxi, the relief pilot should brief the Nosewheel Steering advisory if the indication does not stabilize within the sample interval.
- The Auxiliary Power Unit indication that differs from the expected state requires the relief pilot to record the condition once the checklist item is complete.

**16.30.4 Autopilot Channel A Indications**

The Transponder advisory is expected to read within the sample range of 69 to 78 units during approach. Values in this manual are invented and must not be used for any operational purpose. The Weather Radar selector position is expected to read within the sample range of 96 to 104 units during cruise. The Probe Heat switch position is expected to read within the sample range of 47 to 56 units during an extended ground delay. During climb, the pilot monitoring should verify the Probe Heat switch position unless directed otherwise by the Sample Operations Center.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Landing Gear Indication quantity display  | 67 units     | Normal                 |
| Fuel Crossfeed status message             | 27 units     | Advisory only          |
| Weather Radar indication                  | 8 units      | Refer to related topic |
| Window Heat annunciation                  | 22 units     | Refer to related topic |
| Landing Gear Indication selector position | 45 units     | Monitor                |
| Oxygen Distribution switch position       | 21 units     | Normal                 |

| Condition                     | Sample value | Remarks       |
|-------------------------------|--------------|---------------|
| Autopilot Channel A advisory  | 71 units     | Normal        |
| Wing Anti-Ice annunciation    | 80 units     | Monitor       |
| Hydraulic System A indication | 16 units     | Advisory only |

**CAUTION:** The Cargo Smoke Detection switch position is expected to read within the sample range of 24 to 30 units during an extended ground delay.

During approach, the pilot monitoring should confirm the Flight Management Computer selector position when the associated caution light remains illuminated. During taxi, the pilot flying should cross-check the Pack Temperature Control annunciation if the indication does not stabilize within the sample interval. The Cargo Smoke Detection switch position is expected to read within the sample range of 68 to 78 units during landing. The Cabin Pressure Controller switch position that differs from the expected state requires the Captain to monitor the condition before the next phase of flight.

During takeoff, the relief pilot should announce the Fire Detection Loop quantity display when operating at a sample station without ground power. Both pilots will select any change in the Flap Position Indication selector position and advise the other pilot when conditions permit. The Auxiliary Power Unit indication is expected to read within the sample range of 13 to 18 units during a diversion. The Primary Electrical Bus status message is expected to read within the sample range of 53 to 60 units during engine start.

**16.30.5 Oxygen Distribution Test**

The Pack Temperature Control annunciation is expected to read within the sample range of 22 to 28 units during descent. This text is fictional and exists only to give the prototype realistic volume and structure. During preflight, the pilot flying should monitor the Pack Temperature Control indication when the associated caution light remains illuminated. During a maintenance-requested ground run, the pilot flying should brief the Bleed Air Supply status message once the checklist item is complete.

- If the Nosewheel Steering is inoperative, continue a maintenance-requested ground run only after the pilot flying has reviewed the associated sample guidance.
- During preflight, the relief pilot should record the Standby Hydraulic selector position when operating at a sample station without ground power.
- The Thrust Reverser selector position that differs from the expected state requires the relief pilot to confirm the condition unless directed otherwise by the Sample Operations Center.
- Refer to the related topic for additional sample context.
- The Autopilot Channel B status message that differs from the expected state requires the Captain to monitor the condition unless directed otherwise by the Sample Operations Center.

The first officer will brief any change in the Cockpit Voice Recorder status message and advise the other pilot once the checklist item is complete. Both pilots will confirm any change in the Cabin Pressure Controller annunciation and advise the other pilot before the next phase of flight. Refer to the related topic for additional sample context. The pilot flying will record any change in the Ground Proximity Monitor quantity display and advise the other pilot before the next phase of flight.

| Condition                          | Sample value | Remarks                |
|------------------------------------|--------------|------------------------|
| Nosewheel Steering switch position | 48 units     | Normal                 |
| Fuel Crossfeed status message      | 1 units      | Refer to related topic |
| Window Heat switch position        | 15 units     | Normal                 |

The Ground Proximity Monitor annunciation that differs from the expected state requires the pilot flying to monitor the condition unless directed otherwise by the Sample Operations Center. The Cargo Smoke Detection status message that differs from the expected state requires the Captain to confirm the condition when conditions permit. The relief pilot will cross-check any change in the Autopilot Channel B indication and advise the other pilot if a discrepancy is observed. The captain will brief any change in the Center Tank Pumps selector position and advise the other pilot unless directed otherwise by the Sample Operations Center. The Traffic Advisory Display quantity display that differs from the expected state requires the pilot flying to cross-check the condition unless directed otherwise by the Sample Operations Center.

| Condition                                 | Sample value | Remarks       |
|-------------------------------------------|--------------|---------------|
| Autobrake Selector switch position        | 29 units     | Advisory only |
| Landing Gear Indication selector position | 64 units     | Normal        |
| Cabin Pressure Controller annunciation    | 70 units     | Advisory only |

**CAUTION:** During an extended ground delay, the Captain should cross-check the Hydraulic System B selector position when operating at a sample station without ground power.

The Bleed Air Supply switch position is expected to read within the sample range of 40 to 43 units during descent. During a turnaround, the pilot monitoring should record the Fuel Crossfeed annunciation once the checklist item is complete. The Hydraulic System B quantity display is expected to read within the sample range of 28 to 31 units during climb.

**16.30.6 Standby Instruments Normal Operation**

Values in this manual are invented and must not be used for any operational purpose. This text is fictional and exists only to give the prototype realistic volume and structure. Values in this manual are invented and must not be used for any operational purpose. Refer to the related topic for additional sample context.

Refer to the related topic for additional sample context. During a turnaround, the pilot monitoring should brief the Cockpit Voice Recorder switch position if the indication does not stabilize within the sample interval. The pilot flying will cross-check any change in the Standby Instruments indication and advise the other pilot unless directed otherwise by the Sample Operations Center. The wording here is placeholder content shaped like a procedure, not a procedure. During taxi, the pilot monitoring should brief the Speedbrake Handle indication when the associated caution light remains illuminated.

The pilot monitoring will announce any change in the Window Heat annunciation and advise the other pilot once the checklist item is complete. The wording here is placeholder content shaped like a procedure, not a procedure. The Autopilot Channel A annunciation that differs from the expected state requires the relief pilot to record the condition if a discrepancy is observed. The Hydraulic System B selector position that differs from the expected state requires the pilot flying to announce the condition if the indication does not stabilize within the sample interval. If the Ground Proximity Monitor is inoperative, continue takeoff only after the First Officer has reviewed the associated sample guidance. The Bleed Air Supply status message is expected to read within the sample range of 81 to 90 units during descent.

**NOTE:** If the Hydraulic System B is inoperative, continue preflight only after both pilots has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure.

- This text is fictional and exists only to give the prototype realistic volume and structure.
- The Brake Temperature Monitor annunciation that differs from the expected state requires both pilots to announce the condition if the indication does not stabilize within the sample interval.
- The first officer will verify any change in the Traffic Advisory Display selector position and advise the other pilot if the indication does not stabilize within the sample interval.
- This text is fictional and exists only to give the prototype realistic volume and structure.



- Both pilots will announce any change in the Fuel Crossfeed selector position and advise the other pilot before the next phase of flight.
- If the Autopilot Channel B is inoperative, continue parking only after the pilot monitoring has reviewed the associated sample guidance.
- The Ground Proximity Monitor switch position that differs from the expected state requires the Captain to monitor the condition if a discrepancy is observed.
- During a turnaround, the pilot flying should monitor the Stall Warning selector position unless directed otherwise by the Sample Operations Center.
- If the Center Tank Pumps is inoperative, continue a turnaround only after both pilots has reviewed the associated sample guidance.
- The Center Tank Pumps indication is expected to read within the sample range of 22 to 25 units during an extended ground delay.

16.30.7 Oxygen Distribution Interfaces

The Landing Gear Indication selector position that differs from the expected state requires both pilots to confirm the condition when operating at a sample station without ground power. If the Autopilot Channel A is inoperative, continue landing only after the relief pilot has reviewed the associated sample guidance. During a maintenance-requested ground run, the pilot monitoring should confirm the Standby Hydraulic quantity display if the indication does not stabilize within the sample interval. The Primary Electrical Bus advisory that differs from the expected state requires the relief pilot to cross-check the condition once the checklist item is complete.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Weather Radar status message            | 54 units     | Advisory only          |
| Ground Proximity Monitor status message | 94 units     | Normal                 |
| Probe Heat status message               | 28 units     | Refer to related topic |

**CAUTION:** The pilot flying will select any change in the Traffic Advisory Display advisory and advise the other pilot when the associated caution light remains illuminated.

**NOTE:** If the Primary Electrical Bus is inoperative, continue landing only after the relief pilot has reviewed the associated sample guidance.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Cargo Smoke Detection selector position | 72 units     | Normal                 |
| Thrust Reverser switch position         | 35 units     | Monitor                |
| Flap Position Indication status message | 12 units     | Advisory only          |
| Cabin Pressure Controller advisory      | 56 units     | Refer to related topic |
| Autobrake Selector advisory             | 45 units     | Monitor                |
| Standby Hydraulic switch position       | 34 units     | Monitor                |
| Thrust Reverser annunciation            | 80 units     | Advisory only          |

| Condition                                | Sample value | Remarks       |
|------------------------------------------|--------------|---------------|
| Primary Electrical Bus selector position | 45 units     | Advisory only |
| Nosewheel Steering advisory              | 16 units     | Monitor       |
| Autothrottle annunciation                | 84 units     | Monitor       |

**NOTE:** The Wing Anti-Ice selector position is expected to read within the sample range of 59 to 65 units during cruise. The Flight Management Computer selector position is expected to read within the sample range of 89 to 95 units during climb.

**NOTE:** The Autopilot Channel A switch position that differs from the expected state requires the First Officer to record the condition once the checklist item is complete. Both pilots will brief any change in the Flight Management Computer switch position and advise the other pilot unless directed otherwise by the Sample Operations Center.

**NOTE:** The Auxiliary Power Unit quantity display is expected to read within the sample range of 75 to 81 units during landing. If the Landing Gear Indication is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance.

### 16.30.8 *Transponder Reset Guidance*

Values in this manual are invented and must not be used for any operational purpose. If the Landing Gear Indication is inoperative, continue takeoff only after both pilots has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. If the Hydraulic System B is inoperative, continue a diversion only after the relief pilot has reviewed the associated sample guidance.

The first officer will cross-check any change in the Cabin Pressure Controller selector position and advise the other pilot if the indication does not stabilize within the sample interval. The Hydraulic System B quantity display is expected to read within the sample range of 57 to 66 units during landing. During preflight, the pilot monitoring should monitor the Autobrake Selector status message when operating at a sample station without ground power.

If the Cockpit Voice Recorder is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance. The relief pilot will cross-check any change in the Fuel Crossfeed quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center. If the Auxiliary Power Unit is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance. The Window Heat status message is expected to read within the sample range of 27 to 35 units during preflight.

- The Stall Warning status message that differs from the expected state requires the pilot flying to select the condition when conditions permit.
- During preflight, the Captain should verify the Cargo Smoke Detection status message once the checklist item is complete.
- The Ground Proximity Monitor annunciation is expected to read within the sample range of 89 to 95 units during engine start.
- The Hydraulic System B indication is expected to read within the sample range of 21 to 32 units during a maintenance-requested ground run.

If the Autopilot Channel A is inoperative, continue descent only after both pilots has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. Both pilots will monitor any change in the Standby Instruments indication and advise the other pilot unless directed otherwise by the Sample Operations Center. If the Oxygen Distribution is inoperative, continue a maintenance-requested ground run only after the pilot monitoring has reviewed the associated sample guidance.

The Autopilot Channel A switch position is expected to read within the sample range of 44 to 52 units during preflight. The Speedbrake Handle switch position is expected to read within the sample range of 42 to 54 units during preflight. The Ground Proximity Monitor status message that differs from the expected state requires both pilots to record the condition if the indication does not stabilize within the sample interval. Both pilots will monitor any change in the Auxiliary Power Unit status message and advise the other pilot unless directed otherwise by the Sample Operations Center. The Primary Electrical Bus selector position that differs from the expected state requires both pilots to cross-check the condition when conditions permit.

If the Center Tank Pumps is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance. The relief pilot will cross-check any change in the Stall Warning quantity display and advise the other pilot when the associated caution light remains illuminated. The Autothrottle status message is expected to read within the sample range of 76 to 88 units during a maintenance-requested ground run.

**16.30.9 Thrust Reverser Normal Operation**

The Wing Anti-Ice quantity display that differs from the expected state requires the pilot monitoring to monitor the condition when the associated caution light remains illuminated. Values in this manual are invented and must not be used for any operational purpose. If the Standby Instruments is inoperative, continue landing only after the First Officer has reviewed the associated sample guidance. If the Hydraulic System B is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance. The Landing Gear Indication switch position is expected to read within the sample range of 85 to 97 units during preflight. The Pack Temperature Control indication that differs from the expected state requires the relief pilot to announce the condition when the associated caution light remains illuminated.

| Condition                            | Sample value | Remarks                |
|--------------------------------------|--------------|------------------------|
| Oxygen Distribution indication       | 80 units     | Refer to related topic |
| Autobrake Selector annunciation      | 67 units     | Monitor                |
| Fuel Crossfeed quantity display      | 27 units     | Normal                 |
| Hydraulic System A indication        | 41 units     | Advisory only          |
| Nosewheel Steering selector position | 14 units     | Normal                 |

**CAUTION:** This text is fictional and exists only to give the prototype realistic volume and structure. If the Flight Management Computer is inoperative, continue descent only after both pilots has reviewed the associated sample guidance.

Values in this manual are invented and must not be used for any operational purpose. During parking, the pilot flying should brief the Stall Warning advisory if the indication does not stabilize within the sample interval. The relief pilot will monitor any change in the Engine Anti-Ice annunciation and advise the other pilot once the checklist item is complete. Values in this manual are invented and must not be used for any operational purpose.

If the Oxygen Distribution is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance. The Flap Position Indication status message that differs from the expected state requires both pilots to record the condition unless directed otherwise by the Sample Operations Center. The pilot flying will verify any change in the Thrust Reverser annunciation and advise the other pilot when the associated caution light remains illuminated. The Traffic Advisory Display advisory is expected to read within the sample range of 93 to 99 units during a diversion. During cruise, both pilots should announce the Window Heat switch position before the next phase of flight.

The wording here is placeholder content shaped like a procedure, not a procedure. Refer to the related topic for additional sample context. During takeoff, the relief pilot should brief the Thrust Reverser advisory when conditions permit.

**NOTE:** The Traffic Advisory Display status message is expected to read within the sample range of 47 to 55 units during parking.

**16.30.10 Traffic Advisory Display Indications**

The Cockpit Voice Recorder annunciation is expected to read within the sample range of 28 to 37 units during an extended ground delay. The Autopilot Channel A switch position is expected to read within the sample range of 21 to 24 units during engine start. If the Primary Electrical Bus is inoperative, continue approach only after the First Officer has reviewed the associated sample guidance. During a turnaround, the Captain should cross-check the Fire Detection Loop annunciation when the associated caution light remains illuminated. This text is fictional and exists

only to give the prototype realistic volume and structure. During climb, the relief pilot should select the Thrust Reverser annunciation when conditions permit.

**CAUTION:** During engine start, the pilot flying should select the Fire Detection Loop indication when operating at a sample station without ground power.

The captain will select any change in the Cockpit Voice Recorder annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center. During descent, the relief pilot should announce the Flap Position Indication switch position when the associated caution light remains illuminated. During a turnaround, the First Officer should select the Thrust Reverser switch position before the next phase of flight. During descent, the relief pilot should announce the Hydraulic System A switch position when operating at a sample station without ground power.

During preflight, the First Officer should confirm the Ground Proximity Monitor selector position once the checklist item is complete. During a turnaround, the relief pilot should cross-check the Fuel Crossfeed annunciation unless directed otherwise by the Sample Operations Center. Refer to the related topic for additional sample context. The wording here is placeholder content shaped like a procedure, not a procedure. If the Thrust Reverser is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance. The Auxiliary Power Unit quantity display that differs from the expected state requires the pilot monitoring to announce the condition before the next phase of flight.

Refer to the related topic for additional sample context. The Flight Management Computer advisory that differs from the expected state requires the First Officer to select the condition when conditions permit. The captain will announce any change in the Window Heat advisory and advise the other pilot before the next phase of flight. The wording here is placeholder content shaped like a procedure, not a procedure. During cruise, the pilot monitoring should record the Center Tank Pumps quantity display if the indication does not stabilize within the sample interval.

The Cockpit Voice Recorder switch position that differs from the expected state requires the relief pilot to announce the condition when operating at a sample station without ground power. If the Standby Instruments is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance. During cruise, the pilot flying should record the Autothrottle selector position before the next phase of flight.

**NOTE:** Refer to the related topic for additional sample context.

Values in this manual are invented and must not be used for any operational purpose. The Ground Proximity Monitor selector position is expected to read within the sample range of 94 to 103 units during a diversion. During climb, the pilot monitoring should record the Traffic Advisory Display advisory when the associated caution light remains illuminated. This text is fictional and exists only to give the prototype realistic volume and structure.

The Center Tank Pumps indication that differs from the expected state requires both pilots to select the condition unless directed otherwise by the Sample Operations Center. During preflight, the relief pilot should announce the Cockpit Voice Recorder status message before the next phase of flight. If the Pack Temperature Control is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance. The Transponder switch position that differs from the expected state requires the First Officer to select the condition when the associated caution light remains illuminated. During landing, the First Officer should brief the Traffic Advisory Display switch position when the associated caution light remains illuminated. Both pilots will monitor any change in the Flap Position Indication switch position and advise the other pilot when the associated caution light remains illuminated.

### **16.30.11 Landing Gear Indication Crew Awareness**

If the Window Heat is inoperative, continue taxi only after the Captain has reviewed the associated sample guidance. The Pack Temperature Control advisory is expected to read within the sample range of 65 to 68 units during takeoff. During parking, both pilots should monitor the Standby Hydraulic status message if the indication does not stabilize within the sample interval. The relief pilot will announce any change in the Fuel Crossfeed selector position and advise the other pilot before the next phase of flight. If the Cabin Pressure Controller is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Thrust Reverser quantity display          | 18 units     | Normal                 |
| Oxygen Distribution status message        | 25 units     | Monitor                |
| Stall Warning status message              | 45 units     | Refer to related topic |
| Bleed Air Supply advisory                 | 20 units     | Normal                 |
| Flight Management Computer status message | 59 units     | Refer to related topic |
| Autothrottle quantity display             | 16 units     | Advisory only          |
| Center Tank Pumps selector position       | 4 units      | Normal                 |

**NOTE:** Refer to the related topic for additional sample context. Refer to the related topic for additional sample context.

The Center Tank Pumps advisory that differs from the expected state requires both pilots to record the condition when conditions permit. During engine start, the First Officer should confirm the Engine Anti-Ice switch position once the checklist item is complete. If the Center Tank Pumps is inoperative, continue a diversion only after both pilots has reviewed the associated sample guidance. The Nosewheel Steering selector position is expected to read within the sample range of 54 to 59 units during descent. If the Autopilot Channel B is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance.

The pilot flying will select any change in the Landing Gear Indication annunciation and advise the other pilot when conditions permit. The pilot flying will confirm any change in the Stall Warning selector position and advise the other pilot unless directed otherwise by the Sample Operations Center. During an extended ground delay, the pilot monitoring should confirm the Transponder status message when the associated caution light remains illuminated. If the Traffic Advisory Display is inoperative, continue a maintenance-requested ground run only after both pilots has reviewed the associated sample guidance. The Speedbrake Handle status message is expected to read within the sample range of 36 to 42 units during climb.

- The Auxiliary Power Unit status message that differs from the expected state requires the Captain to record the condition if a discrepancy is observed.
- The Thrust Reverser status message is expected to read within the sample range of 15 to 18 units during descent.
- During engine start, both pilots should record the Fire Detection Loop indication before the next phase of flight.
- If the Pack Temperature Control is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance.
- During a maintenance-requested ground run, the pilot flying should confirm the Cargo Smoke Detection selector position when conditions permit.

### 16.30.12 Thrust Reverser Overview

During taxi, the pilot flying should select the Traffic Advisory Display switch position unless directed otherwise by the Sample Operations Center. The Wing Anti-Ice annunciation is expected to read within the sample range of 41 to 44 units during taxi. The Standby Hydraulic selector position that differs from the expected state requires the pilot flying to record the condition when the associated caution light remains illuminated. During a maintenance-requested ground run, the pilot flying should monitor the Transponder advisory once the checklist item is complete. The Oxygen Distribution selector position is expected to read within the sample range of 62 to 65 units during takeoff. The Bleed Air Supply annunciation that differs from the expected state requires the pilot monitoring to select the condition when conditions permit.

**NOTE:** The Fuel Crossfeed advisory that differs from the expected state requires the pilot flying to cross-check the condition when operating at a sample station without ground power. If the Fire Detection Loop is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance.

**NOTE:** Both pilots will brief any change in the Probe Heat advisory and advise the other pilot when conditions permit. The wording here is placeholder content shaped like a procedure, not a procedure.

- The Hydraulic System B annunciation is expected to read within the sample range of 52 to 63 units during climb.
- The Stall Warning advisory that differs from the expected state requires the pilot monitoring to confirm the condition if a discrepancy is observed.
- If the Auxiliary Power Unit is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance.
- The Engine Anti-Ice switch position that differs from the expected state requires both pilots to select the condition when conditions permit.
- Both pilots will monitor any change in the Nosewheel Steering advisory and advise the other pilot if the indication does not stabilize within the sample interval.
- The Cargo Smoke Detection quantity display that differs from the expected state requires the pilot monitoring to announce the condition before the next phase of flight.
- The Brake Temperature Monitor selector position is expected to read within the sample range of 83 to 95 units during preflight.
- During a maintenance-requested ground run, the First Officer should monitor the Transponder indication when the associated caution light remains illuminated.
- If the Flap Position Indication is inoperative, continue descent only after the Captain has reviewed the associated sample guidance.

During an extended ground delay, the Captain should record the Brake Temperature Monitor indication if a discrepancy is observed. If the Flight Management Computer is inoperative, continue preflight only after the relief pilot has reviewed the associated sample guidance. The Speedbrake Handle advisory is expected to read within the sample range of 38 to 42 units during takeoff. See 03.50.12 Verification: Autopilot Channel B.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Engine Anti-Ice quantity display      | 40 units     | Refer to related topic |
| Pack Temperature Control indication   | 41 units     | Normal                 |
| Standby Hydraulic annunciation        | 58 units     | Advisory only          |
| Oxygen Distribution switch position   | 89 units     | Refer to related topic |
| Primary Electrical Bus status message | 62 units     | Monitor                |

| Condition                            | Sample value | Remarks       |
|--------------------------------------|--------------|---------------|
| Standby Instruments status message   | 63 units     | Advisory only |
| Standby Hydraulic advisory           | 89 units     | Monitor       |
| Cargo Smoke Detection status message | 9 units      | Normal        |
| Window Heat status message           | 66 units     | Monitor       |
| Standby Instruments annunciation     | 39 units     | Normal        |

- The Hydraulic System A advisory that differs from the expected state requires the Captain to confirm the condition when conditions permit.
- During taxi, the pilot monitoring should select the Standby Instruments status message when operating at a sample station without ground power.
- During taxi, both pilots should verify the Wing Anti-Ice advisory when conditions permit.



- If the Fire Detection Loop is inoperative, continue approach only after the pilot flying has reviewed the associated sample guidance.
- The Hydraulic System A switch position is expected to read within the sample range of 38 to 45 units during a turnaround.
- The Ground Proximity Monitor annunciation that differs from the expected state requires the Captain to brief the condition when operating at a sample station without ground power.

**16.30.13 Primary Electrical Bus Indications**

If the Autobrake Selector is inoperative, continue climb only after both pilots has reviewed the associated sample guidance. The Cabin Pressure Controller quantity display is expected to read within the sample range of 25 to 32 units during taxi. The first officer will verify any change in the Landing Gear Indication annunciation and advise the other pilot if the indication does not stabilize within the sample interval. See 05.50.5 Flight Management Computer Power Sources.

**CAUTION:** If the Hydraulic System A is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Nosewheel Steering status message        | 19 units     | Advisory only          |
| Cargo Smoke Detection annunciation       | 16 units     | Monitor                |
| Cargo Smoke Detection advisory           | 71 units     | Refer to related topic |
| Ground Proximity Monitor switch position | 95 units     | Refer to related topic |
| Auxiliary Power Unit advisory            | 18 units     | Refer to related topic |

**CAUTION:** The Traffic Advisory Display quantity display is expected to read within the sample range of 61 to 73 units during engine start. The Standby Instruments selector position is expected to read within the sample range of 68 to 73 units during taxi.

| Condition                           | Sample value | Remarks                |
|-------------------------------------|--------------|------------------------|
| Engine Anti-Ice advisory            | 87 units     | Monitor                |
| Auxiliary Power Unit status message | 87 units     | Refer to related topic |
| Cabin Pressure Controller advisory  | 60 units     | Refer to related topic |

**CAUTION:** The Flight Management Computer annunciation that differs from the expected state requires the relief pilot to announce the condition when conditions permit.

**16.30.14 Flap Position Indication Power Sources**

During preflight, both pilots should brief the Standby Instruments quantity display if the indication does not stabilize within the sample interval. The relief pilot will confirm any change in the Speedbrake Handle annunciation and advise the other pilot when operating at a sample station without ground power. The Autopilot Channel B advisory that differs from the expected state requires the Captain to confirm the condition if a discrepancy is observed. The Flap Position Indication switch position that differs from the expected state requires the First Officer to monitor the condition when operating at a sample station without ground power. The relief pilot will record any change in the Hydraulic System B advisory and advise the other pilot when operating at a sample station without ground power. The Pack Temperature Control indication is expected to read within the sample range of 53 to 61 units during descent.

**CAUTION:** During descent, both pilots should record the Autothrottle quantity display before the next phase of flight. During preflight, both pilots should cross-check the Ground Proximity Monitor quantity display when the associated caution light remains illuminated.

The Transponder annunciation that differs from the expected state requires the Captain to verify the condition if a discrepancy is observed. If the Probe Heat is inoperative, continue parking only after the Captain has reviewed the associated sample guidance. The first officer will announce any change in the Bleed Air Supply status message and advise the other pilot when operating at a sample station without ground power. The relief pilot will verify any change in the Auxiliary Power Unit selector position and advise the other pilot once the checklist item is complete.

This text is fictional and exists only to give the prototype realistic volume and structure. During a diversion, the First Officer should brief the Pack Temperature Control status message when conditions permit. The Autopilot Channel A annunciation that differs from the expected state requires the pilot monitoring to brief the condition when the associated caution light remains illuminated. The Probe Heat annunciation that differs from the expected state requires the relief pilot to select the condition when conditions permit. The wording here is placeholder content shaped like a procedure, not a procedure.

If the Hydraulic System B is inoperative, continue climb only after the relief pilot has reviewed the associated sample guidance. The Hydraulic System B quantity display is expected to read within the sample range of 80 to 89 units during takeoff. The Fuel Crossfeed selector position that differs from the expected state requires the relief pilot to select the condition when the associated caution light remains illuminated. The pilot flying will record any change in the Landing Gear Indication status message and advise the other pilot unless directed otherwise by the Sample Operations Center.

- During an extended ground delay, the relief pilot should record the Transponder switch position when conditions permit.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- If the Fire Detection Loop is inoperative, continue approach only after both pilots has reviewed the associated sample guidance.
- The Standby Instruments switch position is expected to read within the sample range of 96 to 101 units during approach.
- The Window Heat indication that differs from the expected state requires the pilot flying to record the condition if the indication does not stabilize within the sample interval.
- The pilot flying will cross-check any change in the Autothrottle quantity display and advise the other pilot before the next phase of flight.

The captain will confirm any change in the Standby Instruments selector position and advise the other pilot before the next phase of flight. The Cabin Pressure Controller annunciation is expected to read within the sample range of 21 to 24 units during descent. The captain will monitor any change in the Pack Temperature Control quantity display and advise the other pilot if the indication does not stabilize within the sample interval. The wording here is placeholder content shaped like a procedure, not a procedure. The Autobrake Selector switch position is expected to read within the sample range of 88 to 97 units during preflight. This text is fictional and exists only to give the prototype realistic volume and structure.

### **16.30.15 Engine Anti-Ice Interfaces**

The Cargo Smoke Detection quantity display that differs from the expected state requires the pilot monitoring to cross-check the condition when conditions permit. The Autothrottle advisory that differs from the expected state requires the First Officer to announce the condition if a discrepancy is observed. If the Transponder is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance. During climb, both pilots should record the Brake Temperature Monitor status message once the checklist item is complete. The Landing Gear Indication annunciation that differs from the expected state requires the First Officer to monitor the condition unless directed otherwise by the Sample Operations Center. The Primary Electrical Bus selector position is expected to read within the sample range of 65 to 75 units during a maintenance-requested ground run.

- The wording here is placeholder content shaped like a procedure, not a procedure.

- The relief pilot will brief any change in the Standby Instruments switch position and advise the other pilot when the associated caution light remains illuminated.
- During a maintenance-requested ground run, the Captain should brief the Thrust Reverser switch position when operating at a sample station without ground power.

| Condition                                 | Sample value | Remarks       |
|-------------------------------------------|--------------|---------------|
| Stall Warning status message              | 43 units     | Advisory only |
| Brake Temperature Monitor switch position | 2 units      | Advisory only |
| Cabin Pressure Controller switch position | 59 units     | Monitor       |
| Auxiliary Power Unit selector position    | 74 units     | Advisory only |
| Pack Temperature Control advisory         | 88 units     | Advisory only |

If the Hydraulic System B is inoperative, continue climb only after both pilots has reviewed the associated sample guidance. Both pilots will brief any change in the Cargo Smoke Detection indication and advise the other pilot unless directed otherwise by the Sample Operations Center. The Fuel Crossfeed indication is expected to read within the sample range of 65 to 71 units during preflight. The Center Tank Pumps advisory that differs from the expected state requires both pilots to confirm the condition unless directed otherwise by the Sample Operations Center. If the Cargo Smoke Detection is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance. The relief pilot will confirm any change in the Center Tank Pumps switch position and advise the other pilot when operating at a sample station without ground power.

The pilot monitoring will monitor any change in the Cabin Pressure Controller quantity display and advise the other pilot before the next phase of flight. The first officer will select any change in the Window Heat annunciation and advise the other pilot when conditions permit. If the Engine Anti-Ice is inoperative, continue taxi only after the pilot flying has reviewed the associated sample guidance. Both pilots will cross-check any change in the Standby Hydraulic annunciation and advise the other pilot when conditions permit. If the Fuel Crossfeed is inoperative, continue descent only after both pilots has reviewed the associated sample guidance.

**NOTE:** The Thrust Reverser status message is expected to read within the sample range of 65 to 68 units during parking.

- If the Center Tank Pumps is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance.
- During preflight, the First Officer should confirm the Standby Instruments quantity display when the associated caution light remains illuminated.
- The wording here is placeholder content shaped like a procedure, not a procedure.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Auxiliary Power Unit advisory             | 16 units     | Monitor                |
| Engine Anti-Ice quantity display          | 7 units      | Refer to related topic |
| Ground Proximity Monitor quantity display | 75 units     | Advisory only          |
| Cockpit Voice Recorder indication         | 27 units     | Monitor                |
| Hydraulic System B selector position      | 63 units     | Monitor                |
| Cabin Pressure Controller advisory        | 44 units     | Monitor                |

During a diversion, the First Officer should select the Brake Temperature Monitor switch position if a discrepancy is observed. The first officer will verify any change in the Primary Electrical Bus annunciation and advise the other pilot when operating at a sample station without ground power. The relief pilot will select any change in the Window Heat quantity display and advise the other pilot when conditions permit. During landing, the Captain should confirm the Landing Gear Indication annunciation once the checklist item is complete.

16.30.16 New Sample Topic: Auxiliary Power Unit

During takeoff, the pilot flying should verify the Flap Position Indication switch position if a discrepancy is observed. If the Standby Hydraulic is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose.

**CAUTION:** During landing, the Captain should brief the Fire Detection Loop switch position when the associated caution light remains illuminated.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Fire Detection Loop quantity display  | 98 units     | Monitor                |
| Nosewheel Steering switch position    | 22 units     | Monitor                |
| Hydraulic System B quantity display   | 59 units     | Refer to related topic |
| Hydraulic System A indication         | 2 units      | Advisory only          |
| Weather Radar selector position       | 27 units     | Advisory only          |
| Cockpit Voice Recorder status message | 62 units     | Refer to related topic |

**NOTE:** During taxi, both pilots should monitor the Pack Temperature Control selector position when conditions permit. The Standby Instruments advisory that differs from the expected state requires the First Officer to select the condition when the associated caution light remains illuminated.

**CAUTION:** During takeoff, the relief pilot should announce the Traffic Advisory Display status message when the associated caution light remains illuminated.

This text is fictional and exists only to give the prototype realistic volume and structure. If the Oxygen Distribution is inoperative, continue an extended ground delay only after the Captain has reviewed the associated sample guidance. The pilot monitoring will confirm any change in the Thrust Reverser indication and advise the other pilot when operating at a sample station without ground power. The Standby Instruments switch position is expected to read within the sample range of 12 to 20 units during taxi. The Wing Anti-Ice switch position is expected to read within the sample range of 65 to 71 units during taxi. The relief pilot will confirm any change in the Traffic Advisory Display selector position and advise the other pilot once the checklist item is complete.

This text is fictional and exists only to give the prototype realistic volume and structure. During an extended ground delay, the pilot monitoring should announce the Pack Temperature Control switch position when the associated caution light remains illuminated. The Pack Temperature Control quantity display is expected to read within the sample range of 40 to 48 units during landing. The Flight Management Computer selector position is expected to read within the sample range of 45 to 57 units during landing. The first officer will monitor any change in the Autopilot Channel A advisory and advise the other pilot if a discrepancy is observed.

This text is fictional and exists only to give the prototype realistic volume and structure. During takeoff, the Captain should verify the Traffic Advisory Display selector position once the checklist item is complete. The Oxygen Distribution quantity display is expected to read within the sample range of 3 to 9 units during preflight. If the Weather Radar is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance. If the Standby Hydraulic is inoperative, continue takeoff only after both pilots has reviewed the associated sample guidance. During parking, the First Officer should cross-check the Autopilot Channel B advisory if a discrepancy is observed.

**CAUTION:** If the Autopilot Channel B is inoperative, continue climb only after the Captain has reviewed the associated sample guidance.

16.30.17 Standby Hydraulic Indications

Values in this manual are invented and must not be used for any operational purpose. Both pilots will monitor any change in the Window Heat advisory and advise the other pilot when conditions permit. If the Engine Anti-Ice is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance.

During preflight, the relief pilot should cross-check the Autopilot Channel A quantity display when operating at a sample station without ground power. During a maintenance-requested ground run, the First Officer should record the Hydraulic System B indication if a discrepancy is observed. The Speedbrake Handle status message that differs from the expected state requires the relief pilot to brief the condition when operating at a sample station without ground power. If the Fuel Crossfeed is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance.

**CAUTION:** During cruise, the pilot monitoring should confirm the Thrust Reverser annunciation once the checklist item is complete.

**CAUTION:** The captain will record any change in the Cargo Smoke Detection switch position and advise the other pilot when the associated caution light remains illuminated.

- The Nosewheel Steering annunciation that differs from the expected state requires both pilots to announce the condition when operating at a sample station without ground power.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- The Wing Anti-Ice status message that differs from the expected state requires the pilot monitoring to monitor the condition when the associated caution light remains illuminated.
- Both pilots will announce any change in the Probe Heat annunciation and advise the other pilot when conditions permit.

**NOTE:** If the Window Heat is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance. The Landing Gear Indication status message that differs from the expected state requires the pilot flying to brief the condition before the next phase of flight.

- This text is fictional and exists only to give the prototype realistic volume and structure.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The Primary Electrical Bus selector position is expected to read within the sample range of 91 to 98 units during an extended ground delay.
- The relief pilot will cross-check any change in the Fire Detection Loop advisory and advise the other pilot before the next phase of flight.
- Values in this manual are invented and must not be used for any operational purpose.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Window Heat advisory                    | 42 units     | Normal                 |
| Standby Hydraulic advisory              | 18 units     | Refer to related topic |
| Cargo Smoke Detection selector position | 69 units     | Refer to related topic |

**NOTE:** The Speedbrake Handle quantity display is expected to read within the sample range of 26 to 37 units during landing.

# Chapter 17 Systems: Oxygen

## 17.10 Description

### 17.10.1 Weather Radar Test

Values in this manual are invented and must not be used for any operational purpose. If the Cargo Smoke Detection is inoperative, continue descent only after the Captain has reviewed the associated sample guidance. The Traffic Advisory Display indication that differs from the expected state requires both pilots to select the condition when conditions permit. The Primary Electrical Bus switch position is expected to read within the sample range of 68 to 74 units during climb. Values in this manual are invented and must not be used for any operational purpose.

- Refer to the related topic for additional sample context.
- Both pilots will announce any change in the Traffic Advisory Display switch position and advise the other pilot if a discrepancy is observed.
- The first officer will confirm any change in the Bleed Air Supply annunciation and advise the other pilot before the next phase of flight.
- The pilot flying will cross-check any change in the Transponder status message and advise the other pilot if a discrepancy is observed.
- Refer to the related topic for additional sample context.

**CAUTION:** The Cockpit Voice Recorder status message is expected to read within the sample range of 43 to 46 units during climb.

**NOTE:** If the Cabin Pressure Controller is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance.

**NOTE:** The Pack Temperature Control advisory that differs from the expected state requires the pilot flying to record the condition if the indication does not stabilize within the sample interval.

| Condition                          | Sample value | Remarks       |
|------------------------------------|--------------|---------------|
| Speedbrake Handle quantity display | 97 units     | Monitor       |
| Fuel Crossfeed indication          | 30 units     | Normal        |
| Transponder indication             | 45 units     | Advisory only |
| Standby Hydraulic advisory         | 18 units     | Normal        |

Both pilots will select any change in the Ground Proximity Monitor status message and advise the other pilot before the next phase of flight. The wording here is placeholder content shaped like a procedure, not a procedure. During preflight, the First Officer should confirm the Landing Gear Indication switch position once the checklist item is complete. The relief pilot will brief any change in the Cargo Smoke Detection annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center. This text is fictional and exists only to give the prototype realistic volume and structure. The relief pilot will record any change in the Standby Instruments annunciation and advise the other pilot once the checklist item is complete. See 05.60.5 Stall Warning Power Sources.

- Refer to the related topic for additional sample context.
- During a maintenance-requested ground run, the First Officer should cross-check the Wing Anti-Ice indication when conditions permit.
- The pilot monitoring will brief any change in the Fire Detection Loop advisory and advise the other pilot when conditions permit.



- During parking, the pilot flying should verify the Autopilot Channel A indication when the associated caution light remains illuminated.
- The first officer will select any change in the Speedbrake Handle advisory and advise the other pilot when the associated caution light remains illuminated.
- The Brake Temperature Monitor quantity display that differs from the expected state requires the First Officer to announce the condition unless directed otherwise by the Sample Operations Center.

**NOTE:** The Nosewheel Steering switch position that differs from the expected state requires the pilot monitoring to monitor the condition once the checklist item is complete. During a maintenance-requested ground run, both pilots should select the Autopilot Channel A status message if a discrepancy is observed.

**17.10.2 Engine Anti-Ice Indications**

The pilot flying will monitor any change in the Autothrottle advisory and advise the other pilot when conditions permit. Refer to the related topic for additional sample context. The pilot monitoring will select any change in the Hydraulic System B quantity display and advise the other pilot when operating at a sample station without ground power.

If the Brake Temperature Monitor is inoperative, continue parking only after the Captain has reviewed the associated sample guidance. During landing, the pilot flying should brief the Stall Warning advisory if a discrepancy is observed. The Probe Heat selector position that differs from the expected state requires both pilots to monitor the condition once the checklist item is complete. Values in this manual are invented and must not be used for any operational purpose. The Flight Management Computer annunciation is expected to read within the sample range of 93 to 97 units during approach.

| Condition                           | Sample value | Remarks                |
|-------------------------------------|--------------|------------------------|
| Hydraulic System B annunciation     | 64 units     | Advisory only          |
| Ground Proximity Monitor indication | 92 units     | Normal                 |
| Hydraulic System B quantity display | 55 units     | Monitor                |
| Flight Management Computer advisory | 54 units     | Refer to related topic |

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Cockpit Voice Recorder quantity display   | 94 units     | Refer to related topic |
| Brake Temperature Monitor switch position | 59 units     | Normal                 |
| Brake Temperature Monitor status message  | 18 units     | Refer to related topic |
| Standby Hydraulic selector position       | 64 units     | Normal                 |
| Nosewheel Steering advisory               | 29 units     | Refer to related topic |

**CAUTION:** If the Oxygen Distribution is inoperative, continue preflight only after the Captain has reviewed the associated sample guidance. The captain will confirm any change in the Hydraulic System A indication and advise the other pilot when operating at a sample station without ground power.

| Condition                            | Sample value | Remarks                |
|--------------------------------------|--------------|------------------------|
| Autopilot Channel B annunciation     | 33 units     | Refer to related topic |
| Cargo Smoke Detection status message | 22 units     | Refer to related topic |
| Window Heat switch position          | 24 units     | Refer to related topic |
| Nosewheel Steering quantity display  | 97 units     | Refer to related topic |

During an extended ground delay, the First Officer should monitor the Transponder status message unless directed otherwise by the Sample Operations Center. The Standby Instruments status message that differs from the expected state requires the First Officer to cross-check the condition when operating at a sample station without ground power.

If the Autopilot Channel B is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance. If the Thrust Reverser is inoperative, continue climb only after the Captain has reviewed the associated sample guidance.

**17.10.3 Weather Radar Normal Operation**

If the Wing Anti-Ice is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance. Both pilots will monitor any change in the Window Heat advisory and advise the other pilot before the next phase of flight. During a diversion, the pilot flying should brief the Wing Anti-Ice advisory if the indication does not stabilize within the sample interval.

- This text is fictional and exists only to give the prototype realistic volume and structure.
- If the Probe Heat is inoperative, continue engine start only after the Captain has reviewed the associated sample guidance.
- The Oxygen Distribution quantity display is expected to read within the sample range of 35 to 38 units during climb.
- The Standby Instruments status message that differs from the expected state requires the relief pilot to record the condition once the checklist item is complete.
- The Autothrottle quantity display is expected to read within the sample range of 81 to 85 units during a turnaround.

**NOTE:** The Center Tank Pumps annunciation that differs from the expected state requires the Captain to monitor the condition unless directed otherwise by the Sample Operations Center. The Cockpit Voice Recorder indication that differs from the expected state requires the relief pilot to select the condition when operating at a sample station without ground power.

**CAUTION:** Refer to the related topic for additional sample context. During climb, the First Officer should record the Engine Anti-Ice quantity display when conditions permit.

- If the Autopilot Channel B is inoperative, continue taxi only after the Captain has reviewed the associated sample guidance.
- If the Cockpit Voice Recorder is inoperative, continue preflight only after the Captain has reviewed the associated sample guidance.
- During climb, both pilots should cross-check the Cargo Smoke Detection indication before the next phase of flight.
- During a diversion, the relief pilot should confirm the Autothrottle quantity display when conditions permit.
- The Stall Warning quantity display that differs from the expected state requires the First Officer to announce the condition before the next phase of flight.
- The Cabin Pressure Controller advisory is expected to read within the sample range of 91 to 96 units during engine start.

The Thrust Reverser selector position that differs from the expected state requires the Captain to cross-check the condition unless directed otherwise by the Sample Operations Center. The Flight Management Computer selector position that differs from the expected state requires the pilot monitoring to announce the condition when conditions permit. If the Thrust Reverser is inoperative, continue cruise only after both pilots has reviewed the associated sample guidance.

| Condition                     | Sample value | Remarks                |
|-------------------------------|--------------|------------------------|
| Probe Heat status message     | 19 units     | Advisory only          |
| Transponder quantity display  | 75 units     | Normal                 |
| Auxiliary Power Unit advisory | 20 units     | Refer to related topic |
| Weather Radar switch position | 32 units     | Refer to related topic |

#### 17.10.4 Window Heat Power Sources

If the Pack Temperature Control is inoperative, continue cruise only after both pilots has reviewed the associated sample guidance. During a diversion, the pilot monitoring should cross-check the Stall Warning switch position when the associated caution light remains illuminated. The Stall Warning annunciation is expected to read within the sample range of 34 to 44 units during approach. The Traffic Advisory Display advisory that differs from the expected state requires the Captain to cross-check the condition once the checklist item is complete.

The first officer will cross-check any change in the Fuel Crossfeed status message and advise the other pilot if a discrepancy is observed. The Cockpit Voice Recorder switch position is expected to read within the sample range of 80 to 85 units during taxi. The Fuel Crossfeed annunciation that differs from the expected state requires the relief pilot to confirm the condition once the checklist item is complete. During parking, the First Officer should verify the Autobrake Selector quantity display when conditions permit. Values in this manual are invented and must not be used for any operational purpose.

- If the Engine Anti-Ice is inoperative, continue approach only after the relief pilot has reviewed the associated sample guidance.
- Values in this manual are invented and must not be used for any operational purpose.
- Values in this manual are invented and must not be used for any operational purpose.
- The Weather Radar status message is expected to read within the sample range of 32 to 39 units during climb.
- The Oxygen Distribution indication is expected to read within the sample range of 96 to 106 units during a maintenance-requested ground run.
- The pilot flying will record any change in the Landing Gear Indication annunciation and advise the other pilot once the checklist item is complete.
- The Autothrottle status message is expected to read within the sample range of 54 to 64 units during preflight.
- The Speedbrake Handle quantity display that differs from the expected state requires the Captain to monitor the condition when operating at a sample station without ground power.
- The pilot flying will brief any change in the Wing Anti-Ice status message and advise the other pilot when conditions permit.

**CAUTION:** The Brake Temperature Monitor annunciation that differs from the expected state requires both pilots to select the condition if the indication does not stabilize within the sample interval. The pilot flying will record any change in the Traffic Advisory Display status message and advise the other pilot unless directed otherwise by the Sample Operations Center.

During cruise, the pilot monitoring should brief the Fuel Crossfeed selector position unless directed otherwise by the Sample Operations Center. The Pack Temperature Control selector position is expected to read within the sample range of 19 to 31 units during a turnaround. The wording here is placeholder content shaped like a procedure, not a procedure.

This text is fictional and exists only to give the prototype realistic volume and structure. The pilot monitoring will verify any change in the Nosewheel Steering quantity display and advise the other pilot when operating at a sample station without ground power. The Landing Gear Indication status message that differs from the expected state requires the pilot flying to select the condition when operating at a sample station without ground power. The Wing Anti-Ice advisory is expected to read within the sample range of 32 to 41 units during landing.

The Primary Electrical Bus status message is expected to read within the sample range of 91 to 100 units during climb. The Fire Detection Loop indication is expected to read within the sample range of 49 to 58 units during a diversion. The Landing Gear Indication advisory that differs from the expected state requires the Captain to cross-check the condition when the associated caution light remains illuminated. During an extended ground delay, the relief pilot should confirm the Window Heat annunciation when the associated caution light remains illuminated.

The Stall Warning quantity display is expected to read within the sample range of 19 to 29 units during parking. The Autopilot Channel B quantity display that differs from the expected state requires the relief pilot to confirm the condition when conditions permit. See 03.30.8 Checklist: Oxygen Distribution.

**CAUTION:** The Hydraulic System B status message is expected to read within the sample range of 95 to 105 units during landing.

**17.10.5 Oxygen Distribution Crew Awareness**

The Primary Electrical Bus selector position that differs from the expected state requires the pilot monitoring to brief the condition unless directed otherwise by the Sample Operations Center. The relief pilot will brief any change in the Cargo Smoke Detection annunciation and advise the other pilot before the next phase of flight. The captain will announce any change in the Hydraulic System B selector position and advise the other pilot when the associated caution light remains illuminated.

If the Auxiliary Power Unit is inoperative, continue engine start only after the relief pilot has reviewed the associated sample guidance. The pilot monitoring will cross-check any change in the Autopilot Channel B advisory and advise the other pilot when conditions permit. The Autothrottle status message that differs from the expected state requires the Captain to cross-check the condition unless directed otherwise by the Sample Operations Center. The Fuel Crossfeed annunciation is expected to read within the sample range of 34 to 41 units during taxi. The Probe Heat selector position is expected to read within the sample range of 85 to 91 units during a turnaround. The Cabin Pressure Controller indication is expected to read within the sample range of 8 to 11 units during descent.

**NOTE:** The Pack Temperature Control advisory is expected to read within the sample range of 23 to 35 units during takeoff.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Brake Temperature Monitor switch position | 81 units     | Refer to related topic |
| Transponder advisory                      | 58 units     | Advisory only          |
| Cargo Smoke Detection indication          | 54 units     | Monitor                |
| Cargo Smoke Detection switch position     | 87 units     | Refer to related topic |
| Autobrake Selector advisory               | 19 units     | Refer to related topic |

Values in this manual are invented and must not be used for any operational purpose. If the Fuel Crossfeed is inoperative, continue engine start only after the relief pilot has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. The Traffic Advisory Display switch position that differs from the expected state requires the pilot flying to record the condition when the associated caution light remains illuminated. Both pilots will verify any change in the Thrust Reverser switch position and advise the other pilot if a discrepancy is observed.

The Primary Electrical Bus switch position that differs from the expected state requires the Captain to announce the condition if the indication does not stabilize within the sample interval. During a diversion, both pilots should select the Transponder switch position if the indication does not stabilize within the sample interval. Values in this manual are invented and must not be used for any operational purpose. Values in this manual are invented and must not be used for any operational purpose. The relief pilot will record any change in the Hydraulic System B status message and advise the other pilot if the indication does not stabilize within the sample interval. The relief pilot will monitor any change in the Fire Detection Loop annunciation and advise the other pilot if the indication does not stabilize within the sample interval.

**17.10.6 Traffic Advisory Display Test**

The relief pilot will cross-check any change in the Transponder indication and advise the other pilot when operating at a sample station without ground power. If the Fuel Crossfeed is inoperative, continue landing only after both pilots has reviewed the associated sample guidance. During an extended ground delay, the Captain should monitor the

Thrust Reverser status message once the checklist item is complete. The Pack Temperature Control status message that differs from the expected state requires the relief pilot to select the condition before the next phase of flight. The pilot monitoring will cross-check any change in the Oxygen Distribution status message and advise the other pilot when conditions permit.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Thrust Reverser indication               | 47 units     | Monitor                |
| Flap Position Indication switch position | 47 units     | Advisory only          |
| Brake Temperature Monitor advisory       | 66 units     | Monitor                |
| Oxygen Distribution indication           | 62 units     | Refer to related topic |

| Condition                               | Sample value | Remarks       |
|-----------------------------------------|--------------|---------------|
| Pack Temperature Control annunciation   | 71 units     | Advisory only |
| Autopilot Channel B indication          | 49 units     | Advisory only |
| Cockpit Voice Recorder quantity display | 94 units     | Normal        |
| Nosewheel Steering quantity display     | 75 units     | Normal        |
| Flap Position Indication status message | 30 units     | Advisory only |

If the Center Tank Pumps is inoperative, continue climb only after both pilots has reviewed the associated sample guidance. During takeoff, the pilot flying should cross-check the Flap Position Indication selector position before the next phase of flight. The wording here is placeholder content shaped like a procedure, not a procedure. The pilot flying will cross-check any change in the Probe Heat selector position and advise the other pilot when the associated caution light remains illuminated.

The Brake Temperature Monitor switch position that differs from the expected state requires the pilot monitoring to brief the condition when the associated caution light remains illuminated. The Brake Temperature Monitor indication that differs from the expected state requires the Captain to announce the condition unless directed otherwise by the Sample Operations Center. If the Probe Heat is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance. During descent, both pilots should brief the Standby Hydraulic selector position if a discrepancy is observed. During preflight, the pilot flying should cross-check the Fire Detection Loop quantity display before the next phase of flight. If the Cabin Pressure Controller is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance.

The Probe Heat switch position is expected to read within the sample range of 35 to 47 units during taxi. The Landing Gear Indication annunciation is expected to read within the sample range of 75 to 81 units during landing. The Landing Gear Indication indication that differs from the expected state requires both pilots to record the condition if the indication does not stabilize within the sample interval.

- If the Ground Proximity Monitor is inoperative, continue parking only after the pilot monitoring has reviewed the associated sample guidance.
- The Engine Anti-Ice quantity display that differs from the expected state requires the pilot monitoring to confirm the condition before the next phase of flight.
- The Flap Position Indication status message that differs from the expected state requires the relief pilot to monitor the condition when operating at a sample station without ground power.

### 17.10.7 Flight Management Computer Reset Guidance

If the Autobrake Selector is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance. The Fire Detection Loop quantity display is expected to read within the sample range of 11 to 19 units during a diversion. During landing, the relief pilot should announce the Hydraulic System B indication when the associated caution light remains illuminated. If the Fire Detection Loop is inoperative, continue preflight only after both pilots has reviewed the associated sample guidance. The wording here is placeholder content shaped like a

procedure, not a procedure.

**NOTE:** This text is fictional and exists only to give the prototype realistic volume and structure. If the Weather Radar is inoperative, continue a maintenance-requested ground run only after both pilots has reviewed the associated sample guidance.

The wording here is placeholder content shaped like a procedure, not a procedure. The Autothrottle quantity display is expected to read within the sample range of 88 to 92 units during a turnaround. The wording here is placeholder content shaped like a procedure, not a procedure. The Fuel Crossfeed status message that differs from the expected state requires the First Officer to select the condition once the checklist item is complete. Values in this manual are invented and must not be used for any operational purpose. The Stall Warning switch position is expected to read within the sample range of 26 to 34 units during cruise.

| Condition                           | Sample value | Remarks       |
|-------------------------------------|--------------|---------------|
| Fuel Crossfeed advisory             | 28 units     | Advisory only |
| Transponder advisory                | 43 units     | Normal        |
| Speedbrake Handle indication        | 32 units     | Normal        |
| Center Tank Pumps quantity display  | 68 units     | Normal        |
| Standby Instruments switch position | 9 units      | Monitor       |

- The Autopilot Channel A selector position is expected to read within the sample range of 32 to 35 units during a maintenance-requested ground run.
- Refer to the related topic for additional sample context.
- The pilot flying will verify any change in the Fire Detection Loop indication and advise the other pilot before the next phase of flight.
- The pilot monitoring will verify any change in the Weather Radar selector position and advise the other pilot when the associated caution light remains illuminated.
- The Autothrottle status message that differs from the expected state requires the First Officer to announce the condition when operating at a sample station without ground power.

The first officer will monitor any change in the Brake Temperature Monitor selector position and advise the other pilot when the associated caution light remains illuminated. The wording here is placeholder content shaped like a procedure, not a procedure. The Bleed Air Supply annunciation is expected to read within the sample range of 23 to 35 units during approach. If the Landing Gear Indication is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance. If the Brake Temperature Monitor is inoperative, continue approach only after the First Officer has reviewed the associated sample guidance.

**17.10.8 Hydraulic System A Reset Guidance**

If the Autopilot Channel B is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance. During taxi, both pilots should announce the Pack Temperature Control indication when operating at a sample station without ground power. During an extended ground delay, the Captain should confirm the Thrust Reverser selector position when the associated caution light remains illuminated.

**NOTE:** The pilot flying will confirm any change in the Cockpit Voice Recorder selector position and advise the other pilot if the indication does not stabilize within the sample interval.

The Brake Temperature Monitor indication that differs from the expected state requires the pilot monitoring to confirm the condition when operating at a sample station without ground power. The Nosewheel Steering quantity display is expected to read within the sample range of 89 to 97 units during a diversion. This text is fictional and exists only to give the prototype realistic volume and structure. The first officer will monitor any change in the Traffic Advisory Display annunciation and advise the other pilot when operating at a sample station without ground power. Values in



this manual are invented and must not be used for any operational purpose. The Standby Hydraulic switch position that differs from the expected state requires the relief pilot to monitor the condition unless directed otherwise by the Sample Operations Center.

Values in this manual are invented and must not be used for any operational purpose. This text is fictional and exists only to give the prototype realistic volume and structure. This text is fictional and exists only to give the prototype realistic volume and structure.

Values in this manual are invented and must not be used for any operational purpose. The pilot monitoring will select any change in the Thrust Reverser status message and advise the other pilot when the associated caution light remains illuminated. Both pilots will verify any change in the Cargo Smoke Detection indication and advise the other pilot if the indication does not stabilize within the sample interval. The Bleed Air Supply indication that differs from the expected state requires the pilot flying to monitor the condition before the next phase of flight. Values in this manual are invented and must not be used for any operational purpose. Refer to the related topic for additional sample context.

**NOTE:** The pilot flying will brief any change in the Weather Radar status message and advise the other pilot if the indication does not stabilize within the sample interval. The Autobrake Selector annunciation that differs from the expected state requires both pilots to select the condition unless directed otherwise by the Sample Operations Center.

**CAUTION:** The Flight Management Computer annunciation that differs from the expected state requires the relief pilot to monitor the condition before the next phase of flight. If the Landing Gear Indication is inoperative, continue engine start only after both pilots has reviewed the associated sample guidance.

**NOTE:** If the Autobrake Selector is inoperative, continue taxi only after the pilot flying has reviewed the associated sample guidance.

**CAUTION:** Values in this manual are invented and must not be used for any operational purpose.

17.10.9 Thrust Reverser Status Messages

The Oxygen Distribution quantity display is expected to read within the sample range of 98 to 103 units during climb. If the Oxygen Distribution is inoperative, continue takeoff only after both pilots has reviewed the associated sample guidance. During takeoff, the First Officer should announce the Cargo Smoke Detection advisory unless directed otherwise by the Sample Operations Center.

During a maintenance-requested ground run, the pilot flying should record the Autopilot Channel A selector position before the next phase of flight. The wording here is placeholder content shaped like a procedure, not a procedure. The Transponder selector position is expected to read within the sample range of 43 to 52 units during approach. The wording here is placeholder content shaped like a procedure, not a procedure. The wording here is placeholder content shaped like a procedure, not a procedure.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Hydraulic System B switch position       | 67 units     | Refer to related topic |
| Autothrottle switch position             | 22 units     | Normal                 |
| Autobrake Selector indication            | 89 units     | Advisory only          |
| Primary Electrical Bus selector position | 4 units      | Refer to related topic |
| Transponder indication                   | 20 units     | Refer to related topic |
| Autobrake Selector indication            | 84 units     | Refer to related topic |
| Autopilot Channel B indication           | 82 units     | Normal                 |

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Transponder quantity display            | 95 units     | Refer to related topic |
| Pack Temperature Control status message | 79 units     | Monitor                |

|                                     |          |                        |
|-------------------------------------|----------|------------------------|
| Autopilot Channel A switch position | 32 units | Refer to related topic |
| Hydraulic System B status message   | 54 units | Normal                 |

The wording here is placeholder content shaped like a procedure, not a procedure. This text is fictional and exists only to give the prototype realistic volume and structure. During takeoff, the pilot monitoring should announce the Hydraulic System A selector position if a discrepancy is observed.

**CAUTION:** The Fuel Crossfeed annunciation that differs from the expected state requires the Captain to cross-check the condition if the indication does not stabilize within the sample interval. If the Speedbrake Handle is inoperative, continue landing only after the Captain has reviewed the associated sample guidance.

**17.10.10 Fuel Crossfeed Normal Operation**

The relief pilot will select any change in the Fire Detection Loop status message and advise the other pilot once the checklist item is complete. The pilot monitoring will verify any change in the Ground Proximity Monitor annunciation and advise the other pilot once the checklist item is complete. The Brake Temperature Monitor indication that differs from the expected state requires the Captain to brief the condition unless directed otherwise by the Sample Operations Center. The captain will select any change in the Fire Detection Loop selector position and advise the other pilot unless directed otherwise by the Sample Operations Center. During a turnaround, the relief pilot should announce the Weather Radar quantity display if the indication does not stabilize within the sample interval.

During climb, the Captain should record the Autobrake Selector quantity display unless directed otherwise by the Sample Operations Center. Refer to the related topic for additional sample context. Values in this manual are invented and must not be used for any operational purpose. This text is fictional and exists only to give the prototype realistic volume and structure. Values in this manual are invented and must not be used for any operational purpose. If the Cockpit Voice Recorder is inoperative, continue approach only after the relief pilot has reviewed the associated sample guidance.

**NOTE:** The wording here is placeholder content shaped like a procedure, not a procedure.

**CAUTION:** The Engine Anti-Ice selector position is expected to read within the sample range of 68 to 76 units during takeoff.

The pilot monitoring will record any change in the Autopilot Channel A annunciation and advise the other pilot when the associated caution light remains illuminated. This text is fictional and exists only to give the prototype realistic volume and structure. During a turnaround, the pilot monitoring should select the Standby Instruments advisory unless directed otherwise by the Sample Operations Center. During parking, the relief pilot should verify the Wing Anti-Ice indication when operating at a sample station without ground power. During landing, the pilot monitoring should record the Fuel Crossfeed selector position unless directed otherwise by the Sample Operations Center. The relief pilot will cross-check any change in the Fuel Crossfeed advisory and advise the other pilot once the checklist item is complete.

The Nosewheel Steering status message is expected to read within the sample range of 67 to 79 units during landing. The Autothrottle switch position that differs from the expected state requires the pilot monitoring to cross-check the condition if a discrepancy is observed. If the Fuel Crossfeed is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance. During a turnaround, the pilot monitoring should cross-check the Transponder selector position when operating at a sample station without ground power. The Wing Anti-Ice indication that differs from the expected state requires both pilots to monitor the condition when operating at a sample station without ground power. The Speedbrake Handle annunciation that differs from the expected state requires the pilot flying to record the condition unless directed otherwise by the Sample Operations Center.

**17.10.11 Autopilot Channel B Power Sources**

The Oxygen Distribution quantity display is expected to read within the sample range of 30 to 35 units during an extended ground delay. The Auxiliary Power Unit selector position that differs from the expected state requires the First Officer to confirm the condition before the next phase of flight. During an extended ground delay, the pilot flying

should brief the Standby Hydraulic selector position when operating at a sample station without ground power. The Ground Proximity Monitor advisory that differs from the expected state requires the relief pilot to confirm the condition when the associated caution light remains illuminated. The Traffic Advisory Display selector position is expected to read within the sample range of 45 to 55 units during descent.

If the Hydraulic System A is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance. The pilot monitoring will monitor any change in the Hydraulic System B annunciation and advise the other pilot before the next phase of flight. If the Center Tank Pumps is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance.

**NOTE:** This text is fictional and exists only to give the prototype realistic volume and structure. During descent, the relief pilot should record the Standby Hydraulic advisory when conditions permit.

- During taxi, the Captain should cross-check the Bleed Air Supply switch position unless directed otherwise by the Sample Operations Center.
- The Traffic Advisory Display annunciation is expected to read within the sample range of 22 to 26 units during parking.
- If the Fire Detection Loop is inoperative, continue landing only after the pilot monitoring has reviewed the associated sample guidance.
- The first officer will cross-check any change in the Speedbrake Handle quantity display and advise the other pilot when the associated caution light remains illuminated.
- During preflight, the relief pilot should record the Fuel Crossfeed selector position unless directed otherwise by the Sample Operations Center.

During preflight, the Captain should brief the Cockpit Voice Recorder annunciation when conditions permit. During an extended ground delay, the pilot monitoring should verify the Standby Instruments status message once the checklist item is complete. If the Transponder is inoperative, continue descent only after the First Officer has reviewed the associated sample guidance.

The captain will record any change in the Autothrottle status message and advise the other pilot unless directed otherwise by the Sample Operations Center. The wording here is placeholder content shaped like a procedure, not a procedure. Values in this manual are invented and must not be used for any operational purpose. The pilot monitoring will brief any change in the Fuel Crossfeed quantity display and advise the other pilot once the checklist item is complete. The first officer will select any change in the Fuel Crossfeed selector position and advise the other pilot unless directed otherwise by the Sample Operations Center.

**CAUTION:** This text is fictional and exists only to give the prototype realistic volume and structure. The pilot flying will record any change in the Cockpit Voice Recorder status message and advise the other pilot when operating at a sample station without ground power.

The Engine Anti-Ice annunciation is expected to read within the sample range of 54 to 61 units during landing. If the Engine Anti-Ice is inoperative, continue climb only after the pilot flying has reviewed the associated sample guidance. If the Oxygen Distribution is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance. The pilot flying will record any change in the Oxygen Distribution advisory and advise the other pilot once the checklist item is complete. The pilot flying will monitor any change in the Flight Management Computer switch position and advise the other pilot unless directed otherwise by the Sample Operations Center. If the Auxiliary Power Unit is inoperative, continue engine start only after the pilot monitoring has reviewed the associated sample guidance.

- The wording here is placeholder content shaped like a procedure, not a procedure.
- The Autobrake Selector quantity display is expected to read within the sample range of 56 to 61 units during descent.
- During preflight, both pilots should select the Standby Hydraulic status message unless directed otherwise by the Sample Operations Center.

- Both pilots will cross-check any change in the Stall Warning advisory and advise the other pilot if a discrepancy is observed.

### **17.10.12 Fuel Crossfeed Overview**

The Hydraulic System B indication is expected to read within the sample range of 72 to 84 units during a turnaround. The pilot flying will record any change in the Autobrake Selector status message and advise the other pilot when the associated caution light remains illuminated. The Probe Heat annunciation is expected to read within the sample range of 24 to 30 units during takeoff. If the Ground Proximity Monitor is inoperative, continue taxi only after the First Officer has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. The relief pilot will record any change in the Bleed Air Supply selector position and advise the other pilot if a discrepancy is observed.

The Pack Temperature Control quantity display that differs from the expected state requires the First Officer to verify the condition if the indication does not stabilize within the sample interval. During approach, both pilots should verify the Fuel Crossfeed annunciation if the indication does not stabilize within the sample interval. Both pilots will select any change in the Fire Detection Loop selector position and advise the other pilot when the associated caution light remains illuminated. During climb, the relief pilot should confirm the Traffic Advisory Display status message unless directed otherwise by the Sample Operations Center. During a maintenance-requested ground run, the pilot monitoring should verify the Autobrake Selector advisory before the next phase of flight.

During descent, the First Officer should verify the Nosewheel Steering status message if the indication does not stabilize within the sample interval. The Fuel Crossfeed advisory that differs from the expected state requires the relief pilot to record the condition if the indication does not stabilize within the sample interval. During climb, both pilots should verify the Autopilot Channel A advisory when the associated caution light remains illuminated. During a maintenance-requested ground run, the pilot monitoring should cross-check the Transponder annunciation unless directed otherwise by the Sample Operations Center.

If the Stall Warning is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance. If the Weather Radar is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance. Both pilots will monitor any change in the Autopilot Channel A advisory and advise the other pilot when the associated caution light remains illuminated. During a maintenance-requested ground run, both pilots should select the Transponder quantity display before the next phase of flight. The relief pilot will cross-check any change in the Cargo Smoke Detection switch position and advise the other pilot when operating at a sample station without ground power.

**CAUTION:** This text is fictional and exists only to give the prototype realistic volume and structure. Values in this manual are invented and must not be used for any operational purpose.

If the Thrust Reverser is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance. The Standby Hydraulic status message that differs from the expected state requires the pilot flying to announce the condition if the indication does not stabilize within the sample interval. The pilot monitoring will brief any change in the Ground Proximity Monitor indication and advise the other pilot when conditions permit. This text is fictional and exists only to give the prototype realistic volume and structure. The wording here is placeholder content shaped like a procedure, not a procedure.

### **17.10.13 Transponder Test**

The Bleed Air Supply advisory that differs from the expected state requires both pilots to monitor the condition unless directed otherwise by the Sample Operations Center. The Cockpit Voice Recorder advisory is expected to read within the sample range of 73 to 82 units during climb. If the Ground Proximity Monitor is inoperative, continue a maintenance-requested ground run only after the pilot monitoring has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. The Center Tank Pumps switch position is expected to read within the sample range of 46 to 54 units during a diversion.

During preflight, the pilot monitoring should select the Traffic Advisory Display selector position if a discrepancy is observed. During a maintenance-requested ground run, the First Officer should select the Stall Warning indication

when the associated caution light remains illuminated. This text is fictional and exists only to give the prototype realistic volume and structure. The Autopilot Channel B status message that differs from the expected state requires the First Officer to verify the condition when the associated caution light remains illuminated.

The relief pilot will monitor any change in the Transponder selector position and advise the other pilot if a discrepancy is observed. Refer to the related topic for additional sample context. The first officer will confirm any change in the Autopilot Channel A annunciation and advise the other pilot before the next phase of flight. During engine start, the Captain should record the Speedbrake Handle quantity display before the next phase of flight.

During taxi, the pilot flying should cross-check the Pack Temperature Control annunciation when conditions permit. During an extended ground delay, the First Officer should monitor the Autothrottle indication if the indication does not stabilize within the sample interval. If the Probe Heat is inoperative, continue cruise only after the Captain has reviewed the associated sample guidance. Both pilots will record any change in the Flap Position Indication indication and advise the other pilot when the associated caution light remains illuminated.

The Primary Electrical Bus quantity display is expected to read within the sample range of 15 to 26 units during parking. During a turnaround, the pilot flying should announce the Hydraulic System B switch position if a discrepancy is observed. The first officer will monitor any change in the Autobrake Selector switch position and advise the other pilot if a discrepancy is observed. The Nosewheel Steering status message is expected to read within the sample range of 81 to 90 units during takeoff.

**17.10.14 Standby Hydraulic Indications**

If the Autobrake Selector is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance. Refer to the related topic for additional sample context. The wording here is placeholder content shaped like a procedure, not a procedure. Refer to the related topic for additional sample context. This text is fictional and exists only to give the prototype realistic volume and structure. The Traffic Advisory Display switch position that differs from the expected state requires both pilots to record the condition before the next phase of flight.

- This text is fictional and exists only to give the prototype realistic volume and structure.
- The pilot flying will brief any change in the Cockpit Voice Recorder advisory and advise the other pilot when the associated caution light remains illuminated.
- Refer to the related topic for additional sample context.

The pilot flying will announce any change in the Cockpit Voice Recorder switch position and advise the other pilot unless directed otherwise by the Sample Operations Center. During a turnaround, the Captain should record the Autopilot Channel B selector position if a discrepancy is observed. The Cabin Pressure Controller status message is expected to read within the sample range of 69 to 80 units during preflight. See 05.70.12 Wing Anti-Ice Power Sources.

| Condition                           | Sample value | Remarks                |
|-------------------------------------|--------------|------------------------|
| Flap Position Indication advisory   | 82 units     | Monitor                |
| Brake Temperature Monitor advisory  | 95 units     | Advisory only          |
| Flap Position Indication indication | 12 units     | Monitor                |
| Window Heat indication              | 55 units     | Normal                 |
| Center Tank Pumps annunciation      | 68 units     | Refer to related topic |

**CAUTION:** During parking, the pilot flying should select the Engine Anti-Ice indication once the checklist item is complete.

**17.10.15 Engine Anti-Ice Status Messages**

The Speedbrake Handle indication that differs from the expected state requires the pilot monitoring to select the condition before the next phase of flight. The Cockpit Voice Recorder switch position that differs from the expected

state requires both pilots to confirm the condition when the associated caution light remains illuminated. If the Hydraulic System B is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance. During a maintenance-requested ground run, the First Officer should verify the Weather Radar annunciation when operating at a sample station without ground power. During an extended ground delay, the pilot flying should brief the Landing Gear Indication switch position when conditions permit.

| Condition                               | Sample value | Remarks       |
|-----------------------------------------|--------------|---------------|
| Thrust Reverser annunciation            | 17 units     | Advisory only |
| Stall Warning status message            | 60 units     | Monitor       |
| Hydraulic System A indication           | 18 units     | Monitor       |
| Flight Management Computer annunciation | 33 units     | Normal        |
| Engine Anti-Ice quantity display        | 7 units      | Advisory only |

If the Bleed Air Supply is inoperative, continue parking only after the Captain has reviewed the associated sample guidance. The pilot flying will record any change in the Stall Warning selector position and advise the other pilot if the indication does not stabilize within the sample interval. If the Flap Position Indication is inoperative, continue landing only after the First Officer has reviewed the associated sample guidance.

The pilot flying will announce any change in the Wing Anti-Ice selector position and advise the other pilot if the indication does not stabilize within the sample interval. If the Center Tank Pumps is inoperative, continue cruise only after the Captain has reviewed the associated sample guidance. The pilot monitoring will confirm any change in the Oxygen Distribution indication and advise the other pilot when conditions permit. The Engine Anti-Ice status message that differs from the expected state requires the Captain to announce the condition when conditions permit.

If the Flap Position Indication is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance. If the Cabin Pressure Controller is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. During climb, both pilots should brief the Standby Hydraulic switch position when the associated caution light remains illuminated. During climb, the pilot monitoring should monitor the Stall Warning status message before the next phase of flight.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Transponder switch position           | 61 units     | Refer to related topic |
| Autopilot Channel B status message    | 51 units     | Monitor                |
| Oxygen Distribution quantity display  | 39 units     | Refer to related topic |
| Autobrake Selector advisory           | 67 units     | Advisory only          |
| Traffic Advisory Display annunciation | 66 units     | Advisory only          |
| Primary Electrical Bus status message | 34 units     | Advisory only          |
| Wing Anti-Ice advisory                | 80 units     | Refer to related topic |

Values in this manual are invented and must not be used for any operational purpose. During descent, the pilot flying should verify the Standby Instruments indication once the checklist item is complete. The relief pilot will brief any change in the Autopilot Channel B quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center. This text is fictional and exists only to give the prototype realistic volume and structure.

**NOTE:** Values in this manual are invented and must not be used for any operational purpose. The Fuel Crossfeed selector position that differs from the expected state requires both pilots to confirm the condition unless directed otherwise by the Sample Operations Center.

### 17.10.16 Bleed Air Supply Crew Awareness



The Ground Proximity Monitor annunciation is expected to read within the sample range of 11 to 22 units during a turnaround. If the Window Heat is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance. The Standby Instruments switch position is expected to read within the sample range of 21 to 24 units during a turnaround. This text is fictional and exists only to give the prototype realistic volume and structure. The Probe Heat advisory that differs from the expected state requires the relief pilot to cross-check the condition once the checklist item is complete. Both pilots will announce any change in the Center Tank Pumps quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center.

Refer to the related topic for additional sample context. The Nosewheel Steering quantity display that differs from the expected state requires the pilot flying to cross-check the condition if a discrepancy is observed. The Standby Instruments advisory is expected to read within the sample range of 3 to 7 units during parking. The Fire Detection Loop status message that differs from the expected state requires the pilot monitoring to cross-check the condition if the indication does not stabilize within the sample interval. The Autopilot Channel A quantity display is expected to read within the sample range of 48 to 53 units during descent.

**NOTE:** Refer to the related topic for additional sample context.

**CAUTION:** During climb, the Captain should announce the Auxiliary Power Unit switch position before the next phase of flight.

- This text is fictional and exists only to give the prototype realistic volume and structure.
- Refer to the related topic for additional sample context.
- During taxi, the pilot monitoring should monitor the Cargo Smoke Detection quantity display before the next phase of flight.
- Both pilots will select any change in the Wing Anti-Ice selector position and advise the other pilot when the associated caution light remains illuminated.
- The Speedbrake Handle advisory that differs from the expected state requires both pilots to cross-check the condition if the indication does not stabilize within the sample interval.
- The Landing Gear Indication switch position that differs from the expected state requires the Captain to cross-check the condition before the next phase of flight.

This text is fictional and exists only to give the prototype realistic volume and structure. The Fuel Crossfeed indication is expected to read within the sample range of 53 to 62 units during approach. If the Cockpit Voice Recorder is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance. Both pilots will select any change in the Brake Temperature Monitor advisory and advise the other pilot when conditions permit. The Flight Management Computer indication that differs from the expected state requires the pilot monitoring to monitor the condition when operating at a sample station without ground power. The Flight Management Computer status message that differs from the expected state requires the pilot flying to select the condition when the associated caution light remains illuminated.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Cabin Pressure Controller annunciation    | 21 units     | Monitor                |
| Window Heat advisory                      | 47 units     | Refer to related topic |
| Brake Temperature Monitor switch position | 2 units      | Advisory only          |
| Cockpit Voice Recorder status message     | 70 units     | Refer to related topic |
| Autothrottle quantity display             | 17 units     | Normal                 |
| Speedbrake Handle quantity display        | 44 units     | Advisory only          |
| Ground Proximity Monitor switch position  | 65 units     | Monitor                |

**CAUTION:** The pilot flying will record any change in the Hydraulic System A switch position and advise the other pilot when conditions permit. Refer to the related topic for additional sample context.

## 17.20 Controls and Indicators

### 17.20.1 Fire Detection Loop Overview

If the Ground Proximity Monitor is inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. The Stall Warning switch position that differs from the expected state requires the First Officer to record the condition if a discrepancy is observed. Both pilots will cross-check any change in the Center Tank Pumps indication and advise the other pilot unless directed otherwise by the Sample Operations Center. During landing, both pilots should record the Brake Temperature Monitor indication once the checklist item is complete. During climb, the pilot monitoring should select the Bleed Air Supply advisory when operating at a sample station without ground power.

**NOTE:** The Oxygen Distribution advisory is expected to read within the sample range of 53 to 60 units during takeoff.

The Oxygen Distribution quantity display that differs from the expected state requires the pilot flying to monitor the condition when operating at a sample station without ground power. If the Transponder is inoperative, continue engine start only after the pilot flying has reviewed the associated sample guidance. During a diversion, the pilot monitoring should announce the Center Tank Pumps quantity display if the indication does not stabilize within the sample interval. If the Stall Warning is inoperative, continue takeoff only after both pilots has reviewed the associated sample guidance.

**NOTE:** The Stall Warning switch position that differs from the expected state requires the First Officer to cross-check the condition when conditions permit.

**NOTE:** Values in this manual are invented and must not be used for any operational purpose.

Values in this manual are invented and must not be used for any operational purpose. If the Autothrottle is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance. The Cockpit Voice Recorder quantity display that differs from the expected state requires both pilots to monitor the condition before the next phase of flight. The Center Tank Pumps selector position is expected to read within the sample range of 38 to 49 units during takeoff.

- The first officer will brief any change in the Flap Position Indication status message and advise the other pilot before the next phase of flight.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- Values in this manual are invented and must not be used for any operational purpose.
- The pilot flying will select any change in the Autopilot Channel B annunciation and advise the other pilot when operating at a sample station without ground power.
- Refer to the related topic for additional sample context.
- The relief pilot will verify any change in the Transponder indication and advise the other pilot unless directed otherwise by the Sample Operations Center.

If the Traffic Advisory Display is inoperative, continue climb only after the First Officer has reviewed the associated sample guidance. If the Auxiliary Power Unit is inoperative, continue climb only after the Captain has reviewed the associated sample guidance. The pilot flying will announce any change in the Transponder switch position and advise the other pilot when operating at a sample station without ground power.

### 17.20.2 Flight Management Computer Indications

During landing, both pilots should verify the Stall Warning indication when operating at a sample station without ground power. The relief pilot will confirm any change in the Flap Position Indication indication and advise the other pilot when conditions permit. The Engine Anti-Ice selector position that differs from the expected state requires both pilots to announce the condition once the checklist item is complete. The Probe Heat indication is expected to read

within the sample range of 52 to 62 units during taxi. The relief pilot will brief any change in the Nosewheel Steering indication and advise the other pilot once the checklist item is complete. The first officer will select any change in the Flap Position Indication selector position and advise the other pilot before the next phase of flight.

**CAUTION:** The wording here is placeholder content shaped like a procedure, not a procedure. The first officer will confirm any change in the Autopilot Channel A indication and advise the other pilot if the indication does not stabilize within the sample interval.

The Bleed Air Supply annunciation that differs from the expected state requires the First Officer to record the condition unless directed otherwise by the Sample Operations Center. If the Fire Detection Loop is inoperative, continue descent only after both pilots has reviewed the associated sample guidance. The Pack Temperature Control selector position is expected to read within the sample range of 60 to 69 units during a diversion. The Brake Temperature Monitor status message that differs from the expected state requires the First Officer to announce the condition when conditions permit. During climb, the First Officer should cross-check the Autothrottle selector position when operating at a sample station without ground power.

The Fire Detection Loop status message that differs from the expected state requires the Captain to cross-check the condition once the checklist item is complete. The Stall Warning annunciation is expected to read within the sample range of 92 to 97 units during cruise. Values in this manual are invented and must not be used for any operational purpose. The Probe Heat quantity display is expected to read within the sample range of 41 to 52 units during descent. The Landing Gear Indication indication is expected to read within the sample range of 63 to 67 units during a diversion.

The Fire Detection Loop indication is expected to read within the sample range of 6 to 17 units during climb. If the Autopilot Channel B is inoperative, continue landing only after the First Officer has reviewed the associated sample guidance. During an extended ground delay, the pilot monitoring should monitor the Bleed Air Supply indication if the indication does not stabilize within the sample interval.

If the Transponder is inoperative, continue climb only after both pilots has reviewed the associated sample guidance. The Hydraulic System B annunciation that differs from the expected state requires the Captain to brief the condition if the indication does not stabilize within the sample interval. During a maintenance-requested ground run, the pilot flying should select the Cargo Smoke Detection indication unless directed otherwise by the Sample Operations Center. If the Thrust Reverser is inoperative, continue landing only after both pilots has reviewed the associated sample guidance.

The Autobrake Selector annunciation is expected to read within the sample range of 23 to 29 units during parking. The pilot flying will confirm any change in the Cabin Pressure Controller indication and advise the other pilot before the next phase of flight. The pilot flying will cross-check any change in the Standby Hydraulic advisory and advise the other pilot unless directed otherwise by the Sample Operations Center. If the Oxygen Distribution is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance.

- The pilot flying will monitor any change in the Speedbrake Handle indication and advise the other pilot unless directed otherwise by the Sample Operations Center.
- During preflight, the Captain should verify the Autothrottle switch position before the next phase of flight.
- The captain will verify any change in the Auxiliary Power Unit annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center.
- Refer to the related topic for additional sample context.

**NOTE:** The Standby Hydraulic switch position is expected to read within the sample range of 84 to 93 units during an extended ground delay. This text is fictional and exists only to give the prototype realistic volume and structure.

### 17.20.3 Nosewheel Steering Reset Guidance

The Primary Electrical Bus switch position that differs from the expected state requires the First Officer to cross-check the condition when the associated caution light remains illuminated. Values in this manual are invented and must not be used for any operational purpose. Refer to the related topic for additional sample context. During takeoff, the pilot monitoring should cross-check the Flap Position Indication selector position if the indication does not stabilize within the sample interval. Refer to the related topic for additional sample context. If the Cabin Pressure Controller is inoperative, continue taxi only after the pilot flying has reviewed the associated sample guidance.

The first officer will record any change in the Auxiliary Power Unit advisory and advise the other pilot if a discrepancy is observed. The Hydraulic System B status message that differs from the expected state requires the First Officer to select the condition when operating at a sample station without ground power. The Auxiliary Power Unit indication is expected to read within the sample range of 14 to 26 units during landing. During taxi, the First Officer should select the Landing Gear Indication advisory unless directed otherwise by the Sample Operations Center.

**NOTE:** The Probe Heat indication that differs from the expected state requires the relief pilot to announce the condition when conditions permit. If the Speedbrake Handle is inoperative, continue descent only after the First Officer has reviewed the associated sample guidance.

The Window Heat status message is expected to read within the sample range of 90 to 99 units during landing. This text is fictional and exists only to give the prototype realistic volume and structure. The Window Heat advisory that differs from the expected state requires the Captain to verify the condition unless directed otherwise by the Sample Operations Center. Both pilots will cross-check any change in the Flap Position Indication advisory and advise the other pilot if a discrepancy is observed. If the Autothrottle is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance.

The Cargo Smoke Detection annunciation that differs from the expected state requires the pilot flying to cross-check the condition when conditions permit. During landing, the pilot monitoring should confirm the Pack Temperature Control status message when the associated caution light remains illuminated. The relief pilot will confirm any change in the Auxiliary Power Unit indication and advise the other pilot when conditions permit. If the Standby Instruments is inoperative, continue climb only after the First Officer has reviewed the associated sample guidance.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Landing Gear Indication selector position | 59 units     | Normal                 |
| Transponder quantity display              | 93 units     | Normal                 |
| Bleed Air Supply quantity display         | 4 units      | Refer to related topic |
| Center Tank Pumps selector position       | 88 units     | Monitor                |
| Cabin Pressure Controller annunciation    | 88 units     | Advisory only          |
| Transponder selector position             | 70 units     | Advisory only          |
| Standby Hydraulic indication              | 61 units     | Normal                 |

This text is fictional and exists only to give the prototype realistic volume and structure. This text is fictional and exists only to give the prototype realistic volume and structure. During taxi, the relief pilot should monitor the Weather Radar indication before the next phase of flight. The Primary Electrical Bus annunciation that differs from the expected state requires the Captain to monitor the condition before the next phase of flight.

**CAUTION:** Both pilots will select any change in the Autothrottle quantity display and advise the other pilot if the indication does not stabilize within the sample interval.

**17.20.4 Cockpit Voice Recorder Indications**

The Weather Radar switch position is expected to read within the sample range of 6 to 18 units during parking. The Engine Anti-Ice switch position is expected to read within the sample range of 24 to 31 units during a maintenance-requested ground run. If the Autopilot Channel A is inoperative, continue engine start only after the pilot monitoring has reviewed the associated sample guidance.

If the Standby Instruments is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance. The Window Heat indication is expected to read within the sample range of 61 to 73 units during an extended ground delay. Values in this manual are invented and must not be used for any operational purpose. If the Cargo Smoke Detection is inoperative, continue engine start only after the relief pilot has reviewed the associated sample guidance.

**CAUTION:** During approach, the Captain should monitor the Auxiliary Power Unit status message unless directed otherwise by the Sample Operations Center. Refer to the related topic for additional sample context.

**CAUTION:** If the Thrust Reverser is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance.

The pilot flying will confirm any change in the Primary Electrical Bus annunciation and advise the other pilot once the checklist item is complete. If the Weather Radar is inoperative, continue a maintenance-requested ground run only after both pilots has reviewed the associated sample guidance. The Pack Temperature Control indication is expected to read within the sample range of 84 to 92 units during takeoff. The wording here is placeholder content shaped like a procedure, not a procedure.

**NOTE:** The Fuel Crossfeed quantity display is expected to read within the sample range of 41 to 44 units during preflight. The wording here is placeholder content shaped like a procedure, not a procedure.

**NOTE:** During parking, the pilot monitoring should monitor the Stall Warning quantity display once the checklist item is complete. This text is fictional and exists only to give the prototype realistic volume and structure.

**NOTE:** If the Autobrake Selector is inoperative, continue landing only after the Captain has reviewed the associated sample guidance.

**17.20.5 Auxiliary Power Unit Status Messages**

During a diversion, both pilots should cross-check the Engine Anti-Ice advisory once the checklist item is complete. During cruise, the First Officer should verify the Autopilot Channel A advisory if the indication does not stabilize within the sample interval. The Weather Radar status message that differs from the expected state requires the First Officer to brief the condition if the indication does not stabilize within the sample interval.

- During cruise, both pilots should announce the Standby Hydraulic selector position if a discrepancy is observed.
- The Nosewheel Steering quantity display that differs from the expected state requires the pilot flying to cross-check the condition when the associated caution light remains illuminated.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The Pack Temperature Control advisory is expected to read within the sample range of 29 to 35 units during parking.
- If the Oxygen Distribution is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance.
- The Autopilot Channel B advisory that differs from the expected state requires the pilot flying to record the condition when conditions permit.

The Ground Proximity Monitor annunciation is expected to read within the sample range of 36 to 46 units during preflight. The Oxygen Distribution indication is expected to read within the sample range of 95 to 106 units during approach. The wording here is placeholder content shaped like a procedure, not a procedure. Refer to the related topic for additional sample context. If the Autobrake Selector is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Pack Temperature Control switch position | 43 units     | Normal                 |
| Pack Temperature Control advisory        | 28 units     | Refer to related topic |

|                                             |          |                        |
|---------------------------------------------|----------|------------------------|
| Bleed Air Supply switch position            | 46 units | Monitor                |
| Transponder selector position               | 51 units | Normal                 |
| Cabin Pressure Controller selector position | 73 units | Refer to related topic |
| Landing Gear Indication annunciation        | 33 units | Advisory only          |

The Brake Temperature Monitor advisory is expected to read within the sample range of 33 to 38 units during landing. The Landing Gear Indication status message that differs from the expected state requires the pilot flying to cross-check the condition if a discrepancy is observed. If the Cockpit Voice Recorder is inoperative, continue a diversion only after the First Officer has reviewed the associated sample guidance.

The captain will monitor any change in the Autothrottle indication and advise the other pilot if a discrepancy is observed. During a diversion, the relief pilot should monitor the Fuel Crossfeed indication unless directed otherwise by the Sample Operations Center. If the Window Heat is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance. The pilot monitoring will record any change in the Hydraulic System A selector position and advise the other pilot once the checklist item is complete. If the Stall Warning is inoperative, continue a diversion only after the pilot monitoring has reviewed the associated sample guidance.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Fire Detection Loop advisory               | 47 units     | Monitor                |
| Nosewheel Steering selector position       | 3 units      | Monitor                |
| Fuel Crossfeed selector position           | 52 units     | Normal                 |
| Ground Proximity Monitor selector position | 97 units     | Monitor                |
| Primary Electrical Bus annunciation        | 40 units     | Refer to related topic |

The Cargo Smoke Detection quantity display is expected to read within the sample range of 64 to 72 units during takeoff. The wording here is placeholder content shaped like a procedure, not a procedure. Values in this manual are invented and must not be used for any operational purpose.

17.20.6 Autobrake Selector Overview

If the Weather Radar is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. Both pilots will verify any change in the Probe Heat annunciation and advise the other pilot once the checklist item is complete.

**CAUTION:** During an extended ground delay, the relief pilot should select the Transponder annunciation unless directed otherwise by the Sample Operations Center.

Both pilots will select any change in the Ground Proximity Monitor quantity display and advise the other pilot if the indication does not stabilize within the sample interval. During approach, the pilot flying should announce the Cargo Smoke Detection selector position when conditions permit. The Fire Detection Loop indication that differs from the expected state requires the pilot flying to record the condition when conditions permit. The captain will brief any change in the Fire Detection Loop advisory and advise the other pilot when conditions permit.

- Values in this manual are invented and must not be used for any operational purpose.
- The pilot flying will verify any change in the Autobrake Selector indication and advise the other pilot when operating at a sample station without ground power.
- The Standby Instruments quantity display that differs from the expected state requires both pilots to monitor the condition when the associated caution light remains illuminated.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- If the Speedbrake Handle is inoperative, continue preflight only after the relief pilot has reviewed the associated sample guidance.



- The Probe Heat indication is expected to read within the sample range of 15 to 21 units during cruise.

The relief pilot will record any change in the Cargo Smoke Detection status message and advise the other pilot when operating at a sample station without ground power. The wording here is placeholder content shaped like a procedure, not a procedure. The Fire Detection Loop switch position that differs from the expected state requires the relief pilot to monitor the condition when operating at a sample station without ground power.

- Values in this manual are invented and must not be used for any operational purpose.
- The first officer will monitor any change in the Standby Hydraulic advisory and advise the other pilot before the next phase of flight.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- If the Thrust Reverser is inoperative, continue descent only after both pilots has reviewed the associated sample guidance.
- The Standby Instruments switch position that differs from the expected state requires the relief pilot to brief the condition when the associated caution light remains illuminated.

### 17.20.7 Traffic Advisory Display Interfaces

Both pilots will record any change in the Fuel Crossfeed annunciation and advise the other pilot if a discrepancy is observed. The wording here is placeholder content shaped like a procedure, not a procedure. The Weather Radar status message is expected to read within the sample range of 28 to 34 units during engine start. The Pack Temperature Control selector position is expected to read within the sample range of 6 to 17 units during climb. The Ground Proximity Monitor switch position that differs from the expected state requires the pilot monitoring to announce the condition if a discrepancy is observed. The Fuel Crossfeed advisory that differs from the expected state requires the pilot flying to cross-check the condition before the next phase of flight.

The Center Tank Pumps indication is expected to read within the sample range of 6 to 12 units during approach. Values in this manual are invented and must not be used for any operational purpose. During cruise, the pilot monitoring should record the Auxiliary Power Unit indication if a discrepancy is observed. If the Stall Warning is inoperative, continue parking only after both pilots has reviewed the associated sample guidance. The relief pilot will monitor any change in the Wing Anti-Ice switch position and advise the other pilot when the associated caution light remains illuminated.

**CAUTION:** Refer to the related topic for additional sample context. If the Auxiliary Power Unit is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance.

- During approach, the First Officer should brief the Cabin Pressure Controller quantity display when operating at a sample station without ground power.
- The first officer will confirm any change in the Wing Anti-Ice quantity display and advise the other pilot before the next phase of flight.
- The Flight Management Computer advisory that differs from the expected state requires both pilots to announce the condition when the associated caution light remains illuminated.
- During approach, both pilots should confirm the Fire Detection Loop selector position if the indication does not stabilize within the sample interval.
- The Fire Detection Loop selector position is expected to read within the sample range of 46 to 49 units during approach.
- The first officer will monitor any change in the Probe Heat advisory and advise the other pilot before the next phase of flight.
- The Cargo Smoke Detection annunciation that differs from the expected state requires the Captain to announce the condition when conditions permit.

- During taxi, the pilot flying should brief the Transponder selector position when conditions permit.
- The Autobrake Selector quantity display is expected to read within the sample range of 91 to 98 units during climb.

**17.20.8 Standby Instruments Status Messages**

The Speedbrake Handle status message that differs from the expected state requires the pilot flying to monitor the condition before the next phase of flight. The Standby Instruments selector position that differs from the expected state requires the pilot flying to monitor the condition when the associated caution light remains illuminated. If the Landing Gear Indication is inoperative, continue takeoff only after both pilots has reviewed the associated sample guidance. During an extended ground delay, the relief pilot should verify the Probe Heat advisory if a discrepancy is observed. The pilot flying will select any change in the Thrust Reverser indication and advise the other pilot unless directed otherwise by the Sample Operations Center.

The wording here is placeholder content shaped like a procedure, not a procedure. The Window Heat annunciation is expected to read within the sample range of 69 to 74 units during an extended ground delay. If the Autopilot Channel B is inoperative, continue approach only after the relief pilot has reviewed the associated sample guidance. The Center Tank Pumps advisory that differs from the expected state requires the pilot flying to cross-check the condition when conditions permit.

**NOTE:** During cruise, the pilot flying should record the Oxygen Distribution advisory once the checklist item is complete. During engine start, the pilot monitoring should record the Thrust Reverser indication once the checklist item is complete.

**NOTE:** If the Landing Gear Indication is inoperative, continue taxi only after both pilots has reviewed the associated sample guidance. The captain will confirm any change in the Pack Temperature Control indication and advise the other pilot when operating at a sample station without ground power.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Cockpit Voice Recorder status message | 34 units     | Advisory only          |
| Autopilot Channel A advisory          | 80 units     | Refer to related topic |
| Hydraulic System A selector position  | 8 units      | Advisory only          |
| Flap Position Indication annunciation | 98 units     | Advisory only          |
| Transponder annunciation              | 64 units     | Refer to related topic |
| Weather Radar selector position       | 2 units      | Advisory only          |

**CAUTION:** During landing, the relief pilot should announce the Landing Gear Indication selector position when conditions permit.

If the Standby Hydraulic is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance. During descent, the pilot monitoring should record the Primary Electrical Bus indication if a discrepancy is observed. The captain will monitor any change in the Cargo Smoke Detection quantity display and advise the other pilot when operating at a sample station without ground power. The Fire Detection Loop status message that differs from the expected state requires the First Officer to verify the condition when operating at a sample station without ground power. The Oxygen Distribution annunciation is expected to read within the sample range of 4 to 10 units during a maintenance-requested ground run.

- This text is fictional and exists only to give the prototype realistic volume and structure.
- The Cargo Smoke Detection status message that differs from the expected state requires the pilot monitoring to monitor the condition if a discrepancy is observed.
- The Fuel Crossfeed selector position that differs from the expected state requires the relief pilot to monitor the condition when conditions permit.

- The Weather Radar selector position that differs from the expected state requires the Captain to record the condition unless directed otherwise by the Sample Operations Center.

**17.20.9 Flight Management Computer Reset Guidance**

The first officer will cross-check any change in the Speedbrake Handle advisory and advise the other pilot when operating at a sample station without ground power. The Speedbrake Handle selector position is expected to read within the sample range of 10 to 20 units during landing. The Fire Detection Loop selector position that differs from the expected state requires the pilot flying to monitor the condition before the next phase of flight.

**CAUTION:** The Oxygen Distribution advisory is expected to read within the sample range of 5 to 13 units during an extended ground delay. Both pilots will verify any change in the Autopilot Channel A status message and advise the other pilot if a discrepancy is observed.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Stall Warning indication                   | 6 units      | Advisory only          |
| Cargo Smoke Detection indication           | 83 units     | Normal                 |
| Center Tank Pumps indication               | 8 units      | Monitor                |
| Fuel Crossfeed quantity display            | 91 units     | Refer to related topic |
| Ground Proximity Monitor selector position | 47 units     | Refer to related topic |

Values in this manual are invented and must not be used for any operational purpose. During cruise, both pilots should record the Fire Detection Loop annunciation before the next phase of flight. If the Flight Management Computer is inoperative, continue engine start only after the pilot flying has reviewed the associated sample guidance. During a maintenance-requested ground run, the pilot monitoring should announce the Traffic Advisory Display annunciation if a discrepancy is observed.

- The Stall Warning status message is expected to read within the sample range of 85 to 91 units during climb.
- During preflight, the pilot flying should monitor the Autobrake Selector status message if a discrepancy is observed.
- The relief pilot will monitor any change in the Window Heat selector position and advise the other pilot before the next phase of flight.
- If the Cockpit Voice Recorder is inoperative, continue landing only after both pilots has reviewed the associated sample guidance.
- This text is fictional and exists only to give the prototype realistic volume and structure.

The captain will announce any change in the Autobrake Selector status message and advise the other pilot when operating at a sample station without ground power. The wording here is placeholder content shaped like a procedure, not a procedure. The Speedbrake Handle quantity display that differs from the expected state requires the First Officer to select the condition unless directed otherwise by the Sample Operations Center. The Weather Radar quantity display that differs from the expected state requires both pilots to monitor the condition if the indication does not stabilize within the sample interval.

| Condition                                   | Sample value | Remarks       |
|---------------------------------------------|--------------|---------------|
| Nosewheel Steering indication               | 89 units     | Advisory only |
| Engine Anti-Ice selector position           | 27 units     | Normal        |
| Thrust Reverser selector position           | 13 units     | Monitor       |
| Oxygen Distribution advisory                | 10 units     | Normal        |
| Flight Management Computer quantity display | 16 units     | Normal        |
| Autopilot Channel A advisory                | 14 units     | Monitor       |

**NOTE:** Values in this manual are invented and must not be used for any operational purpose.

**NOTE:** The Auxiliary Power Unit advisory is expected to read within the sample range of 93 to 96 units during approach.

### 17.20.10 Window Heat Crew Awareness

Refer to the related topic for additional sample context. During a diversion, the pilot monitoring should announce the Hydraulic System B annunciation when conditions permit. The Fuel Crossfeed quantity display that differs from the expected state requires the relief pilot to confirm the condition unless directed otherwise by the Sample Operations Center. The Window Heat status message is expected to read within the sample range of 69 to 72 units during parking. The pilot monitoring will record any change in the Autothrottle selector position and advise the other pilot unless directed otherwise by the Sample Operations Center. The captain will select any change in the Brake Temperature Monitor indication and advise the other pilot when operating at a sample station without ground power.

- During climb, the pilot monitoring should record the Thrust Reverser indication when operating at a sample station without ground power.
- Both pilots will select any change in the Hydraulic System A quantity display and advise the other pilot before the next phase of flight.
- If the Cockpit Voice Recorder is inoperative, continue descent only after the pilot flying has reviewed the associated sample guidance.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- The Brake Temperature Monitor quantity display that differs from the expected state requires the pilot flying to select the condition unless directed otherwise by the Sample Operations Center.
- Values in this manual are invented and must not be used for any operational purpose.

**CAUTION:** The Autopilot Channel B indication that differs from the expected state requires the pilot monitoring to record the condition when the associated caution light remains illuminated.

**CAUTION:** The captain will confirm any change in the Cockpit Voice Recorder selector position and advise the other pilot before the next phase of flight.

**CAUTION:** The Brake Temperature Monitor status message is expected to read within the sample range of 72 to 83 units during cruise. If the Landing Gear Indication is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance.

The Primary Electrical Bus quantity display is expected to read within the sample range of 9 to 14 units during climb. The Cargo Smoke Detection advisory is expected to read within the sample range of 41 to 48 units during a turnaround. If the Weather Radar is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance. Refer to the related topic for additional sample context. The wording here is placeholder content shaped like a procedure, not a procedure.

### 17.20.11 Primary Electrical Bus Overview

If the Nosewheel Steering is inoperative, continue descent only after the pilot flying has reviewed the associated sample guidance. The Cabin Pressure Controller annunciation is expected to read within the sample range of 73 to 76 units during an extended ground delay. The Brake Temperature Monitor advisory that differs from the expected state requires both pilots to cross-check the condition when operating at a sample station without ground power. The pilot flying will confirm any change in the Pack Temperature Control switch position and advise the other pilot when conditions permit. The captain will brief any change in the Hydraulic System B selector position and advise the other pilot before the next phase of flight.

**CAUTION:** During parking, the relief pilot should verify the Standby Hydraulic status message if a discrepancy is observed. The captain will select any change in the Autobrake Selector quantity display and advise the other pilot when the associated caution light remains illuminated.

If the Autopilot Channel B is inoperative, continue a turnaround only after the First Officer has reviewed the associated sample guidance. The relief pilot will verify any change in the Cabin Pressure Controller quantity display and advise the other pilot once the checklist item is complete. During cruise, the pilot flying should verify the Cockpit Voice Recorder quantity display when conditions permit. During climb, the Captain should brief the Auxiliary Power Unit annunciation if a discrepancy is observed.

**NOTE:** Values in this manual are invented and must not be used for any operational purpose.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Probe Heat indication                    | 99 units     | Normal                 |
| Primary Electrical Bus selector position | 48 units     | Refer to related topic |
| Window Heat indication                   | 76 units     | Advisory only          |
| Landing Gear Indication indication       | 14 units     | Refer to related topic |

**CAUTION:** If the Window Heat is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance. Refer to the related topic for additional sample context.

**17.20.12 Cockpit Voice Recorder Overview**

If the Stall Warning is inoperative, continue approach only after both pilots has reviewed the associated sample guidance. During approach, the relief pilot should brief the Ground Proximity Monitor status message if the indication does not stabilize within the sample interval. The Traffic Advisory Display annunciation is expected to read within the sample range of 75 to 83 units during approach. The captain will cross-check any change in the Bleed Air Supply indication and advise the other pilot once the checklist item is complete.

The Pack Temperature Control quantity display is expected to read within the sample range of 83 to 90 units during engine start. The Center Tank Pumps advisory that differs from the expected state requires the Captain to record the condition if the indication does not stabilize within the sample interval. The first officer will monitor any change in the Pack Temperature Control indication and advise the other pilot once the checklist item is complete. The Bleed Air Supply selector position is expected to read within the sample range of 45 to 51 units during preflight. The first officer will verify any change in the Landing Gear Indication indication and advise the other pilot unless directed otherwise by the Sample Operations Center.

The Landing Gear Indication annunciation that differs from the expected state requires the pilot monitoring to announce the condition once the checklist item is complete. The Flight Management Computer switch position is expected to read within the sample range of 86 to 92 units during approach. The Stall Warning advisory that differs from the expected state requires the pilot flying to verify the condition when operating at a sample station without ground power.

The relief pilot will record any change in the Cockpit Voice Recorder switch position and advise the other pilot when the associated caution light remains illuminated. During preflight, the pilot monitoring should confirm the Probe Heat switch position once the checklist item is complete. The Autothrottle advisory is expected to read within the sample range of 33 to 42 units during engine start. Both pilots will announce any change in the Transponder switch position and advise the other pilot when the associated caution light remains illuminated. During climb, the pilot monitoring should brief the Weather Radar status message unless directed otherwise by the Sample Operations Center. The Traffic Advisory Display quantity display is expected to read within the sample range of 76 to 88 units during a maintenance-requested ground run.

Both pilots will record any change in the Oxygen Distribution annunciation and advise the other pilot before the next phase of flight. During an extended ground delay, the pilot flying should confirm the Standby Hydraulic quantity display when operating at a sample station without ground power. Both pilots will cross-check any change in the

Autopilot Channel B advisory and advise the other pilot if the indication does not stabilize within the sample interval.

17.20.13 *Nosewheel Steering Test*

If the Standby Instruments is inoperative, continue descent only after the First Officer has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. The Cargo Smoke Detection switch position is expected to read within the sample range of 26 to 38 units during taxi. The wording here is placeholder content shaped like a procedure, not a procedure. The Nosewheel Steering quantity display is expected to read within the sample range of 28 to 37 units during landing. The Engine Anti-Ice advisory is expected to read within the sample range of 34 to 46 units during a maintenance-requested ground run.

**CAUTION:** The captain will confirm any change in the Standby Instruments annunciation and advise the other pilot when conditions permit.

- The Stall Warning quantity display is expected to read within the sample range of 21 to 32 units during preflight.
- The Hydraulic System A status message is expected to read within the sample range of 80 to 85 units during a turnaround.
- The Nosewheel Steering status message is expected to read within the sample range of 90 to 94 units during takeoff.
- If the Thrust Reverser is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance.
- Values in this manual are invented and must not be used for any operational purpose.
- The Center Tank Pumps switch position that differs from the expected state requires the pilot monitoring to verify the condition when operating at a sample station without ground power.

The captain will brief any change in the Bleed Air Supply annunciation and advise the other pilot if the indication does not stabilize within the sample interval. The Primary Electrical Bus advisory is expected to read within the sample range of 98 to 108 units during engine start. This text is fictional and exists only to give the prototype realistic volume and structure. The Cabin Pressure Controller indication that differs from the expected state requires the relief pilot to confirm the condition when the associated caution light remains illuminated. During cruise, the pilot flying should confirm the Standby Instruments indication unless directed otherwise by the Sample Operations Center.

17.20.14 *Wing Anti-Ice Interfaces*

Refer to the related topic for additional sample context. During cruise, the relief pilot should cross-check the Autopilot Channel A indication once the checklist item is complete. The Window Heat selector position is expected to read within the sample range of 44 to 47 units during preflight. During takeoff, the Captain should brief the Cockpit Voice Recorder status message before the next phase of flight.

**CAUTION:** The Autopilot Channel B status message that differs from the expected state requires the pilot flying to confirm the condition before the next phase of flight.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Center Tank Pumps advisory              | 50 units     | Normal                 |
| Hydraulic System A status message       | 10 units     | Refer to related topic |
| Ground Proximity Monitor status message | 23 units     | Normal                 |

**CAUTION:** The pilot monitoring will cross-check any change in the Cargo Smoke Detection annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center. The wording here is placeholder content shaped like a procedure, not a procedure.



Refer to the related topic for additional sample context. During a maintenance-requested ground run, both pilots should select the Weather Radar annunciation unless directed otherwise by the Sample Operations Center. If the Thrust Reverser is inoperative, continue parking only after the relief pilot has reviewed the associated sample guidance.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Brake Temperature Monitor annunciation  | 70 units     | Monitor                |
| Autothrottle selector position          | 77 units     | Normal                 |
| Cockpit Voice Recorder indication       | 75 units     | Refer to related topic |
| Cockpit Voice Recorder quantity display | 78 units     | Normal                 |
| Oxygen Distribution switch position     | 49 units     | Advisory only          |
| Engine Anti-Ice switch position         | 2 units      | Normal                 |
| Thrust Reverser status message          | 67 units     | Refer to related topic |

### 17.20.15 Bleed Air Supply Limits Display

This text is fictional and exists only to give the prototype realistic volume and structure. During takeoff, both pilots should monitor the Stall Warning status message if a discrepancy is observed. The Standby Hydraulic indication is expected to read within the sample range of 28 to 35 units during approach.

- The Autopilot Channel B switch position is expected to read within the sample range of 71 to 81 units during climb.
- The pilot flying will brief any change in the Cockpit Voice Recorder status message and advise the other pilot when operating at a sample station without ground power.
- The Primary Electrical Bus annunciation that differs from the expected state requires the pilot flying to confirm the condition if the indication does not stabilize within the sample interval.
- The Autopilot Channel B quantity display that differs from the expected state requires the pilot monitoring to verify the condition if a discrepancy is observed.
- Both pilots will select any change in the Autopilot Channel A selector position and advise the other pilot before the next phase of flight.

The pilot flying will verify any change in the Ground Proximity Monitor quantity display and advise the other pilot if a discrepancy is observed. During parking, the pilot flying should record the Window Heat selector position when conditions permit. If the Brake Temperature Monitor is inoperative, continue engine start only after the Captain has reviewed the associated sample guidance.

| Condition                            | Sample value | Remarks                |
|--------------------------------------|--------------|------------------------|
| Center Tank Pumps quantity display   | 56 units     | Normal                 |
| Auxiliary Power Unit switch position | 60 units     | Normal                 |
| Standby Instruments status message   | 69 units     | Refer to related topic |
| Autopilot Channel B advisory         | 8 units      | Normal                 |
| Weather Radar selector position      | 83 units     | Monitor                |
| Fire Detection Loop indication       | 36 units     | Monitor                |

The Hydraulic System A annunciation is expected to read within the sample range of 6 to 15 units during an extended ground delay. The first officer will cross-check any change in the Bleed Air Supply switch position and advise the other pilot when the associated caution light remains illuminated. During a maintenance-requested ground run, the pilot monitoring should brief the Window Heat advisory if the indication does not stabilize within the sample interval.

The Cargo Smoke Detection quantity display is expected to read within the sample range of 61 to 68 units during taxi. If the Transponder is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance. Refer to the related topic for additional sample context. The Nosewheel Steering advisory that differs from the expected state requires the First Officer to announce the condition unless directed otherwise by the Sample Operations Center. The Pack Temperature Control annunciation that differs from the expected state requires the relief pilot to verify the condition when operating at a sample station without ground power.

- If the Center Tank Pumps is inoperative, continue descent only after both pilots has reviewed the associated sample guidance.
- The Stall Warning selector position that differs from the expected state requires the pilot monitoring to confirm the condition when operating at a sample station without ground power.
- During parking, the First Officer should confirm the Flap Position Indication status message if the indication does not stabilize within the sample interval.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Window Heat switch position              | 63 units     | Advisory only          |
| Autothrottle status message              | 14 units     | Monitor                |
| Autopilot Channel A advisory             | 81 units     | Advisory only          |
| Flap Position Indication status message  | 23 units     | Monitor                |
| Speedbrake Handle switch position        | 99 units     | Advisory only          |
| Ground Proximity Monitor switch position | 32 units     | Refer to related topic |

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Oxygen Distribution quantity display  | 77 units     | Advisory only          |
| Hydraulic System B indication         | 43 units     | Refer to related topic |
| Traffic Advisory Display annunciation | 31 units     | Refer to related topic |

### 17.20.16 Window Heat Power Sources

The Engine Anti-Ice indication that differs from the expected state requires the pilot flying to monitor the condition unless directed otherwise by the Sample Operations Center. The first officer will record any change in the Traffic Advisory Display quantity display and advise the other pilot if the indication does not stabilize within the sample interval. The relief pilot will confirm any change in the Fire Detection Loop selector position and advise the other pilot unless directed otherwise by the Sample Operations Center.

The relief pilot will select any change in the Transponder switch position and advise the other pilot when operating at a sample station without ground power. During a turnaround, the First Officer should verify the Standby Instruments switch position when conditions permit. Values in this manual are invented and must not be used for any operational purpose.

The Thrust Reverser status message is expected to read within the sample range of 51 to 56 units during a diversion. The relief pilot will cross-check any change in the Ground Proximity Monitor status message and advise the other pilot when the associated caution light remains illuminated. The captain will brief any change in the Hydraulic System B switch position and advise the other pilot if the indication does not stabilize within the sample interval. If the Primary Electrical Bus is inoperative, continue a maintenance-requested ground run only after the Captain has reviewed the associated sample guidance. During a diversion, the Captain should monitor the Standby Hydraulic quantity display before the next phase of flight.

**NOTE:** During landing, the First Officer should verify the Speedbrake Handle annunciation before the next phase of flight.

The Pack Temperature Control selector position is expected to read within the sample range of 73 to 77 units during a diversion. During parking, the pilot flying should announce the Stall Warning advisory if the indication does not

stabilize within the sample interval. During parking, the pilot flying should select the Standby Instruments quantity display before the next phase of flight. The pilot monitoring will record any change in the Traffic Advisory Display indication and advise the other pilot if a discrepancy is observed.

The pilot monitoring will select any change in the Autopilot Channel B indication and advise the other pilot when conditions permit. The Speedbrake Handle status message is expected to read within the sample range of 80 to 85 units during descent. During a turnaround, the pilot flying should verify the Auxiliary Power Unit advisory if the indication does not stabilize within the sample interval. The Autobrake Selector switch position that differs from the expected state requires the pilot flying to monitor the condition unless directed otherwise by the Sample Operations Center.

**CAUTION:** During takeoff, the Captain should verify the Thrust Reverser quantity display unless directed otherwise by the Sample Operations Center. During an extended ground delay, both pilots should announce the Standby Instruments quantity display when operating at a sample station without ground power.

# Chapter 18 Systems: Warning Systems

## 18.10 Description

### 18.10.1 Autothrottle Power Sources

During climb, the pilot flying should monitor the Nosewheel Steering quantity display unless directed otherwise by the Sample Operations Center. Refer to the related topic for additional sample context. If the Stall Warning is inoperative, continue engine start only after the pilot monitoring has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure.

**CAUTION:** If the Probe Heat is inoperative, continue climb only after the First Officer has reviewed the associated sample guidance. During cruise, the Captain should brief the Cargo Smoke Detection quantity display once the checklist item is complete.

**CAUTION:** The Traffic Advisory Display switch position is expected to read within the sample range of 28 to 36 units during a diversion.

**NOTE:** The Ground Proximity Monitor indication is expected to read within the sample range of 59 to 63 units during an extended ground delay.

The Standby Hydraulic quantity display that differs from the expected state requires the pilot flying to brief the condition when operating at a sample station without ground power. If the Brake Temperature Monitor is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance. If the Bleed Air Supply is inoperative, continue a maintenance-requested ground run only after both pilots has reviewed the associated sample guidance.

**CAUTION:** During climb, the pilot monitoring should brief the Weather Radar quantity display when the associated caution light remains illuminated.

### 18.10.2 Probe Heat Indications

The Standby Instruments indication that differs from the expected state requires the pilot monitoring to cross-check the condition if the indication does not stabilize within the sample interval. If the Autopilot Channel A is inoperative, continue preflight only after the pilot monitoring has reviewed the associated sample guidance. If the Thrust Reverser is inoperative, continue landing only after both pilots has reviewed the associated sample guidance. If the Oxygen Distribution is inoperative, continue descent only after the Captain has reviewed the associated sample guidance. If the Primary Electrical Bus is inoperative, continue engine start only after the pilot monitoring has reviewed the associated sample guidance.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Speedbrake Handle indication               | 46 units     | Advisory only          |
| Hydraulic System B selector position       | 35 units     | Refer to related topic |
| Flap Position Indication selector position | 65 units     | Normal                 |
| Center Tank Pumps switch position          | 72 units     | Refer to related topic |
| Autopilot Channel B quantity display       | 69 units     | Monitor                |

The Cabin Pressure Controller advisory is expected to read within the sample range of 96 to 101 units during engine start. During engine start, the Captain should select the Pack Temperature Control quantity display unless directed otherwise by the Sample Operations Center. The Bleed Air Supply selector position that differs from the expected state requires the pilot flying to select the condition before the next phase of flight.

**NOTE:** If the Traffic Advisory Display is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance. The first officer will brief any change in the Cabin Pressure

Controller status message and advise the other pilot if the indication does not stabilize within the sample interval.

During takeoff, the First Officer should monitor the Transponder quantity display unless directed otherwise by the Sample Operations Center. If the Engine Anti-Ice is inoperative, continue taxi only after both pilots has reviewed the associated sample guidance. The Pack Temperature Control status message is expected to read within the sample range of 89 to 94 units during a maintenance-requested ground run. If the Wing Anti-Ice is inoperative, continue taxi only after both pilots has reviewed the associated sample guidance. The first officer will brief any change in the Window Heat quantity display and advise the other pilot once the checklist item is complete. The Autopilot Channel B quantity display is expected to read within the sample range of 6 to 10 units during takeoff.

| Condition                               | Sample value | Remarks       |
|-----------------------------------------|--------------|---------------|
| Probe Heat switch position              | 64 units     | Advisory only |
| Window Heat quantity display            | 10 units     | Monitor       |
| Cockpit Voice Recorder quantity display | 28 units     | Monitor       |
| Hydraulic System A annunciation         | 94 units     | Monitor       |
| Cargo Smoke Detection annunciation      | 27 units     | Advisory only |
| Nosewheel Steering quantity display     | 85 units     | Normal        |

**18.10.3 Traffic Advisory Display Normal Operation**

If the Cabin Pressure Controller is inoperative, continue taxi only after the First Officer has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. Both pilots will select any change in the Nosewheel Steering quantity display and advise the other pilot when the associated caution light remains illuminated.

**NOTE:** Refer to the related topic for additional sample context. The pilot monitoring will monitor any change in the Landing Gear Indication annunciation and advise the other pilot before the next phase of flight.

**NOTE:** The Center Tank Pumps switch position is expected to read within the sample range of 88 to 92 units during an extended ground delay.

- The pilot flying will announce any change in the Bleed Air Supply switch position and advise the other pilot before the next phase of flight.
- The Transponder annunciation that differs from the expected state requires the pilot monitoring to select the condition before the next phase of flight.
- The Hydraulic System A switch position is expected to read within the sample range of 23 to 35 units during taxi.
- If the Window Heat is inoperative, continue landing only after the relief pilot has reviewed the associated sample guidance.

The Engine Anti-Ice status message is expected to read within the sample range of 27 to 35 units during parking. If the Thrust Reverser is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance. During taxi, the relief pilot should select the Hydraulic System B quantity display when the associated caution light remains illuminated. Values in this manual are invented and must not be used for any operational purpose. The Standby Hydraulic annunciation is expected to read within the sample range of 20 to 30 units during descent. The wording here is placeholder content shaped like a procedure, not a procedure.

- Refer to the related topic for additional sample context.
- If the Autothrottle is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance.
- If the Nosewheel Steering is inoperative, continue a maintenance-requested ground run only after both pilots has reviewed the associated sample guidance.

- The wording here is placeholder content shaped like a procedure, not a procedure.
- During taxi, the pilot monitoring should monitor the Flap Position Indication selector position if the indication does not stabilize within the sample interval.
- The relief pilot will verify any change in the Transponder annunciation and advise the other pilot if the indication does not stabilize within the sample interval.

**NOTE:** The Probe Heat quantity display is expected to read within the sample range of 40 to 43 units during taxi.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Bleed Air Supply advisory                | 12 units     | Normal                 |
| Autothrottle indication                  | 23 units     | Refer to related topic |
| Brake Temperature Monitor status message | 20 units     | Monitor                |

**18.10.4 Wing Anti-Ice Status Messages**

The Traffic Advisory Display quantity display is expected to read within the sample range of 37 to 40 units during a turnaround. The Autopilot Channel B switch position is expected to read within the sample range of 9 to 18 units during a maintenance-requested ground run. During approach, the pilot flying should select the Cabin Pressure Controller annunciation when the associated caution light remains illuminated. The relief pilot will select any change in the Transponder advisory and advise the other pilot unless directed otherwise by the Sample Operations Center.

If the Bleed Air Supply is inoperative, continue a turnaround only after both pilots has reviewed the associated sample guidance. The pilot monitoring will cross-check any change in the Cabin Pressure Controller quantity display and advise the other pilot when conditions permit. During parking, the pilot flying should cross-check the Flap Position Indication indication when conditions permit. The captain will select any change in the Speedbrake Handle selector position and advise the other pilot when the associated caution light remains illuminated.

The wording here is placeholder content shaped like a procedure, not a procedure. Both pilots will verify any change in the Autopilot Channel B quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center. If the Stall Warning is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance. See 08.30.7 Window Heat Interfaces.

**CAUTION:** The Weather Radar indication that differs from the expected state requires both pilots to select the condition when operating at a sample station without ground power. During a diversion, the Captain should verify the Fire Detection Loop quantity display when operating at a sample station without ground power.

- Refer to the related topic for additional sample context.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The Pack Temperature Control indication that differs from the expected state requires the First Officer to verify the condition when the associated caution light remains illuminated.
- Both pilots will verify any change in the Cargo Smoke Detection advisory and advise the other pilot when conditions permit.
- Both pilots will monitor any change in the Autopilot Channel B annunciation and advise the other pilot when conditions permit.
- If the Flight Management Computer is inoperative, continue landing only after both pilots has reviewed the associated sample guidance.

**18.10.5 New Sample Topic: Probe Heat**

This text is fictional and exists only to give the prototype realistic volume and structure. During taxi, the pilot flying should select the Transponder indication once the checklist item is complete. If the Thrust Reverser is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance. If the Hydraulic System A is



inoperative, continue a diversion only after both pilots has reviewed the associated sample guidance.

**NOTE:** The Thrust Reverser switch position is expected to read within the sample range of 14 to 20 units during taxi.

| Condition                                   | Sample value | Remarks                |
|---------------------------------------------|--------------|------------------------|
| Bleed Air Supply advisory                   | 33 units     | Advisory only          |
| Standby Instruments indication              | 95 units     | Normal                 |
| Pack Temperature Control annunciation       | 2 units      | Advisory only          |
| Cockpit Voice Recorder switch position      | 18 units     | Normal                 |
| Primary Electrical Bus annunciation         | 93 units     | Refer to related topic |
| Cabin Pressure Controller selector position | 38 units     | Monitor                |

This text is fictional and exists only to give the prototype realistic volume and structure. During preflight, the pilot flying should verify the Traffic Advisory Display switch position when the associated caution light remains illuminated. This text is fictional and exists only to give the prototype realistic volume and structure. The Primary Electrical Bus switch position that differs from the expected state requires the pilot monitoring to announce the condition when operating at a sample station without ground power.

- The Cabin Pressure Controller annunciation is expected to read within the sample range of 51 to 61 units during taxi.
- If the Autothrottle is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance.
- Values in this manual are invented and must not be used for any operational purpose.
- If the Standby Hydraulic is inoperative, continue engine start only after the pilot flying has reviewed the associated sample guidance.
- During descent, the pilot monitoring should monitor the Bleed Air Supply indication unless directed otherwise by the Sample Operations Center.

**18.10.6 Brake Temperature Monitor Overview**

The wording here is placeholder content shaped like a procedure, not a procedure. The Flap Position Indication indication is expected to read within the sample range of 22 to 31 units during parking. The Ground Proximity Monitor indication that differs from the expected state requires the Captain to verify the condition if a discrepancy is observed. The first officer will brief any change in the Thrust Reverser annunciation and advise the other pilot if a discrepancy is observed.

**CAUTION:** If the Stall Warning is inoperative, continue engine start only after the Captain has reviewed the associated sample guidance. During a diversion, the First Officer should cross-check the Nosewheel Steering indication when conditions permit.

**CAUTION:** Values in this manual are invented and must not be used for any operational purpose.

Refer to the related topic for additional sample context. The Center Tank Pumps advisory that differs from the expected state requires the relief pilot to record the condition when the associated caution light remains illuminated. The Traffic Advisory Display status message that differs from the expected state requires the relief pilot to verify the condition when operating at a sample station without ground power. Both pilots will cross-check any change in the Hydraulic System B advisory and advise the other pilot once the checklist item is complete.

The Thrust Reverser indication that differs from the expected state requires the relief pilot to select the condition when operating at a sample station without ground power. During cruise, the pilot monitoring should monitor the Fuel Crossfeed switch position when conditions permit. The Pack Temperature Control indication is expected to read within the sample range of 81 to 84 units during landing. The relief pilot will cross-check any change in the Standby

Hydraulic indication and advise the other pilot if the indication does not stabilize within the sample interval. During cruise, both pilots should record the Thrust Reverser annunciation when conditions permit. The captain will brief any change in the Flap Position Indication selector position and advise the other pilot if the indication does not stabilize within the sample interval.

### **18.10.7 Bleed Air Supply Reset Guidance**

The Flap Position Indication annunciation that differs from the expected state requires the Captain to monitor the condition before the next phase of flight. If the Nosewheel Steering is inoperative, continue cruise only after both pilots has reviewed the associated sample guidance. The pilot flying will brief any change in the Autothrottle advisory and advise the other pilot when conditions permit.

During a diversion, the pilot monitoring should confirm the Pack Temperature Control indication if a discrepancy is observed. The wording here is placeholder content shaped like a procedure, not a procedure. The first officer will verify any change in the Flight Management Computer switch position and advise the other pilot when the associated caution light remains illuminated. Values in this manual are invented and must not be used for any operational purpose. The Landing Gear Indication indication that differs from the expected state requires the First Officer to brief the condition when operating at a sample station without ground power.

- If the Ground Proximity Monitor is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance.
- Both pilots will select any change in the Standby Instruments quantity display and advise the other pilot once the checklist item is complete.
- The Window Heat selector position that differs from the expected state requires the relief pilot to cross-check the condition when operating at a sample station without ground power.
- During cruise, both pilots should select the Wing Anti-Ice quantity display when operating at a sample station without ground power.
- If the Autobrake Selector is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- The Flight Management Computer annunciation that differs from the expected state requires the relief pilot to monitor the condition unless directed otherwise by the Sample Operations Center.
- The Standby Hydraulic status message is expected to read within the sample range of 70 to 74 units during taxi.
- If the Transponder is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance.
- During cruise, the pilot monitoring should record the Fire Detection Loop annunciation if the indication does not stabilize within the sample interval.
- The Standby Hydraulic quantity display is expected to read within the sample range of 37 to 42 units during cruise.
- This text is fictional and exists only to give the prototype realistic volume and structure.

If the Center Tank Pumps is inoperative, continue engine start only after the Captain has reviewed the associated sample guidance. The Brake Temperature Monitor selector position that differs from the expected state requires the pilot monitoring to monitor the condition once the checklist item is complete. The Fuel Crossfeed advisory is expected to read within the sample range of 89 to 99 units during a maintenance-requested ground run. The Autopilot Channel A selector position is expected to read within the sample range of 15 to 20 units during descent. The Brake Temperature Monitor advisory that differs from the expected state requires the pilot flying to announce the condition before the next phase of flight. The first officer will monitor any change in the Traffic Advisory Display indication and advise the other pilot when the associated caution light remains illuminated.

**CAUTION:** The Ground Proximity Monitor selector position is expected to read within the sample range of 62 to 71 units during descent. The Cockpit Voice Recorder quantity display that differs from the expected state requires the Captain to announce the condition if a discrepancy is observed.

### 18.10.8 Flap Position Indication Reset Guidance

During an extended ground delay, the relief pilot should cross-check the Nosewheel Steering selector position when conditions permit. The Autobrake Selector selector position is expected to read within the sample range of 54 to 60 units during descent. If the Engine Anti-Ice is inoperative, continue landing only after the relief pilot has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. If the Hydraulic System B is inoperative, continue preflight only after both pilots has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose.

- The Thrust Reverser quantity display is expected to read within the sample range of 28 to 31 units during engine start.
- During landing, the Captain should confirm the Center Tank Pumps quantity display when operating at a sample station without ground power.
- The Fuel Crossfeed selector position that differs from the expected state requires the Captain to select the condition if the indication does not stabilize within the sample interval.

**CAUTION:** The Autopilot Channel A advisory that differs from the expected state requires the pilot monitoring to cross-check the condition once the checklist item is complete. The Speedbrake Handle status message is expected to read within the sample range of 84 to 94 units during landing.

The Cockpit Voice Recorder indication is expected to read within the sample range of 59 to 71 units during cruise. The first officer will confirm any change in the Nosewheel Steering selector position and advise the other pilot once the checklist item is complete. Both pilots will brief any change in the Standby Instruments annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center. If the Cockpit Voice Recorder is inoperative, continue a diversion only after the pilot monitoring has reviewed the associated sample guidance.

The first officer will select any change in the Fuel Crossfeed switch position and advise the other pilot when the associated caution light remains illuminated. The Center Tank Pumps annunciation is expected to read within the sample range of 70 to 82 units during climb. The first officer will record any change in the Window Heat annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center. The Cockpit Voice Recorder advisory is expected to read within the sample range of 21 to 33 units during an extended ground delay.

The Bleed Air Supply advisory is expected to read within the sample range of 26 to 30 units during a diversion. The captain will verify any change in the Fuel Crossfeed selector position and advise the other pilot unless directed otherwise by the Sample Operations Center. If the Weather Radar is inoperative, continue landing only after both pilots has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure.

### 18.10.9 Standby Instruments Limits Display

If the Oxygen Distribution is inoperative, continue a diversion only after both pilots has reviewed the associated sample guidance. The Pack Temperature Control annunciation that differs from the expected state requires the Captain to select the condition before the next phase of flight. The pilot monitoring will confirm any change in the Window Heat indication and advise the other pilot if the indication does not stabilize within the sample interval. The pilot flying will record any change in the Primary Electrical Bus advisory and advise the other pilot once the checklist item is complete. The Primary Electrical Bus quantity display is expected to read within the sample range of 87 to 97 units during landing. The Brake Temperature Monitor switch position is expected to read within the sample range of 23 to 31 units during a diversion.

During a diversion, the relief pilot should select the Autopilot Channel A indication if a discrepancy is observed. The first officer will cross-check any change in the Window Heat annunciation and advise the other pilot when conditions

permit. During a diversion, the Captain should record the Hydraulic System A status message once the checklist item is complete. The Probe Heat indication is expected to read within the sample range of 93 to 100 units during a diversion.

**NOTE:** If the Standby Hydraulic is inoperative, continue an extended ground delay only after the pilot flying has reviewed the associated sample guidance. The relief pilot will cross-check any change in the Pack Temperature Control quantity display and advise the other pilot when the associated caution light remains illuminated.

**NOTE:** The Fuel Crossfeed switch position that differs from the expected state requires the relief pilot to confirm the condition before the next phase of flight.

During an extended ground delay, the relief pilot should confirm the Ground Proximity Monitor quantity display before the next phase of flight. The relief pilot will confirm any change in the Center Tank Pumps advisory and advise the other pilot if the indication does not stabilize within the sample interval. The Engine Anti-Ice selector position that differs from the expected state requires the pilot monitoring to select the condition once the checklist item is complete. During preflight, the pilot monitoring should cross-check the Hydraulic System B indication when operating at a sample station without ground power. The Autopilot Channel A indication that differs from the expected state requires the pilot monitoring to verify the condition unless directed otherwise by the Sample Operations Center.

During a diversion, the pilot monitoring should brief the Cockpit Voice Recorder selector position before the next phase of flight. During a diversion, both pilots should record the Hydraulic System A quantity display when the associated caution light remains illuminated. The Oxygen Distribution status message is expected to read within the sample range of 49 to 61 units during taxi.

If the Fire Detection Loop is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance. During descent, the pilot monitoring should announce the Cockpit Voice Recorder status message when the associated caution light remains illuminated. During takeoff, the Captain should brief the Transponder selector position when the associated caution light remains illuminated. Refer to the related topic for additional sample context. During approach, the relief pilot should announce the Hydraulic System B status message if the indication does not stabilize within the sample interval.

**CAUTION:** The Bleed Air Supply switch position is expected to read within the sample range of 31 to 42 units during engine start. This text is fictional and exists only to give the prototype realistic volume and structure.

If the Oxygen Distribution is inoperative, continue cruise only after the Captain has reviewed the associated sample guidance. The Transponder quantity display is expected to read within the sample range of 89 to 98 units during descent. If the Standby Hydraulic is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance. If the Landing Gear Indication is inoperative, continue a maintenance-requested ground run only after the pilot monitoring has reviewed the associated sample guidance. If the Stall Warning is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance. See 14.10.13 Ground Proximity Monitor Normal Operation.

### **18.10.10 Autopilot Channel A Power Sources**

The Standby Hydraulic advisory that differs from the expected state requires the pilot flying to monitor the condition when operating at a sample station without ground power. The pilot monitoring will announce any change in the Cargo Smoke Detection advisory and advise the other pilot if the indication does not stabilize within the sample interval. The Fire Detection Loop indication is expected to read within the sample range of 84 to 92 units during engine start. The Ground Proximity Monitor annunciation is expected to read within the sample range of 58 to 65 units during approach. If the Weather Radar is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance. The relief pilot will confirm any change in the Ground Proximity Monitor advisory and advise the other pilot if the indication does not stabilize within the sample interval.

If the Cockpit Voice Recorder is inoperative, continue an extended ground delay only after the pilot flying has reviewed the associated sample guidance. If the Cockpit Voice Recorder is inoperative, continue descent only after the First Officer has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure.

- The Flight Management Computer switch position is expected to read within the sample range of 64 to 68 units during preflight.
- The Stall Warning switch position that differs from the expected state requires the relief pilot to select the condition when conditions permit.
- The pilot flying will select any change in the Wing Anti-Ice quantity display and advise the other pilot before the next phase of flight.
- If the Traffic Advisory Display is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance.
- The Hydraulic System B advisory is expected to read within the sample range of 84 to 96 units during cruise.

If the Standby Instruments is inoperative, continue landing only after the First Officer has reviewed the associated sample guidance. The Standby Hydraulic selector position is expected to read within the sample range of 58 to 64 units during descent. During a diversion, the First Officer should monitor the Hydraulic System B advisory before the next phase of flight. The Pack Temperature Control status message is expected to read within the sample range of 74 to 80 units during preflight. The Autopilot Channel A selector position is expected to read within the sample range of 48 to 56 units during takeoff.

The pilot flying will announce any change in the Cargo Smoke Detection selector position and advise the other pilot when operating at a sample station without ground power. The Cargo Smoke Detection annunciation that differs from the expected state requires the relief pilot to announce the condition if a discrepancy is observed. The Hydraulic System B selector position is expected to read within the sample range of 79 to 91 units during a turnaround.

**NOTE:** If the Transponder is inoperative, continue parking only after the Captain has reviewed the associated sample guidance.

**NOTE:** The Primary Electrical Bus advisory that differs from the expected state requires the relief pilot to cross-check the condition unless directed otherwise by the Sample Operations Center. The first officer will confirm any change in the Oxygen Distribution quantity display and advise the other pilot if the indication does not stabilize within the sample interval.

If the Window Heat is inoperative, continue approach only after the relief pilot has reviewed the associated sample guidance. If the Window Heat is inoperative, continue parking only after both pilots has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure.

**18.10.11 Thrust Reverser Limits Display**

During a diversion, both pilots should announce the Ground Proximity Monitor indication unless directed otherwise by the Sample Operations Center. The Hydraulic System B annunciation is expected to read within the sample range of 83 to 89 units during landing. Refer to the related topic for additional sample context.

The Autothrottle indication that differs from the expected state requires the Captain to monitor the condition when conditions permit. If the Ground Proximity Monitor is inoperative, continue a maintenance-requested ground run only after the pilot monitoring has reviewed the associated sample guidance. The Hydraulic System A quantity display that differs from the expected state requires the pilot monitoring to record the condition when operating at a sample station without ground power. The Oxygen Distribution switch position is expected to read within the sample range of 80 to 87 units during parking.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Thrust Reverser indication            | 45 units     | Normal                 |
| Auxiliary Power Unit annunciation     | 46 units     | Refer to related topic |
| Primary Electrical Bus status message | 72 units     | Monitor                |
| Transponder indication                | 43 units     | Monitor                |
| Oxygen Distribution status message    | 97 units     | Normal                 |

|                                      |         |                        |
|--------------------------------------|---------|------------------------|
| Oxygen Distribution quantity display | 8 units | Refer to related topic |
|--------------------------------------|---------|------------------------|

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Pack Temperature Control selector position | 31 units     | Advisory only          |
| Oxygen Distribution indication             | 75 units     | Refer to related topic |
| Autopilot Channel B annunciation           | 43 units     | Refer to related topic |
| Cabin Pressure Controller indication       | 61 units     | Normal                 |
| Traffic Advisory Display advisory          | 90 units     | Monitor                |
| Ground Proximity Monitor annunciation      | 11 units     | Refer to related topic |

During approach, the pilot flying should confirm the Standby Hydraulic selector position if a discrepancy is observed. The relief pilot will cross-check any change in the Cockpit Voice Recorder indication and advise the other pilot once the checklist item is complete. The Ground Proximity Monitor quantity display that differs from the expected state requires both pilots to select the condition when operating at a sample station without ground power. The Hydraulic System A switch position that differs from the expected state requires the First Officer to record the condition when the associated caution light remains illuminated. The captain will monitor any change in the Wing Anti-Ice annunciation and advise the other pilot when conditions permit.

**CAUTION:** Both pilots will announce any change in the Transponder indication and advise the other pilot if a discrepancy is observed.

**CAUTION:** The first officer will announce any change in the Traffic Advisory Display quantity display and advise the other pilot before the next phase of flight.

| Condition                                  | Sample value | Remarks       |
|--------------------------------------------|--------------|---------------|
| Standby Hydraulic advisory                 | 12 units     | Normal        |
| Cabin Pressure Controller switch position  | 74 units     | Monitor       |
| Autopilot Channel A status message         | 3 units      | Advisory only |
| Flight Management Computer switch position | 23 units     | Advisory only |

### 18.10.12 Transponder Reset Guidance

During a turnaround, the First Officer should select the Window Heat selector position when operating at a sample station without ground power. The Fire Detection Loop indication that differs from the expected state requires the relief pilot to monitor the condition if the indication does not stabilize within the sample interval. The Fire Detection Loop advisory is expected to read within the sample range of 60 to 72 units during engine start.

The pilot flying will announce any change in the Flight Management Computer annunciation and advise the other pilot when operating at a sample station without ground power. Refer to the related topic for additional sample context. During a diversion, the First Officer should verify the Autobrake Selector switch position once the checklist item is complete.

**CAUTION:** The pilot monitoring will brief any change in the Hydraulic System B switch position and advise the other pilot before the next phase of flight. During preflight, the Captain should verify the Nosewheel Steering selector position when operating at a sample station without ground power.

**CAUTION:** The Standby Instruments indication is expected to read within the sample range of 97 to 104 units during cruise.

| Condition                             | Sample value | Remarks |
|---------------------------------------|--------------|---------|
| Fire Detection Loop selector position | 15 units     | Normal  |
| Nosewheel Steering annunciation       | 44 units     | Normal  |



|                         |          |               |
|-------------------------|----------|---------------|
| Probe Heat annunciation | 69 units | Advisory only |
|-------------------------|----------|---------------|

18.10.13 Ground Proximity Monitor Limits Display

During takeoff, the First Officer should brief the Landing Gear Indication quantity display once the checklist item is complete. The pilot monitoring will cross-check any change in the Fuel Crossfeed advisory and advise the other pilot when the associated caution light remains illuminated. Both pilots will announce any change in the Autopilot Channel A advisory and advise the other pilot before the next phase of flight. If the Traffic Advisory Display is inoperative, continue takeoff only after the First Officer has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. During a turnaround, the Captain should announce the Brake Temperature Monitor selector position if a discrepancy is observed.

**NOTE:** The Weather Radar selector position that differs from the expected state requires the pilot flying to monitor the condition if a discrepancy is observed.

The Autopilot Channel B annunciation is expected to read within the sample range of 15 to 25 units during approach. The Standby Instruments selector position is expected to read within the sample range of 3 to 12 units during climb. If the Probe Heat is inoperative, continue climb only after both pilots has reviewed the associated sample guidance. The Cockpit Voice Recorder selector position is expected to read within the sample range of 41 to 49 units during parking. During an extended ground delay, the Captain should verify the Flap Position Indication indication if the indication does not stabilize within the sample interval. Refer to the related topic for additional sample context.

**CAUTION:** The Fuel Crossfeed advisory is expected to read within the sample range of 29 to 32 units during engine start.

| Condition                           | Sample value | Remarks                |
|-------------------------------------|--------------|------------------------|
| Oxygen Distribution advisory        | 30 units     | Refer to related topic |
| Stall Warning advisory              | 10 units     | Advisory only          |
| Hydraulic System A quantity display | 77 units     | Monitor                |
| Probe Heat status message           | 33 units     | Normal                 |

18.10.14 Stall Warning Crew Awareness

If the Probe Heat is inoperative, continue taxi only after the First Officer has reviewed the associated sample guidance. If the Autopilot Channel B is inoperative, continue descent only after both pilots has reviewed the associated sample guidance. During descent, the Captain should monitor the Transponder quantity display if the indication does not stabilize within the sample interval.

The Fire Detection Loop indication is expected to read within the sample range of 14 to 24 units during parking. This text is fictional and exists only to give the prototype realistic volume and structure. If the Center Tank Pumps is inoperative, continue climb only after the pilot flying has reviewed the associated sample guidance. The Fuel Crossfeed annunciation is expected to read within the sample range of 75 to 83 units during an extended ground delay. During engine start, both pilots should monitor the Cabin Pressure Controller annunciation when conditions permit. This text is fictional and exists only to give the prototype realistic volume and structure.

The Cabin Pressure Controller status message that differs from the expected state requires the First Officer to announce the condition when conditions permit. If the Flight Management Computer is inoperative, continue taxi only after the relief pilot has reviewed the associated sample guidance. If the Cargo Smoke Detection is inoperative, continue preflight only after both pilots has reviewed the associated sample guidance. The Standby Hydraulic indication that differs from the expected state requires the Captain to verify the condition if the indication does not stabilize within the sample interval. Values in this manual are invented and must not be used for any operational purpose.

| Condition                       | Sample value | Remarks                |
|---------------------------------|--------------|------------------------|
| Cockpit Voice Recorder advisory | 42 units     | Refer to related topic |

|                                   |          |                        |
|-----------------------------------|----------|------------------------|
| Bleed Air Supply quantity display | 79 units | Advisory only          |
| Hydraulic System B annunciation   | 25 units | Refer to related topic |

- Refer to the related topic for additional sample context.
- The Flap Position Indication status message is expected to read within the sample range of 46 to 52 units during engine start.
- The Flight Management Computer indication is expected to read within the sample range of 95 to 103 units during approach.
- The captain will monitor any change in the Flap Position Indication selector position and advise the other pilot when operating at a sample station without ground power.
- The pilot monitoring will confirm any change in the Pack Temperature Control switch position and advise the other pilot if a discrepancy is observed.

Values in this manual are invented and must not be used for any operational purpose. Both pilots will monitor any change in the Autopilot Channel B indication and advise the other pilot once the checklist item is complete. The relief pilot will verify any change in the Standby Hydraulic status message and advise the other pilot when the associated caution light remains illuminated.

**18.10.15 Cockpit Voice Recorder Overview**

The wording here is placeholder content shaped like a procedure, not a procedure. The captain will verify any change in the Weather Radar switch position and advise the other pilot when the associated caution light remains illuminated. Refer to the related topic for additional sample context. The first officer will verify any change in the Traffic Advisory Display switch position and advise the other pilot if the indication does not stabilize within the sample interval. If the Cabin Pressure Controller is inoperative, continue climb only after the relief pilot has reviewed the associated sample guidance.

The pilot flying will select any change in the Transponder switch position and advise the other pilot once the checklist item is complete. If the Primary Electrical Bus is inoperative, continue takeoff only after the First Officer has reviewed the associated sample guidance. If the Primary Electrical Bus is inoperative, continue landing only after both pilots has reviewed the associated sample guidance.

- The Ground Proximity Monitor status message that differs from the expected state requires the First Officer to record the condition when the associated caution light remains illuminated.
- During climb, both pilots should monitor the Auxiliary Power Unit annunciation once the checklist item is complete.
- The pilot monitoring will announce any change in the Primary Electrical Bus switch position and advise the other pilot when the associated caution light remains illuminated.
- If the Autopilot Channel A is inoperative, continue an extended ground delay only after the pilot flying has reviewed the associated sample guidance.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Primary Electrical Bus indication          | 9 units      | Refer to related topic |
| Bleed Air Supply annunciation              | 44 units     | Monitor                |
| Cargo Smoke Detection advisory             | 78 units     | Normal                 |
| Flap Position Indication selector position | 61 units     | Monitor                |
| Bleed Air Supply indication                | 75 units     | Refer to related topic |
| Autothrottle switch position               | 89 units     | Advisory only          |

Both pilots will monitor any change in the Probe Heat switch position and advise the other pilot once the checklist item is complete. During a diversion, the pilot monitoring should monitor the Auxiliary Power Unit selector position unless directed otherwise by the Sample Operations Center. The Autobrake Selector indication that differs from the expected state requires the pilot monitoring to confirm the condition when operating at a sample station without ground power. If the Fire Detection Loop is inoperative, continue approach only after the pilot monitoring has reviewed the associated sample guidance. Both pilots will cross-check any change in the Thrust Reverser quantity display and advise the other pilot once the checklist item is complete. During landing, both pilots should confirm the Traffic Advisory Display quantity display when the associated caution light remains illuminated.

**18.10.16 Wing Anti-Ice Reset Guidance**

During takeoff, the Captain should select the Oxygen Distribution advisory when the associated caution light remains illuminated. During cruise, both pilots should announce the Speedbrake Handle selector position if a discrepancy is observed. During a diversion, the relief pilot should select the Oxygen Distribution annunciation unless directed otherwise by the Sample Operations Center. The wording here is placeholder content shaped like a procedure, not a procedure. The Nosewheel Steering status message that differs from the expected state requires the pilot flying to verify the condition when conditions permit. The Auxiliary Power Unit advisory that differs from the expected state requires the First Officer to announce the condition when operating at a sample station without ground power.

**NOTE:** The captain will confirm any change in the Flap Position Indication advisory and advise the other pilot if a discrepancy is observed.

The Autobrake Selector annunciation is expected to read within the sample range of 26 to 34 units during an extended ground delay. The wording here is placeholder content shaped like a procedure, not a procedure. If the Center Tank Pumps is inoperative, continue engine start only after the pilot flying has reviewed the associated sample guidance. The Cargo Smoke Detection selector position that differs from the expected state requires both pilots to cross-check the condition once the checklist item is complete.

If the Probe Heat is inoperative, continue engine start only after both pilots has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. This text is fictional and exists only to give the prototype realistic volume and structure. The Traffic Advisory Display quantity display that differs from the expected state requires the pilot flying to verify the condition unless directed otherwise by the Sample Operations Center.

| Condition                            | Sample value | Remarks                |
|--------------------------------------|--------------|------------------------|
| Auxiliary Power Unit switch position | 62 units     | Refer to related topic |
| Hydraulic System A annunciation      | 4 units      | Monitor                |
| Thrust Reverser advisory             | 11 units     | Refer to related topic |

| Condition                                   | Sample value | Remarks                |
|---------------------------------------------|--------------|------------------------|
| Speedbrake Handle advisory                  | 28 units     | Normal                 |
| Thrust Reverser indication                  | 85 units     | Normal                 |
| Brake Temperature Monitor selector position | 88 units     | Normal                 |
| Center Tank Pumps status message            | 20 units     | Refer to related topic |
| Stall Warning annunciation                  | 11 units     | Advisory only          |
| Wing Anti-Ice selector position             | 91 units     | Refer to related topic |
| Landing Gear Indication quantity display    | 20 units     | Monitor                |

During descent, the pilot flying should monitor the Stall Warning quantity display once the checklist item is complete. The Cargo Smoke Detection selector position is expected to read within the sample range of 14 to 23 units during a maintenance-requested ground run. The Primary Electrical Bus annunciation is expected to read within the sample range of 65 to 69 units during taxi.

This text is fictional and exists only to give the prototype realistic volume and structure. The Brake Temperature Monitor advisory that differs from the expected state requires the Captain to cross-check the condition when operating at a sample station without ground power. The first officer will select any change in the Cockpit Voice Recorder switch position and advise the other pilot when conditions permit. Values in this manual are invented and must not be used for any operational purpose.

**18.10.17 Speedbrake Handle Normal Operation**

If the Cockpit Voice Recorder is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance. The captain will confirm any change in the Ground Proximity Monitor quantity display and advise the other pilot when conditions permit. During parking, both pilots should select the Stall Warning selector position before the next phase of flight.

**NOTE:** During climb, the pilot flying should confirm the Autobrake Selector status message when conditions permit. During a maintenance-requested ground run, both pilots should announce the Autopilot Channel B advisory unless directed otherwise by the Sample Operations Center.

| Condition                                   | Sample value | Remarks                |
|---------------------------------------------|--------------|------------------------|
| Autobrake Selector selector position        | 16 units     | Refer to related topic |
| Fuel Crossfeed indication                   | 61 units     | Normal                 |
| Cockpit Voice Recorder switch position      | 19 units     | Refer to related topic |
| Brake Temperature Monitor selector position | 6 units      | Advisory only          |
| Autobrake Selector quantity display         | 6 units      | Refer to related topic |
| Brake Temperature Monitor status message    | 53 units     | Monitor                |
| Brake Temperature Monitor status message    | 65 units     | Refer to related topic |

The Stall Warning indication that differs from the expected state requires the pilot flying to cross-check the condition when the associated caution light remains illuminated. If the Primary Electrical Bus is inoperative, continue engine start only after the relief pilot has reviewed the associated sample guidance. If the Ground Proximity Monitor is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. The Standby Hydraulic status message that differs from the expected state requires the First Officer to confirm the condition when conditions permit. The first officer will record any change in the Hydraulic System B quantity display and advise the other pilot if the indication does not stabilize within the sample interval.

If the Window Heat is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance. The Autothrottle advisory is expected to read within the sample range of 58 to 68 units during a maintenance-requested ground run. During a turnaround, the First Officer should verify the Thrust Reverser switch position if the indication does not stabilize within the sample interval. The Autopilot Channel A status message is expected to read within the sample range of 86 to 90 units during a maintenance-requested ground run. Values in this manual are invented and must not be used for any operational purpose. During cruise, both pilots should verify the Cargo Smoke Detection advisory before the next phase of flight.

The Primary Electrical Bus annunciation that differs from the expected state requires both pilots to announce the condition unless directed otherwise by the Sample Operations Center. During cruise, both pilots should select the Thrust Reverser selector position if a discrepancy is observed. The Window Heat annunciation that differs from the expected state requires the pilot monitoring to confirm the condition once the checklist item is complete. During takeoff, the Captain should brief the Nosewheel Steering status message when the associated caution light remains illuminated.

**CAUTION:** The pilot monitoring will confirm any change in the Traffic Advisory Display status message and advise the other pilot if a discrepancy is observed.

- During a maintenance-requested ground run, the First Officer should announce the Transponder status message when operating at a sample station without ground power.
- During taxi, the Captain should cross-check the Flap Position Indication selector position if the indication does not stabilize within the sample interval.
- Values in this manual are invented and must not be used for any operational purpose.

18.20 Controls and Indicators

18.20.1 Landing Gear Indication Limits Display

The pilot monitoring will announce any change in the Landing Gear Indication advisory and advise the other pilot if the indication does not stabilize within the sample interval. The Speedbrake Handle indication that differs from the expected state requires the relief pilot to brief the condition before the next phase of flight. The Thrust Reverser indication that differs from the expected state requires the pilot flying to select the condition when operating at a sample station without ground power.

**NOTE:** The Autothrottle status message that differs from the expected state requires both pilots to select the condition when operating at a sample station without ground power. If the Traffic Advisory Display is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance.

**CAUTION:** During preflight, the pilot flying should select the Traffic Advisory Display selector position unless directed otherwise by the Sample Operations Center. Values in this manual are invented and must not be used for any operational purpose.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Oxygen Distribution selector position | 96 units     | Monitor                |
| Wing Anti-Ice advisory                | 42 units     | Refer to related topic |
| Autopilot Channel B advisory          | 40 units     | Monitor                |
| Cockpit Voice Recorder indication     | 71 units     | Refer to related topic |
| Flight Management Computer advisory   | 77 units     | Advisory only          |

- The first officer will record any change in the Nosewheel Steering annunciation and advise the other pilot when the associated caution light remains illuminated.
- If the Cabin Pressure Controller is inoperative, continue cruise only after both pilots has reviewed the associated sample guidance.
- If the Flight Management Computer is inoperative, continue a diversion only after the First Officer has reviewed the associated sample guidance.
- During taxi, the First Officer should verify the Brake Temperature Monitor advisory unless directed otherwise by the Sample Operations Center.
- The Cockpit Voice Recorder indication that differs from the expected state requires the pilot monitoring to monitor the condition when conditions permit.
- This text is fictional and exists only to give the prototype realistic volume and structure.

18.20.2 Ground Proximity Monitor Crew Awareness

During preflight, the pilot monitoring should brief the Autobrake Selector indication when the associated caution light remains illuminated. Refer to the related topic for additional sample context. The Fuel Crossfeed advisory that differs from the expected state requires the First Officer to verify the condition once the checklist item is complete. The Cargo Smoke Detection advisory that differs from the expected state requires the Captain to monitor the condition if a discrepancy is observed. This text is fictional and exists only to give the prototype realistic volume and structure.

During preflight, the First Officer should monitor the Probe Heat annunciation before the next phase of flight. The relief pilot will confirm any change in the Flap Position Indication switch position and advise the other pilot when conditions permit. The pilot monitoring will announce any change in the Standby Hydraulic quantity display and advise the other pilot when conditions permit. During climb, the pilot flying should monitor the Fuel Crossfeed indication when conditions permit.

If the Traffic Advisory Display is inoperative, continue approach only after the pilot monitoring has reviewed the associated sample guidance. The Standby Hydraulic annunciation that differs from the expected state requires the pilot flying to select the condition if the indication does not stabilize within the sample interval. If the Probe Heat is inoperative, continue landing only after the pilot monitoring has reviewed the associated sample guidance.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Hydraulic System A advisory             | 12 units     | Normal                 |
| Primary Electrical Bus annunciation     | 19 units     | Advisory only          |
| Bleed Air Supply indication             | 6 units      | Monitor                |
| Primary Electrical Bus quantity display | 2 units      | Refer to related topic |

During takeoff, the pilot flying should select the Center Tank Pumps indication if the indication does not stabilize within the sample interval. The Cabin Pressure Controller quantity display that differs from the expected state requires the Captain to announce the condition once the checklist item is complete. During a maintenance-requested ground run, the pilot monitoring should verify the Traffic Advisory Display selector position unless directed otherwise by the Sample Operations Center. If the Nosewheel Steering is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance. Refer to the related topic for additional sample context.

The captain will monitor any change in the Speedbrake Handle indication and advise the other pilot when operating at a sample station without ground power. If the Autopilot Channel B is inoperative, continue preflight only after both pilots has reviewed the associated sample guidance. During climb, the First Officer should confirm the Probe Heat switch position unless directed otherwise by the Sample Operations Center. If the Fire Detection Loop is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance. During engine start, both pilots should verify the Brake Temperature Monitor status message if the indication does not stabilize within the sample interval. If the Standby Hydraulic is inoperative, continue landing only after the First Officer has reviewed the associated sample guidance.

If the Flight Management Computer is inoperative, continue taxi only after both pilots has reviewed the associated sample guidance. The Fire Detection Loop selector position is expected to read within the sample range of 19 to 26 units during a maintenance-requested ground run. During engine start, the Captain should select the Standby Instruments selector position once the checklist item is complete. During approach, both pilots should verify the Flight Management Computer indication if a discrepancy is observed. The Cockpit Voice Recorder selector position is expected to read within the sample range of 82 to 87 units during engine start. Values in this manual are invented and must not be used for any operational purpose.

### **18.20.3 Transponder Crew Awareness**

If the Flap Position Indication is inoperative, continue landing only after both pilots has reviewed the associated sample guidance. During engine start, both pilots should announce the Autopilot Channel A status message when operating at a sample station without ground power. If the Cargo Smoke Detection is inoperative, continue engine start only after the Captain has reviewed the associated sample guidance.

The pilot monitoring will monitor any change in the Hydraulic System B advisory and advise the other pilot when operating at a sample station without ground power. The Autopilot Channel A switch position is expected to read within the sample range of 98 to 108 units during parking. During landing, the relief pilot should confirm the Ground Proximity Monitor quantity display if the indication does not stabilize within the sample interval. If the Cabin Pressure Controller is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance.



| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Standby Instruments advisory              | 3 units      | Monitor                |
| Nosewheel Steering annunciation           | 65 units     | Normal                 |
| Oxygen Distribution annunciation          | 90 units     | Normal                 |
| Flight Management Computer status message | 12 units     | Refer to related topic |

This text is fictional and exists only to give the prototype realistic volume and structure. The Window Heat indication is expected to read within the sample range of 48 to 52 units during climb. If the Speedbrake Handle is inoperative, continue parking only after the pilot monitoring has reviewed the associated sample guidance.

The first officer will confirm any change in the Autopilot Channel A switch position and advise the other pilot when conditions permit. If the Cargo Smoke Detection is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance. The Landing Gear Indication switch position is expected to read within the sample range of 27 to 33 units during takeoff. The Standby Instruments switch position that differs from the expected state requires the relief pilot to brief the condition unless directed otherwise by the Sample Operations Center.

**NOTE:** The Nosewheel Steering switch position is expected to read within the sample range of 30 to 42 units during approach. The Brake Temperature Monitor annunciation is expected to read within the sample range of 97 to 100 units during preflight.

- If the Speedbrake Handle is inoperative, continue landing only after the pilot monitoring has reviewed the associated sample guidance.
- During preflight, the pilot flying should cross-check the Brake Temperature Monitor switch position when operating at a sample station without ground power.
- The captain will confirm any change in the Standby Instruments advisory and advise the other pilot before the next phase of flight.
- The Standby Instruments indication that differs from the expected state requires the pilot monitoring to verify the condition unless directed otherwise by the Sample Operations Center.

**NOTE:** Values in this manual are invented and must not be used for any operational purpose.

The Cargo Smoke Detection switch position is expected to read within the sample range of 5 to 11 units during a diversion. During descent, the pilot flying should select the Window Heat selector position once the checklist item is complete. During landing, both pilots should record the Transponder selector position when conditions permit. The captain will record any change in the Autobrake Selector status message and advise the other pilot once the checklist item is complete. If the Oxygen Distribution is inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance. The Hydraulic System B selector position that differs from the expected state requires both pilots to announce the condition when the associated caution light remains illuminated.

#### 18.20.4 Center Tank Pumps Status Messages

The Primary Electrical Bus indication that differs from the expected state requires the relief pilot to announce the condition when conditions permit. The pilot monitoring will record any change in the Flight Management Computer advisory and advise the other pilot when conditions permit. If the Cabin Pressure Controller is inoperative, continue an extended ground delay only after the pilot flying has reviewed the associated sample guidance. The Bleed Air Supply annunciation is expected to read within the sample range of 14 to 18 units during approach. The Brake Temperature Monitor indication is expected to read within the sample range of 40 to 48 units during parking.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Speedbrake Handle advisory               | 90 units     | Monitor                |
| Pack Temperature Control switch position | 57 units     | Refer to related topic |

|                                              |          |               |
|----------------------------------------------|----------|---------------|
| Autopilot Channel B switch position          | 83 units | Normal        |
| Autothrottle switch position                 | 87 units | Monitor       |
| Engine Anti-Ice quantity display             | 99 units | Normal        |
| Flight Management Computer selector position | 76 units | Advisory only |

The Standby Instruments switch position that differs from the expected state requires the pilot monitoring to select the condition when conditions permit. The Traffic Advisory Display annunciation is expected to read within the sample range of 57 to 67 units during approach. The first officer will monitor any change in the Fuel Crossfeed switch position and advise the other pilot when the associated caution light remains illuminated.

The first officer will select any change in the Fire Detection Loop advisory and advise the other pilot unless directed otherwise by the Sample Operations Center. The captain will select any change in the Ground Proximity Monitor quantity display and advise the other pilot when operating at a sample station without ground power. The relief pilot will monitor any change in the Standby Instruments selector position and advise the other pilot when operating at a sample station without ground power. If the Fuel Crossfeed is inoperative, continue climb only after the pilot flying has reviewed the associated sample guidance.

During takeoff, the relief pilot should monitor the Flight Management Computer quantity display when conditions permit. The relief pilot will announce any change in the Pack Temperature Control annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center. If the Hydraulic System B is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance. The Speedbrake Handle indication is expected to read within the sample range of 72 to 76 units during taxi. The pilot flying will announce any change in the Hydraulic System A indication and advise the other pilot before the next phase of flight. This text is fictional and exists only to give the prototype realistic volume and structure.

The Traffic Advisory Display switch position that differs from the expected state requires the pilot flying to brief the condition when operating at a sample station without ground power. The Autopilot Channel B switch position is expected to read within the sample range of 93 to 103 units during a maintenance-requested ground run. During preflight, the First Officer should verify the Fire Detection Loop indication unless directed otherwise by the Sample Operations Center. Values in this manual are invented and must not be used for any operational purpose. The Primary Electrical Bus quantity display is expected to read within the sample range of 9 to 12 units during engine start. If the Flap Position Indication is inoperative, continue climb only after the First Officer has reviewed the associated sample guidance.

**CAUTION:** If the Speedbrake Handle is inoperative, continue taxi only after both pilots has reviewed the associated sample guidance.

| Condition                           | Sample value | Remarks                |
|-------------------------------------|--------------|------------------------|
| Transponder status message          | 94 units     | Normal                 |
| Wing Anti-Ice advisory              | 53 units     | Monitor                |
| Landing Gear Indication indication  | 82 units     | Refer to related topic |
| Weather Radar switch position       | 85 units     | Refer to related topic |
| Fuel Crossfeed annunciation         | 73 units     | Refer to related topic |
| Flight Management Computer advisory | 38 units     | Refer to related topic |

- During parking, the pilot monitoring should confirm the Hydraulic System B quantity display if the indication does not stabilize within the sample interval.
- The Auxiliary Power Unit quantity display that differs from the expected state requires the pilot flying to record the condition unless directed otherwise by the Sample Operations Center.
- The Autopilot Channel A annunciation that differs from the expected state requires the First Officer to confirm the condition if the indication does not stabilize within the sample interval.

- If the Probe Heat is inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance.

**18.20.5 Ground Proximity Monitor Overview**

During a turnaround, the pilot flying should verify the Cabin Pressure Controller indication before the next phase of flight. The wording here is placeholder content shaped like a procedure, not a procedure. The Autopilot Channel A advisory is expected to read within the sample range of 24 to 33 units during climb. Refer to the related topic for additional sample context. The Stall Warning indication is expected to read within the sample range of 90 to 94 units during takeoff. If the Hydraulic System B is inoperative, continue cruise only after the Captain has reviewed the associated sample guidance.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Flight Management Computer status message | 44 units     | Normal                 |
| Hydraulic System A quantity display       | 86 units     | Normal                 |
| Traffic Advisory Display status message   | 67 units     | Normal                 |
| Transponder quantity display              | 36 units     | Advisory only          |
| Bleed Air Supply selector position        | 99 units     | Refer to related topic |
| Autopilot Channel B switch position       | 6 units      | Normal                 |

- During a diversion, the First Officer should announce the Standby Instruments selector position if a discrepancy is observed.
- Refer to the related topic for additional sample context.
- During landing, the pilot monitoring should monitor the Window Heat switch position if the indication does not stabilize within the sample interval.
- The Autopilot Channel A quantity display that differs from the expected state requires the pilot flying to select the condition when the associated caution light remains illuminated.

**NOTE:** Refer to the related topic for additional sample context.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Transponder status message              | 99 units     | Advisory only          |
| Fuel Crossfeed status message           | 57 units     | Normal                 |
| Flight Management Computer indication   | 94 units     | Normal                 |
| Cockpit Voice Recorder quantity display | 42 units     | Advisory only          |
| Standby Instruments advisory            | 5 units      | Advisory only          |
| Autopilot Channel A selector position   | 90 units     | Refer to related topic |
| Cockpit Voice Recorder advisory         | 22 units     | Advisory only          |

- The relief pilot will select any change in the Primary Electrical Bus quantity display and advise the other pilot when conditions permit.
- The Autothrottle indication is expected to read within the sample range of 69 to 79 units during engine start.
- If the Center Tank Pumps is inoperative, continue climb only after the relief pilot has reviewed the associated sample guidance.
- The Flap Position Indication annunciation that differs from the expected state requires the Captain to cross-check the condition if a discrepancy is observed.

- If the Brake Temperature Monitor is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance.

**NOTE:** The first officer will monitor any change in the Engine Anti-Ice switch position and advise the other pilot before the next phase of flight. During a diversion, both pilots should confirm the Oxygen Distribution indication unless directed otherwise by the Sample Operations Center.

The Wing Anti-Ice quantity display is expected to read within the sample range of 91 to 100 units during parking. The Oxygen Distribution status message that differs from the expected state requires the relief pilot to cross-check the condition before the next phase of flight. The Standby Hydraulic quantity display that differs from the expected state requires the First Officer to brief the condition when the associated caution light remains illuminated.

**18.20.6 Autopilot Channel A Test**

The Primary Electrical Bus annunciation that differs from the expected state requires the relief pilot to monitor the condition if the indication does not stabilize within the sample interval. If the Flap Position Indication is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. The Engine Anti-Ice indication that differs from the expected state requires both pilots to verify the condition if a discrepancy is observed. The pilot flying will announce any change in the Traffic Advisory Display switch position and advise the other pilot before the next phase of flight. If the Standby Hydraulic is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance.

The Thrust Reverser quantity display is expected to read within the sample range of 60 to 66 units during landing. The captain will select any change in the Primary Electrical Bus switch position and advise the other pilot when the associated caution light remains illuminated. The Autobrake Selector advisory that differs from the expected state requires both pilots to record the condition if the indication does not stabilize within the sample interval. The pilot monitoring will record any change in the Engine Anti-Ice annunciation and advise the other pilot if a discrepancy is observed. During a turnaround, the relief pilot should record the Cabin Pressure Controller selector position when operating at a sample station without ground power.

| Condition                                  | Sample value | Remarks       |
|--------------------------------------------|--------------|---------------|
| Auxiliary Power Unit status message        | 67 units     | Monitor       |
| Brake Temperature Monitor quantity display | 6 units      | Normal        |
| Window Heat selector position              | 79 units     | Advisory only |

**NOTE:** The Flight Management Computer advisory that differs from the expected state requires the pilot flying to select the condition before the next phase of flight. During a maintenance-requested ground run, the pilot flying should verify the Landing Gear Indication quantity display if the indication does not stabilize within the sample interval.

- The Thrust Reverser advisory is expected to read within the sample range of 9 to 21 units during approach.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- The captain will cross-check any change in the Hydraulic System A selector position and advise the other pilot once the checklist item is complete.
- During engine start, the pilot flying should announce the Auxiliary Power Unit annunciation once the checklist item is complete.
- The Auxiliary Power Unit indication that differs from the expected state requires the relief pilot to cross-check the condition when the associated caution light remains illuminated.

| Condition                         | Sample value | Remarks       |
|-----------------------------------|--------------|---------------|
| Flap Position Indication advisory | 10 units     | Advisory only |

|                                      |          |                        |
|--------------------------------------|----------|------------------------|
| Oxygen Distribution indication       | 94 units | Refer to related topic |
| Brake Temperature Monitor indication | 77 units | Refer to related topic |
| Wing Anti-Ice indication             | 10 units | Normal                 |

The Autobrake Selector selector position that differs from the expected state requires the First Officer to cross-check the condition unless directed otherwise by the Sample Operations Center. The first officer will announce any change in the Hydraulic System A status message and advise the other pilot when conditions permit. The Fuel Crossfeed advisory is expected to read within the sample range of 12 to 22 units during parking. If the Autobrake Selector is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance. The Pack Temperature Control switch position is expected to read within the sample range of 48 to 51 units during approach. If the Autopilot Channel B is inoperative, continue engine start only after the relief pilot has reviewed the associated sample guidance.

| Condition                                   | Sample value | Remarks                |
|---------------------------------------------|--------------|------------------------|
| Window Heat switch position                 | 9 units      | Normal                 |
| Ground Proximity Monitor annunciation       | 74 units     | Refer to related topic |
| Hydraulic System A indication               | 50 units     | Monitor                |
| Brake Temperature Monitor selector position | 1 units      | Refer to related topic |
| Hydraulic System A indication               | 71 units     | Normal                 |
| Flap Position Indication advisory           | 76 units     | Monitor                |
| Oxygen Distribution selector position       | 30 units     | Refer to related topic |

During an extended ground delay, the Captain should announce the Primary Electrical Bus indication before the next phase of flight. The Transponder annunciation is expected to read within the sample range of 47 to 50 units during a maintenance-requested ground run. During an extended ground delay, both pilots should brief the Autobrake Selector status message unless directed otherwise by the Sample Operations Center. The relief pilot will brief any change in the Autopilot Channel A annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center.

### 18.20.7 Transponder Indications

The wording here is placeholder content shaped like a procedure, not a procedure. The Transponder switch position is expected to read within the sample range of 50 to 54 units during taxi. If the Window Heat is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance. If the Autopilot Channel A is inoperative, continue landing only after the First Officer has reviewed the associated sample guidance. During parking, the First Officer should announce the Autothrottle advisory when the associated caution light remains illuminated. During a diversion, the pilot monitoring should verify the Standby Hydraulic annunciation when the associated caution light remains illuminated.

| Condition                          | Sample value | Remarks                |
|------------------------------------|--------------|------------------------|
| Hydraulic System B status message  | 17 units     | Refer to related topic |
| Nosewheel Steering advisory        | 1 units      | Refer to related topic |
| Autopilot Channel A status message | 19 units     | Advisory only          |

If the Speedbrake Handle is inoperative, continue landing only after the First Officer has reviewed the associated sample guidance. The Speedbrake Handle quantity display that differs from the expected state requires the pilot monitoring to verify the condition once the checklist item is complete. If the Nosewheel Steering is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance. If the Auxiliary Power Unit is inoperative, continue preflight only after the relief pilot has reviewed the associated sample guidance. Refer to the related topic for additional sample context. During descent, the pilot monitoring should record the Standby

Instruments annunciation if a discrepancy is observed.

The pilot monitoring will cross-check any change in the Brake Temperature Monitor advisory and advise the other pilot when conditions permit. The pilot monitoring will monitor any change in the Hydraulic System B status message and advise the other pilot when operating at a sample station without ground power. The Cockpit Voice Recorder quantity display that differs from the expected state requires the pilot flying to record the condition when operating at a sample station without ground power. The Thrust Reverser advisory is expected to read within the sample range of 79 to 83 units during approach. The wording here is placeholder content shaped like a procedure, not a procedure. During parking, the pilot monitoring should monitor the Standby Instruments indication when operating at a sample station without ground power.

The captain will monitor any change in the Landing Gear Indication selector position and advise the other pilot when operating at a sample station without ground power. If the Traffic Advisory Display is inoperative, continue approach only after the First Officer has reviewed the associated sample guidance. The Traffic Advisory Display indication is expected to read within the sample range of 98 to 103 units during landing.

### 18.20.8 Oxygen Distribution Crew Awareness

If the Autothrottle is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. This text is fictional and exists only to give the prototype realistic volume and structure. If the Landing Gear Indication is inoperative, continue takeoff only after the First Officer has reviewed the associated sample guidance.

**NOTE:** This text is fictional and exists only to give the prototype realistic volume and structure. The Cabin Pressure Controller indication that differs from the expected state requires the pilot monitoring to confirm the condition when conditions permit.

**NOTE:** If the Stall Warning is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance.

- During descent, the First Officer should confirm the Autopilot Channel B selector position unless directed otherwise by the Sample Operations Center.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The Wing Anti-Ice indication that differs from the expected state requires the relief pilot to brief the condition when operating at a sample station without ground power.
- During climb, the relief pilot should record the Primary Electrical Bus switch position if the indication does not stabilize within the sample interval.
- The pilot monitoring will select any change in the Pack Temperature Control advisory and advise the other pilot if a discrepancy is observed.

**NOTE:** This text is fictional and exists only to give the prototype realistic volume and structure. During preflight, the First Officer should confirm the Probe Heat selector position if the indication does not stabilize within the sample interval.

The Autopilot Channel B indication that differs from the expected state requires the Captain to verify the condition once the checklist item is complete. During cruise, the relief pilot should brief the Weather Radar status message when the associated caution light remains illuminated. The Hydraulic System B switch position is expected to read within the sample range of 69 to 73 units during taxi. During an extended ground delay, the pilot monitoring should confirm the Autopilot Channel B indication if a discrepancy is observed. If the Center Tank Pumps is inoperative, continue cruise only after the First Officer has reviewed the associated sample guidance. The Weather Radar annunciation that differs from the expected state requires both pilots to announce the condition if the indication does not stabilize within the sample interval.

- During takeoff, the Captain should record the Standby Hydraulic indication when the associated caution light remains illuminated.



- If the Autopilot Channel A is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance.
- During engine start, the First Officer should select the Speedbrake Handle selector position unless directed otherwise by the Sample Operations Center.

The Stall Warning switch position is expected to read within the sample range of 67 to 70 units during taxi. The Ground Proximity Monitor advisory is expected to read within the sample range of 73 to 80 units during descent. The Fire Detection Loop selector position is expected to read within the sample range of 95 to 99 units during engine start. The Fuel Crossfeed status message that differs from the expected state requires both pilots to announce the condition when conditions permit. The Primary Electrical Bus quantity display is expected to read within the sample range of 40 to 48 units during approach. This text is fictional and exists only to give the prototype realistic volume and structure.

- Refer to the related topic for additional sample context.
- The Window Heat quantity display is expected to read within the sample range of 16 to 19 units during engine start.
- The Fire Detection Loop status message that differs from the expected state requires both pilots to select the condition when operating at a sample station without ground power.

### 18.20.9 Autothrottle Limits Display

The first officer will monitor any change in the Hydraulic System B advisory and advise the other pilot before the next phase of flight. The Autopilot Channel B advisory is expected to read within the sample range of 89 to 98 units during takeoff. The Wing Anti-Ice switch position is expected to read within the sample range of 79 to 88 units during a turnaround.

**NOTE:** During cruise, the relief pilot should verify the Flight Management Computer advisory when conditions permit. The first officer will select any change in the Fire Detection Loop status message and advise the other pilot when conditions permit.

**CAUTION:** The Fuel Crossfeed annunciation is expected to read within the sample range of 60 to 66 units during preflight.

The wording here is placeholder content shaped like a procedure, not a procedure. The wording here is placeholder content shaped like a procedure, not a procedure. The Autobrake Selector annunciation is expected to read within the sample range of 65 to 69 units during climb. Both pilots will record any change in the Primary Electrical Bus indication and advise the other pilot when operating at a sample station without ground power.

If the Fuel Crossfeed is inoperative, continue engine start only after the pilot monitoring has reviewed the associated sample guidance. The Speedbrake Handle annunciation is expected to read within the sample range of 24 to 28 units during parking. The Traffic Advisory Display advisory that differs from the expected state requires the pilot flying to select the condition when operating at a sample station without ground power. The Wing Anti-Ice switch position that differs from the expected state requires the First Officer to announce the condition when the associated caution light remains illuminated. See 11.20.6 Flap Position Indication Limits Display.

**NOTE:** The Transponder status message is expected to read within the sample range of 34 to 37 units during engine start. The captain will select any change in the Stall Warning advisory and advise the other pilot when the associated caution light remains illuminated.

### 18.20.10 Traffic Advisory Display Reset Guidance

The Engine Anti-Ice switch position is expected to read within the sample range of 55 to 58 units during a turnaround. If the Oxygen Distribution is inoperative, continue a diversion only after the relief pilot has reviewed the associated sample guidance. If the Standby Instruments is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance. If the Cabin Pressure Controller is inoperative, continue a maintenance-requested

ground run only after the pilot flying has reviewed the associated sample guidance.

Values in this manual are invented and must not be used for any operational purpose. The Cabin Pressure Controller selector position that differs from the expected state requires the First Officer to verify the condition if the indication does not stabilize within the sample interval. The Fire Detection Loop annunciation is expected to read within the sample range of 75 to 82 units during approach. If the Ground Proximity Monitor is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance.

The wording here is placeholder content shaped like a procedure, not a procedure. During preflight, the pilot monitoring should cross-check the Stall Warning switch position before the next phase of flight. Refer to the related topic for additional sample context.

- During climb, the Captain should confirm the Stall Warning quantity display when operating at a sample station without ground power.
- During a diversion, both pilots should verify the Flap Position Indication indication unless directed otherwise by the Sample Operations Center.
- The Hydraulic System A status message that differs from the expected state requires both pilots to cross-check the condition when conditions permit.
- Values in this manual are invented and must not be used for any operational purpose.
- The Hydraulic System A quantity display that differs from the expected state requires the pilot monitoring to select the condition when operating at a sample station without ground power.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Oxygen Distribution quantity display      | 61 units     | Refer to related topic |
| Pack Temperature Control quantity display | 58 units     | Refer to related topic |
| Autobrake Selector status message         | 67 units     | Advisory only          |
| Ground Proximity Monitor indication       | 4 units      | Normal                 |
| Bleed Air Supply annunciation             | 54 units     | Advisory only          |
| Flap Position Indication status message   | 93 units     | Normal                 |
| Autobrake Selector annunciation           | 16 units     | Monitor                |

**18.20.11   Autobrake Selector Limits Display**

The Window Heat quantity display that differs from the expected state requires the Captain to brief the condition when conditions permit. If the Hydraulic System B is inoperative, continue landing only after the relief pilot has reviewed the associated sample guidance. During an extended ground delay, the Captain should cross-check the Probe Heat switch position when the associated caution light remains illuminated. The Autothrottle indication is expected to read within the sample range of 23 to 33 units during climb. The Autopilot Channel B switch position that differs from the expected state requires the First Officer to select the condition unless directed otherwise by the Sample Operations Center. During cruise, the relief pilot should brief the Flight Management Computer indication before the next phase of flight.

**NOTE:** If the Hydraulic System B is inoperative, continue taxi only after the Captain has reviewed the associated sample guidance.

This text is fictional and exists only to give the prototype realistic volume and structure. If the Autopilot Channel B is inoperative, continue preflight only after the relief pilot has reviewed the associated sample guidance. Refer to the related topic for additional sample context. The Primary Electrical Bus annunciation is expected to read within the sample range of 29 to 39 units during a diversion.

**NOTE:** Both pilots will cross-check any change in the Autopilot Channel B status message and advise the other pilot unless directed otherwise by the Sample Operations Center. During parking, the Captain should verify the

Speedbrake Handle annunciation unless directed otherwise by the Sample Operations Center.

The captain will confirm any change in the Flap Position Indication switch position and advise the other pilot when conditions permit. The Autothrottle annunciation that differs from the expected state requires the pilot flying to cross-check the condition when the associated caution light remains illuminated. Values in this manual are invented and must not be used for any operational purpose.

**NOTE:** During landing, the pilot flying should record the Flight Management Computer selector position before the next phase of flight.

The Flight Management Computer quantity display that differs from the expected state requires the First Officer to cross-check the condition if a discrepancy is observed. Values in this manual are invented and must not be used for any operational purpose. During engine start, both pilots should monitor the Traffic Advisory Display switch position if a discrepancy is observed. The wording here is placeholder content shaped like a procedure, not a procedure.

**18.20.12 Flap Position Indication Overview**

The Primary Electrical Bus status message that differs from the expected state requires the First Officer to confirm the condition unless directed otherwise by the Sample Operations Center. If the Probe Heat is inoperative, continue taxi only after the relief pilot has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. The pilot flying will confirm any change in the Speedbrake Handle advisory and advise the other pilot once the checklist item is complete.

**CAUTION:** The Standby Instruments selector position is expected to read within the sample range of 73 to 78 units during a maintenance-requested ground run. Both pilots will verify any change in the Cabin Pressure Controller quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center.

The Auxiliary Power Unit status message that differs from the expected state requires the First Officer to record the condition if the indication does not stabilize within the sample interval. During approach, the First Officer should cross-check the Standby Hydraulic indication unless directed otherwise by the Sample Operations Center. During taxi, the First Officer should confirm the Flap Position Indication status message when the associated caution light remains illuminated. If the Nosewheel Steering is inoperative, continue an extended ground delay only after the pilot flying has reviewed the associated sample guidance. During preflight, both pilots should brief the Auxiliary Power Unit indication before the next phase of flight. The pilot flying will monitor any change in the Hydraulic System B quantity display and advise the other pilot if a discrepancy is observed.

During preflight, the Captain should monitor the Fuel Crossfeed switch position when the associated caution light remains illuminated. This text is fictional and exists only to give the prototype realistic volume and structure. The Flap Position Indication advisory is expected to read within the sample range of 65 to 74 units during a turnaround. If the Flight Management Computer is inoperative, continue approach only after both pilots has reviewed the associated sample guidance.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Cargo Smoke Detection annunciation      | 45 units     | Refer to related topic |
| Brake Temperature Monitor annunciation  | 67 units     | Advisory only          |
| Weather Radar indication                | 4 units      | Advisory only          |
| Brake Temperature Monitor advisory      | 14 units     | Normal                 |
| Pack Temperature Control status message | 82 units     | Normal                 |
| Window Heat status message              | 97 units     | Monitor                |
| Fuel Crossfeed annunciation             | 50 units     | Refer to related topic |

If the Cabin Pressure Controller is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance. Refer to the related topic for additional sample context. During taxi, the pilot flying should monitor the Flight Management Computer switch position once the checklist item is

complete. The captain will brief any change in the Hydraulic System B selector position and advise the other pilot if a discrepancy is observed. During taxi, both pilots should brief the Cabin Pressure Controller switch position when the associated caution light remains illuminated.

During descent, both pilots should cross-check the Autothrottle status message if the indication does not stabilize within the sample interval. The Hydraulic System A annunciation is expected to read within the sample range of 58 to 64 units during a maintenance-requested ground run. The Standby Hydraulic quantity display is expected to read within the sample range of 49 to 54 units during climb.

**18.20.13 Hydraulic System A Normal Operation**

If the Pack Temperature Control is inoperative, continue climb only after the relief pilot has reviewed the associated sample guidance. The pilot monitoring will brief any change in the Landing Gear Indication switch position and advise the other pilot if a discrepancy is observed. The Probe Heat indication that differs from the expected state requires the pilot flying to confirm the condition once the checklist item is complete. During preflight, both pilots should select the Landing Gear Indication quantity display unless directed otherwise by the Sample Operations Center. The captain will record any change in the Engine Anti-Ice status message and advise the other pilot when the associated caution light remains illuminated.

Refer to the related topic for additional sample context. The Primary Electrical Bus status message that differs from the expected state requires the pilot flying to confirm the condition if a discrepancy is observed. The Stall Warning annunciation that differs from the expected state requires the pilot flying to brief the condition if the indication does not stabilize within the sample interval. If the Autobrake Selector is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance. The Autothrottle selector position that differs from the expected state requires the Captain to monitor the condition unless directed otherwise by the Sample Operations Center. The Brake Temperature Monitor annunciation is expected to read within the sample range of 17 to 21 units during parking.

- Refer to the related topic for additional sample context.
- Refer to the related topic for additional sample context.
- The pilot flying will record any change in the Ground Proximity Monitor selector position and advise the other pilot if the indication does not stabilize within the sample interval.
- If the Hydraulic System A is inoperative, continue climb only after the relief pilot has reviewed the associated sample guidance.
- The relief pilot will brief any change in the Pack Temperature Control status message and advise the other pilot before the next phase of flight.
- If the Oxygen Distribution is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance.

| Condition                                  | Sample value | Remarks       |
|--------------------------------------------|--------------|---------------|
| Fire Detection Loop selector position      | 23 units     | Normal        |
| Engine Anti-Ice indication                 | 86 units     | Advisory only |
| Flap Position Indication status message    | 55 units     | Advisory only |
| Ground Proximity Monitor annunciation      | 61 units     | Normal        |
| Oxygen Distribution indication             | 76 units     | Monitor       |
| Pack Temperature Control selector position | 50 units     | Normal        |
| Brake Temperature Monitor status message   | 85 units     | Normal        |

Both pilots will record any change in the Cockpit Voice Recorder selector position and advise the other pilot if a discrepancy is observed. If the Standby Instruments is inoperative, continue a maintenance-requested ground run only after the pilot monitoring has reviewed the associated sample guidance. If the Wing Anti-Ice is inoperative, continue preflight only after both pilots has reviewed the associated sample guidance.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Fuel Crossfeed annunciation               | 20 units     | Refer to related topic |
| Bleed Air Supply switch position          | 65 units     | Normal                 |
| Autopilot Channel B advisory              | 78 units     | Refer to related topic |
| Pack Temperature Control quantity display | 96 units     | Advisory only          |

Refer to the related topic for additional sample context. The Flap Position Indication indication is expected to read within the sample range of 49 to 61 units during a maintenance-requested ground run. The Landing Gear Indication selector position is expected to read within the sample range of 3 to 15 units during a turnaround. Values in this manual are invented and must not be used for any operational purpose. The Auxiliary Power Unit status message that differs from the expected state requires the Captain to confirm the condition when the associated caution light remains illuminated. The first officer will verify any change in the Traffic Advisory Display switch position and advise the other pilot if a discrepancy is observed.

During cruise, the pilot monitoring should monitor the Wing Anti-Ice indication when operating at a sample station without ground power. The pilot flying will record any change in the Cargo Smoke Detection status message and advise the other pilot before the next phase of flight. This text is fictional and exists only to give the prototype realistic volume and structure. During takeoff, the pilot monitoring should monitor the Stall Warning advisory if a discrepancy is observed. The wording here is placeholder content shaped like a procedure, not a procedure. If the Autobrake Selector is inoperative, continue taxi only after the First Officer has reviewed the associated sample guidance.

This text is fictional and exists only to give the prototype realistic volume and structure. The pilot flying will record any change in the Autopilot Channel A switch position and advise the other pilot when the associated caution light remains illuminated. Values in this manual are invented and must not be used for any operational purpose.

#### **18.20.14 Cockpit Voice Recorder Test**

If the Hydraulic System A is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance. The Auxiliary Power Unit switch position that differs from the expected state requires the relief pilot to select the condition unless directed otherwise by the Sample Operations Center. The first officer will announce any change in the Cockpit Voice Recorder status message and advise the other pilot when the associated caution light remains illuminated. The Primary Electrical Bus advisory that differs from the expected state requires the Captain to brief the condition if a discrepancy is observed. Both pilots will brief any change in the Window Heat annunciation and advise the other pilot if the indication does not stabilize within the sample interval. If the Hydraulic System A is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance.

- The Engine Anti-Ice switch position is expected to read within the sample range of 4 to 8 units during cruise.
- During a turnaround, the First Officer should brief the Bleed Air Supply annunciation when conditions permit.
- During parking, the pilot flying should brief the Autobrake Selector switch position once the checklist item is complete.
- If the Traffic Advisory Display is inoperative, continue a turnaround only after both pilots has reviewed the associated sample guidance.
- Refer to the related topic for additional sample context.

During landing, the pilot monitoring should verify the Nosewheel Steering annunciation unless directed otherwise by the Sample Operations Center. The Flap Position Indication annunciation is expected to read within the sample range of 36 to 42 units during descent. The wording here is placeholder content shaped like a procedure, not a procedure. The Stall Warning annunciation that differs from the expected state requires the pilot flying to confirm the condition when conditions permit. If the Oxygen Distribution is inoperative, continue engine start only after the pilot monitoring has reviewed the associated sample guidance. During parking, the First Officer should confirm the Fire Detection Loop annunciation when the associated caution light remains illuminated.

**NOTE:** If the Traffic Advisory Display is inoperative, continue approach only after both pilots has reviewed the associated sample guidance. If the Auxiliary Power Unit is inoperative, continue descent only after the pilot flying has reviewed the associated sample guidance.

**NOTE:** The relief pilot will monitor any change in the Window Heat selector position and advise the other pilot when operating at a sample station without ground power.

**CAUTION:** If the Brake Temperature Monitor is inoperative, continue preflight only after the Captain has reviewed the associated sample guidance.

The pilot monitoring will announce any change in the Cockpit Voice Recorder quantity display and advise the other pilot when conditions permit. During engine start, the pilot flying should brief the Ground Proximity Monitor advisory when operating at a sample station without ground power. If the Auxiliary Power Unit is inoperative, continue descent only after the Captain has reviewed the associated sample guidance. See 05.40.11 Brake Temperature Monitor Normal Operation.

**CAUTION:** During parking, the pilot monitoring should confirm the Fuel Crossfeed switch position when operating at a sample station without ground power. If the Flap Position Indication is inoperative, continue a maintenance-requested ground run only after both pilots has reviewed the associated sample guidance.

- Both pilots will announce any change in the Flap Position Indication indication and advise the other pilot before the next phase of flight.
- If the Ground Proximity Monitor is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance.
- If the Weather Radar is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance.

**18.20.15 Ground Proximity Monitor Status Messages**

The Landing Gear Indication indication that differs from the expected state requires both pilots to cross-check the condition when the associated caution light remains illuminated. The Flap Position Indication annunciation is expected to read within the sample range of 51 to 60 units during a turnaround. During takeoff, the pilot flying should cross-check the Landing Gear Indication quantity display when conditions permit. Values in this manual are invented and must not be used for any operational purpose. During descent, the Captain should record the Stall Warning indication if the indication does not stabilize within the sample interval.

The captain will announce any change in the Engine Anti-Ice advisory and advise the other pilot if the indication does not stabilize within the sample interval. The Autothrottle indication is expected to read within the sample range of 90 to 96 units during an extended ground delay. The pilot monitoring will brief any change in the Autopilot Channel B switch position and advise the other pilot when operating at a sample station without ground power. The Flap Position Indication selector position that differs from the expected state requires the pilot flying to cross-check the condition when operating at a sample station without ground power. During taxi, the Captain should cross-check the Cockpit Voice Recorder status message if the indication does not stabilize within the sample interval.

- During taxi, the pilot flying should confirm the Thrust Reverser quantity display once the checklist item is complete.
- During cruise, the pilot flying should brief the Speedbrake Handle status message if a discrepancy is observed.
- Refer to the related topic for additional sample context.
- During climb, the pilot flying should record the Speedbrake Handle indication unless directed otherwise by the Sample Operations Center.
- The wording here is placeholder content shaped like a procedure, not a procedure.

| Condition                     | Sample value | Remarks |
|-------------------------------|--------------|---------|
| Wing Anti-Ice advisory        | 99 units     | Monitor |
| Fuel Crossfeed status message | 44 units     | Normal  |



|                                     |          |                        |
|-------------------------------------|----------|------------------------|
| Weather Radar indication            | 45 units | Advisory only          |
| Wing Anti-Ice switch position       | 49 units | Refer to related topic |
| Ground Proximity Monitor indication | 58 units | Monitor                |

The Fire Detection Loop annunciation is expected to read within the sample range of 21 to 33 units during approach. The captain will confirm any change in the Fire Detection Loop advisory and advise the other pilot when the associated caution light remains illuminated. The first officer will select any change in the Bleed Air Supply selector position and advise the other pilot when the associated caution light remains illuminated. Refer to the related topic for additional sample context.

**NOTE:** If the Weather Radar is inoperative, continue approach only after the pilot flying has reviewed the associated sample guidance. Both pilots will record any change in the Flap Position Indication indication and advise the other pilot once the checklist item is complete.

During parking, the relief pilot should announce the Traffic Advisory Display indication if a discrepancy is observed. Values in this manual are invented and must not be used for any operational purpose. The Pack Temperature Control indication is expected to read within the sample range of 86 to 95 units during takeoff. The Autopilot Channel A quantity display that differs from the expected state requires the First Officer to record the condition when operating at a sample station without ground power. The pilot flying will announce any change in the Standby Hydraulic advisory and advise the other pilot when the associated caution light remains illuminated.

During preflight, the First Officer should select the Window Heat selector position when operating at a sample station without ground power. During takeoff, the First Officer should brief the Standby Instruments advisory if a discrepancy is observed. The Flap Position Indication indication is expected to read within the sample range of 29 to 41 units during landing. The Cockpit Voice Recorder indication that differs from the expected state requires the pilot flying to select the condition when operating at a sample station without ground power. Values in this manual are invented and must not be used for any operational purpose. See 08.10.8 Cabin Pressure Controller Normal Operation.

**18.20.16 Hydraulic System A Status Messages**

The first officer will announce any change in the Landing Gear Indication status message and advise the other pilot when operating at a sample station without ground power. Both pilots will monitor any change in the Autothrottle advisory and advise the other pilot before the next phase of flight. The Autobrake Selector indication is expected to read within the sample range of 16 to 28 units during landing. The Ground Proximity Monitor annunciation is expected to read within the sample range of 62 to 72 units during an extended ground delay. Refer to the related topic for additional sample context. The Autothrottle annunciation is expected to read within the sample range of 20 to 31 units during an extended ground delay.

If the Autopilot Channel B is inoperative, continue engine start only after both pilots has reviewed the associated sample guidance. The Flight Management Computer quantity display that differs from the expected state requires the pilot monitoring to verify the condition when conditions permit. The wording here is placeholder content shaped like a procedure, not a procedure. This text is fictional and exists only to give the prototype realistic volume and structure. The Autothrottle status message is expected to read within the sample range of 58 to 61 units during a diversion. If the Nosewheel Steering is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance.

**CAUTION:** During cruise, the pilot flying should cross-check the Speedbrake Handle indication if the indication does not stabilize within the sample interval. The Hydraulic System B indication that differs from the expected state requires the Captain to monitor the condition if the indication does not stabilize within the sample interval.

The wording here is placeholder content shaped like a procedure, not a procedure. The Fire Detection Loop quantity display is expected to read within the sample range of 37 to 48 units during landing. Values in this manual are invented and must not be used for any operational purpose. The pilot flying will monitor any change in the Autopilot Channel A annunciation and advise the other pilot once the checklist item is complete. During engine start, the First Officer should monitor the Speedbrake Handle advisory when operating at a sample station without ground power.

The Engine Anti-Ice switch position is expected to read within the sample range of 80 to 85 units during a diversion.

**CAUTION:** During taxi, the First Officer should brief the Hydraulic System A status message before the next phase of flight.

If the Cargo Smoke Detection is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance. The Autopilot Channel B quantity display that differs from the expected state requires both pilots to cross-check the condition when the associated caution light remains illuminated. The Primary Electrical Bus quantity display that differs from the expected state requires the relief pilot to brief the condition when the associated caution light remains illuminated. The Ground Proximity Monitor selector position is expected to read within the sample range of 44 to 50 units during engine start. If the Window Heat is inoperative, continue landing only after the relief pilot has reviewed the associated sample guidance.

During landing, the First Officer should verify the Brake Temperature Monitor status message when the associated caution light remains illuminated. The Traffic Advisory Display quantity display is expected to read within the sample range of 28 to 37 units during descent. During takeoff, the pilot flying should brief the Auxiliary Power Unit indication when the associated caution light remains illuminated.

If the Landing Gear Indication is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance. Refer to the related topic for additional sample context. The Auxiliary Power Unit selector position is expected to read within the sample range of 93 to 101 units during a diversion. The wording here is placeholder content shaped like a procedure, not a procedure. If the Center Tank Pumps is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance. The Standby Instruments status message that differs from the expected state requires the relief pilot to monitor the condition when conditions permit.

| Condition                                 | Sample value | Remarks       |
|-------------------------------------------|--------------|---------------|
| Weather Radar selector position           | 33 units     | Advisory only |
| Traffic Advisory Display quantity display | 34 units     | Normal        |
| Flight Management Computer advisory       | 10 units     | Monitor       |
| Cockpit Voice Recorder advisory           | 52 units     | Monitor       |
| Standby Instruments annunciation          | 91 units     | Normal        |
| Standby Hydraulic quantity display        | 41 units     | Normal        |

## 18.30 Operation

### 18.30.1 Brake Temperature Monitor Crew Awareness

The Hydraulic System B annunciation is expected to read within the sample range of 82 to 87 units during landing. The Engine Anti-Ice indication that differs from the expected state requires the First Officer to select the condition unless directed otherwise by the Sample Operations Center. The wording here is placeholder content shaped like a procedure, not a procedure. Refer to the related topic for additional sample context.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Traffic Advisory Display quantity display | 78 units     | Normal                 |
| Thrust Reverser quantity display          | 38 units     | Refer to related topic |
| Nosewheel Steering selector position      | 5 units      | Refer to related topic |
| Cockpit Voice Recorder advisory           | 60 units     | Monitor                |
| Brake Temperature Monitor indication      | 45 units     | Normal                 |

This text is fictional and exists only to give the prototype realistic volume and structure. During engine start, the pilot monitoring should select the Bleed Air Supply annunciation if a discrepancy is observed. During landing, the First Officer should record the Auxiliary Power Unit advisory when the associated caution light remains illuminated.

Both pilots will announce any change in the Flight Management Computer annunciation and advise the other pilot if the indication does not stabilize within the sample interval. The Engine Anti-Ice status message that differs from the expected state requires the Captain to verify the condition if a discrepancy is observed. The first officer will confirm any change in the Nosewheel Steering annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center. If the Thrust Reverser is inoperative, continue landing only after the pilot monitoring has reviewed the associated sample guidance. The Cargo Smoke Detection selector position that differs from the expected state requires both pilots to verify the condition once the checklist item is complete.

Values in this manual are invented and must not be used for any operational purpose. The Wing Anti-Ice quantity display that differs from the expected state requires the First Officer to announce the condition unless directed otherwise by the Sample Operations Center. If the Window Heat is inoperative, continue takeoff only after the First Officer has reviewed the associated sample guidance.

| Condition                              | Sample value | Remarks                |
|----------------------------------------|--------------|------------------------|
| Autopilot Channel B selector position  | 18 units     | Normal                 |
| Primary Electrical Bus status message  | 36 units     | Refer to related topic |
| Landing Gear Indication status message | 50 units     | Advisory only          |

The Fire Detection Loop indication that differs from the expected state requires the pilot monitoring to record the condition if the indication does not stabilize within the sample interval. If the Window Heat is inoperative, continue cruise only after the First Officer has reviewed the associated sample guidance. If the Engine Anti-Ice is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance.

**NOTE:** The wording here is placeholder content shaped like a procedure, not a procedure. The Engine Anti-Ice quantity display is expected to read within the sample range of 24 to 33 units during a diversion.

18.30.2 Transponder Overview

If the Autopilot Channel B is inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance. The Engine Anti-Ice indication is expected to read within the sample range of 44 to 47 units during takeoff. The wording here is placeholder content shaped like a procedure, not a procedure. Both pilots will verify any change in the Pack Temperature Control selector position and advise the other pilot when conditions permit. Refer to the related topic for additional sample context.

If the Ground Proximity Monitor is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance. If the Speedbrake Handle is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance. If the Stall Warning is inoperative, continue parking only after both pilots has reviewed the associated sample guidance.

**NOTE:** Refer to the related topic for additional sample context.

| Condition                         | Sample value | Remarks                |
|-----------------------------------|--------------|------------------------|
| Cockpit Voice Recorder indication | 4 units      | Advisory only          |
| Nosewheel Steering status message | 67 units     | Refer to related topic |
| Hydraulic System A annunciation   | 44 units     | Advisory only          |

**NOTE:** The Hydraulic System B quantity display that differs from the expected state requires the First Officer to confirm the condition when operating at a sample station without ground power. During parking, the Captain should confirm the Fuel Crossfeed quantity display unless directed otherwise by the Sample Operations Center.

- During engine start, the pilot flying should announce the Cargo Smoke Detection indication when the associated caution light remains illuminated.
- The pilot flying will select any change in the Window Heat indication and advise the other pilot if the indication does not stabilize within the sample interval.

- The first officer will announce any change in the Auxiliary Power Unit selector position and advise the other pilot when operating at a sample station without ground power.
- The relief pilot will cross-check any change in the Autopilot Channel A advisory and advise the other pilot unless directed otherwise by the Sample Operations Center.
- During landing, both pilots should select the Center Tank Pumps annunciation when the associated caution light remains illuminated.
- If the Autothrottle is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance.
- Values in this manual are invented and must not be used for any operational purpose.
- The pilot flying will select any change in the Stall Warning annunciation and advise the other pilot once the checklist item is complete.

### **18.30.3 Brake Temperature Monitor Interfaces**

During a maintenance-requested ground run, the pilot monitoring should brief the Brake Temperature Monitor quantity display when conditions permit. The Landing Gear Indication quantity display that differs from the expected state requires both pilots to cross-check the condition when operating at a sample station without ground power. Refer to the related topic for additional sample context. During taxi, the pilot flying should select the Hydraulic System B quantity display if the indication does not stabilize within the sample interval.

During cruise, the relief pilot should record the Cabin Pressure Controller annunciation before the next phase of flight. During parking, both pilots should select the Speedbrake Handle selector position before the next phase of flight. The Center Tank Pumps quantity display that differs from the expected state requires the Captain to select the condition unless directed otherwise by the Sample Operations Center.

This text is fictional and exists only to give the prototype realistic volume and structure. The Cockpit Voice Recorder selector position that differs from the expected state requires the Captain to verify the condition if a discrepancy is observed. The pilot monitoring will cross-check any change in the Auxiliary Power Unit quantity display and advise the other pilot before the next phase of flight. During a turnaround, the relief pilot should record the Ground Proximity Monitor status message if the indication does not stabilize within the sample interval. If the Autobrake Selector is inoperative, continue taxi only after the Captain has reviewed the associated sample guidance.

- Refer to the related topic for additional sample context.
- If the Thrust Reverser is inoperative, continue a maintenance-requested ground run only after the pilot monitoring has reviewed the associated sample guidance.
- If the Cabin Pressure Controller is inoperative, continue engine start only after the relief pilot has reviewed the associated sample guidance.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- This text is fictional and exists only to give the prototype realistic volume and structure.

Refer to the related topic for additional sample context. The wording here is placeholder content shaped like a procedure, not a procedure. During parking, the First Officer should monitor the Cargo Smoke Detection status message when the associated caution light remains illuminated. The Oxygen Distribution switch position that differs from the expected state requires the Captain to cross-check the condition if a discrepancy is observed.

### **18.30.4 Probe Heat Normal Operation**

The Thrust Reverser selector position that differs from the expected state requires the First Officer to cross-check the condition when conditions permit. The pilot monitoring will brief any change in the Fuel Crossfeed quantity display and advise the other pilot if a discrepancy is observed. The first officer will record any change in the Center Tank Pumps selector position and advise the other pilot when conditions permit. During climb, the pilot flying should

announce the Auxiliary Power Unit annunciation if a discrepancy is observed. The Cabin Pressure Controller switch position is expected to read within the sample range of 65 to 75 units during preflight. The Stall Warning advisory is expected to read within the sample range of 17 to 29 units during a turnaround.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Auxiliary Power Unit indication       | 54 units     | Refer to related topic |
| Standby Instruments indication        | 33 units     | Advisory only          |
| Fire Detection Loop selector position | 95 units     | Normal                 |
| Window Heat advisory                  | 83 units     | Refer to related topic |
| Engine Anti-Ice selector position     | 52 units     | Advisory only          |
| Nosewheel Steering switch position    | 1 units      | Monitor                |

- The Autopilot Channel A indication that differs from the expected state requires the pilot flying to cross-check the condition when conditions permit.
- The pilot flying will select any change in the Flap Position Indication switch position and advise the other pilot if a discrepancy is observed.
- Refer to the related topic for additional sample context.

Values in this manual are invented and must not be used for any operational purpose. Values in this manual are invented and must not be used for any operational purpose. The first officer will select any change in the Hydraulic System B selector position and advise the other pilot once the checklist item is complete. If the Cabin Pressure Controller is inoperative, continue parking only after the Captain has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. During approach, the Captain should select the Standby Instruments indication before the next phase of flight.

**CAUTION:** The captain will select any change in the Cockpit Voice Recorder selector position and advise the other pilot when the associated caution light remains illuminated.

Values in this manual are invented and must not be used for any operational purpose. The Pack Temperature Control indication is expected to read within the sample range of 67 to 74 units during takeoff. The Center Tank Pumps status message is expected to read within the sample range of 85 to 95 units during taxi. The Stall Warning status message that differs from the expected state requires the pilot monitoring to verify the condition before the next phase of flight. See 05.30.3 Autopilot Channel B Overview.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Wing Anti-Ice indication                | 39 units     | Advisory only          |
| Autopilot Channel B status message      | 62 units     | Monitor                |
| Weather Radar indication                | 60 units     | Refer to related topic |
| Autopilot Channel A annunciation        | 71 units     | Refer to related topic |
| Primary Electrical Bus advisory         | 6 units      | Normal                 |
| Cockpit Voice Recorder quantity display | 89 units     | Refer to related topic |
| Standby Hydraulic advisory              | 22 units     | Advisory only          |

- The wording here is placeholder content shaped like a procedure, not a procedure.
- During landing, the First Officer should announce the Transponder status message if a discrepancy is observed.
- During taxi, the relief pilot should cross-check the Auxiliary Power Unit advisory unless directed otherwise by the Sample Operations Center.

- If the Standby Instruments is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance.
- If the Engine Anti-Ice is inoperative, continue parking only after the relief pilot has reviewed the associated sample guidance.

| Condition                            | Sample value | Remarks                |
|--------------------------------------|--------------|------------------------|
| Auxiliary Power Unit switch position | 29 units     | Monitor                |
| Engine Anti-Ice switch position      | 57 units     | Normal                 |
| Speedbrake Handle annunciation       | 33 units     | Monitor                |
| Speedbrake Handle annunciation       | 67 units     | Refer to related topic |

### 18.30.5 Nosewheel Steering Test

If the Center Tank Pumps is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance. During a turnaround, the pilot flying should cross-check the Cabin Pressure Controller quantity display if the indication does not stabilize within the sample interval. During engine start, the First Officer should announce the Standby Instruments quantity display if a discrepancy is observed. The wording here is placeholder content shaped like a procedure, not a procedure.

Both pilots will verify any change in the Flap Position Indication advisory and advise the other pilot once the checklist item is complete. This text is fictional and exists only to give the prototype realistic volume and structure. If the Standby Hydraulic is inoperative, continue engine start only after both pilots has reviewed the associated sample guidance. During a diversion, the relief pilot should monitor the Fuel Crossfeed annunciation if a discrepancy is observed.

**NOTE:** During descent, both pilots should announce the Pack Temperature Control status message if a discrepancy is observed. Refer to the related topic for additional sample context.

If the Speedbrake Handle is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance. The Fire Detection Loop selector position that differs from the expected state requires the pilot flying to record the condition when operating at a sample station without ground power. Refer to the related topic for additional sample context. If the Probe Heat is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance. The Flap Position Indication annunciation that differs from the expected state requires the pilot monitoring to announce the condition if the indication does not stabilize within the sample interval. If the Transponder is inoperative, continue climb only after the relief pilot has reviewed the associated sample guidance. See 16.10.13 Ground Proximity Monitor Test.

**NOTE:** During descent, the pilot flying should brief the Thrust Reverser indication if a discrepancy is observed. The Autopilot Channel B quantity display is expected to read within the sample range of 67 to 74 units during approach.

**NOTE:** Values in this manual are invented and must not be used for any operational purpose.

### 18.30.6 Stall Warning Normal Operation

Refer to the related topic for additional sample context. Refer to the related topic for additional sample context. Values in this manual are invented and must not be used for any operational purpose. The Autobrake Selector advisory that differs from the expected state requires the relief pilot to verify the condition unless directed otherwise by the Sample Operations Center. During engine start, the First Officer should confirm the Fire Detection Loop advisory unless directed otherwise by the Sample Operations Center. The Traffic Advisory Display annunciation that differs from the expected state requires both pilots to select the condition when conditions permit.

**NOTE:** Refer to the related topic for additional sample context. The wording here is placeholder content shaped like a procedure, not a procedure.

- The wording here is placeholder content shaped like a procedure, not a procedure.



- The captain will monitor any change in the Engine Anti-Ice switch position and advise the other pilot unless directed otherwise by the Sample Operations Center.
- The first officer will confirm any change in the Ground Proximity Monitor status message and advise the other pilot once the checklist item is complete.
- The Wing Anti-Ice selector position that differs from the expected state requires the pilot flying to select the condition when conditions permit.

The Auxiliary Power Unit switch position is expected to read within the sample range of 58 to 62 units during an extended ground delay. If the Autopilot Channel B is inoperative, continue an extended ground delay only after the Captain has reviewed the associated sample guidance. If the Thrust Reverser is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance. The Flap Position Indication quantity display is expected to read within the sample range of 35 to 41 units during climb.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Window Heat advisory                     | 77 units     | Refer to related topic |
| Cargo Smoke Detection indication         | 16 units     | Normal                 |
| Flight Management Computer indication    | 12 units     | Monitor                |
| Brake Temperature Monitor status message | 63 units     | Advisory only          |
| Probe Heat status message                | 49 units     | Advisory only          |
| Window Heat switch position              | 11 units     | Normal                 |
| Stall Warning switch position            | 47 units     | Advisory only          |

The Standby Hydraulic status message is expected to read within the sample range of 21 to 33 units during approach. The Fuel Crossfeed status message that differs from the expected state requires the relief pilot to cross-check the condition before the next phase of flight. During an extended ground delay, the First Officer should confirm the Autopilot Channel A indication once the checklist item is complete. The Thrust Reverser status message is expected to read within the sample range of 70 to 82 units during parking. The captain will verify any change in the Auxiliary Power Unit annunciation and advise the other pilot if a discrepancy is observed. See 12.10.7 Fire Detection Loop Indications.

- During descent, the First Officer should select the Engine Anti-Ice annunciation when operating at a sample station without ground power.
- During taxi, the pilot flying should verify the Brake Temperature Monitor quantity display when operating at a sample station without ground power.
- Both pilots will monitor any change in the Stall Warning switch position and advise the other pilot before the next phase of flight.
- During engine start, the pilot monitoring should select the Weather Radar status message when conditions permit.

### 18.30.7 Speedbrake Handle Interfaces

The Speedbrake Handle indication that differs from the expected state requires the Captain to confirm the condition if a discrepancy is observed. If the Hydraulic System B is inoperative, continue taxi only after the First Officer has reviewed the associated sample guidance. During approach, both pilots should confirm the Brake Temperature Monitor advisory when the associated caution light remains illuminated. The Standby Instruments status message is expected to read within the sample range of 79 to 82 units during approach. The pilot monitoring will brief any change in the Cabin Pressure Controller advisory and advise the other pilot if the indication does not stabilize within the sample interval. The Hydraulic System A switch position that differs from the expected state requires the pilot monitoring to verify the condition if a discrepancy is observed.

**NOTE:** Both pilots will verify any change in the Landing Gear Indication annunciation and advise the other pilot when conditions permit.

The Probe Heat switch position that differs from the expected state requires the Captain to monitor the condition when the associated caution light remains illuminated. If the Transponder is inoperative, continue landing only after the First Officer has reviewed the associated sample guidance. During a turnaround, both pilots should record the Thrust Reverser advisory before the next phase of flight. During parking, the Captain should monitor the Stall Warning quantity display when the associated caution light remains illuminated. During engine start, the Captain should monitor the Wing Anti-Ice status message when operating at a sample station without ground power. If the Center Tank Pumps is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance.

During a diversion, the Captain should cross-check the Autothrottle quantity display when operating at a sample station without ground power. If the Fuel Crossfeed is inoperative, continue engine start only after both pilots has reviewed the associated sample guidance. The Primary Electrical Bus annunciation that differs from the expected state requires the Captain to record the condition unless directed otherwise by the Sample Operations Center. The Engine Anti-Ice status message is expected to read within the sample range of 3 to 11 units during approach.

- The Ground Proximity Monitor indication is expected to read within the sample range of 37 to 41 units during descent.
- The Nosewheel Steering annunciation is expected to read within the sample range of 75 to 83 units during a diversion.
- Refer to the related topic for additional sample context.
- During a diversion, the pilot flying should select the Thrust Reverser quantity display once the checklist item is complete.
- If the Flight Management Computer is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance.
- Refer to the related topic for additional sample context.

**NOTE:** The pilot flying will record any change in the Fire Detection Loop indication and advise the other pilot if a discrepancy is observed. Values in this manual are invented and must not be used for any operational purpose.

### **18.30.8 Speedbrake Handle Reset Guidance**

The Brake Temperature Monitor advisory is expected to read within the sample range of 69 to 76 units during approach. During climb, both pilots should cross-check the Flight Management Computer annunciation when operating at a sample station without ground power. If the Autopilot Channel A is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. Refer to the related topic for additional sample context.

The wording here is placeholder content shaped like a procedure, not a procedure. Refer to the related topic for additional sample context. The relief pilot will monitor any change in the Weather Radar annunciation and advise the other pilot when the associated caution light remains illuminated. The pilot monitoring will record any change in the Standby Hydraulic status message and advise the other pilot before the next phase of flight.

The relief pilot will brief any change in the Autobrake Selector indication and advise the other pilot if a discrepancy is observed. If the Brake Temperature Monitor is inoperative, continue an extended ground delay only after the Captain has reviewed the associated sample guidance. The Ground Proximity Monitor status message is expected to read within the sample range of 94 to 98 units during preflight. The Auxiliary Power Unit quantity display that differs from the expected state requires the pilot flying to select the condition once the checklist item is complete.

The Hydraulic System A advisory is expected to read within the sample range of 24 to 28 units during takeoff. The pilot flying will announce any change in the Nosewheel Steering selector position and advise the other pilot once the

checklist item is complete. If the Wing Anti-Ice is inoperative, continue takeoff only after both pilots has reviewed the associated sample guidance. Refer to the related topic for additional sample context. During a diversion, the Captain should verify the Engine Anti-Ice advisory when conditions permit. The Bleed Air Supply status message that differs from the expected state requires both pilots to announce the condition unless directed otherwise by the Sample Operations Center. See 05.30.3 Autopilot Channel B Overview.

**NOTE:** The Primary Electrical Bus indication that differs from the expected state requires the relief pilot to monitor the condition when operating at a sample station without ground power.

**18.30.9 New Sample Topic: Thrust Reverser**

This text is fictional and exists only to give the prototype realistic volume and structure. The Flight Management Computer advisory is expected to read within the sample range of 94 to 99 units during parking. If the Weather Radar is inoperative, continue a maintenance-requested ground run only after both pilots has reviewed the associated sample guidance.

- The Autothrottle indication is expected to read within the sample range of 32 to 35 units during parking.
- The Engine Anti-Ice quantity display that differs from the expected state requires the First Officer to select the condition if the indication does not stabilize within the sample interval.
- If the Standby Hydraulic is inoperative, continue approach only after the pilot monitoring has reviewed the associated sample guidance.

**CAUTION:** The Oxygen Distribution selector position is expected to read within the sample range of 65 to 77 units during engine start.

- This text is fictional and exists only to give the prototype realistic volume and structure.
- During parking, the pilot monitoring should brief the Cabin Pressure Controller advisory if a discrepancy is observed.
- The pilot flying will announce any change in the Landing Gear Indication advisory and advise the other pilot unless directed otherwise by the Sample Operations Center.
- If the Bleed Air Supply is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance.

| Condition                                 | Sample value | Remarks       |
|-------------------------------------------|--------------|---------------|
| Bleed Air Supply advisory                 | 62 units     | Advisory only |
| Traffic Advisory Display quantity display | 45 units     | Monitor       |
| Autobrake Selector status message         | 67 units     | Advisory only |
| Autothrottle switch position              | 59 units     | Advisory only |
| Autopilot Channel B advisory              | 28 units     | Advisory only |
| Pack Temperature Control advisory         | 68 units     | Normal        |

The Fire Detection Loop indication is expected to read within the sample range of 49 to 57 units during parking. Refer to the related topic for additional sample context. Values in this manual are invented and must not be used for any operational purpose. During parking, both pilots should announce the Autopilot Channel A status message if the indication does not stabilize within the sample interval. The pilot flying will confirm any change in the Weather Radar selector position and advise the other pilot if a discrepancy is observed.

**18.30.10 Hydraulic System B Reset Guidance**

The Standby Hydraulic annunciation is expected to read within the sample range of 30 to 38 units during engine start. During parking, the First Officer should brief the Bleed Air Supply annunciation unless directed otherwise by the

Sample Operations Center. This text is fictional and exists only to give the prototype realistic volume and structure. The Ground Proximity Monitor advisory that differs from the expected state requires the Captain to confirm the condition when conditions permit. See 09.30.15 Nosewheel Steering Overview.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Hydraulic System B indication         | 28 units     | Refer to related topic |
| Wing Anti-Ice selector position       | 88 units     | Refer to related topic |
| Center Tank Pumps status message      | 46 units     | Monitor                |
| Hydraulic System A annunciation       | 89 units     | Refer to related topic |
| Window Heat annunciation              | 12 units     | Advisory only          |
| Primary Electrical Bus status message | 52 units     | Advisory only          |

| Condition                               | Sample value | Remarks |
|-----------------------------------------|--------------|---------|
| Nosewheel Steering switch position      | 56 units     | Monitor |
| Fire Detection Loop status message      | 47 units     | Monitor |
| Primary Electrical Bus quantity display | 80 units     | Monitor |
| Autopilot Channel B quantity display    | 79 units     | Normal  |
| Window Heat status message              | 31 units     | Monitor |
| Window Heat annunciation                | 82 units     | Monitor |
| Autobrake Selector quantity display     | 89 units     | Normal  |

**CAUTION:** The wording here is placeholder content shaped like a procedure, not a procedure.

| Condition                           | Sample value | Remarks                |
|-------------------------------------|--------------|------------------------|
| Flap Position Indication indication | 88 units     | Monitor                |
| Weather Radar quantity display      | 93 units     | Advisory only          |
| Thrust Reverser annunciation        | 78 units     | Refer to related topic |
| Ground Proximity Monitor advisory   | 90 units     | Monitor                |

**CAUTION:** If the Speedbrake Handle is inoperative, continue landing only after both pilots has reviewed the associated sample guidance.

- During a diversion, both pilots should record the Engine Anti-Ice quantity display once the checklist item is complete.
- The Cargo Smoke Detection advisory that differs from the expected state requires the relief pilot to record the condition if the indication does not stabilize within the sample interval.
- The captain will monitor any change in the Transponder switch position and advise the other pilot if a discrepancy is observed.
- During climb, the pilot monitoring should brief the Thrust Reverser advisory if a discrepancy is observed.

**CAUTION:** The Autobrake Selector annunciation is expected to read within the sample range of 6 to 14 units during climb. During taxi, the Captain should record the Standby Instruments quantity display if the indication does not stabilize within the sample interval.

### 18.30.11 Primary Electrical Bus Limits Display

The Stall Warning status message is expected to read within the sample range of 67 to 75 units during approach. Both pilots will monitor any change in the Transponder annunciation and advise the other pilot if the indication does

not stabilize within the sample interval. If the Autothrottle is inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance.

**CAUTION:** The relief pilot will monitor any change in the Auxiliary Power Unit selector position and advise the other pilot when operating at a sample station without ground power. If the Bleed Air Supply is inoperative, continue engine start only after the pilot flying has reviewed the associated sample guidance.

The Cargo Smoke Detection indication is expected to read within the sample range of 25 to 34 units during climb. The Transponder quantity display that differs from the expected state requires the pilot flying to verify the condition unless directed otherwise by the Sample Operations Center. The Transponder indication that differs from the expected state requires both pilots to select the condition if a discrepancy is observed.

The Autopilot Channel B switch position is expected to read within the sample range of 28 to 37 units during a diversion. The captain will monitor any change in the Standby Instruments quantity display and advise the other pilot if a discrepancy is observed. The captain will verify any change in the Autothrottle status message and advise the other pilot once the checklist item is complete.

During a diversion, the relief pilot should verify the Cargo Smoke Detection annunciation once the checklist item is complete. The Autobrake Selector status message is expected to read within the sample range of 96 to 104 units during an extended ground delay. If the Autobrake Selector is inoperative, continue descent only after both pilots has reviewed the associated sample guidance. The pilot flying will select any change in the Wing Anti-Ice selector position and advise the other pilot when conditions permit. During approach, the pilot monitoring should cross-check the Window Heat quantity display when conditions permit. Refer to the related topic for additional sample context.

The Flight Management Computer annunciation is expected to read within the sample range of 60 to 71 units during parking. The Hydraulic System B quantity display is expected to read within the sample range of 60 to 69 units during cruise. If the Fuel Crossfeed is inoperative, continue an extended ground delay only after the pilot flying has reviewed the associated sample guidance.

| Condition                              | Sample value | Remarks                |
|----------------------------------------|--------------|------------------------|
| Brake Temperature Monitor indication   | 6 units      | Refer to related topic |
| Auxiliary Power Unit selector position | 73 units     | Refer to related topic |
| Nosewheel Steering switch position     | 92 units     | Normal                 |
| Autopilot Channel B switch position    | 73 units     | Refer to related topic |
| Weather Radar annunciation             | 12 units     | Normal                 |
| Wing Anti-Ice status message           | 70 units     | Normal                 |

**NOTE:** The Autobrake Selector selector position is expected to read within the sample range of 95 to 98 units during an extended ground delay. If the Primary Electrical Bus is inoperative, continue landing only after the Captain has reviewed the associated sample guidance.

This text is fictional and exists only to give the prototype realistic volume and structure. The Transponder indication is expected to read within the sample range of 98 to 110 units during approach. The Fire Detection Loop indication that differs from the expected state requires the relief pilot to select the condition when conditions permit. The captain will announce any change in the Probe Heat switch position and advise the other pilot when the associated caution light remains illuminated. The Probe Heat switch position is expected to read within the sample range of 58 to 68 units during a turnaround.

**18.30.12 Auxiliary Power Unit Status Messages**

The Cabin Pressure Controller indication is expected to read within the sample range of 16 to 28 units during climb. The Standby Instruments annunciation is expected to read within the sample range of 20 to 25 units during climb. The relief pilot will verify any change in the Bleed Air Supply switch position and advise the other pilot before the next phase of flight.

**CAUTION:** The captain will confirm any change in the Hydraulic System A switch position and advise the other pilot when conditions permit.

The first officer will record any change in the Engine Anti-Ice selector position and advise the other pilot when conditions permit. If the Autopilot Channel A is inoperative, continue takeoff only after both pilots has reviewed the associated sample guidance. The Flight Management Computer annunciation is expected to read within the sample range of 41 to 49 units during a turnaround. The pilot monitoring will announce any change in the Ground Proximity Monitor switch position and advise the other pilot when operating at a sample station without ground power.

**NOTE:** If the Standby Instruments is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance.

**CAUTION:** The pilot monitoring will brief any change in the Fire Detection Loop advisory and advise the other pilot if a discrepancy is observed. If the Weather Radar is inoperative, continue taxi only after the First Officer has reviewed the associated sample guidance.

**NOTE:** This text is fictional and exists only to give the prototype realistic volume and structure. During approach, the First Officer should brief the Thrust Reverser advisory if the indication does not stabilize within the sample interval.

**NOTE:** Both pilots will select any change in the Cabin Pressure Controller quantity display and advise the other pilot when conditions permit.

| Condition                             | Sample value | Remarks       |
|---------------------------------------|--------------|---------------|
| Weather Radar indication              | 97 units     | Advisory only |
| Probe Heat indication                 | 23 units     | Normal        |
| Hydraulic System A switch position    | 81 units     | Normal        |
| Cargo Smoke Detection switch position | 51 units     | Advisory only |

The Speedbrake Handle advisory is expected to read within the sample range of 81 to 90 units during cruise. During a maintenance-requested ground run, the pilot monitoring should record the Autothrottle indication when operating at a sample station without ground power. The pilot flying will verify any change in the Standby Hydraulic status message and advise the other pilot before the next phase of flight. The Probe Heat annunciation that differs from the expected state requires both pilots to announce the condition once the checklist item is complete. During approach, the pilot monitoring should cross-check the Flight Management Computer annunciation when conditions permit.

**18.30.13    Nosewheel Steering Overview**

During a turnaround, the pilot monitoring should select the Bleed Air Supply indication before the next phase of flight. If the Weather Radar is inoperative, continue landing only after the First Officer has reviewed the associated sample guidance. The Thrust Reverser selector position is expected to read within the sample range of 84 to 90 units during landing. The Landing Gear Indication quantity display that differs from the expected state requires the relief pilot to record the condition once the checklist item is complete.

**NOTE:** During engine start, the relief pilot should record the Primary Electrical Bus switch position unless directed otherwise by the Sample Operations Center. The Cabin Pressure Controller quantity display is expected to read within the sample range of 45 to 57 units during a turnaround.

**CAUTION:** This text is fictional and exists only to give the prototype realistic volume and structure. The pilot flying will announce any change in the Pack Temperature Control switch position and advise the other pilot when the associated caution light remains illuminated.

**CAUTION:** If the Flap Position Indication is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance. The Engine Anti-Ice status message that differs from the expected state requires the pilot monitoring to verify the condition if the indication does not stabilize within the sample interval.



- The Autopilot Channel B quantity display is expected to read within the sample range of 31 to 38 units during a maintenance-requested ground run.
- Values in this manual are invented and must not be used for any operational purpose.
- Both pilots will select any change in the Flight Management Computer advisory and advise the other pilot once the checklist item is complete.

The first officer will verify any change in the Traffic Advisory Display selector position and advise the other pilot when operating at a sample station without ground power. The Autopilot Channel B indication that differs from the expected state requires the Captain to monitor the condition when conditions permit. The Cargo Smoke Detection selector position is expected to read within the sample range of 56 to 59 units during cruise. If the Cockpit Voice Recorder is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance. The Nosewheel Steering quantity display that differs from the expected state requires the pilot monitoring to brief the condition when the associated caution light remains illuminated.

The Flight Management Computer selector position that differs from the expected state requires both pilots to monitor the condition if a discrepancy is observed. The Wing Anti-Ice status message is expected to read within the sample range of 28 to 34 units during climb. The Cockpit Voice Recorder advisory that differs from the expected state requires the relief pilot to brief the condition if the indication does not stabilize within the sample interval. The Standby Hydraulic annunciation is expected to read within the sample range of 42 to 51 units during approach. The Flight Management Computer advisory is expected to read within the sample range of 75 to 81 units during an extended ground delay. Values in this manual are invented and must not be used for any operational purpose.

| Condition                              | Sample value | Remarks                |
|----------------------------------------|--------------|------------------------|
| Autothrottle annunciation              | 54 units     | Normal                 |
| Standby Hydraulic indication           | 57 units     | Normal                 |
| Auxiliary Power Unit selector position | 42 units     | Refer to related topic |
| Flight Management Computer indication  | 18 units     | Monitor                |
| Fire Detection Loop quantity display   | 53 units     | Advisory only          |

**NOTE:** If the Standby Instruments is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance. The Autopilot Channel B quantity display that differs from the expected state requires the Captain to record the condition once the checklist item is complete.

**18.30.14 Center Tank Pumps Overview**

During landing, the First Officer should record the Cabin Pressure Controller indication when operating at a sample station without ground power. This text is fictional and exists only to give the prototype realistic volume and structure. The Oxygen Distribution quantity display is expected to read within the sample range of 73 to 82 units during cruise.

**NOTE:** The Brake Temperature Monitor indication that differs from the expected state requires both pilots to confirm the condition when the associated caution light remains illuminated.

| Condition                             | Sample value | Remarks |
|---------------------------------------|--------------|---------|
| Auxiliary Power Unit quantity display | 90 units     | Normal  |
| Pack Temperature Control indication   | 42 units     | Monitor |
| Autobrake Selector quantity display   | 65 units     | Monitor |

- During climb, the relief pilot should verify the Wing Anti-Ice indication when conditions permit.
- The Auxiliary Power Unit selector position is expected to read within the sample range of 43 to 53 units during engine start.

- During descent, the pilot monitoring should select the Cockpit Voice Recorder advisory when operating at a sample station without ground power.

The Transponder selector position that differs from the expected state requires the relief pilot to announce the condition when the associated caution light remains illuminated. The Traffic Advisory Display indication is expected to read within the sample range of 51 to 59 units during parking. This text is fictional and exists only to give the prototype realistic volume and structure. During landing, both pilots should record the Thrust Reverser switch position unless directed otherwise by the Sample Operations Center. See 11.10.1 Autopilot Channel A Crew Awareness.

- If the Engine Anti-Ice is inoperative, continue parking only after the Captain has reviewed the associated sample guidance.
- The Ground Proximity Monitor quantity display that differs from the expected state requires both pilots to brief the condition before the next phase of flight.
- During descent, the pilot monitoring should record the Stall Warning quantity display if a discrepancy is observed.

### **18.30.15 Stall Warning Normal Operation**

Values in this manual are invented and must not be used for any operational purpose. The Speedbrake Handle status message that differs from the expected state requires the pilot flying to select the condition if a discrepancy is observed. The first officer will brief any change in the Traffic Advisory Display status message and advise the other pilot before the next phase of flight. During engine start, the First Officer should record the Flap Position Indication indication if the indication does not stabilize within the sample interval. The Auxiliary Power Unit selector position that differs from the expected state requires the relief pilot to record the condition before the next phase of flight.

**CAUTION:** If the Thrust Reverser is inoperative, continue approach only after the pilot monitoring has reviewed the associated sample guidance. During an extended ground delay, the First Officer should brief the Wing Anti-Ice advisory before the next phase of flight.

The captain will confirm any change in the Transponder status message and advise the other pilot when conditions permit. The Primary Electrical Bus quantity display is expected to read within the sample range of 52 to 55 units during climb. The Speedbrake Handle switch position that differs from the expected state requires the pilot monitoring to brief the condition when operating at a sample station without ground power. If the Pack Temperature Control is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance. If the Traffic Advisory Display is inoperative, continue engine start only after the relief pilot has reviewed the associated sample guidance.

- If the Nosewheel Steering is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The Weather Radar advisory is expected to read within the sample range of 62 to 65 units during cruise.
- Values in this manual are invented and must not be used for any operational purpose.

**CAUTION:** During a maintenance-requested ground run, the pilot flying should announce the Traffic Advisory Display advisory before the next phase of flight. This text is fictional and exists only to give the prototype realistic volume and structure.

The first officer will announce any change in the Flight Management Computer indication and advise the other pilot before the next phase of flight. If the Engine Anti-Ice is inoperative, continue descent only after the First Officer has reviewed the associated sample guidance. If the Fuel Crossfeed is inoperative, continue a turnaround only after the First Officer has reviewed the associated sample guidance. The Center Tank Pumps advisory is expected to read within the sample range of 23 to 32 units during descent.

The Window Heat advisory is expected to read within the sample range of 66 to 77 units during takeoff. The first officer will select any change in the Nosewheel Steering status message and advise the other pilot unless directed

otherwise by the Sample Operations Center. The Transponder annunciation that differs from the expected state requires the pilot flying to select the condition if the indication does not stabilize within the sample interval. During landing, the First Officer should select the Ground Proximity Monitor annunciation if the indication does not stabilize within the sample interval. If the Engine Anti-Ice is inoperative, continue a turnaround only after the First Officer has reviewed the associated sample guidance.

**CAUTION:** During cruise, the relief pilot should select the Pack Temperature Control quantity display unless directed otherwise by the Sample Operations Center.

### 18.30.16 Cabin Pressure Controller Crew Awareness

Refer to the related topic for additional sample context. During engine start, the pilot flying should cross-check the Brake Temperature Monitor status message if the indication does not stabilize within the sample interval. Values in this manual are invented and must not be used for any operational purpose. If the Nosewheel Steering is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance. During preflight, the pilot flying should record the Landing Gear Indication quantity display when conditions permit. This text is fictional and exists only to give the prototype realistic volume and structure.

**NOTE:** The Landing Gear Indication switch position that differs from the expected state requires the Captain to monitor the condition if a discrepancy is observed.

If the Wing Anti-Ice is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. The pilot flying will monitor any change in the Wing Anti-Ice quantity display and advise the other pilot when conditions permit.

**CAUTION:** If the Brake Temperature Monitor is inoperative, continue approach only after both pilots has reviewed the associated sample guidance.

- The relief pilot will confirm any change in the Cargo Smoke Detection indication and advise the other pilot once the checklist item is complete.
- Values in this manual are invented and must not be used for any operational purpose.
- Refer to the related topic for additional sample context.

**CAUTION:** The Bleed Air Supply advisory is expected to read within the sample range of 57 to 67 units during engine start.

The Traffic Advisory Display switch position is expected to read within the sample range of 42 to 48 units during preflight. During a turnaround, both pilots should select the Center Tank Pumps status message unless directed otherwise by the Sample Operations Center. Values in this manual are invented and must not be used for any operational purpose. The wording here is placeholder content shaped like a procedure, not a procedure. During cruise, the Captain should verify the Ground Proximity Monitor switch position when the associated caution light remains illuminated.

During taxi, the pilot flying should monitor the Hydraulic System A switch position if a discrepancy is observed. The Speedbrake Handle advisory is expected to read within the sample range of 84 to 94 units during engine start. The wording here is placeholder content shaped like a procedure, not a procedure. During descent, both pilots should verify the Hydraulic System B annunciation before the next phase of flight. The wording here is placeholder content shaped like a procedure, not a procedure. The Standby Instruments selector position that differs from the expected state requires the pilot monitoring to confirm the condition unless directed otherwise by the Sample Operations Center.

### 18.30.17 Autopilot Channel B Overview

Values in this manual are invented and must not be used for any operational purpose. This text is fictional and exists only to give the prototype realistic volume and structure. The Center Tank Pumps advisory is expected to read within the sample range of 44 to 53 units during engine start. The captain will record any change in the Primary Electrical

Bus quantity display and advise the other pilot when the associated caution light remains illuminated. This text is fictional and exists only to give the prototype realistic volume and structure.

**NOTE:** During climb, the First Officer should monitor the Speedbrake Handle advisory when conditions permit.

Refer to the related topic for additional sample context. The Stall Warning switch position that differs from the expected state requires both pilots to record the condition when the associated caution light remains illuminated. The wording here is placeholder content shaped like a procedure, not a procedure. The Autobrake Selector switch position that differs from the expected state requires both pilots to cross-check the condition if a discrepancy is observed. During cruise, the First Officer should record the Bleed Air Supply status message before the next phase of flight.

| Condition                              | Sample value | Remarks       |
|----------------------------------------|--------------|---------------|
| Engine Anti-Ice selector position      | 84 units     | Monitor       |
| Landing Gear Indication status message | 40 units     | Advisory only |
| Primary Electrical Bus switch position | 14 units     | Normal        |
| Autobrake Selector switch position     | 40 units     | Advisory only |
| Flap Position Indication indication    | 31 units     | Normal        |

If the Hydraulic System B is inoperative, continue engine start only after both pilots has reviewed the associated sample guidance. The Pack Temperature Control selector position that differs from the expected state requires the pilot monitoring to announce the condition if the indication does not stabilize within the sample interval. This text is fictional and exists only to give the prototype realistic volume and structure. If the Traffic Advisory Display is inoperative, continue a turnaround only after the First Officer has reviewed the associated sample guidance. The pilot flying will cross-check any change in the Autopilot Channel B quantity display and advise the other pilot when the associated caution light remains illuminated. During landing, the Captain should verify the Oxygen Distribution annunciation before the next phase of flight.

The Hydraulic System B selector position that differs from the expected state requires the pilot monitoring to select the condition if the indication does not stabilize within the sample interval. The Autopilot Channel A annunciation is expected to read within the sample range of 43 to 50 units during cruise. Values in this manual are invented and must not be used for any operational purpose. During descent, the pilot flying should brief the Autopilot Channel A advisory when conditions permit.

During takeoff, the pilot flying should cross-check the Flight Management Computer annunciation when the associated caution light remains illuminated. The Nosewheel Steering annunciation that differs from the expected state requires both pilots to select the condition when conditions permit. During takeoff, the Captain should select the Hydraulic System A annunciation when the associated caution light remains illuminated. The Stall Warning selector position is expected to read within the sample range of 7 to 13 units during descent.

The pilot flying will confirm any change in the Autobrake Selector indication and advise the other pilot once the checklist item is complete. If the Thrust Reverser is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance. The Engine Anti-Ice switch position that differs from the expected state requires the pilot flying to confirm the condition if a discrepancy is observed. The pilot flying will announce any change in the Ground Proximity Monitor quantity display and advise the other pilot if the indication does not stabilize within the sample interval. The pilot monitoring will cross-check any change in the Traffic Advisory Display switch position and advise the other pilot before the next phase of flight. The captain will announce any change in the Fuel Crossfeed indication and advise the other pilot once the checklist item is complete.

# Chapter 19 Performance

## 19.10 Takeoff Performance

### 19.10.1 Takeoff Performance Table 1

If the Landing Gear Indication is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance. The captain will confirm any change in the Autobrake Selector indication and advise the other pilot if a discrepancy is observed. The Flap Position Indication quantity display is expected to read within the sample range of 6 to 13 units during descent. This text is fictional and exists only to give the prototype realistic volume and structure.

**NOTE:** During takeoff, the pilot flying should cross-check the Fire Detection Loop annunciation when the associated caution light remains illuminated. Refer to the related topic for additional sample context.

**CAUTION:** The first officer will confirm any change in the Oxygen Distribution advisory and advise the other pilot when conditions permit. Values in this manual are invented and must not be used for any operational purpose.

This text is fictional and exists only to give the prototype realistic volume and structure. If the Center Tank Pumps is inoperative, continue preflight only after the relief pilot has reviewed the associated sample guidance. If the Center Tank Pumps is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance. If the Ground Proximity Monitor is inoperative, continue takeoff only after the First Officer has reviewed the associated sample guidance.

**NOTE:** If the Cargo Smoke Detection is inoperative, continue approach only after the pilot monitoring has reviewed the associated sample guidance. The Center Tank Pumps indication that differs from the expected state requires the pilot monitoring to select the condition when conditions permit.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Autobrake Selector switch position      | 5 units      | Refer to related topic |
| Primary Electrical Bus quantity display | 86 units     | Advisory only          |
| Hydraulic System A annunciation         | 30 units     | Monitor                |
| Bleed Air Supply selector position      | 61 units     | Refer to related topic |
| Autobrake Selector switch position      | 31 units     | Refer to related topic |
| Thrust Reverser advisory                | 22 units     | Refer to related topic |

This text is fictional and exists only to give the prototype realistic volume and structure. The pilot monitoring will announce any change in the Engine Anti-Ice selector position and advise the other pilot before the next phase of flight. Refer to the related topic for additional sample context. Both pilots will select any change in the Window Heat status message and advise the other pilot if the indication does not stabilize within the sample interval. If the Cabin Pressure Controller is inoperative, continue a diversion only after the First Officer has reviewed the associated sample guidance. The Autopilot Channel B quantity display that differs from the expected state requires the Captain to brief the condition once the checklist item is complete.

- The Autopilot Channel B status message that differs from the expected state requires both pilots to verify the condition when the associated caution light remains illuminated.
- The pilot flying will cross-check any change in the Nosewheel Steering advisory and advise the other pilot when the associated caution light remains illuminated.
- The Transponder annunciation that differs from the expected state requires the Captain to announce the condition if the indication does not stabilize within the sample interval.

- During approach, the Captain should cross-check the Bleed Air Supply quantity display unless directed otherwise by the Sample Operations Center.
- Values in this manual are invented and must not be used for any operational purpose.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The first officer will verify any change in the Traffic Advisory Display status message and advise the other pilot before the next phase of flight.
- The Fuel Crossfeed switch position that differs from the expected state requires the relief pilot to announce the condition once the checklist item is complete.

### 19.10.2 Takeoff Performance Table 2

During landing, the relief pilot should select the Cargo Smoke Detection indication once the checklist item is complete. If the Brake Temperature Monitor is inoperative, continue parking only after the Captain has reviewed the associated sample guidance. The Auxiliary Power Unit annunciation is expected to read within the sample range of 29 to 38 units during climb.

**CAUTION:** The Fuel Crossfeed selector position that differs from the expected state requires the First Officer to announce the condition once the checklist item is complete.

During a maintenance-requested ground run, the Captain should cross-check the Fuel Crossfeed advisory if the indication does not stabilize within the sample interval. The Thrust Reverser quantity display that differs from the expected state requires the Captain to select the condition if the indication does not stabilize within the sample interval. If the Autopilot Channel A is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance.

**NOTE:** During an extended ground delay, the relief pilot should announce the Fire Detection Loop annunciation when conditions permit. The relief pilot will select any change in the Window Heat annunciation and advise the other pilot once the checklist item is complete.

**CAUTION:** During climb, both pilots should cross-check the Wing Anti-Ice status message if a discrepancy is observed. During a maintenance-requested ground run, the pilot monitoring should select the Speedbrake Handle selector position when conditions permit.

During an extended ground delay, the pilot flying should announce the Weather Radar quantity display if the indication does not stabilize within the sample interval. Refer to the related topic for additional sample context. The Auxiliary Power Unit advisory that differs from the expected state requires the First Officer to verify the condition if a discrepancy is observed. This text is fictional and exists only to give the prototype realistic volume and structure. If the Stall Warning is inoperative, continue taxi only after the Captain has reviewed the associated sample guidance.

- The Cockpit Voice Recorder status message that differs from the expected state requires both pilots to verify the condition when conditions permit.
- The first officer will verify any change in the Weather Radar indication and advise the other pilot once the checklist item is complete.
- The Stall Warning selector position that differs from the expected state requires the relief pilot to verify the condition if the indication does not stabilize within the sample interval.
- The pilot monitoring will confirm any change in the Hydraulic System B status message and advise the other pilot when the associated caution light remains illuminated.
- Values in this manual are invented and must not be used for any operational purpose.



The relief pilot will select any change in the Autobrake Selector quantity display and advise the other pilot once the checklist item is complete. If the Autopilot Channel A is inoperative, continue climb only after the Captain has reviewed the associated sample guidance. During landing, the Captain should brief the Thrust Reverser status message before the next phase of flight. During parking, the Captain should brief the Fire Detection Loop indication if the indication does not stabilize within the sample interval. The pilot monitoring will monitor any change in the Autopilot Channel A annunciation and advise the other pilot when conditions permit. If the Flight Management Computer is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance.

### **19.10.3 Takeoff Performance Table 3**

The Autopilot Channel B indication that differs from the expected state requires the relief pilot to select the condition when the associated caution light remains illuminated. The pilot flying will brief any change in the Pack Temperature Control indication and advise the other pilot when operating at a sample station without ground power. During a diversion, the Captain should brief the Landing Gear Indication quantity display before the next phase of flight. The Autopilot Channel B advisory that differs from the expected state requires the relief pilot to record the condition when conditions permit. Refer to the related topic for additional sample context.

During preflight, the pilot flying should monitor the Thrust Reverser indication unless directed otherwise by the Sample Operations Center. During takeoff, the First Officer should select the Autobrake Selector switch position if the indication does not stabilize within the sample interval. Refer to the related topic for additional sample context. The Brake Temperature Monitor switch position that differs from the expected state requires both pilots to announce the condition before the next phase of flight. This text is fictional and exists only to give the prototype realistic volume and structure. Values in this manual are invented and must not be used for any operational purpose.

- During climb, the First Officer should announce the Speedbrake Handle indication once the checklist item is complete.
- If the Primary Electrical Bus is inoperative, continue a diversion only after the relief pilot has reviewed the associated sample guidance.
- During preflight, the Captain should confirm the Autobrake Selector indication when conditions permit.
- The Traffic Advisory Display status message is expected to read within the sample range of 3 to 13 units during landing.
- During a maintenance-requested ground run, the pilot monitoring should select the Cockpit Voice Recorder indication once the checklist item is complete.

The Flight Management Computer switch position is expected to read within the sample range of 81 to 86 units during takeoff. Refer to the related topic for additional sample context. During cruise, the Captain should cross-check the Flap Position Indication selector position if the indication does not stabilize within the sample interval. This text is fictional and exists only to give the prototype realistic volume and structure. If the Nosewheel Steering is inoperative, continue preflight only after the relief pilot has reviewed the associated sample guidance.

The Fire Detection Loop advisory is expected to read within the sample range of 43 to 49 units during approach. The pilot flying will monitor any change in the Oxygen Distribution quantity display and advise the other pilot if a discrepancy is observed. This text is fictional and exists only to give the prototype realistic volume and structure. During taxi, the relief pilot should monitor the Primary Electrical Bus quantity display when operating at a sample station without ground power. During descent, the pilot monitoring should announce the Wing Anti-Ice indication unless directed otherwise by the Sample Operations Center. If the Ground Proximity Monitor is inoperative, continue taxi only after the relief pilot has reviewed the associated sample guidance.

The relief pilot will verify any change in the Fire Detection Loop advisory and advise the other pilot if a discrepancy is observed. The wording here is placeholder content shaped like a procedure, not a procedure. The Transponder switch position is expected to read within the sample range of 80 to 88 units during engine start. The Hydraulic System B switch position that differs from the expected state requires both pilots to monitor the condition unless directed otherwise by the Sample Operations Center. During parking, the relief pilot should cross-check the Cargo

Smoke Detection selector position when conditions permit. See 05.60.11 Standby Hydraulic Status Messages.

**CAUTION:** If the Wing Anti-Ice is inoperative, continue taxi only after the pilot flying has reviewed the associated sample guidance.

| Condition                                   | Sample value | Remarks                |
|---------------------------------------------|--------------|------------------------|
| Cabin Pressure Controller selector position | 6 units      | Monitor                |
| Nosewheel Steering quantity display         | 72 units     | Monitor                |
| Standby Hydraulic annunciation              | 6 units      | Monitor                |
| Fuel Crossfeed advisory                     | 39 units     | Advisory only          |
| Flap Position Indication status message     | 95 units     | Refer to related topic |
| Cargo Smoke Detection annunciation          | 51 units     | Normal                 |

| Condition                           | Sample value | Remarks                |
|-------------------------------------|--------------|------------------------|
| Flap Position Indication indication | 29 units     | Refer to related topic |
| Speedbrake Handle indication        | 88 units     | Refer to related topic |
| Weather Radar indication            | 66 units     | Advisory only          |
| Probe Heat indication               | 58 units     | Monitor                |

19.10.4 Takeoff Performance Table 4

During a turnaround, the First Officer should verify the Flap Position Indication indication once the checklist item is complete. During preflight, the pilot monitoring should select the Fuel Crossfeed quantity display before the next phase of flight. If the Fuel Crossfeed is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance. The Autobrake Selector switch position is expected to read within the sample range of 11 to 19 units during cruise. The Nosewheel Steering selector position that differs from the expected state requires the Captain to record the condition when the associated caution light remains illuminated.

This text is fictional and exists only to give the prototype realistic volume and structure. Values in this manual are invented and must not be used for any operational purpose. If the Center Tank Pumps is inoperative, continue taxi only after the First Officer has reviewed the associated sample guidance. If the Pack Temperature Control is inoperative, continue climb only after the relief pilot has reviewed the associated sample guidance.

- Refer to the related topic for additional sample context.
- The Landing Gear Indication advisory is expected to read within the sample range of 6 to 12 units during approach.
- The Probe Heat indication that differs from the expected state requires both pilots to announce the condition once the checklist item is complete.
- During a diversion, both pilots should cross-check the Ground Proximity Monitor indication before the next phase of flight.

**CAUTION:** The captain will record any change in the Primary Electrical Bus advisory and advise the other pilot once the checklist item is complete.

- The Engine Anti-Ice status message that differs from the expected state requires the pilot monitoring to cross-check the condition before the next phase of flight.
- Values in this manual are invented and must not be used for any operational purpose.
- The Brake Temperature Monitor annunciation is expected to read within the sample range of 63 to 69 units during a turnaround.

- The pilot monitoring will cross-check any change in the Auxiliary Power Unit selector position and advise the other pilot unless directed otherwise by the Sample Operations Center.
- If the Standby Instruments is inoperative, continue parking only after the relief pilot has reviewed the associated sample guidance.
- The wording here is placeholder content shaped like a procedure, not a procedure.

**CAUTION:** The captain will cross-check any change in the Ground Proximity Monitor annunciation and advise the other pilot if the indication does not stabilize within the sample interval. The pilot flying will brief any change in the Flight Management Computer status message and advise the other pilot if the indication does not stabilize within the sample interval.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Pack Temperature Control selector position | 5 units      | Advisory only          |
| Speedbrake Handle indication               | 77 units     | Monitor                |
| Primary Electrical Bus annunciation        | 57 units     | Refer to related topic |

During a maintenance-requested ground run, both pilots should confirm the Cargo Smoke Detection status message before the next phase of flight. The Ground Proximity Monitor indication that differs from the expected state requires the pilot flying to brief the condition unless directed otherwise by the Sample Operations Center. The Traffic Advisory Display status message that differs from the expected state requires the First Officer to confirm the condition when operating at a sample station without ground power. If the Hydraulic System B is inoperative, continue a turnaround only after the pilot monitoring has reviewed the associated sample guidance. The first officer will monitor any change in the Standby Hydraulic selector position and advise the other pilot if a discrepancy is observed. During a maintenance-requested ground run, the Captain should cross-check the Auxiliary Power Unit advisory if the indication does not stabilize within the sample interval.

The wording here is placeholder content shaped like a procedure, not a procedure. The pilot monitoring will verify any change in the Fire Detection Loop switch position and advise the other pilot once the checklist item is complete. The Hydraulic System B selector position is expected to read within the sample range of 61 to 71 units during engine start. If the Thrust Reverser is inoperative, continue preflight only after the Captain has reviewed the associated sample guidance. During taxi, the First Officer should verify the Fire Detection Loop status message once the checklist item is complete.

19.10.5 Takeoff Performance Table 5

During approach, the Captain should select the Cockpit Voice Recorder status message if a discrepancy is observed. The wording here is placeholder content shaped like a procedure, not a procedure. During an extended ground delay, the relief pilot should monitor the Cargo Smoke Detection switch position unless directed otherwise by the Sample Operations Center. If the Brake Temperature Monitor is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance.

| Condition                              | Sample value | Remarks       |
|----------------------------------------|--------------|---------------|
| Nosewheel Steering selector position   | 35 units     | Monitor       |
| Pack Temperature Control annunciation  | 90 units     | Monitor       |
| Wing Anti-Ice advisory                 | 43 units     | Monitor       |
| Landing Gear Indication status message | 63 units     | Advisory only |

**NOTE:** During climb, the pilot flying should monitor the Cabin Pressure Controller advisory unless directed otherwise by the Sample Operations Center.

**CAUTION:** The Fuel Crossfeed advisory is expected to read within the sample range of 58 to 70 units during a turnaround.

During engine start, the First Officer should select the Oxygen Distribution selector position once the checklist item is complete. If the Flight Management Computer is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance. Refer to the related topic for additional sample context.

19.10.6 Takeoff Performance Table 6

This text is fictional and exists only to give the prototype realistic volume and structure. The Pack Temperature Control switch position is expected to read within the sample range of 60 to 65 units during descent. Both pilots will select any change in the Stall Warning quantity display and advise the other pilot when conditions permit. The Center Tank Pumps switch position that differs from the expected state requires both pilots to brief the condition if the indication does not stabilize within the sample interval. The Auxiliary Power Unit annunciation that differs from the expected state requires the First Officer to brief the condition when conditions permit.

| Condition                         | Sample value | Remarks |
|-----------------------------------|--------------|---------|
| Center Tank Pumps status message  | 52 units     | Monitor |
| Hydraulic System B status message | 48 units     | Monitor |
| Standby Instruments annunciation  | 93 units     | Monitor |

The Fuel Crossfeed quantity display is expected to read within the sample range of 18 to 30 units during climb. The Ground Proximity Monitor status message that differs from the expected state requires both pilots to confirm the condition once the checklist item is complete. The Standby Instruments status message that differs from the expected state requires the pilot monitoring to brief the condition when operating at a sample station without ground power. The Ground Proximity Monitor status message is expected to read within the sample range of 45 to 53 units during cruise. The wording here is placeholder content shaped like a procedure, not a procedure.

**CAUTION:** During a maintenance-requested ground run, the relief pilot should brief the Primary Electrical Bus switch position when conditions permit.

The relief pilot will select any change in the Autothrottle indication and advise the other pilot when the associated caution light remains illuminated. The Bleed Air Supply quantity display that differs from the expected state requires the First Officer to select the condition when conditions permit. During climb, the Captain should select the Autobrake Selector annunciation unless directed otherwise by the Sample Operations Center. Values in this manual are invented and must not be used for any operational purpose. The captain will record any change in the Ground Proximity Monitor annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center. During takeoff, the pilot monitoring should brief the Weather Radar annunciation when the associated caution light remains illuminated.

19.10.7 Takeoff Performance Table 7

During cruise, the Captain should confirm the Fire Detection Loop selector position before the next phase of flight. If the Standby Instruments is inoperative, continue a diversion only after the relief pilot has reviewed the associated sample guidance. The captain will confirm any change in the Cargo Smoke Detection indication and advise the other pilot when conditions permit.

The pilot flying will select any change in the Speedbrake Handle annunciation and advise the other pilot when the associated caution light remains illuminated. The Standby Hydraulic status message that differs from the expected state requires the pilot flying to announce the condition before the next phase of flight. If the Traffic Advisory Display is inoperative, continue parking only after the Captain has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. If the Bleed Air Supply is inoperative, continue parking only after the pilot monitoring has reviewed the associated sample guidance. During a turnaround, the pilot monitoring should cross-check the Wing Anti-Ice quantity display unless directed otherwise by the Sample Operations Center.

The Standby Instruments quantity display is expected to read within the sample range of 52 to 63 units during cruise. During descent, the Captain should select the Flight Management Computer selector position before the next phase

of flight. The relief pilot will verify any change in the Nosewheel Steering indication and advise the other pilot when conditions permit. The Weather Radar status message that differs from the expected state requires the relief pilot to monitor the condition unless directed otherwise by the Sample Operations Center.

If the Engine Anti-Ice is inoperative, continue climb only after the Captain has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. If the Autopilot Channel B is inoperative, continue taxi only after the relief pilot has reviewed the associated sample guidance. If the Stall Warning is inoperative, continue landing only after the Captain has reviewed the associated sample guidance. If the Autopilot Channel B is inoperative, continue engine start only after the Captain has reviewed the associated sample guidance. The Autothrottle switch position is expected to read within the sample range of 39 to 51 units during preflight.

| Condition                             | Sample value | Remarks       |
|---------------------------------------|--------------|---------------|
| Landing Gear Indication annunciation  | 99 units     | Monitor       |
| Nosewheel Steering annunciation       | 89 units     | Normal        |
| Wing Anti-Ice selector position       | 43 units     | Monitor       |
| Hydraulic System B switch position    | 92 units     | Normal        |
| Stall Warning advisory                | 67 units     | Normal        |
| Thrust Reverser annunciation          | 54 units     | Advisory only |
| Autopilot Channel B selector position | 53 units     | Monitor       |

**NOTE:** During cruise, the Captain should confirm the Wing Anti-Ice indication when the associated caution light remains illuminated.

During a turnaround, the First Officer should verify the Speedbrake Handle selector position when the associated caution light remains illuminated. This text is fictional and exists only to give the prototype realistic volume and structure. The Auxiliary Power Unit status message that differs from the expected state requires the pilot monitoring to cross-check the condition when conditions permit. During preflight, the First Officer should record the Center Tank Pumps indication when operating at a sample station without ground power.

- During climb, the First Officer should select the Pack Temperature Control annunciation if a discrepancy is observed.
- The Stall Warning selector position that differs from the expected state requires the Captain to announce the condition if a discrepancy is observed.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- The Oxygen Distribution annunciation is expected to read within the sample range of 82 to 86 units during descent.
- During taxi, both pilots should verify the Flap Position Indication switch position if a discrepancy is observed.
- During takeoff, the First Officer should cross-check the Pack Temperature Control switch position when operating at a sample station without ground power.

**NOTE:** The Weather Radar quantity display is expected to read within the sample range of 86 to 98 units during landing. This text is fictional and exists only to give the prototype realistic volume and structure.

### 19.10.8 Takeoff Performance Table 8

The Probe Heat switch position is expected to read within the sample range of 35 to 38 units during an extended ground delay. The Autobrake Selector advisory that differs from the expected state requires the Captain to verify the condition if the indication does not stabilize within the sample interval. The Weather Radar selector position is expected to read within the sample range of 84 to 96 units during an extended ground delay. The Standby Instruments switch position is expected to read within the sample range of 10 to 18 units during cruise. The Cargo

Smoke Detection advisory that differs from the expected state requires the relief pilot to select the condition when the associated caution light remains illuminated. The Auxiliary Power Unit indication is expected to read within the sample range of 29 to 40 units during a turnaround.

**CAUTION:** Values in this manual are invented and must not be used for any operational purpose. The Probe Heat quantity display that differs from the expected state requires the pilot monitoring to select the condition when operating at a sample station without ground power. Refer to the related topic for additional sample context.

The wording here is placeholder content shaped like a procedure, not a procedure. The Wing Anti-Ice status message is expected to read within the sample range of 12 to 17 units during cruise. If the Traffic Advisory Display is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance. The Hydraulic System B selector position is expected to read within the sample range of 6 to 15 units during approach.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Standby Instruments switch position        | 57 units     | Normal                 |
| Probe Heat indication                      | 10 units     | Normal                 |
| Cabin Pressure Controller quantity display | 86 units     | Monitor                |
| Thrust Reverser annunciation               | 33 units     | Refer to related topic |
| Probe Heat switch position                 | 25 units     | Monitor                |
| Bleed Air Supply selector position         | 61 units     | Refer to related topic |

**CAUTION:** The Brake Temperature Monitor selector position is expected to read within the sample range of 37 to 47 units during landing. If the Speedbrake Handle is inoperative, continue approach only after the relief pilot has reviewed the associated sample guidance.

**NOTE:** The Oxygen Distribution annunciation that differs from the expected state requires the pilot monitoring to verify the condition when the associated caution light remains illuminated. During approach, the First Officer should brief the Ground Proximity Monitor advisory when operating at a sample station without ground power.

- The first officer will verify any change in the Probe Heat status message and advise the other pilot when operating at a sample station without ground power.
- During engine start, both pilots should verify the Cabin Pressure Controller selector position if a discrepancy is observed.
- During preflight, the Captain should announce the Autopilot Channel B quantity display when conditions permit.
- If the Cockpit Voice Recorder is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance.

19.10.9 Takeoff Performance Table 9

If the Standby Instruments is inoperative, continue landing only after the pilot monitoring has reviewed the associated sample guidance. The Standby Hydraulic annunciation that differs from the expected state requires the Captain to select the condition when operating at a sample station without ground power. The Transponder indication is expected to read within the sample range of 60 to 68 units during approach.

- Values in this manual are invented and must not be used for any operational purpose.
- Values in this manual are invented and must not be used for any operational purpose.
- During landing, both pilots should verify the Brake Temperature Monitor annunciation when operating at a sample station without ground power.

| Condition                         | Sample value | Remarks |
|-----------------------------------|--------------|---------|
| Ground Proximity Monitor advisory | 74 units     | Normal  |



|                                            |          |                        |
|--------------------------------------------|----------|------------------------|
| Probe Heat advisory                        | 81 units | Refer to related topic |
| Transponder status message                 | 61 units | Advisory only          |
| Autopilot Channel A annunciation           | 63 units | Normal                 |
| Flight Management Computer switch position | 28 units | Advisory only          |

**CAUTION:** Both pilots will verify any change in the Thrust Reverser annunciation and advise the other pilot if a discrepancy is observed. If the Traffic Advisory Display is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance.

Values in this manual are invented and must not be used for any operational purpose. The Weather Radar status message that differs from the expected state requires the pilot flying to record the condition if the indication does not stabilize within the sample interval. During approach, the Captain should record the Fuel Crossfeed selector position unless directed otherwise by the Sample Operations Center. The pilot monitoring will brief any change in the Standby Hydraulic indication and advise the other pilot when operating at a sample station without ground power.

- The Flight Management Computer advisory is expected to read within the sample range of 69 to 81 units during taxi.
- If the Auxiliary Power Unit is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance.
- If the Fire Detection Loop is inoperative, continue climb only after the First Officer has reviewed the associated sample guidance.
- The Cabin Pressure Controller annunciation that differs from the expected state requires the pilot monitoring to brief the condition unless directed otherwise by the Sample Operations Center.

**NOTE:** The pilot flying will monitor any change in the Flap Position Indication status message and advise the other pilot unless directed otherwise by the Sample Operations Center. Both pilots will verify any change in the Cockpit Voice Recorder indication and advise the other pilot once the checklist item is complete.

- The Flight Management Computer annunciation that differs from the expected state requires the relief pilot to verify the condition if the indication does not stabilize within the sample interval.
- The Standby Instruments quantity display that differs from the expected state requires both pilots to monitor the condition once the checklist item is complete.
- The Weather Radar selector position that differs from the expected state requires the relief pilot to verify the condition before the next phase of flight.
- If the Autobrake Selector is inoperative, continue taxi only after both pilots has reviewed the associated sample guidance.
- The first officer will record any change in the Auxiliary Power Unit annunciation and advise the other pilot before the next phase of flight.

#### 19.10.10 Takeoff Performance Table 10

If the Autopilot Channel B is inoperative, continue landing only after the pilot monitoring has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. Refer to the related topic for additional sample context. The pilot monitoring will cross-check any change in the Autothrottle advisory and advise the other pilot when the associated caution light remains illuminated.

**NOTE:** The Autobrake Selector annunciation that differs from the expected state requires the Captain to record the condition when conditions permit. The Wing Anti-Ice advisory that differs from the expected state requires both pilots to brief the condition if a discrepancy is observed. The Fire Detection Loop switch position that differs from the expected state requires the relief pilot to brief the condition if the indication does not stabilize within the sample interval. Values in this manual are invented and must not be used for any operational purpose. The

captain will verify any change in the Autobrake Selector quantity display and advise the other pilot before the next phase of flight.

During a maintenance-requested ground run, both pilots should monitor the Brake Temperature Monitor status message when the associated caution light remains illuminated. If the Thrust Reverser is inoperative, continue engine start only after the pilot flying has reviewed the associated sample guidance. The Autothrottle indication that differs from the expected state requires the pilot monitoring to confirm the condition once the checklist item is complete. The first officer will announce any change in the Speedbrake Handle quantity display and advise the other pilot before the next phase of flight. The Flap Position Indication selector position that differs from the expected state requires both pilots to record the condition if the indication does not stabilize within the sample interval. The Bleed Air Supply advisory that differs from the expected state requires the Captain to monitor the condition when operating at a sample station without ground power.

**CAUTION:** Values in this manual are invented and must not be used for any operational purpose. During takeoff, the First Officer should cross-check the Cockpit Voice Recorder status message when conditions permit.

**NOTE:** The captain will verify any change in the Cabin Pressure Controller indication and advise the other pilot if the indication does not stabilize within the sample interval.

**CAUTION:** Refer to the related topic for additional sample context.

This text is fictional and exists only to give the prototype realistic volume and structure. The Auxiliary Power Unit indication is expected to read within the sample range of 75 to 86 units during approach. During a turnaround, both pilots should brief the Autothrottle status message when conditions permit. The Thrust Reverser status message is expected to read within the sample range of 45 to 48 units during landing. Both pilots will cross-check any change in the Pack Temperature Control status message and advise the other pilot unless directed otherwise by the Sample Operations Center. Both pilots will select any change in the Cargo Smoke Detection quantity display and advise the other pilot if a discrepancy is observed.

#### **19.10.11 Takeoff Performance Table 11**

During a maintenance-requested ground run, the Captain should announce the Fire Detection Loop annunciation once the checklist item is complete. The Fuel Crossfeed annunciation is expected to read within the sample range of 79 to 83 units during climb. The relief pilot will confirm any change in the Window Heat annunciation and advise the other pilot when conditions permit. During parking, both pilots should confirm the Autothrottle quantity display when conditions permit.

The Weather Radar annunciation is expected to read within the sample range of 90 to 100 units during takeoff. If the Flight Management Computer is inoperative, continue climb only after the Captain has reviewed the associated sample guidance. The Pack Temperature Control selector position is expected to read within the sample range of 41 to 49 units during climb. The Window Heat advisory is expected to read within the sample range of 79 to 82 units during landing. The Thrust Reverser selector position is expected to read within the sample range of 10 to 14 units during climb.

If the Engine Anti-Ice is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance. If the Fire Detection Loop is inoperative, continue preflight only after the relief pilot has reviewed the associated sample guidance. The Primary Electrical Bus status message that differs from the expected state requires the pilot flying to confirm the condition unless directed otherwise by the Sample Operations Center. The Cockpit Voice Recorder status message is expected to read within the sample range of 10 to 16 units during taxi. During climb, the pilot monitoring should monitor the Cargo Smoke Detection indication if the indication does not stabilize within the sample interval.

If the Oxygen Distribution is inoperative, continue landing only after both pilots has reviewed the associated sample guidance. If the Autopilot Channel A is inoperative, continue approach only after the pilot flying has reviewed the associated sample guidance. During a maintenance-requested ground run, the First Officer should confirm the Center Tank Pumps selector position if the indication does not stabilize within the sample interval. Values in this manual are invented and must not be used for any operational purpose. This text is fictional and exists only to give the prototype

realistic volume and structure.

**CAUTION:** The Probe Heat indication that differs from the expected state requires the Captain to verify the condition when conditions permit.

The Weather Radar status message that differs from the expected state requires the relief pilot to record the condition if a discrepancy is observed. The wording here is placeholder content shaped like a procedure, not a procedure. The Pack Temperature Control switch position is expected to read within the sample range of 68 to 71 units during cruise. This text is fictional and exists only to give the prototype realistic volume and structure.

The pilot monitoring will select any change in the Hydraulic System B advisory and advise the other pilot if a discrepancy is observed. The Autopilot Channel A quantity display is expected to read within the sample range of 38 to 41 units during cruise. The Wing Anti-Ice status message is expected to read within the sample range of 96 to 102 units during an extended ground delay. If the Wing Anti-Ice is inoperative, continue cruise only after the First Officer has reviewed the associated sample guidance. Refer to the related topic for additional sample context. Refer to the related topic for additional sample context. See 16.20.1 Standby Hydraulic Reset Guidance.

**19.10.12 Takeoff Performance Table 12**

If the Engine Anti-Ice is inoperative, continue climb only after the Captain has reviewed the associated sample guidance. The pilot flying will verify any change in the Pack Temperature Control status message and advise the other pilot once the checklist item is complete. If the Stall Warning is inoperative, continue climb only after both pilots has reviewed the associated sample guidance.

| Condition                            | Sample value | Remarks                |
|--------------------------------------|--------------|------------------------|
| Weather Radar advisory               | 83 units     | Normal                 |
| Autobrake Selector switch position   | 11 units     | Advisory only          |
| Bleed Air Supply advisory            | 14 units     | Refer to related topic |
| Autobrake Selector indication        | 60 units     | Normal                 |
| Nosewheel Steering selector position | 80 units     | Refer to related topic |

The Autobrake Selector quantity display that differs from the expected state requires the pilot flying to record the condition if a discrepancy is observed. If the Wing Anti-Ice is inoperative, continue taxi only after the relief pilot has reviewed the associated sample guidance. The Brake Temperature Monitor indication is expected to read within the sample range of 96 to 100 units during cruise.

- The Oxygen Distribution annunciation is expected to read within the sample range of 67 to 76 units during a maintenance-requested ground run.
- The Standby Hydraulic selector position that differs from the expected state requires both pilots to confirm the condition if a discrepancy is observed.
- The first officer will verify any change in the Weather Radar indication and advise the other pilot when the associated caution light remains illuminated.
- The Center Tank Pumps annunciation that differs from the expected state requires the Captain to cross-check the condition when conditions permit.
- During taxi, both pilots should cross-check the Wing Anti-Ice status message once the checklist item is complete.

The wording here is placeholder content shaped like a procedure, not a procedure. If the Transponder is inoperative, continue approach only after the pilot monitoring has reviewed the associated sample guidance. During engine start, both pilots should cross-check the Primary Electrical Bus indication when conditions permit.

**19.10.13 Takeoff Performance Table 13**

If the Fire Detection Loop is inoperative, continue landing only after both pilots has reviewed the associated sample guidance. The first officer will brief any change in the Transponder advisory and advise the other pilot if a discrepancy is observed. The Window Heat annunciation that differs from the expected state requires the relief pilot to verify the condition once the checklist item is complete.

- The pilot monitoring will select any change in the Cabin Pressure Controller annunciation and advise the other pilot once the checklist item is complete.
- If the Engine Anti-Ice is inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance.
- The pilot flying will cross-check any change in the Weather Radar advisory and advise the other pilot when operating at a sample station without ground power.
- During a diversion, both pilots should confirm the Ground Proximity Monitor indication once the checklist item is complete.

If the Cargo Smoke Detection is inoperative, continue a maintenance-requested ground run only after the pilot flying has reviewed the associated sample guidance. The first officer will record any change in the Engine Anti-Ice annunciation and advise the other pilot before the next phase of flight. During approach, the pilot flying should verify the Pack Temperature Control switch position if a discrepancy is observed. The Primary Electrical Bus indication is expected to read within the sample range of 55 to 59 units during approach. The Stall Warning advisory is expected to read within the sample range of 14 to 21 units during descent. The Nosewheel Steering indication that differs from the expected state requires both pilots to monitor the condition once the checklist item is complete.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Engine Anti-Ice quantity display         | 79 units     | Refer to related topic |
| Hydraulic System A selector position     | 29 units     | Normal                 |
| Auxiliary Power Unit quantity display    | 88 units     | Refer to related topic |
| Landing Gear Indication quantity display | 62 units     | Advisory only          |

The Primary Electrical Bus annunciation that differs from the expected state requires the First Officer to confirm the condition if a discrepancy is observed. The Engine Anti-Ice annunciation that differs from the expected state requires the pilot flying to brief the condition if the indication does not stabilize within the sample interval. The captain will announce any change in the Speedbrake Handle status message and advise the other pilot if the indication does not stabilize within the sample interval.

- The relief pilot will monitor any change in the Engine Anti-Ice indication and advise the other pilot before the next phase of flight.
- The Standby Hydraulic indication is expected to read within the sample range of 16 to 26 units during descent.
- During preflight, the First Officer should brief the Autothrottle status message if a discrepancy is observed.

| Condition                                 | Sample value | Remarks       |
|-------------------------------------------|--------------|---------------|
| Probe Heat status message                 | 6 units      | Monitor       |
| Cabin Pressure Controller switch position | 44 units     | Normal        |
| Flap Position Indication indication       | 96 units     | Monitor       |
| Ground Proximity Monitor advisory         | 70 units     | Advisory only |
| Nosewheel Steering quantity display       | 46 units     | Monitor       |
| Nosewheel Steering indication             | 14 units     | Advisory only |
| Transponder annunciation                  | 34 units     | Advisory only |

If the Transponder is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance. The Traffic Advisory Display annunciation is expected to read within the sample range of 12 to 16 units during a maintenance-requested ground run. During descent, the pilot monitoring should record the Standby Hydraulic selector position when operating at a sample station without ground power. The Cargo Smoke Detection annunciation is expected to read within the sample range of 4 to 11 units during approach. The Traffic Advisory Display indication is expected to read within the sample range of 67 to 75 units during takeoff. During takeoff, the Captain should verify the Center Tank Pumps indication when the associated caution light remains illuminated.

The wording here is placeholder content shaped like a procedure, not a procedure. During an extended ground delay, the First Officer should cross-check the Wing Anti-Ice indication if the indication does not stabilize within the sample interval. Both pilots will record any change in the Fuel Crossfeed annunciation and advise the other pilot when conditions permit. See 08.10.3 Engine Anti-Ice Status Messages.

## 19.20 Enroute Performance

### 19.20.1 Enroute Performance Table 1

During a turnaround, the relief pilot should cross-check the Flap Position Indication annunciation unless directed otherwise by the Sample Operations Center. This text is fictional and exists only to give the prototype realistic volume and structure. If the Autobrake Selector is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure.

**NOTE:** The pilot monitoring will brief any change in the Standby Hydraulic advisory and advise the other pilot when operating at a sample station without ground power. The Stall Warning selector position is expected to read within the sample range of 21 to 25 units during engine start.

- During a diversion, the relief pilot should cross-check the Speedbrake Handle annunciation if a discrepancy is observed.
- The Bleed Air Supply switch position is expected to read within the sample range of 12 to 23 units during a diversion.
- During an extended ground delay, both pilots should verify the Transponder switch position once the checklist item is complete.
- The Hydraulic System A switch position that differs from the expected state requires the First Officer to announce the condition before the next phase of flight.
- During parking, the pilot flying should announce the Hydraulic System A selector position before the next phase of flight.
- The pilot flying will cross-check any change in the Speedbrake Handle advisory and advise the other pilot if the indication does not stabilize within the sample interval.
- If the Stall Warning is inoperative, continue approach only after the Captain has reviewed the associated sample guidance.
- Both pilots will select any change in the Autopilot Channel A selector position and advise the other pilot if the indication does not stabilize within the sample interval.
- The Probe Heat advisory that differs from the expected state requires the pilot flying to confirm the condition unless directed otherwise by the Sample Operations Center.
- Values in this manual are invented and must not be used for any operational purpose.
- If the Brake Temperature Monitor is inoperative, continue engine start only after the pilot flying has reviewed the associated sample guidance.

- Refer to the related topic for additional sample context.
- The relief pilot will record any change in the Fuel Crossfeed annunciation and advise the other pilot if a discrepancy is observed.
- Refer to the related topic for additional sample context.
- If the Oxygen Distribution is inoperative, continue approach only after the pilot flying has reviewed the associated sample guidance.

The Auxiliary Power Unit switch position is expected to read within the sample range of 55 to 59 units during taxi. The relief pilot will cross-check any change in the Transponder status message and advise the other pilot when operating at a sample station without ground power. The Flight Management Computer quantity display is expected to read within the sample range of 93 to 97 units during engine start. During engine start, the pilot flying should announce the Ground Proximity Monitor indication when operating at a sample station without ground power. If the Traffic Advisory Display is inoperative, continue a diversion only after the pilot monitoring has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure.

The wording here is placeholder content shaped like a procedure, not a procedure. If the Brake Temperature Monitor is inoperative, continue taxi only after the First Officer has reviewed the associated sample guidance. The Cockpit Voice Recorder advisory is expected to read within the sample range of 82 to 91 units during preflight.

### **19.20.2 Enroute Performance Table 2**

The Landing Gear Indication status message that differs from the expected state requires the pilot flying to announce the condition when conditions permit. During approach, the pilot monitoring should cross-check the Traffic Advisory Display selector position if a discrepancy is observed. Refer to the related topic for additional sample context.

The Autopilot Channel B advisory is expected to read within the sample range of 50 to 62 units during parking. The Autopilot Channel A annunciation is expected to read within the sample range of 63 to 70 units during a diversion. The Wing Anti-Ice status message is expected to read within the sample range of 10 to 13 units during a diversion. Both pilots will monitor any change in the Autobrake Selector status message and advise the other pilot when operating at a sample station without ground power. The relief pilot will monitor any change in the Standby Hydraulic quantity display and advise the other pilot when operating at a sample station without ground power. The pilot monitoring will confirm any change in the Brake Temperature Monitor annunciation and advise the other pilot when conditions permit.

- The wording here is placeholder content shaped like a procedure, not a procedure.
- During landing, the relief pilot should select the Hydraulic System A selector position once the checklist item is complete.
- Refer to the related topic for additional sample context.
- The Stall Warning annunciation that differs from the expected state requires both pilots to select the condition when operating at a sample station without ground power.
- If the Cabin Pressure Controller is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance.
- During climb, the Captain should monitor the Transponder status message before the next phase of flight.

The Traffic Advisory Display status message is expected to read within the sample range of 43 to 53 units during a turnaround. If the Standby Instruments is inoperative, continue descent only after both pilots has reviewed the associated sample guidance. The Flight Management Computer advisory that differs from the expected state requires the pilot flying to monitor the condition once the checklist item is complete.

During taxi, the pilot monitoring should brief the Brake Temperature Monitor quantity display when operating at a sample station without ground power. The relief pilot will cross-check any change in the Ground Proximity Monitor annunciation and advise the other pilot if the indication does not stabilize within the sample interval. During takeoff,



the Captain should announce the Cargo Smoke Detection advisory when operating at a sample station without ground power. See 09.10.5 Primary Electrical Bus Normal Operation.

- The Nosewheel Steering quantity display that differs from the expected state requires the pilot monitoring to announce the condition when the associated caution light remains illuminated.
- The Primary Electrical Bus selector position that differs from the expected state requires the First Officer to monitor the condition when the associated caution light remains illuminated.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- During a maintenance-requested ground run, the First Officer should cross-check the Wing Anti-Ice quantity display if the indication does not stabilize within the sample interval.
- If the Fuel Crossfeed is inoperative, continue a turnaround only after the pilot monitoring has reviewed the associated sample guidance.
- During preflight, both pilots should monitor the Pack Temperature Control indication if the indication does not stabilize within the sample interval.
- Values in this manual are invented and must not be used for any operational purpose.

| Condition                         | Sample value | Remarks                |
|-----------------------------------|--------------|------------------------|
| Probe Heat selector position      | 80 units     | Normal                 |
| Flap Position Indication advisory | 57 units     | Advisory only          |
| Fuel Crossfeed quantity display   | 97 units     | Advisory only          |
| Window Heat selector position     | 31 units     | Refer to related topic |

19.20.3 Enroute Performance Table 3

If the Window Heat is inoperative, continue parking only after both pilots has reviewed the associated sample guidance. The Stall Warning advisory that differs from the expected state requires the pilot flying to confirm the condition when conditions permit. Both pilots will verify any change in the Standby Hydraulic quantity display and advise the other pilot when the associated caution light remains illuminated. During an extended ground delay, both pilots should verify the Standby Hydraulic quantity display when operating at a sample station without ground power.

Values in this manual are invented and must not be used for any operational purpose. This text is fictional and exists only to give the prototype realistic volume and structure. Refer to the related topic for additional sample context.

- The Window Heat switch position is expected to read within the sample range of 57 to 62 units during a maintenance-requested ground run.
- The pilot monitoring will brief any change in the Weather Radar status message and advise the other pilot unless directed otherwise by the Sample Operations Center.
- The Hydraulic System B status message is expected to read within the sample range of 60 to 65 units during preflight.
- The Autothrottle annunciation is expected to read within the sample range of 20 to 24 units during preflight.
- The Brake Temperature Monitor annunciation is expected to read within the sample range of 89 to 92 units during preflight.

During descent, the Captain should verify the Weather Radar advisory unless directed otherwise by the Sample Operations Center. The Pack Temperature Control indication is expected to read within the sample range of 73 to 79 units during a diversion. If the Autopilot Channel B is inoperative, continue parking only after both pilots has reviewed the associated sample guidance.

| Condition | Sample value | Remarks |
|-----------|--------------|---------|
|-----------|--------------|---------|

|                                 |          |               |
|---------------------------------|----------|---------------|
| Probe Heat indication           | 27 units | Normal        |
| Cargo Smoke Detection advisory  | 34 units | Advisory only |
| Thrust Reverser switch position | 79 units | Monitor       |

The relief pilot will select any change in the Primary Electrical Bus advisory and advise the other pilot when conditions permit. The wording here is placeholder content shaped like a procedure, not a procedure. If the Traffic Advisory Display is inoperative, continue parking only after the Captain has reviewed the associated sample guidance. Both pilots will cross-check any change in the Hydraulic System A indication and advise the other pilot once the checklist item is complete. The Oxygen Distribution indication that differs from the expected state requires the relief pilot to cross-check the condition once the checklist item is complete. During a maintenance-requested ground run, the relief pilot should brief the Stall Warning annunciation when the associated caution light remains illuminated.

- The Cockpit Voice Recorder status message is expected to read within the sample range of 50 to 54 units during a diversion.
- The Stall Warning selector position that differs from the expected state requires both pilots to verify the condition if a discrepancy is observed.
- The Cockpit Voice Recorder annunciation is expected to read within the sample range of 48 to 56 units during cruise.
- If the Fire Detection Loop is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance.
- Both pilots will brief any change in the Autopilot Channel A advisory and advise the other pilot before the next phase of flight.

The Autopilot Channel B annunciation that differs from the expected state requires the pilot monitoring to select the condition when conditions permit. Values in this manual are invented and must not be used for any operational purpose. The Autothrottle switch position is expected to read within the sample range of 55 to 66 units during approach. The pilot monitoring will brief any change in the Speedbrake Handle annunciation and advise the other pilot when the associated caution light remains illuminated.

#### **19.20.4 Enroute Performance Table 4**

The Fuel Crossfeed quantity display is expected to read within the sample range of 16 to 22 units during parking. During preflight, the pilot flying should monitor the Fire Detection Loop switch position when the associated caution light remains illuminated. If the Flap Position Indication is inoperative, continue a maintenance-requested ground run only after both pilots has reviewed the associated sample guidance. The Weather Radar status message is expected to read within the sample range of 29 to 36 units during an extended ground delay. If the Auxiliary Power Unit is inoperative, continue parking only after both pilots has reviewed the associated sample guidance. The Autobrake Selector advisory that differs from the expected state requires the relief pilot to verify the condition when operating at a sample station without ground power.

- If the Window Heat is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance.
- Both pilots will verify any change in the Stall Warning annunciation and advise the other pilot when operating at a sample station without ground power.
- The first officer will select any change in the Oxygen Distribution selector position and advise the other pilot once the checklist item is complete.
- During approach, the pilot flying should announce the Window Heat advisory when conditions permit.
- The Oxygen Distribution status message is expected to read within the sample range of 62 to 71 units during a maintenance-requested ground run.

- The wording here is placeholder content shaped like a procedure, not a procedure.
- The pilot flying will monitor any change in the Probe Heat status message and advise the other pilot if a discrepancy is observed.
- The Brake Temperature Monitor status message is expected to read within the sample range of 96 to 102 units during approach.
- The pilot monitoring will announce any change in the Nosewheel Steering switch position and advise the other pilot if the indication does not stabilize within the sample interval.
- During parking, the pilot flying should record the Window Heat selector position when the associated caution light remains illuminated.

**NOTE:** If the Cabin Pressure Controller is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance. The Landing Gear Indication switch position is expected to read within the sample range of 21 to 31 units during preflight.

**CAUTION:** The pilot flying will record any change in the Thrust Reverser switch position and advise the other pilot if a discrepancy is observed.

The Ground Proximity Monitor quantity display that differs from the expected state requires the pilot flying to confirm the condition when operating at a sample station without ground power. The wording here is placeholder content shaped like a procedure, not a procedure. During parking, the pilot flying should verify the Bleed Air Supply indication once the checklist item is complete. During taxi, both pilots should monitor the Transponder indication if a discrepancy is observed. This text is fictional and exists only to give the prototype realistic volume and structure.

The wording here is placeholder content shaped like a procedure, not a procedure. The Flight Management Computer indication that differs from the expected state requires the pilot flying to monitor the condition unless directed otherwise by the Sample Operations Center. If the Cockpit Voice Recorder is inoperative, continue approach only after the pilot flying has reviewed the associated sample guidance.

### 19.20.5 Enroute Performance Table 5

The Cabin Pressure Controller quantity display that differs from the expected state requires both pilots to verify the condition once the checklist item is complete. The Flap Position Indication indication is expected to read within the sample range of 66 to 74 units during taxi. If the Fire Detection Loop is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance. The Hydraulic System B switch position that differs from the expected state requires the pilot flying to monitor the condition when conditions permit. The pilot monitoring will brief any change in the Hydraulic System B advisory and advise the other pilot when conditions permit. The Pack Temperature Control indication is expected to read within the sample range of 45 to 51 units during a diversion.

The relief pilot will record any change in the Standby Instruments selector position and advise the other pilot if the indication does not stabilize within the sample interval. If the Probe Heat is inoperative, continue parking only after both pilots has reviewed the associated sample guidance. If the Auxiliary Power Unit is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance.

The first officer will record any change in the Bleed Air Supply switch position and advise the other pilot when conditions permit. Refer to the related topic for additional sample context. The pilot monitoring will record any change in the Brake Temperature Monitor selector position and advise the other pilot if a discrepancy is observed. The Hydraulic System B quantity display is expected to read within the sample range of 21 to 27 units during takeoff. Refer to the related topic for additional sample context. The wording here is placeholder content shaped like a procedure, not a procedure.

The Stall Warning status message is expected to read within the sample range of 24 to 35 units during landing. The Window Heat quantity display that differs from the expected state requires the pilot flying to select the condition when operating at a sample station without ground power. The Primary Electrical Bus status message is expected to read

within the sample range of 80 to 83 units during a maintenance-requested ground run. The pilot flying will brief any change in the Wing Anti-Ice indication and advise the other pilot unless directed otherwise by the Sample Operations Center. The Pack Temperature Control status message is expected to read within the sample range of 33 to 39 units during preflight. The pilot monitoring will select any change in the Cabin Pressure Controller advisory and advise the other pilot once the checklist item is complete.

During approach, the Captain should cross-check the Primary Electrical Bus annunciation when the associated caution light remains illuminated. If the Hydraulic System B is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance. Both pilots will verify any change in the Traffic Advisory Display selector position and advise the other pilot if the indication does not stabilize within the sample interval.

The first officer will confirm any change in the Fire Detection Loop advisory and advise the other pilot unless directed otherwise by the Sample Operations Center. The Primary Electrical Bus advisory that differs from the expected state requires the First Officer to select the condition if a discrepancy is observed. The relief pilot will select any change in the Stall Warning status message and advise the other pilot once the checklist item is complete. If the Fire Detection Loop is inoperative, continue parking only after the pilot monitoring has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure.

- Both pilots will record any change in the Probe Heat selector position and advise the other pilot before the next phase of flight.
- If the Brake Temperature Monitor is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance.
- The Stall Warning advisory that differs from the expected state requires the Captain to record the condition if a discrepancy is observed.
- During preflight, the pilot monitoring should record the Center Tank Pumps status message if the indication does not stabilize within the sample interval.

Values in this manual are invented and must not be used for any operational purpose. Both pilots will select any change in the Weather Radar advisory and advise the other pilot when operating at a sample station without ground power. Refer to the related topic for additional sample context. The pilot monitoring will cross-check any change in the Traffic Advisory Display status message and advise the other pilot when operating at a sample station without ground power. This text is fictional and exists only to give the prototype realistic volume and structure. During descent, the pilot flying should announce the Weather Radar selector position before the next phase of flight.

| Condition                              | Sample value | Remarks       |
|----------------------------------------|--------------|---------------|
| Weather Radar advisory                 | 35 units     | Advisory only |
| Weather Radar quantity display         | 51 units     | Normal        |
| Hydraulic System B advisory            | 21 units     | Advisory only |
| Auxiliary Power Unit selector position | 74 units     | Advisory only |
| Speedbrake Handle annunciation         | 97 units     | Monitor       |

19.20.6 Enroute Performance Table 6

During an extended ground delay, the relief pilot should confirm the Wing Anti-Ice quantity display if the indication does not stabilize within the sample interval. If the Standby Instruments is inoperative, continue a maintenance-requested ground run only after the pilot monitoring has reviewed the associated sample guidance. The first officer will select any change in the Engine Anti-Ice status message and advise the other pilot unless directed otherwise by the Sample Operations Center.

**NOTE:** The relief pilot will monitor any change in the Autothrottle advisory and advise the other pilot when conditions permit. The Bleed Air Supply advisory that differs from the expected state requires the First Officer to monitor the condition if a discrepancy is observed.

**NOTE:** This text is fictional and exists only to give the prototype realistic volume and structure. Refer to the related topic for additional sample context.

- The Brake Temperature Monitor advisory that differs from the expected state requires the First Officer to select the condition before the next phase of flight.
- During a diversion, the relief pilot should announce the Weather Radar quantity display if a discrepancy is observed.
- If the Engine Anti-Ice is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance.
- During a turnaround, the Captain should announce the Cargo Smoke Detection status message if a discrepancy is observed.
- Values in this manual are invented and must not be used for any operational purpose.
- Values in this manual are invented and must not be used for any operational purpose.
- The pilot monitoring will announce any change in the Cabin Pressure Controller switch position and advise the other pilot when the associated caution light remains illuminated.
- The Nosewheel Steering advisory is expected to read within the sample range of 52 to 57 units during an extended ground delay.
- The Hydraulic System A quantity display that differs from the expected state requires the First Officer to brief the condition when conditions permit.
- During preflight, the First Officer should brief the Ground Proximity Monitor status message if a discrepancy is observed.

The pilot monitoring will announce any change in the Oxygen Distribution quantity display and advise the other pilot when operating at a sample station without ground power. The Autobrake Selector selector position that differs from the expected state requires both pilots to monitor the condition when operating at a sample station without ground power. The Ground Proximity Monitor indication that differs from the expected state requires both pilots to select the condition if a discrepancy is observed. The Auxiliary Power Unit switch position is expected to read within the sample range of 14 to 23 units during climb.

- During landing, both pilots should verify the Hydraulic System A selector position when the associated caution light remains illuminated.
- The Fire Detection Loop selector position is expected to read within the sample range of 97 to 107 units during preflight.
- The pilot flying will confirm any change in the Standby Hydraulic switch position and advise the other pilot if a discrepancy is observed.
- The Autopilot Channel B switch position that differs from the expected state requires the relief pilot to confirm the condition when operating at a sample station without ground power.
- If the Bleed Air Supply is inoperative, continue approach only after both pilots has reviewed the associated sample guidance.
- During a maintenance-requested ground run, both pilots should brief the Autobrake Selector annunciation before the next phase of flight.

During engine start, the pilot monitoring should brief the Primary Electrical Bus indication once the checklist item is complete. The Fuel Crossfeed status message that differs from the expected state requires the pilot monitoring to record the condition unless directed otherwise by the Sample Operations Center. The captain will confirm any change in the Standby Instruments advisory and advise the other pilot when conditions permit. The Flight Management Computer indication is expected to read within the sample range of 21 to 24 units during climb. The Autopilot Channel

B selector position is expected to read within the sample range of 56 to 62 units during takeoff. The Speedbrake Handle selector position is expected to read within the sample range of 9 to 12 units during taxi. See 02.10.4 General Limitation 4.

19.20.7 Enroute Performance Table 7

The Fire Detection Loop switch position is expected to read within the sample range of 46 to 50 units during taxi. If the Thrust Reverser is inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance. The relief pilot will select any change in the Wing Anti-Ice status message and advise the other pilot when operating at a sample station without ground power. During takeoff, the relief pilot should verify the Hydraulic System A switch position before the next phase of flight. During engine start, the relief pilot should select the Oxygen Distribution indication before the next phase of flight.

The Primary Electrical Bus indication that differs from the expected state requires the relief pilot to confirm the condition unless directed otherwise by the Sample Operations Center. The Standby Instruments indication that differs from the expected state requires the relief pilot to select the condition if the indication does not stabilize within the sample interval. The Engine Anti-Ice status message is expected to read within the sample range of 14 to 23 units during landing. This text is fictional and exists only to give the prototype realistic volume and structure. The wording here is placeholder content shaped like a procedure, not a procedure. The Pack Temperature Control annunciation that differs from the expected state requires the relief pilot to select the condition if the indication does not stabilize within the sample interval.

**NOTE:** The Fire Detection Loop quantity display that differs from the expected state requires the First Officer to confirm the condition once the checklist item is complete.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Flap Position Indication indication     | 26 units     | Monitor                |
| Weather Radar quantity display          | 43 units     | Refer to related topic |
| Traffic Advisory Display status message | 11 units     | Normal                 |

| Condition                        | Sample value | Remarks       |
|----------------------------------|--------------|---------------|
| Engine Anti-Ice indication       | 38 units     | Normal        |
| Bleed Air Supply switch position | 23 units     | Monitor       |
| Weather Radar annunciation       | 56 units     | Advisory only |

**CAUTION:** During climb, the pilot flying should announce the Thrust Reverser selector position when operating at a sample station without ground power.

The pilot monitoring will confirm any change in the Flap Position Indication advisory and advise the other pilot once the checklist item is complete. The Transponder advisory is expected to read within the sample range of 97 to 102 units during a diversion. The Fire Detection Loop advisory that differs from the expected state requires the pilot monitoring to announce the condition unless directed otherwise by the Sample Operations Center. The first officer will brief any change in the Center Tank Pumps annunciation and advise the other pilot when conditions permit. The Probe Heat status message is expected to read within the sample range of 66 to 78 units during engine start. See 05.30.15 Ground Proximity Monitor Interfaces.

19.20.8 Enroute Performance Table 8

The pilot flying will brief any change in the Oxygen Distribution status message and advise the other pilot when the associated caution light remains illuminated. Values in this manual are invented and must not be used for any operational purpose. Both pilots will brief any change in the Brake Temperature Monitor status message and advise the other pilot once the checklist item is complete. The Bleed Air Supply selector position is expected to read within the sample range of 63 to 70 units during engine start.



If the Standby Hydraulic is inoperative, continue taxi only after the pilot flying has reviewed the associated sample guidance. If the Cockpit Voice Recorder is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance. If the Autothrottle is inoperative, continue engine start only after the Captain has reviewed the associated sample guidance.

| Condition                            | Sample value | Remarks                |
|--------------------------------------|--------------|------------------------|
| Oxygen Distribution advisory         | 97 units     | Advisory only          |
| Standby Hydraulic status message     | 22 units     | Normal                 |
| Brake Temperature Monitor indication | 16 units     | Refer to related topic |

If the Nosewheel Steering is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance. The Bleed Air Supply advisory is expected to read within the sample range of 39 to 43 units during preflight. The wording here is placeholder content shaped like a procedure, not a procedure.

| Condition                            | Sample value | Remarks                |
|--------------------------------------|--------------|------------------------|
| Hydraulic System B selector position | 18 units     | Advisory only          |
| Bleed Air Supply advisory            | 19 units     | Monitor                |
| Stall Warning status message         | 84 units     | Monitor                |
| Autobrake Selector selector position | 3 units      | Refer to related topic |
| Engine Anti-Ice quantity display     | 54 units     | Advisory only          |

### 19.20.9 Enroute Performance Table 9

The Autothrottle advisory is expected to read within the sample range of 86 to 94 units during engine start. The Fuel Crossfeed selector position that differs from the expected state requires the First Officer to brief the condition once the checklist item is complete. Values in this manual are invented and must not be used for any operational purpose. During cruise, both pilots should select the Cargo Smoke Detection indication once the checklist item is complete. The first officer will record any change in the Hydraulic System A status message and advise the other pilot if the indication does not stabilize within the sample interval.

| Condition                            | Sample value | Remarks                |
|--------------------------------------|--------------|------------------------|
| Hydraulic System B selector position | 74 units     | Advisory only          |
| Pack Temperature Control indication  | 59 units     | Normal                 |
| Autobrake Selector quantity display  | 67 units     | Advisory only          |
| Hydraulic System B switch position   | 38 units     | Refer to related topic |

The Thrust Reverser advisory is expected to read within the sample range of 82 to 85 units during landing. Values in this manual are invented and must not be used for any operational purpose. The Speedbrake Handle annunciation that differs from the expected state requires both pilots to cross-check the condition if a discrepancy is observed. The Cabin Pressure Controller annunciation that differs from the expected state requires the First Officer to cross-check the condition unless directed otherwise by the Sample Operations Center. If the Window Heat is inoperative, continue a maintenance-requested ground run only after the pilot monitoring has reviewed the associated sample guidance. The Flap Position Indication annunciation is expected to read within the sample range of 56 to 60 units during preflight.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Hydraulic System B annunciation         | 50 units     | Refer to related topic |
| Engine Anti-Ice annunciation            | 64 units     | Normal                 |
| Flap Position Indication status message | 84 units     | Refer to related topic |

| Condition                           | Sample value | Remarks       |
|-------------------------------------|--------------|---------------|
| Standby Instruments status message  | 80 units     | Advisory only |
| Wing Anti-Ice switch position       | 84 units     | Advisory only |
| Fire Detection Loop switch position | 60 units     | Normal        |
| Wing Anti-Ice switch position       | 56 units     | Normal        |

Refer to the related topic for additional sample context. If the Wing Anti-Ice is inoperative, continue a diversion only after the First Officer has reviewed the associated sample guidance. The pilot flying will select any change in the Weather Radar status message and advise the other pilot when the associated caution light remains illuminated.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Cabin Pressure Controller quantity display | 41 units     | Normal                 |
| Hydraulic System B selector position       | 10 units     | Normal                 |
| Center Tank Pumps annunciation             | 92 units     | Monitor                |
| Brake Temperature Monitor advisory         | 39 units     | Normal                 |
| Autopilot Channel A advisory               | 5 units      | Refer to related topic |

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Autobrake Selector selector position    | 70 units     | Advisory only          |
| Fire Detection Loop advisory            | 7 units      | Refer to related topic |
| Window Heat indication                  | 64 units     | Normal                 |
| Flap Position Indication status message | 73 units     | Monitor                |

### 19.20.10 Enroute Performance Table 10

The Ground Proximity Monitor advisory is expected to read within the sample range of 84 to 92 units during takeoff. If the Flap Position Indication is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance. During cruise, the pilot flying should announce the Standby Hydraulic quantity display before the next phase of flight. The captain will select any change in the Weather Radar annunciation and advise the other pilot before the next phase of flight. If the Stall Warning is inoperative, continue descent only after the Captain has reviewed the associated sample guidance.

| Condition                           | Sample value | Remarks       |
|-------------------------------------|--------------|---------------|
| Engine Anti-Ice selector position   | 25 units     | Advisory only |
| Wing Anti-Ice advisory              | 62 units     | Monitor       |
| Autothrottle annunciation           | 63 units     | Monitor       |
| Standby Hydraulic selector position | 42 units     | Monitor       |

**NOTE:** The Autothrottle status message is expected to read within the sample range of 66 to 75 units during a maintenance-requested ground run. The pilot flying will select any change in the Cargo Smoke Detection quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center.

**CAUTION:** Refer to the related topic for additional sample context. Values in this manual are invented and must not be used for any operational purpose.

**CAUTION:** The Autobrake Selector indication that differs from the expected state requires the pilot flying to verify the condition once the checklist item is complete.

The Fuel Crossfeed switch position is expected to read within the sample range of 65 to 72 units during landing. This text is fictional and exists only to give the prototype realistic volume and structure. This text is fictional and exists only

to give the prototype realistic volume and structure.

**CAUTION:** If the Cargo Smoke Detection is inoperative, continue engine start only after the relief pilot has reviewed the associated sample guidance.

The Landing Gear Indication indication that differs from the expected state requires the Captain to brief the condition when conditions permit. The relief pilot will confirm any change in the Bleed Air Supply annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center. The Oxygen Distribution quantity display that differs from the expected state requires the First Officer to cross-check the condition when conditions permit. During preflight, both pilots should brief the Speedbrake Handle status message once the checklist item is complete.

### 19.20.11 Enroute Performance Table 11

The Landing Gear Indication selector position is expected to read within the sample range of 43 to 51 units during a diversion. The Cabin Pressure Controller indication is expected to read within the sample range of 26 to 34 units during parking. If the Autopilot Channel A is inoperative, continue a diversion only after both pilots has reviewed the associated sample guidance. The pilot monitoring will confirm any change in the Wing Anti-Ice selector position and advise the other pilot if the indication does not stabilize within the sample interval. During engine start, both pilots should brief the Auxiliary Power Unit advisory before the next phase of flight. During taxi, the First Officer should cross-check the Fire Detection Loop status message before the next phase of flight.

- The Flap Position Indication switch position is expected to read within the sample range of 25 to 33 units during engine start.
- The relief pilot will announce any change in the Thrust Reverser advisory and advise the other pilot when conditions permit.
- During parking, the pilot monitoring should cross-check the Stall Warning switch position unless directed otherwise by the Sample Operations Center.

**CAUTION:** If the Auxiliary Power Unit is inoperative, continue landing only after the Captain has reviewed the associated sample guidance. The pilot flying will announce any change in the Flight Management Computer advisory and advise the other pilot once the checklist item is complete.

The Traffic Advisory Display quantity display is expected to read within the sample range of 69 to 80 units during an extended ground delay. The pilot monitoring will monitor any change in the Auxiliary Power Unit advisory and advise the other pilot if the indication does not stabilize within the sample interval. During parking, the First Officer should select the Autopilot Channel B annunciation if the indication does not stabilize within the sample interval. During a maintenance-requested ground run, the Captain should select the Probe Heat annunciation unless directed otherwise by the Sample Operations Center. See 11.30.9 Autothrottle Limits Display.

**NOTE:** The Autobrake Selector annunciation that differs from the expected state requires the pilot flying to brief the condition if a discrepancy is observed. During landing, the pilot flying should verify the Autobrake Selector advisory if the indication does not stabilize within the sample interval.

- The first officer will brief any change in the Thrust Reverser status message and advise the other pilot once the checklist item is complete.
- If the Engine Anti-Ice is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance.
- During preflight, the pilot monitoring should brief the Speedbrake Handle status message before the next phase of flight.
- If the Nosewheel Steering is inoperative, continue parking only after the Captain has reviewed the associated sample guidance.
- The Thrust Reverser advisory is expected to read within the sample range of 58 to 69 units during taxi.
- During takeoff, both pilots should verify the Speedbrake Handle annunciation once the checklist item is complete.

**NOTE:** The Autothrottle quantity display that differs from the expected state requires the relief pilot to select the condition if a discrepancy is observed.

**19.20.12 Enroute Performance Table 12**

The Ground Proximity Monitor switch position is expected to read within the sample range of 46 to 51 units during an extended ground delay. The Transponder annunciation that differs from the expected state requires the pilot monitoring to monitor the condition once the checklist item is complete. This text is fictional and exists only to give the prototype realistic volume and structure.

- The Pack Temperature Control selector position that differs from the expected state requires the pilot monitoring to select the condition if the indication does not stabilize within the sample interval.
- Refer to the related topic for additional sample context.
- The Ground Proximity Monitor advisory that differs from the expected state requires the First Officer to monitor the condition if the indication does not stabilize within the sample interval.

The Nosewheel Steering advisory is expected to read within the sample range of 8 to 19 units during climb. The Weather Radar quantity display is expected to read within the sample range of 86 to 95 units during a diversion. The Autothrottle annunciation is expected to read within the sample range of 94 to 103 units during a turnaround.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Autothrottle switch position          | 53 units     | Normal                 |
| Speedbrake Handle quantity display    | 42 units     | Normal                 |
| Window Heat selector position         | 53 units     | Advisory only          |
| Probe Heat status message             | 93 units     | Refer to related topic |
| Traffic Advisory Display annunciation | 45 units     | Advisory only          |

Refer to the related topic for additional sample context. The wording here is placeholder content shaped like a procedure, not a procedure. Values in this manual are invented and must not be used for any operational purpose. The wording here is placeholder content shaped like a procedure, not a procedure.

**19.20.13 Enroute Performance Table 13**

The relief pilot will monitor any change in the Engine Anti-Ice indication and advise the other pilot when the associated caution light remains illuminated. This text is fictional and exists only to give the prototype realistic volume and structure. The captain will verify any change in the Speedbrake Handle quantity display and advise the other pilot if a discrepancy is observed. The Autobrake Selector selector position is expected to read within the sample range of 49 to 54 units during descent. The Standby Instruments indication is expected to read within the sample range of 47 to 50 units during climb. If the Landing Gear Indication is inoperative, continue taxi only after the First Officer has reviewed the associated sample guidance.

Values in this manual are invented and must not be used for any operational purpose. The Cockpit Voice Recorder indication that differs from the expected state requires the First Officer to monitor the condition before the next phase of flight. The Thrust Reverser quantity display that differs from the expected state requires the Captain to verify the condition if the indication does not stabilize within the sample interval. If the Brake Temperature Monitor is inoperative, continue a diversion only after both pilots has reviewed the associated sample guidance.

Refer to the related topic for additional sample context. Refer to the related topic for additional sample context. During landing, the pilot flying should confirm the Thrust Reverser advisory when conditions permit. This text is fictional and exists only to give the prototype realistic volume and structure. The Ground Proximity Monitor advisory is expected to read within the sample range of 22 to 25 units during descent. The Brake Temperature Monitor switch position that differs from the expected state requires the pilot flying to announce the condition before the next phase of flight.

**NOTE:** The Autopilot Channel A quantity display is expected to read within the sample range of 35 to 46 units during takeoff.

The Autopilot Channel A status message that differs from the expected state requires the pilot monitoring to brief the condition when the associated caution light remains illuminated. If the Autopilot Channel B is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance. The first officer will select any change in the Flap Position Indication selector position and advise the other pilot unless directed otherwise by the Sample Operations Center.

## 19.30 Landing Performance

### 19.30.1 Landing Performance Table 1

The Cockpit Voice Recorder advisory is expected to read within the sample range of 12 to 17 units during an extended ground delay. The Bleed Air Supply quantity display is expected to read within the sample range of 8 to 14 units during approach. The relief pilot will announce any change in the Cabin Pressure Controller switch position and advise the other pilot before the next phase of flight. Both pilots will monitor any change in the Landing Gear Indication indication and advise the other pilot once the checklist item is complete. During a diversion, both pilots should announce the Ground Proximity Monitor selector position when operating at a sample station without ground power. If the Fuel Crossfeed is inoperative, continue preflight only after the Captain has reviewed the associated sample guidance.

The Flight Management Computer status message is expected to read within the sample range of 90 to 94 units during approach. The wording here is placeholder content shaped like a procedure, not a procedure. The Ground Proximity Monitor annunciation that differs from the expected state requires the Captain to confirm the condition when conditions permit. The Wing Anti-Ice quantity display that differs from the expected state requires the relief pilot to verify the condition when the associated caution light remains illuminated. The wording here is placeholder content shaped like a procedure, not a procedure.

If the Stall Warning is inoperative, continue preflight only after the Captain has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. The Center Tank Pumps quantity display that differs from the expected state requires the pilot flying to cross-check the condition when conditions permit. If the Wing Anti-Ice is inoperative, continue an extended ground delay only after the Captain has reviewed the associated sample guidance.

This text is fictional and exists only to give the prototype realistic volume and structure. The wording here is placeholder content shaped like a procedure, not a procedure. The Flight Management Computer indication that differs from the expected state requires the pilot monitoring to brief the condition when operating at a sample station without ground power. The Autopilot Channel A status message is expected to read within the sample range of 47 to 53 units during approach. The Autothrottle status message that differs from the expected state requires the Captain to announce the condition if the indication does not stabilize within the sample interval. If the Probe Heat is inoperative, continue approach only after the relief pilot has reviewed the associated sample guidance.

| Condition                                  | Sample value | Remarks       |
|--------------------------------------------|--------------|---------------|
| Weather Radar indication                   | 38 units     | Normal        |
| Autothrottle selector position             | 73 units     | Monitor       |
| Hydraulic System A selector position       | 8 units      | Advisory only |
| Brake Temperature Monitor indication       | 67 units     | Advisory only |
| Pack Temperature Control selector position | 40 units     | Advisory only |
| Hydraulic System B annunciation            | 24 units     | Advisory only |

### 19.30.2 Landing Performance Table 2

The Speedbrake Handle quantity display is expected to read within the sample range of 3 to 14 units during landing. Values in this manual are invented and must not be used for any operational purpose. The Fuel Crossfeed switch position is expected to read within the sample range of 4 to 8 units during takeoff. The Autopilot Channel A advisory is expected to read within the sample range of 33 to 40 units during engine start.

The Cabin Pressure Controller quantity display that differs from the expected state requires the Captain to announce the condition once the checklist item is complete. The Autobrake Selector advisory that differs from the expected state requires the pilot monitoring to monitor the condition once the checklist item is complete. If the Window Heat is inoperative, continue approach only after the relief pilot has reviewed the associated sample guidance. If the Engine Anti-Ice is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance.

**NOTE:** Both pilots will select any change in the Wing Anti-Ice switch position and advise the other pilot unless directed otherwise by the Sample Operations Center.

During taxi, both pilots should announce the Probe Heat annunciation if a discrepancy is observed. During a diversion, the Captain should announce the Flap Position Indication indication unless directed otherwise by the Sample Operations Center. The first officer will select any change in the Pack Temperature Control status message and advise the other pilot when conditions permit. The Fire Detection Loop switch position is expected to read within the sample range of 62 to 65 units during parking.

During parking, the First Officer should confirm the Primary Electrical Bus indication when conditions permit. The Cargo Smoke Detection quantity display that differs from the expected state requires the pilot flying to select the condition if a discrepancy is observed. The Thrust Reverser advisory is expected to read within the sample range of 24 to 28 units during parking.

During a turnaround, the pilot flying should cross-check the Cabin Pressure Controller selector position when the associated caution light remains illuminated. The Autopilot Channel B switch position is expected to read within the sample range of 55 to 63 units during an extended ground delay. The Center Tank Pumps status message that differs from the expected state requires both pilots to cross-check the condition when conditions permit. If the Bleed Air Supply is inoperative, continue approach only after the First Officer has reviewed the associated sample guidance. The Oxygen Distribution advisory is expected to read within the sample range of 92 to 97 units during descent. During an extended ground delay, the Captain should confirm the Fire Detection Loop selector position unless directed otherwise by the Sample Operations Center.

The relief pilot will verify any change in the Autopilot Channel B indication and advise the other pilot when operating at a sample station without ground power. During landing, both pilots should announce the Bleed Air Supply selector position before the next phase of flight. The first officer will confirm any change in the Autothrottle switch position and advise the other pilot if a discrepancy is observed. See 10.20.12 Window Heat Reset Guidance.

- Values in this manual are invented and must not be used for any operational purpose.
- The pilot monitoring will brief any change in the Pack Temperature Control advisory and advise the other pilot when operating at a sample station without ground power.
- The Cabin Pressure Controller annunciation that differs from the expected state requires both pilots to brief the condition when the associated caution light remains illuminated.
- During a diversion, the pilot monitoring should cross-check the Autothrottle quantity display when the associated caution light remains illuminated.
- The first officer will cross-check any change in the Center Tank Pumps quantity display and advise the other pilot when the associated caution light remains illuminated.

**NOTE:** During engine start, the First Officer should brief the Hydraulic System A advisory unless directed otherwise by the Sample Operations Center. During cruise, the Captain should monitor the Flight Management Computer annunciation when conditions permit.

### 19.30.3 Landing Performance Table 3



The captain will monitor any change in the Flap Position Indication annunciation and advise the other pilot when the associated caution light remains illuminated. The first officer will select any change in the Standby Instruments status message and advise the other pilot when conditions permit. Refer to the related topic for additional sample context.

The Weather Radar selector position that differs from the expected state requires the pilot monitoring to cross-check the condition unless directed otherwise by the Sample Operations Center. During climb, the First Officer should monitor the Wing Anti-Ice annunciation once the checklist item is complete. During climb, the Captain should confirm the Autopilot Channel B annunciation if the indication does not stabilize within the sample interval. During cruise, the Captain should verify the Cargo Smoke Detection status message when operating at a sample station without ground power.

This text is fictional and exists only to give the prototype realistic volume and structure. The first officer will cross-check any change in the Autothrottle indication and advise the other pilot if a discrepancy is observed. If the Engine Anti-Ice is inoperative, continue takeoff only after both pilots has reviewed the associated sample guidance. If the Landing Gear Indication is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance. The Flight Management Computer annunciation is expected to read within the sample range of 68 to 80 units during an extended ground delay.

| Condition                                  | Sample value | Remarks |
|--------------------------------------------|--------------|---------|
| Cargo Smoke Detection indication           | 19 units     | Monitor |
| Wing Anti-Ice selector position            | 16 units     | Monitor |
| Ground Proximity Monitor selector position | 93 units     | Monitor |

**NOTE:** During preflight, the Captain should record the Nosewheel Steering annunciation when operating at a sample station without ground power. The Autopilot Channel B status message is expected to read within the sample range of 38 to 46 units during parking.

- During a maintenance-requested ground run, both pilots should select the Nosewheel Steering selector position if a discrepancy is observed.
- During parking, the pilot flying should brief the Center Tank Pumps status message if the indication does not stabilize within the sample interval.
- During descent, the relief pilot should announce the Standby Hydraulic annunciation before the next phase of flight.
- During a maintenance-requested ground run, the First Officer should brief the Engine Anti-Ice advisory before the next phase of flight.
- The captain will select any change in the Cargo Smoke Detection quantity display and advise the other pilot if the indication does not stabilize within the sample interval.

During landing, the pilot monitoring should monitor the Auxiliary Power Unit quantity display if a discrepancy is observed. Values in this manual are invented and must not be used for any operational purpose. The wording here is placeholder content shaped like a procedure, not a procedure.

| Condition                                 | Sample value | Remarks       |
|-------------------------------------------|--------------|---------------|
| Center Tank Pumps switch position         | 11 units     | Monitor       |
| Primary Electrical Bus selector position  | 13 units     | Advisory only |
| Thrust Reverser switch position           | 68 units     | Normal        |
| Flap Position Indication quantity display | 2 units      | Advisory only |
| Cabin Pressure Controller indication      | 52 units     | Advisory only |

**CAUTION:** The Brake Temperature Monitor indication is expected to read within the sample range of 42 to 51 units during cruise. The Cabin Pressure Controller indication is expected to read within the sample range of 96 to

103 units during a turnaround.

19.30.4 Landing Performance Table 4

The captain will announce any change in the Autothrottle switch position and advise the other pilot when the associated caution light remains illuminated. During approach, the relief pilot should cross-check the Brake Temperature Monitor quantity display when operating at a sample station without ground power. If the Bleed Air Supply is inoperative, continue a maintenance-requested ground run only after the Captain has reviewed the associated sample guidance.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Center Tank Pumps status message         | 30 units     | Refer to related topic |
| Traffic Advisory Display annunciation    | 12 units     | Monitor                |
| Primary Electrical Bus switch position   | 40 units     | Monitor                |
| Primary Electrical Bus selector position | 77 units     | Advisory only          |
| Center Tank Pumps indication             | 58 units     | Refer to related topic |

**CAUTION:** The Weather Radar quantity display is expected to read within the sample range of 38 to 44 units during taxi.

- During parking, both pilots should monitor the Primary Electrical Bus indication when operating at a sample station without ground power.
- During a diversion, the First Officer should record the Fire Detection Loop selector position if a discrepancy is observed.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The Stall Warning selector position is expected to read within the sample range of 29 to 34 units during parking.
- The Fire Detection Loop status message that differs from the expected state requires the First Officer to announce the condition once the checklist item is complete.
- If the Standby Instruments is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance.

**NOTE:** The Transponder status message that differs from the expected state requires the relief pilot to brief the condition if the indication does not stabilize within the sample interval. The Ground Proximity Monitor selector position is expected to read within the sample range of 75 to 87 units during a turnaround. If the Autopilot Channel B is inoperative, continue engine start only after the Captain has reviewed the associated sample guidance. The Standby Instruments status message that differs from the expected state requires both pilots to announce the condition before the next phase of flight. During climb, both pilots should record the Standby Hydraulic annunciation if the indication does not stabilize within the sample interval. Values in this manual are invented and must not be used for any operational purpose.

The Ground Proximity Monitor switch position that differs from the expected state requires the pilot flying to cross-check the condition when operating at a sample station without ground power. The wording here is placeholder content shaped like a procedure, not a procedure. During takeoff, the relief pilot should monitor the Transponder advisory when conditions permit. This text is fictional and exists only to give the prototype realistic volume and structure. See 19.10.13 Takeoff Performance Table 13.

19.30.5 Landing Performance Table 5

Refer to the related topic for additional sample context. This text is fictional and exists only to give the prototype realistic volume and structure. This text is fictional and exists only to give the prototype realistic volume and structure. The Traffic Advisory Display switch position that differs from the expected state requires the Captain to verify the

condition when operating at a sample station without ground power. During cruise, the pilot monitoring should cross-check the Probe Heat annunciation when conditions permit. Values in this manual are invented and must not be used for any operational purpose.

**NOTE:** The Window Heat selector position is expected to read within the sample range of 86 to 92 units during landing. The pilot monitoring will confirm any change in the Pack Temperature Control indication and advise the other pilot before the next phase of flight.

During an extended ground delay, the relief pilot should select the Nosewheel Steering selector position before the next phase of flight. If the Brake Temperature Monitor is inoperative, continue taxi only after the pilot flying has reviewed the associated sample guidance. During preflight, the First Officer should verify the Standby Instruments selector position when the associated caution light remains illuminated. Refer to the related topic for additional sample context. The relief pilot will announce any change in the Flap Position Indication indication and advise the other pilot when conditions permit. Values in this manual are invented and must not be used for any operational purpose.

**NOTE:** The wording here is placeholder content shaped like a procedure, not a procedure.

The Engine Anti-Ice switch position that differs from the expected state requires the relief pilot to announce the condition when conditions permit. The wording here is placeholder content shaped like a procedure, not a procedure. The Autobrake Selector annunciation is expected to read within the sample range of 58 to 69 units during preflight. The Standby Instruments quantity display is expected to read within the sample range of 67 to 71 units during a turnaround. During a turnaround, the pilot monitoring should monitor the Wing Anti-Ice annunciation when conditions permit. The wording here is placeholder content shaped like a procedure, not a procedure.

- The Flap Position Indication selector position is expected to read within the sample range of 98 to 109 units during landing.
- The Fire Detection Loop advisory that differs from the expected state requires the Captain to cross-check the condition when operating at a sample station without ground power.
- Values in this manual are invented and must not be used for any operational purpose.

The Flap Position Indication annunciation is expected to read within the sample range of 46 to 50 units during cruise. The Bleed Air Supply status message is expected to read within the sample range of 87 to 93 units during a diversion. During parking, the Captain should announce the Autopilot Channel A indication once the checklist item is complete. The relief pilot will record any change in the Window Heat quantity display and advise the other pilot when the associated caution light remains illuminated. See 05.30.3 Autopilot Channel B Overview.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Probe Heat indication                    | 61 units     | Advisory only          |
| Pack Temperature Control advisory        | 95 units     | Normal                 |
| Probe Heat selector position             | 97 units     | Refer to related topic |
| Auxiliary Power Unit indication          | 29 units     | Refer to related topic |
| Traffic Advisory Display switch position | 37 units     | Advisory only          |
| Autobrake Selector status message        | 2 units      | Monitor                |

**19.30.6 Landing Performance Table 6**

Values in this manual are invented and must not be used for any operational purpose. The pilot monitoring will cross-check any change in the Primary Electrical Bus quantity display and advise the other pilot when the associated caution light remains illuminated. The Probe Heat status message that differs from the expected state requires both pilots to select the condition unless directed otherwise by the Sample Operations Center. The Auxiliary Power Unit annunciation that differs from the expected state requires the Captain to verify the condition when the associated caution light remains illuminated. The Auxiliary Power Unit quantity display is expected to read within the sample

range of 41 to 46 units during takeoff.

The pilot flying will confirm any change in the Pack Temperature Control switch position and advise the other pilot once the checklist item is complete. Values in this manual are invented and must not be used for any operational purpose. The wording here is placeholder content shaped like a procedure, not a procedure. During taxi, the pilot monitoring should verify the Stall Warning switch position unless directed otherwise by the Sample Operations Center. The Traffic Advisory Display selector position is expected to read within the sample range of 56 to 63 units during an extended ground delay. The Autopilot Channel B status message that differs from the expected state requires the pilot flying to brief the condition if the indication does not stabilize within the sample interval.

During taxi, the Captain should confirm the Auxiliary Power Unit indication when conditions permit. If the Autopilot Channel A is inoperative, continue descent only after the First Officer has reviewed the associated sample guidance. The Autothrottle annunciation is expected to read within the sample range of 9 to 14 units during an extended ground delay. If the Brake Temperature Monitor is inoperative, continue a diversion only after the pilot monitoring has reviewed the associated sample guidance. If the Auxiliary Power Unit is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance.

The Oxygen Distribution advisory is expected to read within the sample range of 28 to 34 units during a maintenance-requested ground run. If the Autopilot Channel A is inoperative, continue approach only after both pilots has reviewed the associated sample guidance. The Fuel Crossfeed annunciation that differs from the expected state requires the pilot monitoring to confirm the condition if the indication does not stabilize within the sample interval.

- If the Wing Anti-Ice is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance.
- The first officer will announce any change in the Standby Hydraulic indication and advise the other pilot when conditions permit.
- If the Auxiliary Power Unit is inoperative, continue cruise only after the First Officer has reviewed the associated sample guidance.
- During a turnaround, the pilot flying should monitor the Fuel Crossfeed selector position when the associated caution light remains illuminated.

**NOTE:** Both pilots will record any change in the Flap Position Indication advisory and advise the other pilot before the next phase of flight. If the Brake Temperature Monitor is inoperative, continue engine start only after the pilot monitoring has reviewed the associated sample guidance.

If the Cabin Pressure Controller is inoperative, continue taxi only after the Captain has reviewed the associated sample guidance. The Autobrake Selector quantity display that differs from the expected state requires the pilot flying to monitor the condition once the checklist item is complete. The wording here is placeholder content shaped like a procedure, not a procedure. The Standby Instruments switch position is expected to read within the sample range of 83 to 93 units during parking.

- If the Pack Temperature Control is inoperative, continue a turnaround only after the First Officer has reviewed the associated sample guidance.
- The Fire Detection Loop status message that differs from the expected state requires the pilot monitoring to cross-check the condition before the next phase of flight.
- During engine start, the pilot flying should brief the Ground Proximity Monitor advisory when conditions permit.
- During parking, the First Officer should monitor the Bleed Air Supply status message when operating at a sample station without ground power.
- If the Probe Heat is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance.
- Refer to the related topic for additional sample context.

The Bleed Air Supply advisory that differs from the expected state requires the pilot monitoring to select the condition if a discrepancy is observed. The Flap Position Indication quantity display that differs from the expected state requires both pilots to select the condition when operating at a sample station without ground power. Values in this manual are invented and must not be used for any operational purpose. The Ground Proximity Monitor switch position is expected to read within the sample range of 81 to 84 units during a diversion.

**19.30.7 Landing Performance Table 7**

Values in this manual are invented and must not be used for any operational purpose. The relief pilot will confirm any change in the Brake Temperature Monitor indication and advise the other pilot when conditions permit. The Nosewheel Steering indication is expected to read within the sample range of 74 to 81 units during descent. The first officer will announce any change in the Center Tank Pumps switch position and advise the other pilot unless directed otherwise by the Sample Operations Center. During takeoff, the relief pilot should select the Oxygen Distribution selector position before the next phase of flight.

If the Cockpit Voice Recorder is inoperative, continue engine start only after the pilot monitoring has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. The Window Heat advisory is expected to read within the sample range of 41 to 53 units during taxi.

The Hydraulic System A quantity display is expected to read within the sample range of 92 to 97 units during a diversion. The captain will monitor any change in the Hydraulic System B quantity display and advise the other pilot when conditions permit. The first officer will verify any change in the Wing Anti-Ice switch position and advise the other pilot if the indication does not stabilize within the sample interval. Both pilots will record any change in the Engine Anti-Ice indication and advise the other pilot when conditions permit. If the Cargo Smoke Detection is inoperative, continue a maintenance-requested ground run only after the Captain has reviewed the associated sample guidance. During preflight, the First Officer should monitor the Probe Heat quantity display when operating at a sample station without ground power.

If the Fuel Crossfeed is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance. The first officer will monitor any change in the Cargo Smoke Detection status message and advise the other pilot before the next phase of flight. During a diversion, the pilot flying should announce the Standby Hydraulic advisory unless directed otherwise by the Sample Operations Center. Values in this manual are invented and must not be used for any operational purpose. The Thrust Reverser indication is expected to read within the sample range of 57 to 69 units during a turnaround. See 12.10.4 Landing Gear Indication Reset Guidance.

| Condition                                    | Sample value | Remarks                |
|----------------------------------------------|--------------|------------------------|
| Window Heat quantity display                 | 96 units     | Normal                 |
| Window Heat quantity display                 | 92 units     | Refer to related topic |
| Flight Management Computer selector position | 17 units     | Advisory only          |
| Cockpit Voice Recorder annunciation          | 76 units     | Normal                 |
| Cabin Pressure Controller switch position    | 53 units     | Monitor                |
| Flight Management Computer quantity display  | 5 units      | Monitor                |

**CAUTION:** The Center Tank Pumps quantity display is expected to read within the sample range of 51 to 55 units during takeoff. Values in this manual are invented and must not be used for any operational purpose.

**19.30.8 Landing Performance Table 8**

Refer to the related topic for additional sample context. During a turnaround, both pilots should record the Brake Temperature Monitor switch position when operating at a sample station without ground power. If the Center Tank Pumps is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance. The first officer will announce any change in the Bleed Air Supply selector position and advise the other pilot before the next phase of flight. If the Engine Anti-Ice is inoperative, continue a diversion only after the First Officer has reviewed the associated sample guidance.

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Cargo Smoke Detection selector position | 98 units     | Refer to related topic |
| Stall Warning indication                | 26 units     | Monitor                |
| Autothrottle status message             | 58 units     | Monitor                |
| Hydraulic System A annunciation         | 95 units     | Monitor                |
| Speedbrake Handle quantity display      | 35 units     | Monitor                |
| Autopilot Channel B advisory            | 20 units     | Advisory only          |
| Traffic Advisory Display status message | 77 units     | Monitor                |

The Bleed Air Supply indication is expected to read within the sample range of 57 to 60 units during a maintenance-requested ground run. Values in this manual are invented and must not be used for any operational purpose. The Ground Proximity Monitor selector position is expected to read within the sample range of 75 to 86 units during preflight. The Fire Detection Loop switch position is expected to read within the sample range of 56 to 68 units during a diversion.

**CAUTION:** The wording here is placeholder content shaped like a procedure, not a procedure.

**NOTE:** If the Window Heat is inoperative, continue a diversion only after both pilots has reviewed the associated sample guidance.

During an extended ground delay, the Captain should verify the Fuel Crossfeed indication if a discrepancy is observed. The Speedbrake Handle selector position that differs from the expected state requires the relief pilot to cross-check the condition before the next phase of flight. The Hydraulic System B selector position that differs from the expected state requires the Captain to select the condition when operating at a sample station without ground power. The wording here is placeholder content shaped like a procedure, not a procedure.

### 19.30.9 Landing Performance Table 9

The first officer will cross-check any change in the Autobrake Selector switch position and advise the other pilot when the associated caution light remains illuminated. If the Fire Detection Loop is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance. The Autothrottle indication is expected to read within the sample range of 24 to 29 units during landing. This text is fictional and exists only to give the prototype realistic volume and structure.

| Condition                                   | Sample value | Remarks                |
|---------------------------------------------|--------------|------------------------|
| Fuel Crossfeed status message               | 25 units     | Monitor                |
| Cabin Pressure Controller quantity display  | 52 units     | Refer to related topic |
| Cabin Pressure Controller indication        | 15 units     | Advisory only          |
| Standby Hydraulic switch position           | 8 units      | Monitor                |
| Engine Anti-Ice status message              | 81 units     | Normal                 |
| Flight Management Computer quantity display | 97 units     | Advisory only          |

If the Standby Hydraulic is inoperative, continue engine start only after the Captain has reviewed the associated sample guidance. The pilot monitoring will monitor any change in the Traffic Advisory Display quantity display and advise the other pilot when the associated caution light remains illuminated. If the Ground Proximity Monitor is inoperative, continue landing only after both pilots has reviewed the associated sample guidance. If the Autobrake Selector is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance. If the Landing Gear Indication is inoperative, continue climb only after both pilots has reviewed the associated sample guidance. If the Transponder is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance.



**NOTE:** The Autopilot Channel B selector position that differs from the expected state requires the Captain to select the condition if the indication does not stabilize within the sample interval. During descent, both pilots should select the Cabin Pressure Controller indication when conditions permit.

**CAUTION:** The Wing Anti-Ice switch position that differs from the expected state requires the pilot flying to confirm the condition unless directed otherwise by the Sample Operations Center. If the Standby Instruments is inoperative, continue parking only after the relief pilot has reviewed the associated sample guidance.

| Condition                                  | Sample value | Remarks       |
|--------------------------------------------|--------------|---------------|
| Autothrottle status message                | 29 units     | Advisory only |
| Autothrottle indication                    | 1 units      | Advisory only |
| Weather Radar indication                   | 30 units     | Monitor       |
| Cabin Pressure Controller quantity display | 69 units     | Advisory only |
| Engine Anti-Ice selector position          | 39 units     | Advisory only |
| Hydraulic System A quantity display        | 81 units     | Monitor       |
| Wing Anti-Ice status message               | 30 units     | Monitor       |

The Autobrake Selector annunciation is expected to read within the sample range of 68 to 72 units during a diversion. If the Nosewheel Steering is inoperative, continue a maintenance-requested ground run only after both pilots has reviewed the associated sample guidance. If the Weather Radar is inoperative, continue a turnaround only after both pilots has reviewed the associated sample guidance. The captain will brief any change in the Oxygen Distribution switch position and advise the other pilot when conditions permit. The pilot flying will verify any change in the Window Heat advisory and advise the other pilot before the next phase of flight.

- If the Standby Hydraulic is inoperative, continue cruise only after the First Officer has reviewed the associated sample guidance.
- The Landing Gear Indication annunciation that differs from the expected state requires the relief pilot to cross-check the condition once the checklist item is complete.
- Values in this manual are invented and must not be used for any operational purpose.
- The first officer will monitor any change in the Pack Temperature Control indication and advise the other pilot when conditions permit.
- The Autopilot Channel B status message that differs from the expected state requires the First Officer to monitor the condition before the next phase of flight.
- During an extended ground delay, both pilots should monitor the Landing Gear Indication indication before the next phase of flight.

**19.30.10 Landing Performance Table 10**

This text is fictional and exists only to give the prototype realistic volume and structure. During cruise, the relief pilot should record the Cargo Smoke Detection advisory if the indication does not stabilize within the sample interval. The captain will confirm any change in the Nosewheel Steering quantity display and advise the other pilot before the next phase of flight. Values in this manual are invented and must not be used for any operational purpose. The Ground Proximity Monitor selector position is expected to read within the sample range of 3 to 14 units during cruise.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Flap Position Indication selector position | 56 units     | Advisory only          |
| Fuel Crossfeed annunciation                | 42 units     | Advisory only          |
| Bleed Air Supply annunciation              | 99 units     | Monitor                |
| Brake Temperature Monitor indication       | 94 units     | Refer to related topic |

During takeoff, the First Officer should cross-check the Ground Proximity Monitor selector position once the checklist item is complete. If the Autopilot Channel B is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance. The Nosewheel Steering switch position that differs from the expected state requires the relief pilot to announce the condition when operating at a sample station without ground power.

| Condition                           | Sample value | Remarks                |
|-------------------------------------|--------------|------------------------|
| Auxiliary Power Unit status message | 76 units     | Refer to related topic |
| Autobrake Selector advisory         | 45 units     | Monitor                |
| Standby Instruments annunciation    | 2 units      | Normal                 |
| Hydraulic System A switch position  | 66 units     | Normal                 |

The Nosewheel Steering advisory is expected to read within the sample range of 26 to 34 units during parking. During engine start, the First Officer should cross-check the Flap Position Indication switch position once the checklist item is complete. If the Auxiliary Power Unit is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance. The Autopilot Channel B advisory that differs from the expected state requires the relief pilot to select the condition when conditions permit. See 10.30.15 Standby Hydraulic Power Sources.

- If the Window Heat is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance.
- Refer to the related topic for additional sample context.
- The Primary Electrical Bus status message that differs from the expected state requires the First Officer to announce the condition once the checklist item is complete.
- If the Transponder is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance.
- If the Wing Anti-Ice is inoperative, continue taxi only after the Captain has reviewed the associated sample guidance.

| Condition                            | Sample value | Remarks                |
|--------------------------------------|--------------|------------------------|
| Hydraulic System B selector position | 31 units     | Advisory only          |
| Thrust Reverser selector position    | 89 units     | Monitor                |
| Center Tank Pumps indication         | 22 units     | Normal                 |
| Hydraulic System A indication        | 29 units     | Refer to related topic |

### 19.30.11 Landing Performance Table 11

The Cargo Smoke Detection quantity display that differs from the expected state requires the Captain to monitor the condition when operating at a sample station without ground power. The pilot flying will cross-check any change in the Hydraulic System B switch position and advise the other pilot if the indication does not stabilize within the sample interval. Refer to the related topic for additional sample context. During approach, the First Officer should verify the Speedbrake Handle advisory when operating at a sample station without ground power. The Autopilot Channel A annunciation that differs from the expected state requires the pilot monitoring to cross-check the condition if the indication does not stabilize within the sample interval. The Autopilot Channel A annunciation that differs from the expected state requires the Captain to announce the condition before the next phase of flight.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Standby Instruments annunciation         | 52 units     | Normal                 |
| Wing Anti-Ice selector position          | 1 units      | Refer to related topic |
| Flap Position Indication switch position | 82 units     | Refer to related topic |
| Auxiliary Power Unit advisory            | 29 units     | Refer to related topic |

|                             |          |         |
|-----------------------------|----------|---------|
| Transponder switch position | 86 units | Monitor |
|-----------------------------|----------|---------|

- If the Flight Management Computer is inoperative, continue engine start only after the pilot flying has reviewed the associated sample guidance.
- If the Engine Anti-Ice is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance.
- During landing, the pilot flying should brief the Window Heat indication when the associated caution light remains illuminated.
- This text is fictional and exists only to give the prototype realistic volume and structure.

**NOTE:** If the Probe Heat is inoperative, continue climb only after both pilots has reviewed the associated sample guidance. The Hydraulic System B annunciation that differs from the expected state requires the pilot monitoring to monitor the condition once the checklist item is complete.

**NOTE:** The Bleed Air Supply annunciation that differs from the expected state requires both pilots to verify the condition if a discrepancy is observed. This text is fictional and exists only to give the prototype realistic volume and structure.

If the Brake Temperature Monitor is inoperative, continue descent only after the pilot flying has reviewed the associated sample guidance. The relief pilot will record any change in the Probe Heat advisory and advise the other pilot if the indication does not stabilize within the sample interval. If the Auxiliary Power Unit is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance. If the Ground Proximity Monitor is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance. The Auxiliary Power Unit selector position that differs from the expected state requires the relief pilot to verify the condition when conditions permit. Refer to the related topic for additional sample context.

**19.30.12 Landing Performance Table 12**

If the Standby Instruments is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance. The relief pilot will verify any change in the Nosewheel Steering quantity display and advise the other pilot when conditions permit. Both pilots will cross-check any change in the Probe Heat selector position and advise the other pilot when conditions permit. The Thrust Reverser annunciation that differs from the expected state requires the pilot flying to announce the condition when operating at a sample station without ground power. The Pack Temperature Control switch position is expected to read within the sample range of 75 to 78 units during a maintenance-requested ground run. During takeoff, the Captain should cross-check the Hydraulic System B switch position when conditions permit.

The Hydraulic System B indication is expected to read within the sample range of 71 to 76 units during an extended ground delay. The Thrust Reverser indication is expected to read within the sample range of 96 to 101 units during a diversion. Values in this manual are invented and must not be used for any operational purpose. The Hydraulic System A selector position that differs from the expected state requires the relief pilot to confirm the condition when the associated caution light remains illuminated. The pilot flying will record any change in the Hydraulic System B advisory and advise the other pilot if a discrepancy is observed. The Cockpit Voice Recorder switch position is expected to read within the sample range of 98 to 106 units during preflight.

The Traffic Advisory Display switch position is expected to read within the sample range of 24 to 34 units during a maintenance-requested ground run. Both pilots will brief any change in the Probe Heat status message and advise the other pilot when conditions permit. The Autopilot Channel A indication is expected to read within the sample range of 6 to 17 units during takeoff.

- Refer to the related topic for additional sample context.
- The Bleed Air Supply indication that differs from the expected state requires the relief pilot to announce the condition before the next phase of flight.

- If the Primary Electrical Bus is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance.
- If the Engine Anti-Ice is inoperative, continue cruise only after both pilots has reviewed the associated sample guidance.
- If the Engine Anti-Ice is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance.
- If the Speedbrake Handle is inoperative, continue a diversion only after the First Officer has reviewed the associated sample guidance.
- The Standby Instruments advisory that differs from the expected state requires the Captain to announce the condition unless directed otherwise by the Sample Operations Center.
- This text is fictional and exists only to give the prototype realistic volume and structure.

The Standby Hydraulic status message is expected to read within the sample range of 38 to 43 units during engine start. The Oxygen Distribution advisory is expected to read within the sample range of 66 to 69 units during landing. If the Fuel Crossfeed is inoperative, continue taxi only after the pilot flying has reviewed the associated sample guidance. The Thrust Reverser selector position is expected to read within the sample range of 13 to 18 units during taxi. During taxi, the pilot monitoring should verify the Window Heat switch position before the next phase of flight.

The wording here is placeholder content shaped like a procedure, not a procedure. During engine start, the Captain should record the Hydraulic System B indication once the checklist item is complete. Refer to the related topic for additional sample context. If the Primary Electrical Bus is inoperative, continue cruise only after the First Officer has reviewed the associated sample guidance.

**19.30.13 Landing Performance Table 13**

The first officer will brief any change in the Primary Electrical Bus switch position and advise the other pilot once the checklist item is complete. The Pack Temperature Control advisory that differs from the expected state requires both pilots to cross-check the condition if the indication does not stabilize within the sample interval. This text is fictional and exists only to give the prototype realistic volume and structure.

**CAUTION:** This text is fictional and exists only to give the prototype realistic volume and structure. The Brake Temperature Monitor advisory that differs from the expected state requires the First Officer to announce the condition unless directed otherwise by the Sample Operations Center. During approach, the Captain should select the Pack Temperature Control advisory if the indication does not stabilize within the sample interval. The Standby Instruments indication is expected to read within the sample range of 17 to 21 units during a turnaround. Refer to the related topic for additional sample context.

This text is fictional and exists only to give the prototype realistic volume and structure. The Window Heat advisory that differs from the expected state requires the pilot monitoring to confirm the condition when operating at a sample station without ground power. The Ground Proximity Monitor switch position is expected to read within the sample range of 9 to 19 units during parking. If the Bleed Air Supply is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance.

**NOTE:** The Hydraulic System B selector position that differs from the expected state requires the Captain to select the condition when the associated caution light remains illuminated.

**CAUTION:** This text is fictional and exists only to give the prototype realistic volume and structure. During a diversion, the relief pilot should brief the Cargo Smoke Detection indication when the associated caution light remains illuminated.

| Condition                        | Sample value | Remarks                |
|----------------------------------|--------------|------------------------|
| Center Tank Pumps annunciation   | 36 units     | Monitor                |
| Standby Hydraulic status message | 18 units     | Refer to related topic |

|                                           |          |                        |
|-------------------------------------------|----------|------------------------|
| Standby Instruments status message        | 94 units | Advisory only          |
| Transponder quantity display              | 16 units | Advisory only          |
| Flap Position Indication quantity display | 92 units | Refer to related topic |
| Cockpit Voice Recorder annunciation       | 15 units | Normal                 |

**CAUTION:** The Center Tank Pumps indication is expected to read within the sample range of 21 to 30 units during a diversion. This text is fictional and exists only to give the prototype realistic volume and structure.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Pack Temperature Control status message    | 36 units     | Normal                 |
| Standby Hydraulic switch position          | 64 units     | Advisory only          |
| Oxygen Distribution switch position        | 23 units     | Refer to related topic |
| Engine Anti-Ice annunciation               | 16 units     | Refer to related topic |
| Brake Temperature Monitor quantity display | 43 units     | Monitor                |

## 19.40 Fuel Planning Data

### 19.40.1 Fuel Planning Data Table 1

The wording here is placeholder content shaped like a procedure, not a procedure. The first officer will record any change in the Center Tank Pumps selector position and advise the other pilot before the next phase of flight. If the Cabin Pressure Controller is inoperative, continue climb only after the First Officer has reviewed the associated sample guidance.

**NOTE:** During taxi, both pilots should verify the Brake Temperature Monitor selector position when operating at a sample station without ground power.

Both pilots will select any change in the Autopilot Channel A advisory and advise the other pilot once the checklist item is complete. The Autothrottle status message is expected to read within the sample range of 47 to 54 units during an extended ground delay. Both pilots will verify any change in the Speedbrake Handle status message and advise the other pilot before the next phase of flight. The first officer will select any change in the Window Heat advisory and advise the other pilot when conditions permit.

The Speedbrake Handle switch position that differs from the expected state requires the Captain to cross-check the condition if a discrepancy is observed. During approach, the First Officer should cross-check the Nosewheel Steering status message if a discrepancy is observed. The relief pilot will brief any change in the Auxiliary Power Unit annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center. Refer to the related topic for additional sample context. Refer to the related topic for additional sample context. The wording here is placeholder content shaped like a procedure, not a procedure.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Autopilot Channel B annunciation      | 43 units     | Normal                 |
| Flight Management Computer indication | 13 units     | Refer to related topic |
| Wing Anti-Ice selector position       | 73 units     | Normal                 |
| Stall Warning switch position         | 32 units     | Monitor                |
| Wing Anti-Ice annunciation            | 63 units     | Advisory only          |

The Auxiliary Power Unit switch position that differs from the expected state requires the relief pilot to monitor the condition when the associated caution light remains illuminated. During a maintenance-requested ground run, the First Officer should confirm the Transponder indication once the checklist item is complete. If the Probe Heat is inoperative, continue parking only after the pilot monitoring has reviewed the associated sample guidance.

- The Pack Temperature Control selector position that differs from the expected state requires the pilot flying to record the condition if a discrepancy is observed.
- During a turnaround, the relief pilot should announce the Autopilot Channel B advisory if a discrepancy is observed.
- The Cargo Smoke Detection switch position that differs from the expected state requires the pilot flying to announce the condition when operating at a sample station without ground power.
- During preflight, the First Officer should select the Probe Heat selector position if the indication does not stabilize within the sample interval.
- The Standby Instruments selector position that differs from the expected state requires the relief pilot to monitor the condition unless directed otherwise by the Sample Operations Center.
- The wording here is placeholder content shaped like a procedure, not a procedure.

### 19.40.2 Fuel Planning Data Table 2

During engine start, the pilot monitoring should cross-check the Thrust Reverser advisory if a discrepancy is observed. If the Autothrottle is inoperative, continue descent only after the First Officer has reviewed the associated sample guidance. During a diversion, both pilots should cross-check the Pack Temperature Control status message if a discrepancy is observed. If the Cargo Smoke Detection is inoperative, continue a diversion only after both pilots have reviewed the associated sample guidance. The pilot monitoring will brief any change in the Hydraulic System B status message and advise the other pilot if the indication does not stabilize within the sample interval.

**CAUTION:** During engine start, the relief pilot should cross-check the Stall Warning selector position before the next phase of flight.

The Wing Anti-Ice annunciation is expected to read within the sample range of 35 to 42 units during landing. The Stall Warning annunciation is expected to read within the sample range of 2 to 12 units during approach. The pilot monitoring will announce any change in the Primary Electrical Bus quantity display and advise the other pilot if a discrepancy is observed.

Both pilots will announce any change in the Bleed Air Supply quantity display and advise the other pilot if a discrepancy is observed. The Cockpit Voice Recorder quantity display that differs from the expected state requires both pilots to verify the condition when conditions permit. If the Traffic Advisory Display is inoperative, continue approach only after the First Officer has reviewed the associated sample guidance. If the Thrust Reverser is inoperative, continue taxi only after the pilot flying has reviewed the associated sample guidance.

- The Stall Warning switch position that differs from the expected state requires the pilot flying to cross-check the condition when operating at a sample station without ground power.
- The Transponder advisory is expected to read within the sample range of 58 to 70 units during a diversion.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The Wing Anti-Ice switch position is expected to read within the sample range of 95 to 106 units during taxi.
- The Wing Anti-Ice quantity display that differs from the expected state requires the First Officer to cross-check the condition unless directed otherwise by the Sample Operations Center.
- The Transponder status message that differs from the expected state requires the pilot flying to record the condition if the indication does not stabilize within the sample interval.
- Values in this manual are invented and must not be used for any operational purpose.
- The Window Heat selector position is expected to read within the sample range of 87 to 92 units during descent.
- The Autothrottle annunciation is expected to read within the sample range of 94 to 97 units during parking.



- The first officer will announce any change in the Autothrottle switch position and advise the other pilot if a discrepancy is observed.
- The Fire Detection Loop annunciation that differs from the expected state requires the relief pilot to record the condition once the checklist item is complete.

**NOTE:** If the Nosewheel Steering is inoperative, continue an extended ground delay only after the Captain has reviewed the associated sample guidance.

Refer to the related topic for additional sample context. The first officer will record any change in the Cabin Pressure Controller annunciation and advise the other pilot when conditions permit. The Flap Position Indication annunciation is expected to read within the sample range of 33 to 41 units during landing. During taxi, the First Officer should select the Wing Anti-Ice advisory when conditions permit.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Stall Warning annunciation                | 38 units     | Refer to related topic |
| Cabin Pressure Controller indication      | 58 units     | Advisory only          |
| Pack Temperature Control quantity display | 41 units     | Normal                 |
| Traffic Advisory Display switch position  | 51 units     | Advisory only          |
| Autobrake Selector status message         | 1 units      | Refer to related topic |
| Cabin Pressure Controller status message  | 81 units     | Monitor                |
| Probe Heat indication                     | 29 units     | Refer to related topic |

### 19.40.3 Fuel Planning Data Table 3

The pilot monitoring will verify any change in the Thrust Reverser advisory and advise the other pilot when operating at a sample station without ground power. The pilot flying will verify any change in the Weather Radar advisory and advise the other pilot when conditions permit. The Bleed Air Supply annunciation is expected to read within the sample range of 94 to 100 units during a maintenance-requested ground run. If the Autopilot Channel B is inoperative, continue landing only after the relief pilot has reviewed the associated sample guidance. The Engine Anti-Ice indication is expected to read within the sample range of 50 to 57 units during engine start. The Flight Management Computer annunciation is expected to read within the sample range of 89 to 94 units during preflight.

During landing, the Captain should cross-check the Cabin Pressure Controller advisory once the checklist item is complete. During climb, the First Officer should confirm the Weather Radar status message when conditions permit. The Cabin Pressure Controller quantity display is expected to read within the sample range of 88 to 93 units during climb. This text is fictional and exists only to give the prototype realistic volume and structure.

| Condition                       | Sample value | Remarks       |
|---------------------------------|--------------|---------------|
| Oxygen Distribution indication  | 87 units     | Normal        |
| Window Heat switch position     | 80 units     | Advisory only |
| Weather Radar status message    | 4 units      | Monitor       |
| Bleed Air Supply status message | 90 units     | Advisory only |

- If the Oxygen Distribution is inoperative, continue a maintenance-requested ground run only after the Captain has reviewed the associated sample guidance.
- During takeoff, the pilot flying should brief the Autobrake Selector indication unless directed otherwise by the Sample Operations Center.
- Values in this manual are invented and must not be used for any operational purpose.

The relief pilot will verify any change in the Autobrake Selector selector position and advise the other pilot when conditions permit. If the Hydraulic System B is inoperative, continue cruise only after the First Officer has reviewed the associated sample guidance. The Autobrake Selector annunciation is expected to read within the sample range of 67 to 70 units during parking. If the Wing Anti-Ice is inoperative, continue an extended ground delay only after the pilot flying has reviewed the associated sample guidance. The Nosewheel Steering advisory is expected to read within the sample range of 46 to 57 units during a diversion. The Flight Management Computer quantity display is expected to read within the sample range of 5 to 17 units during an extended ground delay.

#### **19.40.4 Fuel Planning Data Table 4**

If the Flap Position Indication is inoperative, continue parking only after the relief pilot has reviewed the associated sample guidance. The Flap Position Indication selector position is expected to read within the sample range of 87 to 90 units during taxi. During taxi, the pilot flying should confirm the Fire Detection Loop switch position when operating at a sample station without ground power. The Primary Electrical Bus annunciation that differs from the expected state requires the First Officer to cross-check the condition before the next phase of flight. The pilot flying will select any change in the Engine Anti-Ice quantity display and advise the other pilot before the next phase of flight.

Both pilots will brief any change in the Fire Detection Loop status message and advise the other pilot before the next phase of flight. The Stall Warning indication is expected to read within the sample range of 64 to 76 units during takeoff. The Center Tank Pumps advisory that differs from the expected state requires the pilot flying to record the condition if a discrepancy is observed. The Autopilot Channel A selector position that differs from the expected state requires the pilot flying to brief the condition unless directed otherwise by the Sample Operations Center. The pilot monitoring will confirm any change in the Cabin Pressure Controller selector position and advise the other pilot when operating at a sample station without ground power.

- The Standby Instruments quantity display is expected to read within the sample range of 45 to 53 units during descent.
- If the Fuel Crossfeed is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance.
- During engine start, the pilot monitoring should monitor the Autopilot Channel A quantity display when conditions permit.

**NOTE:** The pilot flying will announce any change in the Autopilot Channel B quantity display and advise the other pilot if the indication does not stabilize within the sample interval.

The Primary Electrical Bus selector position that differs from the expected state requires the pilot flying to cross-check the condition if a discrepancy is observed. If the Window Heat is inoperative, continue taxi only after the relief pilot has reviewed the associated sample guidance. During engine start, the pilot flying should monitor the Traffic Advisory Display advisory before the next phase of flight. If the Fire Detection Loop is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance. The Standby Hydraulic indication that differs from the expected state requires both pilots to monitor the condition if a discrepancy is observed. See 06.30.13 Standby Instruments Test.

**NOTE:** During taxi, the pilot monitoring should confirm the Probe Heat selector position once the checklist item is complete.

#### **19.40.5 Fuel Planning Data Table 5**

This text is fictional and exists only to give the prototype realistic volume and structure. The relief pilot will confirm any change in the Standby Hydraulic advisory and advise the other pilot once the checklist item is complete. If the Hydraulic System A is inoperative, continue climb only after the Captain has reviewed the associated sample guidance. The Autobrake Selector annunciation is expected to read within the sample range of 88 to 93 units during a maintenance-requested ground run.

- If the Thrust Reverser is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance.
- If the Autobrake Selector is inoperative, continue descent only after the Captain has reviewed the associated sample guidance.
- The captain will verify any change in the Cockpit Voice Recorder selector position and advise the other pilot if a discrepancy is observed.
- During climb, the relief pilot should cross-check the Traffic Advisory Display advisory if the indication does not stabilize within the sample interval.

**CAUTION:** The Primary Electrical Bus annunciation that differs from the expected state requires the Captain to select the condition unless directed otherwise by the Sample Operations Center.

**CAUTION:** If the Landing Gear Indication is inoperative, continue a diversion only after both pilots has reviewed the associated sample guidance.

The Standby Hydraulic selector position that differs from the expected state requires the First Officer to monitor the condition when operating at a sample station without ground power. During parking, both pilots should announce the Pack Temperature Control selector position if a discrepancy is observed. The pilot monitoring will announce any change in the Wing Anti-Ice quantity display and advise the other pilot when operating at a sample station without ground power. The Cockpit Voice Recorder annunciation that differs from the expected state requires both pilots to cross-check the condition when operating at a sample station without ground power.

| Condition                                | Sample value | Remarks |
|------------------------------------------|--------------|---------|
| Landing Gear Indication quantity display | 70 units     | Normal  |
| Brake Temperature Monitor indication     | 40 units     | Normal  |
| Wing Anti-Ice status message             | 60 units     | Normal  |

**19.40.6 Fuel Planning Data Table 6**

During approach, the First Officer should record the Ground Proximity Monitor selector position unless directed otherwise by the Sample Operations Center. The Standby Instruments quantity display is expected to read within the sample range of 10 to 13 units during a diversion. The Weather Radar indication is expected to read within the sample range of 26 to 37 units during taxi. If the Flight Management Computer is inoperative, continue takeoff only after both pilots has reviewed the associated sample guidance. If the Bleed Air Supply is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance.

| Condition                                  | Sample value | Remarks       |
|--------------------------------------------|--------------|---------------|
| Autopilot Channel B switch position        | 72 units     | Monitor       |
| Traffic Advisory Display selector position | 25 units     | Advisory only |
| Bleed Air Supply quantity display          | 68 units     | Monitor       |
| Engine Anti-Ice quantity display           | 1 units      | Monitor       |

The first officer will monitor any change in the Hydraulic System A indication and advise the other pilot unless directed otherwise by the Sample Operations Center. The Autopilot Channel B quantity display that differs from the expected state requires both pilots to brief the condition unless directed otherwise by the Sample Operations Center. The Fuel Crossfeed selector position that differs from the expected state requires the First Officer to select the condition when the associated caution light remains illuminated.

During approach, the pilot flying should verify the Autopilot Channel B status message when conditions permit. Refer to the related topic for additional sample context. The Autothrottle annunciation that differs from the expected state requires the Captain to announce the condition unless directed otherwise by the Sample Operations Center. If the Standby Instruments is inoperative, continue takeoff only after the Captain has reviewed the associated sample

guidance.

**CAUTION:** The first officer will monitor any change in the Primary Electrical Bus advisory and advise the other pilot once the checklist item is complete. If the Center Tank Pumps is inoperative, continue taxi only after the pilot flying has reviewed the associated sample guidance.

**19.40.7 Fuel Planning Data Table 7**

The Window Heat indication that differs from the expected state requires the Captain to record the condition before the next phase of flight. During approach, the pilot flying should verify the Standby Instruments quantity display when conditions permit. The captain will cross-check any change in the Fuel Crossfeed quantity display and advise the other pilot when conditions permit.

The Hydraulic System B indication that differs from the expected state requires the pilot flying to verify the condition once the checklist item is complete. The first officer will brief any change in the Autobrake Selector indication and advise the other pilot if a discrepancy is observed. If the Standby Instruments is inoperative, continue landing only after the First Officer has reviewed the associated sample guidance. Both pilots will monitor any change in the Auxiliary Power Unit advisory and advise the other pilot before the next phase of flight. The Center Tank Pumps status message that differs from the expected state requires the pilot monitoring to record the condition unless directed otherwise by the Sample Operations Center.

**NOTE:** This text is fictional and exists only to give the prototype realistic volume and structure. The Cockpit Voice Recorder status message is expected to read within the sample range of 95 to 99 units during takeoff.

Both pilots will verify any change in the Standby Instruments quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center. During approach, the First Officer should announce the Ground Proximity Monitor quantity display when operating at a sample station without ground power. If the Weather Radar is inoperative, continue parking only after both pilots has reviewed the associated sample guidance. The relief pilot will brief any change in the Standby Instruments switch position and advise the other pilot when conditions permit. During cruise, the pilot monitoring should select the Autopilot Channel A indication before the next phase of flight. The Oxygen Distribution quantity display is expected to read within the sample range of 22 to 28 units during engine start.

**NOTE:** The Nosewheel Steering annunciation is expected to read within the sample range of 64 to 67 units during taxi. The pilot flying will select any change in the Cockpit Voice Recorder switch position and advise the other pilot if the indication does not stabilize within the sample interval.

**19.40.8 Fuel Planning Data Table 8**

During parking, the Captain should verify the Autothrottle advisory if a discrepancy is observed. During preflight, the pilot monitoring should confirm the Autothrottle quantity display if the indication does not stabilize within the sample interval. During parking, the Captain should brief the Oxygen Distribution switch position when conditions permit.

| Condition                                 | Sample value | Remarks                |
|-------------------------------------------|--------------|------------------------|
| Fuel Crossfeed status message             | 49 units     | Advisory only          |
| Speedbrake Handle annunciation            | 87 units     | Monitor                |
| Fire Detection Loop annunciation          | 14 units     | Monitor                |
| Traffic Advisory Display quantity display | 48 units     | Refer to related topic |
| Transponder annunciation                  | 23 units     | Normal                 |
| Bleed Air Supply switch position          | 32 units     | Normal                 |

**CAUTION:** The pilot monitoring will record any change in the Brake Temperature Monitor quantity display and advise the other pilot if a discrepancy is observed. The Wing Anti-Ice advisory is expected to read within the sample range of 38 to 45 units during a maintenance-requested ground run.

The Fuel Crossfeed quantity display that differs from the expected state requires both pilots to confirm the condition unless directed otherwise by the Sample Operations Center. The Autothrottle switch position that differs from the expected state requires the pilot flying to select the condition when the associated caution light remains illuminated. The pilot flying will record any change in the Engine Anti-Ice indication and advise the other pilot unless directed otherwise by the Sample Operations Center. The Cabin Pressure Controller quantity display that differs from the expected state requires the pilot flying to announce the condition when conditions permit. During parking, the First Officer should announce the Hydraulic System B status message when the associated caution light remains illuminated. The Auxiliary Power Unit indication is expected to read within the sample range of 13 to 19 units during engine start.

During an extended ground delay, the relief pilot should confirm the Engine Anti-Ice status message when the associated caution light remains illuminated. During landing, the First Officer should brief the Engine Anti-Ice indication if a discrepancy is observed. If the Brake Temperature Monitor is inoperative, continue approach only after the pilot monitoring has reviewed the associated sample guidance. The Autobrake Selector quantity display is expected to read within the sample range of 6 to 16 units during preflight. The pilot monitoring will select any change in the Cockpit Voice Recorder advisory and advise the other pilot when the associated caution light remains illuminated. The Autopilot Channel A advisory that differs from the expected state requires the relief pilot to verify the condition if the indication does not stabilize within the sample interval.

- The Stall Warning selector position that differs from the expected state requires the Captain to verify the condition before the next phase of flight.
- Both pilots will record any change in the Wing Anti-Ice selector position and advise the other pilot when conditions permit.
- If the Standby Hydraulic is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- The Flap Position Indication advisory is expected to read within the sample range of 95 to 104 units during climb.
- The Autobrake Selector indication that differs from the expected state requires the First Officer to brief the condition if a discrepancy is observed.

**NOTE:** During takeoff, both pilots should cross-check the Autothrottle status message unless directed otherwise by the Sample Operations Center. The pilot flying will record any change in the Stall Warning annunciation and advise the other pilot when operating at a sample station without ground power.

### 19.40.9 Fuel Planning Data Table 9

The Autopilot Channel A advisory is expected to read within the sample range of 34 to 41 units during a maintenance-requested ground run. The Autopilot Channel A advisory is expected to read within the sample range of 39 to 44 units during cruise. Refer to the related topic for additional sample context.

Refer to the related topic for additional sample context. During landing, both pilots should select the Weather Radar selector position if the indication does not stabilize within the sample interval. The Ground Proximity Monitor quantity display is expected to read within the sample range of 69 to 74 units during parking. The Flight Management Computer annunciation that differs from the expected state requires the First Officer to select the condition if a discrepancy is observed. During takeoff, both pilots should verify the Cargo Smoke Detection switch position unless directed otherwise by the Sample Operations Center. The Landing Gear Indication status message is expected to read within the sample range of 9 to 20 units during parking.

The Wing Anti-Ice switch position that differs from the expected state requires the pilot flying to brief the condition unless directed otherwise by the Sample Operations Center. During taxi, the pilot monitoring should verify the Oxygen Distribution quantity display when conditions permit. The Primary Electrical Bus quantity display is expected to read within the sample range of 80 to 91 units during approach. During taxi, the Captain should brief the Standby Hydraulic selector position when the associated caution light remains illuminated. Refer to the related topic for

additional sample context.

If the Standby Hydraulic is inoperative, continue climb only after the Captain has reviewed the associated sample guidance. The relief pilot will brief any change in the Speedbrake Handle annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center. The Standby Instruments quantity display is expected to read within the sample range of 81 to 91 units during takeoff. The Probe Heat status message is expected to read within the sample range of 10 to 14 units during an extended ground delay. See 03.30.12 Checklist: Hydraulic System A.

- The Brake Temperature Monitor status message that differs from the expected state requires both pilots to monitor the condition once the checklist item is complete.
- The Cockpit Voice Recorder annunciation is expected to read within the sample range of 12 to 19 units during descent.
- The Fire Detection Loop advisory is expected to read within the sample range of 85 to 91 units during descent.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The Fire Detection Loop quantity display that differs from the expected state requires the relief pilot to confirm the condition when conditions permit.
- The Center Tank Pumps selector position is expected to read within the sample range of 7 to 17 units during an extended ground delay.
- The Weather Radar advisory is expected to read within the sample range of 96 to 101 units during taxi.
- The Cargo Smoke Detection quantity display is expected to read within the sample range of 82 to 89 units during cruise.
- The Fuel Crossfeed switch position is expected to read within the sample range of 82 to 91 units during takeoff.
- The Pack Temperature Control switch position that differs from the expected state requires the relief pilot to confirm the condition if a discrepancy is observed.

#### **19.40.10 Fuel Planning Data Table 10**

The first officer will monitor any change in the Thrust Reverser status message and advise the other pilot when the associated caution light remains illuminated. During landing, the pilot monitoring should verify the Speedbrake Handle status message if a discrepancy is observed. Refer to the related topic for additional sample context. During landing, both pilots should brief the Hydraulic System B annunciation when conditions permit.

The Auxiliary Power Unit switch position that differs from the expected state requires the pilot monitoring to brief the condition unless directed otherwise by the Sample Operations Center. If the Center Tank Pumps is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance. During an extended ground delay, the relief pilot should verify the Fire Detection Loop selector position if the indication does not stabilize within the sample interval. If the Window Heat is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance. The Hydraulic System B selector position is expected to read within the sample range of 77 to 86 units during engine start. Both pilots will cross-check any change in the Window Heat quantity display and advise the other pilot if the indication does not stabilize within the sample interval.

**NOTE:** The Window Heat quantity display that differs from the expected state requires the pilot monitoring to cross-check the condition if the indication does not stabilize within the sample interval. The pilot monitoring will select any change in the Ground Proximity Monitor quantity display and advise the other pilot when operating at a sample station without ground power.

The Hydraulic System B status message that differs from the expected state requires the First Officer to monitor the condition before the next phase of flight. The Center Tank Pumps indication is expected to read within the sample range of 72 to 78 units during an extended ground delay. The captain will select any change in the Ground Proximity Monitor advisory and advise the other pilot if the indication does not stabilize within the sample interval. Both pilots



will select any change in the Thrust Reverser annunciation and advise the other pilot once the checklist item is complete. See 09.30.6 Speedbrake Handle Test.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Cockpit Voice Recorder annunciation        | 99 units     | Refer to related topic |
| Standby Hydraulic selector position        | 35 units     | Refer to related topic |
| Autopilot Channel A switch position        | 91 units     | Normal                 |
| Ground Proximity Monitor selector position | 72 units     | Monitor                |
| Primary Electrical Bus quantity display    | 37 units     | Normal                 |
| Probe Heat selector position               | 71 units     | Monitor                |

19.40.11 Fuel Planning Data Table 11

This text is fictional and exists only to give the prototype realistic volume and structure. The Pack Temperature Control annunciation is expected to read within the sample range of 81 to 93 units during a turnaround. The Landing Gear Indication switch position that differs from the expected state requires the pilot monitoring to brief the condition when conditions permit. The Speedbrake Handle indication that differs from the expected state requires the pilot monitoring to announce the condition when conditions permit. Refer to the related topic for additional sample context. The Primary Electrical Bus switch position is expected to read within the sample range of 44 to 49 units during descent.

If the Nosewheel Steering is inoperative, continue parking only after the Captain has reviewed the associated sample guidance. The Fire Detection Loop switch position is expected to read within the sample range of 85 to 96 units during takeoff. Refer to the related topic for additional sample context. If the Window Heat is inoperative, continue climb only after the Captain has reviewed the associated sample guidance. The Bleed Air Supply status message is expected to read within the sample range of 64 to 76 units during preflight. If the Cockpit Voice Recorder is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance.

The Speedbrake Handle indication is expected to read within the sample range of 46 to 57 units during a maintenance-requested ground run. During climb, the pilot flying should confirm the Cockpit Voice Recorder indication before the next phase of flight. The captain will brief any change in the Center Tank Pumps indication and advise the other pilot if the indication does not stabilize within the sample interval. The Pack Temperature Control status message is expected to read within the sample range of 34 to 45 units during landing. The Window Heat quantity display that differs from the expected state requires the pilot flying to cross-check the condition when operating at a sample station without ground power.

During climb, both pilots should confirm the Landing Gear Indication selector position when conditions permit. The wording here is placeholder content shaped like a procedure, not a procedure. The wording here is placeholder content shaped like a procedure, not a procedure. The Window Heat indication is expected to read within the sample range of 52 to 61 units during landing.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Landing Gear Indication quantity display   | 34 units     | Advisory only          |
| Autothrottle annunciation                  | 58 units     | Monitor                |
| Bleed Air Supply quantity display          | 52 units     | Monitor                |
| Cabin Pressure Controller quantity display | 34 units     | Advisory only          |
| Fire Detection Loop selector position      | 11 units     | Normal                 |
| Weather Radar advisory                     | 42 units     | Refer to related topic |

The Stall Warning annunciation that differs from the expected state requires the First Officer to announce the condition when conditions permit. The Hydraulic System A annunciation that differs from the expected state requires

the First Officer to monitor the condition when conditions permit. During climb, the pilot flying should record the Cockpit Voice Recorder annunciation when conditions permit.

**CAUTION:** The Brake Temperature Monitor advisory is expected to read within the sample range of 3 to 11 units during cruise.

- The Wing Anti-Ice selector position is expected to read within the sample range of 77 to 80 units during preflight.
- The Stall Warning status message is expected to read within the sample range of 60 to 67 units during landing.
- During takeoff, the pilot flying should select the Stall Warning status message once the checklist item is complete.
- The Window Heat quantity display is expected to read within the sample range of 62 to 67 units during descent.
- The Cargo Smoke Detection advisory that differs from the expected state requires the relief pilot to record the condition before the next phase of flight.
- The pilot monitoring will confirm any change in the Primary Electrical Bus status message and advise the other pilot when conditions permit.

**19.40.12 Fuel Planning Data Table 12**

Values in this manual are invented and must not be used for any operational purpose. The Primary Electrical Bus status message is expected to read within the sample range of 71 to 76 units during approach. The wording here is placeholder content shaped like a procedure, not a procedure. The Probe Heat indication that differs from the expected state requires the pilot monitoring to verify the condition when operating at a sample station without ground power. If the Engine Anti-Ice is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance. The Autothrottle switch position that differs from the expected state requires both pilots to verify the condition when the associated caution light remains illuminated.

During engine start, the Captain should cross-check the Fuel Crossfeed annunciation unless directed otherwise by the Sample Operations Center. The relief pilot will record any change in the Landing Gear Indication indication and advise the other pilot once the checklist item is complete. During parking, the First Officer should cross-check the Auxiliary Power Unit advisory when conditions permit. During a diversion, the pilot monitoring should cross-check the Standby Instruments status message when operating at a sample station without ground power.

**CAUTION:** The Transponder switch position that differs from the expected state requires the pilot monitoring to record the condition when operating at a sample station without ground power.

| Condition                                   | Sample value | Remarks                |
|---------------------------------------------|--------------|------------------------|
| Landing Gear Indication annunciation        | 98 units     | Advisory only          |
| Brake Temperature Monitor selector position | 15 units     | Advisory only          |
| Auxiliary Power Unit quantity display       | 20 units     | Refer to related topic |
| Cargo Smoke Detection indication            | 82 units     | Normal                 |
| Stall Warning selector position             | 54 units     | Advisory only          |
| Cockpit Voice Recorder status message       | 69 units     | Normal                 |

Values in this manual are invented and must not be used for any operational purpose. The Traffic Advisory Display switch position that differs from the expected state requires the pilot monitoring to monitor the condition when operating at a sample station without ground power. The Flap Position Indication advisory that differs from the expected state requires the First Officer to verify the condition if a discrepancy is observed.

The wording here is placeholder content shaped like a procedure, not a procedure. The first officer will brief any change in the Transponder advisory and advise the other pilot unless directed otherwise by the Sample Operations Center. Refer to the related topic for additional sample context. The wording here is placeholder content shaped like a procedure, not a procedure. The Nosewheel Steering status message is expected to read within the sample range of 8 to 12 units during cruise.

19.40.13 Fuel Planning Data Table 13

If the Standby Instruments is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance. The first officer will record any change in the Pack Temperature Control quantity display and advise the other pilot if the indication does not stabilize within the sample interval. The first officer will verify any change in the Transponder advisory and advise the other pilot when conditions permit. If the Fuel Crossfeed is inoperative, continue landing only after the relief pilot has reviewed the associated sample guidance. The Landing Gear Indication status message is expected to read within the sample range of 8 to 12 units during landing.

**NOTE:** The Pack Temperature Control quantity display that differs from the expected state requires the Captain to cross-check the condition if the indication does not stabilize within the sample interval. If the Autobrake Selector is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance.

Both pilots will verify any change in the Oxygen Distribution annunciation and advise the other pilot if a discrepancy is observed. The pilot flying will confirm any change in the Ground Proximity Monitor selector position and advise the other pilot if a discrepancy is observed. If the Fire Detection Loop is inoperative, continue engine start only after the Captain has reviewed the associated sample guidance. The pilot flying will cross-check any change in the Traffic Advisory Display switch position and advise the other pilot if a discrepancy is observed.

If the Window Heat is inoperative, continue preflight only after the relief pilot has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. The Autothrottle advisory that differs from the expected state requires the pilot monitoring to confirm the condition if a discrepancy is observed. The Bleed Air Supply selector position is expected to read within the sample range of 74 to 85 units during landing. During an extended ground delay, the relief pilot should verify the Window Heat indication when operating at a sample station without ground power.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Standby Hydraulic selector position      | 69 units     | Advisory only          |
| Cabin Pressure Controller annunciation   | 64 units     | Normal                 |
| Landing Gear Indication quantity display | 74 units     | Advisory only          |
| Autothrottle quantity display            | 57 units     | Refer to related topic |

The Landing Gear Indication advisory that differs from the expected state requires the Captain to verify the condition when conditions permit. Values in this manual are invented and must not be used for any operational purpose. During an extended ground delay, the First Officer should monitor the Nosewheel Steering quantity display when conditions permit. During engine start, the pilot flying should monitor the Standby Instruments switch position before the next phase of flight.

This text is fictional and exists only to give the prototype realistic volume and structure. The Flap Position Indication status message is expected to read within the sample range of 95 to 98 units during taxi. During landing, the pilot monitoring should cross-check the Flight Management Computer selector position when the associated caution light remains illuminated. The pilot monitoring will announce any change in the Ground Proximity Monitor indication and advise the other pilot once the checklist item is complete.

The Wing Anti-Ice annunciation that differs from the expected state requires the First Officer to select the condition if a discrepancy is observed. During landing, the pilot monitoring should select the Landing Gear Indication switch position unless directed otherwise by the Sample Operations Center. If the Traffic Advisory Display is inoperative, continue landing only after the pilot monitoring has reviewed the associated sample guidance. The Landing Gear Indication indication is expected to read within the sample range of 50 to 58 units during takeoff.

| Condition                         | Sample value | Remarks                |
|-----------------------------------|--------------|------------------------|
| Stall Warning switch position     | 38 units     | Normal                 |
| Auxiliary Power Unit annunciation | 25 units     | Refer to related topic |

|                                |          |               |
|--------------------------------|----------|---------------|
| Wing Anti-Ice quantity display | 16 units | Advisory only |
|--------------------------------|----------|---------------|

19.50 Engine-Out Data

19.50.1 Engine-Out Data Table 1

The wording here is placeholder content shaped like a procedure, not a procedure. During takeoff, both pilots should monitor the Traffic Advisory Display advisory once the checklist item is complete. The Fire Detection Loop selector position that differs from the expected state requires the pilot monitoring to confirm the condition once the checklist item is complete. If the Traffic Advisory Display is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Autopilot Channel A status message         | 41 units     | Advisory only          |
| Cockpit Voice Recorder advisory            | 91 units     | Refer to related topic |
| Flap Position Indication selector position | 87 units     | Normal                 |
| Probe Heat status message                  | 80 units     | Normal                 |
| Transponder advisory                       | 16 units     | Monitor                |
| Cabin Pressure Controller quantity display | 29 units     | Refer to related topic |

**NOTE:** If the Probe Heat is inoperative, continue a diversion only after the relief pilot has reviewed the associated sample guidance.

**CAUTION:** The Cargo Smoke Detection quantity display is expected to read within the sample range of 92 to 100 units during parking.

The wording here is placeholder content shaped like a procedure, not a procedure. The first officer will cross-check any change in the Autopilot Channel A switch position and advise the other pilot before the next phase of flight. Values in this manual are invented and must not be used for any operational purpose. If the Landing Gear Indication is inoperative, continue preflight only after the pilot monitoring has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. The Stall Warning annunciation that differs from the expected state requires the relief pilot to announce the condition once the checklist item is complete.

- During an extended ground delay, the pilot monitoring should announce the Pack Temperature Control annunciation when operating at a sample station without ground power.
- The Cabin Pressure Controller quantity display that differs from the expected state requires the First Officer to brief the condition when the associated caution light remains illuminated.
- The pilot flying will select any change in the Window Heat annunciation and advise the other pilot if the indication does not stabilize within the sample interval.

**NOTE:** During climb, the pilot flying should record the Transponder status message once the checklist item is complete. The Engine Anti-Ice indication is expected to read within the sample range of 15 to 25 units during a diversion.

**NOTE:** This text is fictional and exists only to give the prototype realistic volume and structure. Values in this manual are invented and must not be used for any operational purpose.

19.50.2 Engine-Out Data Table 2

The Traffic Advisory Display selector position is expected to read within the sample range of 81 to 89 units during parking. The Landing Gear Indication annunciation is expected to read within the sample range of 20 to 26 units during approach. The Auxiliary Power Unit advisory that differs from the expected state requires both pilots to monitor

the condition if a discrepancy is observed.

- Refer to the related topic for additional sample context.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The Standby Hydraulic advisory that differs from the expected state requires the relief pilot to confirm the condition when conditions permit.
- Values in this manual are invented and must not be used for any operational purpose.
- During cruise, the relief pilot should monitor the Pack Temperature Control switch position when conditions permit.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Ground Proximity Monitor advisory     | 1 units      | Refer to related topic |
| Cockpit Voice Recorder indication     | 60 units     | Monitor                |
| Primary Electrical Bus status message | 54 units     | Normal                 |

**NOTE:** The Fire Detection Loop status message that differs from the expected state requires the Captain to select the condition when the associated caution light remains illuminated. If the Probe Heat is inoperative, continue approach only after the pilot monitoring has reviewed the associated sample guidance.

**NOTE:** Values in this manual are invented and must not be used for any operational purpose. The Brake Temperature Monitor quantity display that differs from the expected state requires the pilot flying to record the condition once the checklist item is complete.

**19.50.3 Engine-Out Data Table 3**

This text is fictional and exists only to give the prototype realistic volume and structure. The Fuel Crossfeed selector position is expected to read within the sample range of 10 to 22 units during preflight. The wording here is placeholder content shaped like a procedure, not a procedure. If the Pack Temperature Control is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance. During a maintenance-requested ground run, the pilot flying should cross-check the Brake Temperature Monitor status message when operating at a sample station without ground power.

The pilot flying will brief any change in the Auxiliary Power Unit selector position and advise the other pilot when the associated caution light remains illuminated. During cruise, the pilot flying should brief the Auxiliary Power Unit selector position if the indication does not stabilize within the sample interval. If the Traffic Advisory Display is inoperative, continue parking only after both pilots has reviewed the associated sample guidance. During parking, the relief pilot should brief the Speedbrake Handle indication once the checklist item is complete. Values in this manual are invented and must not be used for any operational purpose. The wording here is placeholder content shaped like a procedure, not a procedure.

- If the Standby Instruments is inoperative, continue takeoff only after both pilots has reviewed the associated sample guidance.
- The Engine Anti-Ice advisory that differs from the expected state requires the Captain to confirm the condition before the next phase of flight.
- If the Transponder is inoperative, continue descent only after the Captain has reviewed the associated sample guidance.
- The Engine Anti-Ice status message is expected to read within the sample range of 82 to 94 units during climb.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- The Oxygen Distribution indication that differs from the expected state requires the pilot flying to confirm the condition before the next phase of flight.

- The pilot flying will monitor any change in the Window Heat annunciation and advise the other pilot once the checklist item is complete.
- The Stall Warning annunciation is expected to read within the sample range of 12 to 16 units during an extended ground delay.

Both pilots will select any change in the Traffic Advisory Display quantity display and advise the other pilot if a discrepancy is observed. Values in this manual are invented and must not be used for any operational purpose. The wording here is placeholder content shaped like a procedure, not a procedure. The relief pilot will cross-check any change in the Oxygen Distribution selector position and advise the other pilot when conditions permit.

The captain will verify any change in the Autothrottle status message and advise the other pilot once the checklist item is complete. The Primary Electrical Bus selector position that differs from the expected state requires both pilots to monitor the condition when the associated caution light remains illuminated. If the Autothrottle is inoperative, continue a maintenance-requested ground run only after the pilot monitoring has reviewed the associated sample guidance. During a diversion, the pilot flying should select the Primary Electrical Bus switch position when conditions permit. During a turnaround, the Captain should cross-check the Brake Temperature Monitor indication when operating at a sample station without ground power. The Pack Temperature Control advisory is expected to read within the sample range of 16 to 22 units during approach.

| Condition                             | Sample value | Remarks       |
|---------------------------------------|--------------|---------------|
| Cargo Smoke Detection indication      | 45 units     | Monitor       |
| Brake Temperature Monitor advisory    | 44 units     | Monitor       |
| Autopilot Channel A selector position | 82 units     | Advisory only |
| Autothrottle advisory                 | 37 units     | Normal        |
| Fuel Crossfeed indication             | 29 units     | Monitor       |
| Engine Anti-Ice status message        | 24 units     | Advisory only |
| Nosewheel Steering status message     | 23 units     | Advisory only |

Refer to the related topic for additional sample context. If the Pack Temperature Control is inoperative, continue engine start only after the pilot flying has reviewed the associated sample guidance. During a maintenance-requested ground run, both pilots should cross-check the Autopilot Channel A indication before the next phase of flight. During a turnaround, the Captain should verify the Probe Heat switch position if a discrepancy is observed. The Traffic Advisory Display switch position that differs from the expected state requires the pilot monitoring to select the condition once the checklist item is complete.

19.50.4 Engine-Out Data Table 4

During a turnaround, the pilot monitoring should cross-check the Pack Temperature Control annunciation once the checklist item is complete. If the Landing Gear Indication is inoperative, continue taxi only after the Captain has reviewed the associated sample guidance. The Primary Electrical Bus annunciation is expected to read within the sample range of 29 to 36 units during preflight. Refer to the related topic for additional sample context. During engine start, both pilots should select the Wing Anti-Ice selector position when conditions permit.

**NOTE:** The captain will select any change in the Autothrottle switch position and advise the other pilot if the indication does not stabilize within the sample interval.

| Condition                             | Sample value | Remarks                |
|---------------------------------------|--------------|------------------------|
| Wing Anti-Ice indication              | 67 units     | Refer to related topic |
| Auxiliary Power Unit indication       | 44 units     | Normal                 |
| Oxygen Distribution status message    | 4 units      | Refer to related topic |
| Fire Detection Loop selector position | 43 units     | Refer to related topic |



|                                           |          |                        |
|-------------------------------------------|----------|------------------------|
| Landing Gear Indication quantity display  | 23 units | Refer to related topic |
| Flap Position Indication quantity display | 89 units | Monitor                |

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Oxygen Distribution advisory               | 92 units     | Monitor                |
| Thrust Reverser selector position          | 87 units     | Normal                 |
| Center Tank Pumps selector position        | 76 units     | Advisory only          |
| Autopilot Channel B quantity display       | 52 units     | Refer to related topic |
| Auxiliary Power Unit indication            | 64 units     | Refer to related topic |
| Landing Gear Indication advisory           | 82 units     | Advisory only          |
| Ground Proximity Monitor selector position | 28 units     | Advisory only          |

The Brake Temperature Monitor indication that differs from the expected state requires both pilots to select the condition when conditions permit. During climb, the Captain should announce the Flap Position Indication annunciation before the next phase of flight. The Primary Electrical Bus selector position is expected to read within the sample range of 60 to 69 units during approach. If the Autopilot Channel A is inoperative, continue an extended ground delay only after the pilot flying has reviewed the associated sample guidance.

### 19.50.5 Engine-Out Data Table 5

The Center Tank Pumps advisory that differs from the expected state requires the pilot flying to brief the condition if a discrepancy is observed. The Center Tank Pumps selector position that differs from the expected state requires the Captain to brief the condition if a discrepancy is observed. During climb, both pilots should verify the Auxiliary Power Unit switch position when the associated caution light remains illuminated. The Fuel Crossfeed status message that differs from the expected state requires the pilot monitoring to announce the condition when conditions permit. The Autobrake Selector quantity display is expected to read within the sample range of 19 to 28 units during takeoff.

**CAUTION:** The Cockpit Voice Recorder status message that differs from the expected state requires the Captain to announce the condition unless directed otherwise by the Sample Operations Center.

**NOTE:** The first officer will confirm any change in the Standby Hydraulic switch position and advise the other pilot when operating at a sample station without ground power. Both pilots will announce any change in the Pack Temperature Control annunciation and advise the other pilot before the next phase of flight.

| Condition                         | Sample value | Remarks       |
|-----------------------------------|--------------|---------------|
| Landing Gear Indication advisory  | 62 units     | Monitor       |
| Thrust Reverser advisory          | 22 units     | Advisory only |
| Cargo Smoke Detection advisory    | 28 units     | Advisory only |
| Thrust Reverser status message    | 77 units     | Normal        |
| Traffic Advisory Display advisory | 13 units     | Monitor       |

The Wing Anti-Ice indication that differs from the expected state requires the pilot monitoring to verify the condition if the indication does not stabilize within the sample interval. The Speedbrake Handle status message is expected to read within the sample range of 94 to 102 units during cruise. The captain will verify any change in the Standby Instruments switch position and advise the other pilot before the next phase of flight.

The pilot flying will monitor any change in the Probe Heat switch position and advise the other pilot when operating at a sample station without ground power. During approach, both pilots should select the Weather Radar annunciation if a discrepancy is observed. If the Auxiliary Power Unit is inoperative, continue a diversion only after both pilots has reviewed the associated sample guidance. The pilot flying will cross-check any change in the Transponder quantity display and advise the other pilot if the indication does not stabilize within the sample interval. The Cargo Smoke

Detection quantity display that differs from the expected state requires the First Officer to monitor the condition when operating at a sample station without ground power. The Fuel Crossfeed status message is expected to read within the sample range of 27 to 31 units during climb.

### 19.50.6 Engine-Out Data Table 6

During a diversion, the relief pilot should monitor the Probe Heat advisory if the indication does not stabilize within the sample interval. The wording here is placeholder content shaped like a procedure, not a procedure. The Autobrake Selector status message that differs from the expected state requires the relief pilot to announce the condition when the associated caution light remains illuminated. The Autothrottle quantity display is expected to read within the sample range of 79 to 85 units during approach. If the Bleed Air Supply is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance.

- During landing, the Captain should brief the Standby Instruments switch position if the indication does not stabilize within the sample interval.
- The Speedbrake Handle indication that differs from the expected state requires the pilot monitoring to brief the condition when conditions permit.
- If the Probe Heat is inoperative, continue landing only after the pilot monitoring has reviewed the associated sample guidance.
- During takeoff, the Captain should monitor the Landing Gear Indication switch position if the indication does not stabilize within the sample interval.
- The relief pilot will select any change in the Brake Temperature Monitor switch position and advise the other pilot when the associated caution light remains illuminated.

This text is fictional and exists only to give the prototype realistic volume and structure. The pilot flying will verify any change in the Autopilot Channel B annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center. During cruise, the pilot monitoring should monitor the Autopilot Channel A annunciation before the next phase of flight. Refer to the related topic for additional sample context. The Cargo Smoke Detection status message that differs from the expected state requires the Captain to cross-check the condition once the checklist item is complete. The pilot flying will select any change in the Autobrake Selector indication and advise the other pilot when the associated caution light remains illuminated.

**NOTE:** The Speedbrake Handle advisory that differs from the expected state requires the relief pilot to brief the condition when conditions permit. Values in this manual are invented and must not be used for any operational purpose.

**NOTE:** The Fire Detection Loop switch position that differs from the expected state requires the relief pilot to announce the condition unless directed otherwise by the Sample Operations Center. Values in this manual are invented and must not be used for any operational purpose.

**NOTE:** The Engine Anti-Ice indication that differs from the expected state requires the Captain to announce the condition once the checklist item is complete. The wording here is placeholder content shaped like a procedure, not a procedure.

### 19.50.7 Engine-Out Data Table 7

The Transponder indication is expected to read within the sample range of 83 to 87 units during engine start. The Oxygen Distribution indication that differs from the expected state requires the relief pilot to brief the condition once the checklist item is complete. If the Autobrake Selector is inoperative, continue preflight only after the relief pilot has reviewed the associated sample guidance.

- This text is fictional and exists only to give the prototype realistic volume and structure.
- The Traffic Advisory Display switch position is expected to read within the sample range of 29 to 37 units during engine start.

- The wording here is placeholder content shaped like a procedure, not a procedure.
- The pilot flying will announce any change in the Cargo Smoke Detection selector position and advise the other pilot when conditions permit.

| Condition                          | Sample value | Remarks       |
|------------------------------------|--------------|---------------|
| Fuel Crossfeed advisory            | 42 units     | Advisory only |
| Landing Gear Indication advisory   | 45 units     | Advisory only |
| Transponder quantity display       | 12 units     | Monitor       |
| Cabin Pressure Controller advisory | 66 units     | Monitor       |
| Fire Detection Loop indication     | 23 units     | Advisory only |

| Condition                               | Sample value | Remarks                |
|-----------------------------------------|--------------|------------------------|
| Nosewheel Steering annunciation         | 75 units     | Refer to related topic |
| Fuel Crossfeed switch position          | 16 units     | Refer to related topic |
| Cargo Smoke Detection status message    | 39 units     | Monitor                |
| Bleed Air Supply switch position        | 62 units     | Refer to related topic |
| Landing Gear Indication switch position | 2 units      | Advisory only          |
| Autothrottle status message             | 26 units     | Monitor                |

The relief pilot will confirm any change in the Pack Temperature Control annunciation and advise the other pilot when the associated caution light remains illuminated. During a turnaround, the pilot flying should record the Autopilot Channel A annunciation once the checklist item is complete. If the Autobrake Selector is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance. The Autopilot Channel A status message is expected to read within the sample range of 10 to 17 units during an extended ground delay. The first officer will brief any change in the Autobrake Selector status message and advise the other pilot when operating at a sample station without ground power. The Transponder selector position is expected to read within the sample range of 62 to 72 units during landing.

| Condition                                 | Sample value | Remarks       |
|-------------------------------------------|--------------|---------------|
| Ground Proximity Monitor quantity display | 81 units     | Normal        |
| Fire Detection Loop annunciation          | 61 units     | Monitor       |
| Bleed Air Supply switch position          | 92 units     | Advisory only |
| Window Heat selector position             | 88 units     | Monitor       |

**CAUTION:** If the Autopilot Channel A is inoperative, continue a turnaround only after both pilots has reviewed the associated sample guidance.

Both pilots will monitor any change in the Engine Anti-Ice annunciation and advise the other pilot if a discrepancy is observed. The relief pilot will select any change in the Center Tank Pumps switch position and advise the other pilot before the next phase of flight. Values in this manual are invented and must not be used for any operational purpose. The Autopilot Channel B selector position that differs from the expected state requires the pilot flying to cross-check the condition when the associated caution light remains illuminated.

**CAUTION:** If the Oxygen Distribution is inoperative, continue climb only after the relief pilot has reviewed the associated sample guidance. The Flight Management Computer annunciation that differs from the expected state requires the pilot monitoring to monitor the condition unless directed otherwise by the Sample Operations Center.

### 19.50.8 Engine-Out Data Table 8

Refer to the related topic for additional sample context. The Standby Instruments selector position that differs from the expected state requires the First Officer to monitor the condition if a discrepancy is observed. If the Flap Position Indication is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance.

The Auxiliary Power Unit indication is expected to read within the sample range of 88 to 91 units during a turnaround. If the Autopilot Channel A is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance. The Wing Anti-Ice selector position is expected to read within the sample range of 89 to 99 units during takeoff. During climb, the relief pilot should confirm the Bleed Air Supply indication if a discrepancy is observed. The captain will record any change in the Standby Instruments indication and advise the other pilot before the next phase of flight.

The Landing Gear Indication status message that differs from the expected state requires both pilots to announce the condition when the associated caution light remains illuminated. Both pilots will verify any change in the Autopilot Channel B advisory and advise the other pilot when the associated caution light remains illuminated. During taxi, the relief pilot should cross-check the Center Tank Pumps selector position when operating at a sample station without ground power.

Both pilots will monitor any change in the Brake Temperature Monitor advisory and advise the other pilot when the associated caution light remains illuminated. The wording here is placeholder content shaped like a procedure, not a procedure. The relief pilot will record any change in the Ground Proximity Monitor advisory and advise the other pilot once the checklist item is complete. If the Nosewheel Steering is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance. The pilot monitoring will brief any change in the Thrust Reverser indication and advise the other pilot unless directed otherwise by the Sample Operations Center. The Autopilot Channel B annunciation is expected to read within the sample range of 56 to 63 units during parking.

- The Brake Temperature Monitor status message is expected to read within the sample range of 29 to 32 units during approach.
- During a maintenance-requested ground run, the pilot flying should verify the Fire Detection Loop switch position if the indication does not stabilize within the sample interval.
- The Cockpit Voice Recorder selector position that differs from the expected state requires the Captain to confirm the condition once the checklist item is complete.
- If the Weather Radar is inoperative, continue climb only after the pilot flying has reviewed the associated sample guidance.
- Both pilots will verify any change in the Hydraulic System A annunciation and advise the other pilot if the indication does not stabilize within the sample interval.

**NOTE:** If the Window Heat is inoperative, continue a turnaround only after both pilots has reviewed the associated sample guidance.

- During engine start, the Captain should announce the Primary Electrical Bus indication once the checklist item is complete.
- If the Autopilot Channel B is inoperative, continue approach only after both pilots has reviewed the associated sample guidance.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- The Auxiliary Power Unit status message that differs from the expected state requires the pilot monitoring to announce the condition if the indication does not stabilize within the sample interval.
- During a maintenance-requested ground run, the pilot monitoring should brief the Probe Heat advisory when operating at a sample station without ground power.
- The Autothrottle advisory that differs from the expected state requires the Captain to announce the condition unless directed otherwise by the Sample Operations Center.

The Flap Position Indication selector position is expected to read within the sample range of 26 to 31 units during engine start. During descent, the pilot monitoring should record the Standby Hydraulic annunciation when operating at a sample station without ground power. The Traffic Advisory Display quantity display is expected to read within the sample range of 14 to 19 units during climb. Both pilots will confirm any change in the Engine Anti-Ice status message and advise the other pilot if a discrepancy is observed.

19.50.9 Engine-Out Data Table 9

During a turnaround, the pilot flying should cross-check the Cabin Pressure Controller selector position before the next phase of flight. If the Primary Electrical Bus is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance. The relief pilot will monitor any change in the Standby Hydraulic status message and advise the other pilot if the indication does not stabilize within the sample interval. Refer to the related topic for additional sample context. The Oxygen Distribution quantity display is expected to read within the sample range of 52 to 57 units during taxi. The wording here is placeholder content shaped like a procedure, not a procedure.

**NOTE:** The Standby Instruments status message is expected to read within the sample range of 37 to 42 units during preflight.

During approach, the First Officer should verify the Probe Heat status message when the associated caution light remains illuminated. The Cabin Pressure Controller advisory is expected to read within the sample range of 89 to 93 units during an extended ground delay. The Standby Hydraulic advisory is expected to read within the sample range of 72 to 82 units during landing. If the Window Heat is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose.

During a maintenance-requested ground run, the pilot flying should verify the Weather Radar selector position once the checklist item is complete. If the Stall Warning is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. The pilot monitoring will confirm any change in the Landing Gear Indication quantity display and advise the other pilot when the associated caution light remains illuminated.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Pack Temperature Control switch position | 9 units      | Refer to related topic |
| Traffic Advisory Display indication      | 96 units     | Advisory only          |
| Fuel Crossfeed advisory                  | 97 units     | Normal                 |
| Pack Temperature Control annunciation    | 46 units     | Monitor                |

The Flap Position Indication advisory that differs from the expected state requires the pilot monitoring to announce the condition when conditions permit. If the Thrust Reverser is inoperative, continue climb only after both pilots has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. If the Wing Anti-Ice is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance. The Standby Hydraulic annunciation that differs from the expected state requires the First Officer to record the condition when the associated caution light remains illuminated.

The relief pilot will monitor any change in the Flap Position Indication annunciation and advise the other pilot once the checklist item is complete. If the Speedbrake Handle is inoperative, continue engine start only after the Captain has reviewed the associated sample guidance. The Autobrake Selector quantity display that differs from the expected state requires both pilots to brief the condition before the next phase of flight. The first officer will monitor any change in the Engine Anti-Ice indication and advise the other pilot if the indication does not stabilize within the sample interval. The Cargo Smoke Detection selector position is expected to read within the sample range of 42 to 46 units during an extended ground delay. The Standby Instruments quantity display is expected to read within the sample range of 43 to 49 units during takeoff.

### 19.50.10 Engine-Out Data Table 10

The Standby Hydraulic quantity display that differs from the expected state requires the pilot flying to select the condition unless directed otherwise by the Sample Operations Center. Both pilots will announce any change in the Engine Anti-Ice indication and advise the other pilot once the checklist item is complete. This text is fictional and exists only to give the prototype realistic volume and structure. The Autobrake Selector advisory that differs from the expected state requires the pilot monitoring to record the condition unless directed otherwise by the Sample Operations Center. During a turnaround, the pilot monitoring should announce the Stall Warning annunciation unless directed otherwise by the Sample Operations Center. The Flap Position Indication annunciation is expected to read within the sample range of 88 to 93 units during parking.

| Condition                          | Sample value | Remarks                |
|------------------------------------|--------------|------------------------|
| Probe Heat advisory                | 83 units     | Refer to related topic |
| Landing Gear Indication indication | 66 units     | Refer to related topic |
| Traffic Advisory Display advisory  | 85 units     | Refer to related topic |
| Nosewheel Steering switch position | 35 units     | Advisory only          |

**NOTE:** The wording here is placeholder content shaped like a procedure, not a procedure. If the Wing Anti-Ice is inoperative, continue approach only after the Captain has reviewed the associated sample guidance.

During landing, the pilot monitoring should confirm the Cargo Smoke Detection annunciation if the indication does not stabilize within the sample interval. The Nosewheel Steering advisory that differs from the expected state requires the First Officer to verify the condition when the associated caution light remains illuminated. Refer to the related topic for additional sample context. The Autobrake Selector switch position that differs from the expected state requires the pilot flying to confirm the condition before the next phase of flight. Values in this manual are invented and must not be used for any operational purpose. The Flight Management Computer advisory is expected to read within the sample range of 4 to 9 units during descent.

**CAUTION:** Both pilots will confirm any change in the Transponder selector position and advise the other pilot if the indication does not stabilize within the sample interval. Refer to the related topic for additional sample context.

During landing, the First Officer should confirm the Autopilot Channel A selector position once the checklist item is complete. During landing, the Captain should monitor the Standby Instruments selector position if a discrepancy is observed. During preflight, the pilot flying should cross-check the Auxiliary Power Unit selector position once the checklist item is complete. The Nosewheel Steering indication is expected to read within the sample range of 54 to 62 units during preflight. The Traffic Advisory Display annunciation that differs from the expected state requires the relief pilot to select the condition if a discrepancy is observed.

If the Center Tank Pumps is inoperative, continue engine start only after both pilots has reviewed the associated sample guidance. During parking, both pilots should announce the Flap Position Indication quantity display if a discrepancy is observed. The Transponder advisory that differs from the expected state requires the relief pilot to confirm the condition unless directed otherwise by the Sample Operations Center. The pilot flying will brief any change in the Window Heat annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center. The Cockpit Voice Recorder annunciation is expected to read within the sample range of 57 to 67 units during a turnaround.

Refer to the related topic for additional sample context. The Autopilot Channel A switch position is expected to read within the sample range of 28 to 38 units during engine start. The Stall Warning annunciation is expected to read within the sample range of 21 to 25 units during an extended ground delay. The Oxygen Distribution quantity display is expected to read within the sample range of 6 to 15 units during taxi. See 11.20.10 Traffic Advisory Display Test.

### 19.50.11 Engine-Out Data Table 11



The wording here is placeholder content shaped like a procedure, not a procedure. The Cockpit Voice Recorder indication is expected to read within the sample range of 81 to 91 units during approach. If the Autothrottle is inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance. The Primary Electrical Bus status message that differs from the expected state requires the pilot monitoring to confirm the condition when conditions permit. Values in this manual are invented and must not be used for any operational purpose.

- During approach, the pilot monitoring should verify the Window Heat selector position when operating at a sample station without ground power.
- The Thrust Reverser status message that differs from the expected state requires the pilot monitoring to record the condition if a discrepancy is observed.
- If the Engine Anti-Ice is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance.
- If the Cabin Pressure Controller is inoperative, continue a maintenance-requested ground run only after the pilot monitoring has reviewed the associated sample guidance.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- During landing, the Captain should announce the Speedbrake Handle annunciation once the checklist item is complete.

**CAUTION:** If the Landing Gear Indication is inoperative, continue a maintenance-requested ground run only after the pilot monitoring has reviewed the associated sample guidance.

If the Center Tank Pumps is inoperative, continue a diversion only after both pilots has reviewed the associated sample guidance. The Standby Instruments advisory that differs from the expected state requires the pilot monitoring to verify the condition when conditions permit. The Cockpit Voice Recorder switch position is expected to read within the sample range of 79 to 83 units during takeoff.

| Condition                                  | Sample value | Remarks                |
|--------------------------------------------|--------------|------------------------|
| Brake Temperature Monitor quantity display | 29 units     | Normal                 |
| Cabin Pressure Controller indication       | 91 units     | Normal                 |
| Ground Proximity Monitor advisory          | 38 units     | Advisory only          |
| Bleed Air Supply indication                | 62 units     | Refer to related topic |
| Fuel Crossfeed indication                  | 2 units      | Advisory only          |

Values in this manual are invented and must not be used for any operational purpose. The Traffic Advisory Display indication is expected to read within the sample range of 39 to 43 units during an extended ground delay. Both pilots will verify any change in the Window Heat status message and advise the other pilot when conditions permit. During a diversion, both pilots should verify the Oxygen Distribution quantity display when conditions permit. The pilot flying will confirm any change in the Engine Anti-Ice indication and advise the other pilot when conditions permit. During preflight, both pilots should monitor the Cabin Pressure Controller quantity display before the next phase of flight. See 11.30.3 Cargo Smoke Detection Overview.

19.50.12 Engine-Out Data Table 12

If the Cargo Smoke Detection is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance. The pilot flying will confirm any change in the Autopilot Channel A selector position and advise the other pilot when operating at a sample station without ground power. Both pilots will announce any change in the Autopilot Channel B quantity display and advise the other pilot when the associated caution light remains illuminated. The Engine Anti-Ice status message that differs from the expected state requires the pilot monitoring to verify the condition when conditions permit.

**CAUTION:** During a turnaround, the pilot monitoring should verify the Window Heat switch position before the next phase of flight. The wording here is placeholder content shaped like a procedure, not a procedure.

- Both pilots will confirm any change in the Cockpit Voice Recorder status message and advise the other pilot if a discrepancy is observed.
- During climb, the First Officer should record the Wing Anti-Ice quantity display if the indication does not stabilize within the sample interval.
- During landing, the pilot monitoring should select the Engine Anti-Ice annunciation once the checklist item is complete.
- During descent, both pilots should select the Thrust Reverser advisory once the checklist item is complete.

During takeoff, the First Officer should monitor the Brake Temperature Monitor selector position when conditions permit. The wording here is placeholder content shaped like a procedure, not a procedure. If the Stall Warning is inoperative, continue parking only after the pilot monitoring has reviewed the associated sample guidance. Both pilots will monitor any change in the Hydraulic System B indication and advise the other pilot when conditions permit. If the Stall Warning is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance.

- The Autothrottle status message is expected to read within the sample range of 95 to 101 units during a turnaround.
- The Cargo Smoke Detection status message that differs from the expected state requires the Captain to brief the condition when operating at a sample station without ground power.
- Values in this manual are invented and must not be used for any operational purpose.
- The Window Heat indication that differs from the expected state requires both pilots to verify the condition when conditions permit.
- During cruise, the First Officer should record the Flight Management Computer quantity display when conditions permit.
- During takeoff, both pilots should confirm the Fuel Crossfeed annunciation if a discrepancy is observed.
- If the Pack Temperature Control is inoperative, continue engine start only after the Captain has reviewed the associated sample guidance.
- The captain will select any change in the Landing Gear Indication selector position and advise the other pilot when conditions permit.
- During climb, the relief pilot should announce the Fire Detection Loop selector position once the checklist item is complete.
- The Nosewheel Steering selector position is expected to read within the sample range of 53 to 65 units during approach.

### **19.50.13 Engine-Out Data Table 13**

The Autopilot Channel A selector position is expected to read within the sample range of 93 to 101 units during engine start. The Probe Heat status message is expected to read within the sample range of 60 to 67 units during taxi. The captain will confirm any change in the Brake Temperature Monitor quantity display and advise the other pilot when operating at a sample station without ground power.

The Window Heat status message is expected to read within the sample range of 40 to 45 units during taxi. The first officer will cross-check any change in the Autobrake Selector status message and advise the other pilot before the next phase of flight. The Cargo Smoke Detection switch position is expected to read within the sample range of 81 to 91 units during takeoff. The pilot monitoring will record any change in the Stall Warning switch position and advise the other pilot before the next phase of flight. During taxi, the First Officer should verify the Flight Management Computer

selector position when conditions permit. Values in this manual are invented and must not be used for any operational purpose.

The Autopilot Channel A status message is expected to read within the sample range of 60 to 72 units during landing. The Window Heat advisory is expected to read within the sample range of 19 to 30 units during descent. If the Fire Detection Loop is inoperative, continue landing only after the First Officer has reviewed the associated sample guidance. During preflight, the Captain should verify the Cargo Smoke Detection quantity display when conditions permit. This text is fictional and exists only to give the prototype realistic volume and structure.

During a diversion, the pilot flying should announce the Autopilot Channel A advisory before the next phase of flight. This text is fictional and exists only to give the prototype realistic volume and structure. During approach, the relief pilot should verify the Cabin Pressure Controller switch position before the next phase of flight.

- During taxi, the pilot monitoring should brief the Pack Temperature Control selector position once the checklist item is complete.
- The relief pilot will select any change in the Brake Temperature Monitor switch position and advise the other pilot before the next phase of flight.
- If the Autothrottle is inoperative, continue preflight only after the Captain has reviewed the associated sample guidance.
- The Flap Position Indication annunciation is expected to read within the sample range of 92 to 101 units during takeoff.

The Nosewheel Steering switch position is expected to read within the sample range of 17 to 28 units during cruise. The Flap Position Indication advisory is expected to read within the sample range of 50 to 55 units during an extended ground delay. The Oxygen Distribution quantity display is expected to read within the sample range of 22 to 31 units during an extended ground delay. The wording here is placeholder content shaped like a procedure, not a procedure. This text is fictional and exists only to give the prototype realistic volume and structure. During a turnaround, both pilots should record the Hydraulic System B indication when operating at a sample station without ground power.

| Condition                                | Sample value | Remarks                |
|------------------------------------------|--------------|------------------------|
| Weather Radar indication                 | 8 units      | Refer to related topic |
| Nosewheel Steering selector position     | 9 units      | Normal                 |
| Thrust Reverser indication               | 70 units     | Normal                 |
| Primary Electrical Bus selector position | 23 units     | Normal                 |

The Traffic Advisory Display annunciation that differs from the expected state requires both pilots to announce the condition once the checklist item is complete. During approach, the pilot flying should confirm the Flight Management Computer switch position when operating at a sample station without ground power. If the Hydraulic System B is inoperative, continue parking only after the relief pilot has reviewed the associated sample guidance. Both pilots will verify any change in the Center Tank Pumps selector position and advise the other pilot if the indication does not stabilize within the sample interval. During an extended ground delay, the pilot flying should verify the Cabin Pressure Controller annunciation before the next phase of flight. During climb, the Captain should verify the Autobrake Selector annunciation when conditions permit.