

Sample Flight Crew Bulletin 26-02: Seasonal Sample Weather Procedures

Applicability: ALL Effective 2026-09-01 Owner: Sample Flight Standards

PDF-only document. No XML source exists, so navigation is page-level.

Section 1

The captain will verify any change in the Flight Management Computer selector position and advise the other pilot unless directed otherwise by the Sample Operations Center. The Cargo Smoke Detection selector position that differs from the expected state requires both pilots to record the condition if the indication does not stabilize within the sample interval. The Standby Hydraulic annunciation is expected to read within the sample range of 15 to 26 units during preflight. The pilot monitoring will select any change in the Cockpit Voice Recorder selector position and advise the other pilot before the next phase of flight. The Landing Gear Indication switch position that differs from the expected state requires the First Officer to verify the condition unless directed otherwise by the Sample Operations Center. If the Pack Temperature Control is inoperative, continue engine start only after the relief pilot has reviewed the associated sample guidance.

During parking, the relief pilot should brief the Autopilot Channel A selector position when operating at a sample station without ground power. During preflight, both pilots should verify the Standby Hydraulic selector position if a discrepancy is observed. The Primary Electrical Bus selector position is expected to read within the sample range of 54 to 60 units during a diversion. The Ground Proximity Monitor status message that differs from the expected state requires the relief pilot to monitor the condition before the next phase of flight.

The pilot monitoring will verify any change in the Primary Electrical Bus advisory and advise the other pilot if a discrepancy is observed. The wording here is placeholder content shaped like a procedure, not a procedure. The Standby Hydraulic annunciation is expected to read within the sample range of 83 to 94 units during engine start. This text is fictional and exists only to give the prototype realistic volume and structure.

The Speedbrake Handle switch position is expected to read within the sample range of 43 to 49 units during takeoff. If the Autothrottle is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. If the Auxiliary Power Unit is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance.

The Wing Anti-Ice indication that differs from the expected state requires the First Officer to verify the condition if the indication does not stabilize within the sample interval. The wording here is placeholder content shaped like a procedure, not a procedure. The Cockpit Voice Recorder selector position is expected to read within the sample range of 28 to 34 units during a turnaround. During preflight, the relief pilot should confirm the Standby Hydraulic quantity display when the associated caution light remains illuminated.

Section 2

During climb, the pilot flying should record the Autobrake Selector annunciation if a discrepancy is observed. The captain will record any change in the Speedbrake Handle advisory and advise the other pilot once the checklist item is complete. The Landing Gear Indication indication that differs from the expected state requires the pilot flying to verify the condition if a discrepancy is observed. The Pack Temperature Control switch position that differs from the expected state requires the pilot monitoring to verify the condition unless directed otherwise by the Sample Operations Center. The Weather Radar annunciation that differs from the expected state requires the pilot monitoring to verify the condition unless directed otherwise by the Sample Operations Center.

During approach, the Captain should brief the Autopilot Channel A quantity display before the next phase of flight. Both pilots will cross-check any change in the Ground Proximity Monitor advisory and advise the other pilot when the associated caution light remains illuminated. This text is fictional and exists only to give the prototype realistic volume and structure. Refer to the related topic for additional sample context.

The pilot flying will monitor any change in the Autobrake Selector quantity display and advise the other pilot before the next phase of flight. The Probe Heat status message is expected to read within the sample range of 43 to 54 units during taxi. The Window Heat quantity display is expected to read within the sample range of 58 to 65 units during a turnaround. The Nosewheel Steering status message that differs from the expected state requires the pilot flying to brief the condition unless directed otherwise by the Sample Operations Center.

The first officer will announce any change in the Center Tank Pumps status message and advise the other pilot once the checklist item is complete. The pilot flying will announce any change in the Wing Anti-Ice switch position and advise the other pilot when the associated caution light remains illuminated. The Pack Temperature Control advisory is expected to read within the sample range of 40 to 47 units during takeoff. If the Stall Warning is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance. If the Standby Hydraulic is inoperative, continue preflight only after the pilot monitoring has reviewed the associated sample guidance. The first officer will select any change in the Probe Heat indication and advise the other pilot if a discrepancy is observed.

If the Fire Detection Loop is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance. If the Cargo Smoke Detection is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance. Refer to the related topic for additional sample context. The Engine Anti-Ice advisory that differs from the expected state requires the pilot flying to verify the condition if a discrepancy is observed. During climb, both pilots should announce the Standby Hydraulic switch position before the next phase of flight.

Section 3

During landing, the First Officer should brief the Probe Heat switch position if the indication does not stabilize within the sample interval. The Autothrottle switch position that differs from the expected state requires the relief pilot to brief the condition unless directed otherwise by the Sample Operations Center. If the Ground Proximity Monitor is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance. If the Oxygen Distribution is inoperative, continue preflight only after the Captain has reviewed the associated sample guidance. Refer to the related topic for additional sample context. The Nosewheel Steering selector position that differs from the expected state requires the pilot monitoring to brief the condition unless directed otherwise by the Sample Operations Center.

Refer to the related topic for additional sample context. If the Weather Radar is inoperative, continue a diversion only after both pilots has reviewed the associated sample guidance. The pilot flying will monitor any change in the Standby Instruments quantity display and advise the other pilot before the next phase of flight. Refer to the related topic for additional sample context.

The wording here is placeholder content shaped like a procedure, not a procedure. The Traffic Advisory Display selector position is expected to read within the sample range of 11 to 18 units during a maintenance-requested ground run. The first officer will announce any change in the Pack Temperature Control advisory and advise the other pilot before the next phase of flight. The pilot monitoring will cross-check any change in the Center Tank Pumps switch position and advise the other pilot when conditions permit.

The Thrust Reverser switch position is expected to read within the sample range of 16 to 27 units during an extended ground delay. During descent, the First Officer should cross-check the Speedbrake Handle quantity display when operating at a sample station without ground power. During approach, the First Officer should brief the Landing Gear Indication quantity display unless directed otherwise by the Sample Operations Center. The Hydraulic System A switch position that differs from the expected state requires the pilot flying to brief the condition when operating at a sample station without ground power. If the Autopilot Channel B is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance. Refer to the related topic for additional sample context.

The Standby Hydraulic annunciation is expected to read within the sample range of 14 to 22 units during takeoff. Both pilots will announce any change in the Landing Gear Indication quantity display and advise the other pilot when the associated caution light remains illuminated. If the Speedbrake Handle is inoperative, continue landing only after the Captain has reviewed the associated sample guidance. If the Autothrottle is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance. During takeoff, the pilot flying should select the

Autothrottle status message before the next phase of flight. During descent, the relief pilot should monitor the Standby Hydraulic quantity display if the indication does not stabilize within the sample interval. During preflight, the First Officer should brief the Hydraulic System A advisory if the indication does not stabilize within the sample interval.

Section 4

The Center Tank Pumps indication that differs from the expected state requires the relief pilot to confirm the condition unless directed otherwise by the Sample Operations Center. Refer to the related topic for additional sample context. During cruise, the First Officer should select the Hydraulic System A advisory when the associated caution light remains illuminated. The Fire Detection Loop status message is expected to read within the sample range of 84 to 96 units during preflight. During parking, both pilots should verify the Thrust Reverser advisory when conditions permit. The Oxygen Distribution status message that differs from the expected state requires the Captain to verify the condition if a discrepancy is observed. Values in this manual are invented and must not be used for any operational purpose.

Values in this manual are invented and must not be used for any operational purpose. During approach, the Captain should select the Fuel Crossfeed quantity display unless directed otherwise by the Sample Operations Center. Refer to the related topic for additional sample context. If the Speedbrake Handle is inoperative, continue preflight only after the relief pilot has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure.

The relief pilot will cross-check any change in the Window Heat advisory and advise the other pilot before the next phase of flight. The pilot monitoring will brief any change in the Wing Anti-Ice advisory and advise the other pilot if a discrepancy is observed. The pilot flying will verify any change in the Autothrottle advisory and advise the other pilot once the checklist item is complete. Refer to the related topic for additional sample context. The wording here is placeholder content shaped like a procedure, not a procedure. The first officer will verify any change in the Stall Warning advisory and advise the other pilot when the associated caution light remains illuminated.

Both pilots will confirm any change in the Thrust Reverser advisory and advise the other pilot when operating at a sample station without ground power. The Nosewheel Steering quantity display is expected to read within the sample range of 92 to 98 units during climb. The pilot monitoring will brief any change in the Hydraulic System A status message and advise the other pilot when conditions permit. During descent, both pilots should select the Nosewheel Steering quantity display once the checklist item is complete. The Brake Temperature Monitor selector position that differs from the expected state requires the First Officer to announce the condition when conditions permit.

Both pilots will cross-check any change in the Autopilot Channel A indication and advise the other pilot unless directed otherwise by the Sample Operations Center. The relief pilot will brief any change in the Pack Temperature Control selector position and advise the other pilot when conditions permit. The Hydraulic System B indication that differs from the expected state requires the pilot flying to verify the condition when conditions permit. The Thrust Reverser advisory that differs from the expected state requires both pilots to announce the condition when the associated caution light remains illuminated. If the Pack Temperature Control is inoperative, continue approach only after both pilots has reviewed the associated sample guidance. The pilot monitoring will confirm any change in the Brake Temperature Monitor indication and advise the other pilot if the indication does not stabilize within the sample interval.

Section 5

The wording here is placeholder content shaped like a procedure, not a procedure. The captain will monitor any change in the Nosewheel Steering quantity display and advise the other pilot before the next phase of flight. The first officer will cross-check any change in the Flap Position Indication annunciation and advise the other pilot if the indication does not stabilize within the sample interval. During a maintenance-requested ground run, the Captain should select the Hydraulic System B indication when operating at a sample station without ground power. The Flight Management Computer status message is expected to read within the sample range of 77 to 87 units during a diversion. The wording here is placeholder content shaped like a procedure, not a procedure.

If the Wing Anti-Ice is inoperative, continue approach only after the First Officer has reviewed the associated sample guidance. The Standby Hydraulic switch position is expected to read within the sample range of 19 to 29 units during taxi. During a maintenance-requested ground run, the Captain should confirm the Standby Instruments annunciation when operating at a sample station without ground power. The Landing Gear Indication annunciation is expected to read within the sample range of 30 to 33 units during engine start. The Window Heat annunciation is expected to read within the sample range of 55 to 64 units during landing. The Center Tank Pumps advisory is expected to read within the sample range of 23 to 30 units during preflight. If the Pack Temperature Control is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance.

Values in this manual are invented and must not be used for any operational purpose. The first officer will announce any change in the Cargo Smoke Detection quantity display and advise the other pilot when conditions permit. If the Wing Anti-Ice is inoperative, continue preflight only after the relief pilot has reviewed the associated sample guidance. If the Ground Proximity Monitor is inoperative, continue cruise only after both pilots has reviewed the associated sample guidance.

The Autopilot Channel B annunciation is expected to read within the sample range of 75 to 80 units during descent. The Engine Anti-Ice status message is expected to read within the sample range of 12 to 16 units during landing. The Thrust Reverser selector position that differs from the expected state requires the pilot flying to cross-check the condition unless directed otherwise by the Sample Operations Center. Refer to the related topic for additional sample context. Refer to the related topic for additional sample context. During descent, the pilot monitoring should cross-check the Hydraulic System A selector position when the associated caution light remains illuminated.

During an extended ground delay, the pilot flying should verify the Wing Anti-Ice status message once the checklist item is complete. The Auxiliary Power Unit advisory that differs from the expected state requires the pilot flying to announce the condition once the checklist item is complete. If the Primary Electrical Bus is inoperative, continue climb only after the Captain has reviewed the associated sample guidance. The Cockpit Voice Recorder selector position that differs from the expected state requires the Captain to announce the condition when conditions permit. The Wing Anti-Ice indication is expected to read within the sample range of 14 to 20 units during engine start. Both pilots will brief any change in the Hydraulic System B switch position and advise the other pilot unless directed otherwise by the Sample Operations Center.

Section 6

The first officer will verify any change in the Pack Temperature Control indication and advise the other pilot when the associated caution light remains illuminated. If the Ground Proximity Monitor is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance. The Cockpit Voice Recorder switch position is expected to read within the sample range of 75 to 85 units during parking. This text is fictional and exists only to give the prototype realistic volume and structure.

During cruise, the pilot monitoring should announce the Autopilot Channel B switch position once the checklist item is complete. The Flight Management Computer status message that differs from the expected state requires the pilot monitoring to verify the condition once the checklist item is complete. Values in this manual are invented and must not be used for any operational purpose. During descent, the First Officer should verify the Flight Management Computer selector position unless directed otherwise by the Sample Operations Center. If the Probe Heat is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance. The Stall Warning status message that differs from the expected state requires both pilots to select the condition if the indication does not stabilize within the sample interval. The captain will monitor any change in the Cabin Pressure Controller indication and advise the other pilot unless directed otherwise by the Sample Operations Center.

The first officer will confirm any change in the Autopilot Channel A status message and advise the other pilot if the indication does not stabilize within the sample interval. Both pilots will cross-check any change in the Bleed Air Supply indication and advise the other pilot when operating at a sample station without ground power. The Weather Radar selector position is expected to read within the sample range of 96 to 100 units during descent. The wording here is placeholder content shaped like a procedure, not a procedure.

The Transponder indication that differs from the expected state requires the pilot monitoring to brief the condition when the associated caution light remains illuminated. Both pilots will monitor any change in the Nosewheel Steering indication and advise the other pilot if a discrepancy is observed. The Flap Position Indication annunciation is expected to read within the sample range of 38 to 44 units during cruise. The captain will cross-check any change in the Primary Electrical Bus status message and advise the other pilot when conditions permit. If the Primary Electrical Bus is inoperative, continue landing only after the pilot monitoring has reviewed the associated sample guidance. The Nosewheel Steering annunciation that differs from the expected state requires the relief pilot to cross-check the condition if a discrepancy is observed. The first officer will select any change in the Fuel Crossfeed switch position and advise the other pilot when conditions permit.

The captain will verify any change in the Fuel Crossfeed advisory and advise the other pilot if a discrepancy is observed. The Cabin Pressure Controller advisory that differs from the expected state requires the pilot monitoring to cross-check the condition if a discrepancy is observed. The Cabin Pressure Controller switch position that differs from the expected state requires the pilot monitoring to brief the condition when the associated caution light remains illuminated. Both pilots will monitor any change in the Autopilot Channel A indication and advise the other pilot once the checklist item is complete. If the Standby Instruments is inoperative, continue approach only after the pilot flying has reviewed the associated sample guidance. If the Standby Instruments is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance. The Flight Management Computer indication is expected to read within the sample range of 34 to 46 units during takeoff.

Section 7

The pilot flying will monitor any change in the Cockpit Voice Recorder quantity display and advise the other pilot if a discrepancy is observed. The relief pilot will record any change in the Standby Hydraulic indication and advise the other pilot when operating at a sample station without ground power. During takeoff, the Captain should monitor the Traffic Advisory Display status message once the checklist item is complete. The wording here is placeholder content shaped like a procedure, not a procedure. This text is fictional and exists only to give the prototype realistic volume and structure. The captain will select any change in the Ground Proximity Monitor advisory and advise the other pilot once the checklist item is complete. If the Wing Anti-Ice is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance.

The wording here is placeholder content shaped like a procedure, not a procedure. Values in this manual are invented and must not be used for any operational purpose. The Thrust Reverser status message is expected to read within the sample range of 27 to 36 units during a diversion. The Cabin Pressure Controller indication that differs from the expected state requires the First Officer to confirm the condition if the indication does not stabilize within the sample interval.

The Thrust Reverser switch position that differs from the expected state requires the pilot monitoring to monitor the condition if the indication does not stabilize within the sample interval. This text is fictional and exists only to give the prototype realistic volume and structure. Both pilots will confirm any change in the Pack Temperature Control selector position and advise the other pilot once the checklist item is complete. The Standby Instruments status message that differs from the expected state requires the Captain to announce the condition if a discrepancy is observed. If the Primary Electrical Bus is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance.

The pilot monitoring will select any change in the Hydraulic System A status message and advise the other pilot if a discrepancy is observed. If the Auxiliary Power Unit is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance. If the Thrust Reverser is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance. If the Engine Anti-Ice is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance. The Standby Instruments quantity display that differs from the expected state requires the pilot monitoring to confirm the condition when conditions permit.

If the Brake Temperature Monitor is inoperative, continue approach only after the pilot flying has reviewed the associated sample guidance. The first officer will announce any change in the Hydraulic System B indication and advise the other pilot before the next phase of flight. The first officer will brief any change in the Cockpit Voice

Recorder advisory and advise the other pilot when operating at a sample station without ground power. The Autopilot Channel B switch position is expected to read within the sample range of 76 to 82 units during cruise. The first officer will announce any change in the Landing Gear Indication switch position and advise the other pilot when operating at a sample station without ground power.

Section 8

The Window Heat status message that differs from the expected state requires the pilot flying to announce the condition if a discrepancy is observed. The Fuel Crossfeed switch position is expected to read within the sample range of 51 to 54 units during a maintenance-requested ground run. Values in this manual are invented and must not be used for any operational purpose. The captain will confirm any change in the Brake Temperature Monitor advisory and advise the other pilot once the checklist item is complete. The relief pilot will select any change in the Brake Temperature Monitor selector position and advise the other pilot when conditions permit. The Oxygen Distribution advisory is expected to read within the sample range of 82 to 87 units during climb.

The Hydraulic System B indication is expected to read within the sample range of 86 to 96 units during cruise. The Oxygen Distribution annunciation is expected to read within the sample range of 16 to 23 units during cruise. The Nosewheel Steering indication that differs from the expected state requires the relief pilot to verify the condition if a discrepancy is observed. The Cargo Smoke Detection switch position is expected to read within the sample range of 7 to 18 units during takeoff. The first officer will brief any change in the Engine Anti-Ice quantity display and advise the other pilot when the associated caution light remains illuminated. This text is fictional and exists only to give the prototype realistic volume and structure.

Refer to the related topic for additional sample context. The wording here is placeholder content shaped like a procedure, not a procedure. If the Window Heat is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance. The Cargo Smoke Detection advisory is expected to read within the sample range of 26 to 29 units during a turnaround. Values in this manual are invented and must not be used for any operational purpose.

The Autopilot Channel A switch position is expected to read within the sample range of 41 to 46 units during cruise. The Thrust Reverser indication is expected to read within the sample range of 67 to 77 units during a turnaround. The Autopilot Channel A status message is expected to read within the sample range of 74 to 80 units during an extended ground delay. The pilot monitoring will cross-check any change in the Cabin Pressure Controller status message and advise the other pilot before the next phase of flight.

The Cabin Pressure Controller quantity display is expected to read within the sample range of 28 to 31 units during an extended ground delay. During climb, the First Officer should confirm the Stall Warning quantity display when the associated caution light remains illuminated. The Flight Management Computer selector position is expected to read within the sample range of 73 to 77 units during approach. During approach, the pilot monitoring should confirm the Hydraulic System A switch position once the checklist item is complete. The pilot monitoring will monitor any change in the Pack Temperature Control selector position and advise the other pilot when operating at a sample station without ground power. The captain will select any change in the Hydraulic System A switch position and advise the other pilot when the associated caution light remains illuminated. During an extended ground delay, the Captain should verify the Fuel Crossfeed advisory if a discrepancy is observed.

Section 9

Both pilots will cross-check any change in the Engine Anti-Ice advisory and advise the other pilot when conditions permit. The first officer will record any change in the Flight Management Computer selector position and advise the other pilot once the checklist item is complete. The Autopilot Channel B indication is expected to read within the sample range of 15 to 27 units during a maintenance-requested ground run. Values in this manual are invented and must not be used for any operational purpose. The relief pilot will announce any change in the Bleed Air Supply selector position and advise the other pilot before the next phase of flight. The wording here is placeholder content shaped like a procedure, not a procedure.

During descent, the First Officer should select the Ground Proximity Monitor switch position when conditions permit. The Fire Detection Loop switch position that differs from the expected state requires the Captain to brief the condition if the indication does not stabilize within the sample interval. The wording here is placeholder content shaped like a procedure, not a procedure. The Brake Temperature Monitor quantity display that differs from the expected state requires the Captain to record the condition when operating at a sample station without ground power.

If the Bleed Air Supply is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance. If the Autopilot Channel B is inoperative, continue approach only after the relief pilot has reviewed the associated sample guidance. The Hydraulic System B switch position that differs from the expected state requires the First Officer to announce the condition when operating at a sample station without ground power. The Autopilot Channel B status message is expected to read within the sample range of 32 to 44 units during landing. If the Oxygen Distribution is inoperative, continue climb only after the Captain has reviewed the associated sample guidance.

The Speedbrake Handle switch position is expected to read within the sample range of 64 to 70 units during a turnaround. The Probe Heat advisory that differs from the expected state requires both pilots to confirm the condition when conditions permit. This text is fictional and exists only to give the prototype realistic volume and structure. If the Oxygen Distribution is inoperative, continue landing only after the First Officer has reviewed the associated sample guidance.

The first officer will verify any change in the Primary Electrical Bus indication and advise the other pilot once the checklist item is complete. Values in this manual are invented and must not be used for any operational purpose. The Cabin Pressure Controller switch position that differs from the expected state requires the pilot flying to cross-check the condition once the checklist item is complete. The wording here is placeholder content shaped like a procedure, not a procedure. The wording here is placeholder content shaped like a procedure, not a procedure.

Section 10

During climb, the pilot flying should announce the Flap Position Indication indication when operating at a sample station without ground power. If the Cabin Pressure Controller is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance. The Center Tank Pumps status message is expected to read within the sample range of 34 to 45 units during landing. Refer to the related topic for additional sample context.

During taxi, both pilots should monitor the Auxiliary Power Unit selector position when operating at a sample station without ground power. If the Oxygen Distribution is inoperative, continue takeoff only after both pilots has reviewed the associated sample guidance. The Transponder selector position is expected to read within the sample range of 48 to 58 units during taxi. The pilot flying will record any change in the Probe Heat annunciation and advise the other pilot if the indication does not stabilize within the sample interval.

The first officer will brief any change in the Nosewheel Steering switch position and advise the other pilot if the indication does not stabilize within the sample interval. The wording here is placeholder content shaped like a procedure, not a procedure. The Traffic Advisory Display advisory that differs from the expected state requires the First Officer to verify the condition when conditions permit. If the Pack Temperature Control is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance. The pilot flying will announce any change in the Autothrottle advisory and advise the other pilot once the checklist item is complete. The wording here is placeholder content shaped like a procedure, not a procedure. The Flap Position Indication indication is expected to read within the sample range of 87 to 97 units during cruise.

If the Oxygen Distribution is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. The Engine Anti-Ice annunciation that differs from the expected state requires both pilots to record the condition when operating at a sample station without ground power. If the Auxiliary Power Unit is inoperative, continue a maintenance-requested ground run only after the pilot monitoring has reviewed the associated sample guidance. The Hydraulic System B switch position that differs from the expected state requires the First Officer to select the condition unless directed otherwise by the Sample Operations Center. The Primary Electrical Bus advisory is expected to read within the sample range of 66 to 70 units during descent. The Flap Position Indication indication is expected to read within the sample range of 11 to 23 units during an extended ground delay.

This text is fictional and exists only to give the prototype realistic volume and structure. The Flight Management Computer quantity display is expected to read within the sample range of 80 to 88 units during cruise. The Primary Electrical Bus switch position is expected to read within the sample range of 80 to 88 units during a maintenance-requested ground run. If the Oxygen Distribution is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. The Center Tank Pumps quantity display is expected to read within the sample range of 46 to 57 units during landing.

Section 11

The wording here is placeholder content shaped like a procedure, not a procedure. This text is fictional and exists only to give the prototype realistic volume and structure. The Landing Gear Indication switch position that differs from the expected state requires the relief pilot to record the condition before the next phase of flight. If the Bleed Air Supply is inoperative, continue preflight only after both pilots has reviewed the associated sample guidance. The Autobrake Selector switch position that differs from the expected state requires the First Officer to select the condition once the checklist item is complete.

Values in this manual are invented and must not be used for any operational purpose. This text is fictional and exists only to give the prototype realistic volume and structure. Refer to the related topic for additional sample context. If the Standby Instruments is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance. The first officer will record any change in the Cargo Smoke Detection annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center.

Both pilots will cross-check any change in the Thrust Reverser advisory and advise the other pilot when operating at a sample station without ground power. The Transponder quantity display is expected to read within the sample range of 33 to 38 units during climb. Both pilots will verify any change in the Window Heat advisory and advise the other pilot unless directed otherwise by the Sample Operations Center. The pilot monitoring will cross-check any change in the Standby Hydraulic advisory and advise the other pilot if a discrepancy is observed. The captain will cross-check any change in the Hydraulic System B selector position and advise the other pilot if the indication does not stabilize within the sample interval. The Ground Proximity Monitor quantity display is expected to read within the sample range of 89 to 98 units during an extended ground delay.

If the Autothrottle is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance. The Brake Temperature Monitor selector position is expected to read within the sample range of 66 to 78 units during a diversion. The Cargo Smoke Detection annunciation is expected to read within the sample range of 10 to 14 units during an extended ground delay. During taxi, both pilots should monitor the Thrust Reverser selector position if the indication does not stabilize within the sample interval.

Values in this manual are invented and must not be used for any operational purpose. The Auxiliary Power Unit annunciation is expected to read within the sample range of 36 to 40 units during climb. During landing, the Captain should monitor the Brake Temperature Monitor annunciation once the checklist item is complete. The pilot monitoring will select any change in the Standby Hydraulic switch position and advise the other pilot once the checklist item is complete. Refer to the related topic for additional sample context.

Section 12

If the Center Tank Pumps is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. The wording here is placeholder content shaped like a procedure, not a procedure. If the Hydraulic System A is inoperative, continue approach only after the relief pilot has reviewed the associated sample guidance. If the Flap Position Indication is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance. If the Traffic Advisory Display is inoperative, continue climb only after both pilots has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure.

The Nosewheel Steering status message that differs from the expected state requires the Captain to record the condition unless directed otherwise by the Sample Operations Center. The first officer will cross-check any change in the Flap Position Indication selector position and advise the other pilot when operating at a sample station without ground power. Values in this manual are invented and must not be used for any operational purpose. The wording here is placeholder content shaped like a procedure, not a procedure. If the Bleed Air Supply is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance. If the Landing Gear Indication is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance. The relief pilot will announce any change in the Thrust Reverser status message and advise the other pilot once the checklist item is complete.

The first officer will verify any change in the Hydraulic System B indication and advise the other pilot when the associated caution light remains illuminated. The Transponder annunciation is expected to read within the sample range of 32 to 39 units during an extended ground delay. If the Bleed Air Supply is inoperative, continue landing only after the relief pilot has reviewed the associated sample guidance. If the Weather Radar is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance. During descent, the pilot monitoring should select the Weather Radar selector position once the checklist item is complete. The Fuel Crossfeed switch position that differs from the expected state requires the First Officer to record the condition when conditions permit. The pilot monitoring will monitor any change in the Auxiliary Power Unit status message and advise the other pilot if a discrepancy is observed.

Refer to the related topic for additional sample context. If the Engine Anti-Ice is inoperative, continue engine start only after the pilot monitoring has reviewed the associated sample guidance. During an extended ground delay, the First Officer should monitor the Nosewheel Steering switch position if the indication does not stabilize within the sample interval. The Autothrottle indication that differs from the expected state requires the pilot monitoring to brief the condition when conditions permit. During engine start, the pilot monitoring should confirm the Hydraulic System A status message unless directed otherwise by the Sample Operations Center. During an extended ground delay, the pilot flying should brief the Brake Temperature Monitor status message if the indication does not stabilize within the sample interval. Values in this manual are invented and must not be used for any operational purpose.

The captain will cross-check any change in the Brake Temperature Monitor status message and advise the other pilot when the associated caution light remains illuminated. During descent, the pilot flying should select the Flight Management Computer status message if a discrepancy is observed. The wording here is placeholder content shaped like a procedure, not a procedure. The captain will announce any change in the Brake Temperature Monitor quantity display and advise the other pilot once the checklist item is complete. If the Center Tank Pumps is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure.