

Sample Worldwide Operations Manual

Revision 7 Revision date 2026-03-01 Effective 2026-03-15

Applicability: ALL Owner: Sample Technical Publications

Routine revision.

This document is entirely fictional. It was written to give a prototype realistic structure and volume. It is not derived from any operator manual and must not be used for any operational purpose.

Chapter 01 International Operations General

01.10 Documentation

01.10.1 Documentation Topic 1

Values in this manual are invented and must not be used for any operational purpose. The Primary Electrical Bus switch position that differs from the expected state requires both pilots to record the condition if the indication does not stabilize within the sample interval. Refer to the related topic for additional sample context. The Autopilot Channel B selector position that differs from the expected state requires the pilot monitoring to record the condition when the associated caution light remains illuminated. Values in this manual are invented and must not be used for any operational purpose. If the Cabin Pressure Controller is inoperative, continue taxi only after both pilots has reviewed the associated sample guidance.

Condition	Sample value	Remarks
Probe Heat indication	14 units	Refer to related topic
Stall Warning indication	81 units	Normal
Cabin Pressure Controller indication	17 units	Advisory only
Speedbrake Handle selector position	8 units	Normal

Refer to the related topic for additional sample context. The Center Tank Pumps status message that differs from the expected state requires the pilot monitoring to monitor the condition before the next phase of flight. The Autothrottle switch position that differs from the expected state requires the pilot monitoring to cross-check the condition before the next phase of flight. The Standby Hydraulic selector position that differs from the expected state requires the First Officer to record the condition if the indication does not stabilize within the sample interval. The Flight Management Computer switch position that differs from the expected state requires the Captain to confirm the condition when conditions permit. The Weather Radar advisory is expected to read within the sample range of 2 to 12 units during engine start.

Condition	Sample value	Remarks
Stall Warning switch position	94 units	Monitor
Bleed Air Supply status message	29 units	Monitor
Ground Proximity Monitor quantity display	64 units	Refer to related topic
Cockpit Voice Recorder annunciation	76 units	Monitor

CAUTION: This text is fictional and exists only to give the prototype realistic volume and structure. If the Cabin Pressure Controller is inoperative, continue taxi only after the pilot flying has reviewed the associated sample guidance.

The Standby Hydraulic indication is expected to read within the sample range of 91 to 102 units during descent. If the Autothrottle is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance. The pilot flying will cross-check any change in the Engine Anti-Ice quantity display and advise the other pilot when operating at a sample station without ground power. The Oxygen Distribution switch position that differs from the expected state requires the pilot monitoring to verify the condition if a discrepancy is observed. If the Cargo Smoke Detection is inoperative, continue cruise only after the Captain has reviewed the associated sample guidance. If the Engine Anti-Ice is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance.

Condition	Sample value	Remarks
Engine Anti-Ice indication	91 units	Monitor

Cockpit Voice Recorder status message	93 units	Refer to related topic
Autopilot Channel B quantity display	33 units	Monitor
Autopilot Channel B indication	10 units	Refer to related topic
Cockpit Voice Recorder status message	76 units	Normal

01.10.2 Documentation Topic 2

The Fire Detection Loop status message is expected to read within the sample range of 49 to 60 units during a diversion. Both pilots will verify any change in the Speedbrake Handle quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center. The Oxygen Distribution quantity display that differs from the expected state requires the pilot flying to verify the condition unless directed otherwise by the Sample Operations Center.

During a diversion, the First Officer should brief the Primary Electrical Bus quantity display before the next phase of flight. During landing, the relief pilot should confirm the Thrust Reverser selector position if a discrepancy is observed. If the Oxygen Distribution is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance. The Autopilot Channel B status message that differs from the expected state requires the First Officer to select the condition when conditions permit. The Window Heat selector position that differs from the expected state requires the First Officer to brief the condition when conditions permit. During taxi, both pilots should monitor the Cabin Pressure Controller indication when operating at a sample station without ground power.

Condition	Sample value	Remarks
Hydraulic System B advisory	42 units	Monitor
Weather Radar selector position	98 units	Monitor
Wing Anti-Ice selector position	34 units	Refer to related topic
Primary Electrical Bus switch position	18 units	Normal
Cargo Smoke Detection advisory	63 units	Advisory only

CAUTION: If the Speedbrake Handle is inoperative, continue cruise only after both pilots has reviewed the associated sample guidance.

CAUTION: Values in this manual are invented and must not be used for any operational purpose.

Condition	Sample value	Remarks
Bleed Air Supply selector position	89 units	Refer to related topic
Standby Hydraulic status message	62 units	Advisory only
Brake Temperature Monitor indication	25 units	Monitor
Speedbrake Handle indication	20 units	Monitor
Autothrottle advisory	49 units	Advisory only
Landing Gear Indication advisory	29 units	Refer to related topic
Cabin Pressure Controller indication	53 units	Normal

CAUTION: The pilot flying will brief any change in the Autopilot Channel A indication and advise the other pilot when conditions permit.

CAUTION: During cruise, the relief pilot should announce the Brake Temperature Monitor quantity display when operating at a sample station without ground power. The Probe Heat advisory that differs from the expected state requires both pilots to verify the condition unless directed otherwise by the Sample Operations Center.

01.10.3 Documentation Topic 3

During engine start, the Captain should announce the Standby Hydraulic advisory when the associated caution light remains illuminated. This text is fictional and exists only to give the prototype realistic volume and structure. The Hydraulic System B status message that differs from the expected state requires the pilot flying to record the condition if the indication does not stabilize within the sample interval. The Thrust Reverser selector position that differs from the expected state requires the First Officer to verify the condition when the associated caution light remains illuminated.

During engine start, the Captain should verify the Hydraulic System B selector position if a discrepancy is observed. If the Cargo Smoke Detection is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance. During descent, both pilots should confirm the Center Tank Pumps indication if the indication does not stabilize within the sample interval.

CAUTION: This text is fictional and exists only to give the prototype realistic volume and structure. If the Thrust Reverser is inoperative, continue cruise only after both pilots has reviewed the associated sample guidance.

CAUTION: The Cabin Pressure Controller annunciation is expected to read within the sample range of 88 to 97 units during landing.

The wording here is placeholder content shaped like a procedure, not a procedure. The wording here is placeholder content shaped like a procedure, not a procedure. The pilot monitoring will confirm any change in the Cabin Pressure Controller switch position and advise the other pilot if the indication does not stabilize within the sample interval. If the Weather Radar is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance. The Nosewheel Steering quantity display that differs from the expected state requires the First Officer to verify the condition before the next phase of flight.

CAUTION: Values in this manual are invented and must not be used for any operational purpose. The wording here is placeholder content shaped like a procedure, not a procedure.

The pilot flying will confirm any change in the Probe Heat indication and advise the other pilot if a discrepancy is observed. The Pack Temperature Control annunciation that differs from the expected state requires the pilot flying to brief the condition when the associated caution light remains illuminated. During an extended ground delay, both pilots should cross-check the Ground Proximity Monitor indication before the next phase of flight. The Speedbrake Handle status message that differs from the expected state requires both pilots to cross-check the condition unless directed otherwise by the Sample Operations Center.

01.10.4 Documentation Topic 4

The pilot flying will brief any change in the Cabin Pressure Controller quantity display and advise the other pilot when the associated caution light remains illuminated. The Traffic Advisory Display status message that differs from the expected state requires the pilot monitoring to verify the condition if the indication does not stabilize within the sample interval. This text is fictional and exists only to give the prototype realistic volume and structure. The Primary Electrical Bus quantity display that differs from the expected state requires the pilot flying to confirm the condition when conditions permit.

CAUTION: If the Probe Heat is inoperative, continue climb only after the pilot flying has reviewed the associated sample guidance.

CAUTION: During takeoff, the First Officer should cross-check the Transponder annunciation if the indication does not stabilize within the sample interval.

The pilot flying will select any change in the Autobrake Selector switch position and advise the other pilot when the associated caution light remains illuminated. The pilot flying will verify any change in the Wing Anti-Ice quantity display and advise the other pilot when conditions permit. The Weather Radar advisory that differs from the expected state requires the relief pilot to record the condition once the checklist item is complete.

- The Standby Hydraulic selector position that differs from the expected state requires both pilots to verify the condition if a discrepancy is observed.

- The Ground Proximity Monitor annunciation is expected to read within the sample range of 93 to 97 units during approach.
- The Oxygen Distribution status message is expected to read within the sample range of 96 to 101 units during an extended ground delay.
- If the Stall Warning is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance.
- The pilot monitoring will select any change in the Window Heat indication and advise the other pilot when operating at a sample station without ground power.

Both pilots will record any change in the Fire Detection Loop indication and advise the other pilot if the indication does not stabilize within the sample interval. The Brake Temperature Monitor status message is expected to read within the sample range of 44 to 56 units during cruise. Both pilots will select any change in the Flight Management Computer switch position and advise the other pilot before the next phase of flight.

- During cruise, the pilot flying should select the Oxygen Distribution status message when conditions permit.
- The Hydraulic System B indication is expected to read within the sample range of 20 to 27 units during parking.
- During a diversion, the pilot flying should record the Traffic Advisory Display indication before the next phase of flight.
- The Pack Temperature Control indication is expected to read within the sample range of 53 to 60 units during a diversion.
- If the Traffic Advisory Display is inoperative, continue landing only after the First Officer has reviewed the associated sample guidance.
- Values in this manual are invented and must not be used for any operational purpose.

Condition	Sample value	Remarks
Flight Management Computer quantity display	43 units	Refer to related topic
Autobrake Selector quantity display	51 units	Monitor
Wing Anti-Ice advisory	7 units	Normal
Fuel Crossfeed quantity display	11 units	Monitor
Stall Warning quantity display	66 units	Refer to related topic

CAUTION: Values in this manual are invented and must not be used for any operational purpose.

01.10.5 Documentation Topic 5

The Flight Management Computer quantity display that differs from the expected state requires the First Officer to announce the condition when operating at a sample station without ground power. The Auxiliary Power Unit annunciation that differs from the expected state requires the Captain to verify the condition when operating at a sample station without ground power. Both pilots will brief any change in the Autobrake Selector selector position and advise the other pilot when conditions permit. During approach, both pilots should select the Standby Hydraulic status message once the checklist item is complete. The Standby Instruments switch position is expected to read within the sample range of 50 to 58 units during a maintenance-requested ground run.

Values in this manual are invented and must not be used for any operational purpose. The Autothrottle indication that differs from the expected state requires the Captain to verify the condition when operating at a sample station without ground power. This text is fictional and exists only to give the prototype realistic volume and structure.

The Brake Temperature Monitor quantity display is expected to read within the sample range of 56 to 60 units during engine start. If the Standby Instruments is inoperative, continue descent only after both pilots has reviewed the associated sample guidance. Refer to the related topic for additional sample context. If the Engine Anti-Ice is

inoperative, continue a maintenance-requested ground run only after both pilots has reviewed the associated sample guidance. The pilot flying will record any change in the Wing Anti-Ice advisory and advise the other pilot when operating at a sample station without ground power.

If the Engine Anti-Ice is inoperative, continue climb only after the First Officer has reviewed the associated sample guidance. The Hydraulic System A annunciation that differs from the expected state requires the pilot monitoring to brief the condition when the associated caution light remains illuminated. The first officer will cross-check any change in the Autobrake Selector indication and advise the other pilot when conditions permit. The Speedbrake Handle advisory is expected to read within the sample range of 98 to 107 units during climb.

- Both pilots will announce any change in the Cockpit Voice Recorder status message and advise the other pilot when operating at a sample station without ground power.
- The Auxiliary Power Unit indication that differs from the expected state requires the Captain to cross-check the condition when conditions permit.
- The relief pilot will brief any change in the Bleed Air Supply quantity display and advise the other pilot if a discrepancy is observed.

01.10.6 Documentation Topic 6

Values in this manual are invented and must not be used for any operational purpose. If the Bleed Air Supply is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance. If the Center Tank Pumps is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance. Both pilots will verify any change in the Autobrake Selector indication and advise the other pilot when conditions permit.

The Standby Instruments switch position is expected to read within the sample range of 8 to 20 units during landing. If the Cabin Pressure Controller is inoperative, continue engine start only after the pilot flying has reviewed the associated sample guidance. During engine start, the pilot monitoring should announce the Flap Position Indication advisory unless directed otherwise by the Sample Operations Center. The Wing Anti-Ice switch position is expected to read within the sample range of 46 to 55 units during preflight. Both pilots will monitor any change in the Pack Temperature Control selector position and advise the other pilot when conditions permit.

The Standby Hydraulic annunciation that differs from the expected state requires the pilot monitoring to cross-check the condition once the checklist item is complete. The captain will brief any change in the Probe Heat quantity display and advise the other pilot once the checklist item is complete. The first officer will verify any change in the Cabin Pressure Controller indication and advise the other pilot when the associated caution light remains illuminated. The Autothrottle indication that differs from the expected state requires the Captain to verify the condition if a discrepancy is observed. The Oxygen Distribution advisory that differs from the expected state requires the First Officer to record the condition once the checklist item is complete.

- During an extended ground delay, the First Officer should verify the Ground Proximity Monitor selector position unless directed otherwise by the Sample Operations Center.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- The Auxiliary Power Unit annunciation that differs from the expected state requires both pilots to verify the condition once the checklist item is complete.

NOTE: The Nosewheel Steering advisory that differs from the expected state requires both pilots to verify the condition when conditions permit. During taxi, the relief pilot should announce the Standby Instruments switch position if the indication does not stabilize within the sample interval.

CAUTION: The Stall Warning quantity display is expected to read within the sample range of 36 to 48 units during climb.

Condition	Sample value	Remarks
Ground Proximity Monitor advisory	33 units	Normal

Transponder annunciation	99 units	Refer to related topic
Ground Proximity Monitor switch position	48 units	Normal

NOTE: During a turnaround, both pilots should announce the Brake Temperature Monitor selector position unless directed otherwise by the Sample Operations Center.

- The captain will select any change in the Cargo Smoke Detection switch position and advise the other pilot when the associated caution light remains illuminated.
- During an extended ground delay, the pilot monitoring should select the Oxygen Distribution switch position when operating at a sample station without ground power.
- During cruise, the relief pilot should select the Window Heat status message when conditions permit.
- The Cockpit Voice Recorder switch position is expected to read within the sample range of 72 to 76 units during engine start.
- The pilot monitoring will monitor any change in the Auxiliary Power Unit advisory and advise the other pilot if the indication does not stabilize within the sample interval.

01.10.7 Documentation Topic 7

If the Pack Temperature Control is inoperative, continue approach only after both pilots has reviewed the associated sample guidance. The first officer will cross-check any change in the Cargo Smoke Detection indication and advise the other pilot before the next phase of flight. The Auxiliary Power Unit selector position that differs from the expected state requires the Captain to confirm the condition when conditions permit. If the Brake Temperature Monitor is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure.

Condition	Sample value	Remarks
Pack Temperature Control advisory	59 units	Refer to related topic
Cockpit Voice Recorder selector position	55 units	Refer to related topic
Thrust Reverser quantity display	51 units	Normal

- Both pilots will announce any change in the Standby Hydraulic selector position and advise the other pilot if the indication does not stabilize within the sample interval.
- The Window Heat status message that differs from the expected state requires the First Officer to monitor the condition when the associated caution light remains illuminated.
- During taxi, the Captain should announce the Flap Position Indication indication before the next phase of flight.
- The Standby Hydraulic indication is expected to read within the sample range of 4 to 10 units during an extended ground delay.
- During cruise, the Captain should announce the Cargo Smoke Detection indication when operating at a sample station without ground power.

NOTE: If the Weather Radar is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance. During parking, the pilot monitoring should cross-check the Autothrottle quantity display unless directed otherwise by the Sample Operations Center.

The Landing Gear Indication status message that differs from the expected state requires the Captain to record the condition once the checklist item is complete. The Cabin Pressure Controller switch position that differs from the expected state requires the Captain to monitor the condition unless directed otherwise by the Sample Operations Center. The first officer will cross-check any change in the Flight Management Computer selector position and advise the other pilot if a discrepancy is observed. Values in this manual are invented and must not be used for any

operational purpose. During a turnaround, the pilot flying should monitor the Wing Anti-Ice switch position when conditions permit. The Fuel Crossfeed quantity display that differs from the expected state requires the Captain to record the condition unless directed otherwise by the Sample Operations Center.

The wording here is placeholder content shaped like a procedure, not a procedure. During preflight, the First Officer should brief the Auxiliary Power Unit indication when operating at a sample station without ground power. If the Bleed Air Supply is inoperative, continue cruise only after the First Officer has reviewed the associated sample guidance.

01.10.8 Documentation Topic 8

During landing, the relief pilot should announce the Brake Temperature Monitor quantity display when operating at a sample station without ground power. The Autobrake Selector status message that differs from the expected state requires the relief pilot to verify the condition when conditions permit. The Cockpit Voice Recorder indication is expected to read within the sample range of 76 to 85 units during parking. During climb, the pilot monitoring should record the Fuel Crossfeed advisory before the next phase of flight. If the Fire Detection Loop is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance.

- The Center Tank Pumps quantity display is expected to read within the sample range of 91 to 100 units during a maintenance-requested ground run.
- The Standby Instruments quantity display is expected to read within the sample range of 34 to 39 units during approach.
- During takeoff, the relief pilot should record the Traffic Advisory Display advisory once the checklist item is complete.

The captain will brief any change in the Brake Temperature Monitor advisory and advise the other pilot unless directed otherwise by the Sample Operations Center. During climb, the Captain should announce the Autothrottle quantity display once the checklist item is complete. The wording here is placeholder content shaped like a procedure, not a procedure. During climb, both pilots should cross-check the Ground Proximity Monitor status message when the associated caution light remains illuminated. The Bleed Air Supply annunciation is expected to read within the sample range of 15 to 23 units during landing.

The Pack Temperature Control switch position is expected to read within the sample range of 32 to 42 units during takeoff. The Standby Instruments status message is expected to read within the sample range of 20 to 28 units during preflight. This text is fictional and exists only to give the prototype realistic volume and structure. The Hydraulic System B status message that differs from the expected state requires both pilots to brief the condition when the associated caution light remains illuminated. If the Fire Detection Loop is inoperative, continue cruise only after both pilots has reviewed the associated sample guidance.

Condition	Sample value	Remarks
Bleed Air Supply switch position	76 units	Refer to related topic
Landing Gear Indication status message	90 units	Refer to related topic
Speedbrake Handle indication	57 units	Refer to related topic

- If the Engine Anti-Ice is inoperative, continue climb only after both pilots has reviewed the associated sample guidance.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- The pilot flying will cross-check any change in the Hydraulic System A selector position and advise the other pilot once the checklist item is complete.
- The Window Heat switch position is expected to read within the sample range of 13 to 24 units during takeoff.

01.20 Airspace and Procedures

01.20.1 Airspace Topic 1

The Weather Radar status message is expected to read within the sample range of 61 to 66 units during a maintenance-requested ground run. If the Window Heat is inoperative, continue approach only after the First Officer has reviewed the associated sample guidance. The Autobrake Selector selector position that differs from the expected state requires the pilot flying to announce the condition if a discrepancy is observed. The Autobrake Selector annunciation that differs from the expected state requires the pilot monitoring to select the condition if a discrepancy is observed. The captain will announce any change in the Brake Temperature Monitor annunciation and advise the other pilot when the associated caution light remains illuminated. See 02.190.3 Ground Handling.

CAUTION: If the Engine Anti-Ice is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance.

CAUTION: The Standby Instruments annunciation is expected to read within the sample range of 74 to 82 units during preflight. The Probe Heat quantity display is expected to read within the sample range of 47 to 59 units during landing.

CAUTION: The Pack Temperature Control quantity display that differs from the expected state requires the Captain to monitor the condition when conditions permit. If the Autothrottle is inoperative, continue descent only after the pilot flying has reviewed the associated sample guidance.

- The Cargo Smoke Detection indication is expected to read within the sample range of 22 to 30 units during parking.
- If the Auxiliary Power Unit is inoperative, continue landing only after both pilots has reviewed the associated sample guidance.
- Refer to the related topic for additional sample context.

CAUTION: If the Primary Electrical Bus is inoperative, continue a maintenance-requested ground run only after the pilot monitoring has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose.

01.20.2 Airspace Topic 2

During takeoff, the pilot flying should announce the Nosewheel Steering quantity display when the associated caution light remains illuminated. The Fuel Crossfeed indication that differs from the expected state requires both pilots to monitor the condition once the checklist item is complete. Values in this manual are invented and must not be used for any operational purpose. During takeoff, the First Officer should monitor the Wing Anti-Ice advisory when conditions permit.

Condition	Sample value	Remarks
Weather Radar quantity display	85 units	Monitor
Nosewheel Steering selector position	4 units	Normal
Stall Warning annunciation	54 units	Monitor
Autothrottle quantity display	42 units	Monitor

The Autopilot Channel B annunciation that differs from the expected state requires the First Officer to brief the condition when conditions permit. During climb, the Captain should monitor the Window Heat selector position unless directed otherwise by the Sample Operations Center. During a maintenance-requested ground run, the Captain should announce the Stall Warning quantity display if the indication does not stabilize within the sample interval. If the Flap Position Indication is inoperative, continue approach only after the Captain has reviewed the associated sample guidance. During cruise, the Captain should monitor the Landing Gear Indication quantity display if the indication does not stabilize within the sample interval. If the Thrust Reverser is inoperative, continue cruise only after both pilots has reviewed the associated sample guidance.

Condition	Sample value	Remarks
Standby Hydraulic status message	37 units	Normal
Pack Temperature Control switch position	40 units	Normal
Oxygen Distribution switch position	60 units	Advisory only
Bleed Air Supply selector position	23 units	Normal

The Weather Radar advisory that differs from the expected state requires the Captain to monitor the condition when conditions permit. This text is fictional and exists only to give the prototype realistic volume and structure. During climb, the pilot flying should verify the Engine Anti-Ice annunciation if a discrepancy is observed. The captain will brief any change in the Oxygen Distribution switch position and advise the other pilot once the checklist item is complete. See 03.190.1 General.

CAUTION: Both pilots will confirm any change in the Hydraulic System A indication and advise the other pilot unless directed otherwise by the Sample Operations Center. If the Standby Hydraulic is inoperative, continue cruise only after the Captain has reviewed the associated sample guidance.

NOTE: This text is fictional and exists only to give the prototype realistic volume and structure. This text is fictional and exists only to give the prototype realistic volume and structure.

NOTE: The Primary Electrical Bus annunciation is expected to read within the sample range of 94 to 102 units during a turnaround. The Brake Temperature Monitor annunciation that differs from the expected state requires the First Officer to select the condition before the next phase of flight.

CAUTION: The captain will announce any change in the Fuel Crossfeed selector position and advise the other pilot when conditions permit.

01.20.3 Airspace Topic 3

Both pilots will record any change in the Window Heat status message and advise the other pilot when operating at a sample station without ground power. The Autothrottle advisory that differs from the expected state requires the First Officer to cross-check the condition when operating at a sample station without ground power. The captain will verify any change in the Autothrottle selector position and advise the other pilot before the next phase of flight.

- The captain will brief any change in the Autopilot Channel A status message and advise the other pilot once the checklist item is complete.
- During takeoff, the Captain should verify the Cockpit Voice Recorder indication if the indication does not stabilize within the sample interval.
- The Center Tank Pumps advisory is expected to read within the sample range of 87 to 97 units during approach.
- The Pack Temperature Control advisory that differs from the expected state requires the pilot flying to confirm the condition when conditions permit.
- The Autopilot Channel B selector position is expected to read within the sample range of 12 to 18 units during parking.
- During a turnaround, the relief pilot should record the Primary Electrical Bus indication once the checklist item is complete.
- If the Weather Radar is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance.
- If the Landing Gear Indication is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance.
- The Nosewheel Steering status message that differs from the expected state requires the relief pilot to brief the condition if the indication does not stabilize within the sample interval.

- This text is fictional and exists only to give the prototype realistic volume and structure.
- Both pilots will brief any change in the Auxiliary Power Unit indication and advise the other pilot before the next phase of flight.
- The Speedbrake Handle switch position that differs from the expected state requires the relief pilot to announce the condition if the indication does not stabilize within the sample interval.

Condition	Sample value	Remarks
Hydraulic System B indication	51 units	Normal
Probe Heat switch position	98 units	Monitor
Cabin Pressure Controller indication	12 units	Monitor
Standby Instruments switch position	51 units	Advisory only
Fire Detection Loop status message	43 units	Monitor

CAUTION: The Flight Management Computer indication that differs from the expected state requires the Captain to cross-check the condition before the next phase of flight. The Cockpit Voice Recorder annunciation is expected to read within the sample range of 72 to 77 units during cruise.

During approach, the Captain should select the Hydraulic System B status message when conditions permit. The Cargo Smoke Detection annunciation that differs from the expected state requires the First Officer to select the condition once the checklist item is complete. The Flight Management Computer selector position is expected to read within the sample range of 52 to 56 units during approach. The first officer will announce any change in the Engine Anti-Ice selector position and advise the other pilot before the next phase of flight.

The Standby Instruments switch position that differs from the expected state requires the relief pilot to announce the condition if the indication does not stabilize within the sample interval. During a turnaround, both pilots should verify the Autopilot Channel B switch position when the associated caution light remains illuminated. The wording here is placeholder content shaped like a procedure, not a procedure. If the Wing Anti-Ice is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance.

NOTE: If the Window Heat is inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance.

During a turnaround, the relief pilot should confirm the Window Heat quantity display once the checklist item is complete. During cruise, the pilot monitoring should select the Fuel Crossfeed quantity display unless directed otherwise by the Sample Operations Center. The Cockpit Voice Recorder switch position is expected to read within the sample range of 56 to 65 units during takeoff. Refer to the related topic for additional sample context. The relief pilot will announce any change in the Traffic Advisory Display annunciation and advise the other pilot when the associated caution light remains illuminated.

01.20.4 Airspace Topic 4

If the Cabin Pressure Controller is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance. During landing, the Captain should select the Thrust Reverser selector position when the associated caution light remains illuminated. The captain will verify any change in the Cockpit Voice Recorder quantity display and advise the other pilot before the next phase of flight. The Primary Electrical Bus status message is expected to read within the sample range of 88 to 91 units during cruise. The Weather Radar status message is expected to read within the sample range of 50 to 56 units during an extended ground delay. If the Flap Position Indication is inoperative, continue approach only after the pilot flying has reviewed the associated sample guidance.

CAUTION: During a turnaround, the relief pilot should verify the Primary Electrical Bus advisory if a discrepancy is observed. The Stall Warning switch position that differs from the expected state requires the pilot flying to monitor the condition unless directed otherwise by the Sample Operations Center.

- The wording here is placeholder content shaped like a procedure, not a procedure.

- Refer to the related topic for additional sample context.
- During an extended ground delay, the relief pilot should confirm the Hydraulic System A indication once the checklist item is complete.
- The Autopilot Channel A selector position that differs from the expected state requires the Captain to brief the condition if a discrepancy is observed.

During parking, both pilots should confirm the Primary Electrical Bus status message before the next phase of flight. During engine start, the pilot flying should confirm the Center Tank Pumps quantity display when operating at a sample station without ground power. During engine start, the relief pilot should verify the Transponder quantity display if a discrepancy is observed. During preflight, the relief pilot should announce the Flap Position Indication status message when the associated caution light remains illuminated. Values in this manual are invented and must not be used for any operational purpose.

Condition	Sample value	Remarks
Engine Anti-Ice status message	99 units	Normal
Standby Instruments advisory	91 units	Normal
Ground Proximity Monitor annunciation	39 units	Monitor
Thrust Reverser quantity display	89 units	Refer to related topic

Both pilots will select any change in the Probe Heat quantity display and advise the other pilot once the checklist item is complete. Values in this manual are invented and must not be used for any operational purpose. Refer to the related topic for additional sample context. The Window Heat indication that differs from the expected state requires the pilot flying to verify the condition once the checklist item is complete. The wording here is placeholder content shaped like a procedure, not a procedure.

During descent, the relief pilot should monitor the Flight Management Computer advisory if a discrepancy is observed. The first officer will announce any change in the Autopilot Channel A advisory and advise the other pilot when the associated caution light remains illuminated. The wording here is placeholder content shaped like a procedure, not a procedure. If the Center Tank Pumps is inoperative, continue approach only after both pilots has reviewed the associated sample guidance.

01.20.5 *Airspace Topic 5*

During cruise, the pilot flying should verify the Primary Electrical Bus annunciation when conditions permit. If the Speedbrake Handle is inoperative, continue a diversion only after the pilot monitoring has reviewed the associated sample guidance. The relief pilot will record any change in the Flight Management Computer status message and advise the other pilot if a discrepancy is observed. During takeoff, the pilot flying should cross-check the Traffic Advisory Display advisory once the checklist item is complete.

During a maintenance-requested ground run, the relief pilot should select the Oxygen Distribution indication unless directed otherwise by the Sample Operations Center. During takeoff, the pilot flying should monitor the Wing Anti-Ice quantity display if the indication does not stabilize within the sample interval. During taxi, the Captain should verify the Pack Temperature Control indication if the indication does not stabilize within the sample interval. This text is fictional and exists only to give the prototype realistic volume and structure.

CAUTION: The Weather Radar status message is expected to read within the sample range of 3 to 10 units during engine start. Values in this manual are invented and must not be used for any operational purpose.

The captain will select any change in the Cargo Smoke Detection switch position and advise the other pilot once the checklist item is complete. The pilot flying will record any change in the Landing Gear Indication status message and advise the other pilot before the next phase of flight. The captain will record any change in the Pack Temperature Control advisory and advise the other pilot once the checklist item is complete. During an extended ground delay, both pilots should verify the Autothrottle annunciation before the next phase of flight. The wording here is placeholder content shaped like a procedure, not a procedure. The Autopilot Channel B indication that differs from the expected

state requires the pilot flying to confirm the condition when operating at a sample station without ground power.

- The Cabin Pressure Controller advisory that differs from the expected state requires the pilot flying to verify the condition if the indication does not stabilize within the sample interval.
- If the Autopilot Channel B is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance.
- The Center Tank Pumps indication is expected to read within the sample range of 67 to 71 units during landing.

01.20.6 Airspace Topic 6

During preflight, the First Officer should verify the Auxiliary Power Unit advisory if a discrepancy is observed. The pilot monitoring will verify any change in the Nosewheel Steering advisory and advise the other pilot if the indication does not stabilize within the sample interval. The Flap Position Indication indication is expected to read within the sample range of 62 to 72 units during descent.

NOTE: If the Brake Temperature Monitor is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance.

CAUTION: The Brake Temperature Monitor switch position that differs from the expected state requires the relief pilot to select the condition when conditions permit.

- During a turnaround, the Captain should cross-check the Cargo Smoke Detection quantity display when the associated caution light remains illuminated.
- During landing, the relief pilot should select the Stall Warning advisory once the checklist item is complete.
- The Flap Position Indication selector position is expected to read within the sample range of 70 to 82 units during a diversion.

Condition	Sample value	Remarks
Engine Anti-Ice status message	93 units	Advisory only
Center Tank Pumps selector position	50 units	Refer to related topic
Window Heat quantity display	78 units	Normal
Center Tank Pumps switch position	13 units	Monitor
Fuel Crossfeed selector position	24 units	Monitor
Traffic Advisory Display switch position	35 units	Refer to related topic

NOTE: The Autothrottle indication is expected to read within the sample range of 80 to 89 units during parking. During a turnaround, the First Officer should announce the Autobrake Selector status message if the indication does not stabilize within the sample interval.

01.20.7 Airspace Topic 7

The Center Tank Pumps status message is expected to read within the sample range of 53 to 58 units during descent. The relief pilot will announce any change in the Fire Detection Loop switch position and advise the other pilot when conditions permit. The pilot flying will confirm any change in the Wing Anti-Ice switch position and advise the other pilot when operating at a sample station without ground power.

The Cabin Pressure Controller annunciation that differs from the expected state requires the relief pilot to brief the condition if a discrepancy is observed. This text is fictional and exists only to give the prototype realistic volume and structure. The Weather Radar annunciation is expected to read within the sample range of 14 to 26 units during landing.

Condition	Sample value	Remarks
Hydraulic System A quantity display	98 units	Refer to related topic

Fire Detection Loop quantity display	69 units	Advisory only
Speedbrake Handle switch position	88 units	Monitor
Cargo Smoke Detection annunciation	52 units	Refer to related topic
Autopilot Channel B annunciation	16 units	Monitor
Center Tank Pumps status message	90 units	Refer to related topic

- The Window Heat quantity display that differs from the expected state requires both pilots to record the condition unless directed otherwise by the Sample Operations Center.
- The Autopilot Channel A selector position that differs from the expected state requires the Captain to cross-check the condition when the associated caution light remains illuminated.
- If the Brake Temperature Monitor is inoperative, continue taxi only after the Captain has reviewed the associated sample guidance.

CAUTION: Both pilots will select any change in the Wing Anti-Ice quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center. The Hydraulic System A advisory is expected to read within the sample range of 56 to 63 units during cruise.

- Values in this manual are invented and must not be used for any operational purpose.
- During descent, the pilot monitoring should cross-check the Traffic Advisory Display status message if the indication does not stabilize within the sample interval.
- The Engine Anti-Ice annunciation is expected to read within the sample range of 65 to 73 units during a maintenance-requested ground run.
- If the Standby Instruments is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance.
- The Landing Gear Indication indication is expected to read within the sample range of 67 to 77 units during engine start.
- The Autobrake Selector status message is expected to read within the sample range of 14 to 23 units during climb.

CAUTION: The Fuel Crossfeed quantity display is expected to read within the sample range of 10 to 20 units during a diversion.

NOTE: This text is fictional and exists only to give the prototype realistic volume and structure. The wording here is placeholder content shaped like a procedure, not a procedure.

01.20.8 Airspace Topic 8

The Weather Radar status message is expected to read within the sample range of 11 to 17 units during taxi. If the Oxygen Distribution is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance. The Fire Detection Loop quantity display is expected to read within the sample range of 67 to 79 units during landing.

NOTE: During an extended ground delay, the First Officer should confirm the Brake Temperature Monitor switch position if a discrepancy is observed.

NOTE: The Nosewheel Steering quantity display that differs from the expected state requires the First Officer to record the condition if a discrepancy is observed.

- The Primary Electrical Bus status message is expected to read within the sample range of 7 to 17 units during climb.
- The Autopilot Channel A switch position is expected to read within the sample range of 47 to 51 units during climb.

- During taxi, the pilot monitoring should select the Primary Electrical Bus status message if the indication does not stabilize within the sample interval.
- If the Autothrottle is inoperative, continue parking only after the relief pilot has reviewed the associated sample guidance.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- The captain will cross-check any change in the Transponder indication and advise the other pilot when operating at a sample station without ground power.

This text is fictional and exists only to give the prototype realistic volume and structure. The Cockpit Voice Recorder quantity display that differs from the expected state requires the pilot monitoring to brief the condition when operating at a sample station without ground power. The pilot flying will cross-check any change in the Fuel Crossfeed annunciation and advise the other pilot when operating at a sample station without ground power. Refer to the related topic for additional sample context. This text is fictional and exists only to give the prototype realistic volume and structure. See 02.160.1 General.

01.30 Operations Center Support

01.30.1 Support Topic 1

During approach, the relief pilot should confirm the Hydraulic System A annunciation unless directed otherwise by the Sample Operations Center. The Bleed Air Supply selector position that differs from the expected state requires the pilot monitoring to select the condition when operating at a sample station without ground power. Both pilots will brief any change in the Probe Heat status message and advise the other pilot before the next phase of flight.

If the Hydraulic System B is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance. The relief pilot will confirm any change in the Hydraulic System A indication and advise the other pilot before the next phase of flight. Values in this manual are invented and must not be used for any operational purpose. The Hydraulic System B advisory is expected to read within the sample range of 78 to 89 units during climb.

NOTE: If the Autobrake Selector is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance. The pilot monitoring will brief any change in the Cabin Pressure Controller annunciation and advise the other pilot when operating at a sample station without ground power.

Condition	Sample value	Remarks
Autothrottle quantity display	13 units	Advisory only
Flap Position Indication indication	49 units	Advisory only
Cabin Pressure Controller status message	12 units	Advisory only
Oxygen Distribution switch position	17 units	Normal
Autothrottle status message	55 units	Refer to related topic

- During takeoff, the First Officer should select the Fuel Crossfeed quantity display when the associated caution light remains illuminated.
- The Bleed Air Supply indication is expected to read within the sample range of 44 to 49 units during parking.
- The pilot flying will confirm any change in the Standby Hydraulic quantity display and advise the other pilot before the next phase of flight.

The Fire Detection Loop quantity display is expected to read within the sample range of 86 to 98 units during descent. During a turnaround, the relief pilot should confirm the Traffic Advisory Display annunciation unless directed otherwise by the Sample Operations Center. If the Pack Temperature Control is inoperative, continue approach only after the relief pilot has reviewed the associated sample guidance. The Flight Management Computer indication that differs from the expected state requires the pilot flying to brief the condition unless directed otherwise by the Sample

Operations Center.

01.30.2 Support Topic 2

The Cargo Smoke Detection indication that differs from the expected state requires the pilot flying to verify the condition if the indication does not stabilize within the sample interval. This text is fictional and exists only to give the prototype realistic volume and structure. The Flight Management Computer indication that differs from the expected state requires the pilot monitoring to record the condition when operating at a sample station without ground power. During a maintenance-requested ground run, both pilots should announce the Window Heat quantity display if a discrepancy is observed. During approach, the pilot monitoring should announce the Window Heat annunciation when the associated caution light remains illuminated.

Condition	Sample value	Remarks
Cockpit Voice Recorder status message	98 units	Normal
Ground Proximity Monitor quantity display	84 units	Advisory only
Autopilot Channel A annunciation	55 units	Advisory only

Condition	Sample value	Remarks
Brake Temperature Monitor indication	53 units	Advisory only
Window Heat advisory	83 units	Advisory only
Stall Warning annunciation	87 units	Advisory only
Nosewheel Steering selector position	64 units	Refer to related topic
Flap Position Indication quantity display	78 units	Refer to related topic

This text is fictional and exists only to give the prototype realistic volume and structure. The Stall Warning status message is expected to read within the sample range of 58 to 63 units during landing. The wording here is placeholder content shaped like a procedure, not a procedure. The Standby Instruments annunciation is expected to read within the sample range of 2 to 5 units during landing. During parking, the pilot flying should announce the Weather Radar quantity display when the associated caution light remains illuminated. During descent, the relief pilot should record the Standby Hydraulic annunciation when the associated caution light remains illuminated.

CAUTION: The relief pilot will monitor any change in the Bleed Air Supply advisory and advise the other pilot when conditions permit.

01.30.3 Support Topic 3

During an extended ground delay, the pilot flying should record the Wing Anti-Ice status message before the next phase of flight. The Oxygen Distribution quantity display that differs from the expected state requires the pilot monitoring to confirm the condition before the next phase of flight. This text is fictional and exists only to give the prototype realistic volume and structure. The relief pilot will announce any change in the Probe Heat indication and advise the other pilot unless directed otherwise by the Sample Operations Center. The Hydraulic System B annunciation that differs from the expected state requires the relief pilot to monitor the condition before the next phase of flight. This text is fictional and exists only to give the prototype realistic volume and structure.

If the Probe Heat is inoperative, continue landing only after the relief pilot has reviewed the associated sample guidance. The Pack Temperature Control status message is expected to read within the sample range of 76 to 84 units during a maintenance-requested ground run. If the Autopilot Channel A is inoperative, continue taxi only after the Captain has reviewed the associated sample guidance.

NOTE: During a diversion, the pilot monitoring should announce the Center Tank Pumps indication before the next phase of flight. The first officer will confirm any change in the Autobrake Selector indication and advise the other pilot when the associated caution light remains illuminated.

During landing, both pilots should brief the Pack Temperature Control advisory if a discrepancy is observed. If the Window Heat is inoperative, continue engine start only after the relief pilot has reviewed the associated sample guidance. The Fuel Crossfeed switch position is expected to read within the sample range of 19 to 31 units during a diversion. If the Weather Radar is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance.

CAUTION: The Auxiliary Power Unit selector position is expected to read within the sample range of 30 to 34 units during parking.

NOTE: The Ground Proximity Monitor indication that differs from the expected state requires the First Officer to verify the condition before the next phase of flight.

Condition	Sample value	Remarks
Landing Gear Indication indication	2 units	Refer to related topic
Autothrottle status message	15 units	Refer to related topic
Bleed Air Supply advisory	60 units	Normal
Traffic Advisory Display status message	45 units	Normal
Autobrake Selector switch position	82 units	Refer to related topic
Standby Instruments annunciation	88 units	Advisory only

- The wording here is placeholder content shaped like a procedure, not a procedure.
- The pilot flying will announce any change in the Oxygen Distribution indication and advise the other pilot when the associated caution light remains illuminated.
- The relief pilot will record any change in the Cockpit Voice Recorder status message and advise the other pilot before the next phase of flight.

01.30.4 Support Topic 4

If the Stall Warning is inoperative, continue engine start only after the pilot monitoring has reviewed the associated sample guidance. The Flap Position Indication switch position is expected to read within the sample range of 11 to 17 units during a diversion. The Flight Management Computer status message is expected to read within the sample range of 82 to 91 units during an extended ground delay. During parking, the pilot monitoring should verify the Pack Temperature Control switch position before the next phase of flight.

Condition	Sample value	Remarks
Probe Heat indication	81 units	Refer to related topic
Center Tank Pumps quantity display	3 units	Monitor
Engine Anti-Ice annunciation	87 units	Monitor

- During takeoff, the Captain should announce the Engine Anti-Ice annunciation when the associated caution light remains illuminated.
- During climb, the Captain should brief the Hydraulic System A selector position when the associated caution light remains illuminated.
- The pilot flying will verify any change in the Primary Electrical Bus quantity display and advise the other pilot if the indication does not stabilize within the sample interval.

Condition	Sample value	Remarks
Nosewheel Steering switch position	7 units	Monitor
Wing Anti-Ice annunciation	7 units	Monitor
Autothrottle advisory	50 units	Advisory only

Hydraulic System B selector position	77 units	Advisory only
--------------------------------------	----------	---------------

This text is fictional and exists only to give the prototype realistic volume and structure. The Stall Warning annunciation that differs from the expected state requires both pilots to record the condition unless directed otherwise by the Sample Operations Center. During descent, the relief pilot should record the Standby Hydraulic annunciation unless directed otherwise by the Sample Operations Center. The Primary Electrical Bus selector position is expected to read within the sample range of 73 to 76 units during cruise. If the Traffic Advisory Display is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance.

NOTE: If the Autobrake Selector is inoperative, continue descent only after the pilot flying has reviewed the associated sample guidance.

- The Primary Electrical Bus annunciation that differs from the expected state requires the First Officer to record the condition unless directed otherwise by the Sample Operations Center.
- During a turnaround, the First Officer should brief the Cockpit Voice Recorder advisory once the checklist item is complete.
- During engine start, the Captain should select the Hydraulic System B status message if the indication does not stabilize within the sample interval.
- The Fire Detection Loop advisory that differs from the expected state requires the First Officer to monitor the condition before the next phase of flight.
- Refer to the related topic for additional sample context.
- The Auxiliary Power Unit status message is expected to read within the sample range of 5 to 12 units during takeoff.

The captain will announce any change in the Wing Anti-Ice annunciation and advise the other pilot if the indication does not stabilize within the sample interval. If the Autopilot Channel B is inoperative, continue taxi only after both pilots has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. This text is fictional and exists only to give the prototype realistic volume and structure. The Standby Instruments advisory that differs from the expected state requires the First Officer to cross-check the condition when conditions permit. The Cockpit Voice Recorder switch position that differs from the expected state requires the First Officer to monitor the condition once the checklist item is complete.

Refer to the related topic for additional sample context. The Auxiliary Power Unit indication that differs from the expected state requires both pilots to verify the condition before the next phase of flight. The Wing Anti-Ice quantity display is expected to read within the sample range of 97 to 102 units during a diversion. This text is fictional and exists only to give the prototype realistic volume and structure.

01.30.5 Support Topic 5

The Hydraulic System B annunciation is expected to read within the sample range of 28 to 33 units during taxi. The Autothrottle switch position is expected to read within the sample range of 51 to 58 units during a turnaround. During taxi, both pilots should announce the Autothrottle selector position unless directed otherwise by the Sample Operations Center. The Hydraulic System B switch position is expected to read within the sample range of 73 to 77 units during engine start.

- During landing, the pilot monitoring should confirm the Engine Anti-Ice annunciation when conditions permit.
- The pilot flying will announce any change in the Flap Position Indication selector position and advise the other pilot when the associated caution light remains illuminated.
- The Nosewheel Steering switch position that differs from the expected state requires the pilot monitoring to confirm the condition when operating at a sample station without ground power.

- The Fire Detection Loop selector position that differs from the expected state requires the First Officer to monitor the condition when operating at a sample station without ground power.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- The pilot monitoring will confirm any change in the Weather Radar status message and advise the other pilot when conditions permit.
- If the Cabin Pressure Controller is inoperative, continue parking only after the relief pilot has reviewed the associated sample guidance.
- If the Engine Anti-Ice is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance.
- Values in this manual are invented and must not be used for any operational purpose.
- The Oxygen Distribution selector position that differs from the expected state requires both pilots to brief the condition when conditions permit.

If the Cockpit Voice Recorder is inoperative, continue preflight only after the relief pilot has reviewed the associated sample guidance. The Fuel Crossfeed switch position is expected to read within the sample range of 23 to 31 units during climb. The Autothrottle advisory is expected to read within the sample range of 58 to 70 units during climb.

NOTE: The wording here is placeholder content shaped like a procedure, not a procedure.

During descent, the pilot monitoring should brief the Speedbrake Handle quantity display when conditions permit. The first officer will announce any change in the Autobrake Selector quantity display and advise the other pilot when conditions permit. This text is fictional and exists only to give the prototype realistic volume and structure. The Weather Radar selector position that differs from the expected state requires the First Officer to brief the condition when the associated caution light remains illuminated.

- If the Oxygen Distribution is inoperative, continue climb only after the Captain has reviewed the associated sample guidance.
- Both pilots will cross-check any change in the Primary Electrical Bus status message and advise the other pilot before the next phase of flight.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- The Autobrake Selector quantity display that differs from the expected state requires the relief pilot to select the condition when operating at a sample station without ground power.
- The Standby Hydraulic indication is expected to read within the sample range of 47 to 57 units during parking.
- The Speedbrake Handle quantity display that differs from the expected state requires the First Officer to record the condition before the next phase of flight.

NOTE: The Window Heat status message is expected to read within the sample range of 15 to 25 units during preflight. If the Cabin Pressure Controller is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance.

The Autobrake Selector indication is expected to read within the sample range of 43 to 47 units during taxi. The Hydraulic System B status message that differs from the expected state requires both pilots to confirm the condition when operating at a sample station without ground power. During engine start, the First Officer should confirm the Speedbrake Handle quantity display when operating at a sample station without ground power. The first officer will cross-check any change in the Primary Electrical Bus status message and advise the other pilot before the next phase of flight. During a diversion, the pilot flying should record the Engine Anti-Ice indication when conditions permit. If the Primary Electrical Bus is inoperative, continue a maintenance-requested ground run only after the pilot monitoring has reviewed the associated sample guidance. See 03.150.2 Airfield Notes.

01.30.6 Support Topic 6

During climb, the relief pilot should record the Nosewheel Steering switch position if the indication does not stabilize within the sample interval. The wording here is placeholder content shaped like a procedure, not a procedure. Refer to the related topic for additional sample context.

- The wording here is placeholder content shaped like a procedure, not a procedure.
- Refer to the related topic for additional sample context.
- During parking, the Captain should brief the Auxiliary Power Unit quantity display unless directed otherwise by the Sample Operations Center.
- If the Flap Position Indication is inoperative, continue landing only after the First Officer has reviewed the associated sample guidance.

Condition	Sample value	Remarks
Autothrottle quantity display	18 units	Refer to related topic
Autobrake Selector annunciation	31 units	Monitor
Fuel Crossfeed indication	38 units	Monitor
Cabin Pressure Controller annunciation	13 units	Refer to related topic
Nosewheel Steering advisory	30 units	Advisory only
Cockpit Voice Recorder indication	32 units	Advisory only

- The Cockpit Voice Recorder selector position that differs from the expected state requires the Captain to brief the condition when the associated caution light remains illuminated.
- During preflight, the pilot flying should confirm the Standby Instruments annunciation unless directed otherwise by the Sample Operations Center.
- During climb, the pilot flying should brief the Bleed Air Supply selector position once the checklist item is complete.
- Both pilots will verify any change in the Autopilot Channel A status message and advise the other pilot when the associated caution light remains illuminated.
- The Standby Hydraulic quantity display that differs from the expected state requires the pilot monitoring to confirm the condition if a discrepancy is observed.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- During a maintenance-requested ground run, the pilot flying should select the Bleed Air Supply switch position when the associated caution light remains illuminated.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The Oxygen Distribution switch position that differs from the expected state requires the relief pilot to cross-check the condition once the checklist item is complete.
- During approach, the First Officer should monitor the Autopilot Channel B indication when conditions permit.
- Values in this manual are invented and must not be used for any operational purpose.
- During landing, both pilots should brief the Transponder advisory once the checklist item is complete.

01.30.7 Support Topic 7

The Auxiliary Power Unit annunciation that differs from the expected state requires the relief pilot to select the condition when operating at a sample station without ground power. The Transponder status message that differs from the expected state requires the Captain to monitor the condition when the associated caution light remains illuminated. This text is fictional and exists only to give the prototype realistic volume and structure. The Primary

Electrical Bus annunciation that differs from the expected state requires the First Officer to announce the condition when the associated caution light remains illuminated. During climb, both pilots should verify the Primary Electrical Bus advisory when conditions permit. During takeoff, the First Officer should confirm the Weather Radar annunciation once the checklist item is complete.

NOTE: The Brake Temperature Monitor quantity display is expected to read within the sample range of 24 to 31 units during takeoff. The Transponder advisory is expected to read within the sample range of 97 to 101 units during a diversion.

The pilot monitoring will announce any change in the Wing Anti-Ice selector position and advise the other pilot when the associated caution light remains illuminated. The pilot monitoring will cross-check any change in the Nosewheel Steering selector position and advise the other pilot if the indication does not stabilize within the sample interval. The Autopilot Channel A annunciation that differs from the expected state requires the relief pilot to confirm the condition once the checklist item is complete. During preflight, the pilot monitoring should cross-check the Hydraulic System B annunciation once the checklist item is complete.

Condition	Sample value	Remarks
Oxygen Distribution status message	93 units	Monitor
Autobrake Selector advisory	9 units	Normal
Autopilot Channel B quantity display	5 units	Normal
Autopilot Channel B indication	86 units	Advisory only

The captain will announce any change in the Transponder selector position and advise the other pilot when the associated caution light remains illuminated. The wording here is placeholder content shaped like a procedure, not a procedure. If the Auxiliary Power Unit is inoperative, continue taxi only after the First Officer has reviewed the associated sample guidance.

01.30.8 Support Topic 8

The Weather Radar status message is expected to read within the sample range of 82 to 89 units during descent. If the Thrust Reverser is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance. The Thrust Reverser indication is expected to read within the sample range of 76 to 87 units during descent. The pilot flying will verify any change in the Brake Temperature Monitor status message and advise the other pilot if the indication does not stabilize within the sample interval. The relief pilot will confirm any change in the Brake Temperature Monitor switch position and advise the other pilot if the indication does not stabilize within the sample interval. During an extended ground delay, the First Officer should record the Autothrottle annunciation if a discrepancy is observed.

If the Bleed Air Supply is inoperative, continue a maintenance-requested ground run only after the pilot flying has reviewed the associated sample guidance. During engine start, the First Officer should verify the Cabin Pressure Controller status message when the associated caution light remains illuminated. If the Primary Electrical Bus is inoperative, continue a maintenance-requested ground run only after the Captain has reviewed the associated sample guidance. The captain will verify any change in the Weather Radar status message and advise the other pilot if a discrepancy is observed.

Refer to the related topic for additional sample context. If the Autopilot Channel B is inoperative, continue a maintenance-requested ground run only after the pilot flying has reviewed the associated sample guidance. The Cockpit Voice Recorder selector position is expected to read within the sample range of 44 to 49 units during taxi. During cruise, the pilot monitoring should monitor the Pack Temperature Control status message before the next phase of flight.

CAUTION: The Thrust Reverser quantity display that differs from the expected state requires the pilot monitoring to confirm the condition once the checklist item is complete. Refer to the related topic for additional sample context.

Refer to the related topic for additional sample context. The pilot monitoring will confirm any change in the Center Tank Pumps selector position and advise the other pilot before the next phase of flight. The Autobrake Selector status message is expected to read within the sample range of 90 to 99 units during landing. This text is fictional and exists only to give the prototype realistic volume and structure. The Cargo Smoke Detection quantity display that differs from the expected state requires the Captain to brief the condition if a discrepancy is observed. Refer to the related topic for additional sample context.

Chapter 02 Station Information: Region 1

02.10 Sample Station S01

02.10.1 General

The pilot monitoring will confirm any change in the Landing Gear Indication annunciation and advise the other pilot when operating at a sample station without ground power. Values in this manual are invented and must not be used for any operational purpose. Values in this manual are invented and must not be used for any operational purpose.

During a maintenance-requested ground run, both pilots should announce the Autopilot Channel B annunciation unless directed otherwise by the Sample Operations Center. Values in this manual are invented and must not be used for any operational purpose. If the Cockpit Voice Recorder is inoperative, continue approach only after both pilots has reviewed the associated sample guidance. Both pilots will confirm any change in the Center Tank Pumps selector position and advise the other pilot before the next phase of flight.

CAUTION: During preflight, the relief pilot should cross-check the Auxiliary Power Unit quantity display when conditions permit. During a maintenance-requested ground run, the Captain should select the Stall Warning selector position once the checklist item is complete.

Condition	Sample value	Remarks
Fire Detection Loop indication	6 units	Monitor
Ground Proximity Monitor indication	97 units	Monitor
Landing Gear Indication status message	17 units	Normal

CAUTION: The Speedbrake Handle indication is expected to read within the sample range of 65 to 74 units during cruise. The Flight Management Computer annunciation is expected to read within the sample range of 80 to 87 units during climb.

If the Cargo Smoke Detection is inoperative, continue descent only after the Captain has reviewed the associated sample guidance. The relief pilot will cross-check any change in the Oxygen Distribution status message and advise the other pilot once the checklist item is complete. The Ground Proximity Monitor indication is expected to read within the sample range of 73 to 78 units during climb. If the Cabin Pressure Controller is inoperative, continue taxi only after the First Officer has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. If the Cockpit Voice Recorder is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance.

NOTE: The Pack Temperature Control quantity display is expected to read within the sample range of 96 to 102 units during parking. The pilot flying will record any change in the Thrust Reverser indication and advise the other pilot unless directed otherwise by the Sample Operations Center.

CAUTION: Both pilots will announce any change in the Autobrake Selector quantity display and advise the other pilot if a discrepancy is observed.

CAUTION: The Auxiliary Power Unit switch position is expected to read within the sample range of 87 to 99 units during a diversion.

02.10.2 Airfield Notes

During climb, the pilot flying should monitor the Bleed Air Supply advisory once the checklist item is complete. The Autothrottle advisory that differs from the expected state requires the First Officer to brief the condition if the indication does not stabilize within the sample interval. The Auxiliary Power Unit quantity display that differs from the expected state requires the relief pilot to brief the condition when conditions permit. This text is fictional and exists only to give the prototype realistic volume and structure. The relief pilot will announce any change in the Probe Heat advisory and advise the other pilot if a discrepancy is observed.

- The relief pilot will select any change in the Fuel Crossfeed quantity display and advise the other pilot before the next phase of flight.
- During a diversion, the pilot flying should select the Autopilot Channel A indication when the associated caution light remains illuminated.
- If the Hydraulic System A is inoperative, continue climb only after the pilot flying has reviewed the associated sample guidance.
- If the Standby Hydraulic is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance.
- If the Ground Proximity Monitor is inoperative, continue a maintenance-requested ground run only after the Captain has reviewed the associated sample guidance.
- The relief pilot will select any change in the Hydraulic System A indication and advise the other pilot when operating at a sample station without ground power.
- Values in this manual are invented and must not be used for any operational purpose.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- This text is fictional and exists only to give the prototype realistic volume and structure.

If the Autopilot Channel B is inoperative, continue an extended ground delay only after the pilot flying has reviewed the associated sample guidance. The pilot flying will verify any change in the Cargo Smoke Detection quantity display and advise the other pilot when operating at a sample station without ground power. If the Autothrottle is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance. During descent, both pilots should confirm the Weather Radar advisory once the checklist item is complete. The Window Heat status message that differs from the expected state requires both pilots to confirm the condition when operating at a sample station without ground power.

The wording here is placeholder content shaped like a procedure, not a procedure. The Fuel Crossfeed indication is expected to read within the sample range of 4 to 7 units during landing. This text is fictional and exists only to give the prototype realistic volume and structure. During cruise, the pilot flying should record the Hydraulic System B switch position when the associated caution light remains illuminated. The Transponder indication is expected to read within the sample range of 34 to 40 units during preflight.

02.10.3 Ground Handling

The Oxygen Distribution status message that differs from the expected state requires the pilot monitoring to record the condition if a discrepancy is observed. The Nosewheel Steering indication is expected to read within the sample range of 36 to 40 units during preflight. The Cockpit Voice Recorder status message is expected to read within the sample range of 56 to 63 units during descent. During parking, both pilots should monitor the Flap Position Indication quantity display when conditions permit. If the Thrust Reverser is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance.

The Autopilot Channel A selector position is expected to read within the sample range of 89 to 101 units during preflight. During cruise, the pilot monitoring should announce the Fire Detection Loop status message if a discrepancy is observed. The Cockpit Voice Recorder selector position that differs from the expected state requires the First Officer to cross-check the condition when the associated caution light remains illuminated. Values in this manual are invented and must not be used for any operational purpose. The Transponder status message is expected to read within the sample range of 26 to 29 units during landing.

The relief pilot will cross-check any change in the Nosewheel Steering status message and advise the other pilot if a discrepancy is observed. The pilot monitoring will brief any change in the Fuel Crossfeed selector position and advise the other pilot once the checklist item is complete. The captain will verify any change in the Oxygen Distribution indication and advise the other pilot when operating at a sample station without ground power. The Ground Proximity Monitor quantity display that differs from the expected state requires the pilot flying to cross-check the condition if a

discrepancy is observed. The first officer will confirm any change in the Center Tank Pumps indication and advise the other pilot if the indication does not stabilize within the sample interval.

CAUTION: Values in this manual are invented and must not be used for any operational purpose. The wording here is placeholder content shaped like a procedure, not a procedure.

The Cabin Pressure Controller advisory that differs from the expected state requires both pilots to confirm the condition if a discrepancy is observed. The Stall Warning advisory that differs from the expected state requires the relief pilot to announce the condition when the associated caution light remains illuminated. The pilot flying will record any change in the Pack Temperature Control quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center. During taxi, both pilots should cross-check the Landing Gear Indication quantity display if a discrepancy is observed. If the Transponder is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance.

CAUTION: During a turnaround, the First Officer should cross-check the Speedbrake Handle advisory if a discrepancy is observed. During parking, the pilot flying should monitor the Hydraulic System A quantity display once the checklist item is complete.

Refer to the related topic for additional sample context. Refer to the related topic for additional sample context. The Autopilot Channel B switch position is expected to read within the sample range of 95 to 106 units during engine start. If the Thrust Reverser is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure.

- If the Pack Temperature Control is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance.
- The first officer will cross-check any change in the Cargo Smoke Detection indication and advise the other pilot when conditions permit.
- Refer to the related topic for additional sample context.
- The Autobrake Selector advisory that differs from the expected state requires both pilots to select the condition when conditions permit.

02.10.4 Local Procedures

The Bleed Air Supply switch position is expected to read within the sample range of 80 to 84 units during descent. During a turnaround, the relief pilot should select the Standby Hydraulic status message when operating at a sample station without ground power. Both pilots will record any change in the Speedbrake Handle annunciation and advise the other pilot if the indication does not stabilize within the sample interval.

NOTE: The first officer will monitor any change in the Fire Detection Loop annunciation and advise the other pilot once the checklist item is complete. During landing, both pilots should select the Transponder annunciation when the associated caution light remains illuminated.

If the Fuel Crossfeed is inoperative, continue climb only after the Captain has reviewed the associated sample guidance. Refer to the related topic for additional sample context. Refer to the related topic for additional sample context. The Autopilot Channel A switch position that differs from the expected state requires both pilots to brief the condition when conditions permit. The wording here is placeholder content shaped like a procedure, not a procedure. During a diversion, the Captain should monitor the Autothrottle status message when conditions permit.

CAUTION: During parking, the pilot monitoring should brief the Cargo Smoke Detection annunciation when the associated caution light remains illuminated.

Refer to the related topic for additional sample context. During climb, the First Officer should record the Hydraulic System A selector position unless directed otherwise by the Sample Operations Center. Values in this manual are invented and must not be used for any operational purpose. The Primary Electrical Bus quantity display that differs from the expected state requires the Captain to brief the condition before the next phase of flight.

The wording here is placeholder content shaped like a procedure, not a procedure. The relief pilot will announce any change in the Autothrottle indication and advise the other pilot if the indication does not stabilize within the sample interval. During descent, the pilot flying should announce the Window Heat status message before the next phase of flight. The Cockpit Voice Recorder indication is expected to read within the sample range of 2 to 6 units during landing. During a diversion, the pilot flying should brief the Speedbrake Handle switch position when conditions permit.

02.20 Sample Station S02

02.20.1 General

The Autopilot Channel A indication that differs from the expected state requires the pilot monitoring to monitor the condition when operating at a sample station without ground power. During an extended ground delay, the relief pilot should record the Stall Warning switch position if the indication does not stabilize within the sample interval. If the Bleed Air Supply is inoperative, continue cruise only after the Captain has reviewed the associated sample guidance.

Condition	Sample value	Remarks
Fire Detection Loop indication	21 units	Normal
Fuel Crossfeed status message	2 units	Monitor
Window Heat annunciation	69 units	Refer to related topic
Cabin Pressure Controller status message	56 units	Normal
Wing Anti-Ice indication	20 units	Monitor
Standby Instruments selector position	78 units	Advisory only
Primary Electrical Bus indication	96 units	Refer to related topic

NOTE: If the Engine Anti-Ice is inoperative, continue a maintenance-requested ground run only after the Captain has reviewed the associated sample guidance.

- The Brake Temperature Monitor quantity display that differs from the expected state requires the pilot flying to monitor the condition when conditions permit.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- Values in this manual are invented and must not be used for any operational purpose.
- The pilot monitoring will select any change in the Hydraulic System A quantity display and advise the other pilot if a discrepancy is observed.
- The Pack Temperature Control switch position that differs from the expected state requires the Captain to verify the condition when operating at a sample station without ground power.
- Values in this manual are invented and must not be used for any operational purpose.

The Brake Temperature Monitor status message that differs from the expected state requires the Captain to select the condition unless directed otherwise by the Sample Operations Center. The Autopilot Channel B advisory is expected to read within the sample range of 15 to 18 units during landing. The relief pilot will record any change in the Auxiliary Power Unit switch position and advise the other pilot unless directed otherwise by the Sample Operations Center. The Oxygen Distribution status message that differs from the expected state requires both pilots to brief the condition before the next phase of flight. The relief pilot will monitor any change in the Flap Position Indication advisory and advise the other pilot if the indication does not stabilize within the sample interval. The Cargo Smoke Detection advisory is expected to read within the sample range of 90 to 102 units during cruise.

NOTE: The relief pilot will brief any change in the Autobrake Selector indication and advise the other pilot once the checklist item is complete.

CAUTION: The Stall Warning advisory that differs from the expected state requires the relief pilot to record the condition when the associated caution light remains illuminated. The Transponder annunciation that differs from the expected state requires the Captain to verify the condition before the next phase of flight.

- During taxi, the pilot flying should monitor the Stall Warning switch position when the associated caution light remains illuminated.
- The Cabin Pressure Controller quantity display that differs from the expected state requires both pilots to verify the condition once the checklist item is complete.
- The Wing Anti-Ice selector position that differs from the expected state requires the pilot monitoring to cross-check the condition before the next phase of flight.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- The Weather Radar indication is expected to read within the sample range of 86 to 97 units during engine start.
- The Bleed Air Supply quantity display is expected to read within the sample range of 2 to 10 units during a maintenance-requested ground run.

02.20.2 Airfield Notes

The pilot flying will verify any change in the Oxygen Distribution status message and advise the other pilot before the next phase of flight. During landing, the relief pilot should announce the Weather Radar indication unless directed otherwise by the Sample Operations Center. During parking, the relief pilot should cross-check the Brake Temperature Monitor indication if a discrepancy is observed. If the Cabin Pressure Controller is inoperative, continue a maintenance-requested ground run only after both pilots has reviewed the associated sample guidance. During approach, the Captain should record the Cabin Pressure Controller advisory once the checklist item is complete. During an extended ground delay, the First Officer should monitor the Nosewheel Steering advisory if a discrepancy is observed.

Condition	Sample value	Remarks
Flight Management Computer switch position	6 units	Refer to related topic
Thrust Reverser quantity display	26 units	Advisory only
Stall Warning annunciation	47 units	Monitor
Autothrottle quantity display	6 units	Advisory only
Flap Position Indication indication	73 units	Advisory only
Probe Heat selector position	62 units	Refer to related topic
Fire Detection Loop annunciation	65 units	Advisory only

The Cargo Smoke Detection indication that differs from the expected state requires the Captain to verify the condition when the associated caution light remains illuminated. The relief pilot will announce any change in the Hydraulic System B status message and advise the other pilot when operating at a sample station without ground power. The Engine Anti-Ice status message that differs from the expected state requires the pilot flying to confirm the condition when the associated caution light remains illuminated. The pilot flying will verify any change in the Hydraulic System A selector position and advise the other pilot if a discrepancy is observed.

Condition	Sample value	Remarks
Transponder quantity display	37 units	Refer to related topic
Landing Gear Indication status message	81 units	Advisory only
Weather Radar selector position	57 units	Monitor
Oxygen Distribution selector position	77 units	Normal
Bleed Air Supply annunciation	48 units	Advisory only

CAUTION: Values in this manual are invented and must not be used for any operational purpose. During approach, the relief pilot should brief the Stall Warning quantity display when conditions permit.

CAUTION: The wording here is placeholder content shaped like a procedure, not a procedure.

NOTE: The Cargo Smoke Detection selector position is expected to read within the sample range of 95 to 98 units during cruise. Values in this manual are invented and must not be used for any operational purpose.

CAUTION: If the Center Tank Pumps is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance.

02.20.3 Ground Handling

The Standby Hydraulic quantity display that differs from the expected state requires the pilot flying to brief the condition if the indication does not stabilize within the sample interval. The pilot monitoring will cross-check any change in the Pack Temperature Control indication and advise the other pilot when the associated caution light remains illuminated. If the Cockpit Voice Recorder is inoperative, continue approach only after the Captain has reviewed the associated sample guidance. If the Nosewheel Steering is inoperative, continue parking only after both pilots has reviewed the associated sample guidance. The Wing Anti-Ice advisory is expected to read within the sample range of 42 to 50 units during a turnaround.

Condition	Sample value	Remarks
Traffic Advisory Display annunciation	24 units	Refer to related topic
Auxiliary Power Unit advisory	31 units	Advisory only
Flap Position Indication switch position	68 units	Advisory only
Landing Gear Indication indication	29 units	Refer to related topic
Stall Warning indication	92 units	Refer to related topic
Cargo Smoke Detection status message	97 units	Normal

Condition	Sample value	Remarks
Cargo Smoke Detection status message	75 units	Refer to related topic
Fire Detection Loop advisory	30 units	Advisory only
Cargo Smoke Detection selector position	83 units	Normal
Nosewheel Steering selector position	52 units	Monitor
Engine Anti-Ice indication	8 units	Normal
Standby Instruments switch position	61 units	Refer to related topic

- If the Speedbrake Handle is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance.
- During a turnaround, the First Officer should monitor the Traffic Advisory Display switch position before the next phase of flight.
- The pilot monitoring will select any change in the Ground Proximity Monitor switch position and advise the other pilot unless directed otherwise by the Sample Operations Center.

Condition	Sample value	Remarks
Transponder annunciation	65 units	Normal
Fuel Crossfeed selector position	77 units	Refer to related topic
Landing Gear Indication switch position	65 units	Normal
Autopilot Channel B advisory	11 units	Refer to related topic
Center Tank Pumps advisory	13 units	Normal

Fuel Crossfeed quantity display	98 units	Refer to related topic
Fuel Crossfeed selector position	71 units	Monitor

NOTE: The Brake Temperature Monitor quantity display is expected to read within the sample range of 40 to 44 units during climb.

Condition	Sample value	Remarks
Center Tank Pumps status message	48 units	Advisory only
Speedbrake Handle selector position	97 units	Advisory only
Cargo Smoke Detection advisory	6 units	Advisory only
Fuel Crossfeed status message	92 units	Refer to related topic

CAUTION: The Fire Detection Loop switch position is expected to read within the sample range of 67 to 79 units during a turnaround.

02.20.4 Local Procedures

The Speedbrake Handle annunciation is expected to read within the sample range of 37 to 47 units during descent. If the Autobrake Selector is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. If the Fuel Crossfeed is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance. The pilot monitoring will record any change in the Cockpit Voice Recorder advisory and advise the other pilot once the checklist item is complete.

CAUTION: The Autothrottle quantity display that differs from the expected state requires the relief pilot to select the condition when operating at a sample station without ground power.

Values in this manual are invented and must not be used for any operational purpose. The Hydraulic System A advisory is expected to read within the sample range of 97 to 100 units during descent. During an extended ground delay, the pilot monitoring should monitor the Fire Detection Loop indication before the next phase of flight. The Center Tank Pumps advisory that differs from the expected state requires the relief pilot to monitor the condition before the next phase of flight.

- The Window Heat advisory is expected to read within the sample range of 44 to 52 units during cruise.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- The Weather Radar advisory that differs from the expected state requires both pilots to select the condition if a discrepancy is observed.
- Refer to the related topic for additional sample context.
- Refer to the related topic for additional sample context.
- During engine start, the relief pilot should select the Traffic Advisory Display switch position if a discrepancy is observed.

Values in this manual are invented and must not be used for any operational purpose. If the Standby Hydraulic is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance. During parking, both pilots should brief the Flap Position Indication indication when the associated caution light remains illuminated.

The captain will brief any change in the Oxygen Distribution switch position and advise the other pilot when conditions permit. The Engine Anti-Ice status message that differs from the expected state requires the pilot monitoring to monitor the condition if the indication does not stabilize within the sample interval. During landing, the pilot flying should confirm the Landing Gear Indication switch position when operating at a sample station without ground power. Refer to the related topic for additional sample context. Refer to the related topic for additional sample context. This

text is fictional and exists only to give the prototype realistic volume and structure.

During approach, the pilot flying should confirm the Hydraulic System A switch position when the associated caution light remains illuminated. The captain will announce any change in the Cabin Pressure Controller quantity display and advise the other pilot if a discrepancy is observed. If the Wing Anti-Ice is inoperative, continue a diversion only after the relief pilot has reviewed the associated sample guidance.

CAUTION: The Landing Gear Indication quantity display that differs from the expected state requires both pilots to verify the condition if the indication does not stabilize within the sample interval. The Wing Anti-Ice switch position that differs from the expected state requires both pilots to confirm the condition if the indication does not stabilize within the sample interval.

02.30 Sample Station S03

02.30.1 General

The Probe Heat advisory is expected to read within the sample range of 10 to 16 units during preflight. During descent, both pilots should monitor the Autobrake Selector annunciation unless directed otherwise by the Sample Operations Center. During an extended ground delay, the relief pilot should cross-check the Autothrottle selector position if the indication does not stabilize within the sample interval.

Refer to the related topic for additional sample context. The wording here is placeholder content shaped like a procedure, not a procedure. If the Standby Hydraulic is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance.

CAUTION: During takeoff, both pilots should verify the Autopilot Channel B status message when the associated caution light remains illuminated.

- Refer to the related topic for additional sample context.
- Refer to the related topic for additional sample context.
- The Hydraulic System A indication that differs from the expected state requires the First Officer to select the condition if the indication does not stabilize within the sample interval.

CAUTION: The Autopilot Channel A advisory is expected to read within the sample range of 37 to 47 units during a diversion.

Condition	Sample value	Remarks
Brake Temperature Monitor switch position	96 units	Normal
Fire Detection Loop switch position	91 units	Refer to related topic
Probe Heat annunciation	90 units	Monitor
Bleed Air Supply indication	72 units	Advisory only

- The Hydraulic System B selector position that differs from the expected state requires the First Officer to record the condition before the next phase of flight.
- During taxi, both pilots should cross-check the Pack Temperature Control annunciation if the indication does not stabilize within the sample interval.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The Oxygen Distribution annunciation is expected to read within the sample range of 3 to 13 units during an extended ground delay.
- This text is fictional and exists only to give the prototype realistic volume and structure.

- The Auxiliary Power Unit quantity display that differs from the expected state requires the relief pilot to brief the condition if a discrepancy is observed.

NOTE: During cruise, the relief pilot should cross-check the Engine Anti-Ice quantity display if a discrepancy is observed.

02.30.2 *Airfield Notes*

Both pilots will brief any change in the Nosewheel Steering advisory and advise the other pilot when the associated caution light remains illuminated. The first officer will cross-check any change in the Auxiliary Power Unit advisory and advise the other pilot before the next phase of flight. During an extended ground delay, the pilot monitoring should record the Weather Radar advisory if the indication does not stabilize within the sample interval. If the Traffic Advisory Display is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance.

NOTE: Refer to the related topic for additional sample context.

- Refer to the related topic for additional sample context.
- The Pack Temperature Control quantity display that differs from the expected state requires the pilot flying to confirm the condition when the associated caution light remains illuminated.
- Values in this manual are invented and must not be used for any operational purpose.
- The Transponder selector position that differs from the expected state requires the pilot monitoring to record the condition when operating at a sample station without ground power.
- If the Cockpit Voice Recorder is inoperative, continue a diversion only after both pilots has reviewed the associated sample guidance.

CAUTION: If the Transponder is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance.

During a maintenance-requested ground run, the Captain should announce the Ground Proximity Monitor quantity display before the next phase of flight. If the Auxiliary Power Unit is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. Refer to the related topic for additional sample context. The pilot flying will confirm any change in the Oxygen Distribution selector position and advise the other pilot when conditions permit.

02.30.3 *Ground Handling*

The Thrust Reverser annunciation that differs from the expected state requires the First Officer to cross-check the condition before the next phase of flight. If the Autopilot Channel B is inoperative, continue climb only after both pilots has reviewed the associated sample guidance. If the Autobrake Selector is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance. During approach, the First Officer should monitor the Weather Radar indication unless directed otherwise by the Sample Operations Center. During cruise, the First Officer should brief the Oxygen Distribution selector position when conditions permit.

If the Standby Hydraulic is inoperative, continue takeoff only after both pilots has reviewed the associated sample guidance. Both pilots will confirm any change in the Flight Management Computer advisory and advise the other pilot once the checklist item is complete. Refer to the related topic for additional sample context. The pilot flying will monitor any change in the Hydraulic System A switch position and advise the other pilot once the checklist item is complete.

If the Fire Detection Loop is inoperative, continue taxi only after the pilot flying has reviewed the associated sample guidance. The Nosewheel Steering switch position is expected to read within the sample range of 6 to 10 units during a maintenance-requested ground run. If the Flap Position Indication is inoperative, continue takeoff only after the First Officer has reviewed the associated sample guidance.

The Hydraulic System A annunciation is expected to read within the sample range of 30 to 35 units during landing. This text is fictional and exists only to give the prototype realistic volume and structure. The Center Tank Pumps switch position is expected to read within the sample range of 74 to 82 units during engine start.

Condition	Sample value	Remarks
Oxygen Distribution quantity display	19 units	Normal
Autopilot Channel A selector position	26 units	Refer to related topic
Engine Anti-Ice switch position	65 units	Refer to related topic

NOTE: The Nosewheel Steering selector position that differs from the expected state requires the pilot monitoring to monitor the condition when the associated caution light remains illuminated. The Cargo Smoke Detection advisory is expected to read within the sample range of 30 to 38 units during landing.

02.30.4 Local Procedures

During approach, the Captain should select the Cabin Pressure Controller annunciation when operating at a sample station without ground power. If the Autopilot Channel B is inoperative, continue climb only after the relief pilot has reviewed the associated sample guidance. If the Probe Heat is inoperative, continue takeoff only after the First Officer has reviewed the associated sample guidance. If the Flap Position Indication is inoperative, continue engine start only after the relief pilot has reviewed the associated sample guidance. If the Weather Radar is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure.

NOTE: During a diversion, both pilots should announce the Standby Instruments indication unless directed otherwise by the Sample Operations Center.

- The Thrust Reverser switch position that differs from the expected state requires the pilot monitoring to confirm the condition unless directed otherwise by the Sample Operations Center.
- The captain will select any change in the Autopilot Channel A switch position and advise the other pilot before the next phase of flight.
- If the Autopilot Channel B is inoperative, continue climb only after both pilots has reviewed the associated sample guidance.
- If the Autopilot Channel A is inoperative, continue descent only after the pilot flying has reviewed the associated sample guidance.
- The Hydraulic System B quantity display that differs from the expected state requires the relief pilot to verify the condition if a discrepancy is observed.
- The wording here is placeholder content shaped like a procedure, not a procedure.

CAUTION: The relief pilot will confirm any change in the Thrust Reverser quantity display and advise the other pilot when operating at a sample station without ground power. The Engine Anti-Ice advisory is expected to read within the sample range of 61 to 68 units during an extended ground delay.

Condition	Sample value	Remarks
Autothrottle switch position	62 units	Normal
Fuel Crossfeed advisory	63 units	Normal
Standby Instruments switch position	7 units	Advisory only
Landing Gear Indication advisory	31 units	Monitor

Condition	Sample value	Remarks
Brake Temperature Monitor indication	11 units	Advisory only

Cockpit Voice Recorder indication	82 units	Advisory only
Auxiliary Power Unit advisory	6 units	Refer to related topic
Hydraulic System B selector position	46 units	Advisory only
Auxiliary Power Unit switch position	82 units	Refer to related topic
Fire Detection Loop status message	68 units	Monitor
Probe Heat annunciation	12 units	Advisory only

The pilot flying will cross-check any change in the Standby Instruments selector position and advise the other pilot before the next phase of flight. If the Standby Instruments is inoperative, continue preflight only after both pilots has reviewed the associated sample guidance. The pilot monitoring will record any change in the Autobrake Selector indication and advise the other pilot unless directed otherwise by the Sample Operations Center. Values in this manual are invented and must not be used for any operational purpose.

CAUTION: If the Nosewheel Steering is inoperative, continue taxi only after the Captain has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure.

02.40 Sample Station S04

02.40.1 General

The pilot monitoring will record any change in the Landing Gear Indication switch position and advise the other pilot when conditions permit. During takeoff, the pilot flying should cross-check the Window Heat status message when conditions permit. The captain will select any change in the Probe Heat status message and advise the other pilot when the associated caution light remains illuminated.

The Oxygen Distribution indication that differs from the expected state requires the relief pilot to brief the condition when the associated caution light remains illuminated. Values in this manual are invented and must not be used for any operational purpose. During takeoff, both pilots should verify the Cargo Smoke Detection annunciation if a discrepancy is observed. The Flap Position Indication indication is expected to read within the sample range of 35 to 42 units during approach.

CAUTION: The Cargo Smoke Detection selector position that differs from the expected state requires the Captain to select the condition when the associated caution light remains illuminated. If the Hydraulic System B is inoperative, continue landing only after the relief pilot has reviewed the associated sample guidance.

Condition	Sample value	Remarks
Autothrottle selector position	85 units	Refer to related topic
Cockpit Voice Recorder indication	37 units	Advisory only
Hydraulic System A indication	79 units	Advisory only

- If the Cockpit Voice Recorder is inoperative, continue climb only after the Captain has reviewed the associated sample guidance.
- Both pilots will brief any change in the Fuel Crossfeed selector position and advise the other pilot when the associated caution light remains illuminated.
- If the Center Tank Pumps is inoperative, continue preflight only after the pilot monitoring has reviewed the associated sample guidance.
- During climb, both pilots should select the Standby Instruments annunciation unless directed otherwise by the Sample Operations Center.
- Refer to the related topic for additional sample context.
- This text is fictional and exists only to give the prototype realistic volume and structure.

The Primary Electrical Bus selector position is expected to read within the sample range of 73 to 77 units during descent. The Window Heat selector position is expected to read within the sample range of 8 to 14 units during landing. The captain will announce any change in the Thrust Reverser quantity display and advise the other pilot once the checklist item is complete. The Auxiliary Power Unit indication is expected to read within the sample range of 19 to 27 units during taxi. During takeoff, the relief pilot should record the Primary Electrical Bus status message before the next phase of flight. Refer to the related topic for additional sample context.

CAUTION: The wording here is placeholder content shaped like a procedure, not a procedure. Both pilots will announce any change in the Fuel Crossfeed annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center.

The Nosewheel Steering annunciation that differs from the expected state requires the pilot flying to record the condition once the checklist item is complete. This text is fictional and exists only to give the prototype realistic volume and structure. The Autopilot Channel B quantity display is expected to read within the sample range of 90 to 97 units during a maintenance-requested ground run. During a turnaround, the relief pilot should monitor the Autobrake Selector switch position when operating at a sample station without ground power. The wording here is placeholder content shaped like a procedure, not a procedure.

02.40.2 Airfield Notes

If the Center Tank Pumps is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. The Flight Management Computer indication is expected to read within the sample range of 27 to 35 units during a diversion. Both pilots will verify any change in the Center Tank Pumps switch position and advise the other pilot when the associated caution light remains illuminated. During an extended ground delay, the Captain should confirm the Autobrake Selector advisory before the next phase of flight. The captain will confirm any change in the Cockpit Voice Recorder status message and advise the other pilot when conditions permit.

If the Probe Heat is inoperative, continue an extended ground delay only after the pilot flying has reviewed the associated sample guidance. Both pilots will verify any change in the Traffic Advisory Display advisory and advise the other pilot when operating at a sample station without ground power. If the Speedbrake Handle is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance. During a maintenance-requested ground run, both pilots should select the Fuel Crossfeed indication once the checklist item is complete. During climb, the pilot flying should verify the Probe Heat annunciation if a discrepancy is observed.

NOTE: Refer to the related topic for additional sample context. If the Speedbrake Handle is inoperative, continue engine start only after the pilot monitoring has reviewed the associated sample guidance.

During taxi, the pilot monitoring should verify the Speedbrake Handle annunciation if the indication does not stabilize within the sample interval. Values in this manual are invented and must not be used for any operational purpose. This text is fictional and exists only to give the prototype realistic volume and structure. The first officer will record any change in the Autobrake Selector annunciation and advise the other pilot when conditions permit.

The Standby Instruments advisory that differs from the expected state requires the relief pilot to record the condition if a discrepancy is observed. The pilot monitoring will verify any change in the Speedbrake Handle indication and advise the other pilot before the next phase of flight. Both pilots will record any change in the Stall Warning switch position and advise the other pilot unless directed otherwise by the Sample Operations Center. If the Brake Temperature Monitor is inoperative, continue engine start only after the pilot monitoring has reviewed the associated sample guidance.

02.40.3 Ground Handling

The Cargo Smoke Detection advisory that differs from the expected state requires the Captain to announce the condition before the next phase of flight. Values in this manual are invented and must not be used for any operational purpose. The Auxiliary Power Unit annunciation is expected to read within the sample range of 5 to 10 units during

approach. The Primary Electrical Bus indication that differs from the expected state requires the relief pilot to monitor the condition when the associated caution light remains illuminated.

The captain will verify any change in the Cockpit Voice Recorder quantity display and advise the other pilot once the checklist item is complete. During takeoff, the Captain should monitor the Cabin Pressure Controller status message once the checklist item is complete. During taxi, both pilots should verify the Primary Electrical Bus status message when the associated caution light remains illuminated. The Window Heat annunciation that differs from the expected state requires both pilots to select the condition once the checklist item is complete. The Standby Hydraulic indication is expected to read within the sample range of 58 to 63 units during takeoff.

During parking, both pilots should cross-check the Flap Position Indication quantity display once the checklist item is complete. If the Probe Heat is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance. During engine start, the pilot flying should brief the Landing Gear Indication switch position unless directed otherwise by the Sample Operations Center. If the Landing Gear Indication is inoperative, continue taxi only after both pilots has reviewed the associated sample guidance. The Ground Proximity Monitor advisory is expected to read within the sample range of 92 to 96 units during an extended ground delay. If the Autothrottle is inoperative, continue descent only after the First Officer has reviewed the associated sample guidance.

- During engine start, the relief pilot should confirm the Speedbrake Handle quantity display when the associated caution light remains illuminated.
- If the Primary Electrical Bus is inoperative, continue preflight only after the Captain has reviewed the associated sample guidance.
- If the Brake Temperature Monitor is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance.
- During preflight, the First Officer should confirm the Standby Instruments selector position when operating at a sample station without ground power.
- The Cargo Smoke Detection status message that differs from the expected state requires the First Officer to cross-check the condition once the checklist item is complete.
- If the Standby Hydraulic is inoperative, continue approach only after the pilot flying has reviewed the associated sample guidance.

NOTE: The Pack Temperature Control quantity display is expected to read within the sample range of 15 to 25 units during engine start. During a turnaround, the pilot flying should announce the Bleed Air Supply selector position when conditions permit.

02.40.4 Local Procedures

The relief pilot will brief any change in the Thrust Reverser selector position and advise the other pilot when conditions permit. The Weather Radar annunciation that differs from the expected state requires the pilot monitoring to cross-check the condition if the indication does not stabilize within the sample interval. The Wing Anti-Ice status message that differs from the expected state requires the First Officer to cross-check the condition when conditions permit. The Transponder quantity display that differs from the expected state requires both pilots to confirm the condition if a discrepancy is observed.

The Autothrottle status message is expected to read within the sample range of 54 to 61 units during preflight. The Hydraulic System B switch position is expected to read within the sample range of 32 to 42 units during cruise. The relief pilot will verify any change in the Center Tank Pumps status message and advise the other pilot once the checklist item is complete. During landing, the pilot monitoring should cross-check the Auxiliary Power Unit status message if a discrepancy is observed. The wording here is placeholder content shaped like a procedure, not a procedure. Refer to the related topic for additional sample context.

NOTE: If the Autopilot Channel B is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance. If the Fire Detection Loop is inoperative, continue parking only after the Captain has reviewed the associated sample guidance.

The Fuel Crossfeed annunciation is expected to read within the sample range of 8 to 11 units during landing. The wording here is placeholder content shaped like a procedure, not a procedure. If the Cockpit Voice Recorder is inoperative, continue cruise only after the First Officer has reviewed the associated sample guidance. The Autothrottle switch position is expected to read within the sample range of 95 to 99 units during engine start. The Weather Radar annunciation that differs from the expected state requires the pilot monitoring to select the condition before the next phase of flight. Values in this manual are invented and must not be used for any operational purpose.

Condition	Sample value	Remarks
Weather Radar selector position	64 units	Advisory only
Hydraulic System B indication	33 units	Advisory only
Hydraulic System B status message	46 units	Advisory only

The Autothrottle status message is expected to read within the sample range of 29 to 34 units during an extended ground delay. If the Speedbrake Handle is inoperative, continue landing only after the Captain has reviewed the associated sample guidance. The Standby Hydraulic selector position is expected to read within the sample range of 2 to 5 units during takeoff. The Nosewheel Steering advisory that differs from the expected state requires the pilot flying to brief the condition when conditions permit. The Cabin Pressure Controller selector position that differs from the expected state requires the pilot flying to record the condition if a discrepancy is observed.

CAUTION: If the Cabin Pressure Controller is inoperative, continue engine start only after the Captain has reviewed the associated sample guidance. The Pack Temperature Control selector position is expected to read within the sample range of 36 to 40 units during a maintenance-requested ground run.

Refer to the related topic for additional sample context. The relief pilot will verify any change in the Primary Electrical Bus indication and advise the other pilot when operating at a sample station without ground power. The pilot flying will monitor any change in the Fire Detection Loop status message and advise the other pilot once the checklist item is complete.

02.50 Sample Station S05

02.50.1 General

This text is fictional and exists only to give the prototype realistic volume and structure. Refer to the related topic for additional sample context. Both pilots will verify any change in the Hydraulic System B annunciation and advise the other pilot if a discrepancy is observed. The Center Tank Pumps quantity display that differs from the expected state requires the pilot flying to confirm the condition before the next phase of flight. During preflight, the relief pilot should cross-check the Landing Gear Indication switch position unless directed otherwise by the Sample Operations Center.

- If the Ground Proximity Monitor is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance.
- If the Nosewheel Steering is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance.
- Values in this manual are invented and must not be used for any operational purpose.
- During preflight, the Captain should select the Standby Hydraulic selector position unless directed otherwise by the Sample Operations Center.

The Standby Instruments status message is expected to read within the sample range of 33 to 37 units during descent. The Fuel Crossfeed selector position that differs from the expected state requires the Captain to select the condition when conditions permit. The Probe Heat indication is expected to read within the sample range of 42 to 48

units during descent. If the Probe Heat is inoperative, continue a turnaround only after both pilots has reviewed the associated sample guidance. The Stall Warning selector position that differs from the expected state requires the pilot flying to brief the condition if a discrepancy is observed. The pilot flying will monitor any change in the Fire Detection Loop indication and advise the other pilot once the checklist item is complete.

Condition	Sample value	Remarks
Center Tank Pumps selector position	40 units	Normal
Cockpit Voice Recorder switch position	78 units	Monitor
Landing Gear Indication quantity display	11 units	Normal

NOTE: The Ground Proximity Monitor annunciation that differs from the expected state requires the pilot monitoring to verify the condition if the indication does not stabilize within the sample interval. During a diversion, both pilots should cross-check the Standby Hydraulic annunciation when operating at a sample station without ground power.

During descent, both pilots should cross-check the Weather Radar indication when conditions permit. The Oxygen Distribution annunciation is expected to read within the sample range of 26 to 35 units during landing. The captain will brief any change in the Ground Proximity Monitor indication and advise the other pilot before the next phase of flight. If the Autobrake Selector is inoperative, continue descent only after the First Officer has reviewed the associated sample guidance.

02.50.2 Airfield Notes

If the Hydraulic System A is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance. The Speedbrake Handle annunciation that differs from the expected state requires both pilots to confirm the condition if the indication does not stabilize within the sample interval. This text is fictional and exists only to give the prototype realistic volume and structure.

Condition	Sample value	Remarks
Autothrottle status message	99 units	Refer to related topic
Flap Position Indication annunciation	65 units	Advisory only
Flap Position Indication quantity display	18 units	Monitor

The Auxiliary Power Unit switch position that differs from the expected state requires the relief pilot to monitor the condition if the indication does not stabilize within the sample interval. The relief pilot will announce any change in the Wing Anti-Ice indication and advise the other pilot once the checklist item is complete. If the Fire Detection Loop is inoperative, continue a diversion only after the First Officer has reviewed the associated sample guidance. If the Bleed Air Supply is inoperative, continue approach only after the First Officer has reviewed the associated sample guidance. During preflight, both pilots should monitor the Weather Radar advisory when conditions permit.

CAUTION: Values in this manual are invented and must not be used for any operational purpose. The captain will announce any change in the Stall Warning quantity display and advise the other pilot when the associated caution light remains illuminated.

During an extended ground delay, the pilot monitoring should select the Ground Proximity Monitor annunciation once the checklist item is complete. During taxi, the Captain should verify the Flap Position Indication advisory if the indication does not stabilize within the sample interval. The relief pilot will cross-check any change in the Wing Anti-Ice indication and advise the other pilot once the checklist item is complete. The Autobrake Selector annunciation that differs from the expected state requires both pilots to verify the condition if the indication does not stabilize within the sample interval.

The pilot monitoring will announce any change in the Nosewheel Steering annunciation and advise the other pilot if the indication does not stabilize within the sample interval. During approach, the pilot monitoring should confirm the Fire Detection Loop annunciation when operating at a sample station without ground power. The Weather Radar

selector position that differs from the expected state requires the relief pilot to confirm the condition if a discrepancy is observed. If the Flight Management Computer is inoperative, continue a maintenance-requested ground run only after the pilot flying has reviewed the associated sample guidance.

Condition	Sample value	Remarks
Primary Electrical Bus advisory	69 units	Advisory only
Cabin Pressure Controller indication	43 units	Monitor
Speedbrake Handle selector position	17 units	Normal

NOTE: The Pack Temperature Control advisory is expected to read within the sample range of 58 to 65 units during parking.

If the Speedbrake Handle is inoperative, continue landing only after the pilot monitoring has reviewed the associated sample guidance. The Auxiliary Power Unit quantity display that differs from the expected state requires the relief pilot to record the condition before the next phase of flight. The Fuel Crossfeed quantity display that differs from the expected state requires the relief pilot to record the condition unless directed otherwise by the Sample Operations Center. If the Brake Temperature Monitor is inoperative, continue landing only after the relief pilot has reviewed the associated sample guidance. Refer to the related topic for additional sample context.

02.50.3 Ground Handling

If the Primary Electrical Bus is inoperative, continue climb only after the relief pilot has reviewed the associated sample guidance. During cruise, the First Officer should cross-check the Ground Proximity Monitor selector position if a discrepancy is observed. If the Standby Hydraulic is inoperative, continue climb only after the Captain has reviewed the associated sample guidance. If the Ground Proximity Monitor is inoperative, continue a maintenance-requested ground run only after the pilot flying has reviewed the associated sample guidance. The Auxiliary Power Unit quantity display that differs from the expected state requires the Captain to confirm the condition if the indication does not stabilize within the sample interval. The relief pilot will monitor any change in the Traffic Advisory Display switch position and advise the other pilot when operating at a sample station without ground power.

CAUTION: During takeoff, both pilots should brief the Hydraulic System B switch position if a discrepancy is observed.

Condition	Sample value	Remarks
Ground Proximity Monitor status message	99 units	Refer to related topic
Wing Anti-Ice advisory	62 units	Refer to related topic
Cargo Smoke Detection switch position	15 units	Monitor
Fuel Crossfeed quantity display	38 units	Monitor

Both pilots will select any change in the Autobrake Selector status message and advise the other pilot when operating at a sample station without ground power. During taxi, the First Officer should cross-check the Autopilot Channel A selector position when operating at a sample station without ground power. During approach, the Captain should cross-check the Probe Heat status message if a discrepancy is observed. The Hydraulic System A annunciation that differs from the expected state requires the First Officer to select the condition when the associated caution light remains illuminated.

Condition	Sample value	Remarks
Fire Detection Loop quantity display	94 units	Advisory only
Standby Instruments switch position	81 units	Advisory only
Stall Warning selector position	96 units	Normal
Primary Electrical Bus selector position	57 units	Monitor
Landing Gear Indication selector position	88 units	Advisory only

Condition	Sample value	Remarks
Transponder advisory	6 units	Refer to related topic
Cockpit Voice Recorder status message	31 units	Advisory only
Probe Heat selector position	7 units	Monitor
Weather Radar quantity display	17 units	Refer to related topic
Cargo Smoke Detection advisory	69 units	Refer to related topic

The Wing Anti-Ice selector position that differs from the expected state requires the First Officer to verify the condition before the next phase of flight. The Window Heat switch position is expected to read within the sample range of 45 to 51 units during an extended ground delay. The Landing Gear Indication annunciation that differs from the expected state requires the relief pilot to select the condition once the checklist item is complete. During approach, the Captain should select the Flap Position Indication quantity display unless directed otherwise by the Sample Operations Center. The Ground Proximity Monitor quantity display that differs from the expected state requires the pilot flying to select the condition when the associated caution light remains illuminated.

The pilot flying will verify any change in the Standby Instruments selector position and advise the other pilot before the next phase of flight. The pilot monitoring will select any change in the Standby Hydraulic indication and advise the other pilot unless directed otherwise by the Sample Operations Center. If the Fire Detection Loop is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance. The Cabin Pressure Controller indication is expected to read within the sample range of 70 to 74 units during a maintenance-requested ground run. The pilot flying will announce any change in the Primary Electrical Bus indication and advise the other pilot when the associated caution light remains illuminated. During landing, both pilots should brief the Hydraulic System A indication when conditions permit.

02.50.4 Local Procedures

The pilot monitoring will brief any change in the Fire Detection Loop indication and advise the other pilot once the checklist item is complete. The pilot monitoring will select any change in the Autothrottle advisory and advise the other pilot when operating at a sample station without ground power. If the Traffic Advisory Display is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance.

CAUTION: If the Cockpit Voice Recorder is inoperative, continue taxi only after the First Officer has reviewed the associated sample guidance.

The Cabin Pressure Controller quantity display is expected to read within the sample range of 34 to 45 units during a diversion. The Hydraulic System A selector position that differs from the expected state requires both pilots to monitor the condition when the associated caution light remains illuminated. If the Landing Gear Indication is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure.

The pilot monitoring will monitor any change in the Oxygen Distribution quantity display and advise the other pilot when conditions permit. During climb, the pilot flying should cross-check the Flight Management Computer quantity display unless directed otherwise by the Sample Operations Center. The Wing Anti-Ice status message is expected to read within the sample range of 23 to 34 units during preflight. During engine start, the First Officer should confirm the Hydraulic System A annunciation before the next phase of flight. During a maintenance-requested ground run, the Captain should select the Stall Warning switch position if a discrepancy is observed. The Standby Instruments selector position that differs from the expected state requires the Captain to announce the condition if the indication does not stabilize within the sample interval.

CAUTION: The Speedbrake Handle indication that differs from the expected state requires the Captain to cross-check the condition before the next phase of flight.

CAUTION: The Probe Heat annunciation is expected to read within the sample range of 48 to 52 units during parking.

The Autopilot Channel B selector position is expected to read within the sample range of 6 to 13 units during engine start. During descent, the pilot monitoring should confirm the Autopilot Channel A advisory when the associated caution light remains illuminated. The pilot flying will cross-check any change in the Center Tank Pumps selector position and advise the other pilot when operating at a sample station without ground power. Both pilots will brief any change in the Engine Anti-Ice annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center. This text is fictional and exists only to give the prototype realistic volume and structure. The Hydraulic System A selector position that differs from the expected state requires the First Officer to cross-check the condition unless directed otherwise by the Sample Operations Center.

During takeoff, the pilot monitoring should cross-check the Primary Electrical Bus switch position when operating at a sample station without ground power. If the Primary Electrical Bus is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance. If the Auxiliary Power Unit is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance. The Probe Heat status message is expected to read within the sample range of 2 to 8 units during taxi. During engine start, the First Officer should verify the Engine Anti-Ice advisory unless directed otherwise by the Sample Operations Center. The Flap Position Indication status message that differs from the expected state requires the pilot flying to cross-check the condition when conditions permit.

This text is fictional and exists only to give the prototype realistic volume and structure. If the Autobrake Selector is inoperative, continue approach only after the Captain has reviewed the associated sample guidance. The Autothrottle advisory is expected to read within the sample range of 89 to 95 units during an extended ground delay. The Landing Gear Indication status message is expected to read within the sample range of 91 to 100 units during takeoff. The first officer will cross-check any change in the Flap Position Indication selector position and advise the other pilot when conditions permit. The relief pilot will verify any change in the Fire Detection Loop switch position and advise the other pilot when operating at a sample station without ground power. See 03.70.4 Local Procedures.

02.60 Sample Station S06

02.60.1 General

The Autopilot Channel A indication is expected to read within the sample range of 87 to 95 units during taxi. If the Wing Anti-Ice is inoperative, continue landing only after both pilots has reviewed the associated sample guidance. During an extended ground delay, the relief pilot should monitor the Window Heat selector position when operating at a sample station without ground power.

CAUTION: The Hydraulic System A status message that differs from the expected state requires the First Officer to brief the condition when conditions permit.

CAUTION: The Autopilot Channel B advisory that differs from the expected state requires the Captain to brief the condition when conditions permit.

During taxi, the relief pilot should record the Primary Electrical Bus quantity display when the associated caution light remains illuminated. The Traffic Advisory Display quantity display that differs from the expected state requires both pilots to verify the condition when conditions permit. During approach, the pilot flying should confirm the Cabin Pressure Controller indication when conditions permit. Both pilots will brief any change in the Nosewheel Steering annunciation and advise the other pilot when operating at a sample station without ground power. During climb, the pilot monitoring should announce the Probe Heat annunciation unless directed otherwise by the Sample Operations Center. During landing, the pilot flying should monitor the Weather Radar advisory once the checklist item is complete.

Refer to the related topic for additional sample context. During preflight, the pilot monitoring should select the Ground Proximity Monitor status message once the checklist item is complete. The Stall Warning annunciation that differs from the expected state requires the First Officer to record the condition before the next phase of flight.

The Standby Instruments switch position that differs from the expected state requires the Captain to announce the condition when operating at a sample station without ground power. If the Cockpit Voice Recorder is inoperative,

continue climb only after both pilots has reviewed the associated sample guidance. The Transponder advisory that differs from the expected state requires the Captain to monitor the condition when operating at a sample station without ground power. The Bleed Air Supply quantity display that differs from the expected state requires the First Officer to announce the condition if a discrepancy is observed. During an extended ground delay, the Captain should monitor the Center Tank Pumps advisory if a discrepancy is observed. During preflight, the pilot monitoring should monitor the Weather Radar switch position if a discrepancy is observed.

NOTE: The Hydraulic System B selector position that differs from the expected state requires the First Officer to cross-check the condition when the associated caution light remains illuminated.

02.60.2 Airfield Notes

The Landing Gear Indication advisory is expected to read within the sample range of 8 to 16 units during a maintenance-requested ground run. The Pack Temperature Control selector position is expected to read within the sample range of 90 to 101 units during takeoff. The Brake Temperature Monitor advisory that differs from the expected state requires both pilots to select the condition once the checklist item is complete.

NOTE: The Window Heat quantity display that differs from the expected state requires the pilot monitoring to verify the condition if a discrepancy is observed.

The Autobrake Selector selector position is expected to read within the sample range of 95 to 99 units during taxi. The Pack Temperature Control advisory is expected to read within the sample range of 53 to 60 units during taxi. The Traffic Advisory Display switch position that differs from the expected state requires the pilot flying to brief the condition if a discrepancy is observed. The Fuel Crossfeed quantity display is expected to read within the sample range of 22 to 34 units during taxi. The Transponder status message is expected to read within the sample range of 98 to 103 units during landing.

The Standby Instruments switch position is expected to read within the sample range of 88 to 91 units during a diversion. During an extended ground delay, the First Officer should select the Ground Proximity Monitor quantity display when conditions permit. During climb, the relief pilot should verify the Wing Anti-Ice switch position if the indication does not stabilize within the sample interval. The pilot monitoring will verify any change in the Autobrake Selector status message and advise the other pilot when the associated caution light remains illuminated. If the Ground Proximity Monitor is inoperative, continue climb only after the Captain has reviewed the associated sample guidance. If the Wing Anti-Ice is inoperative, continue taxi only after the pilot flying has reviewed the associated sample guidance. See 02.130.1 General.

CAUTION: The first officer will brief any change in the Standby Instruments quantity display and advise the other pilot before the next phase of flight.

NOTE: The Hydraulic System B annunciation is expected to read within the sample range of 55 to 59 units during climb. If the Oxygen Distribution is inoperative, continue engine start only after the pilot flying has reviewed the associated sample guidance.

NOTE: During climb, the First Officer should record the Landing Gear Indication selector position if the indication does not stabilize within the sample interval. During cruise, the Captain should confirm the Ground Proximity Monitor quantity display once the checklist item is complete.

- During an extended ground delay, the relief pilot should monitor the Autothrottle advisory unless directed otherwise by the Sample Operations Center.
- During preflight, the relief pilot should brief the Standby Instruments annunciation once the checklist item is complete.
- The Auxiliary Power Unit status message is expected to read within the sample range of 79 to 84 units during a turnaround.
- The Stall Warning switch position that differs from the expected state requires the pilot flying to record the condition if a discrepancy is observed.

- The Autothrottle status message that differs from the expected state requires the pilot monitoring to record the condition once the checklist item is complete.
- If the Cockpit Voice Recorder is inoperative, continue engine start only after the relief pilot has reviewed the associated sample guidance.

CAUTION: The pilot monitoring will select any change in the Transponder annunciation and advise the other pilot when the associated caution light remains illuminated.

02.60.3 Ground Handling

The Engine Anti-Ice selector position is expected to read within the sample range of 41 to 53 units during cruise. During preflight, both pilots should brief the Oxygen Distribution annunciation if the indication does not stabilize within the sample interval. The Flap Position Indication switch position that differs from the expected state requires the Captain to brief the condition before the next phase of flight. The wording here is placeholder content shaped like a procedure, not a procedure. If the Landing Gear Indication is inoperative, continue preflight only after the Captain has reviewed the associated sample guidance. If the Cargo Smoke Detection is inoperative, continue parking only after the pilot monitoring has reviewed the associated sample guidance.

CAUTION: The first officer will brief any change in the Fire Detection Loop advisory and advise the other pilot if the indication does not stabilize within the sample interval. The pilot monitoring will announce any change in the Hydraulic System B advisory and advise the other pilot before the next phase of flight.

The Fire Detection Loop quantity display is expected to read within the sample range of 28 to 32 units during cruise. The relief pilot will announce any change in the Autothrottle annunciation and advise the other pilot if the indication does not stabilize within the sample interval. The captain will record any change in the Hydraulic System B advisory and advise the other pilot if a discrepancy is observed. See 02.140.2 Airfield Notes.

Condition	Sample value	Remarks
Weather Radar annunciation	3 units	Normal
Oxygen Distribution indication	25 units	Monitor
Landing Gear Indication indication	74 units	Advisory only
Bleed Air Supply indication	57 units	Advisory only
Nosewheel Steering switch position	48 units	Monitor

Condition	Sample value	Remarks
Ground Proximity Monitor status message	14 units	Normal
Center Tank Pumps status message	96 units	Normal
Fire Detection Loop annunciation	27 units	Refer to related topic

02.60.4 Local Procedures

If the Window Heat is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance. The Window Heat status message is expected to read within the sample range of 79 to 90 units during an extended ground delay. If the Nosewheel Steering is inoperative, continue approach only after the relief pilot has reviewed the associated sample guidance. If the Cabin Pressure Controller is inoperative, continue landing only after both pilots has reviewed the associated sample guidance. Both pilots will confirm any change in the Standby Hydraulic status message and advise the other pilot when operating at a sample station without ground power.

NOTE: During climb, the pilot monitoring should brief the Cockpit Voice Recorder selector position when operating at a sample station without ground power.

CAUTION: Refer to the related topic for additional sample context.

During a maintenance-requested ground run, the pilot monitoring should verify the Autopilot Channel A indication if a discrepancy is observed. The Stall Warning advisory that differs from the expected state requires the Captain to announce the condition when the associated caution light remains illuminated. The Wing Anti-Ice advisory is expected to read within the sample range of 54 to 61 units during parking. During preflight, the relief pilot should select the Hydraulic System B switch position when the associated caution light remains illuminated. During an extended ground delay, the pilot monitoring should announce the Fire Detection Loop status message once the checklist item is complete.

- The pilot flying will select any change in the Traffic Advisory Display indication and advise the other pilot before the next phase of flight.
- The Brake Temperature Monitor selector position that differs from the expected state requires the First Officer to select the condition when the associated caution light remains illuminated.
- Values in this manual are invented and must not be used for any operational purpose.
- The Traffic Advisory Display switch position that differs from the expected state requires both pilots to cross-check the condition when operating at a sample station without ground power.
- If the Landing Gear Indication is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance.

02.70 Sample Station S07

02.70.1 General

If the Hydraulic System B is inoperative, continue landing only after the relief pilot has reviewed the associated sample guidance. The Brake Temperature Monitor quantity display is expected to read within the sample range of 10 to 16 units during taxi. The Bleed Air Supply switch position that differs from the expected state requires the First Officer to verify the condition when operating at a sample station without ground power. The Weather Radar advisory is expected to read within the sample range of 74 to 83 units during a maintenance-requested ground run.

The Autopilot Channel A quantity display that differs from the expected state requires the pilot flying to announce the condition when conditions permit. The Oxygen Distribution annunciation is expected to read within the sample range of 58 to 67 units during a diversion. Both pilots will monitor any change in the Brake Temperature Monitor annunciation and advise the other pilot when the associated caution light remains illuminated.

- The pilot flying will brief any change in the Flight Management Computer indication and advise the other pilot when operating at a sample station without ground power.
- If the Thrust Reverser is inoperative, continue approach only after the pilot flying has reviewed the associated sample guidance.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The Landing Gear Indication quantity display is expected to read within the sample range of 28 to 38 units during landing.
- During an extended ground delay, both pilots should confirm the Cabin Pressure Controller indication when conditions permit.

Condition	Sample value	Remarks
Autopilot Channel B switch position	4 units	Monitor
Stall Warning quantity display	9 units	Refer to related topic
Traffic Advisory Display status message	61 units	Refer to related topic
Fire Detection Loop advisory	9 units	Advisory only

During a diversion, the relief pilot should announce the Thrust Reverser advisory unless directed otherwise by the Sample Operations Center. This text is fictional and exists only to give the prototype realistic volume and structure. The Weather Radar status message is expected to read within the sample range of 31 to 41 units during a maintenance-requested ground run.

The Transponder selector position that differs from the expected state requires the pilot flying to verify the condition when conditions permit. The Oxygen Distribution annunciation that differs from the expected state requires the relief pilot to select the condition if a discrepancy is observed. The Standby Instruments quantity display that differs from the expected state requires the relief pilot to cross-check the condition unless directed otherwise by the Sample Operations Center.

CAUTION: During a turnaround, the Captain should announce the Flap Position Indication quantity display if the indication does not stabilize within the sample interval.

CAUTION: During cruise, the Captain should announce the Autopilot Channel A status message when conditions permit. If the Probe Heat is inoperative, continue parking only after the pilot monitoring has reviewed the associated sample guidance.

If the Transponder is inoperative, continue climb only after the First Officer has reviewed the associated sample guidance. The Autothrottle advisory that differs from the expected state requires both pilots to record the condition when operating at a sample station without ground power. The Speedbrake Handle selector position that differs from the expected state requires both pilots to verify the condition when operating at a sample station without ground power. During takeoff, the First Officer should select the Center Tank Pumps advisory if the indication does not stabilize within the sample interval.

02.70.2 Airfield Notes

The first officer will confirm any change in the Center Tank Pumps selector position and advise the other pilot unless directed otherwise by the Sample Operations Center. The Stall Warning status message is expected to read within the sample range of 63 to 68 units during a maintenance-requested ground run. Values in this manual are invented and must not be used for any operational purpose. If the Fuel Crossfeed is inoperative, continue cruise only after the Captain has reviewed the associated sample guidance. During landing, the pilot monitoring should brief the Standby Instruments switch position if the indication does not stabilize within the sample interval.

NOTE: The Cabin Pressure Controller annunciation that differs from the expected state requires the Captain to confirm the condition unless directed otherwise by the Sample Operations Center.

The wording here is placeholder content shaped like a procedure, not a procedure. The Hydraulic System A quantity display is expected to read within the sample range of 12 to 23 units during a maintenance-requested ground run. The wording here is placeholder content shaped like a procedure, not a procedure. The wording here is placeholder content shaped like a procedure, not a procedure. The Ground Proximity Monitor advisory is expected to read within the sample range of 38 to 46 units during takeoff.

If the Fuel Crossfeed is inoperative, continue an extended ground delay only after the pilot flying has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. Values in this manual are invented and must not be used for any operational purpose. The pilot flying will cross-check any change in the Auxiliary Power Unit selector position and advise the other pilot if a discrepancy is observed.

NOTE: If the Weather Radar is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance. If the Flap Position Indication is inoperative, continue engine start only after both pilots has reviewed the associated sample guidance.

Condition	Sample value	Remarks
Traffic Advisory Display annunciation	5 units	Refer to related topic
Fuel Crossfeed advisory	18 units	Monitor
Engine Anti-Ice selector position	80 units	Refer to related topic

Brake Temperature Monitor switch position	52 units	Advisory only
Landing Gear Indication quantity display	46 units	Normal

The Ground Proximity Monitor status message that differs from the expected state requires both pilots to brief the condition before the next phase of flight. The Hydraulic System B indication is expected to read within the sample range of 53 to 61 units during approach. If the Window Heat is inoperative, continue a turnaround only after the First Officer has reviewed the associated sample guidance. Refer to the related topic for additional sample context.

02.70.3 Ground Handling

During a turnaround, the Captain should brief the Stall Warning annunciation when the associated caution light remains illuminated. If the Primary Electrical Bus is inoperative, continue descent only after the First Officer has reviewed the associated sample guidance. If the Autothrottle is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. During takeoff, the Captain should monitor the Cockpit Voice Recorder quantity display when conditions permit. The Cockpit Voice Recorder annunciation is expected to read within the sample range of 90 to 98 units during landing.

Condition	Sample value	Remarks
Thrust Reverser annunciation	94 units	Monitor
Autothrottle selector position	47 units	Monitor
Nosewheel Steering quantity display	82 units	Refer to related topic
Window Heat status message	5 units	Normal

If the Flap Position Indication is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance. The Bleed Air Supply quantity display is expected to read within the sample range of 74 to 81 units during cruise. Refer to the related topic for additional sample context. The first officer will confirm any change in the Window Heat annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center. The Nosewheel Steering switch position that differs from the expected state requires the Captain to brief the condition if the indication does not stabilize within the sample interval. During taxi, both pilots should monitor the Flap Position Indication quantity display once the checklist item is complete.

- The Center Tank Pumps annunciation that differs from the expected state requires the Captain to confirm the condition when operating at a sample station without ground power.
- If the Hydraulic System B is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance.
- The pilot flying will cross-check any change in the Weather Radar quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center.
- The relief pilot will monitor any change in the Fire Detection Loop advisory and advise the other pilot if the indication does not stabilize within the sample interval.
- The Flight Management Computer annunciation that differs from the expected state requires the pilot monitoring to brief the condition when operating at a sample station without ground power.

NOTE: The wording here is placeholder content shaped like a procedure, not a procedure. The Primary Electrical Bus switch position is expected to read within the sample range of 42 to 51 units during takeoff.

CAUTION: Values in this manual are invented and must not be used for any operational purpose. The relief pilot will select any change in the Fire Detection Loop annunciation and advise the other pilot when conditions permit.

02.70.4 Local Procedures

The relief pilot will brief any change in the Standby Instruments indication and advise the other pilot when the associated caution light remains illuminated. The Brake Temperature Monitor switch position is expected to read within the sample range of 86 to 97 units during a turnaround. The Probe Heat switch position is expected to read within the sample range of 48 to 57 units during a maintenance-requested ground run.

The Autopilot Channel A selector position that differs from the expected state requires both pilots to cross-check the condition unless directed otherwise by the Sample Operations Center. The relief pilot will monitor any change in the Ground Proximity Monitor switch position and advise the other pilot when operating at a sample station without ground power. The Pack Temperature Control quantity display that differs from the expected state requires the pilot monitoring to cross-check the condition unless directed otherwise by the Sample Operations Center. During taxi, the Captain should announce the Brake Temperature Monitor advisory if the indication does not stabilize within the sample interval.

- Both pilots will monitor any change in the Probe Heat advisory and advise the other pilot if a discrepancy is observed.
- If the Auxiliary Power Unit is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance.
- During engine start, the Captain should verify the Flap Position Indication status message before the next phase of flight.

Condition	Sample value	Remarks
Flap Position Indication switch position	51 units	Advisory only
Flight Management Computer selector position	24 units	Advisory only
Stall Warning indication	16 units	Refer to related topic
Transponder status message	90 units	Advisory only
Cockpit Voice Recorder quantity display	74 units	Normal
Transponder status message	81 units	Refer to related topic

Condition	Sample value	Remarks
Oxygen Distribution annunciation	64 units	Normal
Autothrottle quantity display	1 units	Advisory only
Ground Proximity Monitor selector position	25 units	Refer to related topic
Autopilot Channel A quantity display	94 units	Normal

- During a diversion, the First Officer should record the Autopilot Channel B annunciation when conditions permit.
- During approach, both pilots should verify the Autothrottle quantity display if the indication does not stabilize within the sample interval.
- The Window Heat indication is expected to read within the sample range of 69 to 76 units during a diversion.
- If the Brake Temperature Monitor is inoperative, continue descent only after both pilots has reviewed the associated sample guidance.
- During cruise, both pilots should record the Nosewheel Steering status message if a discrepancy is observed.
- Values in this manual are invented and must not be used for any operational purpose.

During taxi, the pilot flying should brief the Auxiliary Power Unit switch position if the indication does not stabilize within the sample interval. Refer to the related topic for additional sample context. The wording here is placeholder content shaped like a procedure, not a procedure. If the Weather Radar is inoperative, continue a diversion only after the relief pilot has reviewed the associated sample guidance. During takeoff, the Captain should record the Cabin Pressure Controller indication if a discrepancy is observed. If the Traffic Advisory Display is inoperative, continue

cruise only after the First Officer has reviewed the associated sample guidance. See 03.100.1 General.

02.80 Sample Station S08

02.80.1 General

Values in this manual are invented and must not be used for any operational purpose. The relief pilot will confirm any change in the Hydraulic System B status message and advise the other pilot unless directed otherwise by the Sample Operations Center. If the Cockpit Voice Recorder is inoperative, continue cruise only after both pilots has reviewed the associated sample guidance. The relief pilot will announce any change in the Standby Hydraulic quantity display and advise the other pilot before the next phase of flight. Both pilots will announce any change in the Primary Electrical Bus status message and advise the other pilot when the associated caution light remains illuminated. Both pilots will monitor any change in the Oxygen Distribution quantity display and advise the other pilot before the next phase of flight.

Condition	Sample value	Remarks
Auxiliary Power Unit status message	45 units	Advisory only
Standby Instruments selector position	77 units	Monitor
Autobrake Selector indication	57 units	Refer to related topic
Pack Temperature Control quantity display	36 units	Normal

Condition	Sample value	Remarks
Hydraulic System A quantity display	85 units	Monitor
Standby Instruments status message	99 units	Normal
Autopilot Channel A annunciation	9 units	Normal

The Flap Position Indication indication is expected to read within the sample range of 48 to 52 units during preflight. The Traffic Advisory Display switch position is expected to read within the sample range of 59 to 62 units during climb. If the Flap Position Indication is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance.

Condition	Sample value	Remarks
Landing Gear Indication switch position	63 units	Refer to related topic
Autopilot Channel A advisory	35 units	Monitor
Auxiliary Power Unit selector position	63 units	Monitor
Ground Proximity Monitor selector position	98 units	Normal
Flap Position Indication quantity display	69 units	Monitor

During taxi, the relief pilot should select the Cabin Pressure Controller annunciation unless directed otherwise by the Sample Operations Center. The wording here is placeholder content shaped like a procedure, not a procedure. This text is fictional and exists only to give the prototype realistic volume and structure. Values in this manual are invented and must not be used for any operational purpose.

CAUTION: During a maintenance-requested ground run, the First Officer should confirm the Speedbrake Handle advisory if the indication does not stabilize within the sample interval.

This text is fictional and exists only to give the prototype realistic volume and structure. During takeoff, the pilot flying should brief the Pack Temperature Control advisory if the indication does not stabilize within the sample interval. If the Window Heat is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance.

02.80.2 Airfield Notes

The Thrust Reverser switch position is expected to read within the sample range of 47 to 54 units during a diversion. The Flight Management Computer annunciation is expected to read within the sample range of 61 to 68 units during takeoff. If the Ground Proximity Monitor is inoperative, continue approach only after the relief pilot has reviewed the associated sample guidance. The pilot flying will verify any change in the Landing Gear Indication annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center. This text is fictional and exists only to give the prototype realistic volume and structure. If the Fire Detection Loop is inoperative, continue climb only after the Captain has reviewed the associated sample guidance.

- CAUTION:** The Center Tank Pumps indication is expected to read within the sample range of 87 to 94 units during an extended ground delay. If the Standby Instruments is inoperative, continue takeoff only after the First Officer has reviewed the associated sample guidance.

NOTE: The Speedbrake Handle switch position that differs from the expected state requires the First Officer to select the condition once the checklist item is complete. The Standby Hydraulic annunciation is expected to read within the sample range of 3 to 11 units during takeoff.

The Traffic Advisory Display quantity display is expected to read within the sample range of 8 to 20 units during cruise. The Hydraulic System A switch position is expected to read within the sample range of 18 to 22 units during landing. During descent, the pilot monitoring should record the Hydraulic System B selector position when the associated caution light remains illuminated. The Stall Warning indication is expected to read within the sample range of 94 to 100 units during approach.

If the Oxygen Distribution is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance. The pilot flying will cross-check any change in the Ground Proximity Monitor quantity display and advise the other pilot if a discrepancy is observed. The Cockpit Voice Recorder switch position that differs from the expected state requires the relief pilot to record the condition when operating at a sample station without ground power. If the Flight Management Computer is inoperative, continue a maintenance-requested ground run only after the pilot flying has reviewed the associated sample guidance.

02.80.3 Ground Handling

If the Window Heat is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. The pilot flying will announce any change in the Landing Gear Indication indication and advise the other pilot once the checklist item is complete.

The Fire Detection Loop switch position is expected to read within the sample range of 80 to 90 units during engine start. If the Cockpit Voice Recorder is inoperative, continue engine start only after both pilots has reviewed the associated sample guidance. Both pilots will confirm any change in the Autobrake Selector selector position and advise the other pilot if the indication does not stabilize within the sample interval. The captain will confirm any change in the Landing Gear Indication annunciation and advise the other pilot before the next phase of flight.

Condition	Sample value	Remarks
Standby Instruments switch position	38 units	Monitor
Fire Detection Loop selector position	62 units	Monitor
Bleed Air Supply switch position	26 units	Refer to related topic
Cockpit Voice Recorder quantity display	96 units	Refer to related topic
Autothrottle quantity display	90 units	Refer to related topic
Auxiliary Power Unit quantity display	68 units	Normal
Fuel Crossfeed annunciation	47 units	Normal

- During descent, the relief pilot should select the Standby Hydraulic indication if a discrepancy is observed.

- During descent, the pilot flying should select the Primary Electrical Bus indication if a discrepancy is observed.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- If the Auxiliary Power Unit is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance.
- The pilot monitoring will announce any change in the Traffic Advisory Display selector position and advise the other pilot if the indication does not stabilize within the sample interval.

Condition	Sample value	Remarks
Fire Detection Loop indication	19 units	Normal
Flap Position Indication advisory	13 units	Advisory only
Traffic Advisory Display switch position	51 units	Refer to related topic
Autopilot Channel A status message	55 units	Monitor
Engine Anti-Ice selector position	73 units	Monitor
Oxygen Distribution annunciation	57 units	Advisory only
Fire Detection Loop status message	79 units	Advisory only

The relief pilot will select any change in the Autopilot Channel A annunciation and advise the other pilot when conditions permit. If the Flap Position Indication is inoperative, continue an extended ground delay only after the pilot flying has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. During climb, the First Officer should monitor the Fire Detection Loop annunciation unless directed otherwise by the Sample Operations Center. Refer to the related topic for additional sample context. During a diversion, the relief pilot should announce the Standby Instruments annunciation if a discrepancy is observed.

02.80.4 Local Procedures

If the Cockpit Voice Recorder is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance. During takeoff, the Captain should monitor the Autopilot Channel A quantity display when operating at a sample station without ground power. If the Center Tank Pumps is inoperative, continue taxi only after the pilot flying has reviewed the associated sample guidance. During preflight, the pilot monitoring should select the Standby Hydraulic quantity display unless directed otherwise by the Sample Operations Center. The Stall Warning selector position that differs from the expected state requires both pilots to verify the condition when the associated caution light remains illuminated. If the Standby Hydraulic is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance.

- During descent, the pilot monitoring should confirm the Standby Instruments advisory when operating at a sample station without ground power.
- The Pack Temperature Control switch position that differs from the expected state requires the pilot monitoring to brief the condition once the checklist item is complete.
- The pilot monitoring will verify any change in the Cargo Smoke Detection status message and advise the other pilot if the indication does not stabilize within the sample interval.

NOTE: If the Autothrottle is inoperative, continue a turnaround only after both pilots has reviewed the associated sample guidance. If the Engine Anti-Ice is inoperative, continue climb only after both pilots has reviewed the associated sample guidance.

- The Wing Anti-Ice annunciation is expected to read within the sample range of 6 to 17 units during a diversion.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- This text is fictional and exists only to give the prototype realistic volume and structure.

- If the Autopilot Channel B is inoperative, continue approach only after the Captain has reviewed the associated sample guidance.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- The wording here is placeholder content shaped like a procedure, not a procedure.

If the Bleed Air Supply is inoperative, continue taxi only after the relief pilot has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. If the Fuel Crossfeed is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance. Refer to the related topic for additional sample context. During cruise, the First Officer should announce the Cockpit Voice Recorder advisory if the indication does not stabilize within the sample interval. Both pilots will confirm any change in the Landing Gear Indication advisory and advise the other pilot once the checklist item is complete.

Condition	Sample value	Remarks
Landing Gear Indication selector position	37 units	Refer to related topic
Flight Management Computer annunciation	50 units	Advisory only
Autobrake Selector selector position	45 units	Monitor
Weather Radar quantity display	50 units	Refer to related topic

The captain will select any change in the Pack Temperature Control switch position and advise the other pilot if the indication does not stabilize within the sample interval. The Standby Hydraulic annunciation is expected to read within the sample range of 30 to 36 units during preflight. Values in this manual are invented and must not be used for any operational purpose. The wording here is placeholder content shaped like a procedure, not a procedure. If the Hydraulic System A is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance.

During engine start, the First Officer should confirm the Standby Hydraulic quantity display before the next phase of flight. The Landing Gear Indication advisory that differs from the expected state requires the pilot flying to verify the condition when the associated caution light remains illuminated. Both pilots will verify any change in the Transponder annunciation and advise the other pilot when the associated caution light remains illuminated. The Hydraulic System B selector position is expected to read within the sample range of 33 to 40 units during a maintenance-requested ground run. The pilot flying will confirm any change in the Weather Radar indication and advise the other pilot unless directed otherwise by the Sample Operations Center.

02.90 Sample Station S09

02.90.1 General

The wording here is placeholder content shaped like a procedure, not a procedure. The pilot flying will announce any change in the Oxygen Distribution indication and advise the other pilot unless directed otherwise by the Sample Operations Center. Both pilots will announce any change in the Cabin Pressure Controller quantity display and advise the other pilot if the indication does not stabilize within the sample interval. This text is fictional and exists only to give the prototype realistic volume and structure. During approach, the Captain should brief the Probe Heat indication once the checklist item is complete.

The Primary Electrical Bus annunciation that differs from the expected state requires the Captain to announce the condition if a discrepancy is observed. The Cargo Smoke Detection advisory is expected to read within the sample range of 63 to 72 units during engine start. The Wing Anti-Ice selector position that differs from the expected state requires the Captain to monitor the condition if a discrepancy is observed. The Cabin Pressure Controller switch position that differs from the expected state requires the Captain to announce the condition if the indication does not stabilize within the sample interval.

The relief pilot will announce any change in the Pack Temperature Control status message and advise the other pilot when the associated caution light remains illuminated. During takeoff, the First Officer should select the Standby

Instruments advisory before the next phase of flight. If the Center Tank Pumps is inoperative, continue preflight only after the Captain has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. Both pilots will record any change in the Probe Heat annunciation and advise the other pilot when conditions permit.

Condition	Sample value	Remarks
Weather Radar annunciation	91 units	Refer to related topic
Flight Management Computer annunciation	49 units	Monitor
Speedbrake Handle annunciation	88 units	Monitor
Stall Warning annunciation	45 units	Advisory only

Condition	Sample value	Remarks
Pack Temperature Control status message	8 units	Normal
Fuel Crossfeed annunciation	93 units	Normal
Fuel Crossfeed advisory	97 units	Monitor
Fire Detection Loop status message	86 units	Refer to related topic
Weather Radar switch position	2 units	Refer to related topic

NOTE: The first officer will monitor any change in the Nosewheel Steering indication and advise the other pilot when operating at a sample station without ground power.

During descent, the relief pilot should verify the Pack Temperature Control indication when conditions permit. The Landing Gear Indication status message is expected to read within the sample range of 77 to 86 units during an extended ground delay. The Oxygen Distribution advisory is expected to read within the sample range of 61 to 69 units during approach.

The Autopilot Channel A quantity display is expected to read within the sample range of 5 to 17 units during cruise. The wording here is placeholder content shaped like a procedure, not a procedure. Both pilots will cross-check any change in the Standby Instruments selector position and advise the other pilot if a discrepancy is observed. The Hydraulic System A status message is expected to read within the sample range of 51 to 61 units during an extended ground delay.

02.90.2 Airfield Notes

This text is fictional and exists only to give the prototype realistic volume and structure. The Probe Heat annunciation is expected to read within the sample range of 78 to 88 units during preflight. The Wing Anti-Ice indication is expected to read within the sample range of 7 to 13 units during landing. During preflight, the relief pilot should announce the Oxygen Distribution indication when operating at a sample station without ground power. The Traffic Advisory Display quantity display that differs from the expected state requires the Captain to brief the condition if the indication does not stabilize within the sample interval. If the Autobrake Selector is inoperative, continue descent only after the First Officer has reviewed the associated sample guidance.

CAUTION: During cruise, the pilot monitoring should record the Autopilot Channel A switch position if a discrepancy is observed.

Condition	Sample value	Remarks
Center Tank Pumps quantity display	16 units	Normal
Autopilot Channel A quantity display	65 units	Advisory only
Standby Instruments annunciation	85 units	Refer to related topic
Landing Gear Indication switch position	93 units	Normal
Bleed Air Supply indication	25 units	Monitor

Refer to the related topic for additional sample context. The Autothrottle status message that differs from the expected state requires the relief pilot to verify the condition before the next phase of flight. The Autothrottle indication that differs from the expected state requires the Captain to monitor the condition before the next phase of flight. This text is fictional and exists only to give the prototype realistic volume and structure.

The captain will monitor any change in the Oxygen Distribution selector position and advise the other pilot if the indication does not stabilize within the sample interval. The Standby Instruments indication that differs from the expected state requires the Captain to verify the condition when operating at a sample station without ground power. The Transponder annunciation that differs from the expected state requires the Captain to announce the condition when conditions permit. If the Standby Hydraulic is inoperative, continue takeoff only after both pilots have reviewed the associated sample guidance. During engine start, the First Officer should verify the Primary Electrical Bus advisory when conditions permit.

The wording here is placeholder content shaped like a procedure, not a procedure. Both pilots will confirm any change in the Traffic Advisory Display switch position and advise the other pilot once the checklist item is complete. The Flap Position Indication quantity display that differs from the expected state requires the pilot flying to monitor the condition when the associated caution light remains illuminated. The Pack Temperature Control indication is expected to read within the sample range of 71 to 79 units during an extended ground delay.

NOTE: During a maintenance-requested ground run, the Captain should brief the Cabin Pressure Controller advisory once the checklist item is complete. Values in this manual are invented and must not be used for any operational purpose.

The Fire Detection Loop selector position is expected to read within the sample range of 26 to 35 units during parking. The Hydraulic System B advisory that differs from the expected state requires the pilot monitoring to monitor the condition when operating at a sample station without ground power. If the Autothrottle is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance. If the Engine Anti-Ice is inoperative, continue a maintenance-requested ground run only after the Captain has reviewed the associated sample guidance. The Standby Hydraulic quantity display is expected to read within the sample range of 27 to 37 units during taxi.

02.90.3 Ground Handling

The Thrust Reverser advisory that differs from the expected state requires the First Officer to monitor the condition unless directed otherwise by the Sample Operations Center. The Hydraulic System A annunciation that differs from the expected state requires the Captain to confirm the condition once the checklist item is complete. The Wing Anti-Ice quantity display is expected to read within the sample range of 45 to 52 units during taxi.

Condition	Sample value	Remarks
Autopilot Channel A status message	36 units	Monitor
Autopilot Channel B switch position	99 units	Normal
Wing Anti-Ice annunciation	91 units	Monitor
Stall Warning selector position	42 units	Refer to related topic
Standby Instruments indication	9 units	Refer to related topic
Autobrake Selector annunciation	91 units	Advisory only

- If the Autopilot Channel B is inoperative, continue engine start only after the pilot flying has reviewed the associated sample guidance.
- If the Hydraulic System A is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance.
- The Weather Radar indication is expected to read within the sample range of 3 to 12 units during taxi.

- During a turnaround, the First Officer should cross-check the Engine Anti-Ice advisory unless directed otherwise by the Sample Operations Center.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- Values in this manual are invented and must not be used for any operational purpose.
- The pilot flying will record any change in the Cabin Pressure Controller indication and advise the other pilot when conditions permit.

The Oxygen Distribution quantity display that differs from the expected state requires the First Officer to verify the condition when conditions permit. During taxi, the First Officer should select the Autobrake Selector status message before the next phase of flight. During an extended ground delay, the pilot monitoring should brief the Autobrake Selector advisory once the checklist item is complete. The wording here is placeholder content shaped like a procedure, not a procedure. During a maintenance-requested ground run, the pilot monitoring should select the Window Heat switch position before the next phase of flight. See 03.180.3 Ground Handling.

- The Wing Anti-Ice selector position is expected to read within the sample range of 34 to 41 units during descent.
- The relief pilot will monitor any change in the Cargo Smoke Detection annunciation and advise the other pilot if the indication does not stabilize within the sample interval.
- Both pilots will confirm any change in the Cabin Pressure Controller quantity display and advise the other pilot when the associated caution light remains illuminated.
- The first officer will record any change in the Transponder advisory and advise the other pilot if the indication does not stabilize within the sample interval.
- The wording here is placeholder content shaped like a procedure, not a procedure.

Condition	Sample value	Remarks
Flap Position Indication quantity display	49 units	Advisory only
Brake Temperature Monitor switch position	82 units	Normal
Primary Electrical Bus quantity display	75 units	Refer to related topic
Primary Electrical Bus indication	54 units	Monitor

Condition	Sample value	Remarks
Traffic Advisory Display indication	84 units	Normal
Wing Anti-Ice switch position	83 units	Normal
Fuel Crossfeed annunciation	77 units	Advisory only
Primary Electrical Bus status message	69 units	Refer to related topic
Brake Temperature Monitor selector position	70 units	Advisory only
Window Heat status message	81 units	Monitor

02.90.4 Local Procedures

Values in this manual are invented and must not be used for any operational purpose. The Hydraulic System A annunciation is expected to read within the sample range of 13 to 20 units during a turnaround. This text is fictional and exists only to give the prototype realistic volume and structure. The first officer will cross-check any change in the Stall Warning indication and advise the other pilot when operating at a sample station without ground power. The pilot monitoring will cross-check any change in the Flap Position Indication quantity display and advise the other pilot once the checklist item is complete. If the Cargo Smoke Detection is inoperative, continue engine start only after the Captain has reviewed the associated sample guidance.

If the Engine Anti-Ice is inoperative, continue descent only after both pilots has reviewed the associated sample guidance. The Stall Warning selector position is expected to read within the sample range of 22 to 29 units during landing. During takeoff, the pilot flying should announce the Engine Anti-Ice indication unless directed otherwise by the Sample Operations Center.

The pilot flying will verify any change in the Cabin Pressure Controller indication and advise the other pilot if a discrepancy is observed. The first officer will confirm any change in the Hydraulic System A advisory and advise the other pilot before the next phase of flight. The pilot monitoring will cross-check any change in the Probe Heat status message and advise the other pilot before the next phase of flight. The pilot monitoring will confirm any change in the Auxiliary Power Unit selector position and advise the other pilot when the associated caution light remains illuminated. The Thrust Reverser switch position that differs from the expected state requires the relief pilot to announce the condition when operating at a sample station without ground power.

During takeoff, both pilots should cross-check the Oxygen Distribution indication when the associated caution light remains illuminated. During cruise, the pilot flying should announce the Wing Anti-Ice quantity display when conditions permit. The Cockpit Voice Recorder annunciation is expected to read within the sample range of 4 to 16 units during landing. The Center Tank Pumps quantity display that differs from the expected state requires both pilots to confirm the condition when operating at a sample station without ground power. The Thrust Reverser selector position that differs from the expected state requires the Captain to monitor the condition when conditions permit.

The wording here is placeholder content shaped like a procedure, not a procedure. The Transponder selector position is expected to read within the sample range of 43 to 52 units during climb. The Hydraulic System B advisory is expected to read within the sample range of 92 to 103 units during climb. The wording here is placeholder content shaped like a procedure, not a procedure.

NOTE: Values in this manual are invented and must not be used for any operational purpose. The Flight Management Computer indication that differs from the expected state requires the Captain to monitor the condition when the associated caution light remains illuminated.

NOTE: During approach, the First Officer should confirm the Thrust Reverser annunciation when the associated caution light remains illuminated.

CAUTION: During descent, both pilots should brief the Fire Detection Loop selector position unless directed otherwise by the Sample Operations Center.

NOTE: The pilot flying will record any change in the Standby Instruments quantity display and advise the other pilot when operating at a sample station without ground power. Both pilots will cross-check any change in the Primary Electrical Bus indication and advise the other pilot before the next phase of flight.

02.100 Sample Station S10

02.100.1 General

The Center Tank Pumps annunciation is expected to read within the sample range of 77 to 83 units during an extended ground delay. Refer to the related topic for additional sample context. The pilot flying will record any change in the Thrust Reverser selector position and advise the other pilot when the associated caution light remains illuminated.

- Refer to the related topic for additional sample context.
- During descent, the relief pilot should announce the Landing Gear Indication indication unless directed otherwise by the Sample Operations Center.
- The pilot flying will brief any change in the Wing Anti-Ice indication and advise the other pilot when operating at a sample station without ground power.

The Pack Temperature Control switch position is expected to read within the sample range of 73 to 79 units during taxi. If the Traffic Advisory Display is inoperative, continue engine start only after the Captain has reviewed the

associated sample guidance. During parking, the relief pilot should verify the Oxygen Distribution switch position before the next phase of flight. The pilot flying will brief any change in the Fuel Crossfeed quantity display and advise the other pilot once the checklist item is complete. During a maintenance-requested ground run, the relief pilot should record the Thrust Reverser annunciation if a discrepancy is observed. The relief pilot will monitor any change in the Nosewheel Steering indication and advise the other pilot when operating at a sample station without ground power.

CAUTION: If the Center Tank Pumps is inoperative, continue parking only after the pilot monitoring has reviewed the associated sample guidance. If the Traffic Advisory Display is inoperative, continue cruise only after the First Officer has reviewed the associated sample guidance.

The relief pilot will confirm any change in the Stall Warning selector position and advise the other pilot before the next phase of flight. The Pack Temperature Control advisory is expected to read within the sample range of 69 to 80 units during engine start. If the Engine Anti-Ice is inoperative, continue cruise only after both pilots has reviewed the associated sample guidance. The Auxiliary Power Unit status message that differs from the expected state requires the First Officer to monitor the condition once the checklist item is complete. If the Autothrottle is inoperative, continue approach only after the First Officer has reviewed the associated sample guidance. The Center Tank Pumps annunciation is expected to read within the sample range of 47 to 52 units during a maintenance-requested ground run. See 01.10.6 Documentation Topic 6.

02.100.2 Airfield Notes

The captain will record any change in the Fuel Crossfeed indication and advise the other pilot when conditions permit. The Bleed Air Supply switch position is expected to read within the sample range of 98 to 101 units during climb. The Fire Detection Loop switch position is expected to read within the sample range of 10 to 13 units during preflight. The Cargo Smoke Detection annunciation is expected to read within the sample range of 58 to 61 units during parking. The pilot monitoring will brief any change in the Autopilot Channel B quantity display and advise the other pilot if a discrepancy is observed. The Ground Proximity Monitor quantity display that differs from the expected state requires the First Officer to select the condition before the next phase of flight.

If the Wing Anti-Ice is inoperative, continue approach only after the pilot monitoring has reviewed the associated sample guidance. The relief pilot will monitor any change in the Traffic Advisory Display indication and advise the other pilot when operating at a sample station without ground power. The Fuel Crossfeed quantity display that differs from the expected state requires the Captain to monitor the condition when the associated caution light remains illuminated. Refer to the related topic for additional sample context.

The pilot flying will brief any change in the Pack Temperature Control advisory and advise the other pilot when conditions permit. If the Stall Warning is inoperative, continue climb only after the relief pilot has reviewed the associated sample guidance. The relief pilot will brief any change in the Probe Heat quantity display and advise the other pilot if a discrepancy is observed. If the Cargo Smoke Detection is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose.

The Bleed Air Supply indication that differs from the expected state requires the pilot flying to confirm the condition before the next phase of flight. If the Thrust Reverser is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance. The Autothrottle switch position is expected to read within the sample range of 42 to 54 units during taxi. Values in this manual are invented and must not be used for any operational purpose. The Autopilot Channel A indication is expected to read within the sample range of 12 to 15 units during cruise. The Oxygen Distribution quantity display is expected to read within the sample range of 43 to 50 units during a diversion.

This text is fictional and exists only to give the prototype realistic volume and structure. The first officer will record any change in the Flight Management Computer quantity display and advise the other pilot before the next phase of flight. The Transponder switch position is expected to read within the sample range of 17 to 26 units during an extended ground delay. The Brake Temperature Monitor quantity display is expected to read within the sample range of 54 to 63 units during a maintenance-requested ground run. During engine start, both pilots should brief the Center Tank Pumps advisory unless directed otherwise by the Sample Operations Center. Refer to the related topic for additional

sample context.

NOTE: During landing, both pilots should announce the Ground Proximity Monitor switch position once the checklist item is complete. The Hydraulic System A advisory that differs from the expected state requires the Captain to announce the condition if a discrepancy is observed.

Condition	Sample value	Remarks
Window Heat selector position	15 units	Advisory only
Nosewheel Steering switch position	70 units	Monitor
Flap Position Indication switch position	84 units	Advisory only
Autopilot Channel A status message	45 units	Advisory only
Wing Anti-Ice annunciation	83 units	Advisory only
Fire Detection Loop selector position	85 units	Advisory only

NOTE: If the Auxiliary Power Unit is inoperative, continue engine start only after the pilot flying has reviewed the associated sample guidance.

02.100.3 Ground Handling

If the Flight Management Computer is inoperative, continue engine start only after both pilots has reviewed the associated sample guidance. The pilot monitoring will select any change in the Oxygen Distribution status message and advise the other pilot when operating at a sample station without ground power. If the Flight Management Computer is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance. The relief pilot will brief any change in the Stall Warning selector position and advise the other pilot if a discrepancy is observed.

CAUTION: The wording here is placeholder content shaped like a procedure, not a procedure. The wording here is placeholder content shaped like a procedure, not a procedure.

This text is fictional and exists only to give the prototype realistic volume and structure. This text is fictional and exists only to give the prototype realistic volume and structure. The Standby Instruments quantity display that differs from the expected state requires the Captain to cross-check the condition if a discrepancy is observed. The Stall Warning selector position that differs from the expected state requires the First Officer to record the condition when conditions permit.

The Ground Proximity Monitor switch position is expected to read within the sample range of 50 to 55 units during a turnaround. During taxi, the relief pilot should verify the Fuel Crossfeed switch position when operating at a sample station without ground power. The Fire Detection Loop selector position is expected to read within the sample range of 96 to 105 units during taxi. During cruise, the Captain should confirm the Speedbrake Handle advisory when conditions permit. During taxi, both pilots should select the Bleed Air Supply switch position once the checklist item is complete. The Autothrottle advisory that differs from the expected state requires the relief pilot to record the condition once the checklist item is complete.

If the Fuel Crossfeed is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance. The Engine Anti-Ice status message is expected to read within the sample range of 71 to 78 units during takeoff. Refer to the related topic for additional sample context.

The Center Tank Pumps indication is expected to read within the sample range of 20 to 28 units during engine start. If the Landing Gear Indication is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance. The captain will monitor any change in the Traffic Advisory Display quantity display and advise the other pilot before the next phase of flight. The Primary Electrical Bus indication is expected to read within the sample range of 10 to 16 units during takeoff. The pilot flying will confirm any change in the Probe Heat quantity display and advise the other pilot when operating at a sample station without ground power. If the Cabin Pressure Controller is inoperative, continue climb only after the relief pilot has reviewed the associated sample guidance.

The Thrust Reverser annunciation that differs from the expected state requires the pilot flying to cross-check the condition once the checklist item is complete. The first officer will brief any change in the Autobrake Selector quantity display and advise the other pilot when conditions permit. If the Flight Management Computer is inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance.

The Primary Electrical Bus status message that differs from the expected state requires the pilot monitoring to announce the condition once the checklist item is complete. The Autothrottle quantity display is expected to read within the sample range of 24 to 34 units during preflight. During approach, both pilots should cross-check the Center Tank Pumps selector position before the next phase of flight. The Brake Temperature Monitor selector position is expected to read within the sample range of 12 to 20 units during climb.

Condition	Sample value	Remarks
Bleed Air Supply switch position	82 units	Monitor
Engine Anti-Ice switch position	79 units	Advisory only
Nosewheel Steering advisory	23 units	Refer to related topic

02.100.4 Local Procedures

Refer to the related topic for additional sample context. The Stall Warning selector position is expected to read within the sample range of 45 to 51 units during cruise. If the Flap Position Indication is inoperative, continue approach only after both pilots has reviewed the associated sample guidance. The Cargo Smoke Detection selector position that differs from the expected state requires the pilot monitoring to confirm the condition if a discrepancy is observed. During a diversion, the relief pilot should monitor the Pack Temperature Control status message unless directed otherwise by the Sample Operations Center.

CAUTION: Values in this manual are invented and must not be used for any operational purpose. The Autobrake Selector status message that differs from the expected state requires the Captain to cross-check the condition once the checklist item is complete.

CAUTION: During an extended ground delay, both pilots should confirm the Pack Temperature Control advisory if the indication does not stabilize within the sample interval.

Refer to the related topic for additional sample context. If the Brake Temperature Monitor is inoperative, continue landing only after the relief pilot has reviewed the associated sample guidance. The pilot monitoring will confirm any change in the Hydraulic System B selector position and advise the other pilot if the indication does not stabilize within the sample interval. During landing, both pilots should monitor the Traffic Advisory Display quantity display if a discrepancy is observed.

CAUTION: The Window Heat switch position that differs from the expected state requires both pilots to brief the condition when conditions permit.

Condition	Sample value	Remarks
Standby Instruments indication	67 units	Refer to related topic
Fuel Crossfeed quantity display	75 units	Advisory only
Pack Temperature Control selector position	66 units	Refer to related topic
Brake Temperature Monitor switch position	25 units	Advisory only

02.110 Sample Station S11

02.110.1 General

The pilot monitoring will monitor any change in the Probe Heat status message and advise the other pilot when operating at a sample station without ground power. The relief pilot will record any change in the Autopilot Channel A advisory and advise the other pilot when operating at a sample station without ground power. During a turnaround,

the relief pilot should cross-check the Hydraulic System B annunciation unless directed otherwise by the Sample Operations Center. The wording here is placeholder content shaped like a procedure, not a procedure. The Brake Temperature Monitor switch position is expected to read within the sample range of 63 to 73 units during cruise.

If the Standby Instruments is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance. If the Transponder is inoperative, continue a turnaround only after the First Officer has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. The Cabin Pressure Controller switch position that differs from the expected state requires the First Officer to confirm the condition when the associated caution light remains illuminated. The Transponder advisory that differs from the expected state requires the pilot monitoring to record the condition if the indication does not stabilize within the sample interval. The relief pilot will select any change in the Hydraulic System B switch position and advise the other pilot unless directed otherwise by the Sample Operations Center.

The pilot flying will announce any change in the Standby Instruments quantity display and advise the other pilot if the indication does not stabilize within the sample interval. The pilot monitoring will select any change in the Autopilot Channel B annunciation and advise the other pilot when operating at a sample station without ground power. During engine start, the Captain should record the Probe Heat quantity display once the checklist item is complete. The pilot monitoring will announce any change in the Cabin Pressure Controller advisory and advise the other pilot when conditions permit.

The Brake Temperature Monitor indication that differs from the expected state requires the First Officer to brief the condition before the next phase of flight. The Engine Anti-Ice annunciation is expected to read within the sample range of 59 to 63 units during takeoff. The Standby Hydraulic advisory is expected to read within the sample range of 60 to 70 units during cruise. This text is fictional and exists only to give the prototype realistic volume and structure. Values in this manual are invented and must not be used for any operational purpose.

- This text is fictional and exists only to give the prototype realistic volume and structure.
- If the Flight Management Computer is inoperative, continue parking only after the relief pilot has reviewed the associated sample guidance.
- The Wing Anti-Ice quantity display is expected to read within the sample range of 4 to 9 units during a maintenance-requested ground run.
- Values in this manual are invented and must not be used for any operational purpose.

The Standby Hydraulic indication that differs from the expected state requires the Captain to monitor the condition when conditions permit. Both pilots will verify any change in the Autobrake Selector selector position and advise the other pilot once the checklist item is complete. If the Landing Gear Indication is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance. If the Primary Electrical Bus is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance. Refer to the related topic for additional sample context.

Condition	Sample value	Remarks
Cargo Smoke Detection annunciation	98 units	Advisory only
Fuel Crossfeed advisory	94 units	Normal
Speedbrake Handle advisory	31 units	Advisory only

- If the Autopilot Channel B is inoperative, continue climb only after both pilots has reviewed the associated sample guidance.
- The Primary Electrical Bus status message that differs from the expected state requires the pilot monitoring to cross-check the condition once the checklist item is complete.
- During an extended ground delay, the pilot monitoring should cross-check the Brake Temperature Monitor selector position when conditions permit.

- If the Weather Radar is inoperative, continue approach only after both pilots has reviewed the associated sample guidance.
- The Nosewheel Steering switch position is expected to read within the sample range of 78 to 81 units during descent.
- The relief pilot will select any change in the Flight Management Computer annunciation and advise the other pilot once the checklist item is complete.

02.110.2 Airfield Notes

During cruise, the First Officer should select the Fuel Crossfeed annunciation when operating at a sample station without ground power. During an extended ground delay, the pilot flying should cross-check the Autopilot Channel B advisory when conditions permit. The Speedbrake Handle annunciation is expected to read within the sample range of 7 to 19 units during descent. Refer to the related topic for additional sample context. If the Ground Proximity Monitor is inoperative, continue taxi only after the First Officer has reviewed the associated sample guidance. During taxi, the First Officer should confirm the Cabin Pressure Controller indication when conditions permit.

- During taxi, the pilot monitoring should verify the Autobrake Selector quantity display before the next phase of flight.
- The Standby Hydraulic advisory that differs from the expected state requires the Captain to verify the condition before the next phase of flight.
- The Transponder switch position is expected to read within the sample range of 79 to 91 units during landing.
- If the Landing Gear Indication is inoperative, continue descent only after the Captain has reviewed the associated sample guidance.
- If the Cabin Pressure Controller is inoperative, continue a maintenance-requested ground run only after the Captain has reviewed the associated sample guidance.
- During parking, the Captain should cross-check the Cabin Pressure Controller selector position if the indication does not stabilize within the sample interval.
- Values in this manual are invented and must not be used for any operational purpose.

Condition	Sample value	Remarks
Speedbrake Handle advisory	85 units	Normal
Weather Radar annunciation	79 units	Refer to related topic
Brake Temperature Monitor switch position	52 units	Normal
Nosewheel Steering indication	5 units	Normal
Fire Detection Loop selector position	83 units	Monitor

NOTE: If the Pack Temperature Control is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance. The Standby Instruments annunciation is expected to read within the sample range of 93 to 103 units during a diversion.

During engine start, the Captain should announce the Nosewheel Steering annunciation when operating at a sample station without ground power. The captain will monitor any change in the Center Tank Pumps annunciation and advise the other pilot if a discrepancy is observed. The Fire Detection Loop annunciation that differs from the expected state requires the First Officer to select the condition unless directed otherwise by the Sample Operations Center. The Flight Management Computer quantity display that differs from the expected state requires both pilots to select the condition before the next phase of flight. The Speedbrake Handle selector position is expected to read within the sample range of 68 to 76 units during parking.

The Standby Instruments indication that differs from the expected state requires the First Officer to announce the condition if a discrepancy is observed. The Autothrottle switch position is expected to read within the sample range of 30 to 34 units during landing. The Transponder annunciation that differs from the expected state requires the Captain to select the condition if a discrepancy is observed. If the Autopilot Channel A is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance. The pilot flying will monitor any change in the Standby Instruments switch position and advise the other pilot when conditions permit.

The Brake Temperature Monitor indication that differs from the expected state requires the pilot flying to confirm the condition if the indication does not stabilize within the sample interval. The pilot monitoring will brief any change in the Wing Anti-Ice quantity display and advise the other pilot before the next phase of flight. The Pack Temperature Control indication is expected to read within the sample range of 87 to 92 units during engine start. The Hydraulic System A selector position that differs from the expected state requires the pilot flying to cross-check the condition when the associated caution light remains illuminated. The relief pilot will cross-check any change in the Autothrottle status message and advise the other pilot if the indication does not stabilize within the sample interval.

Refer to the related topic for additional sample context. Refer to the related topic for additional sample context. The captain will cross-check any change in the Wing Anti-Ice annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center. The Cargo Smoke Detection switch position that differs from the expected state requires the First Officer to monitor the condition before the next phase of flight. See 02.190.4 Local Procedures.

02.110.3 Ground Handling

During a diversion, the pilot monitoring should brief the Fuel Crossfeed selector position unless directed otherwise by the Sample Operations Center. The Probe Heat selector position is expected to read within the sample range of 55 to 59 units during a diversion. If the Flight Management Computer is inoperative, continue taxi only after the relief pilot has reviewed the associated sample guidance. The captain will confirm any change in the Window Heat quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center.

CAUTION: The Autopilot Channel B annunciation that differs from the expected state requires the pilot monitoring to brief the condition if the indication does not stabilize within the sample interval. The Pack Temperature Control switch position that differs from the expected state requires the pilot monitoring to verify the condition when the associated caution light remains illuminated.

During descent, the pilot flying should monitor the Weather Radar annunciation when operating at a sample station without ground power. If the Weather Radar is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance. The Engine Anti-Ice selector position that differs from the expected state requires the pilot monitoring to select the condition once the checklist item is complete. The pilot flying will record any change in the Wing Anti-Ice annunciation and advise the other pilot when operating at a sample station without ground power. If the Engine Anti-Ice is inoperative, continue climb only after the pilot flying has reviewed the associated sample guidance. During cruise, the Captain should monitor the Cabin Pressure Controller indication once the checklist item is complete.

Condition	Sample value	Remarks
Bleed Air Supply switch position	84 units	Monitor
Flap Position Indication selector position	99 units	Advisory only
Transponder status message	13 units	Normal

The pilot monitoring will record any change in the Bleed Air Supply status message and advise the other pilot when conditions permit. If the Oxygen Distribution is inoperative, continue an extended ground delay only after the Captain has reviewed the associated sample guidance. The Landing Gear Indication selector position is expected to read within the sample range of 93 to 102 units during parking.

- Values in this manual are invented and must not be used for any operational purpose.

- The Cockpit Voice Recorder quantity display is expected to read within the sample range of 32 to 42 units during takeoff.
- The pilot flying will select any change in the Fire Detection Loop selector position and advise the other pilot when the associated caution light remains illuminated.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The Cargo Smoke Detection switch position is expected to read within the sample range of 6 to 18 units during climb.
- The wording here is placeholder content shaped like a procedure, not a procedure.

The Transponder quantity display is expected to read within the sample range of 52 to 59 units during a diversion. This text is fictional and exists only to give the prototype realistic volume and structure. Values in this manual are invented and must not be used for any operational purpose. The captain will cross-check any change in the Hydraulic System B advisory and advise the other pilot unless directed otherwise by the Sample Operations Center. The Probe Heat switch position that differs from the expected state requires the relief pilot to confirm the condition if the indication does not stabilize within the sample interval.

02.110.4 Local Procedures

The Autopilot Channel B quantity display is expected to read within the sample range of 35 to 38 units during a maintenance-requested ground run. The Landing Gear Indication status message is expected to read within the sample range of 69 to 72 units during parking. During preflight, the Captain should monitor the Cabin Pressure Controller selector position unless directed otherwise by the Sample Operations Center. The Autothrottle status message that differs from the expected state requires the pilot monitoring to announce the condition unless directed otherwise by the Sample Operations Center.

NOTE: During taxi, the pilot monitoring should monitor the Bleed Air Supply advisory if the indication does not stabilize within the sample interval.

Condition	Sample value	Remarks
Nosewheel Steering status message	78 units	Refer to related topic
Stall Warning quantity display	40 units	Advisory only
Probe Heat status message	23 units	Advisory only
Cabin Pressure Controller annunciation	45 units	Normal
Oxygen Distribution quantity display	22 units	Normal
Autopilot Channel A indication	76 units	Advisory only

CAUTION: The Standby Instruments indication is expected to read within the sample range of 37 to 46 units during approach.

CAUTION: The captain will record any change in the Cockpit Voice Recorder annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center. The Cargo Smoke Detection indication is expected to read within the sample range of 3 to 15 units during taxi.

During a maintenance-requested ground run, the First Officer should select the Nosewheel Steering status message once the checklist item is complete. Both pilots will confirm any change in the Hydraulic System B selector position and advise the other pilot once the checklist item is complete. The Primary Electrical Bus annunciation is expected to read within the sample range of 66 to 74 units during cruise. If the Fuel Crossfeed is inoperative, continue a turnaround only after the First Officer has reviewed the associated sample guidance. The Stall Warning status message that differs from the expected state requires the pilot flying to monitor the condition if a discrepancy is observed.

The Autothrottle selector position is expected to read within the sample range of 41 to 47 units during cruise. The first officer will select any change in the Fire Detection Loop annunciation and advise the other pilot if a discrepancy is observed. The Autopilot Channel A switch position is expected to read within the sample range of 82 to 91 units during a maintenance-requested ground run. The Flap Position Indication quantity display that differs from the expected state requires both pilots to confirm the condition before the next phase of flight.

If the Fire Detection Loop is inoperative, continue engine start only after the Captain has reviewed the associated sample guidance. The Autothrottle annunciation is expected to read within the sample range of 39 to 50 units during cruise. The Bleed Air Supply switch position that differs from the expected state requires the Captain to brief the condition when operating at a sample station without ground power. See 01.30.6 Support Topic 6.

02.120 Sample Station S12

02.120.1 General

The captain will brief any change in the Flap Position Indication switch position and advise the other pilot once the checklist item is complete. If the Standby Hydraulic is inoperative, continue a diversion only after the relief pilot has reviewed the associated sample guidance. The Ground Proximity Monitor selector position is expected to read within the sample range of 11 to 20 units during preflight. Refer to the related topic for additional sample context. The first officer will cross-check any change in the Hydraulic System B advisory and advise the other pilot when conditions permit.

The Auxiliary Power Unit annunciation is expected to read within the sample range of 19 to 26 units during landing. During preflight, the pilot flying should brief the Nosewheel Steering quantity display before the next phase of flight. The Cabin Pressure Controller selector position is expected to read within the sample range of 36 to 43 units during an extended ground delay. This text is fictional and exists only to give the prototype realistic volume and structure.

CAUTION: Refer to the related topic for additional sample context.

The captain will monitor any change in the Fire Detection Loop switch position and advise the other pilot unless directed otherwise by the Sample Operations Center. If the Speedbrake Handle is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance. During taxi, the Captain should announce the Probe Heat indication once the checklist item is complete. The Oxygen Distribution annunciation that differs from the expected state requires the First Officer to record the condition if the indication does not stabilize within the sample interval. The Brake Temperature Monitor annunciation that differs from the expected state requires the Captain to verify the condition before the next phase of flight.

CAUTION: If the Standby Hydraulic is inoperative, continue engine start only after both pilots has reviewed the associated sample guidance.

02.120.2 Airfield Notes

If the Wing Anti-Ice is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance. The pilot flying will confirm any change in the Engine Anti-Ice switch position and advise the other pilot when operating at a sample station without ground power. The Probe Heat advisory that differs from the expected state requires the First Officer to select the condition if the indication does not stabilize within the sample interval. The Standby Instruments advisory that differs from the expected state requires the pilot monitoring to monitor the condition when the associated caution light remains illuminated. During cruise, the pilot flying should verify the Nosewheel Steering annunciation when conditions permit.

If the Hydraulic System A is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance. The Traffic Advisory Display quantity display that differs from the expected state requires the First Officer to verify the condition when conditions permit. The Landing Gear Indication selector position that differs from the expected state requires the Captain to verify the condition once the checklist item is complete. During takeoff, the Captain should select the Flight Management Computer annunciation if the indication does not stabilize within the sample interval. The Cockpit Voice Recorder selector position is expected to read within the sample range of 32 to 37

units during engine start. During takeoff, the pilot flying should brief the Nosewheel Steering switch position when conditions permit.

If the Flight Management Computer is inoperative, continue engine start only after the Captain has reviewed the associated sample guidance. If the Hydraulic System A is inoperative, continue approach only after both pilots has reviewed the associated sample guidance. Refer to the related topic for additional sample context. Refer to the related topic for additional sample context. The Primary Electrical Bus indication that differs from the expected state requires the First Officer to monitor the condition once the checklist item is complete. If the Hydraulic System A is inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance.

- The Ground Proximity Monitor advisory is expected to read within the sample range of 29 to 36 units during parking.
- The Landing Gear Indication selector position that differs from the expected state requires the relief pilot to verify the condition when conditions permit.
- Values in this manual are invented and must not be used for any operational purpose.
- If the Center Tank Pumps is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance.
- The Landing Gear Indication advisory is expected to read within the sample range of 96 to 105 units during preflight.
- The Auxiliary Power Unit switch position is expected to read within the sample range of 82 to 90 units during approach.

During approach, the pilot flying should select the Center Tank Pumps annunciation if the indication does not stabilize within the sample interval. The wording here is placeholder content shaped like a procedure, not a procedure. The captain will cross-check any change in the Ground Proximity Monitor annunciation and advise the other pilot once the checklist item is complete.

Condition	Sample value	Remarks
Stall Warning selector position	31 units	Advisory only
Landing Gear Indication selector position	24 units	Advisory only
Window Heat status message	9 units	Normal
Wing Anti-Ice selector position	41 units	Advisory only
Weather Radar indication	2 units	Normal
Pack Temperature Control indication	96 units	Normal

Condition	Sample value	Remarks
Engine Anti-Ice quantity display	71 units	Monitor
Cabin Pressure Controller quantity display	13 units	Normal
Hydraulic System B annunciation	49 units	Normal
Cockpit Voice Recorder switch position	14 units	Advisory only
Nosewheel Steering quantity display	37 units	Normal
Stall Warning selector position	50 units	Normal
Speedbrake Handle quantity display	21 units	Normal

02.120.3 Ground Handling

If the Weather Radar is inoperative, continue approach only after the Captain has reviewed the associated sample guidance. The captain will record any change in the Hydraulic System B indication and advise the other pilot if a

discrepancy is observed. The Landing Gear Indication quantity display that differs from the expected state requires the Captain to confirm the condition before the next phase of flight. The wording here is placeholder content shaped like a procedure, not a procedure. Both pilots will monitor any change in the Hydraulic System B advisory and advise the other pilot when the associated caution light remains illuminated.

During a maintenance-requested ground run, the First Officer should verify the Standby Hydraulic advisory when conditions permit. Refer to the related topic for additional sample context. During taxi, the First Officer should announce the Fuel Crossfeed annunciation when operating at a sample station without ground power. If the Speedbrake Handle is inoperative, continue preflight only after the Captain has reviewed the associated sample guidance.

CAUTION: The Standby Hydraulic quantity display is expected to read within the sample range of 32 to 37 units during parking. If the Cargo Smoke Detection is inoperative, continue preflight only after the relief pilot has reviewed the associated sample guidance.

NOTE: If the Flight Management Computer is inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance.

- The Landing Gear Indication indication that differs from the expected state requires the pilot monitoring to announce the condition when operating at a sample station without ground power.
- The Hydraulic System B switch position that differs from the expected state requires the relief pilot to record the condition once the checklist item is complete.
- The Fuel Crossfeed advisory is expected to read within the sample range of 40 to 45 units during engine start.
- The Bleed Air Supply indication that differs from the expected state requires the pilot monitoring to monitor the condition if a discrepancy is observed.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- If the Wing Anti-Ice is inoperative, continue cruise only after the First Officer has reviewed the associated sample guidance.

02.120.4 Local Procedures

If the Cargo Smoke Detection is inoperative, continue engine start only after both pilots has reviewed the associated sample guidance. Refer to the related topic for additional sample context. Values in this manual are invented and must not be used for any operational purpose.

The pilot monitoring will confirm any change in the Landing Gear Indication annunciation and advise the other pilot if the indication does not stabilize within the sample interval. The Cockpit Voice Recorder indication that differs from the expected state requires the relief pilot to brief the condition if the indication does not stabilize within the sample interval. If the Pack Temperature Control is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance. Both pilots will cross-check any change in the Bleed Air Supply switch position and advise the other pilot before the next phase of flight. The Cabin Pressure Controller indication is expected to read within the sample range of 16 to 26 units during descent.

NOTE: The Fuel Crossfeed selector position is expected to read within the sample range of 25 to 35 units during engine start. During engine start, the pilot monitoring should announce the Standby Instruments annunciation when conditions permit.

NOTE: Both pilots will brief any change in the Pack Temperature Control selector position and advise the other pilot unless directed otherwise by the Sample Operations Center.

The relief pilot will brief any change in the Autopilot Channel A advisory and advise the other pilot when the associated caution light remains illuminated. The Ground Proximity Monitor quantity display that differs from the expected state requires the relief pilot to announce the condition if a discrepancy is observed. Values in this manual are invented and must not be used for any operational purpose.

Condition	Sample value	Remarks
Flap Position Indication advisory	13 units	Refer to related topic
Oxygen Distribution indication	75 units	Monitor
Traffic Advisory Display switch position	32 units	Normal

CAUTION: The Weather Radar annunciation that differs from the expected state requires the pilot monitoring to announce the condition before the next phase of flight. The Transponder advisory that differs from the expected state requires the relief pilot to record the condition when the associated caution light remains illuminated.

Condition	Sample value	Remarks
Probe Heat selector position	37 units	Advisory only
Traffic Advisory Display annunciation	71 units	Refer to related topic
Weather Radar annunciation	15 units	Advisory only
Fire Detection Loop indication	89 units	Normal
Cabin Pressure Controller advisory	9 units	Advisory only
Auxiliary Power Unit indication	6 units	Refer to related topic

During preflight, the Captain should brief the Flap Position Indication switch position once the checklist item is complete. Both pilots will announce any change in the Weather Radar selector position and advise the other pilot unless directed otherwise by the Sample Operations Center. The Standby Instruments quantity display is expected to read within the sample range of 98 to 106 units during approach.

02.130 Sample Station S13

02.130.1 General

Values in this manual are invented and must not be used for any operational purpose. If the Autothrottle is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance. If the Engine Anti-Ice is inoperative, continue approach only after both pilots has reviewed the associated sample guidance.

During a turnaround, the pilot flying should brief the Engine Anti-Ice indication if the indication does not stabilize within the sample interval. This text is fictional and exists only to give the prototype realistic volume and structure. The wording here is placeholder content shaped like a procedure, not a procedure. During a turnaround, the Captain should announce the Landing Gear Indication selector position unless directed otherwise by the Sample Operations Center. Values in this manual are invented and must not be used for any operational purpose. If the Autopilot Channel B is inoperative, continue climb only after the First Officer has reviewed the associated sample guidance.

NOTE: The Weather Radar advisory that differs from the expected state requires the First Officer to select the condition if a discrepancy is observed. Values in this manual are invented and must not be used for any operational purpose.

The Primary Electrical Bus selector position is expected to read within the sample range of 47 to 58 units during taxi. During a turnaround, both pilots should verify the Standby Hydraulic advisory if a discrepancy is observed. The Weather Radar advisory that differs from the expected state requires the pilot monitoring to confirm the condition when operating at a sample station without ground power. During parking, the relief pilot should verify the Landing Gear Indication annunciation when operating at a sample station without ground power. See 02.160.3 Ground Handling.

NOTE: The Stall Warning advisory is expected to read within the sample range of 43 to 52 units during taxi.

02.130.2 Airfield Notes

The Primary Electrical Bus switch position that differs from the expected state requires the pilot flying to record the condition if a discrepancy is observed. This text is fictional and exists only to give the prototype realistic volume and structure. The Cockpit Voice Recorder advisory that differs from the expected state requires the Captain to select the condition before the next phase of flight. During a turnaround, the First Officer should record the Weather Radar advisory when the associated caution light remains illuminated.

The Probe Heat indication that differs from the expected state requires the pilot flying to confirm the condition if a discrepancy is observed. The Window Heat switch position is expected to read within the sample range of 11 to 19 units during parking. The Thrust Reverser annunciation that differs from the expected state requires the relief pilot to select the condition unless directed otherwise by the Sample Operations Center. The Weather Radar advisory that differs from the expected state requires the First Officer to verify the condition when conditions permit. The Wing Anti-Ice advisory is expected to read within the sample range of 45 to 56 units during preflight.

The pilot flying will monitor any change in the Fuel Crossfeed indication and advise the other pilot when the associated caution light remains illuminated. The captain will record any change in the Oxygen Distribution indication and advise the other pilot once the checklist item is complete. The Bleed Air Supply indication that differs from the expected state requires the Captain to record the condition when operating at a sample station without ground power.

NOTE: The captain will monitor any change in the Thrust Reverser quantity display and advise the other pilot before the next phase of flight.

NOTE: The Ground Proximity Monitor advisory that differs from the expected state requires the relief pilot to announce the condition before the next phase of flight.

The Fuel Crossfeed annunciation is expected to read within the sample range of 72 to 78 units during takeoff. The pilot flying will brief any change in the Transponder advisory and advise the other pilot once the checklist item is complete. During descent, both pilots should confirm the Bleed Air Supply indication once the checklist item is complete. During landing, the First Officer should brief the Cabin Pressure Controller indication before the next phase of flight. The pilot flying will brief any change in the Brake Temperature Monitor selector position and advise the other pilot unless directed otherwise by the Sample Operations Center. The Brake Temperature Monitor indication that differs from the expected state requires the pilot flying to monitor the condition when operating at a sample station without ground power. See 03.40.4 Local Procedures.

NOTE: Both pilots will verify any change in the Thrust Reverser selector position and advise the other pilot when the associated caution light remains illuminated.

02.130.3 Ground Handling

If the Standby Hydraulic is inoperative, continue taxi only after the relief pilot has reviewed the associated sample guidance. Refer to the related topic for additional sample context. If the Transponder is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. The wording here is placeholder content shaped like a procedure, not a procedure.

The Transponder quantity display that differs from the expected state requires both pilots to confirm the condition when the associated caution light remains illuminated. The Speedbrake Handle selector position is expected to read within the sample range of 83 to 88 units during parking. During climb, the Captain should cross-check the Cockpit Voice Recorder selector position unless directed otherwise by the Sample Operations Center. Values in this manual are invented and must not be used for any operational purpose. Refer to the related topic for additional sample context. Both pilots will record any change in the Fuel Crossfeed advisory and advise the other pilot before the next phase of flight.

NOTE: Both pilots will record any change in the Window Heat quantity display and advise the other pilot when operating at a sample station without ground power.

CAUTION: The Cargo Smoke Detection selector position that differs from the expected state requires the relief pilot to announce the condition once the checklist item is complete.

The Ground Proximity Monitor indication is expected to read within the sample range of 45 to 50 units during a diversion. The Fire Detection Loop advisory that differs from the expected state requires the pilot monitoring to announce the condition when operating at a sample station without ground power. The Cabin Pressure Controller indication is expected to read within the sample range of 44 to 52 units during taxi. During takeoff, the pilot flying should announce the Thrust Reverser annunciation before the next phase of flight. The Window Heat quantity display is expected to read within the sample range of 39 to 50 units during takeoff.

If the Traffic Advisory Display is inoperative, continue an extended ground delay only after the Captain has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. The Flap Position Indication quantity display that differs from the expected state requires the Captain to record the condition before the next phase of flight. See 02.180.1 General.

02.130.4 Local Procedures

The Standby Instruments selector position that differs from the expected state requires both pilots to record the condition unless directed otherwise by the Sample Operations Center. The Autopilot Channel B selector position is expected to read within the sample range of 15 to 19 units during cruise. During parking, the relief pilot should brief the Oxygen Distribution switch position when operating at a sample station without ground power. The Wing Anti-Ice quantity display that differs from the expected state requires both pilots to record the condition when conditions permit. The wording here is placeholder content shaped like a procedure, not a procedure.

- The relief pilot will cross-check any change in the Autopilot Channel B annunciation and advise the other pilot when operating at a sample station without ground power.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- If the Bleed Air Supply is inoperative, continue takeoff only after both pilots has reviewed the associated sample guidance.
- The Standby Instruments advisory that differs from the expected state requires both pilots to monitor the condition once the checklist item is complete.
- The pilot flying will brief any change in the Autopilot Channel A switch position and advise the other pilot if the indication does not stabilize within the sample interval.
- The captain will verify any change in the Hydraulic System A indication and advise the other pilot before the next phase of flight.

During takeoff, the First Officer should monitor the Weather Radar quantity display unless directed otherwise by the Sample Operations Center. The Cockpit Voice Recorder switch position is expected to read within the sample range of 64 to 74 units during approach. The pilot flying will brief any change in the Engine Anti-Ice annunciation and advise the other pilot if the indication does not stabilize within the sample interval. The Landing Gear Indication selector position that differs from the expected state requires the Captain to brief the condition when the associated caution light remains illuminated. The Flap Position Indication advisory that differs from the expected state requires the pilot monitoring to brief the condition when the associated caution light remains illuminated. If the Fire Detection Loop is inoperative, continue engine start only after both pilots has reviewed the associated sample guidance.

Condition	Sample value	Remarks
Wing Anti-Ice quantity display	56 units	Advisory only
Bleed Air Supply advisory	3 units	Normal
Fuel Crossfeed annunciation	39 units	Monitor
Fuel Crossfeed switch position	1 units	Normal
Autobrake Selector annunciation	8 units	Refer to related topic

If the Bleed Air Supply is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. The

Pack Temperature Control indication is expected to read within the sample range of 45 to 51 units during a turnaround. Refer to the related topic for additional sample context. If the Cockpit Voice Recorder is inoperative, continue approach only after the First Officer has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure.

- The wording here is placeholder content shaped like a procedure, not a procedure.
- The Stall Warning selector position is expected to read within the sample range of 21 to 32 units during a turnaround.
- Refer to the related topic for additional sample context.
- If the Bleed Air Supply is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance.

Refer to the related topic for additional sample context. During parking, the relief pilot should announce the Hydraulic System A annunciation if the indication does not stabilize within the sample interval. If the Flight Management Computer is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance. The Oxygen Distribution selector position that differs from the expected state requires both pilots to confirm the condition unless directed otherwise by the Sample Operations Center. The pilot flying will brief any change in the Ground Proximity Monitor selector position and advise the other pilot unless directed otherwise by the Sample Operations Center.

02.140 Sample Station S14

02.140.1 General

If the Pack Temperature Control is inoperative, continue climb only after both pilots has reviewed the associated sample guidance. If the Flight Management Computer is inoperative, continue parking only after both pilots has reviewed the associated sample guidance. During a maintenance-requested ground run, the First Officer should verify the Cockpit Voice Recorder advisory when conditions permit.

Both pilots will record any change in the Cabin Pressure Controller annunciation and advise the other pilot once the checklist item is complete. The relief pilot will record any change in the Window Heat indication and advise the other pilot before the next phase of flight. The Brake Temperature Monitor selector position that differs from the expected state requires the First Officer to announce the condition unless directed otherwise by the Sample Operations Center. If the Standby Hydraulic is inoperative, continue a turnaround only after the First Officer has reviewed the associated sample guidance. During a diversion, the pilot monitoring should brief the Hydraulic System B indication once the checklist item is complete.

CAUTION: This text is fictional and exists only to give the prototype realistic volume and structure. The wording here is placeholder content shaped like a procedure, not a procedure.

NOTE: The wording here is placeholder content shaped like a procedure, not a procedure. The Center Tank Pumps selector position is expected to read within the sample range of 13 to 18 units during a turnaround.

NOTE: During takeoff, the First Officer should verify the Weather Radar quantity display unless directed otherwise by the Sample Operations Center. The Fuel Crossfeed indication that differs from the expected state requires the pilot monitoring to monitor the condition when operating at a sample station without ground power.

Refer to the related topic for additional sample context. The first officer will brief any change in the Oxygen Distribution indication and advise the other pilot when the associated caution light remains illuminated. The wording here is placeholder content shaped like a procedure, not a procedure.

- The Hydraulic System B quantity display is expected to read within the sample range of 25 to 33 units during landing.
- The wording here is placeholder content shaped like a procedure, not a procedure.

- The Auxiliary Power Unit advisory is expected to read within the sample range of 16 to 26 units during descent.

02.140.2 Airfield Notes

During taxi, the First Officer should monitor the Weather Radar selector position before the next phase of flight. If the Fuel Crossfeed is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure.

During landing, the Captain should verify the Fire Detection Loop advisory unless directed otherwise by the Sample Operations Center. The first officer will verify any change in the Fire Detection Loop advisory and advise the other pilot if a discrepancy is observed. If the Autopilot Channel B is inoperative, continue climb only after the Captain has reviewed the associated sample guidance. The relief pilot will announce any change in the Brake Temperature Monitor quantity display and advise the other pilot once the checklist item is complete. The Thrust Reverser switch position that differs from the expected state requires both pilots to verify the condition if a discrepancy is observed.

The captain will record any change in the Speedbrake Handle quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center. If the Landing Gear Indication is inoperative, continue preflight only after the Captain has reviewed the associated sample guidance. The Hydraulic System A selector position that differs from the expected state requires the Captain to announce the condition if a discrepancy is observed.

CAUTION: During engine start, the Captain should verify the Probe Heat selector position if the indication does not stabilize within the sample interval. The captain will record any change in the Speedbrake Handle switch position and advise the other pilot if the indication does not stabilize within the sample interval.

The Standby Instruments status message that differs from the expected state requires the Captain to monitor the condition when the associated caution light remains illuminated. Refer to the related topic for additional sample context. The relief pilot will cross-check any change in the Stall Warning advisory and advise the other pilot if the indication does not stabilize within the sample interval.

The captain will announce any change in the Traffic Advisory Display annunciation and advise the other pilot when conditions permit. The wording here is placeholder content shaped like a procedure, not a procedure. If the Landing Gear Indication is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance. The Probe Heat advisory is expected to read within the sample range of 89 to 98 units during a turnaround.

NOTE: The pilot monitoring will confirm any change in the Stall Warning selector position and advise the other pilot when operating at a sample station without ground power.

Condition	Sample value	Remarks
Autobrake Selector status message	35 units	Monitor
Traffic Advisory Display quantity display	98 units	Normal
Autobrake Selector advisory	54 units	Normal
Pack Temperature Control annunciation	62 units	Monitor
Primary Electrical Bus quantity display	59 units	Advisory only
Hydraulic System A quantity display	59 units	Normal
Landing Gear Indication selector position	16 units	Advisory only

02.140.3 Ground Handling

If the Ground Proximity Monitor is inoperative, continue taxi only after the relief pilot has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. The Wing Anti-Ice selector position is expected to read within the sample range of 98 to 110 units during climb.

Condition	Sample value	Remarks
Brake Temperature Monitor quantity display	68 units	Refer to related topic

Cargo Smoke Detection switch position	40 units	Monitor
Autopilot Channel B advisory	22 units	Monitor
Wing Anti-Ice annunciation	76 units	Monitor
Thrust Reverser switch position	11 units	Refer to related topic

During parking, the pilot flying should cross-check the Autopilot Channel A annunciation when operating at a sample station without ground power. The Center Tank Pumps status message that differs from the expected state requires both pilots to verify the condition when operating at a sample station without ground power. The Autothrottle switch position that differs from the expected state requires the First Officer to brief the condition if a discrepancy is observed. The Auxiliary Power Unit quantity display that differs from the expected state requires the pilot monitoring to brief the condition if the indication does not stabilize within the sample interval.

CAUTION: During parking, both pilots should brief the Oxygen Distribution switch position when conditions permit. The Flap Position Indication selector position is expected to read within the sample range of 55 to 60 units during preflight.

During takeoff, the First Officer should verify the Fire Detection Loop status message unless directed otherwise by the Sample Operations Center. Refer to the related topic for additional sample context. The relief pilot will record any change in the Autothrottle status message and advise the other pilot before the next phase of flight. The Nosewheel Steering advisory is expected to read within the sample range of 56 to 60 units during an extended ground delay.

CAUTION: The wording here is placeholder content shaped like a procedure, not a procedure. The Cockpit Voice Recorder selector position that differs from the expected state requires the pilot monitoring to cross-check the condition unless directed otherwise by the Sample Operations Center.

NOTE: The captain will select any change in the Stall Warning quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center. The Center Tank Pumps switch position is expected to read within the sample range of 21 to 31 units during a diversion.

Condition	Sample value	Remarks
Oxygen Distribution selector position	45 units	Normal
Transponder selector position	3 units	Monitor
Autobrake Selector annunciation	83 units	Monitor

CAUTION: The Autobrake Selector quantity display is expected to read within the sample range of 38 to 44 units during descent.

02.140.4 Local Procedures

Refer to the related topic for additional sample context. The pilot monitoring will record any change in the Auxiliary Power Unit annunciation and advise the other pilot if the indication does not stabilize within the sample interval. The Speedbrake Handle annunciation that differs from the expected state requires the Captain to announce the condition when the associated caution light remains illuminated.

Both pilots will verify any change in the Hydraulic System B advisory and advise the other pilot when conditions permit. Refer to the related topic for additional sample context. The Engine Anti-Ice switch position is expected to read within the sample range of 33 to 41 units during descent. The Oxygen Distribution advisory is expected to read within the sample range of 35 to 41 units during a maintenance-requested ground run. During engine start, the pilot flying should cross-check the Transponder status message before the next phase of flight.

If the Stall Warning is inoperative, continue approach only after the pilot monitoring has reviewed the associated sample guidance. If the Auxiliary Power Unit is inoperative, continue parking only after the pilot monitoring has reviewed the associated sample guidance. The Transponder indication is expected to read within the sample range of 10 to 16 units during parking. The Traffic Advisory Display selector position that differs from the expected state

requires the pilot monitoring to confirm the condition when operating at a sample station without ground power. The Landing Gear Indication quantity display is expected to read within the sample range of 40 to 51 units during taxi. During approach, the pilot monitoring should monitor the Flap Position Indication advisory when the associated caution light remains illuminated.

If the Landing Gear Indication is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance. During preflight, the Captain should cross-check the Bleed Air Supply status message unless directed otherwise by the Sample Operations Center. During an extended ground delay, the First Officer should monitor the Bleed Air Supply annunciation if the indication does not stabilize within the sample interval. During approach, the Captain should confirm the Autobrake Selector selector position if the indication does not stabilize within the sample interval. During engine start, both pilots should announce the Traffic Advisory Display switch position once the checklist item is complete. This text is fictional and exists only to give the prototype realistic volume and structure. See 02.170.3 Ground Handling.

NOTE: Both pilots will monitor any change in the Primary Electrical Bus advisory and advise the other pilot before the next phase of flight. Values in this manual are invented and must not be used for any operational purpose.

NOTE: The Window Heat annunciation that differs from the expected state requires the First Officer to confirm the condition if the indication does not stabilize within the sample interval. The Oxygen Distribution indication is expected to read within the sample range of 20 to 27 units during taxi.

02.150 Sample Station S15

02.150.1 General

The Cockpit Voice Recorder status message that differs from the expected state requires the pilot monitoring to select the condition when operating at a sample station without ground power. The Standby Instruments status message is expected to read within the sample range of 82 to 90 units during cruise. If the Fire Detection Loop is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance. During a turnaround, both pilots should monitor the Wing Anti-Ice indication when conditions permit.

NOTE: The Window Heat switch position that differs from the expected state requires the pilot monitoring to select the condition once the checklist item is complete. The Landing Gear Indication selector position that differs from the expected state requires the First Officer to verify the condition when operating at a sample station without ground power.

CAUTION: The Weather Radar selector position that differs from the expected state requires the pilot flying to cross-check the condition if the indication does not stabilize within the sample interval.

Condition	Sample value	Remarks
Autopilot Channel B advisory	98 units	Normal
Primary Electrical Bus selector position	93 units	Monitor
Autothrottle indication	22 units	Normal
Ground Proximity Monitor selector position	5 units	Refer to related topic
Brake Temperature Monitor status message	79 units	Refer to related topic

During descent, both pilots should brief the Speedbrake Handle selector position when the associated caution light remains illuminated. This text is fictional and exists only to give the prototype realistic volume and structure. The Center Tank Pumps selector position is expected to read within the sample range of 37 to 45 units during descent. If the Flight Management Computer is inoperative, continue preflight only after the pilot monitoring has reviewed the associated sample guidance. If the Wing Anti-Ice is inoperative, continue takeoff only after the First Officer has reviewed the associated sample guidance. If the Bleed Air Supply is inoperative, continue an extended ground delay only after the pilot flying has reviewed the associated sample guidance.

- The Hydraulic System A selector position that differs from the expected state requires the pilot flying to announce the condition before the next phase of flight.
- If the Hydraulic System A is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- Both pilots will verify any change in the Autopilot Channel B advisory and advise the other pilot if the indication does not stabilize within the sample interval.
- Values in this manual are invented and must not be used for any operational purpose.

If the Transponder is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. During a turnaround, the pilot flying should brief the Fuel Crossfeed status message once the checklist item is complete. The Nosewheel Steering switch position is expected to read within the sample range of 97 to 108 units during cruise. Both pilots will cross-check any change in the Wing Anti-Ice selector position and advise the other pilot if a discrepancy is observed. The Thrust Reverser annunciation is expected to read within the sample range of 49 to 59 units during approach.

Condition	Sample value	Remarks
Cockpit Voice Recorder switch position	31 units	Normal
Oxygen Distribution selector position	69 units	Normal
Autopilot Channel B switch position	30 units	Refer to related topic

Both pilots will brief any change in the Oxygen Distribution advisory and advise the other pilot when conditions permit. The captain will announce any change in the Ground Proximity Monitor advisory and advise the other pilot unless directed otherwise by the Sample Operations Center. During approach, the pilot flying should verify the Standby Instruments indication when operating at a sample station without ground power. During taxi, the First Officer should verify the Engine Anti-Ice status message if a discrepancy is observed. See 02.130.2 Airfield Notes.

02.150.2 Airfield Notes

The relief pilot will confirm any change in the Auxiliary Power Unit annunciation and advise the other pilot once the checklist item is complete. If the Center Tank Pumps is inoperative, continue approach only after the relief pilot has reviewed the associated sample guidance. The Standby Instruments switch position that differs from the expected state requires the relief pilot to verify the condition when the associated caution light remains illuminated.

Condition	Sample value	Remarks
Autothrottle advisory	35 units	Monitor
Wing Anti-Ice advisory	21 units	Monitor
Auxiliary Power Unit annunciation	27 units	Monitor

- The Cabin Pressure Controller indication that differs from the expected state requires the First Officer to cross-check the condition before the next phase of flight.
- If the Weather Radar is inoperative, continue preflight only after both pilots has reviewed the associated sample guidance.
- Both pilots will cross-check any change in the Autothrottle indication and advise the other pilot if a discrepancy is observed.
- If the Standby Hydraulic is inoperative, continue taxi only after the First Officer has reviewed the associated sample guidance.

- During approach, the pilot monitoring should select the Speedbrake Handle status message unless directed otherwise by the Sample Operations Center.

NOTE: During climb, the pilot flying should select the Standby Hydraulic indication when the associated caution light remains illuminated.

Refer to the related topic for additional sample context. If the Transponder is inoperative, continue a turnaround only after both pilots has reviewed the associated sample guidance. During a diversion, the First Officer should brief the Nosewheel Steering status message once the checklist item is complete. If the Autobrake Selector is inoperative, continue parking only after the Captain has reviewed the associated sample guidance.

The first officer will select any change in the Brake Temperature Monitor selector position and advise the other pilot unless directed otherwise by the Sample Operations Center. During landing, both pilots should monitor the Weather Radar advisory when conditions permit. The first officer will select any change in the Traffic Advisory Display selector position and advise the other pilot when conditions permit. The Wing Anti-Ice status message that differs from the expected state requires the pilot flying to record the condition before the next phase of flight. The Traffic Advisory Display switch position that differs from the expected state requires both pilots to cross-check the condition when operating at a sample station without ground power.

02.150.3 Ground Handling

The wording here is placeholder content shaped like a procedure, not a procedure. This text is fictional and exists only to give the prototype realistic volume and structure. The first officer will select any change in the Primary Electrical Bus indication and advise the other pilot if the indication does not stabilize within the sample interval. The relief pilot will brief any change in the Traffic Advisory Display status message and advise the other pilot when the associated caution light remains illuminated. The Window Heat indication that differs from the expected state requires the pilot monitoring to select the condition once the checklist item is complete.

The captain will cross-check any change in the Brake Temperature Monitor status message and advise the other pilot if a discrepancy is observed. During a maintenance-requested ground run, both pilots should select the Transponder status message before the next phase of flight. During engine start, the pilot flying should monitor the Window Heat annunciation once the checklist item is complete. The Landing Gear Indication selector position is expected to read within the sample range of 86 to 93 units during descent.

- The wording here is placeholder content shaped like a procedure, not a procedure.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- The pilot monitoring will confirm any change in the Transponder status message and advise the other pilot unless directed otherwise by the Sample Operations Center.
- Values in this manual are invented and must not be used for any operational purpose.

NOTE: If the Cargo Smoke Detection is inoperative, continue taxi only after the First Officer has reviewed the associated sample guidance. Both pilots will record any change in the Standby Instruments annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center.

During an extended ground delay, the relief pilot should record the Oxygen Distribution selector position once the checklist item is complete. During descent, the pilot monitoring should record the Center Tank Pumps advisory if the indication does not stabilize within the sample interval. The Brake Temperature Monitor annunciation that differs from the expected state requires the pilot monitoring to cross-check the condition if a discrepancy is observed.

NOTE: Values in this manual are invented and must not be used for any operational purpose. The wording here is placeholder content shaped like a procedure, not a procedure.

NOTE: If the Standby Hydraulic is inoperative, continue preflight only after the relief pilot has reviewed the associated sample guidance. During parking, the relief pilot should verify the Standby Instruments indication if the indication does not stabilize within the sample interval.

02.150.4 Local Procedures

The Ground Proximity Monitor switch position is expected to read within the sample range of 19 to 27 units during a maintenance-requested ground run. If the Transponder is inoperative, continue descent only after the First Officer has reviewed the associated sample guidance. The Wing Anti-Ice advisory is expected to read within the sample range of 34 to 37 units during preflight.

The Cockpit Voice Recorder annunciation is expected to read within the sample range of 64 to 70 units during climb. The Ground Proximity Monitor quantity display is expected to read within the sample range of 66 to 72 units during engine start. This text is fictional and exists only to give the prototype realistic volume and structure.

This text is fictional and exists only to give the prototype realistic volume and structure. The Nosewheel Steering quantity display that differs from the expected state requires the pilot monitoring to brief the condition before the next phase of flight. The Engine Anti-Ice annunciation that differs from the expected state requires the First Officer to cross-check the condition unless directed otherwise by the Sample Operations Center.

- During preflight, the Captain should announce the Autothrottle quantity display when the associated caution light remains illuminated.
- During landing, the Captain should select the Wing Anti-Ice annunciation if the indication does not stabilize within the sample interval.
- If the Cabin Pressure Controller is inoperative, continue a turnaround only after the First Officer has reviewed the associated sample guidance.
- During cruise, the pilot flying should announce the Traffic Advisory Display annunciation when operating at a sample station without ground power.
- During climb, both pilots should verify the Fuel Crossfeed selector position once the checklist item is complete.

CAUTION: The Traffic Advisory Display annunciation is expected to read within the sample range of 53 to 64 units during a turnaround.

During an extended ground delay, the relief pilot should verify the Speedbrake Handle annunciation if a discrepancy is observed. If the Primary Electrical Bus is inoperative, continue taxi only after the Captain has reviewed the associated sample guidance. If the Primary Electrical Bus is inoperative, continue taxi only after both pilots has reviewed the associated sample guidance. The Cockpit Voice Recorder selector position is expected to read within the sample range of 31 to 38 units during a diversion. During an extended ground delay, the First Officer should confirm the Standby Instruments indication once the checklist item is complete.

The Nosewheel Steering quantity display is expected to read within the sample range of 11 to 18 units during takeoff. The pilot flying will confirm any change in the Standby Hydraulic status message and advise the other pilot unless directed otherwise by the Sample Operations Center. If the Transponder is inoperative, continue a diversion only after the pilot monitoring has reviewed the associated sample guidance.

The relief pilot will verify any change in the Brake Temperature Monitor quantity display and advise the other pilot once the checklist item is complete. Both pilots will select any change in the Autothrottle status message and advise the other pilot when the associated caution light remains illuminated. Refer to the related topic for additional sample context. The Window Heat indication is expected to read within the sample range of 45 to 57 units during landing. If the Speedbrake Handle is inoperative, continue preflight only after the pilot monitoring has reviewed the associated sample guidance. During a diversion, the Captain should monitor the Brake Temperature Monitor indication once the checklist item is complete. See 03.180.2 Airfield Notes.

02.160 Sample Station S16

02.160.1 General

The relief pilot will verify any change in the Cabin Pressure Controller selector position and advise the other pilot before the next phase of flight. If the Speedbrake Handle is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance. The relief pilot will announce any change in the Nosewheel Steering switch position and advise the other pilot unless directed otherwise by the Sample Operations Center.

If the Autopilot Channel A is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance. During landing, the Captain should record the Cockpit Voice Recorder selector position when operating at a sample station without ground power. The Transponder quantity display that differs from the expected state requires the Captain to brief the condition if the indication does not stabilize within the sample interval. During a maintenance-requested ground run, the pilot flying should monitor the Autobrake Selector advisory if the indication does not stabilize within the sample interval. If the Engine Anti-Ice is inoperative, continue a maintenance-requested ground run only after the pilot monitoring has reviewed the associated sample guidance. During taxi, the pilot monitoring should select the Brake Temperature Monitor switch position unless directed otherwise by the Sample Operations Center.

The pilot flying will cross-check any change in the Fire Detection Loop switch position and advise the other pilot once the checklist item is complete. During taxi, both pilots should brief the Probe Heat indication if a discrepancy is observed. Values in this manual are invented and must not be used for any operational purpose.

- If the Traffic Advisory Display is inoperative, continue a diversion only after the First Officer has reviewed the associated sample guidance.
- During takeoff, the pilot flying should confirm the Bleed Air Supply status message before the next phase of flight.
- If the Probe Heat is inoperative, continue a maintenance-requested ground run only after the pilot monitoring has reviewed the associated sample guidance.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- If the Primary Electrical Bus is inoperative, continue preflight only after the pilot monitoring has reviewed the associated sample guidance.
- The relief pilot will cross-check any change in the Autopilot Channel B advisory and advise the other pilot when operating at a sample station without ground power.

During descent, the relief pilot should select the Autobrake Selector advisory when operating at a sample station without ground power. Refer to the related topic for additional sample context. During a turnaround, both pilots should confirm the Autothrottle status message when the associated caution light remains illuminated.

Condition	Sample value	Remarks
Probe Heat selector position	77 units	Monitor
Nosewheel Steering indication	13 units	Refer to related topic
Autothrottle annunciation	81 units	Normal
Stall Warning annunciation	14 units	Advisory only
Hydraulic System A switch position	68 units	Monitor
Traffic Advisory Display selector position	52 units	Advisory only
Ground Proximity Monitor selector position	9 units	Monitor

If the Cockpit Voice Recorder is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance. If the Cockpit Voice Recorder is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance. Both pilots will record any change in the Thrust Reverser quantity display and advise the other pilot if the indication does not stabilize within the sample interval. If the Hydraulic System A is inoperative, continue a turnaround only after the First Officer has reviewed the associated sample guidance. The first officer will brief any change in the Ground Proximity Monitor status message and advise the other pilot before the next phase of flight. See 02.180.4 Local Procedures.

02.160.2 Airfield Notes

The Fire Detection Loop advisory is expected to read within the sample range of 97 to 101 units during a maintenance-requested ground run. The Oxygen Distribution advisory is expected to read within the sample range of 19 to 26 units during parking. The captain will verify any change in the Stall Warning switch position and advise the other pilot when conditions permit.

- The Auxiliary Power Unit annunciation is expected to read within the sample range of 93 to 103 units during an extended ground delay.
- If the Weather Radar is inoperative, continue cruise only after both pilots has reviewed the associated sample guidance.
- The pilot flying will monitor any change in the Cockpit Voice Recorder advisory and advise the other pilot when the associated caution light remains illuminated.

The Bleed Air Supply quantity display is expected to read within the sample range of 80 to 86 units during a turnaround. The Auxiliary Power Unit annunciation that differs from the expected state requires the pilot flying to cross-check the condition if the indication does not stabilize within the sample interval. The Autobrake Selector switch position that differs from the expected state requires the First Officer to announce the condition once the checklist item is complete. The pilot flying will record any change in the Flap Position Indication indication and advise the other pilot once the checklist item is complete. The Autopilot Channel B advisory that differs from the expected state requires both pilots to record the condition once the checklist item is complete.

The Standby Hydraulic annunciation that differs from the expected state requires both pilots to monitor the condition when conditions permit. During cruise, the pilot flying should cross-check the Traffic Advisory Display advisory if the indication does not stabilize within the sample interval. The captain will monitor any change in the Probe Heat status message and advise the other pilot before the next phase of flight. The pilot flying will select any change in the Speedbrake Handle selector position and advise the other pilot when operating at a sample station without ground power.

CAUTION: If the Bleed Air Supply is inoperative, continue a diversion only after both pilots has reviewed the associated sample guidance. The Auxiliary Power Unit quantity display is expected to read within the sample range of 95 to 98 units during a maintenance-requested ground run.

During a turnaround, the pilot monitoring should confirm the Cabin Pressure Controller indication when the associated caution light remains illuminated. This text is fictional and exists only to give the prototype realistic volume and structure. Values in this manual are invented and must not be used for any operational purpose. The wording here is placeholder content shaped like a procedure, not a procedure. The Probe Heat annunciation is expected to read within the sample range of 6 to 18 units during cruise. The Flight Management Computer switch position that differs from the expected state requires the relief pilot to record the condition once the checklist item is complete.

The Autobrake Selector switch position is expected to read within the sample range of 4 to 15 units during preflight. If the Primary Electrical Bus is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance. During landing, the pilot monitoring should brief the Cargo Smoke Detection annunciation if the indication does not stabilize within the sample interval. This text is fictional and exists only to give the prototype realistic volume and structure. The Autopilot Channel B annunciation that differs from the expected state requires both pilots to verify the condition when operating at a sample station without ground power.

If the Brake Temperature Monitor is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance. The Weather Radar indication that differs from the expected state requires the First Officer to confirm the condition unless directed otherwise by the Sample Operations Center. The Fuel Crossfeed advisory is expected to read within the sample range of 8 to 12 units during climb. The Flap Position Indication switch position is expected to read within the sample range of 84 to 88 units during landing.

If the Transponder is inoperative, continue cruise only after the First Officer has reviewed the associated sample guidance. Refer to the related topic for additional sample context. The Bleed Air Supply advisory is expected to read within the sample range of 85 to 90 units during taxi. The first officer will select any change in the Transponder

indication and advise the other pilot unless directed otherwise by the Sample Operations Center. During parking, the pilot flying should brief the Wing Anti-Ice selector position if a discrepancy is observed.

02.160.3 Ground Handling

The first officer will select any change in the Standby Instruments status message and advise the other pilot when operating at a sample station without ground power. This text is fictional and exists only to give the prototype realistic volume and structure. The captain will record any change in the Oxygen Distribution status message and advise the other pilot when operating at a sample station without ground power. The pilot monitoring will brief any change in the Hydraulic System A indication and advise the other pilot if a discrepancy is observed.

If the Engine Anti-Ice is inoperative, continue a diversion only after the First Officer has reviewed the associated sample guidance. If the Cockpit Voice Recorder is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance. Refer to the related topic for additional sample context. The first officer will announce any change in the Pack Temperature Control switch position and advise the other pilot when the associated caution light remains illuminated.

Refer to the related topic for additional sample context. Refer to the related topic for additional sample context. During descent, the pilot monitoring should select the Standby Instruments status message when conditions permit. The Pack Temperature Control indication that differs from the expected state requires the pilot flying to verify the condition if the indication does not stabilize within the sample interval. The Ground Proximity Monitor advisory is expected to read within the sample range of 25 to 32 units during climb.

The pilot monitoring will monitor any change in the Speedbrake Handle selector position and advise the other pilot when the associated caution light remains illuminated. The Autopilot Channel A annunciation that differs from the expected state requires the pilot monitoring to confirm the condition before the next phase of flight. The Cabin Pressure Controller annunciation that differs from the expected state requires the pilot flying to verify the condition when operating at a sample station without ground power. The Fire Detection Loop switch position is expected to read within the sample range of 46 to 55 units during an extended ground delay. The Fuel Crossfeed quantity display that differs from the expected state requires the Captain to confirm the condition when the associated caution light remains illuminated. The wording here is placeholder content shaped like a procedure, not a procedure.

NOTE: If the Brake Temperature Monitor is inoperative, continue a turnaround only after the pilot monitoring has reviewed the associated sample guidance.

If the Brake Temperature Monitor is inoperative, continue taxi only after the relief pilot has reviewed the associated sample guidance. The Oxygen Distribution indication that differs from the expected state requires both pilots to select the condition before the next phase of flight. The Auxiliary Power Unit indication is expected to read within the sample range of 81 to 93 units during landing. During climb, the First Officer should record the Window Heat quantity display when operating at a sample station without ground power. The Bleed Air Supply switch position that differs from the expected state requires the relief pilot to verify the condition when the associated caution light remains illuminated. The Landing Gear Indication quantity display that differs from the expected state requires the pilot monitoring to verify the condition if a discrepancy is observed.

02.160.4 Local Procedures

During approach, the Captain should verify the Ground Proximity Monitor status message when operating at a sample station without ground power. The captain will record any change in the Landing Gear Indication switch position and advise the other pilot once the checklist item is complete. The first officer will cross-check any change in the Center Tank Pumps switch position and advise the other pilot when conditions permit. During engine start, the Captain should confirm the Standby Instruments annunciation when the associated caution light remains illuminated.

CAUTION: The Wing Anti-Ice selector position that differs from the expected state requires the pilot flying to select the condition when conditions permit. Values in this manual are invented and must not be used for any operational purpose.

NOTE: The pilot flying will cross-check any change in the Engine Anti-Ice status message and advise the other pilot when operating at a sample station without ground power.

The Weather Radar indication that differs from the expected state requires the pilot monitoring to select the condition when the associated caution light remains illuminated. The pilot monitoring will announce any change in the Cargo Smoke Detection annunciation and advise the other pilot when conditions permit. The Oxygen Distribution indication that differs from the expected state requires the pilot monitoring to announce the condition when the associated caution light remains illuminated. The wording here is placeholder content shaped like a procedure, not a procedure. The first officer will confirm any change in the Flight Management Computer advisory and advise the other pilot when conditions permit. The Transponder selector position that differs from the expected state requires the First Officer to announce the condition if the indication does not stabilize within the sample interval.

NOTE: During cruise, both pilots should announce the Wing Anti-Ice quantity display unless directed otherwise by the Sample Operations Center. The Weather Radar selector position is expected to read within the sample range of 79 to 84 units during a diversion.

Condition	Sample value	Remarks
Wing Anti-Ice advisory	57 units	Advisory only
Cabin Pressure Controller selector position	91 units	Advisory only
Traffic Advisory Display selector position	6 units	Refer to related topic
Hydraulic System B switch position	97 units	Refer to related topic
Cabin Pressure Controller indication	7 units	Advisory only
Stall Warning annunciation	89 units	Refer to related topic

Condition	Sample value	Remarks
Stall Warning annunciation	3 units	Refer to related topic
Autopilot Channel B indication	32 units	Advisory only
Hydraulic System B quantity display	72 units	Normal
Cockpit Voice Recorder status message	50 units	Monitor
Autobrake Selector advisory	19 units	Monitor

NOTE: During preflight, both pilots should cross-check the Bleed Air Supply status message when operating at a sample station without ground power.

If the Cockpit Voice Recorder is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance. The first officer will confirm any change in the Bleed Air Supply selector position and advise the other pilot unless directed otherwise by the Sample Operations Center. The Brake Temperature Monitor indication that differs from the expected state requires the relief pilot to monitor the condition unless directed otherwise by the Sample Operations Center. If the Flight Management Computer is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance.

02.170 Sample Station S17

02.170.1 General

During approach, the pilot flying should brief the Standby Instruments quantity display when conditions permit. During climb, the First Officer should confirm the Flight Management Computer quantity display if a discrepancy is observed. This text is fictional and exists only to give the prototype realistic volume and structure. The Thrust Reverser indication that differs from the expected state requires the relief pilot to brief the condition before the next phase of flight. The Fuel Crossfeed quantity display is expected to read within the sample range of 27 to 31 units during cruise. The Bleed Air Supply switch position that differs from the expected state requires the First Officer to cross-check the condition when conditions permit.

NOTE: If the Probe Heat is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance. The Autopilot Channel A annunciation is expected to read within the sample range of 24 to 29 units during a maintenance-requested ground run.

CAUTION: The wording here is placeholder content shaped like a procedure, not a procedure.

NOTE: The Transponder advisory that differs from the expected state requires the pilot flying to monitor the condition when the associated caution light remains illuminated. During cruise, both pilots should brief the Transponder quantity display if a discrepancy is observed.

The Hydraulic System B annunciation is expected to read within the sample range of 72 to 82 units during a turnaround. If the Fuel Crossfeed is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. The captain will select any change in the Primary Electrical Bus annunciation and advise the other pilot when the associated caution light remains illuminated. If the Standby Instruments is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance. The relief pilot will confirm any change in the Cargo Smoke Detection annunciation and advise the other pilot when operating at a sample station without ground power.

If the Auxiliary Power Unit is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance. The Wing Anti-Ice quantity display that differs from the expected state requires both pilots to cross-check the condition once the checklist item is complete. The Thrust Reverser quantity display is expected to read within the sample range of 87 to 96 units during an extended ground delay. If the Pack Temperature Control is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance.

The Standby Instruments annunciation is expected to read within the sample range of 88 to 96 units during a diversion. The Autopilot Channel A status message that differs from the expected state requires the Captain to monitor the condition when the associated caution light remains illuminated. The wording here is placeholder content shaped like a procedure, not a procedure. If the Autopilot Channel B is inoperative, continue takeoff only after the First Officer has reviewed the associated sample guidance.

Condition	Sample value	Remarks
Thrust Reverser switch position	70 units	Monitor
Fire Detection Loop switch position	94 units	Normal
Hydraulic System A selector position	78 units	Refer to related topic
Engine Anti-Ice status message	94 units	Refer to related topic
Nosewheel Steering selector position	91 units	Normal

The wording here is placeholder content shaped like a procedure, not a procedure. The Transponder quantity display that differs from the expected state requires the pilot monitoring to brief the condition when conditions permit. The Autopilot Channel A status message that differs from the expected state requires the pilot monitoring to select the condition when conditions permit. If the Ground Proximity Monitor is inoperative, continue approach only after both pilots has reviewed the associated sample guidance. During a diversion, both pilots should select the Standby Instruments indication when operating at a sample station without ground power. Refer to the related topic for additional sample context.

02.170.2 Airfield Notes

If the Oxygen Distribution is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance. If the Fire Detection Loop is inoperative, continue landing only after the First Officer has reviewed the associated sample guidance. The pilot monitoring will record any change in the Engine Anti-Ice selector position and advise the other pilot before the next phase of flight. If the Standby Hydraulic is inoperative, continue a diversion only after the First Officer has reviewed the associated sample guidance. Refer to the related topic for additional sample context.

If the Hydraulic System A is inoperative, continue landing only after both pilots has reviewed the associated sample guidance. During approach, both pilots should brief the Transponder annunciation if the indication does not stabilize within the sample interval. The wording here is placeholder content shaped like a procedure, not a procedure.

CAUTION: The Hydraulic System B status message is expected to read within the sample range of 27 to 38 units during cruise.

CAUTION: If the Oxygen Distribution is inoperative, continue parking only after the pilot monitoring has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure.

The Autothrottle annunciation is expected to read within the sample range of 12 to 22 units during an extended ground delay. During climb, both pilots should select the Probe Heat advisory once the checklist item is complete. If the Cabin Pressure Controller is inoperative, continue approach only after both pilots has reviewed the associated sample guidance. During cruise, the First Officer should record the Traffic Advisory Display quantity display unless directed otherwise by the Sample Operations Center. During a turnaround, the pilot monitoring should record the Engine Anti-Ice advisory if the indication does not stabilize within the sample interval. This text is fictional and exists only to give the prototype realistic volume and structure.

02.170.3 Ground Handling

The Thrust Reverser advisory that differs from the expected state requires the First Officer to monitor the condition when the associated caution light remains illuminated. During engine start, the pilot monitoring should record the Autothrottle advisory when the associated caution light remains illuminated. The Autopilot Channel A annunciation is expected to read within the sample range of 91 to 94 units during taxi. The Autopilot Channel B status message that differs from the expected state requires the Captain to verify the condition once the checklist item is complete.

If the Standby Instruments is inoperative, continue taxi only after the Captain has reviewed the associated sample guidance. The Speedbrake Handle switch position that differs from the expected state requires both pilots to confirm the condition when operating at a sample station without ground power. If the Cabin Pressure Controller is inoperative, continue a diversion only after both pilots has reviewed the associated sample guidance.

During taxi, the relief pilot should record the Nosewheel Steering selector position if the indication does not stabilize within the sample interval. The first officer will verify any change in the Standby Hydraulic status message and advise the other pilot before the next phase of flight. Values in this manual are invented and must not be used for any operational purpose. See 03.40.2 Airfield Notes.

NOTE: If the Oxygen Distribution is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance. If the Transponder is inoperative, continue taxi only after the First Officer has reviewed the associated sample guidance.

NOTE: During preflight, the pilot flying should monitor the Cargo Smoke Detection annunciation once the checklist item is complete. Values in this manual are invented and must not be used for any operational purpose.

02.170.4 Local Procedures

The Stall Warning annunciation that differs from the expected state requires the First Officer to brief the condition if a discrepancy is observed. The pilot monitoring will record any change in the Traffic Advisory Display switch position and advise the other pilot if a discrepancy is observed. If the Autopilot Channel A is inoperative, continue landing only after both pilots has reviewed the associated sample guidance. During takeoff, the First Officer should verify the Engine Anti-Ice advisory if the indication does not stabilize within the sample interval. The pilot flying will record any change in the Cabin Pressure Controller quantity display and advise the other pilot when operating at a sample station without ground power. If the Oxygen Distribution is inoperative, continue approach only after the pilot flying has reviewed the associated sample guidance.

- The Flap Position Indication advisory is expected to read within the sample range of 5 to 8 units during preflight.
- This text is fictional and exists only to give the prototype realistic volume and structure.

- During takeoff, the relief pilot should record the Speedbrake Handle selector position if the indication does not stabilize within the sample interval.
- The Fuel Crossfeed selector position is expected to read within the sample range of 14 to 20 units during engine start.
- The Pack Temperature Control selector position is expected to read within the sample range of 66 to 70 units during landing.

Condition	Sample value	Remarks
Hydraulic System A switch position	68 units	Refer to related topic
Auxiliary Power Unit quantity display	1 units	Refer to related topic
Autothrottle advisory	13 units	Normal
Fuel Crossfeed annunciation	27 units	Normal

- During parking, the First Officer should monitor the Standby Instruments advisory if a discrepancy is observed.
- If the Engine Anti-Ice is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance.
- Refer to the related topic for additional sample context.
- The Flap Position Indication indication that differs from the expected state requires the pilot flying to record the condition if a discrepancy is observed.

If the Oxygen Distribution is inoperative, continue a diversion only after both pilots has reviewed the associated sample guidance. The captain will select any change in the Stall Warning annunciation and advise the other pilot when conditions permit. If the Flight Management Computer is inoperative, continue a turnaround only after the pilot monitoring has reviewed the associated sample guidance. If the Probe Heat is inoperative, continue descent only after the Captain has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure.

The Flap Position Indication quantity display is expected to read within the sample range of 39 to 47 units during parking. During a turnaround, the Captain should record the Bleed Air Supply switch position when operating at a sample station without ground power. The Pack Temperature Control quantity display that differs from the expected state requires both pilots to verify the condition when conditions permit. If the Cockpit Voice Recorder is inoperative, continue engine start only after the Captain has reviewed the associated sample guidance. The Weather Radar indication is expected to read within the sample range of 26 to 31 units during cruise.

If the Engine Anti-Ice is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance. If the Cargo Smoke Detection is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance. During a maintenance-requested ground run, the relief pilot should verify the Probe Heat quantity display before the next phase of flight. The Wing Anti-Ice annunciation that differs from the expected state requires the Captain to cross-check the condition when the associated caution light remains illuminated.

The Flap Position Indication status message that differs from the expected state requires the Captain to cross-check the condition if the indication does not stabilize within the sample interval. Values in this manual are invented and must not be used for any operational purpose. The Cabin Pressure Controller switch position that differs from the expected state requires the First Officer to monitor the condition before the next phase of flight. This text is fictional and exists only to give the prototype realistic volume and structure.

02.180 Sample Station S18

02.180.1 General

The wording here is placeholder content shaped like a procedure, not a procedure. Refer to the related topic for additional sample context. The Oxygen Distribution indication that differs from the expected state requires both pilots to verify the condition when operating at a sample station without ground power.

If the Cabin Pressure Controller is inoperative, continue a diversion only after the relief pilot has reviewed the associated sample guidance. During landing, the relief pilot should record the Landing Gear Indication quantity display when conditions permit. The first officer will brief any change in the Standby Hydraulic quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center. The Probe Heat advisory that differs from the expected state requires the pilot flying to cross-check the condition unless directed otherwise by the Sample Operations Center.

- Refer to the related topic for additional sample context.
- The pilot flying will announce any change in the Pack Temperature Control selector position and advise the other pilot before the next phase of flight.
- The Thrust Reverser status message is expected to read within the sample range of 93 to 100 units during descent.

During engine start, both pilots should confirm the Primary Electrical Bus advisory if the indication does not stabilize within the sample interval. The Brake Temperature Monitor advisory is expected to read within the sample range of 97 to 103 units during preflight. The Thrust Reverser annunciation is expected to read within the sample range of 16 to 22 units during descent. The Autopilot Channel B quantity display that differs from the expected state requires both pilots to announce the condition unless directed otherwise by the Sample Operations Center. The Transponder selector position that differs from the expected state requires the Captain to announce the condition when conditions permit.

During parking, the First Officer should record the Cockpit Voice Recorder selector position unless directed otherwise by the Sample Operations Center. The Fuel Crossfeed switch position that differs from the expected state requires the pilot flying to cross-check the condition if the indication does not stabilize within the sample interval. The captain will announce any change in the Pack Temperature Control annunciation and advise the other pilot when operating at a sample station without ground power.

NOTE: This text is fictional and exists only to give the prototype realistic volume and structure.

02.180.2 Airfield Notes

Both pilots will confirm any change in the Stall Warning advisory and advise the other pilot once the checklist item is complete. During cruise, the relief pilot should verify the Standby Hydraulic quantity display unless directed otherwise by the Sample Operations Center. The Standby Hydraulic advisory is expected to read within the sample range of 23 to 35 units during descent.

NOTE: The Oxygen Distribution status message that differs from the expected state requires both pilots to confirm the condition once the checklist item is complete. Refer to the related topic for additional sample context.

The Cabin Pressure Controller selector position that differs from the expected state requires both pilots to monitor the condition if the indication does not stabilize within the sample interval. The Oxygen Distribution status message that differs from the expected state requires the Captain to brief the condition if a discrepancy is observed. The Flap Position Indication indication that differs from the expected state requires the First Officer to select the condition when operating at a sample station without ground power. The Wing Anti-Ice annunciation that differs from the expected state requires the relief pilot to verify the condition before the next phase of flight.

Refer to the related topic for additional sample context. The Wing Anti-Ice advisory that differs from the expected state requires the pilot flying to record the condition when operating at a sample station without ground power. During an extended ground delay, both pilots should announce the Speedbrake Handle selector position when conditions permit. If the Probe Heat is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance. The Autobrake Selector annunciation that differs from the expected state requires the pilot flying to verify the condition before the next phase of flight. The Primary Electrical Bus selector position that differs from the

expected state requires the pilot flying to brief the condition if the indication does not stabilize within the sample interval.

NOTE: The captain will select any change in the Center Tank Pumps selector position and advise the other pilot when conditions permit.

This text is fictional and exists only to give the prototype realistic volume and structure. During cruise, both pilots should announce the Pack Temperature Control switch position before the next phase of flight. If the Speedbrake Handle is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance.

During a diversion, the Captain should brief the Oxygen Distribution quantity display when the associated caution light remains illuminated. The captain will monitor any change in the Flap Position Indication quantity display and advise the other pilot before the next phase of flight. The Fuel Crossfeed quantity display is expected to read within the sample range of 89 to 94 units during a maintenance-requested ground run.

NOTE: During a maintenance-requested ground run, the pilot monitoring should cross-check the Ground Proximity Monitor advisory unless directed otherwise by the Sample Operations Center.

02.180.3 Ground Handling

Both pilots will confirm any change in the Cabin Pressure Controller advisory and advise the other pilot if the indication does not stabilize within the sample interval. The Transponder switch position that differs from the expected state requires both pilots to announce the condition once the checklist item is complete. If the Standby Hydraulic is inoperative, continue preflight only after the Captain has reviewed the associated sample guidance.

CAUTION: The Oxygen Distribution indication that differs from the expected state requires both pilots to select the condition when operating at a sample station without ground power.

- The captain will record any change in the Hydraulic System A selector position and advise the other pilot if the indication does not stabilize within the sample interval.
- During a maintenance-requested ground run, the pilot flying should verify the Ground Proximity Monitor switch position when the associated caution light remains illuminated.
- The pilot monitoring will confirm any change in the Autopilot Channel B selector position and advise the other pilot if the indication does not stabilize within the sample interval.
- The first officer will brief any change in the Wing Anti-Ice selector position and advise the other pilot when the associated caution light remains illuminated.
- If the Standby Hydraulic is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance.

The Flap Position Indication quantity display is expected to read within the sample range of 95 to 98 units during parking. The captain will confirm any change in the Cargo Smoke Detection advisory and advise the other pilot when the associated caution light remains illuminated. The Center Tank Pumps selector position is expected to read within the sample range of 60 to 66 units during climb.

The Hydraulic System B selector position is expected to read within the sample range of 4 to 12 units during climb. The Standby Hydraulic selector position that differs from the expected state requires the First Officer to confirm the condition when operating at a sample station without ground power. This text is fictional and exists only to give the prototype realistic volume and structure. The first officer will select any change in the Cargo Smoke Detection annunciation and advise the other pilot before the next phase of flight. Refer to the related topic for additional sample context. The Oxygen Distribution indication that differs from the expected state requires the relief pilot to verify the condition if the indication does not stabilize within the sample interval.

NOTE: The wording here is placeholder content shaped like a procedure, not a procedure.

02.180.4 Local Procedures

The Center Tank Pumps annunciation that differs from the expected state requires both pilots to confirm the condition when conditions permit. During approach, the First Officer should record the Standby Instruments annunciation unless directed otherwise by the Sample Operations Center. Both pilots will cross-check any change in the Cargo Smoke Detection status message and advise the other pilot before the next phase of flight. During a turnaround, the Captain should cross-check the Traffic Advisory Display status message unless directed otherwise by the Sample Operations Center.

If the Auxiliary Power Unit is inoperative, continue descent only after the Captain has reviewed the associated sample guidance. The Brake Temperature Monitor switch position is expected to read within the sample range of 55 to 64 units during an extended ground delay. During a diversion, the pilot monitoring should cross-check the Pack Temperature Control selector position unless directed otherwise by the Sample Operations Center. The Wing Anti-Ice advisory is expected to read within the sample range of 54 to 57 units during an extended ground delay. Refer to the related topic for additional sample context. The Center Tank Pumps selector position is expected to read within the sample range of 42 to 53 units during landing.

Condition	Sample value	Remarks
Engine Anti-Ice selector position	38 units	Monitor
Primary Electrical Bus advisory	25 units	Advisory only
Primary Electrical Bus status message	68 units	Advisory only

Values in this manual are invented and must not be used for any operational purpose. During a diversion, the pilot monitoring should select the Standby Hydraulic advisory once the checklist item is complete. The Probe Heat status message that differs from the expected state requires the Captain to verify the condition before the next phase of flight. If the Standby Hydraulic is inoperative, continue engine start only after the pilot monitoring has reviewed the associated sample guidance. During a turnaround, the First Officer should brief the Cargo Smoke Detection advisory unless directed otherwise by the Sample Operations Center.

The captain will record any change in the Hydraulic System A quantity display and advise the other pilot before the next phase of flight. The Autopilot Channel A selector position that differs from the expected state requires the relief pilot to monitor the condition when the associated caution light remains illuminated. The wording here is placeholder content shaped like a procedure, not a procedure. The pilot monitoring will record any change in the Hydraulic System A annunciation and advise the other pilot if the indication does not stabilize within the sample interval.

The Weather Radar quantity display that differs from the expected state requires the Captain to confirm the condition if the indication does not stabilize within the sample interval. The Oxygen Distribution switch position that differs from the expected state requires the Captain to confirm the condition once the checklist item is complete. During taxi, the pilot flying should announce the Brake Temperature Monitor switch position when the associated caution light remains illuminated. The Brake Temperature Monitor annunciation that differs from the expected state requires the Captain to confirm the condition when the associated caution light remains illuminated. Both pilots will announce any change in the Ground Proximity Monitor annunciation and advise the other pilot when conditions permit. During engine start, both pilots should announce the Fuel Crossfeed quantity display if a discrepancy is observed.

If the Engine Anti-Ice is inoperative, continue engine start only after the Captain has reviewed the associated sample guidance. The Oxygen Distribution selector position is expected to read within the sample range of 78 to 86 units during a diversion. The Standby Hydraulic quantity display is expected to read within the sample range of 80 to 84 units during climb. During climb, both pilots should monitor the Center Tank Pumps selector position when operating at a sample station without ground power.

02.190 Sample Station S19

02.190.1 General

The Autopilot Channel B indication is expected to read within the sample range of 29 to 37 units during engine start. Refer to the related topic for additional sample context. The pilot flying will record any change in the Cockpit Voice

Recorder annunciation and advise the other pilot when the associated caution light remains illuminated. The Autothrottle advisory that differs from the expected state requires both pilots to brief the condition if a discrepancy is observed. If the Wing Anti-Ice is inoperative, continue climb only after the pilot flying has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure.

Refer to the related topic for additional sample context. The first officer will select any change in the Flap Position Indication advisory and advise the other pilot unless directed otherwise by the Sample Operations Center. If the Autothrottle is inoperative, continue an extended ground delay only after the pilot flying has reviewed the associated sample guidance. The Autothrottle annunciation is expected to read within the sample range of 7 to 14 units during takeoff. If the Auxiliary Power Unit is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance. If the Center Tank Pumps is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance.

Condition	Sample value	Remarks
Standby Instruments switch position	75 units	Monitor
Cockpit Voice Recorder advisory	76 units	Advisory only
Probe Heat annunciation	46 units	Refer to related topic
Weather Radar indication	48 units	Normal
Engine Anti-Ice quantity display	58 units	Normal

The Brake Temperature Monitor quantity display that differs from the expected state requires the relief pilot to record the condition if a discrepancy is observed. During approach, the Captain should cross-check the Traffic Advisory Display quantity display when the associated caution light remains illuminated. The captain will verify any change in the Center Tank Pumps status message and advise the other pilot if a discrepancy is observed. The Bleed Air Supply switch position is expected to read within the sample range of 33 to 44 units during approach. If the Brake Temperature Monitor is inoperative, continue a turnaround only after the pilot monitoring has reviewed the associated sample guidance. During landing, the relief pilot should monitor the Brake Temperature Monitor switch position when the associated caution light remains illuminated.

During landing, the relief pilot should announce the Autopilot Channel A annunciation unless directed otherwise by the Sample Operations Center. Refer to the related topic for additional sample context. The Flap Position Indication selector position is expected to read within the sample range of 39 to 42 units during landing. During parking, the pilot monitoring should monitor the Fuel Crossfeed advisory when conditions permit. See 02.150.3 Ground Handling.

Condition	Sample value	Remarks
Flight Management Computer advisory	20 units	Advisory only
Window Heat switch position	60 units	Normal
Speedbrake Handle annunciation	84 units	Normal
Stall Warning switch position	88 units	Advisory only
Cockpit Voice Recorder annunciation	63 units	Refer to related topic
Thrust Reverser indication	8 units	Monitor
Autopilot Channel A advisory	61 units	Monitor

02.190.2 Airfield Notes

If the Autopilot Channel A is inoperative, continue a diversion only after the First Officer has reviewed the associated sample guidance. During taxi, the First Officer should brief the Oxygen Distribution switch position when operating at a sample station without ground power. During parking, the pilot monitoring should monitor the Fuel Crossfeed quantity display when conditions permit. The Standby Hydraulic status message that differs from the expected state requires the relief pilot to select the condition before the next phase of flight. Values in this manual are invented and must not be used for any operational purpose.

The Autopilot Channel B quantity display is expected to read within the sample range of 76 to 87 units during an extended ground delay. During a diversion, the relief pilot should verify the Center Tank Pumps annunciation once the checklist item is complete. During taxi, the relief pilot should verify the Auxiliary Power Unit selector position when operating at a sample station without ground power. During approach, both pilots should monitor the Oxygen Distribution indication when operating at a sample station without ground power. The Oxygen Distribution switch position that differs from the expected state requires the relief pilot to brief the condition if a discrepancy is observed. The relief pilot will cross-check any change in the Engine Anti-Ice selector position and advise the other pilot before the next phase of flight.

Values in this manual are invented and must not be used for any operational purpose. Refer to the related topic for additional sample context. The Cabin Pressure Controller quantity display that differs from the expected state requires the pilot flying to confirm the condition if a discrepancy is observed.

If the Oxygen Distribution is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance. If the Autobrake Selector is inoperative, continue preflight only after the Captain has reviewed the associated sample guidance. If the Stall Warning is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure.

Condition	Sample value	Remarks
Cabin Pressure Controller indication	72 units	Monitor
Autopilot Channel A status message	31 units	Normal
Oxygen Distribution advisory	91 units	Normal

02.190.3 Ground Handling

The wording here is placeholder content shaped like a procedure, not a procedure. The Auxiliary Power Unit quantity display that differs from the expected state requires both pilots to verify the condition once the checklist item is complete. The Fuel Crossfeed indication that differs from the expected state requires the relief pilot to announce the condition when conditions permit. If the Landing Gear Indication is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance. If the Fire Detection Loop is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance. The pilot flying will record any change in the Cargo Smoke Detection switch position and advise the other pilot unless directed otherwise by the Sample Operations Center.

If the Pack Temperature Control is inoperative, continue parking only after the Captain has reviewed the associated sample guidance. The pilot flying will monitor any change in the Fire Detection Loop status message and advise the other pilot when the associated caution light remains illuminated. During approach, the Captain should verify the Wing Anti-Ice indication when conditions permit.

NOTE: The relief pilot will announce any change in the Cockpit Voice Recorder status message and advise the other pilot once the checklist item is complete.

If the Autopilot Channel A is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance. The captain will confirm any change in the Cockpit Voice Recorder quantity display and advise the other pilot when operating at a sample station without ground power. The Flight Management Computer selector position that differs from the expected state requires the First Officer to brief the condition if a discrepancy is observed.

Condition	Sample value	Remarks
Traffic Advisory Display status message	5 units	Refer to related topic
Fire Detection Loop selector position	96 units	Advisory only
Cargo Smoke Detection selector position	90 units	Advisory only
Autopilot Channel B switch position	59 units	Refer to related topic

Transponder indication	96 units	Monitor
Hydraulic System A quantity display	4 units	Advisory only
Hydraulic System B advisory	68 units	Normal

NOTE: If the Traffic Advisory Display is inoperative, continue a turnaround only after the pilot monitoring has reviewed the associated sample guidance. During preflight, the relief pilot should brief the Autothrottle status message before the next phase of flight.

The Ground Proximity Monitor annunciation that differs from the expected state requires the relief pilot to select the condition once the checklist item is complete. During a turnaround, the Captain should record the Standby Hydraulic selector position when conditions permit. The Speedbrake Handle quantity display that differs from the expected state requires the pilot monitoring to announce the condition when the associated caution light remains illuminated. Refer to the related topic for additional sample context. During a diversion, the pilot monitoring should cross-check the Stall Warning quantity display before the next phase of flight. If the Autothrottle is inoperative, continue an extended ground delay only after the pilot flying has reviewed the associated sample guidance.

CAUTION: If the Thrust Reverser is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance.

CAUTION: The Fuel Crossfeed indication is expected to read within the sample range of 93 to 105 units during cruise.

02.190.4 Local Procedures

The Autothrottle advisory that differs from the expected state requires both pilots to brief the condition if the indication does not stabilize within the sample interval. If the Standby Instruments is inoperative, continue a diversion only after both pilots has reviewed the associated sample guidance. The Traffic Advisory Display indication is expected to read within the sample range of 11 to 22 units during climb.

The first officer will record any change in the Thrust Reverser selector position and advise the other pilot if a discrepancy is observed. The Probe Heat advisory is expected to read within the sample range of 93 to 96 units during approach. The Flap Position Indication selector position that differs from the expected state requires the Captain to announce the condition unless directed otherwise by the Sample Operations Center. During engine start, both pilots should monitor the Center Tank Pumps quantity display before the next phase of flight. Refer to the related topic for additional sample context. During a maintenance-requested ground run, the relief pilot should announce the Autobrake Selector quantity display when conditions permit.

- The Engine Anti-Ice advisory that differs from the expected state requires the relief pilot to announce the condition once the checklist item is complete.
- If the Wing Anti-Ice is inoperative, continue an extended ground delay only after the pilot flying has reviewed the associated sample guidance.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- If the Fire Detection Loop is inoperative, continue engine start only after the pilot flying has reviewed the associated sample guidance.
- The Probe Heat annunciation is expected to read within the sample range of 4 to 13 units during parking.

Values in this manual are invented and must not be used for any operational purpose. Refer to the related topic for additional sample context. If the Cargo Smoke Detection is inoperative, continue a maintenance-requested ground run only after the pilot monitoring has reviewed the associated sample guidance.

Condition	Sample value	Remarks
Cargo Smoke Detection indication	29 units	Monitor
Wing Anti-Ice quantity display	31 units	Refer to related topic

Nosewheel Steering status message	85 units	Normal
Landing Gear Indication quantity display	41 units	Monitor
Pack Temperature Control advisory	28 units	Refer to related topic
Window Heat advisory	80 units	Monitor
Autobrake Selector selector position	70 units	Refer to related topic

The Brake Temperature Monitor selector position that differs from the expected state requires the pilot monitoring to monitor the condition if the indication does not stabilize within the sample interval. The Transponder switch position that differs from the expected state requires both pilots to monitor the condition if the indication does not stabilize within the sample interval. The Probe Heat switch position is expected to read within the sample range of 63 to 67 units during approach. The Nosewheel Steering advisory is expected to read within the sample range of 18 to 29 units during approach. This text is fictional and exists only to give the prototype realistic volume and structure. The captain will confirm any change in the Autothrottle indication and advise the other pilot once the checklist item is complete.

Values in this manual are invented and must not be used for any operational purpose. If the Window Heat is inoperative, continue engine start only after the relief pilot has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. The relief pilot will announce any change in the Hydraulic System A quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center.

Condition	Sample value	Remarks
Ground Proximity Monitor status message	60 units	Normal
Landing Gear Indication advisory	8 units	Normal
Weather Radar advisory	4 units	Monitor
Wing Anti-Ice annunciation	69 units	Refer to related topic

The Fuel Crossfeed switch position that differs from the expected state requires both pilots to announce the condition if the indication does not stabilize within the sample interval. The Standby Hydraulic indication that differs from the expected state requires the pilot monitoring to cross-check the condition if a discrepancy is observed. If the Brake Temperature Monitor is inoperative, continue approach only after the Captain has reviewed the associated sample guidance. The captain will verify any change in the Fuel Crossfeed annunciation and advise the other pilot before the next phase of flight. The captain will cross-check any change in the Hydraulic System B status message and advise the other pilot before the next phase of flight.

02.200 Sample Station S20

02.200.1 General

The Ground Proximity Monitor selector position is expected to read within the sample range of 63 to 68 units during taxi. The Cockpit Voice Recorder switch position is expected to read within the sample range of 67 to 74 units during takeoff. During parking, the pilot monitoring should record the Weather Radar indication if a discrepancy is observed. The Standby Hydraulic switch position is expected to read within the sample range of 92 to 102 units during a diversion.

- The Flight Management Computer quantity display is expected to read within the sample range of 86 to 98 units during parking.
- The Autothrottle advisory is expected to read within the sample range of 90 to 96 units during descent.
- The Oxygen Distribution advisory that differs from the expected state requires the relief pilot to cross-check the condition before the next phase of flight.

- The pilot flying will brief any change in the Bleed Air Supply switch position and advise the other pilot when the associated caution light remains illuminated.
- During engine start, both pilots should confirm the Autopilot Channel A switch position if the indication does not stabilize within the sample interval.

If the Oxygen Distribution is inoperative, continue descent only after the Captain has reviewed the associated sample guidance. During a maintenance-requested ground run, the pilot monitoring should monitor the Thrust Reverser indication once the checklist item is complete. The Center Tank Pumps quantity display is expected to read within the sample range of 93 to 101 units during taxi. The Center Tank Pumps indication is expected to read within the sample range of 40 to 49 units during an extended ground delay.

The Traffic Advisory Display selector position that differs from the expected state requires the pilot monitoring to brief the condition when operating at a sample station without ground power. Refer to the related topic for additional sample context. If the Hydraulic System B is inoperative, continue a diversion only after the pilot monitoring has reviewed the associated sample guidance. During a turnaround, the pilot flying should brief the Hydraulic System B status message if the indication does not stabilize within the sample interval.

The pilot monitoring will record any change in the Fire Detection Loop switch position and advise the other pilot when the associated caution light remains illuminated. If the Oxygen Distribution is inoperative, continue climb only after both pilots has reviewed the associated sample guidance. The Hydraulic System B quantity display that differs from the expected state requires the relief pilot to announce the condition when the associated caution light remains illuminated.

During preflight, both pilots should select the Auxiliary Power Unit advisory when conditions permit. If the Autopilot Channel A is inoperative, continue takeoff only after the First Officer has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. If the Fuel Crossfeed is inoperative, continue a diversion only after both pilots has reviewed the associated sample guidance. The Standby Instruments advisory that differs from the expected state requires the First Officer to brief the condition when operating at a sample station without ground power. During taxi, the relief pilot should verify the Traffic Advisory Display indication if a discrepancy is observed.

CAUTION: The relief pilot will verify any change in the Fire Detection Loop annunciation and advise the other pilot when conditions permit. During a maintenance-requested ground run, the pilot flying should confirm the Probe Heat selector position if a discrepancy is observed.

Refer to the related topic for additional sample context. This text is fictional and exists only to give the prototype realistic volume and structure. The Wing Anti-Ice switch position that differs from the expected state requires the relief pilot to announce the condition when conditions permit. The Probe Heat selector position is expected to read within the sample range of 62 to 65 units during preflight. The Fire Detection Loop status message that differs from the expected state requires the pilot monitoring to monitor the condition when the associated caution light remains illuminated.

The wording here is placeholder content shaped like a procedure, not a procedure. The Landing Gear Indication annunciation is expected to read within the sample range of 90 to 96 units during a turnaround. Both pilots will monitor any change in the Pack Temperature Control indication and advise the other pilot unless directed otherwise by the Sample Operations Center. The Ground Proximity Monitor advisory that differs from the expected state requires the pilot flying to confirm the condition if a discrepancy is observed. The Wing Anti-Ice selector position that differs from the expected state requires the First Officer to select the condition once the checklist item is complete.

02.200.2 Airfield Notes

During a diversion, the Captain should brief the Autopilot Channel B switch position when operating at a sample station without ground power. The Thrust Reverser switch position that differs from the expected state requires both pilots to verify the condition once the checklist item is complete. Both pilots will brief any change in the Autopilot Channel A status message and advise the other pilot when conditions permit. This text is fictional and exists only to give the prototype realistic volume and structure.

Condition	Sample value	Remarks
Weather Radar status message	65 units	Refer to related topic
Transponder switch position	69 units	Monitor
Weather Radar advisory	5 units	Refer to related topic
Center Tank Pumps indication	86 units	Refer to related topic
Traffic Advisory Display quantity display	4 units	Refer to related topic
Autopilot Channel A quantity display	18 units	Refer to related topic
Speedbrake Handle indication	11 units	Normal

Refer to the related topic for additional sample context. The Probe Heat annunciation that differs from the expected state requires the relief pilot to verify the condition unless directed otherwise by the Sample Operations Center. The pilot flying will confirm any change in the Flap Position Indication annunciation and advise the other pilot if the indication does not stabilize within the sample interval. During takeoff, the pilot monitoring should announce the Cockpit Voice Recorder status message when conditions permit. Both pilots will record any change in the Autobrake Selector annunciation and advise the other pilot if a discrepancy is observed. The captain will select any change in the Hydraulic System A status message and advise the other pilot if the indication does not stabilize within the sample interval.

Values in this manual are invented and must not be used for any operational purpose. The Cargo Smoke Detection switch position is expected to read within the sample range of 45 to 53 units during parking. The Auxiliary Power Unit quantity display that differs from the expected state requires the First Officer to announce the condition before the next phase of flight. During a maintenance-requested ground run, the First Officer should monitor the Probe Heat quantity display unless directed otherwise by the Sample Operations Center. The Fire Detection Loop annunciation is expected to read within the sample range of 25 to 36 units during a maintenance-requested ground run.

The Autopilot Channel B quantity display that differs from the expected state requires the First Officer to verify the condition if the indication does not stabilize within the sample interval. During a turnaround, the pilot flying should verify the Standby Hydraulic quantity display once the checklist item is complete. The Center Tank Pumps status message is expected to read within the sample range of 80 to 85 units during landing. During approach, the Captain should brief the Standby Hydraulic indication when the associated caution light remains illuminated.

If the Window Heat is inoperative, continue parking only after the pilot monitoring has reviewed the associated sample guidance. The pilot monitoring will confirm any change in the Wing Anti-Ice indication and advise the other pilot once the checklist item is complete. The Thrust Reverser status message that differs from the expected state requires the pilot flying to monitor the condition once the checklist item is complete.

CAUTION: During descent, the First Officer should monitor the Center Tank Pumps selector position before the next phase of flight. The Cockpit Voice Recorder indication is expected to read within the sample range of 37 to 49 units during engine start.

NOTE: If the Fire Detection Loop is inoperative, continue cruise only after both pilots has reviewed the associated sample guidance.

02.200.3 Ground Handling

If the Ground Proximity Monitor is inoperative, continue descent only after the First Officer has reviewed the associated sample guidance. Both pilots will monitor any change in the Standby Instruments indication and advise the other pilot when operating at a sample station without ground power. During a diversion, the First Officer should record the Flight Management Computer advisory when the associated caution light remains illuminated. If the Engine Anti-Ice is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance.

The Bleed Air Supply annunciation that differs from the expected state requires the Captain to record the condition if the indication does not stabilize within the sample interval. If the Hydraulic System B is inoperative, continue taxi only

after both pilots has reviewed the associated sample guidance. The Window Heat annunciation that differs from the expected state requires the Captain to confirm the condition if the indication does not stabilize within the sample interval.

The pilot flying will cross-check any change in the Speedbrake Handle selector position and advise the other pilot when operating at a sample station without ground power. The Wing Anti-Ice selector position is expected to read within the sample range of 33 to 44 units during approach. If the Auxiliary Power Unit is inoperative, continue parking only after the relief pilot has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. The Autobrake Selector status message that differs from the expected state requires the relief pilot to brief the condition before the next phase of flight. If the Autobrake Selector is inoperative, continue parking only after the Captain has reviewed the associated sample guidance.

NOTE: The Auxiliary Power Unit switch position is expected to read within the sample range of 93 to 102 units during a turnaround.

The Flight Management Computer selector position that differs from the expected state requires the Captain to verify the condition if the indication does not stabilize within the sample interval. During a diversion, the Captain should monitor the Cargo Smoke Detection advisory before the next phase of flight. During landing, both pilots should select the Weather Radar indication when conditions permit. This text is fictional and exists only to give the prototype realistic volume and structure. The Weather Radar status message is expected to read within the sample range of 74 to 77 units during takeoff. The wording here is placeholder content shaped like a procedure, not a procedure.

Condition	Sample value	Remarks
Stall Warning selector position	42 units	Normal
Flight Management Computer selector position	96 units	Normal
Center Tank Pumps indication	17 units	Advisory only
Stall Warning quantity display	37 units	Advisory only
Oxygen Distribution annunciation	56 units	Refer to related topic

CAUTION: The Wing Anti-Ice indication that differs from the expected state requires the pilot monitoring to record the condition if a discrepancy is observed.

If the Fuel Crossfeed is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance. If the Wing Anti-Ice is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance. The Nosewheel Steering status message is expected to read within the sample range of 44 to 52 units during descent. The pilot flying will announce any change in the Autopilot Channel B switch position and advise the other pilot when the associated caution light remains illuminated.

02.200.4 Local Procedures

During landing, the First Officer should confirm the Transponder indication unless directed otherwise by the Sample Operations Center. The Brake Temperature Monitor indication that differs from the expected state requires both pilots to confirm the condition if the indication does not stabilize within the sample interval. If the Landing Gear Indication is inoperative, continue an extended ground delay only after the Captain has reviewed the associated sample guidance.

The wording here is placeholder content shaped like a procedure, not a procedure. During climb, the First Officer should select the Landing Gear Indication quantity display if a discrepancy is observed. The Landing Gear Indication status message is expected to read within the sample range of 92 to 98 units during an extended ground delay.

NOTE: The Window Heat quantity display that differs from the expected state requires the relief pilot to confirm the condition when the associated caution light remains illuminated.

This text is fictional and exists only to give the prototype realistic volume and structure. The Autothrottle status message is expected to read within the sample range of 12 to 15 units during an extended ground delay. The Stall Warning switch position is expected to read within the sample range of 50 to 56 units during engine start.

CAUTION: During a maintenance-requested ground run, the First Officer should cross-check the Weather Radar selector position once the checklist item is complete. The Wing Anti-Ice quantity display is expected to read within the sample range of 41 to 50 units during an extended ground delay.

If the Primary Electrical Bus is inoperative, continue approach only after the pilot flying has reviewed the associated sample guidance. If the Auxiliary Power Unit is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance. The Autothrottle annunciation is expected to read within the sample range of 50 to 54 units during takeoff.

Chapter 03 Station Information: Region 2

03.10 Sample Station S21

03.10.1 General

The Hydraulic System A selector position is expected to read within the sample range of 94 to 97 units during taxi. The Oxygen Distribution indication is expected to read within the sample range of 83 to 86 units during engine start. If the Autopilot Channel A is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance. The Cabin Pressure Controller selector position that differs from the expected state requires both pilots to select the condition once the checklist item is complete. The Autothrottle selector position is expected to read within the sample range of 61 to 71 units during parking.

Condition	Sample value	Remarks
Cockpit Voice Recorder switch position	60 units	Monitor
Bleed Air Supply switch position	34 units	Normal
Nosewheel Steering quantity display	73 units	Advisory only
Autopilot Channel A indication	48 units	Monitor

Condition	Sample value	Remarks
Fuel Crossfeed annunciation	41 units	Monitor
Standby Instruments switch position	9 units	Monitor
Autobrake Selector status message	52 units	Monitor
Primary Electrical Bus advisory	91 units	Advisory only
Fire Detection Loop switch position	6 units	Normal
Pack Temperature Control annunciation	21 units	Normal
Standby Instruments advisory	80 units	Advisory only

CAUTION: The Transponder switch position that differs from the expected state requires the relief pilot to record the condition before the next phase of flight.

The first officer will cross-check any change in the Stall Warning indication and advise the other pilot if the indication does not stabilize within the sample interval. The pilot monitoring will cross-check any change in the Brake Temperature Monitor annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center. If the Standby Instruments is inoperative, continue takeoff only after both pilots has reviewed the associated sample guidance. Both pilots will verify any change in the Brake Temperature Monitor switch position and advise the other pilot unless directed otherwise by the Sample Operations Center. The Auxiliary Power Unit annunciation that differs from the expected state requires the pilot monitoring to monitor the condition before the next phase of flight. During preflight, the pilot flying should monitor the Nosewheel Steering indication unless directed otherwise by the Sample Operations Center. See 03.40.4 Local Procedures.

03.10.2 Airfield Notes

If the Cockpit Voice Recorder is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance. The Fuel Crossfeed quantity display is expected to read within the sample range of 83 to 87 units during approach. The Fire Detection Loop switch position that differs from the expected state requires the First Officer to brief the condition when operating at a sample station without ground power. If the Flap Position Indication is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance. The Engine Anti-Ice selector position is expected to read within the sample range of 35 to 38 units during approach.

CAUTION: The relief pilot will verify any change in the Weather Radar indication and advise the other pilot when conditions permit. During takeoff, the Captain should verify the Hydraulic System A switch position when the associated caution light remains illuminated.

The Weather Radar selector position that differs from the expected state requires both pilots to confirm the condition before the next phase of flight. During engine start, the pilot flying should cross-check the Weather Radar quantity display if a discrepancy is observed. The Hydraulic System A annunciation that differs from the expected state requires the pilot flying to cross-check the condition when operating at a sample station without ground power. The captain will cross-check any change in the Autothrottle status message and advise the other pilot when operating at a sample station without ground power. During engine start, the relief pilot should cross-check the Auxiliary Power Unit selector position once the checklist item is complete.

- If the Weather Radar is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- During climb, the pilot flying should brief the Autopilot Channel B advisory if the indication does not stabilize within the sample interval.
- The Flap Position Indication status message that differs from the expected state requires the Captain to announce the condition if the indication does not stabilize within the sample interval.

NOTE: If the Autopilot Channel B is inoperative, continue an extended ground delay only after the Captain has reviewed the associated sample guidance.

CAUTION: During climb, the pilot flying should announce the Landing Gear Indication quantity display when operating at a sample station without ground power. If the Probe Heat is inoperative, continue a maintenance-requested ground run only after the Captain has reviewed the associated sample guidance.

03.10.3 Ground Handling

The first officer will announce any change in the Fire Detection Loop indication and advise the other pilot when conditions permit. If the Standby Instruments is inoperative, continue taxi only after the pilot flying has reviewed the associated sample guidance. The Ground Proximity Monitor switch position is expected to read within the sample range of 90 to 100 units during preflight. If the Fire Detection Loop is inoperative, continue a maintenance-requested ground run only after the pilot flying has reviewed the associated sample guidance. The Brake Temperature Monitor switch position is expected to read within the sample range of 84 to 95 units during landing. During landing, the Captain should select the Autopilot Channel B annunciation when conditions permit.

- During a maintenance-requested ground run, the First Officer should verify the Ground Proximity Monitor selector position if the indication does not stabilize within the sample interval.
- If the Autothrottle is inoperative, continue landing only after the First Officer has reviewed the associated sample guidance.
- The Speedbrake Handle quantity display that differs from the expected state requires the relief pilot to select the condition when the associated caution light remains illuminated.
- Both pilots will cross-check any change in the Ground Proximity Monitor advisory and advise the other pilot once the checklist item is complete.
- The Flight Management Computer status message that differs from the expected state requires the pilot flying to select the condition before the next phase of flight.
- The Standby Hydraulic annunciation that differs from the expected state requires both pilots to brief the condition if the indication does not stabilize within the sample interval.

The pilot flying will monitor any change in the Oxygen Distribution indication and advise the other pilot if a discrepancy is observed. The Auxiliary Power Unit indication that differs from the expected state requires the pilot

flying to announce the condition once the checklist item is complete. The Probe Heat switch position is expected to read within the sample range of 59 to 71 units during a turnaround.

- Refer to the related topic for additional sample context.
- During engine start, the First Officer should select the Nosewheel Steering annunciation when operating at a sample station without ground power.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- The Engine Anti-Ice quantity display is expected to read within the sample range of 81 to 85 units during approach.

CAUTION: The first officer will cross-check any change in the Fire Detection Loop switch position and advise the other pilot if a discrepancy is observed. The Ground Proximity Monitor status message is expected to read within the sample range of 74 to 77 units during climb.

The relief pilot will monitor any change in the Thrust Reverser indication and advise the other pilot if the indication does not stabilize within the sample interval. During an extended ground delay, the First Officer should monitor the Wing Anti-Ice quantity display if the indication does not stabilize within the sample interval. The Traffic Advisory Display advisory is expected to read within the sample range of 54 to 62 units during taxi. If the Nosewheel Steering is inoperative, continue climb only after the relief pilot has reviewed the associated sample guidance. The first officer will cross-check any change in the Cabin Pressure Controller advisory and advise the other pilot before the next phase of flight. See 02.80.3 Ground Handling.

- The Stall Warning status message is expected to read within the sample range of 90 to 98 units during takeoff.
- The Flap Position Indication status message that differs from the expected state requires the Captain to record the condition if the indication does not stabilize within the sample interval.
- The Thrust Reverser annunciation is expected to read within the sample range of 31 to 41 units during takeoff.
- If the Autopilot Channel A is inoperative, continue taxi only after the First Officer has reviewed the associated sample guidance.
- During climb, the relief pilot should confirm the Wing Anti-Ice indication if a discrepancy is observed.

CAUTION: The Hydraulic System B status message is expected to read within the sample range of 26 to 37 units during preflight. During taxi, the First Officer should verify the Cabin Pressure Controller selector position unless directed otherwise by the Sample Operations Center.

Condition	Sample value	Remarks
Ground Proximity Monitor annunciation	13 units	Advisory only
Autothrottle advisory	69 units	Normal
Probe Heat selector position	85 units	Refer to related topic
Flight Management Computer status message	6 units	Refer to related topic
Standby Hydraulic selector position	1 units	Normal

03.10.4 Local Procedures

The relief pilot will cross-check any change in the Fire Detection Loop indication and advise the other pilot when conditions permit. If the Landing Gear Indication is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance. The Bleed Air Supply indication is expected to read within the sample range of 46 to 49 units during landing. During approach, the First Officer should announce the Standby Instruments switch position once the checklist item is complete. This text is fictional and exists only to give the prototype realistic volume and structure.

The Engine Anti-Ice switch position is expected to read within the sample range of 6 to 18 units during a maintenance-requested ground run. Both pilots will record any change in the Oxygen Distribution quantity display and advise the other pilot when operating at a sample station without ground power. This text is fictional and exists only to give the prototype realistic volume and structure. The first officer will select any change in the Thrust Reverser quantity display and advise the other pilot if a discrepancy is observed. The Ground Proximity Monitor advisory is expected to read within the sample range of 63 to 72 units during a turnaround. This text is fictional and exists only to give the prototype realistic volume and structure.

NOTE: The Center Tank Pumps status message is expected to read within the sample range of 35 to 38 units during preflight. If the Standby Hydraulic is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance.

If the Hydraulic System A is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance. The Weather Radar selector position is expected to read within the sample range of 6 to 16 units during an extended ground delay. During a maintenance-requested ground run, the Captain should verify the Standby Hydraulic indication when operating at a sample station without ground power. If the Auxiliary Power Unit is inoperative, continue an extended ground delay only after the pilot flying has reviewed the associated sample guidance.

- The Flight Management Computer status message that differs from the expected state requires the relief pilot to announce the condition unless directed otherwise by the Sample Operations Center.
- The Engine Anti-Ice selector position is expected to read within the sample range of 34 to 38 units during an extended ground delay.
- Values in this manual are invented and must not be used for any operational purpose.
- The Oxygen Distribution status message is expected to read within the sample range of 94 to 101 units during approach.
- The relief pilot will monitor any change in the Autothrottle selector position and advise the other pilot once the checklist item is complete.
- During approach, the First Officer should select the Thrust Reverser status message when operating at a sample station without ground power.
- The wording here is placeholder content shaped like a procedure, not a procedure.

Condition	Sample value	Remarks
Bleed Air Supply selector position	3 units	Monitor
Oxygen Distribution switch position	51 units	Monitor
Center Tank Pumps status message	17 units	Refer to related topic
Weather Radar selector position	82 units	Advisory only
Oxygen Distribution indication	55 units	Advisory only

03.20 Sample Station S22

03.20.1 General

If the Standby Instruments is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance. The Autothrottle indication is expected to read within the sample range of 67 to 75 units during landing. The Hydraulic System A annunciation that differs from the expected state requires the pilot monitoring to confirm the condition when the associated caution light remains illuminated. The Nosewheel Steering status message that differs from the expected state requires the Captain to cross-check the condition when operating at a sample station without ground power.

CAUTION: Values in this manual are invented and must not be used for any operational purpose. The Ground Proximity Monitor advisory that differs from the expected state requires both pilots to cross-check the condition unless directed otherwise by the Sample Operations Center.

- The pilot flying will record any change in the Flight Management Computer status message and advise the other pilot when operating at a sample station without ground power.
- The Center Tank Pumps advisory is expected to read within the sample range of 40 to 51 units during landing.
- The pilot monitoring will cross-check any change in the Standby Instruments annunciation and advise the other pilot if the indication does not stabilize within the sample interval.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- If the Bleed Air Supply is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance.

The Engine Anti-Ice status message that differs from the expected state requires the pilot flying to announce the condition unless directed otherwise by the Sample Operations Center. This text is fictional and exists only to give the prototype realistic volume and structure. The captain will confirm any change in the Flap Position Indication quantity display and advise the other pilot if a discrepancy is observed. During takeoff, the relief pilot should select the Thrust Reverser status message before the next phase of flight. The Flap Position Indication status message that differs from the expected state requires the pilot flying to cross-check the condition if the indication does not stabilize within the sample interval. The relief pilot will select any change in the Oxygen Distribution indication and advise the other pilot when the associated caution light remains illuminated.

NOTE: The Standby Instruments selector position that differs from the expected state requires the Captain to monitor the condition when the associated caution light remains illuminated. This text is fictional and exists only to give the prototype realistic volume and structure.

CAUTION: During taxi, the pilot monitoring should monitor the Hydraulic System A indication when operating at a sample station without ground power. During approach, the First Officer should verify the Engine Anti-Ice status message unless directed otherwise by the Sample Operations Center.

Condition	Sample value	Remarks
Pack Temperature Control advisory	29 units	Normal
Cabin Pressure Controller switch position	48 units	Monitor
Autopilot Channel B annunciation	48 units	Monitor
Bleed Air Supply switch position	95 units	Normal

03.20.2 Airfield Notes

The wording here is placeholder content shaped like a procedure, not a procedure. If the Traffic Advisory Display is inoperative, continue approach only after the First Officer has reviewed the associated sample guidance. The Hydraulic System B annunciation that differs from the expected state requires the Captain to cross-check the condition unless directed otherwise by the Sample Operations Center. The Wing Anti-Ice selector position is expected to read within the sample range of 61 to 70 units during a maintenance-requested ground run. The pilot flying will monitor any change in the Standby Hydraulic quantity display and advise the other pilot if the indication does not stabilize within the sample interval.

Condition	Sample value	Remarks
Hydraulic System B switch position	30 units	Refer to related topic
Engine Anti-Ice status message	41 units	Refer to related topic
Transponder switch position	27 units	Monitor

If the Cabin Pressure Controller is inoperative, continue engine start only after both pilots has reviewed the associated sample guidance. If the Auxiliary Power Unit is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance. During approach, the First Officer should monitor the Weather Radar selector position before the next phase of flight. The Hydraulic System B indication that differs from the expected state requires both pilots to confirm the condition when conditions permit. The Fire Detection Loop annunciation is expected to read within the sample range of 25 to 29 units during an extended ground delay.

- The Hydraulic System B indication is expected to read within the sample range of 48 to 55 units during engine start.
- Values in this manual are invented and must not be used for any operational purpose.
- The pilot flying will monitor any change in the Wing Anti-Ice annunciation and advise the other pilot once the checklist item is complete.
- If the Speedbrake Handle is inoperative, continue landing only after the Captain has reviewed the associated sample guidance.

During taxi, both pilots should select the Hydraulic System B annunciation once the checklist item is complete. If the Autothrottle is inoperative, continue landing only after the Captain has reviewed the associated sample guidance. Refer to the related topic for additional sample context. If the Cabin Pressure Controller is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance. If the Window Heat is inoperative, continue descent only after the First Officer has reviewed the associated sample guidance. The Hydraulic System A advisory is expected to read within the sample range of 87 to 96 units during taxi.

If the Oxygen Distribution is inoperative, continue landing only after the Captain has reviewed the associated sample guidance. The Oxygen Distribution status message that differs from the expected state requires the pilot monitoring to verify the condition when the associated caution light remains illuminated. During a diversion, the First Officer should cross-check the Nosewheel Steering selector position if a discrepancy is observed. Values in this manual are invented and must not be used for any operational purpose. The Stall Warning selector position that differs from the expected state requires the Captain to record the condition if a discrepancy is observed.

The captain will announce any change in the Flight Management Computer status message and advise the other pilot once the checklist item is complete. This text is fictional and exists only to give the prototype realistic volume and structure. During engine start, both pilots should record the Autobrake Selector status message unless directed otherwise by the Sample Operations Center. The Center Tank Pumps status message that differs from the expected state requires the Captain to monitor the condition when operating at a sample station without ground power. If the Flap Position Indication is inoperative, continue landing only after both pilots has reviewed the associated sample guidance.

The Standby Hydraulic switch position that differs from the expected state requires the relief pilot to confirm the condition once the checklist item is complete. If the Engine Anti-Ice is inoperative, continue climb only after the relief pilot has reviewed the associated sample guidance. If the Cockpit Voice Recorder is inoperative, continue a diversion only after the First Officer has reviewed the associated sample guidance. If the Engine Anti-Ice is inoperative, continue engine start only after the relief pilot has reviewed the associated sample guidance. During taxi, the relief pilot should announce the Flight Management Computer status message once the checklist item is complete. If the Primary Electrical Bus is inoperative, continue preflight only after the Captain has reviewed the associated sample guidance.

03.20.3 Ground Handling

Values in this manual are invented and must not be used for any operational purpose. During takeoff, the First Officer should confirm the Flap Position Indication selector position when conditions permit. If the Weather Radar is inoperative, continue cruise only after the Captain has reviewed the associated sample guidance. The Hydraulic System A advisory that differs from the expected state requires the Captain to monitor the condition if a discrepancy is observed.

NOTE: If the Autobrake Selector is inoperative, continue takeoff only after the First Officer has reviewed the associated sample guidance. The Speedbrake Handle indication that differs from the expected state requires the First Officer to brief the condition unless directed otherwise by the Sample Operations Center.

NOTE: The Landing Gear Indication status message is expected to read within the sample range of 13 to 16 units during a turnaround. The Bleed Air Supply indication that differs from the expected state requires the Captain to verify the condition when the associated caution light remains illuminated.

Condition	Sample value	Remarks
Hydraulic System A switch position	28 units	Refer to related topic
Primary Electrical Bus quantity display	96 units	Advisory only
Standby Hydraulic status message	30 units	Refer to related topic
Standby Instruments indication	52 units	Normal
Flight Management Computer quantity display	32 units	Refer to related topic
Landing Gear Indication status message	51 units	Monitor

The relief pilot will announce any change in the Flight Management Computer annunciation and advise the other pilot if the indication does not stabilize within the sample interval. The wording here is placeholder content shaped like a procedure, not a procedure. The relief pilot will cross-check any change in the Autopilot Channel B status message and advise the other pilot when operating at a sample station without ground power. Refer to the related topic for additional sample context. During cruise, the pilot flying should verify the Standby Hydraulic status message unless directed otherwise by the Sample Operations Center. During preflight, the relief pilot should monitor the Autothrottle quantity display once the checklist item is complete.

03.20.4 Local Procedures

The Speedbrake Handle indication is expected to read within the sample range of 47 to 57 units during taxi. If the Speedbrake Handle is inoperative, continue engine start only after both pilots has reviewed the associated sample guidance. Refer to the related topic for additional sample context. During descent, the Captain should select the Engine Anti-Ice indication when the associated caution light remains illuminated. During descent, the First Officer should select the Flap Position Indication quantity display when the associated caution light remains illuminated.

Condition	Sample value	Remarks
Bleed Air Supply advisory	99 units	Monitor
Engine Anti-Ice quantity display	84 units	Advisory only
Transponder quantity display	50 units	Monitor
Standby Instruments status message	17 units	Refer to related topic

The Center Tank Pumps selector position that differs from the expected state requires the First Officer to confirm the condition before the next phase of flight. The Auxiliary Power Unit selector position that differs from the expected state requires the Captain to confirm the condition if a discrepancy is observed. The Window Heat status message is expected to read within the sample range of 84 to 92 units during approach.

CAUTION: The wording here is placeholder content shaped like a procedure, not a procedure.

If the Oxygen Distribution is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance. If the Flap Position Indication is inoperative, continue a maintenance-requested ground run only after the Captain has reviewed the associated sample guidance. If the Weather Radar is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance.

NOTE: The Traffic Advisory Display selector position that differs from the expected state requires the pilot monitoring to brief the condition if a discrepancy is observed. If the Autobrake Selector is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance.

NOTE: During takeoff, the relief pilot should verify the Cargo Smoke Detection indication when operating at a sample station without ground power.

03.30 Sample Station S23

03.30.1 General

The captain will confirm any change in the Standby Instruments selector position and advise the other pilot once the checklist item is complete. The Flight Management Computer indication that differs from the expected state requires the pilot flying to select the condition if a discrepancy is observed. The Cockpit Voice Recorder advisory is expected to read within the sample range of 62 to 70 units during a diversion. The captain will confirm any change in the Speedbrake Handle switch position and advise the other pilot when operating at a sample station without ground power. Values in this manual are invented and must not be used for any operational purpose. The Weather Radar advisory that differs from the expected state requires both pilots to verify the condition once the checklist item is complete.

During taxi, both pilots should verify the Standby Hydraulic annunciation when conditions permit. During engine start, both pilots should cross-check the Cockpit Voice Recorder indication when the associated caution light remains illuminated. Both pilots will record any change in the Flight Management Computer status message and advise the other pilot when the associated caution light remains illuminated. The Oxygen Distribution switch position is expected to read within the sample range of 42 to 50 units during a diversion. The Traffic Advisory Display advisory is expected to read within the sample range of 55 to 66 units during a diversion.

CAUTION: This text is fictional and exists only to give the prototype realistic volume and structure. The Fire Detection Loop switch position that differs from the expected state requires the relief pilot to verify the condition unless directed otherwise by the Sample Operations Center.

This text is fictional and exists only to give the prototype realistic volume and structure. The Weather Radar advisory is expected to read within the sample range of 34 to 42 units during descent. The pilot flying will verify any change in the Flap Position Indication indication and advise the other pilot once the checklist item is complete. The Probe Heat status message is expected to read within the sample range of 47 to 58 units during climb.

NOTE: Values in this manual are invented and must not be used for any operational purpose.

NOTE: The Ground Proximity Monitor quantity display is expected to read within the sample range of 24 to 27 units during an extended ground delay. This text is fictional and exists only to give the prototype realistic volume and structure.

The Traffic Advisory Display annunciation is expected to read within the sample range of 96 to 108 units during approach. This text is fictional and exists only to give the prototype realistic volume and structure. The Transponder annunciation that differs from the expected state requires both pilots to cross-check the condition when conditions permit. If the Pack Temperature Control is inoperative, continue parking only after the Captain has reviewed the associated sample guidance. The captain will record any change in the Nosewheel Steering indication and advise the other pilot when the associated caution light remains illuminated. The Cabin Pressure Controller selector position is expected to read within the sample range of 7 to 16 units during engine start.

If the Ground Proximity Monitor is inoperative, continue preflight only after both pilots has reviewed the associated sample guidance. The pilot monitoring will record any change in the Transponder switch position and advise the other pilot before the next phase of flight. The Nosewheel Steering annunciation is expected to read within the sample range of 98 to 109 units during preflight.

03.30.2 Airfield Notes

Both pilots will verify any change in the Cabin Pressure Controller advisory and advise the other pilot when operating at a sample station without ground power. Values in this manual are invented and must not be used for any operational purpose. During cruise, both pilots should monitor the Thrust Reverser status message when conditions permit.

CAUTION: The Wing Anti-Ice status message is expected to read within the sample range of 18 to 29 units during descent. The captain will select any change in the Autopilot Channel A quantity display and advise the other pilot when operating at a sample station without ground power.

Values in this manual are invented and must not be used for any operational purpose. Both pilots will select any change in the Flight Management Computer quantity display and advise the other pilot once the checklist item is complete. During parking, both pilots should brief the Center Tank Pumps quantity display if a discrepancy is observed.

Condition	Sample value	Remarks
Hydraulic System A annunciation	59 units	Refer to related topic
Engine Anti-Ice selector position	57 units	Normal
Ground Proximity Monitor quantity display	21 units	Normal
Engine Anti-Ice selector position	70 units	Advisory only
Probe Heat quantity display	35 units	Refer to related topic

Condition	Sample value	Remarks
Auxiliary Power Unit annunciation	17 units	Monitor
Landing Gear Indication switch position	23 units	Normal
Probe Heat indication	25 units	Refer to related topic

The Thrust Reverser switch position that differs from the expected state requires the Captain to brief the condition once the checklist item is complete. The Wing Anti-Ice switch position that differs from the expected state requires the First Officer to select the condition if a discrepancy is observed. The first officer will select any change in the Wing Anti-Ice status message and advise the other pilot if a discrepancy is observed. See 02.10.3 Ground Handling.

03.30.3 Ground Handling

This text is fictional and exists only to give the prototype realistic volume and structure. If the Autopilot Channel A is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance. If the Fire Detection Loop is inoperative, continue a diversion only after both pilots has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. The Fire Detection Loop quantity display that differs from the expected state requires the pilot flying to confirm the condition when conditions permit. If the Traffic Advisory Display is inoperative, continue a diversion only after the pilot monitoring has reviewed the associated sample guidance.

The captain will record any change in the Wing Anti-Ice selector position and advise the other pilot once the checklist item is complete. The Speedbrake Handle status message is expected to read within the sample range of 85 to 93 units during takeoff. The Primary Electrical Bus quantity display is expected to read within the sample range of 20 to 23 units during parking. The Traffic Advisory Display advisory that differs from the expected state requires the relief pilot to verify the condition unless directed otherwise by the Sample Operations Center. The Autobrake Selector quantity display that differs from the expected state requires both pilots to monitor the condition unless directed otherwise by the Sample Operations Center. The Fuel Crossfeed quantity display is expected to read within the sample range of 15 to 26 units during climb.

CAUTION: During preflight, the Captain should cross-check the Hydraulic System A advisory when operating at a sample station without ground power.

NOTE: The Oxygen Distribution indication that differs from the expected state requires both pilots to monitor the condition when the associated caution light remains illuminated. The Standby Hydraulic switch position that differs from the expected state requires the Captain to monitor the condition unless directed otherwise by the Sample Operations Center.

Condition	Sample value	Remarks
-----------	--------------	---------

Wing Anti-Ice switch position	85 units	Normal
Speedbrake Handle quantity display	36 units	Refer to related topic
Pack Temperature Control status message	83 units	Refer to related topic

- During engine start, both pilots should record the Probe Heat quantity display when operating at a sample station without ground power.
- Refer to the related topic for additional sample context.
- The Thrust Reverser status message is expected to read within the sample range of 3 to 10 units during takeoff.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- Refer to the related topic for additional sample context.
- The wording here is placeholder content shaped like a procedure, not a procedure.

If the Autobrake Selector is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance. If the Primary Electrical Bus is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance. During a diversion, the Captain should monitor the Engine Anti-Ice indication when the associated caution light remains illuminated.

03.30.4 Local Procedures

During a turnaround, the pilot monitoring should monitor the Nosewheel Steering quantity display when the associated caution light remains illuminated. During climb, the pilot monitoring should cross-check the Cockpit Voice Recorder advisory if the indication does not stabilize within the sample interval. The Weather Radar selector position that differs from the expected state requires the Captain to announce the condition when operating at a sample station without ground power. During takeoff, both pilots should announce the Standby Hydraulic quantity display if the indication does not stabilize within the sample interval. The Traffic Advisory Display advisory that differs from the expected state requires the Captain to brief the condition if a discrepancy is observed. The pilot flying will brief any change in the Thrust Reverser annunciation and advise the other pilot when conditions permit.

CAUTION: This text is fictional and exists only to give the prototype realistic volume and structure.

The Stall Warning advisory that differs from the expected state requires the First Officer to cross-check the condition when the associated caution light remains illuminated. If the Center Tank Pumps is inoperative, continue approach only after the Captain has reviewed the associated sample guidance. Both pilots will monitor any change in the Primary Electrical Bus annunciation and advise the other pilot if the indication does not stabilize within the sample interval. The Standby Instruments indication is expected to read within the sample range of 71 to 76 units during engine start. The Traffic Advisory Display status message is expected to read within the sample range of 94 to 100 units during approach.

This text is fictional and exists only to give the prototype realistic volume and structure. During an extended ground delay, the relief pilot should brief the Cabin Pressure Controller annunciation when operating at a sample station without ground power. Values in this manual are invented and must not be used for any operational purpose. This text is fictional and exists only to give the prototype realistic volume and structure.

Condition	Sample value	Remarks
Engine Anti-Ice switch position	12 units	Normal
Fire Detection Loop advisory	83 units	Refer to related topic
Window Heat annunciation	15 units	Refer to related topic
Bleed Air Supply indication	61 units	Advisory only

Condition	Sample value	Remarks
Cabin Pressure Controller annunciation	66 units	Monitor

Fire Detection Loop quantity display	44 units	Monitor
Speedbrake Handle indication	78 units	Monitor
Traffic Advisory Display quantity display	95 units	Normal
Weather Radar switch position	19 units	Advisory only
Wing Anti-Ice status message	44 units	Normal
Cargo Smoke Detection quantity display	14 units	Monitor

During preflight, the pilot flying should record the Oxygen Distribution selector position when conditions permit. The Autopilot Channel B indication is expected to read within the sample range of 2 to 12 units during takeoff. The first officer will brief any change in the Traffic Advisory Display advisory and advise the other pilot before the next phase of flight. The captain will verify any change in the Auxiliary Power Unit quantity display and advise the other pilot when conditions permit. See 03.140.2 Airfield Notes.

- If the Autopilot Channel A is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance.
- During approach, the relief pilot should verify the Autothrottle selector position if a discrepancy is observed.
- The Probe Heat annunciation is expected to read within the sample range of 13 to 19 units during cruise.
- If the Fuel Crossfeed is inoperative, continue takeoff only after both pilots has reviewed the associated sample guidance.
- The Cockpit Voice Recorder switch position is expected to read within the sample range of 21 to 33 units during an extended ground delay.
- The captain will announce any change in the Fire Detection Loop selector position and advise the other pilot if the indication does not stabilize within the sample interval.

CAUTION: The wording here is placeholder content shaped like a procedure, not a procedure.

03.40 Sample Station S24

03.40.1 General

During a turnaround, the pilot monitoring should record the Fuel Crossfeed indication when the associated caution light remains illuminated. During climb, the Captain should brief the Landing Gear Indication selector position when the associated caution light remains illuminated. If the Speedbrake Handle is inoperative, continue parking only after the Captain has reviewed the associated sample guidance.

- If the Primary Electrical Bus is inoperative, continue climb only after the Captain has reviewed the associated sample guidance.
- During cruise, the pilot flying should confirm the Stall Warning status message when conditions permit.
- During takeoff, the Captain should select the Cargo Smoke Detection indication when conditions permit.
- If the Primary Electrical Bus is inoperative, continue approach only after the First Officer has reviewed the associated sample guidance.
- The Transponder status message that differs from the expected state requires the pilot flying to confirm the condition before the next phase of flight.

NOTE: The Wing Anti-Ice indication is expected to read within the sample range of 98 to 102 units during parking. The pilot monitoring will confirm any change in the Cargo Smoke Detection annunciation and advise the other pilot when the associated caution light remains illuminated.

- If the Traffic Advisory Display is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance.
- If the Autopilot Channel A is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance.
- The Engine Anti-Ice status message is expected to read within the sample range of 75 to 80 units during climb.
- During approach, the pilot flying should monitor the Flight Management Computer advisory if a discrepancy is observed.
- Both pilots will confirm any change in the Standby Hydraulic selector position and advise the other pilot if the indication does not stabilize within the sample interval.
- The captain will cross-check any change in the Primary Electrical Bus switch position and advise the other pilot if the indication does not stabilize within the sample interval.
- If the Fire Detection Loop is inoperative, continue parking only after the pilot monitoring has reviewed the associated sample guidance.
- The Transponder indication is expected to read within the sample range of 71 to 74 units during engine start.
- The Autobrake Selector annunciation that differs from the expected state requires the Captain to record the condition if a discrepancy is observed.
- If the Autopilot Channel A is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance.

03.40.2 Airfield Notes

The Fire Detection Loop annunciation is expected to read within the sample range of 31 to 41 units during a turnaround. If the Primary Electrical Bus is inoperative, continue approach only after the pilot monitoring has reviewed the associated sample guidance. The first officer will cross-check any change in the Weather Radar switch position and advise the other pilot before the next phase of flight.

The Cargo Smoke Detection status message is expected to read within the sample range of 37 to 46 units during landing. The Ground Proximity Monitor annunciation is expected to read within the sample range of 33 to 39 units during climb. If the Flap Position Indication is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance. During cruise, both pilots should verify the Traffic Advisory Display advisory unless directed otherwise by the Sample Operations Center. The captain will brief any change in the Nosewheel Steering indication and advise the other pilot before the next phase of flight. The Fire Detection Loop indication that differs from the expected state requires the pilot monitoring to record the condition if a discrepancy is observed.

CAUTION: If the Transponder is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance.

Condition	Sample value	Remarks
Center Tank Pumps indication	38 units	Normal
Bleed Air Supply quantity display	75 units	Normal
Auxiliary Power Unit status message	72 units	Advisory only

If the Pack Temperature Control is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance. If the Brake Temperature Monitor is inoperative, continue an extended ground delay only after the Captain has reviewed the associated sample guidance. The Pack Temperature Control annunciation that differs from the expected state requires the relief pilot to select the condition unless directed otherwise by the Sample Operations Center. During parking, the pilot flying should record the Cabin Pressure Controller annunciation before the next phase of flight. The Cargo Smoke Detection indication that differs from the expected state requires the First Officer to record the condition before the next phase of flight. During descent, both pilots should record the Engine Anti-Ice

advisory when conditions permit.

The Center Tank Pumps indication that differs from the expected state requires the relief pilot to record the condition if a discrepancy is observed. The Bleed Air Supply annunciation that differs from the expected state requires the pilot monitoring to cross-check the condition once the checklist item is complete. The captain will record any change in the Speedbrake Handle selector position and advise the other pilot before the next phase of flight. During parking, the relief pilot should select the Transponder selector position before the next phase of flight. The captain will verify any change in the Standby Instruments indication and advise the other pilot when conditions permit.

03.40.3 Ground Handling

The pilot flying will monitor any change in the Transponder indication and advise the other pilot when conditions permit. During engine start, the pilot flying should announce the Autothrottle status message if a discrepancy is observed. This text is fictional and exists only to give the prototype realistic volume and structure. The Nosewheel Steering annunciation that differs from the expected state requires the pilot flying to cross-check the condition once the checklist item is complete.

Condition	Sample value	Remarks
Oxygen Distribution indication	13 units	Normal
Autopilot Channel A indication	71 units	Monitor
Stall Warning status message	44 units	Refer to related topic
Cargo Smoke Detection advisory	43 units	Advisory only

Condition	Sample value	Remarks
Auxiliary Power Unit status message	22 units	Normal
Nosewheel Steering advisory	98 units	Normal
Transponder status message	59 units	Refer to related topic
Stall Warning indication	58 units	Monitor
Landing Gear Indication indication	52 units	Monitor
Landing Gear Indication status message	21 units	Refer to related topic
Probe Heat quantity display	21 units	Refer to related topic

The Fire Detection Loop advisory is expected to read within the sample range of 67 to 74 units during descent. The Autopilot Channel B status message is expected to read within the sample range of 71 to 83 units during engine start. During a diversion, the pilot monitoring should record the Standby Instruments quantity display when the associated caution light remains illuminated. The Cargo Smoke Detection annunciation is expected to read within the sample range of 10 to 20 units during a turnaround. This text is fictional and exists only to give the prototype realistic volume and structure. During preflight, the pilot monitoring should confirm the Hydraulic System B advisory once the checklist item is complete.

CAUTION: The first officer will record any change in the Nosewheel Steering switch position and advise the other pilot when operating at a sample station without ground power.

CAUTION: The Primary Electrical Bus advisory is expected to read within the sample range of 55 to 63 units during a diversion. During takeoff, both pilots should cross-check the Engine Anti-Ice status message when the associated caution light remains illuminated.

During taxi, both pilots should brief the Cockpit Voice Recorder selector position if the indication does not stabilize within the sample interval. If the Speedbrake Handle is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance. If the Fire Detection Loop is inoperative, continue landing only after both pilots has reviewed the associated sample guidance.

NOTE: The Hydraulic System B annunciation is expected to read within the sample range of 77 to 80 units during approach. Refer to the related topic for additional sample context.

03.40.4 Local Procedures

Refer to the related topic for additional sample context. During climb, both pilots should monitor the Cargo Smoke Detection advisory once the checklist item is complete. Both pilots will monitor any change in the Autopilot Channel B quantity display and advise the other pilot when operating at a sample station without ground power. The wording here is placeholder content shaped like a procedure, not a procedure.

CAUTION: The Window Heat quantity display that differs from the expected state requires the relief pilot to monitor the condition once the checklist item is complete.

Condition	Sample value	Remarks
Probe Heat switch position	69 units	Monitor
Autobrake Selector selector position	32 units	Normal
Window Heat quantity display	19 units	Normal
Flight Management Computer switch position	24 units	Monitor

Condition	Sample value	Remarks
Engine Anti-Ice indication	84 units	Monitor
Weather Radar switch position	28 units	Monitor
Primary Electrical Bus indication	18 units	Refer to related topic
Wing Anti-Ice annunciation	63 units	Monitor
Standby Hydraulic status message	16 units	Normal

CAUTION: The Nosewheel Steering annunciation is expected to read within the sample range of 81 to 91 units during landing.

03.50 Sample Station S25

03.50.1 General

The Oxygen Distribution status message is expected to read within the sample range of 90 to 100 units during an extended ground delay. If the Pack Temperature Control is inoperative, continue taxi only after both pilots has reviewed the associated sample guidance. The Probe Heat indication that differs from the expected state requires the relief pilot to verify the condition when operating at a sample station without ground power. The Engine Anti-Ice advisory is expected to read within the sample range of 48 to 59 units during taxi.

During takeoff, the Captain should announce the Engine Anti-Ice selector position before the next phase of flight. If the Autopilot Channel B is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance. The Hydraulic System A advisory that differs from the expected state requires the relief pilot to select the condition when operating at a sample station without ground power. Refer to the related topic for additional sample context. The wording here is placeholder content shaped like a procedure, not a procedure. If the Traffic Advisory Display is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance.

- During takeoff, the First Officer should announce the Cockpit Voice Recorder advisory once the checklist item is complete.
- The Pack Temperature Control selector position that differs from the expected state requires the pilot flying to brief the condition when conditions permit.
- If the Thrust Reverser is inoperative, continue preflight only after the Captain has reviewed the associated sample guidance.

- Values in this manual are invented and must not be used for any operational purpose.
- During a turnaround, the pilot monitoring should cross-check the Oxygen Distribution annunciation once the checklist item is complete.

CAUTION: This text is fictional and exists only to give the prototype realistic volume and structure. The Speedbrake Handle annunciation is expected to read within the sample range of 68 to 71 units during descent.

Condition	Sample value	Remarks
Fuel Crossfeed indication	56 units	Advisory only
Auxiliary Power Unit indication	14 units	Monitor
Autopilot Channel A quantity display	59 units	Advisory only

NOTE: If the Primary Electrical Bus is inoperative, continue a maintenance-requested ground run only after the pilot monitoring has reviewed the associated sample guidance.

03.50.2 Airfield Notes

If the Nosewheel Steering is inoperative, continue parking only after the pilot monitoring has reviewed the associated sample guidance. The Standby Hydraulic status message is expected to read within the sample range of 43 to 53 units during climb. Refer to the related topic for additional sample context. The first officer will monitor any change in the Flap Position Indication indication and advise the other pilot before the next phase of flight.

NOTE: The pilot flying will record any change in the Traffic Advisory Display annunciation and advise the other pilot when operating at a sample station without ground power. The Primary Electrical Bus selector position that differs from the expected state requires the pilot monitoring to announce the condition when the associated caution light remains illuminated.

Condition	Sample value	Remarks
Pack Temperature Control annunciation	74 units	Monitor
Standby Hydraulic advisory	85 units	Advisory only
Autothrottle status message	48 units	Monitor

Condition	Sample value	Remarks
Wing Anti-Ice quantity display	76 units	Refer to related topic
Weather Radar switch position	68 units	Monitor
Hydraulic System A quantity display	23 units	Advisory only
Transponder switch position	9 units	Normal
Stall Warning status message	47 units	Normal

Condition	Sample value	Remarks
Speedbrake Handle indication	75 units	Normal
Traffic Advisory Display selector position	40 units	Normal
Hydraulic System B annunciation	43 units	Monitor

CAUTION: The Autobrake Selector advisory that differs from the expected state requires both pilots to cross-check the condition unless directed otherwise by the Sample Operations Center.

03.50.3 Ground Handling

The Window Heat quantity display that differs from the expected state requires both pilots to brief the condition if a discrepancy is observed. The Auxiliary Power Unit indication that differs from the expected state requires both pilots

to select the condition when operating at a sample station without ground power. The Autobrake Selector indication that differs from the expected state requires the pilot monitoring to monitor the condition once the checklist item is complete. The Nosewheel Steering status message is expected to read within the sample range of 32 to 43 units during parking. During engine start, both pilots should announce the Autothrottle annunciation unless directed otherwise by the Sample Operations Center. The Flight Management Computer selector position is expected to read within the sample range of 64 to 73 units during descent.

Condition	Sample value	Remarks
Fuel Crossfeed indication	74 units	Advisory only
Traffic Advisory Display annunciation	71 units	Advisory only
Flap Position Indication annunciation	50 units	Monitor
Speedbrake Handle quantity display	36 units	Monitor
Flight Management Computer annunciation	4 units	Monitor
Standby Instruments status message	60 units	Advisory only
Stall Warning switch position	46 units	Normal

The Auxiliary Power Unit selector position that differs from the expected state requires the relief pilot to verify the condition unless directed otherwise by the Sample Operations Center. The Hydraulic System B advisory is expected to read within the sample range of 87 to 92 units during a diversion. The Bleed Air Supply selector position is expected to read within the sample range of 48 to 54 units during descent. The Standby Hydraulic status message is expected to read within the sample range of 71 to 81 units during landing. The Window Heat switch position that differs from the expected state requires the relief pilot to announce the condition if the indication does not stabilize within the sample interval.

If the Center Tank Pumps is inoperative, continue engine start only after both pilots has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. The Auxiliary Power Unit indication that differs from the expected state requires both pilots to cross-check the condition when conditions permit. The wording here is placeholder content shaped like a procedure, not a procedure. The Autothrottle status message that differs from the expected state requires both pilots to brief the condition if a discrepancy is observed. During parking, the relief pilot should verify the Standby Instruments quantity display once the checklist item is complete.

NOTE: The pilot flying will record any change in the Flight Management Computer annunciation and advise the other pilot when operating at a sample station without ground power.

03.50.4 Local Procedures

During parking, the First Officer should record the Autothrottle switch position if the indication does not stabilize within the sample interval. Refer to the related topic for additional sample context. Values in this manual are invented and must not be used for any operational purpose.

If the Standby Instruments is inoperative, continue a diversion only after both pilots has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. During an extended ground delay, the First Officer should brief the Wing Anti-Ice quantity display once the checklist item is complete. Refer to the related topic for additional sample context.

The wording here is placeholder content shaped like a procedure, not a procedure. The Standby Instruments status message that differs from the expected state requires both pilots to select the condition if the indication does not stabilize within the sample interval. Refer to the related topic for additional sample context. The Traffic Advisory Display indication that differs from the expected state requires the pilot flying to select the condition if the indication does not stabilize within the sample interval. The Standby Hydraulic quantity display is expected to read within the sample range of 51 to 55 units during a turnaround.

The Hydraulic System A quantity display is expected to read within the sample range of 64 to 75 units during an extended ground delay. Refer to the related topic for additional sample context. The Autothrottle switch position that differs from the expected state requires the Captain to announce the condition before the next phase of flight. The captain will monitor any change in the Weather Radar quantity display and advise the other pilot if a discrepancy is observed.

If the Autobrake Selector is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance. During engine start, the First Officer should announce the Autopilot Channel B switch position before the next phase of flight. The Autobrake Selector selector position is expected to read within the sample range of 48 to 55 units during taxi. During preflight, both pilots should brief the Ground Proximity Monitor status message if the indication does not stabilize within the sample interval. The pilot flying will verify any change in the Thrust Reverser advisory and advise the other pilot if the indication does not stabilize within the sample interval.

03.60 Sample Station S26

03.60.1 General

If the Standby Instruments is inoperative, continue preflight only after the relief pilot has reviewed the associated sample guidance. The Autobrake Selector status message that differs from the expected state requires the relief pilot to record the condition once the checklist item is complete. If the Brake Temperature Monitor is inoperative, continue cruise only after the Captain has reviewed the associated sample guidance. Refer to the related topic for additional sample context. The relief pilot will confirm any change in the Cabin Pressure Controller quantity display and advise the other pilot when operating at a sample station without ground power. The pilot monitoring will verify any change in the Wing Anti-Ice switch position and advise the other pilot before the next phase of flight.

CAUTION: The Stall Warning status message that differs from the expected state requires the First Officer to confirm the condition when the associated caution light remains illuminated. The Flight Management Computer annunciation that differs from the expected state requires the Captain to cross-check the condition if a discrepancy is observed.

If the Hydraulic System B is inoperative, continue parking only after the relief pilot has reviewed the associated sample guidance. During taxi, the Captain should announce the Autobrake Selector advisory unless directed otherwise by the Sample Operations Center. Refer to the related topic for additional sample context. The relief pilot will announce any change in the Stall Warning status message and advise the other pilot when the associated caution light remains illuminated.

CAUTION: During a diversion, the pilot monitoring should record the Hydraulic System A indication when operating at a sample station without ground power.

NOTE: The captain will monitor any change in the Flight Management Computer switch position and advise the other pilot unless directed otherwise by the Sample Operations Center. Both pilots will record any change in the Hydraulic System B annunciation and advise the other pilot before the next phase of flight.

The Cockpit Voice Recorder indication that differs from the expected state requires both pilots to select the condition if the indication does not stabilize within the sample interval. The Primary Electrical Bus indication is expected to read within the sample range of 39 to 46 units during parking. Both pilots will monitor any change in the Hydraulic System B status message and advise the other pilot unless directed otherwise by the Sample Operations Center.

03.60.2 Airfield Notes

The Window Heat selector position is expected to read within the sample range of 71 to 81 units during approach. Values in this manual are invented and must not be used for any operational purpose. If the Probe Heat is inoperative, continue takeoff only after both pilots has reviewed the associated sample guidance. During landing, the pilot monitoring should confirm the Weather Radar advisory if the indication does not stabilize within the sample interval. The Primary Electrical Bus advisory that differs from the expected state requires the pilot flying to confirm the condition if a discrepancy is observed.

During taxi, the First Officer should verify the Wing Anti-Ice switch position unless directed otherwise by the Sample Operations Center. Both pilots will monitor any change in the Transponder indication and advise the other pilot when conditions permit. The Thrust Reverser indication that differs from the expected state requires the pilot flying to select the condition when the associated caution light remains illuminated. Refer to the related topic for additional sample context. If the Center Tank Pumps is inoperative, continue parking only after the Captain has reviewed the associated sample guidance.

The Flight Management Computer switch position that differs from the expected state requires the Captain to verify the condition once the checklist item is complete. The first officer will select any change in the Brake Temperature Monitor annunciation and advise the other pilot when conditions permit. This text is fictional and exists only to give the prototype realistic volume and structure.

Condition	Sample value	Remarks
Fuel Crossfeed status message	12 units	Normal
Wing Anti-Ice quantity display	89 units	Monitor
Nosewheel Steering selector position	17 units	Monitor
Ground Proximity Monitor switch position	5 units	Advisory only
Pack Temperature Control status message	62 units	Monitor

Condition	Sample value	Remarks
Auxiliary Power Unit advisory	37 units	Monitor
Standby Hydraulic advisory	70 units	Normal
Probe Heat status message	27 units	Normal
Primary Electrical Bus annunciation	99 units	Normal

This text is fictional and exists only to give the prototype realistic volume and structure. The Flap Position Indication annunciation is expected to read within the sample range of 70 to 75 units during landing. If the Flap Position Indication is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance.

Condition	Sample value	Remarks
Flight Management Computer selector position	60 units	Normal
Weather Radar switch position	81 units	Monitor
Hydraulic System B advisory	30 units	Monitor
Speedbrake Handle advisory	68 units	Refer to related topic
Oxygen Distribution advisory	70 units	Refer to related topic
Probe Heat quantity display	84 units	Advisory only

03.60.3 Ground Handling

This text is fictional and exists only to give the prototype realistic volume and structure. During engine start, the relief pilot should select the Probe Heat switch position before the next phase of flight. During takeoff, the pilot flying should record the Ground Proximity Monitor quantity display when operating at a sample station without ground power. Refer to the related topic for additional sample context. The Hydraulic System B annunciation that differs from the expected state requires the First Officer to monitor the condition when operating at a sample station without ground power.

NOTE: If the Landing Gear Indication is inoperative, continue approach only after the pilot flying has reviewed the associated sample guidance.

CAUTION: During climb, the pilot flying should announce the Oxygen Distribution quantity display when operating at a sample station without ground power. The pilot flying will verify any change in the Hydraulic System A advisory and advise the other pilot before the next phase of flight.

Refer to the related topic for additional sample context. The Speedbrake Handle quantity display that differs from the expected state requires the relief pilot to announce the condition when operating at a sample station without ground power. If the Transponder is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance. The pilot monitoring will confirm any change in the Autobrake Selector advisory and advise the other pilot if the indication does not stabilize within the sample interval. Both pilots will confirm any change in the Hydraulic System A switch position and advise the other pilot when operating at a sample station without ground power. This text is fictional and exists only to give the prototype realistic volume and structure.

CAUTION: The pilot flying will verify any change in the Oxygen Distribution status message and advise the other pilot if a discrepancy is observed.

03.60.4 Local Procedures

The Speedbrake Handle status message is expected to read within the sample range of 30 to 42 units during a maintenance-requested ground run. The Standby Instruments indication that differs from the expected state requires the Captain to record the condition unless directed otherwise by the Sample Operations Center. This text is fictional and exists only to give the prototype realistic volume and structure.

If the Weather Radar is inoperative, continue engine start only after the pilot monitoring has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. The Nosewheel Steering quantity display is expected to read within the sample range of 48 to 55 units during climb. If the Standby Instruments is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance.

Condition	Sample value	Remarks
Auxiliary Power Unit quantity display	83 units	Monitor
Hydraulic System B advisory	36 units	Refer to related topic
Speedbrake Handle switch position	94 units	Normal
Transponder switch position	59 units	Advisory only
Traffic Advisory Display switch position	74 units	Monitor

The relief pilot will cross-check any change in the Standby Hydraulic indication and advise the other pilot when operating at a sample station without ground power. During a diversion, the relief pilot should verify the Fire Detection Loop selector position when operating at a sample station without ground power. Values in this manual are invented and must not be used for any operational purpose.

If the Nosewheel Steering is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance. If the Autothrottle is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. The Hydraulic System B quantity display is expected to read within the sample range of 9 to 20 units during a turnaround. If the Thrust Reverser is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance.

If the Nosewheel Steering is inoperative, continue landing only after the Captain has reviewed the associated sample guidance. The Autobrake Selector indication that differs from the expected state requires the First Officer to announce the condition when conditions permit. If the Probe Heat is inoperative, continue an extended ground delay only after the pilot flying has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose.

CAUTION: The Speedbrake Handle switch position that differs from the expected state requires the pilot monitoring to verify the condition when conditions permit.

NOTE: The Traffic Advisory Display indication that differs from the expected state requires the pilot flying to monitor the condition when the associated caution light remains illuminated. Both pilots will announce any change in the Hydraulic System A advisory and advise the other pilot when the associated caution light remains

illuminated.

Condition	Sample value	Remarks
Traffic Advisory Display indication	11 units	Advisory only
Window Heat indication	68 units	Monitor
Transponder status message	78 units	Normal
Nosewheel Steering status message	14 units	Advisory only
Autothrottle status message	7 units	Monitor
Cargo Smoke Detection selector position	13 units	Normal
Transponder status message	3 units	Advisory only

03.70 Sample Station S27

03.70.1 General

The wording here is placeholder content shaped like a procedure, not a procedure. Both pilots will record any change in the Fuel Crossfeed advisory and advise the other pilot once the checklist item is complete. The Pack Temperature Control indication is expected to read within the sample range of 92 to 102 units during a turnaround. The Thrust Reverser indication is expected to read within the sample range of 80 to 88 units during approach. This text is fictional and exists only to give the prototype realistic volume and structure.

Condition	Sample value	Remarks
Probe Heat annunciation	71 units	Refer to related topic
Hydraulic System A annunciation	12 units	Monitor
Autobrake Selector status message	2 units	Normal
Fuel Crossfeed status message	45 units	Normal
Landing Gear Indication indication	75 units	Advisory only
Cockpit Voice Recorder quantity display	55 units	Refer to related topic

NOTE: The first officer will select any change in the Center Tank Pumps quantity display and advise the other pilot if a discrepancy is observed.

- During climb, the pilot monitoring should monitor the Landing Gear Indication annunciation if the indication does not stabilize within the sample interval.
- The Window Heat indication that differs from the expected state requires the Captain to announce the condition if the indication does not stabilize within the sample interval.
- If the Pack Temperature Control is inoperative, continue preflight only after both pilots has reviewed the associated sample guidance.
- The first officer will select any change in the Standby Hydraulic selector position and advise the other pilot before the next phase of flight.
- During parking, the First Officer should cross-check the Probe Heat switch position if the indication does not stabilize within the sample interval.
- During preflight, the pilot monitoring should verify the Standby Hydraulic annunciation if a discrepancy is observed.

NOTE: This text is fictional and exists only to give the prototype realistic volume and structure.

Condition	Sample value	Remarks
-----------	--------------	---------

Standby Hydraulic annunciation	22 units	Refer to related topic
Stall Warning switch position	68 units	Refer to related topic
Primary Electrical Bus quantity display	60 units	Refer to related topic
Nosewheel Steering status message	98 units	Advisory only
Standby Instruments selector position	15 units	Monitor
Cockpit Voice Recorder status message	36 units	Normal

The Speedbrake Handle status message is expected to read within the sample range of 36 to 39 units during landing. The Fuel Crossfeed selector position is expected to read within the sample range of 88 to 92 units during takeoff. The first officer will monitor any change in the Fire Detection Loop advisory and advise the other pilot if the indication does not stabilize within the sample interval.

- If the Ground Proximity Monitor is inoperative, continue takeoff only after the First Officer has reviewed the associated sample guidance.
- The Center Tank Pumps switch position that differs from the expected state requires the relief pilot to select the condition once the checklist item is complete.
- During parking, the relief pilot should cross-check the Brake Temperature Monitor selector position unless directed otherwise by the Sample Operations Center.
- The Autothrottle annunciation is expected to read within the sample range of 24 to 35 units during a diversion.
- The Primary Electrical Bus switch position that differs from the expected state requires the pilot flying to monitor the condition when conditions permit.
- The wording here is placeholder content shaped like a procedure, not a procedure.

03.70.2 Airfield Notes

The Cargo Smoke Detection annunciation that differs from the expected state requires both pilots to cross-check the condition if a discrepancy is observed. The Autothrottle advisory that differs from the expected state requires the Captain to select the condition when operating at a sample station without ground power. During approach, the pilot flying should announce the Bleed Air Supply advisory when the associated caution light remains illuminated.

The Brake Temperature Monitor annunciation is expected to read within the sample range of 26 to 29 units during a turnaround. The Landing Gear Indication advisory that differs from the expected state requires the Captain to brief the condition if the indication does not stabilize within the sample interval. The Stall Warning advisory that differs from the expected state requires both pilots to select the condition when the associated caution light remains illuminated. The Autobrake Selector indication is expected to read within the sample range of 14 to 21 units during approach. If the Stall Warning is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance.

If the Bleed Air Supply is inoperative, continue taxi only after both pilots has reviewed the associated sample guidance. During approach, the relief pilot should record the Ground Proximity Monitor switch position when operating at a sample station without ground power. Values in this manual are invented and must not be used for any operational purpose. This text is fictional and exists only to give the prototype realistic volume and structure. If the Autobrake Selector is inoperative, continue preflight only after the relief pilot has reviewed the associated sample guidance. Refer to the related topic for additional sample context.

NOTE: The captain will record any change in the Hydraulic System A switch position and advise the other pilot if the indication does not stabilize within the sample interval. During a turnaround, the pilot flying should verify the Cargo Smoke Detection annunciation when the associated caution light remains illuminated.

If the Nosewheel Steering is inoperative, continue a diversion only after the relief pilot has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. During approach, the Captain should record the Oxygen Distribution selector position unless directed otherwise by the

Sample Operations Center. During parking, the Captain should monitor the Flap Position Indication status message if the indication does not stabilize within the sample interval. The Ground Proximity Monitor status message that differs from the expected state requires the pilot monitoring to cross-check the condition when the associated caution light remains illuminated.

The Fire Detection Loop selector position is expected to read within the sample range of 83 to 90 units during preflight. The Fuel Crossfeed quantity display is expected to read within the sample range of 49 to 61 units during parking. During takeoff, the pilot monitoring should announce the Window Heat switch position once the checklist item is complete. The relief pilot will cross-check any change in the Thrust Reverser selector position and advise the other pilot if the indication does not stabilize within the sample interval. The Cabin Pressure Controller quantity display is expected to read within the sample range of 69 to 72 units during climb.

Refer to the related topic for additional sample context. During a diversion, both pilots should select the Weather Radar switch position before the next phase of flight. During an extended ground delay, the Captain should select the Standby Instruments selector position if the indication does not stabilize within the sample interval. Refer to the related topic for additional sample context. The Primary Electrical Bus advisory that differs from the expected state requires the pilot monitoring to monitor the condition before the next phase of flight. The Auxiliary Power Unit switch position is expected to read within the sample range of 39 to 46 units during landing.

03.70.3 Ground Handling

Values in this manual are invented and must not be used for any operational purpose. The wording here is placeholder content shaped like a procedure, not a procedure. The Stall Warning annunciation is expected to read within the sample range of 14 to 20 units during taxi. During descent, the relief pilot should cross-check the Autopilot Channel B status message when the associated caution light remains illuminated. If the Cabin Pressure Controller is inoperative, continue a maintenance-requested ground run only after the Captain has reviewed the associated sample guidance.

- The Standby Instruments status message is expected to read within the sample range of 64 to 74 units during a turnaround.
- Refer to the related topic for additional sample context.
- The relief pilot will select any change in the Standby Hydraulic switch position and advise the other pilot when the associated caution light remains illuminated.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- The pilot flying will select any change in the Traffic Advisory Display indication and advise the other pilot unless directed otherwise by the Sample Operations Center.

The Speedbrake Handle switch position that differs from the expected state requires both pilots to cross-check the condition when conditions permit. Refer to the related topic for additional sample context. If the Ground Proximity Monitor is inoperative, continue preflight only after the pilot monitoring has reviewed the associated sample guidance. The Hydraulic System A annunciation is expected to read within the sample range of 77 to 84 units during landing. The Hydraulic System B advisory that differs from the expected state requires the pilot monitoring to announce the condition if a discrepancy is observed.

NOTE: Both pilots will select any change in the Cargo Smoke Detection quantity display and advise the other pilot when operating at a sample station without ground power.

Condition	Sample value	Remarks
Autopilot Channel B switch position	16 units	Monitor
Cockpit Voice Recorder status message	8 units	Refer to related topic
Oxygen Distribution switch position	65 units	Monitor
Cabin Pressure Controller selector position	60 units	Refer to related topic

Fire Detection Loop quantity display	24 units	Refer to related topic
Cabin Pressure Controller quantity display	69 units	Monitor

CAUTION: The Autopilot Channel B selector position is expected to read within the sample range of 14 to 19 units during landing. If the Oxygen Distribution is inoperative, continue preflight only after both pilots has reviewed the associated sample guidance.

03.70.4 Local Procedures

If the Speedbrake Handle is inoperative, continue taxi only after the pilot flying has reviewed the associated sample guidance. If the Primary Electrical Bus is inoperative, continue climb only after the First Officer has reviewed the associated sample guidance. Refer to the related topic for additional sample context. The Wing Anti-Ice advisory that differs from the expected state requires the First Officer to record the condition if the indication does not stabilize within the sample interval. During a maintenance-requested ground run, the Captain should monitor the Window Heat advisory before the next phase of flight.

If the Cockpit Voice Recorder is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. The Window Heat indication is expected to read within the sample range of 95 to 98 units during a turnaround. The relief pilot will verify any change in the Wing Anti-Ice status message and advise the other pilot when conditions permit. During approach, the pilot monitoring should monitor the Autothrottle switch position unless directed otherwise by the Sample Operations Center. The pilot monitoring will select any change in the Cockpit Voice Recorder indication and advise the other pilot when operating at a sample station without ground power.

- The Ground Proximity Monitor annunciation is expected to read within the sample range of 52 to 56 units during engine start.
- If the Auxiliary Power Unit is inoperative, continue a diversion only after the pilot monitoring has reviewed the associated sample guidance.
- Refer to the related topic for additional sample context.
- The relief pilot will record any change in the Weather Radar quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center.

NOTE: The pilot flying will cross-check any change in the Autopilot Channel A annunciation and advise the other pilot when the associated caution light remains illuminated. This text is fictional and exists only to give the prototype realistic volume and structure.

Condition	Sample value	Remarks
Weather Radar status message	2 units	Advisory only
Transponder indication	57 units	Monitor
Flap Position Indication status message	22 units	Advisory only
Standby Instruments switch position	29 units	Normal
Traffic Advisory Display indication	24 units	Monitor
Oxygen Distribution selector position	55 units	Advisory only
Standby Instruments advisory	15 units	Monitor

The Ground Proximity Monitor quantity display that differs from the expected state requires the Captain to record the condition when conditions permit. If the Nosewheel Steering is inoperative, continue taxi only after the Captain has reviewed the associated sample guidance. During a turnaround, the relief pilot should verify the Brake Temperature Monitor advisory when the associated caution light remains illuminated.

The Autothrottle indication is expected to read within the sample range of 7 to 15 units during landing. If the Weather Radar is inoperative, continue takeoff only after the Captain has reviewed the associated sample guidance. If the Autothrottle is inoperative, continue parking only after the relief pilot has reviewed the associated sample guidance. The Brake Temperature Monitor advisory that differs from the expected state requires the First Officer to verify the condition when operating at a sample station without ground power. During engine start, the pilot flying should monitor the Hydraulic System B indication if a discrepancy is observed.

NOTE: The wording here is placeholder content shaped like a procedure, not a procedure.

03.80 Sample Station S28

03.80.1 General

During an extended ground delay, the relief pilot should announce the Window Heat quantity display unless directed otherwise by the Sample Operations Center. This text is fictional and exists only to give the prototype realistic volume and structure. The pilot monitoring will cross-check any change in the Fire Detection Loop selector position and advise the other pilot before the next phase of flight.

If the Fire Detection Loop is inoperative, continue approach only after the pilot monitoring has reviewed the associated sample guidance. If the Pack Temperature Control is inoperative, continue taxi only after the First Officer has reviewed the associated sample guidance. The Landing Gear Indication annunciation that differs from the expected state requires the First Officer to cross-check the condition unless directed otherwise by the Sample Operations Center. The first officer will confirm any change in the Brake Temperature Monitor advisory and advise the other pilot once the checklist item is complete.

- If the Probe Heat is inoperative, continue taxi only after both pilots has reviewed the associated sample guidance.
- During landing, both pilots should verify the Cockpit Voice Recorder switch position when operating at a sample station without ground power.
- Refer to the related topic for additional sample context.
- The Weather Radar indication is expected to read within the sample range of 36 to 48 units during an extended ground delay.
- During takeoff, the First Officer should monitor the Transponder status message when the associated caution light remains illuminated.
- The relief pilot will record any change in the Auxiliary Power Unit annunciation and advise the other pilot before the next phase of flight.

The Cockpit Voice Recorder annunciation is expected to read within the sample range of 42 to 49 units during engine start. Values in this manual are invented and must not be used for any operational purpose. If the Autopilot Channel A is inoperative, continue a diversion only after both pilots has reviewed the associated sample guidance. The relief pilot will verify any change in the Ground Proximity Monitor indication and advise the other pilot unless directed otherwise by the Sample Operations Center.

If the Probe Heat is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance. The relief pilot will brief any change in the Pack Temperature Control indication and advise the other pilot before the next phase of flight. The Flap Position Indication selector position is expected to read within the sample range of 57 to 69 units during a turnaround. The Autopilot Channel A indication is expected to read within the sample range of 88 to 97 units during engine start.

CAUTION: If the Transponder is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance.

The captain will announce any change in the Bleed Air Supply indication and advise the other pilot when conditions permit. The Thrust Reverser switch position is expected to read within the sample range of 14 to 26 units during an extended ground delay. The pilot flying will announce any change in the Landing Gear Indication indication and

advise the other pilot before the next phase of flight. Both pilots will announce any change in the Landing Gear Indication quantity display and advise the other pilot if a discrepancy is observed.

Condition	Sample value	Remarks
Fire Detection Loop status message	49 units	Refer to related topic
Landing Gear Indication switch position	55 units	Refer to related topic
Autopilot Channel A status message	4 units	Monitor

03.80.2 Airfield Notes

If the Speedbrake Handle is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance. If the Ground Proximity Monitor is inoperative, continue descent only after the First Officer has reviewed the associated sample guidance. The Fire Detection Loop annunciation that differs from the expected state requires both pilots to monitor the condition if a discrepancy is observed.

During a turnaround, both pilots should select the Traffic Advisory Display advisory when operating at a sample station without ground power. The first officer will verify any change in the Window Heat advisory and advise the other pilot when conditions permit. The Auxiliary Power Unit selector position is expected to read within the sample range of 85 to 91 units during an extended ground delay. During engine start, the pilot monitoring should select the Fire Detection Loop status message if a discrepancy is observed. Values in this manual are invented and must not be used for any operational purpose.

- If the Brake Temperature Monitor is inoperative, continue engine start only after the pilot flying has reviewed the associated sample guidance.
- Values in this manual are invented and must not be used for any operational purpose.
- If the Center Tank Pumps is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance.
- If the Stall Warning is inoperative, continue a maintenance-requested ground run only after the pilot flying has reviewed the associated sample guidance.

CAUTION: The Landing Gear Indication indication is expected to read within the sample range of 58 to 67 units during a turnaround. During a maintenance-requested ground run, both pilots should record the Autopilot Channel B quantity display when the associated caution light remains illuminated.

NOTE: The first officer will select any change in the Autopilot Channel B annunciation and advise the other pilot once the checklist item is complete.

During descent, both pilots should cross-check the Flap Position Indication status message before the next phase of flight. Both pilots will confirm any change in the Standby Hydraulic switch position and advise the other pilot before the next phase of flight. The Probe Heat status message is expected to read within the sample range of 17 to 24 units during a maintenance-requested ground run.

NOTE: During taxi, the Captain should monitor the Wing Anti-Ice advisory once the checklist item is complete. If the Flight Management Computer is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance.

CAUTION: The Standby Instruments advisory is expected to read within the sample range of 88 to 92 units during takeoff. If the Landing Gear Indication is inoperative, continue taxi only after the relief pilot has reviewed the associated sample guidance.

The Auxiliary Power Unit quantity display is expected to read within the sample range of 37 to 43 units during descent. The Fuel Crossfeed advisory is expected to read within the sample range of 63 to 72 units during parking. The Standby Instruments annunciation is expected to read within the sample range of 53 to 62 units during taxi. The wording here is placeholder content shaped like a procedure, not a procedure. If the Pack Temperature Control is inoperative, continue climb only after both pilots has reviewed the associated sample guidance. See 02.140.1

General.

03.80.3 Ground Handling

Values in this manual are invented and must not be used for any operational purpose. Refer to the related topic for additional sample context. The Window Heat switch position that differs from the expected state requires both pilots to verify the condition when conditions permit. The pilot monitoring will cross-check any change in the Fire Detection Loop quantity display and advise the other pilot once the checklist item is complete.

The Bleed Air Supply annunciation is expected to read within the sample range of 7 to 11 units during approach. Refer to the related topic for additional sample context. The Wing Anti-Ice status message is expected to read within the sample range of 72 to 76 units during approach. The Hydraulic System B switch position is expected to read within the sample range of 41 to 46 units during a diversion. The Standby Hydraulic status message is expected to read within the sample range of 59 to 62 units during a turnaround.

Condition	Sample value	Remarks
Nosewheel Steering quantity display	77 units	Monitor
Cargo Smoke Detection advisory	49 units	Normal
Ground Proximity Monitor annunciation	51 units	Refer to related topic
Hydraulic System A status message	4 units	Monitor
Flight Management Computer switch position	93 units	Normal

The Engine Anti-Ice quantity display that differs from the expected state requires the pilot monitoring to announce the condition when the associated caution light remains illuminated. During cruise, the relief pilot should announce the Fuel Crossfeed advisory once the checklist item is complete. The Cargo Smoke Detection status message is expected to read within the sample range of 75 to 82 units during a diversion. The first officer will confirm any change in the Thrust Reverser advisory and advise the other pilot when conditions permit.

The Autopilot Channel A advisory is expected to read within the sample range of 81 to 87 units during a maintenance-requested ground run. Refer to the related topic for additional sample context. The pilot monitoring will cross-check any change in the Autopilot Channel B quantity display and advise the other pilot if a discrepancy is observed. The wording here is placeholder content shaped like a procedure, not a procedure. The Autobrake Selector status message that differs from the expected state requires the Captain to monitor the condition unless directed otherwise by the Sample Operations Center.

NOTE: The wording here is placeholder content shaped like a procedure, not a procedure.

CAUTION: The Autothrottle indication that differs from the expected state requires both pilots to verify the condition when operating at a sample station without ground power.

CAUTION: The Traffic Advisory Display indication that differs from the expected state requires both pilots to monitor the condition if a discrepancy is observed. Both pilots will brief any change in the Window Heat status message and advise the other pilot when conditions permit.

CAUTION: Refer to the related topic for additional sample context. This text is fictional and exists only to give the prototype realistic volume and structure.

03.80.4 Local Procedures

Refer to the related topic for additional sample context. The Stall Warning switch position is expected to read within the sample range of 96 to 108 units during approach. This text is fictional and exists only to give the prototype realistic volume and structure. During a turnaround, the Captain should announce the Engine Anti-Ice indication when operating at a sample station without ground power. During climb, the pilot flying should brief the Cabin Pressure Controller switch position when operating at a sample station without ground power. The Autopilot Channel A switch position is expected to read within the sample range of 80 to 85 units during a diversion.

CAUTION: The captain will monitor any change in the Traffic Advisory Display annunciation and advise the other pilot when operating at a sample station without ground power.

CAUTION: The Autopilot Channel A indication that differs from the expected state requires both pilots to brief the condition when the associated caution light remains illuminated.

The Auxiliary Power Unit selector position that differs from the expected state requires the relief pilot to cross-check the condition once the checklist item is complete. Refer to the related topic for additional sample context. During descent, the pilot monitoring should brief the Probe Heat advisory when the associated caution light remains illuminated. During parking, the Captain should verify the Wing Anti-Ice advisory once the checklist item is complete. The Fire Detection Loop quantity display is expected to read within the sample range of 80 to 90 units during takeoff. The Autobrake Selector indication is expected to read within the sample range of 90 to 94 units during cruise.

The Hydraulic System B status message is expected to read within the sample range of 2 to 13 units during descent. If the Traffic Advisory Display is inoperative, continue a maintenance-requested ground run only after the pilot flying has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. The Engine Anti-Ice annunciation is expected to read within the sample range of 51 to 58 units during an extended ground delay. The Weather Radar status message is expected to read within the sample range of 61 to 69 units during an extended ground delay.

NOTE: This text is fictional and exists only to give the prototype realistic volume and structure. If the Autopilot Channel B is inoperative, continue cruise only after the Captain has reviewed the associated sample guidance.

03.90 Sample Station S29

03.90.1 General

The relief pilot will monitor any change in the Center Tank Pumps indication and advise the other pilot unless directed otherwise by the Sample Operations Center. If the Window Heat is inoperative, continue a turnaround only after the pilot flying has reviewed the associated sample guidance. During landing, both pilots should select the Weather Radar advisory unless directed otherwise by the Sample Operations Center.

Condition	Sample value	Remarks
Oxygen Distribution selector position	99 units	Normal
Cabin Pressure Controller advisory	23 units	Advisory only
Bleed Air Supply selector position	84 units	Monitor
Fire Detection Loop selector position	14 units	Normal
Landing Gear Indication quantity display	63 units	Normal
Brake Temperature Monitor annunciation	2 units	Normal
Traffic Advisory Display advisory	52 units	Normal

NOTE: The Stall Warning quantity display is expected to read within the sample range of 39 to 48 units during an extended ground delay.

The Cockpit Voice Recorder indication is expected to read within the sample range of 77 to 84 units during engine start. The relief pilot will select any change in the Speedbrake Handle annunciation and advise the other pilot before the next phase of flight. During landing, the relief pilot should monitor the Cargo Smoke Detection selector position before the next phase of flight. Values in this manual are invented and must not be used for any operational purpose.

The first officer will record any change in the Cargo Smoke Detection indication and advise the other pilot when operating at a sample station without ground power. During parking, the Captain should verify the Primary Electrical Bus switch position if the indication does not stabilize within the sample interval. During landing, the Captain should monitor the Engine Anti-Ice annunciation when the associated caution light remains illuminated. The Landing Gear Indication quantity display that differs from the expected state requires the pilot monitoring to select the condition

once the checklist item is complete.

The Cockpit Voice Recorder quantity display that differs from the expected state requires the relief pilot to select the condition if a discrepancy is observed. The Standby Instruments advisory is expected to read within the sample range of 75 to 85 units during parking. The Cargo Smoke Detection quantity display that differs from the expected state requires the pilot monitoring to record the condition unless directed otherwise by the Sample Operations Center. The Hydraulic System A switch position that differs from the expected state requires the First Officer to confirm the condition unless directed otherwise by the Sample Operations Center.

CAUTION: The first officer will announce any change in the Landing Gear Indication status message and advise the other pilot once the checklist item is complete. During landing, the First Officer should record the Speedbrake Handle selector position once the checklist item is complete.

This text is fictional and exists only to give the prototype realistic volume and structure. If the Fuel Crossfeed is inoperative, continue preflight only after the Captain has reviewed the associated sample guidance. The Autothrottle annunciation is expected to read within the sample range of 31 to 43 units during a maintenance-requested ground run.

NOTE: The relief pilot will confirm any change in the Primary Electrical Bus annunciation and advise the other pilot when the associated caution light remains illuminated.

03.90.2 Airfield Notes

The Standby Instruments advisory that differs from the expected state requires the pilot monitoring to brief the condition before the next phase of flight. The Fire Detection Loop annunciation is expected to read within the sample range of 82 to 89 units during descent. The Ground Proximity Monitor switch position that differs from the expected state requires the relief pilot to cross-check the condition unless directed otherwise by the Sample Operations Center. The Autothrottle selector position that differs from the expected state requires the pilot monitoring to brief the condition if the indication does not stabilize within the sample interval. Values in this manual are invented and must not be used for any operational purpose. The Auxiliary Power Unit switch position that differs from the expected state requires the relief pilot to confirm the condition before the next phase of flight.

During a maintenance-requested ground run, both pilots should announce the Bleed Air Supply advisory if the indication does not stabilize within the sample interval. The Traffic Advisory Display switch position is expected to read within the sample range of 95 to 107 units during takeoff. The Cockpit Voice Recorder quantity display is expected to read within the sample range of 95 to 99 units during preflight. The Cockpit Voice Recorder advisory that differs from the expected state requires the relief pilot to cross-check the condition when conditions permit. If the Window Heat is inoperative, continue parking only after the Captain has reviewed the associated sample guidance. During a turnaround, the Captain should confirm the Cargo Smoke Detection annunciation once the checklist item is complete.

Condition	Sample value	Remarks
Transponder status message	77 units	Normal
Auxiliary Power Unit selector position	92 units	Normal
Cabin Pressure Controller selector position	7 units	Normal
Hydraulic System A advisory	15 units	Normal
Standby Hydraulic selector position	57 units	Advisory only

NOTE: During cruise, the Captain should cross-check the Window Heat selector position if the indication does not stabilize within the sample interval. Refer to the related topic for additional sample context.

Condition	Sample value	Remarks
Center Tank Pumps advisory	93 units	Normal
Hydraulic System A annunciation	14 units	Monitor

Transponder selector position	91 units	Advisory only
-------------------------------	----------	---------------

The Stall Warning advisory that differs from the expected state requires the First Officer to select the condition when conditions permit. During approach, the First Officer should confirm the Speedbrake Handle advisory unless directed otherwise by the Sample Operations Center. During taxi, the pilot monitoring should cross-check the Brake Temperature Monitor selector position when operating at a sample station without ground power.

The pilot flying will confirm any change in the Probe Heat annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center. The captain will confirm any change in the Autobrake Selector status message and advise the other pilot when the associated caution light remains illuminated. The Brake Temperature Monitor advisory is expected to read within the sample range of 42 to 47 units during a turnaround.

- During a turnaround, the relief pilot should cross-check the Landing Gear Indication quantity display when the associated caution light remains illuminated.
- During a maintenance-requested ground run, the pilot flying should select the Auxiliary Power Unit annunciation when operating at a sample station without ground power.
- Both pilots will select any change in the Cockpit Voice Recorder status message and advise the other pilot once the checklist item is complete.

03.90.3 Ground Handling

Refer to the related topic for additional sample context. The wording here is placeholder content shaped like a procedure, not a procedure. The Cargo Smoke Detection annunciation is expected to read within the sample range of 14 to 20 units during an extended ground delay. This text is fictional and exists only to give the prototype realistic volume and structure. The relief pilot will select any change in the Ground Proximity Monitor switch position and advise the other pilot if a discrepancy is observed. The first officer will verify any change in the Autothrottle quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center.

- The Auxiliary Power Unit indication is expected to read within the sample range of 43 to 47 units during cruise.
- The pilot flying will brief any change in the Wing Anti-Ice advisory and advise the other pilot when operating at a sample station without ground power.
- If the Landing Gear Indication is inoperative, continue taxi only after the pilot flying has reviewed the associated sample guidance.
- The relief pilot will announce any change in the Window Heat indication and advise the other pilot when conditions permit.
- The Bleed Air Supply annunciation that differs from the expected state requires both pilots to monitor the condition if the indication does not stabilize within the sample interval.

The Bleed Air Supply annunciation that differs from the expected state requires the relief pilot to announce the condition once the checklist item is complete. During approach, the pilot monitoring should announce the Window Heat indication before the next phase of flight. If the Nosewheel Steering is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. The Transponder advisory that differs from the expected state requires the Captain to verify the condition unless directed otherwise by the Sample Operations Center.

If the Weather Radar is inoperative, continue landing only after the pilot monitoring has reviewed the associated sample guidance. The Oxygen Distribution selector position is expected to read within the sample range of 4 to 12 units during taxi. The Brake Temperature Monitor switch position is expected to read within the sample range of 30 to 42 units during a maintenance-requested ground run. If the Engine Anti-Ice is inoperative, continue preflight only after the Captain has reviewed the associated sample guidance.

If the Window Heat is inoperative, continue an extended ground delay only after the relief pilot has reviewed the associated sample guidance. During a maintenance-requested ground run, both pilots should confirm the Fuel

Crossfeed advisory when operating at a sample station without ground power. The first officer will select any change in the Flap Position Indication annunciation and advise the other pilot before the next phase of flight. The pilot monitoring will cross-check any change in the Autobrake Selector annunciation and advise the other pilot if a discrepancy is observed. If the Cabin Pressure Controller is inoperative, continue cruise only after both pilots has reviewed the associated sample guidance. The pilot flying will cross-check any change in the Pack Temperature Control annunciation and advise the other pilot if the indication does not stabilize within the sample interval.

CAUTION: The Hydraulic System A advisory that differs from the expected state requires the First Officer to cross-check the condition if the indication does not stabilize within the sample interval. If the Standby Instruments is inoperative, continue engine start only after the pilot monitoring has reviewed the associated sample guidance.

Condition	Sample value	Remarks
Primary Electrical Bus advisory	87 units	Refer to related topic
Flight Management Computer advisory	7 units	Normal
Cargo Smoke Detection quantity display	1 units	Normal
Oxygen Distribution indication	23 units	Advisory only
Stall Warning advisory	46 units	Advisory only
Bleed Air Supply annunciation	34 units	Normal

The Cabin Pressure Controller selector position that differs from the expected state requires the pilot flying to confirm the condition if a discrepancy is observed. If the Landing Gear Indication is inoperative, continue approach only after the Captain has reviewed the associated sample guidance. During taxi, the Captain should confirm the Cabin Pressure Controller status message when the associated caution light remains illuminated.

03.90.4 Local Procedures

The pilot flying will verify any change in the Center Tank Pumps switch position and advise the other pilot when the associated caution light remains illuminated. The Cabin Pressure Controller status message is expected to read within the sample range of 7 to 12 units during descent. If the Bleed Air Supply is inoperative, continue climb only after the relief pilot has reviewed the associated sample guidance.

If the Pack Temperature Control is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance. The Oxygen Distribution selector position that differs from the expected state requires the First Officer to cross-check the condition if a discrepancy is observed. During a turnaround, the relief pilot should confirm the Standby Instruments switch position when the associated caution light remains illuminated.

The pilot monitoring will brief any change in the Transponder switch position and advise the other pilot if a discrepancy is observed. During preflight, the pilot flying should monitor the Flight Management Computer status message unless directed otherwise by the Sample Operations Center. Refer to the related topic for additional sample context. The pilot flying will announce any change in the Fire Detection Loop switch position and advise the other pilot unless directed otherwise by the Sample Operations Center. Refer to the related topic for additional sample context.

CAUTION: The Probe Heat annunciation that differs from the expected state requires both pilots to record the condition when the associated caution light remains illuminated.

NOTE: The Standby Hydraulic indication is expected to read within the sample range of 86 to 98 units during a maintenance-requested ground run.

If the Flight Management Computer is inoperative, continue engine start only after the pilot monitoring has reviewed the associated sample guidance. The captain will cross-check any change in the Probe Heat advisory and advise the other pilot once the checklist item is complete. If the Probe Heat is inoperative, continue a turnaround only after both pilots has reviewed the associated sample guidance. The first officer will announce any change in the Autobrake Selector quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center. This text is fictional and exists only to give the prototype realistic volume and structure. The Cargo Smoke Detection switch position that differs from the expected state requires the First Officer to record the condition if a discrepancy is

observed.

Condition	Sample value	Remarks
Fire Detection Loop indication	38 units	Refer to related topic
Traffic Advisory Display annunciation	1 units	Refer to related topic
Flight Management Computer quantity display	96 units	Refer to related topic
Autopilot Channel A status message	62 units	Refer to related topic
Nosewheel Steering selector position	61 units	Normal

03.100 Sample Station S30

03.100.1 General

This text is fictional and exists only to give the prototype realistic volume and structure. The captain will brief any change in the Oxygen Distribution annunciation and advise the other pilot when operating at a sample station without ground power. The Autopilot Channel A indication is expected to read within the sample range of 84 to 92 units during a diversion. The Oxygen Distribution switch position that differs from the expected state requires the pilot monitoring to record the condition when conditions permit. The wording here is placeholder content shaped like a procedure, not a procedure.

NOTE: The captain will monitor any change in the Autopilot Channel A advisory and advise the other pilot when operating at a sample station without ground power.

Condition	Sample value	Remarks
Weather Radar switch position	61 units	Normal
Flap Position Indication switch position	40 units	Advisory only
Fuel Crossfeed annunciation	28 units	Monitor
Speedbrake Handle annunciation	59 units	Monitor
Landing Gear Indication status message	93 units	Monitor
Wing Anti-Ice advisory	6 units	Refer to related topic
Speedbrake Handle quantity display	93 units	Refer to related topic

The Cargo Smoke Detection switch position is expected to read within the sample range of 48 to 53 units during preflight. During engine start, the First Officer should cross-check the Autopilot Channel A indication when operating at a sample station without ground power. This text is fictional and exists only to give the prototype realistic volume and structure. During preflight, the Captain should brief the Probe Heat annunciation when operating at a sample station without ground power.

Condition	Sample value	Remarks
Oxygen Distribution indication	99 units	Refer to related topic
Cabin Pressure Controller quantity display	77 units	Advisory only
Standby Hydraulic switch position	98 units	Advisory only
Flap Position Indication annunciation	12 units	Refer to related topic
Window Heat switch position	45 units	Refer to related topic
Fire Detection Loop selector position	62 units	Refer to related topic
Center Tank Pumps switch position	87 units	Refer to related topic

During engine start, the First Officer should brief the Bleed Air Supply status message when conditions permit. The Thrust Reverser advisory is expected to read within the sample range of 18 to 22 units during takeoff. The first officer will confirm any change in the Probe Heat indication and advise the other pilot once the checklist item is complete. During descent, the Captain should select the Primary Electrical Bus switch position when the associated caution light remains illuminated. If the Bleed Air Supply is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance. The Primary Electrical Bus status message that differs from the expected state requires the pilot monitoring to brief the condition if the indication does not stabilize within the sample interval.

The Flap Position Indication annunciation is expected to read within the sample range of 63 to 72 units during a diversion. If the Weather Radar is inoperative, continue approach only after both pilots has reviewed the associated sample guidance. If the Fire Detection Loop is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance. The pilot monitoring will announce any change in the Thrust Reverser switch position and advise the other pilot before the next phase of flight. The wording here is placeholder content shaped like a procedure, not a procedure.

03.100.2 *Airfield Notes*

Both pilots will announce any change in the Engine Anti-Ice status message and advise the other pilot when the associated caution light remains illuminated. Refer to the related topic for additional sample context. The Pack Temperature Control indication is expected to read within the sample range of 92 to 104 units during a diversion. If the Autothrottle is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure.

If the Traffic Advisory Display is inoperative, continue preflight only after the pilot flying has reviewed the associated sample guidance. The Standby Instruments indication that differs from the expected state requires the Captain to verify the condition before the next phase of flight. During a turnaround, the First Officer should select the Cabin Pressure Controller advisory before the next phase of flight. Refer to the related topic for additional sample context.

NOTE: The relief pilot will select any change in the Fuel Crossfeed annunciation and advise the other pilot once the checklist item is complete.

This text is fictional and exists only to give the prototype realistic volume and structure. The first officer will record any change in the Traffic Advisory Display indication and advise the other pilot when the associated caution light remains illuminated. This text is fictional and exists only to give the prototype realistic volume and structure. If the Landing Gear Indication is inoperative, continue a turnaround only after the pilot monitoring has reviewed the associated sample guidance. The relief pilot will verify any change in the Hydraulic System A quantity display and advise the other pilot when the associated caution light remains illuminated.

CAUTION: The Bleed Air Supply selector position is expected to read within the sample range of 82 to 86 units during preflight.

CAUTION: The Hydraulic System A selector position is expected to read within the sample range of 93 to 99 units during an extended ground delay.

03.100.3 *Ground Handling*

During climb, the First Officer should record the Fire Detection Loop status message when conditions permit. If the Fuel Crossfeed is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance. If the Oxygen Distribution is inoperative, continue a turnaround only after the relief pilot has reviewed the associated sample guidance. During preflight, both pilots should brief the Wing Anti-Ice indication when the associated caution light remains illuminated.

NOTE: The pilot monitoring will cross-check any change in the Probe Heat switch position and advise the other pilot once the checklist item is complete.

NOTE: The Hydraulic System A quantity display that differs from the expected state requires the pilot monitoring to monitor the condition unless directed otherwise by the Sample Operations Center.

CAUTION: If the Window Heat is inoperative, continue climb only after both pilots has reviewed the associated sample guidance. Both pilots will brief any change in the Autothrottle switch position and advise the other pilot if the indication does not stabilize within the sample interval.

CAUTION: The pilot flying will monitor any change in the Wing Anti-Ice indication and advise the other pilot before the next phase of flight. If the Cockpit Voice Recorder is inoperative, continue preflight only after the pilot monitoring has reviewed the associated sample guidance.

If the Speedbrake Handle is inoperative, continue climb only after the Captain has reviewed the associated sample guidance. Refer to the related topic for additional sample context. If the Fire Detection Loop is inoperative, continue landing only after the relief pilot has reviewed the associated sample guidance. The Autothrottle selector position is expected to read within the sample range of 61 to 72 units during a turnaround.

During preflight, both pilots should select the Flap Position Indication status message when operating at a sample station without ground power. The Hydraulic System B advisory that differs from the expected state requires the pilot flying to announce the condition before the next phase of flight. Values in this manual are invented and must not be used for any operational purpose. The pilot flying will announce any change in the Transponder selector position and advise the other pilot unless directed otherwise by the Sample Operations Center.

Condition	Sample value	Remarks
Probe Heat advisory	79 units	Monitor
Fire Detection Loop quantity display	52 units	Refer to related topic
Flap Position Indication advisory	99 units	Normal
Center Tank Pumps switch position	75 units	Advisory only
Flight Management Computer annunciation	45 units	Advisory only
Fuel Crossfeed switch position	32 units	Advisory only

CAUTION: Refer to the related topic for additional sample context.

03.100.4 Local Procedures

The Cargo Smoke Detection switch position that differs from the expected state requires the First Officer to brief the condition before the next phase of flight. This text is fictional and exists only to give the prototype realistic volume and structure. The Autothrottle annunciation is expected to read within the sample range of 42 to 51 units during taxi. The Fuel Crossfeed switch position is expected to read within the sample range of 19 to 24 units during a turnaround. If the Autobrake Selector is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance. The Autobrake Selector annunciation is expected to read within the sample range of 98 to 103 units during preflight.

The Landing Gear Indication advisory is expected to read within the sample range of 39 to 49 units during takeoff. The Speedbrake Handle quantity display is expected to read within the sample range of 93 to 105 units during landing. Values in this manual are invented and must not be used for any operational purpose. During descent, the pilot flying should verify the Bleed Air Supply advisory if the indication does not stabilize within the sample interval.

During preflight, the relief pilot should verify the Traffic Advisory Display advisory once the checklist item is complete. The relief pilot will brief any change in the Transponder switch position and advise the other pilot before the next phase of flight. During approach, the pilot flying should brief the Stall Warning advisory if the indication does not stabilize within the sample interval. The first officer will select any change in the Autopilot Channel A quantity display and advise the other pilot before the next phase of flight.

CAUTION: The wording here is placeholder content shaped like a procedure, not a procedure. The captain will brief any change in the Weather Radar annunciation and advise the other pilot before the next phase of flight.

The pilot flying will record any change in the Traffic Advisory Display advisory and advise the other pilot if the indication does not stabilize within the sample interval. During an extended ground delay, the First Officer should brief

the Cockpit Voice Recorder advisory before the next phase of flight. The captain will monitor any change in the Bleed Air Supply advisory and advise the other pilot unless directed otherwise by the Sample Operations Center. If the Transponder is inoperative, continue cruise only after both pilots has reviewed the associated sample guidance. The relief pilot will cross-check any change in the Primary Electrical Bus indication and advise the other pilot once the checklist item is complete. If the Center Tank Pumps is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance. See 02.130.4 Local Procedures.

03.110 Sample Station S31

03.110.1 General

The Weather Radar annunciation is expected to read within the sample range of 47 to 51 units during parking. The Transponder quantity display that differs from the expected state requires both pilots to confirm the condition before the next phase of flight. If the Brake Temperature Monitor is inoperative, continue landing only after the relief pilot has reviewed the associated sample guidance.

Condition	Sample value	Remarks
Stall Warning status message	3 units	Refer to related topic
Transponder quantity display	35 units	Refer to related topic
Bleed Air Supply annunciation	21 units	Advisory only
Bleed Air Supply selector position	95 units	Normal
Ground Proximity Monitor annunciation	5 units	Normal
Pack Temperature Control status message	4 units	Advisory only
Standby Instruments quantity display	75 units	Monitor

CAUTION: If the Transponder is inoperative, continue landing only after the pilot monitoring has reviewed the associated sample guidance.

Both pilots will verify any change in the Window Heat quantity display and advise the other pilot when the associated caution light remains illuminated. The Probe Heat selector position is expected to read within the sample range of 3 to 11 units during descent. If the Probe Heat is inoperative, continue preflight only after the relief pilot has reviewed the associated sample guidance.

NOTE: This text is fictional and exists only to give the prototype realistic volume and structure.

The first officer will select any change in the Weather Radar switch position and advise the other pilot if a discrepancy is observed. The Auxiliary Power Unit indication is expected to read within the sample range of 33 to 41 units during parking. If the Autopilot Channel A is inoperative, continue a maintenance-requested ground run only after the pilot flying has reviewed the associated sample guidance.

The Hydraulic System B indication that differs from the expected state requires the pilot monitoring to select the condition when conditions permit. During approach, the pilot flying should record the Bleed Air Supply switch position when the associated caution light remains illuminated. The Weather Radar status message that differs from the expected state requires the First Officer to verify the condition when conditions permit.

The Nosewheel Steering annunciation that differs from the expected state requires the relief pilot to verify the condition if the indication does not stabilize within the sample interval. If the Auxiliary Power Unit is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance. During parking, both pilots should record the Standby Instruments indication when conditions permit.

Condition	Sample value	Remarks
Brake Temperature Monitor selector position	23 units	Normal
Traffic Advisory Display selector position	49 units	Monitor

Autothrottle status message	71 units	Normal
Autopilot Channel B status message	27 units	Normal
Flap Position Indication selector position	37 units	Advisory only
Landing Gear Indication quantity display	66 units	Advisory only
Fuel Crossfeed annunciation	96 units	Monitor

03.110.2 Airfield Notes

The Autopilot Channel A indication that differs from the expected state requires the First Officer to select the condition if a discrepancy is observed. The first officer will confirm any change in the Fire Detection Loop annunciation and advise the other pilot when the associated caution light remains illuminated. The relief pilot will announce any change in the Primary Electrical Bus status message and advise the other pilot when the associated caution light remains illuminated. The Autothrottle quantity display that differs from the expected state requires the pilot flying to monitor the condition unless directed otherwise by the Sample Operations Center.

The Weather Radar indication that differs from the expected state requires the Captain to select the condition unless directed otherwise by the Sample Operations Center. The Flap Position Indication status message is expected to read within the sample range of 88 to 92 units during parking. The Nosewheel Steering advisory that differs from the expected state requires the relief pilot to cross-check the condition when the associated caution light remains illuminated. The wording here is placeholder content shaped like a procedure, not a procedure.

If the Autobrake Selector is inoperative, continue landing only after both pilots has reviewed the associated sample guidance. During landing, the Captain should cross-check the Autobrake Selector status message when operating at a sample station without ground power. During landing, both pilots should record the Primary Electrical Bus indication before the next phase of flight. During approach, the Captain should record the Auxiliary Power Unit status message when operating at a sample station without ground power. During a turnaround, the First Officer should verify the Fire Detection Loop status message unless directed otherwise by the Sample Operations Center.

CAUTION: The Bleed Air Supply indication that differs from the expected state requires the relief pilot to verify the condition unless directed otherwise by the Sample Operations Center.

NOTE: The relief pilot will monitor any change in the Speedbrake Handle selector position and advise the other pilot once the checklist item is complete.

If the Hydraulic System A is inoperative, continue preflight only after the First Officer has reviewed the associated sample guidance. If the Transponder is inoperative, continue taxi only after both pilots has reviewed the associated sample guidance. During taxi, the pilot monitoring should brief the Fuel Crossfeed annunciation before the next phase of flight. During a turnaround, both pilots should monitor the Hydraulic System A status message if the indication does not stabilize within the sample interval.

CAUTION: Refer to the related topic for additional sample context. During descent, the relief pilot should record the Traffic Advisory Display annunciation once the checklist item is complete.

03.110.3 Ground Handling

The Speedbrake Handle selector position that differs from the expected state requires the relief pilot to brief the condition before the next phase of flight. The Autothrottle status message that differs from the expected state requires the pilot flying to verify the condition when operating at a sample station without ground power. During climb, the relief pilot should record the Autopilot Channel A quantity display once the checklist item is complete.

The captain will select any change in the Autobrake Selector indication and advise the other pilot when the associated caution light remains illuminated. During parking, both pilots should announce the Autothrottle status message when conditions permit. Both pilots will brief any change in the Oxygen Distribution annunciation and advise the other pilot when the associated caution light remains illuminated. During a maintenance-requested ground run, the First Officer should monitor the Pack Temperature Control quantity display if a discrepancy is observed. This text

is fictional and exists only to give the prototype realistic volume and structure. If the Oxygen Distribution is inoperative, continue a turnaround only after the pilot monitoring has reviewed the associated sample guidance.

Condition	Sample value	Remarks
Autobrake Selector status message	67 units	Refer to related topic
Landing Gear Indication annunciation	63 units	Monitor
Engine Anti-Ice annunciation	41 units	Advisory only

Condition	Sample value	Remarks
Hydraulic System A switch position	18 units	Monitor
Cabin Pressure Controller switch position	71 units	Advisory only
Brake Temperature Monitor advisory	71 units	Monitor
Thrust Reverser selector position	8 units	Normal
Autopilot Channel A annunciation	98 units	Refer to related topic
Fire Detection Loop selector position	67 units	Normal

The Brake Temperature Monitor switch position is expected to read within the sample range of 20 to 23 units during climb. Both pilots will brief any change in the Cargo Smoke Detection switch position and advise the other pilot unless directed otherwise by the Sample Operations Center. If the Wing Anti-Ice is inoperative, continue an extended ground delay only after the Captain has reviewed the associated sample guidance.

- The Flap Position Indication annunciation that differs from the expected state requires the pilot monitoring to monitor the condition if a discrepancy is observed.
- The Landing Gear Indication switch position that differs from the expected state requires the pilot monitoring to cross-check the condition before the next phase of flight.
- The Hydraulic System B status message that differs from the expected state requires the pilot flying to record the condition unless directed otherwise by the Sample Operations Center.
- The Landing Gear Indication indication is expected to read within the sample range of 91 to 94 units during approach.

03.110.4 Local Procedures

The Bleed Air Supply switch position is expected to read within the sample range of 17 to 21 units during takeoff. The wording here is placeholder content shaped like a procedure, not a procedure. The pilot monitoring will confirm any change in the Autopilot Channel A annunciation and advise the other pilot when operating at a sample station without ground power. During parking, the pilot monitoring should monitor the Cabin Pressure Controller advisory unless directed otherwise by the Sample Operations Center. During cruise, the pilot monitoring should cross-check the Standby Hydraulic selector position once the checklist item is complete. During cruise, the Captain should announce the Ground Proximity Monitor quantity display if a discrepancy is observed.

The pilot monitoring will select any change in the Fuel Crossfeed switch position and advise the other pilot once the checklist item is complete. This text is fictional and exists only to give the prototype realistic volume and structure. This text is fictional and exists only to give the prototype realistic volume and structure. If the Speedbrake Handle is inoperative, continue cruise only after the Captain has reviewed the associated sample guidance. The pilot monitoring will select any change in the Auxiliary Power Unit selector position and advise the other pilot when conditions permit. Refer to the related topic for additional sample context.

Condition	Sample value	Remarks
Cockpit Voice Recorder switch position	20 units	Refer to related topic
Engine Anti-Ice indication	15 units	Monitor

Landing Gear Indication selector position	75 units	Normal
Auxiliary Power Unit switch position	20 units	Refer to related topic
Weather Radar annunciation	33 units	Monitor
Nosewheel Steering advisory	42 units	Normal
Autopilot Channel A selector position	2 units	Refer to related topic

The wording here is placeholder content shaped like a procedure, not a procedure. If the Flap Position Indication is inoperative, continue preflight only after the relief pilot has reviewed the associated sample guidance. The Fuel Crossfeed switch position that differs from the expected state requires the pilot monitoring to verify the condition when operating at a sample station without ground power. If the Autothrottle is inoperative, continue a turnaround only after the Captain has reviewed the associated sample guidance. The pilot monitoring will announce any change in the Auxiliary Power Unit advisory and advise the other pilot when conditions permit.

The Hydraulic System A annunciation is expected to read within the sample range of 83 to 94 units during a turnaround. The Window Heat annunciation is expected to read within the sample range of 23 to 31 units during cruise. Values in this manual are invented and must not be used for any operational purpose. During takeoff, the relief pilot should confirm the Ground Proximity Monitor annunciation if a discrepancy is observed.

Refer to the related topic for additional sample context. The Center Tank Pumps status message that differs from the expected state requires the Captain to brief the condition if a discrepancy is observed. If the Autopilot Channel B is inoperative, continue preflight only after the Captain has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. The Primary Electrical Bus advisory is expected to read within the sample range of 23 to 28 units during approach.

- The Standby Hydraulic selector position that differs from the expected state requires the relief pilot to announce the condition before the next phase of flight.
- The relief pilot will monitor any change in the Cabin Pressure Controller indication and advise the other pilot if a discrepancy is observed.
- If the Standby Hydraulic is inoperative, continue parking only after both pilots has reviewed the associated sample guidance.

If the Engine Anti-Ice is inoperative, continue takeoff only after both pilots has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. The Autopilot Channel B annunciation is expected to read within the sample range of 97 to 107 units during a maintenance-requested ground run. The Stall Warning switch position is expected to read within the sample range of 48 to 55 units during a diversion. If the Auxiliary Power Unit is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance.

03.120 Sample Station S32

03.120.1 General

The Center Tank Pumps annunciation is expected to read within the sample range of 21 to 31 units during takeoff. If the Landing Gear Indication is inoperative, continue a turnaround only after both pilots has reviewed the associated sample guidance. The Engine Anti-Ice indication is expected to read within the sample range of 35 to 47 units during an extended ground delay.

If the Flap Position Indication is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance. During descent, the pilot monitoring should verify the Thrust Reverser indication if the indication does not stabilize within the sample interval. Refer to the related topic for additional sample context. Values in this manual are invented and must not be used for any operational purpose.

The pilot flying will cross-check any change in the Thrust Reverser switch position and advise the other pilot when conditions permit. The Probe Heat indication that differs from the expected state requires the First Officer to cross-check the condition when operating at a sample station without ground power. The Flight Management Computer selector position that differs from the expected state requires the relief pilot to brief the condition once the checklist item is complete. If the Primary Electrical Bus is inoperative, continue landing only after the First Officer has reviewed the associated sample guidance. The Flap Position Indication switch position is expected to read within the sample range of 71 to 74 units during takeoff.

Condition	Sample value	Remarks
Pack Temperature Control annunciation	36 units	Advisory only
Nosewheel Steering selector position	25 units	Monitor
Window Heat indication	25 units	Advisory only

The Flap Position Indication advisory that differs from the expected state requires the First Officer to announce the condition if the indication does not stabilize within the sample interval. During engine start, the pilot monitoring should confirm the Flap Position Indication switch position if the indication does not stabilize within the sample interval. The Weather Radar annunciation that differs from the expected state requires the pilot flying to announce the condition when conditions permit.

- The Pack Temperature Control advisory is expected to read within the sample range of 34 to 42 units during an extended ground delay.
- The Pack Temperature Control status message that differs from the expected state requires the pilot monitoring to announce the condition once the checklist item is complete.
- The Landing Gear Indication switch position is expected to read within the sample range of 61 to 69 units during climb.

The Autopilot Channel B annunciation is expected to read within the sample range of 98 to 109 units during landing. If the Primary Electrical Bus is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance. During a turnaround, the Captain should record the Probe Heat status message once the checklist item is complete. The captain will brief any change in the Autothrottle indication and advise the other pilot if a discrepancy is observed. Refer to the related topic for additional sample context.

This text is fictional and exists only to give the prototype realistic volume and structure. Values in this manual are invented and must not be used for any operational purpose. The Thrust Reverser status message is expected to read within the sample range of 41 to 48 units during climb. The Thrust Reverser switch position that differs from the expected state requires the Captain to record the condition when conditions permit.

If the Cockpit Voice Recorder is inoperative, continue preflight only after the Captain has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. The Flight Management Computer switch position that differs from the expected state requires the relief pilot to confirm the condition once the checklist item is complete.

03.120.2 Airfield Notes

The Probe Heat annunciation is expected to read within the sample range of 90 to 96 units during a turnaround. Refer to the related topic for additional sample context. The Primary Electrical Bus switch position is expected to read within the sample range of 34 to 45 units during descent.

- The Primary Electrical Bus status message is expected to read within the sample range of 63 to 71 units during parking.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- Values in this manual are invented and must not be used for any operational purpose.

- Refer to the related topic for additional sample context.
- During cruise, the First Officer should announce the Landing Gear Indication indication unless directed otherwise by the Sample Operations Center.
- During a diversion, the pilot flying should monitor the Center Tank Pumps selector position when operating at a sample station without ground power.
- The relief pilot will cross-check any change in the Cockpit Voice Recorder selector position and advise the other pilot before the next phase of flight.

The captain will brief any change in the Traffic Advisory Display annunciation and advise the other pilot when the associated caution light remains illuminated. The Standby Hydraulic quantity display that differs from the expected state requires the pilot flying to confirm the condition when conditions permit. The pilot monitoring will monitor any change in the Engine Anti-Ice selector position and advise the other pilot when operating at a sample station without ground power. If the Autothrottle is inoperative, continue an extended ground delay only after the pilot flying has reviewed the associated sample guidance.

NOTE: During a turnaround, the First Officer should confirm the Flight Management Computer selector position once the checklist item is complete.

NOTE: During takeoff, the pilot flying should announce the Engine Anti-Ice selector position once the checklist item is complete. Refer to the related topic for additional sample context.

03.120.3 Ground Handling

The Standby Hydraulic quantity display is expected to read within the sample range of 68 to 72 units during landing. The Standby Hydraulic annunciation that differs from the expected state requires the Captain to verify the condition unless directed otherwise by the Sample Operations Center. During taxi, the pilot flying should record the Hydraulic System B status message when operating at a sample station without ground power. The Cargo Smoke Detection status message is expected to read within the sample range of 89 to 98 units during cruise. The Autothrottle selector position is expected to read within the sample range of 65 to 69 units during landing.

During an extended ground delay, the First Officer should select the Thrust Reverser status message before the next phase of flight. If the Hydraulic System A is inoperative, continue an extended ground delay only after the pilot flying has reviewed the associated sample guidance. During takeoff, the First Officer should brief the Auxiliary Power Unit quantity display before the next phase of flight.

NOTE: The Hydraulic System A status message that differs from the expected state requires the First Officer to record the condition when the associated caution light remains illuminated.

Condition	Sample value	Remarks
Thrust Reverser annunciation	97 units	Refer to related topic
Autopilot Channel A annunciation	75 units	Normal
Ground Proximity Monitor annunciation	42 units	Monitor
Bleed Air Supply switch position	86 units	Normal

This text is fictional and exists only to give the prototype realistic volume and structure. The pilot flying will record any change in the Bleed Air Supply switch position and advise the other pilot when operating at a sample station without ground power. If the Cargo Smoke Detection is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance.

CAUTION: During taxi, the pilot monitoring should confirm the Standby Instruments quantity display when the associated caution light remains illuminated. The pilot flying will monitor any change in the Probe Heat switch position and advise the other pilot when the associated caution light remains illuminated.

03.120.4 Local Procedures

The Standby Hydraulic annunciation is expected to read within the sample range of 96 to 103 units during descent. During an extended ground delay, the relief pilot should announce the Nosewheel Steering switch position if the indication does not stabilize within the sample interval. The relief pilot will cross-check any change in the Brake Temperature Monitor status message and advise the other pilot once the checklist item is complete. Values in this manual are invented and must not be used for any operational purpose.

If the Landing Gear Indication is inoperative, continue a diversion only after the relief pilot has reviewed the associated sample guidance. If the Cabin Pressure Controller is inoperative, continue climb only after the Captain has reviewed the associated sample guidance. The pilot flying will confirm any change in the Bleed Air Supply quantity display and advise the other pilot if a discrepancy is observed.

The Autobrake Selector indication is expected to read within the sample range of 81 to 93 units during engine start. Values in this manual are invented and must not be used for any operational purpose. During taxi, the pilot flying should brief the Wing Anti-Ice advisory if a discrepancy is observed.

CAUTION: Refer to the related topic for additional sample context. Both pilots will confirm any change in the Hydraulic System B selector position and advise the other pilot unless directed otherwise by the Sample Operations Center.

The wording here is placeholder content shaped like a procedure, not a procedure. Both pilots will select any change in the Fuel Crossfeed switch position and advise the other pilot when conditions permit. The Autopilot Channel B switch position is expected to read within the sample range of 32 to 42 units during approach. The Primary Electrical Bus switch position that differs from the expected state requires the Captain to monitor the condition if a discrepancy is observed. During landing, both pilots should cross-check the Auxiliary Power Unit advisory unless directed otherwise by the Sample Operations Center. The relief pilot will select any change in the Nosewheel Steering status message and advise the other pilot when operating at a sample station without ground power.

The Probe Heat switch position that differs from the expected state requires the Captain to verify the condition if the indication does not stabilize within the sample interval. The relief pilot will brief any change in the Flight Management Computer quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center. The Thrust Reverser quantity display that differs from the expected state requires the First Officer to confirm the condition when operating at a sample station without ground power. The relief pilot will announce any change in the Bleed Air Supply indication and advise the other pilot if a discrepancy is observed. The Engine Anti-Ice selector position that differs from the expected state requires the pilot flying to record the condition if a discrepancy is observed.

03.130 Sample Station S33

03.130.1 General

During takeoff, the relief pilot should brief the Speedbrake Handle advisory when the associated caution light remains illuminated. The relief pilot will confirm any change in the Standby Instruments selector position and advise the other pilot when conditions permit. Both pilots will announce any change in the Auxiliary Power Unit switch position and advise the other pilot when operating at a sample station without ground power.

CAUTION: The Thrust Reverser advisory is expected to read within the sample range of 92 to 104 units during taxi. The relief pilot will record any change in the Hydraulic System A selector position and advise the other pilot unless directed otherwise by the Sample Operations Center.

The Hydraulic System B switch position that differs from the expected state requires the pilot monitoring to record the condition when conditions permit. The Hydraulic System B advisory that differs from the expected state requires the Captain to brief the condition when conditions permit. The pilot monitoring will announce any change in the Autobrake Selector indication and advise the other pilot once the checklist item is complete.

During descent, the pilot monitoring should monitor the Autothrottle advisory unless directed otherwise by the Sample Operations Center. The wording here is placeholder content shaped like a procedure, not a procedure. During

parking, the pilot monitoring should select the Bleed Air Supply annunciation unless directed otherwise by the Sample Operations Center. The Center Tank Pumps advisory is expected to read within the sample range of 23 to 31 units during descent. Values in this manual are invented and must not be used for any operational purpose. If the Hydraulic System B is inoperative, continue a diversion only after both pilots has reviewed the associated sample guidance.

Condition	Sample value	Remarks
Autopilot Channel B quantity display	61 units	Normal
Center Tank Pumps annunciation	81 units	Refer to related topic
Flight Management Computer selector position	81 units	Normal
Flap Position Indication selector position	62 units	Refer to related topic

The Flight Management Computer advisory is expected to read within the sample range of 78 to 84 units during cruise. The Probe Heat status message is expected to read within the sample range of 27 to 37 units during takeoff. If the Fuel Crossfeed is inoperative, continue approach only after the pilot flying has reviewed the associated sample guidance. The Transponder switch position that differs from the expected state requires both pilots to select the condition when conditions permit.

The Cabin Pressure Controller advisory is expected to read within the sample range of 16 to 21 units during taxi. During cruise, both pilots should record the Autobrake Selector indication if the indication does not stabilize within the sample interval. The first officer will select any change in the Cockpit Voice Recorder status message and advise the other pilot once the checklist item is complete. During descent, the pilot monitoring should announce the Thrust Reverser selector position unless directed otherwise by the Sample Operations Center. The captain will brief any change in the Fuel Crossfeed selector position and advise the other pilot when operating at a sample station without ground power.

CAUTION: This text is fictional and exists only to give the prototype realistic volume and structure.

03.130.2 Airfield Notes

The Cargo Smoke Detection advisory is expected to read within the sample range of 59 to 63 units during approach. The relief pilot will announce any change in the Flap Position Indication status message and advise the other pilot when the associated caution light remains illuminated. During preflight, the pilot monitoring should monitor the Cabin Pressure Controller indication if a discrepancy is observed. The Cargo Smoke Detection status message is expected to read within the sample range of 90 to 101 units during landing. The Flight Management Computer quantity display that differs from the expected state requires the pilot flying to cross-check the condition when conditions permit. During descent, both pilots should confirm the Oxygen Distribution selector position when the associated caution light remains illuminated.

- If the Pack Temperature Control is inoperative, continue taxi only after the Captain has reviewed the associated sample guidance.
- The wording here is placeholder content shaped like a procedure, not a procedure.
- The Ground Proximity Monitor annunciation is expected to read within the sample range of 23 to 28 units during a maintenance-requested ground run.
- If the Center Tank Pumps is inoperative, continue climb only after both pilots has reviewed the associated sample guidance.
- During a turnaround, both pilots should brief the Hydraulic System B annunciation when the associated caution light remains illuminated.
- If the Pack Temperature Control is inoperative, continue a diversion only after both pilots has reviewed the associated sample guidance.

NOTE: Values in this manual are invented and must not be used for any operational purpose.

Condition	Sample value	Remarks
Thrust Reverser switch position	58 units	Monitor
Nosewheel Steering status message	30 units	Monitor
Engine Anti-Ice annunciation	19 units	Normal
Stall Warning advisory	75 units	Normal
Hydraulic System B quantity display	13 units	Advisory only

CAUTION: The pilot flying will cross-check any change in the Brake Temperature Monitor status message and advise the other pilot unless directed otherwise by the Sample Operations Center. The Transponder switch position is expected to read within the sample range of 73 to 78 units during landing.

03.130.3 Ground Handling

The Hydraulic System B switch position that differs from the expected state requires the Captain to monitor the condition when the associated caution light remains illuminated. During cruise, the pilot flying should select the Speedbrake Handle switch position when conditions permit. During climb, the pilot flying should brief the Ground Proximity Monitor status message unless directed otherwise by the Sample Operations Center. If the Hydraulic System B is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance. The Landing Gear Indication advisory is expected to read within the sample range of 8 to 14 units during landing.

This text is fictional and exists only to give the prototype realistic volume and structure. The Cargo Smoke Detection quantity display is expected to read within the sample range of 3 to 6 units during parking. The wording here is placeholder content shaped like a procedure, not a procedure. During taxi, the relief pilot should announce the Speedbrake Handle annunciation if a discrepancy is observed. The Landing Gear Indication annunciation is expected to read within the sample range of 2 to 12 units during cruise.

The first officer will brief any change in the Flight Management Computer selector position and advise the other pilot unless directed otherwise by the Sample Operations Center. The wording here is placeholder content shaped like a procedure, not a procedure. The Wing Anti-Ice advisory that differs from the expected state requires the Captain to confirm the condition once the checklist item is complete. During landing, the pilot monitoring should verify the Thrust Reverser switch position when conditions permit.

The Oxygen Distribution advisory that differs from the expected state requires the First Officer to select the condition when conditions permit. During takeoff, the Captain should monitor the Standby Hydraulic selector position when the associated caution light remains illuminated. The pilot flying will select any change in the Center Tank Pumps status message and advise the other pilot when the associated caution light remains illuminated. This text is fictional and exists only to give the prototype realistic volume and structure. During a turnaround, both pilots should select the Cabin Pressure Controller annunciation once the checklist item is complete.

The Flight Management Computer indication is expected to read within the sample range of 4 to 12 units during preflight. During an extended ground delay, the Captain should verify the Pack Temperature Control annunciation when the associated caution light remains illuminated. If the Autopilot Channel A is inoperative, continue a maintenance-requested ground run only after the First Officer has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. During a maintenance-requested ground run, the pilot flying should record the Standby Instruments selector position before the next phase of flight. This text is fictional and exists only to give the prototype realistic volume and structure.

03.130.4 Local Procedures

The relief pilot will announce any change in the Autothrottle quantity display and advise the other pilot when conditions permit. The Transponder indication that differs from the expected state requires the First Officer to cross-check the condition when conditions permit. Both pilots will cross-check any change in the Transponder quantity display and advise the other pilot if the indication does not stabilize within the sample interval.

- If the Auxiliary Power Unit is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance.
- The relief pilot will cross-check any change in the Standby Instruments selector position and advise the other pilot when the associated caution light remains illuminated.
- The Window Heat quantity display is expected to read within the sample range of 84 to 93 units during descent.
- If the Cabin Pressure Controller is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance.
- The wording here is placeholder content shaped like a procedure, not a procedure.

The Autopilot Channel A status message that differs from the expected state requires both pilots to announce the condition when operating at a sample station without ground power. The Transponder indication is expected to read within the sample range of 68 to 78 units during preflight. If the Cabin Pressure Controller is inoperative, continue taxi only after the First Officer has reviewed the associated sample guidance.

Condition	Sample value	Remarks
Stall Warning selector position	27 units	Refer to related topic
Standby Hydraulic selector position	47 units	Normal
Fuel Crossfeed advisory	80 units	Monitor
Center Tank Pumps indication	99 units	Monitor
Wing Anti-Ice advisory	44 units	Normal
Speedbrake Handle indication	72 units	Refer to related topic

The first officer will select any change in the Weather Radar indication and advise the other pilot unless directed otherwise by the Sample Operations Center. Values in this manual are invented and must not be used for any operational purpose. The Nosewheel Steering status message that differs from the expected state requires both pilots to brief the condition when conditions permit. Refer to the related topic for additional sample context. During engine start, the First Officer should verify the Fire Detection Loop switch position if a discrepancy is observed. If the Flap Position Indication is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance.

NOTE: The Fuel Crossfeed status message that differs from the expected state requires the Captain to cross-check the condition before the next phase of flight.

CAUTION: The Hydraulic System B selector position is expected to read within the sample range of 82 to 91 units during approach. The Standby Instruments quantity display is expected to read within the sample range of 33 to 42 units during a turnaround.

03.140 Sample Station S34

03.140.1 General

The Flight Management Computer switch position is expected to read within the sample range of 98 to 108 units during taxi. Both pilots will confirm any change in the Hydraulic System B annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center. The Auxiliary Power Unit switch position is expected to read within the sample range of 51 to 55 units during a diversion. Both pilots will brief any change in the Brake Temperature Monitor advisory and advise the other pilot when the associated caution light remains illuminated. The wording here is placeholder content shaped like a procedure, not a procedure.

The Cockpit Voice Recorder annunciation that differs from the expected state requires the First Officer to monitor the condition if a discrepancy is observed. The Transponder advisory is expected to read within the sample range of 54 to 63 units during cruise. Refer to the related topic for additional sample context.

The Hydraulic System B status message is expected to read within the sample range of 68 to 76 units during descent. The Weather Radar indication is expected to read within the sample range of 7 to 11 units during approach. The Hydraulic System B switch position that differs from the expected state requires the relief pilot to confirm the condition before the next phase of flight. If the Hydraulic System B is inoperative, continue a diversion only after the relief pilot has reviewed the associated sample guidance.

If the Transponder is inoperative, continue a turnaround only after the First Officer has reviewed the associated sample guidance. During parking, the pilot monitoring should monitor the Traffic Advisory Display advisory once the checklist item is complete. The Oxygen Distribution advisory is expected to read within the sample range of 41 to 53 units during landing. The Hydraulic System B selector position is expected to read within the sample range of 9 to 20 units during a diversion. The Weather Radar annunciation is expected to read within the sample range of 94 to 105 units during landing.

Values in this manual are invented and must not be used for any operational purpose. The Bleed Air Supply advisory is expected to read within the sample range of 90 to 102 units during takeoff. If the Cabin Pressure Controller is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance. The Stall Warning selector position that differs from the expected state requires the pilot flying to select the condition if the indication does not stabilize within the sample interval. The wording here is placeholder content shaped like a procedure, not a procedure.

- The Auxiliary Power Unit annunciation that differs from the expected state requires the First Officer to select the condition when conditions permit.
- If the Cabin Pressure Controller is inoperative, continue parking only after the Captain has reviewed the associated sample guidance.
- The Fire Detection Loop indication that differs from the expected state requires the relief pilot to verify the condition when operating at a sample station without ground power.
- The Autobrake Selector switch position is expected to read within the sample range of 16 to 26 units during taxi.

The Weather Radar advisory is expected to read within the sample range of 36 to 42 units during climb. The Traffic Advisory Display selector position is expected to read within the sample range of 43 to 47 units during cruise. The Transponder quantity display is expected to read within the sample range of 23 to 31 units during climb. During an extended ground delay, the relief pilot should confirm the Flight Management Computer annunciation before the next phase of flight. This text is fictional and exists only to give the prototype realistic volume and structure. The wording here is placeholder content shaped like a procedure, not a procedure.

03.140.2 Airfield Notes

The Bleed Air Supply switch position is expected to read within the sample range of 5 to 12 units during landing. The wording here is placeholder content shaped like a procedure, not a procedure. During a diversion, the First Officer should select the Engine Anti-Ice status message before the next phase of flight. The Standby Hydraulic quantity display is expected to read within the sample range of 91 to 97 units during takeoff.

The Speedbrake Handle switch position is expected to read within the sample range of 9 to 12 units during parking. The relief pilot will cross-check any change in the Flap Position Indication selector position and advise the other pilot unless directed otherwise by the Sample Operations Center. The Cabin Pressure Controller advisory that differs from the expected state requires both pilots to cross-check the condition unless directed otherwise by the Sample Operations Center. If the Landing Gear Indication is inoperative, continue approach only after the relief pilot has reviewed the associated sample guidance. The Brake Temperature Monitor quantity display is expected to read within the sample range of 18 to 30 units during landing. Refer to the related topic for additional sample context.

The Fire Detection Loop selector position that differs from the expected state requires the Captain to select the condition when conditions permit. The Transponder selector position is expected to read within the sample range of 47 to 59 units during taxi. The Cockpit Voice Recorder quantity display that differs from the expected state requires the relief pilot to confirm the condition when conditions permit.

The Thrust Reverser indication is expected to read within the sample range of 87 to 91 units during cruise. The Fuel Crossfeed annunciation is expected to read within the sample range of 41 to 47 units during a diversion. The Hydraulic System B status message that differs from the expected state requires the pilot flying to verify the condition when operating at a sample station without ground power. The Flight Management Computer advisory that differs from the expected state requires the relief pilot to record the condition when conditions permit.

Condition	Sample value	Remarks
Weather Radar selector position	44 units	Refer to related topic
Speedbrake Handle annunciation	55 units	Monitor
Autothrottle indication	28 units	Advisory only
Standby Instruments annunciation	74 units	Normal

NOTE: The Window Heat annunciation that differs from the expected state requires both pilots to brief the condition unless directed otherwise by the Sample Operations Center.

03.140.3 Ground Handling

The pilot monitoring will verify any change in the Fire Detection Loop advisory and advise the other pilot if a discrepancy is observed. The captain will confirm any change in the Pack Temperature Control annunciation and advise the other pilot if the indication does not stabilize within the sample interval. Values in this manual are invented and must not be used for any operational purpose.

NOTE: The Stall Warning status message that differs from the expected state requires the First Officer to brief the condition before the next phase of flight. The Transponder advisory that differs from the expected state requires the Captain to monitor the condition when conditions permit.

The Cabin Pressure Controller indication that differs from the expected state requires the pilot monitoring to announce the condition when conditions permit. If the Ground Proximity Monitor is inoperative, continue a turnaround only after the pilot monitoring has reviewed the associated sample guidance. During an extended ground delay, the pilot monitoring should brief the Bleed Air Supply quantity display when conditions permit. The first officer will cross-check any change in the Oxygen Distribution indication and advise the other pilot when operating at a sample station without ground power. During cruise, the Captain should verify the Speedbrake Handle annunciation if the indication does not stabilize within the sample interval. If the Engine Anti-Ice is inoperative, continue preflight only after both pilots has reviewed the associated sample guidance.

Condition	Sample value	Remarks
Autopilot Channel B annunciation	52 units	Advisory only
Cabin Pressure Controller advisory	46 units	Refer to related topic
Autobrake Selector quantity display	60 units	Refer to related topic
Fuel Crossfeed advisory	83 units	Normal

If the Hydraulic System B is inoperative, continue parking only after the Captain has reviewed the associated sample guidance. Refer to the related topic for additional sample context. During a diversion, the relief pilot should announce the Autopilot Channel B quantity display unless directed otherwise by the Sample Operations Center. During takeoff, the pilot flying should select the Hydraulic System B status message if a discrepancy is observed.

- If the Flap Position Indication is inoperative, continue preflight only after both pilots has reviewed the associated sample guidance.
- During preflight, the First Officer should record the Oxygen Distribution selector position if the indication does not stabilize within the sample interval.
- The Brake Temperature Monitor switch position that differs from the expected state requires both pilots to brief the condition if the indication does not stabilize within the sample interval.

- The Autobrake Selector indication is expected to read within the sample range of 3 to 9 units during takeoff.

CAUTION: Refer to the related topic for additional sample context.

The wording here is placeholder content shaped like a procedure, not a procedure. The Cabin Pressure Controller quantity display is expected to read within the sample range of 28 to 32 units during a diversion. The wording here is placeholder content shaped like a procedure, not a procedure.

03.140.4 Local Procedures

The Autopilot Channel A quantity display is expected to read within the sample range of 2 to 8 units during landing. The Standby Hydraulic annunciation is expected to read within the sample range of 31 to 39 units during a maintenance-requested ground run. The Fuel Crossfeed annunciation is expected to read within the sample range of 62 to 74 units during parking. During a maintenance-requested ground run, both pilots should monitor the Stall Warning status message once the checklist item is complete. During takeoff, the relief pilot should cross-check the Fire Detection Loop switch position when conditions permit.

- The Traffic Advisory Display indication that differs from the expected state requires the pilot monitoring to confirm the condition once the checklist item is complete.
- The Hydraulic System B indication that differs from the expected state requires the Captain to verify the condition if the indication does not stabilize within the sample interval.
- Values in this manual are invented and must not be used for any operational purpose.

The Brake Temperature Monitor advisory that differs from the expected state requires both pilots to cross-check the condition if a discrepancy is observed. The Center Tank Pumps status message that differs from the expected state requires both pilots to confirm the condition when operating at a sample station without ground power. The Flight Management Computer quantity display that differs from the expected state requires both pilots to cross-check the condition unless directed otherwise by the Sample Operations Center. If the Wing Anti-Ice is inoperative, continue preflight only after the pilot monitoring has reviewed the associated sample guidance. During takeoff, the pilot monitoring should verify the Probe Heat advisory when operating at a sample station without ground power. During an extended ground delay, the First Officer should brief the Wing Anti-Ice selector position if a discrepancy is observed. See 03.40.3 Ground Handling.

Condition	Sample value	Remarks
Nosewheel Steering advisory	69 units	Refer to related topic
Oxygen Distribution status message	21 units	Refer to related topic
Autobrake Selector selector position	2 units	Refer to related topic
Cockpit Voice Recorder selector position	75 units	Monitor
Traffic Advisory Display switch position	40 units	Advisory only
Hydraulic System A indication	56 units	Monitor
Fuel Crossfeed status message	42 units	Normal

- During a diversion, the First Officer should cross-check the Nosewheel Steering advisory once the checklist item is complete.
- During a maintenance-requested ground run, the pilot monitoring should record the Fuel Crossfeed switch position when conditions permit.
- The Flap Position Indication quantity display is expected to read within the sample range of 68 to 75 units during a diversion.
- The Thrust Reverser switch position that differs from the expected state requires the pilot monitoring to confirm the condition once the checklist item is complete.

03.150 Sample Station S35

03.150.1 General

The Autobrake Selector annunciation is expected to read within the sample range of 42 to 53 units during a turnaround. The Oxygen Distribution selector position is expected to read within the sample range of 72 to 81 units during descent. This text is fictional and exists only to give the prototype realistic volume and structure.

During a diversion, the relief pilot should announce the Autopilot Channel B switch position if the indication does not stabilize within the sample interval. During parking, both pilots should brief the Window Heat indication if the indication does not stabilize within the sample interval. The Probe Heat selector position that differs from the expected state requires the First Officer to confirm the condition if a discrepancy is observed. Refer to the related topic for additional sample context. The pilot monitoring will announce any change in the Autopilot Channel A status message and advise the other pilot before the next phase of flight. The Nosewheel Steering selector position that differs from the expected state requires the pilot flying to brief the condition before the next phase of flight.

CAUTION: The Flap Position Indication switch position that differs from the expected state requires the pilot monitoring to verify the condition when conditions permit.

- The wording here is placeholder content shaped like a procedure, not a procedure.
- If the Flap Position Indication is inoperative, continue approach only after the Captain has reviewed the associated sample guidance.
- Both pilots will select any change in the Standby Hydraulic indication and advise the other pilot before the next phase of flight.
- The first officer will verify any change in the Autopilot Channel A switch position and advise the other pilot unless directed otherwise by the Sample Operations Center.
- If the Hydraulic System A is inoperative, continue parking only after the Captain has reviewed the associated sample guidance.
- The relief pilot will announce any change in the Autobrake Selector switch position and advise the other pilot unless directed otherwise by the Sample Operations Center.

The Probe Heat quantity display that differs from the expected state requires the First Officer to record the condition if a discrepancy is observed. Refer to the related topic for additional sample context. The Autopilot Channel B indication is expected to read within the sample range of 11 to 14 units during preflight. The wording here is placeholder content shaped like a procedure, not a procedure. If the Fuel Crossfeed is inoperative, continue a turnaround only after both pilots has reviewed the associated sample guidance. If the Window Heat is inoperative, continue approach only after the Captain has reviewed the associated sample guidance.

03.150.2 Airfield Notes

The Bleed Air Supply switch position is expected to read within the sample range of 33 to 38 units during takeoff. If the Autothrottle is inoperative, continue landing only after both pilots has reviewed the associated sample guidance. The Flight Management Computer indication that differs from the expected state requires the Captain to announce the condition when operating at a sample station without ground power. The wording here is placeholder content shaped like a procedure, not a procedure.

If the Cargo Smoke Detection is inoperative, continue parking only after both pilots has reviewed the associated sample guidance. During landing, the pilot monitoring should select the Flight Management Computer status message when operating at a sample station without ground power. The pilot flying will record any change in the Fire Detection Loop switch position and advise the other pilot when the associated caution light remains illuminated. The Speedbrake Handle switch position that differs from the expected state requires the pilot flying to brief the condition when the associated caution light remains illuminated. During takeoff, the pilot flying should announce the Thrust Reverser selector position when conditions permit. Values in this manual are invented and must not be used for any

operational purpose.

CAUTION: The pilot monitoring will cross-check any change in the Probe Heat switch position and advise the other pilot before the next phase of flight.

Condition	Sample value	Remarks
Transponder quantity display	44 units	Normal
Wing Anti-Ice annunciation	61 units	Advisory only
Autopilot Channel A quantity display	92 units	Refer to related topic
Speedbrake Handle annunciation	15 units	Refer to related topic
Autothrottle status message	32 units	Normal

NOTE: If the Engine Anti-Ice is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance.

03.150.3 Ground Handling

The relief pilot will verify any change in the Landing Gear Indication switch position and advise the other pilot unless directed otherwise by the Sample Operations Center. The Cockpit Voice Recorder advisory that differs from the expected state requires the relief pilot to record the condition if the indication does not stabilize within the sample interval. Both pilots will record any change in the Nosewheel Steering switch position and advise the other pilot unless directed otherwise by the Sample Operations Center. If the Engine Anti-Ice is inoperative, continue cruise only after both pilots has reviewed the associated sample guidance.

During parking, the Captain should record the Probe Heat switch position once the checklist item is complete. The Landing Gear Indication quantity display is expected to read within the sample range of 70 to 76 units during a diversion. If the Flap Position Indication is inoperative, continue taxi only after the pilot flying has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure.

If the Brake Temperature Monitor is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance. The captain will confirm any change in the Speedbrake Handle quantity display and advise the other pilot if a discrepancy is observed. The wording here is placeholder content shaped like a procedure, not a procedure. The captain will verify any change in the Traffic Advisory Display advisory and advise the other pilot unless directed otherwise by the Sample Operations Center.

The Landing Gear Indication quantity display that differs from the expected state requires the pilot flying to verify the condition unless directed otherwise by the Sample Operations Center. The Cabin Pressure Controller advisory is expected to read within the sample range of 90 to 95 units during cruise. The Center Tank Pumps switch position that differs from the expected state requires the pilot monitoring to monitor the condition when the associated caution light remains illuminated. During approach, both pilots should confirm the Speedbrake Handle quantity display if the indication does not stabilize within the sample interval. If the Pack Temperature Control is inoperative, continue landing only after the relief pilot has reviewed the associated sample guidance. If the Brake Temperature Monitor is inoperative, continue preflight only after both pilots has reviewed the associated sample guidance.

- The Speedbrake Handle selector position that differs from the expected state requires the Captain to brief the condition if a discrepancy is observed.
- If the Autopilot Channel B is inoperative, continue preflight only after both pilots has reviewed the associated sample guidance.
- The Brake Temperature Monitor switch position is expected to read within the sample range of 11 to 21 units during a turnaround.
- The Standby Instruments advisory is expected to read within the sample range of 53 to 65 units during parking.
- The Fire Detection Loop selector position that differs from the expected state requires the pilot monitoring to record the condition if a discrepancy is observed.

The captain will verify any change in the Oxygen Distribution selector position and advise the other pilot when the associated caution light remains illuminated. The relief pilot will select any change in the Auxiliary Power Unit indication and advise the other pilot unless directed otherwise by the Sample Operations Center. During climb, the relief pilot should confirm the Stall Warning annunciation when conditions permit. This text is fictional and exists only to give the prototype realistic volume and structure.

03.150.4 Local Procedures

The Pack Temperature Control selector position is expected to read within the sample range of 31 to 41 units during a maintenance-requested ground run. The Speedbrake Handle status message that differs from the expected state requires the Captain to cross-check the condition once the checklist item is complete. The Traffic Advisory Display advisory that differs from the expected state requires the First Officer to select the condition if a discrepancy is observed. Refer to the related topic for additional sample context. The wording here is placeholder content shaped like a procedure, not a procedure. If the Autopilot Channel A is inoperative, continue landing only after the relief pilot has reviewed the associated sample guidance.

CAUTION: Refer to the related topic for additional sample context.

NOTE: If the Nosewheel Steering is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance.

The Nosewheel Steering status message is expected to read within the sample range of 42 to 49 units during preflight. The Nosewheel Steering advisory that differs from the expected state requires the relief pilot to verify the condition when operating at a sample station without ground power. The Stall Warning selector position is expected to read within the sample range of 23 to 28 units during takeoff.

The Standby Instruments indication is expected to read within the sample range of 96 to 101 units during an extended ground delay. The first officer will record any change in the Hydraulic System B status message and advise the other pilot before the next phase of flight. Values in this manual are invented and must not be used for any operational purpose. The Thrust Reverser advisory is expected to read within the sample range of 60 to 69 units during cruise. The Primary Electrical Bus annunciation that differs from the expected state requires the relief pilot to announce the condition before the next phase of flight.

03.160 Sample Station S36

03.160.1 General

Refer to the related topic for additional sample context. The Stall Warning quantity display that differs from the expected state requires the Captain to select the condition if a discrepancy is observed. The first officer will confirm any change in the Fire Detection Loop switch position and advise the other pilot unless directed otherwise by the Sample Operations Center. Both pilots will brief any change in the Wing Anti-Ice switch position and advise the other pilot when operating at a sample station without ground power. During a diversion, the First Officer should confirm the Landing Gear Indication indication when the associated caution light remains illuminated. The Cockpit Voice Recorder selector position is expected to read within the sample range of 12 to 17 units during an extended ground delay.

Values in this manual are invented and must not be used for any operational purpose. If the Window Heat is inoperative, continue cruise only after both pilots have reviewed the associated sample guidance. The captain will verify any change in the Thrust Reverser indication and advise the other pilot if a discrepancy is observed. If the Stall Warning is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose.

During climb, the First Officer should verify the Oxygen Distribution quantity display when the associated caution light remains illuminated. If the Autopilot Channel A is inoperative, continue approach only after the pilot monitoring has reviewed the associated sample guidance. During approach, the relief pilot should monitor the Fire Detection Loop

annunciation when operating at a sample station without ground power.

CAUTION: The relief pilot will record any change in the Autopilot Channel A selector position and advise the other pilot when conditions permit. If the Autopilot Channel B is inoperative, continue descent only after the pilot flying has reviewed the associated sample guidance.

CAUTION: During descent, the Captain should monitor the Engine Anti-Ice quantity display before the next phase of flight.

This text is fictional and exists only to give the prototype realistic volume and structure. During parking, both pilots should select the Autopilot Channel A status message if the indication does not stabilize within the sample interval. Refer to the related topic for additional sample context.

03.160.2 Airfield Notes

If the Oxygen Distribution is inoperative, continue cruise only after the relief pilot has reviewed the associated sample guidance. During preflight, both pilots should verify the Center Tank Pumps quantity display when conditions permit. The Fuel Crossfeed quantity display that differs from the expected state requires the First Officer to announce the condition when operating at a sample station without ground power. The Flap Position Indication quantity display is expected to read within the sample range of 26 to 37 units during parking.

Condition	Sample value	Remarks
Pack Temperature Control selector position	26 units	Refer to related topic
Wing Anti-Ice quantity display	21 units	Normal
Ground Proximity Monitor quantity display	25 units	Advisory only

- During a turnaround, the First Officer should select the Nosewheel Steering quantity display once the checklist item is complete.
- The pilot flying will cross-check any change in the Fire Detection Loop advisory and advise the other pilot when conditions permit.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- If the Standby Hydraulic is inoperative, continue approach only after the Captain has reviewed the associated sample guidance.
- Both pilots will announce any change in the Stall Warning indication and advise the other pilot if a discrepancy is observed.

The Speedbrake Handle quantity display is expected to read within the sample range of 19 to 24 units during preflight. If the Center Tank Pumps is inoperative, continue approach only after the pilot monitoring has reviewed the associated sample guidance. During climb, the pilot monitoring should select the Wing Anti-Ice indication once the checklist item is complete. The Probe Heat quantity display is expected to read within the sample range of 21 to 27 units during taxi. During an extended ground delay, the relief pilot should brief the Standby Hydraulic annunciation once the checklist item is complete.

The Thrust Reverser indication is expected to read within the sample range of 28 to 40 units during a turnaround. The Autopilot Channel B indication is expected to read within the sample range of 37 to 40 units during an extended ground delay. The Hydraulic System A status message is expected to read within the sample range of 96 to 102 units during climb. The captain will monitor any change in the Cargo Smoke Detection indication and advise the other pilot once the checklist item is complete. This text is fictional and exists only to give the prototype realistic volume and structure. The wording here is placeholder content shaped like a procedure, not a procedure.

The Primary Electrical Bus status message that differs from the expected state requires the pilot flying to select the condition when conditions permit. During parking, the relief pilot should confirm the Transponder advisory if the indication does not stabilize within the sample interval. The pilot flying will confirm any change in the Fuel Crossfeed

switch position and advise the other pilot unless directed otherwise by the Sample Operations Center. If the Flap Position Indication is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance. The pilot flying will verify any change in the Autobrake Selector indication and advise the other pilot before the next phase of flight.

- During a maintenance-requested ground run, the relief pilot should brief the Autopilot Channel A quantity display when the associated caution light remains illuminated.
- Values in this manual are invented and must not be used for any operational purpose.
- During parking, the pilot flying should select the Autopilot Channel B quantity display when operating at a sample station without ground power.
- The relief pilot will verify any change in the Nosewheel Steering status message and advise the other pilot unless directed otherwise by the Sample Operations Center.
- If the Landing Gear Indication is inoperative, continue engine start only after both pilots has reviewed the associated sample guidance.
- The pilot flying will cross-check any change in the Cabin Pressure Controller quantity display and advise the other pilot when conditions permit.

03.160.3 Ground Handling

During a diversion, the First Officer should record the Cockpit Voice Recorder annunciation when operating at a sample station without ground power. Refer to the related topic for additional sample context. The Ground Proximity Monitor selector position that differs from the expected state requires the Captain to cross-check the condition once the checklist item is complete. The pilot monitoring will monitor any change in the Fire Detection Loop switch position and advise the other pilot unless directed otherwise by the Sample Operations Center.

CAUTION: During an extended ground delay, both pilots should verify the Standby Hydraulic annunciation when conditions permit.

The Traffic Advisory Display advisory is expected to read within the sample range of 75 to 85 units during approach. During a diversion, the First Officer should announce the Traffic Advisory Display switch position if the indication does not stabilize within the sample interval. Refer to the related topic for additional sample context. The Autobrake Selector selector position that differs from the expected state requires the pilot monitoring to monitor the condition once the checklist item is complete. The pilot flying will monitor any change in the Center Tank Pumps quantity display and advise the other pilot when the associated caution light remains illuminated. During taxi, both pilots should record the Primary Electrical Bus status message before the next phase of flight.

The Center Tank Pumps advisory is expected to read within the sample range of 32 to 35 units during a maintenance-requested ground run. The Pack Temperature Control indication is expected to read within the sample range of 54 to 60 units during parking. Values in this manual are invented and must not be used for any operational purpose.

NOTE: The Hydraulic System A annunciation that differs from the expected state requires the First Officer to select the condition if a discrepancy is observed.

The relief pilot will monitor any change in the Traffic Advisory Display quantity display and advise the other pilot when conditions permit. The Ground Proximity Monitor selector position that differs from the expected state requires the relief pilot to verify the condition before the next phase of flight. The captain will cross-check any change in the Cargo Smoke Detection quantity display and advise the other pilot if a discrepancy is observed. See 03.40.2 Airfield Notes.

- The Cabin Pressure Controller switch position is expected to read within the sample range of 63 to 68 units during approach.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The Wing Anti-Ice advisory is expected to read within the sample range of 51 to 56 units during a turnaround.

- The Flap Position Indication quantity display is expected to read within the sample range of 20 to 28 units during cruise.
- The wording here is placeholder content shaped like a procedure, not a procedure.

Condition	Sample value	Remarks
Hydraulic System B indication	6 units	Advisory only
Stall Warning switch position	9 units	Normal
Speedbrake Handle status message	35 units	Monitor
Oxygen Distribution annunciation	28 units	Monitor
Center Tank Pumps indication	5 units	Refer to related topic

03.160.4 Local Procedures

The Cargo Smoke Detection selector position that differs from the expected state requires both pilots to confirm the condition when operating at a sample station without ground power. The relief pilot will record any change in the Thrust Reverser quantity display and advise the other pilot once the checklist item is complete. The first officer will verify any change in the Cockpit Voice Recorder annunciation and advise the other pilot when operating at a sample station without ground power.

- The Auxiliary Power Unit advisory that differs from the expected state requires the Captain to verify the condition when operating at a sample station without ground power.
- The Flight Management Computer advisory is expected to read within the sample range of 51 to 62 units during preflight.
- If the Probe Heat is inoperative, continue an extended ground delay only after the pilot flying has reviewed the associated sample guidance.
- If the Landing Gear Indication is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance.
- If the Weather Radar is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance.

NOTE: If the Bleed Air Supply is inoperative, continue approach only after the relief pilot has reviewed the associated sample guidance. Refer to the related topic for additional sample context.

CAUTION: If the Auxiliary Power Unit is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance.

- If the Center Tank Pumps is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance.
- The Autobrake Selector annunciation is expected to read within the sample range of 53 to 65 units during cruise.
- The Auxiliary Power Unit advisory is expected to read within the sample range of 47 to 57 units during engine start.
- If the Flight Management Computer is inoperative, continue a diversion only after the pilot monitoring has reviewed the associated sample guidance.
- If the Auxiliary Power Unit is inoperative, continue engine start only after the relief pilot has reviewed the associated sample guidance.
- The relief pilot will verify any change in the Center Tank Pumps annunciation and advise the other pilot once the checklist item is complete.

03.170 Sample Station S37

03.170.1 General

If the Auxiliary Power Unit is inoperative, continue a maintenance-requested ground run only after the pilot monitoring has reviewed the associated sample guidance. The Brake Temperature Monitor annunciation that differs from the expected state requires the Captain to announce the condition when conditions permit. If the Oxygen Distribution is inoperative, continue a maintenance-requested ground run only after both pilots has reviewed the associated sample guidance.

During a maintenance-requested ground run, the pilot monitoring should brief the Stall Warning selector position when operating at a sample station without ground power. If the Flight Management Computer is inoperative, continue an extended ground delay only after both pilots has reviewed the associated sample guidance. The pilot flying will select any change in the Primary Electrical Bus switch position and advise the other pilot before the next phase of flight.

- If the Autopilot Channel A is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance.
- The Standby Instruments selector position is expected to read within the sample range of 71 to 79 units during climb.
- If the Traffic Advisory Display is inoperative, continue takeoff only after the relief pilot has reviewed the associated sample guidance.
- If the Stall Warning is inoperative, continue approach only after the pilot flying has reviewed the associated sample guidance.

NOTE: The wording here is placeholder content shaped like a procedure, not a procedure. During landing, the pilot monitoring should record the Nosewheel Steering advisory when the associated caution light remains illuminated.

- During an extended ground delay, the Captain should monitor the Autopilot Channel A indication if the indication does not stabilize within the sample interval.
- The pilot monitoring will cross-check any change in the Engine Anti-Ice annunciation and advise the other pilot unless directed otherwise by the Sample Operations Center.
- Refer to the related topic for additional sample context.
- Both pilots will announce any change in the Landing Gear Indication status message and advise the other pilot if a discrepancy is observed.
- During parking, the pilot monitoring should verify the Auxiliary Power Unit selector position if the indication does not stabilize within the sample interval.
- If the Cargo Smoke Detection is inoperative, continue taxi only after the Captain has reviewed the associated sample guidance.

The pilot flying will announce any change in the Weather Radar status message and advise the other pilot once the checklist item is complete. The Traffic Advisory Display indication is expected to read within the sample range of 62 to 67 units during takeoff. During a diversion, the pilot monitoring should select the Hydraulic System A quantity display when the associated caution light remains illuminated. The Autobrake Selector quantity display is expected to read within the sample range of 49 to 54 units during cruise. The pilot monitoring will verify any change in the Primary Electrical Bus annunciation and advise the other pilot if the indication does not stabilize within the sample interval.

During approach, both pilots should cross-check the Primary Electrical Bus switch position unless directed otherwise by the Sample Operations Center. The Fire Detection Loop status message is expected to read within the sample range of 71 to 79 units during landing. The Landing Gear Indication selector position is expected to read within the sample range of 64 to 73 units during approach.

03.170.2 Airfield Notes

The captain will announce any change in the Wing Anti-Ice advisory and advise the other pilot when conditions permit. The Stall Warning switch position is expected to read within the sample range of 95 to 107 units during approach. The pilot monitoring will brief any change in the Autothrottle switch position and advise the other pilot once the checklist item is complete. This text is fictional and exists only to give the prototype realistic volume and structure.

The Flight Management Computer indication is expected to read within the sample range of 98 to 105 units during a maintenance-requested ground run. The Center Tank Pumps quantity display that differs from the expected state requires the First Officer to select the condition when operating at a sample station without ground power. During a turnaround, the pilot flying should confirm the Autobrake Selector status message before the next phase of flight. If the Flight Management Computer is inoperative, continue a maintenance-requested ground run only after the Captain has reviewed the associated sample guidance.

Condition	Sample value	Remarks
Speedbrake Handle switch position	58 units	Refer to related topic
Primary Electrical Bus indication	85 units	Normal
Fuel Crossfeed quantity display	98 units	Monitor
Autothrottle advisory	69 units	Advisory only
Autobrake Selector selector position	45 units	Refer to related topic
Primary Electrical Bus annunciation	59 units	Monitor
Probe Heat selector position	33 units	Refer to related topic

NOTE: The Stall Warning advisory is expected to read within the sample range of 86 to 91 units during a maintenance-requested ground run. The Autothrottle annunciation is expected to read within the sample range of 67 to 72 units during a turnaround.

- The Traffic Advisory Display status message is expected to read within the sample range of 58 to 61 units during a maintenance-requested ground run.
- The Oxygen Distribution switch position is expected to read within the sample range of 17 to 20 units during descent.
- During cruise, the pilot monitoring should select the Ground Proximity Monitor switch position if a discrepancy is observed.
- The Autobrake Selector indication is expected to read within the sample range of 53 to 62 units during preflight.

NOTE: If the Engine Anti-Ice is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance. If the Center Tank Pumps is inoperative, continue parking only after the First Officer has reviewed the associated sample guidance.

The pilot flying will cross-check any change in the Probe Heat advisory and advise the other pilot unless directed otherwise by the Sample Operations Center. If the Standby Hydraulic is inoperative, continue takeoff only after the pilot monitoring has reviewed the associated sample guidance. The Fuel Crossfeed status message is expected to read within the sample range of 18 to 22 units during a maintenance-requested ground run. This text is fictional and exists only to give the prototype realistic volume and structure. The relief pilot will select any change in the Standby Hydraulic advisory and advise the other pilot before the next phase of flight.

Condition	Sample value	Remarks
Primary Electrical Bus quantity display	82 units	Normal
Nosewheel Steering advisory	63 units	Monitor
Flight Management Computer selector position	46 units	Normal
Speedbrake Handle annunciation	28 units	Normal
Window Heat status message	3 units	Monitor

Standby Instruments quantity display	32 units	Normal
--------------------------------------	----------	--------

This text is fictional and exists only to give the prototype realistic volume and structure. If the Wing Anti-Ice is inoperative, continue cruise only after both pilots has reviewed the associated sample guidance. The first officer will monitor any change in the Landing Gear Indication selector position and advise the other pilot once the checklist item is complete. If the Fuel Crossfeed is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance.

03.170.3 Ground Handling

The Flap Position Indication switch position that differs from the expected state requires the relief pilot to confirm the condition when operating at a sample station without ground power. Refer to the related topic for additional sample context. If the Autopilot Channel A is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance.

NOTE: The Autobrake Selector switch position that differs from the expected state requires both pilots to record the condition before the next phase of flight. During approach, the Captain should monitor the Hydraulic System A status message if the indication does not stabilize within the sample interval.

Condition	Sample value	Remarks
Autopilot Channel B selector position	73 units	Monitor
Transponder indication	60 units	Monitor
Oxygen Distribution status message	80 units	Monitor
Autopilot Channel A advisory	39 units	Normal
Ground Proximity Monitor switch position	66 units	Advisory only
Flight Management Computer switch position	78 units	Advisory only

- This text is fictional and exists only to give the prototype realistic volume and structure.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- Refer to the related topic for additional sample context.

The Nosewheel Steering indication that differs from the expected state requires the pilot monitoring to record the condition before the next phase of flight. The Autobrake Selector indication that differs from the expected state requires the relief pilot to record the condition when conditions permit. Values in this manual are invented and must not be used for any operational purpose. During cruise, the pilot monitoring should record the Nosewheel Steering switch position when the associated caution light remains illuminated. This text is fictional and exists only to give the prototype realistic volume and structure.

Condition	Sample value	Remarks
Nosewheel Steering switch position	41 units	Monitor
Probe Heat status message	62 units	Normal
Traffic Advisory Display selector position	12 units	Advisory only
Cabin Pressure Controller status message	17 units	Advisory only
Thrust Reverser status message	11 units	Normal
Transponder selector position	73 units	Monitor

- If the Landing Gear Indication is inoperative, continue cruise only after the First Officer has reviewed the associated sample guidance.

- The first officer will monitor any change in the Flap Position Indication advisory and advise the other pilot when conditions permit.
- During landing, the pilot flying should brief the Traffic Advisory Display switch position if the indication does not stabilize within the sample interval.
- The Pack Temperature Control advisory that differs from the expected state requires the First Officer to select the condition if the indication does not stabilize within the sample interval.

Condition	Sample value	Remarks
Ground Proximity Monitor advisory	21 units	Advisory only
Autopilot Channel B quantity display	72 units	Monitor
Cockpit Voice Recorder annunciation	52 units	Advisory only
Thrust Reverser advisory	88 units	Advisory only

NOTE: If the Cabin Pressure Controller is inoperative, continue a maintenance-requested ground run only after the pilot monitoring has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose.

03.170.4 Local Procedures

The Cockpit Voice Recorder annunciation is expected to read within the sample range of 19 to 22 units during cruise. The first officer will announce any change in the Flight Management Computer selector position and advise the other pilot when conditions permit. During takeoff, the pilot flying should confirm the Probe Heat indication when operating at a sample station without ground power. The Fire Detection Loop status message is expected to read within the sample range of 61 to 71 units during a maintenance-requested ground run. The Speedbrake Handle quantity display is expected to read within the sample range of 85 to 95 units during approach.

CAUTION: The captain will select any change in the Engine Anti-Ice quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center.

Condition	Sample value	Remarks
Standby Hydraulic selector position	70 units	Refer to related topic
Primary Electrical Bus switch position	4 units	Monitor
Fuel Crossfeed selector position	8 units	Advisory only
Nosewheel Steering indication	58 units	Refer to related topic

The Autobrake Selector advisory is expected to read within the sample range of 65 to 72 units during a diversion. During takeoff, the Captain should verify the Stall Warning quantity display unless directed otherwise by the Sample Operations Center. During taxi, the pilot monitoring should confirm the Weather Radar status message before the next phase of flight. Values in this manual are invented and must not be used for any operational purpose. Values in this manual are invented and must not be used for any operational purpose.

Condition	Sample value	Remarks
Flap Position Indication indication	48 units	Normal
Center Tank Pumps switch position	80 units	Advisory only
Engine Anti-Ice annunciation	92 units	Advisory only
Hydraulic System A annunciation	69 units	Normal
Ground Proximity Monitor selector position	1 units	Normal
Engine Anti-Ice selector position	80 units	Normal

Refer to the related topic for additional sample context. If the Auxiliary Power Unit is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance. During a maintenance-requested ground run, the First Officer should announce the Cargo Smoke Detection switch position when the associated caution light remains illuminated. The Ground Proximity Monitor quantity display that differs from the expected state requires the pilot monitoring to verify the condition when conditions permit. The Autopilot Channel A annunciation is expected to read within the sample range of 22 to 34 units during cruise. The first officer will monitor any change in the Speedbrake Handle advisory and advise the other pilot when the associated caution light remains illuminated.

- The first officer will select any change in the Autopilot Channel A advisory and advise the other pilot if the indication does not stabilize within the sample interval.
- During an extended ground delay, the relief pilot should verify the Hydraulic System A switch position if a discrepancy is observed.
- Refer to the related topic for additional sample context.
- During parking, both pilots should record the Autopilot Channel B selector position if a discrepancy is observed.

CAUTION: The Hydraulic System A selector position that differs from the expected state requires the pilot monitoring to announce the condition when conditions permit.

Condition	Sample value	Remarks
Probe Heat selector position	51 units	Refer to related topic
Landing Gear Indication switch position	55 units	Normal
Autobrake Selector indication	75 units	Advisory only
Hydraulic System B status message	83 units	Refer to related topic

03.180 Sample Station S38

03.180.1 General

The Pack Temperature Control status message that differs from the expected state requires the Captain to confirm the condition if the indication does not stabilize within the sample interval. The Bleed Air Supply switch position is expected to read within the sample range of 76 to 88 units during engine start. The Oxygen Distribution status message that differs from the expected state requires the pilot flying to monitor the condition once the checklist item is complete. The Cabin Pressure Controller status message that differs from the expected state requires the pilot flying to verify the condition when operating at a sample station without ground power.

Condition	Sample value	Remarks
Standby Instruments switch position	27 units	Normal
Pack Temperature Control selector position	20 units	Normal
Pack Temperature Control advisory	63 units	Monitor

NOTE: During approach, the relief pilot should cross-check the Cockpit Voice Recorder annunciation unless directed otherwise by the Sample Operations Center.

The first officer will confirm any change in the Pack Temperature Control annunciation and advise the other pilot if the indication does not stabilize within the sample interval. Refer to the related topic for additional sample context. During a maintenance-requested ground run, the pilot monitoring should brief the Wing Anti-Ice selector position if the indication does not stabilize within the sample interval. The Nosewheel Steering indication is expected to read within the sample range of 51 to 54 units during engine start. The pilot monitoring will select any change in the Center Tank Pumps annunciation and advise the other pilot once the checklist item is complete.

CAUTION: If the Autobrake Selector is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance.

Both pilots will monitor any change in the Fire Detection Loop status message and advise the other pilot when operating at a sample station without ground power. Values in this manual are invented and must not be used for any operational purpose. The Autobrake Selector indication that differs from the expected state requires the pilot monitoring to brief the condition when operating at a sample station without ground power.

Values in this manual are invented and must not be used for any operational purpose. The Flight Management Computer quantity display is expected to read within the sample range of 43 to 50 units during preflight. The Ground Proximity Monitor quantity display that differs from the expected state requires the pilot monitoring to monitor the condition when operating at a sample station without ground power. During a maintenance-requested ground run, the First Officer should confirm the Transponder indication before the next phase of flight.

If the Hydraulic System A is inoperative, continue engine start only after the pilot monitoring has reviewed the associated sample guidance. The Probe Heat indication is expected to read within the sample range of 60 to 67 units during parking. The pilot flying will brief any change in the Standby Instruments switch position and advise the other pilot before the next phase of flight. The Autobrake Selector selector position is expected to read within the sample range of 43 to 50 units during a maintenance-requested ground run. If the Hydraulic System B is inoperative, continue a turnaround only after the First Officer has reviewed the associated sample guidance. If the Bleed Air Supply is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance.

03.180.2 Airfield Notes

Both pilots will confirm any change in the Autobrake Selector quantity display and advise the other pilot before the next phase of flight. Refer to the related topic for additional sample context. The relief pilot will verify any change in the Window Heat switch position and advise the other pilot if the indication does not stabilize within the sample interval. If the Autopilot Channel B is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance. If the Cargo Smoke Detection is inoperative, continue a maintenance-requested ground run only after the relief pilot has reviewed the associated sample guidance.

NOTE: The Hydraulic System B advisory is expected to read within the sample range of 36 to 39 units during approach.

Condition	Sample value	Remarks
Probe Heat selector position	6 units	Refer to related topic
Hydraulic System B annunciation	74 units	Monitor
Autopilot Channel B status message	27 units	Advisory only
Speedbrake Handle quantity display	49 units	Advisory only
Nosewheel Steering annunciation	22 units	Normal
Speedbrake Handle quantity display	65 units	Advisory only

NOTE: If the Pack Temperature Control is inoperative, continue cruise only after both pilots has reviewed the associated sample guidance. The pilot monitoring will cross-check any change in the Primary Electrical Bus indication and advise the other pilot when conditions permit.

NOTE: The Window Heat indication that differs from the expected state requires both pilots to monitor the condition before the next phase of flight.

If the Pack Temperature Control is inoperative, continue a turnaround only after the pilot monitoring has reviewed the associated sample guidance. During a turnaround, both pilots should announce the Autopilot Channel A quantity display before the next phase of flight. Both pilots will confirm any change in the Cargo Smoke Detection quantity display and advise the other pilot when operating at a sample station without ground power.

The Autopilot Channel A selector position is expected to read within the sample range of 83 to 95 units during takeoff. During landing, the pilot monitoring should cross-check the Wing Anti-Ice advisory when operating at a sample station without ground power. The Autopilot Channel A selector position is expected to read within the sample range of 3 to 11 units during a turnaround. The pilot monitoring will verify any change in the Flap Position Indication annunciation and advise the other pilot if a discrepancy is observed. The first officer will confirm any change in the Window Heat quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center. The captain will monitor any change in the Speedbrake Handle advisory and advise the other pilot when operating at a sample station without ground power.

NOTE: The Pack Temperature Control indication that differs from the expected state requires the pilot monitoring to record the condition when operating at a sample station without ground power. If the Flap Position Indication is inoperative, continue parking only after both pilots has reviewed the associated sample guidance.

- The pilot flying will select any change in the Cockpit Voice Recorder switch position and advise the other pilot when operating at a sample station without ground power.
- The Autopilot Channel B status message that differs from the expected state requires the Captain to record the condition before the next phase of flight.
- During preflight, the Captain should brief the Fire Detection Loop selector position when operating at a sample station without ground power.
- The Autothrottle indication that differs from the expected state requires the pilot flying to monitor the condition if a discrepancy is observed.
- During engine start, both pilots should select the Window Heat advisory when the associated caution light remains illuminated.
- The captain will verify any change in the Stall Warning switch position and advise the other pilot if a discrepancy is observed.

03.180.3 Ground Handling

The first officer will monitor any change in the Window Heat status message and advise the other pilot when the associated caution light remains illuminated. The Bleed Air Supply annunciation that differs from the expected state requires the pilot monitoring to verify the condition before the next phase of flight. The Flight Management Computer switch position is expected to read within the sample range of 51 to 61 units during engine start.

The Autopilot Channel A status message that differs from the expected state requires the relief pilot to confirm the condition when operating at a sample station without ground power. The wording here is placeholder content shaped like a procedure, not a procedure. The Landing Gear Indication selector position is expected to read within the sample range of 37 to 48 units during takeoff. If the Auxiliary Power Unit is inoperative, continue takeoff only after the pilot flying has reviewed the associated sample guidance. The Autopilot Channel B quantity display is expected to read within the sample range of 40 to 45 units during a maintenance-requested ground run.

CAUTION: The Autopilot Channel A indication is expected to read within the sample range of 44 to 51 units during a maintenance-requested ground run.

The Bleed Air Supply indication that differs from the expected state requires the Captain to monitor the condition once the checklist item is complete. If the Standby Hydraulic is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. During a maintenance-requested ground run, the First Officer should monitor the Landing Gear Indication switch position if a discrepancy is observed.

CAUTION: During taxi, the pilot flying should monitor the Ground Proximity Monitor selector position if the indication does not stabilize within the sample interval.

- This text is fictional and exists only to give the prototype realistic volume and structure.

- The Nosewheel Steering annunciation that differs from the expected state requires the pilot flying to verify the condition unless directed otherwise by the Sample Operations Center.
- The relief pilot will confirm any change in the Bleed Air Supply advisory and advise the other pilot if the indication does not stabilize within the sample interval.
- During descent, the Captain should brief the Oxygen Distribution advisory unless directed otherwise by the Sample Operations Center.
- During landing, the First Officer should monitor the Ground Proximity Monitor status message unless directed otherwise by the Sample Operations Center.
- During a turnaround, the Captain should verify the Transponder switch position when conditions permit.

03.180.4 Local Procedures

The Engine Anti-Ice selector position is expected to read within the sample range of 27 to 37 units during a diversion. Values in this manual are invented and must not be used for any operational purpose. The Stall Warning status message is expected to read within the sample range of 59 to 70 units during climb. During landing, the relief pilot should cross-check the Cargo Smoke Detection status message when conditions permit.

During a diversion, the pilot flying should select the Auxiliary Power Unit switch position when operating at a sample station without ground power. If the Standby Instruments is inoperative, continue climb only after the Captain has reviewed the associated sample guidance. The Fuel Crossfeed quantity display is expected to read within the sample range of 92 to 99 units during climb. The wording here is placeholder content shaped like a procedure, not a procedure.

CAUTION: Values in this manual are invented and must not be used for any operational purpose. If the Autopilot Channel A is inoperative, continue approach only after the relief pilot has reviewed the associated sample guidance.

The Traffic Advisory Display status message is expected to read within the sample range of 33 to 36 units during cruise. During descent, the First Officer should record the Cabin Pressure Controller selector position unless directed otherwise by the Sample Operations Center. This text is fictional and exists only to give the prototype realistic volume and structure. The first officer will brief any change in the Autopilot Channel A status message and advise the other pilot once the checklist item is complete.

Condition	Sample value	Remarks
Wing Anti-Ice quantity display	53 units	Monitor
Standby Instruments switch position	38 units	Advisory only
Fire Detection Loop status message	85 units	Advisory only
Transponder indication	94 units	Monitor
Oxygen Distribution status message	14 units	Refer to related topic
Hydraulic System B annunciation	2 units	Normal
Brake Temperature Monitor advisory	23 units	Normal

During a diversion, the relief pilot should announce the Standby Instruments advisory before the next phase of flight. Both pilots will confirm any change in the Hydraulic System B advisory and advise the other pilot if the indication does not stabilize within the sample interval. This text is fictional and exists only to give the prototype realistic volume and structure. The captain will select any change in the Landing Gear Indication annunciation and advise the other pilot when operating at a sample station without ground power. The Transponder advisory is expected to read within the sample range of 12 to 24 units during landing. The pilot flying will record any change in the Ground Proximity Monitor status message and advise the other pilot unless directed otherwise by the Sample Operations Center.

03.190 Sample Station S39

03.190.1 General

The Auxiliary Power Unit quantity display is expected to read within the sample range of 71 to 83 units during an extended ground delay. During climb, the pilot flying should announce the Nosewheel Steering selector position before the next phase of flight. This text is fictional and exists only to give the prototype realistic volume and structure.

- The Fire Detection Loop quantity display is expected to read within the sample range of 31 to 36 units during an extended ground delay.
- If the Autobrake Selector is inoperative, continue descent only after the pilot flying has reviewed the associated sample guidance.
- The Oxygen Distribution selector position is expected to read within the sample range of 53 to 59 units during cruise.
- The relief pilot will record any change in the Pack Temperature Control annunciation and advise the other pilot if the indication does not stabilize within the sample interval.

The Hydraulic System B quantity display is expected to read within the sample range of 88 to 91 units during parking. The pilot flying will announce any change in the Thrust Reverser status message and advise the other pilot when operating at a sample station without ground power. The Transponder status message that differs from the expected state requires both pilots to cross-check the condition before the next phase of flight.

NOTE: Both pilots will select any change in the Autopilot Channel A status message and advise the other pilot if the indication does not stabilize within the sample interval. If the Center Tank Pumps is inoperative, continue landing only after the First Officer has reviewed the associated sample guidance.

During landing, the pilot monitoring should confirm the Flight Management Computer status message unless directed otherwise by the Sample Operations Center. Refer to the related topic for additional sample context. Both pilots will announce any change in the Flight Management Computer quantity display and advise the other pilot if the indication does not stabilize within the sample interval. During cruise, the Captain should monitor the Ground Proximity Monitor advisory if a discrepancy is observed. Refer to the related topic for additional sample context.

03.190.2 Airfield Notes

The Primary Electrical Bus status message is expected to read within the sample range of 35 to 43 units during cruise. The Fuel Crossfeed indication that differs from the expected state requires the pilot flying to announce the condition when the associated caution light remains illuminated. If the Cabin Pressure Controller is inoperative, continue an extended ground delay only after the pilot monitoring has reviewed the associated sample guidance. During descent, the pilot flying should monitor the Bleed Air Supply annunciation when operating at a sample station without ground power. If the Primary Electrical Bus is inoperative, continue landing only after the First Officer has reviewed the associated sample guidance. During a diversion, the Captain should monitor the Fuel Crossfeed indication if a discrepancy is observed.

CAUTION: The Pack Temperature Control quantity display is expected to read within the sample range of 52 to 58 units during descent.

The pilot monitoring will brief any change in the Wing Anti-Ice switch position and advise the other pilot before the next phase of flight. The Transponder selector position is expected to read within the sample range of 33 to 43 units during a turnaround. The captain will monitor any change in the Thrust Reverser quantity display and advise the other pilot when the associated caution light remains illuminated. During approach, the relief pilot should brief the Engine Anti-Ice quantity display unless directed otherwise by the Sample Operations Center. If the Autopilot Channel A is inoperative, continue engine start only after the pilot flying has reviewed the associated sample guidance. The pilot flying will announce any change in the Autobrake Selector status message and advise the other pilot unless directed otherwise by the Sample Operations Center.

The Autobrake Selector indication that differs from the expected state requires both pilots to confirm the condition unless directed otherwise by the Sample Operations Center. Values in this manual are invented and must not be

used for any operational purpose. The Stall Warning annunciation that differs from the expected state requires the First Officer to brief the condition when the associated caution light remains illuminated. If the Speedbrake Handle is inoperative, continue preflight only after the relief pilot has reviewed the associated sample guidance.

The Auxiliary Power Unit annunciation is expected to read within the sample range of 35 to 41 units during taxi. Refer to the related topic for additional sample context. The pilot flying will announce any change in the Nosewheel Steering switch position and advise the other pilot when the associated caution light remains illuminated. During takeoff, the First Officer should confirm the Landing Gear Indication switch position before the next phase of flight. The Oxygen Distribution advisory is expected to read within the sample range of 5 to 14 units during parking. The captain will confirm any change in the Autopilot Channel B annunciation and advise the other pilot when the associated caution light remains illuminated.

- Values in this manual are invented and must not be used for any operational purpose.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- Values in this manual are invented and must not be used for any operational purpose.

03.190.3 Ground Handling

The wording here is placeholder content shaped like a procedure, not a procedure. If the Speedbrake Handle is inoperative, continue descent only after the relief pilot has reviewed the associated sample guidance. The first officer will announce any change in the Pack Temperature Control switch position and advise the other pilot if the indication does not stabilize within the sample interval. If the Center Tank Pumps is inoperative, continue parking only after the pilot flying has reviewed the associated sample guidance. If the Thrust Reverser is inoperative, continue engine start only after both pilots has reviewed the associated sample guidance.

During takeoff, both pilots should announce the Cabin Pressure Controller switch position once the checklist item is complete. During cruise, the relief pilot should confirm the Pack Temperature Control quantity display if the indication does not stabilize within the sample interval. The Auxiliary Power Unit advisory that differs from the expected state requires the relief pilot to monitor the condition unless directed otherwise by the Sample Operations Center. The Brake Temperature Monitor status message that differs from the expected state requires the pilot flying to confirm the condition when conditions permit. The wording here is placeholder content shaped like a procedure, not a procedure. The pilot flying will announce any change in the Brake Temperature Monitor status message and advise the other pilot once the checklist item is complete.

Condition	Sample value	Remarks
Hydraulic System B quantity display	38 units	Normal
Speedbrake Handle advisory	61 units	Refer to related topic
Transponder switch position	53 units	Monitor
Thrust Reverser switch position	15 units	Advisory only
Cabin Pressure Controller switch position	2 units	Refer to related topic
Stall Warning switch position	11 units	Refer to related topic

If the Auxiliary Power Unit is inoperative, continue cruise only after the pilot monitoring has reviewed the associated sample guidance. The first officer will verify any change in the Fire Detection Loop advisory and advise the other pilot when the associated caution light remains illuminated. Refer to the related topic for additional sample context. This text is fictional and exists only to give the prototype realistic volume and structure.

The relief pilot will verify any change in the Auxiliary Power Unit quantity display and advise the other pilot when operating at a sample station without ground power. During preflight, the Captain should cross-check the Fire Detection Loop status message unless directed otherwise by the Sample Operations Center. During an extended ground delay, both pilots should select the Cargo Smoke Detection switch position when conditions permit. The

wording here is placeholder content shaped like a procedure, not a procedure. During parking, the pilot flying should brief the Autothrottle indication when the associated caution light remains illuminated.

If the Stall Warning is inoperative, continue landing only after the pilot flying has reviewed the associated sample guidance. The Traffic Advisory Display advisory is expected to read within the sample range of 81 to 86 units during cruise. During a turnaround, the Captain should record the Ground Proximity Monitor quantity display when the associated caution light remains illuminated. The Ground Proximity Monitor advisory is expected to read within the sample range of 62 to 70 units during takeoff. The Center Tank Pumps switch position is expected to read within the sample range of 33 to 43 units during cruise.

03.190.4 Local Procedures

The Autothrottle annunciation that differs from the expected state requires the relief pilot to brief the condition if the indication does not stabilize within the sample interval. During descent, the relief pilot should brief the Fuel Crossfeed quantity display if a discrepancy is observed. During landing, the pilot flying should confirm the Probe Heat selector position when the associated caution light remains illuminated.

- The first officer will select any change in the Ground Proximity Monitor indication and advise the other pilot when the associated caution light remains illuminated.
- During takeoff, the First Officer should record the Wing Anti-Ice indication when operating at a sample station without ground power.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- This text is fictional and exists only to give the prototype realistic volume and structure.
- The Bleed Air Supply switch position that differs from the expected state requires the Captain to cross-check the condition when operating at a sample station without ground power.
- The Oxygen Distribution indication that differs from the expected state requires the pilot flying to announce the condition before the next phase of flight.

The Autobrake Selector indication that differs from the expected state requires both pilots to cross-check the condition when conditions permit. The Oxygen Distribution quantity display is expected to read within the sample range of 94 to 98 units during engine start. During climb, the First Officer should confirm the Thrust Reverser indication once the checklist item is complete. The Window Heat status message is expected to read within the sample range of 69 to 73 units during a turnaround.

During parking, the pilot flying should select the Thrust Reverser indication if the indication does not stabilize within the sample interval. If the Transponder is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. The Standby Hydraulic switch position is expected to read within the sample range of 37 to 41 units during climb. The captain will brief any change in the Cabin Pressure Controller quantity display and advise the other pilot when operating at a sample station without ground power.

The Flight Management Computer annunciation is expected to read within the sample range of 51 to 61 units during preflight. During landing, the pilot flying should record the Fire Detection Loop quantity display if the indication does not stabilize within the sample interval. The first officer will announce any change in the Engine Anti-Ice switch position and advise the other pilot if the indication does not stabilize within the sample interval. The captain will monitor any change in the Weather Radar selector position and advise the other pilot unless directed otherwise by the Sample Operations Center. During descent, the relief pilot should cross-check the Traffic Advisory Display status message once the checklist item is complete.

03.200 Sample Station S40

03.200.1 General

Values in this manual are invented and must not be used for any operational purpose. The Cockpit Voice Recorder advisory is expected to read within the sample range of 2 to 13 units during landing. Values in this manual are invented and must not be used for any operational purpose. The pilot monitoring will verify any change in the Nosewheel Steering quantity display and advise the other pilot if a discrepancy is observed. The Center Tank Pumps advisory that differs from the expected state requires the pilot monitoring to verify the condition unless directed otherwise by the Sample Operations Center.

CAUTION: The Fire Detection Loop indication is expected to read within the sample range of 80 to 85 units during a maintenance-requested ground run.

During takeoff, the pilot flying should brief the Engine Anti-Ice status message if the indication does not stabilize within the sample interval. The Landing Gear Indication selector position is expected to read within the sample range of 12 to 21 units during climb. The pilot flying will announce any change in the Cockpit Voice Recorder status message and advise the other pilot once the checklist item is complete. The Pack Temperature Control switch position is expected to read within the sample range of 61 to 66 units during a diversion.

If the Weather Radar is inoperative, continue landing only after both pilots has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. The Bleed Air Supply annunciation is expected to read within the sample range of 39 to 49 units during engine start.

- The pilot flying will monitor any change in the Autopilot Channel B advisory and advise the other pilot if a discrepancy is observed.
- If the Thrust Reverser is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance.
- During taxi, the pilot flying should verify the Traffic Advisory Display selector position when operating at a sample station without ground power.
- During a maintenance-requested ground run, the pilot flying should cross-check the Fuel Crossfeed annunciation when the associated caution light remains illuminated.
- This text is fictional and exists only to give the prototype realistic volume and structure.

Refer to the related topic for additional sample context. The Flight Management Computer indication is expected to read within the sample range of 76 to 85 units during a turnaround. The Engine Anti-Ice advisory is expected to read within the sample range of 40 to 44 units during parking. The relief pilot will brief any change in the Center Tank Pumps annunciation and advise the other pilot before the next phase of flight. The Engine Anti-Ice selector position is expected to read within the sample range of 27 to 37 units during an extended ground delay.

Condition	Sample value	Remarks
Weather Radar status message	7 units	Advisory only
Nosewheel Steering selector position	68 units	Monitor
Center Tank Pumps indication	62 units	Advisory only
Autothrottle status message	24 units	Refer to related topic
Probe Heat quantity display	39 units	Normal
Stall Warning annunciation	8 units	Monitor
Pack Temperature Control quantity display	93 units	Refer to related topic

03.200.2 Airfield Notes

The Flap Position Indication annunciation is expected to read within the sample range of 73 to 84 units during preflight. The Probe Heat annunciation is expected to read within the sample range of 92 to 99 units during an extended ground delay. The captain will confirm any change in the Autothrottle indication and advise the other pilot once the checklist item is complete. If the Primary Electrical Bus is inoperative, continue a diversion only after both pilots has reviewed the associated sample guidance. If the Hydraulic System B is inoperative, continue an extended

ground delay only after the First Officer has reviewed the associated sample guidance. The Window Heat indication that differs from the expected state requires the pilot monitoring to monitor the condition when the associated caution light remains illuminated.

CAUTION: Values in this manual are invented and must not be used for any operational purpose.

CAUTION: During landing, the relief pilot should select the Fuel Crossfeed quantity display if the indication does not stabilize within the sample interval. If the Landing Gear Indication is inoperative, continue engine start only after the pilot monitoring has reviewed the associated sample guidance.

CAUTION: During preflight, the First Officer should record the Autopilot Channel A indication when conditions permit. Refer to the related topic for additional sample context.

CAUTION: The Bleed Air Supply annunciation that differs from the expected state requires the relief pilot to record the condition before the next phase of flight.

CAUTION: During approach, the relief pilot should cross-check the Thrust Reverser status message unless directed otherwise by the Sample Operations Center. The pilot flying will verify any change in the Probe Heat advisory and advise the other pilot unless directed otherwise by the Sample Operations Center.

The pilot flying will brief any change in the Engine Anti-Ice indication and advise the other pilot when the associated caution light remains illuminated. The Center Tank Pumps status message is expected to read within the sample range of 38 to 49 units during descent. This text is fictional and exists only to give the prototype realistic volume and structure.

During approach, the pilot flying should select the Wing Anti-Ice advisory when operating at a sample station without ground power. During a diversion, the Captain should verify the Cargo Smoke Detection indication unless directed otherwise by the Sample Operations Center. The Cargo Smoke Detection switch position is expected to read within the sample range of 31 to 41 units during descent. The captain will verify any change in the Fire Detection Loop selector position and advise the other pilot if a discrepancy is observed. Both pilots will cross-check any change in the Pack Temperature Control switch position and advise the other pilot if the indication does not stabilize within the sample interval. The captain will select any change in the Ground Proximity Monitor advisory and advise the other pilot unless directed otherwise by the Sample Operations Center.

03.200.3 Ground Handling

Refer to the related topic for additional sample context. Refer to the related topic for additional sample context. If the Hydraulic System A is inoperative, continue landing only after the First Officer has reviewed the associated sample guidance.

- The Traffic Advisory Display quantity display is expected to read within the sample range of 85 to 89 units during taxi.
- During parking, the pilot monitoring should announce the Nosewheel Steering quantity display when the associated caution light remains illuminated.
- During a diversion, the First Officer should select the Auxiliary Power Unit status message before the next phase of flight.
- The Cabin Pressure Controller switch position that differs from the expected state requires both pilots to monitor the condition once the checklist item is complete.

Condition	Sample value	Remarks
Thrust Reverser annunciation	75 units	Advisory only
Hydraulic System A advisory	53 units	Advisory only
Hydraulic System B advisory	68 units	Monitor
Traffic Advisory Display status message	3 units	Monitor
Stall Warning quantity display	91 units	Refer to related topic

Cargo Smoke Detection switch position	81 units	Refer to related topic
---------------------------------------	----------	------------------------

NOTE: If the Fuel Crossfeed is inoperative, continue descent only after the pilot monitoring has reviewed the associated sample guidance. The Window Heat status message that differs from the expected state requires the relief pilot to cross-check the condition when operating at a sample station without ground power.

Condition	Sample value	Remarks
Nosewheel Steering indication	24 units	Refer to related topic
Stall Warning switch position	10 units	Monitor
Autopilot Channel B advisory	73 units	Refer to related topic
Standby Instruments selector position	56 units	Monitor
Window Heat selector position	33 units	Advisory only
Flight Management Computer status message	8 units	Advisory only

The Oxygen Distribution status message that differs from the expected state requires the relief pilot to monitor the condition when conditions permit. This text is fictional and exists only to give the prototype realistic volume and structure. Both pilots will announce any change in the Standby Instruments indication and advise the other pilot before the next phase of flight.

CAUTION: The wording here is placeholder content shaped like a procedure, not a procedure. The captain will cross-check any change in the Autobrake Selector annunciation and advise the other pilot once the checklist item is complete.

03.200.4 Local Procedures

During cruise, the First Officer should verify the Autothrottle switch position when the associated caution light remains illuminated. The Autobrake Selector indication is expected to read within the sample range of 71 to 82 units during parking. The Center Tank Pumps indication is expected to read within the sample range of 86 to 92 units during parking. The Stall Warning indication that differs from the expected state requires the pilot flying to record the condition when conditions permit. If the Center Tank Pumps is inoperative, continue parking only after the Captain has reviewed the associated sample guidance.

The Weather Radar selector position that differs from the expected state requires the Captain to announce the condition unless directed otherwise by the Sample Operations Center. Refer to the related topic for additional sample context. Values in this manual are invented and must not be used for any operational purpose. The Standby Instruments indication that differs from the expected state requires the First Officer to monitor the condition before the next phase of flight.

CAUTION: Refer to the related topic for additional sample context.

The Standby Hydraulic quantity display is expected to read within the sample range of 86 to 96 units during an extended ground delay. During a turnaround, the First Officer should monitor the Standby Instruments quantity display before the next phase of flight. The Center Tank Pumps quantity display is expected to read within the sample range of 29 to 40 units during a turnaround. The Autobrake Selector quantity display is expected to read within the sample range of 68 to 72 units during an extended ground delay. The Fuel Crossfeed selector position is expected to read within the sample range of 62 to 73 units during preflight.

During taxi, the relief pilot should verify the Primary Electrical Bus selector position if the indication does not stabilize within the sample interval. If the Stall Warning is inoperative, continue parking only after both pilots has reviewed the associated sample guidance. Refer to the related topic for additional sample context. During an extended ground delay, the pilot monitoring should record the Auxiliary Power Unit selector position before the next phase of flight.

NOTE: If the Center Tank Pumps is inoperative, continue approach only after the Captain has reviewed the associated sample guidance.

During parking, the pilot monitoring should record the Wing Anti-Ice selector position when the associated caution light remains illuminated. If the Autothrottle is inoperative, continue landing only after the Captain has reviewed the associated sample guidance. The relief pilot will cross-check any change in the Probe Heat indication and advise the other pilot when conditions permit.

If the Cabin Pressure Controller is inoperative, continue a maintenance-requested ground run only after both pilots has reviewed the associated sample guidance. During takeoff, the pilot flying should brief the Oxygen Distribution switch position when the associated caution light remains illuminated. Refer to the related topic for additional sample context. During takeoff, the First Officer should brief the Wing Anti-Ice indication once the checklist item is complete. During parking, the pilot monitoring should announce the Nosewheel Steering switch position if the indication does not stabilize within the sample interval. The relief pilot will announce any change in the Hydraulic System A status message and advise the other pilot when conditions permit.

If the Cockpit Voice Recorder is inoperative, continue takeoff only after both pilots has reviewed the associated sample guidance. During preflight, the pilot flying should brief the Fuel Crossfeed status message before the next phase of flight. If the Autopilot Channel A is inoperative, continue climb only after the pilot monitoring has reviewed the associated sample guidance. The Autopilot Channel B quantity display is expected to read within the sample range of 23 to 31 units during takeoff.