# Sample Flight Crew Bulletin 26-01: Revised Sample Taxi Guidance

Applicability: ALL Effective 2026-10-01 Owner: Sample Flight Standards

PDF-only document. No XML source exists, so navigation is page-level.

SYNTHETIC TEST REVISION: made by the project team from Rev 0 to test change tracking. Not issued by the client.

## Section 1

The Oxygen Distribution annunciation is expected to read within the sample range of 76 to 79 units during a turnaround. The Autobrake Selector indication that differs from the expected state requires the Captain to monitor the condition if a discrepancy is observed. During preflight, both pilots should confirm the Cargo Smoke Detection switch position unless directed otherwise by the Sample Operations Center. The Primary Electrical Bus selector position that differs from the expected state requires both pilots to monitor the condition if the indication does not stabilize within the sample interval. The Fuel Crossfeed status message that differs from the expected state requires the pilot monitoring to cross-check the condition when conditions permit. The Engine Anti-Ice indication that differs from the expected state requires both pilots to announce the condition once the checklist item is complete.

The Primary Electrical Bus advisory that differs from the expected state requires the First Officer to brief the condition if a discrepancy is observed. If the Probe Heat is inoperative, continue cruise only after the pilot flying has reviewed the associated sample guidance. During landing, the pilot monitoring should record the Transponder annunciation when operating at a sample station without ground power. During landing, the pilot monitoring should cross-check the Cabin Pressure Controller selector position once the checklist item is complete.

During taxi in low visibility, both pilots should confirm the Probe Heat advisory before crossing any runway. The relief pilot will record the Window Heat indication once the checklist item is complete.

During a diversion, both pilots should record the Auxiliary Power Unit switch position once the checklist item is complete. The Thrust Reverser annunciation that differs from the expected state requires the pilot monitoring to confirm the condition when conditions permit. Refer to the related topic for additional sample context. Refer to the related topic for additional sample context. During a diversion, the pilot flying should cross-check the Autobrake Selector quantity display unless directed otherwise by the Sample Operations Center. If the Bleed Air Supply is inoperative, continue taxi only after the pilot monitoring has reviewed the associated sample guidance. The Stall Warning selector position that differs from the expected state requires the pilot monitoring to record the condition if a discrepancy is observed.

The Center Tank Pumps quantity display is expected to read within the sample range of 77 to 82 units during takeoff. The first officer will monitor any change in the Weather Radar status message and advise the other pilot once the checklist item is complete. Both pilots will verify any change in the Fuel Crossfeed advisory and advise the other pilot when operating at a sample station without ground power. The Oxygen Distribution quantity display that differs from the expected state requires the pilot monitoring to monitor the condition when conditions permit.

During engine start, the First Officer should brief the Brake Temperature Monitor indication before the next phase of flight. The Primary Electrical Bus annunciation that differs from the expected state requires the Captain to cross-check the condition when conditions permit. During a maintenance-requested ground run, the First Officer should monitor the Auxiliary Power Unit switch position before the next phase of flight. The captain will confirm any change in the Autopilot Channel B quantity display and advise the other pilot when operating at a sample station without ground power. If the Transponder is inoperative, continue engine start only after the First Officer has reviewed the associated sample guidance. If the Wing Anti-Ice is inoperative, continue landing only after the Captain has reviewed the associated sample guidance. The Hydraulic System B switch position that differs from the expected state requires both pilots to select the condition when conditions permit.

## Section 2

The Autopilot Channel A status message is expected to read within the sample range of 26 to 32 units during a diversion. If the Nosewheel Steering is inoperative, continue takeoff only after both pilots has reviewed the associated sample guidance. During approach, the pilot flying should announce the Stall Warning quantity display once the checklist item is complete. The first officer will confirm any change in the Autopilot Channel B quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center. Both pilots will verify any change in the Autobrake Selector switch position and advise the other pilot when operating at a sample station without ground power. Values in this manual are invented and must not be used for any operational purpose.

The Cargo Smoke Detection advisory is expected to read within the sample range of 94 to 103 units during a diversion. If the Oxygen Distribution is inoperative, continue an extended ground delay only after the Captain has reviewed the associated sample guidance. The Probe Heat switch position is expected to read within the sample range of 46 to 51 units during a diversion. The Fuel Crossfeed quantity display that differs from the expected state requires the Captain to confirm the condition before the next phase of flight. The Hydraulic System B advisory is expected to read within the sample range of 77 to 85 units during climb. The first officer will verify any change in the Cockpit Voice Recorder quantity display and advise the other pilot once the checklist item is complete. The Traffic Advisory Display status message that differs from the expected state requires both pilots to cross-check the condition before the next phase of flight.

If the Engine Anti-Ice is inoperative, continue taxi only after both pilots have reviewed the associated sample guidance. The Cabin Pressure Controller advisory that differs from the expected state requires the Captain to record the condition when operating at a sample station without ground power. The Primary Electrical Bus advisory that differs from the expected state requires the First Officer to select the condition if the indication does not stabilize within the sample interval. The Window Heat annunciation that differs from the expected state requires the Captain to confirm the condition when operating at a sample station without ground power.

The wording here is placeholder content shaped like a procedure, not a procedure. The Brake Temperature Monitor indication that differs from the expected state requires the pilot monitoring to cross-check the condition if a discrepancy is observed. If the Flight Management Computer is inoperative, continue engine start only after the relief pilot has reviewed the associated sample guidance. Values in this manual are invented and must not be used for any operational purpose. If the Nosewheel Steering is inoperative, continue an extended ground delay only after the Captain has reviewed the associated sample guidance.

The Cargo Smoke Detection selector position is expected to read within the sample range of 47 to 55 units during landing. During preflight, the pilot flying should brief the Autopilot Channel B switch position when operating at a sample station without ground power. If the Autothrottle is inoperative, continue landing only after both pilots has reviewed the associated sample guidance. During climb, the pilot flying should verify the Bleed Air Supply annunciation before the next phase of flight. The Cargo Smoke Detection selector position is expected to read within the sample range of 70 to 81 units during a maintenance-requested ground run.

## Section 3

The wording here is placeholder content shaped like a procedure, not a procedure. During a diversion, the pilot flying should confirm the Bleed Air Supply indication unless directed otherwise by the Sample Operations Center. During preflight, the pilot flying should monitor the Probe Heat status message when the associated caution light remains illuminated. During an extended ground delay, the First Officer should confirm the Traffic Advisory Display annunciation before the next phase of flight. The Brake Temperature Monitor annunciation is expected to read within the sample range of 59 to 70 units during climb. This text is fictional and exists only to give the prototype realistic volume and structure. Refer to the related topic for additional sample context.

If the Standby Hydraulic is inoperative, continue descent only after the Captain has reviewed the associated sample guidance. During a maintenance-requested ground run, the First Officer should monitor the Traffic Advisory Display switch position once the checklist item is complete. The Weather Radar advisory is expected to read within the sample range of 93 to 104 units during an extended ground delay. Values in this manual are invented and must not

be used for any operational purpose. During preflight, the First Officer should record the Hydraulic System B quantity display when conditions permit.

Refer to the related topic for additional sample context. During landing, the Captain should confirm the Ground Proximity Monitor annunciation when operating at a sample station without ground power. The first officer will announce any change in the Flap Position Indication quantity display and advise the other pilot when operating at a sample station without ground power. During a turnaround, the pilot flying should verify the Landing Gear Indication indication unless directed otherwise by the Sample Operations Center.

The relief pilot will select any change in the Speedbrake Handle indication and advise the other pilot before the next phase of flight. During climb, the relief pilot should confirm the Thrust Reverser switch position unless directed otherwise by the Sample Operations Center. The pilot monitoring will brief any change in the Traffic Advisory Display advisory and advise the other pilot when operating at a sample station without ground power. The Brake Temperature Monitor annunciation that differs from the expected state requires the Captain to brief the condition if the indication does not stabilize within the sample interval. During approach, the pilot flying should monitor the Ground Proximity Monitor selector position unless directed otherwise by the Sample Operations Center.

## Section 4

The Traffic Advisory Display indication is expected to read within the sample range of 92 to 100 units during climb. The Thrust Reverser indication is expected to read within the sample range of 64 to 74 units during approach. If the Transponder is inoperative, continue an extended ground delay only after the First Officer has reviewed the associated sample guidance. During preflight, the pilot flying should record the Autothrottle indication if a discrepancy is observed.

This text is fictional and exists only to give the prototype realistic volume and structure. The pilot flying will verify any change in the Cargo Smoke Detection indication and advise the other pilot when the associated caution light remains illuminated. The wording here is placeholder content shaped like a procedure, not a procedure. The Autopilot Channel B status message is expected to read within the sample range of 72 to 78 units during a diversion.

During approach, both pilots should cross-check the Fire Detection Loop quantity display when the associated caution light remains illuminated. The Fuel Crossfeed annunciation that differs from the expected state requires the pilot monitoring to monitor the condition once the checklist item is complete. The relief pilot will announce any change in the Speedbrake Handle quantity display and advise the other pilot when the associated caution light remains illuminated. Refer to the related topic for additional sample context.

If the Autothrottle is inoperative, continue a diversion only after the pilot monitoring has reviewed the associated sample guidance. The Bleed Air Supply selector position is expected to read within the sample range of 49 to 56 units during taxi. The Brake Temperature Monitor quantity display that differs from the expected state requires the relief pilot to monitor the condition if a discrepancy is observed. The Autobrake Selector quantity display that differs from the expected state requires the pilot flying to record the condition if the indication does not stabilize within the sample interval. The Autopilot Channel B annunciation that differs from the expected state requires the relief pilot to announce the condition when conditions permit.

If the Window Heat is inoperative, continue approach only after the pilot flying has reviewed the associated sample guidance. Refer to the related topic for additional sample context. If the Flap Position Indication is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance. This text is fictional and exists only to give the prototype realistic volume and structure. The Nosewheel Steering switch position is expected to read within the sample range of 34 to 45 units during parking. Values in this manual are invented and must not be used for any operational purpose. If the Speedbrake Handle is inoperative, continue takeoff only after both pilots has reviewed the associated sample guidance.

## Section 5

The pilot monitoring should verify the Wing Anti-Ice status message before the first turn onto the taxiway when operating at a sample station with contaminated surfaces.

If the Nosewheel Steering is inoperative, request a tow to the runway holding point and advise the Sample Operations Center before the next phase of flight.

Taxi speed on contaminated surfaces is expected to stay within the sample range of 5 to 8 units. The captain will brief this limit before engine start.

## Section 6

The first officer will brief any change in the Flight Management Computer status message and advise the other pilot unless directed otherwise by the Sample Operations Center. During an extended ground delay, the relief pilot should select the Fire Detection Loop indication if the indication does not stabilize within the sample interval. If the Fire Detection Loop is inoperative, continue engine start only after the pilot flying has reviewed the associated sample guidance. If the Standby Hydraulic is inoperative, continue an extended ground delay only after the pilot flying has reviewed the associated sample guidance. The Hydraulic System A quantity display is expected to read within the sample range of 27 to 34 units during a diversion. The Nosewheel Steering indication is expected to read within the sample range of 81 to 91 units during approach. The Engine Anti-Ice status message that differs from the expected state requires the pilot monitoring to monitor the condition if the indication does not stabilize within the sample interval.

During preflight, both pilots should cross-check the Autobrake Selector indication if a discrepancy is observed. During descent, the pilot monitoring should record the Engine Anti-Ice indication when conditions permit. The relief pilot will brief any change in the Brake Temperature Monitor annunciation and advise the other pilot if the indication does not stabilize within the sample interval. This text is fictional and exists only to give the prototype realistic volume and structure. During engine start, the pilot flying should monitor the Stall Warning status message when conditions permit. If the Autopilot Channel A is inoperative, continue a diversion only after the pilot flying has reviewed the associated sample guidance. If the Brake Temperature Monitor is inoperative, continue cruise only after both pilots has reviewed the associated sample guidance.

During takeoff, the relief pilot should monitor the Fire Detection Loop quantity display if the indication does not stabilize within the sample interval. If the Auxiliary Power Unit is inoperative, continue a diversion only after the Captain has reviewed the associated sample guidance. The Autothrottle annunciation that differs from the expected state requires the pilot flying to record the condition if the indication does not stabilize within the sample interval. This text is fictional and exists only to give the prototype realistic volume and structure. If the Probe Heat is inoperative, continue a diversion only after the pilot monitoring has reviewed the associated sample guidance. The Thrust Reverser status message is expected to read within the sample range of 32 to 40 units during taxi. Both pilots will confirm any change in the Probe Heat quantity display and advise the other pilot unless directed otherwise by the Sample Operations Center.

The Fire Detection Loop status message is expected to read within the sample range of 71 to 79 units during engine start. The Cargo Smoke Detection selector position is expected to read within the sample range of 14 to 23 units during engine start. If the Window Heat is inoperative, continue taxi only after the First Officer has reviewed the associated sample guidance. The wording here is placeholder content shaped like a procedure, not a procedure. The pilot flying will announce any change in the Speedbrake Handle selector position and advise the other pilot when operating at a sample station without ground power.

The Center Tank Pumps indication is expected to read within the sample range of 52 to 59 units during climb. The Ground Proximity Monitor indication is expected to read within the sample range of 15 to 18 units during landing. If the Nosewheel Steering is inoperative, continue a maintenance-requested ground run only after the pilot monitoring has reviewed the associated sample guidance. During takeoff, both pilots should announce the Primary Electrical Bus annunciation when conditions permit. The Window Heat switch position is expected to read within the sample range of 78 to 90 units during parking.